

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250255678

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

Roh; Jeffrey et al.

SYSTEM FOR TRANSCRIBING AND PERFORMING ANALYSIS ON PATIENT DATA

Abstract

Methods, apparatuses, and systems for transcribing and performing analysis on patient data are disclosed. Data is collected from one or more medical professionals as well as sensors and imaging devices positioned on or oriented towards a patient. An analysis is performed on the patient data and the data is presented to a medical professional via a verbal interface in a conversational manner, allowing the medical professional to provide additional data such as observations or instructions which may be used for further analysis or to perform actions related to the patient's care.

Inventors: Roh; Jeffrey (Seattle, WA), Esterberg; Justin (Mesa, AZ), Cronin; John (Jericho, VT), Cronin; Seth (Essex Junction, VT), Baker; Michael John (Georgia, VT)

Applicant: IX Innovation LLC (Seattle, WA)

Family ID: 81944052

Appl. No.: 19/184920

Filed: April 21, 2025

Related U.S. Application Data

parent US continuation 18439056 20240212 parent-grant-document US 12295675 child US 19184920

parent US continuation 17746722 20220517 parent-grant-document US 11896324 child US 18439056

parent US continuation 17568442 20220104 parent-grant-document US 11357582 child US 17746722

Publication Classification

Int. Cl.: A61B34/00 (20160101); **G06T7/00** (20170101); **G06V10/40** (20220101); **G10L13/02** (20130101); **G10L15/06** (20130101); **G10L15/22** (20060101); **G10L15/26** (20060101); **G10L15/30** (20130101); **G16B20/20** (20190101); **G16B40/20** (20190101); **G16H10/60** (20180101); **G16H50/20** (20180101); **G16H50/50** (20180101)

U.S. Cl.:

CPC A61B34/25 (20160201); **G06T7/0012** (20130101); **G06V10/40** (20220101); **G10L13/02** (20130101); **G10L15/063** (20130101); **G10L15/22** (20130101); **G10L15/26** (20130101); **G10L15/30** (20130101); **G16B20/20** (20190201); **G16B40/20** (20190201); **G16H10/60** (20180101); **G16H50/20** (20180101); **G16H50/50** (20180101); **A61B2034/256** (20160201); **G06T2207/30004** (20130101); **G06V2201/03** (20220101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation of U.S. patent application Ser. No. 18/439,056, filed Feb. 12, 2024, which is a continuation of U.S. patent application Ser. No. 17/746,722 (now U.S. Pat. No. 11,896,324), filed May 17, 2022, which is a continuation of U.S. patent application Ser. No. 17/568,442 (now U.S. Pat. No. 11,357,582), filed Jan. 4, 2022, which are all incorporated herein by reference in their entireties.

TECHNICAL FIELD

[0002] The present disclosure is generally related to automated and robotic surgical procedures and specifically to systems and methods for transcribing and performing analysis on patient data.

BACKGROUND

[0003] More than 200 million surgeries are performed worldwide each year, and recent reports reveal that adverse event rates for surgical conditions remain unacceptably high, despite traditional patient safety initiatives. Adverse events resulting from surgical interventions can be related to errors occurring before or after the procedure as well as technical surgical errors during the operation. For example, adverse events can occur due to (i) breakdown in communication within and among the surgical team, care providers, patients, and their families; (ii) delay in diagnosis or failure to diagnose; and (iii) delay in treatment or failure to treat. The risk of complications during surgery can include anesthesia complications, hemorrhaging, high blood pressure, a rise or fall in body temperature, etc. Such adverse events can further occur due to medical errors, infections, underlying physical or health conditions of the patient, reactions to anesthetics or other drugs, etc. Conventional methods for preventing wrong-site, wrong-person, wrong-procedure errors, or retained foreign objects are typically based on communication between the patient, the surgeon(s), and other members of the healthcare team. However, conventional methods are typically insufficient to prevent surgical errors and adverse events during surgery.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0004] FIG. 1 is a block diagram illustrating an example system, in accordance with one or more embodiments.

[0005] FIG. 2 is a block diagram illustrating an example machine learning (ML) system, in accordance with one or more embodiments.

[0006] FIG. 3 is a block diagram illustrating an example computer system, in accordance with one or more embodiments.

[0007] FIG. 4A is a block diagram illustrating an example robotic system, in accordance with one or more embodiments.

[0008] FIG. 4B illustrates an example console of the robotic system of FIG. 4A, in accordance with one or more embodiments.

[0009] FIG. 5 is a schematic block diagram illustrating subcomponents of the robotic system of FIG. 4A, in accordance with one or more embodiments.

[0010] FIG. 6 is a block diagram illustrating an example system for transcribing and performing analysis on patient data, in accordance with one or more embodiments.

[0011] FIG. 7 is a table illustrating an example patient database, in accordance with one or more embodiments.

[0012] FIG. 8 is a flow diagram illustrating an example process for transcribing and performing analysis on patient data, in accordance with one or more embodiments.

[0013] FIG. 9 is a flow diagram illustrating an example process for transcribing and performing analysis on patient data, in accordance with one or more embodiments.

[0014] FIG. 10 is a flow diagram illustrating an example process for transcribing and performing analysis on patient data, in accordance with one or more embodiments.

DETAILED DESCRIPTION

[0015] Embodiments of the present disclosure will be described more thoroughly from now on with reference to the accompanying drawings. Like numerals represent like elements throughout the several figures, and in which example embodiments are shown. However, embodiments of the claims can be embodied in many different forms and should not be construed as limited to the embodiments set forth herein. The examples set forth herein are non-limiting examples and are merely examples, among other possible examples. Throughout this specification, plural instances (e.g., “602”) can implement components, operations, or structures (e.g., “602a”) described as a single instance. Further, plural instances (e.g., “602”) refer collectively to a set of components, operations, or structures (e.g., “602a”) described as a single instance. The description of a single component (e.g., “602a”) applies equally to a like-numbered component (e.g., “602b”) unless indicated otherwise. These and other aspects, features, and implementations can be expressed as methods, apparatuses, systems, components, program products, means or steps for performing a function, and in other ways. These and other aspects, features, and implementations will become apparent from the following descriptions including the claims.

[0016] Medical transcription is a resource intensive process which can additionally consume a large amount of a healthcare provider's time, however, thorough documentation is critical to the long-term care of a patient and ensures the continuity of care when multiple care providers are involved in a patient's care. Quickly and accurately documenting this data can facilitate rapid coordination of patient care, however, this is commonly performed by manual transcription. Beyond recording data, a medical professional, such as a physician, surgeon, imaging technician, pathologist, etc., must analyze the data and make observations ultimately culminating in a diagnosis. This analysis may be computer aided; however, the observations are largely subjective. This results in a large degree of variability in assessments and diagnoses, not to mention time spent manually reviewing data collected about the patient.

[0017] The embodiments disclosed herein describe methods, apparatuses, and systems for transcribing and performing analysis on patient data. In some embodiments, data is collected from one or more medical professionals as well as sensors and imaging devices positioned on or oriented towards a patient. An analysis is performed on the patient data and the data is presented to a medical professional via a user interface in a conversational manner, allowing the medical professional to provide additional data such as observations or instructions which may be used for further analysis or to perform actions related to the patient's care.

[0018] The advantages and benefits of the methods, systems, and apparatuses disclosed herein include compatibility with best practice guidelines for performing surgery in an operating room,

e.g., from regulatory bodies and professional standards organizations such as the Association for Surgical Technologists. The embodiments disclosed provide the ability to analyze data and recognize patterns with greater consistency than humans. Furthermore, the methods disclosed can be implemented in a range of processing capabilities, ranging from simple silicon-based consumer-grade computers, to commercial cloud computers and large-scale supercomputers, to newly developed quantum computers. Each of these implementations represents an increase in scale of computing resources that could be utilized to perform a deeper analysis in a similar amount of time that cannot be matched by a human. The embodiments disclosed improve and automate the transcription process and assist in the analysis of patient data. Thus, a surgeon or other medical professional can decrease the amount of time needed reviewing such data to arrive at a diagnosis, or in the case of a surgeon, planning a surgical procedure. The embodiments result in prompter interventions which may be consequential in more favorable patient outcomes. Similarly, the systems disclosed enable medical professionals to be more efficient allowing them to address the needs of more patients in the same amount of time.

[0019] The robotic surgery technologies disclosed further offer valuable enhancements to medical or surgical processes through improved precision, stability, and dexterity. The disclosed methods relieve medical personnel from routine tasks and make medical procedures safer and less costly for patients. The embodiments disclosed enable performing more accurate surgery in more minute locations on or within the human body. The embodiments also address the use of dangerous substances. The adoption of robotic systems, according to the embodiments disclosed herein, provides several additional benefits, including efficiency and speed improvements, lower costs, and higher accuracy. The equipment tracking system integrated into the disclosed embodiments offers flexibility and other advantages, such as requiring no line-of-sight, reading multiple radio frequency identification (RFID) objects at once, and scanning at a distance. The advantages offered by the surgical tower according to the embodiments disclosed herein are smaller incisions, less pain, lower risk of infection, shorter hospital stays, quicker recovery time, less scarring, and reduced blood loss. The advantages of the convolutional neural network (CNN) used for machine learning (ML) in the disclosed embodiments include the obviation of feature extraction and the use of shared weight in convolutional layers, which means that the same filter (weights bank) is used for each node in the layer; this both reduces memory footprint and improves performance.

[0020] FIG. 1 is a block diagram illustrating an example system **100**, in accordance with one or more embodiments. The system **100** includes various surgical and medical equipment (e.g., a patient monitor **112**) located within an operating room **102** or a doctor's office **110**, a console **108** for performing surgery or other patient care, and a database **106** for storing electronic health records. The console **108** is the same as or similar to the console **420** illustrated and described in more detail with reference to FIG. 4A. The system **100** is implemented using the components of the example computer system **300** illustrated and described in more detail with reference to FIG. 3. Likewise, embodiments of the system **100** can include different and/or additional components or can be connected in different ways.

[0021] The operating room **102** is a facility, e.g., within a hospital, where surgical operations are carried out in an aseptic environment. Proper surgical procedures require a sterile field. In some embodiments, the sterile field is maintained in the operating room **102** in a medical care facility, such as a hospital, the doctor's office **110**, or outpatient surgery center.

[0022] In some embodiments, the system **100** includes one or more medical or surgical patient monitors **112**. The monitors **112** can include a vital signs monitor (a medical diagnostic instrument), which can be a portable, battery powered, multi-parametric, vital signs monitoring device used for both ambulatory and transport applications as well as bedside monitoring. The vital signs monitor can be used with an isolated data link to an interconnected portable computer or the console **108**, allowing snapshot and trended data from the vital signs monitor to be printed automatically at the console **108**, and also allowing default configuration settings to be downloaded

to the vital signs monitor. The vital signs monitor is capable of use as a stand-alone unit as well as part of a bi-directional wireless communications network that includes at least one remote monitoring station (e.g., the console **108**). The vital signs monitor can measure multiple physiologic parameters of a patient wherein various sensor output signals are transmitted either wirelessly or by means of a wired connection to at least one remote site, such as the console **108**. [0023] In some embodiments, the monitors **112** include a heart rate monitor, which is a sensor and/or a sensor system applied in the context of monitoring heart rates. The heart rate monitor measures, directly or indirectly, any physiological condition from which any relevant aspect of heart rate can be gleaned. For example, some embodiments of the heart rate monitor measure different or overlapping physiological conditions to measure the same aspect of heart rate. Alternatively, some embodiments measure the same, different, or overlapping physiological conditions to measure different aspects of heart rate, e.g., number of beats, strength of beats, regularity of beats, beat anomalies, etc.

[0024] In some embodiments, the monitors **112** include a pulse oximeter or SpO₂ monitor, which is a plethysmograph or any instrument that measures variations in the size of an organ or body part of the patient on the basis of the amount of blood passing through or present in the part. The pulse oximeter is a type of plethysmograph that determines the oxygen saturation of the blood by indirectly measuring the oxygen saturation of the patient's blood (as opposed to measuring oxygen saturation directly through a blood sample) and changes in blood volume in the skin. The pulse oximeter can include a light sensor that is placed at a site on the patient, usually a fingertip, toe, forehead, or earlobe, or in the case of a neonate, across a foot. Light, which can be produced by a light source integrated into the pulse oximeter, containing both red and infrared wavelengths, is directed onto the skin of the patient, and the light that passes through the skin is detected by the pulse oximeter. The intensity of light in each wavelength is measured by the pulse oximeter over time. The graph of light intensity versus time is referred to as the photoplethysmogram (PPG) or, more commonly, simply as the "pleth." From the waveform of the PPG, it is possible to identify the pulse rate of the patient and when each individual pulse occurs. In addition, by comparing the intensities of two wavelengths when a pulse occurs, it is possible to determine blood oxygen saturation of hemoglobin in arterial blood. This relies on the observation that highly oxygenated blood will relatively absorb more red light and less infrared light than blood with a lower oxygen saturation.

[0025] In some embodiments, the monitors **112** include an end-tidal CO₂ monitor or capnography monitor used for measurement of the level of carbon dioxide that is released at the end of an exhaled breath (referred to as end-tidal carbon dioxide, ETCO₂). An end-tidal CO₂ monitor or capnography monitor is widely used in anesthesia and intensive care. ETCO₂ can be computed by plotting expiratory CO₂ with time. Further, ETCO₂ monitors are important for the measurement of applications such as cardiopulmonary resuscitation (CPR), airway assessment, procedural sedation and analgesia, pulmonary diseases such as obstructive pulmonary disease, pulmonary embolism, etc., heart failure, metabolic disorders, etc. The end-tidal CO₂ monitor can be configured as side stream (diverting) or mainstream (non-diverting). A diverting end-tidal CO₂ monitor transports a portion of a patient's respired gases from the sampling site to the end-tidal CO₂ monitor while a non-diverting end-tidal CO₂ monitor does not transport gas away. Also, measurement by the end-tidal CO₂ monitor is based on the absorption of infrared light by carbon dioxide where exhaled gas passes through a sampling chamber containing an infrared light source and photodetector on both sides. Based on the amount of infrared light reaching the photodetector, the amount of carbon dioxide present in the gas can be determined.

[0026] In some embodiments, the monitors **112** include a blood pressure monitor that measures blood pressure, particularly in arteries. The blood pressure monitor uses a non-invasive technique (by external cuff application) or an invasive technique (by a cannula needle inserted in artery, used in the operating room **102**) for measurement. The non-invasive method (referred to as a

sphygmomanometer) works by measurement of force exerted against arterial walls during ventricular systole (i.e., systolic blood pressure occurs when the heart beats and pushes blood through the arteries) and ventricular diastole (i.e., diastolic blood pressure occurs when the heart rests and is filling with blood) thereby measuring systole and diastole, respectively. The blood pressure monitor can be of three types: automatic/digital, manual (aneroid-dial), and manual (mercury-column). The sphygmomanometer can include a bladder, a cuff, a pressure meter, a stethoscope, a valve, and a bulb. The cuff inflates until it fits tightly around the patient's arm, cutting off the blood flow, and then the valve opens to deflate it. The blood pressure monitor operates by inflating a cuff tightly around the arm; as the cuff reaches the systolic pressure, blood begins to flow in the artery, creating a vibration, which is detected by the blood pressure monitor, which records the systolic pressure. The techniques used for measurement can be auscultatory or oscillometric.

[0027] In some embodiments, the monitors **112** include a body temperature monitor. The body temperature monitor measures the temperature invasively or non-invasively by placement of a sensor into organs such as bladder, rectum, esophagus, tympanum, etc., and mouth, armpit, etc., respectively. The body temperature monitor is of two types: contact and non-contact. Temperature can be measured in two forms: core temperature and peripheral temperature. Temperature measurement can be done by thermocouples, resistive temperature devices (RTDs, thermistors), infrared radiators, bimetallic devices, liquid expansion devices, molecular change-of-state, and silicon diodes. A body temperature monitor commonly used for the measurement of temperature includes a temperature sensing element (e.g., temperature sensor) and a means for converting to a numerical value.

[0028] In some embodiments, the monitors **112** measure respiration rate or breathing rate, which is the rate at which breathing occurs, and which is measured by the number of breaths the patient takes per minute. The rate is measured when a person is at rest and simply involves counting the number of breaths for one minute by counting how many times the chest rises. Normal respiration rates for an adult patient at rest are in the range: 12 to 16 breaths per minute. A variation can be an indication of an abnormality/medical condition or the patient's demographic parameters. The monitors **112** can indicate hypoxia, a condition with low levels of oxygen in the cells, or hypercapnia, a condition in which high levels of carbon dioxide are in the bloodstream. Pulmonary disorders, asthma, anxiety, pneumonia, heart diseases, dehydration, and drug overdose are some abnormal conditions, which can bring a change to the respiration rate, thereby increasing or reducing the respiration rate from normal levels.

[0029] In some embodiments, the monitors **112** measure an electrocardiogram (EKG or ECG), a representation of the electrical activity of the heart (graphical trace of voltage versus time) by placement of electrodes on skin/body surface. The electrodes capture the electrical impulse, which travels through the heart causing systole and diastole or the pumping of the heart. This impulse provides information related to the normal functioning of the heart and the production of impulses. A change can occur due to medical conditions such as arrhythmias (tachycardia where the heart rate becomes faster and bradycardia where the heart rate becomes slower), coronary heart disease, heart attacks, or cardiomyopathy. The instrument used for measurement of the electrocardiogram is called an electrocardiogram which measures the electrical impulses by the placement of electrodes on the surface of the body and represents the ECG by a PQRST waveform. A PQRST wave is read as: P wave, which represents the depolarization of the left and right atrium and corresponds to atrial contraction; QRS complex, which indicates ventricular depolarization and represents the electrical impulse as it spreads through the ventricles; and T wave, which indicates ventricular repolarization and follows the QRS complex.

[0030] In some embodiments, the monitors **112** perform neuromonitoring, also called intraoperative neurophysiological monitoring (IONM). For example, the monitors **112** assess functions and changes in the brain, brainstem, spinal cord, cranial nerves, and peripheral nerves

during a surgical procedure on these organs. Monitoring includes both continuous monitoring of neural tissue as well as the localization of vital neural structures. IONM measures changes in these organs where the changes are indicative of irreversible damage or injuries in the organs, aiming at reducing the risk of neurological deficits after operations involving the nervous system. Monitoring is effective in localization of anatomical structures, including peripheral nerves and the sensorimotor cortex, which help in guiding the surgeon during dissection. Electrophysiological modalities employed in neuromonitoring are an extracellular single unit and local field recordings (LFP), somatosensory evoked potential (SSEP), transcranial electrical motor evoked potentials (TCeMEP), electromyography (EMG), electroencephalography (EEG), and auditory brainstem response (ABR). The use of neurophysiological monitoring during surgical procedures requires anesthesia techniques to avoid interference and signal alteration due to anesthesia.

[0031] In some embodiments, the monitors **112** measure motor evoked potential (MEP), electrical signals that are recorded from descending motor pathways or muscles following stimulation of motor pathways within the brain. MEP is determined by measurement of the action potential elicited by non-invasive stimulation of the motor cortex through the scalp. MEP is for intraoperative monitoring and neurophysiological testing of the motor pathways specifically during spinal procedures. The technique of monitoring for measurement of MEP is defined based on parameters, such as a site of stimulation (motor cortex or spinal cord), method of stimulation (electrical potential or magnetic field), and site of recording (spinal cord or peripheral mixed nerve and muscle). The target site is stimulated by the use of electrical or magnetic means.

[0032] In some embodiments, the monitors **112** measure somatosensory evoked potential (SSEP or SEP), the electrical signals generated by the brain and the spinal cord in response to sensory stimulus or touch. SSEP is used for intraoperative neurophysiological monitoring in spinal surgeries. The measurements are reliable, which allows for continuous monitoring during a surgical procedure. The sensor stimulus commonly given to the organs can be auditory, visual, or somatosensory SEPs and applied on the skin, peripheral nerves of the upper limbs, lower limbs, or scalp. The stimulation technique can be mechanical, electrical (provides larger and more robust responses), or intraoperative spinal monitoring modality.

[0033] In some embodiments, the monitors **112** provide electromyography (EMG), the evaluation and recording of electrical signals or electrical activity of the skeletal muscles. An electromyography instrument, electromyograph, or electromyogram for the measurement of the EMG activity records electrical activity produced by skeletal muscles and evaluates the functional integrity of individual nerves. The nerves monitored by an EMG instrument can be intracranial, spinal, or peripheral nerves. The electrodes used for the acquisition of signals can be invasive or non-invasive electrodes. The technique used for measurement can be spontaneous or triggered. Spontaneous EMG refers to the recording of myoelectric signals such as compression, stretching, or pulling of nerves during surgical manipulation, and does not perform external stimulation. Spontaneous EMG is recorded by the insertion of a needle electrode. Triggered EMG refers to the recording of myoelectric signals during stimulation of a target site such as pedicle screw with incremental current intensities.

[0034] In some embodiments, the monitors **112** provide electroencephalography (EEG), measuring the electrical signals in the brain. Brain cells communicate with each other through electrical impulses. EEG can be used to help detect potential problems associated with this activity. An electroencephalograph is used for the measurement of EEG activity. Electrodes ranging from 8 to 16 pairs are attached to the scalp, where each pair of electrodes transmits a signal to one or more recording channels. EEG is a modality for intraoperative neurophysiological monitoring and assessing cortical perfusion and oxygenation during a variety of vascular, cardiac, and neurosurgical procedures. The waves produced by EEG are alpha, beta, theta, and delta.

[0035] In some embodiments, the monitors **112** include sensors, such as microphones or optical sensors, that produce images or video captured from at least one of multiple imaging devices, for

example, cameras attached to manipulators or end effectors, cameras mounted to the ceiling or other surface above the surgical theater, or cameras mounted on a tripod or other independent mounting device. In some embodiments, the cameras are body worn by a surgeon or other surgical staff, cameras are incorporated into a wearable device, such as an augmented reality device like Google Glass™, or cameras are integrated into an endoscopic, microscopic, or laparoscopic device. In some embodiments, a camera or other imaging device (e.g., ultrasound) present in the operating room **102** is associated with one or more areas in the operating room **102**. The sensors can be associated with measuring a specific parameter of the patient, such as respiratory rate, blood pressure, blood oxygen level, heart rate, etc.

[0036] In some embodiments, the system **100** includes a medical visualization apparatus **114** used for visualization and analysis of objects (preferably three-dimensional (3D) objects) in the operating room **102**. The medical visualization apparatus **114** provides the selection of points at surfaces, selection of a region of interest, or selection of objects. The medical visualization apparatus **114** can also be used for diagnosis, treatment planning, intraoperative support, documentation, or educational purposes. The medical visualization apparatus **114** can further include microscopes, endoscopes/arthroscopes/laparoscopes, fiber optics, surgical lights, high-definition monitors, operating room cameras, etc. Three-dimensional (3D) visualization software provides visual representations of scanned body parts via virtual models, offering significant depth and nuance to static two-dimensional medical images. The software facilitates improved diagnoses, narrowed surgical operation learning curves, reduced operational costs, and shortened image acquisition times.

[0037] In some embodiments, the system **100** includes an instrument **118** such as an endoscope, arthroscope, or laparoscope for minimally invasive surgery (MIS), in which procedures are performed by performing a minimal incision in the body. An endoscope refers to an instrument used to visualize, diagnose, and treat problems inside hollow organs where the instrument is inserted through natural body openings such as the mouth or anus. An endoscope can perform a procedure as follows: a scope with a tiny camera attached to a long, thin tube is inserted. The doctor moves it through a body passageway or opening to see inside an organ. It can be used for diagnosis and surgery (such as for removing polyps from the colon). An arthroscope refers to an instrument used to visualize, diagnose, and treat problems inside a joint by a TV camera inserted through small portals/incisions and to perform procedures on cartilage, ligaments, tendons, etc. An arthroscope can perform the procedure as follows: a surgeon makes a small incision in a patient's skin and inserts a pencil-sized instrument with a small lens and lighting system to magnify the target site (joint) and viewing of the interior of the joint by means of a miniature TV camera and then performs the procedure. A laparoscope refers to an instrument used to visualize, diagnose, and treat problems inside soft organs like the abdomen and pelvis by a TV camera inserted through small portals/incisions and to perform procedures.

[0038] In some embodiments, the system **100** includes fiber optics **120**, which refer to flexible, transparent fiber made by drawing glass (silica) or plastic to a diameter slightly thicker than that of a human hair. Fiber optics **120** are arranged in bundles called optical cables and used to transmit light signals over long distances. Fiber optics **120** are used most often as a means to transmit light between the two ends of the fiber and find wide usage in the medical field. Traditional surgery requires sizable and invasive incisions to expose internal organs and operate on affected areas, but with fiber optics **120** much smaller surgical incisions can be performed. Fiber optics **120** contain components such as a core, cladding, and buffer coating. Fiber optics **120** can be inserted in hypodermic needles and catheters, endoscopes, operation theater tools, ophthalmological tools, and dentistry tools. Fiber optic sensors include a light source, optical fiber, external transducer, and photodetector. Fiber optic sensors can be intrinsic or extrinsic. Fiber optic sensors can be categorized into four types: physical, imaging, chemical, and biological.

[0039] In some embodiments, the system **100** includes surgical lights **122** (referred to as operating

lights) that perform illumination of a local area or cavity of the patient. Surgical lights **122** play an important role in illumination before, during, and after a medical procedure. Surgical lights **122** can be categorized by lamp type as conventional (incandescent) and LED (light-emitting diode). Surgical lights **122** can be categorized by mounting configuration as ceiling-mounted, wall-mounted, or floor stand. Surgical lights **122** can be categorized by type as tungsten, quartz, xenon halogens, and/or LEDs. Surgical lights **122** include sterilizable handles which allow the surgeon to adjust light positions. Some important factors affecting surgical lights **122** can be illumination, shadow management (cast shadows and contour shadows), the volume of light, heat management, or fail-safe surgical lighting.

[0040] In some embodiments, the system **100** includes a surgical tower **128**, e.g., used in conjunction with the robotic surgical system **160** disclosed herein, for MIS. The surgical tower **128** includes instruments used for performing MIS or surgery which is performed by creating small incisions in the body. The instruments are also referred to as minimally invasive devices or minimally invasive access devices. The procedure of performing MIS can also be referred to as a minimally invasive procedure. MIS is a safer, less invasive, and more precise surgical procedure. Some medical procedures where the surgical tower **128** is useful and widely used are procedures for lung, gynecological, head and neck, heart, and urological conditions. MIS can be robotic or non-robotic/endoscopic. MIS can include endoscopic, laparoscopic, arthroscopic, natural orifice intraluminal, and natural orifice transluminal procedures. A surgical tower access device can also be designed as an outer sleeve and an inner sleeve that telescopingly or slidably engages with one another. When a telescope is used to operate on the abdomen, the procedure is called laparoscopy. The surgical tower **128** typically includes access to a variety of surgical tools, such as, for example, electrocautery, radiofrequency, lasers, sensors, etc.

[0041] In some embodiments, radiofrequency (RF) is used in association with MIS devices. The RF can be used for the treatment of skin by delivering it to the skin through a minimally invasive surgical tool (e.g., fine needles) which does not require skin excision. The RF can be used for real-time tracking of MIS devices such as laparoscopic instruments. The RF can provide radiofrequency ablation to a patient suffering from atrial fibrillation through smaller incisions made between the ribs. The RF can be used to perform an endoscopic surgery on the body such as the spine by delivery of RF energy.

[0042] In some embodiments, the system **100** includes an instrument **130** to perform electrocautery for burning a part of the body to remove or close off a part of it. Various physiological conditions or surgical procedures require the removal of body tissues and organs, a consequence of which is bleeding. In order to achieve hemostasis and for removing and sealing all blood vessels which are supplied to an organ after surgical incision, the electrocautery instrument **130** can be used. For example, after removing part of the liver for removal of a tumor, etc., blood vessels in the liver must be sealed individually. The electrocautery instrument **130** can be used for sealing living tissue such as arteries, veins, lymph nodes, nerves, fats, ligaments, and other soft tissue structures. The electrocautery instrument **130** can be used in applications such as surgery, tumor removal, nasal treatment, or wart removal. Electrocautery can operate in two modes, monopolar or bipolar. The electrocautery instrument can **130** consist of a generator, a handpiece, and one or more electrodes.

[0043] In some embodiments, the system **100** includes a laser **132** used in association with MIS devices. The laser **132** can be used in MIS with an endoscope. The laser **132** is attached to the distal end of the endoscope and steered at high speed by producing higher incision quality than with existing surgical tools and minimizing damage to surrounding tissue. The laser **132** can be used to perform MIS using a laparoscope in the lower and upper gastrointestinal tract, eye, nose, and throat. The laser **132** is used in MIS to ablate soft tissues, such as a herniated spinal disc bulge.

[0044] In some embodiments, sensors **134** are used in association with MIS devices and the robotic surgical system **160** described herein. The sensors **134** can be used in MIS for tactile sensing of surgical tool-tissue interaction forces. During MIS, the field of view and workspace of surgical

tools are compromised due to the indirect access to the anatomy and lack of surgeon's hand-eye coordination. The sensors **134** provide a tactile sensation to the surgeon by providing information of shape, stiffness, and texture of organ or tissue (different characteristics) to the surgeon's hands through a sense of touch. This detects a tumor through palpation, which exhibits a “tougher” feel than that of healthy soft tissue, pulse felt from blood vessels, and abnormal lesions. The sensors **134** can output shape, size, pressure, softness, composition, temperature, vibration, shear, and normal forces. The sensors **134** can be electrical or optical, consisting of capacitive, inductive, piezoelectric, piezoresistive, magnetic, and auditory. The sensors **134** can be used in robotic or laparoscopic surgery, palpation, biopsy, heart ablation, and valvuloplasty.

[0045] In some embodiments, the system **100** includes an imaging system **136** (instruments are used for the creation of images and visualization of the interior of a human body for diagnostic and treatment purposes). The imaging system **136** is used in different medical settings and can help in the screening of health conditions, diagnosing causes of symptoms, or monitoring of health conditions. The imaging system **136** can include various imaging techniques such as X-ray, fluoroscopy, magnetic resonance imaging (MRI), ultrasound, endoscopy, elastography, tactile imaging, thermography, medical photography, and nuclear medicine, e.g., positron emission tomography (PET). Some factors which can drive the market are cost and clinical advantages of medical imaging modalities, a rising share of ageing populations, increasing prevalence of cardiovascular or lifestyle diseases, and increasing demand from emerging economies.

[0046] In some embodiments, the imaging system **136** includes X-ray medical imaging instruments that use X-ray radiation (i.e., X-ray range in the electromagnetic radiation spectrum) for the creation of images of the interior of the human body for diagnostic and treatment purposes. An X-ray instrument is also referred to as an X-ray generator. It is a non-invasive instrument based on different absorption of X-rays by tissues based on their radiological density (radiological density is different for bones and soft tissues). For the creation of an image by the X-ray instrument, X-rays produced by an X-ray tube are passed through a patient positioned to the detector. As the X-rays pass through the body, images appear in shades of black and white, depending on the type and densities of tissue the X-rays pass through. Some of the applications where X-rays are used can be bone fractures, infections, calcification, tumors, arthritis, blood vessel blockages, digestive problems, or heart problems. The X-ray instrument can consist of components such as an X-ray tube, operating console, collimator, grid, detector, radiographic film, etc.

[0047] In some embodiments, the imaging system **136** includes MRI medical imaging instruments that use powerful magnets for the creation of images of the interior of the human body for diagnostic and treatment purposes. Some of the applications where MRI can be used can be brain/spinal cord anomalies, tumors in the body, breast cancer screening, joint injuries, uterine/pelvic pain detection, or heart problems. For the creation of the image by an MRI instrument, magnetic resonance is produced by powerful magnets which produce a strong magnetic field that forces protons in the body to align with that field. When a radiofrequency current is then pulsed through the patient, the protons are stimulated, and spin out of equilibrium, straining against the pull of the magnetic field. Turning off the radiofrequency field allows detection of energy released by realignment of protons with the magnetic field by MRI sensors. The time taken by the protons for realignment with the magnetic field and energy release is dependent on environmental factors and the chemical nature of the molecules. MRI can more widely suit for imaging of non-bony parts or soft tissues of the body. MRI can be less harmful as it does not use damaging ionizing radiation as in the X-ray instrument. MRI instruments can consist of magnets, gradients, radiofrequency systems, or computer control systems. Some areas where imaging by MRI should be prohibited can be people with implants.

[0048] In some embodiments, the imaging system **136** uses computed tomography imaging (CT) that uses an X-ray radiation (i.e., X-ray range in the electromagnetic radiation spectrum) for the creation of cross-sectional images of the interior of the human body. CT refers to a computerized

X-ray imaging procedure in which a narrow beam of X-rays is aimed at a patient and quickly rotated around the body, producing signals that are processed by the machine's computer to generate cross-sectional images—or “slices”—of the body. A CT instrument is different from an X-ray instrument as it creates 3-dimensional cross-sectional images of the body while the X-ray instrument creates 2-dimensional images of the body; the 3-dimensional cross-sectional images are created by taking images from different angles, which is done by taking a series of tomographic images from different angles. The diverse images are collected by a computer and digitally stacked to form a 3-dimensional image of the patient. For creation of images by the CT instrument, a CT scanner uses a motorized X-ray source that rotates around the circular opening of a donut-shaped structure called a gantry while the X-ray tube rotates around the patient shooting narrow beams of X-rays through the body. Some of the applications where CT can be used can be blood clots; bone fractures, including subtle fractures not visible on X-ray; or organ injuries.

[0049] In some embodiments, the imaging system **136** includes ultrasound imaging, also referred to as sonography or ultrasonography, that uses ultrasound or sound waves (also referred to as acoustic waves) for the creation of cross-sectional images of the interior of the human body. Ultrasound waves in the imaging system **136** can be produced by a piezoelectric transducer which produces sound waves and sends them into the body. The sound waves that are reflected are converted into electrical signals which are sent to an ultrasound scanner. Ultrasound instruments can be used for diagnostic and functional imaging or for therapeutic or interventional procedures. Some of the applications where ultrasound can be used are diagnosis/treatment/guidance during medical procedures (e.g., biopsies, internal organs such as liver/kidneys/pancreas, fetal monitoring, etc.), in soft tissues, muscles, blood vessels, tendons, or joints. Ultrasound can be used for internal imaging (where the transducer is placed in organs, e.g., vagina) and external imaging (where the transducer is placed on the chest for heart monitoring or the abdomen for the fetal monitoring). An ultrasound machine can consist of a monitor, keyboard, processor, data storage, probe, and transducer.

[0050] In some embodiments, the system **100** includes a stereotactic navigation system **138** that uses patient imaging (e.g., CT, MRI) to guide surgeons in the placement of specialized surgical instruments and implants. The patient images are taken to guide the physician before or during the medical procedure. The stereotactic navigation system **138** includes a camera having infrared sensors to determine the location of the tip of the probe being used in the surgical procedure. This information is sent in real-time so that the surgeons have a clear image of the precise location where they are working in the body. The stereotactic navigation system **138** can be framed (requires attachment of a frame to the patient's head using screws or pins) or frameless (does not require the placement of a frame on the patient's anatomy). The stereotactic navigation system **138** can be used for diagnostic biopsies, tumor resection, bone preparation/implant placement, placement of electrodes, otolaryngologic procedures, or neurosurgical procedures.

[0051] In some embodiments, the system **100** includes an anesthesiology machine **140** that is used to generate and mix medical gases, such as oxygen or air, and anesthetic agents to induce and maintain anesthesia in patients. The anesthesiology machine **140** delivers oxygen and anesthetic gas to the patient and filters out expiratory carbon dioxide. The anesthesiology machine **140** can perform functions such as providing oxygen (O₂), accurately mixing anesthetic gases and vapors, enabling patient ventilation, and minimizing anesthesia-related risks to patients and staff. The anesthesiology machine **140** can include the following essential components: a source of O₂, O₂ flowmeter, vaporizer (anesthetics include isoflurane, halothane, enflurane, desflurane, sevoflurane, and methoxyflurane), patient breathing circuit (tubing, connectors, and valves), and scavenging system (removes any excess anesthetics gases). The anesthesiology machine **140** can be divided into three parts: the high pressure system, the intermediate pressure system, and the low pressure system. The process of anesthesia starts with oxygen flow from a pipeline or cylinder through the flowmeter; the O₂ flows through the vaporizer and picks up the anesthetic vapors; the O₂-anesthetic mix then flows through the breathing circuit and into the patient's lungs, usually by

spontaneous ventilation or normal respiration.

[0052] In some embodiments, the system **100** includes a surgical bed **142** equipped with mechanisms that can elevate or lower the entire bed platform; flex, or extend individual components of the platform; or raise or lower the head or the feet of the patient independently. The surgical bed **142** can be an operation bed, cardiac bed, amputation bed, or fracture bed. Some essential components of the surgical bed **142** can be a bed sheet, woolen blanket, bath towel, and bed block. The surgical bed **142** can also be referred to as a post-operative bed, which refers to a special type of bed made for the patient who is coming from the operation theater or from another procedure that requires anesthesia. The surgical bed **142** is designed in a manner that makes it easier to transfer an unconscious or weak patient from a stretcher/wheelchair to the bed. The surgical bed **142** should protect bed linen from vomiting, bleeding, drainage, and discharge; provide warmth and comfort to the patient to prevent shock; provide necessary positions, which are suitable for operation; protect patient from being chilled; and be prepared to meet any emergency.

[0053] In some embodiments, the system **100** includes a Jackson frame **144** (or Jackson table), which refers to a frame or table which is designed for use in spinal surgeries and can be used in a variety of spinal procedures in supine, prone, or lateral positions in a safe manner. Two peculiar features of the Jackson table **144** are no central table support and an ability to rotate the table through 180 degrees. The Jackson table **144** is supported at both ends which keeps the whole of the table free. This allows the visualization of a patient's trunk and major parts of extremities as well. The Jackson frame **144** allows the patient to be slid from the cart onto the table in the supine position with appropriate padding placed. The patient is then strapped securely on the Jackson table **144**.

[0054] In some embodiments, the system **100** includes a disposable air warmer **146** (sometimes referred to as a Bair™ or Bair Hugger™). The disposable air warmer **146** is a convective temperature management system used in a hospital or surgery center to maintain a patient's core body temperature. The disposable air warmer **146** includes a reusable warming unit and a single-use disposable warming blanket for use during surgery. It can also be used before and after surgery. The disposable air warmer **146** uses convective warming consisting of two components: a warming unit and a disposable blanket. The disposable air warmer **146** filters air and then forces warm air through disposable blankets which cover the patient. The blanket can be designed to use pressure points on the patient's body to prevent heat from reaching areas at risk for pressure sores or burns. The blanket can also include drain holes where fluid passes through the surface of the blanket to linen underneath which will reduce the risk of skin softening and reduce the risk of unintended cooling because of heat loss from evaporation.

[0055] In some embodiments, the system **100** includes a sequential compression device (SCD) **148** used to help prevent blood clots in the deep veins of legs. The sequential compression device **148** uses cuffs around the legs that fill with air and squeeze the legs. This increases blood flow through the veins of the legs and helps prevent blood clots. A deep vein thrombosis (DVT) is a blood clot that forms in a vein deep inside the body. Some of the risks of using the SCD **148** can be discomfort, warmth, sweating beneath the cuff, skin breakdown, nerve damage, or pressure injury.

[0056] In some embodiments, the system **100** includes a bed position controller **150**, which refers to an instrument for controlling the position of the patient bed. Positioning a patient in bed is important for maintaining alignment and for preventing bedsores (pressure ulcers), foot drop, and contractures. Proper positioning is also vital for providing comfort for patients who are bedridden or have decreased mobility related to a medical condition or treatment. When positioning a patient in bed, supportive devices such as pillows, rolls, and blankets, along with repositioning, can aid in providing comfort and safety. The patient can be in the following positions in a bed: supine position, prone position, lateral position, Sims' position, Fowler's position, semi-Fowler's position, orthopedic or tripod position, or Trendelenburg position.

[0057] In some embodiments, the system **100** includes environmental controls **152**. The

environmental controls **152** can be operating room environmental controls for control or maintenance of the environment in the operating room **102** where procedures are performed to minimize the risk of airborne infection and to provide a conducive environment for everyone in the operating room **102** (e.g., surgeon, anesthesiologist, nurses, and patient). Some factors which can contribute to poor quality in the environment of the operating room **102** are temperature, ventilation, and humidity, and those conditions can lead to profound effects on the health and work productivity of people in the operating room **102**. As an example: surgeons prefer a cool, dry climate since they work in bright, hot lights; anesthesia personnel prefer a warmer, less breezy climate; patient condition demands a relatively warm, humid, and quiet environment. The operating room environmental controls can control the environment by taking care of the following factors: environmental humidity, infection control, or odor control. Humidity control can be performed by controlling the temperature of anesthesia gases; infection can be controlled by the use of filters to purify the air.

[0058] In some embodiments, the environmental controls **152** include a heating, ventilation, and air conditioning (HVAC) system for regulating the environment of indoor settings by moving air between indoor and outdoor areas, along with heating and cooling. HVAC can use a different combination of systems, machines, and technologies to improve comfort. HVAC can be necessary to maintain the environment of the operating room **102**. The operating room **102** can be a traditional operating room (which can have a large diffuser array directly above the operating table) or a hybrid operating room (which can have monitors and imaging equipment **136** that consume valuable ceiling space and complicate the design process). HVAC can include three main units, for example, a heating unit (e.g., furnace or boiler), a ventilation unit (natural or forced), and an air conditioning unit (which can remove existing heat). HVAC can be made of components such as air returns, filters, exhaust outlets, ducts, electrical elements, outdoor units, compressors, coils, and blowers. The HVAC system can use central heating and AC systems that use a single blower to circulate air via internal ducts.

[0059] In some embodiments, the environmental controls **152** include an air purification system for removing contaminants from the air in the operating room **102** to improve indoor air quality. Air purification can be important in the operating room **102** as surgical site infection can be a reason for high mortality and morbidity. The air purification system can deliver clean, filtered, contaminant-free air over the surgical bed **142** using a diffuser, airflow, etc., to remove all infectious particles down and away from the patient. The air purification system can be an air curtain, multi-diffuser array, or single large diffuser (based on laminar diffuser flow) or High-Efficiency Particulate Air filter. High-Efficiency Particulate Air filter (HEPA filter) protects from infection and contamination by a filter which is mounted at the terminal of the duct. A HEPA filter can be mounted on the ceiling and deliver clean, filtered air in a flow to the operating room **102** that provides a sweeping effect that pushes contaminants out via the return grilles that are usually mounted on the lower wall.

[0060] In some embodiments, the system **100** includes one or more medical or surgical tools **154**. The surgical tools **154** can include orthopedic tools (also referred to as orthopedic instruments) used for treatment and prevention of deformities and injuries of the musculoskeletal system or skeleton, articulations, and locomotive system (i.e., set formed by skeleton, muscles attached to it, and the part of the nervous system which controls the muscles). A major percentage of orthopedic tools are made of plastic. The orthopedic tools can be divided into the following specialties: hand and wrist, foot and ankle, shoulder and elbow, arthroscopic, hip, and knee. The orthopedic tools can be fixation tools, relieving tools, corrective tools, or compression-distraction tools. A fixation tool refers to a tool designed to restrict movements partially or completely in a joint, e.g., hinged splints (for preserving a certain range of movement in a joint) or rigid splints. A relieving tool refers to a tool designed to relieve pressure on an ailing part by transferring support to healthy parts of an extremity, e.g., Thomas splint and the Voskoboinikova apparatus. A corrective tool refers to a

surgical tool designed to gradually correct a deformity, e.g., corsets, splints, orthopedic footwear, insoles, and other devices to correct abnormal positions of the foot. A compression-distraction tool refers to a surgical tool designed to correct acquired or congenital deformities of the extremities, e.g., curvature, shortening, and pseudarthrosis such as Gudushauri. A fixation tool can be an internal fixation tool (e.g., screws, plates) or external fixation tools used to correct a radius or tibia fracture. The orthopedic tools can be bone-holding forceps, drill bits, nail pins, hammers, staples, etc.

[0061] In some embodiments, the surgical tools **154** include a drill for making holes in bones for insertion of implants like nails, plates, screws, and wires. The drill tool functions by drilling cylindrical tunnels into bone. Drills can be used in orthopedics for performing medical procedures. If the drill does not stop immediately when used, the use of the drill on bones can have some risks, such as harm caused to bone, muscle, nerves, and venous tissues, which are wrapped by surrounding tissue. Drills vary widely in speed, power, and size. Drills can be powered as electrical, pneumatic, or battery. Drills generally can work on speeds below 1000 rpm in orthopedic settings. Temperature control of drills is an important aspect in the functioning of the drill and is dependent on parameters such as rotation speed, torque, orthotropic site, sharpness of the cutting edges, irrigation, and cooling systems. The drill can include a physical drill, power cord, electronically motorized bone drill, or rotating bone shearing incision work unit.

[0062] In some embodiments, the surgical tools **154** include a scalpel for slicing, cutting, or osteotomy of bone during orthopedic procedure. The scalpel can be designed to provide clean cuts through osseous structures with minimal loss of viable bone while sparing adjacent elastic soft tissues largely unaffected while performing a slicing procedure. This is suited for spine applications where bone must be cut adjacent to the dura and neural structures. The scalpel does not rotate but performs cutting by an ultrasonically oscillating or forward/backward moving metal tip. Scalpels can prevent injuries caused by a drill in a spinal surgery such as complications such as nerve thermal injury, grasping soft tissue, tearing dura mater, and mechanical injury.

[0063] In some embodiments, stitches (also referred to as sutures) or a sterile, surgical thread is used to repair cuts or lacerations and is used to close incisions or hold body tissues together after a surgery or an injury. Stitches can involve the use of a needle along with an attached thread. Stitches can be of type absorbable (the stitches automatically break down harmlessly in the body over time without intervention) and non-absorbable (the stitches do not automatically break down over time and must be manually removed if not left indefinitely). Stitches can be based on material monofilament, multifilament, and barb. Stitches can be classified based on size. Stitches can be based on synthetic or natural material. Stitches can be coated or un-coated.

[0064] In some embodiments, the surgical tools **154** include a stapler used for fragment fixation when inter-fragmental screw fixation is not easy. When there is vast damage and a bone is broken into fragments, staples can be used between these fragments for internal fixation and bone reconstruction. For example, they can be used around joints in ankle and foot surgeries, in cases of soft tissue damage, or to attach tendons or ligaments to the bone for reconstruction surgery. Staplers can be made of surgical grade stainless steel or titanium, and they are thicker, stronger, and larger.

[0065] In some embodiments, other medical or surgical equipment, such as a set of articles, surgical tools, or objects, is used to implement or achieve an operation or activity. A medical equipment refers to an article, instrument, apparatus, or machine used for diagnosis, prevention, or treatment of a medical condition or disease, or to the detection, measurement, restoration, correction, or modification of structure/function of the body for some health purpose. The medical equipment can perform functions invasively or non-invasively. In some embodiments, the medical equipment includes components such as sensor/transducer, signal conditioner, display, data storage unit, etc. In some embodiments, the medical equipment includes a sensor to receive a signal from a measurand/patient; a transducer for converting one form of energy to electrical energy; a signal conditioner such as an amplifier, filter, etc., to convert the output from the transducer into an

electrical value; a display to provide a visual representation of the measured parameter or quantity; and a storage system to store data which can be used for future reference. A medical equipment can perform diagnosis or provide therapy; for example, the equipment delivers air into the lungs of a patient who is physically unable to breathe, or breathes insufficiently, and moves it out of the lungs. [0066] In some embodiments, the system includes a machine **156** to aid in breathing. The machine **156** can be a ventilator (also referred to as a respirator) that provides a patient with oxygen when they are unable to breathe on their own. A ventilator is required when a person is not able to breathe on their own. A ventilator can perform a function of gently pushing air into the lungs and allows it to come back out. The ventilator functions by delivery of positive pressure to force air into the lungs, while usual breathing uses negative pressure by the opening of the mouth, and air flows in. The ventilator can be required during surgery or after surgery. The ventilator can be required in case of respiratory failure due to acute respiratory distress syndrome, head injury, asthma, lung diseases, drug overdose, neonatal respiratory distress syndrome, pneumonia, sepsis, spinal cord injury, cardiac arrest, etc., or during surgery. The ventilator can be used with a face mask (non-invasive ventilation, where the ventilation is required for a shorter duration of time) or with a breathing tube also referred to as an endotracheal tube (invasive ventilation, where the ventilation is required for a longer duration of time). Ventilator use can have some risks such as infections, fluid build-up, muscle weakness, lung damage, etc. The ventilator can be operated in various modes, such as assist-control ventilation (ACV), synchronized intermittent-mandatory ventilation (SIMV), pressure-controlled ventilation (PCV), pressure support ventilation (PSV), pressure-controlled inverse ratio ventilation (PCIRV), airway pressure release ventilation (APRV), etc. The ventilator can include a gas delivery system, power source, control system, safety feature, gas filter, and monitor.

[0067] In some embodiments, the machine **156** is a continuous positive airway pressure (CPAP) used for the treatment of sleep apnea disorder in a patient. Sleep apnea refers to a disorder in which breathing repeatedly stops and starts while a patient is sleeping, often because throat/airways briefly collapse or something temporarily blocks them. Sleep apnea can lead to serious health problems, such as high blood pressure and heart trouble. A CPAP instrument helps the patient with sleep apnea to breathe more easily during sleep by sending a steady flow of oxygen into the nose and mouth during sleep, which keeps the airways open and helps the patient to breathe normally. The CPAP machine can work by a compressor/motor which generates a continuous stream of pressurized air which travels through an air filter into a flexible tube. The tube delivers purified air into a mask sealed around the nose/mouth of the patient. The airstream from the instrument pushes against any blockages, opening the airways so lungs receive plenty of oxygen, and breathing does not stop as nothing obstructs oxygen. This helps the patient to not wake up to resume breathing. CPAP can have a nasal pillow mask, nasal mask, or full mask. CPAP instrument can include a motor, a cushioned mask, a tube that connects the motor to the mask, a headgear frame, and adjustable straps. The essential components can be a motor, a cushioned mask, and a tube that connects the motor to the mask.

[0068] In some embodiments, the system **100** includes surgical supplies, consumables **158**, or necessary supplies for the system **100** to provide care within the hospital or surgical environment. The consumables **158** can include gloves, gowns, masks, syringes, needles, sutures, staples, tubing, catheters, or adhesives for wound dressing, in addition to other surgical tools needed by doctors and nurses to provide care. Depending on the device, mechanical testing can be carried out in tensile, compression, or flexure; in dynamic or fatigue; via impact; or with the application of torsion. The consumables **158** can be disposable (e.g., time-saving, have no risk of healthcare-associated infections, and cost-efficient) or sterilizable (to avoid cross-contamination or risk of surgical site infections).

[0069] In some embodiments, the system **100** includes a robotic surgical system **160** (sometimes referred to as a medical robotic system or a robotic system) that provides intelligent services and

information to the operating room **102** and the console **108** by interacting with the environment, including human beings, via the use of various sensors, actuators, and human interfaces. The robotic surgical system **160** can be employed for automating processes in a wide range of applications, ranging from industrial (manufacturing), domestic, medical, service, military, entertainment, space, etc. The medical robotic system market is segmented by product type into surgical robotic systems, rehabilitative robotic systems, non-invasive radiosurgery robots, and hospital and pharmacy robotic systems. Robotic surgeries are performed using tele-manipulators (e.g., input devices **166** at the console **108**), which use the surgeon's actions on one side to control one or more “effectors” on the other side. The medical robotic system **160** provides precision and can be used for remotely controlled, minimally invasive procedures. The robotic surgical system **160** includes computer-controlled electromechanical devices that work in response to controls (e.g., input devices **166** at the console **108**) manipulated by the surgeons.

[0070] In some embodiments, the system **100** includes equipment tracking systems **162**, such as RFID, which is used to tag an instrument with an electronic tag and tracks it using the tag. Typically, this could involve a centralized platform that provides details such as location, owner, contract, and maintenance history for all equipment in real-time. A variety of techniques can be used to track physical assets, including RFID, global positioning system (GPS), Bluetooth low energy (BLE), barcodes, near-field communication (NFC), Wi-Fi, etc. The equipment tracking system **162** includes hardware components, such as RFID tags, GPS trackers, barcodes, and QR codes. The hardware component is placed on the asset, and it communicates with the software (directly or via a scanner), providing the software with data about the asset's location and properties. In some embodiments, the equipment tracking system **162** uses electromagnetic fields to transmit data from an RFID tag to a reader. Reading of RFID tags can be done by portable or mounted RFID readers. The read range for RFID varies with the frequency used. Managing and locating important assets is a key challenge for tracking medical equipment. Time spent searching for critical equipment can lead to expensive delays or downtime, missed deadlines and customer commitments, and wasted labor. The problem has previously been solved by using barcode labels or manual serial numbers and spreadsheets; however, these require manual labor. The RFID tag can be passive (smaller and less expensive, read ranges are shorter, have no power of their own, and are powered by the radio frequency energy transmitted from RFID readers/antennas) or active (larger and more expensive, read ranges are longer, have a built-in power source and transmitter of their own).

[0071] In some embodiments, the system **100** includes medical equipment, computers, software, etc., located in the doctor's office **110** that is communicably coupled to the operating room **102** over the network **104**. For example, the medical equipment in the doctor's office **110** can include a microscope **116** used for viewing samples and objects that cannot be seen with an unaided eye. The microscope **116** can have components such as eyepieces, objective lenses, adjustment knobs, a stage, an illuminator, a condenser, or a diaphragm. The microscope **116** works by manipulating how light enters the eye using a convex lens, where both sides of the lens are curved outwards. When light reflects off of an object being viewed under the microscope **116** and passes through the lens, it bends toward the eye. This makes the object look bigger than it is. The microscope **116** can be compound (light-illuminated and the image seen with the microscope **116** is two-dimensional), dissection or stereoscope (light-illuminated and the image seen with the microscope **116** is three-dimensional), confocal (laser-illuminated and the image seen with the microscope **116** is on a digital computer screen), scanning electron (SEM) (electron-illuminated and the image seen with the microscope **116** is in black and white), or transmission electron microscope (TEM) (electron-illuminated and the image seen with the microscope **116** is the high magnification and high resolution).

[0072] The system **100** includes an electronic health records (EHR) database **106** that contains patient records. The EHR are a digital version of patients' paper charts. The EHR database **106** can

contain more information than a traditional patient chart, including, but not limited to, a patients' medical history, diagnoses, medications, treatment plans, allergies, diagnostic imaging, lab results, etc. In some embodiments, the steps for each procedure disclosed herein are stored in the EHR database **106**. Electronic health records can also include data collected from the monitors **112** from historical procedures. The EHR database **106** is implemented using components of the example computer system **300** illustrated and described in more detail with reference to FIG. 3.

[0073] In some embodiments, the EHR database **106** includes a digital record of patients' health information, collected and stored systematically over time. The EHR database **106** can include demographics, medical history, history of present illness (HPI), progress notes, problems, medications, vital signs, immunizations, laboratory data, or radiology reports. Software (in memory **164**) operating on the console **108** or implemented on the example computer system **300** (e.g., the instructions **304**, **308** illustrated and described in more detail with reference to FIG. 3) are used to capture, store, and share patient data in a structured way. The EHR database **106** can be created and managed by authorized providers and can make health information accessible to authorized providers across practices and health organizations, such as laboratories, specialists, medical imaging facilities, pharmacies, emergency facilities, etc. The timely availability of EHR data enables healthcare providers to make more accurate decisions and provide better care to the patients by effective diagnosis and reduced medical errors. Besides providing opportunities to enhance patient care, the EHR database **106** can also be used to facilitate clinical research by combining patients' demographics into a large pool. For example, the EHR database **106** can support a wide range of epidemiological research on the natural history of disease, drug utilization, and safety, as well as health services research.

[0074] The console **108** is a computer device, such as a server, computer, tablet, smartphone, smart speaker, etc., implemented using components of the example computer system **300** illustrated and described in more detail with reference to FIG. 3. In some embodiments, the steps for each procedure disclosed herein are stored in memory **164** on the console **108** for execution.

[0075] In some embodiments, the operating room **102** or the console **108** includes high-definition monitors **124**, which refer to displays in which a clearer picture is possible than with low-definition, low-resolution screens. The high-definition monitors **124** have a higher density of pixels per inch than past standard TV screens. Resolution for the high-definition monitors **124** can be 1280×720 pixels or more (e.g., Full HD, 1920×1080; Quad HD, 2560×1440; 4K, 3840×2160; 8K, 7680×4320 pixels). The high-definition monitor **124** can operate in progressive or interlaced scanning mode. High-definition monitors used in medical applications can offer improved visibility; allow for precise and safe surgery with rich color reproduction; provide suitable colors for each clinical discipline; provide better visibility, operability with a large screen and electronic zoom, higher image quality in low light conditions, better visualization of blood vessels and lesions, and high contrast at high spatial frequencies; be twice as sensitive as conventional sensors; and make it easier to determine tissue boundaries (fat, nerves, vessels, etc.).

[0076] In some embodiments, the console **108** includes an input interface or one or more input devices **166**. The input devices **166** can include a keyboard, a mouse, a joystick, any hand-held controller, or a hand-controlled manipulator, e.g., a tele-manipulator used to perform robotic surgery.

[0077] In some embodiments, the console **108**, the equipment in the doctor's office **110**, and the EHR database **106** are communicatively coupled to the equipment in the operating room **102** by a direct connection, such as ethernet, or wirelessly by the cloud over the network **104**. The network **104** is the same as or similar to the network **314** illustrated and described in more detail with reference to FIG. 3. For example, the console **108** can communicate with the robotic surgical system **160** using the network adapter **312** illustrated and described in more detail with reference to FIG. 3.

[0078] FIG. 2 is a block diagram illustrating an example machine learning (ML) system **200**, in

accordance with one or more embodiments. The ML system **200** is implemented using components of the example computer system **300** illustrated and described in more detail with reference to FIG. **3**. For example, the ML system **200** can be implemented on the console **108** using instructions programmed in the memory **164** illustrated and described in more detail with reference to FIG. **1**. Likewise, embodiments of the ML system **200** can include different and/or additional components or be connected in different ways. The ML system **200** is sometimes referred to as a ML module. [0079] The ML system **200** includes a feature extraction module **208** implemented using components of the example computer system **300** illustrated and described in more detail with reference to FIG. **3**. In some embodiments, the feature extraction module **208** extracts a feature vector **212** from input data **204**. For example, the input data **204** can include one or more physiological parameters measured by the monitors **112** illustrated and described in more detail with reference to FIG. **1**. The feature vector **212** includes features **212a**, **212b**, . . . , **212n**. The feature extraction module **208** reduces the redundancy in the input data **204**, e.g., repetitive data values, to transform the input data **204** into the reduced set of features **212**, e.g., features **212a**, **212b**, . . . , **212n**. The feature vector **212** contains the relevant information from the input data **204**, such that events or data value thresholds of interest can be identified by the ML model **216** by using this reduced representation. In some example embodiments, the following dimensionality reduction techniques are used by the feature extraction module **208**: independent component analysis, Isomap, kernel principal component analysis (PCA), latent semantic analysis, partial least squares, PCA, multifactor dimensionality reduction, nonlinear dimensionality reduction, multilinear PCA, multilinear subspace learning, semidefinite embedding, autoencoder, and deep feature synthesis.

[0080] In alternate embodiments, the ML model **216** performs deep learning (also known as deep structured learning or hierarchical learning) directly on the input data **204** to learn data representations, as opposed to using task-specific algorithms. In deep learning, no explicit feature extraction is performed; the features **212** are implicitly extracted by the ML system **200**. For example, the ML model **216** can use a cascade of multiple layers of nonlinear processing units for implicit feature extraction and transformation. Each successive layer uses the output from the previous layer as input. The ML model **216** can thus learn in supervised (e.g., classification) and/or unsupervised (e.g., pattern analysis) modes. The ML model **216** can learn multiple levels of representations that correspond to different levels of abstraction, wherein the different levels form a hierarchy of concepts. In this manner, the ML model **216** can be configured to differentiate features of interest from background features.

[0081] In alternative example embodiments, the ML model **216**, e.g., in the form of a CNN generates the output **224**, without the need for feature extraction, directly from the input data **204**. The output **224** is provided to the computer device **228** or the console **108** illustrated and described in more detail with reference to FIG. **1**. The computer device **228** is a server, computer, tablet, smartphone, smart speaker, etc., implemented using components of the example computer system **300** illustrated and described in more detail with reference to FIG. **3**. In some embodiments, the steps performed by the ML system **200** are stored in memory on the computer device **228** for execution. In other embodiments, the output **224** is displayed on the high-definition monitors **124** illustrated and described in more detail with reference to FIG. **1**.

[0082] A CNN is a type of feed-forward artificial neural network in which the connectivity pattern between its neurons is inspired by the organization of a visual cortex. Individual cortical neurons respond to stimuli in a restricted region of space known as the receptive field. The receptive fields of different neurons partially overlap such that they tile the visual field. The response of an individual neuron to stimuli within its receptive field can be approximated mathematically by a convolution operation. CNNs are based on biological processes and are variations of multilayer perceptrons designed to use minimal amounts of preprocessing.

[0083] The ML model **216** can be a CNN that includes both convolutional layers and max pooling

layers. The architecture of the ML model **216** can be “fully convolutional,” which means that variable sized sensor data vectors can be fed into it. For all convolutional layers, the ML model **216** can specify a kernel size, a stride of the convolution, and an amount of zero padding applied to the input of that layer. For the pooling layers, the model **216** can specify the kernel size and stride of the pooling.

[0084] In some embodiments, the ML system **200** trains the ML model **216**, based on the training data **220**, to correlate the feature vector **212** to expected outputs in the training data **220**. As part of the training of the ML model **216**, the ML system **200** forms a training set of features and training labels by identifying a positive training set of features that have been determined to have a desired property in question, and, in some embodiments, forms a negative training set of features that lack the property in question.

[0085] The ML system **200** applies ML techniques to train the ML model **216**, that when applied to the feature vector **212**, outputs indications of whether the feature vector **212** has an associated desired property or properties, such as a probability that the feature vector **212** has a particular Boolean property, or an estimated value of a scalar property. The ML system **200** can further apply dimensionality reduction (e.g., via linear discriminant analysis (LDA), PCA, or the like) to reduce the amount of data in the feature vector **212** to a smaller, more representative set of data.

[0086] The ML system **200** can use supervised ML to train the ML model **216**, with feature vectors of the positive training set and the negative training set serving as the inputs. In some embodiments, different ML techniques, such as linear support vector machine (linear SVM), boosting for other algorithms (e.g., AdaBoost), logistic regression, naïve Bayes, memory-based learning, random forests, bagged trees, decision trees, boosted trees, boosted stumps, neural networks, CNNs, etc., are used. In some example embodiments, a validation set **232** is formed of additional features, other than those in the training data **220**, which have already been determined to have or to lack the property in question. The ML system **200** applies the trained ML model **216** to the features of the validation set **232** to quantify the accuracy of the ML model **216**. Common metrics applied in accuracy measurement include: Precision and Recall, where Precision refers to a number of results the ML model **216** correctly predicted out of the total it predicted, and Recall is a number of results the ML model **216** correctly predicted out of the total number of features that had the desired property in question. In some embodiments, the ML system **200** iteratively re-trains the ML model **216** until the occurrence of a stopping condition, such as the accuracy measurement indication that the ML model **216** is sufficiently accurate, or a number of training rounds having taken place.

[0087] FIG. **3** is a block diagram illustrating an example computer system, in accordance with one or more embodiments. Components of the example computer system **300** can be used to implement the monitors **112**, the console **108**, or the EHR database **106** illustrated and described in more detail with reference to FIG. **1**. In some embodiments, components of the example computer system **300** are used to implement the ML system **200** illustrated and described in more detail with reference to FIG. **2**. At least some operations described herein can be implemented on the computer system **300**.

[0088] The computer system **300** can include one or more central processing units (“processors”) **302**, main memory **306**, non-volatile memory **310**, network adapters **312** (e.g., network interface), video displays **318**, input/output devices **320**, control devices **322** (e.g., keyboard and pointing devices), drive units **324** including a storage medium **326**, and a signal generation device **320** that are communicatively connected to a bus **316**. The bus **316** is illustrated as an abstraction that represents one or more physical buses and/or point-to-point connections that are connected by appropriate bridges, adapters, or controllers. The bus **316**, therefore, can include a system bus, a Peripheral Component Interconnect (PCI) bus or PCI-Express bus, a HyperTransport or industry standard architecture (ISA) bus, a small computer system interface (SCSI) bus, a universal serial bus (USB), IIC (I2C) bus, or an Institute of Electrical and Electronics Engineers (IEEE) standard 1394 bus (also referred to as “Firewire”).

[0089] The computer system **300** can share a similar computer processor architecture as that of a desktop computer, tablet computer, personal digital assistant (PDA), mobile phone, game console, music player, wearable electronic device (e.g., a watch or fitness tracker), network-connected (“smart”) device (e.g., a television or home assistant device), virtual/augmented reality systems (e.g., a head-mounted display), or another electronic device capable of executing a set of instructions (sequential or otherwise) that specify action(s) to be taken by the computer system **300**.

[0090] While the main memory **306**, non-volatile memory **310**, and storage medium **326** (also called a “machine-readable medium”) are shown to be a single medium, the term “machine-readable medium” and “storage medium” should be taken to include a single medium or multiple media (e.g., a centralized/distributed database and/or associated caches and servers) that store one or more sets of instructions **328**. The term “machine-readable medium” and “storage medium” shall also be taken to include any medium that is capable of storing, encoding, or carrying a set of instructions for execution by the computer system **300**.

[0091] In general, the routines executed to implement the embodiments of the disclosure can be implemented as part of an operating system or a specific application, component, program, object, module, or sequence of instructions (collectively referred to as “computer programs”). The computer programs typically include one or more instructions (e.g., instructions **304**, **308**, **328**) set at various times in various memory and storage devices in a computer device. When read and executed by the one or more processors **302**, the instruction(s) cause the computer system **300** to perform operations to execute elements involving the various aspects of the disclosure.

[0092] Moreover, while embodiments have been described in the context of fully functioning computer devices, those skilled in the art will appreciate that the various embodiments are capable of being distributed as a program product in a variety of forms. The disclosure applies regardless of the particular type of machine or computer-readable media used to actually effect the distribution.

[0093] Further examples of machine-readable storage media, machine-readable media, or computer-readable media include recordable-type media such as volatile and non-volatile memory devices **310**, floppy and other removable disks, hard disk drives, optical discs (e.g., Compact Disc Read-Only Memory (CD-ROMS), Digital Versatile Discs (DVDs)), and transmission-type media such as digital and analog communication links.

[0094] The network adapter **312** enables the computer system **300** to mediate data in a network **314** with an entity that is external to the computer system **300** through any communication protocol supported by the computer system **300** and the external entity. The network adapter **312** can include a network adapter card, a wireless network interface card, a router, an access point, a wireless router, a switch, a multilayer switch, a protocol converter, a gateway, a bridge, a bridge router, a hub, a digital media receiver, and/or a repeater.

[0095] The network adapter **312** can include a firewall that governs and/or manages permission to access proxy data in a computer network and tracks varying levels of trust between different machines and/or applications. The firewall can be any number of modules having any combination of hardware and/or software components able to enforce a predetermined set of access rights between a particular set of machines and applications, machines and machines, and/or applications and applications (e.g., to regulate the flow of traffic and resource sharing between these entities). The firewall can additionally manage and/or have access to an access control list that details permissions including the access and operation rights of an object by an individual, a machine, and/or an application, and the circumstances under which the permission rights stand.

[0096] FIG. **4A** is a block diagram illustrating an example robotic surgical system **400**, in accordance with one or more embodiments. The robotic surgical system **400** is the same as or similar to the robotic surgical system **160** illustrated and described in more detail with reference to FIG. **1**. The robotic surgical system **400** can include components and features discussed in connection with FIGS. **1-3** and **4B-5**. For example, the robotic surgical system **400** can include a console **420** with features of the console **108** of FIG. **1**. Likewise, the components and features of

FIG. 4A can be included or used with other embodiments disclosed herein. For example, the description of the input devices of FIG. 4A applies equally to other input devices (e.g., input devices **166** of FIG. 1).

[0097] The robotic surgical system **400** includes a user device or console **420** (“console **420**”), a surgical robot **440**, and a computer or data system **450**. The console **420** can be operated by a surgeon and can communicate with components in an operating room **402**, remote devices/servers, a network **404**, or databases (e.g., database **106** of FIG. 1) via the network **404**. The robotic surgical system **400** can include surgical control software and can include a guidance system (e.g., ML guidance system, AI guidance system, etc.), surgical planning software, event detection software, surgical tool software, etc. or other features disclosed herein to perform surgical step(s) or procedures or implement steps of processes discussed herein.

[0098] The user **421** can use the console **420** to view and control the surgical robot **440**. The console **420** can be communicatively coupled to one or more components disclosed herein and can include input devices operated by one, two, or more users. The input devices can be hand-operated controls, but can alternatively, or in addition, include controls that can be operated by other parts of the user's body, such as, but not limited to, foot pedals. The console **420** can include a clutch pedal to allow the user **421** to disengage one or more sensor-actuator components from control by the surgical robot **440**. The console **420** can also include display or output so that the one or more users can observe the patient being operated on, or the product being assembled, for example. In some embodiments, the display can show images, such as, but not limited to medical images, video, etc. For surgical applications, the images could include, but are not limited to, real-time optical images, real-time ultrasound, real-time OCT images and/or other modalities, or could include pre-operative images, such as MRI, CT, PET, etc. The various imaging modalities can be selectable, programmed, superimposed and/or can include other information superimposed in graphical and/or numerical or symbolic form.

[0099] The robotic surgical system **400** can include multiple consoles **420** to allow multiple users to simultaneously or sequentially perform portions of a surgical procedure. The term “simultaneous” herein refers to actions performed at the same time or in the same surgical step. The number and configuration of consoles **420** can be selected based on the surgical procedure to be performed, number and configurations of surgical robots, surgical team capabilities, or the like.

[0100] FIG. 4B illustrates an example console **420** of the robotic surgical system **400** of FIG. 4A, in accordance with one or more embodiments. The console **420** includes hand-operated input devices **424**, **426**, illustrated held by the user's left and right hands **427**, **428**, respectively. A viewer **430** includes left and right eye displays **434**, **436**. The user can view, for example, the surgical site, instruments **437**, **438**, or the like. The user's movements of the input devices **424**, **426** can be translated in real-time to, for example, mimic the movement of the user on the viewer **430** and display (e.g., display **124** of FIG. 1) and within the patient's body while the user can be provided with output, such as alerts, notifications, and information. The information can include, without limitation, surgical or implantation plans, patient vitals, modification to surgical plans, values, scores, predictions, simulations, and other output, data, and information disclosed herein. The console **420** can be located at the surgical room or at a remote location.

[0101] The viewer **430** can display at least a portion of a surgical plan, including past and future surgical steps, patient monitor readings (e.g., vitals), surgical room information (e.g., available team members, available surgical equipment, surgical robot status, or the like), images (e.g., pre-operative images, images from simulations, real-time images, instructional images, etc.), and other surgical assist information. In some embodiments, the viewer **430** can be a VR/AR headset, display, or the like. The robotic surgical system **400**, illustrated and described in more detail with reference to FIG. 4A, can further include multiple viewers **430** so that multiple members of a surgical team can view the surgical procedure. The number and configuration of the viewers **430** can be selected based on the configuration and number of surgical robots.

[0102] Referring again to FIG. 4A, the surgical robot **440** can include one or more controllers, computers, sensors, arms, articulators, joints, links, grippers, motors, actuators, imaging systems, effector interfaces, end effectors, or the like. For example, a surgical robot with a high number of degrees of freedom can be used to perform complicated procedures whereas a surgical robot with a low number of degrees of freedom can be used to perform simple procedures. The configuration (e.g., number of arms, articulators, degrees of freedom, etc.) and functionality of the surgical robot **440** can be selected based on the procedures to be performed.

[0103] The surgical robot **440** can operate in different modes selected by a user, set by the surgical plan, and/or selected by the robotic surgical system **400**. In some procedures, the surgical robot **440** can remain in the same mode throughout a surgical procedure. In other procedures, the surgical robot **440** can be switched between modes any number of times. The configuration, functionality, number of modes, and type of modes can be selected based on the desired functionality and user control of the robotic surgical system **400**. The robotic surgical system **400** can switch between modes based on one or more features, such as triggers, notifications, warnings, events, etc. Different example modes are discussed below. A trigger can be implemented in software to execute a jump to a particular instruction or step of a program. A trigger can be implemented in hardware, e.g., by applying a pulse to a trigger circuit.

[0104] In a user control mode, a user **421** controls, via the console **420**, movement of the surgical robot **440**. The user's movements of the input devices can be translated in real-time into movement of end effectors **452** (one identified).

[0105] In a semi-autonomous mode, the user **421** controls selected steps and the surgical robot **440** autonomously performs other steps. For example, the user **421** can control one robotic arm to perform one surgical step while the surgical robot **440** autonomously controls one or more of the other arms to concurrently perform another surgical step. In another example, the user **421** can perform steps suitable for physician control. After completion, the surgical robot **440** can perform steps involving coordination between three or more robotic arms, thereby enabling complicated procedures. For example, the surgical robot **440** can perform steps involving four or five surgical arms, each with one or more end effectors **452**.

[0106] In an autonomous mode, the surgical robot **440** can autonomously perform steps under the control of the data system **450**. The robotic surgical system **400** can be pre-programmed with instructions for performing the steps autonomously. For example, command instructions can be generated based on a surgical plan. The surgical robot **440** autonomously performs steps or the entire procedure. The user **421** and surgical team can observe the surgical procedure to modify or stop the procedure. Advantageously, complicated procedures can be autonomously performed without user intervention to enable the surgical team to focus and attend to other tasks. Although the robotic surgical system **400** can autonomously perform steps, the surgical team can provide information in real-time that is used to continue the surgical procedure. The information can include physician input, surgical team observations, and other data input.

[0107] The robotic surgical system **400** can also adapt to the user control to facilitate completion of the surgical procedure. In some embodiments, the robotic surgical system **400** can monitor, via one or more sensors, at least a portion of the surgical procedure performed by the surgical robot **440**. The robotic surgical system **400** can identify an event, such as a potential adverse surgical event, associated with a robotically performed surgical task. For example, a potential adverse surgical event can be determined based on acquired monitoring data and information for the end effector, such as surgical tool data from a medical device report, database, manufacturer, etc. The robotic surgical system **400** can perform one or more actions based on the identified event. The actions can include, without limitation, modification of the surgical plan to address the potential adverse surgical event, thereby reducing the risk of the event occurring.

[0108] In some embodiments, the robotic surgical system **400** can determine whether a detected event is potentially an adverse surgical event based on one or more criteria set by the robotic

surgical system **400**, user, or both. The adverse surgical event can be an adverse physiological event of the patient, surgical robotic malfunction, surgical errors, or other event that can adversely affect the patient or the outcome of the surgery. Surgical events can be defined and inputted by the user, surgical team, healthcare provider, manufacturer of the robotic surgery system, or the like. [0109] The robotic surgical system **400** can take other actions in response to identification of an event. If the robotic surgical system **400** identifies an end effector malfunction or error, the robotic surgical system **400** can stop usage of the end effector and replace the malfunctioning component (e.g., surgical tool or equipment) to complete the procedure. The robotic surgical system **400** can monitor hospital inventory, available resources in the surgical room **402**, time to acquire equipment (e.g., time to acquire replacement end effectors, surgical tools, or other equipment), and other information to determine how to proceed with surgery. The robotic surgical system **400** can generate multiple proposed surgical plans for continuing with the surgical procedure. The user and surgical team can review the proposed surgical plans to select an appropriate surgical plan. The robotic surgical system **400** can modify a surgical plan with one or more corrective surgical steps based on identified surgical complications, sensor readings, or the like.

[0110] The robotic surgical system **400** can retrieve surgical system information from a database to identify events. The database can describe, for example, maintenance of the robotic surgery system, specifications of the robotic surgery system, specifications of end effectors, surgical procedure information for surgical tools, consumable information associated with surgical tools, operational programs and parameters for surgical tools, monitoring protocols for surgical tools, or the like. The robotic surgical system **400** can use other information in databases disclosed herein to generate rules for triggering actions, identifying warnings, defining events, or the like. Databases can be updated with data (e.g., intraoperative data collected during the surgical procedure, simulation data, etc.) to intraoperatively adjust surgical plans, collect data for ML/AI training sets, or the like. Data from on-site and off-site simulations (e.g., pre- or post-operative virtual simulations, simulations using models, etc.) can be generated and collected.

[0111] The surgical robot **440** can include robotic arms **451** (one identified) with integrated or removable end effectors **452** (one identified). The end effectors **452** can include, without limitation, imagers (e.g., cameras, optical guides, etc.), robotic grippers, instrument holders, cutting instruments (e.g., cutters, scalpels, or the like), drills, cannulas, reamers, rongeurs, scissors, clamps, or other equipment or surgical tools disclosed herein. In some embodiments, the end effectors can be reusable or disposable surgical tools. The number and configuration of end effectors can be selected based on the configuration of the robotic system, procedure to be performed, surgical plan, etc. Imaging and viewing technologies can integrate with the surgical robot **440** to provide more intelligent and intuitive results.

[0112] The data system **450** can improve surgical planning, monitoring (e.g., via the display **422**), data collection, surgical robotics/navigation systems, intelligence for selecting instruments, implants, etc. The data system **450** can execute, for example, surgical control instructions or programs for a guidance system (e.g., ML guidance system, AI guidance system, etc.), surgical planning programs, event detection programs, surgical tool programs, etc. For example, the data system **450** can increase procedure efficiency and reduce surgery duration by providing information insertion paths, surgical steps, or the like. The data system **450** can be incorporated into or include other components and systems disclosed herein.

[0113] The robotic surgical system **400** can be used to perform open procedures, minimally invasive procedures, such as laparoscopic surgeries, non-robotic laparoscopic/abdominal surgery, retroperitoneoscopy, arthroscopy, pelviscopy, nephroscopy, cystoscopy, cisternoscopy, sinoscopy, hysteroscopy, urethroscopy, and the like. The methods, components, apparatuses, and systems can be used with many different systems for conducting robotic or minimally invasive surgery. One example of a surgical system and surgical robots which can incorporate methods and technology is the DAVINCI™ system available from Intuitive Surgical, Inc.™ of Mountain View, California.

However, other surgical systems, robots, and apparatuses can be used.

[0114] The robotic surgical system **400** can perform one or more simulations using selected entry port placements and/or robot positions, to allow a surgeon or other user to practice procedures. The practice session can be used to generate, modify, or select a surgical plan. In some embodiments, the system can generate a set of surgical plans for physician consideration. The physician can perform practice sessions for each surgical plan to determine and select a surgical plan to be implemented. In some embodiments, the systems disclosed herein can perform virtual surgeries to recommend a surgical plan. The physician can review the virtual simulations to accept or reject the recommended surgical plan. The physician can modify surgical plans pre-operatively or intraoperatively.

[0115] Embodiments can provide a means for mapping the surgical path for neurosurgery procedures that minimize damage through artificial intelligence mapping. The software for artificial intelligence is trained to track the least destructive pathway. The physician can make an initial incision based on a laser marking on the skin that illuminates the optimal site. Next, a robot can make a small hole and insert surgical equipment (e.g., guide wires, cannulas, etc.) that highlights the best pathway. This pathway minimizes the amount of tissue damage that occurs during surgery. Mapping can also be used to identify one or more insertion points associated with a surgical path. Mapping can be performed before treatment, during treatment, and/or after treatment. For example, pretreatment and posttreatment mapping can be compared by the surgeon and/or ML/AI system. The comparison can be used to determine next steps in a procedure and/or further train the ML/AI system.

[0116] FIG. 5 is a schematic block diagram illustrating subcomponents of the robotic surgical system **400** of FIG. 4A in accordance with embodiment of the present technology. The data system **450** has one or more processors **504**, a memory **506**, input/output devices **508**, and/or subsystems and other components **510**. The processor **504** can perform any of a wide variety of computing processing, image processing, robotic system control, plan generation or modification, and/or other functions. Components of the data system **450** can be housed in a single unit (e.g., within a hospital or surgical room) or distributed over multiple, interconnected units (e.g., though a communications network). The components of the data system **450** can accordingly include local and/or devices.

[0117] As illustrated in FIG. 5, the processor **504** can include a plurality of functional modules **512**, such as software modules, for execution by the processor **504**. The various implementations of source code (i.e., in a conventional programming language) can be stored on a computer-readable storage medium or can be embodied on a transmission medium in a carrier wave. The modules **512** of the processor **504** can include an input module **514**, a database module **516**, a process module **518**, an output module **520**, and, optionally, a display module **522** for controlling the display.

[0118] In operation, the input module **514** accepts an operator input **524** via the one or more input devices, and communicates the accepted information or selections to other components for further processing. The operator input **524** can be received via one or more keyboards, touchscreens, microphones, or other input devices. For voice input, the operator input **524** can include speech input (e.g., physician notes, observations, etc.) from the physician detected using one or more microphones. The data system **450** can perform voice processing to analyze the speech input, as discussed with reference to FIGS. 6-10 and can perform other data processing techniques disclosed herein. The database module **516** organizes plans (e.g., robotic control plans, surgical plans, etc.), records (e.g., maintenance records, patient records, historical treatment data, etc.), surgical equipment data (e.g., instrument specifications), control programs, and operating records and other operator activities, and facilitates storing and retrieving of these records to and from a data storage device (e.g., internal memory **506**, external databases, etc.). Any type of database organization can be utilized, including a flat file system, hierarchical database, relational database, distributed database, etc.

[0119] In the illustrated example, the process module **518** can generate control variables based on

sensor readings **526** from sensors (e.g., end effector sensors of the surgical robot **440**, patient monitoring equipment, etc.), operator input **524** (e.g., input from the surgeon console **420** and/or other data sources), and the output module **520** can communicate operator input to external computing devices and control variables to controllers. The display module **522** can be configured to convert and transmit processing parameters, sensor readings **526**, output signals **528**, input data, treatment profiles and prescribed operational parameters through one or more connected display devices, such as a display screen, touchscreen, printer, speaker system, etc.

[0120] In various embodiments, the processor **504** can be a standard central processing unit or a secure processor. Secure processors can be special-purpose processors (e.g., reduced instruction set processor) that can withstand sophisticated attacks that attempt to extract data or programming logic. The secure processors cannot have debugging pins that enable an external debugger to monitor the secure processor's execution or registers. In other embodiments, the system can employ a secure field-programmable gate array, a smartcard, or other secure devices.

[0121] The memory **506** can be standard memory, secure memory, or a combination of both memory types. By employing a secure processor and/or secure memory, the system can ensure that data and instructions are both highly secure and sensitive operations such as decryption are shielded from observation. In various embodiments, the memory **506** can be flash memory, secure serial EEPROM, secure field-programmable gate array, or secure application-specific integrated circuit. The memory **506** can store instructions for causing the surgical robot **440** to perform acts disclosed herein.

[0122] The input/output device **508** can include, without limitation, a touchscreen, a keyboard, a mouse, a stylus, a push button, a switch, a potentiometer, a scanner, an audio component such as a microphone, or any other device suitable for accepting user input and can also include one or more video monitors, a medium reader, an audio device such as a speaker, any combination thereof, and any other device or devices suitable for providing user feedback. For example, if an applicator moves an undesirable amount during a treatment session, the input/output device **508** can alert the subject and/or operator via an audible alarm. The input/output device **508** can be a touch screen that functions as both an input device and an output device.

[0123] The data system **450** can output instructions to command the surgical robot **440** and communicate with one or more databases **500**. The surgical robot **440** or other components disclosed herein can communicate to send collected data (e.g., sensor readings, instrument data, surgical robot data, etc.) to the database **500**. This information can be used to, for example, create new training data sets, generate plans, perform future simulations, post-operatively analyze surgical procedures, or the like. The data system **450** can be incorporated, used with, or otherwise interact with other databases, systems, and components disclosed herein. In some embodiments, the data system **450** can be incorporated into the surgical robot **440** or other systems disclosed herein. In some embodiments, the data system **450** can be located at a remote location and can communicate with a surgical robot via one or more networks. For example, the data system **450** can communicate with a hospital via a network, such as a wide area network, a cellular network, etc. One or more local networks at the hospital can establish communication channels between surgical equipment within the surgical room. The database(s) **500** can include, without limitation, user profile databases, vocabulary databases, natural language databases, confidence score databases, training set databases, or the like. Additionally or alternatively, the databases **500** can further be accessed by transcribing modules, diagnostic modules, treatment modules, machine learning modules, or combinations thereof, which can access one or more databases.

[0124] A surgical program or plan ("surgical plan") can include, without limitation, patient data (e.g., pre-operative images, medical history, physician notes, etc.), imaging programs, surgical steps, mode switching programs, criteria, goals, or the like. The imaging programs can include, without limitation, AR/VR programs, identification programs (e.g., fiducial identification programs, tissue identification programs, target tissue identification programs, etc.), image analysis

programs, the output discussed in connection with FIG. 6-10, or the like. Surgical programs can define surgical procedures or a portion thereof. For example, surgical programs can include end effector information, positional information, surgical procedure protocols, safety settings, surgical robot information (e.g., specifications, usage history, maintenance records, performance ratings, etc.), order of surgical steps, acts for a surgical step, feedback (e.g., haptic feedback, audible feedback, etc.), or the like. The mode switching programs can be used to determine when to switch the mode of operation of the surgical robot 440. For example, mode switching programs can include threshold or configuration settings for determining when to switch the mode of operation of the surgical robot 440. Example criteria can include, without limitation, thresholds for identifying events, data for evaluating surgical steps, monitoring criteria, patient health criteria, physician preference, or the like. The goals can include intraoperative goals, post-operative goals (e.g., target outcomes, metrics, etc.), goal rankings, etc. Monitoring equipment or the surgical team can determine goal progress, whether a goal has been achieved, etc. If an intraoperative goal is not met, the surgical plan can be modified in real-time so that, for example, the post-operative goal is achieved. The post-operative goal can be redefined intraoperatively in response to events, such as surgical complications, unplanned changes to patient's vitals, etc.

[0125] The surgical plan can also include healthcare information, surgical team information, assignments for surgical team members, or the like. The healthcare information can include surgical room resources, hospital resources (e.g., blood banks, standby services, available specialists, etc.), local or remote consultant availability, insurance information, analysis models, patient diagnosis, observations, transcription information, cost information (e.g., surgical room costs, surgical team costs, etc.).

[0126] The systems disclosed herein can generate pre-operative plans and simulation plans. Pre-operative plans can include scheduling of equipment, surgical room, staff, surgical teams, and resources for surgery. The systems can retrieve information from one or more databases to generate the pre-operative plan based on physician input, insurance information, regulatory information, reimbursements, patient medical history, patient data, or the like. Pre-operative plans can be used to generate surgical plans, cost estimates, scheduling of consultants and remote resources, or the like. For example, a surgical plan can be generated based on available resources scheduled by the pre-operative plans. If a resource becomes unavailable, the surgical plan can be adjusted for the change in resources. The healthcare provider can be alerted if additional resources are recommended. The systems disclosed herein can generate simulation plans for practicing surgical procedures. On approval, a surgeon can virtually simulate a procedure using a console or another simulation device. Plans (e.g., surgical plans, implantation plans, etc.) can be generated and modified based on the surgeon's performance and simulated outcome.

[0127] The systems disclosed herein can generate post-operative plans for evaluating surgical outcomes, developing physical therapy and/or rehab programs and plans, etc. The post-operative plans can be modified by the surgical team, primary care provider, and others based on the recovery of the patient. In some embodiments, systems generate pre-operative plans, surgical plans, and post-operative plans prior to beginning a surgical procedure. The system then modifies one or more of the plans as additional information is provided. For example, one or more steps of the methods discussed herein can generate data that is incorporated into the plan. ML data sets to be incorporated into the plan generate a wide range of variables to be considered when generating plans. Plans can be generated to optimize patient outcome, reduce or limit the risk of surgical complications, mitigate adverse events, manage costs for surgical procedures, reduce recovery time, or the like. The healthcare provider can modify how plans are generated over time to further optimize based on one or more criteria.

[0128] FIG. 6 is a block diagram illustrating an example system for transcribing and performing analysis on patient data, in accordance with one or more embodiments. The system implements a digital medical assistant. The system includes at least one computing device 602, at least one

controller **604**, at least one memory **606**, at least one communications interface **608**, and at least one user interface **610**. The system is implemented using the components of the example computer system **300** illustrated and described in more detail with reference to FIG. 3. Likewise, embodiments of the system can include different and/or additional components or can be connected in different ways.

[0129] The computing device **602** (see FIG. 3) receives inputs from the user interface **610**, at least one sensor **620**, and at least one imaging device **612**. The computing device **602** performs mathematical computations returning the results via the user interface **610**, such as a display, or via speakers. The computing device **602** may additionally access the cloud **622** or other data sources via the communications interface **608**. The computing device **602** may be a mobile device, which is a computing device characterized by being portable. A mobile device may include any of a mobile phone, tablet, laptop, wearable device such as a smartwatch, a portable gaming device, or a proprietary device built for a specific purpose. The computing device **602** may additionally include or communicate with a quantum computing device (see FIG. 1). The controller **604** is a logic device or processor for performing a series of logic operations. Traditionally, the controller **604** included transistors arranged on a silicon substrate, although the controller **604** included any materials and substrates which form a logic circuit. Common logic circuit elements include OR gates, AND gates, XOR gates, NOR gates, NAND gates, etc. The controller **604** may be a microcontroller or a central processing unit (CPU) in a computer. Similarly, a graphical processing unit (GPU) may be used as the controller. The controller **604** may additionally include the logic element of a quantum computer.

[0130] The controller **604** uses logic operations to perform computations and may be in communication with the memory **606** for storing data and a communications interface **608** for sending and receiving data to and from other controllers or devices. The memory **606** is a medium for storing data. The memory **606** may be volatile memory, such as random-access memory (RAM) which is a cache used by the controller **604** for temporary storage of data for use in computations or persistent memory, such as solid-state drive (SSD), hard disk drive (HDD) or other storage devices including tape drives, flash drives, memory cards, optical drives such as compact disk (CD), digital video disk (DVD), or Blu-ray disc, or data storage on nontraditional mediums. The communications interface **608**, also known as a network interface, is an interface for a device or controller to communicate with another device, controller, or network resource such as the cloud **622** server or drive.

[0131] The communications interface **608** may be wired, such as by ethernet cables or universal serial bus (USB) cables, or wireless as in Wi-Fi, Bluetooth, near field communications (NFC), 4G long-term evolution (LTE), 5G, etc. The user interface **610** is a means of interacting with and providing inputs to the computing device **602**. The user interface **610** may alternatively be a means of interacting with and controlling the surgical robot **614**. The user interface **610** may include any of a traditional keyboard and mouse, a joystick, gamepad, trackpad, touchscreen, etc. The user interface **610** may alternatively include a sensor **620** such as a microphone for receiving an audio input such as spoken language. The user interface **610** may alternatively include eye, facial, body, or gesture tracking using an imaging device **612**. The imaging device **612** is any device capable of detecting sound or electromagnetic waves and assembling a visual representation of the detected waves. Imaging devices **612** may collect waves from any part of the electromagnetic spectrum or sounds at any range of frequencies, often as a matrix of independently acquired measurements which each represent a pixel of a two or three-dimensional image. These measurements may be taken simultaneously or in series via a scanning process or a combination of methods. Some pixels of an image produced by an imaging device may be interpolated from direct measurements representing adjacent pixels in order to increase the resolution of a generated image.

[0132] The surgical robot **614** is a robotic system designed to assist a surgeon in performing a surgical operation on a patient. The surgical robot **614** may include a controller and any of a robotic

arm **614** with an end effector **618** or an imaging device **612**. The surgical robot **614** may further include a user interface for accepting control inputs from a user, such as a surgeon or other medical professional and a communications interface **608** for transmitting and receiving data to and from the cloud **622** for the purpose of training an artificial intelligence operating within the surgical robot or receiving remote commands from a remote user or an artificial intelligence existing external to the surgical robot **614**. The robotic arm **616** is a mechanically actuated arm or lever with at least two degrees of freedom. The robotic arm **616** will typically include at least one end effector **618** or an imaging device **612** and may include both an end effector **618** and an imaging device **612**. The robotic arm **616** may additionally be capable of changing the end effector **618** to facilitate multiple functions and operation of a variety of tools.

[0133] The robotic arm **616** may be manually controlled or operated in an autonomous or semi-autonomous mode. The surgical robot **614** may have one robotic arm **616** or multiple robotic arms **616**, each of which may be operated independently by one or more users or autonomous systems or a combination of users and autonomous systems. The end effector **618** is the end of the robotic arm **616** which is conducting work. The end effector **616** is typically a tool **154** (see FIG. 1) or device for interacting with a physical object and may be a surgical tool intended for acting upon or within a patient or may be a gripping device for securing a separate surgical tool to the robotic arm **616**. The end effector **618** may be permanently affixed to the end of the robotic arm **616** or may be detachable allowing for a system of interchangeable end effectors **618** which may alternatively be selected and swapped by a single robotic arm or multiple robotic arms. The end effector **618** may include features such as lights or other illumination devices, surgical tools, imaging devices **612**, etc.

[0134] In some embodiments, the one or more sensors **620** of the system of FIG. 6 generate sensor data from measurements of a patient's body. In some embodiments, the sensors **620** are the same as or similar to the monitors **112** (see FIG. 1). In other embodiments, a sensor **620** is an input device for measuring a physical quantity and outputting the measurements as a signal which is saved as data representing the measured physical quantity. Sensors **620** may measure a range of physical quantities such as a temperature, distance, movement, orientation, sound frequency, wavelength and intensity, wavelength and intensity of light and other electromagnetic waves, volatile gases, capacitance, resistance, induction, etc. The sensor **620** may output an analog or a digital signal. The sensor **620** may be a discrete device or embedded in another device such as a robotic arm **616**, end effector **618**, etc. and may be accessible to the computing device **602** or cloud **622** via the communications interface **608**. Alternatively, data may be stored local to the sensor **620** which may be later accessed by a device such as the computing device **602** or the cloud **622**. The sensor **620** may additionally refer to an array of sensors **620** such as an image sensor or imaging device **612** for capturing multiple measurement values simultaneous and which may be used to create multidimensional representations of the data such as images.

[0135] The cloud **622** is a distributed network of computers including servers and databases. The cloud **622** may be a private cloud where access is restricted by isolating the network such as preventing external access or by using encryption to limit access to only authorized users. Alternatively, the cloud **622** may be a public cloud where access is widely available via the internet. A public cloud may not be secured or may include limited security features. The patient database **624** stores data about one or more patients. The data may include gender, age, height, weight, previously diagnosed medical conditions, medical history, family medical history, allergies, and vital information such as baseline measurements of heart rate, blood pressure, blood oxygen saturation, and respiration rate. The data may be collected from the sensors **620** or imaging devices **612** or may alternatively be collected from medical records. In some embodiments, the patient database **624** may include patient medical records created by one or more medical professionals. The transcription module **626** calls the training module **628** to train an analysis model which is used by the analysis module to perform an analysis on patient data collected by the transcription

module **626** and stored in the patient database **624**. The transcription module **626** interacts with a surgeon or other medical professional to record observations and instructions from a surgeon, and then present the analysis results from the analysis module to the surgeon, preferably via a speech-based interface in a conversational manner, allowing the surgeon to dictate additional observations and instructions.

[0136] The analysis results may additionally provide insights and feedback to the surgeon prompting the surgeon to provide additional information which otherwise may have been forgotten or overlooked. The training module **628** is used to train an analysis model using historical patient data from the patient database **624**. The data collected or otherwise available during a patient visit is provided and a prediction is made based upon the provided data. In some embodiments, training a machine learning model (see FIG. 2) includes monitoring live surgical procedures. The machine learning model is trained based on the live surgical procedures while the live surgical procedures are being performed. The prediction is then compared to the patient's diagnosis and the analysis model is updated based upon the result, improving the model. The updated analysis model may be stored in the patient database **624** and is available for use by the transcription module **626** and the analysis module **630**. The analysis module **630** is used to collect current patient data by the transcription module **626** and retrieve historical patient data from the patient database **624** to generate insights by the analysis model trained by the training module **628**. The analysis model performs an analysis on the available data which may include image analysis, or other machine learning categorizations to identify any of diagnoses, treatments, additional data which may improve accuracy of the diagnosis, etc. In some embodiments, the analysis model may additionally be used to perform a deeper analysis such as by using a supercomputer or quantum computer (see FIG. 1) to simulate the progression of a disease or a treatment in a patient.

[0137] FIG. 7 is a table illustrating an example patient database **624**, in accordance with one or more embodiments. In some embodiments, one or more processors of the system of FIG. 6 retrieve patient data of a patient from the patient database **624**. The patient data includes at least a medical history of the patient. The patient database **624** (see FIG. 6) stores patient data about one or more patients. The data may include gender, age, height, weight, previously diagnosed medical conditions, medical history, family medical history, allergies, medications, and vital information such as baseline measurements of heart rate, blood pressure, blood oxygen saturation, and respiration rate. The data may be collected from sensors **620** or imaging devices **612** or may be obtained from medical records or provided by medical professionals. The patient database may additionally include medical records created by one or more medical professionals. The patient database **624** is used by the transcription module **626**, training module **628**, and analysis module **630**.

[0138] FIG. 8 is a flow diagram illustrating an example process for transcribing and performing analysis on patient data, in accordance with one or more embodiments. In some embodiments, the process of FIG. 8 is performed by the transcription module **626**. The transcription module **626** is illustrated and described in more detail with reference to FIG. 6. In other embodiments, the process of FIG. 8 is performed by a computer system, e.g., the example computer system **300** illustrated and described in more detail with reference to FIG. 3. Particular entities, for example, the console **108** or the robotic surgical system **160** perform some or all of the steps of the process in other embodiments. The console **108** and the robotic surgical system **160** are illustrated and described in more detail with reference to FIG. 1. Likewise, embodiments can include different and/or additional steps, or perform the steps in different orders.

[0139] In step **802**, the transcription module **626** prompts or triggers the training module **628** (see FIG. 6) to train an analysis model. The analysis model may be generalized or domain specific, such as for use by a diagnostic oncologist. The training module **628** queries the patient database **624** for patient data, selecting patient data received during the diagnosis of a medical condition and predicting the patient's diagnosis. The analysis model is then updated based on the results of the

prediction and further trained with any additional patient data available.

[0140] In step **804**, the transcription module **626** receives a trained analysis model from the training module **628**. The trained analysis model may be generalized or domain specific. For example, the analysis model is trained using images acquired via an MRI to recognize lung cancer. In a further example, the analysis model is additionally trained using non-image data including vital sign measurements, diagnostic test results, symptoms, patient history, and family medical history. In some embodiments, the transcription module **626** receives one or more trained analysis modules that can include, without limitation, one or more transcription modules and/or condition-specific modules, such as cardiac transcribing models, oncology transcribing models, respiratory transcribing models, or the like. In some embodiments, the transcribing module includes a transcribing model and/or a vocabulary database. The vocabulary database can be a cloud database or a local database. For example, the system can select a cardiac transcribing model with one or more transcription models and a cardiac vocabulary database based on received cardiac-related sensor data, such as heart monitor data, EKGs, or the like. In some embodiments, the system generates a condition-specific module and associated condition vocabulary database if a suitable module is not available.

[0141] In step **806**, the transcription module **626** queries the patient database **624** for data relevant to the patient. The data includes the patient's medical history including previous vital sign measurements, symptoms and signs of illness noted by a medical professional, previous diagnostic test results, and previous diagnoses. The data may additionally include the patient's family medical history and their genetic information including sequenced DNA which may be used to identify hereditary medical conditions. For example, data is retrieved describing a 39-year-old male patient with a history of smoking cigarettes for 18 years, a prior diagnosis for pneumonia and images from two MRIs taken at a six-month interval.

[0142] In step **808**, the transcription module **626** collects or retrieves data from one or more sensors **620**. The sensors **620** may include any of a pulse oximeter, sphygmomanometer, electrocardiogram, glucometer, etc. The sensors **620** may additionally include one or more imaging devices.

Alternatively, the transcription module **626** collects data from a medical professional such as a surgeon, nurse, physician's assistant, paramedic, emergency medical technician, etc. The data may be measured manually and either manually inputted using a physical user interface **610** or may be provided via a verbal interface. For example, a heart rate of 120 beats per minute and a blood oxygen saturation of 94 is measured via a pulse oximeter. A series of images is additionally collected from an MRI of the patient's chest focused on the patient's lungs. The data collected further includes a verbal prompt from a nurse manually measuring the patient's blood pressure and saying, "the patient's blood pressure is 145/95."

[0143] In some embodiments, one or more processors of the system of FIG. **6** transcribe speech input received from a surgeon examining a patient into medical notes, including electronic medical notes. The speech input is received via a microphone of the system. For example, in step **810**, the transcription module **626** records a surgeon's observations. The surgeon may alternatively be any medical professional or assisting personnel. The observations may be provided manually via a physical user interface **610**, such as a keyboard or a touchscreen, or in a preferred embodiment, may be orally dictated by the surgeon or other medical professional. The dictation may further include treatments or interventions which are either being performed or alternatively are instructions for execution by the patient or another medical professional such as a nurse. For example, the surgeon observes the procedure and states, "the patient is experiencing shortness of breath and increased work of breathing," and additionally, "we are providing the patient 3 liters per minute of oxygen via nasal canula." The surgeon may further dictate observations while reviewing medical records or medical images. For example, the surgeon notes that, "there appears to be a mass on the inferior lobe of the right lung," and further, "schedule a sputum test and additionally a biopsy if the sputum test is positive."

[0144] The transcription module **626** can perform, without limitation, Fourier analysis, linear predictive coding, perceptual linear coding, and/or extraction routines and can apply one or more speech recognition algorithms, including hidden Markov Models/algorithms, dynamic time warping, and/or artificial neural networks. The Markov algorithms can include, for example, forward algorithms, Viterbi algorithms, forward-backward algorithms, etc. The transcription module **626** can be trained using supervised learning, unsupervised learning, reinforced learning, or other machine-learning techniques disclosed herein (see FIG. 2) for speech recognition, speech-to-text, etc. In some embodiments, the transcription module **626** transcribes speech input from a physician by converting the speech to text by using, for example, one or more profiles (e.g., practitioner profiles, specialty profiles, or a user profile for the physician). The profiles can be trained using one or more machine learning models trained on speech data sets generated by instructing the users to provide input speech.

[0145] In step **812**, the transcription module **626** stores or saves the data (including the medical notes) to the patient database **624**. The data includes sensor data and the medical notes received via manual or verbal dictation including the surgeon's observations. For example, the data includes a measured heart rate of 120 and a blood oxygen concentration of 94, a blood pressure of 145/95 and further the surgeon's observations of the patient indicating, e.g., shortness of breath, increased work of breathing, and a mass on the inferior lobe of the right lung. The data further includes interventions or instructions. Continuing the example, the data indicates that the patient was provided 3 liters per minute of oxygen via nasal canula and that the surgeon requested a sputum test and a biopsy pending a positive result from the sputum test.

[0146] In some embodiments, one or more processors of the system of FIG. 6 determine a diagnosis for a patient using a machine learning model (see FIG. 2) of the system based on sensor data, patient data, and medical notes. The machine learning model is trained based on historical patient data and historical treatment data (see FIG. 7). In step **814**, the transcription module **626** prompts or triggers the analysis module **630** to analyze the patient data. The analysis module **630** receives patient data from the patient's most recent or current assessment and retrieving the patient's medical history from the patient database **624**. In some embodiments, the one or more processors generate a treatment for a patient using the machine learning model based on a diagnosis. For example, the analysis module **630** further selects an analysis model and using the analysis model to analyze the patient data for possible diagnoses, observations not made by the surgeon or other medical professional, additional diagnostic tests, or information to collect from the patient, as well as possible treatments and the likelihood of the treatments benefiting the patient. For example, the data provided to the analysis module **630** indicates a measured heart rate of 120 and a blood oxygen concentration of 94, a blood pressure of 145/95 and further the surgeon's observations of the patient indicating shortness of breath, increased work of breathing, and a mass on the inferior lobe of the right lung. The data further includes interventions or instructions. Continuing the example, the data further indicates that the patient was provided 3 liters per minute of oxygen via nasal canula and that the surgeon requested a sputum test and a biopsy pending a positive result from the sputum test.

[0147] The system of FIG. 6 supports voice-interactive natural language dialogue using natural language with the physician to, for example, provide information, obtain information for analyzing the patient, etc. This process can be repeated until a confidence score exceeding a threshold value is achieved. The confidence score indicates the likelihood of an accurate outcome of the analysis based on, for example, historical data or other data. The system of FIG. 6 can identify additional information (e.g., physician observations, patient feedback, etc.) that are useful for analysis. The system can generate computer-generated natural language requests provided via voice-interactive transcription (text-to-voice) requests. The physician can provide the additional information. The system can include any number of machine learning models, transcription modules, diagnostic modules, treatment modules, and/or databases to support the natural language voice interaction.

[0148] In some embodiments, step **814** includes selecting a machine learning model from a set of machine learning models based on at least one health parameter for the patient. This allows the system to increase accuracy, reduce computation times, and otherwise improve performance. For example, the machine learning model can be selected based on health status, patient condition, physician-selected health parameter for the patient, or other health parameters. The health status can indicate general health status (e.g., good health, poor health, etc.), impact of disease/condition on a patient, etc. In some embodiments, the health status can be generated based on health-related quality-of-life questionnaires. The patient condition can be, for example, undetermined, good, fair, serious, or critical. The physician-selected health parameter can be indicative of the physician's observations.

[0149] In step **816**, the transcription module **626** receives an analysis completed by an analysis model. For example, the analysis indicates that the patient has an 80% likelihood of having lung cancer and further identifying a further question to be asked of, “have you had a persistent cough or chest pain?” The analysis may further indicate that radiotherapy would have a 70% likelihood of benefiting the patient while chemotherapy would have only a 60% likelihood of benefiting the patient.

[0150] The transcription module **626** can function as a conversational speech synthesis module that produces computer-generated speech based on one or more transcription models. In some embodiments, the system can include or interface with speech or language models from MonkeyLearn™, IBM Watson™, or Google Cloud Natural™ and can include or interface with specific application programming interfaces (APIs) for speech input (e.g., natural language requests). The system can process the inputs to extract one or more elements used to identify one or more associated APIs. One or more structured API calls can be generated by mapping the extracted elements to elements of the structured API calls. The system can communicate with remote servers to construct structured API calls. The communications with the APIs can be selected based on the API capabilities, such as natural language processing or other speech processing modules disclosed herein.

[0151] In some embodiments, a user interface of the system of FIG. **6** displays a graphical representation of a generated treatment for viewing by a physician. For example, in step **818**, the transcription module **626** prompts the surgeon or other medical professional to review the analysis results returned by the analysis module **630**. In some embodiments, the prompt is a notification indicating to a surgeon that the analysis results are available for review via a user interface **610** and/or via an audio interface. In a preferred embodiment, the system provides an interactive natural language dialogue in which a surgeon is prompted by a verbal interface in a conversational manner such as, “the analysis for the patient is complete, would you like to review?” The surgeon may respond by saying, “I will review the results later,” or alternatively may reply, “what are the results?” The results may then be presented to the surgeon as, “there is an 80% likelihood that the patient has lung cancer as you identified in your observations. In step **816**, the transcription module **626** can prompt the surgeon to, e.g., ask the patient whether he has a persistent cough or has had chest pain to improve the accuracy of the diagnosis.” The surgeon may further request a deeper analysis, or the results of an already completed deeper analysis such as by, “how would the patient respond to radiotherapy?” to which the surgeon would be told, “there is a 70% likelihood that radiotherapy would benefit the patient.”

[0152] In step **820**, the transcription module **626** stores or records additional observations or instructions provided by the surgeon or other medical professional. The observations may be in response to the analysis results or may include information acquired by the surgeon since the analysis was completed. The surgeon may additionally provide instructions such as additional tests to be completed or treatments. The observations or instructions may be provided via a traditional user interface **610** or may alternatively be dictated verbally. For example, the surgeon dictates that, “if the results of the sputum test are positive, begin the patient on six weekly sessions of

radiotherapy and schedule a follow up appointment one week after the sixth session.”

[0153] In step **822**, the transcription module **626** determines whether a surgical procedure or surgery is complete, by receiving an explicit command from the surgeon, such as the surgeon saying, “end the transcription” or by monitoring the presence of the surgeon and determining a surgery is complete when the surgeon leaves the room. The surgery may be determined to be complete regarding the present patient if the surgeon inquires or otherwise begins a new session with a new patient. If the surgery is not complete, the transcription module **626** retrieves or collects data from sensors if available and continues to collect information, including the surgeon's observations and instructions. In step **824**, the transcription module **626** terminates the transcription if the surgeon is complete. Additionally, instructions may be executed following the completion of the transcription such as scheduling follow up appointments or treatments as provided by the surgeon.

[0154] FIG. **9** is a flow diagram illustrating an example process for transcribing and performing analysis on patient data, in accordance with one or more embodiments. In some embodiments, the process of FIG. **9** is performed by the training module **628**. The training module **628** is illustrated and described in more detail with reference to FIG. **6**. In other embodiments, the process of FIG. **9** is performed by a computer system, e.g., the example computer system **300** illustrated and described in more detail with reference to FIG. **3**. Particular entities, for example, the console **108** or the robotic surgical system **160** perform some or all of the steps of the process in other embodiments. The console **108** and the robotic surgical system **160** are illustrated and described in more detail with reference to FIG. **1**. Likewise, embodiments can include different and/or additional steps, or perform the steps in different orders.

[0155] In some embodiments, received sensor data includes medical images of the patient's body, and the one or more sensors **620** include an imaging device **612**. One or more processors of the system of FIG. **6** extract an anomalous feature from the medical images. A diagnosis is determined using machine learning (see FIG. **2**) performed on the anomalous feature. For example, in step **902**, the training module **628** retrieves or receives an analysis model. The analysis model is an artificial intelligence trained using machine learning (see FIG. **2**) to analyze past and current patient data to identify insights such as potential questions to ask a patient, possible diagnoses, or identification of the presence of an anomalous feature in medical images taken with an imaging device **612**. The analysis model may be generalized, such as which might be used by a physician or other general medical practitioner. Alternatively, the analysis model may be specialized for use by a specialist such as an oncologist, pediatricist, dermatologist, cardiologist, endocrinologist, etc. For example, the analysis model is specialized for use by an oncologist.

[0156] In step **904**, the training module **628** queries the patient database **624** for patient data. The patient data may be limited, such as by the domain of the analysis model it will be used to train. For example, if the domain is oncology, the data retrieved may be only for those patients who have been diagnosed with a cancer. Similarly, data retrieved may be determined by the area in which the doctor who is going to use it is focused, such as diagnostic, surgical, treatment, etc. The data retrieved for a diagnostic oncologist may be limited to images acquired from an imaging device **612**. The data may further include vital sign measurements, symptoms, the patient's medical history, and their family medical history. The data may also include genetic information such as sequenced DNA. In an example, the data includes MRIs from patients who were screened for lung cancer.

[0157] In step **906**, the training module **628** identifies or selects data for a single patient from the patient data retrieved from the patient database. The data includes the information which was available at the time of the patient's diagnosis. In an example, the patient data includes a series of three MRIs taken at an interval of six months. The data may further include vital sign measurements, symptoms noted by the patient or a medical professional and the patient's prior medical history and family medical history prior to the screening.

[0158] In step **908**, the training module **628** generates or predicts the patient's diagnosis using the selected patient data. The prediction is made by performing image analysis, such as using a convolutional neural network (CNN) on one or more medical images captured using an imaging device **612**. The prediction may additionally or alternatively use non-image data such as vital sign measurements, diagnostic test results, symptoms, patient history, and family medical history.

[0159] In some embodiments, determining a diagnosis includes, for each of one or more medical conditions, assigning a statistical probability that a patient has a particular medical condition using a machine learning model (see FIG. 2). The medical condition having the greatest statistical probability is selected. For example, the analysis model assigns a statistical probability that the patient may have a disease or medical condition, and selects the medical condition with the highest probability. In some embodiments, one or more processors of the system of FIG. 6 select each of the one or more medical conditions having a statistical probability greater than a threshold statistical probability. For example, the analysis model assigns a statistical probability that the patient may have a disease or medical condition, and selects one or more illnesses with a probability above a threshold value.

[0160] In some embodiments, training a machine learning model (see FIG. 2) includes generating, by one or more processors of the system of FIG. 6, a predicted diagnosis and a predicted treatment for a previous patient based on the historical patient data (see FIG. 7). The one or more processors compare the predicted diagnosis and the predicted treatment to an actual diagnosis and an actual treatment provided by a previous surgeon in the historical patient data. The comparing is performed for training a regression model of the system based on the comparison results. In an example, the analysis model predicts that the patient has an 85% likelihood of having lung cancer based on analysis of the series of three MRIs from the selected patient data. Continuing the example, the threshold value for a positive diagnosis is 70%, as set by a medical professional, therefore the prediction is that the patient was diagnosed with lung cancer. If there are no diseases or medical conditions with a statistical probability above the threshold value, the patient is determined to be healthy. More than one disease or medical condition may be selected as a diagnosis. The prediction may be made for each possible disease or medical condition discretely, each being considered independent of the others, or the likelihood of each disease or medical condition may be considered relative to each of the other possible diagnoses.

[0161] In step **910**, the training module **628** determines whether the prediction is correct by retrieving the patient's actual diagnosis from the patient database **624** and comparing the patient's actual diagnosis to the predicted diagnosis. If the predicted diagnosis matches the actual diagnosis, then the prediction is correct. In an example, the patient's actual diagnosis is lung cancer, which is the same as the predicted diagnosis, therefore the prediction is correct. In an alternate example, the actual diagnosis is a pulmonary embolism, which is different than the predicted diagnosis of lung cancer, therefore the prediction is incorrect. If multiple diagnoses were predicted, then each may be considered for correctness independently from the others predicted.

[0162] In step **912**, the training module **628** updates the analysis model based upon the results of the prediction. The analysis model may be updated using a regression model, such that a correct prediction reinforces the current model while an incorrect prediction results in an adjustment made to the model. In step **914**, the training module **628** determines or checks whether there is more patient data which has not yet been used to train the analysis model, and if so, queries the patient database **624** for additional data. In an example, there is data on another patient who was screened for lung cancer, therefore there is more patient data available. In an alternate example there is no more patient data for patients screened for lung cancer. In step **916**, the training module **628** returns control to the transcription module **626** if there is no additional data to train the analysis model.

[0163] FIG. 10 is a flow diagram illustrating an example process for transcribing and performing analysis on patient data, in accordance with one or more embodiments. In some embodiments, the process of FIG. 10 is performed by the analysis module **630**. The analysis module **630** is illustrated

and described in more detail with reference to FIG. 6. In other embodiments, the process of FIG. 10 is performed by a computer system, e.g., the example computer system 300 illustrated and described in more detail with reference to FIG. 3. Particular entities, for example, the console 108 or the robotic surgical system 160 perform some or all of the steps of the process in other embodiments. The console 108 and the robotic surgical system 160 are illustrated and described in more detail with reference to FIG. 1. Likewise, embodiments can include different and/or additional steps, or perform the steps in different orders.

[0164] In step 1002, the analysis module 630 receives patient data from the patient's current visit. The data includes sensor data and data received via manual or verbal dictation including the surgeon's observations. In an example, the data includes a measured heart rate of 120, a blood oxygen concentration of 94, a blood pressure of 145/95, and further includes the surgeon's observations of the patient including shortness of breath, increased work of breathing, and a mass on the inferior lobe of the right lung. The data further specifies interventions or instructions. Continuing the example, the data can further indicate that the patient was provided 3 liters per minute of oxygen via nasal canula and that the surgeon requested a sputum test and a biopsy pending a positive result from the sputum test.

[0165] In some embodiments, patient data includes sequenced DNA of a patient and a diagnosis includes a hereditary medical condition. For example, in step 1004, the analysis module 630 queries the patient database 624 for the patient's medical history and family medical history. The data includes the patient's medical history including previous vital sign measurements, symptoms and signs of illness noted by a medical professional, previous diagnostic test results, and previous diagnoses. The data may additionally include the patient's family medical history and their genetic information including sequenced DNA which may be used to identify hereditary medical conditions. The patient database 624 may further be queried for a suitable analysis model for analyzing the patient's past medical history and observations made during the patient's most recent or current assessment. In an example, the analysis module 630 retrieves data describing a 39-year-old male patient with a history of smoking cigarettes for 18 years, a prior diagnosis for pneumonia, and images from two MRIs taken at a six-month interval.

[0166] In step 1006, the analysis module 630 analyzes the patient's data including both the patient's medical history retrieved from the patient database 624 and the most recently acquired information from the patient's most recent or current assessment. The analysis module 630 identifies diagnoses with a high likelihood given the provided information. Additionally, the analysis module 630 identifies missing information which may either confirm or eliminate a possible diagnosis. In an example, the analysis model determines that the patient has an 80% likelihood of having lung cancer. Further, the analysis module 630 generates or suggests a question for the surgeon or other medical professional to ask the patient, "have you had a persistent cough or chest pain?"

[0167] In step 1008, the analysis module 630 determines whether further analysis is needed. Further analysis is required if the analysis is inconclusive or if indicated by the surgeon or other medical professional. A deeper analysis may also be required based upon the information available for analysis. Some image analysis, such as video, may require greater computational capabilities. Similarly, a pathology study may require more resources for genetic sequencing or advanced simulation of a disease's potential progression. Further analysis may also be required for treatments proposed either by a surgeon, other medical professional, or an assessment model to assess whether a treatment is likely to be effective or alternatively to identify an effective treatment. In an example, the patient is suspected of having lung cancer and both radiotherapy and chemotherapy are recommended treatments and further analysis is required to simulate the likely effectiveness of the treatments.

[0168] In some embodiments, one or more processors of the system of FIG. 7 simulates (see FIGS. 4A-5) an effectiveness of a treatment on a patient's body based on a diagnosis, sensor data, the patient data, and medical notes. A user interface displays results of the simulation for viewing by a

physician. For example, in step **1010**, the analysis module **630** performs a deeper analysis of the patient data using alternate analysis models or more powerful computational resources such as cloud computing, a supercomputer, or a quantum computer. The more capable resources enable a more detailed analysis of the patient data in a timely manner. For example, the analysis module **630** simulates the effectiveness of radiotherapy and chemotherapy as treatments for the patient's likely diagnosis of lung cancer and determines that radiotherapy would have a 70% likelihood of benefiting the patient while chemotherapy would have a 40-60% likelihood of benefiting the patient depending on the mixture of drugs. Additionally, the analysis module **630** reassesses and confirms the initial 80% likelihood of a lung cancer diagnosis.

[0169] In step **1012**, the analysis module **630** returns control to the transcription module **626** with the analysis completed by an analysis model. In an example, the analysis indicates that the patient has an 80% likelihood of having lung cancer and generates or identifies a further question to be asked of, "have you had a persistent cough or chest pain?" The analysis may further include that radiotherapy would have a 70% likelihood of benefiting the patient while chemotherapy would have only a 60% likelihood of benefiting the patient.

[0170] The functions performed in the processes and methods can be implemented in differing order. Furthermore, the outlined steps and operations are only provided as examples, and some of the steps and operations can be optional, combined into fewer steps and operations, or expanded into additional steps and operations without detracting from the essence of the disclosed embodiments. The methods and steps discussed in connection with FIGS. **8-10** can be performed using the systems and components discussed in connection with FIGS. **1-6**. For example, the console **108** of FIG. **1** can include one or more microphones for receiving voice input from an individual, the database **106** of FIG. **1** can include any databases disclosed herein, and the operating room **102** of FIG. **1** can include the systems and components discussed in connection with FIGS. **4A-10**.

[0171] The machine learning system **200** of FIG. **2** can be used for transcribing, diagnosing, treatment planning, or other actions disclosed herein. For example, the machine learning model discussed in FIG. **2** can be trained using voice training data. A diagnostic machine learning model can be trained using diagnostic training data. A treatment planning machine learning model can be trained using treatment training data. The data sets can be obtained by the healthcare provider, from a remote database (e.g., database **108** of FIG. **1**), or other source. In some embodiments, simulations can be performed to generate additional data sets.

[0172] The systems disclosed herein can also determine whether to train a machine learning model. This allows further training to increase accuracy. For example, if a confidence score for a trained machine learning model is below a threshold value, the system can determine a training protocol to further train the machine learning system or transition to a different machine learning system. In some training protocols, the system identifies a training database based on the patient data. The system can match the patient data with training sets in available databases. The system can then train the machine learning model using the matched training data. If the surgeon determines that the received analysis at a step (e.g., steps **816**, **818**, **906**) is inaccurate, the surgeon can provide additional information to the system. The surgeon can request re-training the machine learning model to re-train the previously used machine learning model or to use another machine learning model. Additional training of machine learning models can also be performed at steps discussed in connection with of FIGS. **8-10**.

[0173] The techniques introduced here can be implemented by programmable circuitry (e.g., one or more microprocessors), software and/or firmware, special-purpose hardwired (i.e., non-programmable) circuitry, or a combination of such forms. Special-purpose circuitry can be in the form of one or more application-specific integrated circuits (ASICs), programmable logic devices (PLDs), field-programmable gate arrays (FPGAs), etc.

[0174] The description and drawings herein are illustrative and are not to be construed as limiting.

Numerous specific details are described to provide a thorough understanding of the disclosure. However, in certain instances, well-known details are not described in order to avoid obscuring the description. Further, various modifications can be made without deviating from the scope of the embodiments.

[0175] The terms used in this specification generally have their ordinary meanings in the art, within the context of the disclosure, and in the specific context where each term is used. Certain terms that are used to describe the disclosure are discussed above, or elsewhere in the specification, to provide additional guidance to the practitioner regarding the description of the disclosure. For convenience, certain terms can be highlighted, for example using italics and/or quotation marks. The use of highlighting has no influence on the scope and meaning of a term; the scope and meaning of a term is the same, in the same context, whether or not it is highlighted. It will be appreciated that the same thing can be said in more than one way. One will recognize that “memory” is one form of a “storage” and that the terms can on occasion be used interchangeably.

[0176] Consequently, alternative language and synonyms can be used for any one or more of the terms discussed herein, nor is any special significance to be placed upon whether or not a term is elaborated or discussed herein. Synonyms for certain terms are provided. A recital of one or more synonyms does not exclude the use of other synonyms. The use of examples anywhere in this specification including examples of any term discussed herein is illustrative only and is not intended to further limit the scope and meaning of the disclosure or of any exemplified term. Likewise, the disclosure is not limited to various embodiments given in this specification.

[0177] It is to be understood that the embodiments and variations shown and described herein are merely illustrative of the principles of this invention and that various modifications can be implemented by those skilled in the art.

Claims

1. A method comprising: retrieving, by a computer system, patient data of a patient from a patient database, the patient data comprising at least one of a medical history of the patient or an image of the patient; performing, by the computer system, a computer-generated voice-controlled real-time transcription for a physician using a user interface to obtain speech input from the physician, wherein the user interface comprises a microphone; transcribing, by the computer system, the speech input received via the microphone from the physician into medical notes associated with the patient data, wherein the medical notes are generated by at least one machine learning model trained for context-based medical transcription; and outputting, by the computer system, computer-generated audible speech associated with the medical notes.
2. The method of claim 1, further comprising: generating, by the computer system, the computer-generated audible speech using a conversational speech synthesis module, wherein the computer-generated audible speech describes a treatment associated with a diagnosis.
3. The method of claim 1, further comprising: receiving, from an imaging device, at least one image of the patient; selecting the at least one machine learning model from a plurality of machine learning models based on the at least one image; and inputting the at least one image into the at least one machine learning model to analyze the at least one image.
4. The method of claim 1, further comprising: using, by the computer system, one or more machine learning models trained using conversation training sets for the computer-generated audible speech and/or voice recognition of an oncologist, a pediatricist, a dermatologist, a cardiologist, or an endocrinologist.
5. The method of claim 1, further comprising: generating, by the computer system, a therapeutic treatment plan for the patient using the at least one machine learning model trained on a diagnosis training set; and presenting, by the computer system, the therapeutic treatment plan to the physician using the user interface.

- 6.** The method of claim 1, wherein the patient data comprises medical images of a body of the patient, the method further comprising: extracting, by the computer system, an anomalous feature from the medical images; and determining a diagnosis using the at least one machine learning model on the anomalous feature.
- 7.** The method of claim 1, further comprising: determining a diagnosis for each of one or more medical conditions, by: assigning, by the computer system, a statistical probability that the patient has each medical condition using the at least one machine learning model; and selecting, by the computer system, a medical condition having a greatest statistical probability.
- 8.** The method of claim 7, further comprising: selecting, by the computer system, each of the one or more medical conditions having a statistical probability greater than a threshold statistical probability.
- 9.** The method of claim 1, wherein training the at least one machine learning model comprises: generating, by the computer system, a predicted diagnosis and a predicted treatment for a previous patient based on the patient data; and comparing, by the computer system, the predicted diagnosis and the predicted treatment to an actual diagnosis and an actual treatment provided by a previous surgeon in the patient data.
- 10.** The method of claim 1, further comprising: simulating, by the computer system, an effectiveness of a treatment on a body of the patient based on a diagnosis, the patient data, and the medical notes; and displaying, by the computer system, results of the simulation using the user interface for viewing by the physician.
- 11.** A system comprising: one or more processors; and one or more memories storing instructions that, when executed by the one or more processors, cause the system to perform a process comprising: retrieving, by a computer system, patient data of a patient from a patient database, the patient data comprising at least one of a medical history of the patient or an image of the patient; performing, by the computer system, a computer-generated voice-controlled real-time transcription for a physician using a user interface to obtain speech input from the physician, wherein the user interface comprises a microphone; transcribing, by the computer system, the speech input received via the microphone from the physician into medical notes associated with the patient data, wherein the medical notes are generated by at least one machine learning model trained for context-based medical transcription; and outputting, by the computer system, computer-generated audible speech associated with the medical notes.
- 12.** The system of claim 11, wherein the process further comprises: generating, by the computer system, the computer-generated audible speech using a conversational speech synthesis module, wherein the computer-generated audible speech describes a treatment associated with a diagnosis.
- 13.** The system of claim 11, wherein the process further comprises: receiving, from an imaging device, at least one image of the patient; selecting the at least one machine learning model from a plurality of machine learning models based on the at least one image; and inputting the at least one image into the at least one machine learning model to analyze the at least one image.
- 14.** The system of claim 11, wherein the process further comprises: generating, by the computer system, a therapeutic treatment plan for the patient using the at least one machine learning model trained on a diagnosis training set; and presenting, by the computer system, the therapeutic treatment plan to the physician using the user interface.
- 15.** The system of claim 11, wherein the process further comprises: determining a diagnosis for each of one or more medical conditions, by: assigning, by the computer system, a statistical probability that the patient has each medical condition using the at least one machine learning model; and selecting, by the computer system, a medical condition having a greatest statistical probability.
- 16.** A non-transitory computer-readable medium storing instructions that, when executed by a computing system, cause the computing system to perform operations comprising: retrieving, by a computer system, patient data of a patient from a patient database, the patient data comprising at

least one of a medical history of the patient or an image of the patient; performing, by the computer system, a computer-generated voice-controlled real-time transcription for a physician using a user interface to obtain speech input from the physician, wherein the user interface comprises a microphone; transcribing, by the computer system, the speech input received via the microphone from the physician into medical notes associated with the patient data, wherein the medical notes are generated by at least one machine learning model trained for context-based medical transcription; and outputting, by the computer system, computer-generated audible speech associated with the medical notes.

17. The non-transitory computer-readable medium of claim 16, wherein the operations further comprise: generating, by the computer system, the computer-generated audible speech using a conversational speech synthesis module, wherein the computer-generated audible speech describes a treatment associated with a diagnosis.

18. The non-transitory computer-readable medium of claim 16, wherein the operations further comprise: receiving, from an imaging device, at least one image of the patient; selecting the at least one machine learning model from a plurality of machine learning models based on the at least one image; and inputting the at least one image into the at least one machine learning model to analyze the at least one image.

19. The non-transitory computer-readable medium of claim 16, wherein the operations further comprise: generating, by the computer system, a therapeutic treatment plan for the patient using the at least one machine learning model trained on a diagnosis training set; and presenting, by the computer system, the therapeutic treatment plan to the physician using the user interface.

20. The non-transitory computer-readable medium of claim 16, wherein the operations further comprise: determining a diagnosis for each of one or more medical conditions, by: assigning, by the computer system, a statistical probability that the patient has each medical condition using the at least one machine learning model; and selecting, by the computer system, a medical condition having a greatest statistical probability.
