

# US Patent & Trademark Office

## Patent Public Search | Text View

United States Patent Application Publication

20250266023

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

AKAMA; Taketo

### INFORMATION PROCESSING METHOD, INFORMATION PROCESSING APPARATUS, AND INFORMATION PROCESSING PROGRAM

#### Abstract

An information processing apparatus according to the present disclosure includes an extraction unit that extracts first data from an element constituting first content, and a model generation unit that generates a learned model that has a first encoder that calculates a first feature quantity which is a feature quantity of first content, and a second encoder that calculates a second feature quantity which is a feature quantity of the extracted first data.

**Inventors:** AKAMA; Taketo (Chiba, JP)

**Applicant:** Sony Group Corporation (Tokyo, JP)

**Family ID:** 1000008575186

**Assignee:** Sony Group Corporation (Tokyo, JP)

**Appl. No.:** 19/199417

**Filed:** May 06, 2025

#### Foreign Application Priority Data

JP 2018-197972

Oct. 19, 2018

JP 2019-061040

Mar. 27, 2019

#### Related U.S. Application Data

parent US continuation 18513693 20231120 PENDING child US 19199417

parent US continuation 16772171 20200612 parent-grant-document US 11869467 WO

continuation PCT/JP2019/039939 20191010 child US 18513693

## Publication Classification

**Int. Cl.:** G10H1/00 (20060101); G06N3/045 (20230101); G06N3/08 (20230101)

**U.S. Cl.:**

**CPC** G10H1/0025 (20130101); G06N3/045 (20230101); G06N3/08 (20130101);  
G10H2210/071 (20130101); G10H2250/311 (20130101)

---

## Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] The present application is a continuation of U.S. application Ser. No. 18/513,693, filed Nov. 20, 2023, which is a continuation of U.S. application Ser. No. 16/772,171, filed Jun. 12, 2020 (now U.S. Pat. No. 11,869,467), which is based on PCT filing PCT/JP2019/039939, filed Oct. 10, 2019, which claims priority to JP 2018-197972, filed Oct. 19, 2018, and JP 2019-061040, filed Mar. 27, 2019, the entire contents of each are incorporated herein by reference.

### FIELD

[0002] The present disclosure relates to an information processing method, an information processing apparatus, and an information processing program. More specifically, the present disclosure relates to a process of generating a learned model that is generated through machine learning.

### BACKGROUND

[0003] In various technical fields, information processing using machine learning has been used. For example, by learning features of content (image, music, or the like) using a neural network imitating mechanism of a cerebral nervous system, other content is automatically generated.

[0004] For example, there has been proposed a technology that enables a user to automatically compose appropriate songs that match lyrics by learning features of the existing song without requiring the user to input parameters other than the lyrics.

### CITATION LIST

#### Patent Literature

[0005] Patent Literature 1: JP 2011-175006 A

### SUMMARY

#### Technical Problem

[0006] According to the related art, by learning language feature quantities calculated from lyrics data representing lyrics of each song and attribute data representing attributes of the song, if new lyrics data is given, it is possible to automatically generate a song that matches the new lyrics data.

[0007] However, in the related art, a melody or a chord that matches lyrics is merely generated, and a song is not necessarily generated in a manner desired by the user. For example, in the related art, it is difficult to generate a song holding a feature designated by a user, such as changing a melody while holding only a rhythm of a certain existing song. That is, in the conventional learning process, it has been difficult to perform a process of selectively learning some features (for example, a rhythm, a melody, and a constituent sound of a song) of content.

[0008] Therefore, the present disclosure proposes an information processing apparatus, an information processing method, and an information processing program that can selectively learn a feature quantity designated by a user.

#### Solution to Problem

[0009] To solve the problem described above, an information processing apparatus includes: an

extraction unit that extracts first data from an element constituting first content; and a model generation unit that generates a learned model that has a first encoder that calculates a first feature quantity as a feature quantity of the first content, and a second encoder that calculates a second feature quantity as a feature quantity of the extracted first data.

---

## Description

### BRIEF DESCRIPTION OF DRAWINGS

[0010] FIG. 1 is a diagram illustrating an example of information processing according to an embodiment of the present disclosure.

[0011] FIG. 2 is a diagram illustrating a feature quantity according to an embodiment of the present disclosure.

[0012] FIG. 3 is a diagram for explaining a generation process according to an embodiment of the present disclosure.

[0013] FIG. 4 is a diagram illustrating a configuration example of an information processing apparatus according to an embodiment of the present disclosure.

[0014] FIG. 5 is a diagram illustrating an example of a song data storage unit according to an embodiment of the present disclosure.

[0015] FIG. 6 is a flowchart (1) illustrating an example of an information processing procedure according to an embodiment of the present disclosure.

[0016] FIG. 7 is a flowchart (2) illustrating the information processing procedure according to the embodiment of the present disclosure.

[0017] FIG. 8 is a diagram illustrating an example of learning process according to a first modification of the present disclosure.

[0018] FIG. 9 is a diagram illustrating an example of learning process according to a second modification of the present disclosure.

[0019] FIG. 10 is a diagram illustrating an example of a generation process according to a third modification of the present disclosure.

[0020] FIG. 11 is a diagram for conceptually describing the generation process according to the present disclosure.

[0021] FIG. 12 is a diagram (1) illustrating an example of learning process according to a fourth modification of the present disclosure.

[0022] FIG. 13 is a diagram (2) illustrating an example of the learning process according to the fourth modification of the present disclosure.

[0023] FIG. 14 is a diagram (3) illustrating an example of the learning process according to the fourth modification of the present disclosure.

[0024] FIG. 15 is a diagram (4) illustrating an example of the learning process according to the fourth modification of the present disclosure.

[0025] FIG. 16 is a diagram illustrating an example of learning process according to a fifth modification of the present disclosure.

[0026] FIG. 17 is a diagram (1) illustrating an example of a generation process according to the fifth modification of the present disclosure.

[0027] FIG. 18 is a diagram (2) illustrating an example of the generation process according to the fifth modification of the present disclosure.

[0028] FIG. 19 is a diagram (1) illustrating an example of information processing according to a sixth modification of the present disclosure.

[0029] FIG. 20 is a diagram (2) illustrating the example of information processing according to the sixth modification of the present disclosure.

[0030] FIG. 21 is a diagram (3) illustrating the example of information processing according to the

sixth modification of the present disclosure.

[0031] FIG. 22 is a hardware configuration diagram illustrating an example of a computer that realizes a function of an information processing apparatus.

## DESCRIPTION OF EMBODIMENTS

[0032] Embodiments of the present disclosure will be described below in detail with reference to the drawings. In each of the following embodiments, the same parts are denoted by the same reference symbols, and a repetitive description thereof will be omitted.

[0033] The present disclosure will be described in the following item order. [0034] 1. Embodiment

[0035] 1-1. Overview of Information Processing according to Embodiment of Present Disclosure

[0036] 1-2. Configuration of Information Processing Apparatus according to Embodiment [0037]

1-3. Information Processing Procedure according to Embodiment [0038] 2. Other Embodiments

[0039] 3. Hardware Configuration

### 1. Embodiment

1-1. Overview of Information Processing According to Embodiment of the Present Disclosure

[0040] FIG. 1 is a diagram illustrating an example of information processing according to an embodiment of the present disclosure. The information processing according to the embodiment of the present disclosure is realized by an information processing apparatus **100** illustrated in FIG. 1.

[0041] The information processing apparatus **100** is an apparatus that executes information processing according to the present disclosure, and is, for example, an information processing terminal or a server apparatus.

[0042] In the embodiment, the information processing apparatus **100** generates a learned model for extracting features of content, and generates new content based on the generated learned model. In the embodiment, the content is constituted by digital data of a predetermined format such as music (song), an image, and a moving image. In the example of FIG. 1, the information processing apparatus **100** is used to process a song as an example of the content.

[0043] The learned model according to the embodiment has an encoder that extracts a feature quantity from data constituting content, and a decoder that reconstitutes the content from the extracted feature quantity. For example, the information processing apparatus **100** learns an encoder by unsupervised learning such as a variational auto encoder (VAE) and generative adversarial networks (GANs). Specifically, the information processing apparatus **100** inputs content to the encoder, reconstitutes the content from the extracted feature quantity, compares content before and after the reconstituted content, and adjusts parameters of the encoder and the decoder. The information processing apparatus **100** generates a learned model by repeating such processing and optimizing the parameters of the encoder and the decoder. Thereby, the information processing apparatus **100** can generate a learned model that can obtain an appropriate feature quantity from the data constituting the content. Note that the feature quantity is represented by, for example, a vector having the number of dimensions lower than the data of the input content.

[0044] Note that the learned model is not limited to the above example, and may be any model as long as the learned model can extract the feature quantity and reconstitute the content from the extracted feature quantity.

[0045] In the example of FIG. 1, the information processing apparatus **100** inputs a song (in other words, digital data indicating a sound constituting the song) to the encoder, and extracts elements indicating features of the song such as a melody line, a constituent sound, a rhythm (temporal structure in music, for example, how many notes and rests are included, in what order sounds are reproduced, and the like), a tempo, and a beat as the feature quantities of the song.

[0046] Here, in the case of generating the learned model for extracting the feature quantity of the existing song as described above, there may be a problem of appropriately extracting the feature designated by the user. For example, if a feature quantity of an arbitrary song is extracted as it is, it is possible to reproduce features of the song, but it is sometimes difficult to use the feature quantity, such as generating new content using the feature quantity. Specifically, the feature quantity

extracted using the above-described VAE or the like is a list of vector numerical values, and it is difficult for a human to recognize what features each numerical value indicate. For example, even if a new song that incorporates only a rhythmic feature of the existing song is automatically generated, it is difficult for a human to determine whether a feature quantity vector (in other words, a latent space indicating the feature quantity) is generated using any numerical value.

[0047] Therefore, the information processing apparatus **100** according to the present disclosure generates, by the information processing described below, a learned model that can extract not only the feature quantity of the entire song but also the feature quantity desired by the user. Specifically, the information processing apparatus **100** extracts predetermined data (hereinafter, referred to as “first data” for distinction) from elements (in other words, digital data constituting first content) constituting content (hereinafter, referred to as “first content for distinction”) which is a target for which a feature quantity is calculated. The information processing apparatus **100** generates a learned model that has a first encoder that calculates a first feature quantity as a feature quantity of the first content, and a second encoder that calculates a second feature quantity as a feature quantity of the extracted first data.

[0048] In this manner, the information processing apparatus **100** generates a learned model having a configuration that includes the first encoder that extracts the feature quantity of the entire first content when extracting the feature quantity of the first content, and the second encoder that handles only specific data of the first content. Although described in detail later, the first data is data extracted from the first content by a predetermined operation in order to easily extract a feature quantity designated by a user. In this way, the information processing apparatus **100** generates a learned model that can separately extract a feature quantity from the first content and some elements of the first content by using a plurality of encoders. As a result, the information processing apparatus **100** can obtain the feature quantity in which only the features desired by the user are separately expressed. In addition, the information processing apparatus **100** uses the feature quantity separately obtained to change only the features (for example, the rhythm of the song and the like) designated by the user in the existing content or not to change the feature, thereby making it possible to automatically generate new content (hereinafter, referred to as “second content” for distinction). For the sake of explanation, an encoder that extracts the feature quantity of the first content is referred to as the first encoder, and an encoder that extracts the feature quantity of the first data is referred to as the second encoder, which is for convenience. For example, the encoder that extracts the feature quantity of the first content may be the second encoder.

[0049] Hereinafter, the outline of information processing of the present disclosure will be described along with the flow with reference to FIG. **1**. FIG. **1** illustrates a flow of a process in which the information processing apparatus **100** learns a learned model (first encoder **50**, second encoder **55**, and decoder **60**) using learning data.

[0050] First, the information processing apparatus **100** acquires a song **30** as an example of the learning data (step **S1**). The song **30** is constituted by, for example, a symbol string (digital data) indicating a pitch, a sound length, and a rest. As an example, the pitch is a pitch that expresses a frequency indicating a pitch of a sound in predetermined steps (for example, 128 steps and the like). In addition, the sound length expresses how long the reproduced sound is maintained. In addition, the rest expresses a timing at which the reproduction of the sound stops. Further, the data indicating the song **30** may include information such as a beat or a tempo of the song **30**, a symbol indicating a pause of a bar, a chord at certain timing, or a constituent sound constituting the chord.

[0051] For example, the information processing apparatus **100** converts the symbol string so that the symbol can be handled by a model. As an example, the information processing apparatus **100** uses a symbol string represented as a vector (for example, an embedding vector indicating sound information in which a pitch, a sound length, or the like is assigned to each dimension) for processing. The data indicating such a sound may be represented, for example, in a musical

instrument digital interface (MIDI) (registered trademark) format, may be digital data in a known format that can be reproduced by a general-purpose sequencer, or may be represented as waveform data in a WAV format or the like.

[0052] By the above processing, the information processing apparatus **100** obtains data indicating the song **30** (step S2). In the example of FIG. **1**, the data (vector) indicating the song **30** is expressed as “x.sub.1”.

[0053] Next, the information processing apparatus **100** executes an extraction operation **40** on the data x.sub.1 (step S3). The extraction operation **40** is pre-processing for separating only a specific feature (for example, a feature desired by the user) from the song **30**, which means an operation of performing a predetermined operation on the data x.sub.1 and extracting predetermined data (corresponding to the “first data”).

[0054] As an example, the information processing apparatus **100** extracts the first data by performing operation processing with order invariance on the data x.sub.1 (step S4). The operation with order invariance means, for example, an operation using a commutative operator. Specifically, the operation with order invariance means an operation (for example, including an operation that may mean an operation with almost order invariance, such that a calculation result is slightly changed by including a predetermined coefficient) that do not depend on an order, such as addition or multiplication and a max operation. Note that in the example of FIG. **1**, the information extracted from the data x.sub.1 by the extraction operation **40** is expressed as feature information “f.sub.1”.

[0055] For example, in the example of FIG. **1**, it is assumed that a user who makes the information processing apparatus **100** performs the processing desires to extract “rhythm” from the features of the song **30**. The rhythm in the song is a feature that is related to time (order). For this reason, for example, when trying to extract only the rhythm from the song **30**, a method for leaving information indicating an arrangement of notes (relationship between a sound length and a rest) and hiding (masking) other information can be considered.

[0056] For example, the information processing apparatus **100** performs the operation with order invariance on the data included in the data x.sub.1, and loses “information indicating an order of sounds”. As an example, the information processing apparatus **100** can take an average of embedding vectors in the data x.sub.1 as the operation with order invariance.

[0057] Such a method will be described based on a specific example. It is assumed that an arrangement of notes corresponding to 8 beats constituting the song **30** is “C4, \_, \_, \_, E4, \_, \_, R”. In this example, “C4” and “E4” indicate a pitch of a sound. In addition, a symbol “\_” indicates that the previous sound is extended. In addition, “R” indicates the “rest”.

[0058] Here, it is assumed that the information processing apparatus **100** has a data table indicating embedding vectors corresponding to each sound or rest. The embedding vector is, for example, a d dimension (d is an arbitrary integer), and is a vector in which “1” is input to a dimension corresponding to the corresponding sound (such as “C4” or “E4”), and “0” is input to other dimensions.

[0059] That is, when referring to the arrangement of the data such as “C4, \_, \_, \_, E4, \_, \_, R”, the information processing apparatus **100** refers to an embedding vector of “C4” four times, and then an embedding vector of “E4” three times and an embedding vector of “R” once.

[0060] Here, the information processing apparatus **100** takes an average (may be an addition) of the embedding vectors corresponding to “C4, \_, \_, \_, E4, \_, \_, R”. Then, in the averaged vector, information (that is, rhythm) depending on the order is lost, and information (for example, constituent sound or the like) other than the information indicating the order of sounds is extracted. In this manner, the information processing apparatus **100** can extract “information other than the information indicating the order of sounds” in a local portion of a song.

[0061] In the feature information f.sub.1 obtained in this manner, the constituent sound (that is, the pitch of the constituent sound constituting the song **30**) included in the data x.sub.1 is maintained,

but the information (at which timing the sound is emitted, at which timing the rest is, or the like) indicating the rhythm is lost.

[0062] Subsequently, the information processing apparatus **100** inputs the original data x.sub.1 to the first encoder **50** and inputs the feature information f.sub.1 to the second encoder **55** which is an encoder different from the first encoder **50** (step S5). Note that the first encoder **50** and the second encoder **55** are encoders in, for example, the above-described VAE and the like, and extract a feature quantity of input data as a low-dimensional vector.

[0063] The information processing apparatus **100** obtains the feature quantities output from each of the first encoder **50** and the second encoder **55** (step S6). In the example of FIG. **1**, the feature quantity of the data x.sub.1 is expressed as “z.sub.1”, and the feature quantity of the feature information f.sub.1 is expressed as “Z.sub.2”.

[0064] Note that the feature quantity z.sub.1 and the feature quantity z.sub.2 are separately described for description, but are actually included in one feature quantity vector. This will be described with reference to FIG. **2**. FIG. **2** is a diagram for explaining a feature quantity according to an embodiment of the present disclosure.

[0065] As illustrated in FIG. **2**, it is assumed that the feature quantity vector is a 64-dimensional vector in the learned model generated by the information processing apparatus **100**. In this case, the feature quantity z.sub.1 output from the first encoder **50** constitutes a part (for example, the first half of the feature quantity vector) of the feature quantity vector. In addition, the feature quantity z.sub.2 output from the second encoder **55** also constitutes a part (for example, the second half of the feature quantity vector) of the feature quantity vector. Note that setting the feature quantity vector to be 64 dimensions, how many of the dimensions are allocated to the output of the first encoder **50**, how many of dimensions are allocated to the output of the second encoder **55**, or the like can be arbitrarily set.

[0066] That is, by constituting a model using a plurality of encoders, the information processing apparatus **100** can determine which dimension of the feature quantity vector is a value output from which encoder. That is, the information processing apparatus **100** can output a feature quantity vector capable of artificially interpreting which dimension indicates which feature.

[0067] Returning to FIG. **1**, the description will be continued. The information processing apparatus **100** inputs to the decoder **60** the feature quantity z.sub.1 and the feature quantity z.sub.2 output from each of the first encoder **50** and the second encoder **55** (step S7).

[0068] The decoder **60** is a decoder that is learned to reconstitute the content based on the feature quantity extracted by the encoder. In the example of FIG. **1**, the decoder **60** outputs the data x.sub.2 based on the feature quantity z.sub.1 and the feature quantity z.sub.2 output from each of the first encoder **50** and the second encoder **55** (step S8).

[0069] The data x.sub.2 has the same format as the data x.sub.1 that is the data of the first content. That is, the data x.sub.2 may mean data (symbol string) for reproducing the song **35** having the same format as the song **30**. In other words, the information processing apparatus **100** reconstitutes the content (the song **35** in the example of FIG. **1**) based on the data x2 output from the decoder **60** (step S9).

[0070] Then, the information processing apparatus **100** performs a learning process of the model based on the reconstituted content. Specifically, the information processing apparatus **100** compares the data before and after the extraction processing of the feature quantity, that is, the data x.sub.1 and the data x.sub.2, and optimizes parameters of the first encoder **50**, the second encoder **55**, and the decoder **60** so that the data x.sub.2 approaches the data x.sub.1 (step S10). More specifically, the information processing apparatus **100** optimizes the parameters so that a reconstitution error between the data x.sub.1 and the data x.sub.2 is reduced and a posterior distribution of the feature quantity approaches a prior distribution. Further, the information processing apparatus **100** acquires a plurality of pieces of learning data other than the data x.sub.1 and repeats the learning process illustrated in FIG. **1** to optimize the learned model. Thereby, the

information processing apparatus **100** can generate the learned model according to the present disclosure.

[0071] According to the learned model generated through the processing of FIG. **1**, when a new song is input to the model, it is possible to obtain the feature quantity vector in which the feature quantity of the song is separated. In the example of FIG. **1**, since the second encoder **55** according to the learned model has been learned based on data (for example, feature information f.sub.1) in which the rhythm information has been lost among the learning data, the second encoder **55** is an encoder learned to extract features other than the rhythm. In other words, the feature quantity output from the second encoder **55** may mean one (one that can be interpreted by a human as to which dimension indicates the “constituent sound”) that captures an order-invariant feature quantity such as the constituent sound in the song. On the other hand, the first encoder **50** according to the learned model may mean an encoder that has been learned to mainly extract the order-variable feature quantity (that is, rhythm) from the feature quantity vector. In other words, the feature quantity output from the first encoder **50** may mean one (one that can be interpreted by a human as to which dimension indicates the “rhythm”) that captures only the rhythmic feature in the song.

[0072] As described above, the information processing apparatus **100** inputs the separated and extracted information to a plurality of encoders in advance and performs the learning based on the information, thereby making it possible to separate the feature quantity vector, which is normally indicated as a simple sequence of numerical values, into a specific feature. For example, if the content is a song, the information processing apparatus **100** can output the feature quantity vector in which the rhythm or the melody (such as the constituent sound of the chord) are separated. That is, the information processing apparatus **100** can generate a learned model that can separate features specified by the user (can selectively learn the feature quantity designated by the user).

[0073] In addition, the information processing apparatus **100** can also generate new content (second content) having the feature designated by the user by using the generated learned model. This will be described with reference to FIG. **3**. FIG. **3** is a diagram for explaining the generation process according to the embodiment of the present disclosure.

[0074] As illustrated in FIG. **3**, the information processing apparatus **100** acquires the feature quantity z.sub.1 illustrated in FIG. **1** (step S11). As described above, the feature quantity z.sub.1 is the feature quantity that includes relatively more rhythm-related features in the song **30**. In other words, the feature quantity z.sub.1 is the feature quantity for which the target is separated from the song **30**.

[0075] On the other hand, the information processing apparatus **100** acquires a feature quantity z.sub.3 which is the feature quantity having the same dimension as the feature quantity z.sub.2 illustrated in FIG. **1** (step S11). The feature quantity z.sub.3 indicates a feature quantity of arbitrary data. The feature quantity of the arbitrary data is, for example, feature quantities extracted from other songs other than the song **30** using the second encoder **55**. Alternatively, the feature quantity of the arbitrary data may also be the feature quantity sampled from the prior distribution of the feature quantity such as the feature quantity z.sub.2.

[0076] Then, the information processing apparatus **100** inputs the feature quantity z.sub.1 and the feature quantity z.sub.2 to the decoder **60** (step S12). The information processing apparatus **100** acquires the data x.sub.3 output from the decoder **60** (step S13). Subsequently, the information processing apparatus **100** reconstitutes the song **45** as the second content from the data x.sub.3 (step S14).

[0077] As described above, the feature quantity z.sub.1 is a feature quantity indicating a rhythmic feature of a song **30**. For this reason, the song **45** reconstituted by the data x.sub.3 takes over the features of the rhythm of the song **30** (for example, an arrangement order of notes, a division of notes, the number of bars, a tempo, and the like), and the constituent sound or the like is a song having a feature indicated by the feature quantity z.sub.3. Specifically, the song **45** maintains a



song that has a scale played by the rhythm different from that (for example, a scale that reflects the features of the constituent sound in the feature quantity z.sub.3) of the song **30** while maintaining the rhythm of the song **30**. Note that after reconstituting the song **45**, the information processing apparatus **100** may repeat re-sampling of the feature quantity z.sub.3 from the prior distribution while fixing the feature quantity z.sub.1 (fixing the rhythm). As a result, the information processing apparatus **100** can automatically generate a plurality of songs played on different scales while maintaining the same rhythmic feature. Here, upon generating the second content, the feature quantity z.sub.1 is not necessarily the same as the feature quantity z.sub.1 illustrated in FIG. **1**, and a value sampled from the prior distribution of the feature quantity z.sub.1 may be used.

[0078] Thereby, the information processing apparatus **100** can separate and extract a certain feature (rhythm in this example) and generate content using the extracted feature quantity, and as a result, can freely generate a song having the user desired feature. For example, the information processing apparatus **100** can generate a variation of a song having a different constituent sound while fixing the rhythm. In addition, when not fixing the rhythm but fixing the features of the constituent sound (in the above example, the feature quantity z.sub.2 is fixed, and different feature quantities are input to a location corresponding to the feature quantity z.sub.1), the information processing apparatus **100** can generate a variety of arpeggio variations, such as playing various rhythms (phrases), with fixed chord types. In other words, if the feature is a feature that can be designated by a user (in other words, can describe a rule that generates the feature information), the information processing apparatus **100** fixes any music concept and can automatically generate songs having various variations.

[0079] Note that in the above step **S4**, an example has been illustrated in which the information processing apparatus **100** extracts the feature information f.sub.1 on the rhythm using the order invariance in the data x.sub.1. Here, the information processing apparatus **100** may extract the feature information f.sub.1 by using a method for losing information indicating a pitch.

[0080] A description will be given based on a specific example similar to that in the above step **S4**. It is assumed that an arrangement of notes corresponding to 8 beats constituting the song **30** is “C4,  $\_$ ,  $\_$ ,  $\_$ , E4,  $\_$ ,  $\_$ , R”. In this example, “C4” and “E4” indicate a pitch of a sound. In addition, a symbol “ $\_$ ” indicates that the previous sound is extended. In addition, “R” indicates the “rest”.

[0081] Here, the information processing apparatus **100** deletes the information indicating the pitch. For example, the information processing apparatus **100** replaces information such as “C4” and “E4” with common information such as “M”. As a result, the information constituting the song **30** is “M,  $\_$ ,  $\_$ ,  $\_$ , M,  $\_$ ,  $\_$ , R”. Such information is information in which only the pitch is lost, but the information in which the rhythm is maintained.

[0082] In this case, since the extracted information (referred to as “feature information f.sub.2”) is different, the learning of the encoder after step **S5** is also different. That is, since the feature information f.sub.2 has information that maintains the rhythm of the song **30**, the second encoder **55** that learns such information is learned to output the feature quantity z.sub.2 indicating the “rhythmic feature” of the song. On the other hand, the first encoder **50** is learned to output the feature quantity z.sub.1 other than the “rhythmic feature” of the song. That is, the encoder that extracts information different from the example illustrated in FIG. **1** is learned. In this manner, the learning of the first encoder **50** and the second encoder **55** variously varies in advance depending on the type of the extraction operation **40**.

[0083] Note that the example of FIG. **1** illustrates an example of learning the features of the entire song **30**, but the information processing apparatus **100** may pause a song **30** in each predetermined section and acquire data (partial data) of content in each section.

[0084] In this case, the information processing apparatus **100** may divide the song **30** into the partial data using various known methods. For example, the information processing apparatus **100** detects a preset pause of a bar and divides the song **30** into the partial data (bar). Alternatively, the information processing apparatus **100** may divide the song **30** into the partial data based on the

relationship between the beat and the note. For example, if the song **30** is 4/4 beat, the information processing apparatus **100** detects, as one pause, a point in time when four sounds having a length corresponding to a quarter note are reproduced, and divides the song **30** into the bars.

[0085] In addition, the information processing apparatus **100** may use the pause other than the bar as the partial data. For example, the information processing apparatus **100** may detect a pause of a melody line of the song **30** (for example, a location where a rest having a length exceeding a predetermined threshold appears, and the like) and divide the song into the partial data. In this case, the partial data does not necessarily need to match the bar. Further, the information processing apparatus **100** may detect timing when the chord is changed in the song **30**, or the like and may divide the song **30** into the partial data based on the detected timing.

#### 1-2. Configuration of Information Processing Apparatus According to Embodiment

[0086] Next, a configuration of an information processing apparatus **100** that is an example of an information processing apparatus that executes information processing according to an embodiment will be described. FIG. **4** is a diagram illustrating a configuration example of the information processing apparatus **100** according to the embodiment of the present disclosure.

[0087] As illustrated in FIG. **4**, the information processing apparatus **100** has a communication unit **110**, a storage unit **120**, and a control unit **130**. Note that the information processing apparatus **100** may have an input unit (for example, a keyboard or a mouse) that receives various operations from a manager or the like who manages the information processing apparatus **100**, or a display unit (for example, a liquid crystal display or the like) that displays various information.

[0088] The communication unit **110** is realized by, for example, a network interface card (NIC) or the like. The communication unit **110** is connected to a network N (such as the Internet) in a wired or wireless manner, and transmits and receives information to and from other apparatuses or the like via the network N.

[0089] The storage unit **120** is realized by, for example, semiconductor memory elements such as a random access memory (RAM) or a flash memory, or storage devices such as a hard disk or an optical disk. The storage unit **120** includes a model storage unit **121** and a song data storage unit **122**.

[0090] The model storage unit **121** stores the learned model. Specifically, the model storage unit **121** includes the first encoder **50** and the second encoder **55** that extract a feature quantity of content, and the decoder **60** that reconstitutes the content. Note that the model storage unit **121** may store learning data such as content used for learning.

[0091] The song data storage unit **122** stores data related to content (song) input to the model. FIG. **5** illustrates an example of the song data storage unit **122** according to the embodiment. FIG. **5** is a diagram illustrating an example of the song data storage unit **122** according to the embodiment of the present disclosure. In the example illustrated in FIG. **5**, the song data storage unit **122** has items such as “song ID”, “partial data ID”, “pitch information”, “sound length rest information”, “chord information”, and “rhythm information”.

[0092] The “song ID” is identification information for identifying a song. The “partial data ID” is identification information for identifying the partial data. The partial data corresponds to, for example, one or a plurality of bars constituting a song.

[0093] The “pitch information” indicates information on a pitch (scale) of a sound included in the partial data. The “sound length rest information” indicates a length of sound (reproduction time or reproduced beat) included in the partial data or a length or timing of the rest. The “chord information” indicates a type of chords included in the partial data, the constituent sound of the chord, the switching of the chords in the bar, and the like. The “rhythm information” indicates a beat or a tempo of a bar, a position of a strong beat, a position of a weak beat, and the like.

[0094] Note that in FIG. **5**, items such as the pitch information are conceptually described as “C01”, but in actuality, each item stores specific data indicating the sound as described above. In addition, for the sake of explanation, FIG. **5** illustrates an example in which the “pitch

information”, the “sound length rest information”, or the like are stored as different items, but these pieces of information may be collectively stored in one item or the like as the information indicating notes included in the bar. That is, the format of the data indicating the song is not limited to the format illustrated in FIG. 5, but may be any format as long as the format can be handled by the model.

[0095] For example, the example illustrated in FIG. 5 illustrates that a song identified by song ID “A01” has partial data identified by partial data ID “B01” or “B02”. In addition, partial data having partial data ID “B01” includes sound data whose pitch information is “C01”, sound length rest information is “D01”, chord information is “E01”, and rhythm information is “F01”.

[0096] Returning to FIG. 4, the description will be continued. The control unit **130** is realized by, for example, a central processing unit (CPU), a micro processing unit (MPU), or the like which causes a program (for example, the information processing program according to the present disclosure) stored in the information processing apparatus **100** to execute a random access memory (RAM) or the like as a work area. In addition, the control unit **130** is a controller, and may be realized by an integrated circuit such as an application specific integrated circuit (ASIC) or a field programmable gate array (FPGA).

[0097] As illustrated in FIG. 4, the control unit **130** includes an extraction unit **131**, a model generation unit **132**, an acquisition unit **133**, and a content generation unit **134**, and implements or executes functions or operations of information processing described below. Note that the internal configuration of the control unit **130** is not limited to the configuration illustrated in FIG. 4, but may be other configurations as long as the control unit **130** performs information processing described later.

[0098] The extraction unit **131** extracts the first data from the elements constituting the first content. For example, the extraction unit **131** extracts the first data from the elements constituting the first content based on a predetermined rule according to the user's designation. For example, the extraction unit **131** performs the extraction operation on the digital data constituting the first content which is a song to extract the first data.

[0099] For example, the extraction unit **131** receives the operation designated by the user for the first content and the designation of the range in which the operation is performed, and executes the operation in the received range. Specifically, in the song **30** illustrated in FIG. 1, the extraction unit **131** receives from the user the operation of extracting only the rhythm from the song **30** and the designation of the range (for example, bar and the like) in which the rhythm is extracted. Then, the extraction unit **131** executes the operation related to the extraction according to the user's designation.

[0100] As an example of the operation, the extraction unit **131** extracts the first data by performing the operation processing with order invariance on the elements included in the range. For example, the extraction unit **131** performs an order-invariant operation, such as addition, multiplication, or max operation, on the data constituting the first content. By such processing, the extraction unit **131** can extract, from the first content, the first data in which only the information (rhythm in the example of the song) depending on the order is masked.

[0101] Note that the extraction unit **131** may extract, from the elements included in the range, the first data by losing information that is not time-dependent or order-dependent. In the song, the information that is not time-dependent or order-dependent includes, for example, the constituent sound of the chord in a certain bar, tonality of the song, the total number of notes, the beat of the song, and the like. On the other hand, examples of the information depending on the time or the order include the rhythm information of the song.

[0102] For example, the extraction unit **131** can extract the first data in which only the rhythm information is maintained by losing the pitch information which is the information that is not time-dependent or order-dependent among information in a specific range of the first content.

[0103] The model generation unit **132** generates a learned model that has the first encoder **50** that

calculates the first feature quantity as the feature quantity of the first content, and the second encoder **55** that calculates the second feature quantity as the feature quantity of the first data extracted by the extraction unit **131**. Note that the number of encoders included in the learned model is not limited to two, and a larger number of encoders may be included in the learned model. [0104] Further, the model generation unit **132** generates a learned model including the decoder **60** that decodes data corresponding to the first content based on the first feature quantity and the second feature quantity. That is, when decoding the feature quantity extracted from the plurality of encoders, the model generation unit **132** generates a learned model that is configured to be decoded by one common decoder **60**.

[0105] For example, in the case of learning content data such as a song, the model generation unit **132** inputs the content data to the first encoder **50**, and inputs the feature information extracted from the content data to the second encoder **55**. Subsequently, the model generation unit **132** inputs the feature quantities output from the first encoder **50** and the second encoder **55** to the decoder **60**, and reconstitutes the content (song). Then, the model generation unit **132** adjusts parameters of the first encoder **50**, the second encoder **55**, and the decoder **60** so that the difference between the data of the previous and next contents is reduced. The model generation unit **132** repeats such processing, and generates the learned model in which the first encoder **50**, the second encoder **55**, and the decoder **60** are optimized. As described above, the model generation unit **132** may generate the model using various known methods such as VAE and GAN.

[0106] The acquisition unit **133** acquires various information. For example, the acquisition unit **133** acquires data input to the learned model generated by the model generation unit **132**.

[0107] For example, the acquisition unit **133** acquires the feature quantity output from the first encoder **50** or the feature quantity output from the second encoder **55**. Further, the acquisition unit **133** may change the output feature quantity and acquire the acquired information as the information to be input to the learned model. For example, the acquisition unit **133** may obtain new feature quantities by sampling the known feature quantity from the prior distribution of the known feature quantity.

[0108] Further, the acquisition unit **133** may acquire arbitrary data from the information processing terminal used by the user. For example, the acquisition unit **133** acquires data constituting a song. Then, the acquisition unit **133** may input the acquired data to the learned model (in this case, inputs the same data to the first encoder **50** and the second encoder **55**, respectively), and acquire the feature quantities output from each encoder.

[0109] The content generation unit **134** inputs to the decoder the feature quantities output from the learned first encoder **50** or second encoder **55**, or values obtained by combining any of the feature quantities generated based on these feature quantities, thereby generating the second content which is new content having the same format as the first content. Note that the feature quantity generated based on the feature quantities output from the learned first encoder **50** or second encoder **55** are, for example, the feature quantity which is obtained by being sampled from the prior distribution of the feature quantity output from any of the encoders.

[0110] For example, the content generation unit **134** may generate the second content based on the feature quantities output by inputting arbitrary data to the learned first encoder **50** or second encoder **55**. Alternatively, as in the example illustrated in FIG. 3, the content generation unit **134** may generate the second content from values (for example, 64-dimensional vector) by combining the known feature quantity (feature quantity  $z_{\text{sub.1}}$  in the example of FIG. 3) generated and the feature quantity (feature quantity  $z_{\text{sub.3}}$  in the example of FIG. 3) obtained by inputting arbitrary data to the learned first encoder **50** or second encoder **55**.

[0111] Note that, as described above, the feature quantity holding the user desired features is changed according to the operation designated by the user. That is, which of the feature quantity output from the first encoder **50** and the feature quantity output from the second encoder **55** holds the user desired feature is changed according to the type of operation or extraction operation

designated by the user. In any case, if a value (for example, a value forming the 64-dimensional vector if the feature quantity is the 64-dimensional vector) corresponding to the feature quantity input to the decoder **60** is obtained, the content generation unit **134** can generate the second content corresponding to the feature quantity.

[0112] In addition, the content generation unit **134** may input to the decoder **60** the values obtained by combining the feature quantity output from the learned first encoder **50** and the feature quantity output from the learned second encoder **55** to generate the second content, without using the known feature quantity. For example, the content generation unit **134** may generate the second content based on the values obtained by combining arbitrary data (song or the like) obtained by the acquisition unit **133** and each feature quantity output by inputting the arbitrary data to the learned first encoder **50** or second encoder **55**.

[0113] In addition, the content generation unit **134** may generate a plurality of second contents in order by fixing the values corresponding to any of the feature quantities among the combined values and changing values corresponding to other feature quantities in order. For example, when the first half of the feature quantity indicates the rhythmic feature, the content generation unit **134** can generate a plurality of songs whose rhythms are maintained in order by fixing the first half of the feature quantity and changing the second half.

### 1-3. Information Processing Procedure According to Embodiment

[0114] Next, an information processing procedure according to the embodiment will be described with reference to FIGS. **6** and **7**. First, the flow of the learning process according to the embodiment of the present disclosure will be described with reference to FIG. **6**. FIG. **6** is a flowchart (1) illustrating the information processing procedure according to the embodiment of the present disclosure.

[0115] As illustrated in FIG. **6**, the information processing apparatus **100** determines whether or not learning data (content) has been acquired (step **S101**). When the learning data is not acquired (step **S101**; No), the information processing apparatus **100** waits until acquiring the learning data.

[0116] On the other hand, when the learning data is acquired (step **S101**; Yes), the information processing apparatus **100** extracts targeted information (feature information) (step **S102**).

[0117] Then, the information processing apparatus **100** inputs the original learning data and the extracted information to separate encoders (step **S103**). For example, the information processing apparatus **100** inputs the original learning data to the first encoder **50** and inputs the extracted information to the second encoder **55**.

[0118] Then, the information processing apparatus **100** calculates feature quantities of each of the original learning data and the extracted information (step **S104**). Subsequently, the information processing apparatus **100** inputs the calculated feature quantity to the decoder **60** (step **S105**).

[0119] Thereby, the information processing apparatus **100** causes the decoder **60** to output data in the same format as the original learning data (step **S106**). Then, the information processing apparatus **100** optimizes a model based on the output data and the original learning data (step **S107**). For example, the information processing apparatus **100** compares the output data with the original learning data, and optimizes parameters of the model so as to reduce a reconstitution error. Note that the information processing apparatus **100** may repeat the processes from step **S101** to step **S107** a sufficient number of times (for example, until the parameters are settled within a predetermined threshold) for model optimization.

[0120] The information processing apparatus **100** stores the learned model (the first encoder **50**, the second encoder **55**, and the decoder **60**) in the storage unit **120** (step **S108**). As a result, the information processing apparatus **100** ends the learning process.

[0121] Next, the flow of the generation process according to the embodiment of the present disclosure will be described with reference to FIG. **7**. FIG. **7** is a flowchart (2) illustrating the information processing procedure according to the embodiment of the present disclosure.

[0122] As illustrated in FIG. **7**, the information processing apparatus **100** acquires a first feature

quantity (step S201). For example, the first feature quantity is an output from the learned first encoder **50**. Further, the information processing apparatus **100** acquires the second feature quantity (step S202). For example, the second feature quantity is an output from the learned second encoder **55**.

[0123] Then, the information processing apparatus **100** inputs values obtained by combining the acquired first feature quantity and second feature quantity to the decoder **60** (step S203).

[0124] Subsequently, the information processing apparatus **100** generates the second content based on the data output from the decoder **60** (step S204).

## 2. Other Embodiments

[0125] The process according to each embodiment described above may be performed in various different forms (modifications) in addition to each embodiment described above.

### 2-1. Variation of Learning and Generation Process

[0126] In the above embodiment, a learned model including two encoders and one decoder has been described. Here, the information processing apparatus **100** may learn various models having configurations different from those in the above embodiment. This will be described with reference to FIG. **8**.

[0127] FIG. **8** is a diagram illustrating an example of a learning process according to a first modification of the present disclosure. Compared with the example illustrated in FIG. **1**, the example illustrated in FIG. **8** is different from the example illustrated in FIG. **1** in that the model has a first decoder **61** and a second decoder **62**.

[0128] In the example illustrated in FIG. **8**, the information processing apparatus **100** executes the extraction operation **40** on the data  $x_{sub.1}$  (step S15), and extracts the feature information  $f_{sub.1}$  (step S16) as in step S1 illustrated in FIG. **1**. Further, the information processing apparatus **100** inputs the data  $x_{sub.1}$  to the first encoder **50** and inputs the feature information  $f_{sub.1}$  to the second encoder **55** as in step S5 illustrated in FIG. **1** (step S17). Thereby, the information processing apparatus **100** acquires the feature quantity  $z_{sub.1}$  and the feature quantity  $z_{sub.2}$  (step S18). In other words, such operation means that the information processing apparatus **100** performs a function operation corresponding to the first encoder **50** or the second encoder **55** on the data  $x_{sub.1}$  and the feature information  $f_{sub.1}$  and outputs the feature quantity  $z_{sub.1}$  and the feature quantity  $z_{sub.2}$ .

[0129] Subsequently, the information processing apparatus **100** inputs the feature quantity  $z_{sub.1}$  and the feature quantity  $z_{sub.2}$  to the first decoder **61**, and inputs the feature quantity  $z_{sub.2}$  to the second decoder **62** (step S19). In other words, such operation means that the information processing apparatus **100** performs a function operation corresponding to the first decoder **61** on the feature quantity  $z_{sub.1}$  and the feature quantity  $z_{sub.2}$ , and performs a function operation corresponding to the second decoder **62** on the feature quantity  $z_{sub.2}$ .

[0130] The information processing apparatus **100** obtains data  $x'$  from the first decoder **61** by the operation in step S19. Further, the information processing apparatus **100** obtains feature information  $f'$  from the second decoder **62** (step S20). Note that the data  $x'$  is data having the same format as the data  $x_{sub.1}$ , and conceptually indicates data output via the decoder. In addition, the feature information  $f'$  is data having the same format as the feature information  $f_{sub.1}$ , and conceptually indicates the feature information output via the decoder.

[0131] Thereafter, the information processing apparatus **100** adjusts the parameters of each encoder and decoder so that the data  $x'$  approaches the data  $x_{sub.1}$  and the feature information  $f'$  approaches the feature information  $f_{sub.1}$ . That is, the information processing apparatus **100** performs a model optimization process in the same manner as in step S10 illustrated in FIG. **1**.

[0132] Thus, the information processing apparatus **100** may learn a model having two decoders. In other words, the information processing apparatus **100** generates the learned model that has a first decoder **61** that decodes data corresponding to the first content (data  $x_{sub.1}$ ) based on the first feature quantity (feature quantity  $z_{sub.1}$ ) and the second feature quantity (feature quantity  $z_{sub.2}$ ),

and a second decoder **62** that decodes data (feature information f.sub.2) corresponding to first data (feature information f.sub.1) extracted from elements constituting the first content based on the second feature quantity.

[0133] According to such configuration, the feature quantity z.sub.2 learned by the second encoder **55** and the second decoder **62** reliably has the information on the feature information f.sub.1 as compared with the configuration illustrated in FIG. **1**. For this reason, the information processing apparatus **100** can stably perform learning in which features are separated. More specifically, the information processing apparatus **100** can more reliably learn information (for example, the rhythm of the song) separated as the feature information f.sub.1 by the configuration illustrated in FIG. **8**.

[0134] Note that the model illustrated in FIG. **8** can have a further different configuration. This will be described with reference to FIG. **9**. FIG. **9** is a diagram illustrating an example of a learning process according to a second modification of the present disclosure.

[0135] Compared with the example illustrated in FIG. **8**, the example illustrated in FIG. **9** is different from the example illustrated in FIG. **8** in that the model does not have the second encoder **55**.

[0136] In the example illustrated in FIG. **9**, the information processing apparatus **100** executes the extraction operation **40** on the data x.sub.1 (step S31), and extracts the feature information f.sub.1 (step S32) as in step S15 illustrated in FIG. **8**. Here, the information processing apparatus **100** inputs the data x.sub.1 to the first encoder **50** (step S33) and obtains the feature quantity z.sub.1 and the feature quantity z.sub.2 (step S34). In this case, the information processing apparatus **100** sets a predetermined rule in advance for the value output from the first encoder **50**, and outputs the feature quantity z.sub.1 and the feature quantity z.sub.2. For example, the information processing apparatus **100** sets rules in advance so that the first 32 dimensions of the 64-dimensional vector output are the feature quantity z.sub.1 and the second 32 dimensions are the feature quantity z.sub.2.

[0137] Subsequently, the information processing apparatus **100** inputs the feature quantity z.sub.1 and the feature quantity z.sub.2 to the first decoder **61**, and inputs the feature quantity z.sub.2 to the second decoder **62** (step S35). The information processing apparatus **100** obtains the data x' from the first decoder **61** by the operation in step S35. Further, the information processing apparatus **100** obtains the feature information f' from the second decoder **62** (step S36).

[0138] Thereafter, the information processing apparatus **100** adjusts the parameters of each encoder and decoder so that the data x' approaches the data x.sub.1 and the feature information f' approaches the feature information f.sub.1.

[0139] As described above, the information processing apparatus **100** can perform the learning in which the feature quantity is separated as illustrated in FIGS. **1** and **8** even in the configuration in which the second encoder **55** is omitted. Thereby, the information processing apparatus **100** can simplify the configuration of the model, and as a result, for example, the learning process can be performed quickly or the processing load can be reduced.

[0140] Next, a modification of the generation process in a case of generating new content will be described with reference to FIG. **10**. FIG. **10** is a diagram illustrating an example of a generation process according to a third modification of the present disclosure.

[0141] FIG. **10** illustrates a flow of a process upon generating new content from the learned first encoder **50** and first decoder **61**. Note that the first encoder **50** and the first decoder **61** are, for example, an encoder and a decoder whose parameters have been learned through learning in FIG. **9** and the like.

[0142] The information processing apparatus **100** inputs arbitrary data x.sub.1 to the first encoder **50** (step S41) and obtains the feature quantity z.sub.1 and the feature quantity z.sub.2 (step S42). Then, the information processing apparatus **100** inputs the feature quantity z.sub.1 and the feature quantity z.sub.2 to the first decoder **61** (step S43), and obtains the data x' (step S44). Note that the information processing apparatus **100** may not obtain a feature quantity input to the first decoder **61**

from the first encoder **50**, but obtain a feature quantity by sampling the feature quantity input to the first decoder **61** from the distribution of the pre-learned feature quantity.

[0143] In this way, the information processing apparatus **100** can generate the data  $x'$ , which is new content, from the learned model (in this example, the first encoder **50** and the first decoder **61**) having a simple configuration. According to such a configuration, the information processing apparatus **100** inputs both the feature quantity  $z_{\text{sub.1}}$  and the feature quantity  $z_{\text{sub.2}}$  to one decoder, and as a result, can obtain, for example, the data  $x'$  including features that are not completely separated. As a result, the information processing apparatus **100** can generate new content including even rhythm information that is not completely separated into, for example, the feature quantity  $z_{\text{sub.2}}$  and is also assumed to remain even in the feature quantity  $z_{\text{sub.1}}$ .

## 2-2. Variation of Extraction Operation

[0144] In the above embodiment, as an example of the extraction operation **40**, an example has been described in which a predetermined operation is performed to extract order-invariant information (for example, rhythm information) from a song **30**. The information processing apparatus **100** may perform various operations as the extraction operation **40** in addition to this example.

[0145] For example, in the above embodiment, the example has been illustrated in which the information processing apparatus **100** extracts a chord constituent sound of the song **30**, but the information processing apparatus **100** may extract not only the chord constituent sound but also a constituent sound of a melody or a constituent sound of a drum. The constituent sound of the melody indicates, for example, the type of sound and the like that appears in a certain section, such as a bar of a song. In addition, the constituent sound of the drum indicates, for example, a type of sound (snare drum, bass drum, or the like) of the drum set and the like that appears in a certain section, such as the bar of the song.

[0146] In addition, the information processing apparatus **100** may extract information (so-called Melodic Contour) indicating a flow of a pitch, such as whether the pitch is raised, lowered, or stopped in a flow of a song. In addition, the information processing apparatus **100** may extract the scale of the sound that constitutes the song (information indicating which of the 12 sounds is used to compose a song). Further, the information processing apparatus **100** may extract information (ordered constituent sound) that gives an order to constituent sounds. For example, the information processing apparatus **100** may extract information (for example, a sequence of pitches such as 1 degree, 1 degree, and 2 degree) in which pitches of adjacent notes are ordered and arranged.

[0147] In addition, the information processing apparatus **100** may extract a pattern-classified sequence (for example, an implication/realization model or the like) in a song. Further, the information processing apparatus **100** may employ a method for extracting an important note sequence determined by, for example, a depth of a time span tree of generative theory of tonal music (GTTM).

[0148] In addition, the information processing apparatus **100** may extract information which is a lead sound, a chord sound, a chord type, a root of a chord, a bass line, and the like from the sounds constituting the song.

[0149] Further, the information processing apparatus **100** may extract strength information (velocity) in a certain section when a song is composed of MIDI information.

[0150] Further, the information processing apparatus **100** may extract sounds for each musical instrument constituting a song or for each musical instrument group. In addition, the information processing apparatus **100** may extract a style feature quantity or the like in which a correlation between features of a certain layer is calculated when features of a certain song are learned by a deep neural network (DNN). Further, the information processing apparatus **100** may extract self-similarity or the like in the song.

[0151] In addition, the information processing apparatus **100** may learn the features of the song and extract features based on the learned result. For example, the information processing apparatus **100**



may learn a task of modulating a song with a sequence-to-sequence network (model), and sets conditions, such as modulation, for the decoder to extract features which are invariant with respect to the modulation.

### 2-3. Variation of Application

[0152] As described in the above embodiment, according to the information processing according to the present disclosure, it is possible to perform learning in which predetermined features are separated, so the influence of features appearing in new content can be selectively increased or decreased. This will be described with reference to FIG. 11. FIG. 11 is a diagram for conceptually describing the generation processing according to the present disclosure.

[0153] FIG. 11 illustrates a graph 64 conceptually illustrating an image (pitch and sound length) of a song generated by the generation process according to the present disclosure. As described above, the information processing apparatus 100 can extract a rhythm as one of the features representing a song, and generate a new song reflecting the influence of fixing or changing the rhythm.

[0154] For example, when changing features other than the rhythm factor while fixing a factor (referred to as a “rhythm factor”) that determines the rhythmic feature of the song, the information processing apparatus 100 generates a song along an axis of fixing the rhythm factor illustrated in FIG. 11. On the other hand, when the features other than the rhythm factor are fixed and the rhythm factor is changed, the information processing apparatus 100 generates the song along the axis of fixing other than the rhythm factor illustrated in FIG. 11.

[0155] In general, in the generation of content, when the feature quantity cannot be separated, some change can be given to the original data, but it is difficult to adjust the direction of the change. For example, the information processing apparatus 100 can generate a new song 66 by changing a feature quantity of a song 65 indicating sound information of 1 bar, but when the feature quantity is not separated, sets the direction in change to be one direction (so-called 1D-interpolation) on a diagonal line.

[0156] However, according to the information processing apparatus 100, since the elements such as the rhythm factor can be separated from the features of the song, the song 65 can be changed in a direction in which the rhythm factor is fixed and in a direction (so-called 2D-interpolation) in which elements other than the rhythm factor are fixed. For example, the information processing apparatus 100 can change the song 65 to images of the entire song illustrated in the graph 64 according to the user's request. As described above, the information processing apparatus 100 can generate new content so as to adjust a blend ratio of the feature quantity.

[0157] That is, the information processing apparatus 100 can generate new content or variations not only by fixing a rhythm or a degree of modulation of a song, a scale, and the like, but also by controlling the degree of change. As a specific method, the variation of the feature quantity can be generated by obtaining two noises and adding each noise to the two feature quantities  $z_{\text{sub}.1}$  and  $z_{\text{sub}.2}$ . At this time, when the noise is scaled, the degree of variation can be controlled for each of the two feature quantities  $z_{\text{sub}.1}$  and  $z_{\text{sub}.2}$ . For example, when there are two methods for obtaining noise, there is a method for (1) obtaining noise from a certain fixed distribution such as a normal distribution, and a method for (2) learning an encoder using VAE and using noise output from the encoder. In addition, the information processing apparatus 100 can perform a flexible generation process, such as generating new content by exchanging features of certain two songs.

### 2-4. Variation of Feature Quantity

[0158] In the above embodiment, an example has been described in which the information processing apparatus 100 learns two types of feature quantities (rhythm and elements other than the rhythm) in a song. However, the information processing apparatus 100 may learn two or more types of feature quantities.

[0159] This will be described with reference to FIG. 12. FIG. 12 is a diagram (1) illustrating an example of a learning process according to a fourth modification of the present disclosure. FIG. 12 conceptually illustrates feature quantities  $z_{\text{sub}.o}$ ,  $z_{\text{sub}.a}$ ,  $z_{\text{sub}.b}$ , and  $z_{\text{sub}.e}$  separated in the

learning process and variations in the relationship between the feature quantities.

[0160] A conceptual diagram **67** illustrated in FIG. **12(a)** illustrates that three types of feature quantities each are a feature group that is an exclusive feature. A conceptual diagram **68** illustrated in FIG. **12(b)** illustrates that four types of feature quantities each are a feature group which is a certain space of a common portion. A conceptual diagram **69** illustrated in FIG. **12(c)** illustrates that three types of feature quantities are a feature group that is a nesting space.

[0161] FIG. **13** illustrates an example of learning the feature group illustrated in FIG. **12(a)**. FIG. **13** is a diagram (2) illustrating an example of a learning process according to a fourth modification of the present disclosure.

[0162] As illustrated in FIG. **13**, the information processing apparatus **100** executes a first extraction operation **41** and a second extraction operation **42** on the data x.sub.1 (step S51). Then, the information processing apparatus **100** obtains the feature information f.sub.1 by the first extraction operation **41**, and obtains the feature information f.sub.2 by the second extraction operation **42** (step S52). Subsequently, the information processing apparatus **100** inputs the data x.sub.1 to the first encoder **50**, inputs the feature information f.sub.1 to the second encoder **55**, and inputs the feature information f.sub.2 to the third encoder **56** (step S53).

[0163] The information processing apparatus **100** obtains the feature quantity z.sub.o from the first encoder **50**, obtains the feature quantity z.sub.a from the second encoder **55**, and obtains the feature quantity z.sub.b from the third encoder **56**, respectively (step S54). Subsequently, the information processing apparatus **100** inputs the feature quantity z.sub.o, the feature quantity z.sub.a, and the feature quantity z.sub.b to the first decoder **61**, the feature quantity z.sub.a to the second decoder **62**, and the feature quantity z.sub.b to the third decoder **63**, respectively (step S55). Then, the information processing apparatus **100** obtains the data x' from the first decoder **61**, the feature information f.sub.i' from the second decoder **62**, and the feature information f.sub.2' from the third decoder **63** (step S56). Subsequently, the information processing apparatus **100** optimizes the decoder and the encoder so that the data x' approaches the data x.sub.1, the feature information f.sub.i' approaches the feature information f.sub.1, and the feature information f.sub.2' approaches the feature information f.sub.2, respectively.

[0164] With the configuration illustrated in FIG. **13**, the information processing apparatus **100** can learn the feature group having the relationship illustrated in FIG. **12(a)**. Note that as a specific example of the learning illustrated in FIG. **13**, for example, the first decoder **61** executes a task related to the melody of the song, the second decoder **62** executes a task related to the rhythm of the melody of the song, and the third decoder **63** executes a task related to the melody constituent sound of the song. In other words, in the model illustrated in FIG. **13**, it can be said that the second decoder **62** captures the feature quantity z.sub.a, the third decoder **63** captures the feature quantity z.sub.b, and the first decoder **61** captures other features.

[0165] Next, FIG. **14** illustrates an example of learning the feature group illustrated in FIG. **12(b)**. FIG. **14** is a diagram (3) illustrating an example of a learning process according to a fourth modification of the present disclosure.

[0166] As illustrated in FIG. **14**, the information processing apparatus **100** inputs the data x.sub.1 to the first encoder **50** (step S61). Then, the information processing apparatus **100** outputs the feature quantities z.sub.o, z.sub.a, z.sub.b, and z.sub.e from the first encoder **50** (step S62). Note that in this case, the information processing apparatus **100** may set a predetermined rule regarding the separation of the feature quantity in the same manner as in step S33 of FIG. **9** or the like.

[0167] Subsequently, the information processing apparatus **100** inputs the feature quantities z.sub.o, z.sub.a, z.sub.b, and z.sub.e to the first decoder **61**, the feature quantity z.sub.a and the feature quantity z.sub.e to the second decoder **62**, and the feature quantities z.sub.b and z.sub.e to the third decoder **63**, respectively (step S63). Such processing is based on the fact that feature quantity z.sub.e has features in common with the feature quantity z.sub.a and the feature quantity z.sub.b, as illustrated in FIG. **12(b)**.

[0168] Then, the information processing apparatus **100** obtains the data  $x'$  from the first decoder **61**, the feature information  $f_{\text{sub}.i'}$  from the second decoder **62**, and the feature information  $f_{\text{sub}.2'}$  from the third decoder **63** (step S56). Subsequently, the information processing apparatus **100** optimizes the decoder and the encoder so that the data  $x'$  approaches the data  $x_{\text{sub}.1}$ , the feature information  $f_{\text{sub}.i'}$  approaches the feature information  $f_{\text{sub}.1}$ , and the feature information  $f_{\text{sub}.2'}$  approaches the feature information  $f_{\text{sub}.2}$ , respectively.

[0169] With the configuration illustrated in FIG. **14**, the information processing apparatus **100** can learn the feature group having the relationship illustrated in FIG. **12(b)**.

[0170] Next, FIG. **15** illustrates an example of learning the feature group illustrated in FIG. **12(c)**. FIG. **15** is a diagram (4) illustrating an example of a learning process according to a fourth modification of the present disclosure.

[0171] In the processing illustrated in FIG. **15**, steps S71 to S74 are common to steps S51 to S54 illustrated in FIG. **13**, and thus a description thereof will be omitted.

[0172] The information processing apparatus **100** inputs the feature quantity  $z_{\text{sub}.o}$ , the feature quantity  $z_{\text{sub}.a}$ , and the feature quantity  $z_{\text{sub}.b}$  obtained in step S74 to the first decoder **61**, the feature quantity  $z_{\text{sub}.a}$  and the feature quantity  $z_{\text{sub}.b}$  to the second decoder **62**, and the feature quantity  $z_{\text{sub}.b}$  to the third decoder **63**, respectively (step S75). As illustrated in FIG. **12(c)**, such processing is based on the fact that feature quantity  $z_{\text{sub}.b}$  has a nesting structure with the feature quantity  $z_{\text{sub}.a}$  and the feature quantity  $z_{\text{sub}.o}$ .

[0173] Then, the information processing apparatus **100** obtains the data  $x'$  from the first decoder **61**, the feature information  $f_{\text{sub}.i'}$  from the second decoder **62**, and the feature information  $f_{\text{sub}.2'}$  from the third decoder **63**, respectively (step S76). Subsequently, the information processing apparatus **100** optimizes the decoder and the encoder so that the data  $x'$  approaches the data  $x_{\text{sub}.1}$ , the feature information  $f_{\text{sub}.i'}$  approaches the feature information  $f_{\text{sub}.1}$ , and the feature information  $f_{\text{sub}.2'}$  approaches the feature information  $f_{\text{sub}.2}$ , respectively.

[0174] With the configuration illustrated in FIG. **15**, the information processing apparatus **100** can learn the feature group having the relationship illustrated in FIG. **12(c)**. As described with reference to FIGS. **12** to **15**, the information processing apparatus **100** can perform learning by separating each feature even when a plurality of feature quantities (feature groups) have various relationships.

## 2-5. Variation of Information Processing

[0175] When there is a dependency relationship between two feature quantities (for example, feature quantity  $z_{\text{sub}.1}$  and feature quantity  $z_{\text{sub}.2}$ ), the information processing apparatus **100** may be dependent on the encoder or the prior distribution used for each processing.

[0176] Further, the information processing apparatus **100** may share an embedding vector (embedding) in two passes of the encoder. For example, when the information processing apparatus **100** performs learning by extracting a constituent sound or the like of a song, the information processing apparatus **100** shares the embedding vector in two passes of the encoder.

[0177] Further, the information processing apparatus **100** may separate the feature quantity using hostile learning. Specifically, the information processing apparatus **100** may learn an identifier that classifies the feature quantity  $z_{\text{sub}.2}$  and the noise of the normal distribution in order to separate two feature quantities (for example, feature quantity  $z_{\text{sub}.1}$  and feature quantity  $z_{\text{sub}.2}$ ), and may perform the hostile learning such as learning feature quantity  $z_{\text{sub}.1}$  so that the identification becomes impossible.

## 2-6. Variation of Model Structure

[0178] The information processing apparatus **100** may learn a model having a further different structure with respect to the handling of the feature quantity or the feature information. This will be described below with reference to FIG. **16**. FIG. **16** is a diagram illustrating an example of a learning process according to a fifth modification of the present disclosure.

[0179] In the example illustrated in FIG. **16**, the information processing apparatus **100** executes the extraction operation **40** on the data  $x_{\text{sub}.1}$  (step S81), and extracts the feature information  $f_{\text{sub}.1}$

(step S82). Thereafter, the information processing apparatus **100** inputs the feature information  $f_{sub.1}$  to the first encoder **50** together with the data  $x_{sub.1}$ , and inputs the feature information  $f_{sub.1}$  to the second encoder **55** (step S83). Thereby, the information processing apparatus **100** obtains the feature quantity  $z_{sub.1}$  and the feature quantity  $z_{sub.2}$  (step S84).

[0180] Subsequently, the information processing apparatus **100** inputs the feature quantity  $z_{sub.1}$  and the feature information  $f_{sub.1}$  to the first decoder **61**, and inputs the feature quantity  $z_{sub.2}$  to the second decoder **62** (step S85). Then, the information processing apparatus **100** obtains the data  $x'$  from the first decoder **61**, and obtains the feature information  $f'$  from the second decoder **62** (step S86).

[0181] Thereafter, the information processing apparatus **100** adjusts the parameters of each encoder and decoder so that the data  $x'$  approaches the data  $x_{sub.1}$  and the feature information  $f'$  approaches the feature information  $f_{sub.1}$ . That is, the information processing apparatus **100** performs model optimization processing.

[0182] As described above, the information processing apparatus **100** may generate a learned model that has the first decoder **61** that decodes the data corresponding to the first content (data  $x_{sub.1}$ ) based on the first feature quantity (feature quantity  $z_{sub.1}$ ) and the first data (feature information  $f_{sub.1}$ ) and the second decoder **62** that decodes the data (feature information  $f'$ ) corresponding to the first data based on the second feature quantity (feature quantity  $z_{sub.2}$ ).

[0183] Specifically, unlike the model or the like illustrated in FIG. **8**, the information processing apparatus **100** inputs the feature information  $f_{sub.1}$  to the first decoder **61** in step S85. Thereby, the information processing apparatus **100** can perform the learning of the encoder and the decoder after conditioning the feature information  $f_{sub.1}$ . That is, the information processing apparatus **100** can perform the learning including the feature information  $f_{sub.1}$ , thereby excluding the uncertainty related to the feature information  $f_{sub.1}$ . Specifically, the information processing apparatus **100** can perform the learning including the feature information  $f_{sub.1}$  in advance, so it is possible to prevent the situation where the learning that separates the feature quantity is not performed (for example, only the rhythm information of the song is extracted as the feature quantity, and the like) for some factors.

[0184] More specifically, according to the structure of the model in FIG. **16**, the uncertainty of the feature information  $f_{sub.1}$  is not learned for the feature quantity  $z_{sub.1}$ , and only the uncertainty of the portion of the data  $x_{sub.1}$  other than the feature information  $f_{sub.1}$  is learned. In other words, a space irrelevant to the feature information  $f_{sub.1}$  is learned for the feature quantity  $z_{sub.1}$ . On the other hand, the space related to feature information  $f_{sub.1}$  is learned by the other encoder (in the example of FIG. **16**, the second encoder **55**). As a result, the feature quantity  $z_{sub.1}$  and the feature quantity  $z_{sub.2}$  are learned as a clearly separated space. That is, according to the learning process according to the fifth modification, the information processing apparatus **100** can improve learning stability.

[0185] Next, a modification of the generation process in a case of generating new content will be described with reference to FIG. **17**. FIG. **17** is a diagram (1) illustrating an example of a generation process according to a fifth modification of the present disclosure.

[0186] FIG. **17** illustrates a flow of a process upon generating new content from the learned first encoder **50**, first decoder **61**, and second decoder **62**. Note that the first encoder **50**, the first decoder **61**, and the second decoder **62** are, for example, an encoder and a decoder whose parameters have been learned through learning in FIG. **16**.

[0187] The information processing apparatus **100** executes the extraction operation **40** on the arbitrary data  $x_{sub.1}$  (step S87), and extracts feature information  $f_{sub.1}$  (step S88). Thereafter, the information processing apparatus **100** inputs the feature information  $f_{sub.1}$  to the first encoder **50** together with the data  $x_{sub.1}$  (step S89). As a result, the information processing apparatus **100** obtains the feature quantity  $z_{sub.1}$  (step S90). In addition, the information processing apparatus **100** obtains the arbitrary feature quantity  $z_{sub.2}$  by sampling the pre-learned feature quantity

(space) from the distribution of the pre-learned feature quantity (space).

[0188] Subsequently, the information processing apparatus **100** inputs the obtained feature quantity  $z.sub.2$  to the second decoder **62** (step **S91**), and inputs the obtained feature information  $f'$ , feature quantity  $z.sub.1$ , and feature information  $f.sub.1$  to the first decoder **61** (step **S91**). Thereby, the information processing apparatus **100** obtains the data  $x'$  which is new content (step **S92**).

[0189] With the configuration in FIG. **17**, the information processing apparatus **100** can generate the data  $x'$  as new content reflecting the influence of the feature (feature information  $f.sub.1$  in the example of FIG. **17**) extracted by the extraction operation.

[0190] Note that the information processing apparatus **100** may employ a further different configuration in generation. This will be described with reference to FIG. **18**.

[0191] FIG. **18** illustrates a flow of a process upon generating new content from the learned first encoder **50**, second encoder **55**, first decoder **61**, and second decoder **62**. Note that the first encoder **50**, the second encoder **55**, the first decoder **61**, and the second decoder **62** are, for example, an encoder and a decoder whose parameters have been learned through the learning in FIG. **16**.

[0192] The information processing apparatus **100** executes the extraction operation **40** on the arbitrary data  $x.sub.1$  (step **S93**), and extracts the feature information  $f.sub.1$  (step **S94**). Thereafter, the information processing apparatus **100** inputs the feature information  $f.sub.1$  to the first encoder **50** together with the data  $x.sub.1$ , and inputs the feature information  $f.sub.1$  to the second encoder **55** (step **S95**). Thereby, the information processing apparatus **100** obtains the feature quantity  $z.sub.1$  from the first encoder **50** and the feature quantity  $z.sub.2$  from the second encoder **55** (step **S96**). At this time, the information processing apparatus **100** may obtain the arbitrary feature quantity  $z.sub.1$  by sampling the pre-learned feature quantity (space) from the distribution of the pre-learned feature quantity (space).

[0193] Subsequently, the information processing apparatus **100** inputs the obtained feature quantity  $z.sub.2$  to the second decoder **62** (step **S97**), and inputs the obtained feature information  $f'$  and feature quantity  $z.sub.1$  to the first decoder **61**. Thereby, the information processing apparatus **100** obtains the data  $x'$  which is new content (step **S98**).

[0194] With the configuration in FIG. **18**, the information processing apparatus **100** can generate the data  $x'$  as new content reflecting the influence of the feature (feature information  $f.sub.1$  in the example of FIG. **18**) extracted by the extraction operation.

## 2-7. Variation of Content

[0195] In the above embodiment, examples of the content include a song (music). Here, the information processing apparatus **100** according to the modification may perform the information processing according to the present disclosure using an image, text data, and the like as content.

[0196] An example in which the information processing apparatus **100** handles the images as content will be described with reference to FIGS. **19** to **21**. FIG. **19** is a diagram (1) illustrating an example of information processing according to a sixth modification of the present disclosure.

[0197] When handling an image as content, the information processing apparatus **100** performs, for example, an operation of extracting high-resolution information or low-resolution information from the image.

[0198] For example, it is assumed that the information processing apparatus **100** learns an image **80** illustrated in FIG. **19** as content and generates a learned model. It is assumed that the number of pixels constituting the image **80** is "128×128 pixels". In this case, each pixel information is pooled in a rough range occupying a certain size such as "32×32 pixels" in the image **80**. Thereby, the low-resolution image (image obtained by performing mosaic processing on the image **80**) in which the image **80** is represented by one pixel for each "32×32 pixels" is obtained.

[0199] Then, the information processing apparatus **100** learns original data of the image **80** with the first encoder **50** and learns the low-resolution image with the second encoder **55**. Then, the feature quantity  $z.sub.1$  output from the first encoder **50** is a feature quantity indicating a feature in a range smaller than 32×32 pixels. On the other hand, the feature quantity  $z.sub.2$  output from the second

encoder **55** is a feature quantity indicating a feature in a wider range other than the feature indicated by the feature quantity  $z.sub.1$ .

[0200] For example, the feature represented by  $32 \times 32$  pixels in the image **80** does not correspond to a person, but corresponds to a wide range of colors such as a background. On the other hand, the feature indicated in the range smaller than  $32 \times 32$  pixels in the image **80** corresponds to, for example, information or the like that features a smaller range such as parts of a person's eyes and nose.

[0201] For this reason, the information processing apparatus **100** changes the feature quantity  $z.sub.2$  while fixing the feature quantity  $z.sub.1$  (for example, sampling the feature quantity  $z.sub.2$  with the prior distribution while fixing the feature quantity  $z.sub.1$ ), and when a plurality of second contents are generated, an image group **82** illustrated in FIG. **19** can be generated. Each image included in the image group **82** illustrated in FIG. **19** is an image in which fine parts such as a person's eyes or nose included in the image **80** is hardly changed, and only a background color and the ambient light is changed.

[0202] The image group **82** generated in this way means a plurality of images obtained by imaging the same person under various backgrounds and environments. That is, according to the information processing apparatus **100**, it is possible to obtain, from one image **80** obtained by imaging a certain person, a number of images equivalent to those obtained by imaging the same person under different environments. Thereby, the information processing apparatus **100** can obtain a large number of images useful for generating a machine learning model (for example, a classifier of a face recognition or facial expression recognition, or the like) that performs specific processing from a very small number of original images. In other words, the information processing apparatus **100** can inflate an image used for learning in an appropriate form.

[0203] Further, the information processing apparatus **100** can perform learning differently from that in FIG. **19**. An example of different learning will be described with reference to FIG. **20**. FIG. **20** is a diagram (2) illustrating an example of the information processing according to the sixth modification of the present disclosure.

[0204] As the original data of the learning, the same image **80** as that in FIG. **19** is used. In the example of FIG. **20**, each pixel information is pooled in a range occupying a smaller range as compared with FIG. **19**, such as " $8 \times 8$  pixels" of the image **80**.

[0205] Then, the information processing apparatus **100** learns the original data of the image **80** with the first encoder **50** and learns the pooled image with the second encoder **55**. Then, the feature quantity  $z.sub.1$  output from the first encoder **50** is a feature quantity indicating a feature in a range smaller than  $8 \times 8$  pixels. On the other hand, the feature quantity  $z.sub.2$  output from the second encoder **55** is a feature quantity indicating a feature in a wider range other than the feature indicated by the feature quantity  $z.sub.1$ .

[0206] For example, the feature indicated in the range smaller than  $8 \times 8$  pixels in the image **80** corresponds to, for example, information or the like that features a smaller range such as parts of a person's eyes and nose.

[0207] In the example of FIG. **20**, the information processing apparatus **100** changes the feature quantity  $z.sub.1$  while fixing the feature quantity  $z.sub.2$  (for example, sampling the feature quantity  $z.sub.1$  with the prior distribution while fixing the feature quantity  $z.sub.2$ ), and when a plurality of second contents are generated, an image group **87** illustrated in FIG. **20** can be generated. Unlike FIG. **19**, each image included in the image group **87** illustrated in FIG. **20** is an image in which the background color or the ambient light is hardly changed and fine parts such as a person's eyes or nose included in the image **80** are changed.

[0208] The image group **87** generated in this manner can be, for example, a large number of images useful for generating a highly accurate face recognition model. That is, when a person captured in the image **80** is finely changed, it is possible to use the image group **87** to generate a model that makes a determination not to recognize a person who was erroneously captured in the image **80**.

Thereby, the information processing apparatus **100** can improve the performance of the facial recognition model.

[0209] Note that the information processing apparatus **100** can use a further different learning method. This will be described with reference to FIG. **21**. FIG. **21** is a diagram (3) illustrating an example of the information processing according to the sixth modification of the present disclosure.

[0210] As the original data of the learning, the same image **80** as that in FIG. **19** is used. Here, in the example of FIG. **21**, the second encoder **55** is learned using data appearing in an intermediate layer while encoding the image **80**. For example, the information processing apparatus **100** performs a global average pooling (GAP) operation on the data (for example, data of 4×4 pixels) of the intermediate layer of the second encoder **55**, and learns the second encoder **55** so as to output the feature quantity  $z_{sub.2}$ . Thereby, in the feature quantity  $z_{sub.2}$ , the image **80** from which the location information (background and the like) has disappeared is learned, and in the feature quantity  $z_{sub.1}$ , the location information is learned. In this case, it is possible to operate those other than the location information in the image by fixing the feature quantity  $z_{sub.1}$  and sampling the feature quantity  $z_{sub.2}$ . For example, as illustrated in FIG. **21**, an image group **92** in which the rough atmosphere of the background is maintained, but a person's face or hairstyle of the person included in the image is variously different is generated. In other words, the information processing apparatus **100** can generate various images including various people with changed featured attributes (alignment) of the face. According to such processing, the information processing apparatus **100** can generate a large number of learning images labeled by a “person” from, for example, one image.

[0211] As described above, the information processing apparatus **100** may perform the extraction operation on the digital data constituting the first content, which is an image, and extract the first data. For example, the information processing apparatus **100** extracts the first data by performing operation processing (for example, pooling) with order invariance on pixel information of each pixel included in a specific region of the image as the extraction operation.

[0212] As described above, even when the content is not a song but an image, the information processing apparatus **100** can perform learning in which features targeted by the user are separated. In addition, the information processing apparatus **100** can use the generated learned model to automatically generate an image that maintains features designated by the user, such as an image in which certain features (such as a background or a human face) are fixed and other features are changed.

[0213] In addition, the information processing apparatus **100** may use text data, a moving image, and the like as content. That is, the information processing apparatus **100** can perform learning to separate the targeted feature quantity if it is possible to learn the information extracted by some operation and the original content data by separate encoders, regardless of the type of content.

[0214] Further, the information processing apparatus **100** may apply the information processing according to the present disclosure to perform processing of detecting a substance or the like emitting a similar taste based on human taste information. For example, the information processing apparatus **100** separates elements having a certain taste from a specific substance, and inputs information obtained by digitalizing each of the elements to separate encoders, thereby learning features obtained by separating only the features of a specific taste from a certain substance.

[0215] In addition, in the above embodiment, an example has been described in which the information processing apparatus **100** performs an operation of extracting the feature information by performing a certain operation with order invariance or losing certain information. However, the extraction operation is not limited to this example. For example, the information processing apparatus **100** learns a supervised regression function such as which phrase has a higher “degree of excitement” based on the “degree of excitement in a song” artificially set in advance for each bar of the song. Then, the information processing apparatus **100** calculates the degree of excitement of each bar of the song to be processed based on the learned result. Then, the information processing

apparatus **100** extracts only a bar whose degree of excitement exceeds a predetermined threshold value, and learns the extracted bar with the second encoder **55**. Thereby, the information processing apparatus **100** can generate a learned model that can separate artificially set features such as the “degree of excitement”.

[0216] That is, the information processing apparatus **100** does not necessarily extract the feature information from the content by an arithmetic operation, but can also extract the feature information from the content based on the artificially set features. With such a configuration, for example, since features corresponding to an emotion can be separated, it is possible to automatically generate, for example, content having some features felt by a human, such as content causing a happy emotion. As an example, the information processing apparatus **100** applies such a configuration to natural language processing to automatically generate content (sentences) having features that recall certain emotions, such as “sentences that cause happy emotions”.

## 2-8. Others

[0217] Further, among each process described in the above embodiments, all or a part of the processes described as being performed automatically may be manually performed or the processes described as being performed manually can be performed automatically by the known method. In addition, the processing procedures, specific names, and information including various data and parameters illustrated in the above documents and drawings can be arbitrarily changed unless otherwise specified. For example, various information illustrated in each drawing is not limited to the information illustrated.

[0218] In addition, each component of each device illustrated is a functional concept, and does not necessarily need to be physically configured as illustrated. That is, the specific form of distribution/integration of each device is not limited to the those illustrated in the drawings, and all or a part thereof may be functionally or physically distributed/integrated into arbitrary units according to various loads and usage conditions.

[0219] Further, the above-described embodiments and modifications can be appropriately combined within a range that does not contradict processing contents.

[0220] In addition, the effects described in the present specification are merely illustrative and not limited to the illustration and additional effects may be present.

## 3. Hardware Configuration

[0221] Information devices such as the information processing apparatus **100** according to each embodiment described above are implemented by, for example, a computer **1000** having the configuration as illustrated in FIG. **11**. Hereinafter, the information processing apparatus **100** according to the embodiment will be described as an example. FIG. **22** is a hardware configuration diagram illustrating an example of the computer **1000** that implements the functions of the information processing apparatus **100**. The computer **1000** includes a CPU **1100**, a RAM **1200**, a read only memory (ROM) **1300**, a hard disk drive (HDD) **1400**, a communication interface **1500**, and an input/output interface **1600**. Each part of the computer **1000** is connected by a bus **1050**.

[0222] The CPU **1100** is operated based on a program stored in the ROM **1300** or the HDD **1400**, and controls each unit. For example, the CPU **1100** develops a program stored in the ROM **1300** or the HDD **1400** into the RAM **1200** and executes processes corresponding to various programs.

[0223] The ROM **1300** stores a boot program such as a basic input output system (BIOS) executed by the CPU **1100** when the computer **1000** starts up, a program depending on hardware of the computer **1000**, and the like.

[0224] The HDD **1400** is a computer-readable recording medium that non-temporarily records a program executed by the CPU **1100**, data used by the program, and the like. Specifically, the HDD **1400** is a recording medium that records an information processing program according to the present disclosure, which is an example of the program data **1450**.

[0225] The communication interface **1500** is an interface for connecting the computer **1000** to an external network **1550** (for example, the Internet). For example, the CPU **1100** receives data from



other devices or transmits data generated by the CPU **1100** to the other devices via the communication interface **1500**.

[0226] The input/output interface **1600** is an interface for connecting between the input/output device **1650** and the computer **1000**. For example, the CPU **1100** receives data from an input device such as a keyboard or a mouse via the input/output interface **1600**. In addition, the CPU **1100** transmits data to an output device such as a display, a speaker, or a printer via the input/output interface **1600**. Further, the input/output interface **1600** may function as a media interface for reading a program or the like recorded on predetermined recording media. The media are, for example, optical recording media such as a digital versatile disc (DVD) or a phase change rewritable disk (PD) a magneto-optical recording medium such as a magneto-optical disk (MO), a tape medium, a magnetic recording medium, a semiconductor memory, or the like.

[0227] For example, when the computer **1000** functions as the information processing apparatus **100** according to the embodiment, the CPU **1100** of the computer **1000** implements the functions of the control unit **130** and the like by executing the information processing program loaded on the RAM **1200**. Further, the HDD **1400** stores the information processing program according to the present disclosure or data in the storage unit **120**. Note that the CPU **1100** reads and executes the program data **1450** from the HDD **1400**, but as another example, the CPU **1100** may acquire these programs from other devices via the external network **1550**.

[0228] Note that the present technology can also be configured as follows.

(1)

[0229] An information processing apparatus, comprising: [0230] an extraction unit that extracts first data from an element constituting first content; and [0231] a model generation unit that generates a learned model that has a first encoder that calculates a first feature quantity as a feature quantity of the first content, and a second encoder that calculates a second feature quantity as a feature quantity of the extracted first data.

(2)

[0232] The information processing apparatus according to (1), wherein [0233] the model generation unit [0234] generates the learned model that has a decoder that decodes data corresponding to the first content based on the first feature quantity and the second feature quantity.

(3)

[0235] The information processing apparatus according to (1) or (2), wherein [0236] the extraction unit [0237] receives an operation specified by a user for the first content and a designation of a range in which the operation is executed, and executes the operation on the received range.

(4)

[0238] The information processing apparatus according to (3), wherein [0239] the extraction unit [0240] extracts the first data by performing operation processing with order invariance on the element included in the range as the operation.

(5)

[0241] The information processing apparatus according to (3) or (4), wherein [0242] the extraction unit [0243] extracts, from the element included in the range, the first data by losing time-independent or order-independent information.

(6)

[0244] The information processing apparatus according to any one of (3) to (5), wherein [0245] the extraction unit [0246] executes the operation on digital data constituting the first content as a song, and extracts the first data.

(7)

[0247] The information processing apparatus according to (6), wherein [0248] the extraction unit [0249] executes the operation of losing information on a height of a sound of sound information included in the range, and extracts the first data from the first content.

(8)

[0250] The information processing apparatus according to any one of (3) to (5), wherein [0251] the extraction unit [0252] executes the operation on digital data constituting the first content as an image, and extracts the first data.

(9)

[0253] The information processing apparatus according to (8), wherein [0254] the extraction unit [0255] extracts the first data by performing operation processing with order invariance on pixel information of each pixel included in a specific region of the image, as the operation.

(10)

[0256] The information processing apparatus according to any one of (2) to (9), further comprising: [0257] a content generation unit that generates second content as new content having the same format as the first content by inputting to the decoder a feature quantity output from a learned first encoder or second encoder or values obtained by combining any of feature quantities generated based on the feature quantity.

(11)

[0258] The information processing apparatus according to (10), wherein [0259] the content generation unit [0260] generates the second content by inputting to the decoder values obtained by combining the feature quantity output from the learned first encoder with the feature quantity output from the learned second encoder.

(12)

[0261] The information processing apparatus according to (10) or (11), wherein [0262] the content generation unit [0263] generates a plurality of the second contents in order by fixing a value corresponding to any of the feature quantities among the combined values and changing values corresponding to other feature quantities in order.

(13)

[0264] An information processing method, comprising: [0265] allowing a computer to [0266] extract first data from an element constituting first content, and [0267] generate a learned model that has a first encoder that calculates a first feature quantity as a feature quantity of the first content, and a second encoder that calculates a second feature quantity as a feature quantity of the extracted first data.

(14)

[0268] A program for executing a computer to function as [0269] an extraction unit that extracts first data from an element constituting first content; and [0270] a model generation unit that generates a learned model that has a first encoder that calculates a first feature quantity as a feature quantity of the first content, and a second encoder that calculates a second feature quantity as a feature quantity of the extracted first data.

(15)

[0271] The information processing apparatus according to any one of (1) or (3) to (12), in which [0272] the model generation unit [0273] generates a learned model that has a first decoder that decodes data corresponding to the first content based on the first feature quantity and the second feature quantity, and a second decoder that decodes data corresponding to the first data based on the second feature quantity.

(16)

[0274] The information processing apparatus according to any one of (1) or (3) to (12), in which [0275] the model generation unit [0276] generates a learned model that has a first decoder that decodes data corresponding to the first content based on the first feature quantity and the first data, and a second decoder that decodes data corresponding to the first data based on the second feature quantity.

#### REFERENCE SIGNS LIST

[0277] **100** Information processing apparatus [0278] **110** Communication unit [0279] **120** Storage unit [0280] **121** Model storage unit [0281] **122** Song data storage unit [0282] **130** Control unit

## Claims

1. An information processing apparatus comprising: processing circuitry configured to receive a first content and a second content, wherein the first content is an image or a moving image, extract, from the first content, a first feature amount corresponding to a first feature, extract, from the second content, a second feature amount corresponding to a second feature, and generate a third content based on the first feature amount and the second feature amount.
2. The information processing apparatus according to claim 1, wherein the processing circuitry is further configured to: receive operation to specify the first feature for the first content, and identify a type of the first feature based on the received operation.
3. The information processing apparatus according to claim 1, wherein the processing circuitry is further configured to extract the first feature amount and the second feature amount via at least one encoder.
4. The information processing apparatus according to claim 3, wherein the processing circuitry is further configured to extract, from the first content, the first feature amount via a first encoder, and extract, from the second content, the second feature amount via a second encoder.
5. The information processing apparatus according to claim 4, wherein the processing circuitry is further configured to apply preprocessing to the first content to extract a first data, output the first feature amount in response to the first data being input into a first encoder, apply preprocessing to the second content to extract a second data, and output the second feature amount in response to the second data being input into a second encoder.
6. The information processing apparatus according to claim 1, wherein the third content is generated based on the first feature amount and the second feature amount via at least one decoder.
7. The information processing apparatus according to claim 6, wherein the processing circuitry is further configured to input the first feature amount and the second feature amount to a decoder, receive a third data output from the decoder, and reconstitute the third content from the third data.
8. The information processing apparatus according to claim 1, wherein the first feature amount is a feature amount for which the corresponding first feature is interpretable by humans.
9. The information processing apparatus according to claim 1, wherein the processing circuitry is further configured to extract, from the first content, a third feature amount corresponding to a third feature, and wherein the third feature is different from the first feature.
10. The information processing apparatus according to claim 9, wherein the third feature amount corresponds to the second feature.
11. The information processing apparatus according to claim 1, wherein the first feature includes at least one of a feature of background of the first content or a feature of a subject of the first content.
12. The information processing apparatus according to claim 11, wherein the feature of background of the first content includes at least one of color of the background and ambient light of the background.
13. The information processing apparatus according to claim 11, wherein the feature of the subject of the first content includes at least one of appearance characteristics of part of the subject and alignment of the part of the subject.
14. The information processing apparatus according to claim 1, wherein the processing circuitry is further configured to extract the first feature amount by an order invariant operation performed on the first content.
15. The information processing apparatus according to claim 1, wherein the processing circuitry is further configured to extract the first feature amount through removal of information that is not time-dependent or order-dependent.

**16.** The information processing apparatus according to claim 1, wherein the processing circuitry is further configured to extract the first feature amount by using a trained model that can separate an artificially set feature.

**17.** The information processing apparatus according to claim 1, wherein the third content is a content used for learning.

**18.** The information processing apparatus according to claim 17, wherein a label for a subject of the third content is the same as a label for a subject of the first content.

**19.** A method for generating content by an information processing apparatus comprising processing circuitry, the method comprising: receiving a first content and a second content; extracting, from the first content, a first feature amount corresponding to a first feature; extracting, from the second content, a second feature amount corresponding to a second feature; and generating a third content based on the first feature amount and the second feature amount.

**20.** A non-transitory computer readable medium containing instructions for a method for generating content by an information processing apparatus comprising processing circuitry, the method comprising: receiving a first content and a second content; extracting, from the first content, a first feature amount corresponding to a first feature; extracting, from the second content, a second feature amount corresponding to a second feature; and generating a third content based on the first feature amount and the second feature amount.

---