

# US Patent & Trademark Office

## Patent Public Search | Text View

United States Patent Application Publication

20250266530

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

Liang; Jiwei et al.

### Battery-Charging Devices Having Thermally Conductive Thermal-Management Systems for Managing Battery Temperature During Charging Operations, and Related Methods

#### Abstract

Battery-charging devices having thermal-management systems that each include one or more thermoelectric devices used to manage the temperature of one or more secondary batteries during charging operations. Each thermoelectric device is operated to cool and/or heat the corresponding battery(ies) using the Peltier effect. The transfer of heat between the battery(ies) and the corresponding thermoelectric device(s) is by thermal conduction via a thermal-conduction interface between the battery(ies) and the corresponding thermoelectric device(s). Related methods of charging batteries are also disclosed.

**Inventors:** Liang; Jiwei (Shanghai, CN), Wang; Xianjie (Shanghai, CN), Zheng; Chengcheng (Shanghai, CN)

**Applicant:** SES (Shanghai) Co. Ltd. (Shanghai, CN)

**Family ID:** 1000007864439

**Appl. No.:** 18/608647

**Filed:** March 18, 2024

#### Foreign Application Priority Data

CN

2024101862023

Feb. 19, 2024

#### Publication Classification

**Int. Cl.:** H01M10/6572 (20140101); H01M10/63 (20140101); H02J7/00 (20060101); H05K7/20 (20060101)

**U.S. Cl.:**

## **Background/Summary**

### **FIELD**

[0001] The present disclosure generally relates to devices for charging secondary batteries. More particularly, the present disclosure is directed to battery-charging devices having thermally conductive thermal-management systems for managing battery temperature during charging operations, and related methods.

### **BACKGROUND**

[0002] Conventional battery chargers often manage heat generated by batteries during charging using either forced-air cooling or forced-liquid cooling. Forced-air cooling schemes can be problematic because ambient air used for cooling can contain dust and/or other contaminant(s) and can also or alternatively carry excessive amounts of moisture. Consequently, when the ambient air is flowed through internal parts of the battery chargers, the contaminants and/or moisture can cause fouling and/or damage to the batteries being charged and/or components of the chargers, such as circuit boards, among others. Forced-liquid cooling schemes can be problematic due to the additional components and complexity that come with providing liquid-coolant passageways, fittings, pumps, and other cooling-system components, not to mention the potential damage that can occur when the liquid coolant leaks from the cooling systems.

### **SUMMARY**

[0003] In one implementation, the present disclosure is directed to a battery-charging device for charging a secondary battery that includes electrical terminals and a heat-transfer face. The battery-charging device includes a charging region that receives the secondary battery during a charging operations; a charging system that, when the secondary battery is present in the charging region, electrically connects to the electrical terminals of the secondary battery and charges the secondary battery during the charging operations; a thermal-management system that includes: a thermal-conduction interface that contactingly receives the heat-transfer face of the secondary battery when the battery is located in the charging region so that heat can be conducted between the secondary battery and the thermal management system during the charging operations; a heat sink/source; and a thermoelectric device thermally coupled between the thermal-conduction interface and the heat sink/source, wherein during the charging operations with the secondary battery located in the charging region, the thermoelectric device transfers heat between the secondary battery and the heat sink/source.

[0004] In another implementation, the present disclosure is directed to a method of charging a secondary battery. The method includes causing a battery-charging device to perform charging operations upon the secondary battery; and during the charging operations, causing a thermoelectric device, that is directly thermally coupled to the secondary battery, to transfer heat between the secondary battery and a heat sink/source by thermal conduction.

---

## **Description**

### **BRIEF DESCRIPTION OF THE DRAWINGS**

[0005] For the purpose of illustration, the accompanying drawings show aspects of one or more embodiments of the disclosure. However, it should be understood that the scope of this disclosure is/are not limited to the precise arrangements and instrumentalities shown in the drawings, wherein:

[0006] FIG. 1 is a high-level schematic/block diagram of an example battery-charging device made in accordance with aspects of the present disclosure;

[0007] FIG. 2 is an isometric view of an example battery-charging device of the present disclosure configured to charge two battery packs in corresponding respective charging compartments;

[0008] FIG. 3 is an exploded isometric view of the battery-charging device of FIG. 2;

[0009] FIG. 4 is an enlarged cross-sectional view of each of the battery packs operatively engaged with a corresponding one of thermal-management components of the battery-charging device of FIGS. 2 and 3, shown in FIG. 4 in isolation from other components of the battery-charging device; and

[0010] FIG. 5 is a further enlarged partial cross-sectional view of the battery pack and the thermal-management component of the battery-charging device of FIGS. 1 and 2 as taken at detail region A of FIG. 4.

## DETAILED DESCRIPTION

[0011] The technical content of the appended claims are incorporated by reference into this Detailed Description section so that they are included herein as if they were literally present in this section.

### General

[0012] In some aspects, the present disclosure is directed to battery-charging devices for electrically charging secondary batteries of any of a variety of types and any of a variety of chemistries, wherein each battery-charging device includes at least one thermoelectric device that is directly thermally coupled to each of the one or more secondary batteries that are charged by the battery-charging device. Examples of secondary battery types that can be used with a battery-charging device of this disclosure include, but are not limited to, secondary batteries that include one or more pouch cells or one or more cylindrical cells, among others. Examples of battery chemistries include, but are not limited to, chemistries based on one or more alkali metals, such as lithium, sodium, and potassium, chemistries based on sulfur, and chemistries based on nickel, among others, and may be of the intercalating-de-intercalating type, the plating-stripping type, or any combination thereof, among others. Fundamentally, there is no limitation on the type of secondary batteries suitable for use with a battery-charging device of this disclosure other than that it can be electrically charged and that the temperature of the secondary battery may need to be controlled during charging operations. In this disclosure and in the appended claims, the term “secondary battery” and “battery”, unless noted otherwise, is broadly used to denote a rechargeable electrochemical device of any form, including, but not limited to an electrochemical cell, a battery module containing one or more electrochemical cells, and a battery pack comprising one or more battery modules, among others.

[0013] As used herein and in the appended claims, the term “thermoelectric device” denotes a solid-state device that, when electrically powered, exhibits the well-known Peltier phenomenon that results in a temperature difference at the junction of two dissimilar materials. Thermoelectric devices are typically made of two dissimilar semiconductor materials, such as bismuth telluride and antimony telluride, that, when a DC voltage is applied to them, experience electron flow from one of the semiconductor materials to the other across the junction, causing one of the semiconductor materials to absorb heat and the other semiconductor material to reject heat. Controlling the absolute magnitude of the DC voltage, within limits, controls the magnitude of the temperature-change-causing electron flow within the thermoelectric device, thereby controlling the amounts of heat absorption and heat rejection. Controlling the direction of the DC voltage controls the absorption-rejection behavior of the two materials, thereby controlling the ability of each side of the junction to provide heat or absorb heat.

[0014] In some aspects, the present disclosure is directed to methods of performing charging operations for electrically charging a secondary battery that is in direct thermal contact with a thermoelectric device. In an example, a method of the present disclosure includes causing a battery-

charging device to perform charging operations upon a secondary battery. During the charging operations, a thermoelectric device that is directly thermally coupled to the secondary battery is caused to transfer heat between the secondary battery and a heat sink/source by thermal conduction. In some embodiments, if the secondary battery is initially at a temperature below a preset minimum charging temperature, the thermoelectric device is operated to provide heat to the secondary battery to raise the temperature of the battery to the minimum charging temperature or above. When the temperature of the secondary battery rises above a maximum charging temperature during charging, the thermoelectric device is operated to remove heat from the secondary battery to drop the temperature of the secondary battery to or below the maximum charging temperature. Other methods are disclosed. The foregoing and other aspects of the present disclosure are described below in detail.

[0015] Referring now to the drawings, FIG. 1 shows an example battery-charging device **100** that includes various features of the present disclosure. In this example, the battery charging device **100** includes a charging region **104** configured to a secondary battery **108** (hereinafter, simply “battery”) for performing charging operations so as to charge the battery. As noted above, the battery **108** can be any of a variety of battery devices in any of a variety of forms. In this example, the battery **108** is a battery module having positive and negative electrical terminals **108T(1)** and **108T(2)** in electrical communication with the battery core (not shown) within the battery. The battery-charging device **100** has a charging system **112** that, during the charging operations, is electrically connected to the electrical terminals **108T(1)** and **108T(2)** of the battery **108** and that include all of the necessary electronics (not shown), which includes any necessary control software and/or hardware for charging the battery using any one or more of a variety of charging protocols, including, but not limited to a constant-current constant-voltage protocol, a multistage constant current protocol, and/or a constant-current+pulsed charging protocol, among others. Those skilled in the art are readily familiar with charging protocols and corresponding electronics that can be used in the charging system **112** such that further details are not needed herein for those of ordinary skill in the art to make and use a battery-charging device of the present disclosure, such as the battery-charging device **100** of FIG. 1.

[0016] The battery-charging device **100** of this example also includes a thermal-management system **116** that comprises one or more thermoelectric devices (singly and collectively shown at thermoelectric device(s) **120**) and thermal-management-system electronics **124** for operating the thermoelectric device(s). Each thermoelectric device **120** includes first and second sides **120S(1)** and **120S(2)**, made of dissimilar materials, that form a junction **120J** as noted above. As discussed above, the dissimilar materials of the first and second sides may be, for example, any suitable dissimilar semiconductor materials, such as, but not limited to, bismuth telluride and antimony telluride, among others. Those skilled in the art will be readily familiar with thermoelectric devices suitable for use as any thermoelectric device(s) **120** of a battery-charging device of the present disclosure, such as the battery-charging device **100** of FIG. 1, such that further details are not needed herein for those of ordinary skill in the art to make and use such a battery-charging device.

[0017] The thermal-management-system electronics **124** includes any and all components needed to power and control the operation of the thermoelectric device(s) **120**, such as, but not limited to, one or more DC power supplies (not shown), such as one or more variable-voltage DC power supplies, and any necessary support electronics (not show). Thermoelectric devices and thermal-management-system electronics suitable for use in the thermal-management system **116** are well-known such that further details are not needed herein for those of ordinary skill in the art to make and use a battery-charging device of the present disclosure, such as the battery-charging device **100** of FIG. 1.

[0018] In this example, the battery-charging device **100** further includes a control system **128**, which is configured to control the overall operations of the battery-charging device partially or fully automatically, including controlling each of the charging system **112** and the thermal-

management system **116** so that the battery-charging device performs the desired charging operations. In some embodiments, the charging operations include stopping and starting charging, for example, stopping and/or starting charging in conjunction with controlling the thermal-management system **116**. For example, in some situations, the battery **108** is optimally charged when the temperature of the battery is at or above a minimum charging temperature. If the battery **108** is below the minimum charging temperature before charging begins, for example, when the battery is first placed into the battery-charging region **104**, then the control system **128** may cause the thermal-management system **116** to operate the thermoelectric device(s) **120** in a manner to warm the battery to at least the minimum charging temperature before causing the charging system **112** to start charging the battery. As another example, if the battery **108** is above a maximum charging temperature before charging begins, for example, when the battery is first placed into the battery-charging region **104**, then the control system **128** may cause the thermal-management system **116** to operate the thermoelectric device(s) in a manner to cool the battery to at most the maximum charging temperature before causing the charging system **112** to start charging the battery.

[0019] As a further example, charging the battery **108** can cause the battery **108** to heat up. Consequently, during charging operations, when the control system **128** determines that the temperature of the battery **108** has exceeded the maximum charging temperature, it may then cause the thermal-management system **116** to operate the thermoelectric device(s) **120** in a manner that removes heat from the battery, for example, until the temperature of the battery has fallen below the maximum charging temperature. The control scheme that the control system **128** uses to cause the thermal-management system **116** to keep the battery **108** within a charging-temperature range during charging may be any suitable control scheme. For example, the control system **128** may cause the thermal-management system **116** to keep the temperature of the battery **108** within a relatively narrow optimal-charging-temperature range by controlling the thermal-management system to operate nearly continuously during charging so as to essentially balance the amount of heat that the thermal-management system removes with the amount of heat that charging generates. As those skilled in the art will appreciate, this balancing may be accomplished using a tight temperature control loop that varies the DC voltage applied across the first and second sides **120S(1)** and **120S(2)** of the thermoelectric device(s) **120**.

[0020] In another example, the control system **128** may cause the thermal-management system **116** to operate intermittently so as to cool the battery **108** to a relatively low temperature, such as close to the minimum charging temperature, and then allow the battery to heat up to a relatively high temperature, such as close to the maximum charging temperature, before causing the thermal-management system to reenergize the thermoelectrical device(s) **120**. Those skilled in the art will appreciate that in an intermittent control scheme, the control system **128** may, in some embodiments, cause the thermal management system **116** to operate the thermoelectric device(s) **120** at or near its/their maximum DC voltage while it/they are energized so as to minimize the amount of cooling time. Those skilled in the art will readily appreciate that these example control schemes are merely examples and are not limiting and that the control system **128** may use any suitable control scheme(s) for controlling the temperature of the battery **108** during charging.

[0021] In the embodiment shown, the control system **128** includes a processor **132**, one or more hardware memories (singly and collectively represented as memory **136**) in operative communication with the processor, machine-executable instructions **140** stored in the memory and configured for execution by the processor, and any needed user interface (UI) **144**. The processor **132** may be any suitable processor, such as, for example, system on chip or a microprocessor. In some embodiments, the processor **132**, memory **136**, and machine-executable instructions **140** may be embodied in specialized circuitry, such as a system on chip, an application-specific integrated circuit, or a field-programmable gate array, among other options. The memory **136** may be any one or more hardware memories, such as RAM, ROM, cache, magnetic, optical, bubble, etc.

Fundamentally, there is no limitation on the type(s) of the memory **136** as long as it/they can store the machine-executable instructions **140** and can communicate the machine-executable instructions to the processor **132**. In this connection, it is noted that the term “machine-readable hardware storage medium” as used herein and in any appended claim, means any hardware memory, standing alone or in combination with one another, that stores the machine-executable instructions, such as the machine-executable instructions **140**, that cause any one or more processors, such as the processor **132**, to perform the requisite functionality(ies). The term “machine-readable hardware storage medium” does not include transitory signals, such as signals containing digital information encoded onto carrier waves and signals containing digital information encoded in pulses.

[0022] If provided, the UI **144** may include any soft control(s), hard control(s), or combination of soft and hardware controls needed for performing the desired operation(s), as well as any needed electronic display needed to convey information visually to a user. For example, the UI **144** may include one or more controls for turning the battery-charging device **100** on and/or off, one or more controls for starting and/or stopping charging operations, one or more controls for imputing charging-operation parameters, such as type of the battery **108**, capacity of the battery, maximum state of charge for charging, type of charging protocol, and minimum and/or maximum charging temperatures, among others. Those skilled in the art will readily understand what, if any, soft and/or hard controls to include for a particular implementation of the battery-charging device **100**. In some embodiments, the battery-charging device **100** may be in operative communication with another device (not shown), such as a broader charging-system controller, laptop computer, etc., that provides UI functionality, including any one or more of the functionalities described above, such that the onboard UI **144** is not needed.

[0023] The machine-executable instructions **140** include machine-executable instructions for executing any or all of the control scheme(s) (e.g., as one or more algorithms) that the control system **128** is configured to perform, as well as for providing any or all of the functionality(ies) of the UI **144**, if present, not to mention any other functionality(ies) that need to be performed, such as communicating with one or more offboard devices, among many others. Those skilled in the art will readily understand how to code any needed machine-executable instructions needed for performing the necessary control algorithm(s) (e.g., charging-operations control algorithm(s)) and for providing any other required functionality(ies) such that it is not necessary to describe the machine-executable instructions **140** in any further detail herein for those skilled in the art to make and use a battery-charging device of the present disclosure, such as the battery-charging device **100**.

[0024] The thermal-management system **116** includes a thermal-conduction interface **148** between the battery **108** and thermoelectric device **120** so as to provide a direct contact-type coupling between the battery and the thermoelectric device to allow heat to be thermally conducted between the two elements. By “direct contact-type coupling” it is meant that the thermal-conduction interface **148** physically contacts both the battery **108** and the thermoelectric device **120** so that the transfer of heat between the battery and the thermoelectric device is by thermal conduction through the thermal-conduction interface. The thermal-conduction interface **148** may be composed of any one or more materials and disposed in any one or more layers. For example, in some embodiments, the thermal-conduction interface **148** may be a sheet, plate, or other structure composed of a highly thermally conductive material, such as a metal, among others. Alternatively, the thermal-conduction interface **148** may simply be a surface of the thermoelectric device **120** that physically contacts the battery **108**. Fundamentally, there is no limitation on the physical embodiments of the thermal-conduction interface **148** other than it enables the transfer of heat between the battery **108** and the thermoelectric device **120** by thermal conduction to an extent that allows the proper cooling and/or heating of the battery contemplated by a battery-charging device of the present disclosure, such as the battery-charging device **100** of FIG. 1.

[0025] In some embodiments, the thermal-management system **116** also includes a heat sink/source

**152** thermally conductively coupled to the thermoelectric device **120**. The “sink/source” designation is intended to denote that the heat sink/source **152** functions as a heat sink or a heat source depending on the manner in which the control system **128** is controlling the operation of the thermoelectric device **120**. That is, if the control system **128** is causing the thermal-management system **116** to remove heat from the battery **108**, then the heat sink/source **152** functions as a heat sink to remove heat from the thermoelectric device **120**. Conversely, if the control system **128** is causing the thermal-management system **116** to provide heat to the battery **108**, then the heat sink/source **152** functions as a heat source to provide heat to the thermoelectric device **120**. It is noted that any use of the designation “heat sink/source” herein or in the appended claims does not necessarily mean that the heat sink/source has to function as both a heat sink and a heat source. For example, some embodiments of a battery-charging device of the present disclosure may not include a battery-warming function and so many never utilize the heat sink/source as a heat source. In such an embodiment, the term “heat sink/source” shall be taken to mean only “heat sink”.

[0026] As with the thermal-conduction interface **148** when the thermal-conduction interface is a distinct physical structure, the heat sink/source **152** may be made of any one or more suitable thermally conductive materials, such as one or more metals, among others. In some embodiments, the heat sink/source **152** may include one or more types of features, such as fins, vanes, ridges, louvers, channels, passageways, etc., and any combination thereof, to increase the surface area exposed to the environment surrounding the heat sink/source to increase the heat-transfer efficiency of the heat sink/source as between the heat sink/source and the surrounding environment.

[0027] In this connection, in some embodiments the thermal-management system **116** may optionally include one or more fans **156(1)** and/or **156(2)** for moving ambient air (as indicated by arrows **160**) across the heat sink/source **152** to increase the efficiency of heat transfer between the heat sink/source and the ambient air. Each of the one or more fans (here, fans **156(1)** and **156(2)**) may be located at any suitable location for moving the ambient air **160** across the heat sink/source **152**. Although not illustrated in FIG. 1, each fan **156(1)** and **156(2)** provided may be controlled by the control system **128**, for example, as a function of the temperature(s) of the first and/or second sides **120S(1)** and **120S(2)** of the thermoelectric device **120** and/or of the ambient air surrounding the battery-charging device **100** and/or the amount of heat needed to be removed from or added to the battery **108** and/or the thermoelectric device at any particular time.

[0028] In some embodiments, the battery-charging device **100** may be contained in an optional housing **164**. If one or more fans, such as one or both of the fans **156(1)** and **156(2)**, are provided, the thermal-management system **116** may further include an air passageway **168** for directing the ambient air **160** through the housing **164** and into contact with the heat sink/source **152**. In some embodiments the air passageway **168** may include dedicated ducting, while in other embodiments the air passageway may be defined by other structures within the housing **164**, such as one or more circuit boards (not shown), or one or more internal support structures, such as a battery support structure **172**, or an interior surface of the housing, among other things.

[0029] As discussed above, the control system **128** can control the temperature of the battery **108** during charging operations. Consequently, the control system **128** must know the temperature of the battery **108**. This may be accomplished in any one or more of manners. For example, if the battery **108** has one or more integrated temperature sensors (not shown), it may have a data port **108P** for providing temperature data to the charging system **112** and/or to the control system **128**. As another example, the battery-charging device **100** may have one or more integrated sensors, such as integrated temperature sensors **176(1)** and **176(2)**, which may each be of any suitable type, such as a contact-type sensor or a standoff-type sensor. In the examples shown, the temperature sensor **176(1)** is a standoff-type sensor, such as an infrared sensor, and the temperature sensor **176(2)** is a contact-type sensor, such as a thermocouple.

[0030] In some embodiments in which the battery-charging device **100** includes the housing **164**, the charging region **104** may be provided as a compartment within the housing, and, if provided,

the compartment may include a suitable closure (not shown) that seals the compartment from the ambient environment. It is noted that while FIG. 1 illustrates the battery-charging device **100** as being designed for charging only a single battery **108** at a time, in other embodiments the battery-charging device may be modified to accommodate charging two or more batteries. For example, such a modified battery-charging device may include multiple charging regions like charging region **104**, each designed and configured to receive a corresponding battery for charging. In this connection, the charging system **112** may be modified to accommodate the charging of as many batteries as the modified battery-charging device is designed to hold. In such multiple-battery embodiments, multiple independently operated thermoelectric devices, each the same as or similar to the thermoelectric device **120** of FIG. 1, may be provided and controlled collectively by the thermal-management-system electronics **124** or controlled independently by separate thermal-management-system electronics (not shown), which may all be controlled by the control system **128** for the entire battery-charging device.

#### DETAILED EXAMPLES

[0031] FIGS. 2 through 5 illustrate an example battery-charging device **200** that is designed and configured to charge two battery packs, or simply batteries, **204(1)** and **204(2)** in corresponding respective separate charging compartments **208(1)** and **208(2)**. In this example and as best seen in FIGS. 2 and 3, the battery-charging device **200** includes a housing **212** having end walls **212E(1)** and **212E(2)** and an upper central portion **212CP** extending between the end walls. A charging-compartment pan **216** and a central dividing structure **220** are located inside an upper portion of the housing **212**. A pair of compartment closures **212C(1)** and **212C(2)** are hingedly attached to the central dividing structure **220**.

[0032] A pair of thermal-management components **224(1)** and **224(2)** extends between, and is supported by, the end wall **212E(1)** and **212E(2)**. The charging-compartment pan **216** includes a pair of openings **2160(1)** and **2160(2)** that receive therethrough corresponding parts of the thermal-management components **224(1)** and **224(2)**, namely, portions of first and second thermoelectric devices **228(1)** and **228(2)** and corresponding first and second thermal-conduction interfaces **232(1)** and **232(2)**. Each of the compartment closures **212C(1)** and **212C(2)**, corresponding one of the thermal-conduction interfaces **232(1)** and **232(2)**, corresponding faces of the central dividing structure **220**, and corresponding faces of the charging-compartment pan **216** define the corresponding charging compartment **208(1)**, **208(2)**, each of which comprises a corresponding charging region (not labeled) that is similar to the charging region **104** of FIG. 1.

[0033] As best seen in FIG. 3, the housing **212** includes a base **212B**, which contains various electronics **236** for assisting with making the battery-charging device **200** operational. As also seen in FIG. 3, the central dividing structure **220** also includes electronics **240** for assisting with making the battery-charging device **200** operational. Without going into detail, the electronics **236** and **240** includes electronics for a charging system, such as the charging system **112** of FIG. 1, thermal-management-system electronics, such as the thermal-management-system electronics **124** of FIG. 1, and a control system, such as the control system **128** of FIG. 1, and any other necessary electronics, such as one or more power supplies, among others.

[0034] FIG. 4 shows each of the example batteries **204(1)** and **204(2)** (identified in FIGS. 4 and 5 as “battery **204**” in the singular for simplicity) operatively engaged with the corresponding one of the thermal-management components **224(1)** and **224(2)** (identified in FIGS. 4 and 5 as “thermal-management component **224**” in the singular for simplicity). As seen in FIG. 4, the thermal-management component **224** includes a support structure **224S** that supports, among other things, the thermoelectric device **228** (**228(1)** and **228(2)** in FIG. 3) and the battery **204** when it is engaged with the thermal-management component. In this embodiment, the support structure **224S** defines an air duct **400** that flows air (represented by arrows **404**) in contact with a heat sink/source **408** that is thermally coupled to the thermoelectric device **228**. The air duct **400** includes an inlet end **400I** that is enlarged to accommodate the physical size of fans (not shown) that draw ambient air



from outside the battery-charging device **200** (FIGS. 2 and 3). In this connection and referring back to FIGS. 2 and 3, each of these figures shows two pairs of openings **2120** in the housing end wall **212E(2)** over which corresponding pairs of fans (not shown) are mounted to force ambient air into the inlet end **400I** of the air duct **400** of each of the thermal-management components **224(1)** and **224(2)**.

[0035] Referring again to FIG. 4, and also to FIG. 5, in this example, the thermoelectric device **228** is composed of a plurality of thermoelectric-device segments **228S** each in thermal contact with the thermal-conduction interface **232** and the heat sink/source **408** on the opposite side of the dissimilar-material junction (not shown, but see junction **120J** of FIG. 1) of that thermoelectric-device segment. Adjacent ones of the thermoelectric-device segments **228S** are separated by insulation **412** that provides both thermal and electrical insulation. In the example shown, each of the thermoelectric-device segments **228S** is in the form of a strip that extends lengthwise in a direction into and out of the pages containing FIGS. 4 and 5. However, in other embodiments, some of the thermoelectric-device segments **228S** may be in the form of islands surrounded on all sides by insulation **412**. In yet other embodiments, the individual thermoelectric-device segments **228S** may be replaced by a single continuous thermoelectric device.

[0036] As best seen in FIG. 5, in this example the heat sink/source **408** consists of a flat plate. However, in other embodiments, the heat sink/source **408** may include other structures, such as fins **408F**, for increasing the surface area that the flow of air **404** through the air duct **400** contacts. FIG. 5 also illustrates some details of the battery **204**. As noted above, in this example the battery **204** is a battery pack, and it is composed of a plurality of individual cells **204I** (only a few labeled to avoid cluttering the figure) that are electrically connected to one another in electrical series and/or in electrical parallel to form the core **204C** of the battery and so as to provide the battery pack with its design output current and voltage.

[0037] In the embodiment shown, due to its construction, the battery **204** needs to be engaged with the thermal-conduction interface **232** in a specific orientation so as to maximize the effectiveness of the thermal management of the battery during charging operations by maximizing the thermal conductance of heat between the battery core **204C** and the thermal-conduction interface **232**. In this example, the battery **204** has an exterior housing **204H** having a bottom wall **204B** (relative to FIG. 5), which is the wall of the battery that is designed to contact the thermal-conduction interface **232** of the thermal-management component **224**. As can be seen in FIG. 5, the battery core **204C** is located proximate to the bottom wall **204B** and is secured to the bottom wall using a thermally conductive adhesive **204A** so as to provide a continuous thermal pathway from the battery core to the bottom wall.

[0038] Various modifications and additions can be made without departing from the spirit and scope of this invention. Features of each of the various embodiments described above may be combined with features of other described embodiments as appropriate in order to provide a multiplicity of feature combinations in associated new embodiments. Furthermore, while the foregoing describes a number of separate embodiments, what has been described herein is merely illustrative of the application of the principles of the present invention. Additionally, although particular methods herein may be illustrated and/or described as being performed in a specific order, the ordering is highly variable within ordinary skill to achieve aspects of the present disclosure. Accordingly, this description is meant to be taken only by way of example, and not to otherwise limit the scope of this invention.

[0039] Exemplary embodiments have been disclosed above and illustrated in the accompanying drawings. It will be understood by those skilled in the art that various changes, omissions and additions may be made to that which is specifically disclosed herein without departing from the spirit and scope of the present invention.

## Claims

1. A battery-charging device for charging a secondary battery that includes electrical terminals and a heat-transfer face, the battery-charging device comprising: a charging region that receives the secondary battery during a charging operations; a charging system that, when the secondary battery is present in the charging region, electrically connects to the electrical terminals of the secondary battery and charges the secondary battery during the charging operations; a thermal-management system that includes: a thermal-conduction interface that contactingly receives the heat-transfer face of the secondary battery when the battery is located in the charging region so that heat can be conducted between the secondary battery and the thermal management system during the charging operations; a heat sink/source; and a thermoelectric device thermally coupled between the thermal-conduction interface and the heat sink/source, wherein during the charging operations with the secondary battery located in the charging region, the thermoelectric device transfers heat between the secondary battery and the heat sink/source.
2. The battery-charging device of claim 1, wherein the thermal-conduction interface comprises a thermally conductive contact plate having battery-contacting surface that contacts the heat-transfer face of the secondary battery when the secondary battery is located in the charging region for the charging operations.
3. The battery-charging device of claim 2, comprising a plurality of thermoelectric devices thermally coupled between the thermally conductive contact plate and the heat sink/source.
4. The battery-charging device of claim 3, wherein the thermoelectric devices are spaced apart from one another and thermal insulation is contained in spaces between adjacent ones of the thermoelectric devices.
5. The battery-charging device of claim 1, further comprising an ambient-air heat-transfer system that includes a passageway for providing a flow of ambient air from outside of the battery-charging device to the heat sink/source so as to transfer heat between the flow and the heat sink/source.
6. The battery-charging device of claim 5, wherein the ambient-air heat-transfer system includes a fan for providing the flow of ambient air within the passageway.
7. The battery-charging device of claim 5, wherein the passageway includes an inlet for receiving the ambient air from outside the battery-charging device and an outlet for exhausting the flow of ambient air within the passageway to outside the battery-charging device.
8. The battery-charging device of claim 1, further comprising a control system configured to cause the thermoelectrical device to provide heat to the secondary battery when the secondary battery is at a measured temperature lower than a preset minimum charging temperature.
9. The battery-charging device of claim 8, wherein the control system is further configured to cause the charging system to begin charging once the measured temperature reaches the minimum charging temperature.
10. The battery-charging device of claim 9, wherein the control system is further configured to cause the thermoelectric device to remove heat from the secondary battery when the measured temperature of the secondary battery reaches a preset cooling temperature.
11. The battery-charging device of claim 10, further comprising an ambient-air heat-transfer system that includes: a passageway for providing a flow of ambient air from outside of the battery-charging device to the heat sink/source so as to transfer heat between the flow and the heat sink/source; and a fan for providing the flow of ambient air within the passageway; wherein the control system is further configured to activate the fan in conjunction with causing the thermoelectric device to remove heat from the secondary battery.
12. The battery-charging device of claim 8, further comprising an ambient-air heat-transfer system that includes: a passageway for providing a flow of ambient air from outside of the battery-charging device to the heat sink/source so as to transfer heat between the flow and the heat

sink/source; and a fan for providing the flow of ambient air within the passageway; wherein the control system is further configured to activate the fan in conjunction with causing the thermoelectric device to provide heat to the secondary battery.

**13.** The battery-charging device of claim 1, further comprising a control system configured to cause the thermoelectrical device to remove heat from the secondary battery when the secondary battery is at a measured temperature higher than a preset cooling temperature.

**14.** The battery-charging device of claim 13, further comprising an ambient-air heat-transfer system that includes: a passageway for providing a flow of ambient air from outside of the battery-charging device to the heat sink/source so as to transfer heat between the flow and the heat sink/source; and a fan for providing the flow of ambient air within the passageway; wherein the control system is further configured to activate the fan in conjunction with causing the thermoelectric device to remove heat from the secondary battery.

**15.** A method of charging a secondary battery, the method comprising: causing a battery-charging device to perform charging operations upon the secondary battery; and during the charging operations, causing a thermoelectric device, that is directly thermally coupled to the secondary battery, to transfer heat between the secondary battery and a heat sink/source by thermal conduction.

**16.** The method of claim 15, wherein the charging operation includes electrically charging the secondary battery, and the causing of the thermoelectric device to transfer heat between the secondary battery and the heat sink/source includes removing heat from the secondary battery by thermal conduction.

**17.** The method of claim 16, further comprising measuring a temperature of the secondary battery, and, when the temperature of the secondary battery exceeds a preset cooling temperature, executing the causing of the thermoelectric device to remove heat from the secondary battery.

**18.** The method of claim 16, further comprising causing a fan to flow ambient air across the heat sink/source so as to remove heat from the heat sink/source.

**19.** The method of claim 16, further comprising, prior to electrically charging the secondary battery, causing the thermoelectric device to provide heat to the secondary battery.

**20.** The method of claim 19, further comprising measuring a temperature of the secondary battery, and, when the temperature of the secondary battery is below a preset minimum charging temperature, executing the causing of the thermoelectric device to provide heat to the secondary battery.

**21.** The method of claim 20, further comprising causing a fan to flow ambient air across the heat sink/source so as to provide heat to the heat sink/source.

---