

# US Patent & Trademark Office

## Patent Public Search | Text View

United States Patent Application Publication

20250265986

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

Lin; Chin-Wei et al.

### Electronic Devices With Low Refresh Rate Display Pixels

#### Abstract

A display may have an array of organic light-emitting diode display pixels operating at a low refresh rate. Each display pixel may have six thin-film transistors and one capacitor. One of the six transistors may serve as the drive transistor and may be compensated using the remaining five transistors and the capacitor. One or more on-bias stress operations may be applied before threshold voltage sampling to mitigate first frame dimming. Multiple anode reset and on-bias stress operations may be inserted during vertical blanking periods to reduce flicker and maintain balance and may also be inserted between successive data refreshes to improve first frame performance. Two different emission signals controlling each pixel may be toggled together using a pulse width modulation scheme to help provide darker black levels.

**Inventors:** Lin; Chin-Wei (San Jose, CA), Yang; Shyuan (San Jose, CA), Qian; Chuang (Santa Clara, CA), Jamshidi Roudbari; Abbas (Saratoga, CA), Chang; Ting-Kuo (San Jose, CA)

**Applicant:** Apple Inc. (Cupertino, CA)

**Family ID:** 1000008578135

**Appl. No.:** 19/200516

**Filed:** May 06, 2025

#### Related U.S. Application Data

parent US continuation 18483282 20231009 parent-grant-document US 12322330 child US 19200516

parent US continuation 17576619 20220114 parent-grant-document US 11823621 child US 18483282

parent US continuation 17080685 20201026 parent-grant-document US 11257426 child US 17576619

parent US continuation 16696578 20191126 parent-grant-document US 10854139 child US 17080685

parent US continuation 16379323 20190409 parent-grant-document US 10741121 child US 16696578  
parent US division 15996366 20180601 parent-grant-document US 10304378 child US 16379323  
us-provisional-application US 62547030 20170817

---

## Publication Classification

**Int. Cl.:** G09G3/3225 (20160101); G09G3/3233 (20160101)

**U.S. Cl.:**

CPC G09G3/3225 (20130101); G09G3/3233 (20130101); G09G2300/0417 (20130101); G09G2300/043 (20130101); G09G2300/0819 (20130101); G09G2300/0861 (20130101); G09G2310/0262 (20130101); G09G2310/0297 (20130101); G09G2310/06 (20130101); G09G2310/061 (20130101); G09G2320/0214 (20130101); G09G2320/0242 (20130101); G09G2320/0247 (20130101); G09G2320/0252 (20130101); G09G2320/043 (20130101); G09G2320/045 (20130101); G09G2320/064 (20130101); G09G2340/0435 (20130101)

---

## Background/Summary

[0001] This application is a continuation of patent application Ser. No. 18/483,282, filed Oct. 9, 2023, which is a continuation of patent application Ser. No. 17/576,619, filed Jan. 14, 2022, now U.S. Pat. No. 11,823,621, which is a continuation of patent application Ser. No. 17/080,685, filed Oct. 26, 2020, now U.S. Pat. No. 11,257,426, which is a continuation of patent application Ser. No. 16/696,578, filed Nov. 26, 2019, now U.S. Pat. No. 10,854,139, which is a continuation of patent application Ser. No. 16/379,323, filed Apr. 9, 2019, now U.S. Pat. No. 10,741,121, which is a division of application Ser. No. 15/996,366, filed Jun. 1, 2018, now U.S. Pat. No. 10,304,378, which claims the benefit of provisional patent application No. 62/547,030, filed Aug. 17, 2017, which are hereby incorporated by reference herein in their entireties.

### FIELD

[0002] This relates generally to electronic devices and, more particularly, to electronic devices with displays.

### BACKGROUND

[0003] Electronic devices often include displays. For example, cellular telephones and portable computers include displays for presenting information to users.

[0004] Displays such as organic light-emitting diode displays have an array of display pixels based on light-emitting diodes. In this type of display, each display pixel includes a light-emitting diode and thin-film transistors for controlling application of a signal to the light-emitting diode to produce light.

[0005] Threshold voltage variations in the thin-film transistors can cause undesired visible display artifacts. For example, threshold voltage hysteresis can cause white pixels to be displayed differently depending on context. The white pixels in a frame may, as an example, be displayed accurately if they were preceded by a frame of white pixels, but may be displayed inaccurately (i.e., they may have a gray appearance) if they were preceded by a frame of black pixels. This type of history-dependent behavior of the light output of the display pixels in a display causes the display to exhibit a low response time. To address the issues associated with threshold voltage variations, displays such as organic light-emitting diode displays are provided with threshold voltage compensation circuitry. Such circuitry may not, however, adequately address all threshold voltage

variations, may not satisfactorily improve response times, and may have a design that is difficult to implement.

## SUMMARY

[0006] An electronic device may include a display having an array of display pixels. The display pixels may be organic light-emitting diode display pixels. Each display pixel may include a light-emitting diode, a power supply line, a data line, an initialization line, a first transistor with a drain terminal coupled to the data line and a source terminal, a second transistor with a source terminal coupled to the source terminal of the first transistor, a drain terminal, and a gate terminal, a third transistor coupled between the drain and gate terminals of the second transistor, a fourth transistor coupled between the power supply line and the second transistor, a fifth transistor coupled between the second transistor and light-emitting diode, a sixth transistor coupled between the initialization line and the light-emitting diode, and a storage capacitor coupled in series between the third transistor and the sixth transistor.

[0007] The third transistor has a gate terminal that receives a first scan signal. The sixth transistor has a gate terminal that receives the first scan signal. The first transistor has a gate terminal that receives a second scan signal that is different than the first scan signal. The fifth transistor has a gate terminal that receives a first emission signal. The fourth transistor has a gate terminal that receives a second emission signal that is different than the first emission signal.

[0008] The display pixel may be refreshed using a four-phase refresh scheme, which includes an initialization phase during which only the first scan signal and the second emission signal are asserted, an on-bias stress phase during which only the second scan signal is asserted, a threshold voltage sampling and data writing phase during which only the first and second scan signals are asserted, and an emission phase during which only the first and second emission signals are asserted. Performing the on-bias stress phase before the threshold voltage sampling and data writing phase can help mitigate threshold voltage hysteresis of the second transistor, which prevents first frame dimming (e.g., prevents noticeable luminance dimming when the pixel is transitioning from displaying a black level to a white level).

[0009] This type of display pixel may also be suitable for operating in low refresh rate (e.g., 1 Hz, 2 Hz, etc.) in which the vertical blanking period is at least ten times longer than the data refresh period. Multiple anode reset operations may be inserted during the vertical blanking period to help reduce flicker. Additional on-bias stress operations may be performed along with the anode reset operations during the vertical blanking period to help balance the transistor stressing. Multiple data refreshes and multiple anode resets (with on-bias stress) may be applied when the display pixel is transitioning from black to white (or from one gray level to another) to help provide faster threshold voltage settling and improved first frame performance. The first and second emission control signals may also be toggled at the same time using a pulse width modulation (PWM) scheme to control the luminance of the display while reducing leakage.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

[0010] FIG. 1 is a diagram of an illustrative display such as an organic light-emitting diode display having an array of organic light-emitting diode display pixels in accordance with an embodiment.

[0011] FIG. 2 is a circuit diagram of an illustrative display driver circuitry in accordance with an embodiment.

[0012] FIG. 3 is a diagram of a low refresh rate display driving scheme in accordance with an embodiment.

[0013] FIG. 4 is a circuit diagram of an illustrative organic light-emitting diode display pixel in accordance with an embodiment.

[0014] FIG. 5 is a timing diagram showing how on-bias stress may be applied before threshold voltage sampling in accordance with an embodiment.

[0015] FIGS. 6A-6D are diagrams showing the configuration of the display pixel of FIG. 4 during the four different phases shown in FIG. 5 in accordance with an embodiment.

[0016] FIG. 7 is a diagram illustrating a thin-film transistor hysteresis effect that causes first frame dimming in accordance with an embodiment.

[0017] FIG. 8A is a timing diagram showing how one or more anode reset operations can be performed during the extended blanking period in accordance with an embodiment.

[0018] FIG. 8B is a timing diagram showing the behavior of relevant signals during the anode reset operations shown in FIG. 8A in accordance with an embodiment.

[0019] FIGS. 9A and 9B are diagrams showing the configuration of the display pixel of FIG. 4 during the two different phases shown in FIG. 8B in accordance with an embodiment.

[0020] FIG. 10 is a timing diagram showing how on-bias stress may be applied before anode reset during the extended blanking period in accordance with an embodiment.

[0021] FIGS. 11A-11D are diagrams showing the configuration of the display pixel of FIG. 4 during the different phases shown in FIG. 10 in accordance with an embodiment.

[0022] FIG. 12 is a diagram illustrating how multiple anode reset and on-bias stress operations can be inserted during multi-refresh driving schemes to help reduce first frame dimming in accordance with an embodiment.

[0023] FIG. 13 is a timing diagram illustrating how first and second emission signals may be simultaneously toggled to help mitigate poor gray tracking issues during the data refresh phase in accordance with an embodiment.

[0024] FIG. 14 is a timing diagram illustrating how first and second emission signals may have different duty cycles only during a first PWM (pulse width modulation) period of the anode reset phase to help minimize leakage in accordance with an embodiment.

#### DETAILED DESCRIPTION

[0025] A display in an electronic device may be provided with driver circuitry for displaying images on an array of display pixels. An illustrative display is shown in FIG. 1. As shown in FIG. 1, display 14 may have one or more layers such as substrate 24. Layers such as substrate 24 may be formed from planar rectangular layers of material such as planar glass layers. Display 14 may have an array of display pixels 22 for displaying images for a user. The array of display pixels 22 may be formed from rows and columns of display pixel structures on substrate 24. These structures may include thin-film transistors such as polysilicon thin-film transistors, semiconducting oxide thin-film transistors, etc. There may be any suitable number of rows and columns in the array of display pixels 22 (e.g., ten or more, one hundred or more, or one thousand or more).

[0026] Display driver circuitry such as display driver integrated circuit 16 may be coupled to conductive paths such as metal traces on substrate 24 using solder or conductive adhesive. Display driver integrated circuit 16 (sometimes referred to as a timing controller chip) may contain communications circuitry for communicating with system control circuitry over path 25. Path 25 may be formed from traces on a flexible printed circuit or other cable. The system control circuitry may be located on a main logic board in an electronic device such as a cellular telephone, computer, television, set-top box, media player, portable electronic device, or other electronic equipment in which display 14 is being used. During operation, the system control circuitry may supply display driver integrated circuit 16 with information on images to be displayed on display 14 via path 25. To display the images on display pixels 22, display driver integrated circuit 16 may supply clock signals and other control signals to display driver circuitry such as row driver circuitry 18 and column driver circuitry 20. Row driver circuitry 18 and/or column driver circuitry 20 may be formed from one or more integrated circuits and/or one or more thin-film transistor circuits on substrate 24.

[0027] Row driver circuitry 18 may be located on the left and right edges of display 14, on only a

single edge of display **14**, or elsewhere in display **14**. During operation, row driver circuitry **18** may provide row control signals on horizontal lines **28** (sometimes referred to as row lines or “scan” lines). Row driver circuitry **18** may therefore sometimes be referred to as scan line driver circuitry. Row driver circuitry **18** may also be used to provide other row control signals, if desired.

[0028] Column driver circuitry **20** may be used to provide data signals D from display driver integrated circuit **16** onto a plurality of corresponding vertical lines **26**. Column driver circuitry **20** may sometimes be referred to as data line driver circuitry or source driver circuitry. Vertical lines **26** are sometimes referred to as data lines. During compensation operations, column driver circuitry **20** may use paths such as vertical lines **26** to supply a reference voltage. During programming operations, display data is loaded into display pixels **22** using lines **26**.

[0029] Each data line **26** is associated with a respective column of display pixels **22**. Sets of horizontal signal lines **28** run horizontally through display **14**. Power supply paths and other lines may also supply signals to pixels **22**. Each set of horizontal signal lines **28** is associated with a respective row of display pixels **22**. The number of horizontal signal lines in each row may be determined by the number of transistors in the display pixels **22** that are being controlled independently by the horizontal signal lines. Display pixels of different configurations may be operated by different numbers of control lines, data lines, power supply lines, etc.

[0030] Row driver circuitry **18** may assert control signals on the row lines **28** in display **14**. For example, driver circuitry **18** may receive clock signals and other control signals from display driver integrated circuit **16** and may, in response to the received signals, assert control signals in each row of display pixels **22**. Rows of display pixels **22** may be processed in sequence, with processing for each frame of image data starting at the top of the array of display pixels and ending at the bottom of the array (as an example). While the scan lines in a row are being asserted, the control signals and data signals that are provided to column driver circuitry **20** by circuitry **16** direct circuitry **20** to demultiplex and drive associated data signals D onto data lines **26** so that the display pixels in the row will be programmed with the display data appearing on the data lines D. The display pixels can then display the loaded display data.

[0031] Column driver circuitry **20** may output data line signals that contain grayscale information for multiple color channels, such as red, green, and blue channels (see, e.g., FIG. 2).

Demultiplexing circuitry **54** may demultiplex this data line signal into respective R, G, and B data line signals on respective data lines **48**. As shown in the example of FIG. 2, a display demultiplexer control circuit such as display demultiplexer control circuit **58** in column circuitry **20** may be used to supply data line demultiplexer control signals R, G, and B (corresponding to red, green, and blue channels in this example) to the gate terminals of demultiplexing transistors **60**. Data line drivers **62** may produce data line output signals SO1, SO2, . . . (sometimes referred to as source output signals) on data line paths **64**. The source output signals contain analog pixel data for image pixels of all three colors (i.e., red, blue, and green). The control signals that are applied to the gates of demultiplexing transistors **60** turn transistors **60** on and off in a pattern that routes red channel information from the source output signals to red data lines RDL, that routes green channel information from the source output signals to green data lines GDL, and that routes blue channel information from the source output signals to blue data lines BDL.

[0032] Optional loading circuits **66** may be implemented using one or more discrete components (e.g., capacitors, inductors, and resistors) that are interposed within lines **54** or may be implemented in a distributed fashion using some or all of the structures that form lines **54**. Optional loading circuits **66** and/or circuitry in column driver circuitry **20** (e.g., circuit **58**) may be used to control the shape of the demultiplexing control signals R, G, and B. Signal shaping techniques such as these may be used to smooth display control signal pulses such as the demultiplexer control signal pulses and thereby reduce harmonic signal production and radio-frequency interference.

[0033] In an organic light-emitting diode display such as display **14**, each display pixel contains a respective organic light-emitting diode for emitting light. A drive transistor controls the amount of

light output from the organic light-emitting diode. Control circuitry in the display pixel is configured to perform threshold voltage compensation operations so that the strength of the output signal from the organic light-emitting diode is proportional to the size of the data signal loaded into the display pixel while being independent of the threshold voltage of the drive transistor.

[0034] Display **14** may be configured to support low refresh rate operation. Operating display **14** using a relatively low refresh rate (e.g., a refresh rate of 1 Hz, 2 Hz, or other suitably low rate) may be suitable for applications outputting content that is static or nearly static and/or for applications that require minimal power consumption. FIG. **3** is a diagram of a low refresh rate display driving scheme in accordance with an embodiment. As shown in FIG. **3**, display **14** may alternate between a short data refresh phase (as indicated by period  $T_{\text{refresh}}$ ) and an extended vertical blanking phase (as indicated by period  $T_{\text{blank}}$ ). As an example, each data refresh period  $T_{\text{refresh}}$  may be approximately 16.67 milliseconds (ms) in accordance with a 60 Hz data refresh operation, whereas each vertical blanking period  $T_{\text{blank}}$  may be approximately 1 second so that the overall refresh rate of display **14** is lowered to 1 Hz. Configured as such,  $T_{\text{blank}}$  can be adjusted to tune the overall refresh rate of display **14**. For example, if the duration of  $T_{\text{blank}}$  was tuned to half a second, the overall refresh rate would be increased to approximately 2 Hz. In the embodiments described herein,  $T_{\text{blank}}$  may be at least two times, at least ten times, at least 30 times, or at least 60 times longer in duration than  $T_{\text{refresh}}$  (as examples).

[0035] A schematic diagram of an illustrative organic light-emitting diode display pixel **22** in display **14** that can be used to support low refresh rate operation is shown in FIG. **4**. As shown in FIG. **4**, display pixel **22** may include a storage capacitor  $C_{\text{st}}$  and transistors such as n-type (i.e., n-channel) transistors **T1**, **T2**, **T3**, **T4**, **T5**, and **T6**. The transistors of pixel **22** may be thin-film transistors formed from a semiconductor such as silicon (e.g., polysilicon deposited using a low temperature process, sometimes referred to as LTPS or low-temperature polysilicon), semiconducting oxide (e.g., indium gallium zinc oxide (IGZO)), etc.

[0036] In one suitable arrangement, transistor **T3** may be implemented as a semiconducting-oxide transistor while remaining transistors **T1**, **T2**, and **T4-T6** are silicon transistors. Semiconducting-oxide transistors exhibit relatively lower leakage than silicon transistors, so implementing transistor **T3** as a semiconducting-oxide transistor will help reduce flicker at low refresh rates (e.g., by preventing current from leakage through **T3**).

[0037] In another suitable arrangement, transistors **T3** and **T6** may be implemented as semiconducting-oxide transistors while remaining transistors **T1**, **T2**, **T4**, and **T5** are silicon transistors. Since both transistors **T3** and **T6** are controlled by signal **Scan1**, forming them as the same transistor type can help simplify fabrication.

[0038] In yet another suitable arrangement, transistors **T3**, **T6**, and also **T2** may be implemented as semiconducting-oxide transistors while remaining transistors **T1**, **T4**, and **T5** are silicon transistors. Transistor **T2** serves as the drive transistor and has a threshold voltage that is critical to the emission current of pixel **22**. As described below in connection with at least FIG. **7**, the threshold voltage of the drive transistor may experience hysteresis. Thus, forming the drive transistor as a top-gate semiconducting-oxide transistor can help reduce the hysteresis (e.g., a top-gate IGZO transistor experiences less  $V_{\text{th}}$  hysteresis than a silicon transistor). If desired, all of transistors **T1-T6** may be semiconducting-oxide transistors. Moreover, any one or more of transistors **T1-T6** may be p-type (i.e., p-channel) thin-film transistors.

[0039] Display pixel **22** may include light-emitting diode **304**. A positive power supply voltage  $V_{\text{DEL}}$  may be supplied to positive power supply terminal **300** and a ground power supply voltage  $V_{\text{SEL}}$  (e.g., 0 volts or other suitable voltage) may be supplied to ground power supply terminal **302**. The state of drive transistor **T2** controls the amount of current flowing from terminal **300** to terminal **302** through diode **304**, and therefore the amount of emitted light **306** from display pixel **22**. Diode **304** may have an associated parasitic capacitance  $C_{\text{sub.OLED}}$  (not shown).

[0040] Terminal **308** is used to supply an initialization voltage  $V_{\text{ini}}$  (e.g., a negative voltage such as

-1 V or -2 V or other suitable voltage) to assist in turning off diode **304** when diode **304** is not in use. Control signals from display driver circuitry such as row driver circuitry **18** of FIG. **1** are supplied to control terminals such as terminals **312**, **313**, **314**, and **315**. Terminals **312** and **313** may serve respectively as first and second scan control terminals, whereas terminals **314** and **315** may serve respectively as first and second emission control terminals. Scan control signals Scan1 and Scan2 may be applied to scan terminals **312** and **313**, respectively. Emission control signals EM1 and EM2 may be supplied to terminals **314** and **315**, respectively. A data input terminal such as data signal terminal **310** is coupled to a respective data line **26** of FIG. **1** for receiving image data for display pixel **22**.

[0041] In the example of FIG. **4**, transistors T4, T2, T5, and diode **304** may be coupled in series between power supply terminals **300** and **302**. In particular, transistor T4 may have a drain terminal that is coupled to positive power supply terminal **300**, a gate terminal that receives emission control signal EM2, and a source terminal (labeled as Node1). The terms “source” and “drain” terminals of a transistor can sometimes be used interchangeably and may therefore be referred to herein as “source-drain” terminals. Drive transistor T2 may have a drain terminal that is coupled to Node1, a gate terminal (labeled as Node2), and a source terminal (labeled as Node3). Transistor T5 may have a drain terminal that is coupled to Node3, a gate terminal that receives emission control signal EM1, and a source terminal (labeled as Node4) that is coupled to ground power supply terminal **302** via diode **304**.

[0042] Transistor T3, capacitor Cst, and transistor T6 may be coupled in series between Node1 and power supply terminal **308**. Transistor T3 may have a drain terminal that is coupled to Node1, a gate terminal that receives scan control signal Scan1, and a source terminal that is coupled Node2. Storage capacitor Cst may have a first terminal that is coupled to Node2 and a second terminal that is coupled to Node4. Transistor T6 may have a drain terminal that is coupled to Node4, a gate terminal that receives scan control signal Scan1, and a source terminal that receives voltage Vini via terminal **308**. Transistor T1 may have a drain terminal that receives data line signal DL via terminal **310**, a gate terminal that receives scan control signal Scan2, and a source terminal that is coupled to Node3. Connected in this way, signal EM2 may be asserted to enable transistor T4; signal EM1 may be asserted to activate transistor T5; signal Scan2 may be asserted to turn on transistor T1; and signal Scan1 may be asserted to switch into use transistors T3 and T6.

[0043] During the data refresh period, display pixel **22** may be operated in at least four phases: (1) a reset/initialization phase, (2) an on-bias stress phase, (3) a threshold voltage sampling and data writing phase, and (4) an emission phase. FIG. **5** is a timing diagram showing relevant signal waveforms that may be applied to display pixel **22** during the four phases of the data refresh operation.

[0044] At time t1 (at the beginning of the initialization phase), signal Scan1 may be pulsed high and signal EM1 may be deasserted (e.g., driven low) while signal Scan2 is low and signal EM2 is high. FIG. **6A** illustrates the configuration of pixel **22** during this time. As shown in FIG. **6A**, only transistors T3, T4, and T6 are turned on (since signals Scan1 and EM2 are asserted), so the first terminal of capacitor Cst is charged to VDDEL and the second terminal of capacitor Cst is pulled down to Vini. During the initialization phase, the voltage across capacitor Cst is therefore reset to a predetermined voltage difference (VDDEL-Vini). Node3 may also be charged up to (VDDEL-Vth2), where Vth2 is the threshold voltage of transistor T2.

[0045] At time t2, signal Scan1 falls low, signal Scan2 is asserted (e.g., driven high), and signal EM2 is deasserted (e.g., driven low), which signifies the end of the initialization phase and the beginning of the on-bias stress phase. FIG. **6B** illustrates the configuration of pixel **22** during this time. As shown in FIG. **6B**, only transistors T1 and T2 are turned on (since signal Scan2 is high and Node2 is charged up during the initialization phase). Configured in this way, Node2 remains at VDDEL, and Node3 will be biased to Vdata using transistor T1. In other words, the gate-to-source voltage Vgs of transistor T2 will be set to (VDDEL-Vdata). Vdata is at least partially applied to

transistor T2 before any threshold voltage sampling.

[0046] At time t3, signal Scan1 pulses high, which signifies the end of the on-bias stress phase and the beginning of the threshold voltage Vth sampling and data writing phase. FIG. 6C illustrates the configuration of pixel 22 during this time. As shown in FIG. 6C, only transistors T1, T2, and T6 are turned on (since signals Scan1 and Scan2 are asserted). Configured in this way, Node1 and Node2 will be pulled from VDDEL down to (Vdata+Vth2) while Node3 is set to Vdata. In other words, the gate-to-source voltage Vgs of transistor T2 will be set to Vth2 (i.e., Vdata+Vth2-Vdata, where Vdata cancels out). The voltage across capacitor Cst is (Vdata+Vth2-Vini). At time t4, both Scan1 and Scan2 are deasserted, signifying the end of the threshold voltage and data writing phase.

[0047] At time t5, signals EM1 and EM2 are asserted to signify the beginning of the emission phase. FIG. 6D illustrates the configuration of pixel 22 during this time. As shown in FIG. 6D, transistors T2, T4, and T5 are turned on to allow an emission current 650 to flow through diode 304. The gate-to-source voltage Vgs of transistor T2 will be set by the voltage across storage capacitor Cst, which was previously set to (Vdata+Vth2-Vini) during the data writing phase. Since emission current 650 is proportion to Vgs minus Vth2, emission current 650 will be independent of Vth2 since Vth2 cancels out when subtracting Vth2 from (Vdata+Vth2-Vini).

[0048] In certain situations, threshold voltage Vth2 can shift, such as when display 14 is transitioning from a black image to a white image or when transitioning from one gray level to another. This shifting in Vth2 (sometimes referred to herein as thin-film transistor “hysteresis”) can cause a reduction in luminance, which is otherwise known as “first frame dimming.” The TFT hysteresis is illustrated in FIG. 7. As shown in FIG. 7, curve 700 represents the saturation current Ids waveform as a function of Vgs of transistor T2 for a black frame, whereas curve 704 represents the target Ids waveform as a function of Vgs of transistor T2 for a white frame. Without performing the on-bias stress, the sampled Vth' corresponds to the black frame and will therefore deviate from the target curve 702 by quite a large margin. By performing the on-bias stress, the sampled Vth" will correspond to Vdata and will therefore be much closer to the target curve 702 (see curve 702 realized by applying the on-bias stress). Performing the on-bias stress phase to bias the Vgs of transistor T2 with Vdata before sampling Vth2 can therefore help mitigate hysteresis and prevent first frame dimming.

[0049] Another issue that may arise when operating display 14 under low refresh rates is the emission current only being toggled during the data refresh periods. FIG. 8A shows display luminance as a function of time. As shown in FIG. 8, the luminance may experience dips 800 during data refresh periods T\_refresh. The luminance dips 800 are caused by sequentially shutting off and then turning on transistor T4, such as during the four phases shown in FIG. 5-6. Having luminance dips 800 at 1 Hz may result in noticeable flicker to the user.

[0050] In an effort to eliminate flicker, additional luminance dips 802 may be inserted during the vertical blanking period T\_blank. In the example of FIG. 8A, three additional dips 802 are inserted, which is merely illustrative. In general, at least 10 dips, at least 100 dips, or more than 100 dips may be produced during the extended blanking period T\_blank. By artificially and intentionally generating luminance dips at a higher frequency, the flickering is less noticeable to the human eye.

[0051] Dips 802 during the blanking period may be produced by alternating between an anode reset phase and the emission phase. FIG. 8B is a timing diagram showing the behavior of relevant signals during the anode reset phase and the emission phase. At time t1, signal Scan2 may be pulsed high and signal EM2 may be deasserted (e.g., EM2 may be driven low) while signal Scan1 remains low and signal EM1 remains high. FIG. 9A illustrates the configuration of pixel 22 during this time. As shown in FIG. 9A, transistors T1 and T5 are turned on (since signals Scan2 and EM1 are asserted), so Node4 (which is the anode of diode 304) will be reset to voltage Vp via transistor 900. The data signal may be parked or held at voltage Vp during the blanking interval. Voltage Vp may, for example, be at VSSEL, 2 V, or any data voltage level in between VSSEL and 2 V. Source driver 62 (see also FIG. 2) will be deactivated during this time. Transistor T4 is turned off so no



emission current can flow during the anode reset phase. At time t2, signal Scan2 is driven low, which marks the end of the anode reset phase.

[0052] At time t3, signal EM2 is asserted (e.g., EM2 is driven high), which reactivates transistor T4. FIG. 9B illustrates the configuration of pixel 22 during this time. As shown in FIG. 9B, transistors T4, T2, and T5 are all turned on, so emission current 950 will flow through diode 304. Emission current 950 will continue to flow until the next anode reset phase, which occurs at time t4. The period of time from t3 to t4 therefore delineates the emission phase. The diagram of FIG. 8B is not drawn to scale. In general, the emission phase may be longer than the anode reset phase. It is also possible for the emission phase to be shorter than the anode reset phase. The anode reset operation can be performed as frequently as necessary (e.g., to produce as many luminance dips 802 as desired during the vertical blanking period) to help reduce or minimize low refresh rate flicker.

[0053] Since on-bias stress is applied during the data refresh period, on-bias stress may also be applied during the vertical blanking period to help maintain balance in terms of biasing the pixel transistors. FIG. 10 is a timing diagram illustrating how an on-bias stress phase can be inserted before the anode reset phase during the vertical blanking period (e.g., FIG. 10 expands upon FIG. 9 by inserting an on-bias stress phase immediate before the anode reset phase). FIGS. 11A-11D illustrate the configuration of pixel 22 during the various phases of operation shown in FIG. 10. In particular, FIGS. 11A and 11D illustrate the emission phase, which is identical to the emission phase described in connection with FIGS. 6D and 9B, and therefore need not be iterated.

[0054] As shown in FIG. 10, signal EM1 may be deasserted prior to time t1, which prepares pixel 22 for the on-bias stress. At time t1, signal Scan2 is asserted and marks the beginning of the on-bias stress phase. FIG. 11B illustrates the configuration of pixel 22 during this time. As shown in FIG. 11B, only transistors T1 and T2 are turned on. Configured in this way, Node3 will be biased to Vdata using transistor T1.

[0055] At time t2, signal EM1 is asserted (e.g., EM1 is driven high) to turn on transistor T5, which marks the end of the on-bias stress phase and the beginning of the anode reset phase. FIG. 11C illustrates the configuration of pixel 22 during this time. As shown in FIG. 11C, transistors T1 and T5 are both on, so diode anode terminal Node4 is reset to Vdata. At time t3, signal Scan2 can be deasserted to mark the end of the anode reset phase. From time t4-t5, emission signals EM1 and EM2 are both high to allow the emission current to flow. In general, an on-bias stress phase may accompany and immediately precede any number of anode reset operations during the extended vertical blanking period to help replicate and mirror the on-bias stress throughout the operation of display 14.

[0056] In accordance with another suitable embodiment, multiple data refreshes and multiple anode reset operations may be performed when display 14 is transitioning from a black frame to a white frame (or in general, when display 14 is transitioning from one gray level to another). FIG. 12 is a diagram illustrating how multiple anode reset and on-bias stress operations can be inserted during multi-refresh driving schemes to help reduce first frame dimming. The top waveform shows how the threshold voltage of drive transistor T2 can change when transitioning from a black frame to a white frame. The bottom waveform shows how the luminance of display 14 can change as a result of performing multiple data refreshes and/or anode resets when transitioning from a black frame to a white frame.

[0057] In the example of FIG. 12, at least two data refreshes can be performed at 30 Hz (e.g., at time t1 and t3). At each of time t1 and t3, the four phases of FIGS. 5-6 can be carried out. Solid curves 1202 and 1206 illustrate the threshold voltage tracking and the luminance behavior, respectively, if only the two data refreshes are performed. Performing more than one data refresh enables enhanced Vth tracking and therefore a better luminance response that minimizes first frame dimming.

[0058] In addition to the multi-refresh operation, additional anode reset+on-bias stress operations

may be performed at 60 Hz (e.g., at time t1, t2, t3, t4, and t5). The anode reset rate may be greater than the multi-refresh rate. During each of these times (as indicated by “X” in FIG. 12), the on-bias stress and anode reset may be applied as shown in FIG. 10-11. Dotted curves 1204 and 1208 illustrate the threshold voltage tracking and the luminance behavior, respectively, if the 30 Hz data refreshes and 60 Hz anode reset+on-bias stress are performed. As shown by curve 1204, Vth tracking is further improved by the additional on-bias stress applied, which helps with faster Vth settling. As shown by curve 1208, the luminance at time t3 is closer to the target level, thereby providing better first frame performance.

[0059] The example of FIG. 12 in which the anode reset rate is twice the multi-refresh rate is merely illustrative. In another suitable arrangement, the anode reset rate can be three times the multi-refresh rate. Configured in this way, the frequency of on-bias stress is increased between each successive data refresh phase, which can provide even faster Vth settling and further improve first frame performance. In yet other suitable arrangements, the anode reset can be any integer multiple of the data refresh rate (e.g., at least four times greater, at least eight times greater, more than ten times, etc.).

[0060] Typically, during the emission phase, the brightness of display 14 can be adjusted via pulse width modulation (PWM). In conventional display driving schemes, signal EM2 is pulsed repeatedly and has a duty cycle that is adjustable to control the brightness while signal EM1 remains high without toggling. If signal EM1 remains high (which turns on transistor t5), it is possible for excess current to leak through transistor T5, which results in a poor black level. In order to mitigate this issue, signals EM1 and EM2 may be toggled simultaneously and in synchronization with one another.

[0061] FIG. 13 is a timing diagram illustrating how the EM1 and EM2 pulses 1300 can have the same duty cycle and are in-phase with each other. Deasserting EM1 at the same time as EM2 turns off transistor T5, thereby cutting off the leakage current path (e.g., there is not direct current path from Node1 to the diode when both EM1 and EM2 are low). The number of pulses and the pulse width can be tuned to output the desired luminance level of the display. Details of time period 1350 are shown in FIG. 5 and also FIG. 12 if multi-refresh schemes are supported.

[0062] The behavior of emission signals EM1 and EM2 may also be similar during the anode reset phases. During the anode reset phase, signal EM1 has to be asserted for a longer period of time (see, e.g., FIG. 8B). As shown in FIG. 13, signal EM1 may be high for substantially a quarter of the whole anode reset period (e.g., during the first PWM period). For the remaining three-quarters of the anode reset period, signals EM1 and EM2 may be toggled together.

[0063] Details of time period 1352 at the beginning of each anode reset period is shown in FIG. 14. As shown in FIG. 14, signals EM1 and EM2 are simultaneously asserted (e.g., EM1 and EM2 are driven high) at time t1. At time t2, signals EM1 and EM2 are simultaneously deasserted and signal Scan2 is pulsed high. During this time from t2 to t3, Vdata will be biased to a low voltage and both Node1 and Node3 will then be discharged via transistor T1 to the low voltage. This operation is similar to the on-bias stress operation described in connection with FIGS. 5-6. By discharging Node1 and Node3 through transistor T1, there is no more charge to leak from Node1 to the diode even if signal EM1 goes high afterwards (at time t3). The period between t2 and t3 is therefore sometimes referred to as the discharge time period T<sub>discharge</sub>. As described above, for the rest of the anode reset period, signals EM1 and EM2 have the same duty cycle, so there is no direct current path from Node1 to the diode either.

[0064] The various ways for operating display 14 described in connection with FIGS. 5-14 are not mutually exclusive and can be used in conjunction with one another in a single embodiment to help reduce flicker, improve first frame performance, and improve better black levels in for low-refresh-rate displays.

[0065] The foregoing is merely illustrative and various modifications can be made to the described

embodiments. The foregoing embodiments may be implemented individually or in any combination.

## Claims

1. A display pixel comprising: a light-emitting diode; a drive transistor coupled to the light-emitting diode; and a capacitor coupled between the drive transistor and the light-emitting diode.
2. The display pixel of claim 1, wherein the capacitor has a first terminal coupled to a gate terminal of the drive transistor and a second terminal coupled to an anode of the light-emitting diode.
3. The display pixel of claim 1, further comprising: a first emission transistor coupled between the drive transistor and the light-emitting diode.
4. The display pixel of claim 3, further comprising: a second emission transistor coupled between the drive transistor and a power supply line.
5. The display pixel of claim 3, further comprising: an initialization transistor coupled between an initialization line and a node disposed between the capacitor and the light-emitting diode.
6. The display pixel of claim 3, further comprising: a switching transistor coupled between a data line and a node disposed between the drive transistor and the first emission transistor.
7. The display pixel of claim 1, wherein the drive transistor comprises a silicon transistor, further comprising: a first semiconducting-oxide transistor directly coupled to the light-emitting diode.
8. The display pixel of claim 7, further comprising: a second semiconducting-oxide transistor directly coupled to the drive transistor.
9. The display pixel of claim 8, wherein: the first semiconducting-oxide transistor has a gate terminal configured to receive a scan signal; and the second semiconducting-oxide transistor has a gate terminal configured to receive the scan signal.
10. The display pixel of claim 8, wherein: the first semiconducting-oxide transistor is coupled to a first terminal of the capacitor; and the second semiconducting-oxide transistor is coupled to a second terminal of the capacitor.
11. A method of operating a display pixel having a drive transistor, a light-emitting diode, and a switching transistor, the method comprising: during an emission period, using the drive transistor to pass a drive current through the light-emitting diode; and during a blanking period, performing a reset operation by using the switching transistor to load a reset voltage into the display pixel.
12. The method of claim 11, further comprising: during a refresh operation, using the switching transistor to load a data signal into the display pixel.
13. The method of claim 11, further comprising: during the reset operation, activating an emission transistor coupled between the drive transistor and the light-emitting diode.
14. The method of claim 13, further comprising: before the reset operation, performing an on-bias stress operation by using the switching transistor to load a data voltage into the display pixel.
15. The method of claim 13, further comprising: during the on-bias stress operation, deactivating the emission transistor.
16. A display pixel comprising: a light-emitting diode; a silicon drive transistor coupled in series with the light-emitting diode; and a first semiconducting-oxide transistor coupled to an anode of the light-emitting diode.
17. The display pixel of claim 16, further comprising: one or more silicon emission transistors coupled in series with the silicon drive transistor.
18. The display pixel of claim 16, further comprising: a second semiconducting-oxide transistor coupled across two terminals of the silicon drive transistor.
19. The display pixel of claim 16, further comprising: a switching transistor configured to load a data signal onto the display pixel during a first time period and to load a reset voltage onto the

display pixel during a second time period.

**20.** The display pixel of claim 19, wherein the switching transistor comprises a silicon transistor.

---