

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250258743

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

Hurri; Pasi Markus et al.

SYSTEM AND METHOD FOR SOFTWARE MIGRATION BASED ON CAPABILITIES OF HOST DEVICE

Abstract

In one embodiment, a system may obtain first capability parameters associated with a software object executing on a first host. The first capability parameters may include an indication of resources required to execute the software object. The system may obtain second capability parameters associated with the software object, which are different from the first capability parameters. The system may determine that the first host has insufficient resources to execute the software object based at least in part on the second capability parameters. A target host with sufficient resources to execute the software object may be identified based at least in part on the second capability parameters, and the software object may be migrated from the first host to the target host.

Inventors: Hurri; Pasi Markus (Degerby, FI), Bunn; Erik Jackson (Basel, CH), Niemi; Kaj Johannes (Helsinki, FI)

Applicant: BaseN Corporation (Helsinki, FI)

Family ID: 58691146

Appl. No.: 19/065757

Filed: February 27, 2025

Related U.S. Application Data

parent US continuation 18219724 20230710 parent-grant-document US 12265456 child US 19065757

parent US continuation 17475580 20210915 parent-grant-document US 11755434 child US 18219724

parent US continuation 16672500 20191103 parent-grant-document US 11151004 child US 17475580

parent US continuation 15421330 20170131 parent-grant-document US 10503615 child US 16672500

Publication Classification

Int. Cl.: **G06F11/20** (20060101); **G01D4/00** (20060101); **G06F9/455** (20180101); **G06F9/50** (20060101); **G06F11/07** (20060101); **G06F11/16** (20060101); **G06Q30/0251** (20230101); **G06Q50/06** (20240101); **G06Q50/10** (20120101); **H04L41/0654** (20220101); **H04L67/1097** (20220101)

U.S. Cl.:

CPC **G06F11/203** (20130101); **G01D4/002** (20130101); **G06F9/5027** (20130101); **G06F9/5088** (20130101); **G06F11/0754** (20130101); **G06F11/1612** (20130101); **G06F11/1666** (20130101); **H04L41/0654** (20130101); **H04L67/1097** (20130101); G06F2009/4557 (20130101); G06Q30/0251 (20130101); G06Q50/06 (20130101); G06Q50/10 (20130101); Y02B90/20 (20130101); Y04S20/30 (20130101)

Background/Summary

RELATED APPLICATIONS [0001] This application is a continuation of U.S. patent application Ser. No. 18/219,724, titled, “SYSTEM AND METHOD FOR SOFTWARE MIGRATION BASED ON CAPABILITIES OF HOST DEVICE,” filed on Jul. 10, 2023, which is a continuation of U.S. Pat. No. 11,755,434 filed on Sep. 15, 2021, which is a continuation of U.S. Pat. No. 11,151,004 filed on Nov. 3, 2019, which is a continuation of U.S. Pat. No. 10,503,615 filed on Jan. 31, 2017; which is a continuation-in-part application of U.S. patent application Ser. No. 15/073,949 (now abandoned), which was filed on Mar. 18, 2016; all of which claim priority to the following patent application, filed on Dec. 16, 2011: [0002] U.S. patent application Ser. No. 13/328,952 titled SMARTGRID ENERGY-USAGE-DATA STORAGE AND PRESENTATION SYSTEMS, DEVICES, PROTOCOL, AND PROCESSES, which incorporated therein in their entirety the following co-filed and cross-referenced related patent applications: [0003] U.S. patent application Ser. No. 13/328,963 titled SMARTGRID ENERGY-USAGE-DATA STORAGE AND PRESENTATION SYSTEMS, DEVICES, PROTOCOL, AND PROCESSES INCLUDING A STORAGE DISTRIBUTION PROCESS; [0004] U.S. patent application Ser. No. 13/328,968 titled SMARTGRID ENERGY-USAGE-DATA STORAGE AND PRESENTATION SYSTEMS, DEVICES, PROTOCOL, AND PROCESSES INCLUDING A STORAGE DISTRIBUTION PROCESS AND PROTOCOL; [0005] U.S. patent application Ser. No. 13/328,972 titled SMARTGRID ENERGY-USAGE-DATA STORAGE AND PRESENTATION SYSTEMS, DEVICES, PROTOCOL, AND PROCESSES INCLUDING AN ANNOUNCEMENT PROTOCOL; [0006] U.S. patent application Ser. No. 13/328,979 titled SMARTGRID ENERGY-USAGE-DATA STORAGE AND PRESENTATION SYSTEMS, DEVICES, PROTOCOL, AND PROCESSES INCLUDING A VISUALIZATION, AND LOAD FINGERPRINTING PROCESS. [0007] The above-identified patent applications are incorporated herein by reference in their entirety.

TECHNICAL FIELD

[0008] The present disclosure relates generally to a host system, process, object, module, and host device, and more particularly to a system which evaluates capability parameters and determines

when to migrate a software object to another host device to maintain optimal operation.

BACKGROUND

[0009] Conventional data storage systems and conventional service providing systems use distributed computing platforms to store data or host user services. Such systems are file storage systems, remote monitoring systems, remote control systems, etc. In order to maintain continuous operations, providers of these systems use conventional failure tolerance mechanisms.

[0010] Some system failures are planned and others are unplanned. Unplanned failures include hardware failure, power outages, software bugs, user error, or other individual resource or network problems. To correct for unplanned system failures, some providers designed their systems to have fault tolerance mechanisms. Conventional fault tolerance mechanisms require human intervention with some automated redundant device techniques.

[0011] For unplanned system faults, conventional automatic redundant techniques include information redundancy, which uses error correction codes. Other conventional automatic redundant techniques include time redundancy by performing a faulty operation several times, such as retransmission. Other techniques include physical device redundancy, whereby one device is active and another is standby to take over when the active device fails. Other techniques include replication where several units operate concurrently and use a voting system to select the outcome. Typically, the more fault tolerance built into the system the more costly the system is.

[0012] An example of a planned system fault is when a resource in a system requires improvement via maintenance or an upgrade. Conventional systems can be improved when a human physically disconnects the old resource and configures the software of the improved resource and physically integrates the improved resource. This conventional technique causes system down time.

[0013] Providers of conventional systems are under pressure to reduce downtime and maintain seamless operation during planned and unplanned system failures. To evaluate different failure tolerance mechanisms, providers have developed a measurement, termed system “availability,” to describe a desired or achieved level of fault tolerance, which results in continued system access for their users. Availability refers to the amount of time a system is functioning without interruption. The fraction of time the system is available may be expressed as a percentage. A system available an entire year with a maximum of 5.26 minutes of downtime is said to be highly fault tolerant or to have 99.999% availability. Telephone systems have the goal of achieving this level of tolerance. Other systems, such as an energy monitoring system may experience 44-87 hours of downtime for a year, which amounts to a 99-99.5% availability.

[0014] On top of operating demands, complexity of storage and service host systems has grown with the advent of the need for increased data storage, delivery, analysis, transformation, and presentation. In addition, commercial and customer data and software service providers have moved storage and hosting functionality from local to remote locations. Some rely on global networks to host their storage or service capabilities. Providers find themselves using larger and more complicated systems, which have more difficult problems in maintaining system availability.

[0015] There is a need for improved system availability in data storage and service providing systems.

SUMMARY

[0016] A Spime™ self-determination apparatus including an object including instructions to execute a portion of a service which is part of at least one service provided by a system including a distributed computing platform, instructions to determine its own Spime™ object capability parameters, and instructions to store information about at least one target Spime™ host device; a Spime™ announcement module to generate an announcement message reporting presence of a Spime™ service type and the Spime™ object capability parameters; a Spime™ host evaluator module: to receive information from other Spime™ announcement messages, to evaluate current host device capability parameters with respect to the Spime™ object capability parameters or target capability parameters, to determine when the current host device capability parameters meet a

criterion, and to initiate a migration request message from the Spime™ object for migration of the Spime™ object, the object including software code and processing instructions and service function instructions, the migration to a target Spime™ object host device, when the module capability parameters meet a criterion; and a Spime™ migration module to manage the migration of the Spime™ object to the target Spime™ host device.

[0017] A Spime™ self-determination apparatus including an object including instructions to execute a portion of a service which is part of at least one service provided by a system including a distributed computing platform, instructions to determine its own Spime™ object capability parameters, and instructions to store information about at least one target Spime™ host device; a Spime™ announcement module to generate an announcement message reporting presence of a Spime™ service type and the Spime™ object capability parameters; a Spime™ host evaluator module: to receive information from other Spime™ announcement messages, to evaluate current host device capability parameters with respect to the Spime™ object capability parameters and target host device capability parameters, to determine when the current host device capability parameters meet a criterion, and to initiate a migration request message from the Spime™ object for migration of the Spime™ object, the object including software code and processing instructions and service function instructions, the migration to a target Spime™ object host device, when the module capability parameters meet a criterion; and a Spime™ migration module **216** to manage the migration of the Spime™ object to the target Spime™ host device.

[0018] A system including a distributed computing platform including a plurality of Spime™ host devices, wherein each Spime™ host device of the plurality includes: a Spime™ self-determination apparatus including: a Spime™ object including Spime™ object software including instructions to execute a portion of a service which is part of at least one service provided by a system designed to run on a distributed computing platform, instructions to determine its own Spime™ object capability parameters, and instructions to store information about at least one target Spime™ host device; a Spime™ announcement module to generate an announcement message reporting presence of a Spime™ service type and the Spime™ object capability parameters of the Spime™ self-determination apparatus; a Spime™ host evaluator module: to receive information from other Spime™ announcement messages, to evaluate current host device capability parameters with respect to the Spime™ object capability parameters or target capability parameters or both the Spime™ object capability parameters and the target capability parameters, to determine when the current host device capability parameters meet a criterion, and to initiate a migration request message from the Spime™ object for migration of the Spime object, the object including software code and processing instructions and service function instructions, the migration to a target Spime object host device, when the module capability parameters meet a criterion; a Spime™ migration module to manage the migration of the Spime™ object to the target Spime™ host device; and the system further comprising: a Spime™ available agent host device; a second Spime™ host device determined to include the target Spime™ object host device.

[0019] A process including determining whether current capability parameters of a Spime™ object stored at a first host device have increased responsibilities for storage; updating current capability parameters of the Spime™ object to reflect the increase; determining whether the current capability parameters approach the limits of the storage used to store the Spime™ object; determining whether a suitable target host device exists; initiating a migration process for the Spime™ object from the first host device to a suitable target host device, when it was determined the suitable target host device existed.

[0020] A process including determining current capability parameters of a Spime™ object; generating an announcement message including the current capability parameters; receiving potential target host messages from potential target hosts; checking whether a criterion of the Spime™ object is met by information found in the received target host messages; determining whether criterion for initiating a migration process is met; initiating the migration process to

migrate the Spime™ object to one of the potential target hosts.

[0021] A Spime™ system including a distributed computing platform including a plurality of Spime™ host devices, wherein at least one Spime™ host device includes: a Spime™ self-determination apparatus including: a Spime™ object including instructions to execute a portion of a manufactured-product-tracking service method and instructions to establish and maintain a user account with a manufacturer, instructions to determine its own function capability parameters (e.g., current price of item); instructions for communicating outside the host device, using local resources allocated to it by a host resource manager object of the host device; a Spime™ announcement module to generate an announcement message reporting presence of a Spime™ service type (e.g., indicating it performs at least a part of a manufactured product tracking service method or any other method of a service described herein or known to one of ordinary skill in the art at the time of the invention having the benefit of the description herein, offered as a service executed by a distributed computing platform) and the Spime™ object capability parameters (e.g., current price of item); a Spime™ function evaluator module: to receive information from another Spime™ announcement message, to evaluate current function capability parameters (e.g., current price from current associated user-manufacturer account) with received capability parameters, to determine when the current capability parameters meet a criterion (e.g., initiate price search when current manufacturer price exceeds limit), and to initiate generation of a migration request message when the criterion is met, the migration request message initiating migration of stored instructions from an originator Spime™ object and its host device to the target Spime™ object and its host device, the stored instructions to be migrated include instructions to manage a client account, the instructions to manage the client account being in accordance with the manufactured-product tracking service instructions; a Spime™ migration module to manage the migration of the instructions to manage the client account from the originator Spime™ object host device to the target Spime™ object host device, along with its own local resource manager object including instructions for communicating outside its new host device using its new local host resources of the target host in accordance with a host resource manager of the target host device.

[0022] A Spime™ system including a distributed computing platform including a plurality of Spime™ host devices, wherein at least one Spime™ host device of the plurality includes: a Spime™ self-determination apparatus including: a Spime™ object including instructions to manage private client information and instructions to provide access to the private client information, instructions to determine its own Spime™ object capability parameters including privacy settings indicating which entity is allowed access to the private client information; a Spime™ announcement module to generate an announcement message reporting presence of a Spime™ service type and the Spime™ object capability parameters of the Spime™ self-determination apparatus; a Spime™ host evaluator module: to receive information from a target Spime™ announcement message, to evaluate current capability parameters (e.g., current privacy settings), to determine when target capability parameters meet a criterion (e.g., access to private client information), and to initiate generation of a migration request message when the criterion is met, the migration request message initiating migration of a copy of stored data or stored instructions from the Spime™ object and its host device to a target Spime™ object and its associated target host device, the stored instructions including instructions for accessing private client information; a Spime™ migration module to manage the migration of stored data and stored instructions from the Spime™ object to the target Spime™ object.

[0023] A Spime™ system including a distributed computing platform including a plurality of Spime™ host devices, wherein at least one Spime™ host device of the plurality includes: a Spime™ self-determination apparatus including: a Spime™ object including instructions to manage private client information and instructions to provide access to the private client information, instructions to determine its own Spime™ object capability parameters including privacy requirements; a Spime™ announcement module to generate an announcement message

reporting presence of a Spime™ service type (e.g., privacy manager) and the Spime™ object capability parameters of the Spime™ self-determination apparatus; a Spime™ host evaluator module: to receive information from a target Spime™ announcement message, to evaluate current capability parameters (e.g., current privacy settings), to determine when target capability parameters meet a criterion (e.g., jurisdiction with privacy rights in accordance with privacy requirements), and to initiate generation of a migration request message when the criterion is met, the migration request message initiating migration of the Spime™ object to a target Spime™ object and its associated target host device; a Spime™ migration module to manage the migration of stored data and stored instructions from the Spime™ host device to the target Spime™ host device.

[0024] A Spime™ system including a distributed computing platform including a plurality of Spime™ host devices, wherein at least one Spime™ host device includes: a Spime™ self-determination apparatus including: a Spime™ object including instructions to establish and manage a customer energy account, instructions to determine its own Spime™ object capability parameters (e.g., current price of energy); a Spime™ announcement module to generate an announcement message reporting presence of a Spime™ service type (e.g., energy manager) and the Spime™ object capability parameters (e.g., current price of energy); a Spime™ host evaluator module: to receive information from another Spime™ announcement message, to evaluate current capability parameters (e.g., current import energy price) and target capability parameters (e.g., offered export energy price), to determine when the current and received capability parameters meet a criterion (e.g., current import price obtained is greater than offered export energy cost), and to initiate generation of a migration request message when the criterion is met, the migration request message initiating migration of stored instructions from an originator Spime™ object and its host device to the target Spime™ object and its associated target host device, the stored instructions including instructions for maintaining a client energy account; a Spime™ migration module to manage the migration of the instructions from the originator Spime™ object to the target Spime™ object.

[0025] A Spime™ system including a distributed computing platform including a plurality of Spime™ host devices, wherein at least one Spime™ host device includes: a Spime™ self-determination apparatus including: a Spime™ object including instructions to manage security of a customer account, instructions to determine its own Spime™ object capability parameters (e.g., current security level provided by host resources); a Spime™ announcement module to generate an announcement message reporting presence of a Spime™ service type (e.g., security manager) and the Spime™ object capability parameters (e.g., current security level); a Spime™ host evaluator module: to receive information from another Spime™ announcement message, to evaluate current capability parameters (e.g., current security level) and target capability parameters (e.g., offered security level), to determine when the current and received capability parameters meet a criterion (e.g., better security level exists), and to initiate generation of a migration request message when the criterion is met, the migration request message initiating migration of stored instructions from an originator Spime™ object and its host device to the target Spime™ object and its associated target host device; a Spime™ migration module to manage the migration of the stored instructions from the originator Spime™ host device to the target Spime™ host device.

[0026] A Spime™ self-determination apparatus including a Spime™ object including instructions to execute a portion of a method for providing a service which is part of at least one service provided by a system including a distributed computing platform, instructions to determine its own Spime™ object capability parameters, and instructions to store information about at least one target Spime™ host device; a Spime™ announcement module to generate an announcement message reporting presence of a Spime™ service type and the Spime™ object capability parameters required by the Spime™ object; a Spime™ host evaluator module: to receive information from other Spime™ announcement messages, to evaluate current capability parameters, to determine when the current capability parameters meet a criterion, and to initiate a migration request message from the Spime™ object for migration of the Spime™ object to or from another Spime™ object,

the migrating object including software code and processing instructions and service function instructions, when the current or received capability parameters meet a criterion; a Spime™ migration module to manage the migration of the Spime™; and a Spime™ local resource manager object to keep track of local resources available to the Spime™ self-determination apparatus. [0027] A Spime™ host device including a Spime™ self-determination apparatus and further including a processor, a memory, a network interface module, and a host resource manager object, the host resource manager object to keep track of available local resources and non-local resources, to communicate information regarding available resources to a Spime™ local resource manager object. The Spime™ host resource manager object to communicate information regarding available resources to the Spime™ local resource manager object when migration of a migrated Spime™ service object occurred to the Spime™ self-determination apparatus. The Spime™ local resource manager object to communicate information regarding required resources to the Spime™ host resource manager object when migration of a migrated Spime™ service object occurred to the Spime™ host device. The host device including resources of computing devices known to a person having ordinary skill in the art at the time of the invention having the benefit of the description herein. Local resources and non-local resources including local as determined by architecture of the distributed computing platform or other system architecture. Local resources and non-local resources including local as determined as being local to the Spime™ object requirements or current capability parameters and non-local as being associated with the host device, e.g., current host device or target host device or potential host device or available agent device or production apparatus.

[0028] A Spime™ system including a distributed computing platform including a plurality of Spime™ host devices, wherein at least one Spime™ host device includes: a Spime™ self-determination apparatus including: a Spime™ object including instructions to manage delivery of a product for a group of customers, instructions to determine its own Spime™ object capability parameters (e.g., current delivery price per unit); a Spime™ announcement module to generate an announcement message reporting presence of a Spime™ service type (e.g., delivery manager) and the Spime™ object capability parameters (e.g., current delivery price per unit); Spime™ host evaluator module: to receive information from another Spime™ announcement message, to evaluate current capability parameters (e.g., current price per unit delivery) and target capability parameters (e.g., delivery price offered), to determine when the current and received capability parameters meet a criterion (e.g., better delivery price exists), and to initiate generation of a migration request message when the criterion is met, the migration request message initiating migration of an instance of an originator Spime™ object from its host device to the Spime™ object and its associated target host device; a Spime™ migration module to manage the migration of the instance from the originator Spime™ host device to the target Spime™ host device.

[0029] A process including determining current capability parameters of a Spime™ object; generating an announcement message including the current capability parameters; receiving responding object message; checking whether a criterion of the Spime™ object is met by information found in the received responding object message; determining whether criterion for initiating an object migration process is met; initiating the migration process to migrate the responding object to be stored with the Spime™ object.

[0030] A Spime™ system including a distributed computing platform including a plurality of Spime™ host devices, wherein at least one Spime™ host device includes: a Spime™ self-determination apparatus including: a Spime™ object including instructions to assist in managing a flight path, instructions to determine its own Spime™ object capability parameters (e.g., communication speed and geographical direction); a Spime™ announcement module to generate an announcement message reporting presence of a Spime™ service type (e.g., flight path assistant manager) and the Spime™ object capability parameters (e.g., guaranteed continuous minimum communication speed at direction); a Spime™ host evaluator module: to receive information from

a plurality of another Spime™ announcement message, to evaluate a plurality of received current capability parameters (e.g., current communication throughput and direction), to determine which of the received capability parameters best meets a criterion (e.g., best received communications throughput), and to initiate generation of a migration request message **800** when the criterion is met, the migration request message initiating migration of stored instructions from the Spime™ object and its host device to a target Spime™ object associated with the determined capability parameters which best met the criterion, and its associated target host device; a Spime™ migration module to manage the migration of the stored instructions from the Spime™ host device to the target Spime™ host device.

[0031] Also disclosed herein is any process i.e., method, described herein including the physical architecture described herein or regardless of the physical architecture described herein. In an embodiment, any method described herein in accordance with the physical architecture described herein is disclosed and understood to include any computing device architecture or physical component, as would be understood by a person having ordinary skill in the art at the time of the invention having the benefit of the description herein. An example of a computing device embodiment available to a person having ordinary skill in the art at the time of the invention is public U.S. Pat. No. 8,515,829, incorporated herein by reference.

[0032] Also described herein is one or more storage devices storing instructions that are executable to perform operations of any method described herein, as would be understood by a person having ordinary skill in the art at the time of the invention having the benefit of the description herein.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0033] The accompanying figures, where like reference numerals refer to identical or functionally similar elements throughout the separate views, together with the detailed description below, are incorporated in and form part of the specification, and serve to further illustrate embodiments of concepts that include the claimed embodiments, and explain various principles and advantages of some of those embodiments.

[0034] FIG. **1** is a block diagram of example architecture of a Spime™ host system including a plurality of different types of embodiments of Spime™ self-determination apparatus in accordance with an embodiment of the present disclosure.

[0035] FIG. **2** is a block diagram of example architecture of a Spime™ host device including a Spime™ self-determination apparatus in accordance with an embodiment of the present disclosure.

[0036] FIG. **3** illustrates example message flows between different Spime™ host devices in accordance with an embodiment of the present disclosure.

[0037] FIG. **4** illustrates an exemplary Spime™ announcement message in accordance with an embodiment of the present disclosure.

[0038] FIG. **5** illustrates an exemplary Spime™ available agent announcement message in accordance with an embodiment of the present disclosure.

[0039] FIG. **6** illustrates a flow diagram of a Spime™ host evaluator module process in accordance with an embodiment of the present disclosure.

[0040] FIG. **7** illustrates an exemplary Spime™ new resource request message in accordance with an embodiment of the present disclosure.

[0041] FIG. **8** illustrates an exemplary initiate Spime™ migration message in accordance with an embodiment of the present disclosure.

[0042] FIG. **9** illustrates an exemplary Spime™ module migration message in accordance with an embodiment of the present disclosure.

[0043] FIG. **10** illustrates an exemplary complete Spime™ module migration message in

accordance with an embodiment of the present disclosure.

[0044] FIG. **11** illustrates a flow diagram of a Spime™ self-determination apparatus process in accordance with an embodiment of the present disclosure.

[0045] FIG. **12** illustrates an example Spime™ object and Spime™ system in accordance with an embodiment of the present disclosure.

[0046] FIG. **13** illustrates an example Spime™ object and Spime™ system in accordance with an embodiment of the present disclosure.

[0047] FIG. **14** is a block diagram of example architecture of a Spime™ host device including a Spime™ self-determination apparatus in accordance with an embodiment of the present disclosure.

[0048] FIG. **15** illustrates an example Spime™ object and Spime™ system in accordance with an embodiment of the present disclosure.

[0049] FIG. **16** illustrates a flow diagram of a Spime™ self-determination apparatus process in accordance with an embodiment of the present disclosure.

[0050] FIG. **17** illustrates an example Spime™ object and Spime™ system in accordance with an embodiment of the present disclosure.

[0051] The apparatus and method components have been represented where appropriate by conventional symbols in the drawings, showing only those specific details that are pertinent to understanding the embodiments of the disclosure herein so as not to obscure the disclosure with details that will be readily apparent to those of ordinary skill in the art having the benefit of the description herein.

DETAILED DESCRIPTION

[0052] As stated above, there is a need for improved system availability of data storage and service providing systems. Some embodiments of the invention described herein provide for improved system availability to handle fault tolerance, upgrades, or maintenance. Described herein are embodiments of: a Spime™ object, Spime™ self-determination apparatus, Spime™ host device, Spime™ processes including protocol messages, and a Spime™ host system.

[0053] An example architecture embodiment of a Spime™ host system can include one or more of a Spime™ self-determination apparatus or different types of Spime™ self-determination apparatuses. An example architecture embodiment is described in U.S. Pat. No. 9,322,668 in FIG. 7, which is reprinted herein as FIG. **1**, including a different identifier for description purposes. FIG. **1** illustrates an example system, which can include a Spime™ host system **100** including at least one Spime™ self-determination apparatus. A Spime™ self-determination apparatus can be one of a service module of a plurality of different types of service modules, each of which are indicated with identifier **102**. In the embodiment, each of the service modules depicted with the identifier **102** are part of the BaseN™ cloud computing system. In an embodiment, a Spime™ self-determination apparatus **102** is capable of communicating all or a part of the service announcement protocol described in U.S. Pat. No. 9,322,668. Spime™ self-determination apparatus **102** is also capable of executing a Spime™ protocol or portion thereof including a procedure generating an embodiment of a Spime™ protocol message described herein.

[0054] Before providing more detailed description, Spime™ is a term first used and described by fiction writer Bruce Sterling in his speeches and his book “Shaping Things” to mean an “object precisely localized in time and space [. . .] always associated with a history.” Bruce Sterling conceptualized a Spime™ object to be trackable through space and time throughout its lifetime. BaseN™ developed an invention that moved the Spime™ concept from imagination to reality.

[0055] BaseN™ has built embodiments, which provide functionalities, described herein, inspired by Sterling's Spime™ concept. The invention described herein provides a physical manifestation of a Spime™ concept along with the capability to provide increased seamless system operation or improved availability using embodiments of a Spime™ host system, Spime™ processes and protocol messages, Spime™ objects, self-determination apparatus, and host devices. In an embodiment, hosting a Spime™ object on a Spime™ host device includes solving a complex

problem of scaling or improving the system while maintaining the information of the Spime™ object in the Spime™ module throughout its lifetime, while reducing system downtime. In an embodiment, hosting a Spime™ object on a Spime™ host device in a Spime™ host system includes maintaining access to historical information of the Spime™ object for its full life-cycle in a Spime™ self-determination apparatus.

[0056] FIG. 1 illustrates an example architecture embodiment, which can include a Spime™ host System **100**. The system can include a distributed computing platform. System **100** can include a plurality of host devices including at least one self-determination apparatus. A Spime™ self-determination apparatus **102** includes the example embodiment of a software or hardware or software and hardware combination module e.g., a smart programmable device. Module **102** can perform any one of: agent service, logger service, storage unit, event monitoring and alerting, search engine, visualization, data filtering, autodiscovery, inventory, issue correlation, report manager, user management, map tile service, content manager, insite map, issue manager, report manager, customer portal, end-user portal, data export service, or interface service, or any combination of the described services, as described in U.S. Pat. No. 9,322,668 incorporated herein in its entirety, or other service described herein or available to a person having ordinary skill in the art at the time of the invention with the benefit of the present disclosure. Any one of these particular service modules includes specified instructions and procedures for performing at least a part of a method for the respective service. The particular specified instructions are an example embodiment of Spime™ object. In the example architecture illustrated in FIG. 1, the different service modules can be examples of different embodiments of a Spime™ self-determination apparatus.

[0057] FIG. 2 illustrates an embodiment of a Spime™ host device **206**, and Spime™ self-determination apparatus **204**, and Spime™ object **202**. In particular, a Spime™ object **202** includes a specific set of instructions for at least a part of a method to perform a particular service in a Spime™ host system, e.g., system **100**. Spime™ object **202** can include bi-directional communication and control instructions to communicate with another Spime™ object or host device or to communicate to logical or physical components internal to its current Spime™ self-determination apparatus **204** or its current Spime™ host device **206**. Object **202** can include a local resource manager object **230** including instructions for communicating with logical or physical components within its host device or outside its host device or both.

[0058] In the embodiment illustrated in FIG. 2, local resource manager object **230** can be stored as part of object **202**, or outside object **202** and within the self-determination apparatus **204**. Local resource management object **230** can include instructions to help object **202** determine its own Spime™ object current capability parameters. Spime™ object **202** can include local resource manager object **230** instructions. The local resource manager object **230** instructions can include instructions to retrieve logical current capability parameters, which the Spime™ object **202** receives for some of its functioning. For example, the instructions can include instructions to send a message on any coupling or connection, e.g., a communication bus. The logical-current-capability-parameters-request message can be sent to each local module (e.g., local includes sharing part of memory allocation of the Spime™ self-determination apparatus **204**) with local communications with the Spime™ object **202**. When the logical-current-capability-parameters-request message is received by a module in local communication with the Spime™ object **202**, the module sends the requested information. The received logical current capability parameters information is stored within the Spime™ object **202**.

[0059] For example, when prompted: Spime™ announcement module **212** sends current capability parameters indicating the functionality it provides to Spime™ object **202**; Spime™ evaluator module **214** does the respective same, as do any remaining modules sharing local storage with the Spime™ object **202** (as allocated by the Spime™ self-determination apparatus **204**). For example, when prompted by Spime™ object **202**, local resource manager object **230** will provide its logical

current capability parameters.

[0060] In an embodiment, local resource manager object **230** can include instructions to prompt the current Spime™ host device **206** components so that it may keep track of and store what components make up the Spime™ host device **206**. Each component of the Spime™ host device **206** includes instructions to respond to a prompt (e.g., a physical-current-capability-parameter-request message) with information regarding its functionality including its current capability parameters. Note, the term current capability parameters includes the non-plural case when there is only one current capability parameter.

[0061] For example, information regarding its functionality includes what physical current capability parameters or both logical current capability parameters and physical current capability parameters a component provides to Spime™ object **202**. Physical current capability parameters can include design specification information, usage information, or other current capability parameters listed herein, or any combination thereof.

[0062] In an embodiment illustrated in FIG. 2, local resource manager object **230** can include instructions to communicate with a Spime™ host resource manager object **232**. Host resource manager object **232** can coordinate information associated with execution capabilities of the local host device **206** or with execution capabilities of a higher architecture level software or hardware or both of a local system architecture including the host device **206**.

[0063] In an embodiment illustrated in FIG. 2, the above prompting and storage of physical current capability parameters or the above prompting and storage of both logical current capability parameters and physical current capability parameters, from each component of the Spime™ host device **206** can be performed by a Spime™ host resource manager object **232** so that the Spime™ self determination apparatus **204** is free to only provide the functionality of prompting and storing only logical current capability parameters of the Spime™ self determination apparatus **204**.

[0064] Depending upon the component type, when a local component of the Spime™ host device **206** receives a prompt, it sends its physical current capability parameters or sends both logical current capability parameters and physical current capability parameters. Each component of a Spime™ host device **206** includes memory including its stored current capability parameter information. Example components include a component illustrated in FIG. 2 and FIG. 14 herein, and also include any component known to one of ordinary skill in the art at the time of the invention having the benefit of the disclosure herein.

[0065] The host device Spime™ object **202** can include any one or more of data input and output interface instructions, algorithms, procedures, or functionality. Spime™ object **202** can include software that is adaptable to one or more different hardware hosts. Spime™ object **202** can include data associated with an inception of an object to its current state, and all of any in between history data including one or more states. Spime™ object **202** can include data associated with a continuous feed of usage, performance, and fault data. Spime™ object **202** can include data associated with customer support and research and development. Spime™ object **202** can include data associated with a physical object and some or all data associated with it so that the physical object can transform into Spime™ object **202** of a service model. For example, a service model can include a business transaction wherein a represented physical object is replaceable or disposable.

[0066] In an embodiment, the set of instructions of the Spime™ object **202** can include instructions to execute a portion of a method for a service in a distributed computing platform. In an embodiment, a distributed computing platform includes multiple computer modules working on a single problem. For example, a single problem is divided into many parts, and each part is solved by different computer modules. As long as the computer modules are networked, they can communicate with each other to solve the problem.

[0067] In an embodiment, a distributed computing platform includes a number of client servicing modules including Spime™ host devices and sensor agents. A client-servicing module detects when the host device is idle or has excess capability parameters and sends a notification to another

Spime™ host device. The notification indicates that the module is not in use or available for a processing job.

[0068] A goal of an example distributed computing platform using a Spime™ object embodiment included herein is to maximize performance by connecting users or maintaining services using information technology resources in a more cost-effective, transparent, resilient, or reliable manner. For example, some embodiments described herein can improve fault tolerance and resource availability in the event that one of its modules fails. For example, some embodiments described herein enable a distributed computing platform system to seamlessly scale with new resources or have legacy resources removed or upgraded. In an embodiment, a distributed computing platform includes hardware architecture, an operating system (OS), procedures, and runtime libraries.

[0069] The services provided by an embodiment of a Spime™ system can be related to maintaining or tracking a physical object or can be related to providing a service, e.g. a service distributed over a closed or open network, such as the Internet. In an embodiment, a Spime™ object **202** can include instructions for at least a part of a method for a communications service, instructions for at least a part of a method for a service provided to a user or client by a smart phone device. In an embodiment, a Spime™ object **202** can include instructions for at least a part of a method for a maintenance or preventative maintenance service associated with a physical object. Spime™ object can include instructions for a broad range of instructions for at least a part of a method for a service. In an embodiment, a Spime™ object **202** can include instructions for at least a part of a method for a lifting service, e.g., service associated with a fork lift or crane. In an embodiment, a Spime™ object **202** can include instructions for at least a part of a method for a service control capability for an electric device, such as a light bulb, physical package delivery device, flying machines, etc. A Spime™ object can include instructions for at least a part of a method to perform many kinds of services, ranging from a physical control service or sensing service e.g., from industrial automation and machinery, autonomous and semi-autonomous vehicles, home automation; to home automation type applications; to a purely virtual service, e.g. a consumer phone application service.

[0070] A Spime™ object **202** can consist entirely of stored software instructions. A Spime™ object **202** includes information about current capability parameters it requires in determining whether a host device is capable of hosting its service providing instructions. In an embodiment, a Spime™ object **202** can include information about one or more capability parameters it requires in determining which Spime™ host device can be used to execute its instructions sufficiently. For example, a long-term storage service Spime™ object in a long-term storage service self-determination apparatus of U.S. Pat. No. 9,322,668 can require a host device with at least a memory requirement, e.g., 16 megabytes of addressable memory and pointers. In another example, a logger service Spime™ object in a data reception logger service self-determination apparatus of U.S. Pat. No. 9,322,668 can require a host device with at least a minimum bandwidth, e.g., a minimum 10 Gigabit per second bandwidth. In an embodiment, capability parameters required to host a Spime™ object adapt to changes of the Spime™ object. For example, if a Spime™ object requiring 16 gigabytes of memory is hosted in a host with 32 gigabytes of memory, the available 16 gigabytes of memory are adjusted to the host's capability parameters to reflect the new state. For example, a Spime™ object initially requiring 16 gigabytes of memory can be hosted by a host with 32 gigabytes of memory capacity. The Spime™ object can grow in responsibility by assigning itself or being assigned more processing requirements. For example, a Spime™ object can include an artificial intelligence procedure, which generates new processing functionality and instructions, which require additional memory. For example, a Spime™ object can grow to require current capability requirements which exceed current host resources or which reach a criteria for migration. For example, a Spime™ object can outgrow its host's memory capacity. When a Spime™ object increases its host's memory capacity or other current capability parameter, the Spime™ object stores information to reflect its new updated state. The Spime self-determination apparatus of claim

1, wherein the Spime™ object includes instructions of a procedure, e.g., an artificial intelligence procedure, which generates new processing functionality and instructions, which require an update to its current capability parameters. The Spime self-determination apparatus of claim **1**, wherein the Spime™ object includes instructions of a procedure, e.g., an artificial intelligence procedure, which monitors its memory requirements.

[0071] In an embodiment, capability parameters required to determine or evaluate capability of hosting a Spime™ object can adapt to system changes including changes in resources associated with the most local host device, or local distributed platform hosting device groups, or a group of available host devices. In an embodiment, capability parameters can include distance vector information or link state information or both when evaluating a potential host device. For example, in an embodiment of a Spime™ object or a Spime™ process, routing protocol information can be used to make a current capability parameter determination or migration determination. Information from routing protocols, such as routing protocol information (RIP), open shortest path first (OSPF), or a routing protocol including artificial intelligence determinations including using a predetermined path, or a protocol using a combination of distance vector routing and link state routing, or a protocol that maintains the states of available neighboring host devices, e.g., available agent Spime™ host devices or other possible combination of routing protocols described herein or a service announcement protocol, with distance information and service (capability) parameter information, such as SoDa protocol, or a protocol otherwise known to a person having ordinary skill in the art at the time of the filing of this invention having the benefit of the description herein can be used with embodiments described herein.

[0072] As illustrated in FIG. **2**, in an embodiment, a Spime™ object **202** is stored and executed in a Spime™ self-determination apparatus **204**. Apparatus **204** includes other software modules, such as a Spime™ announcement module **212**, a Spime™ host evaluator module **214**, and a Spime™ migration module **216**, and can include a Spime™ local resource manager object **230** or module. Memory **222** can be allocated or distributed in Spime™ host device **206** to store each Spime™ object and module. In an alternative embodiment, the stored instructions of any one or more of modules **212**, **214**, **216** or object **230** can be included in the Spime™ object **202** and not coded or fixed at a separate physical memory location. Other embodiments described herein can use alternative embodiments of Spime™ object architecture, as known to one of ordinary skill in the art at the time of this invention having the benefit of the description herein.

[0073] In an embodiment, a Spime™ self-determination apparatus **204** comprises a Spime™ object **202** including Spime™ object software including instructions to execute a portion of a service which is part of at least one service provided by a system **100** including a distributed computing platform, instructions to determine its own Spime™ object capability parameters, and instructions to store information about at least one target Spime™ host device; a Spime™ announcement module **212** to generate an announcement message reporting presence of a Spime™ service type and the Spime™ object capability parameters of the Spime™ self-determination apparatus **204**; a Spime™ host evaluator module **214** to receive information from other Spime™ announcement messages, to evaluate current host device capability parameters with respect to the Spime™ object capability parameters or target capability parameters, to determine when the current host device capability parameters meet a criterion, and to initiate a migration request message from the Spime™ object **202**, including software code and processing instructions and service function instructions, to a target Spime™ object host module, when the module capability parameters meet a criterion; a Spime™ migration module **216** to migrate the Spime™ object to the target Spime™ host device while not disrupting a system availability level of the system.

[0074] FIG. **2** illustrates an embodiment of a Spime™ host device **206** including some example hardware resources. Hardware resources are examples of current capability parameters of Spime™ object **202**. For example, a particular memory **222**, processor **224**, and a network interface module **226** can meet the current capability parameters of Spime™ object **202**. A different Spime™ object

202 embodiment can require other software or hardware or combination of requirements of capability parameters. For example, an embodiment of a host resource manager object **232** or module can be used to manage the hardware associated with a host device **206**. The object or module can be stored more local to the hardware resources than the storage of the software resources associated with the self-determination apparatus. Storage location of manager objects can be associated based upon the most local system architecture or some other level of system architecture.

[0075] Spime™ announcement module **212** generates an announcement message reporting presence of the Spime™ object **202** and current capability parameters of the self-determination apparatus **204** associated with the particular Spime™ object **202**. For example, any of the information in the service announcement messages described in U.S. Pat. No. 9,322,668 can be included in an embodiment of a Spime™ announcement message described herein. For example, an embodiment of a service announcement message includes information from or including any one or more from the following list of possible service announcement messages: agent service announcement, logger service announcement, storage unit announcement, event monitoring and alerting announcement, search engine announcement, visualization announcement, data filtering announcement, autodiscovery announcement, inventory announcement, issue correlation announcement, report manager announcement, user management announcement, map tile service announcement, content manager announcement, insite map announcement, issue manager announcement, report manager announcement, customer portal announcement, end-user portal announcement, data export service announcement, interface announcement, or service announcement messages described herein.

[0076] As described above, capability parameters required to evaluate or determine potential hosting of a Spime™ object can adapt to host or system changes, including changes in resources associated with a host device or local device including information obtained from any routing protocol, such as RIP, OSPF, a combination, a proprietary routing protocol, or a routing protocol including artificial intelligence determinations.

[0077] Each of the service announcement messages can have associated predetermined current capability parameters including a particular hardware or software or combination resource required for the operation of the service performance instructions of the particular Spime™ object **202**. In an embodiment, a Spime™ object **202** tracks and updates its capability parameters including associated resource requirements and stores information about optimal operation including minimal, or sufficient, or economical values associated with its required resources and capability parameters.

[0078] A Spime™ object **202** can store a single set of one or more minimal resources required or optimal resources required. The set of minimal or optimal resources required can be described as capability parameters for the object. For example, a Spime™ object **202** of the service type long-term storage can send a long-term storage service announcement message to another module, such as a receiving module including a Spime™ host device or Spime™ available agent device.

[0079] The receiving module can receive the announcement message and imply one or more capability parameters are necessary or optimal to host the Spime™ object **202** of the particular service type, e.g., long-term storage. For example, a pre-determined set of capability parameters can be associated with a particular announcement message type across some logical system delineation or hardware architecture specification. For example, receipt of a particular service type announcement message can imply a pre-determined specified amount of memory and a pre-determined specified amount of processing power is required to operate, for example, a long-term storage Spime™ object **202** at a host device, such as a Spime™ host device **206**. For example, the below table, Table 1, lists some service type indications and some respective current capability parameter requirements that would be pre-determined, and so implied, by receiving their corresponding announcement message. The corresponding implied or explicitly specified current

capability requirements can go up to any number n. Some examples of current capability parameters are listed below.

TABLE-US-00001 TABLE 1 Current Current Current Type of capability capability capability
Service parameter 1: parameter 2: parameter n: logger service memory: processing legal
jurisdiction: announcement e.g., minimum performance: e.g., Maintain of 16 megabytes e.g.,
provision or borders of specific of addressable authorization or entity (e.g. memory and quality of
access German) pointers of 10 Gigabit jurisdiction per second bandwidth to the customer data (e.g.,
when real time analytics connectivity is a memory requirement) storage unit memory: processing
legal jurisdiction: announcement e.g., minimum performance: e.g., Maintain of 122 Gigabit e.g.,
provision or borders of specific local capability authorization or entity (e.g. quality of access
German) of 10 Gigabit per jurisdiction second

[0080] FIG. 3, in combination with FIG. 1 and FIG. 2, illustrate embodiments of some Spime™ protocol message processes 300 including particular protocol messages. Messages can be communicated between embodiments of Spime™ self-determination apparatuses e.g., 102, 204 via a Spime™ host device 206 to another Spime™ host device 206, which can be selected as the target host device. For example, an announcement message 302 with its respective implied, as described above, or explicit current capability requirements can be transmitted to or from a first Spime™ host device 312 and to or from another Spime™ host device 314.

[0081] In another embodiment, the Spime™ announcement module 212 of FIG. 2 obtains information of the particular current capability requirements from its associated Spime™ object 202. The Spime™ announcement module 212 generates an announcement message 304, which is populated with information generated from its retrieved current capability requirements.

[0082] FIG. 4 illustrates an embodiment of information, which can be transmitted via a Spime™ protocol announcement message 304. Other message structures, including other order of the information described herein, is included in other embodiments of Spime™ protocol messages described herein. FIG. 4 illustrates an embodiment of Spime™ announcement message 400, which can be generated by the Spime™ announcement module 212. For example, Spime™ message 400 includes a Spime™ identifier (ID) field 402, a Spime™ message type field 404, a Spime™ service type field 406. In an embodiment, Spime™ message 400 can include an explicit indication of current capability parameters in field 408.

[0083] Other fields containing other information can also be included in other embodiments indicated as such in FIGS. 4-10 with the use of dashed-line depictions, e.g., fields, such as ownership, extension, Spime™ payload information, additional payload information, Spime™ history data, etc. Additional information not listed herein but known to one of ordinary skill in the art at the time of the invention having the benefit of the description herein can be transmitted using an additional field, e.g., field labeled etc. In an embodiment, additional fields can be used to transmit information pertaining to cryptographic verification-of-authenticity, authentication, or secrecy.

[0084] In an embodiment, explicit current capability parameters can be indicated in field 408. For example, an identification of one or more criterion of interest field 410 can be used to indicate which current parameter capabilities are more important than others. In an embodiment, an ownership field 412 can announce what entity has ownership of the Spime™ object. Ownership can indicate which entity or service provider owns the physical or logical Spime™ object representation. In an alternative embodiment, ownership can be shared or ownership rights can be subject to jurisdictional laws of property and intellectual property rights. Some Spime™ objects 202 include a capability parameter indicating that it can only be hosted by devices on a particular manufacturer-owned Spime™ system, while others can migrate to other manufacturer's Spime™ systems. Some Spime™ objects 202 include a capability parameter indicating that it can only be hosted where the legal jurisdiction requirement is met.

[0085] Other fields include an excess capabilities field 414, whereby, for example, a Spime™ host

device **206** announces that it has excess resources including capability parameters to possibly host another Spime™ object **202**. Another field is one or more of an extension field **416**, which can be configured to enable the Spime™ self-determination apparatus **204** to take on additional functionality, which can be particular to an embodiment of the Spime™ host system **100**. In an embodiment, cryptography or digital signature information or a combination of both is provided in a field of the announcement message or other Spime™ protocol messages described herein, e.g., via the extension field or another type of dedicated field. In an embodiment, extension field **416** includes a specific field particular for a particular user and their requirements. The coding and length of the fields can be set initially or configured later or reconfigured as needed.

[0086] In an embodiment, a Spime™ object **202** can set flags in a pre-specified bit stream in the current capability parameters field **408**. In an embodiment, field **408** can include bits indicating a pointer to a storage location or a pointer to instructions on how to read storage location bits of the field **408**. In an embodiment, field **408** can include bits indicating predetermined code instructions.

[0087] Information designated by the field **408** can indicate physical current capability parameters including any one of the following: processing speed, memory, SRAM, processing performance, instructions per cycle, floating-point operations per potential transfer host, computing capacity, computing load maximum per requested process, internal storage capacity, number of CPUs cache memory, different level cache memory including second level cache etc., main memory, hard drive capacity, memory bandwidth, input/output bandwidth, communications bandwidth, communications throughput, memory controller parameters, remote associated storage capacity, or any combination of the herein listed current capability parameters, or a logical capability parameter associated with a particular service capability.

[0088] The current capability parameters include physical current capability parameters including any one of: processing speed, memory, SRAM, processing performance, instructions per cycle, floating-point operations per potential transfer host, computing capacity, computing load maximum per requested process, internal storage capacity, number of CPUs cache memory, different level cache memory including second level cache etc., main memory, hard drive capacity, memory bandwidth, input/output bandwidth, communications bandwidth, communications throughput, memory controller parameters, or remote associated storage capacity, or any combination including one or more of the physical current capability parameters.

[0089] Information designated by the field **408** can indicate other logical current capability parameters including any one or more of the following: data security, security level, security cost limit, legal jurisdiction, privacy selection, advertiser selection, economic requirement, financial requirement, energy efficiency, energy cost, energy source, energy use, operation cost, relative trust, geographic location, ownership, communications cost limit, and availability.

[0090] Logical current capability parameters include any one of: data security type, security level, security cost limit, legal jurisdiction, privacy selection, advertiser selection, economic requirement, financial requirement, energy efficiency, energy cost, energy source, energy use, operation cost, relative trust, geographic location, ownership, communications cost limit, or availability, or a logical capability parameter associated with a particular service capability, or any combination including one or more of the logical current capability parameters.

[0091] Referring back to FIG. 3, in an embodiment of a Spime™ host system **100**, the system can include a free agent Spime™ host device **318**. The available agent device **318** can be made available after an upgrade of new resources is made into the system **100**. The new resource and its associated capability parameters can be identified to the system **100** by its generating a available agent announcement message **308**.

[0092] FIG. 5 illustrates an exemplary Spime™ free host announcement message **500** in accordance with an embodiment of the present disclosure. An embodiment of a Spime™ free host announcement message **500** can include a Spime™ host identifier (ID) field **502**, a Spime™ message type field **504**, a current capabilities field **506**, and a Spime™ distance vector field **508**.

The Spime™ host ID can be set by a maintenance person or can be automatically generated by a Spime™ object **202**, as will be described later. The current capabilities field **506** can be generated by an embodiment of a Spime™ announcement module of an available agent device, similar to the Spime™ announcement module **212** of FIG. 2. An embodiment of the Spime™ distance vector field **508** includes a network distance, such as hop counts, or: GPS information, wifi access point location information, or any other type of location information, etc.

[0093] The remaining fields illustrated in the embodiment of the Spime™ free host announcement message **500** include fields, such as an ownership field **510**, similar or as the ownership field **412**. Other fields include one or more of an extension field **512**, which can be configured later after the initial setup of the available agent Spime™ host device **318**, to enable the device to take on additional functionality, as described above.

[0094] Referring back to the embodiment illustrated in FIG. 1 and FIG. 2, there are times when the Spime™ object **202**, for example a long-term storage Spime™ object **102**, has taken on additional storage responsibilities. For example, a system may scale to include more storage devices as described in U.S. Pat. No. 9,322,668 incorporated in its entirety by reference herein. In an embodiment, Spime™ object **102** can update its current capability parameters and check if they come close to a criterion, such as the maximum of its current memory resources **222**, associated with its current host device **206**.

[0095] FIG. 6 illustrates a flow diagram of an embodiment of a process **600** executed by instructions of the Spime™ Host Evaluator module **214**. Process **600** includes determining whether current capability parameters, e.g., storage responsibilities or data throughput processing requirements have increased (**602**). If yes, then the Spime™ host evaluator module **214** updates its current capability parameters accordingly (**604**) and checks whether the updated capability parameters approach a criterion, such as the limits of the current host resources (**606**). Example host resources include hardware embodiments illustrated in FIG. 2, e.g., memory **222** or processor **224** or network interface **226** or other resources which would be associated with any of the other current capability parameters listed herein or otherwise. If a criterion is met, e.g., limits are being approached (or violated, depending on the particular capability parameter or otherwise depending upon the particular capability parameter) according to an associated threshold setting, then the Spime™ host evaluator module **214** process determines whether a suitable target host device exists (**608**). If yes, it will initiate a migration procedure (**610**). If not, it will initiate a new resource request procedure (**612**). The migration module can migrate the Spime™ object to the target host device in an effort to not reduce a system availability level of the system, e.g., by including maintaining an instance of the object at an originator host device until the migration is complete or other means available.

[0096] In other embodiments, a Spime™ object can migrate to a location determined to be in greater proximity to a particular resource of the system. In other embodiments, a Spime™ object can reproduce, for example, to provide access to locally collected data or to provide expanded storage capacity. Such providing of expanded storage capacity can be a part of an embodiment of a data collection service.

[0097] Referring back to the procedure illustrated in FIG. 6, if the storage capacity of all of the storage service providing Spime™ objects associated with current physical storage capabilities (local or across a network) of a Spime™ system are have reached a limit, then the Spime™ object requiring the increased storage would request a new resource for the Spime™ system by sending a Spime™ new resource request message **700** to a type of Spime™ object. A particular type of Spime™ object can initiate production of the required device.

[0098] FIG. 7 illustrates an embodiment of a Spime™ new resource request message **700**.

Referring back to FIG. 3, a Spime™ host device **302** can send a Spime™ new resource request message **320** to an embodiment of Spime™ production apparatus **322**. For example, a Spime™ host system **100** includes a 3-dimensional printing resource and its associated Spime™ production

module **322**. In the example embodiment, a Spime™ production module **322** is a Spime™ object with instructions to produce a 3-dimensional model in accordance with the design specification it receives from the Spime™ new resource request message **320**.

[0099] A Spime™ production module **322** receives the message **320** and then generates communications with a system associated with a manufacturer of the product or it can control a Spime™ 3-dimensional-printer module to produce the specified product. In a simple example, the system associated with the manufacturer of the requested product can be a system that receives an email generated by the Spime™ production module **322** or it may be a more automated system, which receives specifications for the design of the newly requested product and generates the product. The newly requested product can be assigned a Spime™ object automatically in accordance with a Spime™ ID generating procedure. The Spime™ generating procedure can be performed by the requesting Spime™ object or by the target Spime™ object. For example, a Spime™ generating procedure can include generating an identification including a unique manufacturer trademark combination with a sequential or random generated number up to a numerical limit or not limited. Any unique identification generating procedure can be implemented with embodiments herein.

[0100] For example, in the embodiment illustrated in FIG. 7, Spime™ Host Evaluator module **214** generates a new resource request message at block (**612**). The message includes the requesting Spime™ ID field **702** including the ID of the Spime™ object **202** associated with the requesting Spime™ Host Evaluator module **214**. The message further includes a message type field **704** identifying the message as being a particular kind. In this example, the message type is a Spime™ new resource message.

[0101] Embodiments of message **700** include a Type of new resource request indicator field **706**. This field indicates, to Spime™ production modules **322**, which kind of Spime™ production module should act upon receipt of the message **700**. For example, a Spime™ production module designed to produce memory would respond when the Type of New Resource Request indicates “memory” as the resource type. In another example, a Spime™ production module, designed to produce hosting hardware would respond accordingly when the Type of New Resource Request indicates “new hardware” as the resource type. In another example, a Spime™ production module designed to produce a product would respond accordingly when the Type of New Resource Request indicates “new product” as the resource type.

[0102] Embodiments of message **700** include a new resource design specification field **708**, which may be a pointer to a location in the Spime™ system **100** where a larger set of more particular data may be stored. For example, a particular Spime™ object **202** may generate a custom design specification. In an alternative embodiment, the field **708** may have preconfigured design specification data associated with a particular field setting or bit code. Embodiments of message **700** include the optional ownership field **710** and extension field **712**, similar to or as described above.

[0103] Referring back to FIG. 3, when the Spime™ host evaluator module initiates Migration procedure (**610**), the embodiments of the Spime™ Migration module **216** will start a Spime™ module transfer process by generating Spime™ migration messages. FIGS. **8-10** illustrate some example embodiments of Spime™ migration protocol messages **800**, **900**, **1000**.

[0104] FIG. **8** illustrates an embodiment of an Initiate Spime™ module migration message **800**. It includes a Spime™ ID field **802** indicating the ID of the Spime™ object, which is initiating the migration process. Message **800** includes a Spime™ Msg type field **804** indicating the message to be an Initiate Spime™ Module Migration message type. Message **800** includes the ID of the Target Host Device, which was selected by the Spime™ host evaluator module **214** and communicated to the Spime™ Migration module **216**. Message **800** can include payload information in its initial migration message in a payload field **808**. Additional payload information fields **810** and so on can also be used. Message **800** can also include an extension field **812**. In an alternative embodiment,

message **800** can leave all payload information to be migrated by one or more Spime™ Migration messages **900**.

[0105] FIG. **9** illustrates an embodiment of a Spime™ module migration message **900**. It includes a Spime™ ID field **902**, Spime™ message type field **904**, and Spime™ target ID field **906**. It also includes payload information. In an embodiment Spime™ payload information includes Spime™ object **202** instructions **920** and Spime™ object **202** history data information **922**. In an embodiment, one or both of, instructions **920** or history data **922** is set with actual data in the payload field **908** itself or one or both of field **920** or **922** can identify a pointer location of where the respective data is stored. For example, Spime™ instructions field **920** can be set to a pointer, which, for example, includes an address in the Spime™ host system **100**, or elsewhere including outside the Spime™ host system, such as a URL location, where the payload information is stored. Spime™ History data field **922** can be set to a pointer.

[0106] Spime™ Migration module **216** communicates all of the Spime™ module migration messages **900** needed to migrate the Spime™ Object instructions **920** or Spime™ history data **922** or both to a Spime™ target host device. Any transport technology is capable of use to perform the migration process. After the migration of the Spime™ object instructions **920** and Spime™ history data is complete, the Spime™ migration module sends a Complete Spime™ module transfer message **1000**.

[0107] FIG. **10** illustrates an embodiment of a Complete the Spime™ Module Transfer Message **1000**. Message **1000** includes a Spime™ ID field **1002**, a Spime™ message type field indicating this is an instruction to Complete Spime™ Module Transfer Message type. This can be enough information to signal to the Target Spime™ host device to initiate action in accordance with its Spime™ object **202** instructions. After the Spime™ Migration Module **216** has sent this message out, the Spime™ Migration Module **216** removes the Spime™ object **202** from its previous host device. In an embodiment of a Spime™ Host system **100**, a Spime™ object **202** indicated by its associated ID may be hosted in only a single Spime™ host device **206**.

[0108] In an embodiment, when a Spime™ object **202** migrates to a Spime™ target host device, which is a Spime™ Host device **316** similar to its previous Spime™ host device **312**, the Spime™ object **202** provides information to the existing announcement module **212**, evaluator module **214**, and migration module **216** of the target device so that the modules generate the processes and messages the originating Spime™ object **202** and host device were capable of producing.

[0109] In an embodiment, when a Spime™ object **202** migrates to a Spime™ target host device, the entire contents of its associated self-determination apparatus **204** including the announcement **212**, evaluator **214**, and migration **216** modules are migrated along to the target host device also.

[0110] FIG. **11** illustrates an embodiment of a process **1100** performed by a self-determination apparatus **204**. A Spime™ object **202** executes an embodiment of a self-determination apparatus **204** process **1100**. The Spime™ object **202** determines what current capability parameters it requires (**1102**) to provide its particular service. It transfers the information to a Spime™ announcement module **212**, which generates a Spime™ announcement message **400** (**1104**) populated with associated field information. For example, a particular type of Spime™ object type can generate an associated announcement message. In an embodiment, there is a Spime™ object of a type which tracks a product for its life-cycle and it is referred to herein as a manufactured-product-tracker Spime™ object **202**. In the example, the announcement message can include a unique Spime™ ID in field **402**; an Announcement type Spime™ message type indication in field **404**; and a service type, e.g., a manufactured-product-tracker Spime™ service type in field **406**.

[0111] For example, a particular manufacturer manufactures a product at a particular facility including particular factory details and product design specification details. The product design specification details can be generic or customized to a particular customer. Such manufacturing information and other information can be termed as information associated with the beginning of the life-cycle of a product or other Spime™ object service type entity. The beginning of the life-

cycle includes the initiation or instantiation of the life-cycle for the product. An embodiment of a generic manufactured-product-tracker Spime™ object **202** receives and stores beginning of life-cycle information and associates the information with a new unique Spime™ ID. After initialization the generic manufactured-product-tracker Spime™ object **202** has become a particular manufactured-product-tracker Spime™ object **202** with its new unique Spime™ ID.

[0112] The particular manufactured-product-tracker type of Spime™ object **202** stores some or all other information acquired along the life-cycle of the product. For example, the Spime™ object **202** can store information about the individual who ordered the product, any change in the product, e.g., degradation of the product, location of the product, use of the product, fit of the product, user measurement information gathered from the product or supplied by the user, etc. Information about the owner of the product can include information such as legal jurisdiction. Information of the owner can include privacy selections the owner chose for his information collected by the Spime™ object **202**. Information about the owner can include advertiser selections indicating which advertisers are interested in selling advertisements to the owner or which advertisers the owner has indicated permission to send advertisements or other communications.

[0113] Referring back to FIG. **11**, using the above embodiment of the manufactured-product-tracker Spime™ object **202** and its associated self-determination apparatus **204** to explain more detail of process **1100**, some or all of the information gathered by the Spime™ object **102** can be used to determine current parameter capabilities information eventually transmitted into the field **408** of the announcement message **400**. For example, some other information the Spime™ object **202** can acquire is the geographic location of the owner. In an embodiment, the Spime™ object **202** for the example manufactured-product-tracker Spime™ object **202** embodiment can be part of a global Spime™ host system **100**. The geographic location of the owner that bought the product can be part of the current capabilities parameters. The geographic location information can be acquired repeatedly to make sure the most up to date geographic location information is stored.

[0114] Continuing on with the example, the Spime™ object **202** receives the most current geographic information and updates its current capability parameters to reflect the new information. The customer can travel across the globe and still maintain communications with a Spime™ system **100** embodiment. In the example, the customer moved from a prior home location to a new home location, e.g., the customer moved from New York, NY, USA to Sydney, Australia. In this example, the Spime™ object **102** determines its current capability parameters (**1102**) to include the new home geographic location of Sydney, Australia. The Spime™ object **202** sends the current capability parameters to its associated Spime™ announcement module **212**. The Spime™ announcement module **212** generates an embodiment of the announcement message **400** (**1104**) including an indication that its current capability parameter includes a geographic location update to Sydney, Australia. Spime™ object **102** receives a potential target host message (**1106**), such as an Announcement message **400** or an available agent host device message **500** from a Spime™ host device **206** having geographic information indicating it is located closer to the owner in Sydney.

[0115] Referring back to the embodiment of the flow diagram illustrated in FIG. **11**, the Spime™ object **102** which has prior geographic location information of NY will call upon its Spime™ host evaluator module **214** to check its criterion (**1108**) to see if any of the received messages have information which when run through its specific criterion cause the Spime™ object to have to migrate (**1110**). In the example, the criterion of geographic location is checked for optimal proximity. If a more optimal proximity criterion is met (**1112**) by another Spime™ object, or an available host device capable of housing the Spime™ object, the hosting availability information is relayed via an announcement message.

[0116] Then Spime™ object **202** can call upon its Spime™ migration module **216** to initiate a migration process including sending migration messages **800**, **900**, **1000** to the target host device. The target host device met the better proximity criterion, which indicated it had a better geographic

location capability parameter. If the better proximity criterion is not met (**1110**), the Spime™ object **202** determines whether a New Resource Request Spime™ object exists (**1114**) in its table of possible targets. Possible target information is generated from information received from received potential target host messages (**1106**), such as an announcement message **400** or an available agent host device message **500**. Possible target information can be stored in a possible target table. Spime™ object **202** can receive messages from different types of potential targets. For example, if there is no sufficient target to host the object, then there can be a target that can be generated by a process initiated by the object depending upon what resources are available in the system to which the object is a part. For example, a system can include the capability to generate a new resource. A New Resource Request Spime™ object can be part of a Spime™ production apparatus **322**, which is part of the system.

[0117] For example, a New resource request Spime™ object **102** from the Spime™ host system **100** or from an outside system which had announced itself as such in the Spime™ service type field **406** of its announcement message **400** can be stored in a table of possible targets of the Spime™ object **202**. When its table includes the correct new Resource Request Spime™ object (here the resource requested is a new generic Spime™ host device **206**) the Spime™ object **202** initiates a new resource request process (**1116**) by generating a Spime™ New Resource request message **700** to the corresponding target.

[0118] In the example, a generic host device is an available host device **206**, which does not have a unique Spime™ ID. A Spime™ host device **206**, which hosted a Spime™ object that completed the migration process to the available host device **206**, would assign itself a new Spime™ ID after sending a Complete Spime™ module Migration message **1000**.

[0119] As described herein, the Spime™ object **202** includes numerous current capability requirements and criterion, which can integrate with embodiments of the invention. For example, the above manufactured-product-tracker Spime™ object **202** embodiment had, in the example, a single current capability parameter criterion of geographic location, which caused its Spime™ object to migrate out of its Spime™ host device **206**. In other embodiments, there can be evaluation of one or more of the parameters listed herein according to any of the criterion listed herein. In other embodiments, there can be evaluation of one or more of the parameters known to one of ordinary skill in the art at the time of the invention having the benefit of the description herein according to any of the criterion known to one of ordinary skill in the art at the time of the invention having the benefit of the description herein.

[0120] Embodiments described herein help solve the existing problem of conventional systems not having enough system availability to meet increased demands of scaling systems. Other embodiments described herein provide other benefits including enabling use of automated and artificial intelligence to make information transfer decisions from Spime™ object to another Spime™ object.

[0121] As described above, embodiments of the Spime™ implementation solution provide a solution for increased system availability using the described Spime™ solutions. Envisioning growth and control over larger systems by using a common communication protocol messaging and integration solution as described herein, using the Spime™ implementation solution, leads to other problems that require solving, such as security and privacy maintenance across the larger systems.

[0122] Security and privacy and other benefits can also be obtained with the use of embodiments of the Spime™ implementation solution described herein via the setting up of particular capability parameters and criterion including the claims with their most broad and most narrow examples. Data modeling and its implementation is difficult to create when needing to cover scalable systems including microsystems, sub-systems, systems, and larger macrosystems, which can include one or more microsystems that reach large coverage across the globe while maintaining a high data transmission rate. Data structure and meaning between system wide applications must be

understood to be effective. Data meaning is made clear in embodiments described herein. Some embodiments of the data modeling and implementations described herein solve the problem of combining legacy systems and devices with newer devices and systems by having a well-defined solution, which can grow and change as needed throughout the life-cycle of the systems.

[0123] FIG. 12 illustrates another embodiment of a Spime™ system **1200**. Spime™ system **1200** provides a manufactured product tracking service. Spime™ system **1200** includes Spime™ objects **202 202**, etc. including another example of a particular manufactured-product-tracker Spime™ object **202**, for example a clothing identification Spime™ object **1202**. Object **1202** includes instructions to execute a portion of a manufactured product tracking service and instructions to establish and maintain an account with a current manufacturer in cooperation with a corresponding Spime™ object hosted by resources of the manufacturer.

[0124] Spime™ object **1202** can receive information gathered from thread sensor information in clothing. A thread sensor can perform agent services of collecting and sending sensor data to an associated Spime™ object in the system. Thread sensor information can be obtained from any paper or cloth item having a thread sensor. For example, paper towel, toilet paper, wipes, diapers, a towel, a sock or shoe, or pant, or top, etc. any article of paper or cloth can have a thread sensor **1204** attached or sewn into it.

[0125] An agent device, such as a smart phone or smart home appliance or smart washer or dryer **1206** or combination washer/dryer agent device, can receive information from any sensor, such as thread sensor **1204**. See U.S. Pat. No. 9,322,668 herein incorporated in its entirety for more information of agent devices and supporting system resources along with other devices and sensors known at the time of filing this invention with the help of the disclosure herein.

[0126] The example dryer agent device **1206** sends clothing product information to its associated Spime™ object **1202**. Spime™ object **1202** stores manufactured product tracking service information including life-cycle information of a clothing item e.g., a sock. For example, sock **1208** can have Spime™ object **1202** store associated information it needs to perform its product tracking service. The information can be information the object identified as a capability parameter. Capability parameters can include any one or more items from the following: information regarding its manufacturer, purchase date, price, material, wear time information, washings, wear coordination information (e.g. what other items were worn at same time), etc. Spime™ object **1202** can also store information about the owner of the sock **1208**, such as identification information, location information, age, size, foot shape, foot size, etc. Spime™ object **1202** can also store information about objects associated with the sock, like shoe manufacturer information of shoes the owner has. Spime™ object **1202** can also store weather information of the owner's location. Spime™ object **1202** can receive data from different agent devices and store the received information as a capability parameter, such as current quality of an item, degradation level of the item, electrical resistance measurement of the sensor in the item, monthly subscription information for the item, etc.

[0127] In an embodiment, Spime™ object **1202** can store and determine its capability parameters to include logical or functional capability parameters including economic information associated with the item it is set to manage. In an embodiment, the total price of an item, or price of shipping an item to an owner, or the total price of both can be stored by object **1202**. For example, the total price of the item and shipping to the owner at his residence in NY, NY from the current manufacturer in China can be stored with the current price of \$5.00. Spime™ object **1202** can communicate with a current manufacturer Spime™ **1220** to obtain the item price of \$0.78.

[0128] In an embodiment, a current capability parameter of Spime™ object **1202** includes the current price of the item for a particular customer. Spime™ object **1202** can monitor when the price of the item exceeds a limit price. Spime™ object **1202** can store a limit price for the item as a criterion. When the criterion is met, Spime™ object **1202** can initiate a shop-around-procedure or other procedure associated with the particular Spime™ object.

[0129] For example, object **1202** can initiate self-determination apparatus process **1100**. Spime™ object **1202** can determine its one or more current capability parameters to include the price it has obtained for one or more clients for an item (**1102**). Object **1202** can generate an announcement message (**1104**), similar to the embodiment of the announcement message in FIG. 4, including a Spime™ ID, Spime™ msg type (e.g., announcement), Spime™ service type (e.g., manufactured product tracking service), and current capability parameters including the current item price.

[0130] The embodiment of the announcement message can include current item ownership information, which in this embodiment can be the current manufacturer information. In another embodiment, the ownership information can be information of what entity maintains the Spime™ object information, e.g., a cloud based data management provider, such as BaseN™. In another embodiment, the ownership information can be information of what entity is to store the retrieved information.

[0131] Referring back to the clothing item cost example embodiment illustrated in FIG. 12, Spime™ object **1202** can send out an embodiment of announcement message **400**. Other Spime™ objects **202** of competing item manufacturers, e.g., a manufacturer of an item similar to an item, e.g., sock **1208**, can receive the embodiment of announcement message **400**. For example, a manufacturer located in China hosts Spime™ object **1220**, which has a current purchase agreement with object **1202** for the particular customer. Another manufacturer located in India hosts Spime™ object **1230**. Object **1230** can receive the announcement message and can send an embodiment of a Spime™ announcement message **400** including a Spime™ ID, Spime™ msg type, Spime™ service type (e.g., available manufacturer), current function capability parameters (e.g., a lower item price than the current price and ownership information).

[0132] Distance vector information can be missing when price of the item outweighs operational communication costs related to the latency caused by the distance between operating resources for the operation of the Spime™ object.

[0133] Referring back to the embodiment of a Spime™ self-determination apparatus process **1100**, Spime™ **1202** receives the announcement message from Spime™ **1230** as an embodiment of receiving a potential target host message (**1108**). Spime™ **1202** checks (**1108**) if its price criterion for migration is met (**1110**). If the price criterion of the potential target host, e.g., Spime™ object **1230**, meets the price criterion of Spime™ object **1202**, then Spime™ **1202** initiates a migration procedure (**1112**) of the instructions to establish and maintain a client account with a manufacturer to be transferred from Spime™ object **1220** to Spime™ object **1230**.

[0134] The migration procedure can include additional notification and authorization messaging between the Spime™ objects. For example, Spime™ object **1202** can notify the owner of the item of the existence of the Spime™ object that meets the criterion, can wait for authorization, and can then complete migration, including updating other associated Spime™ objects, such as an object that manages billing matters.

[0135] In other words, an embodiment of system **1200** includes a distributed computing platform **100** including a plurality of host devices **206**, wherein at least one host device **206** includes a self-determination apparatus **204** including an object **1202**. Spime™ object **1202** includes instructions to execute a portion of a manufactured-product-tracking service and instructions to establish and maintain an account with a manufacturer, instructions to determine its own function capability parameters (e.g., price of item when using a current manufacturer, as obtained by current manufacturer hosted object **1220**).

[0136] Object **1202** can store information about at least one target host device (**206** of **1230**) from which it receives information. The Spime™ self-determination apparatus **204** further includes an announcement module **212** to generate an announcement message **400** reporting presence of a service type (e.g., manufactured-product-tracking service) and object capability parameters (e.g., current price of item).

[0137] The Spime™ self-determination apparatus **204** further includes a host evaluator module **214**

to receive information from other announcement messages (**500** or **400** from **1230**) to evaluate target capability parameters (e.g., current price of item in accordance with potential manufacturer). Evaluator module **214** determines when the current function capability parameters meet a criterion (e.g., exceed a price limit or receive a lower price from a target host device), and when the criterion is met, initiates generation of a migration request message (**800**). Sending a migration request message initiates migration of stored instructions (See FIG. **14**, **1420** indicated in FIG. **13** using dashed line depicting migrating, e.g., representing migrating across networks using packet data) from an originator object **1220** and its host device **206** to a target object **1230** and its host device **206**.

[0138] The originator object **1220** receives the migration message and then the originator object can continue the migration process. The migrated instructions including instructions to manage a client account being in accordance with the manufactured-product tracking service instructions stored by object **1202**. The Spime™ self-determination apparatus **204** further includes a Spime™ migration module **216** to manage the migration of the instructions to manage the client account from the originator Spime™ object **1220** host **206** to the target Spime™ object **1230** **206**. Spime™ migration module **216** manages the migration of the instructions along with its own instructions for communicating outside its new host device using its new local resources of the target host.

[0139] In another embodiment, using the illustration in FIG. **12** and assigning a new example to the illustrated Spime™ objects, a provider of maintenance for all or part of a network including a Spime™ system **1200** can own the rights to Spime™ object **1202** or an associated Spime™ object as part of a service agreement to manage information. The agreement can be between the entity providing the maintenance and the owner of an item **1208**, or the manufacturer of the item **1208**, or a third party.

[0140] Each Spime™ object in system **1200** can be associated with its own embodiment of a respective local server e.g., **1260** and storage e.g., **1262**. The object's local server and storage can be part of the resources included in the object's host device e.g., **206**. Private client information associated with ownership or use of an item e.g., **1208** can be part of the data and instructions included in Spime™ object **1202**. Object **1202** can also store instructions, which provide access to the private client information. For example, access can be single use, temporary, or subscription based.

[0141] Spime™ object **1202** can include capability parameters including privacy settings. Privacy settings can indicate which entity is allowed access to the private client information. The user or the owner of the item or the owner of information associated with the item can select one or more privacy settings. In an embodiment, the owner (owner of an item **1208**, or the manufacturer of the item **1208**, or other third party) of the information tracked by Spime™ object **1202** can set a privacy setting to allow information transfer between itself or another object (i.e., originator) and a target Spime™ object for utilization by others, such as advertisers, or manufacturers of similar or associated items in accordance with the privacy setting.

[0142] For example, Spime™ object **1202** can store private client information along with privacy settings to control access to the private client information. For example, the privacy settings can include a setting to enable advertisers of particular shoe brands to have temporary access to the private client information. A manufacturer of a shoe item can request access to the private client information, e.g., foot size information. In the example, Spime™ object **1202** determines its current capability parameters to include a privacy setting (**1102**) and sends out an embodiment of announcement message **400** (**1104**) including a Spime™ ID, Spime™ message type (e.g., announcement message), Spime™ service type (e.g., private client information and access), current capability parameters (e.g., privacy setting, e.g., allowing access by particular manufacturers of shoe items). Other Spime™ objects receive the announcement message and can read the current capability parameter as including a privacy setting as allowing access by Spime™ objects belonging to different shoe manufacturers interested in obtaining the private client information. In

the embodiment, each of Spime™ objects **1220**, **1230**, **1240**, **1250** can receive the announcement message **400** sent by Spime™ object **1202**.

[0143] Spime™ object **1202** can be a Spime™ object controlled and maintained by a shoe manufacturer. The manufacturer owning Spime™ object **1202** can have stored private client information of a customer who purchased one of their products. Another manufacturer, owning Spime™ object **1250**, can already have had access to private owner identification information stored by object **1202**. The manufacturer owning Spime™ object **1250** can add instructions to object **1250**, which cause it to request for additional private client information, such as access to the more private client information from object **1202**, e.g., foot size information, style or color preference information, shopping habit information.

[0144] Spime™ object **1202** can send an announcement message **400** (**1104**) out on a network. The network can include a Spime™ system that communicates across other networks or can be a combination of only Spime™ systems. For example, the Spime™ system **1200** currently hosting Spime™ object **1202** can communicate with other Spime™ systems when the current capability parameters of the object indicate privacy access can be obtained by outside systems, e.g., systems managed by an entity different from the entity managing the current hosting Spime™ system.

[0145] Spime™ object **1250** can receive the announcement message (**1106**) from Spime™ object **1202** and can send a potential target host message. The potential target host message can be in the form of its own announcement message **400** indicating it is a manufacturer and indicating it has current capability parameters including having all or some, or requesting all or some, access to private client information. For example, object **1250** can indicate a desire to have access to some or all of the private client information stored by object **1202**. For example, object **1250** can request access to client size information. Spime™ object **1202** can check if the potential target host of Spime™ object **1250** meets a criterion (**1108**), such as which entities are allowed requested access.

[0146] In the embodiment, if the criterion (**1110**) is met (e.g., access to requested private client information is allowed), then the Spime™ object **1202** can make a copy of the requested object information **1420**. In an embodiment, the Spime™ object **1202** can make a copy of the requested object information including the data along with instructions for what to do with the data. The object **1202** can initiate migration of the copy of the requested private client object information (**1112**) to Spime™ object **1250** for a temporary duration. During the temporary duration time, the Spime™ object **1250** can store the requested and received private client information, e.g. the size information.

[0147] In the embodiment, the target host Spime™ object **1250** was only allowed one time access. In another embodiment, the access may be a subscription type access, which defaults to having any update to the private client information migrated. In a large network of systems including systems managed by different entities, it is beneficial to have only one Spime™ object, e.g., object **1202** control access to the private client information. When the criterion is met, object **1202** initiates migration of the requested information and instructions for accessing private client information. Instructions for accessing private client information can include allowed rate of access, or allowed private client information items, or a combination in accordance with a privacy agreement.

[0148] In an embodiment, initiation of the migration process or the migrated instructions for accessing the private client information can be used to record an account for a per transaction or other agreed billing arrangement. The billing arrangement can be used to initiate sending of an invoice. For example, the managing entity of Spime™ object **1202** can charge for each migration of information from Spime™ object **1202**. For example, after the Spime™ migration module **216** completes a migration it can automatically generate an invoice to the entity, which received the migration. In another embodiment, the invoice can be sent to an entity having an agreement to pay for the migration of particular information including data or execution instructions.

[0149] In another embodiment, object **1202** may store private client information and be subject to privacy laws of a given jurisdiction of its current host device **206**. If the privacy laws of the

jurisdiction change, then object **1202** may announce its capability parameters including privacy requirements. Other objects e.g., object **1250** whose host device falls in a jurisdiction capable of protecting the announced privacy requirements can send an announcement message indicating its jurisdiction. Spime™ object **1250** can evaluate the received capability parameters and determine if its jurisdictional criterion is met and when met can initiate its own migration to the host device **206**, which has a jurisdiction, which meets its criteria for privacy requirements.

[0150] FIG. **13** illustrates an example of a Spime™ system, which can be used with smart grid energy systems. “Smart” is a term that denotes an improvement from old systems. “Smart” as a qualifier can denote any one or more of the following: digital communication capabilities, two way communication where there was none before, distributed technology, sensor measurements, self-monitoring, self-healing, adaptive architecture, more customer choice, pervasive computing (i.e., microprocessors being prevalent throughout the devices in a system), islanding (i.e., continuing to supply power when off of the grid). Smart grid energy systems can include a combination of heterogeneous systems such as a separate system for power generation, transmission, and distribution, along with a system for data management system, and a system for sensor collection, data monitoring and measurement and presentation. Any of these systems individually or as a whole, can be run by one or more separate enterprise entities. Any of these systems individually or as a whole, can benefit from a Spime™ implementation solution.

[0151] FIG. **13** illustrates an example communication system **1300** made up of interconnected energy provider systems, each managed by different energy providers, e.g., providers in the US and Canada. For example, each energy provider system can include a cloud based smart grid energy provider infrastructure system. Each system can include subsystems for generating, transporting, and distributing electricity. Each system can be managed and controlled with its own cloud based smart management system and protected by its own smart protection system. Each smart energy provider management system (e.g., solar **1350**, wind **1352**, nuclear **1354**, coal **1356**, gas **1358**, oil **1360**, or hydro **1362**) can include an embodiment of a Spime™ implementation solution described herein. For example, each cloud based energy management subsystem includes a respective host device **206** embodiment and respective embodiment of a Spime™ object (e.g., **1351**, **1353**, **1355**, **1357**, **159**, **1361**, **1363**) including respective instructions for communicating energy price information.

[0152] The large example communication system **1300** can include one or more other cloud based systems, which provide software or platform or infrastructure as a service, such as, for example, a customer management system, an energy market system, bulk generation system, managing energy movement system, etc. The term cloud based herein refers to a capability of delivering on-demand computing solutions to customer requests. Spime™ cloud based systems include Spime™ objects and their resources, processes, and protocol messages as described herein.

[0153] In this example, customer management system **1320** manages a customer account, such as individual or group commercial, residential, or industrial user customer accounts. System **1320** includes Spime™ object **1321**. Customer management system **1320** can be set as a private cloud or public cloud or some hybrid system or other type of Spime™ system, which communicates with other Spime™ interoperable systems.

[0154] Spime™ object **1321** includes instructions establish and manage a customer energy account. The instructions can further include instructions to seek the lowest energy price for a customer account. For example, one or more customer account billing Spime™ object **1302**, **1304**, **1306** can be stored at a host device at any energy provider management system. FIG. **13** shows with dotted lines the migration of each account from an originator host device to a target host device. Energy manager Spime™ object **1321** includes stored instructions including current capability parameters including energy price associated with the current provider of energy for a customer account. Energy manager Spime™ object **1321** executes an embodiment of Spime™ self-determination apparatus process **1100**. Energy manager Spime™ object **1321** can determine its one or more

current capability parameters to include current price of energy it has obtained or negotiated for a customer account (**1102**). Energy manager Spime™ object **1321** can generate an announcement message (**1104**), similar to the embodiment of the announcement message in FIG. 4, including a Spime™ ID, Spime™ msg type (e.g., announcement), Spime™ service type (e.g., energy manager), and current capability parameters including its import energy price.

[0155] One or more of the Spime™ objects (e.g., **1351, 1353, 1355, 1357, 1359, 1361, 1363**) of their respective smart energy provider management system (e.g., solar **1350**, wind **1352**, nuclear **1354**, coal **1356**, gas **1358**, oil **1360**, hydro **1362**) can receive the announcement message and send back its own announcement message, similar to the embodiment of the announcement message in FIG. 4, including a its own Spime™ ID, Spime™ msg type (e.g., announcement), Spime™ service type (e.g., energy provider), and current capability parameters including its export energy price for a potential customer.

[0156] Energy accounts manager Spime™ object **1321** receives one or more Spime™ messages from Spime™ objects **1351, 1353, 1355, 1357, 1359, 1361, and 1363**. Energy manager Spime™ object **1321** includes instructions including information of which of its customer accounts have customer billing Spime™ objects, which have migrated onto particular energy provider management systems. For example, energy cost manager Spime™ object **1321** has instructions storing information on where one or more customer account billing Spime™ objects, e.g., a first customer account billing information Spime™ object **1302** and a second customer account billing information Spime™ object **1304** and a third customer account billing information Spime™ **1306** are hosted.

[0157] For example, first customer account billing Spime™ object **1302** is initially hosted by the smart energy provider management system (nuclear) **1354** at its Spime™ object **1355**; second customer account billing Spime™ object **1304** is hosted by the smart energy provider management system (natural gas) **1354** at its Spime™ object **1359**; and third customer account billing Spime™ object **1306** is hosted by the smart energy provider management system (solar) **1350** at its Spime™ object **1351**.

[0158] Referring back to FIG. 13, FIG. 11, and FIG. 4, energy cost manager Spime™ object **1321** receives the announcement messages from one or more of each energy provider management system Spime™ object **1351, 1353, 1355, 1357, 1359, 1361, 1363** (**1106**). Energy manager Spime™ object **1321** checks if information it received met a criterion (e.g., export energy price is less than current import energy price) (**1108**) and checks if criterion for migration (e.g., migrate if export is less than import or e.g., migrate if energy type is preferred from existing energy type) (**1110**) is met.

[0159] Migration, in this embodiment, is migration for the one or more of the individual customer account billing Spime™ objects **1302, 1304, 1306**. Spime™ object **1321** includes instructions containing information of all its managed customer account billing Spime™ objects **1302, 1304, 1306** and their Spime™ IDs. After the energy manager Spime™ object **1321** determines what export energy capability parameter meets its criteria best, it stores possible target host information and then checks for migration criteria. Based upon comparison and evaluation of when a possible target host is suitable for migration, it initiates a migration process (**1112**) for the individual customer account billing Spime™ objects **1302, 1304, 1306** it manages. In an alternative embodiment, a plurality of user accounts can be migrated based upon an evaluation for a single account similar to a group of accounts.

[0160] When energy manager Spime™ object **1321** initiates the migration process for each of individual customer account billing Spime™ objects **1302, 1304, 1306** it generates individual embodiments of an initiate Spime™ module migration message (FIG. 8) for one or more of each migrating individual customer account billing Spime™ objects **1302, 1304, 1306**. For example, energy provider management system Spime™ object **1350** (solar) had sent an announcement message including capability parameter of export energy cost, which was lower than the current

capability parameter of import energy cost, which was included in the announcement message, which Spime™ object **1321** sent out. This met the criterion of the energy manager Spime™ object **1321**. This caused the energy manager Spime™ object **1321** to generate an embodiment of an initiate Spime™ module migration message **800** for the individual customer account billing Spime™ objects **1302**, **1304** and not Spime™ object **1306** because it was already being hosted by energy provider management system Spime™ object **1350** (solar).

[0161] In another embodiment, using FIG. **13**, with a different example, customer management system **1320** can include a security level manager Spime™ object **1371**. Security level manager Spime™ object **1371** can manage customer account billing Spime™ objects **1302**, **1304**, and **1306** including instructions including capability parameters including security level information. For example, security level manager Spime™ object **1370** can generate an announcement message embodiment **400** including its Spime™ ID, Spime™ message type (announcement) its Spime™ service type (security check) including an indication of current security level of security, e.g., **3** and a criteria of interest being a higher level of security in field **410** of an embodiment of announcement message **400**. In the example, Spime™ energy provider management system Spime™ object **1351** sends back an announcement message indicating it can provide a higher level of security due it having capability parameters including higher level security hardware or physical security resources, which are not found at the current host device of **1353** e.g., of object **1302**. Security level manager Spime™ object **1371** can generate a migration message, which initiates migration of object **1302** to the host device in system **1350**.

[0162] In an alternative embodiment of process **1100**, when two options exist meeting the criterion (**1108**) but not enough criterion is met for migration of individual customer account billing Spime™ objects **1302**, **1304**, **1306** (**1110**), then other criteria can be checked (**1108**) until all criterion is checked. So for example, security level manager Spime™ Object **1371** can look to a secondary criteria, such as lower price or other user energy preference, between the capability parameters indicated in the received announcement messages. After making a migration decision based upon one or more criteria (**1110**) security manager Spime™ object **1371** initiates a migration process generating a migration message **800** for one or more of the individual customer account billing Spime™ objects **1302**, **1304**, **1306**.

[0163] In an alternative embodiment, the functionality of the stored security management instructions can be stored at as a separate object stored with each individual customer account object **1302**. Each customer account object can have the functionality described above with respect to object **1321**, except that in this embodiment the customer account object evaluates and determines when to move itself from one host to another host when a criterion is met.

[0164] FIG. **14** illustrates another embodiment of a Spime™ object host device **1406**. A Spime™ object host device **1406** includes a Spime™ evaluator object **1414**, which evaluates capability parameters. Capability parameters can include physical resource capability parameters (as described above with reference to some embodiments corresponding to FIG. **2**) or functional resource capability parameters, as described otherwise herein.

[0165] Spime™ host evaluator object **1414** can evaluate capability parameters for migration of an object it manages or for migration of itself. Spime™ host evaluator object **1414** can evaluate capability parameters for migration of an object it manages but where the object is stored at a host device different from its host device. Spime™ host evaluator object **1414** can evaluate capability parameters for migration of an object it manages and wherein the object it manages is stored at the same host device as itself.

[0166] In some embodiments described herein, capability parameters are associated with evaluation of physical resources for determining where to host an object. In some embodiments described herein, capability parameters are not associated with physical resources for hosting the object, but are associated with one or more service function capability resources used to serve a Spime™ object **1402** or another associated object that is served by the Spime™ object **1402**. For example,

Spime™ evaluator object **1414** evaluates services outside of its host device **1406** capable of delivering a product or service to a user associated with account Spime™ object **1402**.

[0167] In the embodiment, Spime™ migration module **1416** can be used to migrate the object **1402** to another host device, or can be used to migrate a service Spime™ object **1420** originally found outside the host device **1406** to the host device **1406**, or can be used to migrate a service Spime™ object **1420** originally found outside the host device **1406** to the another host device outside the host device **1406**. Spime™ object **1402** can be added to or updated to include additional instructions from another Spime™ object **1420**. Spime™ object **1402** can select another Spime™ object to be migrated into its host device **1406** and stored as part of its Spime™ object **1402**. In another embodiment, Spime™ object **1402** can evaluate and determine when to cause itself to be migrated to another host, in accordance with embodiments described herein. In another embodiment, Spime™ object **1402** can evaluate and determine when to cause object **1420** to be migrated to another host device, in accordance with embodiments described herein.

[0168] When a migration process is initiated, the process can further include migrating a local resource manager object **230** associated with an object set for migration. The local resource manager object **230** communicates with a host resource manager **232** of a target host device to ensure operation of the migrated object on the target host device.

[0169] FIG. 15 and FIG. 16 illustrate an embodiment of a Spime™ system **1500** and process **1600** including an example embodiment of service object **1420** which can be migrated from an originator host device **1406** of system **1504** to a target host device **1406** and object **1402** of system **1502**, as indicated with the dashed lines showing the migration propagation across networks coupling the sub-systems **1504** and **1502**. For example, Spime™ system **1500** includes sub-systems including a product ordering service Spime™ sub-system **1502** and one or more of a product delivery service Spime™ sub-system **1504**, **1506**, **1508**. Sub-system **1502** can be operated by a manufacturer of a product. The manufacturer is interested in finding a better delivery service to use to deliver its products to a group of its customers.

[0170] Object **1520** can keep track of a group of customer orders, including one-time orders, which may be stored for purposes of possibly being repeated, or recurring orders e.g., subscription orders. For example, object **1520** can manage a group of customer wine orders. The orders are for wine from its manufacturing facility located in California. Spime™ object **1520** can store customer account information associated with its determined current service function capability parameters (**1602**) including a current delivery operation price, including one or more economic options for packaging and delivering of a product. Spime™ object **1520** can determine its current capability parameters to include delivery operation price (**1602**). Spime™ object **1520** via its host device can generate an announcement message **400** (See FIG. 3, **312** and FIG. 16, **1604**) including a Spime™ ID, Spime™ message type (e.g., announcement message), Spime™ service type (e.g., customer account information), current service function capability parameters (e.g., delivery operation price). Spime™ object **1520** via a host device (FIG. 3, **312**) can generate an embodiment of announcement message **400** including an ownership field **412** indicating that ownership of any offered objects are to be stored with Spime™ object **1520**.

[0171] Sub-systems **1504**, **1506**, **1508** receive the customer account announcement message **400** and generate their own respective Spime™ embodiment of an announcement message **400**. For example, Spime™ object **1514** of system **1504** can be a delivery service object, which maintains information of the different delivery services it provides. For example, Spime™ object **1514** sends an embodiment of an announcement message **400** including information about its one or more small unmanned aircraft package delivery service prices, e.g., delivery price per unit, along with a respective associated variable delivery speed.

[0172] Spime™ object **1520** receives one or more of the responding announcement messages (**1606**) from the different delivery option Spime™ objects on its system **1500**. For example, Spime™ object **1514** generates an announcement message indicating its current capability

parameters of its commercial unmanned aircraft package delivery service price option (e.g., price per unit offered for a specified time) and associated delivery speeds. Spime™ object **1516** generates an announcement message indicating its current capability parameters of its truck package delivery service price option and associated delivery speeds. Spime™ object **1518** generates an announcement message indicating its current capability parameters of its plane package delivery service price option and associated delivery speeds.

[0173] Spime™ customer account type object **1520** receives the announcement messages from the responding Spime™ objects (**1606**) and evaluates the data received with its criterion (**1608**). For example, Spime™ customer account type object **1520** receives all of the information from the different delivery option Spime™ objects **1514**, **1516**, **1518** and checks information from their messages against its delivery criterion (**1608**). For example, the delivery criterion for the example customer can be for lowest price delivery, which can be met by the commercial unmanned aircraft package delivery service Spime™ object **1514**. When the criterion is determined to be met by the commercial unmanned aircraft package delivery service Spime™ object **1514** (**1610**), the initiation of the migration of a particular customer instance **1420** of the object **1514**, which met the criteria, to the Spime™ customer account type object **1520**.

[0174] For example, the commercial unmanned aircraft package delivery service Spime™ object **1514** can instantiate a delivery object with a new Spime™ ID for use by the particular Spime™ customer account type object **1520**. For example, commercial unmanned aircraft package delivery service Spime™ object **1514** can then initiate migration of the newly instantiated commercial unmanned aircraft package delivery service Spime™ object **1420** by generating an embodiment of an initiate Spime™ module migration message **800**. Migration of packets of one or more corresponding migration messages **800**, **900**, **1000** can be achieved across any packet data communication system coupling the source and target Spime™ objects.

[0175] For example, an embodiment of an initiate Spime™ module migration message **800** in the example above can include a newly generated Spime™ ID, a Spime™ message of the type “migration of instantiated object”, a target Spime™ ID of the requesting Spime™ customer account type object **1520**, and payload information including the instructions of the new commercial unmanned aircraft package delivery service Spime™ object **1420**. In the above example, the commercial unmanned aircraft package delivery service Spime™ object **1420** corresponds to an embodiment of a migrated service Spime™ object **1420** in FIG. 14 and the requesting Spime™ customer account type object **1520** can be part of an embodiment of the Spime™ object **1402** in FIG. 14.

[0176] FIG. 17 illustrates an example Spime™ object and Spime™ system in accordance with an embodiment of the present disclosure. Spime™ macro-system **1700** includes systems with coverage across large areas, which can include satellite communication systems (not shown). Spime™ system **1700** also includes land based landline and wireless communication systems covering, for example, a land area delineation **1799**. The communication systems are coupled with the Internet and so denoted as open cloud based systems, **1702**, **1704**, **1706**, **1708**, **1710**, **1712**, and **1714**. In the example, land area is divided into hexagonal shaped areas for more generic illustration purposes. In the example, Spime™ system **1702** covers communications across a first geographical area, A, and so on, as depicted in FIG. 17.

[0177] For example, using another embodiment of a commercial unmanned aircraft-package-delivery-service Spime™ object, object **1750**, stored at host **1760**, is a flight-path-controller object of a commercial unmanned aircraft delivery system apparatus **1740**. Instructions stored by Spime™ object **1750** include instructions that negotiate the commercial unmanned aircraft communications pathway from package origination source area A to package delivery target area G. The flight path may be negotiated to optimize for a particular path criteria such as, for example, avoiding collisions with other commercial unmanned aircrafts **1792**, **1994**. Another example of a path criteria includes finding a fastest route or a least expensive route, or route controlled by an entity, or a route meeting

a particular user requested criteria or artificial intelligence determined or controlled criteria.

[0178] Flight-path-controller Spime™ object **1750** operates in conjunction with land-based flight-path-assistant Spime™ object **1712**. For example, flight-path-assistant Spime™ object **1712** can store local information related to what airspace other commercial unmanned aircrafts are in or expected to be and if the other commercial unmanned aircrafts are in the same air space or expected to be in the same air space at the same time as commercial unmanned aircraft system apparatus **1740**. Flight-path-assistant Spime™ object **1712** can also store local area air space information, such as weather information, current or expected rain or snow, wind, temperature, solar energy. Local air space information is used to assist the commercial unmanned aircraft-package-delivery-service Spime™ object **1750** to control the flight path of the commercial unmanned aircraft **1740**.

[0179] Commercial unmanned aircraft-package-delivery-service Spime™ object **1750** needs to be in constant communications with flight-path-assistant Spime™ object **1712**. Flight-path-assistant Spime™ object **1750** needs to be in constant communication with access points of the neighboring communication systems. Access points to the neighboring systems **1702, 1704, 1706, 1708, 1710, 1712, 1714** for each has a respective object **1712, 1714, 1716, 1718, 1720, 1722, 1724**, hosted by each individual respective Spime™ host device **1722, 1724, 1726, 1728, 1732, 1734**.

[0180] Communication systems **1702, 1704, 1706, 1708, 1710, 1712, 1714** provide wireless communications for commercial unmanned aircrafts, e.g. commercial unmanned aircraft **1740** while traveling across a land area. Commercial unmanned aircraft **1740** is to travel between source location A and target location G. Each system used to execute a flight path across the land area has an associated communication speed including an available throughput rate. Commercial unmanned aircraft-package-delivery-service Spime™ object **1750** needs to maintain communication at a minimum throughput rate as it travels across each region that falls under communication coverage of the combined different communication systems.

[0181] As commercial unmanned aircraft-package-delivery-service Spime™ object **1750** travels, it executes, alone or as part of an embodiment of a self-determination apparatus **204** or host device **206 (1760)**, an embodiment of the process illustrated in FIG. **11**. For example, Spime™ object **1712** determines one or more of a minimum capability parameter, wherein a minimum capability parameter includes a physical capability requirement of a minimum guaranteed continuous communication speed (**1102**) between itself and Spime™ object **1750**. In another embodiment, an additional capability parameter can be used in conjunction with minimum guaranteed continuous communication speed capability parameter. For example, the capability parameter of having a matching geographic direction (within a specified degree range, e.g., within 30 degrees of a specified direction e.g., of a two-dimensional 360 degree plane) can be used to evaluate the received potential target messages.

[0182] For example, a minimum communication speed can be a minimum communication throughput. Spime™ object **1712** generates (**1104**) a Spime™ announcement message **400** embodiment including its ID **402**, message type **404**, service type **406**, and a criteria of interest **410** including an indication of a minimum communication throughput required for a flight-path-assistant Spime™ object to communication with the commercial unmanned aircraft **1740**. The Spime™ announcement message is received by one or more systems within the future expected communication range (e.g., neighboring communications systems or systems detected by the object) of the commercial unmanned aircraft headed to the target location area G. For example, systems located at or near the start of the delivery path area A can be system **1704** and **1706**.

[0183] In the embodiment, Spime™ object **1714** and object **1716** each receive the announcement message and determine whether they have enough resources to meet the criteria of interest **410**. If they do, then each object responds with its respective Spime™ announcement message **400** or Spime™ available agent announcement message **500** including an indication of how much throughput it can provide. For example, Spime™ object **1714** checks that it has over the minimum

throughput requirement criteria (e.g., 10 Mbits/see downlink and 5 Mbits/see uplink) and indicates it has 14.7 Mbits/see downlink and 5.75 Mbits/see uplink. Spime™ object **1716** indicates is has 28 Mbits/see downlink and 22 Mbits/see uplink. Spime™ object **1712** receives the respective responding message from Spime™ object **1714** and **1716** (**1106**). In this embodiment, block **1106** of process **1100** includes determining which responding object met the criteria best and compares the best response with its criteria (**1108**). Spime™ object **1712** determines if criteria for migration of itself to another host is met (**1110**) and if yes initiates a migration process (**1112**) of object **1712** to a target Spime™ host device, e.g., **1726**.

[0184] This process repeats with Spime™ object **1712** moving from Spime™ host to Spime™ host, e.g., Spime™ host **1726** to Spime™ host **1728** to host **1732** until it reaches Spime™ host **1734**, assuming all had met the criteria throughout the execution of embodiments of process **1100** by Spime™ object **1714** for each of the Spime™ hosts encountered along the way to the target destination area.

[0185] Embodiments of the invention described herein enable the internet of things (IoT) technology to expand beyond any of its current conventional implementations. Spime™ objects designed in accordance with some embodiments described herein can be applied to other commercial applications and to some military applications. Spime™ objects designed in accordance with some embodiments described herein enable a scalability technique of systems using IoT technology to have greater system availability and less failure. Spime™ objects designed in accordance with some embodiments described herein enable a system of like distributed sensors to scale automatically. Spime™ objects designed in accordance with some embodiments described herein enable a distributed system of software modules to communicate and grow to include artificial intelligence more seamlessly or in a controlled research setting while not affecting existing use of a system. Advanced distributed sensor networks and systems could scale seamlessly by including one or more embodiments described herein. Spime™ objects designed in accordance with some embodiments described herein enable improved data processing and cybersecurity protections. Spime™ objects designed in accordance with some embodiments described herein enable cybersecurity across distributed networks to scale seamlessly and to be maintained automatically. Spime™ objects designed in accordance with some embodiments described herein enable artificial intelligence to be implemented in a more seamless way into an existing network. Spime™ objects designed in accordance with some embodiments described herein describe a computational architecture for next generation machine learning. Spime™ objects designed in accordance with some embodiments described herein enable more energy efficient computing. Spime™ objects designed in accordance with some embodiments described herein enable signal processing that reduces hardware requirements. Spime™ objects designed in accordance with some embodiments described herein enable greater assurance, reliability and validation techniques. Spime™ objects designed in accordance with some embodiments described herein enable heterogeneous integration. Spime™ objects designed in accordance with some embodiments described herein enable microsystem design and computer aided design (CAD). Spime™ objects designed in accordance with some embodiments described herein enable systems of microsystems to scale and grow in an automatic method. Spime™ objects designed in accordance with some embodiments described herein enable systems of microsystems including sensor or actuation devices to scale and grow using an automatic process including a process using artificial intelligence.

Claims

1: A system for communicating an a network, the system comprising: one or more processors; one or more computer memories coupled to the one or more processors, the one or more computer memories comprising instructions which, when executed by the one or more processors, cause the

system to: obtain first capability parameters associated with a software object executing on a first host, wherein the first capability parameters comprise an indication of resources required to execute the software object; obtain second capability parameters associated with the software object, the second capability parameters being different from the first capability parameters; determine, based at least in part on the second capability parameters, that resources of the first host are insufficient to continue executing the software object; identify a target host based at least in part on the second capability parameters, wherein the target host has sufficient resources to execute the software object; and migrate the software object from the first host to the target host over the network.

2: The system claim 1, wherein the instructions, when executed by the one or more processors, further cause the system to determine, using an artificial intelligence procedure, that the first capability parameters of the software object have changed to the second capability parameters.

3: The system of claim 2, wherein the second capability parameters for the software object are determined, at least in part, by the artificial intelligence procedure.

4: The system of claim 1, wherein the instructions, when executed by the one or more processors, further cause the system to send a resource request message on the network when it is determined that the first host has insufficient resources.

5: The system of claim 1, wherein the resources of the first host are determined to be insufficient when below a threshold associated with the second capability parameters.

6: The system of claim 1, wherein the second capability parameters comprise at least one of a memory storage capability and/or a processing capability.

7: The system of claim 1, wherein the instructions, when executed by the one or more processors, further cause the system to maintain an instance of the software object at the first host until migration is complete.

8: The system of claim 1, wherein the instructions, when executed by the one or more processors, further cause the system to receive target capability parameters from the target host over the network, wherein the target capability parameters comprise an indication of available resources of the target host.

9: The system of claim 8, wherein the instructions, when executed by the one or more processors, further cause the system to identify the target host from among a plurality of hosts, based at least in part on the second capability parameters and the received target capability parameters.

10: The system of claim 8, wherein the target capability parameters comprise distance information comprising an indication of a distance between a geographic location and the target host, and wherein the instructions, when executed by the one or more processors, further cause the system to identify the target host from among a plurality of hosts based on the distance information.

11: A method for communicating on a network, the method comprising: obtaining first capability parameters associated with a software object executing on a first host, wherein the first capability parameters comprise an indication of resources required to execute the software object; obtaining second capability parameters associated with the software object, the second capability parameters being different from the first capability parameters; determining, based at least in part on the second capability parameters, that resources of the first host are insufficient to continue executing the software object; identifying a target host based at least in part on the second capability parameters, wherein the target host has sufficient resources to execute the software object; and migrating the software object from the first host to the target host over the network.

12: The method of claim 11, further comprising: determining, using an artificial intelligence procedure, that the first capability parameters of the software object have changed to the second capability parameters.

13: The method of claim 12, wherein the second capability parameters for the software object are determined, at least in part, by the artificial intelligence procedure.

14: The method of claim 11, further comprising sending a resource request message on the network when it is determined that the first host has insufficient resources.

- 15:** The method of claim 14, wherein the resources of the first host are determined to be insufficient when below a threshold associated with the second capability parameters.
- 16:** The method of claim 15, wherein the second capability parameters comprise at least one of a memory storage capability and/or a processing capability.
- 17:** The method of claim 11, further comprising maintaining an instance of the software object at the first host until the migration is complete.
- 18:** The method of claim 11, further comprising: receiving target capability parameters from the target host over the network, wherein the target capability parameters comprise an indication of available resources of the target host; and identifying the target host from among a plurality of hosts, based at least in part on the second capability parameters and the received target capability parameters.
- 19:** The method of claim 18, wherein the target capability parameters comprise distance information comprising an indication of a distance between a geographic location and the target host, and wherein the instructions, when executed by the one or more processors, further cause the system to identify the target host from among a plurality of hosts based on the distance information.
- 20:** A method for communicating on a network comprising a first host, the method comprising: obtaining capability parameters associated with a software object executing on the first host, wherein the capability parameters comprise an indication of resources required to execute the software object; obtaining a geographic location associated with the software object; determining whether a target host is closer to the geographic location than the first host, wherein the target host has sufficient resources to execute the software object; and migrating the software object from the first host to the target host when the target host is determined to be closer to the geographic location than the first host.
-