

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent Application Publication	20250264518
Kind Code	A1
Publication Date	August 21, 2025
Inventor(s)	Whetsel; Lee D.

---

### INTEGRATED CIRCUIT DIE TEST ARCHITECTURE

---

#### Abstract

A test control port (TCP) includes a state machine SM, an instruction register IR, data registers DRs, a gating circuit and a TDO MX. The SM inputs TCI signals and outputs control signals to the IR and to the DR. During instruction or data scans, the IR or DRs are enabled to input data from TDI and output data to the TDO MX and the top surface TDO signal. The bottom surface TCI inputs may be coupled to the top surface TCO signals via the gating circuit. The top surface TDI signal may be coupled to the bottom surface TDO signal via TDO MX. This allows concatenating or daisy-chaining the IR and DR of a TCP of a lower die with an IR and DR of a TCP of a die stacked on top of the lower die.

---

<b>Inventors:</b>	<b>Whetsel; Lee D. (Parker, TX)</b>
<b>Applicant:</b>	<b>Texas Instruments Incorporated (Dallas, TX)</b>
<b>Family ID:</b>	<b>1000008575111</b>
<b>Appl. No.:</b>	<b>19/198712</b>
<b>Filed:</b>	<b>May 05, 2025</b>

#### Related U.S. Application Data

parent US division 18754683 20240626 parent-grant-document US 12313667 child US 19198712  
parent US division 18226924 20230727 parent-grant-document US 12025649 child US 18754683  
parent US division 17858122 20220706 parent-grant-document US 11726135 child US 18226924  
parent US division 17162025 20210129 parent-grant-document US 11391769 child US 17858122  
parent US division 16713938 20191213 parent-grant-document US 10935591 child US 17162025  
parent US division 16047263 20180727 parent-grant-document US 10539606 child US 16713938  
parent US division 15616476 20170607 parent-grant-document US 10067188 child US 16047263  
parent US division 14590502 20150106 parent-grant-document US 9709630 child US 15616476  
parent US division 13765260 20130212 parent-grant-document US 8977919 child US 14590502

## Publication Classification

**Int. Cl.:** **G01R31/26** (20200101); **G01R31/3177** (20060101); **G01R31/3185** (20060101)

**U.S. Cl.:**

**CPC** **G01R31/2607** (20130101); **G01R31/3177** (20130101); **G01R31/318513** (20130101);  
**G01R31/318558** (20130101); **G01R31/318572** (20130101); G01R31/318552  
(20130101); G01R31/318594 (20130101)

---

## Background/Summary

RELATED APPLICATIONS [0001] This application is a divisional of prior application Ser. No. 18/754,683, filed Jun. 26, 2024, currently pending; [0002] Which was a divisional of prior application Ser. No. 18/226,924, filed Jul. 27, 2023, now U.S. Pat. No. 12,025,649, granted Jul. 2, 2024; [0003] Which was a divisional of prior application Ser. No. 17/858,122, filed Jul. 6, 2022, now U.S. Pat. No. 11,726,135, granted Aug. 15, 2023; [0004] Which was a divisional of prior application Ser. No. 17/162,025, filed Jan. 29, 2021, now U.S. Pat. No. 11,391,769, granted Jul. 19, 2022; [0005] Which was a divisional of prior application Ser. No. 16/713,938, filed Dec. 13, 2019, now U.S. Pat. No. 10,935,591, granted Mar. 2, 2021; [0006] Which was a divisional of prior application Ser. No. 16/047,263, filed Jul. 27, 2018, now U.S. Pat. No. 10,539,606, granted Jan. 21, 2020; [0007] Which was a divisional of prior application Ser. No. 15/616,476, filed Jun. 7, 2017, now U.S. Pat. No. 10,067,188, granted Sep. 4, 2018; [0008] Which was a divisional of prior application Ser. No. 14/590,502, filed Jan. 6, 2015, now U.S. Pat. No. 9,709,630, granted Jul. 18, 2017; [0009] Which was a divisional of prior application Ser. No. 13/765,260, filed Feb. 12, 2013, now U.S. Pat. No. 8,977,919, granted Mar. 10, 2015; [0010] Which claims priority from Provisional Application No. 61/654,207, filed Jun. 1, 2012; [0011] And also claims priority from Provisional Application No. 61/601,292, filed Feb. 21, 2012, each of which is incorporated by reference in its entirety.

[0012] This disclosure is related to pending patent application TI-71343 which is incorporated herein by reference.

### FIELD OF DISCLOSURE

[0013] This disclosure relates to die that are designed to be used in a 3D die stack and in particular to a common test architecture designed into each die of the 3D die stack for accessing and testing digital circuits of each die using parallel scan techniques.

### BACKGROUND OF THE DISCLOSURE

[0014] Die manufactured for use in a die stack must be tested at the wafer level and then potentially retested after the die are singulated to ensure only known good die are used in the stack. Each time an upper die is stacked on top of a lower die that has been tested, the upper die needs to be retested to ensure it has not been damaged during the stacking process. Also, the interconnect between the lower and upper die needs to be tested and determined good. The interconnect between die in a 3D stack is provided by Through Silicon Vias (TSVs), which are vertical signaling paths between the bottom and top surfaces of each die. This testing process is repeated for each additional upper die assembled onto the stack. It is therefore advantageous to have a common test architecture in each die and a common method of accessing the test architecture in each die, independent of the stacked

location of the die.

## BRIEF SUMMARY OF THE DISCLOSURE

[0015] The disclosure provides a test architecture for providing access to and control of parallel scan paths within a single die or to parallel scan paths in dies that are stacked.

---

## Description

### DESCRIPTIONS OF THE VIEWS OF THE DISCLOSURE

[0016] FIG. 1 illustrates a die containing the test architecture of the disclosure.

[0017] FIG. 2 illustrates a conventional parallel scan path arrangement that can be accessed and controlled by the test architecture of the disclosure.

[0018] FIG. 3 illustrates a conventional parallel scan compression arrangement that can be accessed and controlled by the test architecture of the disclosure.

[0019] FIG. 4 illustrates a test circuit of the disclosure for either outputting parallel test output data to a tester or comparing the parallel test output data to data input from a tester.

[0020] FIG. 5 illustrates a first example implementation of the comparator of FIG. 4 of the disclosure.

[0021] FIG. 6 illustrates a second example implementation of the comparator of FIG. 4 of the disclosure.

[0022] FIG. 7 illustrates a first example implementation of the test control port (TCP) of the disclosure.

[0023] FIG. 8 illustrates a second example implementation of the TCP of the disclosure.

[0024] FIG. 9 illustrates the test architecture in a die operating to input parallel test input data to a parallel scan test circuit in the die and outputting parallel test output data from the parallel test circuit, according to the disclosure.

[0025] FIG. 10 illustrates the test architecture operating to input parallel test input data to a parallel test circuit and comparing the parallel test output data with data input to the test circuit, according to the disclosure.

[0026] FIG. 11 illustrates a stack die arrangement where the lower die is tested as described in FIG. 9, according to the disclosure.

[0027] FIG. 12 illustrates a stack die arrangement where the lower die is tested as described in FIG. 10, according to the disclosure.

[0028] FIG. 13 illustrates a stack die arrangement where the upper die is tested as described in FIG. 9, via the lower die, according to the disclosure.

[0029] FIG. 14 illustrates a stack die arrangement where the upper die is tested as described in FIG. 10, via the lower die, according to the disclosure.

[0030] FIG. 15 illustrates a stack die arrangement where the parallel scan circuits of the lower and upper die are daisy-chained together and tested as described in FIG. 9, according to the disclosure.

[0031] FIG. 16 illustrates a stack die arrangement where the parallel scan circuits of the lower and upper die are daisy-chained together and tested as described in FIG. 10, according to the disclosure.

[0032] FIG. 17 illustrates a die containing multiple selectable parallel scan circuits that may be tested as described in FIG. 9 or FIG. 10, according to the disclosure.

[0033] FIG. 18 illustrates the die of FIG. 17 further illustrating the TCP of the disclosure for clarity.

[0034] FIG. 19 illustrates an alternate implementation of the TCP of FIG. 7.

[0035] FIG. 20 illustrates the TCP of FIG. 19 where the state machine is an IEEE standard 1149.1 Tap state machine.

[0036] FIG. 21 illustrates an alternate implementation of the TCP of FIG. 8.

[0037] FIG. 22 illustrates the TCP of FIG. 21 where the Test Control Inputs (TCI) inputs include IEEE standard 1500 signals.

[0038] FIG. 23 illustrates a die including the test architecture of the disclosure where the Parallel Test Input (PTI) and Parallel Test Inputs and Outputs (PTIO) are shared for both test and functional signaling.

[0039] FIG. 24 illustrates the die of FIG. 23 where a multiplexer is substituted for buffers “a” and “b”.

#### DETAILED DESCRIPTION OF THE DISCLOSURE

[0040] FIG. 1 illustrates a die 100 including the test architecture of the disclosure. The bottom surface of the die includes signal contact points (micro bumps or metal pads) for a Parallel Test Input (PTI) bus 102, a Test Data input (TDI) 104, Test Control Inputs (TCI) 106, a Test Data Output 108 and a Parallel Test Input/Output (PTIO) bus 110. The top surface of the die includes signal contact points for a Parallel Test Output (PTO) bus 112, TDO 114, Test Control Outputs (TCO) 116, TDI 118 and a PTIO bus 120. The architecture includes a Test Control Port (TCP) 122, a Test Circuit (TC) 124, at least one Parallel Scan Circuit 126 to be tested, a first signal coupling means illustrated in this example as signal buffers “a” 128 and a second signal coupling means illustrated in this example as signal buffers “b” 130. TCP is connected to the TDI, TCI and TDO bottom surface signals and the TDO, TCO and TDI top surface signals. TCP includes a control (CTL) output bus 131 that is connected to the buffers, Parallel Scan Circuit and TC.

[0041] The Parallel Scan Circuit inputs PTI signals from the PTI bus 102 via TSV signal connections 132 and outputs PTO signals to buffers “b” and to the TC. The TC is connected to the PTIO bus TSV signal connections 134 for outputting data onto the PTIO 110 bus or inputting data from the PTIO bus 120. The outputs of buffers “a” and “b” are connected together and to the top surface PTO bus 112 via TSV signal connections 136. If the top surface PTO bus 112 is to be driven from the bottom PTO bus, buffers “a” are enabled by an enable 3 (E3) signal from the TCP CTL bus 131 and buffers “b” are disabled by enable 4 (E4) from the TCP CTL bus 131. If the top surface PTO bus 112 is to be driven by the PTO output 138 of the Parallel Scan Circuit, buffers “b” are enabled by E4 and buffers “a” are disabled by E3.

[0042] While the first and second signal coupling means are shown to be buffers “a” 128 and “b” 130, the first and second coupling means could be realized using other types of circuitry such as but not limited to a multiplexer or transistor switches to allow the PTO bus 112 to be driven by either the PTI bus 102 or by the PTO bus 138 output from the Parallel Scan Circuit.

[0043] FIG. 2 illustrates one example implementation of the Parallel Scan Circuit 126 of FIG. 1. In this example, scan paths 202 input test data from PTI and output test data to PTO. The scan paths are controlled by the CTL inputs from the TCP.

[0044] FIG. 3 illustrates another example implementation of the Parallel Scan Circuit 126 of FIG. 1. In this example, a decompressor (D) 302 inputs compressed test data from PTI and outputs decompressed test data to parallel scan paths 304, and a compactor (C) 306 inputs test data from the parallel scan paths and outputs compacted data on PTO. The decompressor, scan paths and compactor are controlled by the CTL inputs from the TCP.

[0045] While not shown in FIGS. 2 and 3, system clock inputs and associated circuitry may be used in conjunction with the TCP CTL signals to improve the at-speed testing of the circuits, such as well known clock leaker system clock circuits.

[0046] FIG. 4 illustrates an example implementation of the TC 124 of FIG. 1. In a first mode of operation, the TC inputs PTO data 138 from the Parallel Scan Circuit and outputs it to the PTIO bus 134, via 3-state buffers 402 1-N. In a second mode of operation, the TC inputs PTO data from the Parallel Scan Circuit and compares it to data input from the PTIO bus, using comparators (C) 404 1-N. The modes are controlled by enable (E1 and E2) inputs from the CTL bus of the TCP. The comparators (C) have fail 405 1-N outputs that are set whenever a comparison failure occurs. The fail outputs are input to a gating circuit 406 that can detect when one or more fail outputs are set to indicate a failure. The output of the gating circuit passes through a 3-state buffer 408 to a Compare Fail Output (CFO) 410 that is connected to a signal path in the PTIO bus. The second mode of

operation is advantageous at wafer probe since it enables multiple dies to be tested using a common PTI and PTIO bus from a tester to input test data to multiple die commonly connected to the PTI and PTIO buses.

[0047] FIG. 5 illustrates a first example comparator (C) **404** of FIG. 4 for comparing PTO data to expected (EXP) data from the PTIO bus.

[0048] FIG. 6 illustrates a second example maskable comparator (C) **404** of FIG. 4 for comparing PTO data to expected (EXP) data from the PTIO bus or masking the compare operation off using mask (MSK) data input from the PTIO bus. When masked, the Fail signal output does not output a failure indication when a comparison fails.

[0049] FIG. 7 illustrates a first example implementation of the TCP **122** of FIG. 1 which includes a state machine (SM) **702**, an instruction register (IR) **704**, data registers (DRs) **706**, a gating circuit **708** and a TDO multiplexer (MX) **710**. The SM inputs TCI signals **714** and outputs instruction register control (IRC) signals to the IR and data register control (DRC) signals to the DR. During instruction scans, the IR is enabled by IRC inputs to input data from TDI **712** and output data to the TDO multiplexer **710** and the top surface TDO signal **718**. During data scans, a DR is enabled by the DRC inputs to input data from TDI **712** and output data to the TDO multiplexer **710** and the top surface TDO signal **718**.

[0050] The bottom surface TCI inputs **714** may be coupled to the top surface TCO signals **720** via the gating circuit **708**. The top surface TDI signal **722** may be coupled to the bottom surface TDO signal **716** via TDO multiplexer **710**. This allows concatenating or daisy-chaining the IR and DR of a TCP of a lower die with an IR and DR of a TCP of a die stacked on top of the lower die. The instruction register outputs (IRO) include an enable (ENA) signal for the gating circuit **708** and a second select (SEL) signal for TDO multiplexer **710**. The CTL bus output from the TCP includes IRO signals and DRC signals. The gating circuit **708** may gate one, more than one or all of the TCI signals. Non-gated TCI signals are coupled to appropriate top surface TCO signals, as shown in dotted line. The SM, IR, and DRs of this implementation could be the TAP SM, IR and DRs as defined in the IEEE 1149.1 boundary scan standard.

[0051] FIG. 8 illustrates a second example implementation **800** of the TCP **122** of FIG. 1. This implementation is identical to the FIG. 7 implementation with the exception that it does not include a SM **702**. The TCI inputs **802** are coupled to the IRC inputs of IR **704** and DRC inputs of DR **706**. During instruction scans, the IR is enabled by the IRC signals from the TCI inputs **802** to input data from TDI **712** and output data to the TDO multiplexer **710** and the top surface TDO signal **718**. During data scans, a DR is enabled by DRC signals from the TCI inputs **802** to input data from TDI **712** and output data to the TDO multiplexer **710** and the top surface TDO signal **718**.

[0052] The bottom surface TCI inputs **802** may be coupled to the top surface TCO signals **720** via the gating circuit **708**. The top surface TDI signal **722** may be coupled to the bottom surface TDO signal **716** via the TDO multiplexer **710**. This allows concatenating or daisy-chaining the IR and DR of a TCP **122** of a lower die with an IR and DR of a TCP **122** of a die stacked on top of the lower die. The instruction register outputs (IRO) include an enable (ENA) signal for the gating **708** circuit and the SEL signal to TDO multiplexer **710**. The CTL bus output **724** from the TCP includes IRO signals and DRC signals. The gating circuit **708** may gate one, more than one or all of the TCI signals. Non-gated TCI signals are coupled to appropriate top surface TCO signals, as shown in dotted line. The TCI input bus **802**, IR **704** and DRs **706** of this implementation could be the control inputs, IR and DRs as defined in IEEE 1500 core wrapper test standard.

[0053] FIG. 9 illustrates the die test architecture of FIG. 1 when an instruction has been loaded into the TCP's IR to enable the Parallel Scan Circuit to be tested by inputting PTI data from the PTI bus **102** and outputting PTO data to the PTIO bus **110**, as seen in darkened line. The CTL outputs **131** from the TCP **122** controls the capture and input and output shift operations of Parallel Scan Circuit **126** during test.

[0054] FIG. 10 illustrates the die test architecture of FIG. 1 when an instruction has been loaded

into the TCP's IR to enable the Parallel Scan Circuit **126** to be tested by inputting PTI data from the PTI bus **102** and comparing the PTO output data from the Parallel Scan Path **126** with data input from the PTIO bus **110**, as seen in darkened line. The CTL outputs from the TCP **122** controls the capture and input and output shift operations of Parallel Scan Circuit **126** during test. During this test, the CFO output **410** (dotted line) of the TC **124** of FIG. **4** is enabled to output comparison failures on the PTIO bus **110**.

[0055] FIG. **11** illustrates a stack **1100** including a bottom die **100** and a top die **1102**, both including the die test architecture of FIG. **1**. In this example, the Parallel Scan Circuit **126** of the bottom die **100** is being tested as described in FIG. **9**. The IR of the TCP **1122** of the top die has been loaded with an instruction which place the top die in a quiescent mode that ignores the testing of the bottom die, does not interfere with the testing of the bottom die and disables the tri-state buffers of TC **1124** of the top die. The TCO outputs **116** from the bottom die to the TCI inputs **1106** of the top die will typically be gated off during testing of the bottom die.

[0056] FIG. **12** illustrates a stack **1100** including a bottom die **100** and a top die **1102**, both including the die test architecture of FIG. **1**. In this example, the Parallel Scan Circuit **126** of the bottom die **100** is being tested as described in FIG. **10**. The IR of the TCP **1122** of the top die **1102** has been loaded with an instruction which places the top die in a quiescent mode that ignores the testing of the bottom die, does not interfere with the testing of the bottom die and disables the tri-state buffers of TC **1124** of the top die. The TCO outputs **116** from the bottom die to the TCI inputs **1106** of the top die will typically be gated off during testing of the bottom die.

[0057] FIG. **13** illustrates a stack **1100** including a bottom die **100** and a top die **1102**, both including the die test architecture of FIG. **1**. In this example, the Parallel Scan Circuit **1126** of the top die **1102** is being tested as described in FIG. **9**. The IR of the TCP **122** of the bottom die **100** has been loaded with an instruction which place the bottom die **100** in a quiescent mode that ignores the testing of the top die **1102**, does not interfere with the testing of the top die, disables the tri-state buffers of TC **124** of the bottom die and enables buffers "a" **128** to pass the PTI signals up to the top die. The TCO outputs from the bottom die **100** to the top die **1102** will be gated on during testing of the top die to control the top die's TCP **1122**.

[0058] FIG. **14** illustrates a stack **1100** including a bottom die **100** and a top die **1102**, both including the die test architecture of FIG. **1**. In this example, the Parallel Scan Circuit **1126** of the top die **1102** is being tested as described in FIG. **10**. The IR of the TCP **122** of the bottom die **100** has been loaded with an instruction which place the bottom die in a quiescent mode that ignores the testing of the top die, does not interfere with the testing of the top die, disables the tri-state buffers of TC **124** of the bottom die and enables buffers "a" **128** to pass the PTI signals up to the top die. The TCO outputs from the bottom die **100** to the top die **1102** will be gated on during testing of the top die to control the top die's TCP **1122**.

[0059] FIG. **15** illustrates a stack **1100** including a bottom die **100** and a top die **1102**, both including the die test architecture of FIG. **1**. In this example, instructions have been loaded into the IRs of the TCPs **122**, **1122** of the bottom and top die to daisy-chain the Parallel Scan Circuits **126**, **1126** of the bottom and top die together to form a PTI to PTO path through both Parallel Scan Circuits, from the PTI **102** of the bottom die to the PTIO **110** of the bottom die. The instruction loaded in the bottom die TCP **122** enables buffers "b" **130** to drive the PTI inputs to the top die, disables the tri-state buffers of TC **124** of the bottom die and gates on the TCO outputs **116** to the TCI inputs **1116** of the top die. The instruction in the TCP of the top die enables the tri-state buffers of TC **1124** of the top die to drive the PTIO bus **1134**, **134**, **110**.

[0060] FIG. **16** illustrates a stack **1100** including a bottom die **100** and a top die **1102**, both including the die test architecture of FIG. **1**. In this example, instructions have been loaded into the IRs of the TCPs **122**, **1122** of the bottom and top die to daisy-chain the Parallel Scan Circuits **126**, **1126** of the bottom and top die together to form a PTI to PTO path through both Parallel Scan Circuits, from the PTI **102** of the bottom die to the PTO inputs to TC **1124** of the top die. The

instruction loaded in the bottom die TCP **122** enables buffers “b” **130** to drive the PTI inputs to the top die, disables the tri-state buffers of TC **124** of the bottom die and gates on the TCO **116** outputs to the TCI inputs **1106** of the top die. The instruction in the TCP **1122** of the top die disables the tri-state buffers of TC **1124** of the top die so that data from PTIO **110** can be input to the comparators of TC **1124** to compare against the PTO data being input to the comparator from the Parallel Scan Circuit **1126** of the top die.

[0061] While the stack die examples of FIGS. **11-16** show only two dies including the test architecture of the disclosure in the stack, the stack could contain any number of stacked dies including the test architecture of the disclosure.

[0062] While in the preceding Figure examples, only one Parallel Scan Circuit **126** was shown in a die, any number of Parallel Scan Circuits may be included in a die and tested using the test architecture of the disclosure. FIG. **17** below shows one preferred way of accessing plural Parallel Scan Circuits in a die.

[0063] FIG. **17** illustrates multiple Parallel Scan Circuits **126a**, **126b** in a die **1700** outputting their PTO outputs to a multiplexer **1702**. The PTO outputs of the Parallel Scan Circuit to be tested are selected by the multiplexer **1702** to be output on the PTO bus to the TC **124** and to the inputs of buffers “b” **130**. Multiplexer **1702** is controlled by PTO select (PTOSEL) signals from the IRO part of the CTL bus of the TCP **122**. The multiplexer **1702** allows multiple Parallel Scan Circuits to share a common TC **124**, which reduces test circuit overhead in the die **100**.

[0064] FIG. **18** is the same as FIG. **17** but it includes the TCP **1822** to more clearly illustrate the TCP CTL outputs being connected buffers “a” **128** and “b” **130**, Parallel Scan Circuits **126a**, **126b**, multiplexer **1702** and TC **124**.

[0065] FIG. **19** illustrates a third example implementation of the TCP **122** of FIG. **1**, similar to the first example implementation of FIG. **7**. This third example implementation TCP **1900** includes a state machine (SM) **702**, an instruction register (IR) **704**, data registers (DRs) **706**, a gating circuit **708**, first TDO multiplexer (MX) **1912** and a second TDO multiplexer (MX) **710**. The SM inputs TCI signals and outputs instruction register control (IRC) signals to the IR, data register control (DRC) signals to the DR and a first select (SEL) signal to the first multiplexer **1912**. During instruction scans, the IR inputs data from TDI and outputs data to the TDO multiplexer **710** and the top surface TDO signal **718**, via TDO multiplexer **1912**. During data scans, a DR inputs data from TDI and outputs data to the TDO multiplexer **710** and the top surface TDO signal **718**, via TDO multiplexer **1912**.

[0066] The bottom surface TCI inputs **714** may be coupled to the top surface TCO signals **720** via the gating circuit **708**. The top surface TDI signal **722** may be coupled to the bottom surface TDO signal **716** via TDO multiplexer **710**. This allows concatenating or daisy-chaining the IR and DR of a TCP of a lower die with an IR and DR of a TCP of a die stacked on top of the lower die. The instruction register outputs (IRO) include an enable (ENA) signal for the gating circuit and a second select (SEL) signal for TDO multiplexer **710**. The CTL bus output from the TCP includes IRO signals and DRC signals. The gating circuit **708** may gate one, more than one or all of the TCI signals. Non-gated TCI signals are coupled to appropriate top surface TCO signals, as shown in dotted line. The SM, IR, and DRs of this implementation could be the TAP SM, IR and DRs as defined in the IEEE 1149.1 boundary scan standard.

[0067] FIG. **20** illustrates the TCP **2000** of FIG. **19** where the SM **702** is realized as an IEEE standard 1149.1 Tap State Machine (TSM) **2002**. The TCI inputs **714** to the TSM **2002** include a test clock (TCK) **2004** and test mode select (TMS) signal **2006**. The gating circuit **708** may gate the TMS signal, the TCK signal or both the TMS and TCK signals. Non-gated TCI signals are coupled to appropriate top surface TCO signals, as shown in dotted line.

[0068] FIG. **21** illustrates a fourth example implementation **2100** of the TCP **122** of FIG. **1**. This implementation is identical to the FIG. **19** implementation with the exception that it does not include a SM **702**. The TCI inputs are coupled to the IRC inputs of IR **704**, the DRC inputs of DRs

**706** and SEL input of TDO multiplexer **1912**. During instruction scans, the IR is controlled by IRC signals from the TCI inputs to input data from TDI **712** and output data to the TDO multiplexer **710** and the top surface TDO signal **718**, via TDO multiplexer **1912**. During data scans, a DR is controlled by the DRC signals from the TCI inputs **714** to input data from TDI **712** and output data to the TDO multiplexer **710** and the top surface TDO signal **718**, via TDO multiplexer **1912**.

[0069] The bottom surface TCI inputs **714** may be coupled to the top surface TCO signals **720** via the gating circuit **708**. The top surface TDI signal **722** may be coupled to the bottom surface TDO signal **716** via the TDO multiplexer **710**. This allows concatenating or daisy-chaining the IR and DR of a TCP of a lower die with an IR and DR of a TCP of a die stacked on top of the lower die. The instruction register outputs (IRO) include an enable (ENA) signal for the gating circuit and the SEL signal to TDO multiplexer **710**. The CTL bus output from the TCP includes IRO signals and DRC signals. The gating circuit **708** may gate one, more than one or all of the TCI signals. Non-gated TCI are coupled to appropriate top surface TCO signals, as shown in dotted line. The TCI input bus **714**, IR and DRs of this implementation could be the control inputs, IR and DRs as defined in IEEE 1500 core wrapper test standard.

[0070] FIG. **22** illustrates the TCP **2200** of FIG. **21** where the TCI inputs **714** are defined to be the wrapper control input signals defined in IEEE standard 1500, which includes a wrapper clock (WRCK) signal, select wrapper instruction register (SelectWIR) signal, shift wrapper (ShiftWR) signal, capture wrapper (CaptureWR) signal, update wrapper (UpdateWR) signal and reset wrapper (ResetWR) signal. The wrapper instruction register (WIR) **2202** is the same as the IR of FIG. **8**, it is just labeled WIR by IEEE 1500. The gating circuit **708** may gate one, more than one or all of the TCI signals. Non-gated TCI signals are coupled to appropriate top surface TCO signals, as shown in dotted line.

[0071] FIG. **23** illustrates a die **2302** including the test architecture of the disclosure. Die **2302** differs from die **100** of FIG. **1** as follows; (1) the PTI TSVs **132** are shared between inputting PTI signals **102** to the test architecture and inputting functional data input (FDI) signals **2310** to functional circuitry (FC) **2304** of the die, (2) the PTO TSVs **136** are shared between outputting PTO signals **112** from the test architecture and outputting function data output (FDO) signals **2312** from the FC **2304** and (3) the PTIO TSVs **134** are shared between inputting or outputting PTIO **110**, **120** signals to the test architecture and inputting or outputting functional data input/output (FDIO) signals **2314**, **2316** to functional circuitry (FC) **2306** of the die. When the die is in functional mode, an instruction in the TCP **122** will disable buffers “a” **128** and “b” **130** and disable the buffers in the TC **124**.

[0072] In functional mode, FDI can be input to FC **2304** via TSVs **132**, FDO can be output from FC **2304** via TSVs **136** and FDIO can be input and output to FC **2306** via TSVs **134**. When the die is in test mode, an instruction in the TCP **122** will disable the outputs of FC **2304** and **2306** using an enable signal (E5) from the CTL output of TCP **122**. In test mode, PTI can be input to the test architecture via TSVs **132**, PTO can be output from the test architecture via TSVs **136** and PTIO can be input to or output from the test architecture via TSVs **134**, as previously described.

[0073] FIG. **24** illustrates a die **2402** include the test architecture of the disclosure. The only difference between the die **2302** of FIG. **23** and die **2402** of FIG. **24** is that a 3-state multiplexer **2404** is shown being used in die **2402** in place of buffers “a” and “b”. The E3 input to the multiplexer selects either PTI data from TSVs **132** or the PTO data from the Parallel Scan Circuit to be output to TSVs **136**. The E4 input to the multiplexer enables or disables the multiplexer outputs to TSVs **136**. The multiplexer operates the same as the buffers “a” and “b” described in FIG. **23**.

[0074] In this disclosure the words connected and coupled both mean a “link” formed between elements mentioned in this disclosure. The elements could be, but are not limited to circuits, buses and contact points. The links may be direct links such as links formed between two elements by a



wire or they may be indirect links such as a links formed between elements through intermediate circuitry, registered circuitry or buffered circuitry for example.

## Claims

1. A device comprising: a first die including: parallel test output (PTO) contacts; a first parallel scan circuit coupled to the PTO contacts; and first functional circuitry coupled to the PTO contacts and configurable to share the PTO contacts with the first parallel scan circuit; and a second die coupled to the first die, wherein the second die includes: parallel test input (PTI) contacts coupled to the PTO contacts on the first die; a second parallel scan circuit coupled to the PTI contacts; and second functional circuitry coupled to the PTI contacts and configurable to share the PTI contacts with the second parallel scan circuit.
2. The device of claim 1, wherein the PTI contacts are shared between inputting test data to the second parallel scan circuit and inputting functional data to the second functional circuitry.
3. The device of claim 1, wherein the PTO contacts are shared between outputting test data from the first parallel scan circuit and outputting functional data from the first functional circuitry.
4. The device of claim 1, wherein the first die includes: a first buffer coupled between the PTO contacts and the first parallel scan circuit; and a second buffer coupled between the first parallel scan circuit and the PTO contacts.
5. The device of claim 1, wherein the first parallel scan circuit is configurable to output test data to the PTO contacts.
6. The device of claim 1, wherein the first parallel scan circuit includes an input, wherein the first die includes: a first buffer coupled between the PTO contacts and the first parallel scan circuit; and a test control port configurable to: enable the first buffer in a test mode; and disable the first buffer in a functional mode.
7. The device of claim 6, wherein the first parallel scan circuit includes an output, wherein the first die includes a second buffer coupled between the first parallel scan circuit and the PTO contacts, and wherein the test control port is configurable to: enable the second buffer in the test mode; and disable the second buffer in the functional mode.
8. The device of claim 1, wherein the first die includes a first multiplexer coupled to the PTO contacts, the first parallel scan circuit, and the first functional circuitry, and wherein the second die includes a second multiplexer coupled to the PTI contacts, the second parallel scan circuit, and the second functional circuitry.
9. The device of claim 1, wherein the first die includes: a multiplexer coupled to the PTO contacts; and a test control port configurable to: enable the multiplexer in a test mode; and disable the multiplexer in a functional mode.
10. The device of claim 1, wherein the first die includes a first test control port (TCP), wherein when the device is powered on, the first TCP is configurable to enter a first functional mode, and wherein after entering the first functional mode, the first TCP is configurable to enter a first test mode in response to an external input.
11. The device of claim 10, wherein the second die includes a second TCP, wherein when the device is powered on, the second TCP is configurable to enter a second functional mode, and wherein after entering the second functional mode, the second TCP is configurable to enter a second test mode in response to the external input.
12. The device of claim 1, wherein the second die includes: parallel test input/output (PTIO) contacts coupled to the first die; and a test control port configurable to allow the second parallel scan circuit to output test data to the PTIO contacts.
13. The device of claim 12, wherein the second die further comprises third functional circuitry coupled to the PTIO contacts.
14. The device of claim 1, wherein the first die includes parallel test input/output (PTIO) contacts,

wherein the first parallel scan circuit is configurable to output response test data based on stimulus test data, and wherein the first die further includes a test circuit configurable to: receive test comparison data from the PTIO contacts; receive the response test data from the first parallel scan circuit; and output comparison failure data to the PTIO contacts based on the response test data and the test comparison data.

**15.** The device of claim 14, wherein the first die includes: second PTIO contacts coupled to the second die; and a test control port configurable to allow the first parallel scan circuit to output test data to the PTO contacts, wherein the first die is configurable to: receive additional test data from the first PTIO contacts; and output the additional test data to the second PTIO contacts.

**16.** A device comprising: a first die including: parallel test output (PTO) contacts; first parallel test input/output (PTIO) contacts; a first parallel scan circuit coupled to the PTO contacts; first functional circuitry coupled to the PTO contacts and configurable to share the PTO contacts with the first parallel scan circuit; and second functional circuitry coupled to the first PTIO contacts and configurable to share the first PTIO contacts with the first parallel scan circuit; and a second die coupled to the first die, wherein the second die includes: parallel test input (PTI) contacts coupled to the PTO contacts on the first die; second PTIO contacts coupled to the first PTIO contacts; a second parallel scan circuit coupled to the PTI contacts; third functional circuitry coupled to the PTI contacts and configurable to share the PTI contacts with the second parallel scan circuit; and fourth functional circuitry coupled to the second PTIO contacts and configurable to share the second PTIO contacts with the second parallel scan circuit.

**17.** The device of claim 16, wherein the first die includes a first test circuit coupled to the first PTIO contacts and the first parallel scan circuit, and wherein the second die includes a second test circuit coupled to the second PTIO contacts and the second parallel scan circuit.

**18.** The device of claim 16, wherein the first die includes: a first buffer coupled between the PTO contacts and the first parallel scan circuit; and a second buffer coupled between the first parallel scan circuit and the PTO contacts.

**19.** The device of claim 16, wherein the first die includes a first multiplexer coupled to the PTO contacts, the first parallel scan circuit, and the first functional circuitry, and wherein the second die includes a second multiplexer coupled to the PTI contacts, the second parallel scan circuit, and the second functional circuitry.

**20.** The device of claim 16, wherein when the device is powered on, the first die is configured to enter a first functional mode, and wherein after entering the first functional mode, the first die is configured to enter a first test mode in response to an external input.

---