

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12391634
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Pigamo; Anne et al.

Method for producing 1-chloro-3,3,3-trifluoropropene

Abstract

A composition including at least 98 mol % of (E/Z)-1-chloro-3,3,3-trifluoropropene and less than 0.5 mol % of coproducts selected from 1,3,3,3-tetrafluoropropene and 1,1,1,3,3-pentafluoropropane. A composition obtained from a process for producing 1-chloro-3,3,3-trifluoropropene, including the step i) of contacting hydrofluoric acid (HF) in a reactor with a starting composition including at least one of the chloro compounds selected from 1,1,3,3-tetrachloropropene (1230za), 1,3,3,3-tetrachloropropene (1230zd) and 1,1,1,3,3-pentachloropropane (240fa), or a mixture thereof, to produce a stream A including 1-chloro-3,3,3-trifluoropropene (1233zd), wherein the step i) is carried out in a low-HF liquid phase.

Inventors: Pigamo; Anne (Pierre-Benite, FR), Lavy; Cédric (Pierre-Benite, FR)

Applicant: Arkema France (Colombes, FR)

Family ID: 1000008765776

Assignee: Arkema France (Puteaux, FR)

Appl. No.: 17/557668

Filed: December 21, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20220112145 A1	Apr. 14, 2022

Foreign Application Priority Data

FR	1854069	May. 16, 2018
----	---------	---------------

Related U.S. Application Data

Publication Classification

Int. Cl.: C07C21/18 (20060101); C07C17/20 (20060101)

U.S. Cl.:

CPC C07C21/18 (20130101); C07C17/206 (20130101); C07C17/206 (20130101); C07C21/18 (20130101);

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2583812	12/1951	Briggs et al.	N/A	N/A
2882243	12/1958	Milton	N/A	N/A
4013566	12/1976	Taylor	N/A	N/A
5616819	12/1996	Boyce et al.	N/A	N/A
5684219	12/1996	Boyce et al.	N/A	N/A
5705779	12/1997	Demmin et al.	N/A	N/A
5877359	12/1998	Elsheikh	570/160	C07C 17/00
6166274	12/1999	Bolmer et al.	N/A	N/A
6403847	12/2001	Nakada et al.	N/A	N/A
8404907	12/2012	Nair et al.	N/A	N/A
8426656	12/2012	Tung et al.	N/A	N/A
8436217	12/2012	Tung et al.	N/A	N/A
8704017	12/2013	Pokrovski et al.	N/A	N/A
8877990	12/2013	Fukuju et al.	N/A	N/A
9255045	12/2015	Bonnet et al.	N/A	N/A
9643903	12/2016	Pokrovski et al.	N/A	N/A
9834499	12/2016	Pigamo et al.	N/A	N/A
10077221	12/2017	Bonnet et al.	N/A	N/A
10227275	12/2018	Pigamo et al.	N/A	N/A
10335623	12/2018	Kennoy	N/A	C11D 7/5018
10343963	12/2018	Bonnet et al.	N/A	N/A
10427998	12/2018	Pigamo et al.	N/A	N/A
10532965	12/2019	Pigamo et al.	N/A	N/A
10669465	12/2019	Rached	N/A	N/A
10858561	12/2019	Abbas et al.	N/A	N/A
11028027	12/2020	Wendlinger et al.	N/A	N/A
11034635	12/2020	Wendlinger et al.	N/A	N/A

11084768	12/2020	Wendlinger et al.	N/A	N/A
11242304	12/2021	Pigamo et al.	N/A	N/A
11286221	12/2021	Hisler et al.	N/A	N/A
2001/0014707	12/2000	Thomas et al.	N/A	N/A
2010/0191025	12/2009	Perdrieux et al.	N/A	N/A
2011/0196178	12/2010	Nyberg	N/A	N/A
2011/0197602	12/2010	Abbas et al.	N/A	N/A
2011/0201853	12/2010	Tung et al.	N/A	N/A
2011/0218370	12/2010	Elsheikh et al.	N/A	N/A
2011/0245549	12/2010	Merkel et al.	N/A	N/A
2011/0259828	12/2010	Bouvier et al.	N/A	N/A
2012/0059199	12/2011	Pokrovski et al.	N/A	N/A
2012/0172636	12/2011	Pokrovski	570/135	C07C 17/361
2012/0190902	12/2011	Nyberg	N/A	N/A
2012/0226081	12/2011	Elsheikh et al.	N/A	N/A
2012/0256119	12/2011	Bouvier et al.	N/A	N/A
2012/0256120	12/2011	Bouvier et al.	N/A	N/A
2012/0261485	12/2011	Mickos	N/A	N/A
2012/0271070	12/2011	Wang et al.	N/A	N/A
2012/0329893	12/2011	Abbas et al.	N/A	N/A
2013/0035410	12/2012	Chen	521/131	C08J 9/144
2013/0037058	12/2012	Abbas et al.	N/A	N/A
2013/0211154	12/2012	Cottrell et al.	N/A	N/A
2013/0261353	12/2012	Pokrovski et al.	N/A	N/A
2013/0261354	12/2012	Merkel et al.	N/A	N/A
2014/0213831	12/2013	Nyberg	N/A	N/A
2014/0221704	12/2013	Tung et al.	N/A	N/A
2014/0264173	12/2013	Merkel et al.	N/A	N/A
2015/0152235	12/2014	Abbas	N/A	N/A
2015/0197467	12/2014	Bonnet et al.	N/A	N/A
2016/0023974	12/2015	Bonnet et al.	N/A	N/A
2016/0115104	12/2015	Pigamo et al.	N/A	N/A
2016/0272561	12/2015	Rached et al.	N/A	N/A
2017/0050904	12/2016	Ondrus et al.	N/A	N/A
2017/0081263	12/2016	Klausmeyer et al.	N/A	N/A
2017/0174965	12/2016	Tsuchiya et al.	N/A	N/A
2017/0210686	12/2016	Pigamo et al.	N/A	N/A
2018/0015407	12/2017	Vittenet et al.	N/A	N/A
2018/0093934	12/2017	Pigamo et al.	N/A	N/A
2018/0148394	12/2017	Pigamo et al.	N/A	N/A
2018/0346396	12/2017	Pigamo et al.	N/A	N/A
2018/0354875	12/2017	Bonnet et al.	N/A	N/A
2019/0048241	12/2018	Abbas et al.	N/A	N/A
2019/0152883	12/2018	Pigamo et al.	N/A	N/A
2019/0276721	12/2018	Rached	N/A	N/A
2019/0375698	12/2018	Pigamo et al.	N/A	N/A
2020/0407293	12/2019	Wendlinger et al.	N/A	N/A
2021/0002188	12/2020	Wendlinger et al.	N/A	N/A
2021/0002189	12/2020	Wendlinger et al.	N/A	N/A

2021/0238112	12/2020	Pigamo et al.	N/A	N/A
2021/0261485	12/2020	Hisler et al.	N/A	N/A
2021/0340083	12/2020	Boutier et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
101687735	12/2009	CN	N/A
102216247	12/2010	CN	N/A
939071	12/1998	EP	C07C 17/00
0940382	12/1998	EP	N/A
1566600	12/2004	EP	N/A
2035117	12/2008	EP	N/A
1257034	12/1960	FR	N/A
2768727	12/1998	FR	N/A
2973717	12/2011	FR	N/A
2973809	12/2011	FR	N/A
3032131	12/2015	FR	N/A
3041632	12/2016	FR	N/A
2000095714	12/1999	JP	N/A
2012509324	12/2011	JP	N/A
0181353	12/2000	WO	N/A
2007144632	12/2006	WO	N/A
2008127940	12/2007	WO	N/A
2008149011	12/2007	WO	N/A
2008149011	12/2008	WO	N/A
2010059496	12/2009	WO	N/A
2010063975	12/2009	WO	N/A
2010111067	12/2009	WO	N/A
2012067980	12/2011	WO	N/A
2014116562	12/2013	WO	N/A
2015175791	12/2014	WO	N/A
2016146940	12/2015	WO	N/A
2017031046	12/2016	WO	N/A

OTHER PUBLICATIONS

International Search Report (PCT/ISA/210) mailed on Jul. 30, 2019, by the European Patent Office as the International Searching Authority for International Application No. PCT/FR2019/051067. cited by applicant

Written Opinion (PCT/ISA/237) mailed on Jul. 30, 2019, by the European Patent Office as the International Searching Authority for International Application No. PCT/FR2019/051067. cited by applicant

Test No. 102: Melting point/Melting range, OECD guidelines for the testing of chemical products, Section 1, OECD Editions, Paris, 1995, available at <http://dx.doi.org/10.1787/9789264069534-fr> (with English translation) (17 pages). cited by applicant

Boutier, Jean-Christophe, et al., U.S. Appl. No. 17/280,547 entitled “Stabilization of 1-Chloro-3,3,3-Trifluoropropene,” filed in the U.S. Patent and Trademark Office Mar. 26, 2021. cited by applicant

Breck, Donald W., et al., “Zeolite Molecular Sieves”, John Wiley & Sons Eds, (1974), 159 pages. cited by applicant

Ghanem, Akram, et al., “Static mixers; Mechanisms, applications, and characterization methods—

A review," Chemical Engineering Research and Design, 2014, pp. 205-228, vol. 92, Elsevier B.V., NL. cited by applicant
U.S. Appl. No. 17/280,547, filed Mar. 26, 2021, Jean-Christophe Boutier and Wissam Rached. cited by applicant
U.S. Appl. No. 16/250,141, filed Jan. 17, 2019, Anne Pigamo, Laurent Wendlinger, Dominique Duer-Bert. cited by applicant

Primary Examiner: Bahta; Medhanit W

Attorney, Agent or Firm: Buchanan Ingersoll & Rooney PC

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) The present application is a divisional of U.S. application Ser. No. 17/053,250, filed on Nov. 5, 2020, which is a U.S. national stage of International Application No. PCT/FR2019/051067, filed on May 13, 2019, which claims the benefit of French Application No. 1854069, filed on May 16, 2018. The entire contents of each of U.S. application Ser. No. 17/053,250, International Application No. PCT/FR2019/051067, French Application No. 1854069 are hereby incorporated herein by reference in their entirety.

TECHNICAL FIELD

(1) The present invention concerns the production of hydrochlorofluoroolefins. More particularly, the present invention relates to the production of 1-chloro-3,3,3-trifluoropropene.

TECHNOLOGICAL BACKGROUND

(2) 3,3,3-Trifluoro-1-chloropropene, or alternatively 1-chloro-3,3,3-trifluoropropene (HCFO-1233zd), exists in the form of two isomers: the cis isomer, namely Z-3,3,3-trifluoro-1-chloropropene (HCFO-1233zdZ), and the trans isomer, namely E-3,3,3-trifluoro-1-chloropropene (HCFO-1233zdE). They have different boiling points of, respectively, 18.5° C. for the trans compound and 39.5° C. for the cis compound.

(3) Fluids based on E-3,3,3-trifluoro-1-chloropropene (HCFO-1233zdE) have found numerous applications in varied industrial fields, in particular as heat transfer fluids, propellants, foaming agents, blowing agents, gaseous dielectrics, monomers or polymerization media, support fluids, abrasive agents, drying agents, and fluids for energy production units.

(4) Manufacture of HCFO-1233zdE is accompanied by a multitude of byproducts having a boiling point close to HCFO-1233zdE. This results in purification steps which are relatively complex and costly. The difficulties encountered during the purification of HCFO-1233zdE generally entail an appreciable loss of target product. In addition, the byproducts may form azeotropic compositions with the HCFO-1233zdE, so making it very difficult if not impossible to carry out separation by simple distillation.

(5) There is a process known through U.S. Pat. No. 5,877,359 for preparing HCFO-1233zdE from 1,1,3,3-tetrachloropropene in liquid phase and in the absence of catalyst. The molar HF/1230za ratio in the fluorination reactor is from 12 to 500. There is also a process known, through U.S. Pat. No. 9,643,903, for fluorinating 1,1,3,3-tetrachloropropene in liquid phase and in the absence of catalyst, in an HF-rich medium. A substantial amount of HF present at start-up or in a steady-state regime of an industrial reactor under pressure is undesirable for obvious environmental and safety reasons. The concern for new processes which respect the environment more forms part of an ongoing process of improvement.

(6) Furthermore, a not inconsiderable amount of overfluorinated byproducts are observed, linked to the presence of this HF in large amount. The presence of 245fa may give rise to a loss of yield, it

being known that this mixture forms an azeotropic mixture with the primary product, the 1233zdE (see in particular US 2017/174965). It will therefore be difficult to separate and will have to be removed in the form of an azeotropic mixture, so giving rise to a loss of yield.

(7) There is a need, consequently, for new processes which minimize the drawbacks described above.

SUMMARY

(8) According to a first aspect, the present invention provides a process for producing 1-chloro-3,3,3-trifluoropropene, comprising the step i) of contacting hydrofluoric acid (HF) in a reactor with a starting composition comprising at least one of the chloro compounds selected from the group consisting of 1,1,3,3-tetrachloropropene (1230za), 1,3,3,3-tetrachloropropene (1230zd) and 1,1,1,3,3-pentachloropropane (240fa), or a mixture thereof, to produce a stream A comprising 1-chloro-3,3,3-trifluoropropene (1233zd), characterized in that said step i) is carried out in a low-HF liquid phase.

(9) Reducing the amount of HF in the fluorination reactor tends to protect the reactor from corrosion phenomena. Moreover, reducing the amount of HF in the reactor provides an operational reliability which makes the process readily amenable to the industrial scale. The risks of decantation in the liquid-phase reactor are therefore minimized. Additionally, the amount of overfluorinated coproducts is reduced by virtue of the process according to the present invention.

(10) According to one preferred embodiment, said low-HF liquid phase is a liquid phase comprising less than 15% by weight of HF, advantageously less than 10% by weight of HF, preferably less than 8% by weight of HF, more preferably less than 6% by weight of HF, in particular less than 5% by weight of HF, more particularly less than 4% by weight of HF, preferentially less than 2% by weight of HF, based on the total weight of said liquid phase.

(11) According to one preferred embodiment, said at least one of the chloro compounds is 1,1,3,3-tetrachloropropene (1230za).

(12) According to one preferred embodiment, said starting composition comprises at least 10% by weight of said at least one of the chloro compounds, based on the total weight of said starting composition.

(13) According to one preferred embodiment, said starting composition comprises less than 10% by weight of HF, based on the total weight of said starting composition.

(14) According to one preferred embodiment, said liquid phase comprises at least 10% by weight of compounds of formula (I) $C_{\text{sub}3}H_{\text{sub}n}F_{\text{sub}m}Cl_{\text{sub}p}$ (I) in which n is an integer from 0 to 8, m is an integer from 0 to 8, and p is an integer from 0 to 8.

(15) According to one preferred embodiment, step i) is carried out in the absence of catalyst.

(16) According to one preferred embodiment, the stream A comprises coproducts selected from the group consisting of 1,3,3,3-tetrafluoropropene and 1,1,1,3,3-pentafluoropropane.

(17) According to one preferred embodiment, the amount of coproducts selected from the group consisting of 1,3,3,3-tetrafluoropropene and 1,1,1,3,3-pentafluoropropane is less than 0.5% by weight, based on the total weight of the stream A at the exit of the reactor.

(18) According to one preferred embodiment, step i) is carried out at a temperature of 50° C. to 150° C.

(19) According to one preferred embodiment, step i) is carried out at a pressure of 5 to 20 bara.

(20) According to a second aspect, the present invention provides a composition comprising at least 98 mol % of (E/Z)-1-chloro-3,3,3-trifluoropropene and less than 0.5 mol % of coproducts selected from the group consisting of 1,3,3,3-tetrafluoropropene and 1,1,1,3,3-pentafluoropropane.

(21) According to one preferred embodiment, the composition comprises at least 99.5 mol % of (E/Z)-1-chloro-3,3,3-trifluoropropene, less than 0.3 mol % of 1,3,3,3-tetrafluoropropene and less than 0.05 mol % of 1,1,1,3,3-pentafluoropropane.

(22) According to one preferred embodiment, said composition is obtained at the exit of a reactor carrying out the process according to the present invention.

Description

DETAILED DESCRIPTION

(1) According to a first aspect of the invention, a process for producing 1-chloro-3,3,3-trifluoropropene is provided. Said process comprises a step i) of contacting hydrofluoric acid (HF) in a reactor with a starting composition comprising at least one of the chloro compounds selected from the group consisting of 1,1,3,3-tetrachloropropene (1230za), 1,3,3,3-tetrachloropropene (1230zd) and 1,1,1,3,3-pentachloropropane (240fa), or a mixture thereof, to produce a stream A comprising 1-chloro-3,3,3-trifluoropropene (1233zd). Said step i) is preferably carried out in a low-HF liquid phase.

(2) As mentioned above, the present process enables production of 1-chloro-3,3,3-trifluoropropene with a high yield and a high selectivity to be obtained. The amount of coproducts in the final reaction mixture is greatly reduced when the present process is carried out in a medium which is low in HF, relative to a process carried out in a medium which is rich in HF. The present invention therefore provides a more efficient process.

(3) According to one preferred embodiment, said starting composition comprises at least 10% by weight of said at least one of the chloro compounds, based on the total weight of said starting composition. Said starting composition advantageously comprises at least 15% by weight of said at least one of the chloro compounds, preferably at least 20% by weight of said at least one of the chloro compounds, more preferably at least 25% by weight of said at least one of the chloro compounds, in particular at least 30% by weight of said at least one of the chloro compounds, more particularly at least 35% by weight of said at least one of the chloro compounds, preferentially at least 40% by weight of said at least one of the chloro compounds, advantageously preferentially at least 45% by weight of said at least one of the chloro compounds, preferably preferentially at least 50% by weight of said at least one of the chloro compounds, particularly preferentially at least 55% by weight of said at least one of the chloro compounds, based on the total weight of said starting composition.

(4) Said starting composition preferably comprises at least 60% by weight or at least 65% by weight or at least 70% by weight or at least 75% by weight or at least 80% by weight or at least 85% by weight or at least 90% by weight or at least 95% by weight or at least 99% by weight of said at least one of the chloro compounds, based on the total weight of said starting composition.

(5) The process according to the present invention is efficient if the starting composition comprises one of said at least one of the chloro compounds at high purity or in a mixture with other organic compounds.

(6) According to one preferred embodiment, said at least one of the chloro compounds is 1,1,3,3-tetrachloropropene (1230za). Said process therefore comprises a step i) of contacting hydrofluoric acid (HF) in a reactor with a starting composition comprising 1,1,3,3-tetrachloropropene (1230za) to produce a stream A comprising 1-chloro-3,3,3-trifluoropropene (1233zd); said step i) is carried out in a low-HF liquid phase as defined above. The present process preferably enables the production of 1-chloro-3,3,3-trifluoropropene in the form of a mixture of the two cis and trans isomers. The present process enables majority production of the trans-1-chloro-3,3,3-trifluoropropene isomer, preferably at least 90 mol % of the trans isomer.

(7) Said starting composition therefore comprises at least 10% by weight of 1,1,3,3-tétrachloropropene, based on the total weight of said starting composition. Said starting composition advantageously comprises at least 15% by weight of 1,1,3,3-tetrachloropropene, preferably at least 20% by weight of 1,1,3,3-tetrachloropropene, more preferably at least 25% by weight of 1,1,3,3-tetrachloropropene, in particular at least 30% by weight of 1,1,3,3-tetrachloropropene, more particularly at least 35% by weight of 1,1,3,3-tetrachloropropene, preferentially at least 40% by weight of 1,1,3,3-tetrachloropropene, advantageously preferentially

at least 45% by weight of 1,1,3,3-tetrachloropropene, preferably preferentially at least 50% by weight of 1,1,3,3-tetrachloropropene, particularly preferentially at least 55% by weight of 1,1,3,3-tetrachloropropene, based on the total weight of said starting composition.

(8) Said starting composition preferably comprises at least 60% by weight or at least 65% by weight or at least 70% by weight or at least 75% by weight or at least 80% by weight or at least 85% by weight or at least 90% by weight or at least 95% by weight or at least 99% by weight of 1,1,3,3-tetrachloropropene, based on the total weight of said starting composition.

(9) According to one preferred embodiment, said starting composition comprises less than 15% by weight of HF, based on the total weight of said starting composition, advantageously less than 10% by weight of HF, preferably less than 8% by weight of HF, more preferably less than 6% by weight of HF, in particular less than 5% by weight of HF, more particularly less than 4% by weight of HF, preferentially less than 2% by weight of HF, based on the total weight of said starting composition.

(10) In the present process, preferably, the starting composition is devoid of HF. The term “devoid” signifies an amount by weight of less than 500 ppm, preferably less than 100 ppm, more particularly less than 10 ppm.

(11) Carrying out step i) of the present process enables the fluorination of chloro compounds such as 1,1,3,3-tetrachloropropene (1230za), 1,3,3,3-tetrachloropropene (1230zd) or 1,1,1,3,3-pentachloropropane (240fa). Said liquid phase will therefore accumulate fluorinated organic compounds, while maintaining a low HF content therein.

(12) Said low-HF liquid phase is preferably a liquid phase comprising less than 15% by weight of HF, advantageously less than 10% by weight of HF, preferably less than 8% by weight of HF, more preferably less than 6% by weight of HF, in particular less than 5% by weight of HF, more particularly less than 4% by weight of HF, preferentially less than 2% by weight of HF, based on the total weight of said liquid phase.

(13) While step i) is being carried out, said liquid phase may comprise at least 10% by weight of compounds of formula (I) $C_{\text{sub}}.3H_{\text{sub}}.nF_{\text{sub}}.mCl_{\text{sub}}.p$ (I) in which n is an integer from 0 to 8, m is an integer from 0 to 8, and p is an integer from 0 to 8; preferably, n is an integer from 0 to 8, m is an integer from 0 to 6, and p is an integer from 0 to 6. Compounds of formula (I) may, for example, be $C_{\text{sub}}.3Cl_{\text{sub}}.6$, $C_{\text{sub}}.3H_{\text{sub}}.4Cl_{\text{sub}}.4$ or $C_{\text{sub}}.3H_{\text{sub}}.3Cl_{\text{sub}}.5$.

(14) Preferably, while step i) is being carried out, said liquid phase may comprise at least 10% by weight of compounds of formula (I) $C_{\text{sub}}.3H_{\text{sub}}.nF_{\text{sub}}.mCl_{\text{sub}}.p$ (I) in which n is an integer from 1 to 8, m is an integer from 0 to 4, and p is an integer from 0 to 4; preferably, n is an integer from 1 to 4, m is an integer from 0 to 3, and p is an integer from 2 to 4. The compounds of formula (I) may be propane or propene compounds comprising one or more chlorine atoms and/or one or more fluorine atoms. Said liquid phase may preferably comprise at least 10% by weight of compounds of formula (I) selected from the group consisting of $C_{\text{sub}}.3H_{\text{sub}}.2Cl_{\text{sub}}.4$, $C_{\text{sub}}.3H_{\text{sub}}.2Cl_{\text{sub}}.3F$, $C_{\text{sub}}.3H_{\text{sub}}.2Cl_{\text{sub}}.2F_{\text{sub}}.2$, $C_{\text{sub}}.3H_{\text{sub}}.3Cl_{\text{sub}}.5$, $C_{\text{sub}}.3H_{\text{sub}}.3Cl_{\text{sub}}.4F$, $C_{\text{sub}}.3H_{\text{sub}}.3Cl_{\text{sub}}.3F_{\text{sub}}.2$, and $C_{\text{sub}}.3H_{\text{sub}}.3Cl_{\text{sub}}.2F_{\text{sub}}.3$. More particularly, said liquid phase may comprise at least 10% by weight of compounds of formula (I) selected from the group consisting of $C_{\text{sub}}.3H_{\text{sub}}.2Cl_{\text{sub}}.4$, $C_{\text{sub}}.3H_{\text{sub}}.2Cl_{\text{sub}}.3F$, and $C_{\text{sub}}.3H_{\text{sub}}.2Cl_{\text{sub}}.2F_{\text{sub}}.2$.

(15) Said liquid phase may comprise at least 15% by weight of compounds of formula (I) $C_{\text{sub}}.3H_{\text{sub}}.nF_{\text{sub}}.mCl_{\text{sub}}.p$ (I) in which n is an integer from 0 to 8, m is an integer from 0 to 8, and p is an integer from 0 to 8; preferably, n is an integer from 0 to 8, m is an integer from 0 to 6, and p is an integer from 0 to 6.

(16) More particularly, while step i) is being carried out, said liquid phase may comprise at least 15% by weight of compounds of formula (I) $C_{\text{sub}}.3H_{\text{sub}}.nF_{\text{sub}}.mCl_{\text{sub}}.p$ (I) in which n is an integer from 1 to 8, m is an integer from 0 to 4, and p is an integer from 0 to 4; preferably, n is an integer from 1 to 4, m is an integer from 0 to 3, and p is an integer from 2 to 4. Said liquid phase may preferably comprise at least 15% by weight of compounds of formula (I) selected from the

group consisting of C.sub.3H.sub.2Cl.sub.4, C.sub.3H.sub.2Cl.sub.3F, C.sub.3H.sub.2Cl.sub.2F.sub.2, C.sub.3H.sub.3Cl.sub.5, C.sub.3H.sub.3Cl.sub.4F, C.sub.3H.sub.3Cl.sub.3F.sub.2, and C.sub.3H.sub.3Cl.sub.2F.sub.3. More particularly, said liquid phase may comprise at least 15% by weight of compounds of formula (I) selected from the group consisting of C.sub.3H.sub.2Cl.sub.4, C.sub.3H.sub.2Cl.sub.3F, and C.sub.3H.sub.2Cl.sub.2F.sub.2.

(17) Said liquid phase may comprise at least 20%, at least 30%, at least 40%, at least 50%, at least 60%, at least 70%, at least 80% or at least 90% by weight of compounds of formula (I)

C.sub.3H.sub.nF.sub.mCl.sub.p (I) in which n is an integer from 0 to 8, m is an integer from 0 to 8, and p is an integer from 0 to 8; preferably, n is an integer from 0 to 8, m is an integer from 0 to 6, and p is an integer from 0 to 6.

(18) Said liquid phase may comprise at least 20%, at least 30%, at least 40%, at least 50%, at least 60%, at least 70%, at least 80% or at least 90% by weight of compounds of formula (I)

C.sub.3H.sub.nF.sub.mCl.sub.p (I) in which n is an integer from 1 to 8, m is an integer from 0 to 4, and p is an integer from 0 to 4; preferably, n is an integer from 1 to 4, m is an integer from 0 to 3, and p is an integer from 2 to 4. Said liquid phase may preferably comprise at least 20%, at least 30%, at least 40%, at least 50%, at least 60%, at least 70%, at least 80% or at least 90% by weight of compounds of formula (I) selected from the group consisting of C.sub.3H.sub.2Cl.sub.4, C.sub.3H.sub.2Cl.sub.3F, C.sub.3H.sub.2Cl.sub.2F.sub.2, C.sub.3H.sub.3Cl.sub.5, C.sub.3H.sub.3Cl.sub.4F, C.sub.3H.sub.3Cl.sub.3F.sub.2, and C.sub.3H.sub.3Cl.sub.2F.sub.3.

(19) More particularly, said liquid phase may comprise at least 20%, at least 30%, at least 40%, at least 50%, at least 60%, at least 70%, at least 80% or at least 90% by weight of compounds of formula (I) selected from the group consisting of C.sub.3H.sub.2Cl.sub.4, C.sub.3H.sub.2Cl.sub.3F, and C.sub.3H.sub.2Cl.sub.2F.sub.2.

(20) Said liquid phase may also comprise heavy compounds resulting from the dimerization or from the polymerization of the compounds of formula (I) as defined above.

(21) Step i) is preferably carried out in the absence of catalyst.

(22) Step i) may alternatively be carried out in the presence of a catalyst. The catalyst may be a TiCl.sub.4 or SbCl.sub.5 catalyst. The catalyst may also be an ionic liquid. The ionic liquids which may be suitable are Lewis acid derivatives based on aluminum, titanium, niobium, tantalum, tin, antimony, nickel, zinc or iron. The term "ionic liquids" refers to nonaqueous salts of ionic nature which are liquid at moderate temperatures (preferably below 120° C.). Ionic liquids preferably result from the reaction between an organic salt and an inorganic compound. Ionic liquids are preferably obtained by reaction of at least one halogen or oxyhalogen Lewis acid based on aluminum, titanium, niobium, tantalum, tin, antimony, nickel, zinc or iron with a salt of general formula Y.sup.+A.sup.-, in which A.sup.- denotes a halide anion (bromide, iodide and, preferably, chloride or fluoride) or hexafluoroantimonate (SbF.sub.6.sup.-) and Y.sup.+ a quaternary ammonium, quaternary phosphonium or ternary sulfonium cation. The halogen Lewis acid based on aluminum, titanium, niobium, tantalum, antimony, nickel, zinc or iron may be a chloro, bromo, fluoro or mixed derivative, for example a chlorofluoro acid. Mention may be made more particularly of the chlorides, fluorides or chlorofluorides having the following formulae:

TiCl.sub.xF.sub.y with $x+y=4$ and $0 \leq x \leq 4$

TaCl.sub.xF.sub.y with $x+y=5$ and $0 \leq x \leq 5$

NbCl.sub.xF.sub.y with $x+y=5$ and $0 \leq x \leq 5$

SnCl.sub.xF.sub.y with $x+y=4$ and $1 \leq x \leq 4$

SbCl.sub.xF.sub.y with $x+y=5$ and $0 \leq x \leq 5$

AlCl.sub.xF.sub.y with $x+y=3$ and $0 \leq x \leq 3$

NiCl.sub.xF.sub.y with $x+y=2$ and $0 \leq x \leq 2$

FeCl.sub.xF.sub.y with $x+y=3$ and $0 \leq x \leq 3$

(23) As examples of such compounds, mention may be made of the following compounds:

TiCl.sub.4, TiF.sub.4, TaCl.sub.5, TaF.sub.5, NbCl.sub.5, NbF.sub.5, SbCl.sub.5, SbCl.sub.4F, SbCl.sub.3F.sub.2, SbCl.sub.2F.sub.3, SbClF.sub.4, SbF.sub.5, and mixtures thereof. The following compounds are preferentially used: TiCl.sub.4, TaCl.sub.5+TaF.sub.5, NbCl.sub.5+NbF.sub.5, SbCl.sub.5, SbFCl.sub.4, SbF.sub.2Cl.sub.3, SbF.sub.3Cl.sub.2, SbF.sub.4Cl, SbF.sub.5, and SbCl.sub.5+SbF.sub.5. The antimony-based compounds are more particularly preferred. As examples of oxyhalogen Lewis acids that may be used according to the invention, mention may be made of TiOCl.sub.2, TiOF.sub.2 and SbOCl.sub.xF.sub.y (x+y=3). In the salt Y.sup.+A.sup.-, the cation Y.sup.+ may correspond to one of the following general formulae:

R.sup.1R.sup.2R.sup.3R.sup.4N.sup.+, R.sup.1R.sup.2R.sup.3R.sup.4P.sup.+,

R.sup.1R.sup.2R.sup.3S.sup.+ in which the symbols R.sup.1 to R.sup.4, which are identical or different, each denote a saturated or unsaturated, cyclic or noncyclic, or aromatic hydrocarbyl, chlorohydrocarbyl, fluorohydrocarbyl, chlorofluorohydrocarbyl or fluorocarbyl group having from 1 to 10 carbon atoms, with one or more of these groups possibly also containing one or more heteroatoms such as N, P, S or O. The ammonium, phosphonium or sulfonium cation r may also form part of a saturated or unsaturated, or aromatic, heterocycle having from 1 to 3 nitrogen, phosphorus or sulfur atoms, and may correspond to one or other of the following general formulae:

(24) ##STR00001## in which R.sup.1 and R.sup.2 are as defined previously. A salt containing two or three ammonium, phosphonium or sulfonium sites in its formula may also be suitable for use. As examples of salts Y.sup.+A.sup.-, mention may be made of tetraalkylammonium chlorides and fluorides, tetraalkylphosphonium chlorides and fluorides, and trialkylsulfonium chlorides and fluorides, alkylpyridinium chlorides and fluorides, dialkylimidazolium chlorides, fluorides and bromides, and trialkylimidazolium chlorides and fluorides. Trimethylsulfonium fluoride or chloride, N-ethylpyridinium chloride or fluoride, N-butylpyridinium chloride or fluoride, 1-ethyl-3-methylimidazolium chloride or fluoride, and 1-butyl-3-methylimidazolium chloride or fluoride are more particularly valued. The ionic liquids may be prepared in a manner known per se by appropriate mixing of the halogen or oxyhalogen Lewis acid and the organic salt Y.sup.+A.sup.-. Reference may be made notably to the method described in WO 01/81353. The catalyst may alternatively be triflic or trifluoroacetic acid as stated in U.S. Pat. No. 6,166,274.

(25) According to one preferred embodiment, as well as the 1-chloro-3,3,3-trifluoropropene, the stream A comprises coproducts selected from the group consisting of 1,3,3,3-tetrafluoropropene and 1,1,1,3,3-pentafluoropropane. The 1-chloro-3,3,3-trifluoropropene recovered in said stream A is in the form of a mixture of the two Z and E isomers, as stated above.

(26) According to one preferred embodiment, the amount, in the stream A, of coproducts selected from the group consisting of 1,3,3,3-tetrafluoropropene and 1,1,1,3,3-pentafluoropropane is less than 0.5 mol %. The 1,3,3,3-tetrafluoropropene content of said stream A is preferably less than 0.5 mol %, more preferably less than 0.4 mol %, more particularly less than 0.3 mol %. The 1,1,1,3,3-pentafluoropropane content of said stream A is preferably less than 0.1 mol %, more preferably less than 0.075 mol %, more particularly less than 0.05 mol %.

(27) Said stream A may also comprise HF and HCl.

(28) Step i) is preferably carried out at a temperature of 50° C. to 150° C., preferably at a temperature of 75° C. to 100° C.

(29) Step i) is preferably carried out at a pressure of 5 to 20 bara, preferably at a pressure of 10 to 18 bara, more particularly of 12 to 18 bara.

(30) The molar HF/[chloro compounds] ratio at the entry of the reactor is preferably between 5 and 10, more preferably between 5 and 7, more particularly between 5 and 6. More particularly, when said chloro compound in the starting composition is 1,1,3,3-tetrachloropropene (1230za), the molar HF/1230za ratio is between 5 and 10, more preferably between 5 and 7, more particularly between 5 and 6.

(31) Said process preferably further comprises the steps of: (ii) at least one step of treating the stream A to give a stream B comprising E-1-chloro-3,3,3-trifluoropropene, HCl, HF and Z-1-

chloro-3,3,3-trifluoropropene, and a stream C comprising primarily HF (for example at least 50% by weight, preferably at least 70% by weight, of HF); (iii) at least one step of recovering the hydrochloric acid in the stream B, to give a stream D of HCl and a stream E comprising E-1-chloro-3,3,3-trifluoropropene, HCl, HF, and Z-1-chloro-3,3,3-trifluoropropene; (iv) at least one step of purifying the stream E obtained from step (iii) to give E-1233zd, preferably with a purity of not less than 98%, advantageously not less than 99%, and very advantageously not less than 99.9% by weight.

(32) Before the purification step, the stream E obtained in step (iii) is preferably subjected to at least one separation step to give a flow comprising primarily HF (for example, at least 90% by weight, preferably at least 98% by weight, and advantageously at least 99% by weight of HF), which can be recycled to the reactor, and a flow comprising E-1-chloro-3,3,3-trifluoropropene, HCl, HF, and Z-1-chloro-3,3,3-trifluoropropene. The separation step is preferably a decantation, carried out at a temperature advantageously of between -50 and 50°C ., preferably between -20°C . and 10°C .

(33) The treatment step (ii) is preferably a reflux column, carried out advantageously at a temperature of between 30 and 120°C . to give the stream C, which is recycled to the reactor.

(34) The recovery of HCl in step (iii) is preferably obtained by means of a distillation column equipped with a bottoms reboiler and a top reflux system. The bottom temperature is advantageously between 20 and 110°C . The overhead temperature is advantageously between -50 and 0°C . The distillation of HCl is typically performed at a pressure of between 7 and 25 bar.

(35) According to one embodiment, the purification step (iv) preferably comprises at least one distillation step and advantageously at least two distillation steps. According to one preferred embodiment, the purification step (iv) comprises at least one step of washing with water and/or washing by means of a basic solution, a drying step, and at least one distillation step. The goal of this distillation step is to remove the light products and also the heavy products, which may be partly recycled to the reactor, depending on whether they are recyclable or not.

(36) The process is preferably carried out continuously.

(37) According to a second aspect, the present invention provides a composition comprising at least 98 mol % of (E/Z)-1-chloro-3,3,3-trifluoropropene and less than 0.5 mol % of coproducts selected from the group consisting of 1,3,3,3-tetrafluoropropene and 1,1,1,3,3-pentafluoropropane. Said composition preferably comprises at least 99 mol % of (E/Z)-1-chloro-3,3,3-trifluoropropene and less than 0.5 mol % of coproducts selected from the group consisting of 1,3,3,3-tetrafluoropropene and 1,1,1,3,3-pentafluoropropane. Said composition more particularly comprises at least 99.5 mol % of (E/Z)-1-chloro-3,3,3-trifluoropropene and less than 0.5 mol % of coproducts selected from the group consisting of 1,3,3,3-tetrafluoropropene and 1,1,1,3,3-pentafluoropropane.

(38) Said composition preferably comprises at least 99 mol % of (E/Z)-1-chloro-3,3,3-trifluoropropene, less than 0.5 mol % of 1,3,3,3-tetrafluoropropene and less than 0.1 mol % of 1,1,1,3,3-pentafluoropropane. Said composition more particularly comprises at least 99 mol % of (E/Z)-1-chloro-3,3,3-trifluoropropene, less than 0.4 mol % of 1,3,3,3-tetrafluoropropene and less than 0.075 mol % of 1,1,1,3,3-pentafluoropropane. Said composition very particularly comprises at least 99 mol % of (E/Z)-1-chloro-3,3,3-trifluoropropene, less than 0.3 mol % of 1,3,3,3-tetrafluoropropene and less than 0.05 mol % of 1,1,1,3,3-pentafluoropropane.

(39) Said composition preferably comprises at least 99.5 mol % of (E/Z)-1-chloro-3,3,3-trifluoropropene, less than 0.3 mol % of 1,3,3,3-tetrafluoropropene and less than 0.05 mol % of 1,1,1,3,3-pentafluoropropane.

(40) According to one preferred embodiment, said composition is obtained at the exit of a reactor carrying out the process according to the present invention.

EXAMPLES

(41) The apparatus used consists of a reactor with a capacity of 60 liters, made of 316L stainless steel. It possesses means for measuring temperature, pressure, and liquid level. The reactants can be

fed in via a dip tube, while the products formed circulate through a 5 meter reflux column before being condensed overhead. This column is filled with a structured metal packing which allows the low-boiling-point products to be separated, while the raw material, the intermediate compounds and the unreacted HF drop back into the reactor. A pressure regulation valve imposes an operating pressure on the assembly. An in-line withdrawal system allows the flow of outgoing gas to be sampled, for which it is guided to a gas chromatograph. The reactants are fed in continuously, and the products are analyzed and collected continuously.

Example 1 (Comparative)

(42) An amount of HF of 25 liters is introduced into the reactor. The reactor is maintained at a temperature of 90° C. The pressure regulation is adjusted to 15 bara. The reactants are then fed in at the following rates: 2 kg/h of HF and 3.5 kg/h of 1230za, giving a molar ratio of the HF to the organic compound of 5.2. The resulting composition of the gas flow after five hours of operation is given in table 1.

Example 2

(43) The procedure of example 1 is reproduced with a start-up amount of 25 liters of a mixture comprising organic compounds and devoid of HF. The mixture comprises an amount by weight of 10.7% of 1230za, 0.9% by weight of 1231 (trichloromonofluoropropene) isomers and 5.7% by weight of 1232 (dichlorodifluoropropene) isomers. The remainder is made up primarily of dimers and of heavy compounds. The reactor is heated in the same way as before, and then the reactants are fed in at the following rates: 2 kg/h of HF and 3.3 kg/h of 1230za, giving a molar ratio of the HF to the organic compound of 5.4. The resulting composition of the gas flow after five hours of operation is given in table 1.

Example 3

(44) The procedure of example 1 is reproduced with a start-up amount of 25 liters of 1230za alone. The reactor is heated in the same way as before, and then the reactants are fed in at the following rates: 1.8 kg/h of HF and 2.9 kg/h of 1230za, giving a molar ratio of the HF to 1230za of 5.6. The resulting composition of the gas flow after five hours of operation is given in table 1.

(45) TABLE-US-00001 TABLE 1 Molar composition at reactor exit (mol %) F1233zd-(E/Z) F1234ze (E + Z) F245fa Example 1 (comp.) 98.88% 0.57% 0.26% Example 2 99.77% 0.15% 0.01% Example 3 99.56% 0.26% 0.01%

Claims

1. A composition consisting of: at least 99.5 mol %, based on a total molar amount of the composition, of cis and trans 1-chloro-3,3,3-trifluoropropene; and coproducts, wherein the coproducts consist of less than 0.3 mol %, based on the total molar amount of the composition, of 1,3,3,3-tetrafluoropropene and less than 0.1 mol %, based on the total molar amount of the composition, of 1,1,1,3,3-pentafluoropropane, and wherein the composition is obtained at an exit of a reactor carrying out a process carried out in a liquid phase comprising less than 15% by weight of hydrofluoric acid (HF), based on the total weight of said liquid phase.
2. The composition as claimed in claim 1, wherein the process comprises a step comprising contacting hydrofluoric acid (HF) in a reactor with a starting composition comprising at least one of the chloro compounds selected from the group consisting of 1,1,3,3-tetrachloropropene (1230za), 1,3,3,3-tetrachloropropene (1230zd) and 1,1,1,3,3-pentachloropropane (240fa), or a mixture thereof, to produce a stream A comprising 1-chloro-3,3,3-trifluoropropene (1233zd).
3. The composition as claimed in claim 2, wherein said liquid phase comprises less than 10% by weight of HF, based on the total weight of said liquid phase.