

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12389820
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Rylander; David J

Map based seed vacuum control

Abstract

A method including adjusting a changeable component of a seed planting machine when switching from a first variety of seed to a second variety of seed during planting, wherein the adjusting is based on a location of the planting machine.

Inventors:	Rylander; David J (Milan, IL)
Applicant:	DEERE & COMPANY (Moline, IL)
Family ID:	1000008768094
Assignee:	DEERE & COMPANY (Moline, IL)
Appl. No.:	17/723134
Filed:	April 18, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230034279 A1	Feb. 02, 2023

Related U.S. Application Data

continuation parent-doc US 16562152 20190905 US 11304361 child-doc US 17723134
division parent-doc US 15451414 20170307 US 10426078 20191001 child-doc US 16562152
division parent-doc US 14327844 20140710 US 9585303 20170307 child-doc US 15451414

Publication Classification

Int. Cl.: **A01C7/10** (20060101); **A01B79/00** (20060101); **A01C7/04** (20060101); **A01C7/20** (20060101); **A01C21/00** (20060101)

U.S. Cl.:

CPC **A01C7/10** (20130101); **A01B79/005** (20130101); **A01C7/0443** (20230501); **A01C7/20** (20130101); **A01C21/005** (20130101); A01C7/046 (20130101)

Field of Classification Search

CPC: A01C (7/10); A01C (7/042); A01C (7/044); A01C (7/046); A01C (7/20); A01C (21/005); A01C (7/08); A01C (7/00); A01C (7/04); A01C (21/00); A01C (7/0443); A01B (79/005); A01B (79/00)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5995895	12/1998	Watt et al.	N/A	N/A
6516733	12/2002	Sauder et al.	N/A	N/A
9585303	12/2016	Rylander	N/A	N/A
10426078	12/2018	Rylander	N/A	N/A
11304361	12/2021	Rylander	N/A	A01C 7/20
2008/0047475	12/2007	Stehling et al.	N/A	N/A
2009/0118910	12/2008	Carr et al.	N/A	N/A
2009/0164281	12/2008	Norgaard et al.	N/A	N/A
2011/0054743	12/2010	Kocer et al.	N/A	N/A
2012/0266795	12/2011	Silbernagel et al.	N/A	N/A
2014/0277959	12/2013	Wagers et al.	N/A	N/A
2016/0007523	12/2015	Rylander	N/A	N/A
2016/0100519	12/2015	Noer et al.	N/A	N/A
2017/0172057	12/2016	Rylander	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2734608	12/2009	CA	A01C 7/04
2047735	12/2008	EP	N/A
2061301	12/2012	EP	N/A
WO03055291	12/2002	WO	N/A
WO2008024760	12/2007	WO	N/A
WO2015120247	12/2014	WO	N/A

OTHER PUBLICATIONS

Grisso et al., "Precision Farming Tools: Variable-Rate Application," Virginia Cooperative Extension, Publication 442-505, 2011, pp. 1-16. cited by applicant

"AgLeader: Application," Precision Management Services, 4 pages, accessed Jul. 10, 2014, <http://www.agronomytech.com/application>. cited by applicant

Featherston, "Variable Seeding Rate Technologies", SOIL/BAE 4213, Apr. 19, 2003, 15 pages. cited by applicant

Extended European Search Report and Written Opinion issued in European Patent Application No. 15176114.5, dated Dec. 1, 2015, in 09 pages. cited by applicant

European Patent Office Examination Report, dated Jun. 27, 2017, regarding Application No. 15176114.5, 8 pages. cited by applicant

Office Action, dated Aug. 3, 2016, regarding U.S. Appl. No. 14/327,844, 25 pages. cited by applicant

Notice of Allowance, dated Oct. 20, 2016, regarding U.S. Appl. No. 14/327,844, 5 pages. cited by applicant

Office Action, dated Sep. 7, 2018, regarding U.S. Appl. No. 15/451,414, 17 pages. cited by applicant

Final Office Action, dated Jan. 11, 2019, regarding U.S. Appl. No. 15/451,414, 9 pages. cited by applicant

Notice Of Allowance, dated May 22, 2019, regarding U.S. Appl. No. 15/451,414, 10 pages. cited by applicant

Primary Examiner: Novosad; Christopher J.

Background/Summary

FIELD OF THE DISCLOSURE

(1) The present application relates generally to techniques for planting seeds by a seed planter, and in particular is directed to improved vacuum seed meters for multiple variety planting operations.

BACKGROUND

(2) Seed planters may be used to automatically plant seeds into rows of a field. Whether towed or part of the tractor or other machine, seed planters dispense seeds at a controlled rate into one or more seed furrows or rows as the planter moves along a field. Seed planters typically have several planting or row units in a spaced-apart arrangement such that several rows can be simultaneously planted.

(3) The planting or row units may include one or more seed hoppers that hold seeds. A seed hopper holds a seed supply that feeds a seed meter. In turn, a seed meter may control a rate at which seeds are dispensed as the seed planter traverses a field. Each planting or row unit may also include other equipment, such as a furrow opener and/or a furrow closer, or other equipment.

(4) Attention is turned to the seed meter in particular. Seed meters may use a variety of different mechanical principles to control how seeds are dispensed, but generally all seed meters are designed to dispense seeds at a controlled rate, often one seed at a time. However, seed meters will have occasional errors, for example, “doubles” in which multiple seeds are dispensed when only one seed is intended to be dispensed, or “skips” in which no seed is dispensed when a seed is intended to be dispensed.

(5) One particular type of seed meter is known as a vacuum seed meter. A vacuum seed meter may use a vacuum to control how seeds are taken from a hopper seed pool and are dispensed from the meter. In one specific example, a vacuum seed meter may use a vacuum to gently pull and hold individual seeds to a seed disk. The disk then rotates, and at a designated place during rotation, the seed is released from the seed disk and dispensed for planting. A vacuum seed meter may include a double eliminator configured to remove doubles at individual seed apertures of the seed disk. Vacuum seed meters may plant a wide variety of crops and seed types by, for example, changing seed disks.

(6) Multiple variety planting is a planting operation in which multiple varieties of seed are to be dispensed in a field. Typically the varieties of seed are of the same plant species, but the varieties have different characteristics. For example, one variety of corn may be more disease resistant but have a lower yield than a second variety of corn. If a particular part of a field has had a history of disease, then the disease resistant variety may be planted in that particular part of the field, but the

higher yield variety may be planted in other parts of the field. A drought resistant variety of corn may be desired for planting in a third part of the field where water is expected to be scarce. One possible goal of multiple variety planting is to maximize the total overall yield of a field.

(7) Thus, multiple variety planting utilizes a map-based prescription that indicates what varieties of seed are to be planted in corresponding different portions of a field. The physical characteristics of the different seed varieties, may suggest that the seed meter be adjusted differently for the different varieties. However, since adjustment of the meters will be difficult or impossible to accomplish while planting, the meter may be adjusted to an acceptable, but not optimal, setting and left there for all seed varieties. Thus, devices and methods are desired that allow a seed meter, including vacuum seed meters in particular, to automatically implement changes to the seed meter in order to optimize planting of different varieties of seed at different times during a multiple variety planting operation.

SUMMARY

(8) The illustrative embodiments include a first method. The method includes adjusting a changeable component of a seed planting machine when switching from a first variety of seed to a second variety of seed during planting, wherein the adjusting is based on a location of the planting machine.

(9) The illustrative embodiments include a second method. The second method includes planting a first variety of seed in a first location of a field of land using a planting machine, the planting machine comprising a component, the component having a first setting configured to improve a first performance of the planting machine when planting the first variety of seed, wherein the first performance is gauged relative to the planting machine planting the first variety of seed using other settings of the component. The second method also includes sensing that the planting machine will reach or has reached a second location of the field, different than the first location, wherein a second variety of seed, different than the first variety of seed, is to be planted in the second location. The second method also includes responsive to sensing, automatically adjusting the component of the planting machine to a second setting, the second setting configured to improve a second performance of the planting machine while planting the second variety of seed, wherein the second performance is gauged relative to the planting machine planting the second variety of seed using other settings of the component. The second method also includes planting the second variety of seed in the second location of the field using the component at the second setting.

(10) The illustrative embodiments also provide for a multiple variety planter. The multiple variety planter includes a planting machine comprising an adjustable component, the adjustable component being adjustable between a first configuration and a second configuration, the first configuration set to maximize planting efficiency of a first variety of seed relative to other varieties of seeds, the second configuration set to maximize planting efficiency of a second variety of seed relative to other varieties of seeds. The multiple variety planter also includes a controller in communication with the automatic seed planter, the controller configured to automatically adjust the adjustable component between the first configuration and the second configuration based on a particular location of the automatic seed planter in a field of land comprising a plurality of different locations that include the particular location.

(11) The illustrative embodiments provide for a third method. The third method includes adjusting a vacuum level applied to a vacuum seed meter of a seed planting machine based on an attitude of the seed planting machine.

(12) The features, functions, and advantages can be achieved independently in various embodiments of the present invention or may be combined in yet other embodiments in which further details can be seen with reference to the following description and drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The novel features believed characteristic of the illustrative embodiments are set forth in the appended claims. The illustrative embodiments, however, as well as a preferred mode of use, further objectives and advantages thereof, will best be understood by reference to the following detailed description of an illustrative embodiment of the present invention when read in conjunction with the accompanying drawings, wherein:
- (2) FIG. 1 shows an automatic seed planter attached to a tractor, in accordance with an illustrative embodiment;
- (3) FIG. 2 shows an example of one type of vacuum seed meter, in accordance with an illustrative embodiment;
- (4) FIG. 3 is a block diagram illustrating zones of a field, wherein a different variety of seed is to be planted in each different zone, in accordance with an illustrative embodiment;
- (5) FIG. 4 shows a block diagram of a system for automatically controlling a vacuum seed meter, in accordance with an illustrative embodiment;
- (6) FIG. 5 illustrates an example of a method for performing a multiple variety planting operation using a control system, in accordance with an illustrative embodiment;
- (7) FIG. 6 is a flowchart of a method of adjusting a changeable component, in accordance with an illustrative embodiment;
- (8) FIG. 7 is a flowchart of a method of planting seeds, in accordance with an illustrative embodiment;
- (9) FIG. 8 is a flowchart of a method of planting seeds, in accordance with an illustrative embodiment;
- (10) FIG. 9 is a block diagram of a multiple variety planter, in accordance with an illustrative embodiment; and
- (11) FIG. 10 is an illustration of a data processing system, in accordance with an illustrative embodiment.

DETAILED DESCRIPTION

- (12) The illustrative embodiments recognize and take into account that available multiple variety seed meters are not automatically optimized for the different variety seeds when changing what variety of seed is dispensed during a multiple variety planting operation. The illustrative embodiments provide for a seed meter configured to automatically adjust to optimize planting of a particular seed variety within a particular location of a field during a multiple variety planting operation. In an illustrative embodiment, the term “automatically adjust” means the machine makes adjustments to the seed meter in real time while planting seed, with no input from the operator.
- (13) The illustrative embodiments recognize and take into account that multiple variety planting operations typically use a map-based prescription that indicates what specific variety of seed is to be planted in a corresponding specific portion of a field. The illustrative embodiments thus provide for a seed meter that automatically adjusts in order to dispense a specific variety of seed based on a location of the seed planting machine within the field. Specifically, the illustrative embodiments may automatically adjust a double eliminator, a vacuum level, or both in order to most efficiently dispense a specific variety of seed at a particular portion of a field. The settings of the double eliminator and the vacuum level may be made based on a size and shape of a seed of a particular seed variety.
- (14) Thus, the illustrative embodiments provide for an optimal adjustment of a row unit meter system for variable variety planting situations. To accomplish this goal, the illustrative embodiments may include two parts that work with a map-based prescription system. The first part stores vacuum and double eliminator settings in map data with the variety locations. The second part provides for a method to adjust the row units for vacuum setting and double eliminator setting as the planter transverses the field. Vacuum control may be accomplished by a closed loop control

system based on the vacuum sensor and control of a tractor selective control valve (SVC). The double eliminator (DE) setting may be controlled with a linear actuator used to correctly position the position of the double eliminator. Other control methods are possible.

(15) Attention is now turned to the Figures. FIG. 1 shows a seed planter attached to a tractor, in accordance with an illustrative embodiment. Tractor **100** may traverse field **102** as part of a planting operation, including a multiple variety planting operation. Tractor **100** may tow seed planting machine **104**, which plants seeds in field **102** as tractor **100** moves. Seed planting machine **104** may include a vacuum seed meter, as shown in FIG. 2.

(16) FIG. 2 shows an example of one type of vacuum seed meter, in accordance with an illustrative embodiment. Vacuum seed meter **200** may be used in a seed planting machine, such as seed planting machine **104** of FIG. 1. Such a seed planting machine may include multiple vacuum seed meters, such as vacuum seed meter **200**. Vacuum seed meter **200** of FIG. 2 is only an example of a wide variety of vacuum seed meters. Thus, the arrangement of vacuum seed meter **200** in FIG. 2 does not necessarily limit the claimed inventions.

(17) Vacuum seed meter **200** includes seed disk **208** having multiple apertures, such as aperture **202**. Vacuum system **204** may draw air through these apertures and create a partial vacuum within housing **206**. As a result, seeds fed to vacuum seed meter **200** from a hopper are drawn to be held against the apertures. A double eliminator (not shown) may then be used to reduce the incidence of doubles, which again is the dispensing of two seeds where only one seed is desired to be dispensed.

(18) In use, seed disk **208** may rotate about hub **210** while vacuum system **204** draws a vacuum through at least some of the apertures, such as aperture **202**. Seeds may be dispensed as gravity causes seeds to fall from the apertures when the vacuum is released and through an opening in housing **206**.

(19) While one disk, seed disk **208**, is shown in FIG. 2, other types of disks may be substituted for seed disk **208**. Different disks may have different sizes or arrangements of apertures, may have multiple concentric rings of apertures, and may have other features designed to guide seeds during operation. Selection of the disk to be used may be based on the type of seed and seed variety to be planted.

(20) FIG. 3 is a block diagram illustrating zones of a field, wherein a different variety of seed is to be planted in each different zone, in accordance with an illustrative embodiment. FIG. 3 shows a map-based prescription for which varieties of seed are to be planted in different zones of field **300** during a multiple variety planting operation. In an illustrative embodiment, seed planting machine **104** of FIG. 1 will be used to plant seeds in field **300**. One or more vacuum seed meters, such as vacuum seed meter **200** of FIG. 2, will be used to plant the seeds. The same vacuum seed meters will be used to plant each different variety of seed in the various zones of field **300**.

(21) Field **300** includes two zones, zone A **302** and zone B **304**. More zones could be present. Each of these zones is to receive a different variety of seed. For example, variety X **306** is to be planted in zone A **302** and variety Y **308** is to be planted in zone B **304**. Multiple zones of the same type may be present in field **300**. For example, as shown in FIG. 3, five instances of zone B **304** may be present. Areas in between these zones are all part of zone A **302**, in which variety X **306** is to be planted. Because the arrangement of instances of zone B **304** shown in FIG. 3 are dispersed within another zone, zone A **302**, manual adjustment of a seed planting machine would be inconvenient, impractical, or impossible.

(22) In an illustrative embodiment, field **300** is being planted using a single plant species, such as corn, wheat, or some other plant. Each variety is a variety of that single plant species. For example, variety X **306** may have a very high crop yield of corn, but a lower resistance to disease. Because a higher incidence of disease has historically occurred in zone B **304**, a relatively lower crop yield but more disease resistant variety of corn, variety Y **308**, may be planted in zone B **304**. Likewise, for different reasons, different varieties of corn may be planted in each different zone. Thus, field **300** shows a map-based prescription for which variety of seed is to be planted in a given zone of

field **300**. This map-based prescription may be designed to maximize the overall total crop yield for field **300**.

(23) One variety of seed may have different physical characteristics from another variety of seed, such as different size, shape, or weight. Each vacuum seed meter may be adjusted to accommodate these different physical characteristics so that efficiency of planting is optimized for a given variety of seed in a given zone. Maximum planting efficiency may be defined in one example as defined as eliminating all, or substantially all, skips and doubles to maximize the seed spacing consistency. Optimizing planting efficiency is defined as achieving as close to maximum planting efficiency as possible for a given vacuum seed meter or other seed planting machine.

(24) FIG. 4 shows a block diagram of a system for automatically controlling a vacuum seed meter, in accordance with an illustrative embodiment. Vacuum seed meter **400** may be, for example, vacuum seed meter **200** of FIG. 2, which in turn may be part of seed planting machine **104** in FIG. 1. The arrangement of blocks shown in FIG. 4 is not necessarily limiting of the claimed inventions, and more and fewer blocks may be present, as described in part below.

(25) Vacuum seed meter control **402** may control operation of vacuum seed meter **400**. In particular, vacuum seed meter control **402** may control the amount of vacuum applied within the vacuum seed meter. However, vacuum seed meter control **402** may control other aspects of operation of the vacuum seed meter, including but not limited to disk rotation speed or other controllable aspects of a vacuum seed meter.

(26) If a double eliminator is present in vacuum seed meter, then double eliminator control **404** may control operation of a double eliminator in the vacuum seed meter. In some cases double eliminator control **404** may be part of vacuum seed meter control **402**.

(27) In turn, processor **406** issues commands to control vacuum seed meter control **402** and, if present, double eliminator control **404**. Processor **406** may take as input data from a variety of sources. For example, processor **406** may take position data from global positioning system **408**, the position data informing processor **406** of where the seed planting machine is located. Processor **406** may also retrieve or receive map data stored on non-transitory computer readable storage medium **410**. The map data includes a map of a field that may be divided into zones, along with a map-based prescription of what seed varieties are to be planted in a given zone. Processor **406** may use the position data and the map data to determine when the seed planting machine has changed zones within a field. Upon detecting a change in zone, processor **406** may order vacuum seed meter control **402** and double eliminator control **404** to change settings of the vacuum, the double eliminator, or other parameters of vacuum seed meter **400** in order to optimize planting of a new and different variety of seed.

(28) Processor **406** may also take as input data from vacuum sensor **412** and/or speed sensor **414** to measure a vacuum within vacuum seed meter **400** and a speed of the seed planting machine. These data may be used to either verify that vacuum seed meter **400** is operating as desired for the zone being planted, or to modify operation of double eliminator control **404** and/or vacuum seed meter control **402** to optimize planting efficiency of the desired seed variety.

(29) Processor **406** may communicate with the various other systems described in FIG. 4 by means of wireless transceiver **416**. However, communication also may be established by wired communications, or a combination of wired and wireless communications for different components.

(30) The blocks shown in FIG. 4 may be varied, and more or fewer blocks may be present. For example, in some cases a double eliminator may not be desired or available, and thus double eliminator control **404** may not be present. In another example, other sensors may be used to gather additional data that processor **406** can use to further modify operation of vacuum seed meter control **402**. Additional equipment may be present as part of vacuum seed meter **400**, and additional sensors and controls may be present to control operation of this additional equipment. Further modifications may be made; thus, the features shown in FIG. 4 do not necessarily limit the

claimed inventions.

(31) FIG. 5 illustrates an example of a method for performing a multiple variety planting operation using a control system, in accordance with an illustrative embodiment. The control system may be, for example, the control system shown in FIG. 4. The operations of method **500** are described as being carried out by a “system”. As used herein, the “system” may be one or more components of the control system shown in FIG. 4. Method **500** is implemented using one or more physical components, including one or more of a processor, a non-transitory computer readable storage medium, and physical equipment including a seed planting machine.

(32) Method **500** begins as the system determines a current location of the seed planting machine (operation **502**). The system then uses a landscape position zone map to determine a zone associated with the current location (operation **504**). The system sets a vacuum seed meter for the current zone (operation **506**). The vacuum seed meter may be part of the seed planting machine.

(33) The system then determines whether the zone changes (operation **508**). If the zone does not change, then the method returns to operation **502** in order to continue to monitor the zone in which the seed planting machine is located and to continue the setting for the vacuum seed meter of the seed planting machine. However, if the zone does change, then the system accesses a parameter control table to determine one or more optimized settings for the vacuum seed meter for the new zone (operation **510**). The parameter control table may be a table, or other data not necessarily in table form, that specifies for a given zone one or more settings to be used for the vacuum seed meter, double eliminator, or other parts of a seed planting machine. For example, the parameter control table may specify that for zone A **302** of FIG. 3 the vacuum pressure may be at or about a specified value, that the double eliminator be adjusted in a particular manner, and/or some other aspect of the seed planting machine be adjusted while performing a planting operation in zone A **302**.

(34) The system then uses the parameter control table and controllers to adjust one or more settings of the vacuum seed meter to match the parameters of the parameter control table (operation **512**). Other aspects or components of the seed planting machine may also be adjusted accordingly, if desired. In any case, the system continues the planting operation using the one or more new settings (operation **514**).

(35) The system may then determine whether the planting operation should continue (operation **516**). If the planting operation should continue, then the method may return to operation **502** and continue accordingly. Otherwise, the process may terminate thereafter.

(36) Method **500** does not necessarily limit the claimed inventions. Alternative methods having more, fewer, or different operations are possible. For example, FIG. 6 and FIG. 7 provide for alternative methods.

(37) FIG. 6 is a flowchart of a method of adjusting a changeable component, in accordance with an illustrative embodiment. Method **600** of FIG. 6 is an alternative method to controlling a seed planting machine, relative to method **500** of FIG. 5. Method **600** may be implemented using the control system shown in FIG. 4 using vacuum seed meter **200** of FIG. 2 and seed planting machine **104** of FIG. 1.

(38) In an illustrative embodiment, method **600** includes adjusting a changeable component of a seed planting machine when switching from a first variety of seed to a second variety of seed during planting, wherein the adjusting is based on a location of the seed planting machine (operation **602**). The process may terminate thereafter.

(39) Method **600** may be modified by adding additional operations or modifying operation **602**. For example, the component may be a double eliminator configured to prevent multiple seeds from being planted at a particular location. In another example, the seed planting machine comprises a vacuum seed meter, and wherein adjusting the changeable component comprises adjusting a vacuum level applied to the vacuum seed meter.

(40) In another example, the seed planting machine includes a double eliminator and a vacuum

seed meter. In this case, operation **602** may include changing the double eliminator to prevent multiple seeds from being planted at a particular location, and adjusting a vacuum level applied to the vacuum seed meter. In another example, adjusting configures the seed planting machine to maximize performance of planting of the one of the plurality of different varieties of seed. (41) FIG. 7 is a flowchart of a method of planting seeds, in accordance with an illustrative embodiment. Method **700** of FIG. 7 is an alternative method to controlling a seed planting machine, relative to method **500** of FIG. 5 or method **600** of FIG. 6. Method **700** may be implemented using the control system shown in FIG. 4 using vacuum seed meter **200** of FIG. 2 and seed planting machine **104** of FIG. 1.

(42) Method **700** may begin by planting a first variety of seed in a first location of a field of land using a planting machine, the planting machine comprising a component, the component having a first setting configured to improve a first performance of the planting machine when planting the first variety of seed, wherein the first performance is gauged relative to the planting machine planting the first variety of seed using other settings of the component (operation **702**). Next, method **700** may include sensing that the planting machine will reach or has reached a second location of the field, different than the first location, wherein a second variety of seed, different than the first variety of seed, is to be planted in the second location (operation **704**).

(43) Next, method **700** may include, responsive to sensing, automatically adjusting the component of the planting machine to a second setting, the second setting configured to improve a second performance of the planting machine while planting the second variety of seed, wherein the second performance is gauged relative to the planting machine planting the second variety of seed using other settings of the component (operation **706**). Next, method **700** may include planting the second variety of seed in the second location of the field using the component at the second setting (operation **708**). The process may terminate thereafter.

(44) Method **700** may be modified by replacing, removing, adding, or modifying operations. Thus, method **700** does not necessarily limit the claimed inventions.

(45) For example, in an illustrative embodiment the component is a double eliminator to prevent multiple seeds from being planted during a given planting operation at a particular location, and wherein automatically adjusting comprises changing the setting of the double eliminator to a second setting. In another example, the component is a vacuum seed meter, and wherein automatically adjusting comprises changing a level of vacuum applied to the vacuum seed meter.

(46) In still another example, the component includes both a double eliminator to prevent multiple seeds from being planted during a given planting operation at a particular location, and a vacuum seed meter. In this case, automatically adjusting includes changing the double eliminator to a second setting changing the level of vacuum applied to the seed meter to a second setting.

(47) FIG. 8 is a flowchart of a method of planting seeds, in accordance with an illustrative embodiment. Method **800** of FIG. 8 is an alternative method to controlling a seed planting machine, relative to method **500** of FIG. 5, method **600** of FIG. 6, or method **700** of FIG. 7. Method **800** may be implemented using the control system shown in FIG. 4 using vacuum seed meter **200** of FIG. 2 and seed planting machine **104** of FIG. 1.

(48) Method **800** includes adjusting a vacuum level applied to a vacuum seed meter of a seed planting machine based on an attitude of the seed planting machine (operation **802**). Method **800** represents an alternative or possibly additional parameter used to control a seed planting machine or vacuum seed meter. For example, FIG. 3 illustrates one principle of operation, which is to use a map-based prescription for controlling optimization of which variety of seed is to be planted within a given zone. In addition, an attitude of the seed planting machine may be used to control the vacuum pressure, double eliminator settings, and/or other aspects of a seed planting machine.

(49) In an example embodiment, “attitude” refers to a tilt of the seed planting machine relative to a plane perpendicular to the direction of the force of gravity. For example, a seed planting machine has an attitude of zero when it is level, but may have a non-zero attitude when on a slope of a hill.

Sometimes, the attitude of the seed planting machine side-to-side may affect how much vacuum is needed to optimize the pick-up of seeds on the seed disk. In this case, adjustment of a meter parameter does not use a map based approach but rather simply a tilt of the seed planting machine may be monitored. However, in a different illustrative embodiment, a zone of a field, such as described with respect to FIG. 3, may be designated because the ground in that zone has a slope. Thus, the illustrative embodiments described with respect to FIGS. 3-7 may still be applied to a zone defined because the ground has a slope within that zone.

(50) Nevertheless, method **800** may be further modified or may have additional operations. For example, the attitude of the seed planting machine may be detected by a sensor. In another illustrative embodiment, the attitude of the seed planting machine may be determined based on a location of the seed planting machine in a field, a map of the field containing information of field contours and a direction of travel of the seed planting machine. In still another illustrative embodiment, adjusting configures the seed planting machine to maximize performance of planting of one of a plurality of different varieties of seed.

(51) In yet another illustrative embodiment, the seed planting machine further includes a double eliminator configured to prevent multiple seeds from being planted at a particular location. In this case, the method may further include adjusting the double eliminator based on the attitude. Additionally, adjusting the vacuum level and adjusting the double eliminator together may configure the seed planting machine to maximize performance of planting of one of a plurality of different varieties of seed.

(52) FIG. 9 is a block diagram of a multiple variety planter, in accordance with an illustrative embodiment. Multiple variety planter **900** may be seed planting machine **104** of FIG. 1. Multiple variety planter **900** may include vacuum seed meter **200** of FIG. 2. Multiple variety planter **900** may include or be in communication with the control system shown in FIG. 4. Multiple variety planter **900** may be used to implement any of the methods shown in FIG. 5 through FIG. 8.

(53) Multiple variety planter **900** may include planting machine **902**. Planting machine may include adjustable component **904**. Adjustable component **904** may be adjustable between first configuration **906** and second configuration **908**. First configuration **906** may be set to maximize planting efficiency of a first variety of seed relative to other varieties of seeds. Second configuration **908** may be set to maximize planting efficiency of a second variety of seed relative to other varieties of seeds.

(54) Multiple variety planter **900** may also include controller **910** in communication with planting machine **902**. Controller **910** may be configured to automatically adjust adjustable component **904** between first configuration **906** and second configuration **908** based on a particular location of planting machine **902** in a field of land comprising a plurality of different locations that include the particular location.

(55) Multiple variety planter **900** may be varied or modified. For example, controller **910** may be one or more components of the control system shown in FIG. 4. In another example, adjustable component **904** may be a double eliminator to prevent multiple seeds from being planted in the particular location. In still another example, adjustable component **904** may be a vacuum control system configured to control a vacuum level applied to a vacuum seed meter configured to dispense seeds during a given planting operation.

(56) In yet another example, adjustable component **904** may further be a double eliminator. In other words, adjustable component **904** includes both a vacuum control system and a double eliminator. In this case, the double eliminator may be configured to prevent multiple seeds from being planted in the particular location during a given planting operation. Additionally, both the double eliminator and the vacuum control system are configured to be adjusted as part of the adjustable component being adjusted.

(57) FIG. 10 is an illustration of a data processing system, in accordance with an illustrative embodiment. Data processing system **1000** in FIG. 10 is an example of a data processing system

that may be used to implement the illustrative embodiments, such as the control system shown in FIG. 4. For example, processor unit **1004** may be processor **406** of FIG. 4 and computer readable media **1020** may be non-transitory computer readable storage medium **410** of FIG. 4. Data processing system **1000** and computer readable media **1020** of FIG. 10 may be used to implement any of the methods shown in FIG. 5 through FIG. 8. Data processing system **1000** and computer readable media **1020** of FIG. 10 may be used as part or all of controller **910** of FIG. 9.

(58) In this illustrative example, data processing system **1000** includes communications fabric **1002**, which provides communications between processor unit **1004**, memory **1006**, persistent storage **1008**, communications unit **1010**, input/output (I/O) unit **1012**, and display **1014**. Processor unit **1004** serves to execute instructions for software that may be loaded into memory **1006**. Processor unit **1004** may be a number of processors, a multi-processor core, or some other type of processor, depending on the particular implementation. A number, as used herein with reference to an item, means one or more items. Further, processor unit **1004** may be implemented using a number of heterogeneous processor systems in which a main processor is present with secondary processors on a single chip. As another illustrative example, processor unit **1004** may be a symmetric multi-processor system containing multiple processors of the same type.

(59) Memory **1006** and persistent storage **1008** are examples of storage devices **1016**. A storage device is any piece of hardware that is capable of storing information, such as, for example, without limitation, data, program code in functional form, and/or other suitable information either on a temporary basis and/or a permanent basis. Storage devices **1016** may also be referred to as computer readable storage devices in these examples. Memory **1006**, in these examples, may be, for example, a random access memory or any other suitable volatile or non-volatile storage device. Persistent storage **1008** may take various forms, depending on the particular implementation.

(60) For example, persistent storage **1008** may contain one or more components or devices. For example, persistent storage **1008** may be a hard drive, a flash memory, a rewritable optical disk, a rewritable magnetic tape, or some combination of the above. The media used by persistent storage **1008** also may be removable. For example, a removable hard drive may be used for persistent storage **1008**.

(61) Communications unit **1010**, in these examples, provides for communications with other data processing systems or devices. In these examples, communications unit **1010** is a network interface card. Communications unit **1010** may provide communications through the use of either or both physical and wireless communications links.

(62) Input/output (I/O) unit **1012** allows for input and output of data with other devices that may be connected to data processing system **1000**. For example, input/output (I/O) unit **1012** may provide a connection for user input through a keyboard, a mouse, and/or some other suitable input device. Further, input/output (I/O) unit **1012** may send output to a printer. Display **1014** provides a mechanism to display information to a user.

(63) Instructions for the operating system, applications, and/or programs may be located in storage devices **1016**, which are in communication with processor unit **1004** through communications fabric **1002**. In these illustrative examples, the instructions are in a functional form on persistent storage **1008**. These instructions may be loaded into memory **1006** for execution by processor unit **1004**. The processes of the different embodiments may be performed by processor unit **1004** using computer implemented instructions, which may be located in a memory, such as memory **1006**.

(64) These instructions are referred to as program code, computer usable program code, or computer readable program code that may be read and executed by a processor in processor unit **1004**. The program code in the different embodiments may be embodied on different physical or computer readable storage media, such as memory **1006** or persistent storage **1008**.

(65) Program code **1018** is located in a functional form on computer readable media **1020** that is selectively removable and may be loaded onto or transferred to data processing system **1000** for execution by processor unit **1004**. Program code **1018** and computer readable media **1020** form

computer program product **1022** in these examples. In one example, computer readable media **1020** may be computer readable storage media **1024** or computer readable signal media **1026**. Computer readable storage media **1024** may include, for example, an optical or magnetic disk that is inserted or placed into a drive or other device that is part of persistent storage **1008** for transfer onto a storage device, such as a hard drive, that is part of persistent storage **1008**. Computer readable storage media **1024** also may take the form of a persistent storage, such as a hard drive, a thumb drive, or a flash memory, that is connected to data processing system **1000**. In some instances, computer readable storage media **1024** may not be removable from data processing system **1000**.

(66) Alternatively, program code **1018** may be transferred to data processing system **1000** using computer readable signal media **1026**. Computer readable signal media **1026** may be, for example, a propagated data signal containing program code **1018**. For example, computer readable signal media **1026** may be an electromagnetic signal, an optical signal, and/or any other suitable type of signal. These signals may be transmitted over communications links, such as wireless communications links, optical fiber cable, coaxial cable, a wire, and/or any other suitable type of communications link. In other words, the communications link and/or the connection may be physical or wireless in the illustrative examples.

(67) In some illustrative embodiments, program code **1018** may be downloaded over a network to persistent storage **1008** from another device or data processing system through computer readable signal media **1026** for use within data processing system **1000**. For instance, program code stored in a computer readable storage medium in a server data processing system may be downloaded over a network from the server to data processing system **1000**. The data processing system providing program code **1018** may be a server computer, a client computer, or some other device capable of storing and transmitting program code **1018**.

(68) The different components illustrated for data processing system **1000** are not meant to provide architectural limitations to the manner in which different embodiments may be implemented. The different illustrative embodiments may be implemented in a data processing system including components in addition to or in place of those illustrated for data processing system **1000**. Other components shown in FIG. **10** can be varied from the illustrative examples shown. The different embodiments may be implemented using any hardware device or system capable of running program code. As one example, the data processing system may include organic components integrated with inorganic components and/or may be comprised entirely of organic components excluding a human being. For example, a storage device may be comprised of an organic semiconductor.

(69) In another illustrative example, processor unit **1004** may take the form of a hardware unit that has circuits that are manufactured or configured for a particular use. This type of hardware may perform operations without needing program code to be loaded into a memory from a storage device to be configured to perform the operations.

(70) For example, when processor unit **1004** takes the form of a hardware unit, processor unit **1004** may be a circuit system, an application specific integrated circuit (ASIC), a programmable logic device, or some other suitable type of hardware configured to perform a number of operations. With a programmable logic device, the device is configured to perform the number of operations. The device may be reconfigured at a later time or may be permanently configured to perform the number of operations. Examples of programmable logic devices include, for example, a programmable logic array, programmable array logic, a field programmable logic array, a field programmable gate array, and other suitable hardware devices. With this type of implementation, program code **1018** may be omitted because the processes for the different embodiments are implemented in a hardware unit.

(71) In still another illustrative example, processor unit **1004** may be implemented using a combination of processors found in computers and hardware units. Processor unit **1004** may have a number of hardware units and a number of processors that are configured to run program code

1018. With this depicted example, some of the processes may be implemented in the number of hardware units, while other processes may be implemented in the number of processors.

(72) As another example, a storage device in data processing system **1000** is any hardware apparatus that may store data. Memory **1006**, persistent storage **1008**, and computer readable media **1020** are examples of storage devices in a tangible form.

(73) In another example, a bus system may be used to implement communications fabric **1002** and may be comprised of one or more buses, such as a system bus or an input/output bus. Of course, the bus system may be implemented using any suitable type of architecture that provides for a transfer of data between different components or devices attached to the bus system. Additionally, a communications unit may include one or more devices used to transmit and receive data, such as a modem or a network adapter. Further, a memory may be, for example, memory **1006**, or a cache, such as found in an interface and memory controller hub that may be present in communications fabric **1002**.

(74) The different illustrative embodiments can take the form of an entirely hardware embodiment, an entirely software embodiment, or an embodiment containing both hardware and software elements. Some embodiments are implemented in software, which includes but is not limited to forms, such as, for example, firmware, resident software, and microcode.

(75) Furthermore, the different embodiments can take the form of a computer program product accessible from a computer usable or computer readable medium providing program code for use by or in connection with a computer or any device or system that executes instructions. For the purposes of this disclosure, a computer usable or computer readable medium can generally be any tangible apparatus that can contain, store, communicate, propagate, or transport the program for use by or in connection with the instruction execution system, apparatus, or device.

(76) The computer usable or computer readable medium can be, for example, without limitation an electronic, magnetic, optical, electromagnetic, infrared, or semiconductor system, or a propagation medium. Non-limiting examples of a computer readable medium include a semiconductor or solid state memory, magnetic tape, a removable computer diskette, a random access memory (RAM), a read-only memory (ROM), a rigid magnetic disk, and an optical disk. Optical disks may include compact disk-read only memory (CD-ROM), compact disk-read/write (CD-R/W), and DVD.

(77) Further, a computer usable or computer readable medium may contain or store a computer readable or usable program code such that when the computer readable or usable program code is executed on a computer, the execution of this computer readable or usable program code causes the computer to transmit another computer readable or usable program code over a communications link. This communications link may use a medium that is, for example without limitation, physical or wireless.

(78) A data processing system suitable for storing and/or executing computer readable or computer usable program code will include one or more processors coupled directly or indirectly to memory elements through a communications fabric, such as a system bus. The memory elements may include local memory employed during actual execution of the program code, bulk storage, and cache memories which provide temporary storage of at least some computer readable or computer usable program code to reduce the number of times code may be retrieved from bulk storage during execution of the code.

(79) Input/output or I/O devices can be coupled to the system either directly or through intervening I/O controllers. These devices may include, for example, without limitation, keyboards, touch screen displays, and pointing devices. Different communications adapters may also be coupled to the system to enable the data processing system to become coupled to other data processing systems or remote printers or storage devices through intervening private or public networks. Non-limiting examples of modems and network adapters are just a few of the currently available types of communications adapters.

(80) The description of the different advantageous embodiments has been presented for purposes of

illustration and description, and is not intended to be exhaustive or limited to the embodiments in the form disclosed. Many modifications and variations will be apparent to those of ordinary skill in the art. Further, different embodiments may provide different advantages as compared to other embodiments. The embodiment or embodiments selected are chosen and described in order to best explain the principles of the invention, the practical application, and to enable others of ordinary skill in the art to understand the invention for various embodiments with various modifications as are suited to the particular use contemplated.

Claims

1. A planting system for planting seeds, the planting system comprising: an agricultural machine moveable through a field; and a planting control system, the planting control system comprising: a seed planting machine coupled to the agricultural machine and transported by the agricultural machine through the field, the seed planting machine configured to receive: map data including a map of the field, the map data of the field including a plurality of zones; and position data of a location of the seed planting machine in the field; and a changeable component that is adjustable in response to a zone of the plurality of zones in which the seed planting machine is located based at least on the received position data.
 2. The planting system of claim 1, further comprising a controller that includes a processor, wherein the processor is configured to determine that the seed planting machine has change in zones and, in response, is configured to automatically adjust the adjustable component based on the change in zones.
 3. The planting system of claim 1, wherein the changeable component comprises a vacuum seed meter, wherein a vacuum level applied to the vacuum seed meter is configured to be adjusted based at least on a zone of the plurality of zones in which the seed planting machine is present.
 4. The planting system of claim 3, further comprising a controller that utilizes the map data and position data to determine a location of the seed planting machine in the field and wherein the vacuum level applied to the vacuum seed meter is configured to be adjusted when the controller detects that the seed planting machine has moved from a first zone of the plurality of zones into a second zone of the plurality of zones.
 5. The planting system of claim 1, wherein the changeable component comprises a double eliminator.
 6. The planting system of claim 5, further comprising a controller that that utilizes the map data and position data to determine a location of the seed planting machine in the field and wherein the controller is configured to automatically adjust a setting of the double eliminator when the controller detects that the seed planting machine has moved from a first zone of the plurality of zones to a second zone of the plurality of zones.
-