

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent Application Publication

20250267595

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

ZHANG; Xiaobo

---

### USER EQUIPMENT AND BASE STATION FOR WIRELESS COMMUNICATION AND METHODS OF USING SAME

---

#### Abstract

A method and a device in a User Equipment (UE) and a base station for wireless communication. The UE first receives a first radio signal and a second radio signal, and then transmits a third radio signal. The first radio signal is used for determining a first signature sequence, and a receiving timing of the second radio signal is used for determining a transmitting timing of the third radio signal. The first signature sequence is used for generating the third radio signal. The first radio signal and the second radio signal are associated with a first synchronization sequence and a second synchronization sequence respectively, and the first synchronization sequence is different from the second synchronization sequence. Through the designs of the first radio signal and the second radio signal, system performances and transmission efficiency are improved.

---

**Inventors:** ZHANG; Xiaobo (Shanghai, CN)

**Applicant:** BUNKER HILL TECHNOLOGIES LLC (Allen, TX)

**Family ID:** 1000008577993

**Appl. No.:** 19/200165

**Filed:** May 06, 2025

#### Related U.S. Application Data

parent US continuation 18592470 20240229 parent-grant-document US 12317208 child US 19200165

parent US continuation 17971652 20221024 parent-grant-document US 11963118 child US 18592470

parent US continuation 17720331 20220414 parent-grant-document US 11895605 child US 17971652

parent US continuation 16662044 20191024 parent-grant-document US 11343785 child US

## Publication Classification

**Int. Cl.:** **H04W56/00** (20090101); **H04L5/00** (20060101); **H04L27/26** (20060101); **H04W52/04** (20090101); **H04W72/12** (20230101)

**U.S. Cl.:**

**CPC** **H04W56/001** (20130101); **H04L5/0048** (20130101); **H04L27/2613** (20130101); **H04W52/04** (20130101); **H04W72/12** (20130101);

---

## Background/Summary

**CROSS-REFERENCE TO RELATED APPLICATIONS [0001]** This application is a continuation of U.S. patent application Ser. No. 18/592,470, filed Feb. 29, 2024, which is a continuation of U.S. patent application Ser. No. 17/971,652, filed Oct. 24, 2022, now U.S. Pat. No. 11,963,118, which is a continuation of U.S. patent application Ser. No. 17/720,331, filed Apr. 14, 2022, now U.S. Pat. No. 11,895,605, which is a continuation of U.S. patent application Ser. No. 16/662,044, filed Oct. 24, 2019, now U.S. Pat. No. 11,343,785, which is a continuation of International patent application No. PCT/CN2017/081176, filed Apr. 27, 2017, the full disclosures of each which are incorporated herein by reference.

### FIELD OF THE INVENTION

[0002] The disclosure relates to transmission methods and devices in wireless communication systems, and in particular to a method and a device for communication between an air terminal and a ground device.

### BACKGROUND

[0003] In the 3rd Generation Partner Project (3GPP) R12, Device to Device (D2D) communication is approved and discussed. The nature of the D2D is to allow data transmission between User Equipments (UEs). In conventional D2D communication, considering the robustness of D2D transmission and interferences to cellular communication, when a D2D UE is in coverage, transmissions of the D2D UE on both sidelink and cellular link are controlled by a serving cell corresponding to the D2D UE.

[0004] In discussions about 5G in 3GPP, a Study Item (SI) of Enhanced Support for Aerial Vehicles has been approved and discussed in 3GPP. One feature of air communication is that transmissions of one air terminal device would be detected by multiple base stations, correspondingly, the transmission method between the air terminal and ground terminal needs to be reconsidered.

### SUMMARY

[0005] One important feature of air communication is that a terminal located in air, after reaching a certain height, generally has a Line of Sight (LOS) to a ground terminal and a base station. Due to reasons of LOS, when an air terminal in a target cell communicates with a ground terminal corresponding to the air terminal or a base station corresponding to the target cell, ground terminals in neighbor cells of the target cell and base stations corresponding to the neighbor cells can both receive signals coming from the air terminal, thereby causing large inter-cell interferences.

[0006] In current LTE D2D application scenarios, no matter the receiving object is a base station, or the receiving object is an opposite-end UE of a D2D transmitting terminal, transmissions of the

D2D transmitting terminal are all controlled by a serving cell of the transmitting terminal. The above method is to ensure that the transmissions of the D2D transmitting terminal do not cause interferences to cellular links. Communications between an air terminal and a ground terminal in air communication to a great extent will inherit transport protocols of LTE D2D communication. Meanwhile, in discussions of Vehicle to X (V2X) evolution based on D2D in Release 14, synchronization of the Global Navigation Satellite System (GNSS) is also introduced to the synchronization applications between D2D pair. In view of the feature that transmissions of an air terminal may be received by base stations corresponding to multiple ground cells and the feature that an air terminal is easier to synchronize with the GNSS, a new transmission method based on air terminal needs to be considered.

[0007] In view of the above problems, the disclosure provides a solution. It should be noted that the embodiments of the disclosure and the characteristics in the embodiments may be mutually combined arbitrarily if no conflict is incurred. For example, the embodiments of the UE of the disclosure and the characteristics in the embodiments may be applied to the base station, and vice versa.

[0008] The disclosure provides a method in a UE for wireless communication, wherein the method includes: [0009] receiving a first radio signal; [0010] receiving a second radio signal; and [0011] transmitting a third radio signal. [0012] wherein, the first radio signal is used for determining a first signature sequence, and a receiving timing of the second radio signal is used for determining a transmitting timing of the third radio signal; the first signature sequence is used for generating the third radio signal; the first radio signal and the second radio signal are associated with a first synchronization sequence and a second synchronization sequence respectively, and the first synchronization sequence is different from the second synchronization sequence.

[0013] In one embodiment, the above method is characterized in that: a transmitter of the first radio signal is different from a transmitter of the second radio signal, and the UE acquires generation indicators of timing and synchronization sequence from the two transmitters respectively.

[0014] In one embodiment, the above method has the following benefits: since an air terminal has an LOS to a ground base station or terminal, the air terminal communicates simultaneously with two ground devices, one of which is used for synchronization while the other is used for transmitting control information. The above method enables a more flexible transmission between the air terminal and the ground terminal, without transmitting all information of the air terminal through a serving cell, thereby avoiding the problem of frequent switching of the air terminal.

[0015] In one embodiment, the above method is further characterized in that: in present V2X design, when a synchronization source of the D2D device is the GNSS, a Sidelink Synchronization Sequence Identifier (SLSSID) of the D2D device used for generating a signature sequence of a synchronization sequence is fixed. In the above method, when the third radio signal is applied to an opposite-end device of the air device to perform synchronization and the second radio signal is a signal coming from the GNSS, the first signature sequence is configurable. The above method improves the flexibility of the system, thereby being easier to distinguish synchronization signals coming from different air devices.

[0016] In one embodiment, the above method is further characterized in that: when the third radio signal is used for at least one of Transmission Power Control (TPC), triggering the UE to transmit a reference signal, or triggering the UE to transmit channel state information, the transmission of the third radio signal triggers a cell other than the transmitter of the first radio signal and the transmitter of the second radio signal, thus, when an air terminal moves out of a serving cell, any one cell in the coverage of the air terminal supports transmission of non-scheduling control signalings to the air terminal, thereby further improving the mobility of the air terminal and increasing the flexibility of the system. Herein, all ground devices in the coverage can successfully detect signals transmitted from the air terminal.

[0017] In one embodiment, the first radio signal and the second radio signal are transmitted on one

same carrier.

[0018] In one embodiment, the first radio signal and the second radio signal are transmitted by a first transmitter and a second transmitter respectively. The first transmitter is associated with the first synchronization sequence, and the second transmitter is associated with the second synchronization sequence.

[0019] In one subembodiment, the first synchronization sequence corresponds to a first target identifier, the second synchronization sequence corresponds to a second target identifier, and the first target identifier is different from the second target identifier.

[0020] In one affiliated embodiment of the above subembodiment, the first target identifier is a Physical Cell Identifier (PCI).

[0021] In one affiliated embodiment of the above subembodiment, the second target identifier is a Physical Cell Identifier (PCI), or the second target identifier is a UE ID.

[0022] In one subembodiment, the first transmitter is one cell, and the second transmitter is one cell.

[0023] In one affiliated embodiment of the above subembodiment, the first transmitter is a serving cell corresponding to the UE.

[0024] In one affiliated embodiment of the above subembodiment, the second transmitter is a serving cell corresponding to the UE.

[0025] In one subembodiment, the first radio signal indicates a first identifier, and the first identifier is used for generating the first signature sequence.

[0026] In one affiliated embodiment of the above subembodiment, the first identifier is an SLSSID.

[0027] In one affiliated embodiment of the above subembodiment, the first identifier is an integer not less than 0 but not greater than 167.

[0028] In one affiliated embodiment of the above subembodiment, the first radio signal includes an SL-SyncConfig IE (Information Element) in TS 36.331.

[0029] In one subembodiment, the first transmitter is a cell, and the second transmitter is a target terminal.

[0030] In one affiliated embodiment of the above subembodiment, the first transmitter is a serving cell corresponding to the UE.

[0031] In one affiliated embodiment of the above subembodiment, the target terminal is an opposite-end terminal of the UE.

[0032] In one affiliated embodiment of the above subembodiment, the target terminal and the UE form a D2D pair.

[0033] In one affiliated embodiment of the above subembodiment, the first transmitter is a serving cell of the target terminal.

[0034] In one affiliated embodiment of the above subembodiment, the target terminal is a terminal used for terrestrial radio access.

[0035] In one embodiment, a receiving timing of the first radio signal is also used for determining the transmitting timing of the third radio signal.

[0036] In one embodiment, the first radio signal indicates a first identifier, and the first identifier is used for generating the first signature sequence.

[0037] In one embodiment, the first radio signal is generated by a target signature sequence, and the target signature sequence is equal to the first signature sequence.

[0038] In one embodiment, a target radio signal includes at least one of a Primary Synchronization Signal (PSS), a Secondary Synchronization Signal (SSS), a Primary Sidelink Synchronization Signal (PSSS) or a Secondary Sidelink Synchronization Signal (SSSS). The target radio signal is one of the first radio signal or the second radio signal.

[0039] In one embodiment, a target radio signal includes at least one of a Common Reference Signal (CRS), a Mobility Reference Signal (MRS), a Phase Tracking Reference Signal (PTRS), a Channel State Information-Reference Signal (CRS-RS), a Demodulation Reference Signal

(DMRS), a Discovery Reference Signal (DRS) or a NarrowBand Reference Signal (NRS). The target radio signal is one of the first radio signal or the second radio signal.

[0040] In one embodiment, a physical layer channel corresponding to the second radio signal is one of a Physical Sidelink Shared Channel (PSSCH), a Physical Sidelink Control Channel (PSCCH), a Physical Sidelink Discovery Channel (PSDCH) or a Physical Sidelink Broadcasting Channel (PSBCH).

[0041] In one embodiment, the third radio signal includes at least one of a PSSS, an SSSS, a Sounding Reference Signal (SRS) or an uplink DMRS.

[0042] In one embodiment, a physical layer channel corresponding to the third radio signal is one of a Physical Uplink Shared Channel (PUSCH), a Physical Uplink Control Channel (PUCCH), a New Radio PUSCH (N-PUSCH) or a New Radio PUCCH (N-PUCCH).

[0043] In one embodiment, a first transmitter transmits the first radio signal, a second transmitter transmits the second radio signal, the first transmitter includes one or more satellites, and the second transmitter is one cell.

[0044] In one subembodiment, the first transmitter is a GNSS.

[0045] In one subembodiment, a given SLSSID is used for initializing a generator of the first signature sequence, and the given SLS SID is equal to 0.

[0046] In one embodiment, a first transmitter transmits the first radio signal, a second transmitter transmits the second radio signal, the first transmitter is one cell, and the second transmitter includes one or more satellites.

[0047] In one subembodiment, the second transmitter is a GNSS.

[0048] In one embodiment, the first radio signal is generated after the first synchronization sequence is processed in sequence through a resource element mapper and an Orthogonal Frequency Division Multiplexing (OFDM) symbol generator.

[0049] In one embodiment, the second radio signal is generated after the second synchronization sequence is processed in sequence through a resource element mapper and an OFDM symbol generator.

[0050] In one embodiment, the first radio signal is generated after the first synchronization sequence is processed in sequence through precoding, a resource element mapper and an OFDM symbol generator.

[0051] In one embodiment, the second radio signal is generated after the second synchronization sequence is processed in sequence through precoding, a resource element mapper and an OFDM symbol generator.

[0052] In one embodiment, the first radio signal includes a given physical layer signaling, and a DCI format corresponding to the given physical layer signaling is one of DCI Formats 3, 3A or 3B.

[0053] In one embodiment, the cell in the disclosure corresponds to one LTE cell.

[0054] In one embodiment, the cell in the disclosure corresponds to one 5G cell.

[0055] In one embodiment, the cell in the disclosure corresponds to one 5G base station.

[0056] In one embodiment, the cell in the disclosure corresponds to one 5G Transmission Reception Point (TRP).

[0057] In one embodiment, a receiver of the third radio signal includes at least the former one of a target base station or a ground terminal.

[0058] In one subembodiment, the target base station includes a serving cell of the user terminal. In one subembodiment, the ground terminal and the UE share one same serving cell.

[0059] In one embodiment, the first radio signal is used for determining a first identifier, the first identifier is used for initializing a generator of the first signature sequence, the third radio signal corresponds to a PSSS, the first identifier corresponds to NDDSL in TS 36.211, and the first signature sequence corresponds to  $d_{sub,i}(n)$  in Chapter 9.7.1 in TS 36.211.

[0060] In one embodiment, the first radio signal is used for determining a first identifier, the first identifier is used for initializing a generator of the first signature sequence, the third radio signal

corresponds to an SSSS, the first identifier corresponds to NDDSL in TS 36.211, and the first signature sequence corresponds to d.sub.i(n) in Chapter 9.7.2 in TS 36.211.

[0061] In one embodiment, the first radio signal is used for determining a first identifier, the first identifier is used for initializing a generator of the first signature sequence, the third radio signal includes an SRS, and the first identifier corresponds to noDR RS in TS 36.211.

[0062] In one embodiment, the phrase that a receiving timing of the second radio signal is used for determining a transmitting timing of the third radio signal refers that: the UE selects a transmitter of the second radio signal as a synchronization reference source.

[0063] In one embodiment, the phrase that a receiving timing of the second radio signal is used for determining a transmitting timing of the third radio signal refers that: the UE selects a transmitter of the second radio signal as a synchronization reference source, and employs the second radio signal as a timing reference of the third radio signal.

[0064] According to one aspect of the disclosure, the method includes: [0065] monitoring K downlink signalings. [0066] wherein, the downlink signaling is a physical layer signaling, and the K downlink signalings are associated with K synchronization sequences respectively; any two of the K synchronization sequences are different; the K is a positive integer greater than 1; the second synchronization sequence is one of the K synchronization sequences; the K downlink signalings are identified by a first index respectively, and the first index is an integer.

[0067] In one embodiment, the above method is characterized in that: the UE monitors downlink signalings from multiple cells, so that the multiple cells can perform non-scheduling physical layer control on the UE simultaneously, thereby optimizing the mobility of the UE and the design flexibility of the system.

[0068] In one embodiment, the first index is a Cell Radio Network Temporary Identifier (C-RNTI).

[0069] In one embodiment, the downlink signaling is Downlink Control Information (DCI).

[0070] In one subembodiment, the K downlink signalings include K Cyclic Redundancy Check (CRC) parts respectively, and the K CRC parts are scrambled with the first index respectively.

[0071] In one embodiment, a physical layer identifier corresponding to the synchronization sequence is used for generating a scrambling sequence, and the scrambling sequence is used for scrambling of an associated downlink signaling.

[0072] In one subembodiment, the physical layer identifier is one PCI.

[0073] In one embodiment, the K synchronization sequences identify K cells respectively.

[0074] In one embodiment, the K downlink signalings are transmitted by K cells respectively, and the K cells are associated with the K synchronization sequences respectively.

[0075] In one subembodiment of the above two embodiments, the K cells are serving cells of the UE.

[0076] In one subembodiment of the above two embodiments, the first transmitter in the disclosure is one of the K cells.

[0077] In one subembodiment of the above two embodiments, the second transmitter in the disclosure is one of the K cells.

[0078] In one subembodiment of the above two embodiments, the K cells belong to a target cell group.

[0079] In one affiliated embodiment of the above subembodiment, any two cells in the target cell group have a backhaul link therebetween.

[0080] In one affiliated embodiment of the above subembodiment, all cells in the target cell group are Quasi Co-Located (QCLed) for the UE.

[0081] In an example of the above affiliated embodiment, the phrase that a given cell and a target cell are QCLed for the UE refers that: the UE can deduce large-scale properties of channels of radio signals transmitted by the target cell from large-scale properties of channels of radio signals transmitted from the given cell. The large-scale properties include one or more of delay spread, Doppler spread, Doppler shift, average gain, average delay, angle of arrival or angle of departure.

[0082] In one affiliated embodiment of the above subembodiment, the UE and all cells in the target cell group share one same Timing Advance (TA).

[0083] In one affiliated embodiment of the above subembodiment, the UE realizes uplink synchronization with any cell in the target cell group, and the UE considers that the UE realizes uplink synchronization with all cells in the target cell group.

[0084] In one embodiment, the UE monitors the K downlink signalings on one same carrier.

[0085] In one subembodiment, the monitoring refers that the UE determines the K downlink signalings through a blind decoding method.

[0086] In one embodiment, the UE blind decodes the K downlink signalings in K search spaces respectively.

[0087] In one embodiment, the UE blind decodes the K downlink signalings in K time-frequency resource sets respectively.

[0088] In one subembodiment, the time-frequency resource set includes a positive integer number of Resource Elements (REs).

[0089] In one subembodiment, the K time-frequency resource sets include two time-frequency resource sets which share one same RE.

[0090] In one subembodiment, the time-frequency resource set includes a positive integer number of Control Resource Sets (CORESETs).

[0091] In one embodiment, the synchronization sequence includes at least one of a pseudorandom sequence or a Zadoff-Chu sequence.

[0092] In one embodiment, the synchronization signal corresponds to a New Radio PSS (NR-PSS), and the synchronization sequence is a pure BPSK M sequence with a length of 127.

[0093] In one subembodiment, the NR-PSS is generated through one polynomial, and the polynomial corresponds to decimal **145**.

[0094] In one affiliated embodiment of the above subembodiment, the phrase that the polynomial corresponds to decimal **145** refers that the polynomial is  $g(x)=x^7+x^4+1$ .

[0095] In one subembodiment, the NR-PSS frequency-domain obtains three PSS signals through three cyclic shifts (0, 43, 86).

[0096] In one subembodiment, an initial Poly Shift Register Value of the NR-PSS is binary 1110110.

[0097] According to one aspect of the disclosure, the above method includes: [0098] monitoring a first signaling. [0099] wherein, the first synchronization sequence is one of the K synchronization sequences, and the UE assumes that only the first synchronization sequence among the K synchronization sequences is associated with the first signaling; a format of the first signaling is any one candidate format in a format set; and the format set includes a positive integer number of candidate formats.

[0100] In one embodiment, the above method is characterized in that: the first signaling is used for transmitting schedulings of data communication between the UE and a serving cell of the UE; or the first signaling is used for transmitting configurations of a control channel between the UE and a serving cell of the UE.

[0101] In one embodiment, the phase that the UE assumes that only the first synchronization sequence among the K synchronization sequences is associated with the first signaling refers that: the user terminal descrambles the first signaling using one scrambling sequence only, and only the first synchronization sequence among the K synchronization sequences is used for generating the scrambling sequence.

[0102] In one embodiment, the UE assumes that a transmitter of the first signaling and a transmitter of the first radio signal are one same cell, and the cell is a serving cell of the UE.

[0103] In one embodiment, the phase that the UE assumes that only the first synchronization sequence among the K synchronization sequences is associated with the first signaling refers that: only the first synchronization sequence among the K synchronization sequences shares one

transmitter with the first signaling.

[0104] In one embodiment, the phase that only the first synchronization sequence among the K synchronization sequences is associated with the first signaling refers that: only the first synchronization sequence among the K synchronization sequences shares a unique given identifier with the first signaling.

[0105] In one subembodiment, the given identifier is used for initializing a generator of the first synchronization sequence.

[0106] In one subembodiment, the given identifier is used for scrambling of a CRC of the first signaling.

[0107] In one subembodiment, the given identifier is one PCI.

[0108] In one embodiment, the format set includes a DCI Format 5.

[0109] In one embodiment, the format set includes a DCI Format 5A.

[0110] In one embodiment, the format set includes at least one of a first format or a second format. The first format is an uplink grant DCI, and the second format is a downlink grant DCI.

[0111] In one subembodiment, the uplink grant DCI includes DCI formats 0, 4, 4A or 4B.

[0112] In one subembodiment, the downlink grant DCI includes DCI formats 1, 1A, 1B, 1C, 1D, 2, 2A, 2B, 2C, 2D.

[0113] According to one aspect of the disclosure, the method includes: [0114] transmitting a fourth radio signal. [0115] wherein, the first signaling is used for determining scheduling information of the fourth radio signal; and the scheduling information includes at least one of occupied time-domain resources, occupied frequency-domain resources, a Modulation and Coding Status (MCS), a New Data Indicator (NDI), a Redundancy Version (RV), or a Hybrid Automatic Repeat reQuest (HARQ) process number.

[0116] In one embodiment, the above method is characterized in that: the fourth radio signal is a data channel scheduled by the first signaling; or the fourth radio signal is a control channel configured by the first signaling.

[0117] In one embodiment, the Modulation and Coding Status is abbreviated to MCS.

[0118] In one embodiment, the New Data Indicator is abbreviated to NDI.

[0119] In one embodiment, the Redundancy Version is abbreviated to RV.

[0120] In one embodiment, the Hybrid Automatic Repeat reQuest is abbreviated to HARQ.

[0121] In one embodiment, the first signaling is a higher-layer signaling, and the fourth radio signal is transmitted on a Physical Sidelink Control Channel (PSCCH).

[0122] In one embodiment, the first signaling is a higher-layer signaling, and the fourth radio signal is transmitted on one of a PUCCH or an N-PUCCH.

[0123] In one embodiment, the first signaling is a higher-layer signaling, and the fourth radio signal is transmitted on a Physical Sidelink Shared Channel (PSSCH).

[0124] In one embodiment, the first signaling is a higher-layer signaling, and the fourth radio signal is transmitted on one of a PUSCH or an N-PUSCH.

[0125] In one subembodiment of the above two embodiments, the physical layer signaling is a DCI.

[0126] In one subembodiment of the above two embodiments, the physical layer signaling is an SCI.

[0127] According to one aspect of the disclosure, the method includes: receiving a second signaling. [0128] wherein, the second signaling is used for determining K time-frequency resource sets or the K synchronization sequences or both; the second signaling is associated with the first synchronization sequence; the first radio signal indicates a first identifier, and the first identifier is used for generating the first signature sequence.

[0129] In one embodiment, the above method is characterized in that: the second signaling is used for configuring the K time-frequency resource sets, and is used for configuring the K synchronization sequences. The above method increases the flexibility of the system.



[0130] In one embodiment, the UE monitors the K downlink signalings in the K time-frequency resource sets respectively.

[0131] In one embodiment, a transmitter of the second signaling is a serving cell of the UE.

[0132] In one embodiment, the first synchronization sequence is one of the K synchronization sequences.

[0133] In one embodiment, the second signaling is a higher-layer signaling.

[0134] In one subembodiment, the higher-layer signaling is a Radio Resource Control (RRC) signaling.

[0135] In one subembodiment, the higher-layer signaling is UE-specific.

[0136] In one subembodiment, the higher-layer signaling is cell-specific.

[0137] In one subembodiment, a physical layer identifier corresponding to the first synchronization sequence is used for generating a first scrambling sequence, the first scrambling sequence is used for scrambling of a second physical layer signaling, and the second physical layer signaling is used for determining time-frequency resources occupied by the second signaling.

[0138] In one affiliated embodiment of the above subembodiment, the physical layer identifier is one PCI.

[0139] In one embodiment, a transmitter of the second signaling is a terminal.

[0140] In one embodiment, a transmitter of the second signaling is a transmitter of the first radio signal.

[0141] In one embodiment, the first identifier is an integer not less than 0 but not greater than 167.

[0142] In one embodiment, the first identifier belongs to a given identifier set, and the given identifier set includes a positive integer number of identifiers.

[0143] In one subembodiment, the second signaling indicates the given identifier set.

[0144] In one subembodiment, a higher-layer signaling indicates the given identifier set.

[0145] In one subembodiment, the first radio signal is used for determining the first identifier from the given identifier set.

[0146] In one subembodiment, the K synchronization sequences correspond to K nodes respectively, and the K nodes share the given identifier set.

[0147] In one affiliated embodiment of the subembodiment, the K nodes correspond to K cells respectively, and the first identifier corresponds to the UE uniquely among terminals served by the K cells.

[0148] In one affiliated embodiment of the subembodiment, the K nodes correspond to transmitters of the K downlink signalings respectively.

[0149] According to one aspect of the disclosure, the method includes: [0150] transmitting a fifth radio signal. [0151] wherein, a receiving timing of the first radio signal is used for determining a transmitting timing of the fifth radio signal, and the first signature sequence is used for generating the fifth radio signal.

[0152] In one embodiment, the above method is characterized in that: when the UE does not receive the second radio signal, the UE takes a receiving timing of the first radio signal as a transmitting timing.

[0153] In one embodiment, the fifth radio signal includes at least one of a PSSS, an SSSS, an SRS or an uplink DMRS.

[0154] In one embodiment, a physical layer channel corresponding to the fifth radio signal is one of a PUSCH, a PUCCH, an N-PUSCH or an N-PUCCH.

[0155] In one embodiment, a receiver of the fifth radio signal includes at least the former one of a target base station or a ground terminal.

[0156] In one embodiment, the first radio signal is used for determining a first identifier, the first identifier is used for initializing a generator of the first signature sequence, the fifth radio signal corresponds to a PSSS, the first identifier corresponds to N.sub.ID.sup.SL in TS 36.211, and the first signature sequence corresponds to d.sub.i(n) in Chapter 9.7.1 in TS 36.211.

[0157] In one embodiment, the first radio signal is used for determining a first identifier, the first identifier is used for initializing a generator of the first signature sequence, the fifth radio signal corresponds to an SSSS, the first identifier corresponds to N.sub.ID.sup.SL in TS 36.211, and the first signature sequence corresponds to d.sub.i(n) in Chapter 9.7.2 in TS 36.211.

[0158] In one embodiment, the first radio signal is used for determining a first identifier, the first identifier is used for initializing a generator of the first signature sequence, the fifth radio signal includes an SRS, and the first identifier corresponds to n.sub.ID.sup.DRS in TS 36.211.

[0159] According to one aspect of the disclosure, the downlink signaling is used for at least one of Transmission Power Control (TPC), triggering the UE to transmit a reference signal, or triggering the UE to transmit channel state information.

[0160] In one embodiment, the Transmission Power Control is abbreviated to PTC.

[0161] In one embodiment, the reference signal includes an SRS.

[0162] In one embodiment, the Channel State information is abbreviated to CSI.

[0163] In one embodiment, the channel state information includes at least one of a Channel Quality Indicator (CQI), a Precoding Matrix Indicator (PMI), an Rank Indicator (RI) or a CSI-RS Resource Indicator (CRI).

[0164] In one embodiment, a given downlink signaling is used for at least one of a TPC of the UE, triggering the UE to transmit a reference signal, or triggering the UE to transmit channel state information, and the given downlink signaling is one of the K downlink signalings.

[0165] In one subembodiment, a transmitter of the given downlink signaling is different from a transmitter of the first signaling.

[0166] In one subembodiment, a transmitter of the given downlink signaling is the same as a transmitter of the first signaling.

[0167] In one subembodiment, a transmitter of the given downlink signaling is a cell other than a serving cell of the UE.

[0168] The disclosure provides a method in a base station for wireless communication, wherein the method includes: [0169] transmitting a first radio signal. [0170] wherein, the first radio signal is used for determining a first signature sequence, and a receiving timing of a second radio signal is used for determining a transmitting timing of a third radio signal; the first signature sequence is used for generating the third radio signal; the first radio signal and the second radio signal are associated with a first synchronization sequence and a second synchronization sequence respectively, and the first synchronization sequence is different from the second synchronization sequence.

[0171] In one embodiment, the base station is a serving cell of a transmitter of the third radio signal.

[0172] According to one aspect of the disclosure, the method includes: [0173] receiving a third radio signal.

[0174] According to one aspect of the disclosure, the method includes: [0175] transmitting a first downlink signaling. [0176] wherein, the first downlink signaling is a physical layer signaling, and K downlink signalings are associated with K synchronization sequences respectively; any two of the K synchronization sequences are different; the K is a positive integer greater than 1; the second synchronization sequence is one of the K synchronization sequences; the K downlink signalings are identified by a first index respectively, and the first index is an integer; and the first downlink signaling is one of the K downlink signalings.

[0177] According to one aspect of the disclosure, the method includes: [0178] transmitting a first signaling. [0179] wherein, the first synchronization sequence is one of the K synchronization sequences, and only the first synchronization sequence among the K synchronization sequences is associated with the first signaling; a format of the first signaling is any one candidate format in a format set; and the format set includes a positive integer number of candidate formats.

[0180] According to one aspect of the disclosure, the method includes: [0181] receiving a fourth

radio signal. [0182] wherein, the first signaling is used for determining scheduling information of the fourth radio signal; and the scheduling information includes at least one of occupied time-domain resources, occupied frequency-domain resources, an MCS, an NDI, an RV, or a HARQ process number.

[0183] According to one aspect of the disclosure, the method includes: [0184] transmitting a second signaling. [0185] wherein, the second signaling is used for determining K time-frequency resource sets or the K synchronization sequences or both; the second signaling is associated with the first synchronization sequence; the first radio signal indicates a first identifier, and the first identifier is used for generating the first signature sequence.

[0186] According to one aspect of the disclosure, the method includes: [0187] receiving a fifth radio signal. [0188] wherein, a receiving timing of the first radio signal is used for determining a transmitting timing of the fifth radio signal, and the first signature sequence is used for generating the fifth radio signal.

[0189] According to one aspect of the disclosure, the above method is characterized in that: the downlink signaling is used for at least one of TPC, triggering a transmitter of the third radio signal to transmit a reference signal, or triggering a transmitter of the third radio signal to transmit channel state information.

[0190] The disclosure provides a method in a communication node for wireless communication, wherein the method includes: [0191] transmitting a second radio signal. [0192] wherein, a receiving timing of the second radio signal is used for determining a transmitting timing of a third radio signal; a first signature sequence is used for generating the third radio signal; a first radio signal is used for determining the first signature sequence; the first radio signal and the second radio signal are associated with a first synchronization sequence and a second synchronization sequence respectively, and the first synchronization sequence is different from the second synchronization sequence.

[0193] In one embodiment, the communication node is a GNSS.

[0194] In one embodiment, the communication node includes one or more satellites.

[0195] In one embodiment, the second radio signal is a Global Positioning System (GPS) signal.

[0196] In one embodiment, the communication node is one cell.

[0197] In one embodiment, the communication node is one terminal.

[0198] According to one aspect of the disclosure, the method includes: [0199] receiving a third radio signal.

[0200] In one embodiment, when the communication node is one terminal, the communication node receives the third radio signal.

[0201] The disclosure provides a UE for wireless communication, wherein the UE includes: [0202] a first transceiver, to receive a first radio signal; [0203] a first receiver, to receive a second radio signal; and [0204] a first transmitter, to transmit a third radio signal. [0205] wherein, the first radio signal is used for determining a first signature sequence, and a receiving timing of the second radio signal is used for determining a transmitting timing of the third radio signal; the first signature sequence is used for generating the third radio signal; the first radio signal and the second radio signal are associated with a first synchronization sequence and a second synchronization sequence respectively, and the first synchronization sequence is different from the second synchronization sequence.

[0206] In one embodiment, the above UE for wireless communication is characterized in that: the first transceiver further monitors K downlink signalings; the downlink signaling is a physical layer signaling, and the K downlink signalings are associated with K synchronization sequences respectively; any two of the K synchronization sequences are different; the K is a positive integer greater than 1; the second synchronization sequence is one of the K synchronization sequences; the K downlink signalings are identified by a first index respectively, and the first index is an integer.

[0207] In one embodiment, the above UE for wireless communication is characterized in that: the

first transceiver further monitors a first signaling; the first synchronization sequence is one of the K synchronization sequences, and the UE assumes that only the first synchronization sequence among the K synchronization sequences is associated with the first signaling; a format of the first signaling is any one candidate format in a format set; and the format set includes a positive integer number of candidate formats.

[0208] In one embodiment, the above UE for wireless communication is characterized in that: the first transceiver further transmits a fourth radio signal; the first signaling is used for determining scheduling information of the fourth radio signal; and the scheduling information includes at least one of occupied time-domain resources, occupied frequency-domain resources, an MCS, an NDI, an RV, or a HARQ process number.

[0209] In one embodiment, the above UE for wireless communication is characterized in that: the first transceiver further receives a second signaling; the second signaling is used for determining K time-frequency resource sets or the K synchronization sequences or both; the second signaling is associated with the first synchronization sequence; the first radio signal indicates a first identifier, and the first identifier is used for generating the first signature sequence.

[0210] In one embodiment, the above UE for wireless communication is characterized in that: the first transceiver further transmits a fifth radio signal; a receiving timing of the first radio signal is used for determining a transmitting timing of the fifth radio signal, and the first signature sequence is used for generating the fifth radio signal.

[0211] In one embodiment, the above UE for wireless communication is characterized in that: the downlink signaling is used for at least one of TPC, triggering the UE to transmit a reference signal, or triggering the UE to transmit channel state information.

[0212] The disclosure provides a base station for wireless communication, wherein the base station includes: [0213] a second transceiver, to transmit a first radio signal. [0214] wherein, the first radio signal is used for determining a first signature sequence, and a receiving timing of a second radio signal is used for determining a transmitting timing of a third radio signal; the first signature sequence is used for generating the third radio signal; the first radio signal and the second radio signal are associated with a first synchronization sequence and a second synchronization sequence respectively, and the first synchronization sequence is different from the second synchronization sequence.

[0215] In one embodiment, the above base station for wireless communication includes: [0216] a second receiver, to receive a third radio signal.

[0217] In one embodiment, the above base station for wireless communication is characterized in that: the second transceiver further transmits a first downlink signaling; the first downlink signaling is a physical layer signaling, and K downlink signalings are associated with K synchronization sequences respectively; any two of the K synchronization sequences are different; the K is a positive integer greater than 1; the second synchronization sequence is one of the K synchronization sequences; the K downlink signalings are identified by a first index respectively, and the first index is an integer; and the first downlink signaling is one of the K downlink signalings.

[0218] In one embodiment, the above base station for wireless communication is characterized in that: the second transceiver further transmits a first signaling; the first synchronization sequence is one of the K synchronization sequences, and only the first synchronization sequence among the K synchronization sequences is associated with the first signaling; a format of the first signaling is any one candidate format in a format set; and the format set includes a positive integer number of candidate formats.

[0219] In one embodiment, the above base station for wireless communication is characterized in that: the second transceiver further receives a fourth radio signal; the first signaling is used for determining scheduling information of the fourth radio signal; and the scheduling information includes at least one of occupied time-domain resources, occupied frequency-domain resources, an

MCS, an NDI, an RV, or a HARQ process number.

[0220] In one embodiment, the above base station for wireless communication is characterized in that: the second transceiver further transmits a second signaling; the second signaling is used for determining K time-frequency resource sets or the K synchronization sequences or both; the second signaling is associated with the first synchronization sequence; the first radio signal indicates a first identifier, and the first identifier is used for generating the first signature sequence.

[0221] In one embodiment, the above base station for wireless communication is characterized in that: the second transceiver further receives a fifth radio signal; a receiving timing of the first radio signal is used for determining a transmitting timing of the fifth radio signal, and the first signature sequence is used for generating the fifth radio signal.

[0222] In one embodiment, the above base station for wireless communication is characterized in that: the downlink signaling is used for at least one of TPC, triggering a transmitter of the third radio signal to transmit a reference signal, or triggering a transmitter of the third radio signal to transmit channel state information.

[0223] The disclosure provides a communication node for wireless communication, wherein the communication node includes: [0224] a third transceiver, to transmit a second radio signal. [0225] wherein, a receiving timing of the second radio signal is used for determining a transmitting timing of a third radio signal; a first signature sequence is used for generating the third radio signal; a first radio signal is used for determining the first signature sequence; the first radio signal and the second radio signal are associated with a first synchronization sequence and a second synchronization sequence respectively, and the first synchronization sequence is different from the second synchronization sequence.

[0226] In one embodiment, the above communication node for wireless communication is characterized in that: the third transceiver further receives a third radio signal.

[0227] In one embodiment, the above communication node for wireless communication is characterized in that: the communication node is a GNSS.

[0228] In one embodiment, the above communication node for wireless communication is characterized in that: the communication node includes one or more satellites.

[0229] In one embodiment, the above communication node for wireless communication is characterized in that: the second radio signal is a GPS signal.

[0230] In one embodiment, the above communication node for wireless communication is characterized in that: the communication node is one cell.

[0231] In one embodiment, the above communication node for wireless communication is characterized in that: the communication node is one terminal.

[0232] In one embodiment, compared with the prior art, the disclosure has the following advantages.

[0233] According to the design in the disclosure, a transmitter of the first radio signal is different from a transmitter of the second radio signal, and the UE acquires generation indicators of timing and synchronization sequence from the two transmitters respectively. When the disclosure is applied to an air terminal, the air terminal communicates simultaneously with two ground devices, one of which is used for synchronization while the other is used for transmitting control information. The above method enables a more flexible transmission between the air terminal and the ground terminal, without transmitting all information of the air terminal through a serving cell, thereby avoiding the problem of frequent switching of the air terminal.

[0234] In present V2X design, when a synchronization source of the D2D device is GNSS, an SLSSID of the D2D device used for generating a signature sequence of a synchronization sequence is fixed. In the above method, when the third radio signal is applied to an opposite-end device of the air device to perform synchronization and the second radio signal is a signal coming from the GNSS, the first signature sequence is configurable. The above method improves the flexibility of the system, thereby being easier to distinguish synchronization signals coming from different air

devices.

[0235] Through the design of the third radio signal, when the third radio signal is used for at least one of TPC, triggering the UE to transmit a reference signal, or triggering the UE to transmit channel state information, the transmission of the third radio signal triggers a cell other than the transmitter of the first radio signal and the transmitter of the second radio signal, thus, when an air terminal moves out of a serving cell, any one cell in the coverage of the air terminal supports transmission of non-scheduling control signalings to the air terminal, thereby further improving the mobility of the air terminal and increasing the flexibility of the system.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

[0236] Other features, purposes and advantages of the disclosure will become more apparent from the detailed description of non-restrictive embodiments taken in conjunction with the following drawings.

[0237] FIG. 1 is a flowchart of processing of a UE according to one embodiment of the disclosure.

[0238] FIG. 2 is a diagram illustrating a network architecture according to one embodiment of the disclosure.

[0239] FIG. 3 is a diagram illustrating an embodiment of a radio protocol architecture of a user plane and a control plane according to one embodiment of the disclosure.

[0240] FIG. 4 is a diagram illustrating a first communication equipment and a second communication equipment according to one embodiment of the disclosure.

[0241] FIG. 5 is a flowchart of transmission of a first radio signal according to one embodiment of the disclosure.

[0242] FIG. 6 is a diagram illustrating an application scenario according to one embodiment of the disclosure.

[0243] FIG. 7 is a diagram illustrating an application scenario according to another embodiment of the disclosure.

[0244] FIG. 8 is a diagram illustrating a time sequence of a first radio signal and a second radio signal according to one embodiment of the disclosure.

[0245] FIG. 9 is a structure block diagram illustrating a processing device in a UE according to one embodiment of the disclosure.

[0246] FIG. 10 is a structure block diagram illustrating a processing device in a base station according to one embodiment of the disclosure.

[0247] FIG. 11 is a structure block diagram illustrating a processing device in a communication node according to one embodiment of the disclosure.

### DESCRIPTION OF THE EMBODIMENTS

[0248] The technical scheme of the disclosure is described below in further detail in conjunction with the drawings. It should be noted that the embodiments in the disclosure and the characteristics of the embodiments may be mutually combined arbitrarily if no conflict is incurred.

#### Embodiment 1

[0249] Embodiment 1 illustrates an example of a flowchart of processing of one UE, as shown in FIG. 1. In 100 shown in FIG. 1, each box represents one step. In Embodiment 1, the UE receives a first radio signal in S101, receives a second radio signal in S102, and transmits a third radio signal in S103; the first radio signal is used for determining a first signature sequence, and a receiving timing of the second radio signal is used for determining a transmitting timing of the third radio signal; the first signature sequence is used for generating the third radio signal; the first radio signal and the second radio signal are associated with a first synchronization sequence and a second synchronization sequence respectively, and the first synchronization sequence is different from the

second synchronization sequence.

## Embodiment 2

[0250] Embodiment 2 illustrates an example of a diagram of a network architecture, as shown in FIG. 2.

[0251] FIG. 2 is a diagram illustrating a network architecture **200** of 5G NR, Long-Term Evolution (LTE) and Long-Term Evolution Advanced (LTE-A) systems. The 5G NR or LTE network architecture **200** may be called an Evolved Packet System (EPS) **200** or some other appropriate terms. The EPS **200** may include one or more UEs **201**, a Next Generation-Radio Access Network (NG-RAN) **202**, an Evolved Packet Core/5G-Core Network (EPC/5G-CN) **210**, a Home Subscriber Server (HSS) **220** and an Internet service **230**. The EPS may be interconnected with other access networks. For simple description, the entities/interfaces are not shown. As shown in FIG. 2, the EPS provides packet switching services. Those skilled in the art are easy to understand that various concepts presented throughout the disclosure can be extended to networks providing circuit switching services or other cellular networks. The NG-RAN includes an NR node B (gNB) **203** and other gNBs **204**. The gNB **203** provides UE **201** oriented user plane and control plane protocol terminations. The gNB **203** may be connected to other gNBs **204** via an Xn interface (for example, backhaul). The gNB **203** may be called a base station, a base transceiver station, a radio base station, a radio transceiver, a transceiver function, a Basic Service Set (BSS), an Extended Service Set (ESS), a TRP or some other appropriate terms. The gNB **203** provides an access point of the EPC/5G-CN **210** for the UE **201**. Examples of UE **201** include cellular phones, smart phones, Session Initiation Protocol (SIP) phones, laptop computers, Personal Digital Assistants (PDAs), satellite radios, non-terrestrial base station communications, satellite mobile communications, Global Positioning Systems (GPSs), multimedia devices, video devices, digital audio player (for example, MP3 players), cameras, games consoles, unmanned aerial vehicles, air vehicles, narrow-band physical network equipment, machine-type communication equipment, land vehicles, automobiles, wearable equipment, or any other devices having similar functions. Those skilled in the art may also call the UE **201** a mobile station, a subscriber station, a mobile unit, a subscriber unit, a wireless unit, a remote unit, a mobile device, a wireless device, a radio communication device, a remote device, a mobile subscriber station, an access terminal, a mobile terminal, a wireless terminal, a remote terminal, a handset, a user proxy, a mobile client, a client or some other appropriate terms. The gNB **203** is connected to the EPC/5G-CN **210** via an S1/NG interface. The EPC/5G-CN **210** includes a Mobility Management Entity/Authentication Management Field/User Plane Function (MME/AMF/UPF) **211**, other MMEs/AMFs/UPFs **214**, a Service Gateway (S-GW) **212** and a Packet Data Network Gateway (P-GW) **213**. The MME/AMF/UPF **211** is a control node for processing a signaling between the UE **201** and the EPC/5G-CN **210**. Generally, the MME/AMF/UPF **211** provides bearer and connection management. All user Internet Protocol (IP) packets are transmitted through the S-GW **212**. The S-GW **212** is connected to the P-GW **213**. The P-GW **213** provides UE IP address allocation and other functions. The P-GW **213** is connected to the Internet service **230**. The Internet service **230** includes IP services corresponding to operators, specifically including internet, intranet, IP Multimedia Subsystems (IP IMSs) and PS Streaming Services (PSSs).

[0252] In one embodiment, the UE **201** corresponds to the UE in the disclosure.

[0253] In one embodiment, the UE **241** corresponds to the communication node in the disclosure.

[0254] In one embodiment, the gNB **203** corresponds to the base station in the disclosure.

## Embodiment 3

[0255] Embodiment 3 illustrates a diagram of an embodiment of a radio protocol architecture of a user plane and a control plane according to the disclosure, as shown in FIG. 3. FIG. 3 is a diagram illustrating an embodiment of a radio protocol architecture of a user plane **350** and a control plane **300**. In FIG. 3, the radio protocol architecture of a control plane **300** between a first communication node (UE, gNB or RSU in V2X) and a second communication node (gNB, UE or RSU in V2X) or

between two UEs is illustrated by three layers, which are a Layer 1, a Layer 2 and a Layer 3 respectively. The Layer 1 (L1 layer) **301** is the lowest layer and implements various PHY (physical layer) signal processing functions. The L1 layer will be referred to herein as the PHY **301**. The Layer 2 (L2 layer) **305** is above the PHY **301**, and is responsible for the link between the first communication node and the second communication node and between two UEs over the PHY **301**. The L2 layer **305** includes a Medium Access Control (MAC) sublayer **302**, a Radio Link Control (RLC) sublayer **303**, and a Packet Data Convergence Protocol (PDCP) sublayer **304**, which are terminated at the second communication node. The PDCP sublayer **304** provides multiplexing between different radio bearers and logical channels. The PDCP sublayer **304** also provides security by encrypting packets and provides support for handover of the first communication node between the second communication nodes. The RLC sublayer **303** provides segmentation and reassembling of higher-layer packets, retransmission of lost packets, and reordering of lost packets to as to compensate for out-of-order reception due to HARQ. The MAC sublayer **302** provides multiplexing between logical channels and transport channels. The MAC sublayer **302** is also responsible for allocating various radio resources (i.e., resource blocks) in one cell among the first communication nodes. The MAC sublayer **302** is also in charge of HARQ operations. The RRC sublayer **306** in the Layer 3 (L3 layer) in the control plane **300** is responsible for acquiring radio resources (i.e. radio bearers) and configuring lower layers using an RRC signaling between the second communication node and the first communication node. The radio protocol architecture of the user plane **350** includes a Layer 1 (L1 layer) and a Layer 2 (L2 layer); the radio protocol architecture for the first communication node and the second communication node in the user plane **350** on the PHY **351**, the PDCP sublayer **354** in the L2 layer **305**, the RLC sublayer **353** in the L2 layer **355** and the MAC sublayer **352** in the L2 layer **355** is substantially the same as the radio protocol architecture on corresponding layers and sublayers in the control plane **300**, with the exception that the PDCP sublayer **354** also provides header compression for higher-layer packets so as to reduce radio transmission overheads. The L2 layer **355** in the user plane **350** further includes a Service Data Adaptation Protocol (SDAP) sublayer **356**; the SDAP sublayer **356** is in charge of mappings between QoS flows and Data Radio Bearers (DRBs), so as to support diversification of services. Although not shown, the first communication node may include several higher layers above the L2 layer **355**, including a network layer (i.e. IP layer) terminated at the P-GW on the network side and an application layer terminated at the other end (i.e. a peer UE, a server, etc.) of the connection.

[0256] In one embodiment, the radio protocol architecture shown in FIG. 3 is applicable to the UE in the disclosure.

[0257] In one embodiment, the radio protocol architecture shown in FIG. 3 is applicable to the base station in the disclosure.

[0258] In one embodiment, the radio protocol architecture shown in FIG. 3 is applicable to the communication node in the disclosure.

#### Embodiment 4

[0259] Embodiment 4 illustrates a diagram of a first communication equipment and a second communication equipment according to the disclosure, as shown in FIG. 4. FIG. 4 is a block diagram of a first communication equipment **450** and a second communication equipment **410** that are in communication with each other in an access network.

[0260] The first communication equipment **450** includes a controller/processor **459**, a memory **460**, a data source **467**, a transmitting processor **468**, a receiving processor **456**, a multi-antenna transmitting processor **457**, a multi-antenna receiving processor **458**, a transmitter/receiver **454** and an antenna **452**.

[0261] The second communication equipment **410** includes a controller/processor **475**, a memory **476**, a receiving processor **470**, a transmitting processor **416**, a multi-antenna receiving processor **472**, a multi-antenna transmitting processor **471**, a transmitter/receiver **418** and an antenna **420**.



[0262] In a transmission from the second communication equipment **410** to the first communication equipment **450**, at the second communication equipment **410**, a higher-layer packet from a core network is provided to the controller/processor **475**. The controller/processor **475** provides functions of Layer 2. In the transmission from the second communication equipment **410** to the first communication equipment **450**, the controller/processor **475** provides header compression, encryption, packet segmentation and reordering, multiplexing between a logical channel and a transport channel, and a radio resource allocation for the first communication equipment **450** based on various priority metrics. The controller/processor **475** is also in charge of retransmission of lost packets, and signalings to the first communication equipment **450**. The transmitting processor **416** and the multi-antenna transmitting processor **471** perform various signal processing functions used for Layer 1 (that is, PHY). The transmitting processor **416** performs encoding and interleaving so as to ensure FEC (Forward Error Correction) at the second communication equipment **410** and mappings to signal clusters corresponding to different modulation schemes (i.e., BPSK, QPSK, M-PSK M-QAM, etc.). The multi-antenna transmitting processor **471** processes the encoded and modulated symbols with digital spatial precoding (including precoding based on codebook and precoding based on non-codebook) and beamforming to generate one or more spatial streams. The transmitting processor **416** subsequently maps each spatial stream into a subcarrier to be multiplexed with a reference signal (i.e., pilot) in time domain and/or frequency domain, and then processes it with Inverse Fast Fourier Transform (IFFT) to generate a physical channel carrying time-domain multicarrier symbol streams. Then, the multi-antenna transmitting processor **471** processes the time-domain multicarrier symbol streams with a transmitting analog precoding/beamforming operation. Each transmitter **418** converts a baseband multicarrier symbol stream provided by the multi-antenna transmitting processor **471** into a radio frequency stream and then provides it to different antennas **420**.

[0263] In a transmission from the second communication equipment **410** to the first communication equipment **450**, at the first communication equipment **450**, each receiver **454** receives a signal via the corresponding antenna **452**. Each receiver **454** recovers the information modulated to the RF carrier and converts the radio frequency stream into a baseband multicarrier symbol stream to provide to the receiving processor **456**. The receiving processor **456** and the multi-antenna receiving processor **458** perform various signal processing functions of Layer 1. The multi-antenna receiving processor **458** processes the baseband multicarrier symbol stream coming from the receiver **454** with a receiving analog precoding/beamforming operation. The receiving processor **458** converts the baseband multicarrier symbol stream subjected to the receiving analog precoding/beamforming operation from time domain into frequency domain using FFT (Fast Fourier Transform). In frequency domain, a physical layer data signal and a reference signal are demultiplexed by the receiving processor **456**, wherein the reference signal is used for channel estimation, and the data signal is subjected to multi-antenna detection in the multi-antenna receiving processor **458** to recover any spatial stream targeting the UE **450**. Symbols on each spatial stream are demodulated and recovered in the receiving processor **456** to generate a soft decision. Then, the receiving processor **456** decodes and de-interleaves the soft decision to recover the higher-layer data and control signal on the physical channel transmitted by the second communication equipment **410**. Next, the higher-layer data and control signal are provided to the controller/processor **459**. The controller/processor **459** performs functions of Layer 2. The controller/processor **459** may be connected to the memory **460** that stores program codes and data. The memory **460** may be called a computer readable media. In the transmission from the second communication equipment **410** to the first communication equipment **450**, the controller/processor **459** provides multiplexing between the transport channel and the logical channel, packet reassembling, decryption, header decompression, and control signal processing so as to recover the higher-layer packet coming from the core network. The higher-layer packet is then provided to all protocol layers above Layer 2, or various control signals can be provided to Layer 3 for processing.

[0264] In a transmission from the first communication equipment **450** to the second communication equipment **410**, at the first communication equipment **450**, the data source **467** provides a higher-layer packet to the controller/processor **459**. The data source **467** illustrates all protocol layers above the L2 layer. Similar as the transmitting function of the second communication equipment **410** described in the transmission from the second communication equipment **410** to the first communication equipment **450**, the controller/processor **459** provides header compression, encryption, packet segmentation and reordering, and multiplexing between a logical channel and a transport channel based on radio resource allocation so as to provide the functions of L2 layer used for the control plane and user plane. The controller/processor **459** is also in charge of retransmission of lost packets, and signalings to the second communication equipment **410**. The transmitting processor **468** conducts modulation mapping and channel encoding processing; the multi-antenna transmitting processor **457** performs digital multi-antenna spatial precoding (including precoding based on codebook and precoding based on non-codebook) and beamforming processing; and subsequently, the transmitting processor **468** modulates the generated spatial streams into a multicarrier/single-carrier symbol stream, which is subjected to an analog precoding/beamforming operation in the multi-antenna transmitting processor **457** and then is provided to different antennas **452** via the transmitter **454**. Each transmitter **452** first converts the baseband symbol stream provided by the multi-antenna transmitting processor **457** into a radio frequency symbol stream and then provides the radio frequency symbol stream to the antenna **452**.

[0265] In a transmission from the first communication equipment **450** to the second communication equipment **410**, the function of the second communication equipment **410** is similar as the receiving function of the first communication equipment **450** described in the transmission from second communication equipment **410** to the first communication equipment **450**. Each receiver **418** receives a radio frequency signal via the corresponding antenna **420**, converts the received radio frequency signal into a baseband signal, and provides the baseband signal to the multi-antenna receiving processor **472** and the receiving processor **470**. The receiving processor **470** and the multi-antenna receiving processor **472** together provide functions of Layer 1. The controller/processor **475** provides functions of Layer 2. The controller/processor **475** may be connected to the memory **476** that stores program codes and data. The memory **476** may be called a computer readable media. In the transmission from the first communication equipment **450** to the second communication equipment **410**, the controller/processor **475** provides de-multiplexing between the transport channel and the logical channel, packet reassembling, decryption, header decompression, and control signal processing so as to recover higher-layer packets coming from the UE **450**. The higher-layer packet, coming from the controller/processor **475**, may be provided to the core network.

[0266] In one embodiment, the first communication equipment **450** includes at least one processor and at least one memory. The at least one memory includes computer program codes. The at least one memory and the computer program codes are configured to be used in collaboration with the at least one processor. The first communication equipment **450** at least receives a first radio signal, receives a second radio signal and transmits a third radio signal; the first radio signal is used for determining a first signature sequence, and a receiving timing of the second radio signal is used for determining a transmitting timing of the third radio signal; the first signature sequence is used for generating the third radio signal; the first radio signal and the second radio signal are associated with a first synchronization sequence and a second synchronization sequence respectively, and the first synchronization sequence is different from the second synchronization sequence.

[0267] In one embodiment, the first communication equipment **450** includes a memory that stores a computer readable instruction program. The computer readable instruction program generates an action when executed by at least one processor. The action includes: receiving a first radio signal, receiving a second radio signal and transmitting a third radio signal; the first radio signal is used for determining a first signature sequence, and a receiving timing of the second radio signal is used for

determining a transmitting timing of the third radio signal; the first signature sequence is used for generating the third radio signal; the first radio signal and the second radio signal are associated with a first synchronization sequence and a second synchronization sequence respectively, and the first synchronization sequence is different from the second synchronization sequence.

[0268] In one embodiment, the second communication equipment **410** includes at least one processor and at least one memory. The at least one memory includes computer program codes. The at least one memory and the computer program codes are configured to be used in collaboration with the at least one processor. The second communication equipment **410** at least transmits a first radio signal; the first radio signal is used for determining a first signature sequence, and a receiving timing of a second radio signal is used for determining a transmitting timing of a third radio signal; the first signature sequence is used for generating the third radio signal; the first radio signal and the second radio signal are associated with a first synchronization sequence and a second synchronization sequence respectively, and the first synchronization sequence is different from the second synchronization sequence.

[0269] In one embodiment, the second communication equipment **410** includes a memory that stores a computer readable instruction program. The computer readable instruction program generates an action when executed by at least one processor. The action includes: transmitting a first radio signal; the first radio signal is used for determining a first signature sequence, and a receiving timing of a second radio signal is used for determining a transmitting timing of a third radio signal; the first signature sequence is used for generating the third radio signal; the first radio signal and the second radio signal are associated with a first synchronization sequence and a second synchronization sequence respectively, and the first synchronization sequence is different from the second synchronization sequence. In one embodiment, the second communication equipment **410** includes at least one processor and at least one memory. The at least one memory includes computer program codes. The at least one memory and the computer program codes are configured to be used in collaboration with the at least one processor. The second communication equipment **410** at least transmits a second radio signal; a receiving timing of the second radio signal is used for determining a transmitting timing of a third radio signal; a first signature sequence is used for generating the third radio signal; a first radio signal is used for determining the first signature sequence; the first radio signal and the second radio signal are associated with a first synchronization sequence and a second synchronization sequence respectively, and the first synchronization sequence is different from the second synchronization sequence.

[0270] In one embodiment, the second communication equipment **410** includes a memory that stores a computer readable instruction program. The computer readable instruction program generates an action when executed by at least one processor. The action includes: transmitting a second radio signal; a receiving timing of the second radio signal is used for determining a transmitting timing of a third radio signal; a first signature sequence is used for generating the third radio signal; a first radio signal is used for determining the first signature sequence; the first radio signal and the second radio signal are associated with a first synchronization sequence and a second synchronization sequence respectively, and the first synchronization sequence is different from the second synchronization sequence.

[0271] In one embodiment, the first communication equipment **450** corresponds to the UE in the disclosure.

[0272] In one embodiment, the second communication equipment **410** corresponds to the base station in the disclosure.

[0273] In one embodiment, the second communication equipment **410** corresponds to the communication node in the disclosure.

[0274] In one embodiment, the first communication equipment **450** is one UE.

[0275] In one embodiment, the second communication equipment **410** is one base station.

[0276] In one embodiment, the second communication equipment **410** is one communication node.

[0277] In one embodiment, at least one of the antenna **452**, the receiver **454**, the multi-antenna receiving processor **458**, the receiving processor **456** and the controller/processor **459** is used for receiving a first radio signal; and at least one of the antenna **420**, the transmitter **418**, the multi-antenna transmitting processor **471**, the transmitting processor **416** and the controller/processor **475** is used for transmitting a first radio signal.

[0278] In one embodiment, at least one of the antenna **452**, the receiver **454**, the multi-antenna receiving processor **458**, the receiving processor **456** and the controller/processor **459** is used for receiving a second radio signal; and at least one of the antenna **420**, the transmitter **418**, the multi-antenna transmitting processor **471**, the transmitting processor **416** and the controller/processor **475** is used for transmitting a second radio signal.

[0279] In one embodiment, at least one of the antenna **452**, the transmitter **454**, the multi-antenna transmitting processor **457**, the transmitting processor **468** and the controller/processor **459** is used for transmitting a third radio signal; and at least one of the antenna **420**, the receiver **418**, the multi-antenna receiving processor **472**, the receiving processor **470** and the controller/processor **475** is used for receiving a third radio signal.

[0280] In one embodiment, at least one of the antenna **452**, the receiver **454**, the multi-antenna receiving processor **458**, the receiving processor **456** and the controller/processor **459** is used for monitoring K downlink signalings; and at least one of the antenna **420**, the transmitter **418**, the multi-antenna transmitting processor **471**, the transmitting processor **416** and the controller/processor **475** is used for transmitting K downlink signalings.

[0281] In one embodiment, at least one of the antenna **452**, the receiver **454**, the multi-antenna receiving processor **458**, the receiving processor **456** and the controller/processor **459** is used for monitoring a first signaling; and at least one of the antenna **420**, the transmitter **418**, the multi-antenna transmitting processor **471**, the transmitting processor **416** and the controller/processor **475** is used for transmitting a first signaling.

[0282] In one embodiment, at least one of the antenna **452**, the transmitter **454**, the multi-antenna transmitting processor **457**, the transmitting processor **468** and the controller/processor **459** is used for transmitting a fourth radio signal; and at least one of the antenna **420**, the receiver **418**, the multi-antenna receiving processor **472**, the receiving processor **470** and the controller/processor **475** is used for receiving a fourth radio signal.

[0283] In one embodiment, at least one of the antenna **452**, the receiver **454**, the multi-antenna receiving processor **458**, the receiving processor **456** and the controller/processor **459** is used for receiving a second signaling; and at least one of the antenna **420**, the transmitter **418**, the multi-antenna transmitting processor **471**, the transmitting processor **416** and the controller/processor **475** is used for transmitting a second signaling.

[0284] In one embodiment, at least one of the antenna **452**, the transmitter **454**, the multi-antenna transmitting processor **457**, the transmitting processor **468** and the controller/processor **459** is used for transmitting a fifth radio signal; and at least one of the antenna **420**, the receiver **418**, the multi-antenna receiving processor **472**, the receiving processor **470** and the controller/processor **475** is used for receiving a fifth radio signal.

## Embodiment 5

[0285] Embodiment 5 illustrates an example of a flowchart of transmission of a first radio signal according to the disclosure, as shown in FIG. 1. In FIG. 1, a base station N1 is a maintenance base station for a serving cell of a UE U2, and a communication node I3 is a device taken as a synchronization reference by the UE U2. In FIG. 5, steps in boxes F0, F1 and F2 are optional.

[0286] The base station N1 transmits a second signaling in S10, transmits a first radio signal in S11, receives a fifth radio signal in S110, transmits a first downlink signaling in S12, receives a third radio signal in S13, transmits a first signaling in S14 and receives a fourth radio signal in S15.

[0287] The UE U2 receives a second signaling in S20, receives a first radio signal in S21, transmits a fifth radio signal in S210, receives a second radio signal in S22, monitors K downlink signalings

in S23, transmits a third radio signal in S24, receives a first signaling in S25 and transmits a fourth radio signal in S26.

[0288] The communication node I3 transmits a second radio signal in S30 and receives a third radio signal in S31.

[0289] Embodiment 1, the first radio signal is used for determining a first signature sequence, and a receiving timing of the second radio signal is used for determining a transmitting timing of the third radio signal; the first signature sequence is used for generating the third radio signal. The first radio signal and the second radio signal are associated with a first synchronization sequence and a second synchronization sequence respectively, and the first synchronization sequence is different from the second synchronization sequence. The downlink signaling is a physical layer signaling, and the K downlink signalings are associated with K synchronization sequences respectively. Any two of the K synchronization sequences are different. The K is a positive integer greater than 1. The second synchronization sequence is one of the K synchronization sequences. The K downlink signalings are identified by a first index respectively, and the first index is an integer. The first synchronization sequence is one of the K synchronization sequences, and the UE U2 assumes that only the first synchronization sequence among the K synchronization sequences is associated with the first signaling. A format of the first signaling is any one candidate format in a format set. The format set includes a positive integer number of candidate formats. The first signaling is used for determining scheduling information of the fourth radio signal and the scheduling information includes at least one of occupied time-domain resources, occupied frequency-domain resources, an MCS, an NDI, an RV, or a HARQ process number. The second signaling is used for determining K time-frequency resource sets or the K synchronization sequences or both. The second signaling is associated with the first synchronization sequence. The first radio signal indicates a first identifier, and the first identifier is used for generating the first signature sequence. A receiving timing of the first radio signal is used for determining a transmitting timing of the fifth radio signal, and the first signature sequence is used for generating the fifth radio signal. The downlink signaling is used for at least one of TPC, triggering the UE U2 to transmit a reference signal, or triggering the UE U2 to transmit channel state information.

[0290] In one subembodiment, the K downlink signalings include (K-1) downlink signalings shown in FIG. 5 and the first downlink signaling.

[0291] In one subembodiment, a transmission channel corresponding to the third radio signal is an Uplink Shared Channel (UL-SCH).

[0292] In one subembodiment, a transmission channel corresponding to the third radio signal is a Sidelink Shared Channel (SL-SCH).

[0293] In one subembodiment, a transmission channel corresponding to the third radio signal is a Sidelink Discovery Channel (SL-DCH).

[0294] In one subembodiment, a transmission channel corresponding to the third radio signal is a Sidelink Broadcast Channel (SL-BCH).

[0295] In one subembodiment, the second signaling is semi-statically configured.

[0296] In one subembodiment, the communication node I3 is a ground device used by the UE U2 to position.

[0297] In one subembodiment, the communication node I3 is a GNSS.

[0298] In one subembodiment, the communication node I3 includes one or more satellites.

[0299] In one subembodiment, the communication node I3 is one cell, and the K downlink signalings include one given downlink signal which is transmitted by the communication node I3.

[0300] In one affiliated embodiment of the above subembodiment, the communication node I3 is further used for monitoring the third radio signal.

[0301] In one subembodiment, a receiver of the third radio signal includes a node other than the base station N1 and the communication node I3.

Embodiment 6

[0302] Embodiment 6 illustrates an example of a diagram of one application scenario according to the disclosure, as shown in FIG. 6. An air terminal shown in FIG. 6 corresponds to the UE in the disclosure. A first node to a Qth node shown in FIG. 6 are Q ground devices, the Q being a positive integer greater than 1. A ground terminal shown in FIG. 6 is an opposite-end terminal of the air terminal. A target node shown in FIG. 6 is one or more satellites, or the target node shown in FIG. 6 is a GNSS.

[0303] In one subembodiment, the first node is a serving cell of the air terminal.

[0304] In one subembodiment, the first node is a serving cell of the ground terminal.

[0305] In one subembodiment, the air terminal and the ground terminal belong to one D2D pair.

[0306] In one subembodiment, the air terminal is a transmitter of the third radio signal in the disclosure.

[0307] In one affiliated embodiment of the above subembodiment, a receiver of the third radio signal includes the first node.

[0308] In one affiliated embodiment of the above subembodiment, a receiver of the third radio signal includes a first given node, and the first given node is one of the second node to the Qth node shown in FIG. 6.

[0309] In one affiliated embodiment of the above subembodiment, a receiver of the third radio signal includes the ground terminal.

[0310] In one subembodiment, the first node transmits the first downlink signaling in the disclosure, and the third radio signal is triggered by the first downlink signaling.

[0311] In one subembodiment, a given downlink signaling is used for triggering the third radio signal, the given downlink signaling is a downlink signaling among the K downlink signalings in the disclosure other than the first downlink signaling, and a transmitter of the given downlink signaling is one of the second node to the Qth node.

[0312] In one subembodiment, the Q is equal to the K in the disclosure, and the first node to the Qth node transmit the K downlink signalings in the disclosure respectively.

[0313] In one subembodiment, the Q is equal to a summation of the K and 1, and the first node to the Qth node and the ground terminal transmit the K downlink signalings in the disclosure respectively.

[0314] In one subembodiment, the first node transmits the first radio signal in the disclosure, and the target node transmits the second radio signal in the disclosure.

[0315] In one affiliated embodiment of the above subembodiment, the first radio signal indicates explicitly the first identifier in the disclosure, and the first identifier is used for generating the first signature sequence in the disclosure.

[0316] In one subembodiment, the first node transmits the second radio signal in the disclosure, and the target node transmits the first radio signal in the disclosure.

[0317] In one affiliated embodiment of the above subembodiment, the first identifier in the disclosure is equal to Y, the Y is a predefined integer, and the first identifier is used for generating the first signature sequence in the disclosure.

[0318] In an example of the above affiliated embodiment, the Y is equal to 0.

#### Embodiment 7

[0319] Embodiment 7 illustrates an example of a diagram of one application scenario according to the disclosure, as shown in FIG. 7. An air terminal shown in FIG. 7 corresponds to the UE in the disclosure. A first node to an Rth node shown in FIG. 7 are R ground devices, the R being a positive integer greater than 1. A ground terminal shown in FIG. 7 is an opposite-end terminal of the air terminal.

[0320] In one subembodiment, the first node is a serving cell of the air terminal.

[0321] In one subembodiment, the first node is a serving cell of the ground terminal.

[0322] In one subembodiment, the air terminal and the ground terminal belong to one D2D pair.

[0323] In one subembodiment, the air terminal is a transmitter of the third radio signal in the

disclosure.

[0324] In one affiliated embodiment of the above subembodiment, a receiver of the third radio signal includes the first node.

[0325] In one affiliated embodiment of the above subembodiment, a receiver of the third radio signal includes a second given node, and the second given node is one of the second node to the  $R$ th node shown in FIG. 7.

[0326] In one affiliated embodiment of the above subembodiment, a receiver of the third radio signal includes the ground terminal.

[0327] In one subembodiment, the first node transmits the first downlink signaling in the disclosure, and the third radio signal is triggered by the first downlink signaling.

[0328] In one subembodiment, a given downlink signaling is used for triggering the third radio signal, the given downlink signaling is a downlink signaling among the  $K$  downlink signaling in the disclosure other than the first downlink signaling, and a transmitter of the given downlink signaling is one of the second node to the  $R$ th node.

[0329] In one subembodiment, the  $R$  is equal to the  $K$  in the disclosure, and the first node to the  $R$ th node transmit the  $K$  downlink signalings in the disclosure respectively.

[0330] In one subembodiment, the  $R$  is equal to a summation of the  $K$  and 1, and the first node to the  $R$ th node and the ground terminal transmit the  $K$  downlink signalings in the disclosure respectively.

[0331] In one subembodiment, the first node transmits the first radio signal in the disclosure, and one of the second node to the  $R$ th node transmits the second radio signal in the disclosure.

[0332] In one subembodiment, the first node transmits the second radio signal in the disclosure, and one of the second node to the  $R$ th node transmits the first radio signal in the disclosure.

[0333] In one affiliated embodiment of the above subembodiment, the first radio signal indicates explicitly the first identifier in the disclosure, and the first identifier is used for generating the first signature sequence in the disclosure.

[0334] In one subembodiment, the first node transmits the second radio signal in the disclosure, and the ground terminal transmits the first radio signal in the disclosure.

[0335] In one affiliated embodiment of the above subembodiment, the first identifier in the disclosure is equal to a second identifier, the second identifier is used for generating a second signature sequence, the second signature sequence is used for generating the first radio signal, and the first identifier is used for generating the first signature sequence in the disclosure.

[0336] In an example of the above affiliated embodiment, the second identifier is equal to 169, and a synchronization source of the ground terminal is a GNSS.

[0337] In an example of the above affiliated embodiment, the second identifier belongs to a second identifier set, the second identifier set is predefined, and the ground terminal selects the second identifier from the second identifier set autonomously.

[0338] In a dependent embodiment of the above example, the second identifier is a positive integer not less than 168 but not greater than 335.

[0339] In a dependent embodiment of the above example, the ground terminal is Out Of Coverage (OOC).

#### Embodiment 8

[0340] Embodiment 8 illustrates a diagram of a time sequence of a first radio signal and a second radio signal, as shown in FIG. 8. In FIG. 8, a first time window is used for transmitting the first radio signal in the disclosure, a second time window is used for transmitting the second radio signal in the disclosure, and a third time window is used for transmitting the third radio signal in the disclosure. The UE in the disclosure further transmits a fifth radio signal in a given time window shown in FIG. 8. The first time window, the second time window, the third time window and the given time window all belong to a target time window.

[0341] In one subembodiment, the first radio signal is used for determining a first signature

sequence, and the UE keeps the first signature sequence unchanged in the target time window.  
[0342] In one subembodiment, a transmitter of the third radio signal transmits a fifth radio signal in the first time window, the first radio signal is used for determining a first signature sequence, and the first signature sequence is used for generating the fifth radio signal, and a receiving timing of the first radio signal is used for determining a transmitting timing of the fifth radio signal.

[0343] In one affiliated embodiment of the above subembodiment, the phrase that a receiving timing of the first radio signal is used for determining a transmitting timing of the fifth radio signal refers that: the UE selects a transmitter of the first radio signal as a synchronization reference source.

[0344] In one affiliated embodiment of the above subembodiment, the phrase that a receiving timing of the first radio signal is used for determining a transmitting timing of the fifth radio signal refers that: the UE selects a transmitter of the first radio signal as a synchronization reference source, and employs the first radio signal as a timing reference of the fifth radio signal.

#### Embodiment 9

[0345] Embodiment 9 illustrates an example of a structure block diagram of a processing device in a UE, as shown in FIG. 9. In FIG. 9, the processing device **900** in the UE includes a first transceiver **901**, a first receiver **902** and a first transmitter **903**.

[0346] The first transceiver **901** receives a first radio signal.

[0347] The first receiver **902** receives a second radio signal.

[0348] The first transmitter **903** transmits a third radio signal.

[0349] In Embodiment 9, the first radio signal is used for determining a first signature sequence, and a receiving timing of the second radio signal is used for determining a transmitting timing of the third radio signal. The first signature sequence is used for generating the third radio signal. The first radio signal and the second radio signal are associated with a first synchronization sequence and a second synchronization sequence respectively, and the first synchronization sequence is different from the second synchronization sequence.

[0350] In one subembodiment, the first transceiver **901** further monitors K downlink signalings. The downlink signaling is a physical layer signaling, and the K downlink signalings are associated with K synchronization sequences respectively. Any two of the K synchronization sequences are different. The K is a positive integer greater than 1. The second synchronization sequence is one of the K synchronization sequences. The K downlink signalings are identified by a first index respectively, and the first index is an integer.

[0351] In one subembodiment, the first transceiver **901** monitors a first signaling. The first synchronization sequence is one of the K synchronization sequences, and the UE assumes that only the first synchronization sequence among the K synchronization sequences is associated with the first signaling. A format of the first signaling is any one candidate format in a format set. The format set includes a positive integer number of candidate formats.

[0352] In one subembodiment, the first transceiver **901** further transmits a fourth radio signal. The first signaling is used for determining scheduling information of the fourth radio signal; and the scheduling information includes at least one of occupied time-domain resources, occupied frequency-domain resources, an MCS, an NDI, an RV, or a HARQ process number.

[0353] In one subembodiment, the first transceiver **901** further receives a second signaling. The second signaling is used for determining K time-frequency resource sets or the K synchronization sequences or both. The second signaling is associated with the first synchronization sequence. The first radio signal indicates a first identifier, and the first identifier is used for generating the first signature sequence.

[0354] In one subembodiment, the first transceiver **901** further transmits a fifth radio signal. A receiving timing of the first radio signal is used for determining a transmitting timing of the fifth radio signal, and the first signature sequence is used for generating the fifth radio signal.

[0355] In one subembodiment, the downlink signaling is used for at least one of TPC, triggering



the UE to transmit a reference signal, or triggering the UE to transmit channel state information.

[0356] In one subembodiment, the first receiver **902** belongs to the first transceiver **901**.

[0357] In one embodiment, the first transceiver **901** includes at least the former six of the antenna **452**, the receiver/transmitter **454**, the multi-antenna receiving processor **458**, the receiving processor **456**, the multi-antenna transmitting processor **457**, the transmitting processor **468** and the controller/processor **459** illustrated in Embodiment 4.

[0358] In one embodiment, the first receiver **902** includes at least the former four of the antenna **452**, the receiver **454**, the multi-antenna receiving processor **458**, the receiving processor **456** and the controller/processor **459** illustrated in Embodiment 4.

[0359] In one embodiment, the first transmitter **903** includes at least the former four of the antenna **452**, the transmitter **454**, the multi-antenna transmitting processor **457**, the transmitting processor **468** and the controller/processor **459** illustrated in Embodiment 4.

#### Embodiment 10

[0360] Embodiment 10 illustrates an example of a structure block diagram of a processing device in a base station, as shown in FIG. **10**. In FIG. **10**, the processing device **1000** in the base station includes a second transceiver **1001** and a second receiver **1002**.

[0361] The second transceiver **1001** transmits a first radio signal.

[0362] The second receiver **1002** receives a third radio signal.

[0363] In Embodiment 10, the first radio signal is used for determining a first signature sequence, and a receiving timing of a second radio signal is used for determining a transmitting timing of a third radio signal. The first signature sequence is used for generating the third radio signal. The first radio signal and the second radio signal are associated with a first synchronization sequence and a second synchronization sequence respectively, and the first synchronization sequence is different from the second synchronization sequence.

[0364] In one subembodiment, the second transceiver **1001** further transmits a first downlink signaling. The first downlink signaling is a physical layer signaling, and K downlink signalings are associated with K synchronization sequences respectively. Any two of the K synchronization sequences are different. The K is a positive integer greater than 1. The second synchronization sequence is one of the K synchronization sequences. The K downlink signalings are identified by a first index respectively, and the first index is an integer. The first downlink signaling is one of the K downlink signalings.

[0365] In one subembodiment, the second transceiver **1001** further transmits a first signaling. The first synchronization sequence is one of the K synchronization sequences, and only the first synchronization sequence among the K synchronization sequences is associated with the first signaling. A format of the first signaling is any one candidate format in a format set. The format set includes a positive integer number of candidate formats.

[0366] In one subembodiment, the second transceiver **1001** further receives a fourth radio signal. The first signaling is used for determining scheduling information of the fourth radio signal; and the scheduling information includes at least one of occupied time-domain resources, occupied frequency-domain resources, an MCS, an NDI, an RV, or a HARQ process number.

[0367] In one subembodiment, the second transceiver **1001** further transmits a second signaling. The second signaling is used for determining K time-frequency resource sets or the K synchronization sequences or both. The second signaling is associated with the first synchronization sequence. The first radio signal indicates a first identifier, and the first identifier is used for generating the first signature sequence.

[0368] In one subembodiment, the second transceiver **1001** further receives a fifth radio signal. A receiving timing of the first radio signal is used for determining a transmitting timing of the fifth radio signal, and the first signature sequence is used for generating the fifth radio signal.

[0369] In one subembodiment, the downlink signaling is used for at least one of TPC, triggering a transmitter of the third radio signal to transmit a reference signal, or triggering a transmitter of the

third radio signal to transmit channel state information.

[0370] In one embodiment, the second transceiver **1001** includes at least the former six of the antenna **420**, the transmitter/receiver **418**, the multi-antenna transmitting processor **471**, the multi-antenna receiving processor **472**, the transmitting processor **416**, the receiving processor **470** and the controller/processor **475**.

[0371] In one embodiment, the second receiver **1002** includes at least the former four of the antenna **420**, the receiver **418**, the multi-antenna receiving processor **472**, the receiving processor **470** and the controller/processor **475**.

Embodiment 11

[0372] Embodiment 11 illustrates an example of a structure block diagram of a processing device in a communication node, as shown in FIG. **11**. In FIG. **11**, the processing device **1100** in the communication node includes a third transceiver **1101**.

[0373] The third transceiver **1101** transmits a second radio signal.

[0374] In Embodiment 11, a receiving timing of the second radio signal is used for determining a transmitting timing of a third radio signal. A first signature sequence is used for generating the third radio signal. A first radio signal is used for determining the first signature sequence. The first radio signal and the second radio signal are associated with a first synchronization sequence and a second synchronization sequence respectively, and the first synchronization sequence is different from the second synchronization sequence.

[0375] In one subembodiment, the third transceiver **1101** further receives a third radio signal

[0376] In one subembodiment, the communication node processing device **300** is a GNSS.

[0377] In one subembodiment, the communication node processing device **300** includes one or more satellites.

[0378] In one subembodiment, the second radio signal is a GPS signal.

[0379] In one subembodiment, the communication node processing device **300** is one cell.

[0380] In one subembodiment, the communication node processing device **300** is one terminal.

[0381] The ordinary skill in the art may understand that all or part steps in the above method may be implemented by instructing related hardware through a program. The program may be stored in a computer readable storage medium, for example Read-Only Memory (ROM), hard disk or compact disc, etc. Optionally, all or part steps in the above embodiments also may be implemented by one or more integrated circuits. Correspondingly, each module unit in the above embodiment may be realized in the form of hardware, or in the form of software function modules. The disclosure is not limited to any combination of hardware and software in specific forms. The UE and terminal in the disclosure include but not limited to unmanned aerial vehicles, communication modules on unmanned aerial vehicles, telecontrolled aircrafts, aircrafts, diminutive airplanes, mobile phones, tablet computers, notebooks, vehicle-mounted communication equipment, wireless sensor, network cards, terminals for Internet of Things, REID terminals, NB-IoT terminals, Machine Type Communication (MTC) terminals, enhanced MTC (eMTC) terminals, data cards, low-cost mobile phones, low-cost tablet computers, and other radio communication equipment. The base station in the disclosure includes but not limited to macro-cellular base stations, micro-cellular base stations, home base stations, relay base station, and other radio communication equipment.

[0382] The above are merely the preferred embodiments of the disclosure and are not intended to limit the scope of protection of the disclosure. Any modification, equivalent substitute and improvement made within the spirit and principle of the disclosure are intended to be included within the scope of protection of the disclosure.

## Claims

1. A method in a user equipment (UE) for wireless communication, the method comprising: receiving a first radio signal from a first transmitter, the first radio signal being associated with a

first synchronization sequence, and receiving a second radio signal from a second transmitter, the second radio signal being associated with a second synchronization sequence, wherein the first transmitter is different from the second transmitter and the first synchronization sequence is different from the second synchronization sequence; acquiring generation indicators of timing and synchronization sequences from the first and second transmitters, respectively; and transmitting a third radio signal, the first signature sequence being used for generating the third radio signal, and a receiving timing of the second radio signal is used for determining a transmitting timing of the third radio signal.

2. The method of claim 1, wherein the first synchronization sequence corresponds to a first target identifier, the second synchronization sequence corresponds to a second target identifier, and the first target identifier is different from the second target identifier.

3. The method of claim 2, wherein the first target identifier is a Physical Cell Identifier (PCI), and the second target identifier is one of a Physical Cell Identifier (PCI) or a UE Identifier (ID).

4. The method of claim 2, wherein at least one of the first transmitter and the second transmitter is a serving cell corresponding to the UE.

5. The method of claim 2, wherein the first radio signal indicates a first identifier used for generating the first signature sequence.

6. The method of claim 5, wherein the first identifier is a Sidelink Synchronization Sequence Identifier (SLSSID).

7. The method of claim 5, wherein the first identifier is an integer not less than 0 but not greater than 167.

8. The method of claim 2, wherein the first identifier includes an SL-SyncConfig Information Element.

9. The method of claim 2, wherein at least one of the first transmitter and the second transmitter is a target terminal.

10. The method of claim 9, wherein the target terminal is an opposite-end terminal of the UE.

11. The method of claim 9, wherein the target terminal and the UE form a device-to-device pair.

12. The method of claim 9, wherein the first transmitter is a serving cell of the target terminal.

13. The method of claim 9, wherein the target terminal is a terminal used for terrestrial radio access.

14. The method of claim 1, wherein a receiving timing of the first radio signal is also used for determining the transmitting timing of the third radio signal.

15. The method of claim 1, wherein a physical layer channel corresponding to the second radio signal is one of a Physical Sidelink Shared Channel (PSSCH), a Physical Sidelink Control Channel (PSCCH), a Physical Sidelink Discovery Channel (PSDCH) or a Physical Sidelink Broadcasting Channel (PSBCH).

16. The method of claim 1, wherein the third radio signal includes at least one of a Primary Sidelink Synchronization Signal (PSSS), a Secondary Sidelink Synchronization Signal (SSSS), a Sounding Reference Signal (SRS) or an uplink Demodulation Reference Signal (DMRS).

17. The method of claim 1, wherein a physical layer channel corresponding to the third radio signal is one of a Physical Uplink Shared Channel (PUSCH), a Physical Uplink Control Channel (PUCCH), a New Radio PUSCH (N-PUSCH) or a New Radio PUCCH (N-PUCCH).

18. The method of claim 1, wherein at least one of the first transmitter and the second transmitter includes one or more satellites.

19. The method of claim 1, wherein one of the first transmitter and the second transmitter includes one or more satellites and the other of the first transmitter and the second transmitter is one cell.

20. The method of claim 1 wherein the first radio signal is used for determining a first identifier, the first identifier is used for initializing a generator of the first signature sequence, and the third radio signal corresponds to one of a Primary Sidelink Synchronization Signal (PSSS) or a Secondary Sidelink Synchronization Signal (SSSS), or is a Sounding reference Signal (SRS).

