

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250264784

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

ZHU; Junlong et al.

REFLECTIVE MODULE, REFLECTIVE DRIVING ASSEMBLY, AND CAMERA MODULE

Abstract

This application discloses a reflective module and a camera module. Particularly, the reflective module comprises: a reflective element and a reflection driving assembly; wherein the reflective element reflects the light rays propagating in a direction of a first axis to a direction of a second axis intersecting with the first axis at a certain angle, and the reflection driving assembly comprises a reflection base, a frame supporting the reflective element and capable of rotating around the first axis, and a shaft support member and at least two auxiliary balls which are provided between the reflection base and the frame. Particularly, the shaft support member is passed through by the first axis and fixed to the reflection base or frame; and the at least two auxiliary balls are provided between at least two auxiliary upper grooves of the frame and at least two auxiliary lower grooves of the reflection base, wherein one of the at least two auxiliary upper grooves and at least two auxiliary lower grooves are straight-line grooves extending along a tangent direction of a virtual circle centered on the first axis.

Inventors: ZHU; Junlong (Zhejiang, CN), OSADA; Hiroshi (Zhejiang, CN), XU; Zhiqiang (Zhejiang, CN), FU; Xuepeng (Zhejiang, CN), ZHENG; Chengchang (Zhejiang, CN), WANG; Haitao (Zhejiang, CN), WU; Jin (Zhejiang, CN)

Applicant: NINGBO SUNNY OPOTECH CO., LTD. (Zhejiang, CN)

Family ID: 1000008461706

Assignee: NINGBO SUNNY OPOTECH CO., LTD. (Zhejiang, CN)

Appl. No.: 18/715428

Filed (or PCT Filed): April 18, 2024

PCT No.: PCT/CN2024/088574

Foreign Application Priority Data

CN	202410185792.8	Feb. 19, 2024
CN	202410278978.8	Mar. 12, 2024

Publication Classification

Int. Cl.: G03B17/17 (20210101); G03B5/00 (20210101)

U.S. Cl.:

CPC G03B17/17 (20130101); G03B5/00 (20130101); G03B2205/0069 (20130101)

Background/Summary

TECHNICAL FIELD

[0001] The present application relates to the field of camera technology, particularly to a reflective module and a camera module.

BACKGROUND ART

[0002] With the popularization of mobile electronic devices, the related technology of camera modules for helping users obtain images has undergone rapid development and progress. In the current market, there is an increasing demand from consumers for remote shooting of camera modules configured on mobile electronic devices.

[0003] A camera module with telephoto imaging function needs to have a longer focal length to obtain clear images of the subject at a longer distance. However, having a longer focal length means that the camera module has a longer length size. Therefore, at least one reflective module reflecting light may be provided in the camera module to fold the optical path of the camera module, thereby avoiding the size of the camera module being too long. A reflective driving assembly can be correspondingly provided in the reflective module to adjust the optical path of the camera module, thereby further improving the imaging function of the camera module.

[0004] Correspondingly, this application provides a reflective module and a camera module with the reflective module.

SUMMARY OF THE APPLICATION

[0005] One object of this application is to provide a reflective module and a camera module, which overcomes the shortcomings of the prior art, optimizes the structure of the reflective module, and improves the imaging quality of the camera module with the reflective module.

[0006] One object of this application is to provide a reflection driving assembly and a camera module, which overcomes the shortcomings of the prior art, optimizes the structure of the reflection driving assembly, and improves the imaging quality of the camera module with the reflection driving assembly.

[0007] According to one aspect of the present application, there provides a reflective module, which comprises: [0008] a reflective element, which reflects the light rays propagating in the direction of a first axis to the direction of a second axis intersecting with the first axis at a certain angle; and [0009] a reflection driving assembly, which comprises: a reflection base, a frame supporting the reflective element and capable of rotating around the first axis, and a shaft support member and at least two auxiliary balls which are provided between the reflection base and the frame; wherein the shaft support member is passed through by the first axis and fixed to the

reflection base or the frame; and the at least two auxiliary balls are provided between at least two auxiliary upper grooves of the frame and at least two auxiliary lower grooves of the reflection base, and one of the at least two auxiliary upper grooves and the at least two auxiliary lower grooves are straight-line grooves extending along the tangent direction of a virtual circle centered on the first axis.

[0010] In some examples, at least two symmetry axes along the length direction of the straight-line grooves are tangent to the virtual circle.

[0011] In some examples, the other of the at least two auxiliary upper grooves and at least two auxiliary lower grooves are positioning grooves for locating the auxiliary balls.

[0012] In some examples, the at least two auxiliary upper grooves are the straight-line grooves, the at least two auxiliary lower grooves are the positioning grooves, and the maximum gap between the at least two auxiliary balls and the at least two auxiliary lower grooves is less than the maximum gap between the at least two auxiliary balls and the at least two auxiliary upper grooves.

[0013] In some examples, the initial position of each auxiliary lower groove is projected in the direction of the first axis onto a middle region of the opposite auxiliary upper groove.

[0014] In some examples, the shaft support member is fixed to the reflection substrate of the reflection base, and the shaft support member protrudes from the top surface of the reflection substrate which faces the frame, and a shaft positioning groove is provided on the bottom surface of the frame which faces the reflection substrate, and the shaft support member is accommodated in the shaft positioning groove and maintains contact with the shaft positioning groove.

[0015] In some examples, the reflection driving assembly further comprises a carrier and a second support portion provided between the carrier and the frame, and the reflective element is fixed to the carrier.

[0016] In some examples, the second support portion comprises two shaft balls, and the two shaft balls have same height and are passed through by a third axis perpendicular to the first axis and second axis, and the carrier can rotate around the third axis relative to the frame.

[0017] In some examples, the reflection driving assembly further comprises a reflective magnetic attraction portion, and the carrier is supported on the reflection base through the magnetic attraction force of the reflective magnetic attraction portion with the frame sandwiched between them.

[0018] In some examples, viewing in the direction of the first axis, the acting direction of the magnetic attraction force of the reflective magnetic attraction portion intersects with the third axis.

[0019] In some examples, the first axis and the third axis do not intersect, and the distance from the shaft support member to the third axis is less than the distance from at least two auxiliary balls to the third axis.

[0020] In some examples, the reflection driving assembly further comprises a reflection driving portion for driving the rotation of the reflective element, and the reflection driving portion comprises at least two rotating magnets fixed on the carrier and at least two rotating coils fixed on the reflection base, and the at least two rotating magnets are provided opposite to the at least two rotating coils.

[0021] In some examples, the reflection driving assembly further comprises a rotating-position sensing portion, wherein the rotating-position sensing portion comprises a first rotation sensing element and a second rotation sensing element, and the rotating-position sensing portion obtain the magnetic field change information of the reflective magnetic attraction portion of the reflection driving assembly and the magnetic field change information of the at least two rotating magnets through the first and second rotation sensing elements respectively, thereby obtaining the attitude change information of the reflective element.

[0022] According to another aspect of the present application, there provides: [0023] a reflective module according to any one of the preceding examples; [0024] a lens module, which is maintained on the light reflection path of the reflective module; and [0025] an imaging module, which receives the light emitted by the lens module for imaging.

[0026] In this application, the shaft support member is fixed on the reflection base or the frame, and the first axis passing through the shaft support member is used as the rotation axis to drive the frame to rotate relative to the reflection base, so that the rotation of the frame is more accurate and less prone to deviation. Furthermore, the at least two auxiliary balls are provided between the frame and the reflection base to form a stable support plane, and one of the at least two auxiliary upper grooves formed in the frame and the at least two auxiliary lower grooves formed in the reflection base is used for accommodating at least two auxiliary balls is a straight-line groove extending along the tangent direction of the virtual circle centered on the first axis. In this way, the freedom of motion of the at least two auxiliary balls is increased, the friction is reduced, and wear between the at least two auxiliary balls and wall of the groove is also reduced, thereby improving the energy conversion efficiency of the reflection driving assembly. Correspondingly, the response speed of the reflection driving assembly is improved, and the rotation speed and accuracy of the reflective element are improved, thereby improving the imaging quality of the camera module.

[0027] According to one aspect of the present application, there provides a reflection driving assembly, which comprises: [0028] a reflection base; [0029] a carrier, which is rotatably mounted on the reflection base; and [0030] a reflection driving portion, which comprises at least one first rotating magnet and at least one first rotating coil for driving the carrier to rotate around a first axis, and at least one second rotating magnet and at least one second rotating coil for driving the carrier to rotate around a third axis perpendicular to the first axis; wherein the first rotating magnet and the first rotating coil are provided opposite to each other along a second axis perpendicular to the first axis and the third axis, and the second rotating magnet and the second rotating coil are also provided opposite to each other along the second axis.

[0031] In some examples, a surface of the first rotating magnet which faces the first rotating coil has at least two magnetic pole regions provided along the direction of the third axis, and a surface of the second rotating magnet which faces the second rotating coil has at least two magnetic pole regions provided along the direction of the first axis.

[0032] In some examples, the number of first rotating magnets is two, and the number of second rotating magnets is one, and the number of first rotating coils is two, and the number of second rotating coils is one; wherein two first rotating magnets are provided on both sides of one second rotating magnet, and two first rotating coils are provided on both sides of one second rotating coil.

[0033] In some examples, the gap between the first rotating coil and the first rotating magnet is not less than the gap between the second rotating coil and the second rotating magnet, and the thickness of the first rotating coil is less than the thickness of the second rotating coil.

[0034] In some examples, the length direction of the first rotating coil and the length direction of the second rotating coil are perpendicular to each other.

[0035] In some examples, the first and second rotating magnets are fixed to the carrier, and the first and second rotating coils are fixed to the reflection base.

[0036] In some examples, the first axis and the third axis do not intersect with each other, and the first axis and the third axis are spatially perpendicular to each other.

[0037] In some examples, the second axis and third axis do not intersect with each other, and the second axis and third axis are spatially perpendicular to each other.

[0038] In some examples, the vertical distance between the first axis and the center of the first rotating magnet is 2-5.5 mm.

[0039] In some examples, the first axis is located on a side of the third axis which is away from the reflection driving portion.

[0040] In some examples, the reflection driving assembly further comprises a first rotation sensing element and a second rotation sensing element for obtaining attitude change information of the carrier, wherein the projection of the first rotation sensing element in the direction of the second axis overlaps with the third axis, and the projection of the second rotation sensing element in the direction of the second axis overlaps with the first axis.

[0041] In some examples, the height of the top surface of the first rotating magnet is lower than the height of the top surface of the second rotating magnet.

[0042] In some examples, the reflection driving assembly further comprises a frame and a first support portion provided between the reflection base and the frame, and a second support portion provided between the carrier and the frame.

[0043] In some examples, the reflection driving assembly further comprises a reflective magnetic attraction portion, wherein the carrier is supported on the reflection base through the magnetic attraction force of the reflective magnetic attraction portion with the frame sandwiched between them, and viewing in the direction of the first axis, the acting direction of the magnetic attraction force of the reflective magnetic attraction portion intersects with the third axis.

[0044] In some examples, the reflective magnetic attraction portion comprises two first reflection magnetic components and two second reflection magnetic components, and the two first reflection magnetic components are respectively fixed to the bottom surface of the carrier, and the two second reflection magnetic components are respectively fixed to the top portion of the reflection substrate of the reflection base, and viewing in the direction of the first axis, the two first reflection magnetic components are symmetrically provided relative to the third axis.

[0045] In some examples, the first support portion comprises a shaft support member and at least two auxiliary balls, wherein the shaft support member is passed through by the first axis and fixed to the reflection base or the frame, and the at least two auxiliary balls are provided between the at least two auxiliary upper grooves of the frame and the at least two auxiliary lower grooves of the reflection base, and one of the at least two auxiliary upper grooves and the at least two auxiliary lower grooves are straight-line grooves extending along the tangent direction of a virtual circle centered on the first axis.

[0046] In some examples, the at least two auxiliary upper grooves are the straight-line grooves, and the at least two auxiliary lower grooves are the positioning grooves for positioning the auxiliary balls; and wherein the initial position of each auxiliary lower groove is projected in the direction of the first axis onto the middle area of the opposite auxiliary upper groove, and the maximum gap between the at least two auxiliary balls and the at least two auxiliary lower grooves is less than the maximum gap between the at least two auxiliary balls and the at least two auxiliary upper grooves.

[0047] According to another aspect of the present application, there also provides a camera module, which comprises: [0048] a reflective module, which comprises a reflection driving assembly according to any one of the examples, and a reflective element installed in the reflection driving assembly; [0049] a lens module, which is maintained on the light reflection path of the reflective module; and [0050] an imaging module, which receives the light emitted by the lens module for imaging.

[0051] In the present application, at least two rotating magnet-rotating coil pairs for driving the carrier to rotate around the first and third axes are provided on the same side of the carrier; particularly, this provision mode causes the rotating magnets and rotating coils to be concentrated on one side along the second axis, so that the reflection driving assembly will not cause electromagnetic interference to other components in electronic devices within the camera module according to the present application on other sides.

[0052] Other implementation schemes and features are partially described in the following description, and those skilled in the art will understand or learn these implementation schemes and features through the practice of the disclosed subject matter after reviewing the specification. Further understanding of the features and advantages of this application can be achieved by referring to the remaining parts of the specification and drawings that constitute a part of this application.

[0053] Other implementation schemes and features are partially described in the following description, and those skilled in the art will understand or learn these implementation schemes and features through the practice of the disclosed subject matter after reviewing the specification.

Further understanding of the features and advantages of this application can be achieved by referring to the remaining parts of the specification and drawings that constitute a part of this application.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0054] FIG. 1 is a cross-sectional schematic diagram of a camera module according to the present application;

[0055] FIG. 2 is an exploded schematic diagram of a reflection driving assembly according to the present application;

[0056] FIGS. 3A and 3B are respectively top view explosion diagram and bottom view explosion diagram of partial components including a frame and a reflection base in the reflection driving assembly according to the present application;

[0057] FIG. 4 is a schematic diagram of a bottom surface of the frame according to the present application;

[0058] FIG. 5 is an enlarged local view of FIG. 4;

[0059] FIG. 6 is an exploded schematic diagram of partial components comprising a carrier and a frame in the reflection driving assembly according to the present application;

[0060] FIG. 7 is a three-dimensional schematic diagram of the carrier according to the present application;

[0061] FIG. 8 is a cross-sectional schematic diagram of the reflection driving assembly according to the present application;

[0062] FIG. 9 is a top view schematic diagram of the reflection base in the direction along the first axis according to the present application.

[0063] FIG. 10 is a cross-sectional schematic diagram of the camera module according to the present application;

[0064] FIG. 11 is an explosion schematic diagram of the reflection driving assembly according to the present application;

[0065] FIG. 12A is an exploded schematic diagram of partial components comprising the carrier and the frame in the reflection driving assembly according to the present application;

[0066] FIG. 12B is a three-dimensional schematic diagram of the carrier and the frame assembled together according to the present application;

[0067] FIGS. 13A and 13B are respectively top view explosion diagram and bottom view explosion diagram of partial components comprising the frame and the reflection base in the reflection driving assembly according to the present application;

[0068] FIG. 14 is a three-dimensional schematic diagram of the reflection driving portion, a rotating-position sensing portion, and a reflective magnetic attraction portion in the reflection driving assembly according to the present application;

[0069] FIG. 15 is a schematic diagram of the position relationship between the reflection driving portion and the rotating-position sensing portion in the reflection driving assembly according to the present application;

[0070] FIG. 16 is a schematic diagram of the bottom surface of the frame according to the present application;

[0071] FIG. 17 is an enlarged local view of FIG. 16;

[0072] FIG. 18 is a three-dimensional schematic diagram of the carrier according to the present application;

[0073] FIG. 19 is a cross-sectional schematic diagram of a reflection driving assembly according to the present application;

[0074] FIG. **20** is a top view schematic diagram of the reflection base in the direction along the first axis according to the present application;

[0075] FIG. **21** is a three-dimensional schematic diagram of the carrier and the frame assembled together according to another variant example of the present application.

DETAILED DESCRIPTION OF THE APPLICATION

[0076] In combination with particular implementation modes, the present application will be further described below. It should be noted that, on the premise of no conflict, the various examples or technical features described below can be arbitrarily combined to form new examples.

[0077] In the description of the present application, it should be noted that for directional words, if there are terms such as “center”, “horizontal”, “vertical”, “length”, “width”, “thickness”, “upper”, “lower”, “front”, “back”, “left”, “right”, “vertical”, “horizontal”, “top”, “bottom”, “inside”, “outside”, “clockwise”, “counterclockwise”, etc. indicating directional and positional relationships based on the directional or positional relationships shown in the drawings, it is only for the convenience of describing the present application and simplifying the description, and not to indicate or imply that the device or component referred to must have a specific orientation, be constructed and operated in a specific direction, and these terms cannot be understood as limiting the specific protection scope of this application.

[0078] It should be noted that the terms “first”, “second”, etc. in the specification and claims of this application are used to distinguish similar objects, and do not need to be used to describe a specific order or sequence.

[0079] The terms “including/comprising” and “having” and any variations thereof in the specification and claims of this application are intended to cover non-exclusive inclusion, for example, a process, method, system, product or device comprising a series of steps or units need not be limited to those clearly listed steps or units, but may comprise other steps or units that are not clearly listed or inherent to the process, method, product or device.

[0080] It should be noted that as used herein, the terms “basically”, “approximately”, and similar terms are used as expressions of approximation rather than degree, and are intended to illustrate inherent deviations in measured or calculated values that will be recognized by those skilled in the art.

[0081] In the description of this application, it should also be noted that unless otherwise specified and limited, the terms “provide/provision”, “install/installation”, “connect/connection”, “link/linkage” should be broadly understood. For example, it can be a fixed connection, a detachable connection, or an integrated connection. It can be a mechanical connection, or an electrical connection. It can be a direct connection, a contact connection, or an indirect connection through an intermediate medium, or an internal connection between two components. For ordinary technical personnel in this field, the specific meanings of the above terms in this application can be understood based on specific circumstances.

[0082] The terms used in the description of this application are only intended to describe particular implementation schemes, and are not intended to be restrictive. As used in the specification and claims, singular forms of “a”, “an”, and “the” are intended to also encompass plural forms, unless the context explicitly indicates otherwise. It will also be understood that the terms “and/or” used herein refer to and include any and all possible combinations of one or more of the projects listed in association. It will also be understood that, the terms “include/including” and/or “comprise/comprising” used herein refer to the existence of the stated features, integers, steps, operations, components, and/or components, but do not exclude the existence or addition of one or more other features, integers, steps, operations, components, components, and/or their grouping.

[0083] FIGS. **1-9** illustrate a camera module and a reflective module **10** provided in the camera module according to some implementation modes of the present application. As shown in FIG. **1**, the camera module includes a reflective module **10**, a lens module **20**, and an imaging module **30**. Particularly, the reflective module **10** is used to change the propagation direction of the light from

the photographed target so that the light points to the lens module **20**, the lens module **20** is used to converge the light to the imaging module **30**, and the imaging module **30** is used to output the resulting image. That is to say, the reflective module **10** turns the light from the target being photographed, the lens module **20** is maintained on the light reflection path of the reflective module **10** and receives the light from the reflective module **10**, and the imaging module **30** is maintained on the light propagation path of the lens module **20** and receives the light emitted from the lens module **20** for imaging. In one example, the reflective module **10**, lens module **20**, and imaging module **30** are sequentially provided along the direction of light propagation, and the reflective module **10** and imaging module **30** are fixed on both sides of the lens module **20**, respectively. [0084] Correspondingly, the reflective module **10** includes a reflection driving assembly **12** and a reflective element **11** installed in the reflection driving assembly **12**, wherein the reflective element **11** is adapted for reflecting light to turn the imaging optical path of the camera module. In one example, the reflective element **11** is adapted for turning the incident light at a certain angle and then exiting it to the lens module **20**, particularly the angle may be 90° . In other words, the reflective element **11** reflects the light rays propagating in the direction of the first axis Y to the direction of the second axis X that intersects with the first axis Y at a certain angle, and the angle between the first axis Y and the second axis X may be 90° . Particularly, the first axis Y is the incident optical axis of the reflective module **10**, i.e., it is also the incident optical axis of the camera module; and the second axis X is the emergent optical axis of the reflective module **10**, and when the angle between the first axis Y and the second axis X is 90, the first axis Y is perpendicular to the second axis X. It should be understood that, considering manufacturing tolerances, there may be an error of up to 1° in the angle at which the reflective element **11** turns the light.

[0085] In a particular implementation mode, the reflection driving assembly **12** is adapted for driving the movement of the reflective element **11**, thereby changing the propagation path of light, and realizing the optical anti-shake or camera angle adjustment function of the camera module. The reflective element **11** can be implemented as a prism (such as a prism) or a reflector. When the reflective element **11** is implemented as a prism, the reflective element **11** includes a light incident surface **17**, a light reflecting surface **18**, and a light emitting surface **19**. The light incident surface **17** is perpendicular to the light emitting surface **19**, and the light reflecting surface **18** is inclined at a 45° angle with the light incident surface **17** and the light emitting surface **19**, so that the light can undergo a 90° turn at the light reflecting surface **18**. When the reflective element **11** is implemented as a reflector, the reflective element **11** only comprises a light reflecting surface, which is inclined at a 45° angle with the incident light and the emergent light.

[0086] The lens module **20** includes an optical lens **21**, of which an optical axis is the same as the optical axis of the lens module **20**. The optical axis of the optical lens **21** is provided along the direction of the second axis X, so that the light reflected by the reflective module **10** enters the optical lens **21** in the direction of the second axis X, and is transmitted to the imaging module **30** through the optical lens **21**. In one example, the optical lens **21** has a fixed focal length, and the spacing between one optical lens and another adjacent optical lens in the optical lens **21** is fixed and not adjustable. However, the optical lens **21** as a whole can be driven to move along direction of the optical axis of the optical lens **21** to achieve focusing function, or move along the direction perpendicular to the optical axis of the optical lens **21** to achieve optical anti-shake function. In another example, the optical lens **21** has a variable focal length, that is, the focal length of the lens module **20** is variable. The optical lens **21** includes at least one fixed group **211** and at least one active group **212**. The distance between the fixed group **211** and the imaging module **30** in the direction of the optical axis of the optical lens **21** is fixed, and the distance between the active group **212** and the fixed group **211** or the imaging module **30** in the direction of the optical axis of the optical lens **21** is adjustable, so that the focal length of the optical lens **21** is adjustable. Particularly, the optical lens **21** includes a fixed group **211** and an active group **212**, wherein the active group **212** is provided between the fixed group **211** and the imaging module **30**. The fixed

group **211** includes a fixed lens barrel **2111** and at least one fixed lens **2112** contained in the fixed lens barrel **2111**, and the active group **212** includes an active lens barrel **2121** and at least one active lens **2122** contained in the active lens barrel **2121**. It should be understandable that, there can be more than one fixed group **211** and activity group **212**, depending on the specific needs.

[0087] Furthermore, the lens module **20** further includes a lens driving assembly **22**, wherein the optical lens **21** is installed within the lens driving assembly **22**. The lens driving assembly **22** drives the optical lens **21** to move, so as to change the propagation path of light, and thereby achieve functions such as anti-shake, focusing, and zoom. It should be understandable that, the lens driving assembly **22** can drive the overall movement of the optical lens **21** to achieve focusing or anti-shake functions. The lens driving assembly **22** can also drive partial movement of the optical lens **21**, for example, the lens driving assembly **22** can drive the active group **212** of the optical lens **21** to move to achieve zoom or anti-shake functions.

[0088] The imaging module **30** includes a photosensitive assembly **31** and a light filtering assembly **32**. Particularly, the photosensitive assembly **31** includes a photosensitive circuit board **312**, a photosensitive chip **311** installed on the photosensitive circuit board **312**, and electronic components (not shown in the figure). The photosensitive chip **311** is fixed to the photosensitive circuit board **312** by bonding, for example, and electrically connected to the photosensitive circuit board **312** by wire bonding, so that the photosensitive chip **311** receives light for imaging and then is electrically connected to the mobile electronic device through the photosensitive circuit board **312**. The light filtering assembly **32** includes a light filtering bracket **322** and a light filtering element **321** installed on the light filtering bracket **322**. The filter bracket **322** is fixed to the photosensitive circuit board **312** by bonding; for example, the filter element **321** is fixed to the filter bracket **322** by bonding, and is maintained on the photosensitive path of the photosensitive chip **311**. The light filtering element **321** filters the light entering the photosensitive chip **311**.

[0089] In some examples of this application, the imaging module **30** and the lens module **20** are fixed to each other, and the reflective module **10** and the lens module **20** are fixed to each other, thereby forming a periscope camera module with a folded optical path. It should be understood that, the mutual fixation between the reflective module **10** and the lens module **20** can be realized through an adhesive medium, for example, the reflection base **121** of the reflective module **10** and the lens base **221** of the lens module **20** can be fixed through an adhesive medium. Alternatively, the reflective module **10** and the lens module **20** can be fixed by integrated molding, for example, the reflection base **121** of the reflective module **10** and the lens base **221** of the lens module **20** can be fixed by integrated molding. In other words, the reflective module **10** and the lens module **20** use the same base, and the reflective element **11** and the optical lens **21** are installed on the same base to form an integrated periscope camera module.

[0090] As mentioned above, the reflective element **11** is adapted for turning the incident light at a certain angle and then exiting it to achieve imaging path turning. A reflection driving assembly **12** is further provided to drive the reflective element **11** to rotate, thereby achieving the optical anti-shake function or camera angle adjustment function of the camera module. Therefore, this application provides a reflection driving assembly **12** adapted for driving the rotation of the reflective element **11**.

[0091] As shown in FIGS. 2-9, the reflection driving assembly **12** includes a reflection base **121**, a frame **123** that supports the reflective element **11** and can rotate around the first axis Y, and a first support portion **122** provided between the reflection base **121** and the frame **123**. Particularly, the first support portion **122** includes a shaft support member **1221** and at least two auxiliary balls **1222**. The shaft support member **1221** is passed through by the first axis Y, and is fixed to the reflection base **121** or the frame **123**. The at least two auxiliary balls **1222** are provided between at least two auxiliary upper grooves **1235** of the frame **123** and at least two auxiliary lower grooves **1216** of the reflection base **121**. Herein, it should be understood that, the reflective element **11** can be directly provided on the frame **123**, so that the frame **123** can directly support the reflective

element **11**; other elements can also be further installed between the reflective element **11** and the frame **123**, so that the frame **123** may indirectly support the reflective element **11**. In other words, the frame **123** is also considered to support the reflective element **11** in this application, if it supports the reflective element **11** indirectly through other elements.

[0092] Particularly, as shown in FIGS. 3A and 3B, the reflection base **121** includes a reflection substrate **1211** and a first reflection base side portion **1212**, a second reflection base side portion **1213**, and a third reflection base side portion **1214** fixed around the reflection substrate **1211**, wherein the first reflection base side portion **1212** and the third reflection base side portion **1214** are provided opposite to each other on both sides of the reflection substrate **1211**, the second reflection base side portion **1213** is connected to the first reflection base side portion **1212** and the third reflection base side portion **1214**, and the second reflection base side portion **1213** is located on one side of the reflective module **10** which is away from the emergent light, i.e., the second reflection base side portion **1213** is located on the side which is away from the lens module **20**. In this way, the reflection base **121** forms an installation space and has an opening in the direction of light entering the reflective module **10** and an opening in the direction of light exiting the reflective module **10**, so that the frame **123**, the first support portion **122**, and the reflective element **11** can all be accommodated in the installation space of the reflection base **121**, and the reflective element **11** can reflect the light propagating along the first axis Y direction to the direction of the second axis X and transmit it to the lens module **20** through the above two openings.

[0093] As mentioned above, there is the first support portion **122** between the reflection base **121** and the frame **123**. The frame **123** is rotatably supported above the reflection substrate **1211** of the reflection base **121** through the first support portion **122**. The first support portion **122** includes a shaft support member **1221** and at least two auxiliary balls **1222**. In one example, the shaft support member **1221** is fixed to the reflection substrate **1211** of the reflection base **121**, and the shaft support member **1221** protrudes from the top surface of the reflection substrate **1211** which faces the frame **123**. The bottom surface of the frame **123** which faces the reflection substrate **1211** has a shaft positioning groove **1234**. The shaft support member **1221** is accommodated in the shaft positioning groove **1234**, and maintains contact with the shaft positioning groove **1234**. The shaft support member **1221** and the shaft positioning groove **1234** are provided opposite to each other along the direction of the first axis Y. Particularly, the position of the shaft positioning groove **1234** corresponds to the position of the shaft support member **1221**. Both the shaft positioning groove **1234** and the shaft support member **1221** are passed through by the first axis Y. The shape of the shaft support member **1221** matches the shape of the shaft positioning groove **1234**. The shaft support member **1221** and the shaft positioning groove **1234** are mutually limited, and the frame **123** is limited to rotate around the first axis Y relative to the reflection base **121** through the position-limiting relationship between the shaft positioning groove **1234** and the shaft support member **1221**. At this point, the first axis Y is the rotation axis of the frame **123**. The first axis Y coincides with the rotation axis of the frame **123**, and the frame **123** and the reflective element **11** supported on the frame **123** rotate around the first axis Y. Correspondingly, the shaft support member **1221** has an arc-shaped top surface; for example, the shaft support member **1221** protrudes from the reflection substrate **1211** in a hemispherical shape. Of course, the top surface of the hemispherical shaped shaft support member **1221** can also have a plane, thereby reducing the difficulty of forming the shaft support member **1221**. In this example, the shaft support member **1221** is fixed on the reflection substrate **1211** of the reflection base **121**, making the rotation of the frame **123** less prone to deviation. The matching shape of the shaft positioning groove **1234** of the frame **123** with that of the shaft support member **1221** further limits the frame **123** to only rotate around the first axis Y passing through the shaft support member **1221**, making the rotation of the reflective element **11** less susceptible to external influences. It is worth mentioning that, due to the fixed and immovable nature of the shaft support member **1221**, the shape requirements for the shaft positioning groove **1234** are reduced. Maintaining at least three point or line contacts between the

shaft positioning groove **1234** and the shaft support member **1221** can ensure that rotation axis of the frame **123** does not deviate during the rotation process of the frame **123** relative to the reflection base **121**. Herein, in a particular example, line contact refers to circular line contact. [0094] Furthermore, in a particular example, the shaft support member **1221** is made of metal material. The shaft support member **1221** is embedded in the reflection substrate **1211** through an injection molding process for insert member, thereby maintaining the durability of the shaft support member **1221**. However, when the material used to form the shaft positioning groove **1234** is plastic or resin, the metal material of the shaft support member **1221** can easily cause the formation of pits on the shaft positioning groove **1234**, which will affect the rotation effect of the frame **123**. Therefore, the material of the shaft support member **1221** can be made consistent with the material used to form the shaft positioning groove **1234**. For example, the material of the shaft support member **1221** and the material used to form the shaft positioning groove **1234** are both metal, plastic or resin, thereby reducing the probability of forming pits on the shaft positioning groove **1234**. Particularly, the shaft support member **1221** is integrally formed on the top surface of the reflection substrate **1211** through injection molding process, so that the shaft support member **1221** is fixed on the top surface of the reflection substrate **1211**.

[0095] It should be understood that in other examples of the present application, the shaft support member **1221** can also be fixed to the bottom surface of the frame **123**, and correspondingly, the top surface of the reflection substrate **1211** correspondingly has a shaft positioning groove **1234**. In other words, the shaft support member **1221** is fixed to one of the reflection base **121** and the frame **123**, and the shaft positioning groove **1234** is correspondingly provided on one side of the other of the reflection base **121** and the frame **123** which faces the shaft support member **1221**.

[0096] Furthermore, the first support portion **122** further includes at least two auxiliary balls **1222** for assisting the shaft support member **1221** to support the frame **123**. The shaft support member **1221** and the at least two auxiliary balls **1222** form a support plane for supporting the frame **123**, thereby avoiding unnecessary tilting of the frame **123** during rotation. It should be understood that in one example, the at least two auxiliary balls **1222** protrude from the reflection substrate **1211** at a height equal to the height of the shaft support member **1221** protruding from the reflection substrate **1211**, so that the shaft support member **1221** and the at least two auxiliary balls **1222** can provide a horizontal support plane. Particularly, the diameter of the auxiliary ball **1222** is 0.6-1.2 mm; and in a particular example, the diameter of the auxiliary ball **1222** is 0.9 mm.

[0097] To limit the position of the at least two auxiliary balls **1222** between the frame **123** and the reflection base **121**, the bottom surface of the frame **123** has at least two auxiliary upper grooves **1235**, and the top surface of the reflection substrate **1211** has at least two auxiliary lower grooves **1216**. The at least two auxiliary upper grooves **1235** and the at least two auxiliary lower grooves **1216** correspond to each other, and form at least two ball movement spaces, respectively. The at least two auxiliary balls **1222** are provided between the at least two auxiliary upper grooves **1235** of the frame **123** and the at least two auxiliary lower grooves **1216** of the reflection base **121**. In one example, the number of the auxiliary upper grooves **1235** and the number of the auxiliary lower grooves **1216** are equal to the number of the auxiliary balls **1222**, and only one auxiliary ball **1222** is accommodated between one auxiliary upper groove **1235** and one auxiliary lower groove **1216**. For example, as shown in FIG. 3A of this application, the number of the auxiliary balls **1222** is two, and correspondingly, the number of the auxiliary upper grooves **1235** and the auxiliary lower grooves **1216** are also two, respectively.

[0098] Furthermore, the frame **123** is further embedded with a metal piece **1236** for supporting the auxiliary ball, and the metal piece **1236** for supporting the auxiliary ball is embedded in the frame **123** through the insert injection molding process for insert member and exposed as the bottom of the auxiliary upper groove **1235**, thereby enhancing the structure of the frame **123** and making the auxiliary upper groove **1235** have a harder groove bottom.

[0099] In this application, the position-limiting relationship between the shaft support member

1221 and the shaft positioning groove **1234** provides a rotation axis for the frame **123** to rotate. The at least two auxiliary balls **1222** only serve to support the frame **123** on the reflection base **121**. To reduce the resistance force generated by the auxiliary balls **1222**, the at least one of the two auxiliary upper grooves **1235** and the at least two auxiliary lower grooves **1216** are straight-line grooves extending along the tangent direction of the virtual circle centered on the first axis Y. Particularly, the auxiliary balls **1222** are loosely accommodated in the straight-line grooves, and the auxiliary balls **1222** only contact one point with the straight-line grooves in a minimum state, while the auxiliary balls **1222** only contact three points with the straight-line groove in a maximum state. In this way, during the rotation of the frame **123** relative to the reflection base **121**, the motion freedom of the at least two auxiliary balls **1222** is increased, the friction force is reduced, and the wear between at least two auxiliary balls **1222** and wall of the grooves is reduced, thereby improving the energy conversion efficiency of the reflection driving assembly **12**. Correspondingly, the response speed of the reflection driving assembly **12** is improved. It should be understood that, the straight-line groove refers to a groove that extends along the direction of a straight line. In this application, the above-mentioned straight-line groove extends in a straight line along the tangent direction of a virtual circle centered on the first axis Y, and the symmetry axes of the at least two straight-line grooves are tangent to the virtual circle along the length direction. In a particular example, the symmetry axes of the at least two auxiliary upper grooves **1235** or the at least two auxiliary lower grooves **1216** as straight-line grooves are tangent to the virtual circle centered on the first axis Y along the length direction, in other words, one of the at least two auxiliary upper grooves **1235** and the at least two auxiliary lower grooves **1216** are straight-line grooves with symmetry axes tangent to the virtual circle centered on the first axis Y along the length direction. Furthermore, the straight-line groove has two long edge groove walls and two short edge groove walls. The two long edge groove walls are provided opposite each other, and the two short edge groove walls are respectively connected to the two long edge groove walls. The two long edge groove walls are parallel to each other, and extend along the straight line. The connections between the two short side groove walls and the two long side groove walls can be arc-shaped, thereby reducing the difficulty of forming a straight-line groove. Correspondingly, a straight-line groove has a rounded rectangular shape.

[0100] Furthermore, the other of the at least two auxiliary upper grooves **1235** and the at least two auxiliary lower grooves **1216** may also be straight-line grooves. However, considering that when the at least two auxiliary upper grooves **1235** and the at least two auxiliary lower grooves **1216** are straight-line grooves, the position of the auxiliary balls **1222** is not controlled when the frame **123** is driven to rotate relative to the reflection base **121**, resulting in the auxiliary balls **1222** being stuck by the auxiliary upper grooves **1235** and the auxiliary lower grooves **1216**, thereby affecting the rotation of the frame **123** relative to the reflection base **121** around the first axis Y. For example, during the driving process, when the auxiliary balls **1222** are located on the side closest to the rotation direction of the frame **123** in the auxiliary lower groove **1216** for accommodating the auxiliary balls **1222** and on the side farthest from the rotation direction of the frame **123** in the auxiliary upper groove **1235** or accommodating the auxiliary balls **1222**, then the frame **123** is continuously driven to rotate relative to the reflection base **121**. The auxiliary balls **1222** are clamped by the corresponding groove walls of the auxiliary upper groove **1235** and the auxiliary lower groove **1216**, so that it is difficult for the auxiliary balls **1222** to roll or translate, thereby affecting the rotation of the frame **123**. To solve this problem, it can be achieved by increasing the length of the auxiliary upper groove **1235** or the auxiliary lower groove **1216**. However, increasing the length of the auxiliary upper groove **1235** or the auxiliary lower groove **1216** will occupy more space in the frame **123** or the reflection substrate **1211**, causing an increase in the size of the frame **123** or the reflection substrate **1211**, and thus leading to an increase in the size of the reflection driving assembly **12**.

[0101] Therefore, in one example of the present application, the other of the at least two auxiliary

upper grooves **1235** and the at least two auxiliary lower grooves **1216** are positioning grooves for positioning the auxiliary balls **1222**, which are tightly fitted and accommodated in the positioning grooves. It is worth mentioning that, being tightly matched and placed in the positioning grooves does not mean that there is no gap between the auxiliary ball **1222** and the positioning groove. There can still be a certain gap between the auxiliary ball **1222** and the positioning groove, so that the auxiliary ball **1222** can still roll or translate in the positioning groove while being positioned by the positioning groove. Particularly, tightly fitting accommodation refers to centered arrangement of the auxiliary ball **1222** in the positioning groove, and the minimum distance between the auxiliary ball **1222** and the side wall of the positioning groove is less than 0.1 mm. Preferably, the minimum distance is less than 0.05 mm. Correspondingly, loosely fitting accommodation refers to centered arrangement of the auxiliary ball **1222** in the straight-line groove, and the minimum distance between the auxiliary ball **1222** and the long edge groove wall is greater than 0.1 mm, preferably greater than 0.15 mm. The minimum distance between the auxiliary ball **1222** and the short groove wall is at least 0.2 mm greater than the movement stroke of the auxiliary ball **1222**. Correspondingly, the maximum gap between the at least two auxiliary balls **1222** and the at least two auxiliary lower grooves **1216** is less than the maximum gap between the at least two auxiliary balls **1222** and the at least two auxiliary upper grooves **1235**.

[0102] It should be understood that in one particular example, the at least two auxiliary lower grooves **1216** are straight-line grooves extending along the tangent direction of a virtual circle centered on the first axis Y, and the at least two auxiliary upper grooves **1235** are positioning grooves for locating the auxiliary balls **1222**. The at least two auxiliary balls **1222** are loosely accommodated in the at least two auxiliary lower grooves **1216**, and the at least two auxiliary balls **1222** are tightly accommodated in the at least two auxiliary upper grooves **1235**. At this time, the at least the two auxiliary balls **1222** are respectively positioned through the at least two auxiliary upper grooves **1235**. In another particular example, the at least two auxiliary upper grooves **1235** are straight-line grooves extending along the tangent direction of a virtual circle centered on the first axis Y, and the at least two auxiliary lower grooves **1216** are positioning grooves for positioning the auxiliary balls **1222**. The at least two auxiliary balls **1222** are loosely accommodated in the at least two auxiliary upper grooves **1235**, and the at least two auxiliary balls **1222** are tightly accommodated in the at least two auxiliary lower grooves **1216**. At this time, the at least two auxiliary balls **1222** are respectively positioned through the at least two auxiliary lower grooves **1216**. From the perspective of driving the frame **123** to rotate relative to the reflection base **121**, there are no obvious advantages or disadvantages between the two particular examples. However, considering the assembly process, the straight-line grooves cannot locate the balls, and during the installation process, the auxiliary balls **1222** need to be provided in the positioning grooves first. Therefore, to simplify the assembly process and avoid flipping the semi-finished reflection driving assembly during the assembly of the auxiliary balls **1222**, it is preferable to use the at least two auxiliary lower grooves **1216** as positioning grooves for positioning the auxiliary balls **1222**. Correspondingly, the gap between the at least two auxiliary balls **1222** and the at least two auxiliary lower grooves **1216** is smaller than the gap between the at least two auxiliary balls **1222** and the at least two auxiliary upper grooves **1235**.

[0103] Further combining FIGS. 4-5, particularly, **1216'** is a projection of the auxiliary lower groove **1216** along the direction of the first axis Y on the bottom surface of the frame **123**, C is the virtual circle centered on the first axis Y, and A is a symmetry axis of the auxiliary upper groove **1235** along the length direction. In this example, the number of auxiliary balls **1222**, the auxiliary upper grooves **1235**, and the auxiliary lower grooves **1216** are all two. The first support portion **122** includes two auxiliary balls **1222**, the bottom surface of the frame **123** has two auxiliary upper grooves **1235**, the reflection substrate **1211** has two auxiliary lower grooves **1216**, the two auxiliary upper grooves **1235** are symmetrically formed on the bottom surface of the frame **123**, the two auxiliary lower grooves **1216** are symmetrically formed on the top surface of the reflection

substrate **1211**, and the two auxiliary upper grooves **1235** are respectively provided opposite to the two auxiliary lower grooves **1216**, forming two ball movement spaces. Particularly, the two auxiliary upper grooves **1235** are straight-line grooves, and the two auxiliary lower grooves **1216** are positioning grooves. A virtual circle C is formed with the first axis Y as the center. The two auxiliary upper grooves **1235** extend along the tangent direction of the virtual circle C. The initial position of each auxiliary lower groove **1216** is respectively projected along the direction of the first axis Y on a middle area of the opposite auxiliary upper groove **1235**. It should be understood that, the initial positions of the two auxiliary lower grooves **1216** refer to the positions of the two auxiliary lower grooves **1216** when the angle at which the frame **123** can rotate relative to the reflection base **121** in two opposite directions is equal; accordingly, when the reflection driving assembly **12** drives the frame **123** and the reflective element **11** to rotate around the first axis Y, the reflective element **11** can have a large rotation angle in both directions. In a particular example, the center points of two auxiliary upper grooves **1235** are located on the virtual circle C centered on the first axis Y.

[0104] Particularly, both auxiliary upper grooves **1235** have a symmetrical axis A that is tangent to the virtual circle C centered on the first axis Y along the length direction, and the two auxiliary balls **1222** are loosely accommodated in the two auxiliary upper grooves **1235**. When the auxiliary ball **1222** is centered in the auxiliary upper groove **1235**, the minimum distance L2 between the auxiliary ball **1222** and the long side groove wall of the auxiliary upper groove **1235** is greater than 0.1 mm; preferably, the minimum distance L2 is greater than 0.15 mm. The minimum distance L3 between the auxiliary ball **1222** and the short side groove wall of the auxiliary upper groove **1235** is at least 0.2 mm larger than the movement stroke of the auxiliary ball **1222**. The movement stroke of the auxiliary ball **1222** is related to the angle at which the frame **123** can rotate around the first axis Y and the distance between the auxiliary ball **1222** and the first axis Y. Furthermore, in one example, the angle α between the perpendicular lines from the first axis Y to the two auxiliary upper grooves **1235** is a range of 80-100°, which provides better support for the auxiliary ball **1222** during the rotation of the frame **123**, and does not cause the size of the frame **123** to be too large due to the arrangement of the auxiliary upper groove **1235**. In a particular example, the angle α between the perpendicular lines of the symmetry axis A along the length direction from the first axis Y to the two auxiliary upper grooves **1235** is respectively 90°.

[0105] The two auxiliary lower grooves **1216** correspond to the two auxiliary upper grooves **1235**, and the two auxiliary balls **1222** are tightly matched and accommodated in the two auxiliary lower grooves **1216**, respectively. When the auxiliary ball **1222** is centered in the auxiliary lower groove **1216**, the minimum distance L1 between the auxiliary ball **1222** and the side wall of the auxiliary lower groove **1216** is less than 0.1 mm; preferably, the minimum distance L1 is less than 0.05 mm. Correspondingly, the maximum gap between the two auxiliary balls **1222** and the two auxiliary lower grooves **1216** is smaller than the maximum gap between the two auxiliary balls **1222** and the two auxiliary upper grooves **1235**. It should be understood that, tightly fitting only indicates that when an auxiliary ball **1222** is provided between the auxiliary upper groove **1235** and the auxiliary lower groove **1216**, the gap between the auxiliary ball **1222** and the auxiliary lower groove **1216** is smaller than the gap between the auxiliary ball **1222** and the auxiliary upper groove **1235**, so that the auxiliary lower groove **1216** can play a positioning role, and does not mean that the auxiliary ball **1222** is stuck in the auxiliary lower groove **1216**.

[0106] It should be understood that, the tightly fitting relationship between the auxiliary lower groove **1216** and the auxiliary ball **1222** determines the position of the auxiliary ball **1222** relative to the frame **123**, so that when the frame **123** rotates relative to the reflection base **121**, the position of the auxiliary ball **1222** will not be in an unfavorable position, which will cause the auxiliary ball **1222** to be stuck. Therefore, this implementation mode has obvious advantages. It should be understood that, more auxiliary balls **1222**, as well as auxiliary upper grooves **1235** and auxiliary lower grooves **1216** for accommodating auxiliary balls **1222**, can be provided, for example, all of

which has the number of three, four or more, and this application is not limited to this.

[0107] Referring further to FIG. 6, the reflection driving assembly **12** further includes a carrier **125**, and a second support portion **124** provided between the carrier **125** and the frame **123**. The reflective element **11** is fixed to the carrier **125**, and the frame **123** indirectly supports the reflective element **11** through the carrier **125**. Therefore, when the frame **123** is driven to rotate relative to the reflection base **121** around the first axis Y, the carrier **125** will also rotate relative to the reflection base **121** along with the frame **123** around the first axis Y. The carrier **125** is rotatably supported above the frame **123** through the second support portion **124**. Particularly, the carrier **125** can rotate relative to the frame **123** around the third axis Z perpendicular to the first axis Y and the second axis X. In this way, the reflective element **11** can rotate around the first axis Y and the third axis Z, thereby adjusting the angles of the light entering into and emitting from reflective elements **11** in two directions, and achieving the function of anti-shake in two directions or adjusting the camera angle in two directions of the camera module.

[0108] Particularly, the frame **123** includes a frame main body **1231** and a first frame side portion **1232** and a second frame side portion **1233** respectively fixed on both sides of the frame main body **1231** along the direction of the third axis Z. In one example, the first frame side portion **1232** and the second frame side portion **1233** are fixed to the frame main body **1231** by integrated molding. More particularly, the first frame side portion **1232** and the second frame side portion **1233** extend in the direction of the carrier **125** from both sides of the frame main body **1231**, and the top surfaces of the first frame side portion **1232** and the second frame side portion **1233** which face the carrier **125** are respectively concave downwards to form the first shaft lower groove **12321** and the second shaft lower groove **12331**. The second support portion **124** includes two shaft balls **1241**, which are respectively accommodated in the first shaft lower groove **12321** and the second shaft lower groove **12331**. The two shaft balls **1241** have the same height and are passed through by the third axis Z perpendicular to the first axis Y and the second axis X, so that the carrier **125** supported by the two shaft balls **1241** can rotate relative to the frame **123** around the third axis Z. The first frame side portion **1232** and the second frame side portion **1233** extend from both sides of the frame main body **1231** in the direction of the carrier **125**, and adjust the height of the two shaft balls **1241** through the first shaft lower groove **12321** and the second shaft lower groove **12331** respectively, thereby controlling the height of the third axis Z passing through the two shaft balls **1241**. It is worth mentioning that in one example, by adjusting the height of the first frame side portion **1232** and the second frame side portion **1233** extending upwards from the frame main body **1231** and their position in the direction of the second axis X, so that the third axis Z passes through the gravity center of the reflective element **11** or is close to the gravity center of the reflective element **11**, thereby maintaining the stability of the reflective element **11** while rotating around the third axis Z.

[0109] As shown in FIGS. 6-7, the carrier **125** includes a carrier main body **1251** and a first carrier side portion **1252** and a second carrier side portion **1253** fixed on both sides of the carrier main body **1251** along the third axis Z direction. In one example, the first carrier side portion **1252** and the second carrier side portion **1253** are fixed to the carrier main body **1251** by integrated molding. More particularly, the carrier main body **1251** has an inclined mounting surface, with the first carrier side portion **1252** and the second carrier side portion **1253** fixed on both sides of the carrier main body **1251** and forming a reflective element accommodating cavity **1254** with the carrier main body **1251** having the inclined mounting surface. The reflective element **11** is fixed to the carrier **125** by being installed in the reflective element accommodating cavity **1254**.

[0110] As shown in FIGS. 3A and 6-8, in order to respectively accommodate the protruding first frame side portion **1232** and second frame side portion **1233**, the outer sides of the first carrier side portion **1252** and the second carrier side portion **1253**, i.e. the side away from the reflective element **11**, a first carrier side recess **12521** and a second carrier side recess **12531** are concavely formed respectively, so that the first frame side portion **1232** can extend into the first carrier side

recess **12521** of the first carrier side portion **1252**, and the second frame side portion **1233** can extend into the second carrier side recess **12531** of the second carrier side portion **1253**. Furthermore, the position of the first carrier side portion **1252** which faces the first shaft lower groove **12321** has a corresponding first shaft upper groove **12522**, and the position of the second carrier side portion **1253** which faces the second shaft lower groove **12331** has a corresponding second shaft upper groove **12532**. The first shaft upper groove **12522** and the first shaft lower groove **12321** form a ball motion space, and the second shaft upper groove **12532** and the second shaft lower groove **12331** also form a ball motion space. The two shaft balls **1241** are respectively provided between the first shaft upper groove **12522** and the first shaft lower groove **12321**, as well as between the second shaft upper groove **12532** and the second shaft groove **12331**. In this way, the two shaft balls **1241** are respectively provided between the first carrier side portion **1252** and the first frame side portion **1232**, as well as between the second carrier side portion **1253** and the second frame side portion **1233**. It should be understood that, the two shaft balls **1241** can be rolled between the carrier **125** and the frame **123**, and the two shaft balls **1241** can also be fixed onto the carrier **125** or the frame **123**.

[0111] Particularly in one example, the first shaft lower groove **12321** and the second shaft lower groove **12331** respectively maintain at least three point contacts or line contacts with the two shaft balls **1241**, so that the two shaft balls **1241** are determined at the first shaft lower groove **12321** and the second shaft lower groove **12331**, respectively. One of the first shaft upper groove **12522** and the second shaft upper groove **12532** maintains at least three points or line contact with one of the shaft balls **1241**, while the other of the first shaft upper groove **12522** and the second shaft upper groove **12532** only maintains two points contact with the other shaft ball **1241**. For example, the first shaft upper groove **12522** maintains at least three points contact or line contact with one of the shaft balls **1241**, while the second shaft upper groove **12532** only maintains two points contact with the other shaft ball **1241**. In this way, carrier **125** can be positioned on frame **123** through one of the shaft balls **1241**, while the other shaft ball **1241** does not play a positioning role, so that when the carrier **125** is supported on the frame **123** through the two shaft balls **1241**, it will not be difficult to respectively arrange the two shaft balls **1241** between the first shaft upper groove **12522** and the first shaft lower groove **12321**, as well as between the second shaft upper groove **12532** and the second shaft lower groove **12331** due to manufacturing tolerances of the components. In a particular example, line contact refers to circular line contact.

[0112] With further reference to FIGS. 3A and 7, the first shaft lower groove **12321**, the second shaft lower groove **12331**, and the first shaft upper groove **12522** are all frustum shaped grooves. The second shaft upper groove **12532** is a groove that extends along the direction of the third axis Z and has a trapezoidal cross-section, so that one of the shaft roller balls **1241** maintains line contact with the first shaft lower groove **12321** and the first shaft upper groove **12522** respectively, while the other shaft roller ball **1241** maintains line contact with the second shaft lower groove **12331** and maintains two points contact with the second shaft upper groove **12532**.

[0113] Correspondingly, in the present application, the two shaft balls **1241** and the at least two auxiliary balls **1222** are respectively provided at different heights, but the two shaft balls **1241** and the at least two auxiliary balls **1222** can be provided in the reflection driving assembly **12** in the height direction (i.e., the direction of the first axis Y), which makes the assembly of the reflection driving assembly **12** simple, and it only requires to stack various components along the height direction.

[0114] In one example of the present application, as shown in FIG. 6, the surface of the carrier **125** is further fixed with a carrier buffer **1257**. Particularly, the carrier buffer **1257** is fixed to the surface of the carrier **125** through a process such as secondary injection molding, thereby providing a buffering effect when the carrier **125** collides with the frame **123** or the reflection base **121**. The carrier buffer **1257** can be made of flexible materials such as silicone.

[0115] It is worth mentioning that, as mentioned above, considering that the reflection base **121** has

an opening facing the direction of the light exiting from the reflective module **10**, in order to prevent the carrier **125** from exceeding the rotation stroke or falling off when rotating around the third axis Z, the frame **123** further includes two rotation stop members **1237**. The two rotation stop members **1237** extend from both sides of the frame main body **1231** along the direction of the second axis X to the bottom of the first carrier side **1252** and the second carrier side **1253**, so that the projection of the two rotation stop members **1237** in the direction of the first axis Y falls on the first carrier side **1252** and the second carrier side **1253**, respectively. Therefore, when the rotation angle of the carrier **125** exceeds the designed angle, it can be stopped by the two rotation stop members **1237** and stop rotating.

[0116] Furthermore, the reflection driving assembly **12** further includes a reflection driving portion **126** for driving the rotation of the reflective element **11**. The reflection driving portion **126** includes at least two rotating magnets fixed on the carrier **125** and at least two rotating coils fixed on the reflection base **121**. The at least two rotating magnets are provided opposite to the at least two rotating coils, so as to drive the at least two rotating magnets to move after the at least two rotating coils are electrified. Correspondingly, the reflection driving assembly **12** may also include a reflection driving circuit, which is electrically connected to the at least two rotating coils and provides driving current. It should be understood that, the reflection driving circuit can be implemented as a flexible circuit board attached to the reflection base **121**, or a conductive metal insert piece embedded in the reflection base **121**.

[0117] Particularly, as shown in FIGS. **3A-3B** and **6**, the at least two rotating magnets include two first rotating magnets **1261** fixed on the first carrier side portion **1252** and the second carrier side portion **1253**, and one second rotating magnet **1263** fixed on the carrier main body **1251**. The at least two rotating coils include two first rotating coils **1262** fixed on the first reflection base side portion **1212** and the third reflection base side portion **1214**, and one second rotating coil **1264** fixed on the second reflection base side portion **1213**. Particularly, the two first rotating magnets **1261** and the two first rotating coils **1262** are respectively provided opposite to each other, so as to drive the carrier **125** and the reflective element **11** carried on the carrier **125** to rotate around the first axis Y after the two first rotating coils **1262** are electrified. The second rotating magnet **1263** and the second rotating coil **1264** are provided opposite to each other, so that after the second rotating coil **1264** is electrified, the frame **123**, the carrier **125** carried on the frame **123**, and the reflective element **11** are driven to rotate together around the third axis Z.

[0118] In one example, the first carrier side portion **1252**, the second carrier side portion **1253**, and one side of the carrier main body **1251** which faces the reflection base **121** respectively have a rotating magnet groove **1255**. The two first rotating magnets **1261** and one second rotating magnet **1263** are fixed to the carrier **125** by being installed in three rotating magnet grooves **1255**. The first reflection base side portion **1212**, the third reflection base side portion **1214**, and one side of the second reflection base side portion **1213** which faces the carrier **125** respectively have a rotating coil groove **1217**. The two first rotating coils **1262** and one second rotating coil **1264** are fixed to the reflection base **121** by being installed in three rotating coil grooves **1217**.

[0119] More particularly, as shown in FIG. **1**, the reflection driving portion **126** further includes a reflection magnetic conductive plate **1265**, which is embedded in the carrier **125** and provided on one side of the at least two rotating magnets which is away from the at least two rotating coils, thereby constraining the magnetic field of the rotating magnets, and enhancing the magnetic field strength of one side of the rotating magnets which faces the rotating coil.

[0120] In the above example, the first rotating magnet **1261** has two magnets, and the two magnets are respectively provided on both sides of the carrier **125**. At this time, the corresponding two sides of the reflective module **10** will generate a magnetic field, which will affect other components provided near these two sides. Therefore, in order to reduce this problem, in another example of the present application, the at least two rotating magnets only include the first rotating magnet **1261** fixed on one of the first carrier side **1252** and the second carrier side **1253**, and a second rotating

magnet **1263** fixed on the carrier main body **1251**, the other of the first carrier side **1252** and the second carrier side **1253** is not provided a second rotating magnet **1263**.

[0121] Furthermore, as shown in FIGS. 7 and 8, the reflection driving assembly **12** further includes a reflective magnetic attraction portion **127**. The reflective magnetic attraction portion **127** includes two first reflection magnetic components **1271** and two second reflection magnetic components **1272**. The two first reflection magnetic components **1271** are fixed to the bottom surface of the carrier **125**, and the two second reflection magnetic components **1272** are fixed to the top surface of the reflection substrate **1211** of the reflection base **121**. The two first reflection magnetic components **1271** and the two second reflection magnetic components **1272** are magnetically attracted to each other, so that the carrier **125** is magnetically attracted to the top surface of the reflection substrate **1211** with the frame **123** sandwiched between them. Correspondingly, the carrier **125** is supported on the reflection base **121** through the magnetic attraction force of the reflective magnetic attraction portion **127**, with the frame **123** sandwiched between them. Particularly, one of the first reflection magnetic component **1271** and the second reflection magnetic component **1272** is implemented as a magnet, and the other of the first reflection magnetic component **1271** and the second reflection magnetic component **1272** is made of a material that can be attracted by the magnet. For example, the other of the first reflection magnetic component **1271** and the second reflection magnetic component **1272** can be implemented as a magnet or a magnet yoke.

[0122] In one example, two first reflection magnetic components **1271** protrude from the bottom surface of the carrier **125**, and two second reflection magnetic components **1272** protrude from the top surface of the reflection base **121**, thereby reducing the distance between the two first reflection magnetic components **1271** and the two second reflection magnetic components **1272**, and increasing the magnetic attraction between the first reflection magnetic component **1271** and the second reflection magnetic component **1272**. Furthermore, the positions of the frame **123** which face the two first reflection magnetic components **1271** and the two second reflection magnetic components **1272** is concave inwardly and respectively, to provide avoidance space. It should be understood that, the positions of the frame **123** which face the two first reflection magnetic components **1271** and the two second reflection magnetic components **1272** can also form two through grooves directly to provide avoidance space, but retaining some of the structure and forming four half grooves can maintain the structural strength of the frame **123**.

[0123] In one example, as shown in FIG. 7, the bottom surface of carrier **125** is concave inward to form two carrier magnetic attraction grooves **1256**. Two first reflection magnetic components **1271** are fixed to the bottom surface of carrier **125** by being installed separately in the two carrier magnetic attraction grooves **1256**. The top surface of the reflection substrate **1211** also has two reflection base magnetic attraction grooves **1215**, and two second reflection magnetic components **1272** are fixed to the top surface of the reflection substrate **1211** by being installed separately in the two reflection base magnetic attraction grooves **1215**.

[0124] It is worth noting that, FIG. 9 shows a schematic diagram of the reflection base **121** viewed from above in the direction of the first axis Y, wherein the two shaft balls **1241** and the two first reflection magnetic components **1271** are projected onto the reflection substrate **1211** of the reflection base **121** in the direction of the first axis Y. It should be understood that, when the reflective magnetic attraction portion **127** makes the carrier **125** magnetically attracted onto the reflection base **121** through magnetic attraction with the frame **123** sandwiched between them, the reflective magnetic attraction portion **127** also applies magnetic attraction to the first support portion **122** and the second support portion **124**. But if the magnetic attraction of the reflective magnetic attraction portion **127** does not directly act on the third axis Z of the two shaft balls **1241** passing through the second support portion **124**, the magnetic attraction will affect the rotation of the carrier **125** relative to the frame **123** around the third axis Z. Particularly, when the direction of the magnetic attraction of the reflective magnetic attraction portion **127** does not intersect with the

third axis Z, the magnetic attraction of the reflective magnetic attraction portion **127** does not directly act on the third axis Z, resulting in significant recovery resistance that hinders the rotation of the carrier **125** around the third axis Z, so that it is necessary to increase the thrust of the reflection driving assembly **12**, thereby causing the rotation of the carrier **125** relative to the frame **123** around the third axis Z to tilt in one direction. In other words, in order to ensure the normal and stable rotation of the carrier **125** relative to the frame **123**, it is necessary to control the position relationship of the acting direction of the magnetic attraction of the reflective magnetic attraction portion **127** and the third axis Z. Any deviation may cause uneven rotation or increase unnecessary thrust demand, thereby affecting the stability and efficiency of the entire system. It is worth mentioning that, the acting direction of the magnetic attraction of the reflective magnetic attraction portion **127** refers to the acting direction of the combined force of all magnetic attraction forces in the reflective magnetic attraction portion **127**. For example, when two magnetic attraction component forces are generated between the two first and second reflection magnetic components **1271** and **1272** of the reflective magnetic attraction portion **127**, the direction of the combined force of the two magnetic attraction component forces is the acting direction of the magnetic attraction action of the reflective magnetic attraction portion **127**. Alternatively, when the reflective magnetic attraction portion **127** only generates one magnetic attraction force, the acting direction of the magnetic attraction force is the acting direction of the magnetic attraction force of the reflective magnetic attraction portion **127**.

[0125] However, when the magnetic attraction force of the reflective magnetic attraction portion **127** directly acts on the shaft support member **1221** of the first support portion **122**, it will increase wear on the shaft support member **1221**, thereby damaging and affecting the rotation accuracy of the frame **123** relative to the reflection base **121**.

[0126] In order to solve the above problem, in one example, the first axis Y around which the frame **123** rotates relative to the reflection base **121** does not intersect with the third axis Z around which the carrier **125** rotates relative to the frame **123**, and there is a certain distance between the first axis Y and the third axis Z. Correspondingly, when viewing in the direction of the first axis Y, the first axis Y is not located on the third axis Z, and the third axis Z is located between the shaft support member **1221** and the at least two auxiliary balls **1222**. In one particular example, the distance between the shaft support member **1221** and the third axis Z is less than the distance between the at least two auxiliary balls **1222** and the third axis Z. Furthermore, when viewing in the direction of the first axis Y, acting direction of the magnetic attraction force of the reflective magnetic attraction portion **127** intersects with the third axis Z, the magnetic attraction force of the reflective magnetic attraction portion **127** directly acts on the third axis Z, and the reflective magnetic attraction portion **127** is symmetrical about the third axis Z.

[0127] Furthermore, the reflection driving assembly **12** further includes a rotating-position sensing portion **128**, which is used to obtain attitude change information of the reflective element **11**. Particularly, as shown in FIG. 3A, the rotating-position sensing portion **128** includes a first rotation sensing element **1281** and a second rotation sensing element **1282**, which are respectively and electrically connected to the reflection driving circuit. Particularly, in one example, the first rotation sensing element **1281** is fixed on the reflection substrate **1211**, and the first rotation sensing element **1281** senses the magnetic field change of one of the first reflection magnetic components **1271** fixed on the bottom surface of the carrier **125**, thereby obtaining the attitude change information of the carrier **125**. Correspondingly, in this example, the first reflection magnetic component **1271** is implemented as a magnet. The second rotation sensing element **1282** is fixed on the second reflection base side portion **1213**, and the second rotation sensing element **1282** senses the magnetic field change of the second rotating magnet **1263** fixed on the carrier main body **1251**, thereby obtaining the attitude change information of the carrier **125**. In a particular example, the second rotation sensing element **1282** is provided in the second rotating coil **1264**.

[0128] In other words, the rotating-position sensing portion **128** obtains the attitude change

information of the reflective element **11** by obtaining the magnetic field change information of the reflective magnetic attraction section **127** and the at least two rotating magnets through the first rotation sensing element **1281** and the second rotation sensing element **1282**, respectively. Particularly, the rotating-position sensing portion **128** obtains the attitude change information of the carrier **125** and the reflective element **11** by obtaining the magnetic field changes of the first reflection magnetic component **1271** for magnetic attraction and the second rotating magnet **1263** for driving through the first and second rotation sensing elements **1281** and **1282**, respectively. It should be understood that, the first rotation sensing element **1281** and the second rotation sensing element **1282** may be TMR (tunnel magneto resistance), Hall element, or driver chip, and this application is not limited to these.

[0129] Furthermore, as shown in FIG. 2, the reflection driving assembly **12** further includes a reflection cover body **129**, which is fixed to the reflection base **121** and forms an accommodating space to accommodate other components of the reflection driving assembly **12**. Particularly, the reflection cover body **129** includes: a reflection cover body top portion **1291**; and a first reflection cover body side portion **1292**, a second reflection cover body side portion **1293** and a third reflection cover body side portion **1294** which are fixed to the reflection cover body top portion **1291**. Particularly, the reflection cover body top portion **1291** has an incident window **12911**, the first reflection cover body side portion **1292** and the third reflection cover body side portion **1294** are provided opposite to each other on both sides of the reflection cover body top portion **1291**, the second reflection cover body side portion **1293** is connected to the first reflection cover body side portion **1292** and the third reflection cover body side portion **1294**, and the second reflection cover body side portion **1293** is located on the side away from the lens module **20**. In this way, light can enter the reflective module **10** through the incident window **12911** at the reflection cover body top portion **1291**, and leave the reflective module **10** from the side where no side portion of the reflection cover body **129** is provided.

[0130] In summary, the camera module and its reflective module **10** and reflection driving assembly **12** based on the examples of the present application are illustrated, wherein the reflection driving assembly **12** drives the reflective element **11** to rotate through a reasonable structural arrangement, thereby achieving optical anti-shake or camera angle adjustment of the camera module. Particularly, the reflection driving assembly **12** according to this application can drive the reflective element **11** to rotate at an angle of $\pm 2.2^\circ$ around the first axis Y, and drive the reflective element **11** to rotate at an angle of $\pm 1.2^\circ$ around the third axis Z.

[0131] FIGS. 10-20 illustrate the camera module and the reflection driving assembly **12** provided in the camera module according to some implementation modes of the present application. As shown in FIG. 10, the camera module includes the reflective module **10**, the lens module **20**, and the imaging module **30**; wherein the reflective module **10** is used to change the propagation direction of the light from the photographed target so that the light points to the lens module **20**, the lens module **20** is used to converge the light to the imaging module **30**, and the imaging module **30** is used to output the resulting image. That is to say, the reflective module **10** turns the light from the target being photographed, the lens module **20** is maintained on the light reflection path of the reflective module **10** and receives the light from the reflective module **10**, and the imaging module **30** is maintained on the light propagation path of the lens module **20** and receives the light emitted from the lens module **20** for imaging. In one example, the reflective module **10**, the lens module **20**, and the imaging module **30** are sequentially provided along the direction of light propagation, and the reflective module **10** and the imaging module **30** are fixed on both sides of the lens module **20**, respectively.

[0132] Correspondingly, the reflective module **10** includes the reflection driving assembly **12** and the reflective element **11** installed in the reflection driving assembly **12**, wherein the reflective element **11** is adapted to reflect light to fold the imaging optical path of the camera module. In one example, the reflective element **11** is adapted for turning the incident light at a certain angle and

then exiting to the lens module **20**, particularly the angle can be 90° . In other words, the reflective element **11** reflects the light rays propagating along the first axis Y to the direction of the second axis X that intersects with the first axis Y at a certain angle, and the angle between the first axis Y and the second axis X can be 90° . Particularly, the first axis Y is parallel or coincides with the incident optical axis of the reflective module **10**, and the incident optical axis of the reflective module **10** is also the incident optical axis of the camera module. The second axis X, also known as the output optical axis of the reflective module **10**, the first axis Y is perpendicular to the second axis X when the angle between the first axis Y and the second axis X is 90° . It should be understandable that, considering manufacturing tolerances, there may be an error of up to 10 in the angle at which the reflective element **11** turns the light. Furthermore, a third axis Z is defined, and the third axis Z is perpendicular to the first axis Y and the second axis X.

[0133] It is worth mentioning that in this application, the case in which two axes are perpendicular to each other can include the following two types: one is that the two axes intersect in the same plane at right angles to form a traditional vertical relationship; another type is that when two axes are located in different planes, although they do not intersect, their respective direction vectors are perpendicular to each other, thereby forming a spatial vertical relationship. In other words, the vertical relationship between any two axes in the first axis Y, the second axis X, and the third axis Z can be intersecting or spatial. When they intersect, the angle of intersection is a right angle, thereby forming the traditional vertical relationship. When they do not intersect, their respective direction vectors are perpendicular to each other, thereby forming a spatial vertical relationship. In an example, as shown in FIG. **10**, the first axis Y and the third axis Z do not intersect with each other, the direction vector of the first axis Y and the direction vector of the third axis Z are perpendicular to each other, and the first axis Y and the third axis Z have a spatial perpendicular relationship with each other. Furthermore, the second axis X and the third axis Z do not intersect with each other, and the direction vectors of the second axis X and the third axis Z are perpendicular to each other, so that the second axis X and the third axis Z have a spatial perpendicular relationship with each other.

[0134] In a particular implementation mode, the reflection driving assembly **12** is adapted for driving the movement of the reflective element **11**, thereby changing the propagation path of light, and realizing the optical anti-shake or camera angle adjustment function of the camera module. The reflective element **11** can be implemented as a prism (such as a triangular prism) or a reflector. When the reflective element **11** is implemented as a prism, it includes the light incident surface **17**, the light reflecting surface **18**, and the light emitting surface **19**. The light incident surface **17** is perpendicular to the light emitting surface **19**, and the light reflecting surface **18** is inclined at a 45° angle with respect to both of the light incident surface **17** and the light emitting surface **19**. Therefore, the light can undergo a 90° turn at the light reflecting surface **18**. When the reflective element **11** is implemented as a reflector, it only includes the light reflecting surface **18**, which is inclined at a 45° angle relative to the incident light and emitting light.

[0135] The lens module **20** includes the optical lens **21**, of which optical axis is the same as the optical axis of the lens module **20**. The optical axis of the optical lens **21** is provided along the direction of the second axis X, so that the light reflected by the reflective module **10** enters the optical lens **21** in the direction of the second axis X and propagates through the optical lens **21** to the imaging module **30**. In one example, the optical lens **21** has a fixed focal length, and the spacing between one optical lens and another adjacent optical lens in the optical lens **21** is fixed and cannot be adjusted. However, the optical lens **21** as a whole can be driven to move along the direction of the optical axis of the optical lens **21** to achieve focusing function, or move along the direction perpendicular to the optical axis of the optical lens **21** to achieve optical anti-shake function. In another example, the optical lens **21** has a variable focal length (i.e., the focal length of the lens module **20** is variable), and the optical lens **21** includes at least one fixed group **211** and at least one active group **212**. The distance of the fixed group **211** relative to the imaging module **30** in the direction of the optical axis of the optical lens **21** is fixed, and the distance of the active

group **212** relative to the fixed group **211** or the imaging module **30** in the direction of the optical axis of the optical lens **21** is adjustable, so that the focal length of the optical lens **21** is adjustable. Particularly, the optical lens **21** includes the fixed group **211** and the active group **212**; wherein the active group **212** is provided between the fixed group **211** and the imaging module **30**. The fixed group **211** includes the fixed lens barrel **2111** and the at least one fixed lens **2112** contained in the fixed lens barrel **2111**, and the active group **212** include the active lens barrel **2121** and the at least one active lens **2122** contained in the active lens barrel **2121**. It should be understandable that, there can be more than one fixed group **211** and activity group **212**, depending on the specific needs.

[0136] Furthermore, the lens module **20** further includes the lens driving assembly **22**, wherein the optical lens **21** is installed within the lens driving assembly **22**. The lens driving assembly **22** drives the optical lens **21** to move, and change the propagation path of light, thereby achieving functions such as anti-shake, focusing, and zooming. It should be understandable that, the lens driving assembly **22** can drive the overall movement of the optical lens **21** to achieve focusing or anti-shake functions. The lens driving assembly **22** can also drive partial movement of the optical lens **21**, for example, the lens driving assembly **22** can drive the active group **212** of the optical lens **21** to move, there achieving zooming or anti-shake functions.

[0137] The imaging module **30** includes the photosensitive assembly **31** and the light filtering assembly **32**. Particularly, the photosensitive assembly **31** includes the photosensitive circuit board **312**, the photosensitive chip **311** installed on the photosensitive circuit board **312**, and electronic components (not shown in the figure). The photosensitive chip **311** is fixed to the photosensitive circuit board **312** by bonding, for example, electrically connected to the photosensitive circuit board **312** by wire bonding, so that the photosensitive chip **311** receives light for imaging and then is electrically connected to the mobile electronic device through the photosensitive circuit board **312**. The light filtering assembly **32** includes the light filtering bracket **322** and the light filtering element **321** installed on the light filtering bracket **322**. The filter bracket **322** is fixed to the photosensitive circuit board **312** by bonding, e.g., the filter element **321** is fixed to the filter bracket **322** by bonding, thereby being maintained on the photosensitive path of the photosensitive chip **311**. The light filtering element **321** filters the light entering the photosensitive chip **311**.

[0138] In some examples of this application, the imaging module **30** and the lens module **20** are fixed to each other, and the reflective module **10** and the lens module **20** are fixed to each other, thereby forming a periscope camera module with a folded optical path. It should be understood that, the mutual fixation between the reflective module **10** and the lens module **20** can be fixed through an adhesive medium (for example, the reflection base **121** of the reflective module **10** and the lens base **221** of the lens module **20** are fixed through an adhesive medium); alternatively, the reflective module **10** and the lens module **20** are fixed by integrated molding (for example, the reflection base **121** of the reflective module **10** and the lens base **221** of the lens module **20** are fixed by integrated molding). In other words, the same base is used by the reflective module **10** and the lens module **20**, i.e., the reflective element **11** and the optical lens **21** are installed in the same base, thereby forming an integrated periscope camera module.

[0139] As mentioned above, the reflective element **11** is adapted for turning the incident light at a certain angle and then exiting it to achieve imaging path turning, and the reflection driving assembly **12** is further provided to drive the reflective element **11** to rotate, thereby achieving the optical anti-shake function or camera angle adjustment function of the camera module. Therefore, this application provides the reflection driving assembly **12** suitable for driving the rotation of the reflective element **11**.

[0140] As shown in FIGS. **11-20**, the reflection driving assembly **12** includes the reflection base **121**, the carrier **125**, and the reflection driving portion **126** for driving the carrier **125** to rotate relative to the reflection base **121**. Particularly, the reflective element **11** is fixed on the carrier **125**, and the carrier **125** is rotatably provided on the reflection base **121**; the reflective driving part **126** includes at least two rotating magnets and at least two rotating coils, wherein the at least two

rotating magnets and the at least two rotating coils are respectively fixed on the carrier **125** and the reflection base **121**. The at least two rotating magnets and the at least two rotating coils are provided opposite to each other. When the rotating coil is electrified, an interaction force is generated between the rotating coil and the rotating magnet, thereby driving the carrier **125** and the reflective element **11** fixed on the carrier **125** to rotate relative to the reflection base **121**. Correspondingly, the reflection driving assembly **12** may also include the reflection driving circuit, which is electrically connected to the at least two rotating coils and provides driving current. It should be understood that, the reflection driving circuit can be implemented as a flexible circuit board attached to the reflection base **121**, or a conductive metal insert piece embedded in the reflection base **121**.

[0141] The rotating magnet and the rotating coil are relatively provided to form a rotating magnet-rotating coil pair. After the rotating coil is electrified, an interaction force is generated between the rotating magnet and the rotating coil, thereby driving the carrier **125** to rotate relative to the reflection base **121**. It should be understood that, in order to make the reflection driving assembly **12** drive the carrier **125** to rotate around the first axis Y and the third axis Z, the number of rotating magnets and rotating coils should be at least two, respectively. For example, the number of rotating magnets and the number of rotating coils can be two, three, four or more, respectively.

[0142] In one example, the reflection driving portion **126** includes at least one first rotating magnet **1261** and at least one first rotating coil **1262** for driving the carrier **125** to rotate around the first axis Y, as well as at least one second rotating magnet **1263** and at least one second rotating coil **1264** for driving the carrier **125** to rotate around the third axis Z perpendicular to the first axis Y; wherein the at least one first rotating magnet **1261** and the at least one first rotating coil **1262** are provided opposite to each other along the second axis X perpendicular to the first axis Y and the third axis Z, and the at least one second rotating magnet **1263** and the at least one second rotating coil **1264** are also provided opposite to each other along the second axis X.

[0143] In other words, the at least two rotating magnet-rotating coil pairs for driving the carrier **125** to rotate around the first axis Y and the third axis Z are provided on the same side of the carrier **125**. It should be understood that, this implementation mode causes the rotating magnet and rotating coil to be concentrated on one side along the second axis X, so that the reflection driving assembly **12** will not cause electromagnetic interference to other devices on the other side.

[0144] Particularly, as shown in FIGS. **11-13B**, the carrier **125** includes the carrier main body **1251** and the first carrier side portion **1252** and the second carrier side portion **1253** fixed on both sides of the carrier main body **1251** along the third axis Z direction. In one example, the first carrier side portion **1252** and the second carrier side portion **1253** are fixed to the carrier main body **1251** by integrated molding. More particularly, the carrier main body **1251** has an inclined mounting surface, with the first carrier side portion **1252** and the second carrier side portion **1253** fixed on both sides of the carrier main body **1251** and forming the reflective element accommodating cavity **1254** with the carrier main body **1251** having the inclined mounting surface. The reflective element **11** is fixed to the carrier **125** by being installed in the reflective element accommodating cavity **1254**. In this way, the reflective element **11** can follow the carrier **125** to rotate around the reflection base **121**, so that the reflective element **11** can rotate around the first axis Y and the third axis Z, thereby adjusting the angle at which light enters into and exits from the reflective elements **11** in two directions, and achieving the function of anti-shake in two directions or adjusting the camera angle in two directions of the camera module. It should be understood that, the inclined installation surface of the carrier main body **1251** can be further concave to form a groove, which can reduce the mass of the carrier **125** and reduce the demand for driving force without affecting the installation of the reflective element **11**.

[0145] The reflection base **121** includes the reflection substrate **1211** and the first reflection base side portion **1212**, the second reflection base side portion **1213**, and the third reflection base side portion **1214** around and fixed onto the reflection substrate **1211**. Particularly, the first reflection

base side portion **1212** and the third reflection base side portion **1214** are provided opposite to each other on both sides of the reflection substrate **1211**, and the second reflection base side portion **1213** is connected to the first reflection base side portion **1212** and the third reflection base side portion **1214**, and the second reflection base side portion **1213** is located on the side away from the reflective module **10**, i.e., the second reflection base side portion **1213** is located on the side away from the lens module **20**. In this way, the reflection base **121** forms an installation space, and has an opening in the direction of light entering the reflective module **10** and an opening in the direction of light exiting the reflective module **10**, so that the carrier **125** and the reflective element **11** can be accommodated in the installation space of the reflection base **121**. Through the above two openings, light can enter the reflecting element **11** along the first axis Y direction, and after being reflected by the reflecting element **11**, the light can also propagate along the second axis X direction to the lens module **20**.

[0146] In one example of the present application, the at least one first rotating magnet **1261** and the at least one second rotating magnet **1263** are fixed to the carrier **125**, and the at least one first rotating coil **1262** and the at least one second rotating coil **1264** are fixed to the reflection base **121**. In this example, when the rotating coil is electrified, the rotating magnet and the carrier **125** rotate relative to the reflection base **121**, achieving a dynamic magnetic reflection driving assembly **12**, facilitating to simplify the circuit design of the reflection driving assembly **12**, and avoiding the problem of electrifying the movable parts.

[0147] Furthermore, in order to arrange all rotating magnets and rotating coils opposite to each other along the second axis X, the at least one first rotating magnet **1261** and the at least one second rotating magnet **1263** are fixed on one side of the carrier main body **1251** which faces the second reflection base side portion **1213**, and the at least one first rotating coil **1262** and the at least one second rotating coil **1264** are fixed on one side of the second reflection base side portion **1213** which faces the carrier main body **1251**. It should be understood that, one side of the carrier main body **1251** which faces the second reflection base side portion **1213** is the side of the carrier **125** away from the lens module **20**, and the side of the carrier main body **1251** which faces the second reflection base side portion **1213** can also be referred to as the back of the carrier **125**. In other words, the at least one first rotating magnet **1261** and the at least one second rotating magnet **1263** are fixed to the back of the carrier main body **1251** which faces the second reflection base side portion **1213**.

[0148] In a particular example, the number of the first rotating magnets **1261** is two, and the number of the second rotating magnets **1263** is one. The two first rotating magnets **1261** and one second rotating magnet **1263** are respectively fixed on one side of the carrier main body **1251** which faces the second reflection base side portion **1213**. Particularly, the two first rotating magnets **1261** are provided on both sides of the second rotating magnet **1263**, so as to balance the distribution of gravity and make the rotation of the carrier **125** fixed with rotating magnets more stable and balanced. In a preferred example, the two first rotating magnets **1261** are symmetrically provided on both sides of the second rotating magnet **1263**.

[0149] Correspondingly, the number of the first rotating coils **1262** and the second rotating coils **1264** is consistent with that of the first rotating magnets **1261** and the second rotating magnets **1263**, respectively. The number of the first rotating coils **1262** is two, and the number of the second rotating coils **1264** is one. The two first rotating coils **1262** and one second rotating coil **1264** are respectively fixed on one side of the second reflection base side portion **1213** which faces the carrier main body **1251**. Particularly, the two first rotating coils **1262** are provided on both sides of the second rotating coil **1264**, and the two first rotating coils **1262** are provided respectively opposite to the two first rotating magnets **1261**, and the second rotating coil **1264** is opposite to the second rotating magnet **1263**.

[0150] It is worth mentioning that, the arrangement of two first rotating coils **1262** can also reduce the number of turns per first rotating coil **1262** while providing the same or even greater driving

force, thereby avoiding the need to have a too large thickness of the first rotating coil **1262**. Particularly, the thickness of the coil can be understood as the size of the coil extending along the second axis X. It should be understood that, when the thickness of the rotating coil is designed to be large, the wires far away from the rotating magnet in the rotating coil are less affected by the magnetic field of the rotating magnet, and have little effect on the driving force. The arrangement of the two rotating coils can make the thickness of the first rotating coil **1262** unnecessary to be large while having sufficient driving force. Meanwhile, when the carrier **125** rotates around the first axis Y relative to the reflection base **121**, the minimum gap between the first rotating coil **1262** and the first rotating magnet **1261** on both sides will decrease. Therefore, to avoid damage caused by collision between the first rotating coil **1262** and the first rotating magnet **1261**, making the first rotating coil **1262** have a smaller thickness brings a significant advantage in increasing the gap between the first rotating coil **1262** and the first rotating magnet **1261**.

[0151] Correspondingly, in one example, the gap between the first rotating coil **1262** and the first rotating magnet **1261** is not less than the gap between the second rotating coil **1264** and the second rotating magnet **1263**. Particularly, the gap between the two first rotating coils **1262** and the two first rotating magnets **1261** on both sides is not less than the gap between the second rotating coil **1264** and the second rotating magnet **1263** located in the middle. Furthermore, as shown in FIG. **20**, the thickness of the first rotating coil **1262** is smaller than that of the second rotating coil **1264**, in order to create a larger design space for the gap between the two first rotating coils **1262** and the two first rotating magnets **1261** on both sides.

[0152] It is worth mentioning that in one example of the present application, the first rotating magnet **1261** and the second rotating magnet **1263** may be unipolar magnets with only one N pole and one S pole. In another example of the present application, the first rotating magnet **1261** and the second rotating magnet **1263** may be a multipole magnet with at least two N poles and at least two S poles, or a magnet composed of a combination of multiple unipolar magnets. Regardless of whether the first rotating magnet **1261** and the second rotating magnet **1263** are multipole magnets, as shown in FIG. **14**, a surface of the first rotating magnet **1261** which faces the first rotating coil **1262** has at least two magnetic pole regions provided along the third axis Z, and a surface of the second rotating magnet **1263** which faces the second rotating coil **1264** has at least two magnetic pole regions provided along the first axis Y. Particularly, the N-pole region and S-pole region on the surface of the first rotating magnet **1261** which faces the first rotating coil **1262** are provided along the direction of the third axis Z, while the N-pole region and S-pole region on the surface of the second rotating magnet **1263** which faces the second rotating coil **1264** are provided along the direction of the first axis Y. Correspondingly, in the direction of the third axis Z, the size of the second rotating magnet **1263** is greater than that of the first rotating magnet **1261**. It should be understood that in this application, the magnetic pole region refers to an N-pole region or an S-pole region.

[0153] Rotating magnets with multiple N and S poles can provide higher magnetic flux and more complex magnetic field distribution, thereby providing more precise control. It should be understood that, the second rotating magnet **1263** is located at the middle of the two first rotating magnets **1261**. When the second rotating magnet **1263** is implemented as composed of two unipolar magnets, the installation and arrangement of the two unipolar magnets will become difficult due to the magnetic field influence of the first rotating magnets **1261** on both sides. Therefore, in a particular example, the second rotating magnet **1263** located in the middle is a multipolar magnet with two N poles and two S poles instead of being composed of two unipolar magnets. Furthermore, considering that the size of the second rotating magnet **1263** in the direction of the third axis Z should be designed as large as possible, in order to maximize the driving force for rotation around the third axis Z, and there will be a demagnetized zone in the middle of the multipole magnet; accordingly, the two first rotating magnets **1261** can be composed of two unipolar magnets respectively, thereby avoiding the presence of demagnetized zones, and reducing

the space occupied by the two first rotating magnets **1261** in the direction of the third axis Z.

[0154] Furthermore, as shown in FIG. **12B**, one side of the carrier main body **1251** which faces the reflection base **121** is concave inward to form the rotating magnet groove **1255**, and the two first rotating magnets **1261** and one second rotating magnet **1263** are fixed in the rotating magnet groove **1255**. One side of the side portion **1213** of the second reflection base which faces the carrier **125** is concave inward to form the rotating coil groove **1217**, and the two first rotating coils **1262** and one second rotating coil **1264** are fixed to the reflection base **121** by being installed in the rotating coil groove **1217**. In one example, the reflection driving portion **126** further includes the reflection magnetic conductive plate **1265**, which is embedded in the carrier **125** and provided on one side of the at least two rotating magnets which is away from the at least two rotating coils, thereby constraining the magnetic field of the rotating magnet and enhancing the magnetic field strength of one side of the rotating magnet which faces the rotating coil. In a particular example, the reflection magnetic conductive plate **1265** is exposed and serves as the bottom of the rotating magnet groove **1255**.

[0155] Furthermore, the reflection driving assembly **12** further includes the rotating-position sensing portion **128**, which is used to obtain attitude change information of the carrier **125**, and thereby obtain attitude change information of the reflective element **11** installed on the carrier **125**. Particularly, as shown in FIGS. **13A**, **14-15**, the rotating-position sensing portion **128** includes the first rotation sensing element **1281** and the second rotation sensing element **1282** for obtaining attitude change information of the carrier **125**; wherein the first and second rotation sensing elements **1281** and **1282** are respectively electrically connected to the reflection driving circuit. In one example, the first rotation sensing element **1281** and the second rotation sensing element **1282** are both fixed to the side portion of the second reflection base **1213**, wherein the first rotation sensing element **1281** is provided in the middle of one of the first rotating coils **1262** and faces one of the first rotating magnets **1261**, wherein the first rotation sensing element **1281** is used to sense the attitude change information of the carrier **125** while rotating around the first axis Y. The second rotation sensing element **1282** is provided in the middle of the second rotation coil **1264** and faces the second rotating magnet **1263**, wherein the second rotation sensing element **1282** is used to sense the attitude change information of the carrier **125** while rotating around the third axis Z. It should be understood that in this application, the first rotation sensing element **1281** and the second rotation sensing element **1282** may be TMR (tunnel magneto resistance), Hall element, or driver chip, and this application is not limited to these.

[0156] More particularly, due to the need for carrier **125** to rotate around the first axis Y and the third axis Z, when the first and second rotation sensing elements **1281** and **1282** detect positional changes in one direction, they will be affected by positional changes in other direction. Therefore, in order to reduce the impact of positional changes in other directions on sensing accuracy, in a particular example of the present application, as shown in FIG. **15**, the projection of the first rotation sensing element **1281** along the direction of the second axis X overlaps with the third axis Z, and the projection of the second rotation sensing element **1282** along the direction of the second axis X overlaps with the first axis Y. Furthermore, considering that a rotation sensing element will have a good detection effect when it is provided opposite to a connecting region of the N-pole and S-pole regions of the rotating magnet, correspondingly, the first rotation sensing element **1281** is provided opposite to a connecting region of the N-pole and S-pole regions of the first rotating magnet **1261**, and the second rotation sensing element **1282** is provided opposite to a connecting region of the N-pole and S-pole regions of the second rotating magnet **1263**.

[0157] In this application, the main portion of the first rotating coil **1262** which interacts with the first rotating magnet **1261** is the portion of the first rotating coil **1262** which extends along the direction of the first axis Y. Therefore, the first rotating coil **1262** has a length direction which extends along the direction of the first axis Y. The main portion of the second rotating coil **1264** which interacts with the second rotating magnet **1263** is the portion of the second rotating coil **1264**

which extends along the direction of the third axis Z. Therefore, the second rotating coil **1264** has a length direction which extends along the third axis Z. The length direction of the first rotating coil **1262** and the length direction of the second rotating coil **1264** are perpendicular to each other. Correspondingly, in a particular example, the first rotation sensing element **1281** provided in the first rotating coil **1262** is perpendicular to the second rotation sensing element **1282** provided in the second rotating coil **1264**.

[0158] Furthermore, referring to FIGS. **11-13B**, in this application, the reflection driving assembly **12** further includes: the frame **123**, the first support portion **122** provided between the reflection base **121** and the frame **123**, and the second support portion **124** provided between the carrier **125** and the frame **123**. Particularly, the frame **123** is rotatably supported on the reflection base **121** through the first support portion **122**, the carrier **125** is rotatably supported on the frame **123** through the second support portion **124**, then the carrier **125** is rotatably provided on the reflection base **121**, and the frame **123** indirectly carries the reflective element **11** through the carrier **125**. Particularly, the carrier **125** rotates relative to the frame **123** around the third axis Z, and the frame **123** rotates relative to the reflection base **121** around the first axis Y. When the frame **123** is driven to rotate relative to the reflection base **121** around the first axis Y, the carrier **125** will also rotate along with the frame **123** relative to the reflection base **121** around the first axis Y. In this way, the reflective element **11** can rotate around the first axis Y and the third axis Z, thereby adjusting the angle at which light enters into and emits from the reflective elements **11** in both directions, and achieving the function of anti-shake in two directions or adjusting the camera angle in two directions of the camera module.

[0159] As mentioned above, the first support portion **122** is provided between the reflection base **121** and the frame **123**, and the frame **123** is rotatably supported above the reflection substrate **1211** of the reflection base **121** through the first support portion **122**. The first support portion **122** includes the shaft support member **1221** and at least two auxiliary balls **1222**. The shaft support member **1221** is passed through by the first axis Y and fixed to the reflection base **121** or the frame **123**. The at least two auxiliary balls **1222** are provided between at least two auxiliary upper grooves **1235** of the frame **123** and at least two auxiliary lower grooves **1216** of the reflection base **121**. In one example, the shaft support member **1221** is fixed to the reflection substrate **1211** of the reflection base **121**, and the shaft support member **1221** protrudes from the top surface of the reflection substrate **1211** which faces the frame **123**. The bottom surface of the frame **123** which faces the reflection substrate **1211** has the shaft positioning groove **1234**. The shaft support member **1221** is accommodated in the shaft positioning groove **1234**, and maintains contact with the shaft positioning groove **1234**. The shaft support member **1221** and the shaft positioning groove **1234** are provided opposite to each other along the first axis Y direction. Particularly, the position of the shaft positioning groove **1234** corresponds to the position of the shaft support member **1221**. Both of the shaft positioning groove **1234** and the shaft support member **1221** are passed through by the first axis Y. The shape of the shaft support member **1221** matches the shape of the shaft positioning groove **1234**. The positions of the shaft support member **1221** and the shaft positioning groove **1234** are mutually limited, and the frame **123** is limited to rotate relative to the reflection base **121** around the first axis Y through the position-limiting relationship between the shaft positioning groove **1234** and the shaft support member **1221**. At this point, the first axis Y is the rotation axis of frame **123**, the first axis Y coincides with the rotation axis of frame **123**, and frame **123** and the reflective element **11** carried on frame **123** rotate around the first axis Y. Correspondingly, the shaft support member **1221** has an arc-shaped top surface, for example, the shaft support member **1221** protrudes from the reflection substrate **1211** in a hemispherical shape. Of course, the top surface of the hemispherical shaped shaft support member **1221** can also have a plane, thereby reducing the difficulty of forming the shaft support member **1221**. In this example, the shaft support member **1221** is fixed on the reflection substrate **1211** of the reflection base **121**, making the rotation of the frame **123** less prone to deviation. The matching shapes of the shaft positioning groove **1234** of the

frame **123** and the shaft support member **1221** further limit the frame **123** to only rotate around the first axis Y passing through the shaft support member **1221**, making the rotation of the reflective element **11** less susceptible to external influences. It is worth mentioning that, due to the fixed and immovable nature of the shaft support member **1221**, the shape requirements for the shaft positioning groove **1234** are reduced. Maintaining at least three point or line contacts between the shaft positioning groove **1234** and the shaft support member **1221** can ensure that the frame **123** does not deviate from its rotation axis during the process of its rotation relative to reflection base **121**. Herein, in a particular example, line contact refers to circular line contact.

[0160] Furthermore, in a particular example, the shaft support member **1221** is made of metal material, and the shaft support member **1221** is embedded in the reflection substrate **1211** through an insert injection molding process, thereby maintaining the durability of the shaft support member **1221**. However, when the material used to form the shaft positioning groove **1234** is plastic or resin, the metal material of the shaft support member **1221** can easily cause the shaft positioning groove **1234** to form pits, thereby affecting the rotation effect of the frame **123**. Therefore, the material of the shaft support member **1221** can be made consistent with the material used to form the shaft positioning groove **1234**. For example, the material of the shaft support member **1221** and the material used to form the shaft positioning groove **1234** are both metal, plastic or resin, thereby reducing the probability of the shaft positioning groove **1234** to form pits. Particularly, the shaft support member **1221** is integrally formed on the top surface of the reflection substrate **1211** through injection molding process, so that the shaft support member **1221** is fixed on the top surface of the reflection substrate **1211**.

[0161] It should be understood that in other examples of the present application, the shaft support member **1221** can also be fixed to the bottom surface of the frame **123**, and correspondingly, the top surface of the reflection substrate **1211** has the shaft positioning groove **1234**. In other words, the shaft support member **1221** is fixed to one of the reflection base **121** and the frame **123**, and the shaft positioning groove **1234** is correspondingly provided on one side of the other of the reflection base **121** and the frame **123** which faces the shaft support member **1221**.

[0162] Furthermore, the first support portion **122** further includes at least two auxiliary balls **1222** for assisting the shaft support member **1221** to support the frame **123**. The shaft support member **1221** and the at least two auxiliary balls **1222** form a support plane for supporting the frame **123**, thereby avoiding unnecessary tilting of the frame **123** during the rotation process. It should be understood that in one example, the at least two auxiliary balls **1222** protrude from the reflection substrate **1211** at a height equal to the height of the shaft support member **1221** protruding from the reflection substrate **1211**, so that the shaft support member **1221** and the at least two auxiliary balls **1222** can provide a horizontal support plane. Particularly, the diameter of an auxiliary ball **1222** is 0.6-1.2 mm, including 0.6 mm and 1.2 mm. In a particular example, the diameter of an auxiliary ball **1222** is 0.9 mm.

[0163] To limit the position of the at least two auxiliary balls **1222** between the frame **123** and the reflection base **121**, the bottom surface of the frame **123** has at least two auxiliary upper grooves **1235**, and the top surface of the reflection substrate **1211** has at least two auxiliary lower grooves **1216**. The at least two auxiliary upper grooves **1235** and the at least two auxiliary lower grooves **1216** correspond to each other, and form at least two ball movement spaces, respectively. The at least two auxiliary balls **1222** are provided between the at least two auxiliary upper grooves **1235** of the frame **123** and the at least two auxiliary lower grooves **1216** of the reflection base **121**. In one example, the number of the auxiliary upper grooves **1235** and the auxiliary lower grooves **1216** are equal to the number of the auxiliary balls **1222**, and only one auxiliary ball **1222** is accommodated between one auxiliary upper groove **1235** and one auxiliary lower groove **1216**. For example, as shown in FIG. 13A of this application, the number of the auxiliary balls **1222** is two, and correspondingly, the number of the auxiliary upper grooves **1235** and the auxiliary lower grooves **1216** are also two, respectively. It should be understood that, in order to improve the

reliability of the reflection driving assembly **12**, the depth of the auxiliary upper groove **1235** and the auxiliary lower groove **1216** is smaller than the radius of the auxiliary ball **1222**, so that when the auxiliary ball **1222** is provided in the auxiliary upper groove **1235** or the auxiliary lower groove **1216**, at least half of the auxiliary ball **1222** is exposed from the auxiliary upper groove **1235** or the auxiliary lower groove **1216**.

[0164] Furthermore, the frame **123** is further embedded with a metal piece **1236** for supporting the auxiliary ball, and the metal piece **1236** for supporting the auxiliary ball is embedded in the frame **123** through the insert injection molding process for insert piece and exposed as the bottom of the auxiliary upper groove **1235**, thereby enhancing the structure of the frame **123** and making the auxiliary upper groove **1235** have a harder groove bottom.

[0165] In this application, the position-limiting relationship between the shaft support member **1221** and the shaft positioning groove **1234** provides a rotation axis for the frame **123** to rotate. The at least two auxiliary balls **1222** only serve to support the frame **123** on the reflection base **121**. To reduce the resistance force generated by the auxiliary balls **1222**, at least one of the two auxiliary upper grooves **1235** and the at least two auxiliary lower grooves **1216** is a straight-line groove extending along the tangent direction of the virtual circle centered on the first axis Y. Particularly, the auxiliary balls **1222** are loosely accommodated in the straight-line groove, and the auxiliary balls **1222** only contact one point with the straight-line groove in a minimum state, while the auxiliary balls **1222** only contact three points with the straight-line groove in a maximum state. In this way, during the rotation of the frame **123** relative to the reflection base **121**, the motion freedom of the at least two auxiliary balls **1222** is increased, the friction force is reduced, and the wear between the at least two auxiliary balls **1222** and walls of the groove is reduced, thereby improving the energy conversion efficiency of the reflection driving assembly **12**. Correspondingly, the response speed of the reflection driving assembly **12** is improved. It should be understood that, a straight-line groove refers to a groove that extends along the direction of a straight line. In this application, the above-mentioned straight-line groove extends in a straight line along the tangent direction of a virtual circle centered on the first axis Y, and the symmetry axes of the at least two straight-line grooves are tangent to the virtual circle along the length direction. In a particular example, the symmetry axes of the at least two auxiliary upper grooves **1235** or the at least two auxiliary lower grooves **1216** as straight-line grooves are tangent to the virtual circle centered on the first axis Y along the length direction, in other words, one of the at least two auxiliary upper grooves **1235** and the at least two auxiliary lower grooves **1216** is a straight-line groove with a symmetry axis tangent to the virtual circle centered on the first axis Y along the length direction. Furthermore, the straight-line groove has two long edge groove walls and two short edge groove walls. The two long edge groove walls are provided opposite each other, and the two short edge groove walls are respectively connected to the two long edge groove walls. The two long edge groove walls are parallel to each other, and extend along the straight line. The connections between the two short side groove walls and the two long side groove walls can be arc-shaped, thereby reducing the difficulty of forming a straight-line groove. Correspondingly, a straight-line groove has a rounded rectangular shape.

[0166] Furthermore, the other of the at least two auxiliary upper grooves **1235** and the at least two auxiliary lower grooves **1216** may also be a straight-line groove. However, considering that when the at least two auxiliary upper grooves **1235** and the at least two auxiliary lower grooves **1216** are straight-line grooves, the position of the auxiliary balls **1222** is not controlled when the frame **123** is driven to rotate relative to the reflection base **121**, resulting in the auxiliary balls **1222** being stuck by the auxiliary upper grooves **1235** and the auxiliary lower grooves **1216**, thereby affecting the rotation of the frame **123** relative to the reflection base **121** around the first axis Y. For example, during the driving process, when the auxiliary balls **1222** are located on the side closest to the rotation direction of the frame **123** in the auxiliary lower groove **1216** for accommodating the auxiliary balls **1222** and on the side farthest from the rotation direction of the frame **123** in the

auxiliary upper groove **1235** or accommodating the auxiliary balls **1222**, then the frame **123** is continuously driven to rotate relative to the reflection base **121**. The auxiliary balls **1222** are clamped by the corresponding groove walls of the auxiliary upper groove **1235** and the auxiliary lower groove **1216**, so that it is difficult for the auxiliary balls **1222** to roll or translate, thereby affecting the rotation of the frame **123**. To solve this problem, it can be achieved by increasing the length of the auxiliary upper groove **1235** or the auxiliary lower groove **1216**. However, increasing the length of the auxiliary upper groove **1235** or the auxiliary lower groove **1216** will occupy more space in the frame **123** or reflection substrate **1211**, causing an increase in the size of the frame **123** or the reflection substrate **1211**, and thus leading to an increase in the size of the reflection driving assembly **12**.

[0167] Therefore, in one example of the present application, the other of the at least two auxiliary upper grooves **1235** and the at least two auxiliary lower grooves **1216** are positioning grooves for positioning the auxiliary ball **1222**, which is tightly fitted and accommodated in the positioning groove. It is worth mentioning that, being tightly matched and placed in the positioning groove does not mean that there is no gap between the auxiliary ball **1222** and the positioning groove. There can still be a certain gap between the auxiliary ball **1222** and the positioning groove, so that the auxiliary ball **1222** can still roll or translate in the positioning groove while being positioned by the positioning groove. Particularly, tightly fitting accommodation refers to centered arrangement of the auxiliary ball **1222** in the positioning groove, and the minimum distance between the auxiliary ball **1222** and the side wall of the positioning groove is equal to or less than 0.1 mm. Preferably, the minimum distance is equal to or less than 0.05 mm. Correspondingly, loosely fitting accommodation refers to centered arrangement of the auxiliary ball **1222** in a straight-line groove, and the minimum distance between the auxiliary ball **1222** and the long edge groove wall is equal to or greater than 0.1 mm, preferably equal to or greater than 0.15 mm. The minimum distance between auxiliary ball **1222** and the short groove wall is at least 0.2 mm greater than the movement stroke of auxiliary ball **1222**. Correspondingly, the maximum gap between the at least two auxiliary balls **1222** and the at least two auxiliary lower grooves **1216** is less than the maximum gap between the at least two auxiliary balls **1222** and the at least two auxiliary upper grooves **1235**.

[0168] It should be understood that in one particular example, the at least two auxiliary lower grooves **1216** are straight-line grooves extending along the tangent direction of a virtual circle centered on the first axis Y, and the at least two auxiliary upper grooves **1235** are positioning grooves for locating the auxiliary balls **1222**. The at least two auxiliary balls **1222** are loosely accommodated in the at least two auxiliary lower grooves **1216**, and the at least two auxiliary balls **1222** are tightly accommodated in the at least two auxiliary upper grooves **1235**. At this time, the at least the two auxiliary balls **1222** are respectively positioned through the at least two auxiliary upper grooves **1235**. In another particular example, the at least two auxiliary upper grooves **1235** are straight-line grooves extending along the tangent direction of a virtual circle centered on the first axis Y, and the at least two auxiliary lower grooves **1216** are positioning grooves for positioning the auxiliary balls **1222**. The at least two auxiliary balls **1222** are loosely accommodated in the at least two auxiliary upper grooves **1235**, and the at least two auxiliary balls **1222** are tightly accommodated in the at least two auxiliary lower grooves **1216**. At this time, the at least two auxiliary balls **1222** are respectively positioned through the at least two auxiliary lower grooves **1216**. From the perspective of driving the frame **123** to rotate relative to the reflection base **121**, there are no obvious advantages or disadvantages between the two particular examples. However, considering the assembly process, the straight-line groove cannot locate the balls, and during the installation process, the auxiliary balls **1222** need to be provided in the positioning groove first. Therefore, to simplify the assembly process and avoid flipping the semi-finished reflection driving assembly **12** during the assembly of the auxiliary balls **1222**, it is preferable to use the at least two auxiliary lower grooves **1216** as positioning grooves for positioning the auxiliary balls **1222**. Correspondingly, the gap between the at least two auxiliary balls **1222** and the

at least two auxiliary lower grooves **1216** is smaller than the gap between the at least two auxiliary balls **1222** and the at least two auxiliary upper grooves **1235**.

[0169] Further combining FIGS. **16** and **17**, particularly **1216'** is the projection of the auxiliary lower groove **1216** along the direction of the first axis Y on the bottom surface of the frame **123**, C is the virtual circle centered on the first axis Y, and A is the symmetry axis of the auxiliary upper groove **1235** along the length direction. In this example, the number of the auxiliary balls **1222**, the auxiliary upper grooves **1235**, and the auxiliary lower grooves **1216** are all two. The first support portion **122** includes two auxiliary balls **1222**, the bottom surface of the frame **123** has two auxiliary upper grooves **1235**, the reflection substrate **1211** has two auxiliary lower grooves **1216**, the two auxiliary upper grooves **1235** are symmetrically formed on the bottom surface of the frame **123**, the two auxiliary lower grooves **1216** are symmetrically formed on the top surface of the reflection substrate **1211**, and the two auxiliary upper grooves **1235** are respectively provided opposite to the two auxiliary lower grooves **1216**, forming two ball movement spaces. Particularly, the two auxiliary upper grooves **1235** are straight-line grooves, and the two auxiliary lower grooves **1216** are positioning grooves. A virtual circle C is formed with the first axis Y as the center. The two auxiliary upper grooves **1235** extend along the tangent direction of the virtual circle C. The initial position of each auxiliary lower groove **1216** is respectively projected along the direction of the first axis Y on the middle area of the opposite auxiliary upper groove **1235**. It should be understood that, the initial positions of the two auxiliary lower grooves **1216** refer to the positions of the two auxiliary lower grooves **1216** when the angle at which the frame **123** can rotate relative to the reflection base **121** around the first axis Y in two opposite directions is equal; accordingly, when the reflection driving assembly **12** drives the frame **123** to rotate around the first axis Y, the reflective element **11** can have a large rotation angle in both directions. In a particular example, at initial position, the center points of two auxiliary upper grooves **1235** are located on a virtual circle C centered on the first axis Y.

[0170] Particularly, both of the auxiliary upper grooves **1235** have a symmetrical axis A that is tangent to the virtual circle C centered on the first axis Y along the length direction, and the two auxiliary balls **1222** are loosely accommodated in the two auxiliary upper grooves **1235**. When the auxiliary ball **1222** is centered in the auxiliary upper groove **1235**, the minimum distance L2 between the auxiliary ball **1222** and the long side groove wall of the auxiliary upper groove **1235** is greater than 0.1 mm; preferably, the minimum distance L2 is greater than 0.15 mm. The minimum distance L3 between the auxiliary ball **1222** and the short side groove wall of the auxiliary upper groove **1235** is at least 0.2 mm larger than the movement stroke of the auxiliary ball **1222**. The movement stroke of the auxiliary ball **1222** is related to the angle at which the frame **123** can rotate around the first axis Y and the distance between the auxiliary ball **1222** and the first axis Y. Furthermore, in one example, the angle α between the perpendicular lines from the first axis Y to the two auxiliary upper grooves **1235** is a range of 80-100°, which provides better support for the auxiliary ball **1222** during the rotation of the frame **123**, and does not cause the size of the frame **123** to be too large due to the arrangement of the auxiliary upper groove **1235**. In a particular example, the angle α between the perpendicular lines of the symmetry axis A along the length direction from the first axis Y to the two auxiliary upper grooves **1235** is respectively 90°.

[0171] The two auxiliary lower grooves **1216** correspond to the two auxiliary upper grooves **1235**, and the two auxiliary balls **1222** are tightly matched and accommodated in the two auxiliary lower grooves **1216**, respectively. When the auxiliary ball **1222** is centered in the auxiliary lower groove **1216**, the minimum distance L1 between the auxiliary ball **1222** and the side wall of the auxiliary lower groove **1216** is less than 0.1 mm; preferably, the minimum distance L1 is less than 0.05 mm. Correspondingly, the maximum gap between the two auxiliary balls **1222** and the two auxiliary lower grooves **1216** is smaller than the maximum gap between the two auxiliary balls **1222** and the two auxiliary upper grooves **1235**. It should be understood that, tightly fitting only indicates that when an auxiliary ball **1222** is provided between the auxiliary upper groove **1235** and the auxiliary

lower groove **1216**, the gap between the auxiliary ball **1222** and the auxiliary lower groove **1216** is smaller than the gap between the auxiliary ball **1222** and the auxiliary upper groove **1235**, so that the auxiliary lower groove **1216** can play a positioning role, and does not mean that the auxiliary ball **1222** is stuck in the auxiliary lower groove **1216**.

[0172] It should be understood that, the tightly fitting relationship between the auxiliary lower groove **1216** and the auxiliary ball **1222** determines the position of the auxiliary ball **1222** relative to the frame **123**, so that when the frame **123** rotates relative to the reflection base **121**, the position of the auxiliary ball **1222** will not be in an unfavorable position, which will cause the auxiliary ball **1222** to be stuck. Therefore, this implementation mode has obvious advantages. It should be understood that, more auxiliary balls **1222**, as well as auxiliary upper grooves **1235** and auxiliary lower grooves **1216** for accommodating auxiliary balls **1222**, can be provided, for example, all of which has the number of three, four or more, and this application is not limited to this.

[0173] Referring further to FIGS. **11** to **13B**, the frame **123** includes the frame main body **1231** and the first frame side portion **1232** and the second frame side portion **1233** respectively fixed on both sides of the frame main body **1231** along the direction of the third axis Z. In one example, the first frame side portion **1232** and the second frame side portion **1233** are fixed to the frame main body **1231** by integrated molding. More particularly, the first frame side portion **1232** and the second frame side portion **1233** extend in the direction of the carrier **125** from both sides of the frame main body **1231**, and the top surfaces of the first frame side portion **1232** and the second frame side portion **1233** which face the carrier **125** are respectively concave downwards to form the first shaft lower groove **12321** and the second shaft lower groove **12331**. The second support portion **124** includes two shaft balls **1241**, which are respectively accommodated in the first shaft lower groove **12321** and the second shaft lower groove **12331**. The two shaft balls **1241** have the same height and are passed through by the third axis Z perpendicular to the first axis Y and the second axis X, so that the carrier **125** supported by the two shaft balls **1241** can rotate relative to the frame **123** around the third axis Z. The first frame side portion **1232** and the second frame side portion **1233** extend from both sides of the frame main body **1231** in the direction of the carrier **125**, and adjust the height of the two shaft balls **1241** through the heights of the first shaft lower groove **12321** and the second shaft lower groove **12331** respectively, thereby controlling the height of the third axis Z passing through the two shaft balls **1241**. It is worth mentioning that in one example, by adjusting the height of the first frame side portion **1232** and the second frame side portion **1233** extending upwards from the frame main body **1231** and their position in the direction of the second axis X, so that the third axis Z passes through the gravity center of the reflective element **11** or is close to the gravity center of the reflective element **11**, thereby maintaining the stability of the reflective element **11** while rotating around the third axis Z.

[0174] In order to respectively accommodate the protruding first frame side portion **1232** and second frame side portion **1233**, as shown in FIG. **18**, the outer sides of the first carrier side portion **1252** and the second carrier side portion **1253** (i.e. the side away from the reflective element **11**), the first carrier side recess **12521** and the second carrier side recess **12531** are concavely formed respectively, so that the first frame side portion **1232** can extend into the first carrier side recess **12521** of the first carrier side portion **1252**, and the second frame side portion **1233** can extend into the second carrier side recess **12531** of the second carrier side portion **1253**. Furthermore, the position of the first carrier side portion **1252** which faces the first shaft lower groove **12321** has a corresponding first shaft upper groove **12522**, and the position of the second carrier side portion **1253** which faces the second shaft lower groove **12331** has a corresponding second shaft upper groove **12532**. The first shaft upper groove **12522** and the first shaft lower groove **12321** form a ball motion space, and the second shaft upper groove **12532** and the second shaft lower groove **12331** also form a ball motion space. The two shaft balls **1241** are respectively provided between the first shaft upper groove **12522** and the first shaft lower groove **12321**, as well as between the second shaft upper groove **12532** and the second shaft groove **12331**. In this way, the two shaft

balls **1241** are respectively provided between the first carrier side portion **1252** and the first frame side portion **1232**, as well as between the second carrier side portion **1253** and the second frame side portion **1233**. It should be understood that, the two shaft balls **1241** can be rolled between the carrier **125** and the frame **123**, and the two shaft balls **1241** can also be fixed onto the carrier **125** or the frame **123**.

[0175] Particularly in one example, the first shaft lower groove **12321** and the second shaft lower groove **12331** respectively maintain at least three point contacts or line contacts with the two shaft balls **1241**, so that the two shaft balls **1241** are determined at the first shaft lower groove **12321** and the second shaft lower groove **12331**, respectively. One of the first shaft upper groove **12522** and the second shaft upper groove **12532** maintains at least three points or line contact with one of the shaft balls **1241**, while the other of the first shaft upper groove **12522** and the second shaft upper groove **12532** only maintains two points contact with the other shaft ball **1241**. For example, the first shaft upper groove **12522** maintains at least three points contact or line contact with one of the shaft balls **1241**, while the second shaft upper groove **12532** only maintains two points contact with the other shaft ball **1241**. In this way, carrier **125** can be positioned on frame **123** through one of the shaft balls **1241**, while the other shaft ball **1241** does not play a positioning role, so that when the carrier **125** is supported on the frame **123** through the two shaft balls **1241**, it will not be difficult to respectively arrange the two shaft balls **1241** between the first shaft upper groove **12522** and the first shaft lower groove **12321**, as well as between the second shaft upper groove **12532** and the second shaft lower groove **12331** due to manufacturing tolerances of the components. In a particular example, line contact refers to circular line contact.

[0176] Continuing with reference to FIGS. **13A** and **18**, the first shaft lower groove **12321**, the second shaft lower groove **12331**, and the first shaft upper groove **12522** are all frustum shaped grooves. The second shaft upper groove **12532** is a groove that extends along the direction of the third axis Z and has a trapezoidal cross-section, so that one of the shaft roller balls **1241** maintains line contact with the first shaft lower groove **12321** and the first shaft upper groove **12522** respectively, while the other shaft roller ball **1241** maintains line contact with the second shaft lower groove **12331** and maintains two points contact with the second shaft upper groove **12532**.

[0177] Correspondingly, in the present application, the two shaft balls **1241** and the at least two auxiliary balls **1222** are respectively provided at different heights, but the two shaft balls **1241** and the at least two auxiliary balls **1222** can be provided in the reflection driving assembly **12** in the height direction (i.e., the direction of the first axis Y), which makes the assembly of the reflection driving assembly **12** simple, and it only requires to stack various components along the height direction.

[0178] In one example of the present application, as shown in FIG. **12A**, the surface of the carrier **125** is further fixed with the carrier buffer **1257**. Particularly, the carrier buffer **1257** is fixed to the surface of the carrier **125** through a process such as bonding with glue or secondary injection molding, thereby providing a buffering effect when the carrier **125** collides with the frame **123** or the reflection base **121**. The carrier buffer **1257** can be made of flexible materials such as silicone.

[0179] It is worth mentioning that, as mentioned above, considering that the reflection base **121** has an opening facing the direction of the light exiting from the reflective module **10**, in order to prevent the carrier **125** from exceeding the rotation stroke or falling off when rotating around the third axis Z, the frame **123** further includes two rotation stop members **1237**. The two rotation stop members **1237** are provided at both sides of the frame main body **1231** along the direction of the third axis Z, and respectively extend from both sides of the frame main body **1231** along the direction of the second axis X to the bottom of the first carrier side **1252** and the second carrier side **1253**, so that the projection of the two rotation stop members **1237** in the direction of the first axis Y falls on the first carrier side **1252** and the second carrier side **1253**, respectively. Therefore, when the rotation angle of the carrier **125** exceeds the designed angle, it can be stopped by the two rotation stop members **1237** and stop rotating.

[0180] Furthermore, as shown in FIGS. 14, 18, and 20, the reflection driving assembly 12 further includes the reflective magnetic attraction portion 127. The reflective magnetic attraction portion 127 includes two first reflection magnetic components 1271 and two second reflection magnetic components 1272. The two first reflection magnetic components 1271 are respectively fixed to the bottom surface of the carrier 125, and the two second reflection magnetic components 1272 are respectively fixed to the top of the reflection substrate 1211 of the reflection base 121. The two first reflection magnetic components 1271 and the two second reflection magnetic components 1272 are magnetically attracted to each other, so that the carrier 125 is magnetically attracted to the top surface of the reflection substrate 1211 with the frame 123 sandwiched between them.

Correspondingly, the carrier 125 is supported on the reflection base 121 through the magnetic attraction force of the reflective magnetic attraction portion 127, with the frame 123 sandwiched between them. Particularly, one of the first reflection magnetic component 1271 and the second reflection magnetic component 1272 is implemented as a magnet, and the other of the first reflection magnetic component 1271 and the second reflection magnetic component 1272 is made of a material that can be attracted by the magnet. For example, the other of the first reflection magnetic component 1271 and the second reflection magnetic component 1272 can be implemented as a magnet or a magnet yoke.

[0181] In one example of the present application, the two first reflection magnetic components 1271 are implemented as magnetic attraction magnets, and the two second reflection magnetic components 1272 are implemented as magnetic attraction yokes. Due to the fact that the two first reflection magnetic components 1271 implemented as magnetic attraction magnets are further away from the edge of the reflective module 10 compared to the two second reflection magnetic components 1272 implemented as magnetic attraction yokes, the magnetic interference generated by the reflective magnetic attraction portion 127 can be reduced. Correspondingly, in order to further reduce the magnetic interference problem, the two first reflection magnetic components 1271 are implemented as magnetic attraction multipole magnets. It should be understood that, the external expansion magnetic induction lines of multipole magnets are closer than those of monopole magnets, thereby facilitating to reduce magnetic leakage.

[0182] More particularly, the two first reflection magnetic components 1271 protrude from the bottom surface of the carrier 125, and the two second reflection magnetic components 1272 are exposed from the top surface of the reflection base 121, thereby reducing the distance between the two first reflection magnetic components 1271 and the two second reflection magnetic components 1272, and increasing the magnetic attraction force between the first reflection magnetic component 1271 and the second reflection magnetic component 1272. Furthermore, the positions of the frame 123 which face the two first reflection magnetic components 1271 and the two second reflection magnetic components 1272 respectively are concave inwardly to provide avoidance spaces. It should be understood that, two through grooves can also respectively and directly be formed at the positions of the frame 123 which face the two first reflection magnetic components 1271 and the two second reflection magnetic components 1272, so as to provide avoidance space. For example, as shown in FIG. 19, the two through grooves are respectively and directly formed at the positions of the frame 123 which face the two first reflection magnetic components 1271 and the two second reflection magnetic components 1272, wherein the two first reflection magnetic components 1271 respectively pass through the two through grooves directly, so that the distance between the first and second magnetic components is not limited by the arrangement of the frame 123.

[0183] In one example, the bottom surface of carrier 125 is concave inwardly to form two carrier magnetic attraction grooves 1256, and two first reflection magnetic components 1271 are fixed to the bottom surface of carrier 125 by being installed in each of the two carrier magnetic attraction grooves 1256; two second reflection magnetic components 1272 are respectively fixed on the top surface of the reflection substrate 1211 of the reflection base 121 by bonding or insert injection molding. To maintain sufficient gap between the first reflection magnetic component 1271 and the

second reflection magnetic component **1272** while generating sufficient magnetic attraction, the area of the second reflection magnetic component **1272** can also be increased. Correspondingly, in a particular example, the projection of the first reflection magnetic component **1271** in the direction of the first axis Y falls on the second reflection magnetic component **1272**, i.e., the area of the projection of the first reflection magnetic component **1271** in the direction of the first axis Y is smaller than the area of the projection of the second reflection magnetic component **1272** in the direction of the first axis Y. It is worth mentioning that, in order to facilitate the installation of the two second reflection magnetic components **1272**, a magnetic attraction connection portion **1273** can also be provided between the two second reflection magnetic components **1272**. The magnetic attraction connection portion **1273** has an opening in the middle to avoid the shaft support member **1221**, and the magnetic attraction connection portion **1273** protrudes downwards to be fixed in the reflection base **121** by insert injection molding.

[0184] Herein, in order to facilitate the installation of the first reflection magnetic component **1271**, the two first reflection magnetic components **1271** are also magnetically attracted by the reflection magnetic conductive plate **1265** embedded in the carrier **125**. In one example, the reflection magnetic conductive plate **1265** is exposed from two carrier magnetic attraction grooves **1256**, and the two reflection magnetic components are respectively provided in two carrier magnetic attraction grooves **1256**, and attracted each other with the reflection magnetic conductive plate **1265**.

[0185] Furthermore, FIG. **20** shows a schematic diagram of the reflection base **121** viewed from above in the direction of the first axis Y, wherein the two shaft balls **1241** and the two first reflection magnetic components **1271** are projected onto the reflection substrate **1211** of the reflection base **121** in the direction of the first axis Y. It should be understood that, when the reflective magnetic attraction portion **127** makes the carrier **125** magnetically attracted onto the reflection base **121** through magnetic attraction with the frame **123** sandwiched between them, the reflective magnetic attraction portion **127** also applies magnetic attraction to the first support portion **122** and the second support portion **124**. But if the magnetic attraction of the reflective magnetic attraction portion **127** does not directly act on the third axis Z of the two rotating axis balls **1241** passing through the second support portion **124**, the magnetic attraction will affect the rotation of the carrier **125** relative to the frame **123** around the third axis Z. Particularly, when the direction of the magnetic attraction of the reflective magnetic attraction portion **127** does not intersect with the third axis Z, the magnetic attraction of the reflective magnetic attraction portion **127** does not directly act on the third axis Z, resulting in significant recovery resistance that hinders the rotation of the carrier **125** around the third axis Z, so that it is necessary to increase the thrust of the reflection driving assembly **12**, thereby causing the rotation of the carrier **125** relative to the frame **123** around the third axis Z to tilt in one direction. In other words, in order to ensure the normal and stable rotation of the carrier **125** relative to the frame **123**, it is necessary to control the position relationship of the acting direction of the magnetic attraction of the reflective magnetic attraction portion **127** and the third axis Z. Any deviation may cause uneven rotation or increase unnecessary thrust demand, thereby affecting the stability and efficiency of the entire system. It is worth mentioning that, the acting direction of the magnetic attraction of the reflective magnetic attraction portion **127** refers to the acting direction of the combined force of all magnetic attraction forces in the reflective magnetic attraction portion **127**. For example, when two magnetic attraction component forces are generated between the two first and second reflection magnetic components **1271** and **1272** of the reflective magnetic attraction portion **127**, the direction of the combined force of the two magnetic attraction component forces is the acting direction of the magnetic attraction action of the reflective magnetic attraction portion **127**. Alternatively, when the reflective magnetic attraction portion **127** only generates one magnetic attraction force, the acting direction of the magnetic attraction force is the acting direction of the magnetic attraction force of the reflective magnetic attraction portion **127**.

[0186] However, when the magnetic attraction force of the reflective magnetic attraction portion **127** directly acts on the shaft support member **1221** of the first support portion **122**, it will increase wear on the shaft support member **1221**, thereby damaging and affecting the rotation accuracy of the frame **123** relative to the reflection base **121**.

[0187] In order to solve the above problem, in one example, the first axis Y around which the frame **123** rotates relative to the reflection base **121** does not intersect with the third axis Z around which the carrier **125** rotates relative to the frame **123**, and there is a certain distance between the first axis Y and the third axis Z. Correspondingly, when viewing in the direction of the first axis Y, the first axis Y is not located on the third axis Z, and the third axis Z is located between the shaft support member **1221** and the at least two auxiliary balls **1222**. In one particular example, the distance between the shaft support member **1221** and the third axis Z is less than the distance between the at least two auxiliary balls **1222** and the third axis Z. Furthermore, when viewing in the direction of the first axis Y, acting direction of the magnetic attraction force of the reflective magnetic attraction portion **127** intersects with the third axis Z, the magnetic attraction force of the reflective magnetic attraction portion **127** directly acts on the third axis Z, and the reflective magnetic attraction portion **127** is symmetrical about the third axis Z. In a particular example, when viewing along the first axis Y direction, the two first reflection magnetic components **1271** are symmetrically provided about the third axis Z.

[0188] It is worth mentioning that, since the rotating magnets driving the carrier **125** to rotate around the first axis Y are all provided on the back of the carrier **125** which is away from the lens module **20**; accordingly, for the driving carrier **125** to rotate around the first axis Y, the farther the first axis Y is away from the reflection driving portion **126**, the greater the torque of the driving force provided by the reflection driving portion **126** for rotating around the first axis Y is. Therefore, in one example of the present application, the vertical distance L4 between the first axis Y and the center of the first rotating magnet **1261** of the reflection driving portion **126** is equal to or greater than 2 mm, so that the driving force of the reflection driving portion **126** for driving the carrier **125** to rotate around the first axis Y has a sufficient torque, thereby driving the carrier **125**, the frame **123**, and other components fixed on the above two to rotate. Furthermore, considering the limitation of mobile electronic devices on the working current of the rotating coil, the larger the working current of the rotating coil is, the greater the power consumption for the reflection driving assembly **12** is. Therefore, it can be considered to increase the vertical distance L4 between the first axis Y and the center of the first rotating magnet **1261**, thereby reducing the demand for the maximum working current of the first rotating coil **1262**. For example, the maximum working current of the first rotating coil **1262** can be designed below 100 mA. In an example, the vertical distance L4 between the first axis Y and the center of the first rotating magnet **1261** is equal to or greater than 3.5 mm.

[0189] However, when the distance between the first axis Y and the third axis Z is too large, it will result in insufficient utilization of the reflection surface of the reflective element **11** fixed on the carrier **125**, which is not conducive to the overall design of the reflective module **10**. Therefore, further considering the design issue of the spacing between the third axis Z and the first axis Y, in combination with the position of the first axis Y, the vertical distance L4 between the first axis Y and the center of the first rotating magnet **1261** may be 2-5.5 mm, and preferably 3.5-5.5 mm (both including the two end values). Furthermore, the first axis Y is located on the side of the third axis Z which is away from the reflection driving portion **126**, accordingly under approximate conditions, the driving force provided by the reflection driving portion **126** for rotating around the first axis Y may have a large torque, thereby reducing the requirement for the working current of the first rotating coil **1262**, and thus reducing the power consumption of the reflective module **10**.

[0190] It is worth mentioning that, during the usage of the camera module, it is necessary to consider that the gravity of the carrier **125** and the active part composed of the components fixed to the carrier **125** will hinder the carrier **125** from being supported on the reflection base **121** through

the magnetic attraction force of the reflective magnetic attraction portion **127** with the frame **123** sandwiched between them, during the attitude change process of the reflective module **10**; in severe cases, this problem may cause the carrier **125** to fall off. To reduce the likelihood of this situation, the height of the gravity center of the active part can be lowered to bring the gravity center closer to the reflection substrate **1211**, thereby reducing the torque generated by the weight of the active part. Correspondingly, as shown in FIGS. **12B**, and **14-15**, in one example of the present application, the height of the top surface of the first rotating magnet **1261** is lower than the height of the top surface of the second rotating magnet **1263**, thereby reducing the height of the gravity center of the active part. Furthermore, in a particular example, the size of the first rotating magnet **1261** in the direction of the first axis Y is also smaller than the size of the second rotating magnet **1263** in the direction of the first axis Y.

[0191] Furthermore, as shown in FIG. **10**, in one example of the present application, the first axis Y and the third axis Z are not in the same plane, and the first axis Y and the third axis Z are perpendicular to each other but not intersecting. The second axis X and the third axis Z are not in the same plane, and the second axis X and the third axis Z are perpendicular to each other but do not intersect. The first axis Y and the second axis X are located in the same plane, and the first axis Y and the second axis X are perpendicular to and intersect with each other. In other words, the first axis Y and the third axis Z do not intersect with each other, and the first axis Y and the third axis Z are mutually perpendicular in space. The second axis X and the third axis Z do not intersect with each other, and the second axis X and the third axis Z are mutually perpendicular in space. The first axis Y and the second axis X intersect with and are perpendicular to each other. Particularly, the intersection point of the first axis Y and the second axis X is not located on the light reflection surface **18** of the reflective element **11**, while the intersection point of the first axis Y and the second axis X is located above the light reflection surface **18** of the reflective element **11**. It should be understood that, this implementation mode reduces the design difficulty of the reflection driving assembly **12**, and the design of rotation axis of the reflection driving assembly **12** does not need to be limited to the optical axis position of the lens module **20**. Of course, in another example of this application, the intersection point of the first axis Y and the second axis X can also be located on the light reflecting surface **18** of the reflecting element **11**.

[0192] It should be understood that in another example of the present application, the first axis Y and the second axis X may also not intersect with each other, but the first axis Y and the second axis X are mutually perpendicular in space, i.e., any two axes of the first axis Y, the second axis X and the third axis Z do not intersect with each other, but they are mutually perpendicular in space, and any two axes of the first axis Y, the second axis X and the third axis Z do not extend in the same plane.

[0193] Furthermore, as shown in FIG. **11**, the reflection driving assembly **12** further includes the reflection cover body **129**, which is fixed to the reflection base **121** and forms an accommodating space to accommodate other components of the reflection driving assembly **12**. Particularly, the reflection cover body **129** includes: a top portion **1291** of the reflection cover body; and a first reflection cover body side portion **1292**, a second reflection cover body side portion **1293** and a third reflection cover body side portion **1294** which are fixed to the top portion **1291** of the reflection cover body. Particularly, the top portion of the reflection cover body **1291** has an incident window **12911**, the first reflection cover body side portion **1292** and the third reflection cover body side portion **1294** are provided opposite to each other on both sides of the top of the reflection cover body, the second reflection cover body side portion **1293** is connected to the first reflection cover body side portion **1292** and the third reflection cover body side portion **1294**, and the second reflection cover body side portion **1293** is located on the side away from the lens module **20**. In this way, light can enter the reflective module **10** through the incident window **12911** at the top of the reflection cover body **1291**, and leave the reflective module **10** from the side where no side portion of the reflection cover body **129** is provided.

[0194] In another example of the present application, as shown in FIG. 21, the second rotation sensing element **1282** is still provided in the middle of the second rotating coil **1264** and faces the second rotating magnet **1263**. The rotating-position sensing portion **128** also includes a first rotation sensing magnet **1283** fixed to the carrier **125**. The first rotation sensing element **1281** is provided opposite to the first rotation sensing magnet **1283**, and obtains the attitude change information of the carrier **125** rotating around the first axis Y by sensing the magnetic field information change of the first rotation sensing magnet **1283**. Particularly, the first rotation sensing magnet **1283** is fixed in a groove on the first carrier side portion **1252** of the carrier **125**; the first rotation sensing element **1281** is fixed on the first reflection base side portion **1212**, and the second rotation sensing element **1282** is fixed on the second reflection base side portion **1213**.

[0195] In this example, the first rotation sensing element **1281** and the first rotation sensing magnet **1283** are located on a plane passing through the third axis Z and perpendicular to the first axis Y, thereby reducing the magnetic crosstalk problem encountered by the first rotation sensing element **1281** during the sensing process. Particularly, the first rotation sensing element **1281** is used to sense the rotation of the carrier **125** around the first axis Y, and the carrier **125** also rotates relative to the frame **123** around the third axis Z. The first rotation sensing element **1281** and the first rotation sensing magnet **1283** are provided on a plane passing through the third axis Z and perpendicular to the first axis Y, thereby reducing the impact of the rotation of the carrier **125** around the third axis Z on the sensing function of the first rotation sensing element **1281**.

Furthermore, when viewing in the direction of the third axis Z, the distance between the first rotation sensing element **1281** and the first axis Y is equal to or less than 3.5 mm, so as to ensure the symmetry of the sensing by the first rotation sensing element **1281**. Particularly, the smaller the distance between the first rotation sensing element **1281** and the first axis Y is, the better the sensing symmetry of the first rotation sensing element **1281** is. When viewing in the direction of the third axis Z, due to the fact that the second support portion **124** is provided near the first axis Y, it is difficult for the first rotation sensing magnet **1283** to be provided near the first axis Y. Therefore, when viewing in the direction of the third axis Z, the distance between the first rotation sensing element **1281** and the first axis Y may be 0.5-3.5 mm (including the two end values). More particularly, since the third axis Z is located between the first axis Y and the reflection driving portion **126**, the first rotation sensing element **1281** and the first rotation sensing magnet **1283** are provided on the side of the first axis Y which is away from the third axis Z; that is to say, the first rotation sensing element **1281** and the first rotation sensing magnet **1283** are provided on the side of the first axis Y which is away from the second support portion **124**. In this way, when viewing in the direction of the third axis Z, the distance between the first rotation sensing element **1281** and the first axis Y can be provided closer, and the distance between the first rotation sensing element **1281** and the reflection driving portion **126** may be provided farther, thereby further reducing the interference of the reflection driving portion **126** on the first rotation sensing element **1281**.

[0196] In summary, the camera module and the reflection driving assembly **12** based on the examples of the present application are illustrated, wherein the reflection driving assembly **12** drives the reflective element **11** to rotate through a reasonable structural arrangement, thereby achieving optical anti-shake or camera angle adjustment of the camera module. Particularly, the reflection driving assembly **12** according to the present application can drive the reflective element **11** to rotate around the first axis Y at an angle of $\pm 2.2^\circ$, and can drive the reflective element **11** to rotate around the third axis Z at an angle of $\pm 1.2^\circ$. The symbol \pm indicates that the reflective element **11** can rotate around the rotation axis (first axis Y or third axis Z) in two opposite directions clockwise or counterclockwise based on its initial position.

[0197] The basic principles, main features, and advantages of the present application are described. A person skilled in the art should understand that, this application is not limited by the above mentioned examples, and the above mentioned examples and the principles of this application are described in the specification. Without departing from the spirit and scope of this application, there

may be various changes and modifications in this application, all of which fall within the protection scope of the application. The protection scope of this application is defined by the attached claims and their equivalents.

Claims

1. A reflective module comprising: a reflective element, which reflects the light rays propagating in a direction of a first axis to a direction of a second axis intersecting with the first axis at a certain angle; and a reflection driving assembly, which includes a reflection base, a frame supporting the reflective element and capable of rotating around the first axis, and a shaft support member and at least two auxiliary balls which are provided between the reflection base and the frame; wherein the shaft support member is passed through by the first axis and fixed to the reflection base or the frame; and the at least two auxiliary balls are provided between at least two auxiliary upper grooves of the frame and at least two auxiliary lower grooves of the reflection base, and one of the at least two auxiliary upper grooves and at least two auxiliary lower grooves are straight-line grooves extending along the tangent direction of a virtual circle centered on the first axis.
2. The reflective module according to claim 1, wherein symmetry axes along a length direction of the at least two straight-line grooves are tangent to the virtual circle.
3. The reflective module according to claim 1, wherein the other of the at least two auxiliary upper grooves and the at least two auxiliary lower grooves are positioning grooves for locating the auxiliary balls.
4. The reflective module according to claim 3, wherein the at least two auxiliary upper grooves are the straight-line grooves, and the at least two auxiliary lower grooves are the positioning grooves, and a maximum gap between the at least two auxiliary balls and the at least two auxiliary lower grooves is less than a maximum gap between the at least two auxiliary balls and the at least two auxiliary upper grooves.
5. The reflective module according to claim 4, wherein an initial position of each auxiliary lower groove is projected in the direction of the first axis onto a middle area of the opposite auxiliary upper groove.
6. The reflective module according to claim 1, wherein the shaft support member is fixed to a reflection substrate of the reflection base, and the shaft support member protrudes from a top surface of the reflection substrate which faces the frame, and a shaft positioning groove is located on a bottom surface of the frame which faces the reflection substrate, and the shaft support member is accommodated in the shaft positioning groove and maintains contact with the shaft positioning groove.
7. The reflective module according to claim 1, wherein the reflection driving assembly further comprises a carrier and a second support portion provided between the carrier and the frame, and the reflective element is fixed to the carrier.
8. The reflective module according to claim 7, wherein the second support portion comprises two shaft balls, and the two shaft balls have same height and are passed through by a third axis perpendicular to the first axis and the second axis, and the carrier rotates relative to the frame around the third axis.
9. The reflective module according to claim 8, wherein the reflection driving assembly further comprises a reflective magnetic attraction portion, and the carrier is supported on the reflection base through the magnetic attraction force of the reflective magnetic attraction portion with the frame sandwiched between them.
10. The reflective module according to claim 9, wherein viewing in the direction of the first axis, an acting direction of the magnetic attraction force of the reflective magnetic attraction portion intersects with the third axis.
11. The reflective module according to claim 10, wherein the first axis and the third axis do not

intersect, and the distance between the shaft support member and the third axis is less than the distance between the at least two auxiliary balls and the third axis.

12. The reflective module according to claim 7, wherein the reflection driving assembly further comprises a reflection driving portion for driving the rotation of the reflective element, and the reflection driving portion comprises at least two rotating magnets fixed on the carrier and at least two rotating coils fixed on the reflection base, and the at least two rotating magnets are provided opposite to the at least two rotating coils.

13. The reflective module according to claim 12, wherein the reflection driving assembly further comprises a rotating-position sensing portion, and the rotating-position sensing portion comprises a first rotation sensing element and a second rotation sensing element, and the rotating-position sensing portion respectively obtains the magnetic field change information of the reflective magnetic attraction portion of the reflection driving assembly and the magnetic field change information of the at least two rotating magnets through the first rotation sensing element and the second rotation sensing element, thereby obtaining the attitude change information of reflective element.

14. A camera module comprising: a reflective module according to claim 1; a lens module, which is maintained on a light reflection path of the reflective module; and an imaging module, which receives the light emitted by the lens module for imaging.

15-32. (canceled)
