

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250260693

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

Harris; Richard H.

Handling Encoded Information

Abstract

A method comprises a portable device obtaining a graphical encoded information item which is displayed on a display of a computing apparatus, decoding the encoded information from the encoded information item, and transmitting a first message to first server apparatus, the first message including the decoded information and a first identifier identifying the device or a user of the device, wherein the decoded information includes an apparatus identification information item for allowing identification of the computing apparatus, and the first server apparatus receiving the first message from the device, establishing the identity of the user of the device, wherein establishing the identity of the user comprises using the first identifier to determine if the user is registered with the first server apparatus in response to establishing the identity of the user, authorising the user to access a service, and providing the service to the user via the computing apparatus using the apparatus identification information item or sending a second message to a second server apparatus, the second message including the apparatus identification information item and indicating that the user is authorised to access the service provided by the second server apparatus, the second server apparatus responding to receipt of the second message by providing the service to the user via the computing apparatus using the apparatus identification information item.

Inventors: Harris; Richard H. (Hampshire, GB)

Applicant: ENSYGNIA IP LTD (EIPL) (London, GB)

Family ID: 43500646

Appl. No.: 18/888970

Filed: September 18, 2024

Foreign Application Priority Data

GB 1020025.1

Nov. 25, 2010

Related U.S. Application Data

parent US continuation 18212010 20230620 ABANDONED child US 18888970
parent US continuation 17450328 20211008 ABANDONED child US 18212010
parent US continuation 16734984 20200106 parent-grant-document US 11146561 child US
17450328
parent US continuation 15450837 20170306 parent-grant-document US 10530769 child US
16734984
parent US continuation 13989519 20130815 parent-grant-document US 9614849 WO continuation
PCT/GB2011/052320 20111125 child US 15450837

Publication Classification

Int. Cl.: **H04L9/40** (20220101); **G06F16/955** (20190101); **G06F21/34** (20130101); **G06F21/35** (20130101); **G06F21/36** (20130101); **G06F21/43** (20130101); **G06Q20/32** (20120101); **G06Q20/40** (20120101); **H04L9/32** (20060101); **H04W12/77** (20210101)

U.S. Cl.:

CPC **H04L63/10** (20130101); **G06F16/9554** (20190101); **G06F21/34** (20130101); **G06F21/35** (20130101); **G06F21/36** (20130101); **G06F21/43** (20130101); **G06Q20/3276** (20130101); **G06Q20/401** (20130101); **G06Q20/407** (20130101); **H04L9/32** (20130101); **H04L63/08** (20130101); **H04L63/083** (20130101); **H04L63/0853** (20130101); **H04L63/18** (20130101); H04L2463/082 (20130101); H04W12/77 (20210101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION [0001] This application is a continuation application of U.S. patent application Ser. No. 18/212,010, filed Jun. 20, 2023, which is a continuation of U.S. patent application Ser. No. 17/450,328, filed Oct. 8, 2021, which is a continuation of U.S. patent application Ser. No. 16/734,984, filed Jan. 6, 2020, which is a continuation of U.S. patent application Ser. No. 15/450,837, filed Mar. 6, 2017, which is a continuation application of U.S. patent application Ser. No. 13/989,519, filed Aug. 15, 2013, which is a U.S. National Stage Application under 35 U.S.C. Section 371 of International Patent Application No. PCT/GB2011/052320, filed Nov. 25, 2011, which claims benefit to British Application No. 1020025.1, filed Nov. 25, 2010, the entirety of each application being incorporated herein by reference.

FIELD OF THE INVENTION

[0002] The invention relates to the handling of encoded information.

BACKGROUND TO THE INVENTION

[0003] Identity cloning is an increasingly common phenomenon. Fraudsters use a wide variety of mechanisms to in order to illegally elicit personal information such as usernames, passwords, dates of birth and addresses with a view to cloning identities. One such mechanism is where a fraudster provides a spoof (or clone) of a website, which to an unsuspecting user appears identical to the original. Believing that the website is the original, the user provides personal information, such as login details or credit card details, which are recorded by the fraudster. A more sophisticated approach is a “man-in-the-middle attack” in which a fraudster provides the clone website and records the personal information, but also passes the personal information to the real website, which logs the user in as normal. In this way, the user does not notice anything different and the

fraudster is able to obtain the personal information without alerting the user. This invention was made with a view to preventing these and other similar types of fraudulent activity.

SUMMARY OF THE INVENTION

[0004] According to a first aspect, this specification describes a method comprising a device obtaining an encoded information item, decoding the encoded information from the encoded information item, and transmitting a first message to first server apparatus, the first message including the decoded information and a first identifier identifying the device or a user of the device; and the first server apparatus receiving the first message from the device, using the first identifier to establish the identity of the user of the device, and in response to establishing the identity of the user, performing an action based on the decoded information.

[0005] The encoded information may comprise a third identifier, the third identifier identifying the first server apparatus, and the first message may be transmitted to the first server apparatus based on the third identifier.

[0006] According to a second aspect, this specification describes a method comprising a device obtaining an encoded information item, and transmitting a first message to first server apparatus, the first message including the encoded information item and a first identifier identifying the device or a user of the device, and the first server apparatus receiving the first message from the device, decoding the encoded information from the encoded information item, using the first identifier to establish the identity of the user of the device, and in response to establishing the identity of the user, performing an action based on the decoded information.

[0007] In the first or second aspects, the decoded information may comprise a verification information item and the method may further comprise the first server apparatus comparing the verification information item with a reference verification item, if there is identity between the verification information item and the reference verification item, performing the action based on the decoded information, and if there is not identity between the verification information item and the reference verification item aborting the method before prior to performing the action based on the decoded information.

[0008] The decoded information may include an apparatus identification information item for allowing identification of computing apparatus on, by, or near to which the encoded information object is provided.

[0009] Performing the action may comprise sending a signal to the computing apparatus based on the apparatus identification information item. Performing the action may also comprise allowing the user to access a service, wherein the signal comprises an indication that the user is allowed access to the service.

[0010] The encoded information may comprise a second identifier, the second identifier identifying second server apparatus and performing an action based on the decoded information may comprise sending a second message to the second server, the second message including authorisation information relating to the identified user. The decoded information may include an apparatus identification information item for allowing identification of computing apparatus on, by, or near to which the encoded information object is provided, the second message may include the apparatus identification information item, and the method may further comprise the second server apparatus responding to receipt of the second message by sending a signal to the computing apparatus based on the apparatus identification information item. The second server apparatus may respond to receipt of the second message by allowing the user to access a service, and the signal may comprise an indication that the user is allowed access to the service.

[0011] According to a third aspect, this specification describes a system comprising a device configured to obtain an encoded information item, to decode the encoded information from the encoded information item, and to transmit a first message to first server apparatus, the first message including the decoded information and a first identifier identifying the device or a user of the device, and first server apparatus configured to receive the first message from the device, to use the

first identifier to establish the identity of the user of the device, and in response to establishing the identity of the user, to perform an action based on the decoded information.

[0012] According a fourth aspect, this specification describes a system comprising a device configured to obtain an encoded information item, and to transmit a first message to first server apparatus, the first message including the encoded information item and a first identifier identifying the device or a user of the device, and first server apparatus configured to receive the first message from the device, to decode the encoded information from the encoded information item, to use the first identifier to establish the identity of the user of the device, and in response to establishing the identity of the user, to perform an action based on the decoded information.

[0013] The device and the first server apparatus may be configured as described above by way of one or more processors operating under control of computer-readable code, optionally stored on one or more memory. The one or more memory may comprise one or more non-transitory memory media.

[0014] This specification also describes a method comprising a portable device obtaining a graphical encoded information item which is displayed on a display of a computing apparatus, decoding the encoded information from the encoded information item; and transmitting a first message to first server apparatus, the first message including the decoded information and a first identifier identifying the device or a user of the device, wherein the decoded information includes an apparatus identification information item for allowing identification of the computing apparatus, and the first server apparatus receiving the first message from the device, establishing the identity of the user of the device, wherein establishing the identity of the user comprises using the first identifier to determine if the user is registered with the first server apparatus, in response to establishing the identity of the user, authorising the user to access a service, and providing the service to the user via the computing apparatus using the apparatus identification information item, or sending a second message to a second server apparatus, the second message including the apparatus identification information item and indicating that the user is authorised to access the service provided by the second server apparatus, the second server apparatus responding to receipt of the second message by providing the service to the user via the computing apparatus using the apparatus identification information item.

[0015] This specification also describes method comprising a portable device obtaining a graphical encoded information item which is displayed on a display of a computing apparatus and transmitting a first message to first server apparatus, the first message including the encoded information item and a first identifier identifying the device or a user of the device, and the first server apparatus receiving the first message from the device, decoding the encoded information from the encoded information item, wherein the decoded information includes an apparatus identification information item for allowing identification of the computing apparatus, establishing the identity of the user of the device, wherein establishing the identity of the user comprises using the first identifier to determine if the user is registered with the first server apparatus, in response to establishing the identity of the user, authorising the user to access a service, and providing the service to the user via the computing apparatus using the apparatus identification information item or sending a second message to a second server apparatus, the second message including the apparatus identification information item and indicating that the user is authorised to access the service provided by the second server apparatus, the second server apparatus responding to receipt of the second message by providing the service to the user via the computing apparatus using the apparatus identification information item.

[0016] The specification also describes systems for performing the above-described methods.

[0017] This specification also describes computer-readable code, optionally stored on a non-transitory memory medium, which when executed by computing apparatus, causes the computing apparatus to perform any of the above methods.

Description

BRIEF DESCRIPTION OF THE FIGURES

[0018] For a more complete understanding of example embodiments of the present invention, reference is now made to the following description taken in connection with the accompanying drawings in which:

[0019] FIG. 1 is a schematic illustration of a system in which embodiments of the invention can be implemented;

[0020] FIG. 2 is a schematic illustration of a method according to embodiments of the invention; and

[0021] FIG. 3 is a schematic diagram illustration of a system and methods according to alternative embodiments of the invention.

DETAILED DESCRIPTION OF EMBODIMENTS OF THE INVENTION

[0022] In the drawings and the following description, like reference numerals refer to like elements.

[0023] FIG. 1 is a schematic illustration of a system in which embodiments of the invention can be implemented.

[0024] The system 1 comprises computing apparatus 10, a mobile device 12, a first server apparatus 14 and a second server apparatus 16. The first and second server apparatuses 14, 16 may be located in “the cloud”.

[0025] The mobile device 12 is operable to communicate wirelessly with the first server apparatus 14. Wireless communication with the first server apparatus is carried out via a transceiver 124. The communication with the first server apparatus may be via a telephone network or a data network. The mobile device 12 comprises a controller 120 and one or more memory 122. The controller 120 comprises at least one processor 120A. The controller 120 may also comprise at least one application specific integrated circuit (ASIC) not shown. The at least one memory 122 may comprise any suitable type of fixed or removable memory medium, such as but not limited to ROM, RAM or EEPROM. The at least one memory 120 has stored thereon computer-readable instructions 122A. The controller 120 is operable to read the computer-readable instructions 122A and operate under the control of the computer-readable instructions 122A. The controller 20 is operable to control the other components of the mobile device 12.

[0026] The mobile device 12 comprises obtaining means 124 for obtaining encoded information items which are external to the device 12. The obtaining means 124 may comprise a camera or a scanner for obtaining graphical information or any other type of means suitable for obtaining encoded information items.

[0027] The mobile device 12 also comprises a user interface 126 for receiving user inputs. The mobile device may also comprise a display 128. In this example, the user interface 126 and display 128 form a touchscreen. It will be appreciated however, that the user interface 126 may be of any type. For example, it may comprise one or more or a hardware key or keys, a trackball, a touchpad, a scroll wheel etc.

[0028] The first server apparatus 14 is operable to communicate with the mobile device 12. The first server apparatus 14 is operable also to communicate with the second server apparatus 16. The first server apparatus 14 comprises a controller 140 and one or more memory 142. The controller 140 comprises at least one processor 140A. The controller 140 may also comprise at least one application specific integrated circuit (ASIC) not shown. The at least one memory 142 may comprise any suitable type of fixed or removable memory medium, such as but not limited to ROM, RAM or EEPROM. The at least one memory 140 has stored thereon computer-readable instructions 142A. The controller 140 is operable to read the computer-readable instructions 142A and to operate under their control.

[0029] The first server apparatus **14** comprises also one or more transceivers **146** for communicating with the mobile device **12** and the second server apparatus **16**. The communication between the first and second server apparatuses **14**, **16** may be carried out in any suitable manner. [0030] The first server apparatus **14** may be located at a single location and may comprise one or more separate devices or machines. Alternatively, the first server apparatus **14** may be distributed over a plurality of locations.

[0031] The second server apparatus **16** is operable to communicate with the computing apparatus **10** and the first server apparatus **14** in any suitable manner. The second server apparatus **16** comprises one or more transceivers **164** for communicating with the computing apparatus **10** and the first server apparatus **14**. The second server apparatus **16** comprises a controller **160** and one or more memory **162**. The controller **160** comprises at least one processor **160A**. The controller **160** may also comprise at least one application specific integrated circuit (ASIC) not shown. The at least one memory **162** may comprise any suitable type of fixed or removable memory medium, such as but not limited to ROM, RAM or EEPROM. The at least one memory **160** has stored thereon computer-readable instructions **162A**. The controller **160** is operable to read the computer-readable instructions **162A** and to operate under their control. The controller **160** is operable also under the control of the computer-readable code to control the other components of the second server apparatus **16**.

[0032] The second server apparatus **16** may be located at a single location and may comprise one or more separate devices or machines. Alternatively, the second server apparatus **16** may be distributed over a plurality of locations.

[0033] The computing apparatus **10** is operable to receive signals from the second server apparatus **16** via a transceiver **106**, to interpret the information contained therein and to display it on a display **104** for consumption by a user. The computing apparatus **10** may also comprise a user interface **108**, such as but not limited to a mouse, a touch pad, or a keyboard via which a user input can be received. The computing apparatus **10** comprises a controller **100** and one or more memory **102**. The controller **100** comprises at least one processor **100A**. The controller **100** may also comprise at least one application specific integrated circuit (ASIC) not shown. The at least one memory **102** may comprise any suitable type of fixed or removable memory medium, such as but not limited to ROM, RAM or EEPROM. The at least one memory **100** has stored thereon computer-readable instructions **102A**. The controller **100** is operable to read the computer-readable instructions **102A** and to operate under their control. The controller **100** is operable under the control of the computer-readable code to control the other components, such as the display **104** and the transceiver **106**.

[0034] FIG. 2 is a schematic illustration of a method according to a first embodiment of the invention.

[0035] In step S2-1, the second server apparatus **16**, which is in this example a web server, provides the computing apparatus **10** with information. In this example, the information is web page information. The provision of the web page information may be in response to a request received from the computing apparatus **10** following receipt at the computing apparatus **10** of a user input.

[0036] In step S2-2, the computing apparatus receives and displays the web page information. In this example, the webpage information comprises a "Login" page **110**. The "Login" page **110** contains fields into which a user is able to provide details, in this example a username and password. The second server apparatus **16** is operable to verify these details and subsequently to allow the user to access services and content provided within the web page.

[0037] The web page comprises an encoded information item **112** which contains encoded information. In this example, the encoded information item **112** is a graphical object (GO) (which is depicted in the Figures as a "quick response" (QR) code). It will be appreciated that various other types of graphical object may instead be used. Examples of such are barcodes, fractal patterns and moving images.

[0038] The GO **112** comprises a GO address information item. The GO address information item comprises an address of the computer apparatus **10** on or by which the GO **112** is displayed. The GO address information item may comprise a code, for example a numeric code or an alphanumeric code, which identifies a route or a number of routes to the device. Examples of such codes are an IP address, a telephone number, a domain name and a Blackberry® PIN.

[0039] According to other embodiments, the GO address information item may not comprise address information per se, but may instead comprise information which allows the address of the apparatus on which the GO **112** is displayed to be determined. This may include for example a code or number, such as but not limited to a hardware serial number, which can be used to determine the route to the computing apparatus (e.g. the IP address) from a look-up table.

[0040] In this example, the GO **112** also comprises a second server identification (SSID) information item for allowing the second server apparatus **16** to be identified. The SSID information item may comprise an address of the second server apparatus **16**. Alternatively, the SSID information item may comprise information allowing the application of the mobile device **12** or the first server apparatus **14** to be determined, for example from a look up table.

[0041] The GO **112** may also comprise a first server identification (FSID) information item for allowing the mobile device **12** to identify the first server apparatus **14** with which the GO **112** is associated. The FSID information item may comprise an address of the first server apparatus **14** or may instead comprise a data item such as a code which allows an application (which is described in more detail below) stored on the mobile device **12** to retrieve the address of the first server apparatus **14** from memory **122**.

[0042] The GO **112** may also comprise a verification information item or items for allowing verification of the graphical object to ensure it is not a fraud.

[0043] The information required to display the GO **112** may be generated by the second server apparatus **16**. Alternatively, part of the information of the GO **112**, such as the SSID and the FSID information items, may be generated by the second server apparatus **16** or the first server apparatus **14**, and other information, such as the GO address information item, may be generated by the computing apparatus **10**. The verification information item or items may be generated by the second server apparatus **16**, in which case a copy the verification item or items is passed to, and stored in the memory **142** of, the first server apparatus **14**. Alternatively, the verification item or items may be generated by the first server apparatus **14** and passed to the computing apparatus **10** via the second server apparatus **16**.

[0044] According to some embodiments, the GO **112** may be displayed by computer program code embedded within the web page. Alternatively, the GO **112** may be displayed by computer program code stored on the computing apparatus **10**, for example, during a registration process. The computer program code that is stored on the computer apparatus **10**, and which generates the GO **112**, may, when executed by the controller **100**, be in direct communication with the second server apparatus **16**. The computer program code may be configured such that the GO **112** is only displayed if direct communication with the second server apparatus **16** can be established. If direct communication is not possible, the GO **112** is not displayed and so cannot be used to access the service. The computer program may determine if it is in direct communication in any suitable way. For example, the IP address of the second server apparatus may be encoded into the computer program and this may be used to determine if communication is with the second server apparatus **16**. If a proxy server is between the second server apparatus **16** and the computer apparatus **10**, the computer program will recognise that the IP address of the server with which it is communicating (i.e. that of the proxy server) is not the IP address which it expects. The computer program thus determines that it is not in communication with the second server apparatus **16** and does not display the GO **112**. Alternatively, the computer program may send request to the second server apparatus for a token, which should be stored in memory of the second server apparatus **16**. A proxy server will not have the token in memory and so will not be able to return it to the computer apparatus **10**.

In this way, the computer apparatus **10** can determine that it is not in direct communication with the second server apparatus **16**. Similarly, the computer program may send a request for evidence of a process that is expected to be running on the second server apparatus **16**. If the process is not running on the computer at which the request arrives, the computer program determines that it is not in communication with the second server apparatus **16**. It will be appreciated that any suitable mechanism, including for example PKI, SSL or DNS pooling, may be used to make this determination.

[0045] In step S2-3, the GO **112** is obtained by the mobile device **12**. This may involve the user of the device **12** taking a photograph of the GO **112** with a camera of the device **12**. Alternatively, any other type of scanner may be used to obtain the GO **112**.

[0046] In step S2-4, an application decodes the encoded information from the obtained GO **112**. The application is a dedicated portion of the computer-readable code **122A** stored in the memory **122** of the device, which is able to decode the GO **112** and perform subsequent operations.

[0047] The application may have been stored on the mobile device **12** prior to, during or following a registration process between the mobile device **12** and the first server apparatus **14**. Either way, the user of the device **12** must register with the first server apparatus **14** to allow the user to utilise the service provided by the first server apparatus **14**.

[0048] During the registration process, the first server apparatus **14** may store in its memory **142** a user identification (UID) information item relating to the user. This may comprise, for example, a username or user number. Alternatively, the first server apparatus **14** may store device identification (DID) information item relating to the mobile device **12**. This DID information item may comprise, for example, a telephone number of the device, an IP address of the device or a device ID code such as a serial number. The DID or the UID information item is stored in association with user registration information, such as a name, address etc. Thus, the DID and the UID information items are usable to allow identification of the user by the first server apparatus **14**. A copy of the DID or UID information item is stored in the memory **122** of the mobile device **12**.

[0049] In step S2-5, subsequent to decoding the obtained GO **112**, the application prepares and transmits a first message (in this example, a login request) **314** to the first server apparatus **14**.

[0050] The first message **214** is sent to the first server apparatus **14** using an address of the first server apparatus **14**. The application may be configured to interoperate with just one first server apparatus **14** and thus whenever a GO **112** is obtained, the first message **214** is sent to the same first server apparatus **14** using an address stored in the memory **122**. Alternatively, in embodiments in which the GO **112** includes an FSID information item, this may be used to send the first message **214** (either directly, when the FSID information item comprises an address of the first server information item, or indirectly by using the FSID information item to retrieve the address from memory **122**). In other alternative embodiments, the first message **214** may be sent to an address selected by the user from a plurality of addresses stored on the device **12**.

[0051] The first message **214** comprises a first information portion comprising the DID information or the UID information. The first message **214** also comprises a second information portion comprising the GO address information item. The first message **214** may also comprise the SSID information item.

[0052] In embodiments in which a verification information item is present in the GO **112**, the application may, prior to preparing and sending the first message **214**, check the verification information item against a reference information item received from the first server apparatus **14** to determine whether the GO **112** is genuine. If the GO **112** is determined not to be genuine, the application alerts the user of the device **12**. If the GO **112** is determined to be genuine, the application prepares and transmits the first message **214** to the server apparatus **14**. The reference information against which the verification object is checked may be updated periodically, following receipt of update messages from the first server apparatus **14**. According to alternative embodiments, the application may not check the verification information item, but may instead

include it in the first message **214**.

[0053] Prior to preparing and sending the first message, the application may request security information to be entered by the user via the user interface **124** of the device **12** thereby to allow the identity of the user to be verified. The security information may comprise a pin or password, a disguised pin or password, a one-time code which has been sent to the user, a pattern drawn on the device, biometric information (such as face or fingerprint recognition), or any other suitable mechanism by which the identity of the user of the device can be verified.

[0054] Next, in step **S2-6**, the first server apparatus **14** receives the first message **214** (login request) and uses the UID or DID information to establish the identity of the user of the device **12**. Establishing the identity of the user comprises using the UID or DID information item to determine whether the user is registered with the first server apparatus **14**. Thus, the first server apparatus **14** may check the UID or DID information against information stored in a database of registered users to establish the identity of the user. Subsequent to establishing the identity of the user, the first server apparatus proceeds to step **S2-7**.

[0055] In embodiments in which the first message **214** includes the verification information item, the first server apparatus **14** may, prior to either of steps **S2-6** and **S2-7**, check the verification information item against a reference information item stored in memory **142**. If there is identity between the reference information item and the verification item, the first server apparatus **14** proceeds to step **S2-6** or **S2-7** as appropriate. If there is not identity, the first server may send a message to the mobile device **12** to alert the user that the GO **112** is not genuine and may subsequently abort the method.

[0056] In step **S2-7**, the first server apparatus **14** prepares and sends a second message **216** to the second server apparatus **16**. In this example, the second message **216** comprises authorisation information informing the second server apparatus **16** of the identity of the user and that the user is authorised to access the service provided by the second server apparatus **16**. The second message **216** also comprises the GO address information item.

[0057] The second message **216** is sent on the basis of the SSID information item, either directly when the SSID information item is an address of the second server apparatus **16**, or indirectly when the SSID information item enables the first server apparatus to retrieve the address of the second server apparatus **14** from memory **142**.

[0058] In step **S2-8**, upon receipt of the second message **216** the second server apparatus **16** performs an action. In this example, the second server apparatus **16** is a web server and thus in response to receiving the authorisation information, the second server apparatus **16** logs the user into their account and subsequently uses the GO address information item to send a signal indicative of such to the computing apparatus **10**.

[0059] In step **S2-9**, the computing apparatus **10** displays the received information which indicates that the user is now logged into the website.

[0060] According to some embodiments, step **S2-6**, in which the first server apparatus **14** establishes the identity of the user may include additional steps for verifying the identity of the user. In embodiments in which the mobile device **12** is a mobile telephone, these steps may include the first server apparatus **14** responding to receipt of the first message **214** by initiating a voice call with the mobile device **12**. During the voice call, the user is asked to provide information with which their identity can be verified. The information may comprise, for example, a pin number sent via DTMF, or a spoken password or any other information which allows the identity of the user to be established and verified. The information from the user may be compared with information stored in the memory **142** of the first server apparatus **14** and which is associated with the user. The voice call may be conducted using IVR, a human agent, or a combination of the two. In embodiments in which the mobile device **12** does not have telephony capabilities, the steps may be conducted using messages, such as instant messages, sent using internet protocol.

[0061] FIG. **3** depicts an alternate system in which the invention can be implemented and illustrates

a method according to the invention.

[0062] The example of FIG. 3 is similar to that of FIGS. 1 and 2, but differs in that it does not include the second server apparatus 16. Thus, the system comprises the computing apparatus 10, the mobile device 12 and the first server apparatus 14.

[0063] In the system 3 of FIG. 3, the first server apparatus 14 is a web server and thus is operable to provide web page information to the computing apparatus 10 to display for consumption by the user.

[0064] A method according to the invention will now be described with reference to FIG. 3.

[0065] In step S3-1, the first server apparatus 14 provides the computing apparatus 10 with web page information. The provision of the web page information may be in response to a request received from the computing apparatus 10 following receipt at the computing apparatus 10 of a user input.

[0066] In step S3-2, the computing apparatus 10 receives and displays the web page information. In this example, the web page information comprises a "Login" page 110. The "Login" page 110 is as described with reference to FIG. 2 and comprises the encoded information item 312, which is in this example is a graphical object (GO), in particular a "quick response" (QR) code.

[0067] The GO 312 comprises a GO address information item. The GO address information item comprises an address of the computer apparatus 10 on or by which the GO 312 is displayed. The GO address information item may comprise a code, for example a numeric code or an alpha-numeric code, which identifies a route or a number of routes to the computer apparatus 10.

Examples of such codes are an IP address, a telephone number, a domain name and a Blackberry® PIN.

[0068] According to other embodiments, the GO address information item may not comprise address information per se, but may instead comprise information which allows the address of the apparatus on or by which the GO 312 is displayed to be determined. This may include for example a code or number, such as but not limited to a hardware serial number, which can be used to determine the route to the computing apparatus (e.g. the IP address) from a look-up table.

[0069] The GO 312 may also comprise a first server identification (FSID) information item allowing the mobile device to identify the first server apparatus 14 with which the GO 312 is associated. The FSID information item may comprise an address of the first server apparatus 14 or may instead comprise a data item which allows the application stored on the mobile device 12 to retrieve the address of the first server apparatus 14 from memory 122.

[0070] The GO 312 may also comprise a verification information item for allowing verification of the graphical object to ensure it is not a fraud.

[0071] The information required to display the GO 312 may be generated entirely by the first server apparatus 14. Alternatively, part of the information of the GO 312, such as the SSID and the FSID information items, may be generated by the first server apparatus 14, and other information, such as the GO address information item, may be generated by the computing apparatus 10. The verification information item or items are generated by the first server apparatus 14 and a copy of the verification item or items is retained in the memory 142 of the first server apparatus 14.

[0072] According to some embodiments, the GO 312 may be displayed by computer program code embedded within the web page. Alternatively, the GO 312 may be displayed by computer program code stored on the computing apparatus 10, for example, during a registration process. The computer program code that is stored on the computer apparatus 10, and which generates the GO 312, may, when executed by the controller 20, be in direct communication with the first server apparatus 14. The computer program code may be configured such that the GO 312 is only displayed if the direct communication with the first server apparatus 14 can be established. This may be determined in any suitable way, for example as described with reference to FIG. 2 in respect of the second server apparatus 16.

[0073] In step S3-3, the GO 312 is obtained by the mobile device 12. This may involve the user of

the device **12** taking a photograph of the GO **312** with a camera of the device **12**. Alternatively, any other type of scanner may be used to obtain the GO **312**.

[0074] In step **S3-4**, an application decodes the encoded information from the obtained GO **312**.

The application is a dedicated portion of the computer-readable code **122A** stored in the memory **122**, which is able to decode the GO **312** and perform subsequent operations.

[0075] The application may have been stored on the mobile device **12** prior to, during or following a registration process between the mobile device **12** and the first server apparatus **14**. Either way, the user of the device **12** must register with the first server apparatus **14** to allow the user to utilise the service provided by the first server apparatus **14**. Registration with the first server apparatus is as described with reference to FIG. 2.

[0076] In step **S3-5**, subsequent to decoding the obtained GO **312**, the application prepares and transmits a first message **314** to the first server apparatus **14**.

[0077] The first message **314** is sent to the first server apparatus **14** using an address of the first server apparatus **14**. The application may be configured to interoperate with just one first server apparatus **14** and thus whenever a GO **312** is obtained, the first message **314** is sent to the same first server apparatus **14** using an address stored in the memory **122**. Alternatively, in embodiments in which the GO **312** includes an FSID information item, this may be used to send the first message **314** (either directly, when the FSID information item comprises an address of the first server information item, or indirectly by using the FSID information item to retrieve the address from memory **122**). In other alternative embodiments, the first message may be sent to an address selected by the user from a plurality of addresses stored on the device **12**.

[0078] The first message **314** comprises a first information portion comprising the DID information item or the UID information item. The first message **314** also comprises a second information portion comprising the GO address information item.

[0079] The first message may also comprise a verification information item. Alternatively, the application may, prior to preparing and sending the first message **314**, check the verification information item against a reference information item received from the first server apparatus **14** to determine whether the GO **312** is genuine. If the GO **312** is determined not to be genuine, the application alerts the user of the device **12**. If the GO **312** is determined to be genuine, the application prepares and transmits the first message **314** to the server apparatus **14**.

[0080] Prior to preparing and sending the first message **314**, the application may request security information to be provided by the user via the user interface **124** of the device **12**, thereby to allow the identity of the user to be verified. The security information may comprise a pin or password, a disguised pin or password, a one-time code which has been sent to the user, a pattern drawn on the device, biometric information (such as face or fingerprint recognition), or any other suitable mechanism by which the identity of the user of the device can be verified.

[0081] Next, in step **S3-6**, the first server apparatus **14** receives the first message **314** and uses the UID or DID information item to establish the identity of the user of the device **12**. Establishing the identity of the user comprises using UID or DID information item to determine whether the user is registered with the first server apparatus **14**. Thus, the first server apparatus **14** may check the UID or DID information against information stored in a database of registered users to establish the identity of the user. Subsequent to establishing the identity of the user, the first server apparatus proceeds to step **S3-7**.

[0082] In embodiments in which the first message **314** includes the verification information item, the first server apparatus **14** may, prior to either of steps **S3-6** and **S3-7**, check the verification information item against a reference information item stored in memory **142**. If there is identity between the reference information item and the verification item, the first server apparatus proceeds to step **S3-6** or **S3-7** as appropriate. If there is not identity, the first server may send a message to the mobile device **12** to alert the user that the GO **312** is not genuine and may abort the method.

[0083] In step S3-7, the first server apparatus **14**, subsequent to establishing the identity of the user, performs an action. In this example, as the first server apparatus **14** is a web server, the first server apparatus **14** logs the user into their account. The first server apparatus **14** uses the GO address information item to send a signal indicative of such to the computing apparatus. In this example, the GO address information comprises the IP address of the computing apparatus **10** and so the first server apparatus **16** transmits information indicative of the user having been logged into their account to the computing apparatus **10**.

[0084] In step S3-9, the computing apparatus **10** displays the received information which indicates that the user is now logged into the web page.

[0085] According to some embodiments, step S3-6 in which the first server apparatus **14** establishes the identity of the user may include additional steps to verify the identity of the user. These steps may be those as described above with reference to step S2-6 of FIG. 2.

[0086] In the embodiments of FIGS. 2 and 3, the GO **112, 312** is displayed in conjunction with the fields into which a username and password can be entered. However, it will be appreciated that the GO **112, 312** alternatively may be displayed instead of the username and password fields. Also, although in the embodiments described with reference to FIGS. 2 and 3, the GO **112, 312** is used instead of a username and password to log the user into the web page, it will be understood the GO **112, 312** could be used in conjunction with a conventional login procedure using the username and password fields. This adds an extra layer of security both for the web server and the user.

[0087] It will be understood that the invention may be implemented within systems other than those described above. Such implementations are described in brief below. Although these are described briefly, it will be understood that the operations may be substantially the same as those described above and may include some or all of the same steps and features.

[0088] According to one alternative embodiment, the invention can be implemented in a building security system. In such an embodiment, the computing apparatus **10** may comprise an electronic door lock. The encoded information item **112, 312**, such as a GO as described above, may be displayed on a sign geographically proximate to the electronic door lock. Alternatively, the GO **112, 312** may be provided on an electronic display geographically proximate to the electronic door lock. In such embodiments, the encoded information item may be periodically updated following receipt of signals from the first server apparatus **14** (or from the second server apparatus **16** if the system is as shown in FIG. 2). The GO **112, 312** includes a GO address information allowing the electronic door lock to be identified. The encoded information item **112, 312** may also include an FSID information item as described above. Upon approaching the door, a user uses their mobile device **12** to obtain and decode the encoded information item **112, 312**. Subsequently, optionally following the successful provision of security information by the user to the mobile device, a first message **214, 314** (including the GO address information object and the UID or DID information item) is sent to the first server apparatus **14**. In this example, the first message **214, 314** comprises an “entry request”. In response to receiving the entry request **214, 314**, the first server apparatus **14** establishes the identity of the user using the UID or DID information item. Next, if the system does not comprise the second server apparatus, the first server apparatus **14** transmits a signal to the electronic door lock (using the GO address information item) authorising the electronic door lock to open and thereby to allow the user to pass through the door. Alternatively, if the system does comprise the second server apparatus **16**, the first server apparatus **14** transmits the second message **216** (including authorisation information indicating that the user is authorised to enter the door) to the second server apparatus **16** which responds by transmitting a signal to the electronic door lock (using the GO address information item), authorising the electronic door lock to open.

[0089] According to another alternative embodiment, the invention may be implemented so as to enable a shopper to pay for their goods at a checkout device. In this embodiment, the computing apparatus **10** is a checkout device. Once the goods to be purchased have been scanned through the checkout device, the checkout device **10** produces and displays an encoded information item **112**,

312, in this example a GO. The GO **112, 312** comprises a GO address information item (as described above) which allows the checkout device to be identified, and a total price that is to be paid. The GO may also comprise an information item identifying (or allowing identification by the application of) a banking establishment to which the monies are to be paid. Optionally, following provision by the user of security information to the mobile device **12**, the application of the mobile device **12** transmits the first message **214, 314** (a payment request) to the first server apparatus **14**. The payment request **214, 312** includes the GO address information item, the UID or DID information item (as described previously), the price information and the information item identifying the payee banking establishment. The identity of the user is established by the first server apparatus **14** using the UID or DID information item. In response to establishing the identity of the user, the first server apparatus **14**, which, for example, may be associated with a banking establishment, authorises payment from the user's account to the payee banking establishment of an amount identified by the price information. Next, if the system does not comprise the second server apparatus, the first server apparatus **14** transmits (using the GO address information item) a signal to the checkout device indicating that the balance has been paid. Alternatively, if the system does comprise the second server apparatus **16**, the first server apparatus **14** transmits the second message **216** (indicating that the user is authorised to make this payment) to the second server apparatus **16** (which may be associated with payee banking establishment) which responds by transmitting the signal to the checkout device (using the GO address information item) indicating that the balance has been paid.

[0090] According to another alternative embodiment, the invention may be implemented within an ATM system. In this embodiment, the computing apparatus **10** is an ATM. The user requests withdrawal of an amount of money from the ATM. In response to this the ATM produces and displays an encoded information item **112, 312**, in this example a GO. The GO **112, 312** comprises a GO address information item to allow the ATM to be identified and information indicating the withdrawal amount. The GO **112** may also comprise a SSID information item. Following provision of security information, such as a pin etc., to the mobile device **12** by the user, the application of the mobile device **12** transmits the first message **214** (a withdrawal request) to the first server apparatus **14**. The withdrawal request **214** includes the GO address information item, the UID or DID information item identifying the device or the user, the withdrawal amount information and if applicable the SSID information item. The identity of the user is established by the first server apparatus **14** using the UID or DID information item, and in response to establishing the identity of the user, the first server apparatus **14**, which in this example is associated with the a banking establishment, authorises the withdrawal and debits the user's account by the amount indicated by the withdrawal amount information. Next, if the system does not comprise the second server apparatus **16**, the first server apparatus **14** transmits (using the GO address information item) a signal to the ATM authorising the ATM to dispense the requested amount. Alternatively, if the system does comprise the second server apparatus **16**, the first server apparatus **14** transmits (using the SSID information item) the second message **216** to the second server apparatus **16** (which may be associated with a banking establishment that owns the ATM, if this is not the same as the user's banking establishment) which responds transmits the signal (using the GO address information item) to the ATM authorising the ATM to dispense the requested amount.

[0091] According to another alternative embodiment, the invention can be implemented in a self-service shopping environment. In such an embodiment, an encoded information item **112**, in this example a GO, may be provided on a smart tag of a product for sale. The user obtains the GO **112** using their mobile device **14**. In this embodiment, the GO **112, 312** contains the GO address information item for allowing the smart tag to be identified (as described above) and a price of the product. The GO **112, 312** may also comprise an information item identifying (or allowing identification by the application of) a banking establishment to which the monies are to be paid. Optionally following provision by the user of security information to the mobile device **12**, the

application of the mobile device transmits the first message **214** (a purchase request) which includes the GO address information item, the UID or DID information item and the price information to the first server apparatus. The identity of the user is then established by the first server apparatus **14** using the UID or DID and in response to establishing the identity of the user, the first server apparatus **14** authorises payment for an amount identified by the price information. Next, the first server apparatus **14** transmits the second message **216** to the second server apparatus **16**, which may be an in-store security system. The second message **216** comprises the GO address information item and authorisation information indicating that the product has been paid for. In response to receiving the second message **216**, the second server apparatus uses the GO address information item to transmit a signal to the smart tag thereby to disable it, such that an alarm is not activated when the user attempts to leave the shop).

[0092] Although in the above embodiments the encoded information item **112**, **312** has been described as a graphical object, it will be understood that this may instead be a different type of encoded information item. These may include, for example, an encoded audible information item, which may be emitted by the computing apparatus **10** and recorded and decoded by the mobile device **12**. Other types of encoded information item include encoded radio frequency (RF) information items.

[0093] In some embodiments, the encoded information item **112**, **312** may comprise a sequence of numbers, letters or symbols. In such embodiments, the device **12** may obtain the encoded information item as a result of the user manually typing the sequence into the device using the user interface **126**. In other alternative embodiments, the encoded information item may be obtained via a wired connection between the device **12** and the computing apparatus **10**.

[0094] In some embodiments, the encoded information item **112**, **312** may be changed periodically, for example, by updating the verification item. In such embodiments, when the verification item is not created by the same entity that is responsible for checking it, the verification item is transmitted to the checking entity each time it is updated.

[0095] In the embodiments described above, the encoded information object **312**, **112** is decoded by the device prior to sending the first message **214** to the first server apparatus **14**. However, in alternative embodiments the encoded information item **112**, **312** may be transmitted in the first message **214** for decoding by the first server apparatus **14**. In such embodiments, the device **12** has pre-stored the address of the first server apparatus. The application may be configured to send the first message **214** to that address when each time encoded information item **112**, **312** is obtained. Alternatively, the user may select the address to which the first message **214** is to be sent from a plurality of addresses stored in the device **12**. In these embodiments in which the first message includes the encoded information item, it will be appreciated that, where the encoded information item includes a verification item, this will be verified by the first server apparatus **14** and not by the device **12**.

[0096] In FIGS. **2** and **3**, the mobile device **12** is depicted as a mobile telephone. However, it will be appreciated that it may be any other type of device comprising obtaining means **124** for obtaining an encoded information item in one or more of the aforementioned manners. The obtaining means **124** may comprise, for example, a physical interface for receiving from the computing apparatus **10** an encoded information item in the form of a computer-readable electrical signal, an RF transceiver for receiving an RF encoded information item as an RF signal, or an audio receiver for obtaining audible encoded data items.

[0097] The mobile device **12** is depicted in FIG. **1** as a single unit. However, it will be appreciated that it may instead comprise plural separate units, for example a webcam and a laptop computer.

[0098] The invention provides a new and inventive way of providing secure access to services. The provision of the encoded information item reduces the possibility of a so-called “man-in-the-middle attack”. The invention is particularly effective in this respect in embodiments in which the computer program code for generating the encoded information item is stored on the computer

apparatus **10** and is configured such that the encoded information item is only provided (i.e. displayed, emitted, output etc.) when direct communication with an application running on the web server **14; 16** is established. This is because, if a proxy server is placed between the computer apparatus **10** and the web server **14; 16** for intercepting communications between the two, direct communication between the computer program code running on the computer apparatus **10** and the application running on the web server can not be established and so the encoded information item will not be provided. Thus, the user is unable access the service and so cannot divulge sensitive information to the fraudster operating the proxy server.

[0099] The use of a verification item by which the first server apparatus can verify the encoded data item, which may be changed periodically, reduces the chance of fraudsters being able to clone the encoded information item and thereby to clone service in order to elicit information illegally from a user. Moreover, the use of a mechanism according to the invention reduces the amount of personal information (such as usernames and passwords) that is required to be entered to the computing apparatus **10**, the security of which may be compromised through the presence of viruses and the like.

[0100] The invention also allows for an expedited the log-in process as the user may not need to spend time entering password and username information. Similarly, the invention may remove the need for users to remember many passwords to many different services etc.

[0101] In some embodiments of the invention, in which the encoded information item need to be obtained and a password needs to be entered, an additional layer of security is introduced and so the system is safer for the users.

[0102] The invention also allows for tiered strengths of authentication to be applied based on risk, transaction value and/or user profile. For example for some websites simply being in possession of the mobile device **12** and obtaining the encoded data item may be sufficient to allow the user to access the services provided by the website. For other implementations such as payment and banking implementations, a more comprehensive collection of authenticating factors (for example, possession of the device and knowledge of a password) may be employed. If the device **12** is lost or stolen, the network provider (if the device is a mobile telephone) may disable the device, thereby preventing the thief or finder of the device being able to use the device and the application stored thereon to access the user's websites and services to which they are subscribed etc. Alternatively, the user may contact the owner or maintainer of the first service apparatus to instruct them to ensure that any requests from the lost or stolen device be denied. A new device subsequently can be associated with the user's registration at the first server apparatus **14**.

[0103] In some embodiments of the invention, it may only be permitted for the user to register their device with the first server **14** if they have a monthly contract with a mobile telephone network provider. Such contracts (as opposed to so-called "pay-as-you-go" tariffs) involve a stringent identification process, including the user providing proof of address and bank details etc. Therefore, for services for which security is important, such as banking and the like, it may only be possible to register to log in by way of the encoded information item if the user has a pay monthly contract and so their identity is known with more certainty.

[0104] Security advantages are achieved by using a separate device (i.e. the mobile device **12** and not the computer apparatus **10** with which the service is being accessed) to communicate with the server apparatus **14** which is configured to establish the identity of the user (see steps **S2-6** and **S3-6** of FIGS. **2** and **3** respectively). By taking the authentication process "out-of-band" in this way, the complexity of the system is increased. It is significantly more difficult and costly for a fraudster to detect, intercept or compromise the multiple communication channels (bands) and/or server apparatuses involved. Thus, the system is more secure.

[0105] It should be realised that the foregoing embodiments are not limiting. Other variations and modifications will be apparent to persons skilled in the art upon reading the present application. Moreover, the disclosure of the present application should be understood to include any novel

features or any novel combination of features either explicitly or implicitly disclosed herein or any generalisation thereof and during the prosecution of the present application or of any application derived therefrom, new claims may be formulated to cover any such features and/or combination of such features.

Claims

1-15. (canceled)

16. A method comprising: a portable device: obtaining a graphical encoded information item which is displayed on a display of a computing apparatus; decoding the encoded information from the encoded information item; and transmitting a first message to first server apparatus, the first message including the decoded information and a first identifier identifying the device or a user of the device, wherein the decoded information includes an apparatus identification information item for allowing identification of the computing apparatus; and the first server apparatus: receiving the first message from the device; establishing the identity of the user of the device, wherein establishing the identity of the user comprises using the first identifier to determine if the user is registered with the first server apparatus; in response to establishing the identity of the user, authorising the user to access a service; and providing the service to the user via the computing apparatus using the apparatus identification information item; or sending a second message to a second server apparatus, the second message including the apparatus identification information item and indicating that the user is authorised to access the service provided by the second server apparatus, the second server apparatus responding to receipt of the second message by providing the service to the user via the computing apparatus using the apparatus identification information item.

17. A method comprising: a portable device: obtaining a graphical encoded information item which is displayed on a display of a computing apparatus; and transmitting a first message to first server apparatus, the first message including the encoded information item and a first identifier identifying the device or a user of the device; and the first server apparatus: receiving the first message from the device; decoding the encoded information from the encoded information item, wherein the decoded information includes an apparatus identification information item for allowing identification of the computing apparatus; establishing the identity of the user of the device, wherein establishing the identity of the user comprises using the first identifier to determine if the user is registered with the first server apparatus; in response to establishing the identity of the user, authorising the user to access a service; and providing the service to the user via the computing apparatus using the apparatus identification information item; or sending a second message to a second server apparatus, the second message including the apparatus identification information item and indicating that the user is authorised to access the service provided by the second server apparatus, the second server apparatus responding to receipt of the second message by providing the service to the user via the computing apparatus using the apparatus identification information item.

18. The method of claim 16, wherein the decoded information comprises a verification information item, the method further comprising the first server apparatus: comparing the verification information item with a reference verification item; if there is identity between the verification information item and the reference verification item, providing the service to the user via the computing apparatus using the apparatus identification information item; and if there is not identity between the verification information item and the reference verification item aborting the method prior to providing the service to the user via the computing apparatus using the apparatus identification information item.

19. The method of claim 16, comprising sending the second message to the second server apparatus, wherein the encoded information comprises a second identifier, the second identifier

identifying second server apparatus.

20. The method of claim 16, when dependent on claim 1, wherein the encoded information comprises a third identifier, the third identifier identifying the first server apparatus, and wherein the first message is transmitted to the first server apparatus based on the third identifier.

21. The method of claim 16, comprising: the portable device: prior to transmitting the first message, receiving a user input; comparing the received user input to a stored reference input; and transmitting the first message, when it is determined that there is identity between the received user input and the stored reference user input.

22. The method of claim 16, wherein establishing the identity of the user of the device comprises: initiating a communication channel with the device based on the first identifier; receiving user-provided information from the device via the communication channel; comparing the received user-provided information with stored reference user-provided information; and verifying, and thereby establishing, the identity of the user when it is determined that there is identity between the received user-provided information and the reference user-provided information.

23. The method of claim 17, wherein the decoded information comprises a verification information item, the method further comprising the first server apparatus: comparing the verification information item with a reference verification item; if there is identity between the verification information item and the reference verification item, providing the service to the user via the computing apparatus using the apparatus identification information item; and if there is not identity between the verification information item and the reference verification item aborting the method prior to providing the service to the user via the computing apparatus using the apparatus identification information item.

24. The method of claim 17, comprising sending the second message to the second server apparatus, wherein the encoded information comprises a second identifier, the second identifier identifying second server apparatus.

25. The method of claim 17, when dependent on claim 1, wherein the encoded information comprises a third identifier, the third identifier identifying the first server apparatus, and wherein the first message is transmitted to the first server apparatus based on the third identifier.

26. The method of claim 17, comprising: the portable device: prior to transmitting the first message, receiving a user input; comparing the received user input to a stored reference input; and transmitting the first message, when it is determined that there is identity between the received user input and the stored reference user input.

27. The method of claim 17, wherein establishing the identity of the user of the device comprises: initiating a communication channel with the device based on the first identifier; receiving user-provided information from the device via the communication channel; comparing the received user-provided information with stored reference user-provided information; and verifying, and thereby establishing, the identity of the user when it is determined that there is identity between the received user-provided information and the reference user-provided information.

28. A system comprising: a portable device configured: to obtain a graphical encoded information item which is displayed on a display of a computing apparatus; to decode the encoded information from the encoded information item; and to transmit a first message to first server apparatus, the first message including the decoded information and a first identifier identifying the device or a user of the device, wherein the decoded information includes an apparatus identification information item for allowing identification of the computing apparatus; and first server apparatus configured: to receive the first message from the device; to establish the identity of the user of the device, wherein establishing the identity of the user comprises using the first identifier to determine if the user is registered with the first server apparatus; and in response to establishing the identity of the user, to authorise the user to access a service; and to provide the service to the user via the computing apparatus using the apparatus identification information item; or to send a second message to a second server apparatus, the second message including the apparatus identification

information item and indicating that the user is authorised to access the service provided by the second server apparatus, wherein the system further comprises the second server apparatus which is configured to respond to the receipt of the second message by providing the service to the user via the computing apparatus using the apparatus identification information item.

29. The system of claim 28, wherein the decoded information comprises a verification information item, the first server apparatus being configured: to compare the verification information item with a reference verification item; if there is identity between the verification information item and the reference verification item, to provide the service to the user via the computing apparatus using the apparatus identification information item; and if there is not identity between the verification information item and the reference verification item, to abort the method prior to providing the service to the user via the computing apparatus using the apparatus identification information item.

30. The system of claim 28, wherein the first server apparatus is configured to send the second message to the second server and wherein the encoded information comprises a second identifier, the second identifier identifying second server apparatus.

31. The system of claim 28, wherein the encoded information comprises a third identifier, the third identifier identifying the first server apparatus, and wherein the device is configured to transmit the first message to the first server apparatus based on the third identifier.

32. The system of claim 28, wherein the device is configured: prior to transmitting the first message, to receive a user input; to compare the received user input to a stored reference input; and to transmit the first message, when it is determined that there is identity between the received user input and the stored reference user input.

33. The system of claim 28, wherein the first server apparatus being configured to establish the identity of the user of the device comprises being configured: to initiate a communication channel with the device based on the first identifier; to receive a user-provided information from the device via the communication channel; to compare the received user-provided information with stored reference user-provided information; and to verify, and thereby to establish, the identity of the user when it is determined that there is identity between the received user-provided information and the reference user-provided information.
