

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250261749

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

MENG; Fandi

ORAL CARE DEVICE

Abstract

The present disclosure provides an oral care device. The oral care device includes a handle part and a care head part; the handle part includes: a sonic motor including a motor body and a power output shaft, the power output shaft being provided with an axial channel as well as a first inlet and a first outlet communicating with the axial channel; a fluid mechanism provided with a fluid inlet and a fluid outlet, the fluid outlet communicating with the first inlet; and a housing including a machine mounting part and a water storage cavity, the machine mounting part being internally provided with a mounting rack, the mounting rack being provided with a motor compartment and a pump body compartment, the sonic motor being mounted in the motor compartment, the fluid mechanism being mounted in the pump body compartment, and a head of the machine mounting part being provided with a mounting shaft hole; and the care head part is provided with a rinsing stem and a brush head, the rinsing stem being provided with a fluid channel capable of communicating a spray nozzle with the axial channel. By using the oral care device provided by the present disclosure, the reasonable layout of a rinsing flow path can be achieved, the overall size of the oral care device can be reduced, it is convenient for a user to perform an operation, and the comfort level provided for a user during use can be improved.

Inventors: MENG; Fandi (Shenzhen, CN)

Applicant: Shenzhen Soocas Technology Co., Ltd. (Shenzhen, CN)

Family ID: 1000008586457

Assignee: Shenzhen Soocas Technology Co., Ltd. (Shenzhen, CN)

Appl. No.: 19/188003

Filed: April 24, 2025

Foreign Application Priority Data

CN

202210944150.2

Aug. 05, 2022

Related U.S. Application Data

parent US continuation-in-part 18178021 20230303 parent-grant-document US 12310809 child US 19188003

Publication Classification

Int. Cl.: A46B11/00 (20060101); A61C17/02 (20060101); A61C17/22 (20060101)

U.S. Cl.:

CPC A46B11/0006 (20130101); A61C17/0202 (20130101); A61C17/227 (20130101);

Background/Summary

CROSS REFERENCE TO RELATED APPLICATION [0001] This application is a continuation-in-part of U.S. patent application Ser. No. 18/178,021, titled “ORAL CARE DEVICE”, filed on Mar. 3, 2023, which claims priority to Chinese Patent Application No. 202210944150.2, filed on Aug. 5, 2022. The entire contents of all of the above-mentioned patent applications are hereby incorporated herein by reference.

TECHNICAL FIELD

[0002] The present disclosure relates to the technical field of oral cleaning, in particular to an oral care device.

BACKGROUND

[0003] A sonic motor assembly unit includes a motor, an eccentric driving shaft, an output shaft, the output shaft being operably connected to the motor, and a power transmission system assembly, the power transmission system assembly being connected between the eccentric driving shaft and the output shaft. A power transmission system converts rotation of the eccentric driving shaft into an oscillatory motion of the output shaft.

[0004] In the above-mentioned solution, eccentric rotation of a shaft lever on a front end of the motor is transmitted to a middle hollow shaft lever end by an eccentric mechanism, so that the shaft lever thereof vibrates. This solution has the defect that the shaft lever of the motor and a hollow shaft lever are not concentric, which causes superfluous vibration. A principle of a balance weight is applied as a principle of balance. By reasonably distributing weights, a brush head is balanced in theory, so that centrifugal forces of the brush head in the horizontal and vertical directions during work are approximately balanced.

[0005] Furthermore, there is a lack of an oral care device not only capable of achieving a toothbrushing function, but also capable of achieving a rinsing effect in the prior art. Even if there is an oral care device having toothbrushing and rinsing functions at the same time, a motor providing kinetic energy for a rinsing liquid is required to be additionally disposed in addition to a motor providing kinetic energy for toothbrushing; moreover, in order to avoid interference between the motor and a rinsing pipeline, the rinsing pipeline has to be disposed on an outer side of the motor providing kinetic energy for toothbrushing; in this way, not only is an additional implementation pipeline needed, but also an additional volume can be increased, so that the oral care device is increased in size, inconvenient to hold with a hand and operate and reduced in comfort level provided for a user during use.

SUMMARY

[0006] A main objective of the present disclosure is to provide an oral care device, by which the reasonable layout of a rinsing flow path can be achieved, the overall size of the oral care device can be reduced, it is convenient for a user to perform an operation, and the comfort level provided for a user during use can be improved.

[0007] In order to achieve the above-mentioned objective, according to a first aspect of the present disclosure, provided is an oral care device including a handle part and a care head part; wherein the handle part is configured to be suitable for hand-holding and includes: [0008] a motor including a motor body and a power output shaft, the motor body having an output axis extending in a power output direction; the power output shaft being a columnar object extending along the output axis and passing through the motor body, the power output shaft being configured to cooperate with the motor body and transmit output power from the motor body and having an axial channel parallel to the output axis as well as a first inlet and a first outlet communicating with the axial channel; [0009] a fluid mechanism provided with a fluid inlet and a fluid outlet, the fluid outlet communicating with the first inlet; and [0010] a housing extending in the axial direction of the power output shaft and forming a cylindrical structure of which the inside is hollow, the housing including a machine mounting part and a water storage cavity, the machine mounting part being internally provided with a mounting rack, the mounting rack having a motor compartment and a pump body compartment, the motor being mounted in the motor compartment, the fluid mechanism being mounted in the pump body compartment, and a head of the machine mounting part being provided with a mounting shaft hole which allows the power output shaft to penetrate through and is in an assembly fit with the power output shaft; [0011] wherein the care head part is provided with a rinsing stem parallel to the output axis and a brush head disposed on a head of the rinsing stem, the rinsing stem is mounted on the power output shaft, the brush head includes bristles and a spray nozzle, the bristles extend in a direction which forms a preset included angle with the output axis, and the rinsing stem is provided with a fluid channel capable of communicating the spray nozzle with the axial channel; [0012] in the extension direction of the output axis, the first outlet of the axial channel is capable of communicating with the fluid channel of the care head part, and during use of the oral care device, water in the water storage cavity can enter the axial channel from the first inlet of the axial channel under the action of the fluid mechanism, flow from a first end to a second end of the motor body via the axial channel, then, enter the fluid channel of the care head part from the first outlet of the axial channel and be sprayed out of the brush head of the care head part.

[0013] Further, the power output shaft has a Rockwell hardness HRC ranging from 17 to 70 and a single-sided wall thickness ranging from 0.3 mm to 1 mm.

[0014] Further, in a section perpendicular to the output axis, a ratio of a sectional area of the power output shaft to a sectional area of the axial channel ranges from 1.5 to 9, a single-sided wall thickness of the power output shaft ranges from 0.3 mm to 1 mm, and an internal diameter of the axial channel ranges from 0.5 mm to 3 mm.

[0015] Further, the handle part further includes: [0016] a front damping cushion sleeving on a front end of the motor, the front end of the motor being mounted in the machine mounting part by the front damping cushion; and [0017] a rear damping cushion sleeving on a rear end of the motor, the rear end of the motor being mounted in the motor compartment by the rear damping cushion; [0018] wherein multi-point elastic contact is formed between the periphery of the mounting rack and an inner wall of the machine mounting part.

[0019] Further, the mounting rack includes a mounting base, the mounting base is provided with the motor compartment, two opposite sides of the mounting base are respectively provided with mounting side plates facing away from each other, edges, away from the mounting base, of the mounting side plates are provided with first elastic bosses; and through grooves passing through each of the mounting side plates in the thickness direction are formed in the mounting side plates, and connecting arms located on sides, away from the mounting base, of the through grooves

protrude in a direction away from the mounting base to form the first elastic bosses.

[0020] Further, an inner wall of the machine mounting part is provided with mounting grooves extending in a mounting direction of the mounting rack, the mounting side plates are clamped in the mounting grooves, two opposite side walls of each of the mounting side plates are provided with second elastic bosses protruding towards side walls of the mounting grooves, and multi-point elastic contact is formed between the mounting side plates and the side walls of the mounting grooves by the second elastic bosses.

[0021] Further, the front damping cushion has a damping plane, an inner wall of the machine mounting part is provided with first strip-shaped walls protruding towards the damping plane, the first strip-shaped walls are tightly pressed and fitted to the damping plane, the rear damping cushion is provided with a damping boss on a side where the damping plane is located, the inner wall of the machine mounting part is provided with second strip-shaped walls protruding towards the damping boss, and the second strip-shaped walls are tightly pressed and fitted to the damping boss.

[0022] Further, on a side opposite to the damping plane, two side edges of both the front damping cushion and the rear damping cushion are provided with supporting planes, the inner wall of the machine mounting part is provided with third strip-shaped walls protruding towards the supporting planes, and the third strip-shaped walls are tightly pressed and fitted to the supporting planes of both the front damping cushion and the rear damping cushion.

[0023] Further, the fluid mechanism includes a casing and a fluid pump located in the casing, the fluid pump is located between the fluid inlet and the fluid outlet, the fluid inlet communicates with a suction inlet of the fluid pump, and the fluid outlet communicates with a pump outlet of the fluid pump.

[0024] Further, an outlet end of the fluid mechanism is provided with a fluid delivery shaft, the fluid delivery shaft is provided with a fluid channel, the fluid channel communicates with the fluid outlet, and the fluid delivery shaft communicates with the power output shaft by a connector.

[0025] Further, the connector has a communication cavity, a first end facing the power output shaft and a second end facing the fluid mechanism, a first end of the power output shaft extends into the first end of the connector, and an end of the fluid mechanism where the fluid outlet is located extends into the second end of the connector.

[0026] Further, the communication cavity includes a first communication segment communicating with the first inlet and a second communication segment communicating with the fluid outlet, the first communication segment communicates with the second communication segment, an end part of the first communication segment is provided with a first sealing groove, an end part of the second communication segment is provided with a second sealing groove, and each of the first sealing groove and the second sealing groove is provided with a sealing element therein.

[0027] Further, the first communication segment and the second communication segment are disposed in a staggered manner, the connector is provided with an avoidance groove on one side of the first communication segment, the connector is provided with adjusting grooves on two opposite sides of the second communication segment, and the connector has the same wall thickness on both sides of each of the adjusting grooves.

[0028] Further, the care head part further includes a connecting structure configured to be capable of transmitting a driving force of the power output shaft to the rinsing stem, the connecting structure is disposed on an end, away from the brush head, of the rinsing stem and is capable of being snap-fitted with the power output shaft to limit axial movement of the power output shaft relative to the rinsing stem.

[0029] Further, the periphery of the power output shaft is provided with a clamping groove extending in the circumferential direction of the power output shaft, the connecting structure includes: [0030] a connecting support having an internal through hole parallel to the output axis, wherein the power output shaft can be inserted in the internal through hole; and [0031] a clamping

piece disposed on the connecting support, the clamping piece including two clamping arms spaced apart in the radial direction of the power output shaft, and the two clamping arms having a clamping position, in which the two clamping arms are close to each other and become snap-fitted with the clamping groove, and an unclamping position, in which the two clamping arms are away from each other and become not snap-fitted with the clamping groove.

[0032] Further, the clamping piece further includes an elastic arm for connecting the two clamping arms so that the two clamping arms can be switched from the unclamping position to the clamping position.

[0033] Further, the connecting support is provided with a mounting via groove communicating with the internal through hole, and the mounting via groove passes through the connecting support in the radial direction of the power output shaft; and inner walls on circumferential sides of the mounting via groove are in clearance fit with the clamping arms.

[0034] Further, the clamping piece further includes an elastic arm for connecting the two clamping arms, the connecting structure further includes a retaining rib connected to the connecting support, one end of the mounting via groove is provided with the retaining rib, and the elastic arm is partially located on a side, facing away from the internal through hole, of the retaining rib so that the displacement of the elastic arm is limited thereby.

[0035] Further, the connecting structure further includes a locating rib disposed on the other end of the mounting via groove, the clamping piece further includes two locating arms respectively connected to the two clamping arms, and the two locating arms are spaced apart and are located on two sides of the locating rib.

[0036] Further, the rinsing stem is provided with a mounting through hole communicating with the fluid channel, a step surface is disposed between the mounting through hole and the fluid channel, and the connecting structure is located in the mounting through hole and is constrained between the step surface and an end face of the housing.

[0037] Further, the care head part further includes a limiting groove disposed in the rinsing stem and a limiting rib disposed on the connecting support of the connecting structure, the limiting groove communicates with the mounting through hole, and the limiting rib is constrained by and cooperates with the limiting groove.

[0038] By applying the technical solutions in the present disclosure, for the oral care device, the power output shaft of the motor is disposed as the columnar object extending along the output axis and passing through the motor body and is enabled to form the axial channel parallel to the output axis; when a fluid pumped out of the fluid mechanism reaches a position where the motor is located, a pipe is not needed to be disposed outside the motor, but can be directly connected to the power output shaft of the motor, so that the fluid outlet of the fluid mechanism communicates with the axial channel of the power output shaft, and then, the fluid can be delivered by the axial channel of the power output shaft; and the structure of the motor can be more sufficiently and reasonably utilized, so that the structural layout of a rinsing flow path is more reasonable, fluid pipelines are reduced, the occupied space is saved, and the oral care device is smaller in overall size and lighter in weight; and the handle part can be made thinner so as to be more convenient to hold with a hand and be convenient for a user to operate, and thus, the comfort level provided for a user during use can be improved.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0039] The accompanying drawings of the description constituting one part of the present application are provided for further understanding of the present disclosure. Illustrative embodiments of the present disclosure and the descriptions thereof are intended to explain the

present disclosure, rather than to limit the present disclosure in any inappropriate manner. In the accompanying drawings:

[0040] FIG. 1 shows a schematic structural view of an oral care device in an embodiment of the present disclosure;

[0041] FIG. 2 shows a partial enlarged view of the oral care device in FIG. 1;

[0042] FIG. 3 shows a schematic structural view of a rinsing stem of the oral care device in FIG. 1;

[0043] FIG. 4 shows a schematic structural view of a connecting structure of the oral care device in FIG. 1;

[0044] FIG. 5 shows a schematic structural view of a connecting support of the connecting structure in FIG. 4;

[0045] FIG. 6 shows a schematic view showing an exploded structure of the connecting support and the rinsing stem of the oral care device in FIG. 1;

[0046] FIG. 7 shows a schematic structural view of a clamping piece of the connecting structure in FIG. 4;

[0047] FIG. 8 shows a schematic view showing an exploded structure of a machine of the oral care device in an embodiment of the present disclosure;

[0048] FIG. 9 shows a first axonometric view of the machine of the oral care device in an embodiment of the present disclosure;

[0049] FIG. 10 shows a second axonometric view of the machine of the oral care device in an embodiment of the present disclosure;

[0050] FIG. 11 shows a schematic view showing an internal structure of a handle of the oral care device in an embodiment of the present disclosure;

[0051] FIG. 12 shows a schematic structural view of a machine mounting part of the handle of the oral care device in an embodiment of the present disclosure;

[0052] FIG. 13 shows a schematic view showing a sectional structure of a connector of the handle of the oral care device in an embodiment of the present disclosure; and

[0053] FIG. 14 shows a schematic view showing a three-dimensional structure of the connector of the handle of the oral care device in an embodiment of the present disclosure.

[0054] FIG. 15(a) to FIG. 15(d) show arrangements of a motor, a fluid mechanism and a battery in the handle part of the oral care device in accordance with embodiments of the present disclosure.

[0055] FIG. 16(a) to FIG. 16(d) show arrangements of a motor, a fluid mechanism and a battery in the handle part of the oral care device when any two of them are arranged in the same row or in the same column, in accordance with embodiments of the present disclosure.

[0056] FIG. 17(a) to FIG. 17(c) show arrangements of a water storage cavity and the handle part.

[0057] The following reference signs are included in the above-mentioned accompanying drawings: [0058] 1, handle part; 2, care head part; 3, motor body; 4, power output shaft; 5, axial channel; 6, first inlet; 7, first outlet; 8, fluid mechanism; 9, fluid inlet; 10, fluid outlet; 11, housing; 12, machine mounting part; 13, water storage cavity; 14, mounting rack; 15, motor compartment; 16, pump body compartment; 17, rinsing stem; 18, brush head; 19, bristle; 20, spray nozzle; 21, fluid channel; 22, front damping cushion; 23, rear damping cushion; 24, mounting base; 25, mounting side plate; 26, first elastic boss; 27, through groove; 28, connecting arm; 29, mounting groove; 30, second elastic boss; 31, damping plane; 32, first strip-shaped wall; 33, damping boss; 34, second strip-shaped wall; 35, supporting plane; 36, third strip-shaped wall; 37, casing; 38, fluid pump; 39, fluid delivery shaft; 40, connector; 41, communication cavity; 42, first communication segment; 43, second communication segment; 44, first sealing groove; 45, second sealing groove; 46, sealing element; 47, avoidance groove; 48, adjusting groove; 49, connecting structure; 50, clamping groove; 51, connecting support; 52, clamping piece; 53, clamping arm; 54, elastic arm; 55, mounting via groove; 56, retaining rib; 57, locating rib; 58, locating arm; 59, mounting through hole; 60, limiting groove; 61, limiting rib; and 62, mounting shaft hole.

DETAILED DESCRIPTION

[0059] It should be noted that the embodiments in the present application and features in the embodiments may be combined with each other without conflicts. The present disclosure will be described in detail below with reference to the accompanying drawings and in conjunction with the embodiments.

[0060] With reference to FIG. 1 to FIG. 14, the present disclosure provides an oral care device, including a handle part 1 and a care head part 2; wherein the handle part 1 is configured to be suitable for hand-holding and includes: [0061] a sonic motor including a motor body 3 and a power output shaft 4, the motor body 3 having an output axis extending in a power output direction; the power output shaft 4 being a columnar object extending along the output axis and passing through the motor body 3, the power output shaft 4 being configured to cooperate with the motor body 3 and transmit output power from the motor body 3 and having an axial channel 5 parallel to the output axis as well as a first inlet 6 and a first outlet 7 communicating with the axial channel 5; [0062] a fluid mechanism 8 provided with a fluid inlet 9 and a fluid outlet 10, the fluid outlet 10 communicating with the first inlet 6; and [0063] a housing 11 extending in the axial direction of the power output shaft 4 and forming a cylindrical structure of which the inside is hollow, the housing 11 including a machine mounting part 12 and a water storage cavity 13, the machine mounting part 12 being internally provided with a mounting rack 14, the mounting rack 14 having a motor compartment 15 and a pump body compartment 16, the sonic motor being mounted in the motor compartment 15, the fluid mechanism 8 being mounted in the pump body compartment 16, and a head of the machine mounting part 12 being provided with a mounting shaft hole 62 which allows the power output shaft 4 to penetrate through and is in an assembly fit with the power output shaft 4; [0064] wherein the care head part 2 is provided with a rinsing stem 17 parallel to the output axis and a brush head 18 disposed on a head of the rinsing stem 17, the rinsing stem 17 is mounted on the power output shaft 4, the brush head 18 includes bristles 19 and a spray nozzle 20, the bristles 19 extend in a direction which forms a preset included angle with the output axis, and the rinsing stem 17 is provided with a fluid channel 21 capable of communicating the spray nozzle 20 with the axial channel 5; [0065] in the extension direction of the output axis, the first outlet 7 of the axial channel 5 is capable of communicating with the fluid channel 21 of the care head part 2, and during use of the oral care device, water in the water storage cavity 13 can enter the axial channel 5 from the first inlet 6 of the axial channel 5 under the action of the fluid mechanism 8, flow from a first end to a second end of the motor body 3 via the axial channel 5, then, enter the fluid channel 21 of the care head part 2 from the first outlet 7 of the axial channel 5 and be sprayed out of the brush head 18 of the care head part 2.

[0066] For the oral care device, the power output shaft 4 of the sonic motor is disposed as the columnar object extending along the output axis and passing through the motor body 3 and is enabled to form the axial channel 5 parallel to the output axis; when a fluid pumped out of the fluid mechanism 8 reaches a position where the sonic motor is located, a pipe is not needed to be disposed outside the sonic motor, but can be directly connected to the power output shaft 4 of the sonic motor, so that the fluid outlet of the fluid mechanism 8 communicates with the axial channel 5 of the power output shaft 4, then, the fluid can be delivered by the axial channel 5 of the power output shaft 4, and thus, the fluid flows through the inside of the power output shaft 4 inside the sonic motor; it is unnecessary to perform other variations in a structure of a product, no additional space is occupied, and the structure of the sonic motor can be more sufficiently and reasonably utilized, so that the structural layout of a rinsing flow path is more reasonable, fluid pipelines are reduced, the occupied space is saved, and the oral care device is smaller in overall size and lighter in weight; and the handle part 1 can be made thinner so as to be more convenient to hold with a hand and be convenient for a user to operate, and thus, the comfort level provided for a user during use can be improved.

[0067] The use of a sonic motor for oral care device is only an example. In one embodiment, the oral care device can employ either of the motors, such as a rotary motor or a stepping motor, etc.

The type of motor is not limited in this application.

[0068] In one embodiment, the power output shaft **4** has a Rockwell hardness HRC ranging from 17 to 70 and a single-sided wall thickness ranging from 0.3 mm to 1 mm. It is proven by practice that there are similar corresponding relationships among various hardness values of a material and between a hardness value and a strength value, the hardness value is determined by an initial plastic deformation resistance and a further plastic deformation resistance, the higher the strength of the material is, the higher the plastic deformation resistance and the hardness value are. Generally, if the material is higher in hardness, it is better in wear resistance and higher in brittleness, and therefore, in order to guarantee the hardness and toughness of the power output shaft **4** at the same time, the hardness of the power output shaft **4** has to be constrained reasonably. By setting the hardness of the power output shaft **4** within the above-mentioned range, it can be ensured that the hardness of the power output shaft **4** satisfies a power output requirement of the sonic motor, the problem that the plastic deformation of the power output shaft **4** occurs due to insufficient hardness can be effectively avoided, and meanwhile, the problem that fracture easily occurs due to overhigh brittleness caused by overhigh hardness can also be avoided, so that the power output shaft **4** can still have good hardness and toughness after the axial channel **5** is provided, the power output capacity as well as the service life and working stability of the sonic motor can be guaranteed while fluid delivery is satisfied.

[0069] A wall thickness of the power output shaft **4** is optimized within the above-mentioned hardness range, which can ensure that the wall thickness of the power output shaft **4** may be cast to be thin under the condition that the structural strength of the power output shaft **4** satisfies the requirement on the service life of the sonic motor, so that the dosage of the material is reduced, the cost of the material is reduced, the overall weight of the handle part **1** is reduced, and the overall weight of the oral care device is more suitable for a user.

[0070] The power output shaft **4** may be made by machining stainless steel which may be specifically **303** steel or **304** steel, and may also be made of other types of metallic or nonmetallic materials as long as the above-mentioned hardness requirement can be satisfied.

[0071] In one embodiment, the axial channel **5** has a circular cross section and has the diameter ranging from 2 mm to 5 mm; and the power output shaft **4** is cylindrical and has the diameter ranging from 3 mm to 6 mm. In this embodiment, the diameter of the axial channel **5** ranges from 2 mm to 5 mm, and the diameter of the power output shaft **4** ranges from 3 mm to 6 mm, which not only can ensure that the fluid in the axial channel **5** smoothly passes through the axial channel **5** to provide sufficient rinsing water for the care head part **2**, but also can avoid the problems of increment of the basically required wall thickness of the power output shaft **4** and increment of the overall diameter of the sonic motor due to the overlarge diameter of the axial channel **5** and can avoid increasing the sectional area of the handle part **1**, so that the handle part **1** is always convenient to hold with a hand.

[0072] In one embodiment, an inner wall of the axial channel **5** of the power output shaft **4** is subjected to surface treatment which may be finish drawing or polishing, so that the surface precision of the inner wall of the axial channel **5** can be improved, the flow resistance of the fluid can be lowered, the energy consumption of fluid delivery can be reduced, and the delivery efficiency of the fluid can be increased.

[0073] In one embodiment, in a section perpendicular to the output axis, a ratio of a sectional area of the power output shaft **4** to a sectional area of the axial channel **5** ranges from 1.5 to 9, a single-sided wall thickness of the power output shaft **4** ranges from 0.3 mm to 1 mm, and an internal diameter of the axial channel **5** ranges from 0.5 mm to 3 mm, so that there may be a good coordination relationship among the wall thickness of the power output shaft **4**, the internal diameter of the axial channel **5** and the overall sectional area of the power output shaft **4**, which not only can guarantee the flow resistance of the fluid in the axial channel **5**, but also can ensure that the wall thickness of the power output shaft **4** satisfies the power output requirement of the power

output shaft **4**, and can further ensure that the diameter of the power output shaft **4** cannot be overlarge, thereby avoiding the problem that the sectional area of the handle part **1** is overlarge due to excessive increment of the diameter of the sonic motor.

[0074] In one embodiment, the axial channel **5** passes through the power output shaft **4** in the axial direction of the power output shaft **4**, the first inlet **6** is located on an end, away from the care head part **2**, of the axial channel **5**, and the first outlet **7** is located on an end, close to the care head part **2**, of the axial channel **5**. In this embodiment, the axial channel **5** passes through the power output shaft **4** in the axial direction, which facilitates machining the axial channel **5** and reduces the machining difficulty of the axial channel **5** on the power output shaft **4** on one hand, and can conveniently achieve the communication and cooperation with the fluid outlet **10** of the fluid mechanism **8** and lower the cooperation difficulty on the other hand.

[0075] In one embodiment, the power output shaft **4** is of an integrally formed structure, so that the structural strength, integrality and structural consistency of the power output shaft **4** can be improved, the overall sealing performance of the power output shaft **4** can be guaranteed, meanwhile, machining processes can be reduced, and the overall structural stability can be improved.

[0076] In one embodiment, the power output shaft **4** is of a segmented structure, and segments of the power output shaft **4** are fixedly connected. Since the power output shaft **4** is of a thin-walled slender tubular structure, and a groove is required to be machined in a peripheral wall, if the power output shaft **4** is machined as a whole, the machining difficulty can be improved, and deformation is easy to occur during machining to cause a higher scrap rate; and the power output shaft **4** is designed to be segmented, i.e. the power output shaft **4** can be segmented according to functions, each segment achieves a different functional requirement, in this way, each segment of power output shaft **4** is shorter, and a slender hole required to be machined is also shorter, so that the machining difficulty can be greatly lowered, and the machining stability can also be effectively guaranteed. After the segments are machined, the segments of the power output shaft **4** can be fixedly connected together in a form of welding or bonding, thereby forming an integrated fixed structure.

[0077] In one embodiment, the power output shaft **4** includes a first shaft segment, a second shaft segment and a third shaft segment which are connected in sequence, the first shaft segment is configured to cooperate with the motor body **3**, the second shaft segment is configured to cooperate with the mounting shaft hole **62**, and the third shaft segment is configured to cooperate with the care head part **2**. In this embodiment, the power output shaft **4** is divided into three parts according to different cooperation structures, and the three parts are fixedly connected after being machined, so that machining is facilitated, and the machining efficiency is increased.

[0078] In one embodiment, the first shaft segment has a diameter ranging from 3 mm to 3.5 mm and a wall thickness ranging from 0.5 mm to 0.75 mm, the second shaft segment has a diameter ranging from 4 mm to 6 mm and a wall thickness ranging from 1 mm to 2 mm, the third shaft segment has a diameter ranging from 3.5 mm to 6 mm and a wall thickness ranging from 0.75 mm to 2 mm, the second shaft segment is provided with a sealing groove having a depth ranging from 0.1 mm to 0.3 mm, and the third shaft segment is provided with a locating clamping groove having a depth ranging from 0.3 mm to 0.5 mm.

[0079] In this embodiment, the first shaft segment is disposed in the motor body **3** and is mainly used to rotatably cooperate with the motor body **3** and delivery the fluid, the periphery of the first shaft segment is of a smooth structure and is not required to machine a groove structure, in this way, the first shaft segment can be designed according to a smaller wall thickness capable of satisfying a requirement to satisfy a requirement on cooperation with the motor body **3**, and therefore, the wall thickness of this segment is designed to be minimum; the second shaft segment is required to be in an assembly fit and sealing fit with the machine mounting part **12**, in this way, a peripheral wall of the second shaft segment is required to be provided with the sealing groove, the

disposing of the sealing groove may affect the structural strength of the second shaft segment, and therefore, when the second shaft segment is structurally designed, influences from the sealing groove have to be taken into account at the same time during the design of the wall thickness, the wall thickness required to be designed is required to increase depth influences of the sealing groove while satisfying a requirement on the minimum wall thickness to ensure that the disposing of the sealing groove cannot cause a situation that the second shaft segment cannot satisfy the requirement on the structural design of the power output shaft **4**, and therefore, the diameter and wall thickness of the second shaft segment are greater than those of the first shaft segment; the third shaft segment is required to satisfy a requirement on an assembly fit with the care head part **2** and provide a spring clamping position for the care head part **2**, and therefore, the locating clamping groove is required to be machined in the third shaft segment; and when the third shaft segment is designed, structural influences of the design of the locating clamping groove on the third shaft segment are also required to be taken into account, and therefore, the diameter of the third shaft segment is also required to be greater than the diameter of the first shaft segment. The diameters of the second shaft segment and the third shaft segment can be the same or different as long as the strength required by respective structure design can be satisfied.

[0080] In one embodiment, the oral care device further includes the fluid mechanism **8** and a battery; the fluid mechanism **8** includes the fluid inlet **9** capable of delivering an incoming flow into the fluid mechanism **8** and the fluid outlet **10** capable of delivering the incoming flow into the first inlet **6** of the axial channel **5** and further includes a power apparatus capable of providing a driving action force for the flow of the fluid; and the battery can provide energy for the power apparatus and the sonic motor and is disposed on an end, away from the sonic motor, of the fluid mechanism **8**, and the sonic motor, the fluid mechanism **8** and the battery are disposed in sequence in a direction parallel to the output axis.

[0081] The motor, the fluid mechanism and the battery are arranged along a direction of the output axis extending in the power output direction.

[0082] In one embodiment, the motor is located between the fluid mechanism and the battery, or the battery is located between the motor and fluid mechanism, or the fluid mechanism is located between the motor and the battery.

[0083] Referring to FIG. **15(a)** to FIG. **15(d)**, a motor, a fluid mechanism and a battery are vertically arranged. Wherein, the central axes of the motor, the central axes of the fluid mechanism and the central axes of the battery are drawn with dashed lines. The central axes of the motor, the central axes of the fluid mechanism and the central axes of the battery may be collinear or non-collinear.

[0084] As shown in FIG. **15(a)**, a motor, a fluid mechanism and a battery are vertically arranged from the upper end of the handle part to the lower end of the handle part. In other words, the distance between the motor and one end of the handle part that used to assemble the care head part, is shorter than the distance between the battery and the end of the handle part that used to assemble the care head part. And, the central axes of the motor, the central axes of the fluid mechanism and the central axes of the battery are collinear.

[0085] As shown in FIG. **15(b)**, the central axes of the motor, the central axes of the fluid mechanism and the central axes of the battery are non-collinear.

[0086] As shown in FIG. **15(c)**, a battery, a fluid mechanism and a motor are vertically arranged from the upper end of the handle part to the lower end of the handle part. In other words, the distance between the battery and one end of the handle part that used to assemble the care head part, is shorter than the distance between the motor and the end of the handle part that used to assemble the care head part. And, the central axes of the battery, the central axes of the fluid mechanism and the central axes of the motor are collinear.

[0087] As shown in FIG. **15(d)**, the central axes of the battery, the central axes of the fluid mechanism and the central axes of the motor are non-collinear.

[0088] It is worth noting that, the foregoing are merely certain preferred embodiments of the present application and are not intended to limit the present application. In the case that the motor is located between the fluid mechanism and the battery, the distance between the fluid mechanism and the end of the handle part that used to assemble the care head part, is shorter or longer than the distance between the battery and the end of the handle part that used to assemble the care head part. In the case that the battery is located between the motor and fluid mechanism, the distance between the motor and the end of the handle part that used to assemble the care head part, is shorter or longer than the distance between the fluid mechanism and the end of the handle part that used to assemble the care head part. And, the central axes of the fluid mechanism, the central axes of the motor and the central axes of the battery is collinear or non-collinear.

[0089] In one embodiment, any two of a motor, a fluid mechanism and a battery are arranged in the same row. And the distance between the said any two of the three and the end of the handle part that used to assemble the care head part, is shorter or longer than the distance between the remaining one of the three and the end of the handle part that used to assemble the care head part.

[0090] Referring to FIG. **16(a)** and FIG. **16(b)**, a motor and a fluid mechanism are arranged in the same row, the motor and a battery are arranged in different rows.

[0091] In the disclosure of FIG. **16(a)**, the distance between the motor and the end of the handle part that used to assemble the care head part, or the distance between the fluid mechanism and the end of the handle part that used to assemble the care head part, is shorter than the distance between the battery and the end of the handle part that used to assemble the care head part.

[0092] In the disclosure of FIG. **16(b)**, the distance between the motor and the end of the handle part that used to assemble the care head part, or the distance between the fluid mechanism and the end of the handle part that used to assemble the care head part, is longer than the distance between the battery and the end of the handle part that used to assemble the care head part.

[0093] It is worth noting that, in the case that a motor and a battery are arranged in the same row, the distance between the motor and the end of the handle part that used to assemble the care head part, or the distance between the battery and the end of the handle part that used to assemble the care head part, is shorter or longer than the distance between the fluid mechanism and the end of the handle part that used to assemble the care head part. In the case that a fluid mechanism and a battery are arranged in the same row, the distance between the fluid mechanism and the end of the handle part that used to assemble the care head part, or the distance between the battery and the end of the handle part that used to assemble the care head part, is shorter or longer than the distance between the motor and the end of the handle part that used to assemble the care head part.

[0094] In one embodiment, any two of a motor, a fluid mechanism and a battery are arranged in the same column.

[0095] Referring to FIG. **16(c)** and FIG. **16(d)**, a motor and a fluid mechanism are arranged in the same column, the motor and a battery are arranged in different columns.

[0096] In the disclosure of FIG. **16(c)**, the distance between the motor and the end of the handle part that used to assemble the care head part, is shorter than the distance between the fluid mechanism and the end of the handle part that used to assemble the care head part.

[0097] In the disclosure of FIG. **16(d)**, the distance between the motor and the end of the handle part that used to assemble the care head part, is longer than the distance between the fluid mechanism and the end of the handle part that used to assemble the care head part.

[0098] It is worth noting that, in the case that a motor and a battery are arranged in the same column, the distance between the motor and the end of the handle part that used to assemble the care head part, is shorter or longer than the distance between the battery and the end of the handle part that used to assemble the care head part. In the case that a fluid mechanism and a battery are arranged in the same column, the distance between the fluid mechanism and the end of the handle part that used to assemble the care head part, is shorter or longer than the distance between the battery and the end of the handle part that used to assemble the care head part.

[0099] In one embodiment, a water storage cavity can be arranged inside the outer shell of the handle part, such as FIG. 1 and FIG. 17(a) show.

[0100] The water storage cavity also can be arranged outside the outer shell of the handle part, such as FIG. 17(b) and FIG. 17(c) show. For example, the water storage cavity and the outer shell of the handle part are not integrally molded but are separate components. The water storage cavity and the outer shell of the handle part can be assembled together via mounting structures.

[0101] Wherein, a outlet of the water storage cavity is interconnected to a inlet of a fluid mechanism of the handle part, so that the fluid mechanism can output the water from the water storage cavity to the outside. Referring to FIG. 17(b), a connecting part between the water storage cavity and the fluid mechanism of the handle part may be concealed from view. Referring FIG. 5(c), the water storage cavity and the fluid mechanism of the handle part can be interconnected via an tube outside the the outer shell of the handle part.

[0102] In the case that the fluid mechanism is interconnected with the tube outside the outer shell of the handle part, the water storage cavity can be part of the oral care device. In another embodiment, the water storage cavity can be any kind of water-hoding apparatus not forming part of the oral care device, such as a cup, a water bottle, a tap water supply, etc.

[0103] In one embodiment, the water storage cavity and the outer shell of the handle part, once assembled, are not easily detachable. For example, the water storage cavity and the outer shell of the handle part are securely assembled via screws.

[0104] In another embodiment, the water storage cavity and the outer shell of the handle part can be disassembled after assembly. A snap connection is set between the water storage cavity and the outer shell of the handle part.

[0105] For example, magnets may be arranged on both the water storage cavity and the handle part to enable magnetic attachment. Moreover, if one of the water storage cavity and the handle part is made with magnetic material, or both the water storage cavity and the handle part are made with magnetic material, the magnetic can not be arranged on anyone which is made with magnetic material and another one of the water storage cavity and the handle part is arranged with the magnet.

[0106] As another example, the snap connection between the water storage cavity and the handle part can be a plug-in connection, a snap-fit connection, a threaded connection, etc.

[0107] In this embodiment, after flowing out of the water storage cavity 13 under the driving action of the power apparatus of the fluid mechanism 8, the fluid enters the fluid mechanism 8 through the fluid inlet 9 of the fluid mechanism 8, then, flows out of the fluid mechanism 8 through the fluid outlet 10 of the fluid mechanism 8 and is delivered to the power output shaft 4, enters the axial channel 5 from the first inlet 6 of the axial channel 5 of the power output shaft 4, then, flows from the inside of the axial channel 5 to the other end of the motor body 3 and flows out of the first outlet 7 of the axial channel 5 to enter the care head part 2, and is finally sprayed out of the spray nozzle 20 of the care head part 2 to rinse an oral cavity. Furthermore, the sonic motor can output power to the care head part 2 by the power output shaft 4 and transmit the power to the brush head 18 by the rinsing stem 17 of the care head part 2, so that the brush head 18 can perform brushing under the action of the sonic motor to clean the oral cavity by virtue of the bristles 19 of the brush head 18.

[0108] The handle part 1 further includes: a front damping cushion 22 sleeving on a front end of the sonic motor, the front end of the sonic motor being mounted in the machine mounting part 12 by the front damping cushion 22; and a rear damping cushion 23 sleeving on a rear end of the sonic motor, the rear end of the sonic motor being mounted in the motor compartment 15 by the rear damping cushion 23; wherein multi-point elastic contact is formed between the periphery of the mounting rack 14 and an inner wall of the machine mounting part 12.

[0109] The sonic motor cooperates with the machine mounting part 12 by both the front damping cushion 22 and the rear damping cushion 23, by both the front damping cushion 22 and the rear

damping cushion **23**, it is possible that the sonic motor is not in direct contact with the machine mounting part **12** and therefore, the sonic motor can be damped by virtue of the damping performance of both the front damping cushion **22** and the rear damping cushion **23**, direct contact between the sonic motor and the housing **11** can be avoided, vibration transmitted from the sonic motor to the machine mounting part **12** can be effectively reduced, vibration felt when a handle is held can be reduced, vibration noise can be reduced, and the use experience of a user can be improved.

[0110] The multi-point elastic contact is formed between the periphery of the mounting rack **14** and the inner wall of the machine mounting part **12**, so that damping fit can also be formed between the mounting rack **14** and the machine mounting part **12**; both the motor compartment **15** and the pump body compartment **16** are located on the mounting rack **14**, and therefore, vibration of each of the sonic motor and the fluid mechanism **8** is transmitted to the machine mounting part **12** by the front damping cushion **22**, the rear damping cushion **23** and the mounting rack **14**; and the mounting rack **14** and the machine mounting part **12** are in multi-point contact and cooperate with both the front damping cushion **22** and the rear damping cushion **23**, which ensures that the vibration can be dispersed from centralized points of vibration sources to contact points of the front damping cushion **22**, the rear damping cushion **23**, the mounting rack **14** and the machine mounting part **12** when being transmitted to the housing **11** by all the vibration sources, so that the vibration action is dispersed, the overall vibration effect of the machine mounting part **12** is weakened, the vibration noise is reduced, and a good damping effect is achieved.

[0111] In one embodiment, the mounting rack **14** includes a mounting base **24**, the mounting base **24** is provided with the motor compartment **15**, two opposite sides of the mounting base **24** are respectively provided with mounting side plates **25** facing away from each other, and edges, away from the mounting base **24**, of the mounting side plates **25** are provided with first elastic bosses **26**.

[0112] In this embodiment, the mounting rack **14** facilitates the mounting and fixing of a structure such as a control panel by virtue of a mounting gap formed between the mounting base **24** and the machine mounting part **12**, and can provide a sufficient mounting space for disposing the structure such as the control panel; due to the existence of the mounting side plates **25**, the assembly fit between the mounting base **24** and the machine mounting part **12** can be facilitated, and the mounting and fixing of the mounting base **24** in the machine mounting part **12** are achieved without affecting the mounting and fixing of the structure such as the control panel. By respectively disposing one of the mounting side plates **25** on the two opposite sides of the mounting base **24** and enabling the mounting side plates **25** to protrude in a direction away from the mounting base **24**, assembly spaces can be formed on two sides of the mounting side plates **25** while the mounting and fixing of the mounting base **24** are achieved by the mounting side plates **25**, so that the mounting of the structure such as the control panel is achieved, and the structure is set to be more reasonable.

[0113] The mounting base **24** cooperates with the machine mounting part **12** by the mounting side plates **25**, and therefore, the edges on the sides, away from the mounting base **24**, of the mounting side plates **25** are provided with the first elastic bosses **26**, the mounting base **24** may form the multi-point elastic contact with the inner wall of the machine mounting part **12** only by the first elastic bosses **26**, but other positions cannot be in contact with the machine mounting part **12**, which ensures that the vibration of each of the sonic motor and the fluid mechanism **8** can only be transmitted to the machine mounting part **12** by the first elastic bosses **26** after being transmitted to the mounting base **24**, so that the damping effect of the mounting rack **14** can be further improved and the damping noise can be reduced.

[0114] In one embodiment, through grooves **27** passing through each of the mounting side plates **25** in a thickness direction are formed in the mounting side plates **25**, and connecting arms **28** located on sides, away from the mounting base **24**, of the through grooves **27** protrude in a direction away from the mounting base **24** to form the first elastic bosses **26**.

[0115] In this embodiment, the through grooves **27** are elongated grooves extending in the length

directions of the mounting side plates **25**, the connecting arms **28** are formed on outer sides of the elongated grooves, and the connecting arms **28** protrude outwards on middle positions to form the first elastic bosses **26**. The connecting arms **28** are of elastic structures with uniform thicknesses and outwards form arc-shaped protrusions on the middle positions; and the arc-shaped protrusions are located on the connecting arms **28**, the connecting arms **28** are located on outer sides of the through grooves **27**, the connecting arms **28** are easier to deform, great in deformation and capable of more effectively absorbing and digesting vibration energy by virtue of its deformation, and therefore, the damping effect can be further improved.

[0116] In one embodiment, the inner wall of the machine mounting part **12** is provided with mounting grooves **29** extending in a mounting direction of the mounting rack **14**, and the mounting side plates **25** are clamped in the mounting grooves **29**.

[0117] In this embodiment, by disposing the mounting grooves **29** in the inner wall of the machine mounting part **12**, a guide structure can be formed, so that it is convenient to mount the mounting rack **14** into the machine mounting part **12** from an open side of the machine mounting part **12**, the mounting difficulty is lowered, and the mounting efficiency is increased.

[0118] In this embodiment, the two opposite inner walls of the machine mounting part **12** are respectively provided with the mounting grooves **29**, so that a more balanced and reliable mounting guiding and supporting structure can be formed.

[0119] The mounting grooves **29** may be formed in the following ways: the inner wall of the machine mounting part **12** is provided with two guide plates extending in the mounting direction of the mounting rack **14**, the two guide plates extend from one end to the other end of the machine mounting part **12**, and the mounting grooves **29** are formed between the two guide plates.

[0120] By disposing the mounting grooves **29**, the mounting rack **14** can be guided and constrained by the mounting grooves **29** when being mounted, and a good locating effect can be achieved after the mounting rack **14** is mounted in place.

[0121] In one embodiment, two opposite side walls of each of the mounting side plates **25** are provided with second elastic bosses **30** protruding towards side walls of the mounting grooves **29**, and multi-point elastic contact is formed between the mounting side plates **25** and the side walls of the mounting grooves **29** by the second elastic bosses **30**.

[0122] In this embodiment, after the mounting grooves **29** are disposed, surface contact is formed between the mounting side plates **25** and side walls of the mounting grooves **29**, which can improve the vibration transmission effect to cause the lowering of the damping effect; and in order to avoid such a problem, multi-point elastic contact can be formed between the two side walls of the mounting side plates **25** and the side walls of the mounting grooves **29** in a way of disposing the second elastic bosses **30** on the two side walls, cooperate with the mounting grooves **29**, of the mounting side plates **25**, so that the vibration transmission action between the mounting side plates **25** and the side walls of the mounting grooves **29** is reduced, the vibration transmission effect between the mounting side plates **25** and the side walls of the mounting grooves **29** is weakened, and the multi-point elastic contact is formed between the mounting rack **14** and the machine mounting part **12** on the whole to play a more effective damping effect.

[0123] In one embodiment, arc-shaped protrusions are formed on the surfaces of both the first elastic bosses **26** and the second elastic bosses **30**, so that it can be more effectively ensured that point contact or line contact is formed between the mounting rack **14** and the machine mounting part **12** by the first elastic bosses **26** and the second elastic bosses **30**, the contact area between the mounting rack **14** and the machine mounting part **12** can be reduced, the vibration transmission effect can be weakened, and the damping effect can be improved.

[0124] In one embodiment, the front damping cushion **22** has a damping plane **31**, an inner wall of the machine mounting part **12** is provided with first strip-shaped walls **32** protruding towards the damping plane **31**, the first strip-shaped walls **32** are tightly pressed and fitted to the damping plane **31**.

[0125] In this embodiment, in a way of disposing the first strip-shaped walls 32 on the inner wall of the machine mounting part 12, the damping plane 31 of the front damping cushion 22 can cooperate with the machine mounting part 12 by the first strip-shaped walls 32; in a way of extruding the damping plane 31 by the first strip-shaped walls 32, the mounting and fixing effects of the machine mounting part 12 on the front damping cushion 22 can be guaranteed, and then, the mounting and fixing effects for the sonic motor are achieved by the front damping cushion 22; and furthermore, by contact between the first strip-shaped walls 32 and the damping plane 31, the contact area between the machine mounting part 12 and the front damping cushion 22 is reduced, the vibration transmission action is lowered, the damping effect of the sonic motor is improved, the phenomenon that the sonic motor is loosened and damaged during work is avoided, and the service life of the sonic motor is guaranteed.

[0126] In one embodiment, the rear damping cushion 23 is provided with a damping boss 33 on a side where the damping plane 31 is located, the inner wall of the machine mounting part 12 is provided with second strip-shaped walls 34 protruding towards the damping boss 33, and the second strip-shaped walls 34 are tightly pressed and fitted to the damping boss 33.

[0127] In this embodiment, two first strip-shaped walls 32 and two second strip-shaped walls 34 are provided, wherein the two first strip-shaped walls 32 are located on outer sides of the two second strip-shaped walls 34; and since the cooperation between the machine mounting part 12 and the damping plane 31 is achieved by the two first strip-shaped walls 32 located on the two sides, it can be ensured that stresses on two sides are balanced, and the overall structural stability is higher.

[0128] The two second strip-shaped walls 34 are tightly pressed on the damping boss 33, so that the rear damping cushion 23 can cooperate with the two second strip-shaped walls 34 to achieve the mounting and fixing of a rear end of the sonic motor, and meanwhile, the damping of the sonic motor can be achieved by virtue of the damping effect of the rear damping cushion 23. Due to the existence of the damping boss 33, the supporting height of the rear damping cushion 23 is different from that of the damping plane 31, and therefore, the first strip-shaped walls 32 and the second strip-shaped walls 34 are different in height; in this way, the first strip-shaped walls 32 and the second strip-shaped walls 34 can form good adaption relationships with cooperation structures, meanwhile, the vibration action is transmitted more dispersedly, and the damping effect is better.

[0129] Due to the cooperation between both the front damping cushion 22 and the rear damping cushion 23, a more comprehensive supporting structure can be formed for the sonic motor, meanwhile, the direct contact between the sonic motor and the machine mounting part 12 can be more effectively avoided, and thus, a better damping effect is formed for the sonic motor.

[0130] In one embodiment, the damping boss 33 is provided with limiting grooves, and two second strip-shaped walls 34 are provided, wherein an edge of one of the second strip-shaped walls 34 is fitted to a wall of each of the limiting grooves, and an edge of the other second strip-shaped wall 34, is fitted to the other wall of each of the limiting grooves.

[0131] In this embodiment, the two second strip-shaped walls 34 are constrained in the limiting grooves, and the limiting grooves can cooperate with the second strip-shaped walls 34 to more effectively limit the rear damping cushion 23, thereby preventing the rear damping cushion 23 from moving relative to the second strip-shaped walls 34 during work and guaranteeing the damping effect of the rear damping cushion 23.

[0132] In one embodiment, on a side opposite to the damping plane 31, two side edges of both the front damping cushion 22 and the rear damping cushion 23 are provided with supporting planes 35, the inner wall of the machine mounting part 12 is provided with third strip-shaped walls 36 protruding towards the supporting planes 35, and the third strip-shaped walls 36 are tightly pressed and fitted to the supporting planes 35 of both the front damping cushion 22 and the rear damping cushion 23.

[0133] In this embodiment, the third strip-shaped walls 36 are located on opposite sides of the first strip-shaped walls 32 and the second strip-shaped walls 34, and the front damping cushion 22 can

be tightly pressed and fixed from the other side of the front damping cushion **22**, so that the sonic motor is tightly pressed and fixed in a direction perpendicular to the mounting side plates **25**; and by cooperation with the limiting effects of the mounting side plates **25**, the omni-directional damping and limiting for the sonic motor can be achieved, the phenomenon that the sonic motor is loosened and damaged during work is effectively avoided, and the long-term stable and reliable operation of the sonic motor is guaranteed.

[0134] In one embodiment, the front damping cushion **22** is provided with a plurality of spacing ribs on a side where the supporting plane **35** of the front damping cushion **22** is located, and line passing channels are formed between the adjacent spacing ribs.

[0135] The fluid mechanism **8** includes a casing **37** and a fluid pump **38** located in the casing **37**, the fluid pump **38** is located between the fluid inlet **9** and the fluid outlet **10**, the fluid inlet **9** communicates with a suction inlet of the fluid pump **38**, and the fluid outlet **10** communicates with a pump outlet of the fluid pump **38**.

[0136] In this embodiment, the fluid pump **38** can provide power for the flow of water and facilitate pumping the water from the water storage cavity **13** to the axial channel **5** of the power output shaft **4**, thereby delivering the water by the axial channel **5**. For such a structure, an internal structure of the machine mounting part **12** is sufficiently utilized, meanwhile, the power output shaft **4** located in the motor body **3** is utilized to form the fluid channel, and it is unnecessary to increase an additional guide pipe to guide water, so that the structural assembly is simpler, the structure is more compact, fewer structural components are required, the cost is lower, moreover, the overall size of the handle cannot be increased, and the hand-holding comfort level is higher.

[0137] In one embodiment, the fluid pump **38** is a diaphragm pump which is simple in structure, convenient to mount and few in quick-wear parts. The fluid pump **38** can also be a centrifugal pump or a gear pump.

[0138] An outlet end of the fluid mechanism **8** is provided with a fluid delivery shaft **39**, the fluid delivery shaft **39** is provided with a fluid channel **21**, the fluid channel **21** communicates with the fluid outlet **10**, and the fluid delivery shaft **39** communicates with the power output shaft **4** by a connector **40**.

[0139] The connector **40** has a communication cavity **41**, a first end facing the power output shaft **4** and a second end facing the fluid mechanism **8**, a first end of the power output shaft **4** extends into the first end of the connector **40**, and an end of the fluid mechanism **8** where the fluid outlet **10** is located extends into the second end of the connector **40**.

[0140] In this embodiment, the first end of the power output shaft **4** extends into the first end of the connector **40**, the end of the fluid mechanism **8** where the fluid outlet **10** is located extends into the second end of the connector **40**, and the power output shaft **4** and the fluid mechanism **8** are connected by the connector **40**, in this way, the fluid in the fluid mechanism **8** can flow into the axial channel of the power output shaft **4** by the communication cavity **41** and then flows out along the axial channel to enter the rinsing head so as to provide a water source for the rinsing head.

[0141] The communication cavity **41** includes a first communication segment **42** communicating with the first inlet **6** and a second communication segment **43** communicating with the fluid outlet **10**, the first communication segment **42** communicates with the second communication segment **43**, an end part of the first communication segment **42** is provided with a first sealing groove **44**, an end part of the second communication segment **43** is provided with a second sealing groove **45**, and each of the first sealing groove **44** and the second sealing groove **45** is provided with a sealing element **46** therein.

[0142] In this embodiment, the first inlet **6** communicates with the first communication segment **42**, and the fluid outlet **10** communicates with the second communication segment **43**, in this way, the fluid in the fluid mechanism **8** can flow from the fluid outlet **10** to the second communication segment **43**, then flow from the second communication segment **43** to the first communication segment **42**, and finally enter the first inlet **6** from the first communication segment **42**, and thus,

the delivery of the fluid from the fluid mechanism **8** to the power output shaft **4** is achieved. Each of the first sealing groove **44** and the second sealing groove **45** is provided with the sealing element **46** therein by which a gap between the first end of the power output shaft **4** and the first communication segment **42** and a gap between the fluid mechanism **8** and the second communication segment **43** can be sealed to form a sealed fluid delivery channel, so that the situation that the fluid flows out of the gap between the first end of the power output shaft **4** and the first communication segment **42** and the gap between the fluid mechanism **8** and the second communication segment **43** to result in short circuit or water damage of components inside the handle part in a process that the fluid flows from the fluid mechanism **8** to the axial channel is avoided.

[0143] The first communication segment **42** and the second communication segment **43** are disposed in a staggered manner, the connector **40** is provided with an avoidance groove **47** on one side of the first communication segment **42**, the connector **40** is provided with adjusting grooves **48** on two opposite sides of the second communication segment **43**, and the connector **40** has the same wall thickness on both sides of each of the adjusting grooves **48**.

[0144] In this embodiment, both the first communication segment **42** and the second communication segment **43** extend in the extension direction of the output axis so as to be simpler in structure, and they can be more adapted to the layout of axial structures of the power output shaft **4** and the fluid mechanism **8**, thereby facilitating achieving the connection and communication between the connector and each of the power output shaft **4** and the fluid mechanism **8**. The first communication segment **42** and the second communication segment **43** are disposed coaxially or in a staggered manner and can cooperate with a structure that the motor is not coaxial with the fluid delivery shaft **39** of the fluid mechanism **8**, so that the adaptability is better, the connection between different sonic motors and the fluid mechanism **8** can also be satisfied, and the applicability of the connector **40** is improved.

[0145] In one embodiment of the present disclosure, when the first communication segment **42** and the second communication segment **43** are disposed in a staggered manner, the connector **40** is provided with the avoidance groove **47** on one side of the first communication segment **42**, the connector **40** is provided with adjusting grooves **48** on two opposite sides of the second communication segment **43**, and the connector **40** has the same wall thickness on both sides of each of the adjusting grooves **48**.

[0146] In this embodiment, when the first communication segment **42** and the second communication segment **43** are disposed in a staggered manner, the connector **40** is provided with the avoidance groove **47** on one side of the first communication segment **42** to avoid interference to the mounting of other parts.

[0147] The connector **40** has the same wall thickness on both sides of each of the adjusting grooves **48**, which not only can avoid collapse and deformation caused by a too large wall thickness during injection molding of the connector **40**, but also can ensure that the connector **40** has good elastic deformation on two sides of the adjusting grooves **48** so as to be better in adaptability.

[0148] The care head part **2** further includes a connecting structure **49** configured to be capable of transmitting a driving force of the power output shaft **4** to the rinsing stem **17**, the connecting structure **49** is disposed on an end, away from the brush head **18**, of the rinsing stem **17** and is capable of being in snap-fitted with the power output shaft **4** to limit the axial movement of the power output shaft **4** relative to the rinsing stem **17**.

[0149] In the above-mentioned technical solutions, compared with an electric toothbrush which is only required to satisfy vibration transmission or a tooth rinser which is only required to take a hydraulic impact force into account in the prior art, this embodiment has the advantages that by disposing the connecting structure **49**, the connecting structure **49** may transmit the driving force of the power output shaft **4** to the rinsing stem **17** to ensure that vibration is transmitted to the rinsing stem **17**, thereby achieving a tooth cleaning function of the electric toothbrush by virtue of the

vibration of the sonic motor; moreover, the connecting structure **49** is snap-fitted with the power output shaft **4** so as to be further capable of limiting the axial displacement of the power output shaft **4** relative to the rinsing stem **17**, in this way, the problem that the power output shaft **4** is detached from the rinsing stem **17** due to the hydraulic impact force can be avoided, and thus, a shaking force transmitted by the power output shaft **4** can be more stably transmitted to the rinsing stem **17**; furthermore, the oral care device in this embodiment not only has the tooth brushing function of the electric toothbrush, but also has the rinsing function of the tooth rinser, so that the experience of a user is improved, and the cleaning effect of the oral care device is improved. Therefore, the oral care device in this embodiment has a synchronous rinsing function.

[0150] Specifically, in an embodiment of the present disclosure, by disposing the axial channel **5** on the power output shaft **4** for transmitting power and disposing the fluid channel **21** and the spray nozzle **20** communicating with the fluid channel **21** on the rinsing stem **17**, the fluid may be sprayed out of the spray nozzle **20** after flowing through the axial channel **5** and the fluid channel **21** in sequence, so that a function of rinsing the oral cavity by the fluid sprayed out of the spray nozzle **20** can also be achieved while or after tooth brushing.

[0151] Specifically, in this embodiment, the power output shaft **4** is provided with the axial channel **5** parallel to the output axis, in this way, when a fluid on the incoming flow side reaches a position where the sonic motor is located, a pipe is not needed to be disposed outside the sonic motor, but can be directly connected to the power output shaft **4** of the sonic motor, so that the fluid can be delivered by the axial channel **5** of the power output shaft **4**, and thus, the fluid passes through the inside of the power output shaft **4** inside the sonic motor; it is unnecessary to perform other variations in a structure of a product, i.e. additionally disposing a delivery pipeline to deliver the fluid is avoided, no additional space is occupied, and the structure of the sonic motor can be more sufficiently and reasonably utilized, so that the structural layout of a rinsing flow path is more reasonable, fluid pipelines are reduced, the occupied space is saved, and the oral care device is smaller in overall size and lighter in weight; and the handle part is more convenient to hold with a hand.

[0152] It should be noted that, in an embodiment of the present disclosure, the fluid flows from the power output shaft **4** to the fluid channel **21** of the rinsing stem **17**, and the high-pressure fluid can generate a water flow impact force for a tail end of the power output shaft **4**, in this way, the power output shaft **4** in FIG. **1** is easily detached from the rinsing stem **17**. In this embodiment, such a problem can be solved by disposing the connecting structure **49**.

[0153] The periphery of the power output shaft **4** is provided with a clamping groove **50** extending in the circumferential direction of the power output shaft **4**, the connecting structure **49** includes: a connecting support **51** having an internal through hole parallel to the output axis, wherein the power output shaft **4** can be inserted in the internal through hole; and a clamping piece **52** disposed on the connecting support **51**, the clamping piece **52** including two clamping arms **53** spaced apart in the radial direction of the power output shaft **4**, and the two clamping arms **53** having a clamping position, in which the two clamping arms **53** are close to each other and become snap-fitted with the clamping groove **50** and an unclamping position, in which the two clamping arms **53** are away from each other and become not snap-fitted with the clamping groove **50**.

[0154] By the above arrangement, when the power output shaft **4** is inserted in the internal through hole and between the two clamping arms **53**, the two clamping arms **53** may be away from each other under the action of the power output shaft **4** until the clamping groove **50** of the power output shaft **4** moves to positions corresponding to the clamping arms **53**, the two clamping arms **53** may be close to each other and clamped into the clamping groove **50** to limit the axial displacement of the power output shaft **4** relative to the connecting support **51**, in this way, the problem that the power output shaft **4** is detached from the rinsing stem **17** due to the hydraulic impact force can be avoided, the shaking force transmitted by the power output shaft **4** can be more stably transmitted to the rinsing stem **17**, and thus, the oral care device in this embodiment not only has the tooth

brushing function of the electric toothbrush, but also has the rinsing function of rinsing teeth.

[0155] As shown in FIG. 7, in an embodiment of the present disclosure, the clamping piece 52 further includes an elastic arm 54 for connecting the two clamping arms 53 so that the two clamping arms 53 can be switched from the unclamping position to the clamping position.

[0156] By the above arrangement, when the power output shaft 4 is put into the internal through hole, the two clamping arms 53 can be struted under the action of an assembly force of the power output shaft 4, the elastic arm 54 deforms until the clamping groove 50 of the power output shaft 4 moves to positions corresponding to the clamping arms 53, then, the elastic arm 54 is recovered from deformation to drive the two clamping arms 53 to be close to each other so as to be clamped into the clamping groove 50, so that the power output shaft 4 is prevented from axially moving relative to the connecting support 51. In this way, the problem that the power output shaft 4 is detached from the rinsing stem 17 due to the hydraulic impact force can be avoided.

[0157] Further, the elastic arm 54 has elasticity, and when the power output shaft 4 is required to be dismounted from the rinsing stem 17, a user can pull the power output shaft 4 out of the internal through hole by using a force greater than the water flow impact force, in this way, the elastic arm 54 may deform to drive the two clamping arms 53 to be away from each other so that the clamping arms 53 are detached from the clamping groove 50. In this way, when the brush head 18 is required to be replaced due to abrasion after being used for a long time, by using the above-mentioned structure, quick dismounting can be achieved, and it is convenient for a user to replace the care head part 2 in time.

[0158] Preferably, in an embodiment of the present disclosure, an inner wall of the clamping groove 50 and a side wall of the power output shaft 4 are connected by an arc-shaped transition segment, in this way, when the power output shaft 4 is mounted, the clamping arms 53 can be more smoothly slid into the clamping groove 50 from the side wall of the power output shaft 4, and when the power output shaft 4 is dismounted, the clamping arms 53 can be more smoothly slid out of the clamping groove 50.

[0159] In an alternative embodiment, there may also be only two clamping arms 53 made of an elastic material, in this way, the two clamping arms 53 may be away from each other under the action of the power output shaft 4, and when the clamping groove 50 of the power output shaft 4 moves to the positions corresponding to the clamping arms 53, the two clamping arms 53 may be recovered from deformation and close to each other so as to be clamped into the clamping groove 50.

[0160] As shown in FIG. 2, FIG. 4, FIG. 5 and FIG. 6, in an embodiment of the present disclosure, the connecting support 51 is provided with a mounting via groove 55 communicating with the internal through hole, and the mounting via groove 55 passes through the connecting support 51 in the radial direction of the power output shaft 4; and inner walls on circumferential sides of the mounting via groove 55 are in clearance fit with the clamping arms 53.

[0161] By the above arrangement, the clamping piece 52 can be mounted in the mounting via groove 55, and the two clamping arms 53 can be exposed from the internal through hole and clamped to the clamping groove 50; and further, inner walls on circumferential sides of the mounting via groove 55 are in clearance fit with the clamping arms 53, in this way, the inner walls on the circumferential sides of the mounting via groove 55 can limit ultimate displacements of the clamping arms 53 to avoid invalidation caused by greater deformation of the elastic arm 54 in a process that the two clamping arms 53 are away from each other.

[0162] Specifically, in an embodiment of the present disclosure, a width of the mounting via groove 55 on a horizontal plane in FIG. 5 is greater than an internal diameter of the internal through hole, in this way, the inner walls on the circumferential sides of the mounting via groove 55 can be in clearance fit with the clamping arms 53.

[0163] As shown in FIG. 2 and FIG. 7, in an embodiment of the present disclosure, the clamping piece 52 further includes an elastic arm 54 for connecting the two clamping arms 53, the

connecting structure **49** further includes a retaining rib **56** connected to the connecting support **51**, one end of the mounting via groove **55** is provided with the retaining rib **56**, and the elastic arm **54** is partially located on a side, facing away from the internal through hole, of the retaining rib **56** so that the displacement of the elastic arm **54** is constrained thereby.

[0164] In the above-mentioned technical solutions, when the clamping piece **52** is mounted in the mounting via groove **55**, the retaining rib **56** can limit displacement of the elastic arm **54** to avoid a situation that the power output shaft **4** penetrates in or out of the internal through hole to bring the elastic arm **54** into the internal through hole, so that a situation that the dismounting or mounting of the power output shaft **4** is affected by the elastic arm **54** entering the internal through hole is avoided.

[0165] As shown in FIG. 2 and FIG. 4, in an embodiment of the present disclosure, the connecting structure **49** further includes a locating rib **57** disposed on the other end of the mounting via groove **55**, the clamping piece **52** further includes two locating arms **58** respectively connected to the two clamping arms **53**, and the two locating arms **58** are spaced apart and are located on two sides of the locating rib **57**.

[0166] By the above arrangement, on one hand, the locating rib **57** can locate the two locating arms **58**, and the locating rib **57** can ensure that the clamping piece **52** is located on the same position of the mounting via groove **55** during the dismounting or mounting of the power output shaft **4**, so that a situation that the power output shaft **4** penetrates in or out of the internal through hole to result in position deviation of the clamping piece **52** can be avoided, and then, the power output shaft **4** can be dismounted or mounted conveniently and quickly; and on the other hand, the locating rib **57** can strut the two locating arms **58**, so that a spacing between the two clamping arms **53** allows the power output shaft **4** to penetrate in.

[0167] Preferably, in an embodiment of the present disclosure, the retaining rib **56** and the locating rib **57** are symmetrically disposed with respect to an axis of the internal through hole of the connecting support **51**, in this way, any one of the locating rib **57** and the retaining rib **56** can limit the displacement of the elastic arm **51** or locate the clamping piece **52**, thereby facilitating machining.

[0168] Preferably, in an embodiment of the present disclosure, the clamping piece **52** is a U-shaped clamping spring, and of course, may also be other forms of springs.

[0169] The rinsing stem **17** is provided with a mounting through hole **59** communicating with the fluid channel **21**, a step surface is disposed between the mounting through hole **59** and the fluid channel **21**, and the connecting structure **49** is located in the mounting through hole **59** and is constrained between the step surface and an end face of the housing **11**.

[0170] The care head part **2** further includes a limiting groove **60** disposed in the rinsing stem **17** and a limiting rib **61** disposed on the connecting support **51** of the connecting structure **49**, the limiting groove **60** communicates with the mounting through hole **59**, and the limiting rib **61** is constrained by and cooperates with the limiting groove **60**.

[0171] By the above arrangement, the connecting structure **49** can be mounted in the rinsing stem **17**, and the displacement of the connecting structure **49** in an axis direction of the mounting through hole **59** can be constrained, in this way, when the connecting structure **49** transmits power, axial movement of the connecting structure **49** can be avoided, so that the experience of a user is improved.

[0172] In an alternative embodiment, it is also possible to additionally provide a cylindrical structure between the rinsing stem **17** and the housing **11**, and the connecting structure **49** is mounted in the cylindrical structure as long as power transmission can be achieved.

[0173] As shown in FIG. 3 and FIG. 4, in an embodiment of the present disclosure, the care head part **2** further includes the limiting groove disposed in the rinsing stem **17** and the limiting rib **61** disposed on the connecting support **51**, the limiting groove communicates with the mounting through hole **59**, and the limiting rib **61** is constrained by and cooperates with the limiting groove

60.

[0174] By the above arrangement, when the connecting support **51** is mounted in the mounting through hole **59**, the limiting rib **61** is constrained by and cooperates with the limiting groove, so that the displacement of the connecting support **51** in the axis direction of the mounting through hole **59** can be constrained. In this way, when the connecting structure **49** transmits power or the care head part **2** is placed as an independent accessory, the axial movement of the connecting structure **49** can be avoided, and thus, the experience of a user can be improved.

[0175] Preferably, in an embodiment of the present disclosure, the care head part **2** includes a plurality of limiting grooves and a plurality of limiting ribs **61** correspondingly cooperating with the plurality of limiting grooves, and the plurality of limiting grooves are spaced apart around the axis of the mounting through hole **59**, in this way, an effect of avoiding axial movement can be improved.

[0176] It should be noted that the limiting grooves can be loop-closed annular grooves extending in a circumferential direction, and can also be grooves disposed in the inner wall of the rinsing stem **17**.

[0177] As shown in FIG. **2** and FIG. **3**, in an embodiment of the present disclosure, transition pieces are disposed on connections of side walls of the limiting grooves and an inner wall of the mounting through hole **59**, the transition pieces are located on sides, facing the housing **11**, of the limiting grooves, and the transition pieces have arc-shaped curved surfaces protruding towards a side where the axis of the mounting through hole **59** is located so as to be smoothly connected to the side walls of the limiting grooves and the inner wall of the mounting through hole **59**.

[0178] In the above-mentioned technical solutions, the transition pieces with the arc-shaped curved surfaces are disposed, in this way, the connecting support **51** is convenient to mount by virtue of the elastic deformation of the transition pieces, so that the limiting ribs **61** can slide into the limiting grooves, and the transition pieces can also limit the limiting ribs **61** to avoid the situation that the connecting support **51** is detached from the mounting through hole **59** under the influence of the gravity.

[0179] It should be noted that terms used herein are merely intended to describe specific implementations, rather than to limit exemplary implementations of the present application. For example, a singular form used herein is also intended to include a plural form unless the context expressly indicates otherwise. Furthermore, it should be further understood that, when a term “including” and/or “comprising” is used in the present description, it shows that there are features, steps, operations, devices, components and/or combinations thereof.

[0180] It should be noted that terms such as “first” and “second” in the description and claims of the present application and the above-mentioned accompanying drawings are used for distinguishing similar objects, but are unnecessarily used for describing a specific sequential or chronological order. It should be understood that data used in such a way are interchangeable under appropriate circumstances, such that the implementations of the present application described herein can be implemented in other sequences than illustrated or described herein.

[0181] The above descriptions are merely preferred embodiments of the present disclosure, and are not intended to limit the present disclosure. For those skilled in the art, various alterations and variations can be made to the present disclosure. Any modifications, equivalent replacements, improvements, etc. made within the spirit and principle of the present disclosure should fall within the protection scope of the present disclosure.

Claims

1. An oral care device, comprising a handle part and a care head part; wherein the handle part is configured to be suitable for hand-holding and comprises: a motor comprising a motor body and a power output shaft, the motor body having an output axis extending in a power output direction;

the power output shaft being a columnar object extending along the output axis and passing through the motor body, the power output shaft being configured to cooperate with the motor body and transmit output power from the motor body and having an axial channel parallel to the output axis as well as a first inlet and a first outlet communicating with the axial channel; a fluid mechanism provided with a fluid inlet and a fluid outlet, the fluid outlet communicating with the first inlet; and a housing extending in the axial direction of the power output shaft and forming a cylindrical structure of which an inside is hollow, the housing comprising a machine mounting part and a water storage cavity, the machine mounting part being internally provided with a mounting rack, the mounting rack having a motor compartment and a pump body compartment, the motor being mounted in the motor compartment, the fluid mechanism being mounted in the pump body compartment, and a head of the machine mounting part being provided with a mounting shaft hole which allows the power output shaft to penetrate through and is in an assembly fit with the power output shaft; wherein the care head part is provided with a rinsing stem parallel to the output axis and a brush head disposed on a head of the rinsing stem, the rinsing stem is mounted on the power output shaft, the brush head comprises bristles and a spray nozzle, the bristles extend in a direction which forms a preset included angle with the output axis, and the rinsing stem is provided with a fluid channel capable of communicating the spray nozzle with the axial channel; in an extension direction of the output axis, the first outlet of the axial channel is capable of communicating with the fluid channel of the care head part, and during use of the oral care device, water in the water storage cavity can enter the axial channel from the first inlet of the axial channel under an action of the fluid mechanism, flow from a first end to a second end of the motor body via the axial channel, then, enter the fluid channel of the care head part from the first outlet of the axial channel and be sprayed out of the brush head of the care head part.

2. The oral care device of claim 1, wherein the power output shaft has a Rockwell hardness HRC ranging from 17 to 70 and a single-sided wall thickness ranging from 0.3 mm to 1 mm.

3. The oral care device of claim 1, wherein in a section perpendicular to the output axis, a ratio of a sectional area of the power output shaft to a sectional area of the axial channel ranges from 1.5 to 9, a single-sided wall thickness of the power output shaft ranges from 0.3 mm to 1 mm, and an internal diameter of the axial channel ranges from 0.5 mm to 3 mm.

4. The oral care device of claim 1, wherein the handle part further comprises: a front damping cushion sleeving on a front end of the motor, the front end of the motor being mounted in the machine mounting part by the front damping cushion; and a rear damping cushion sleeving on a rear end of the motor, the rear end of the motor being mounted in the motor compartment by the rear damping cushion; wherein multi-point elastic contact is formed between a periphery of the mounting rack and an inner wall of the machine mounting part.

5. The oral care device of claim 4, wherein the mounting rack comprises a mounting base, the mounting base is provided with the motor compartment, two opposite sides of the mounting base are respectively provided with mounting side plates facing away from each other, edges, away from the mounting base, of the mounting side plates are provided with first elastic bosses; and through grooves passing through each of the mounting side plates in a thickness direction are formed in the mounting side plates, and connecting arms located on sides, away from the mounting base, of the through grooves protrude in a direction away from the mounting base to form the first elastic bosses.

6. The oral care device of claim 5, wherein an inner wall of the machine mounting part is provided with mounting grooves extending in a mounting direction of the mounting rack, the mounting side plates are clamped in the mounting grooves, two opposite side walls of each of the mounting side plates are provided with second elastic bosses protruding towards side walls of the mounting grooves, and multi-point elastic contact is formed between the mounting side plates and the side walls of the mounting grooves by the second elastic bosses.

7. The oral care device of claim 4, wherein the front damping cushion has a damping plane, an

inner wall of the machine mounting part is provided with first strip-shaped walls protruding towards the damping plane, the first strip-shaped walls are tightly pressed and fitted to the damping plane, the rear damping cushion is provided with a damping boss on a side where the damping plane is located, the inner wall of the machine mounting part is provided with second strip-shaped walls protruding towards the damping boss, and the second strip-shaped walls are tightly pressed and fitted to the damping boss.

8. The oral care device of claim 7, wherein on a side opposite to the damping plane, two side edges of both the front damping cushion and the rear damping cushion are provided with supporting planes, the inner wall of the machine mounting part is provided with third strip-shaped walls protruding towards the supporting planes, and the third strip-shaped walls (36) are tightly pressed and fitted to the supporting planes of both the front damping cushion and the rear damping cushion.

9. The oral care device of claim 1, wherein the fluid mechanism comprises a casing and a fluid pump located in the casing, the fluid pump is located between the fluid inlet and the fluid outlet, the fluid inlet communicates with a suction inlet of the fluid pump, and the fluid outlet communicates with a pump outlet of the fluid pump.

10. The oral care device of claim 9, wherein an outlet end of the fluid mechanism is provided with a fluid delivery shaft, the fluid delivery shaft is provided with a fluid channel, the fluid channel communicates with the fluid outlet, and the fluid delivery shaft communicates with the power output shaft by a connector.

11. The oral care device of claim 10, wherein the connector has a communication cavity, a first end facing the power output shaft and a second end facing the fluid mechanism, a first end of the power output shaft extends into the first end of the connector, and an end of the fluid mechanism where the fluid outlet is located extends into the second end of the connector.

12. The oral care device of claim 11, wherein the communication cavity comprises a first communication segment communicating with the first inlet and a second communication segment communicating with the fluid outlet, the first communication segment communicates with the second communication segment, an end part of the first communication segment is provided with a first sealing groove, an end part of the second communication segment is provided with a second sealing groove, and each of the first sealing groove and the second sealing groove is provided with a sealing element therein.

13. The oral care device of claim 12, wherein the first communication segment and the second communication segment are disposed in a staggered manner, the connector is provided with an avoidance groove on one side of the first communication segment, the connector is provided with adjusting grooves on two opposite sides of the second communication segment, and the connector has a same wall thickness on both sides of each of the adjusting grooves.

14. The oral care device of claim 1, wherein the care head part further comprises a connecting structure configured to be capable of transmitting a driving force of the power output shaft to the rinsing stem, the connecting structure is disposed on an end, away from the brush head, of the rinsing stem and is capable of being snap-fitted with the power output shaft to limit axial movement of the power output shaft relative to the rinsing stem.

15. The oral care device of claim 14, wherein a periphery of the power output shaft is provided with a clamping groove extending in a circumferential direction of the power output shaft, the connecting structure comprises: a connecting support having an internal through hole parallel to the output axis, wherein the power output shaft can be inserted in the internal through hole; and a clamping piece disposed on the connecting support, the clamping piece comprising two clamping arms spaced apart in a radial direction of the power output shaft, and the two clamping arms having a clamping position, in which the two clamping arms are close to each other and become snap-fitted with the clamping groove, and an unclamping position, in which the two clamping arms are away from each other and become not snap-fitted with the clamping groove.

16. The oral care device of claim 15, wherein the clamping piece further comprises an elastic arm

for connecting the two clamping arms so that the two clamping arms can be switched from the unclamping position to the clamping position.

17. The oral care device of claim 15, wherein the connecting support is provided with a mounting via groove communicating with the internal through hole, and the mounting via groove passes through the connecting support in the radial direction of the power output shaft; and inner walls on circumferential sides of the mounting via groove are in clearance fit with the clamping arms.

18. The oral care device of claim 17, wherein the clamping piece further comprises an elastic arm for connecting the two clamping arms, the connecting structure further comprises a retaining rib connected to the connecting support, one end of the mounting via groove is provided with the retaining rib, and the elastic arm is partially located on a side, facing away from the internal through hole, of the retaining rib so that a displacement of the elastic arm is limited thereby.

19. The oral care device of claim 18, wherein the connecting structure further comprises a locating rib disposed on the other end of the mounting via groove, the clamping piece further comprises two locating arms respectively connected to the two clamping arms, and the two locating arms are spaced apart and are located on two sides of the locating rib.

20. The oral care device of claim 15, wherein the rinsing stem is provided with a mounting through hole communicating with the fluid channel, a step surface is disposed between the mounting through hole and the fluid channel, and the connecting structure is located in the mounting through hole and is constrained between the step surface and an end face of the housing.
