

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12389380
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Hosseini; Seyedkianoush et al.

Grant-free downlink transmission

Abstract

Methods, systems, and devices for wireless communications are described. The described techniques generally support downlink transmissions. For example, a user equipment (UE) may receive a resource configuration for reception of a downlink transmission within a repetition window, the resource configuration including an indicator of a repetition window size for the downlink transmission. The UE may monitor, according to the resource configuration, one or more transmission time intervals (TTIs) of the repetition window for reception of the downlink transmission. In some cases, the downlink transmission may be a grant-free downlink transmission. Here, the UE may attempt to decode the grant-free downlink transmission during the one or more TTIs based at least in part on the repetition window size. Using the described techniques, the UE may efficiently determine one or more decoding parameters for the grant-free downlink transmission, thereby providing benefits in terms of latency reduction, power consumption, etc.

Inventors: Hosseini; Seyedkianoush (San Diego, CA), Chen; Wanshi (San Diego, CA), Patel; Shimman Arvind (San Diego, CA)

Applicant: QUALCOMM Incorporated (San Diego, CA)

Family ID: 66950887

Assignee: QUALCOMM Incorporated (San Diego, CA)

Appl. No.: 17/930836

Filed: September 09, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230109628 A1	Apr. 06, 2023

Related U.S. Application Data

continuation parent-doc US 17065106 20201007 US 11477782 child-doc US 17930836
division parent-doc US 16223834 20181218 US 10849124 child-doc US 17065106
us-provisional-application US 62609266 20171221

Publication Classification

Int. Cl.: H04W72/0446 (20230101); H04L1/1812 (20230101); H04W72/23 (20230101)

U.S. Cl.:

CPC H04W72/0446 (20130101); H04L1/1812 (20130101); H04W72/23 (20230101);

Field of Classification Search

CPC: H04W (72/0446); H04W (72/23); H04L (1/08); H04L (1/1812); H04L (1/1822); Y02D (30/70)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8897202	12/2013	Chen et al.	N/A	N/A
10172155	12/2018	Rico et al.	N/A	N/A
10849124	12/2019	Hosseini et al.	N/A	N/A
11102786	12/2020	Salem et al.	N/A	N/A
2013/0083753	12/2012	Lee	370/329	H04W 72/0453
2014/0328260	12/2013	Papasakellariou	370/329	H04W 72/23
2015/0181576	12/2014	Papasakellariou	370/329	H04L 1/08
2016/0183112	12/2015	Yang	370/252	H04L 5/0053
2016/0211949	12/2015	You	N/A	H04W 72/23
2016/0309475	12/2015	Wong	N/A	H04W 4/70
2017/0273058	12/2016	Agiwal et al.	N/A	N/A
2017/0289899	12/2016	You	N/A	H04L 5/0007
2017/0310431	12/2016	Iyer et al.	N/A	N/A
2017/0374640	12/2016	Kim	N/A	G01S 1/042
2018/0132237	12/2017	Sundararajan	N/A	H04W 72/0446
2018/0199322	12/2017	Takeda	N/A	H04L 5/0053
2018/0242280	12/2017	Axmon	N/A	H04L 1/203
2018/0279268	12/2017	You	N/A	H04L 5/0035
2018/0368024	12/2017	Cheng et al.	N/A	N/A
2019/0044646	12/2018	Xu	N/A	H04L 27/36
2019/0053211	12/2018	Ying	N/A	H04W 72/044
2019/0104539	12/2018	Park et al.	N/A	N/A
2019/0141742	12/2018	Zhou	N/A	H04L 5/0064
2019/0174446	12/2018	Zhang et al.	N/A	N/A
2019/0200352	12/2018	Hosseini et al.	N/A	N/A

2020/0021388	12/2019	Lyu et al.	N/A	N/A
2020/0036481	12/2019	Chen et al.	N/A	N/A
2020/0178228	12/2019	Li	N/A	H04W 68/02
2020/0213980	12/2019	Takeda	N/A	H04L 1/1861
2020/0288438	12/2019	Takeda et al.	N/A	N/A
2020/0322973	12/2019	Li et al.	N/A	N/A
2021/0022138	12/2020	Hosseini et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
WO-2017019587	12/2016	WO	N/A
WO-2017034096	12/2016	WO	N/A

OTHER PUBLICATIONS

International Preliminary Report on Patentability—PCT/US2018/066456, The International Bureau of WIPO—Geneva, Switzerland, Jul. 2, 2020. cited by applicant

International Search Report and Written Opinion—PCT/US2018/066456—ISA/EPO—Feb. 28, 2019. cited by applicant

Taiwan Search Report—TW107145871—TIPO—Jul. 13, 2021. cited by applicant

Primary Examiner: Yuen; Kan

Attorney, Agent or Firm: Holland & Hart LLP

Background/Summary

CROSS REFERENCES (1) The present Application for Patent is a Continuation of U.S. patent application Ser. No. 17/065,106 by HOSSEINI et al., entitled “GRANT-FREE DOWNLINK TRANSMISSION” filed Oct. 7, 2020, which is a Divisional of U.S. patent application Ser. No. 16/223,834 by HOSSEINI, et al., entitled “GRANT-FREE DOWNLINK TRANSMISSION” filed Dec. 18, 2018, which claims the benefit of U.S. Provisional Patent Application No. 62/609,266 by HOSSEINI et al., entitled “GRANT-FREE DOWNLINK TRANSMISSION,” filed Dec. 21, 2017, assigned to the assignee hereof, and expressly incorporated by reference herein.

BACKGROUND

(1) The following relates generally to wireless communication, and more specifically to grant-free downlink transmission.

(2) Wireless communications systems are widely deployed to provide various types of communication content such as voice, video, packet data, messaging, broadcast, and so on. These systems may be capable of supporting communication with multiple users by sharing the available system resources (e.g., time, frequency, and power). Examples of such multiple-access systems include fourth generation (4G) systems such as Long Term Evolution (LTE) systems, LTE-Advanced (LTE-A) systems, or LTE-A Pro systems, and fifth generation (5G) systems which may be referred to as New Radio (NR) systems. These systems may employ technologies such as code division multiple access (CDMA), time division multiple access (TDMA), frequency division multiple access (FDMA), orthogonal frequency division multiple access (OFDMA), or discrete Fourier transform-spread-OFDM (DFT-s-OFDM). A wireless multiple-access communications system may include a number of base stations or network access nodes, each simultaneously supporting communication for multiple communication devices, which may be otherwise known as user equipment (UE).

(3) Some wireless communications may require or benefit from low latency access. For example, ultra-reliable low latency communications (URLLC) may achieve such low latency through the use of small packet sizes, short transmission intervals, or the like. In some wireless systems, downlink transmissions (from a base station to a UE) may be scheduled, which scheduling may consume wireless resources and introduce overhead for the system. This overhead may, in turn, increase latency and may therefore be undesirable in some cases (e.g., for URLLC). Improved techniques for downlink transmissions that support low latency communications may thus be desired.

SUMMARY

(4) The described techniques relate to improved methods, systems, devices, or apparatuses that support grant-free downlink transmission. Generally, the described techniques provide for one or more frameworks for grant-free downlink transmissions, which frameworks may be leveraged by a user equipment (UE) to decode the grant-free downlink transmissions. Specifically, the UE may be configured (e.g., via radio resource control (RRC) signaling) with parameters (e.g., time/frequency resources, a transport block size (TBS), a redundancy version (RV) sequence, a repetition window size, etc.) for the grant-free downlink transmission. Based on applying the configured parameters within the one or more frameworks discussed below, the UE may efficiently decode a grant-free downlink transmission. For example, the reduced number of blind decoding attempts supported by aspects of the following (e.g., as compared to an unconstrained search across candidate RV indices and/or hybrid automatic repeat request (HARQ) process identifications (IDs)) may provide for low latency communications (e.g., by allowing a downlink transmission to be decoded within a threshold amount of time corresponding to the low latency process).

(5) A method of wireless communication at a UE is described. The method may include receiving a resource configuration for reception of a downlink transmission within a repetition window, the resource configuration including an indicator of a repetition window size for the downlink transmission, monitoring, in accordance with the resource configuration, one or more transmission time intervals (TTIs) of the repetition window for reception of the downlink transmission, and attempting to decode the downlink transmission during the one or more TTIs of the repetition window based on the repetition window size.

(6) An apparatus for wireless communication at a UE is described. The apparatus may include a processor, memory in electronic communication with the processor, and instructions stored in the memory. The instructions may be executable by the processor to cause the apparatus to receive a resource configuration for reception of a downlink transmission within a repetition window, the resource configuration including an indicator of a repetition window size for the downlink transmission, monitor, in accordance with the resource configuration, one or more transmission time intervals (TTIs) of the repetition window for reception of the downlink transmission, and attempt to decode the downlink transmission during the one or more TTIs of the repetition window based on the repetition window size.

(7) Another apparatus for wireless communication at a UE is described. The apparatus may include means for receiving a resource configuration for reception of a downlink transmission within a repetition window, the resource configuration including an indicator of a repetition window size for the downlink transmission, monitoring, in accordance with the resource configuration, one or more transmission time intervals (TTIs) of the repetition window for reception of the downlink transmission, and attempting to decode the downlink transmission during the one or more TTIs of the repetition window based on the repetition window size.

(8) A non-transitory computer-readable medium storing code for wireless communication at a UE is described. The code may include instructions executable by a processor to receive a resource configuration for reception of a downlink transmission within a repetition window, the resource configuration including an indicator of a repetition window size for the downlink transmission, monitor, in accordance with the resource configuration, one or more transmission time intervals (TTIs) of the repetition window for reception of the downlink transmission, and attempt to decode

the downlink transmission during the one or more TTIs of the repetition window based on the repetition window size.

(9) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, monitoring the one or more TTIs of the repetition window for reception of the downlink transmission may include operations, features, means, or instructions for monitoring for a first repetition of the downlink transmission in an initial TTI of the repetition window, where the repetition window size may be greater than one TTI.

(10) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, attempting to decode the downlink transmission may include operations, features, means, or instructions for identifying a series of redundancy version (RV) indices for the repetition window based on the resource configuration, each RV index of the series of RV indices associated with a respective TTI of the repetition window, and attempting to decode the downlink transmission during a given TTI of the repetition window based on the RV index associated with the given TTI.

(11) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the resource configuration may be received via RRC signaling, the resource configuration further including a series of redundancy version (RV) indices for repeated transmissions of the downlink transmission within the repetition window.

(12) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, attempting to decode the downlink transmission may include operations, features, means, or instructions for transmitting an indication that the downlink transmission was successfully decoded.

(13) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the downlink transmission may be a grant-free downlink transmission.

(14) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, attempting to decode the grant-free downlink transmission may include operations, features, means, or instructions for identifying a potential redundancy version (RV) index and a corresponding HARQ process identification (ID) for the grant-free downlink transmission, where each decoding attempt may be based on a unique pair of potential RV index and corresponding HARQ process ID.

(15) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, identifying the potential RV index and the corresponding HARQ process ID for the grant-free downlink transmission may include operations, features, means, or instructions for determining a TTI index for each of the one or more TTIs of the repetition window, where the corresponding HARQ process ID for a given TTI may be based on the TTI index for the given TTI.

(16) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, monitoring the one or more TTIs of the repetition window for reception of the grant-free downlink transmission may include operations, features, means, or instructions for identifying, based on the resource configuration, a subset of TTIs within the repetition window during which a first repetition of the grant-free downlink transmission may be allowed to be transmitted, where the repetition window includes the subset of TTIs and at least one other TTI, and monitoring for a first repetition of the grant-free downlink transmission during at least one TTI of the subset of TTIs.

(17) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, a redundancy version (RV) index of the first repetition of the grant-free downlink transmission may be zero (0).

(18) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, attempting to decode the grant-free downlink transmission may include operations, features, means, or instructions for identifying a series of redundancy version (RV) indices for the repetition window based on the resource configuration, determining one or more

potential RV indices for each TTI of the repetition window, where each potential RV index for each TTI may be based on the series of RV indices beginning at a respective TTI of the subset of TTIs, and attempting to decode the grant-free downlink transmission during a given TTI of the repetition window based on the one or more potential RV indices for the given TTI.

(19) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, attempting to decode the grant-free downlink transmission may include operations, features, means, or instructions for identifying a series of redundancy version (RV) indices for the repetition window based on the resource configuration, identifying a HARQ process identification (ID) for each TTI of the repetition window, where the HARQ process ID for each TTI may be based on the series of RV indices beginning at a respective TTI of the subset of TTIs, and combining logarithmic likelihood ratios (LLRs) of the grant-free downlink transmission for a given TTI with a previously received signal based on the HARQ process ID.

(20) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for failing to decode the first repetition of the grant-free downlink transmission during an initial TTI of the subset of TTIs, and attempting to decode the first repetition of the grant-free downlink transmission during an immediately subsequent TTI of the subset of TTIs based on failing to decode the first repetition during the initial TTI of the subset of TTIs.

(21) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, monitoring the one or more TTIs of the repetition window for reception of the grant-free downlink transmission may include operations, features, means, or instructions for monitoring for a first repetition of the grant-free downlink transmission during any TTI of the repetition window, where the repetition window includes a set of TTIs.

(22) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, attempting to decode the grant-free downlink transmission may include operations, features, means, or instructions for identifying a series of redundancy version (RV) indices for the repetition window based on the resource configuration, determining one or more potential RV indices for each TTI of the repetition window, where each potential RV index for each TTI may be based on the series of RV indices beginning at any TTI of the repetition window, and attempting to decode the grant-free downlink transmission during a given TTI of the repetition window based on the one or more potential RV indices for the given TTI.

(23) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, attempting to decode the grant-free downlink transmission may include operations, features, means, or instructions for identifying a series of redundancy version (RV) indices for the repetition window based on the resource configuration, identifying a HARQ process identification (ID) for each TTI of the repetition window, where the HARQ process ID for each TTI may be based on the series of RV indices beginning at any TTI of the repetition window, and combining logarithmic likelihood ratios (LLRs) of the grant-free downlink transmission for a given TTI with a previously received signal based on the HARQ process ID.

(24) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for determining that a first decoding hypothesis corresponding to decoding the first repetition of the grant-free downlink transmission during a given TTI of the repetition window may have failed, and attempting to decode a second repetition of the grant-free downlink transmission using a second decoding hypothesis during the given TTI of the repetition window based on the determination that the first decoding hypothesis may have failed.

(25) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for attempting to decode the first repetition of the grant-free downlink transmission using an additional decoding hypothesis during a subsequent TTI of the repetition window based on the determination that the

first decoding hypothesis may have failed.

(26) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for transmitting an indication of a capability of the UE, the capability indicating a maximum repetition window size supported by the UE, a timing within the repetition window for which the UE supports transmission of a first repetition of the grant-free downlink transmission, or combinations of the same.

(27) A method of wireless communication at a base station is described. The method may include transmitting, to a UE, a resource configuration for transmission of a downlink transmission within a repetition window, the resource configuration including an indicator of a repetition window size for the downlink transmission and transmitting the downlink transmission to the UE in accordance with the resource configuration.

(28) An apparatus for wireless communication at a base station is described. The apparatus may include a processor, memory in electronic communication with the processor, and instructions stored in the memory. The instructions may be executable by the processor to cause the apparatus to transmit, to a UE, a resource configuration for transmission of a downlink transmission within a repetition window, the resource configuration including an indicator of a repetition window size for the downlink transmission and transmit the downlink transmission to the UE in accordance with the resource configuration.

(29) Another apparatus for wireless communication at a base station is described. The apparatus may include means for transmitting, to a UE, a resource configuration for transmission of a downlink transmission within a repetition window, the resource configuration including an indicator of a repetition window size for the downlink transmission and transmitting the downlink transmission to the UE in accordance with the resource configuration.

(30) A non-transitory computer-readable medium storing code for wireless communication at a base station is described. The code may include instructions executable by a processor to transmit, to a UE, a resource configuration for transmission of a downlink transmission within a repetition window, the resource configuration including an indicator of a repetition window size for the downlink transmission and transmit the downlink transmission to the UE in accordance with the resource configuration.

(31) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, transmitting the downlink transmission to the UE may include operations, features, means, or instructions for transmitting a first repetition of the downlink transmission during an initial TTI of the repetition window, the first repetition being associated with a first redundancy version (RV) index, and transmitting one or more additional repetitions of the downlink transmission during one or more corresponding subsequent TTIs of the repetition window, each of the one or more additional repetitions being associated with a respective RV index.

(32) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the resource configuration may be transmitted via RRC signaling, the resource configuration further including a series of redundancy version (RV) indices for the repetition window.

(33) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for receiving, from the UE, an indication of a successful decoding of the downlink transmission.

(34) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the downlink transmission may be a grant-free downlink transmission.

(35) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, transmitting the grant-free downlink transmission to the UE may include operations, features, means, or instructions for identifying a subset of transmission time intervals

(TTIs) within the repetition window during which a first repetition of the grant-free downlink transmission may be allowed to be transmitted, where the repetition window includes the subset of TTIs and at least one other TTI, transmitting the first repetition of the grant-free downlink transmission during a TTI of the subset of TTIs, the first repetition being associated with a first redundancy version (RV) index, and transmitting one or more additional repetitions of the grant-free downlink transmission during one or more corresponding subsequent TTIs of the at least one other TTI, each of the one or more additional repetitions being associated with a respective RV index.

(36) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, transmitting the grant-free downlink transmission to the UE may include operations, features, means, or instructions for transmitting a first repetition of the grant-free downlink transmission during any TTI of the repetition window, the first repetition being associated with a first redundancy version (RV) index, and transmitting one or more additional repetitions of the grant-free downlink transmission during one or more corresponding subsequent TTIs of the repetition window, each of the one or more additional repetitions being associated with a respective RV index.

(37) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for receiving, from the UE, an indication of a capability of the UE, where the capability indicates a maximum repetition window size supported by the UE, a timing within the repetition window for which the UE supports transmission of a first repetition of the grant-free downlink transmission, or combinations of the same.

(38) A method of wireless communication at a UE is described. The method may include receiving a resource configuration for reception of a downlink transmission within a repetition window, the resource configuration including an indicator of a repetition window size for the downlink transmission, monitoring, in accordance with the resource configuration, one or more TTIs of the repetition window for reception of the downlink transmission, and attempting to decode the downlink transmission during the one or more TTIs of the repetition window based on the repetition window size.

(39) An apparatus for wireless communication at a UE is described. The apparatus may include a processor, memory in electronic communication with the processor, and instructions stored in the memory. The instructions may be executable by the processor to cause the apparatus to receive a resource configuration for reception of a downlink transmission within a repetition window, the resource configuration including an indicator of a repetition window size for the downlink transmission, monitor, in accordance with the resource configuration, one or more TTIs of the repetition window for reception of the downlink transmission, and attempt to decode the downlink transmission during the one or more TTIs of the repetition window based on the repetition window size.

(40) Another apparatus for wireless communication at a UE is described. The apparatus may include means for receiving a resource configuration for reception of a downlink transmission within a repetition window, the resource configuration including an indicator of a repetition window size for the downlink transmission, means for monitoring, in accordance with the resource configuration, one or more TTIs of the repetition window for reception of the downlink transmission, and means for attempting to decode the downlink transmission during the one or more TTIs of the repetition window based on the repetition window size.

(41) A non-transitory computer-readable medium storing code for wireless communication at a UE is described. The code may include instructions executable by a processor to receive a resource configuration for reception of a downlink transmission within a repetition window, the resource configuration including an indicator of a repetition window size for the downlink transmission, monitor, in accordance with the resource configuration, one or more TTIs of the repetition window

for reception of the downlink transmission, and attempt to decode the downlink transmission during the one or more TTIs of the repetition window based on the repetition window size.

(42) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for monitoring for a first repetition of the downlink transmission in an initial TTI of the repetition window, where the repetition window size may be greater than one TTI.

(43) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for identifying a series of redundancy version (RV) indices for the repetition window based on the resource configuration, each RV index of the series of RV indices associated with a respective TTI of the repetition window, and attempt to decode the downlink transmission during a given TTI of the repetition window based on the RV index associated with the given TTI.

(44) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the downlink transmission may be a grant-free downlink transmission.

(45) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for identifying a potential redundancy version (RV) index and a corresponding HARQ process identification (ID) for the grant-free downlink transmission, where each decoding attempt may be based on a unique pair of potential RV index and corresponding HARQ process ID.

(46) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for determining a TTI index for each of the one or more TTIs of the repetition window, where the corresponding HARQ process ID for a given TTI may be based on the TTI index for the given TTI.

(47) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for identifying, based on the resource configuration, a subset of TTIs within the repetition window during which a first repetition of the grant-free downlink transmission may be allowed to be transmitted, where the repetition window includes the subset of TTIs and at least one other TTI, and monitor for a first repetition of the grant-free downlink transmission during at least one TTI of the subset of TTIs.

(48) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, a redundancy version (RV) index of the first repetition of the grant-free downlink transmission may be zero (0).

(49) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for identifying a series of redundancy version (RV) indices for the repetition window based on the resource configuration, determine one or more potential RV indices for each TTI of the repetition window, where each potential RV index for each TTI may be based on the series of RV indices beginning at a respective TTI of the subset of TTIs, and attempt to decode the grant-free downlink transmission during a given TTI of the repetition window based on the one or more potential RV indices for the given TTI.

(50) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for identifying a series of redundancy version (RV) indices for the repetition window based on the resource configuration, identify a HARQ process identification (ID) for each TTI of the repetition window, where the HARQ process ID for each TTI may be based on the series of RV indices beginning at a respective TTI of the subset of TTIs, and combine logarithmic likelihood ratios (LLRs) of the grant-free downlink transmission for a given TTI with a previously received signal based on the HARQ process ID.

(51) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for failing to

decode the first repetition of the grant-free downlink transmission during an initial TTI of the subset of TTIs, and attempt to decode the first repetition of the grant-free downlink transmission during an immediately subsequent TTI of the subset of TTIs based on failing to decode the first repetition during the initial TTI of the subset of TTIs.

(52) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for monitoring for a first repetition of the grant-free downlink transmission during any TTI of the repetition window, where the repetition window includes a set of TTIs.

(53) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for identifying a series of redundancy version (RV) indices for the repetition window based on the resource configuration, determine one or more potential RV indices for each TTI of the repetition window, where each potential RV index for each TTI may be based on the series of RV indices beginning at any TTI of the repetition window, and attempt to decode the grant-free downlink transmission during a given TTI of the repetition window based on the one or more potential RV indices for the given TTI.

(54) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for identifying a series of redundancy version (RV) indices for the repetition window based on the resource configuration, identify a HARQ process identification (ID) for each TTI of the repetition window, where the HARQ process ID for each TTI may be based on the series of RV indices beginning at any TTI of the repetition window, and combine logarithmic likelihood ratios (LLRs) of the grant-free downlink transmission for a given TTI with a previously received signal based on the HARQ process ID.

(55) A method of wireless communication at a base station is described. The method may include transmitting, to a UE, a resource configuration for transmission of a downlink transmission within a repetition window, the resource configuration including an indicator of a repetition window size for the downlink transmission, and transmitting the downlink transmission to the UE in accordance with the resource configuration.

(56) An apparatus for wireless communication at a base station is described. The apparatus may include a processor, memory in electronic communication with the processor, and instructions stored in the memory. The instructions may be executable by the processor to cause the apparatus to transmit, to a UE, a resource configuration for transmission of a downlink transmission within a repetition window, the resource configuration including an indicator of a repetition window size for the downlink transmission, and transmit the downlink transmission to the UE in accordance with the resource configuration.

(57) Another apparatus for wireless communication at a base station is described. The apparatus may include means for transmitting, to a UE, a resource configuration for transmission of a downlink transmission within a repetition window, the resource configuration including an indicator of a repetition window size for the downlink transmission, and means for transmitting the downlink transmission to the UE in accordance with the resource configuration.

(58) A non-transitory computer-readable medium storing code for wireless communication at a base station is described. The code may include instructions executable by a processor to transmit, to a UE, resource configuration for transmission of a downlink transmission within a repetition window, the resource configuration including an indicator of a repetition window size for the downlink transmission, and transmit the downlink transmission to the UE in accordance with the resource configuration.

(59) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for transmitting a first repetition of the downlink transmission during an initial TTI of the repetition window, the first

repetition being associated with a first redundancy version (RV) index, and transmit one or more additional repetitions of the downlink transmission during one or more corresponding subsequent TTIs of the repetition window, each of the one or more additional repetitions being associated with a respective RV index.

(60) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the downlink transmission may be a grant-free downlink transmission.

(61) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for identifying a subset of transmission time intervals (TTIs) within the repetition window during which a first repetition of the grant-free downlink transmission may be allowed to be transmitted, where the repetition window includes the subset of TTIs and at least one other TTI, transmit the first repetition of the grant-free downlink transmission during a TTI of the subset of TTIs, the first repetition being associated with a first redundancy version (RV) index, and transmit one or more additional repetitions of the grant-free downlink transmission during one or more corresponding subsequent TTIs of the at least one other TTI, each of the one or more additional repetitions being associated with a respective RV index.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 illustrates an example of a wireless communications system that supports downlink transmission in accordance with aspects of the present disclosure.
- (2) FIG. 2 illustrates an example of a wireless communications system that supports downlink transmission in accordance with aspects of the present disclosure.
- (3) FIGS. 3 through 5 illustrate example timing diagrams that support grant-free downlink transmission in accordance with aspects of the present disclosure.
- (4) FIG. 6 illustrates an example of a process flow that supports downlink transmission in accordance with aspects of the present disclosure.
- (5) FIGS. 7 and 8 show block diagrams of a device that supports downlink transmission in accordance with aspects of the present disclosure.
- (6) FIG. 9 illustrates a user equipment (UE) communications manager that supports downlink transmission in accordance with aspects of the present disclosure.
- (7) FIG. 10 illustrates a block diagram of a system including a UE that supports downlink transmission in accordance with aspects of the present disclosure.
- (8) FIGS. 11 and 12 show block diagrams of a device that supports downlink transmission in accordance with aspects of the present disclosure.
- (9) FIG. 13 illustrates a base station communications manager that supports downlink transmission in accordance with aspects of the present disclosure.
- (10) FIG. 14 illustrates a block diagram of a system including a base station that supports downlink transmission in accordance with aspects of the present disclosure.
- (11) FIGS. 15 through 24 illustrate methods for grant-free downlink transmission in accordance with aspects of the present disclosure.

DETAILED DESCRIPTION

(12) Some wireless communications systems may support grant-free uplink transmissions (e.g., to reduce latency associated with scheduling request (SR) transmissions in grant-based uplink schemes). Similarly, grant-free transmission may be supported in the downlink (e.g., which may reduce control overhead associated with scheduling downlink transmissions). For example, the reduced control overhead may benefit low latency communication schemes which employ small packet sizes. In some cases, grant-free transmissions may be associated with increased complexity

of decoding operations (e.g., because such transmissions are not scheduled by a grant and may therefore be associated with some degree of uncertainty in the decoding operation). Techniques are discussed herein to address such complexities. In some cases, aspects of the techniques discussed may be applied to grant-based downlink transmissions.

(13) An example downlink transmission is provided in the context of activation-based transmissions. For activation-based transmissions, some downlink parameters may be set via radio resource control (RRC) configuration, while other parameters may be given by an activating downlink control information (DCI) transmission. By way of example, a hybrid automatic repeat request (HARQ) process identification (ID) and redundancy version (RV) index for each transmission in the activation-based scheme may be known (e.g., either based on DCI or as a function of the transmission time interval (TTI) index). As an example of activation-based transmissions, repetition-based activated downlink transmissions may employ a scheme in which the same transport block is sent (e.g., multiple times) in each repetition window. Based on the DCI and RRC-configured parameters, the HARQ process ID and RV index for each repetition of the transport block in the repetition window may be known. Any re-transmissions (e.g., based on a negative acknowledgement by the receiving device following the repetition window) may be transmitted using a grant-based scheme. In some cases, activation-based transmissions may be repetition-based activated uplink transmissions employing a scheme in which the same transport block is sent in each repetition window.

(14) Alternatively, in an activation-less grant-free downlink transmission scheme, the UE may be configured with a set of parameters via RRC (e.g., time/frequency resources, transport block size (TBS), RV sequence, repetition window size, etc.) without receiving an activating DCI. Thus, the UE may attempt to blindly decode repeated instances of a downlink transmission over the given time/frequency resources (e.g., using different pairs of RV indices and HARQ process IDs) within a given repetition window. Aspects of the present disclosure relate to techniques for determining one or more potential RV indices and HARQ process IDs for each TTI of the repetition window (e.g., rather than searching across all possible pairings). Such techniques may benefit a UE in terms of power consumption, access latency, communication throughput, or the like.

(15) In some cases, a wireless communications system may utilize an activation-less grant-free transmission scheme (e.g., for uplink, downlink, sidelink transmissions), where a receiving device (e.g., a UE, a base station) may be configured with a set of parameters (e.g., time/frequency resources, TBS sizes, RV sequence, repetition window size) without utilizing an activating DCI. Here, the receiving device may blindly decode repeated instances of the transmission over the given time/frequency resources. Here, similar techniques for determining one or more potential RV indices and HARQ process IDs for each TTI of the repetition window discussed herein may be applied to both uplink and downlink transmissions.

(16) Aspects of the disclosure are initially described in the context of a wireless communications system. Aspects of the disclosure are then described in the context of timing diagrams and a process flow. Aspects of the disclosure are further illustrated by and described with reference to apparatus diagrams, system diagrams, and flowcharts that relate to grant-free downlink transmission.

(17) FIG. 1 illustrates an example of a wireless communications system **100** in accordance with various aspects of the present disclosure. The wireless communications system **100** includes base stations **105**, UEs **115**, and a core network **130**. In some examples, the wireless communications system **100** may be a LTE network, an LTE-A network, an LTE-A Pro network, or a new radio (NR) network. In some cases, wireless communications system **100** may support enhanced broadband communications, ultra-reliable (e.g., mission critical) communications, low latency communications, or communications with low-cost and low-complexity devices.

(18) Base stations **105** may wirelessly communicate with UEs **115** via one or more base station antennas. Base stations **105** described herein may include or may be referred to by those skilled in

the art as a base transceiver station, a radio base station, an access point, a radio transceiver, a NodeB, an eNodeB (eNB), a next-generation Node B or giga-nodeB (either of which may be referred to as a gNB), a Home NodeB, a Home eNodeB, or some other suitable terminology. Wireless communications system **100** may include base stations **105** of different types (e.g., macro or small cell base stations). The UEs **115** described herein may be able to communicate with various types of base stations **105** and network equipment including macro eNBs, small cell eNBs, gNBs, relay base stations, and the like.

(19) Each base station **105** may be associated with a particular geographic coverage area **110** in which communications with various UEs **115** is supported. Each base station **105** may provide communication coverage for a respective geographic coverage area **110** via communication links **125**, and communication links **125** between a base station **105** and a UE **115** may utilize one or more carriers. Communication links **125** shown in wireless communications system **100** may include uplink transmissions from a UE **115** to a base station **105**, or downlink transmissions from a base station **105** to a UE **115**. Downlink transmissions may also be called forward link transmissions while uplink transmissions may also be called reverse link transmissions.

(20) The geographic coverage area **110** for a base station **105** may be divided into sectors making up only a portion of the geographic coverage area **110**, and each sector may be associated with a cell. For example, each base station **105** may provide communication coverage for a macro cell, a small cell, a hot spot, or other types of cells, or various combinations thereof. In some examples, a base station **105** may be movable and therefore provide communication coverage for a moving geographic coverage area **110**. In some examples, different geographic coverage areas **110** associated with different technologies may overlap, and overlapping geographic coverage areas **110** associated with different technologies may be supported by the same base station **105** or by different base stations **105**. The wireless communications system **100** may include, for example, a heterogeneous LTE/LTE-A/LTE-A Pro or NR network in which different types of base stations **105** provide coverage for various geographic coverage areas **110**.

(21) The term “cell” refers to a logical communication entity used for communication with a base station **105** (e.g., over a carrier), and may be associated with an identifier for distinguishing neighboring cells (e.g., a physical cell identifier (PCID), a virtual cell identifier (VCID)) operating via the same or a different carrier. In some examples, a carrier may support multiple cells, and different cells may be configured according to different protocol types (e.g., machine-type communication (MTC), narrowband Internet-of-Things (NB-IoT), enhanced mobile broadband (eMBB), or others) that may provide access for different types of devices. In some cases, the term “cell” may refer to a portion of a geographic coverage area **110** (e.g., a sector) over which the logical entity operates.

(22) UEs **115** may be dispersed throughout the wireless communications system **100**, and each UE **115** may be stationary or mobile. A UE **115** may also be referred to as a mobile device, a wireless device, a remote device, a handheld device, or a subscriber device, or some other suitable terminology, where the “device” may also be referred to as a unit, a station, a terminal, or a client. A UE **115** may also be a personal electronic device such as a cellular phone, a personal digital assistant (PDA), a tablet computer, a laptop computer, or a personal computer. In some examples, a UE **115** may also refer to a wireless local loop (WLL) station, an Internet of Things (IoT) device, an Internet of Everything (IoE) device, or an MTC device, or the like, which may be implemented in various articles such as appliances, vehicles, meters, or the like.

(23) Some UEs **115**, such as MTC or IoT devices, may be low cost or low complexity devices, and may provide for automated communication between machines (e.g., via Machine-to-Machine (M2M) communication). M2M communication or MTC may refer to data communication technologies that allow devices to communicate with one another or a base station **105** without human intervention. In some examples, M2M communication or MTC may include communications from devices that integrate sensors or meters to measure or capture information

and relay that information to a central server or application program that can make use of the information or present the information to humans interacting with the program or application. Some UEs **115** may be designed to collect information or enable automated behavior of machines. Examples of applications for MTC devices include smart metering, inventory monitoring, water level monitoring, equipment monitoring, healthcare monitoring, wildlife monitoring, weather and geological event monitoring, fleet management and tracking, remote security sensing, physical access control, and transaction-based business charging.

(24) Some UEs **115** may be configured to employ operating modes that reduce power consumption, such as half-duplex communications (e.g., a mode that supports one-way communication via transmission or reception, but not transmission and reception simultaneously). In some examples half-duplex communications may be performed at a reduced peak rate. Other power conservation techniques for UEs **115** include entering a power saving “deep sleep” mode when not engaging in active communications, or operating over a limited bandwidth (e.g., according to narrowband communications). In some cases, UEs **115** may be designed to support critical functions (e.g., mission critical functions), and a wireless communications system **100** may be configured to provide ultra-reliable communications for these functions.

(25) In some cases, a UE **115** may also be able to communicate directly with other UEs **115** (e.g., using a peer-to-peer (P2P) or device-to-device (D2D) protocol). One or more of a group of UEs **115** utilizing D2D communications may be within the geographic coverage area **110** of a base station **105**. Other UEs **115** in such a group may be outside the geographic coverage area **110** of a base station **105**, or be otherwise unable to receive transmissions from a base station **105**. In some cases, groups of UEs **115** communicating via D2D communications may utilize a one-to-many (1:M) system in which each UE **115** transmits to every other UE **115** in the group. In some cases, a base station **105** facilitates the scheduling of resources for D2D communications. In other cases, D2D communications are carried out between UEs **115** without the involvement of a base station **105**.

(26) Base stations **105** may communicate with the core network **130** and with one another. For example, base stations **105** may interface with the core network **130** through backhaul links **132** (e.g., via an S1 or other interface). Base stations **105** may communicate with one another over backhaul links **134** (e.g., via an X2 or other interface) either directly (e.g., directly between base stations **105**) or indirectly (e.g., via core network **130**).

(27) The core network **130** may provide user authentication, access authorization, tracking, Internet Protocol (IP) connectivity, and other access, routing, or mobility functions. The core network **130** may be an evolved packet core (EPC), which may include at least one mobility management entity (MME), at least one serving gateway (S-GW), and at least one Packet Data Network (PDN) gateway (P-GW). The MME may manage non-access stratum (e.g., control plane) functions such as mobility, authentication, and bearer management for UEs **115** served by base stations **105** associated with the EPC. User IP packets may be transferred through the S-GW, which itself may be connected to the P-GW. The P-GW may provide IP address allocation as well as other functions. The P-GW may be connected to the network operators IP services. The operators IP services may include access to the Internet, Intranet(s), an IP Multimedia Subsystem (IMS), or a Packet-Switched (PS) Streaming Service.

(28) At least some of the network devices, such as a base station **105**, may include subcomponents such as an access network entity, which may be an example of an access node controller (ANC). Each access network entity may communicate with UEs **115** through a number of other access network transmission entities, which may be referred to as a radio head, a smart radio head, or a transmission/reception point (TRP). In some configurations, various functions of each access network entity or base station **105** may be distributed across various network devices (e.g., radio heads and access network controllers) or consolidated into a single network device (e.g., a base station **105**).

(29) Wireless communications system **100** may operate using one or more frequency bands, typically in the range of 300 MHz to 300 GHz. Generally, the region from 300 MHz to 3 GHz is known as the ultra-high frequency (UHF) region or decimeter band, since the wavelengths range from approximately one decimeter to one meter in length. UHF waves may be blocked or redirected by buildings and environmental features. However, the waves may penetrate structures sufficiently for a macro cell to provide service to UEs **115** located indoors. Transmission of UHF waves may be associated with smaller antennas and shorter range (e.g., less than 100 km) compared to transmission using the smaller frequencies and longer waves of the high frequency (HF) or very high frequency (VHF) portion of the spectrum below 300 MHz.

(30) Wireless communications system **100** may also operate in a super high frequency (SHF) region using frequency bands from 3 GHz to 30 GHz, also known as the centimeter band. The SHF region includes bands such as the 5 GHz industrial, scientific, and medical (ISM) bands, which may be used opportunistically by devices that can tolerate interference from other users.

(31) Wireless communications system **100** may also operate in an extremely high frequency (EHF) region of the spectrum (e.g., from 30 GHz to 300 GHz), also known as the millimeter band. In some examples, wireless communications system **100** may support millimeter wave (mmW) communications between UEs **115** and base stations **105**, and EHF antennas of the respective devices may be even smaller and more closely spaced than UHF antennas. In some cases, this may facilitate use of antenna arrays within a UE **115**. However, the propagation of EHF transmissions may be subject to even greater atmospheric attenuation and shorter range than SHF or UHF transmissions. Techniques disclosed herein may be employed across transmissions that use one or more different frequency regions, and designated use of bands across these frequency regions may differ by country or regulating body.

(32) In some cases, wireless communications system **100** may utilize both licensed and unlicensed radio frequency spectrum bands. For example, wireless communications system **100** may employ License Assisted Access (LAA), LTE-Unlicensed (LTE-U) radio access technology, or NR technology in an unlicensed band such as the 5 GHz ISM band. When operating in unlicensed radio frequency spectrum bands, wireless devices such as base stations **105** and UEs **115** may employ listen-before-talk (LBT) procedures to ensure a frequency channel is clear before transmitting data. In some cases, operations in unlicensed bands may be based on a CA configuration in conjunction with CCs operating in a licensed band (e.g., LAA). Operations in unlicensed spectrum may include downlink transmissions, uplink transmissions, peer-to-peer transmissions, or a combination of these. Duplexing in unlicensed spectrum may be based on frequency division duplexing (FDD), time division duplexing (TDD), or a combination of both.

(33) In some examples, base station **105** or UE **115** may be equipped with multiple antennas, which may be used to employ techniques such as transmit diversity, receive diversity, multiple-input multiple-output (MIMO) communications, or beamforming. For example, wireless communications system **100** may use a transmission scheme between a transmitting device (e.g., a base station **105**) and a receiving device (e.g., a UE **115**), where the transmitting device is equipped with multiple antennas and the receiving devices are equipped with one or more antennas. MIMO communications may employ multipath signal propagation to increase the spectral efficiency by transmitting or receiving multiple signals via different spatial layers, which may be referred to as spatial multiplexing. The multiple signals may, for example, be transmitted by the transmitting device via different antennas or different combinations of antennas. Likewise, the multiple signals may be received by the receiving device via different antennas or different combinations of antennas. Each of the multiple signals may be referred to as a separate spatial stream, and may carry bits associated with the same data stream (e.g., the same codeword) or different data streams. Different spatial layers may be associated with different antenna ports used for channel measurement and reporting. MIMO techniques include single-user MIMO (SU-MIMO) where multiple spatial layers are transmitted to the same receiving device, and multiple-user MIMO (MU-

MIMO) where multiple spatial layers are transmitted to multiple devices.

(34) Beamforming, which may also be referred to as spatial filtering, directional transmission, or directional reception, is a signal processing technique that may be used at a transmitting device or a receiving device (e.g., a base station **105** or a UE **115**) to shape or steer an antenna beam (e.g., a transmit beam or receive beam) along a spatial path between the transmitting device and the receiving device. Beamforming may be achieved by combining the signals communicated via antenna elements of an antenna array such that signals propagating at particular orientations with respect to an antenna array experience constructive interference while others experience destructive interference. The adjustment of signals communicated via the antenna elements may include a transmitting device or a receiving device applying certain amplitude and phase offsets to signals carried via each of the antenna elements associated with the device. The adjustments associated with each of the antenna elements may be defined by a beamforming weight set associated with a particular orientation (e.g., with respect to the antenna array of the transmitting device or receiving device, or with respect to some other orientation).

(35) In one example, a base station **105** may use multiple antennas or antenna arrays to conduct beamforming operations for directional communications with a UE **115**. For instance, some signals (e.g., synchronization signals, reference signals, beam selection signals, or other control signals) may be transmitted by a base station **105** multiple times in different directions, which may include a signal being transmitted according to different beamforming weight sets associated with different directions of transmission. Transmissions in different beam directions may be used to identify (e.g., by the base station **105** or a receiving device, such as a UE **115**) a beam direction for subsequent transmission and/or reception by the base station **105**. Some signals, such as data signals associated with a particular receiving device, may be transmitted by a base station **105** in a single beam direction (e.g., a direction associated with the receiving device, such as a UE **115**). In some examples, the beam direction associated with transmissions along a single beam direction may be determined based at least in part on a signal that was transmitted in different beam directions. For example, a UE **115** may receive one or more of the signals transmitted by the base station **105** in different directions, and the UE **115** may report to the base station **105** an indication of the signal it received with a highest signal quality, or an otherwise acceptable signal quality. Although these techniques are described with reference to signals transmitted in one or more directions by a base station **105**, a UE **115** may employ similar techniques for transmitting signals multiple times in different directions (e.g., for identifying a beam direction for subsequent transmission or reception by the UE **115**), or transmitting a signal in a single direction (e.g., for transmitting data to a receiving device).

(36) A receiving device (e.g., a UE **115**, which may be an example of a mmW receiving device) may try multiple receive beams when receiving various signals from the base station **105**, such as synchronization signals, reference signals, beam selection signals, or other control signals. For example, a receiving device may try multiple receive directions by receiving via different antenna subarrays, by processing received signals according to different antenna subarrays, by receiving according to different receive beamforming weight sets applied to signals received at a plurality of antenna elements of an antenna array, or by processing received signals according to different receive beamforming weight sets applied to signals received at a plurality of antenna elements of an antenna array, any of which may be referred to as “listening” according to different receive beams or receive directions. In some examples a receiving device may use a single receive beam to receive along a single beam direction (e.g., when receiving a data signal). The single receive beam may be aligned in a beam direction determined based at least in part on listening according to different receive beam directions (e.g., a beam direction determined to have a highest signal strength, highest signal-to-noise ratio, or otherwise acceptable signal quality based at least in part on listening according to multiple beam directions).

(37) In some cases, the antennas of a base station **105** or UE **115** may be located within one or

more antenna arrays, which may support MIMO operations, or transmit or receive beamforming. For example, one or more base station antennas or antenna arrays may be co-located at an antenna assembly, such as an antenna tower. In some cases, antennas or antenna arrays associated with a base station **105** may be located in diverse geographic locations. A base station **105** may have an antenna array with a number of rows and columns of antenna ports that the base station **105** may use to support beamforming of communications with a UE **115**. Likewise, a UE **115** may have one or more antenna arrays that may support various MIMO or beamforming operations.

(38) In some cases, wireless communications system **100** may be a packet-based network that operate according to a layered protocol stack. In the user plane, communications at the bearer or Packet Data Convergence Protocol (PDCP) layer may be IP-based. A Radio Link Control (RLC) layer may in some cases perform packet segmentation and reassembly to communicate over logical channels. A Medium Access Control (MAC) layer may perform priority handling and multiplexing of logical channels into transport channels. The MAC layer may also use HARQ to provide retransmission at the MAC layer to improve link efficiency. In the control plane, the RRC protocol layer may provide establishment, configuration, and maintenance of an RRC connection between a UE **115** and a base station **105** or core network **130** supporting radio bearers for user plane data. At the Physical (PHY) layer, transport channels may be mapped to physical channels.

(39) In some cases, UEs **115** and base stations **105** may support retransmissions of data to increase the likelihood that data is received successfully. HARQ feedback is one technique of increasing the likelihood that data is received correctly over a communication link **125**. HARQ may include a combination of error detection (e.g., using a cyclic redundancy check (CRC)), forward error correction (FEC), and retransmission (e.g., automatic repeat request (ARQ)). HARQ may improve throughput at the MAC layer in poor radio conditions (e.g., signal-to-noise conditions). In some cases, a wireless device may support same-slot HARQ feedback, where the device may provide HARQ feedback in a specific slot for data received in a previous symbol in the slot. In other cases, the device may provide HARQ feedback in a subsequent slot, or according to some other time interval. In some cases, multiple parallel HARQ processes (e.g., each associated with a respective HARQ process ID) may run concurrently. Each HARQ process may be based on transmissions of different redundancy versions of a transport block (e.g., where the different redundancy versions provide some level of diversity between transmissions, which diversity may be leveraged when combining the redundancy versions to decipher the transport block).

(40) Time intervals in LTE or NR may be expressed in multiples of a basic time unit, which may, for example, refer to a sampling period of $T_{\text{sub.s}} = 1/30,720,000$ seconds. Time intervals of a communications resource may be organized according to radio frames each having a duration of 10 milliseconds (ms), where the frame period may be expressed as $T_{\text{sub.f}} = 307,200 T_{\text{sub.s}}$. The radio frames may be identified by a system frame number (SFN) ranging from 0 to 1023. Each frame may include 10 subframes numbered from 0 to 9, and each subframe may have a duration of 1 ms. A subframe may be further divided into 2 slots each having a duration of 0.5 ms, and each slot may contain 6 or 7 modulation symbol periods (e.g., depending on the length of the cyclic prefix prepended to each symbol period). Excluding the cyclic prefix, each symbol period may contain 2048 sampling periods. In some cases a subframe may be the smallest scheduling unit of the wireless communications system **100**, and may be referred to as a TTI. In other cases, a smallest scheduling unit of the wireless communications system **100** may be shorter than a subframe or may be dynamically selected (e.g., in bursts of shortened TTIs (sTTIs) or in selected component carriers using sTTIs).

(41) In some wireless communications systems, a slot may further be divided into multiple mini-slots containing one or more symbols. In some instances, a symbol of a mini-slot or a mini-slot may be the smallest unit of scheduling. Each symbol may vary in duration depending on the subcarrier spacing or frequency band of operation, for example. Further, some wireless communications systems may implement slot aggregation in which multiple slots or mini-slots are

aggregated together and used for communication between a UE **115** and a base station **105**.

(42) The term “carrier” refers to a set of radio frequency spectrum resources having a defined physical layer structure for supporting communications over a communication link **125**. For example, a carrier of a communication link **125** may include a portion of a radio frequency spectrum band that is operated according to physical layer channels for a given radio access technology. Each physical layer channel may carry user data, control information, or other signaling. A carrier may be associated with a pre-defined frequency channel (e.g., an E-UTRA absolute radio frequency channel number (EARFCN)), and may be positioned according to a channel raster for discovery by UEs **115**. Carriers may be downlink or uplink (e.g., in an FDD mode), or be configured to carry downlink and uplink communications (e.g., in a TDD mode). In some examples, signal waveforms transmitted over a carrier may be made up of multiple sub-carriers (e.g., using multi-carrier modulation (MCM) techniques such as OFDM or DFT-s-OFDM).

(43) The organizational structure of the carriers may be different for different radio access technologies (e.g., LTE, LTE-A, LTE-A Pro, NR, etc.). For example, communications over a carrier may be organized according to TTIs or slots, each of which may include user data as well as control information or signaling to support decoding the user data. A carrier may also include dedicated acquisition signaling (e.g., synchronization signals or system information, etc.) and control signaling that coordinates operation for the carrier. In some examples (e.g., in a carrier aggregation configuration), a carrier may also have acquisition signaling or control signaling that coordinates operations for other carriers.

(44) Physical channels may be multiplexed on a carrier according to various techniques. A physical control channel and a physical data channel may be multiplexed on a downlink carrier, for example, using time division multiplexing (TDM) techniques, frequency division multiplexing (FDM) techniques, or hybrid TDM-FDM techniques. In some examples, control information transmitted in a physical control channel may be distributed between different control regions in a cascaded manner (e.g., between a common control region or common search space and one or more UE-specific control regions or UE-specific search spaces).

(45) A carrier may be associated with a particular bandwidth of the radio frequency spectrum, and in some examples the carrier bandwidth may be referred to as a “system bandwidth” of the carrier or the wireless communications system **100**. For example, the carrier bandwidth may be one of a number of predetermined bandwidths for carriers of a particular radio access technology (e.g., 1.4, 3, 5, 10, 15, 20, 40, or 80 MHz). In some examples, each served UE **115** may be configured for operating over portions or all of the carrier bandwidth. In other examples, some UEs **115** may be configured for operation using a narrowband protocol type that is associated with a predefined portion or range (e.g., set of subcarriers or RBs) within a carrier (e.g., “in-band” deployment of a narrowband protocol type).

(46) In a system employing MCM techniques, a resource element may consist of one symbol period (e.g., a duration of one modulation symbol) and one subcarrier, where the symbol period and subcarrier spacing are inversely related. The number of bits carried by each resource element may depend on the modulation scheme (e.g., the order of the modulation scheme). Thus, the more resource elements that a UE **115** receives and the higher the order of the modulation scheme, the higher the data rate may be for the UE **115**. In MIMO systems, a wireless communications resource may refer to a combination of a radio frequency spectrum resource, a time resource, and a spatial resource (e.g., spatial layers), and the use of multiple spatial layers may further increase the data rate for communications with a UE **115**.

(47) Devices of the wireless communications system **100** (e.g., base stations **105** or UEs **115**) may have a hardware configuration that supports communications over a particular carrier bandwidth, or may be configurable to support communications over one of a set of carrier bandwidths. In some examples, the wireless communications system **100** may include base stations **105** and/or UEs that can support simultaneous communications via carriers associated with more than one different

carrier bandwidth.

(48) Wireless communications system **100** may support communication with a UE **115** on multiple cells or carriers, a feature which may be referred to as carrier aggregation (CA) or multi-carrier operation. A UE **115** may be configured with multiple downlink CCs and one or more uplink CCs according to a carrier aggregation configuration. Carrier aggregation may be used with both FDD and TDD component carriers.

(49) In some cases, wireless communications system **100** may utilize enhanced component carriers (eCCs). An eCC may be characterized by one or more features including wider carrier or frequency channel bandwidth, shorter symbol duration, shorter TTI duration, or modified control channel configuration. In some cases, an eCC may be associated with a carrier aggregation configuration or a dual connectivity configuration (e.g., when multiple serving cells have a suboptimal or non-ideal backhaul link). An eCC may also be configured for use in unlicensed spectrum or shared spectrum (e.g., where more than one operator is allowed to use the spectrum). An eCC characterized by wide carrier bandwidth may include one or more segments that may be utilized by UEs **115** that are not capable of monitoring the whole carrier bandwidth or are otherwise configured to use a limited carrier bandwidth (e.g., to conserve power).

(50) In some cases, an eCC may utilize a different symbol duration than other CCs, which may include use of a reduced symbol duration as compared with symbol durations of the other CCs. A shorter symbol duration may be associated with increased spacing between adjacent subcarriers. A device, such as a UE **115** or base station **105**, utilizing eCCs may transmit wideband signals (e.g., according to frequency channel or carrier bandwidths of 20, 40, 60, 80 MHz, etc.) at reduced symbol durations (e.g., 16.67 microseconds). A TTI in eCC may consist of one or multiple symbol periods. In some cases, the TTI duration (that is, the number of symbol periods in a TTI) may be variable.

(51) Wireless communications systems such as an NR system may utilize any combination of licensed, shared, and unlicensed spectrum bands, among others. The flexibility of eCC symbol duration and subcarrier spacing may allow for the use of eCC across multiple spectrums. In some examples, NR shared spectrum may increase spectrum utilization and spectral efficiency, specifically through dynamic vertical (e.g., across frequency) and horizontal (e.g., across time) sharing of resources.

(52) In accordance with the described techniques, a UE **115** may receive a resource configuration for reception of a downlink transmission (e.g., a grant-free downlink transmission) within a repetition window from a base station **105**. The resource configuration may, for example, include an indicator of a repetition window size for the downlink transmission. The UE **115** may monitor, in accordance with the resource configuration, one or more TTIs of the repetition window for reception of the downlink transmission from the base station **105**. The UE **115** may attempt to decode the downlink transmission during the one or more TTIs of the repetition window based at least in part on the repetition window size. Using the described techniques, the UE **115** may efficiently determine one or more decoding parameters for the downlink transmission, thereby providing benefits in terms of latency reduction, power consumption, etc.

(53) FIG. 2 illustrates an example of a wireless communications system **200** that supports downlink transmission in accordance with various aspects of the present disclosure. In some examples, wireless communications system **200** may implement aspects of wireless communications system **100**. Wireless communications system **200** includes base station **105-a**, UE **115-a**, and UE **115-b**, each of which may be an example of the corresponding device described with reference to wireless communications system **100**.

(54) As illustrated, base station **105-a** may be in communication with UE **115-a** via wireless link **205-a** and may be in communication with UE **115-b** via wireless link **205-b**. In some examples, wireless link **205-a** and/or wireless link **205-b** may support grant-free downlink transmissions. For example, wireless link **205-a** may support URLLC for UE **115-a**. In some cases, base station **105-a**

may configure UE **115-a** with one or more parameters via higher layer signaling (e.g., RRC signaling). For example, the parameters may include one or more of time/frequency resources associated with a given repetition window, a TBS for transmissions within the repetition window, a number of TTIs in the repetition window (i.e., a repetition window size), a RV sequence, and the like. Thus, UE **115-a** may support activation-less, repetition-based downlink transmissions as described herein. Additionally or alternatively, base station **105-a** may configure UE **115-b** with one or more parameters via higher layer signaling (e.g., RRC signaling). One or more parameters for UE **115-b** may be the same as the parameters for UE **115-a**, or each UE **115** may receive a unique set of parameters. By way of example, and as described further below, each of UE **115-a** and UE **115-b** may indicate a maximum supported repetition window size (e.g., in a capability report), and the respective repetition window sizes for each UE **115** may be based on the maximum supported repetition window sizes.

(55) In some examples, information for multiple UEs **115** may be multiplexed on the time/frequency resources associated with the repetition window for UE **115-a**. Because a transmission intended for UE **115-a** within the repetition window may not be triggered (e.g., by a DCI transmission), UE **115-a** may employ one or more of the techniques described herein to determine a HARQ process ID, a RV index, etc. for a transmission received within the repetition window.

(56) As a first example, the repetition window size for UE **115-a** may be one TTI (i.e., repetition-based transmission may not be configured). In some cases of the first example, HARQ re-transmissions may therefore be enabled. In each TTI (e.g., or in the TTIs configured by the RRC signaling), UE **115-a** may attempt to blindly decode a transmission, such as a physical downlink shared channel (PDSCH) transmission. For example, the blind decoding may be based on iteratively applying potential pairings of HARQ process IDs and RV indices. That is, in each TTI UE **115-a** may attempt to decode the PDSCH transmission assuming it is a first transmission (i.e., having a first RV index in the RV sequence configured by the RRC signaling and a HARQ process ID given by the TTI index). If this decoding attempt fails, UE **115-a** may try decoding the PDSCH transmission assuming it is a subsequent transmission (i.e., having a subsequent RV index in the RV sequence configured by the RRC signaling). Thus, UE **115-a** may attempt to combine the logarithmic likelihood ratios (LLRs) for the PDSCH transmission with any pending HARQ processes received some defined number of TTIs prior to the current TTI (e.g., which may be based on some pre-determined rule or negotiated between UE **115-a** and base station **105-a**). By way of example, UE **115-a** may expect to receive any retransmissions of a transport block received in a prior TTI in a given TTI that occurs after some predetermined (e.g., configured) time has elapsed. Thus, upon failing to decode the PDSCH transmission using a first RV index hypothesis (e.g., based on the RV sequence received in the RRC configuration), the UE **115-a** may apply (e.g., iteratively) other candidate RV indices (e.g., and HARQ process IDs) based on a given periodicity associated with the HARQ retransmission process. Alternatively, the HARQ re-transmissions may be sent with a grant (e.g., a DCI transmission), which may address various complications of the scheme described herein. However, aspects of the scheme described herein may apply to repetition-based transmission schemes, as discussed with reference to FIGS. **3**, **4**, and **5**.

(57) FIG. **3** illustrates an example of a timing diagram **300** that supports downlink transmission in accordance with various aspects of the present disclosure. In some examples, timing diagram **300** may implement aspects of wireless communication system **100**.

(58) Timing diagram **300** contains a plurality of TTIs **310**, some of which may be grouped into repetition windows **305**. In the present example, each repetition window **305** contains four (4) TTIs **310**, though it is to be understood that other numbers of TTIs **310** may be included in each repetition window **305** (e.g., based on some UE-indicated capability) without deviating from the scope of the present disclosure. Similarly, while repetition window **305-a** and repetition window **305-b** are illustrated as being adjacent in time, it is to be understood that in some cases, the

repetition windows **305** may occur with a given periodicity (e.g., one or more TTIs **310** may separate repetition window **305-a** and repetition window **305-b**) without deviating from the scope of the present disclosure.

(59) Within repetition window **305-a**, the same transport block may be sent multiple times (e.g., with different RVs). Repetition window **305-a** may thus employ a RV sequence (e.g., configured via RRC signaling) for each TTI **310**. By way of example, the RV sequence may be [0, 2, 3, 1] such that RV 0 is sent in TTI **310-a**, RV 2 is sent in TTI **310-b**, RV 3 is sent in TTI **310-c**, and RV 1 is sent in TTI **310-d**. In the case that repetition window **305-a** contains more than four (4) TTIs **310**, the RV sequence (or a portion thereof) may repeat. Thus, a UE **115** monitoring resources of repetition window **305-a** may only expect to receive a new transport block (e.g., RV 0) during TTI **310-a**.

(60) In some cases, the TTIs **310** may be transmitted within a grant-free downlink transmission. The UE **115** may therefore infer both the HARQ process ID (e.g., based on the TTI index of TTI **310-a**) and RV index (e.g., based on the RV sequence applied to the TTIs **310** of repetition window **305**). Here, the index of the first TTI **310-a** may indicate (e.g., implicitly) a HARQ process ID. For example, a receiver (e.g., UE **115**, base station **105**) may perform blind decodes based on the RV sequence applied to the TTIs **310** and then determine the index of the first TTI **310-a**. Based on the index of TTI **310-a**, the receiver may then determine the HARQ process ID. Accordingly, the number of blind decoding attempts for each TTI **310** may be reduced compared to the search described with reference to FIG. 2 (e.g., only one decoding hypothesis may be attempted for each TTI **310**). In some other cases, the TTIs **310** may be transmitted within a grant-based downlink transmission. The receiver may know (e.g., based on DCI signaling from a base station) the HARQ process ID and RV index.

(61) FIG. 4 illustrates an example of a timing diagram **400** that supports downlink transmission in accordance with various aspects of the present disclosure. In some examples, timing diagram **400** may implement aspects of wireless communication system **100**. Timing diagram **400** contains a plurality of TTIs **410**, some of which may be grouped into repetition window **405**. In the present example, repetition window **405** contains six (6) TTIs **410**, though it is to be understood that other numbers of TTIs **410** may be included in repetition window **405** (e.g., based on some UE-indicated capability) without deviating from the scope of the present disclosure.

(62) Within repetition window **405**, the same transport block may be sent multiple times (e.g., with different RVs). In accordance with the present disclosure, a subset of the TTIs **410** in repetition window **405** may contain a new transport block (e.g., having RV 0). By way of example, the new transport block may be contained in TTI **410-a** or TTI **410-b** (e.g., but not TTI **410-c**). Thus, a UE **115** may attempt to blindly decode a PDSCH transmission in TTI **410-a** using a first RV index in a RV sequence received via RRC configuration and a HARQ process ID given by an index of TTI **410-a**. If the decoding attempt is successful, the UE **115** may subsequently attempt to decode a second repetition of the transport block (e.g., having a second RV index in the RV sequence received via RRC signaling) in a second TTI **410** of timing alignment **415-a**. Alternatively (e.g., if the decoding attempt for the first RV index at TTI **410-a** and the decoding attempt for the second RV index at the second TTI **410** of repetition window **405**), the UE **115** may attempt to blindly decode the PDSCH transmission in TTI **410-b** using the first RV index (e.g., assuming that the PDSCH transmission is sent according to timing alignment **415-b**). If this decoding attempt fails, the UE **115** may attempt to blindly decode the PDSCH transmission in TTI **410-b** using the third RV index in the RV sequence (e.g., assuming that the PDSCH transmission is sent according to timing alignment **415-a** despite the previously failed decoding attempts, which may be due to interference, lack of signal, etc.).

(63) FIG. 5 illustrates an example of a timing diagram **500** that supports downlink transmission in accordance with various aspects of the present disclosure. In some examples, timing diagram **500** may implement aspects of wireless communication system **100**. Timing diagram **500** contains a

plurality of TTIs **510**, some of which may be grouped into repetition window **505**. In the present example, repetition window **505** contains six (6) TTIs **510**, though it is to be understood that other numbers of TTIs **510** may be included in repetition window **505** (e.g., based on some UE-indicated capability) without deviating from the scope of the present disclosure.

(64) Within repetition window **405**, the same transport block may be sent multiple times (e.g., with different RVs). In accordance with the present disclosure, each TTI **510** in repetition window **505** may contain a new transport block (e.g., having RV **0**). By way of example, the new transport block may be contained in TTI **510-a** (e.g., as illustrated by timing alignment **515-a**), TTI **510-b** (e.g., as illustrated by timing alignment **515-b**), TTI **510-c** (e.g., as illustrated by timing alignment **515-c**), etc. Thus, a UE **115** may attempt to blindly decode a PDSCH transmission in TTI **510-a** using a first RV index in a RV sequence received via RRC configuration and a HARQ process ID given by an index of TTI **510-a**. If the decoding attempt is successful, the UE **115** may subsequently attempt to decode a second transport block (e.g., corresponding to timing alignment **515-b** or timing alignment **515-c**) in TTI **510-b**.

(65) Alternatively (e.g., if the decoding attempt for the first RV index at TTI **510-a** is unsuccessful), the UE **115** may attempt to decode the PDSCH transmission in TTI **510-b** using the first RV index (e.g., assuming that the PDSCH transmission is sent according to timing alignment **515-b**) and the HARQ process ID corresponding to TTI **510-b**. If this decoding attempt fails, the UE **115** may attempt to blindly decode the PDSCH transmission in TTI **510-b** using the second RV index in the RV sequence (e.g., assuming that the PDSCH transmission is sent according to timing alignment **515-b**) and the HARQ process ID corresponding to TTI **510-a**. Similarly, if these decoding attempts fail, the UE **115** may attempt to decode the PDSCH transmission in TTI **510-c** according to timing alignment **515-c** (e.g., using the first RV index and the HARQ process ID corresponding to TTI **510-c**), followed by timing alignment **515-b** (e.g., using the second RV index and the HARQ process ID corresponding to TTI **510-b**), followed by timing alignment **515-a** (e.g., using the third RV index and the HARQ process ID corresponding to TTI **510-c**). The decoding attempts may be performed in a different order (e.g., the UE **115** may attempt to decode the PDSCH transmission in TTI **510-c** according to timing alignment **515-a** before attempting to decode the PDSCH transmission according to timing alignment **515-b**) without deviating from the scope of the present disclosure.

(66) Thus, in some cases, as the size of repetition window **505** increases, the UE **115** may experience a corresponding increase in blind decoding attempts (e.g., for TTIs **510** later in the repetition window **505**) based on the additional potential timing alignment **515** introduced at each TTI **510**. Accordingly, there may in some cases be a repetition window **505** threshold (e.g., above which grant-based downlink transmissions may be performed and below which grant-free downlink transmissions may be performed). As discussed herein, the length of the repetition window **505** may in some cases be an example of a UE **115** capability (e.g., which may be conveyed via RRC signaling or otherwise communicated to a base station **105**).

(67) FIG. **6** illustrates an example of a process flow **600** that supports downlink transmission in accordance with various aspects of the present disclosure. In some examples, process flow **600** may implement aspects of wireless communication system **100**. For example, process flow **600** includes base station **105-b** and UE **115-c**, each of which may be an example of the corresponding devices described with reference to FIGS. **1** and **2**.

(68) At **605**, base station **105-b** may transmit (e.g., and UE **115-c** may receive) a resource configuration for reception of a grant-free downlink transmission within a repetition window. For example, the resource configuration may include an indicator of a repetition window size for the grant-free downlink transmission. Additionally or alternatively, the resource configuration may include a series of RV indices (i.e., a RV sequence), a TBS, time/frequency resources associated with the repetition window, etc. In some cases, the resource configuration may be sent via RRC signaling. In some examples, the repetition window size may be based at least in part on a

capability of UE **115-c** (e.g., which may be communicated to base station **105-b** prior to **605**). For example, the capability may indicate a maximum repetition window size supported by UE **115-c**, a timing within the repetition window for which UE **115-c** supports transmission of a first repetition of the grant-free downlink transmission (e.g., where possible different timings for the first repetition are discussed with reference to FIG. 3, FIG. 4, and FIG. 5), or combinations of the same.

(69) At **610**, UE **115-c** may monitor, in accordance with the resource configuration, one or more TTIs of the repetition window for reception of the grant-free downlink transmission. For example, UE **115-c** may monitor for a first repetition of the grant-free downlink transmission in an initial TTI of the repetition window (e.g., as described with reference to FIG. 3). Additionally or alternatively, UE **115-c** may identify, based at least in part on the resource configuration, a subset of TTIs within the repetition window during which the grant-free downlink transmission is allowed to be transmitted and monitor for a first repetition of the grant-free downlink transmission during at least one TTI of the subset of TTIs (e.g., as described with reference to FIG. 4). Additionally or alternatively, UE **115-c** may monitor for a first repetition of the grant-free downlink transmission during any TTI of the repetition window (e.g., as described with reference to FIG. 5).

(70) At **615**, UE **115-c** may attempt to decode the grant-free downlink transmission during the one or more TTIs of the repetition window based at least in part on the repetition window size. For example, UE **115-c** may identify a potential RV index and a corresponding HARQ process ID for the grant-free downlink transmission, where each decoding attempt is based on a unique pair of potential RV index and corresponding HARQ process ID. In some cases, UE **115-c** may determine a TTI index for each of the one or more TTIs of the repetition window, where the corresponding HARQ process ID for a given TTI is based at least in part on the TTI index for the given TTI. In some cases, UE **115-c** may identify a series of RV indices for the repetition window based at least in part on the resource configuration, each RV index of the series of RV indices associated with a respective TTI of the repetition window and attempt to decode the grant-free downlink transmission during a given TTI of the repetition window based at least in part on the RV index associated with the given TTI (e.g., as described with reference to FIG. 3).

(71) Additionally or alternatively, at **615**, UE **115-c** may identify a series of RV indices for the repetition window based at least in part on the resource configuration, determine one or more potential RV indices for each TTI of the repetition window, where each potential RV index for each TTI is based at least in part on the series of RV indices beginning at a respective TTI of the subset of TTIs, and attempt to decode the grant-free downlink transmission during a given TTI of the repetition window based at least in part on the one or more potential RV indices for the given TTI (e.g., as described with reference to FIG. 4). For example, UE **115-c** may fail to decode the first repetition of the grant-free downlink transmission during an initial TTI of the subset of TTIs and attempt to decode the first repetition of the grant-free downlink transmission during an immediately subsequent TTI of the subset of TTIs based at least in part on failing to decode the first repetition during the initial TTI of the subset of TTIs (e.g., as described with reference to FIG. 4).

(72) Additionally or alternatively, at **615**, UE **115-c** may identifying a series of RV indices for the repetition window based at least in part on the resource configuration, determine one or more potential RV indices for each TTI of the repetition window, where each potential RV index for each TTI is based at least in part on the series of RV indices beginning at any TTI of the repetition window, and attempt to decode the grant-free downlink transmission during a given TTI of the repetition window based at least in part on the one or more potential RV indices for the given TTI (e.g., as described with reference to FIG. 5). For example, UE **115-c** may determine that a first decoding hypothesis corresponding to decoding the first repetition of the grant-free downlink transmission during a given TTI of the repetition window has failed and attempt to decode a second repetition of the grant-free downlink transmission using a second decoding hypothesis during the given TTI of the repetition window based at least in part on the determination that the first decoding hypothesis has failed (e.g., as described with reference to FIG. 5). In some cases, UE **115-**

c may attempt to decode the first repetition of the grant-free downlink transmission using an additional decoding hypothesis during a subsequent TTI of the repetition window based at least in part on the determination that the first decoding hypothesis has failed (e.g., as described with reference to FIG. 5).

(73) At **620**, base station **105-b** may transmit the grant-free downlink transmission to the UE in accordance with the resource configuration. In some cases, base station **105-b** may transmit a first repetition of the grant-free downlink transmission during an initial TTI of the repetition window, the first repetition being associated with a first RV index and transmit one or more additional repetitions of the grant-free downlink transmission during one or more corresponding subsequent TTIs of the repetition window, each of the one or more additional repetitions being associated with a respective RV index (e.g., as described with reference to FIG. 3). In some cases, base station **105-b** may identify a subset of TTIs within the repetition window during which a first repetition of the grant-free downlink transmission is allowed to be transmitted, where the repetition window includes the subset of TTIs and at least one other TTI, transmit the first repetition of the grant-free downlink transmission during a TTI of the subset of TTIs, the first repetition being associated with a first RV index, and transmit one or more additional repetitions of the grant-free downlink transmission during one or more corresponding subsequent TTIs of the at least one other TTI, each of the one or more additional repetitions being associated with a respective RV index (e.g., as described with reference to FIG. 4). In some cases, base station **105-b** may transmit a first repetition of the grant-free downlink transmission during any TTI of the repetition window, the first repetition being associated with a first RV index and transmit one or more additional repetitions of the grant-free downlink transmission during one or more corresponding subsequent TTIs of the repetition window, each of the one or more additional repetitions being associated with a respective RV index (e.g., as described with reference to FIG. 5). Thus, in some cases the operations at **620** (i.e., the transmission(s) from base station **105-b**) may overlap in time with the operations at **615** (i.e., the decoding attempt(s) at UE **115-c**).

(74) At **625**, UE **115-c** may optionally transmit (e.g., and base station **105-b** may receive) an indication (e.g., an acknowledgment (ACK)) that the grant-free downlink transmission was successfully decoded (e.g., after a conclusion of the repetition window).

(75) FIG. 7 shows a block diagram **700** of a wireless device **705** that supports downlink transmission in accordance with aspects of the present disclosure. Wireless device **705** may be an example of aspects of a UE **115** as described herein. Wireless device **705** may include receiver **710**, UE communications manager **715**, and transmitter **720**. Wireless device **705** may also include a processor. Each of these components may be in communication with one another (e.g., via one or more buses).

(76) Receiver **710** may receive information such as packets, user data, or control information associated with various information channels (e.g., control channels, data channels, and information related to grant-free downlink transmission, etc.). Information may be passed on to other components of the device. The receiver **710** may be an example of aspects of the transceiver **1035** described with reference to FIG. 10. The receiver **710** may utilize a single antenna or a set of antennas.

(77) UE communications manager **715** may be an example of aspects of the UE communications manager **1015** described with reference to FIG. 10. UE communications manager **715** and/or at least some of its various sub-components may be implemented in hardware, software executed by a processor, firmware, or any combination thereof. If implemented in software executed by a processor, the functions of the UE communications manager **715** and/or at least some of its various sub-components may be executed by a general-purpose processor, a digital signal processor (DSP), an application-specific integrated circuit (ASIC), an field-programmable gate array (FPGA) or other programmable logic device, discrete gate or transistor logic, discrete hardware components, or any combination thereof designed to perform the functions described in the present disclosure.

(78) UE communications manager **715** and/or at least some of its various sub-components may be physically located at various positions, including being distributed such that portions of functions are implemented at different physical locations by one or more physical devices. In some examples, UE communications manager **715** and/or at least some of its various sub-components may be a separate and distinct component in accordance with various aspects of the present disclosure. In other examples, UE communications manager **715** and/or at least some of its various sub-components may be combined with one or more other hardware components, including but not limited to an I/O component, a transceiver, a network server, another computing device, one or more other components described in the present disclosure, or a combination thereof in accordance with various aspects of the present disclosure.

(79) UE communications manager **715** may receive a resource configuration for reception of a downlink transmission within a repetition window, the resource configuration including an indicator of a repetition window size for the downlink transmission. UE communications manager **715** may monitor, in accordance with the resource configuration, one or more TTIs of the repetition window for reception of the downlink transmission. UE communications manager **715** may attempt to decode the downlink transmission during the one or more TTIs of the repetition window based on the repetition window size.

(80) Transmitter **720** may transmit signals generated by other components of the device. In some examples, the transmitter **720** may be collocated with a receiver **710** in a transceiver module. For example, the transmitter **720** may be an example of aspects of the transceiver **1035** described with reference to FIG. **10**. The transmitter **720** may utilize a single antenna or a set of antennas.

(81) FIG. **8** shows a block diagram **800** of a wireless device **805** that supports downlink transmission in accordance with aspects of the present disclosure. Wireless device **805** may be an example of aspects of a wireless device **705** or a UE **115** as described with reference to FIG. **7**. Wireless device **805** may include receiver **810**, UE communications manager **815**, and transmitter **820**. Wireless device **805** may also include a processor. Each of these components may be in communication with one another (e.g., via one or more buses). UE communications manager **815** may be an example of aspects of the UE communications manager **1015** described with reference to FIG. **10**. UE communications manager **815** may also include configuration manager **825**, resource monitoring controller **830**, and decoding manager **835**.

(82) Receiver **810** may receive information such as packets, user data, or control information associated with various information channels (e.g., control channels, data channels, and information related to grant-free downlink transmission, etc.). Information may be passed on to other components of the device. The receiver **810** may be an example of aspects of the transceiver **1035** described with reference to FIG. **10**. The receiver **810** may utilize a single antenna or a set of antennas.

(83) Configuration manager **825** may receive a resource configuration for reception of a downlink transmission within a repetition window, the resource configuration including an indicator of a repetition window size for the downlink transmission. In some cases, the resource configuration is received via RRC signaling. In some cases, the resource configuration includes a series of RV indices for repeated transmissions of the downlink transmission within the repetition window, a TBS, an indication of time/frequency resources, or combinations thereof.

(84) Resource monitoring controller **830** may monitor, in accordance with the resource configuration, one or more TTIs of the repetition window for reception of the downlink transmission. In some cases, monitoring the one or more TTIs of the repetition window for reception of the downlink transmission includes identifying, based on the resource configuration, a subset of TTIs within the repetition window during which a first repetition of the downlink transmission, which may be a grant-free downlink transmission, is allowed to be transmitted, where the repetition window includes the subset of TTIs and at least one other TTI. For example, resource monitoring controller **830** may monitor for a first repetition of the grant-free downlink transmission

during at least one TTI of the subset of TTIs. In some cases, monitoring the one or more TTIs of the repetition window for reception of the grant-free downlink transmission includes monitoring for a first repetition of the grant-free downlink transmission during any TTI of the repetition window, where the repetition window includes multiple TTIs. In some cases, monitoring the one or more TTIs of the repetition window for reception of the grant-free downlink transmission includes monitoring for a first repetition of the grant-free downlink transmission in an initial TTI of the repetition window, where the repetition window size is greater than one TTI.

(85) Decoding manager **835** may attempt to decode the downlink transmission during the one or more TTIs of the repetition window based on the repetition window size. In some cases, attempting to decode the downlink transmission, which may be a grant-free downlink transmission, includes identifying a series of RV indices for the repetition window based on the resource configuration. In some cases, each RV index of the series of RV indices is associated with a respective TTI of the repetition window. In some cases, attempting to decode the grant-free downlink transmission includes identifying a potential RV index and a corresponding HARQ process ID for the grant-free downlink transmission, where each decoding attempt is based on a unique pair of potential RV index and corresponding HARQ process ID. In some cases, identifying the potential RV index and the corresponding HARQ process ID for the grant-free downlink transmission includes determining a TTI index for each of the one or more TTIs of the repetition window, where the corresponding HARQ process ID for a given TTI is based on the TTI index for the given TTI.

(86) Decoding manager **835** may determine one or more potential RV indices for each TTI of the repetition window, where each potential RV index for each TTI is based on the series of RV indices beginning at a respective TTI of the subset of TTIs. Decoding manager **835** may determine one or more potential RV indices for each TTI of the repetition window, where each potential RV index for each TTI is based on the series of RV indices beginning at any TTI of the repetition window. Decoding manager **835** may attempt to decode the grant-free downlink transmission during a given TTI of the repetition window based on the one or more potential RV indices for the given TTI.

(87) Decoding manager **835** may determine that a first decoding hypothesis corresponding to decoding the first repetition of the downlink transmission during a given TTI of the repetition window has failed. Decoding manager **835** may attempt to decode a second repetition of the downlink transmission, which may be a grant-free downlink transmission, using a second decoding hypothesis during the given TTI of the repetition window based on the determination that the first decoding hypothesis has failed. Decoding manager **835** may attempt to decode the first repetition of the grant-free downlink transmission using an additional decoding hypothesis during a subsequent TTI of the repetition window based on the determination that the first decoding hypothesis has failed. Decoding manager **835** may attempt to decode the first repetition of the grant-free downlink transmission during an immediately subsequent TTI of the subset of TTIs based on failing to decode the first repetition during the initial TTI of the subset of TTIs. Decoding manager **835** may transmit an indication that the downlink transmission was successfully decoded.

(88) Decoding manager **835** may identify a series of RV indices for the repetition window based at least in part on the resource configuration. Decoding manager **835** may identify a HARQ process ID for each TTI of the repetition window, where the HARQ process ID for each TTI is based at least in part on the series of RV indices beginning at a respective TTI of the subset of TTIs. Decoding manager **835** may combine LLRs of the grant-free downlink transmission for a given TTI with a previously received signal based at least in part on the HARQ process ID. Decoding manager **835** may identify a HARQ process ID for each TTI of the repetition window, where the HARQ process ID for each TTI is based at least in part on the series of RV indices beginning at any TTI of the repetition window. Decoding manager **835** may combine LLRs of the grant-free downlink transmission for a given TTI with a previously received signal based at least in part on the HARQ process ID.

(89) Transmitter **820** may transmit signals generated by other components of the device. In some

examples, the transmitter **820** may be collocated with a receiver **810** in a transceiver module. For example, the transmitter **820** may be an example of aspects of the transceiver **1035** described with reference to FIG. **10**. The transmitter **820** may utilize a single antenna or a set of antennas.

(90) FIG. **9** shows a block diagram **900** of a UE communications manager **915** that supports downlink transmission in accordance with aspects of the present disclosure. The UE communications manager **915** may be an example of aspects of a UE communications manager **715**, a UE communications manager **815**, or a UE communications manager **1015** described with reference to FIGS. **7**, **8**, and **10**. The UE communications manager **915** may include configuration manager **920**, resource monitoring controller **925**, decoding manager **930**, and capability manager **935**. Each of these modules may communicate, directly or indirectly, with one another (e.g., via one or more buses).

(91) Configuration manager **920** may receive a resource configuration for reception of a downlink transmission within a repetition window, the resource configuration including an indicator of a repetition window size for the downlink transmission. In some cases, the resource configuration is received via RRC signaling. In some cases, the resource configuration includes a series of RV indices for repeated transmissions of the downlink transmission within the repetition window, a TBS, an indication of time/frequency resources, or combinations thereof.

(92) Resource monitoring controller **925** may monitor, in accordance with the resource configuration, one or more TTIs of the repetition window for reception of the downlink transmission. In some cases, monitoring the one or more TTIs of the repetition window for reception of the downlink transmission, which may be a grant-free downlink transmission, includes identifying, based on the resource configuration, a subset of TTIs within the repetition window during which a first repetition of the grant-free downlink transmission is allowed to be transmitted, where the repetition window includes the subset of TTIs and at least one other TTI. For example, resource monitoring controller **925** may monitor for a first repetition of the grant-free downlink transmission during at least one TTI of the subset of TTIs. In some cases, monitoring the one or more TTIs of the repetition window for reception of the grant-free downlink transmission includes monitoring for a first repetition of the grant-free downlink transmission during any TTI of the repetition window, where the repetition window includes multiple TTIs. In some cases, monitoring the one or more TTIs of the repetition window for reception of the downlink transmission includes monitoring for a first repetition of the downlink transmission in an initial TTI of the repetition window, where the repetition window size is greater than one TTI.

(93) Decoding manager **930** may attempt to decode the downlink transmission during the one or more TTIs of the repetition window based on the repetition window size. In some cases, attempting to decode the downlink transmission, which may be a grant-free downlink transmission, includes identifying a series of RV indices for the repetition window based on the resource configuration. In some cases, each RV index of the series of RV indices is associated with a respective TTI of the repetition window. In some cases, attempting to decode the grant-free downlink transmission includes identifying a potential RV index and a corresponding HARQ process ID for the grant-free downlink transmission, where each decoding attempt is based on a unique pair of potential RV index and corresponding HARQ process ID. In some cases, identifying the potential RV index and the corresponding HARQ process ID for the grant-free downlink transmission includes determining a TTI index for each of the one or more TTIs of the repetition window, where the corresponding HARQ process ID for a given TTI is based on the TTI index for the given TTI.

(94) Decoding manager **930** may determine one or more potential RV indices for each TTI of the repetition window, where each potential RV index for each TTI is based on the series of RV indices beginning at a respective TTI of the subset of TTIs. Decoding manager **930** may determine one or more potential RV indices for each TTI of the repetition window, where each potential RV index for each TTI is based on the series of RV indices beginning at any TTI of the repetition window. Decoding manager **930** may attempt to decode the grant-free downlink transmission during a given

TTI of the repetition window based on the one or more potential RV indices for the given TTI.

(95) Decoding manager **930** may determine that a first decoding hypothesis corresponding to decoding the first repetition of the grant-free downlink transmission during a given TTI of the repetition window has failed. Decoding manager **930** may attempt to decode a second repetition of the grant-free downlink transmission using a second decoding hypothesis during the given TTI of the repetition window based on the determination that the first decoding hypothesis has failed. Decoding manager **930** may attempt to decode the first repetition of the grant-free downlink transmission using an additional decoding hypothesis during a subsequent TTI of the repetition window based on the determination that the first decoding hypothesis has failed. Decoding manager **930** may attempt to decode the first repetition of the grant-free downlink transmission during an immediately subsequent TTI of the subset of TTIs based on failing to decode the first repetition during the initial TTI of the subset of TTIs. Decoding manager **930** may transmit an indication that the downlink transmission was successfully decoded.

(96) Decoding manager **930** may identify a series of RV indices for the repetition window based at least in part on the resource configuration. Decoding manager **930** may identify a HARQ process ID for each TTI of the repetition window, where the HARQ process ID for each TTI is based at least in part on the series of RV indices beginning at a respective TTI of the subset of TTIs. Decoding manager **930** may combine LLRs of the grant-free downlink transmission for a given TTI with a previously received signal based at least in part on the HARQ process ID. Decoding manager **930** may identify a HARQ process ID for each TTI of the repetition window, where the HARQ process ID for each TTI is based at least in part on the series of RV indices beginning at any TTI of the repetition window. Decoding manager **930** may combine LLRs of the grant-free downlink transmission for a given TTI with a previously received signal based at least in part on the HARQ process ID.

(97) Capability manager **935** may transmit an indication of a capability of the UE, the capability indicating a maximum repetition window size supported by the UE, a timing within the repetition window for which the UE supports transmission of a first repetition of the grant-free downlink transmission, or combinations of the same.

(98) FIG. **10** shows a diagram of a system **1000** including a device **1005** that supports downlink transmission in accordance with aspects of the present disclosure. Device **1005** may be an example of or include the components of wireless device **705**, wireless device **805**, or a UE **115** as described herein, e.g., with reference to FIGS. **7** and **8**. Device **1005** may include components for bi-directional voice and data communications including components for transmitting and receiving communications, including UE communications manager **1015**, processor **1020**, memory **1025**, software **1030**, transceiver **1035**, antenna **1040**, and I/O controller **1045**. These components may be in electronic communication via one or more buses (e.g., bus **1010**). Device **1005** may communicate wirelessly with one or more base stations **105**.

(99) Processor **1020** may include an intelligent hardware device, (e.g., a general-purpose processor, a DSP, a central processing unit (CPU), a microcontroller, an ASIC, an FPGA, a programmable logic device, a discrete gate or transistor logic component, a discrete hardware component, or any combination thereof). In some cases, processor **1020** may be configured to operate a memory array using a memory controller. In other cases, a memory controller may be integrated into processor **1020**. Processor **1020** may be configured to execute computer-readable instructions stored in a memory to perform various functions (e.g., functions or tasks supporting grant-free downlink transmission).

(100) Memory **1025** may include random access memory (RAM) and read only memory (ROM). The memory **1025** may store computer-readable, computer-executable software **1030** including instructions that, when executed, cause the processor to perform various functions described herein. In some cases, the memory **1025** may contain, among other things, a basic input/output system (BIOS) which may control basic hardware or software operation such as the interaction with

peripheral components or devices.

(101) Software **1030** may include code to implement aspects of the present disclosure, including code to support downlink transmission. Software **1030** may be stored in a non-transitory computer-readable medium such as system memory or other memory. In some cases, the software **1030** may not be directly executable by the processor but may cause a computer (e.g., when compiled and executed) to perform functions described herein.

(102) Transceiver **1035** may communicate bi-directionally, via one or more antennas, wired, or wireless links as described herein. For example, the transceiver **1035** may represent a wireless transceiver and may communicate bi-directionally with another wireless transceiver. The transceiver **1035** may also include a modem to modulate the packets and provide the modulated packets to the antennas for transmission, and to demodulate packets received from the antennas. In some cases, the wireless device may include a single antenna **1040**. However, in some cases the device may have more than one antenna **1040**, which may be capable of concurrently transmitting or receiving multiple wireless transmissions.

(103) I/O controller **1045** may manage input and output signals for device **1005**. I/O controller **1045** may also manage peripherals not integrated into device **1005**. In some cases, I/O controller **1045** may represent a physical connection or port to an external peripheral. In some cases, I/O controller **1045** may utilize an operating system such as iOS®, ANDROID®, MS-DOS®, MS-WINDOWS®, OS/2®, UNIX®, LINUX®, or another known operating system. In other cases, I/O controller **1045** may represent or interact with a modem, a keyboard, a mouse, a touchscreen, or a similar device. In some cases, I/O controller **1045** may be implemented as part of a processor. In some cases, a user may interact with device **1005** via I/O controller **1045** or via hardware components controlled by I/O controller **1045**.

(104) FIG. **11** shows a block diagram **1100** of a wireless device **1105** that supports downlink transmission in accordance with aspects of the present disclosure. Wireless device **1105** may be an example of aspects of a base station **105** as described herein. Wireless device **1105** may include receiver **1110**, base station communications manager **1115**, and transmitter **1120**. Wireless device **1105** may also include a processor. Each of these components may be in communication with one another (e.g., via one or more buses).

(105) Receiver **1110** may receive information such as packets, user data, or control information associated with various information channels (e.g., control channels, data channels, and information related to grant-free downlink transmission, etc.). Information may be passed on to other components of the device. The receiver **1110** may be an example of aspects of the transceiver **1435** described with reference to FIG. **14**. The receiver **1110** may utilize a single antenna or a set of antennas.

(106) Base station communications manager **1115** may be an example of aspects of the base station communications manager **1415** described with reference to FIG. **14**. Base station communications manager **1115** and/or at least some of its various sub-components may be implemented in hardware, software executed by a processor, firmware, or any combination thereof. If implemented in software executed by a processor, the functions of the base station communications manager **1115** and/or at least some of its various sub-components may be executed by a general-purpose processor, a DSP, an ASIC, an FPGA or other programmable logic device, discrete gate or transistor logic, discrete hardware components, or any combination thereof designed to perform the functions described in the present disclosure.

(107) The base station communications manager **1115** and/or at least some of its various sub-components may be physically located at various positions, including being distributed such that portions of functions are implemented at different physical locations by one or more physical devices. In some examples, base station communications manager **1115** and/or at least some of its various sub-components may be a separate and distinct component in accordance with various aspects of the present disclosure. In other examples, base station communications manager **1115**

and/or at least some of its various sub-components may be combined with one or more other hardware components, including but not limited to an I/O component, a transceiver, a network server, another computing device, one or more other components described in the present disclosure, or a combination thereof in accordance with various aspects of the present disclosure.

(108) Base station communications manager **1115** may transmit, to a UE, a resource configuration for transmission of a downlink transmission within a repetition window, the resource configuration including an indicator of a repetition window size for the downlink transmission. Base station communications manager **1115** may transmit the downlink transmission to the UE in accordance with the resource configuration.

(109) Transmitter **1120** may transmit signals generated by other components of the device. In some examples, the transmitter **1120** may be collocated with a receiver **1110** in a transceiver module. For example, the transmitter **1120** may be an example of aspects of the transceiver **1435** described with reference to FIG. **14**. The transmitter **1120** may utilize a single antenna or a set of antennas.

(110) FIG. **12** shows a block diagram **1200** of a wireless device **1205** that supports downlink transmission in accordance with aspects of the present disclosure. Wireless device **1205** may be an example of aspects of a wireless device **1105** or a base station **105** as described with reference to FIG. **11**. Wireless device **1205** may include receiver **1210**, base station communications manager **1215**, and transmitter **1220**. Wireless device **1205** may also include a processor. Each of these components may be in communication with one another (e.g., via one or more buses). Base station communications manager **1215** may be an example of aspects of the base station communications manager **1415** described with reference to FIG. **14**. Base station communications manager **1215** may also include configuration controller **1225** and downlink transmission manager **1230**.

(111) Receiver **1210** may receive information such as packets, user data, or control information associated with various information channels (e.g., control channels, data channels, and information related to grant-free downlink transmission, etc.). Information may be passed on to other components of the device. The receiver **1210** may be an example of aspects of the transceiver **1435** described with reference to FIG. **14**. The receiver **1210** may utilize a single antenna or a set of antennas.

(112) Configuration controller **1225** may transmit, to a UE, a resource configuration for transmission of a downlink transmission within a repetition window, the resource configuration including an indicator of a repetition window size for the downlink transmission. In some cases, the resource configuration is transmitted via RRC signaling, the resource configuration further including a series of RV indices for the repetition window.

(113) Downlink transmission manager **1230** may transmit the downlink transmission to the UE in accordance with the resource configuration. For example, downlink transmission manager **1230** may transmit one or more additional repetitions of the downlink transmission during one or more corresponding subsequent TTIs of the repetition window, each of the one or more additional repetitions being associated with a respective RV index. As another example, downlink transmission manager **1230** may transmit the first repetition of the downlink transmission, which may be a grant-free downlink transmission, during a TTI of the subset of TTIs, the first repetition being associated with a first RV index. Downlink transmission manager **1230** may transmit one or more additional repetitions of the grant-free downlink transmission during one or more corresponding subsequent TTIs of the at least one other TTI, each of the one or more additional repetitions being associated with a respective RV index. Downlink transmission manager **1230** may receive, from the UE, an indication of a successful decoding of the downlink transmission.

(114) In some cases, transmitting the downlink transmission to the UE includes transmitting a first repetition of the downlink transmission during an initial TTI of the repetition window, the first repetition being associated with a first RV index. In some cases, transmitting the downlink transmission, which may be a grant-free downlink transmission, to the UE includes identifying a subset of TTIs within the repetition window during which a first repetition of the grant-free

downlink transmission is allowed to be transmitted, where the repetition window includes the subset of TTIs and at least one other TTI. In some cases, transmitting the grant-free downlink transmission to the UE includes transmitting a first repetition of the grant-free downlink transmission during any TTI of the repetition window, the first repetition being associated with a first RV index.

(115) Transmitter **1220** may transmit signals generated by other components of the device. In some examples, the transmitter **1220** may be collocated with a receiver **1210** in a transceiver module. For example, the transmitter **1220** may be an example of aspects of the transceiver **1435** described with reference to FIG. **14**. The transmitter **1220** may utilize a single antenna or a set of antennas.

(116) FIG. **13** shows a block diagram **1300** of a base station communications manager **1315** that supports downlink transmission in accordance with aspects of the present disclosure. The base station communications manager **1315** may be an example of aspects of a base station communications manager **1415** described with reference to FIGS. **11**, **12**, and **14**. The base station communications manager **1315** may include configuration controller **1320**, downlink transmission manager **1325**, and capability identifier **1330**. Each of these modules may communicate, directly or indirectly, with one another (e.g., via one or more buses).

(117) Configuration controller **1320** may transmit, to a UE, a resource configuration for transmission of a downlink transmission within a repetition window, the resource configuration including an indicator of a repetition window size for the downlink transmission. In some cases, the resource configuration is transmitted via RRC signaling, the resource configuration further including a series of RV indices for the repetition window.

(118) Downlink transmission manager **1325** may transmit the downlink transmission to the UE in accordance with the resource configuration. For example, downlink transmission manager **1325** may transmit one or more additional repetitions of the downlink transmission during one or more corresponding subsequent TTIs of the repetition window, each of the one or more additional repetitions being associated with a respective RV index. As another example, downlink transmission manager **1325** may transmit the first repetition of the downlink transmission, which may be a grant-free downlink transmission, during a TTI of the subset of TTIs, the first repetition being associated with a first RV index. Downlink transmission manager **1325** may transmit one or more additional repetitions of the grant-free downlink transmission during one or more corresponding subsequent TTIs of the at least one other TTI, each of the one or more additional repetitions being associated with a respective RV index. Downlink transmission manager **1325** may receive, from the UE, an indication of a successful decoding of the downlink transmission.

(119) In some cases, transmitting the downlink transmission to the UE includes transmitting a first repetition of the downlink transmission during an initial TTI of the repetition window, the first repetition being associated with a first RV index. In some cases, transmitting the downlink transmission, which may be a grant-free downlink transmission, to the UE includes identifying a subset of TTIs within the repetition window during which a first repetition of the grant-free downlink transmission is allowed to be transmitted, where the repetition window includes the subset of TTIs and at least one other TTI. In some cases, transmitting the downlink transmission to the UE includes transmitting a first repetition of the downlink transmission during any TTI of the repetition window, the first repetition being associated with a first RV index.

(120) Capability identifier **1330** may receive, from the UE, an indication of a capability of the UE, where the capability indicates a maximum repetition window size supported by the UE, a timing within the repetition window for which the UE supports transmission of a first repetition of the grant-free downlink transmission, or combinations of the same.

(121) FIG. **14** shows a diagram of a system **1400** including a device **1405** that supports downlink transmission in accordance with aspects of the present disclosure. Device **1405** may be an example of or include the components of base station **105** as described herein, e.g., with reference to FIG. **1**. Device **1405** may include components for bi-directional voice and data communications including

components for transmitting and receiving communications, including base station communications manager **1415**, processor **1420**, memory **1425**, software **1430**, transceiver **1435**, antenna **1440**, network communications manager **1445**, and inter-station communications manager **1450**. These components may be in electronic communication via one or more buses (e.g., bus **1410**). Device **1405** may communicate wirelessly with one or more UEs **115**.

(122) Processor **1420** may include an intelligent hardware device, (e.g., a general-purpose processor, a DSP, a CPU, a microcontroller, an ASIC, an FPGA, a programmable logic device, a discrete gate or transistor logic component, a discrete hardware component, or any combination thereof). In some cases, processor **1420** may be configured to operate a memory array using a memory controller. In other cases, a memory controller may be integrated into processor **1420**. Processor **1420** may be configured to execute computer-readable instructions stored in a memory to perform various functions (e.g., functions or tasks supporting grant-free downlink transmission).

(123) Memory **1425** may include RAM and ROM. The memory **1425** may store computer-readable, computer-executable software **1430** including instructions that, when executed, cause the processor to perform various functions described herein. In some cases, the memory **1425** may contain, among other things, a BIOS which may control basic hardware or software operation such as the interaction with peripheral components or devices.

(124) Software **1430** may include code to implement aspects of the present disclosure, including code to support grant-free downlink transmission. Software **1430** may be stored in a non-transitory computer-readable medium such as system memory or other memory. In some cases, the software **1430** may not be directly executable by the processor but may cause a computer (e.g., when compiled and executed) to perform functions described herein.

(125) Transceiver **1435** may communicate bi-directionally, via one or more antennas, wired, or wireless links as described herein. For example, the transceiver **1435** may represent a wireless transceiver and may communicate bi-directionally with another wireless transceiver. The transceiver **1435** may also include a modem to modulate the packets and provide the modulated packets to the antennas for transmission, and to demodulate packets received from the antennas. In some cases, the wireless device may include a single antenna **1440**. However, in some cases the device may have more than one antenna **1440**, which may be capable of concurrently transmitting or receiving multiple wireless transmissions.

(126) Network communications manager **1445** may manage communications with the core network (e.g., via one or more wired backhaul links). For example, the network communications manager **1445** may manage the transfer of data communications for client devices, such as one or more UEs **115**.

(127) Inter-station communications manager **1450** may manage communications with other base station **105**, and may include a controller or scheduler for controlling communications with UEs **115** in cooperation with other base stations **105**. For example, the inter-station communications manager **1450** may coordinate scheduling for transmissions to UEs **115** for various interference mitigation techniques such as beamforming or joint transmission. In some examples, inter-station communications manager **1450** may provide an X2 interface within an Long Term Evolution (LTE)/LTE-A wireless communication network technology to provide communication between base stations **105**.

(128) FIG. **15** shows a flowchart illustrating a method **1500** for downlink transmission in accordance with aspects of the present disclosure. The operations of method **1500** may be implemented by a UE **115** or its components as described herein. For example, the operations of method **1500** may be performed by a UE communications manager as described with reference to FIGS. **7** through **10**. In some examples, a UE **115** may execute a set of codes to control the functional elements of the device to perform the functions described herein. Additionally or alternatively, the UE **115** may perform aspects of the functions described herein using special-purpose hardware.

(129) At **1505** the UE **115** may receive a resource configuration for reception of a downlink transmission within a repetition window, the resource configuration including an indicator of a repetition window size for the downlink transmission. The operations of **1505** may be performed according to the methods described herein. In certain examples, aspects of the operations of **1505** may be performed by a configuration manager as described with reference to FIGS. 7 through 10.

(130) At **1510** the UE **115** may monitor, in accordance with the resource configuration, one or more TTIs of the repetition window for reception of the downlink transmission. The operations of **1510** may be performed according to the methods described herein. In certain examples, aspects of the operations of **1510** may be performed by a resource monitoring controller as described with reference to FIGS. 7 through 10.

(131) At **1515** the UE **115** may attempt to decode the downlink transmission during the one or more TTIs of the repetition window based at least in part on the repetition window size. The operations of **1515** may be performed according to the methods described herein. In certain examples, aspects of the operations of **1515** may be performed by a decoding manager as described with reference to FIGS. 7 through 10.

(132) FIG. 16 shows a flowchart illustrating a method **1600** for downlink transmission in accordance with aspects of the present disclosure. The operations of method **1600** may be implemented by a UE **115** or its components as described herein. For example, the operations of method **1600** may be performed by a UE communications manager as described with reference to FIGS. 7 through 10. In some examples, a UE **115** may execute a set of codes to control the functional elements of the device to perform the functions described herein. Additionally or alternatively, the UE **115** may perform aspects of the functions described herein using special-purpose hardware.

(133) At **1605** the UE **115** may receive a resource configuration for reception of a downlink transmission within a repetition window, the resource configuration including an indicator of a repetition window size for the downlink transmission. The operations of **1605** may be performed according to the methods described herein. In certain examples, aspects of the operations of **1605** may be performed by a configuration manager as described with reference to FIGS. 7 through 10.

(134) At **1610** the UE **115** may monitor for a first repetition of the downlink transmission in an initial TTI of the repetition window, where the repetition window size is greater than one TTI. The operations of **1610** may be performed according to the methods described herein. In certain examples, aspects of the operations of **1610** may be performed by a resource monitoring controller as described with reference to FIGS. 7 through 10.

(135) At **1615** the UE **115** may identify a series of RV indices for the repetition window based at least in part on the resource configuration, each RV index of the series of RV indices associated with a respective TTI of the repetition window. The operations of **1615** may be performed according to the methods described herein. In certain examples, aspects of the operations of **1615** may be performed by a decoding manager as described with reference to FIGS. 7 through 10.

(136) At **1620** the UE **115** may attempt to decode the downlink transmission during a given TTI of the repetition window based at least in part on the RV index associated with the given TTI. The operations of **1620** may be performed according to the methods described herein. In certain examples, aspects of the operations of **1620** may be performed by a decoding manager as described with reference to FIGS. 7 through 10.

(137) FIG. 17 shows a flowchart illustrating a method **1700** for downlink transmission in accordance with aspects of the present disclosure. The operations of method **1700** may be implemented by a UE **115** or its components as described herein. For example, the operations of method **1700** may be performed by a UE communications manager as described with reference to FIGS. 7 through 10. In some examples, a UE **115** may execute a set of codes to control the functional elements of the device to perform the functions described herein. Additionally or alternatively, the UE **115** may perform aspects of the functions described herein using special-

purpose hardware.

(138) At **1705** the UE **115** may receive a resource configuration for reception of a grant-free downlink transmission within a repetition window, the resource configuration including an indicator of a repetition window size for the grant-free downlink transmission. The operations of **1705** may be performed according to the methods described herein. In certain examples, aspects of the operations of **1705** may be performed by a configuration manager as described with reference to FIGS. 7 through 10.

(139) At **1710** the UE **115** may identify, based at least in part on the resource configuration, a subset of TTIs within the repetition window during which a first repetition of the grant-free downlink transmission is allowed to be transmitted, where the repetition window includes the subset of TTIs and at least one other TTI. The operations of **1710** may be performed according to the methods described herein. In certain examples, aspects of the operations of **1710** may be performed by a resource monitoring controller as described with reference to FIGS. 7 through 10.

(140) At **1715** the UE **115** may monitor for the first repetition of the grant-free downlink transmission during at least one TTI of the subset of TTIs. The operations of **1715** may be performed according to the methods described herein. In certain examples, aspects of the operations of **1715** may be performed by a resource monitoring controller as described with reference to FIGS. 7 through 10.

(141) At **1720** the UE **115** may identify a series of RV indices for the repetition window based at least in part on the resource configuration. The operations of **1720** may be performed according to the methods described herein. In certain examples, aspects of the operations of **1720** may be performed by a decoding manager as described with reference to FIGS. 7 through 10.

(142) At **1725** the UE **115** may determine one or more potential RV indices for each TTI of the repetition window, where each potential RV index for each TTI is based at least in part on the series of RV indices beginning at a respective TTI of the subset of TTIs. The operations of **1725** may be performed according to the methods described herein. In certain examples, aspects of the operations of **1725** may be performed by a decoding manager as described with reference to FIGS. 7 through 10.

(143) At **1730** the UE **115** may attempt to decode the grant-free downlink transmission during a given TTI of the repetition window based at least in part on the one or more potential RV indices for the given TTI. The operations of **1730** may be performed according to the methods described herein. In certain examples, aspects of the operations of **1730** may be performed by a decoding manager as described with reference to FIGS. 7 through 10.

(144) FIG. 18 shows a flowchart illustrating a method **1800** for downlink transmission in accordance with aspects of the present disclosure. The operations of method **1800** may be implemented by a UE **115** or its components as described herein. For example, the operations of method **1800** may be performed by a UE communications manager as described with reference to FIGS. 7 through 10. In some examples, a UE **115** may execute a set of codes to control the functional elements of the device to perform the functions described herein. Additionally or alternatively, the UE **115** may perform aspects of the functions described herein using special-purpose hardware.

(145) At **1805** the UE **115** may receive a resource configuration for reception of a grant-free downlink transmission within a repetition window, the resource configuration including an indicator of a repetition window size for the grant-free downlink transmission. The operations of **1805** may be performed according to the methods described herein. In certain examples, aspects of the operations of **1805** may be performed by a configuration manager as described with reference to FIGS. 7 through 10.

(146) At **1810** the UE **115** may monitor for a first repetition of the grant-free downlink transmission during any TTI of the repetition window, where the repetition window includes a plurality of TTIs. The operations of **1810** may be performed according to the methods described herein. In certain

examples, aspects of the operations of **1810** may be performed by a resource monitoring controller as described with reference to FIGS. 7 through 10.

(147) At **1815** the UE **115** may identify a series of RV indices for the repetition window based at least in part on the resource configuration. The operations of **1815** may be performed according to the methods described herein. In certain examples, aspects of the operations of **1815** may be performed by a decoding manager as described with reference to FIGS. 7 through 10.

(148) At **1820** the UE **115** may determine one or more potential RV indices for each TTI of the repetition window, where each potential RV index for each TTI is based at least in part on the series of RV indices beginning at any TTI of the repetition window. The operations of **1820** may be performed according to the methods described herein. In certain examples, aspects of the operations of **1820** may be performed by a decoding manager as described with reference to FIGS. 7 through 10.

(149) At **1825** the UE **115** may attempt to decode the grant-free downlink transmission during a given TTI of the repetition window based at least in part on the one or more potential RV indices for the given TTI. The operations of **1825** may be performed according to the methods described herein. In certain examples, aspects of the operations of **1825** may be performed by a decoding manager as described with reference to FIGS. 7 through 10.

(150) FIG. 19 shows a flowchart illustrating a method **1900** for downlink transmission in accordance with aspects of the present disclosure. The operations of method **1900** may be implemented by a UE **115** or its components as described herein. For example, the operations of method **1900** may be performed by a UE communications manager as described with reference to FIGS. 7 through 10. In some examples, a UE **115** may execute a set of codes to control the functional elements of the device to perform the functions described herein. Additionally or alternatively, the UE **115** may perform aspects of the functions described herein using special-purpose hardware.

(151) At **1905** the UE **115** may transmit an indication of a capability of the UE, the capability indicating a maximum repetition window size supported by the UE, a timing within the repetition window for which the UE supports transmission of a first repetition of the grant-free downlink transmission, or combinations of the same. The operations of **1905** may be performed according to the methods described herein. In certain examples, aspects of the operations of **1905** may be performed by a capability manager as described with reference to FIGS. 7 through 10.

(152) At **1910** the UE **115** may receive a resource configuration for reception of a grant-free downlink transmission within a repetition window, the resource configuration including an indicator of a repetition window size for the grant-free downlink transmission. The operations of **1910** may be performed according to the methods described herein. In certain examples, aspects of the operations of **1910** may be performed by a configuration manager as described with reference to FIGS. 7 through 10.

(153) At **1915** the UE **115** may monitor, in accordance with the resource configuration, one or more TTIs of the repetition window for reception of the grant-free downlink transmission. The operations of **1915** may be performed according to the methods described herein. In certain examples, aspects of the operations of **1915** may be performed by a resource monitoring controller as described with reference to FIGS. 7 through 10.

(154) At **1920** the UE **115** may attempt to decode the grant-free downlink transmission during the one or more TTIs of the repetition window based at least in part on the repetition window size. The operations of **1920** may be performed according to the methods described herein. In certain examples, aspects of the operations of **1920** may be performed by a decoding manager as described with reference to FIGS. 7 through 10.

(155) At **1925** the UE **115** may transmit an indication that the grant-free downlink transmission was successfully decoded. The operations of **1925** may be performed according to the methods described herein. In certain examples, aspects of the operations of **1925** may be performed by a

decoding manager as described with reference to FIGS. 7 through 10.

(156) FIG. 20 shows a flowchart illustrating a method 2000 for downlink transmission in accordance with aspects of the present disclosure. The operations of method 2000 may be implemented by a base station 105 or its components as described herein. For example, the operations of method 2000 may be performed by a base station communications manager as described with reference to FIGS. 11 through 14. In some examples, a base station 105 may execute a set of codes to control the functional elements of the device to perform the functions described herein. Additionally or alternatively, the base station 105 may perform aspects of the functions described herein using special-purpose hardware.

(157) At 2005 the base station 105 may transmit, to a UE, a resource configuration for transmission of a downlink transmission within a repetition window, the resource configuration including an indicator of a repetition window size for the downlink transmission. The operations of 2005 may be performed according to the methods described herein. In certain examples, aspects of the operations of 2005 may be performed by a configuration controller as described with reference to FIGS. 11 through 14.

(158) At 2010 the base station 105 may transmit the downlink transmission to the UE in accordance with the resource configuration. The operations of 2010 may be performed according to the methods described herein. In certain examples, aspects of the operations of 2010 may be performed by a downlink transmission manager as described with reference to FIGS. 11 through 14.

(159) FIG. 21 shows a flowchart illustrating a method 2100 for downlink transmission in accordance with aspects of the present disclosure. The operations of method 2100 may be implemented by a base station 105 or its components as described herein. For example, the operations of method 2100 may be performed by a base station communications manager as described with reference to FIGS. 11 through 14. In some examples, a base station 105 may execute a set of codes to control the functional elements of the device to perform the functions described herein. Additionally or alternatively, the base station 105 may perform aspects of the functions described herein using special-purpose hardware.

(160) At 2105 the base station 105 may transmit, to a UE, a resource configuration for transmission of a downlink transmission within a repetition window, the resource configuration including an indicator of a repetition window size for the downlink transmission. The operations of 2105 may be performed according to the methods described herein. In certain examples, aspects of the operations of 2105 may be performed by a configuration controller as described with reference to FIGS. 11 through 14.

(161) At 2110 the base station 105 may transmit a first repetition of the downlink transmission during an initial TTI of the repetition window, the first repetition being associated with a first RV index. The operations of 2110 may be performed according to the methods described herein. In certain examples, aspects of the operations of 2110 may be performed by a downlink transmission manager as described with reference to FIGS. 11 through 14.

(162) At 2115 the base station 105 may transmit one or more additional repetitions of the downlink transmission during one or more corresponding subsequent TTIs of the repetition window, each of the one or more additional repetitions being associated with a respective RV index. The operations of 2115 may be performed according to the methods described herein. In certain examples, aspects of the operations of 2115 may be performed by a downlink transmission manager as described with reference to FIGS. 11 through 14.

(163) FIG. 22 shows a flowchart illustrating a method 2200 for downlink transmission in accordance with aspects of the present disclosure. The operations of method 2200 may be implemented by a base station 105 or its components as described herein. For example, the operations of method 2200 may be performed by a base station communications manager as described with reference to FIGS. 11 through 14. In some examples, a base station 105 may

execute a set of codes to control the functional elements of the device to perform the functions described herein. Additionally or alternatively, the base station **105** may perform aspects of the functions described herein using special-purpose hardware.

(164) At **2205** the base station **105** may transmit, to a UE, a resource configuration for transmission of a grant-free downlink transmission within a repetition window, the resource configuration including an indicator of a repetition window size for the grant-free downlink transmission. The operations of **2205** may be performed according to the methods described herein. In certain examples, aspects of the operations of **2205** may be performed by a configuration controller as described with reference to FIGS. **11** through **14**.

(165) At **2210** the base station **105** may identify a subset of TTIs within the repetition window during which a first repetition of the grant-free downlink transmission is allowed to be transmitted, where the repetition window includes the subset of TTIs and at least one other TTI. The operations of **2210** may be performed according to the methods described herein. In certain examples, aspects of the operations of **2210** may be performed by a downlink transmission manager as described with reference to FIGS. **11** through **14**.

(166) At **2215** the base station **105** may transmit the first repetition of the grant-free downlink transmission during a TTI of the subset of TTIs, the first repetition being associated with a first RV index. The operations of **2215** may be performed according to the methods described herein. In certain examples, aspects of the operations of **2215** may be performed by a downlink transmission manager as described with reference to FIGS. **11** through **14**.

(167) At **2220** the base station **105** may transmit one or more additional repetitions of the grant-free downlink transmission during one or more corresponding subsequent TTIs of the at least one other TTI, each of the one or more additional repetitions being associated with a respective RV index. The operations of **2220** may be performed according to the methods described herein. In certain examples, aspects of the operations of **2220** may be performed by a downlink transmission manager as described with reference to FIGS. **11** through **14**.

(168) FIG. **23** shows a flowchart illustrating a method **2300** for downlink transmission in accordance with aspects of the present disclosure. The operations of method **2300** may be implemented by a base station **105** or its components as described herein. For example, the operations of method **2300** may be performed by a base station communications manager as described with reference to FIGS. **11** through **14**. In some examples, a base station **105** may execute a set of codes to control the functional elements of the device to perform the functions described herein. Additionally or alternatively, the base station **105** may perform aspects of the functions described herein using special-purpose hardware.

(169) At **2305** the base station **105** may transmit, to a user equipment (UE), a resource configuration for transmission of a grant-free downlink transmission within a repetition window, the resource configuration including an indicator of a repetition window size for the grant-free downlink transmission. The operations of **2305** may be performed according to the methods described herein. In certain examples, aspects of the operations of **2305** may be performed by a configuration controller as described with reference to FIGS. **11** through **14**.

(170) At **2310** the base station **105** may transmit a first repetition of the grant-free downlink transmission during any TTI of the repetition window, the first repetition being associated with a first RV index. The operations of **2310** may be performed according to the methods described herein. In certain examples, aspects of the operations of **2310** may be performed by a downlink transmission manager as described with reference to FIGS. **11** through **14**.

(171) At **2315** the base station **105** may transmit one or more additional repetitions of the grant-free downlink transmission during one or more corresponding subsequent TTIs of the repetition window, each of the one or more additional repetitions being associated with a respective RV index. The operations of **2315** may be performed according to the methods described herein. In certain examples, aspects of the operations of **2315** may be performed by a downlink transmission

manager as described with reference to FIGS. 11 through 14.

(172) FIG. 24 shows a flowchart illustrating a method 2400 for downlink transmission in accordance with aspects of the present disclosure. The operations of method 2400 may be implemented by a base station 105 or its components as described herein. For example, the operations of method 2400 may be performed by a base station communications manager as described with reference to FIGS. 11 through 14. In some examples, a base station 105 may execute a set of codes to control the functional elements of the device to perform the functions described herein. Additionally or alternatively, the base station 105 may perform aspects of the functions described herein using special-purpose hardware.

(173) At 2405 the base station 105 may receive, from a UE, an indication of a capability of the UE, where the capability indicates a maximum repetition window size supported by the UE, a timing within the repetition window for which the UE supports transmission of a first repetition of the grant-free downlink transmission, or combinations of the same. The operations of 2405 may be performed according to the methods described herein. In certain examples, aspects of the operations of 2405 may be performed by a capability identifier as described with reference to FIGS. 11 through 14.

(174) At 2410 the base station 105 may transmit, to the UE, a resource configuration for transmission of a grant-free downlink transmission within a repetition window, the resource configuration including an indicator of a repetition window size for the grant-free downlink transmission. The operations of 2410 may be performed according to the methods described herein. In certain examples, aspects of the operations of 2410 may be performed by a configuration controller as described with reference to FIGS. 11 through 14.

(175) At 2415 the base station 105 may transmit the grant-free downlink transmission to the UE in accordance with the resource configuration. The operations of 2415 may be performed according to the methods described herein. In certain examples, aspects of the operations of 2415 may be performed by a downlink transmission manager as described with reference to FIGS. 11 through 14.

(176) At 2420 the base station 105 may receive, from the UE, an indication of a successful decoding of the grant-free downlink transmission. The operations of 2420 may be performed according to the methods described herein. In certain examples, aspects of the operations of 2420 may be performed by a downlink transmission manager as described with reference to FIGS. 11 through 14.

(177) It should be noted that the methods described herein describe possible implementations, and that the operations and the steps may be rearranged or otherwise modified and that other implementations are possible. Further, aspects from two or more of the methods may be combined.

(178) Techniques described herein may be used for various wireless communications systems such as code division multiple access (CDMA), time division multiple access (TDMA), frequency division multiple access (FDMA), orthogonal frequency division multiple access (OFDMA), single carrier frequency division multiple access (SC-FDMA), and other systems. A CDMA system may implement a radio technology such as CDMA2000, Universal Terrestrial Radio Access (UTRA), etc. CDMA2000 covers IS-2000, IS-95, and IS-856 standards. IS-2000 Releases may be commonly referred to as CDMA2000 1×, 1×, etc. IS-856 (TIA-856) is commonly referred to as CDMA2000 1×EV-DO, High Rate Packet Data (HRPD), etc. UTRA includes Wideband CDMA (WCDMA) and other variants of CDMA. A TDMA system may implement a radio technology such as Global System for Mobile Communications (GSM).

(179) An OFDMA system may implement a radio technology such as Ultra Mobile Broadband (UMB), Evolved UTRA (E-UTRA), Institute of Electrical and Electronics Engineers (IEEE) 802.11 (Wi-Fi), IEEE 802.16 (WiMAX), IEEE 802.20, Flash-OFDM, etc. UTRA and E-UTRA are part of Universal Mobile Telecommunications System (UMTS). LTE, LTE-A, and LTE-A Pro are releases of UMTS that use E-UTRA. UTRA, E-UTRA, UMTS, LTE, LTE-A, LTE-A Pro, NR, and

GSM are described in documents from the organization named “3rd Generation Partnership Project” (3GPP). CDMA2000 and UMB are described in documents from an organization named “3rd Generation Partnership Project 2” (3GPP2). The techniques described herein may be used for the systems and radio technologies mentioned above as well as other systems and radio technologies. While aspects of an LTE, LTE-A, LTE-A Pro, or NR system may be described for purposes of example, and LTE, LTE-A, LTE-A Pro, or NR terminology may be used in much of the description, the techniques described herein are applicable beyond LTE, LTE-A, LTE-A Pro, or NR applications.

(180) A macro cell generally covers a relatively large geographic area (e.g., several kilometers in radius) and may allow unrestricted access by UEs **115** with service subscriptions with the network provider. A small cell may be associated with a lower-powered base station **105**, as compared with a macro cell, and a small cell may operate in the same or different (e.g., licensed, unlicensed, etc.) frequency bands as macro cells. Small cells may include pico cells, femto cells, and micro cells according to various examples. A pico cell, for example, may cover a small geographic area and may allow unrestricted access by UEs **115** with service subscriptions with the network provider. A femto cell may also cover a small geographic area (e.g., a home) and may provide restricted access by UEs **115** having an association with the femto cell (e.g., UEs **115** in a closed subscriber group (CSG), UEs **115** for users in the home, and the like). An eNB for a macro cell may be referred to as a macro eNB. An eNB for a small cell may be referred to as a small cell eNB, a pico eNB, a femto eNB, or a home eNB. An eNB may support one or multiple (e.g., two, three, four, and the like) cells, and may also support communications using one or multiple component carriers.

(181) The wireless communications system **100** or systems described herein may support synchronous or asynchronous operation. For synchronous operation, the base stations **105** may have similar frame timing, and transmissions from different base stations **105** may be approximately aligned in time. For asynchronous operation, the base stations **105** may have different frame timing, and transmissions from different base stations **105** may not be aligned in time. The techniques described herein may be used for either synchronous or asynchronous operations.

(182) Information and signals described herein may be represented using any of a variety of different technologies and techniques. For example, data, instructions, commands, information, signals, bits, symbols, and chips that may be referenced throughout the above description may be represented by voltages, currents, electromagnetic waves, magnetic fields or particles, optical fields or particles, or any combination thereof.

(183) The various illustrative blocks and modules described in connection with the disclosure herein may be implemented or performed with a general-purpose processor, a DSP, an ASIC, an FPGA or other programmable logic device (PLD), discrete gate or transistor logic, discrete hardware components, or any combination thereof designed to perform the functions described herein. A general-purpose processor may be a microprocessor, but in the alternative, the processor may be any conventional processor, controller, microcontroller, or state machine. A processor may also be implemented as a combination of computing devices (e.g., a combination of a DSP and a microprocessor, multiple microprocessors, one or more microprocessors in conjunction with a DSP core, or any other such configuration).

(184) The functions described herein may be implemented in hardware, software executed by a processor, firmware, or any combination thereof. If implemented in software executed by a processor, the functions may be stored on or transmitted over as one or more instructions or code on a computer-readable medium. Other examples and implementations are within the scope of the disclosure and appended claims. For example, due to the nature of software, functions described herein can be implemented using software executed by a processor, hardware, firmware, hardwiring, or combinations of any of these. Features implementing functions may also be physically located at various positions, including being distributed such that portions of functions

are implemented at different physical locations.

(185) Computer-readable media includes both non-transitory computer storage media and communication media including any medium that facilitates transfer of a computer program from one place to another. A non-transitory storage medium may be any available medium that can be accessed by a general purpose or special purpose computer. By way of example, and not limitation, non-transitory computer-readable media may comprise RAM, ROM, electrically erasable programmable read only memory (EEPROM), flash memory, compact disk (CD) ROM or other optical disk storage, magnetic disk storage or other magnetic storage devices, or any other non-transitory medium that can be used to carry or store desired program code means in the form of instructions or data structures and that can be accessed by a general-purpose or special-purpose computer, or a general-purpose or special-purpose processor. Also, any connection is properly termed a computer-readable medium. For example, if the software is transmitted from a website, server, or other remote source using a coaxial cable, fiber optic cable, twisted pair, digital subscriber line (DSL), or wireless technologies such as infrared, radio, and microwave, then the coaxial cable, fiber optic cable, twisted pair, DSL, or wireless technologies such as infrared, radio, and microwave are included in the definition of medium. Disk and disc, as used herein, include CD, laser disc, optical disc, digital versatile disc (DVD), floppy disk and Blu-ray disc where disks usually reproduce data magnetically, while discs reproduce data optically with lasers.

Combinations of the above are also included within the scope of computer-readable media.

(186) As used herein, including in the claims, “or” as used in a list of items (e.g., a list of items prefaced by a phrase such as “at least one of” or “one or more of”) indicates an inclusive list such that, for example, a list of at least one of A, B, or C means A or B or C or AB or AC or BC or ABC (i.e., A and B and C). Also, as used herein, the phrase “based on” shall not be construed as a reference to a closed set of conditions. For example, an exemplary step that is described as “based on condition A” may be based on both a condition A and a condition B without departing from the scope of the present disclosure. In other words, as used herein, the phrase “based on” shall be construed in the same manner as the phrase “based at least in part on.”

(187) In the appended figures, similar components or features may have the same reference label. Further, various components of the same type may be distinguished by following the reference label by a dash and a second label that distinguishes among the similar components. If just the first reference label is used in the specification, the description is applicable to any one of the similar components having the same first reference label irrespective of the second reference label, or other subsequent reference label.

(188) The description set forth herein, in connection with the appended drawings, describes example configurations and does not represent all the examples that may be implemented or that are within the scope of the claims. The term “exemplary” used herein means “serving as an example, instance, or illustration,” and not “preferred” or “advantageous over other examples.” The detailed description includes specific details for the purpose of providing an understanding of the described techniques. These techniques, however, may be practiced without these specific details. In some instances, well-known structures and devices are shown in block diagram form in order to avoid obscuring the concepts of the described examples.

(189) The description herein is provided to enable a person skilled in the art to make or use the disclosure. Various modifications to the disclosure will be readily apparent to those skilled in the art, and the generic principles defined herein may be applied to other variations without departing from the scope of the disclosure. Thus, the disclosure is not limited to the examples and designs described herein, but is to be accorded the broadest scope consistent with the principles and novel features disclosed herein.

Claims

1. A network entity, comprising: one or more memories storing processor-executable code; and one or more processors coupled with the one or more memories and individually or collectively operable to execute the code to cause the network entity to: transmit a message indicating one or more parameters for transmission of a downlink message within a time window, the one or more parameters comprising a set of time resources for the transmission of the downlink message and comprising an indicator of a size of the time window for transmission of one or more repetitions of the downlink message, wherein the transmission of the downlink message is a grant-free downlink transmission; receive, from a user equipment (UE), an indication of a capability of the UE to support the transmission of the one or more repetitions of the downlink message, wherein the capability of the UE indicates a timing within the time window for which the UE supports transmission of a first repetition of the downlink message that is the grant-free downlink transmission; transmit, via the set of time resources and within the time window, the first repetition of the one or more repetitions of the downlink message, the first repetition being associated with a first redundancy version (RV) index for the transmission of the downlink message within the time window, wherein the first repetition is transmitted during a first subset of time resources of the set of time resources that the first repetition is allowed to be transmitted within; and transmit, via the set of time resources and within the time window, one or more additional repetitions of the one or more repetitions of the downlink message in accordance with the message indicating the one or more parameters for the transmission of the downlink message, each of the one or more additional repetitions being associated with a respective RV index for the transmission of the downlink message within the time window, wherein the one or more additional repetitions are transmitted during one or more time resources of the set of time resources subsequent to the first subset of time resources.
2. The network entity of claim 1, wherein to transmit the message indicating the one or more parameters, the one or more processors are individually or collectively further operable to execute the code to cause the network entity to: transmit the one or more parameters for the transmission of the downlink message via radio resource control signaling.
3. The network entity of claim 1, wherein the one or more processors are individually or collectively further operable to execute the code to cause the network entity to: transmit a downlink control information message indicating the first RV index for the transmission of the downlink message.
4. The network entity of claim 1, wherein the one or more processors are individually or collectively further operable to execute the code to cause the network entity to: receive, from the UE, an indication of a successful decoding of the downlink message.
5. The network entity of claim 1, wherein the downlink message is a physical downlink shared channel message.
6. A method for wireless communication at a network entity, comprising: transmitting a message indicating one or more parameters for transmission of a downlink message within a time window, the one or more parameters comprising a set of time resources for the transmission of the downlink message and comprising an indicator of a size of the time window for transmission of one or more repetitions of the downlink message, wherein the transmission of the downlink message is a grant-free downlink transmission; receiving, from a user equipment (UE), an indication of a capability of the UE to support the transmission of the one or more repetitions of the downlink message, wherein the capability of the UE indicates a timing within the time window for which the UE supports transmission of a first repetition of the downlink message that is the grant-free downlink transmission; transmitting, via the set of time resources and within the time window, the first repetition of the one or more repetitions of the downlink message, the first repetition being associated with a first redundancy version (RV) index for the transmission of the downlink message within the time window, wherein the first repetition is transmitted during a first subset of time

resources of the set of time resources that the first repetition is allowed to be transmitted within; and transmitting, via the set of time resources and within the time window, one or more additional repetitions of the one or more repetitions of the downlink message in accordance with the message indicating the one or more parameters for the transmission of the downlink message, each of the one or more additional repetitions being associated with a respective RV index for the transmission of the downlink message within the time window, wherein the one or more additional repetitions are transmitted during one or more time resources of the set of time resources subsequent to the first subset of time resources.

7. The method of claim 6, wherein transmitting the message indicating the one or more parameters comprises: transmitting the one or more parameters for the transmission of the downlink message via radio resource control signaling.

8. The method of claim 6, further comprising: transmitting a downlink control information message indicating the first RV index for the transmission of the downlink message.

9. The method of claim 6, further comprising: receiving, from the UE, an indication of a successful decoding of the downlink message.

10. The method of claim 6, wherein the downlink message is a physical downlink shared channel message.

11. A network entity, comprising: means for transmitting a message indicating one or more parameters for transmission of a downlink message within a time window, the one or more parameters comprising a set of time resources for the transmission of the downlink message and comprising an indicator of a size of the time window for transmission of one or more repetitions of the downlink message, wherein the transmission of the downlink message is a grant-free downlink transmission; means for receiving, from a user equipment (UE), an indication of a capability of the UE to support the transmission of the one or more repetitions of the downlink message, wherein the capability of the UE indicates a timing within the time window for which the UE supports transmission of a first repetition of the downlink message that is the grant-free downlink transmission; means for transmitting, via the set of time resources and within the time window, the first repetition of the one or more repetitions of the downlink message, the first repetition being associated with a first redundancy version (RV) index for the transmission of the downlink message within the time window, wherein the first repetition is transmitted during a first subset of time resources of the set of time resources that the first repetition is allowed to be transmitted within; and means for transmitting, via the set of time resources and within the time window, one or more additional repetitions of the one or more repetitions of the downlink message in accordance with the message indicating the one or more parameters for the transmission of the downlink message, each of the one or more additional repetitions being associated with a respective RV index for the transmission of the downlink message within the time window, wherein the one or more additional repetitions are transmitted during one or more time resources of the set of time resources subsequent to the first subset of time resources.

12. The network entity of claim 11, further comprising: means for transmitting the one or more parameters for the transmission of the downlink message via radio resource control signaling.

13. The network entity of claim 11, further comprising: means for transmitting a downlink control information message indicating the first RV index for the transmission of the downlink message.

14. The network entity of claim 11, further comprising: means for receiving, from the UE, an indication of a successful decoding of the downlink message.

15. The network entity of claim 11, wherein the downlink message is a physical downlink shared channel message.

16. A non-transitory computer-readable medium storing code for wireless communication at a network entity, the code executable by one or more processors to: transmit a message indicating one or more parameters for transmission of a downlink message within a time window, the one or more parameters comprising a set of time resources for the transmission of the downlink message

and comprising an indicator of a size of the time window for transmission of one or more repetitions of the downlink message, wherein the transmission of the downlink message is a grant-free downlink transmission; receive, from a user equipment (UE), an indication of a capability of the UE to support the transmission of the one or more repetitions of the downlink message, wherein the capability of the UE indicates a timing within the time window for which the UE supports transmission of a first repetition of the downlink message that is the grant-free downlink transmission; transmit, via the set of time resources and within the time window, the first repetition of the one or more repetitions of the downlink message, the first repetition being associated with a first redundancy version (RV) index for the transmission of the downlink message within the time window, wherein the first repetition is transmitted during a first subset of time resources of the set of time resources that the first repetition is allowed to be transmitted within; and transmit, via the set of time resources and within the time window, one or more additional repetitions of the one or more repetitions of the downlink message in accordance with the message indicating the one or more parameters for the transmission of the downlink message, each of the one or more additional repetitions being associated with a respective RV index for the transmission of the downlink message within the time window, wherein the one or more additional repetitions are transmitted during one or more time resources of the set of time resources subsequent to the first subset of time resources.

17. The non-transitory computer-readable medium of claim 16, wherein the one or more processors are configured to: transmit the one or more parameters for the transmission of the downlink message via radio resource control signaling.

18. The non-transitory computer-readable medium of claim 16, wherein the one or more processors are configured to: transmit a downlink control information message indicating the first RV index for the transmission of the downlink message.

19. The non-transitory computer-readable medium of claim 16, wherein the one or more processors are configured to: receive, from the UE, an indication of a successful decoding of the downlink message.

20. The non-transitory computer-readable medium of claim 16, wherein the downlink message is a physical downlink shared channel message.
