

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12389944
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Choi; Won C. et al.

Hybrid gel-fiber wick for use in a vaporizer device

Abstract

A vaporization device includes a cartridge having a reservoir that holds a vaporizable material, a heating element, and a wicking element that can draw the vaporizable material to the heating element to be vaporized. The vaporizer cartridge is configured for coupling to a vaporizer device body and containing a vaporizable material. Various embodiments of the vaporizer cartridge are described that include one or more features for a hybrid gel-fiber wick. Related systems, methods, and articles of manufacture are also described.

Inventors:	Choi; Won C. (San Francisco, CA), Lee; Namhey (Hayward, CA)
Applicant:	JUUL Labs, Inc. (San Francisco, CA)
Family ID:	1000008766130
Assignee:	JUUL Labs, Inc. (Washington, DC)
Appl. No.:	17/862615
Filed:	July 12, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20220354173 A1	Nov. 10, 2022

Related U.S. Application Data

continuation parent-doc WO PCT/US2021/013194 20210113 PENDING child-doc US 17862615
us-provisional-application US 62960886 20200114

Publication Classification

Int. Cl.: **A24F40/44** (20200101); **A24F40/10** (20200101); **A24F40/42** (20200101); **A24F40/46** (20200101); **A24F40/70** (20200101); **H05B3/22** (20060101)

U.S. Cl.:

CPC **A24F40/44** (20200101); **A24F40/10** (20200101); **A24F40/42** (20200101); **A24F40/46** (20200101); **A24F40/70** (20200101); **H05B3/22** (20130101);

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4312367	12/1981	Seeman	N/A	N/A
6090331	12/1999	Schwarz et al.	N/A	N/A
8314591	12/2011	Terry et al.	N/A	N/A
8746240	12/2013	Terry et al.	N/A	N/A
9004073	12/2014	Tucker et al.	N/A	N/A
9095175	12/2014	Terry et al.	N/A	N/A
9198466	12/2014	Liu	N/A	N/A
9247773	12/2015	Memari et al.	N/A	N/A
9259035	12/2015	Terry et al.	N/A	N/A
9380812	12/2015	Chung	N/A	N/A
9408416	12/2015	Monsees et al.	N/A	N/A
9439454	12/2015	Fernando et al.	N/A	N/A
9554597	12/2016	Liu	N/A	N/A
9555203	12/2016	Terry et al.	N/A	N/A
9723872	12/2016	Liu	N/A	N/A
9743691	12/2016	Minskoff et al.	N/A	N/A
9999250	12/2017	Minskoff et al.	N/A	N/A
10136672	12/2017	Minskoff et al.	N/A	N/A
10159278	12/2017	Minskoff et al.	N/A	N/A
10244793	12/2018	Monsees et al.	N/A	N/A
10300225	12/2018	Terry et al.	N/A	N/A
10328443	12/2018	Ricketts et al.	N/A	N/A
10772352	12/2019	Mishra et al.	N/A	N/A
10786010	12/2019	Hubbard et al.	N/A	N/A
10849358	12/2019	Mishra et al.	N/A	N/A
11160936	12/2020	Bache et al.	N/A	N/A
2005/0172976	12/2004	Newman et al.	N/A	N/A
2006/0191546	12/2005	Takano	N/A	N/A
2007/0014549	12/2006	Demarest et al.	N/A	N/A
2007/0295347	12/2006	Paine, III et al.	N/A	N/A
2008/0056691	12/2007	Wingo et al.	N/A	N/A
2008/0241255	12/2007	Rose	N/A	N/A
2010/0065653	12/2009	Wingo et al.	N/A	N/A

2011/0083684	12/2010	Luan et al.	N/A	N/A
2011/0277757	12/2010	Terry et al.	N/A	N/A
2013/0228191	12/2012	Newton	N/A	N/A
2014/0209105	12/2013	Sears et al.	N/A	N/A
2014/0232707	12/2013	Alschinger et al.	N/A	N/A
2014/0246031	12/2013	Liu	N/A	N/A
2014/0338684	12/2013	Liu	N/A	N/A
2015/0136158	12/2014	Stevens et al.	N/A	N/A
2015/0209530	12/2014	White	N/A	N/A
2015/0216234	12/2014	Chung	N/A	N/A
2015/0257444	12/2014	Chung	N/A	N/A
2015/0328415	12/2014	Minskoff et al.	N/A	N/A
2015/0374035	12/2014	Sanchez et al.	N/A	N/A
2016/0135506	12/2015	Sanchez et al.	N/A	N/A
2016/0143360	12/2015	Sanchez et al.	N/A	N/A
2016/0262459	12/2015	Monsees et al.	N/A	N/A
2016/0345631	12/2015	Monsees et al.	N/A	N/A
2017/0030882	12/2016	Skoda	N/A	N/A
2017/0181427	12/2016	Shani et al.	N/A	N/A
2017/0188626	12/2016	Davis et al.	N/A	N/A
2017/0280769	12/2016	Li et al.	N/A	N/A
2017/0295846	12/2016	Liu	N/A	N/A
2018/0020722	12/2017	Davis et al.	N/A	N/A
2018/0070633	12/2017	Phillips et al.	N/A	N/A
2018/0084823	12/2017	Fuisz et al.	N/A	N/A
2018/0141073	12/2017	Tan et al.	N/A	N/A
2018/0279673	12/2017	Sebastian et al.	N/A	N/A
2018/0296777	12/2017	Terry et al.	N/A	N/A
2018/0368472	12/2017	Mishra et al.	N/A	N/A
2022/0046979	12/2021	Campitelli	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
100589726	12/2006	CN	N/A
204426692	12/2014	CN	N/A
105962419	12/2015	CN	N/A
109744577	12/2018	CN	N/A
111356378	12/2019	CN	N/A
112023203	12/2019	CN	N/A
2693902	12/2013	EP	N/A
3292775	12/2017	EP	N/A
3402347	12/2017	EP	N/A
3487564	12/2018	EP	N/A
3510649	12/2018	EP	N/A
3732938	12/2019	EP	N/A
3943186	12/2021	EP	N/A
2009505649	12/2008	JP	N/A
2015500025	12/2014	JP	N/A
2015504653	12/2014	JP	N/A
101622528	12/2015	KR	N/A

10020480	12/2018	VN	A24F 40/40
WO-9853866	12/1997	WO	N/A
WO-0028842	12/1999	WO	N/A
WO-2011146174	12/2010	WO	N/A
WO-2013030202	12/2012	WO	N/A
WO-2014144678	12/2013	WO	N/A
WO-2015032093	12/2014	WO	N/A
WO-2016055653	12/2015	WO	N/A
WO-2017205838	12/2016	WO	N/A
WO-2019193311	12/2018	WO	N/A
WO-2020161336	12/2019	WO	N/A
WO-2021127097	12/2020	WO	N/A
WO-2021127101	12/2020	WO	N/A
WO-2021127168	12/2020	WO	N/A

OTHER PUBLICATIONS

VN 10020480 B English translation obtained from Search, pp. 1-17 (Year: 2019). cited by examiner

Li et al. (Oct. 2012) “Effect of Acid-Catalyzed Sol-Gel Silica coating on the Properties of Cotton Fabric”, The Journal of The Textile Institute, vol. 103 (10) pp. 1099-1107. cited by applicant

Primary Examiner: Louie; Philip Y

Assistant Examiner: Delacruz; Madeleine P

Attorney, Agent or Firm: Mintz, Levin, Cohn, Ferris, Glovsky, and Popeo, P.C.

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation application, filed under 35 U.S.C. § 120, of PCT International Patent Application No. PCT/US21/13194 with an International Filing Date of Jan. 13, 2021, and entitled “Hybrid Gel-Fiber Wick for Use in a Vaporizer Device,” which claims priority to U.S. Provisional Patent Application No. 62/960,886 filed on Jan. 14, 2020, and entitled “Hybrid Gel-Fiber Wick for Use in a Vaporizer Device.” the disclosures of all of which is-are incorporated by reference in their entirety and for all purposes.

TECHNICAL FIELD

(1) The subject matter described herein relates to vaporizer devices, including hybrid gel-fiber wicks for use in vaporizer devices.

BACKGROUND

(2) Vaporizer devices, which can also be referred to as vaporizers, electronic vaporizer devices, or e-vaporizer devices, can be used for delivery of an aerosol (for example, a vapor-phase and/or condensed-phase material suspended in a stationary or moving mass of air or some other gas carrier) containing one or more active ingredients by inhalation of the aerosol by a user of the vaporizing device. For example, electronic nicotine delivery systems (ENDS) include a class of vaporizer devices that are battery powered and that can be used to simulate the experience of smoking, but without burning of tobacco or other substances. Vaporizers are gaining increasing popularity both for prescriptive medical use, in delivering medicaments, and for consumption of

tobacco, nicotine, and other plant-based materials. Vaporizer devices can be portable, self-contained, and/or convenient for use.

(3) In use of a vaporizer device, the user inhales an aerosol, colloquially referred to as “vapor,” which can be generated by a heating element that vaporizes (e.g., causes a liquid or solid to at least partially transition to the gas phase) a vaporizable material, which can be liquid, a solution, a solid, a paste, a wax, and/or any other form compatible for use with a specific vaporizer device. The vaporizable material used with a vaporizer can be provided within a cartridge for example, a separable part of the vaporizer device that contains vaporizable material) that includes an outlet (for example, a mouthpiece) for inhalation of the aerosol by a user.

(4) To receive the inhalable aerosol generated by a vaporizer device, a user may, in certain examples, activate the vaporizer device by taking a puff, by pressing a button, and/or by some other approach. A puff as used herein can refer to inhalation by the user in a manner that causes a volume of air to be drawn into the vaporizer device such that the inhalable aerosol is generated by a combination of the vaporized vaporizable material with the volume of air.

(5) An approach by which a vaporizer device generates an inhalable aerosol from a vaporizable material involves heating the vaporizable material in a vaporization chamber (e.g., a heater chamber) to cause the vaporizable material to be converted to the gas (or vapor) phase. A vaporization chamber can refer to an area or volume in the vaporizer device within which a heat source (for example, a conductive, convective, and/or radiative heat source) causes heating of a vaporizable material to produce a mixture of air and vaporized material to form a vapor for inhalation of the vaporizable material by a user of the vaporization device.

(6) In some implementations, the vaporizable material can be drawn out of a reservoir and into the vaporization chamber via a wicking element (e.g., a wick). Drawing of the vaporizable material into the vaporization chamber can be at least partially due to capillary action provided by the wick as the wick pulls the vaporizable material along the wick in the direction of the vaporization chamber.

(7) Vaporizer devices can be controlled by one or more controllers, electronic circuits (for example, sensors, heating elements), and/or the like on the vaporizer. Vaporizer devices can also wirelessly communicate with an external controller for example, a computing device such as a smartphone).

SUMMARY

(8) In certain aspects of the current subject matter, challenges associated with consistent aerosol production and delivery by vaporizer devices can be addressed by inclusion of one or more of the features described herein or comparable/equivalent approaches as would be understood by one of ordinary skill in the art. Aspects of the current subject matter relate to systems, methods and apparatus using hybrid gel-fiber wicks for consistent, enhanced aerosol delivery in a vaporizer device.

(9) In an aspect, a hybrid gel-fiber wick is provided, including a plurality of fibers bundled together to form a fiber core. The fiber core has a first end portion, a second end portion, and a middle portion therebetween, and a gel coating a portion of the fiber core.

(10) In another interrelated aspect, a cartridge is provided. The cartridge includes the hybrid gel-fiber wick as described and illustrated herein including embodiments.

(11) In another interrelated aspect, a device is provided, including a receptacle configured to receive the cartridge as described and illustrated herein, including embodiments.

(12) In another interrelated aspect, a method of manufacturing a vaporizer cartridge is provided. The method includes providing a plurality of fibers bundled together to form a fiber core, the fiber core having a first end portion, a second end portion, and a middle portion therebetween. The method further includes wrapping the middle portion of the fiber core with a heating element, coating the middle portion of the fiber core with a gel to form a hybrid gel-fiber wick, and inserting the gel-fiber hybrid wick into the vaporizer cartridge, such that the middle portion of the fiber core is disposed in an atomizer, and the first end portion and the second end portion of the fiber core are

disposed in a reservoir of the vaporizer cartridge.

(13) In some variations, one or more of the following features may optionally be included in any feasible combination.

(14) The middle portion of the fiber core can include the gel coating. The first end portion and/or the second end portion of the fiber core may not include the gel coating.

(15) The hybrid gel-fiber wick can further include a heating element, wherein at least a portion of the heating element can be disposed between the fiber core and the gel coating. The heating element can be a nichrome wire. The heating element can be spirally wound around the fiber core. The fiber core can include a cotton material. The fiber core can include a silica material.

(16) The gel can include a polymer. The gel can include silicon. The gel can include a silane. The gel can include a silicate. The gel can include tetraethoxysilane. The gel coating can be 250 microns to 500 microns in thickness.

(17) The cartridge can include a reservoir configured to contain a vaporizable material, and a portion of the hybrid gel-fiber wick can be disposed within the reservoir. The first end portion and/or the second end portion of the fiber core can be disposed within the reservoir. The cartridge can include an atomizer configured to vaporize the vaporizable material. The middle portion of the fiber core can be disposed within the atomizer.

(18) The method can further include filling the reservoir with a vaporizable material. Coating the middle portion of the fiber core with a gel can include dispensing the gel on the middle portion of the fiber core with a needle to form the gel coating. Coating the middle portion of the fiber core with a gel can include printing the gel on the middle portion of the fiber core with a printer to form the gel coating. Coating the middle portion of the fiber core with a gel can include molding the gel on the middle portion of the fiber core using a mold to form the gel coating. The gel can include a compound containing silicon. The gel can include a silane. The gel can include a silicate. The gel can include tetraethoxysilane. The gel coating can be 250 microns to 500 microns in thickness.

(19) The hybrid gel-fiber wick can have a total particulate matter (TPM) per puff at least 50% greater than a TPM of the fiber core not including the gel coating.

(20) The details of one or more variations of the subject matter described herein are set forth in the accompanying drawings and the description below. Other features and advantages of the subject matter described herein will be apparent from the description and drawings, and from the claims. The claims that follow this disclosure are intended to define the scope of the protected subject matter.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The accompanying drawings, which are incorporated into and constitute a part of this specification, show certain aspects of the subject matter disclosed herein and, together with the description, help explain some of the principles associated with the disclosed implementations. In the drawings:

(2) FIG. 1A is a block diagram of a vaporizer device;

(3) FIG. 1B is a schematic representation of a vaporizer device and vaporizer cartridge;

(4) FIG. 1C is a front view of a vaporizer device and an embodiment of a vaporizer cartridge;

(5) FIG. 1D is a front view of a vaporizer cartridge coupled to a vaporizer device;

(6) FIG. 1E is a perspective view of a vaporizer cartridge;

(7) FIG. 1F is a perspective view of another embodiment of a vaporizer cartridge coupled to a vaporizer device;

(8) FIG. 2A is a block diagram of an embodiment of a vaporizer device, according to implementations of the present disclosure;

- (9) FIG. 2B illustrates an embodiment of a hybrid gel-fiber wick for use in a vaporizer cartridge, according to implementations of the present disclosure;
- (10) FIG. 3 illustrates a method of preparing the hybrid gel-fiber wick of FIG. 2B, according to implementations of the present disclosure;
- (11) FIG. 4 illustrates a puff and replenish cycle of the hybrid gel-fiber wick of FIG. 2B, according to implementations of the present disclosure;
- (12) FIG. 5 is a graph of total particulate matter (TPM) as a function of puff interval for a hybrid gel-fiber wick consistent with implementations of the present disclosure;
- (13) FIG. 6 is a graph of TPM as a function of viscosity for various embodiments of a gel for use in a hybrid gel-fiber wick consistent with implementations of the present disclosure;
- (14) FIG. 7 is a graph of TPM as a function of replenish rate of a hybrid gel-fiber wick consistent with implementations of the present disclosure; and
- (15) FIG. 8 is a flowchart for a method of manufacturing a vaporizer cartridge consistent with implementations of the present disclosure.

(16) When practical, similar reference numbers denote similar structures, features, or elements.

DETAILED DESCRIPTION

(17) Implementations of the current subject matter include methods, apparatuses, articles of manufacture, and systems relating to vaporization of one or more materials for inhalation by a user. Example implementations include vaporizer devices and systems including vaporizer devices. The term “vaporizer device” as used in the following description and claims refers to any of a self-contained apparatus, an apparatus that includes two or more separable parts (for example, a vaporizer body that includes a battery and other hardware, and a cartridge that includes a vaporizable material), and/or the like. A “vaporizer system,” as used herein, can include one or more components, such as a vaporizer device. Examples of vaporizer devices consistent with implementations of the current subject matter include electronic vaporizers, electronic nicotine delivery systems (ENDS), and/or the like. In general, such vaporizer devices are hand-held devices that heat (such as by convection, conduction, radiation, and/or some combination thereof) a vaporizable material to provide an inhalable dose of the material. The vaporizable material used with a vaporizer device can be provided within a cartridge (for example, a part of the vaporizer that contains the vaporizable material in a reservoir or other container) which can be refillable when empty, or disposable such that a new cartridge containing additional vaporizable material of a same or different type can be used). A vaporizer device can be a cartridge-using vaporizer device, a cartridge-less vaporizer device, or a multi-use vaporizer device capable of use with or without a cartridge. For example, a vaporizer device can include a heating chamber (for example, an oven or other region in which material is heated by a heating element) configured to receive a vaporizable material directly into the heating chamber, and/or a reservoir or the like for containing the vaporizable material. In some implementations, a vaporizer device can be configured for use with a liquid vaporizable material (for example, a carrier solution in which an active and/or inactive ingredient(s) are suspended or held in solution, or a liquid form of the vaporizable material itself), a paste, a wax, and/or a solid vaporizable material. A solid vaporizable material can include a plant material that emits some part of the plant material as the vaporizable material (for example, some part of the plant material remains as waste after the material is vaporized for inhalation by a user) or optionally can be a solid form of the vaporizable material itself, such that all of the solid material can eventually be vaporized for inhalation. A liquid vaporizable material can likewise be capable of being completely vaporized, or can include some portion of the liquid material that remains after all of the material suitable for inhalation has been vaporized.

(18) Referring to the block diagram of FIG. 1A, a vaporizer device **100** can include a power source **112** (for example, a battery, which can be a rechargeable battery), and a controller **104** (for example, a processor, circuitry, etc. capable of executing logic) for controlling delivery of heat to an atomizer **141** to cause a vaporizable material **102** to be converted from a condensed form (such

as a solid, a liquid, a solution, a suspension, a part of an at least partially unprocessed plant material, etc.) to the gas phase. The controller **104** can be part of one or more printed circuit boards (PCBs) consistent with certain implementations of the current subject matter. After conversion of the vaporizable material **102** to the gas phase, at least some of the vaporizable material **102** in the gas phase can condense to form particulate matter in at least a partial local equilibrium with the gas phase as part of an aerosol, which can form some or all of an inhalable dose provided by the vaporizer device **100** during a user's puff or draw on the vaporizer device **100**. It should be appreciated that the interplay between gas and condensed phases in an aerosol generated by a vaporizer device **100** can be complex and dynamic, due to factors such as ambient temperature, relative humidity, chemistry, flow conditions in airflow paths (both inside the vaporizer and in the airways of a human or other animal), and/or mixing of the vaporizable material **102** in the gas phase or in the aerosol phase with other air streams, which can affect one or more physical parameters of an aerosol. In some vaporizer devices, and particularly for vaporizer devices configured for delivery of volatile vaporizable materials, the inhalable dose can exist predominantly in the gas phase (for example, formation of condensed phase particles can be very limited).

(19) The atomizer **141** in the vaporizer device **100** can be configured to vaporize a vaporizable material **102**. The vaporizable material **102** can be a liquid. Examples of the vaporizable material **102** include neat liquids, suspensions, solutions, mixtures, and/or the like. The atomizer **141** can include a wicking element (i.e., a wick) configured to convey an amount of the vaporizable material **102** to a part of the atomizer **141** that includes a heating element (not shown in FIG. **1A**).

(20) For example, the wicking element can be configured to draw the vaporizable material **102** from a reservoir **140** configured to contain the vaporizable material **102**, such that the vaporizable material **102** can be vaporized by heat delivered from a heating element. The wicking element can also optionally allow air to enter the reservoir **140** and replace the volume of vaporizable material **102** removed. In some implementations of the current subject matter, capillary action can pull vaporizable material **102** into the wick for vaporization by the heating element, and air can return to the reservoir **140** through the wick to at least partially equalize pressure in the reservoir **140**. Other methods of allowing air back into the reservoir **140** to equalize pressure are also within the scope of the current subject matter.

(21) As used herein, the terms “wick” or “wicking element” include any material capable of causing fluid motion via capillary pressure.

(22) The heating element can include one or more of a conductive heater, a radiative heater, and/or a convective heater. One type of heating element is a resistive heating element, which can include a material (such as a metal or alloy, for example a nickel-chromium (nichrome) alloy, or a non-metallic resistor) configured to dissipate electrical power in the form of heat when electrical current is passed through one or more resistive segments of the heating element. In some implementations of the current subject matter, the atomizer **141** can include a heating element which includes a resistive coil or other heating element wrapped around, positioned within, integrated into a bulk shape of, pressed into thermal contact with, or otherwise arranged to deliver heat to a wicking element, to cause the vaporizable material **102** drawn from the reservoir **140** by the wicking element to be vaporized for subsequent inhalation by a user in a gas and/or a condensed (for example, aerosol particles or droplets) phase. Other wicking elements, heating elements, and/or atomizer assembly configurations are also possible.

(23) Certain vaporizer devices may, additionally or alternatively, be configured to create an inhalable dose of the vaporizable material **102** in the gas phase and/or aerosol phase via heating of the vaporizable material **102**. The vaporizable material **102** can be a solid-phase material (such as a wax or the like) or plant material (for example, tobacco leaves and/or parts of tobacco leaves). In such vaporizer devices, a resistive heating element can be part of, or otherwise incorporated into or in thermal contact with, the walls of an oven or other heating chamber into which the vaporizable

material **102** is placed. Alternatively, a resistive heating element or elements can be used to heat air passing through or past the vaporizable material **102**, to cause convective heating of the vaporizable material **102**. In still other examples, a resistive heating element or elements can be disposed in intimate contact with plant material such that direct conductive heating of the plant material occurs from within a mass of the plant material, as opposed to only by conduction inward from walls of an oven.

(24) The heating element can be activated in association with a user puffing (i.e., drawing, inhaling, etc.) on a mouthpiece **130** of the vaporizer device **100** to cause air to flow from an air inlet, along an airflow path that passes the atomizer **141** (i.e., wicking element and heating element).

Optionally, air can flow from an air inlet through one or more condensation areas or chambers, to an air outlet in the mouthpiece **130**. Incoming air moving along the airflow path moves over or through the atomizer **141**, where vaporizable material **102** in the gas phase is entrained into the air. The heating element can be activated via the controller **104**, which can optionally be a part of a vaporizer body **110** as discussed herein, causing current to pass from the power source **112** through a circuit including the resistive heating element, which is optionally part of a vaporizer cartridge **120** as discussed herein. As noted herein, the entrained vaporizable material **102** in the gas phase can condense as it passes through the remainder of the airflow path such that an inhalable dose of the vaporizable material **102** in an aerosol form can be delivered from the air outlet (for example, the mouthpiece **130**) for inhalation by a user.

(25) Activation of the heating element can be caused by automatic detection of a puff based on one or more signals generated by one or more of a sensor **113**. The sensor **113** and the signals generated by the sensor **113** can include one or more of: a pressure sensor or sensors disposed to detect pressure along the airflow path relative to ambient pressure (or optionally to measure changes in absolute pressure), a motion sensor or sensors (for example, an accelerometer) of the vaporizer device **100**, a flow sensor or sensors of the vaporizer device **100**, a capacitive lip sensor of the vaporizer device **100**, detection of interaction of a user with the vaporizer device **100** via one or more input devices **116** (for example, buttons or other tactile control devices of the vaporizer device **100**), receipt of signals from a computing device in communication with the vaporizer device **100**, and/or via other approaches for determining that a puff is occurring or imminent.

(26) As discussed herein, the vaporizer device **100** consistent with implementations of the current subject matter can be configured to connect (such as, for example, wirelessly or via a wired connection) to a computing device (or optionally two or more devices) in communication with the vaporizer device **100**. To this end, the controller **104** can include communication hardware **105**. The controller **104** can also include a memory **108**. The communication hardware **105** can include firmware and/or can be controlled by software for executing one or more cryptographic protocols for the communication.

(27) A computing device can be a component of a vaporizer system that also includes the vaporizer device **100**, and can include its own hardware for communication, which can establish a wireless communication channel with the communication hardware **105** of the vaporizer device **100**. For example, a computing device used as part of a vaporizer system can include a general-purpose computing device (such as a smartphone, a tablet, a personal computer, some other portable device such as a smartwatch, or the like) that executes software to produce a user interface for enabling a user to interact with the vaporizer device **100**. In other implementations of the current subject matter, such a device used as part of a vaporizer system can be a dedicated piece of hardware such as a remote control or other wireless or wired device having one or more physical or soft (i.e., configurable on a screen or other display device and selectable via user interaction with a touch-sensitive screen or some other input device like a mouse, pointer, trackball, cursor buttons, or the like) interface controls. The vaporizer device **100** can also include one or more outputs **117** or devices for providing information to the user. For example, the outputs **117** can include one or more light emitting diodes (LEDs) configured to provide feedback to a user based on a status

and/or in mode of operation of the vaporizer device **100**.

(28) In the example in which a computing device provides signals related to activation of the resistive heating element, or in other examples of coupling of a computing device with the vaporizer device **100** for implementation of various control or other functions, the computing device executes one or more computer instruction sets to provide a user interface and underlying data handling. In one example, detection by the computing device of user interaction with one or more user interface elements can cause the computing device to signal the vaporizer device **100** to activate the heating element to reach an operating temperature for creation of an inhalable dose of vapor/aerosol. Other functions of the vaporizer device **100** can be controlled by interaction of a user with a user interface on a computing device in communication with the vaporizer device **100**.

(29) The temperature of a resistive heating element of the vaporizer device **100** can depend on a number of factors, including an amount of electrical power delivered to the resistive heating element and/or a duty cycle at which the electrical power is delivered, conductive heat transfer to other parts of the electronic vaporizer device **100** and/or to the environment, latent heat losses due to vaporization of the vaporizable material **102** from the wicking element and/or the atomizer **141** as a whole, and convective heat losses due to airflow (i.e., air moving across the heating element or the atomizer **141** as a whole when a user inhales on the vaporizer device **100**). As noted herein, to reliably activate the heating element or heat the heating element to a desired temperature, the vaporizer device **100** may, in some implementations of the current subject matter, make use of signals from the sensor **113** (for example, a pressure sensor) to determine when a user is inhaling. The sensor **113** can be positioned in the airflow path and/or can be connected (for example, by a passageway or other path) to an airflow path containing an inlet for air to enter the vaporizer device **100** and an outlet via which the user inhales the resulting vapor and/or aerosol such that the sensor **113** experiences changes (for example, pressure changes) concurrently with air passing through the vaporizer device **100** from the air inlet to the air outlet. In some implementations of the current subject matter, the heating element can be activated in association with a user's puff, for example by automatic detection of the puff, or by the sensor **113** detecting a change (such as a pressure change) in the airflow path.

(30) The sensor **113** can be positioned on or coupled to (i.e., electrically or electronically connected, either physically or via a wireless connection) the controller **104** (for example, a printed circuit board assembly or other type of circuit board). To take measurements accurately and maintain durability of the vaporizer device **100**, it can be beneficial to provide a seal **127** resilient enough to separate an airflow path from other parts of the vaporizer device **100**. The seal **127**, which can be a gasket, can be configured to at least partially surround the sensor **113** such that connections of the sensor **113** to the internal circuitry of the vaporizer device **100** are separated from a part of the sensor **113** exposed to the airflow path. In an example of a cartridge-based vaporizer, the seal **127** can also separate parts of one or more electrical connections between the vaporizer body **110** and the vaporizer cartridge **120**. Such arrangements of the seal **127** in the vaporizer device **100** can be helpful in mitigating against potentially disruptive impacts on vaporizer components resulting from interactions with environmental factors such as water in the vapor or liquid phases, other fluids such as the vaporizable material **102**, etc., and/or to reduce the escape of air from the designated airflow path in the vaporizer device **100**. Unwanted air, liquid or other fluid passing and/or contacting circuitry of the vaporizer device **100** can cause various unwanted effects, such as altered pressure readings, and/or can result in the buildup of unwanted material, such as moisture, excess vaporizable material **102**, etc., in parts of the vaporizer device **100** where they can result in poor pressure signal, degradation of the sensor **113** or other components, and/or a shorter life of the vaporizer device **100**. Leaks in the seal **127** can also result in a user inhaling air that has passed over parts of the vaporizer device **100** containing, or constructed of, materials that may not be desirable to be inhaled.

(31) In some implementations, the vaporizer body **110** includes the controller **104**, the power

source **112** (for example, a battery), one more of the sensor **113**, charging contacts (such as those for charging the power source **112**), the seal **127**, and a cartridge receptacle **118** configured to receive the vaporizer cartridge **120** for coupling with the vaporizer body **110** through one or more of a variety of attachment structures. In some examples, the vaporizer cartridge **120** includes the reservoir **140** for containing the vaporizable material **102**, and the mouthpiece **130** has an aerosol outlet for delivering an inhalable dose to a user. The vaporizer cartridge **120** can include the atomizer **141** having a wicking element and a heating element. Alternatively, one or both of the wicking element and the heating element can be part of the vaporizer body **110**. In implementations in which any part of the atomizer **141** (i.e., heating element and/or wicking element) is part of the vaporizer body **110**, the vaporizer device **100** can be configured to supply vaporizable material **102** from the reservoir **140** in the vaporizer cartridge **120** to the part(s) of the atomizer **141** included in the vaporizer body **110**.

(32) Cartridge-based configurations for the vaporizer device **100** that generate an inhalable dose of a vaporizable material **102** that is not a liquid, via heating of a non-liquid material, are also within the scope of the current subject matter. For example, the vaporizer cartridge **120** can include a mass of a plant material that is processed and formed to have direct contact with parts of one or more resistive heating elements, and the vaporizer cartridge **120** can be configured to be coupled mechanically and/or electrically to the vaporizer body **110** that includes the controller **104**, the power source **112**, and one or more receptacle contacts **125a** and **125b** configured to connect to one or more corresponding cartridge contacts **124a** and **124b** and complete a circuit with the one or more resistive heating elements.

(33) In an embodiment of the vaporizer device **100** in which the power source **112** is part of the vaporizer body **110**, and a heating element is disposed in the vaporizer cartridge **120** and configured to couple with the vaporizer body **110**, the vaporizer device **100** can include electrical connection features (for example, means for completing a circuit) for completing a circuit that includes the controller **104** (for example, a printed circuit board, a microcontroller, or the like), the power source **112**, and the heating element (for example, a heating element within the atomizer **141**). These features can include one or more contacts (referred to herein as cartridge contacts **124a** and **124b**) on a bottom surface of the vaporizer cartridge **120** and at least two contacts (referred to herein as receptacle contacts **125a** and **125b**) disposed near a base of the cartridge receptacle **118** of the vaporizer device **100** such that the cartridge contacts **124a** and **124b** and the receptacle contacts **125a** and **125b** make electrical connections when the vaporizer cartridge **120** is inserted into and coupled with the cartridge receptacle **118**. The circuit completed by these electrical connections can allow delivery of electrical current to a heating element and can further be used for additional functions, such as measuring a resistance of the heating element for use in determining and/or controlling a temperature of the heating element based on a thermal coefficient of resistivity of the heating element.

(34) In some implementations of the current subject matter, the cartridge contacts **124a** and **124b** and the receptacle contacts **125a** and **125b** can be configured to electrically connect in either of at least two orientations. In other words, one or more circuits necessary for operation of the vaporizer device **100** can be completed by insertion of the vaporizer cartridge **120** into the cartridge receptacle **118** in a first rotational orientation (around an axis along which the vaporizer cartridge **120** is inserted into the cartridge receptacle **118** of the vaporizer body **110**) such that the cartridge contact **124a** is electrically connected to the receptacle contact **125a** and the cartridge contact **124b** is electrically connected to the receptacle contact **125b**. Furthermore, the one or more circuits necessary for operation of the vaporizer device **100** can be completed by insertion of the vaporizer cartridge **120** in the cartridge receptacle **118** in a second rotational orientation such that cartridge contact **124a** is electrically connected to the receptacle contact **125b** and cartridge contact **124b** is electrically connected to the receptacle contact **125a**.

(35) In one example of an attachment structure for coupling the vaporizer cartridge **120** to the

vaporizer body **110**, the vaporizer body **110** includes one or more detents (for example, dimples, protrusions, etc.) protruding inwardly from an inner surface of the cartridge receptacle **118**, additional material (such as metal, plastic, etc.) formed to include a portion protruding into the cartridge receptacle **118**, and/or the like. One or more exterior surfaces of the vaporizer cartridge **120** can include corresponding recesses (not shown in FIG. 1A) that can fit and/or otherwise snap over such detents or protruding portions when the vaporizer cartridge **120** is inserted into the cartridge receptacle **118** on the vaporizer body **110**. When the vaporizer cartridge **120** and the vaporizer body **110** are coupled (e.g., by insertion of the vaporizer cartridge **120** into the cartridge receptacle **118** of the vaporizer body **110**), the detents or protrusions of the vaporizer body **110** can fit within and/or otherwise be held within the recesses of the vaporizer cartridge **120**, to hold the vaporizer cartridge **120** in place when assembled. Such an assembly can provide enough support to hold the vaporizer cartridge **120** in place to ensure good contact between the cartridge contacts **124a** and **124b** and the receptacle contacts **125a** and **125b**, while allowing release of the vaporizer cartridge **120** from the vaporizer body **110** when a user pulls with reasonable force on the vaporizer cartridge **120** to disengage the vaporizer cartridge **120** from the cartridge receptacle **118**.

(36) In some implementations, the vaporizer cartridge **120**, or at least an insertable end **122** of the vaporizer cartridge **120** configured for insertion in the cartridge receptacle **118**, can have a non-circular cross section transverse to the axis along which the vaporizer cartridge **120** is inserted into the cartridge receptacle **118**. For example, the non-circular cross section can be approximately rectangular, approximately elliptical (i.e., have an approximately oval shape), non-rectangular but with two sets of parallel or approximately parallel opposing sides (i.e., having a parallelogram-like shape), or other shapes having rotational symmetry of at least order two. In this context, approximate shape indicates that a basic likeness to the described shape is apparent, but that sides of the shape in question need not be completely linear and vertices need not be completely sharp. Rounding of both or either of the edges or the vertices of the cross-sectional shape is contemplated in the description of any non-circular cross section referred to herein.

(37) The cartridge contacts **124a** and **124b** and the receptacle contacts **125a** and **125b** can take various forms. For example, one or both sets of contacts can include conductive pins, tabs, posts, receiving holes for pins or posts, or the like. Some types of contacts can include springs or other features to facilitate better physical and electrical contact between the contacts on the vaporizer cartridge **120** and the vaporizer body **110**. The electrical contacts can optionally be gold-plated, and/or include other materials.

(38) FIG. 1B illustrates an embodiment of the vaporizer body **110** and the cartridge receptacle **118** into which the vaporizer cartridge **120** can be releasably inserted. FIG. 1B shows a top view of the vaporizer device **100** illustrating the vaporizer cartridge **120** positioned for insertion into the vaporizer body **110**. When a user puffs on the vaporizer device **100**, air can pass between an outer surface of the vaporizer cartridge **120** and an inner surface of the cartridge receptacle **118** on the vaporizer body **110**. Air can then be drawn into the insertable end **122** of the cartridge, through the vaporization chamber that includes or contains the heating element and wick, and out through an outlet of the mouthpiece **130** for delivery of the inhalable aerosol to a user. The reservoir **140** of the vaporizer cartridge **120** can be formed in whole or in part from translucent material such that a level of the vaporizable material **102** is visible within the vaporizer cartridge **120**. The mouthpiece **130** can be a separable component of the vaporizer cartridge **120** or can be integrally formed with other component(s) of the vaporizer cartridge **120** (for example, formed as a unitary structure with the reservoir **140** and/or the like).

(39) Further to the discussion above regarding the electrical connections between the vaporizer cartridge **120** and the vaporizer body **110** being reversible such that at least two rotational orientations of the vaporizer cartridge **120** in the cartridge receptacle **118** are possible, in some embodiments of the vaporizer device **100**, the shape of the vaporizer cartridge **120**, or at least a shape of the insertable end **122** of the vaporizer cartridge **120** that is configured for insertion into

the cartridge receptacle **118**, can have rotational symmetry of at least order two. In other words, the vaporizer cartridge **120** or at least the insertable end **122** of the vaporizer cartridge **120** can be symmetrical upon a rotation of 180° around an axis along which the vaporizer cartridge **120** is inserted into the cartridge receptacle **118**. In such a configuration, the circuitry of the vaporizer device **100** can support identical operation regardless of which symmetrical orientation of the vaporizer cartridge **120** occurs.

(40) FIGS. **1C-1D** illustrate example features that can be included in embodiments of the vaporizer device **100** consistent with implementations of the current subject matter. FIGS. **1C** and **1D** show top views of an example of the vaporizer device **100** before (FIG. **1C**) and after (FIG. **1D**) connecting the vaporizer cartridge **120** to the vaporizer body **110**.

(41) FIG. **1E** illustrates a perspective view of one variation of the vaporizer cartridge **120** holding the vaporizable material **102**. Any appropriate vaporizable material **102** can be contained within the vaporizer cartridge **120** (for example, within the reservoir **140**), including solutions of nicotine or other organic materials.

(42) FIG. **1F** shows a perspective view of another example of a vaporizer device **100** including a vaporizer body **110** coupled to a separable vaporizer cartridge **120**. As illustrated, the vaporizer device **100** can include one or more outputs **117** (for example, LEDs) configured to provide information to a user based on a status, mode of operation, and/or the like, of the vaporizer device **100**. In some aspects, the one or more outputs **117** can include a plurality of LEDs (i.e., two, three, four, five, or six LEDs). The one or more outputs **117** (i.e., each individual LED) can be configured to display light in one or more colors (for example, white, red, blue, green, yellow, etc.). The one or more outputs **117** can be configured to display different light patterns (for example, by illuminating specific LEDs, varying a light intensity of one or more of the LEDs over time, illuminating one or more LEDs with a different color, and/or the like) to indicate different statuses, modes of operation, and/or the like of the vaporizer device **100**. In some implementations, the one or more outputs **117** can be proximal to and/or at least partially disposed within a bottom end region **160** of the vaporizer device **100**. The vaporizer device **100** may, additionally or alternatively, include externally accessible charging contacts **128**, which can be proximate to and/or at least partially disposed within the bottom end region **160** of the vaporizer device **100**.

(43) Referring to the block diagram of FIG. **2A**, a vaporizer device **200** can include an atomizer **241** configured to cause a vaporizable material **202** to be converted from a condensed form (such as a solid, a liquid, a solution, a suspension, a part of an at least partially unprocessed plant material, etc.) to the gas phase. The atomizer **241** in the vaporizer device **200** can be configured to include a hybrid gel-fiber wick **260**. The atomizer **241** can include a hybrid gel-fiber wick **260** (i.e., a wick) configured to convey an amount of the vaporizable material **202** to a part of the atomizer **241** that includes a heating element **242** (not shown in FIG. **2A**).

(44) For example, the hybrid gel-fiber wick **260** can be configured to draw the vaporizable material **202** from a reservoir **240** configured to contain the vaporizable material **202**, such that the vaporizable material **202** can be vaporized by heat delivered from a heating element **242**. In some embodiments of the current subject matter, capillary action, diffusion, and attractive intermolecular forces can pull vaporizable material **202** into the hybrid gel-fiber wick **260** for vaporization by the heating element **242**, and air can return to the reservoir **240** to at least partially equalize pressure in the reservoir **240**. Various methods of allowing air back into the reservoir **240** to equalize pressure are within the scope of the current subject matter.

(45) The heating element **242** can include one or more of a conductive heater, a radiative heater, and/or a convective heater. One type of heating element **242** is a resistive heating element **242**, which can include a material (such as a metal or alloy, for example a nickel-chromium alloy, or a non-metallic resistor) configured to dissipate electrical power in the form of heat when electrical current is passed through one or more resistive segments of the heating element **242**. In implementations of the current subject matter, the atomizer **241** can include a heating element **242**

which includes a resistive coil or other heat conducting element wrapped around, positioned within, integrated into a bulk shape of, pressed into thermal contact with, or otherwise arranged relative to the gel coating **244** of the hybrid gel-fiber wick **260** to deliver heat to the hybrid gel-fiber wick **260** and cause the vaporizable material **202** drawn from the reservoir **240** by the hybrid gel-fiber wick **260** to be vaporized for subsequent inhalation by a user in a gas and/or a condensed phase (for example, aerosol particles or droplets).

(46) FIG. 2B illustrates an embodiment of a hybrid gel-fiber wick **260** positioned within the vaporizer cartridge **220** of FIG. 2A. The hybrid gel-fiber wick **260** includes a fiber core **250** and a gel coating **244**, each in thermal contact with the heating element **242**. The fiber core **250** can include a plurality of fibers bundled together to form a fiber core **250** with the fibers including silica, cotton, or other suitable fibrous materials. The fiber core **250** includes a first end portion **251**, a second end portion **253**, and a middle portion **252**. The gel coating **244** is disposed on the middle portion **252** of the fiber core **250**, with first end portion **251** and the second end portion **253** remaining uncoated. When the hybrid gel-fiber wick **260** is disposed in the cartridge **220**, the first end portion **251** and the second end portion **253**, each not coated with the gel, are located within the reservoir **240**. The middle portion **252** coated with gel coating **244** is located within the atomizer **241** of the cartridge **220**.

(47) The gel coating **244** can include a silicon-based gel, a polymeric gel, or other suitable gel compositions. In embodiments, the gel comprises silicon. In embodiments, the gel comprises a silane. In embodiments, the gel comprises a silicate. In embodiments, the gel comprises tetraethoxysilane. In embodiments, the gel is an inorganic gel. In embodiments, the gel is an organic gel.

(48) The arrows **290** depicted within the vaporizer cartridge **220** indicate the flow of vaporizable material **202** into the hybrid gel-fiber wick **260**. This flow of vaporizable material **202** can be due to a combination of capillary pressure between the fiber core **250** and the gel coating **244** of the hybrid gel-fiber wick **260**, diffusion of the vaporizable material **202** through the gel coating **244**, and attractive intermolecular forces between the hybrid gel-fiber wick **260** and the vaporizable material **202**. This flow of vaporizable material **202** can result in increased and consistent TPM delivery to the user, as compared to a traditional, uncoated wick. As shown in the exploded view of the hybrid gel-fiber wick **260** in FIG. 2B, the first end portion **251** and the second end portion **253** remains uncoated with the gel coating **244**, such that the initial contact between the hybrid gel-fiber wick **260** and the vaporizable material **202**, and transport out of the reservoir **240** is via capillary action. The concentration gradient between the fiber core **250** of the hybrid gel-fiber wick **260** and the gel coating **244** of the hybrid gel-fiber wick **260** creates a diffusive driving force.

(49) In embodiments, the hybrid gel-fiber wick **260** includes the heating element **242**, such as a heating coil, disposed between the fiber core **250** and the gel coating **244** of the hybrid gel-fiber wick **260**. In other embodiments, the hybrid gel-fiber wick **260** does not include the heating element **242** disposed between the fiber core **250** and the gel coating **244** of the hybrid gel-fiber wick **260**.

(50) FIG. 3 depicts a fiber core **250**, comprising a plurality of fibers bundled together, that is wrapped with a heating element **242**. Subsequently, a gel coating **244** is disposed on a middle portion **252** to form the hybrid gel-fiber wick **260**. The gel coating **244** is in contact with the heating element **242** and the middle portion **252** of the hybrid gel-fiber wick **260**. In embodiments, the gel coating **244** coats the heating element **242** and the middle portion **252** to a thickness of about 500 microns. The thickness of the gel coating **244** may vary without departing from the scope of this disclosure. In embodiments, the gel coating **244** is applied by dispensing the gel directly onto the fiber core **250** using a needle, for example by using a syringe. In embodiments, the gel coating **244** is applied by printing the gel directly onto the fiber core **250** using a printer, for example by using a 3D printer. In embodiments, the gel coating **244** is applied by molding the gel directly onto the fiber core **250** using a mold. In other embodiments, the gel coating **244** is applied

to the hybrid gel-fiber wick **260** prior to wrapping the heating element **242** around the hybrid gel-fiber wick **260**, and prior to inserting the hybrid gel-fiber wick **260** into the vaporizer cartridge **220**. (51) The mechanism for generating aerosol within the vaporizer cartridge **220** includes heating the coil of the heating element **242**, which in turn heats the gel coating **244** of the hybrid gel-fiber wick **260** that has been saturated with vaporizable material **202**. The gel coating **244** generates aerosol at a lower temperature to reduce any generation of harmful and potentially harmful chemicals (HPHCs). The gel coating **244** also provides thermal stability that can also enhance the thermal transfer of heat from the heating element **242** to the hybrid gel-fiber wick **260**, which reinforces the ability of the hybrid gel-fiber wick **260** to maintain consistent TPM delivery across all vaporizer cartridges **220** manufactured with a hybrid gel-fiber wick **260**.

(52) Using a hybrid gel-fiber wick **260** in a vaporizer device **200** can resolve the variability in TPM delivery between vaporizer cartridges **220** that typically occurs when using a traditional wick. The hybrid gel-fiber wick **260** can enhance the replenish rate of vaporizable material **202** into the hybrid gel-fiber wick **260** and the vaporizable material **202** capacity of the hybrid gel-fiber wick **260**, thereby eliminating the inconsistencies in average amount of aerosol delivered to the user per puff, and increasing the average amount of aerosol generated each time the vaporizer device **200** is puffed. As a result of these benefits, the temperature of the heating element **242** may be lowered thereby reducing power consumption and reducing the generation of any HPHCs.

(53) It has been observed that a positive relationship exists between the tightness of a heating coil wrapped around a wicking element, and the resulting TPM generated during operation. This positive relationship is due to the fact that an increased contact area between the wicking element and the heating coil increases the thermal energy transfer. Therefore, variations in the tightness of the heating coil around the wicking element can create variations in TPM delivered. By utilizing a hybrid gel-fiber wick, the variations in TPM delivery can be reduced due to the gel coating **244** of the hybrid gel-fiber wick, which is in contact with the heating element and has the inherent ability to swell and thereby maximize the surface area in contact with the heating element. This can establish consistent TPM delivery across all vaporizer cartridges manufactured with a hybrid gel-fiber wick, and can also increase TPM delivered to the user per puff.

(54) The hybrid gel-fiber wick has the capability to increase the replenish rate of vaporizable material into the hybrid gel-fiber wick and ultimately bring consistency to the aerosol delivered to the user over consecutive puffs. The primary driving force of saturation of a traditional wick is via capillary action, wherein the vaporizable material is able to flow through the wick's matrices by exhibiting an affinity towards its composition. However, due to the viscous nature of the vaporizable material, capillary action alone may not replenish the wick fast enough to maintain consistent TPM delivery across consecutive puffs, and an initial spike in TPM may occur at the initial puff due to the fully saturated wick. A prolonged time interval may be necessary for a traditional wick to become fully saturated again, and the negative headspace pressure created within the vaporizer cartridge by consecutive puffs may further reduce the traditional wick's capillary pressure and decrease its ability to replenish efficiently. The hybrid gel-fiber wick can decrease the replenish rate by introducing diffusion mechanisms across the fiber core and the gel coating of the hybrid gel-fiber wick, thereby creating more resistance to negative headspace pressure within the reservoir of the vaporizer cartridge.

(55) FIG. 4 illustrates a puff cycle of a hybrid gel-fiber wick **260**. At the beginning of a puff (left side), the gel coating **244** and the fiber core **250** of the hybrid gel-fiber wick **260** are saturated with a vaporizable material. After the user has puffed (right side), the gel coating **244** is no longer fully saturated with vaporizable material. The exploded view of the interface between the fiber core **250** and the gel coating **244** after the user has puffed illustrates the transport of vaporizable material from the fiber core into the gel coating **244**, thereby saturating the gel coating **244** and readying the hybrid gel-fiber wick **260** for the next puff cycle. Due to a difference in concentration of vaporizable material between the fiber core **250** and the gel coating **244** after a puff, the hybrid gel-

fiber wick **260** can draw vaporizable material from a reservoir until an equilibrium is established between the fiber core **250** and the gel coating **244**. The smaller pore size of the gel coating **244** relative to the fiber core **250** can also significantly increase the holding capacity of the hybrid gel-fiber wick **260**, compared to that of a traditional fiber wick. Additionally, combining the ability of the gel coating **244** of the hybrid gel-fiber wick **260** to swell with the creation of a formulation for the gel coating **244** that exhibits an affinity to the constituents of the vaporizable material creates attracting intermolecular forces between the vaporizable material and the hybrid gel-fiber wick **260**, thereby increasing the average TPM delivered per puff. These additional driving forces introduced by the hybrid gel-fiber wick **260** can improve the kinetics of the vaporizable material when it is within the hybrid gel-fiber wick **260**, thus increasing the replenish rate and holding capacity and ensuring that the user will experience consistent, increased aerosol delivery over the course of a use session.

Example 1: Tetraethoxysilane Gel Preparation Protocol

(56) The purpose of this protocol is to prepare a tetraethoxysilane (TEOS) e-liquid based gel, and also to prepare a tetraethoxysilane 5% nicotine gel without propylene glycol or a glycerol.

(57) The following materials were used: tetraethoxysilane (CAS #78-10-4), nicotine (CAS #54-11-5), benzoic acid crystals (CAS #65-85-0), ethanol (CAS #64-17-5), hydrochloric acid (1.0 M, CAS #7647-01-0), deionized water (CAS #7732-18-5), Virginia tobacco (5% nicotine) e-liquid, scintillation vial and cap, stir bar, hot plate, spatula, analytical balance, and a sonication bath.

(58) For the benzoic acid solution preparation, 5 mL of liquid nicotine was heated with a stir bar in a 20 mL scintillation vial at 80 degrees Celsius. 3.8 mg of benzoic acid crystals were added to the scintillation vial. The stir bar was set to stir at 500 RPM and the solution was allowed to mix for one hour until all benzoic crystals had completely dissolved. The solution was cooled before use.

(59) For preparation of a 30% by volume tetraethoxysilane (TEOS) formulation, 3 mL of TEOS was added to a 20 mL scintillation vial. 3 mL ethanol was added into the vial. The solution was mixed thoroughly. 4 mL of water were slowly added into the vial, mixing thoroughly as more water was added. Once the mixture was homogenously mixed, 100 μ L of benzoic acid solution (1.0 M) and 100 μ L of HCl (1.0 M) were slowly added dropwise, stirring the solution between drop additions. The solution was heated at 60° C. on a hot plate with a stir bar at 500 RPM for 2 hours. The solution was allowed to cool before using.

(60) For preparation of a 7.5% by volume TEOS formulation, 0.7 mL of TEOS was added into a 20 mL scintillation vial. 4 mL ethanol was added into the vial. The solution was mixed thoroughly. Slowly, 5.3 mL of water was added into the vial, mixing thoroughly as more water was added. Once the mixture was homogenously mixed, 100 μ L of benzoic acid solution (1.0 M) and 100 μ L of HCl (1.0 M) were slowly added (dropwise), stirring the solution between drop additions. The solution was heated at 60° C. on a hot plate with a stir bar at 500 RPM for 2 hours and allowed to cool before using.


(61) For preparation of a TEOS e-liquid gel, 7.5 mL of Virginia tobacco (5% nicotine) e-liquid was added into a 20 mL scintillation vial. 2.5 mL of 30% by volume TEOS formulation (prepared as described previously) was added into the vial. It was ensured that the formulation was at room temperature. The solution was mixed thoroughly until homogenous. The scintillation vial was capped and the solution was allowed to crosslink overnight.

(62) For preparation of a TEOS 5% nicotine gel, 9.5 mL of 7.5% by volume TEOS Formulation (prepared as described previously) was added into a 20 mL scintillation vial. It was ensured that the formulation was at room temperature. 0.5 mL of benzoic acid solution (prepared as described previously) was added into the vial. The solution was mixed thoroughly until homogenous. The scintillation vial was capped and the solution was allowed to crosslink overnight.

Example 2: Wick Coating Optimization

(63) To ensure maximum functionality of a hybrid gel-fiber wick, various viscosities of the gel portion of the hybrid gel-fiber wick were tested. The gel portion comprises TEOS, and in order to

increase the viscosity of the gel portion, various TEOS solutions were prepared by adding varying amounts of 50:50 propylene glycol/vegetable glycerin (PG/VG.) Increased viscosity, along with precise application of the gel portion to the fiber portion of the hybrid gel-fiber wick using a precise 10 uL syringe, enabled more precise control over the application of the TEOS gel solution. Along with varying viscosity, different volumes of gel to be applied to the hybrid gel-fiber wick were tested to see if there was an effect on TPM. Table 1 below shows a matrix of TEOS/PG:VG formulations tested.

(64) TABLE-US-00001 TABLE 1 TEOS/PG:VG Formulations Matrices 

(65) To establish a baseline, or control, TPM measurement, a traditional wick was utilized. The instrument used was the Puffmaster 3000, and Table 2 below shows the instrument parameters.

(66) TABLE-US-00002 TABLE 2 Puffmaster 3000 Parameters Instrument Parameters Instrument Puffmaster 3000 Puff Volume 70 cc Puff Duration 3 seconds Puff Interval 30 seconds

(67) The Puffmaster 3000 has eight channels, therefore the wicks with 1 uL TEOS gel solution applied for wick modification were omitted from testing. Qualitatively, 1 uL injection volume did not appear to coat the fiber core as thoroughly as 3 uL or 5 uL injection volumes, due to the small amount of gel solution. Table 3 below outlines the solutions tested in each channel of the Puffmaster 3000.

(68) TABLE-US-00003 TABLE 3 Solutions Under Testing Channel 1 Control Channel 2 3 uL 1:1 TEOS:50% PG/VG Channel 3 3 uL 1:3 TEOS:50% PG/VG Channel 4 3 uL 1:5 TEOS:50% PG/VG Channel 5 5 uL 1:1 TEOS:50% PG/VG Channel 6 5 uL 1:3 TEOS:50% PG/VG Channel 7 5 uL 1:5 TEOS:50% PG/VG

(69) As shown in FIG. 5, TPM data was collected using the above TEOS solutions. Ten puff intervals were performed, and the TPM delivered per puff interval was calculated by dividing the mass change during puffing by the number of puffs in the puff interval (10). As can be seen in the graph, the 3 uL and 5 uL volumes of 1:5 TEOS:50% PG/VG consistently exhibited higher TPM than that of the control wick, and the 3 uL and 5 uL volumes of 1:3 TEOS:50% PG/VG and 1:1 TEOS:50% PG/VG consistently exhibited lower TPM than that of the control wick. These initial TPM tests show that the injection volume has little to no effect on TPM delivered to the user, however higher viscosity of the TEOS solution appears to increase TPM. The consistent TPM observed among the hybrid gel-fiber wicks suggests that the gel structure is not collapsing during the puffing sequence.

(70) As shown in FIG. 6, all TPM data points were plotted for their respective formulations, regardless of the volume of gel solution applied on the wick, in order to further investigate the effect of viscosity on TPM. Trend lines were plotted, and the coefficient of correlation (R) was calculated by taking the square root of the coefficient of determination ($R_{\text{sup.2}}$). With $R=0.9798$, it was determined that there exists a positive relationship between increased viscosity of TEOS gel solution and increased TPM delivered to the user. Increased viscosity can enable more controlled application of the TEOS gel solution onto the fiber core, as more time is required for the TEOS gel solution to disperse through the matrices of the fiber core.

(71) FIG. 7 is a graph of TPM as a function of replenish rate for various TEOS gel solutions. To observe the time required for each hybrid gel-fiber wick to be fully replenished, various TEOS gel solutions and volumes were puffed after various replenish times, starting at 10 minutes and increasing by increments of 10 minutes. This was done to measure the amount of time the user would have to wait between puffing sessions to experience the maximum aerosol output, as the hybrid gel-fiber wick replenishes via capillary action and diffusion mechanisms. As can be seen in FIG. 7, hybrid gel-fiber wicks show better holding capacity for vaporizable material, and better replenish rates, by displaying consistent TPM across all time intervals. The control wick showed an initially high TPM, however it is unable to recover to initial conditions, even with a longer replenish time. Volume appears to have little to no effect on replenish rate. The high viscosity formulation, 1:5 TEOS/50% PG/VG, showed the highest TPM and were relatively consistent

through all time points compared to the control wick.

(72) A vaporizer cartridge containing the hybrid gel-fiber wick can be manufactured according to a method **800**, as shown in FIG. **8**. In step **805**, the method includes providing a plurality of fibers bundled together to form a fiber core, the fiber core having a first end portion, a second end portion, and a middle portion therebetween. In step **815**, the middle portion of the fiber core is wrapped with a heating element. In step **825**, the middle portion of the fiber core can be coated with gel, resulting in forming the hybrid gel-fiber wick in step **835**. In step **845**, the hybrid gel-fiber wick can be inserted into the vaporizer cartridge, the middle portion of the fiber core being disposed in an atomizer, and the first end portion and the second end portion of the fiber core being disposed in a reservoir of the vaporizer cartridge. In step **850**, the reservoir is filled with a vaporizable material.

Terminology

(73) As used herein, the terms “wick” or “wicking element” include any material capable of causing fluid transport (e.g. liquid flow) from one place to another.

(74) When a feature or element is herein referred to as being “on” another feature or element, it can be directly on the other feature or element or intervening features and/or elements can also be present. In contrast, when a feature or element is referred to as being “directly on” another feature or element, there are no intervening features or elements present. It will also be understood that, when a feature or element is referred to as being “connected”, “attached” or “coupled” to another feature or element, it can be directly connected, attached or coupled to the other feature or element or intervening features or elements can be present. In contrast, when a feature or element is referred to as being “directly connected”, “directly attached” or “directly coupled” to another feature or element, there are no intervening features or elements present.

(75) Although described or shown with respect to one embodiment, the features and elements so described or shown can apply to other embodiments. It will also be appreciated by those of skill in the art that references to a structure or feature that is disposed “adjacent” another feature can have portions that overlap or underlie the adjacent feature.

(76) Terminology used herein is for the purpose of describing particular embodiments and implementations only and is not intended to be limiting. For example, as used herein, the singular forms “a,” “an,” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise.

(77) In the descriptions above and in the claims, phrases such as “at least one of” or “one or more of” may occur followed by a conjunctive list of elements or features. The term “and/or” may also occur in a list of two or more elements or features. Unless otherwise implicitly or explicitly contradicted by the context in which it is used, such a phrase is intended to mean any of the listed elements or features individually or any of the recited elements or features in combination with any of the other recited elements or features. For example, the phrases “at least one of A and B;” “one or more of A and B;” and “A and/or B” are each intended to mean “A alone, B alone, or A and B together.” A similar interpretation is also intended for lists including three or more items. For example, the phrases “at least one of A, B, and C;” “one or more of A, B, and C;” and “A, B, and/or C” are each intended to mean “A alone, B alone, C alone, A and B together, A and C together, B and C together, or A and B and C together.” Use of the term “based on,” above and in the claims is intended to mean, “based at least in part on,” such that an unrecited feature or element is also permissible.

(78) Spatially relative terms, such as “forward”, “rearward”, “under”, “below”, “lower”, “over”, “upper” and the like, may be used herein for ease of description to describe one element or feature's relationship to another element(s) or feature(s) as illustrated in the figures. It will be understood that the spatially relative terms are intended to encompass different orientations of the device in use or operation in addition to the orientation depicted in the figures. For example, if a device in the figures is inverted, elements described as “under” or “beneath” other elements or features would

then be oriented “over” the other elements or features. Thus, the exemplary term “under” can encompass both an orientation of over and under. The device can be otherwise oriented (rotated 90 degrees or at other orientations) and the spatially relative descriptors used herein interpreted accordingly. Similarly, the terms “upwardly”, “downwardly”, “vertical”, “horizontal” and the like are used herein for the purpose of explanation only unless specifically indicated otherwise.

(79) Although the terms “first” and “second” may be used herein to describe various features/elements (including steps), these features/elements should not be limited by these terms, unless the context indicates otherwise. These terms may be used to distinguish one feature/element from another feature/element. Thus, a first feature/element discussed below could be termed a second feature/element, and similarly, a second feature/element discussed below could be termed a first feature/element without departing from the teachings provided herein.

(80) As used herein in the specification and claims, including as used in the examples and unless otherwise expressly specified, all numbers can be read as if prefaced by the word “about” or “approximately,” even if the term does not expressly appear. The phrase “about” or “approximately” may be used when describing magnitude and/or position to indicate that the value and/or position described is within a reasonable expected range of values and/or positions. For example, a numeric value can have a value that is $\pm 0.1\%$ of the stated value (or range of values), $\pm 1\%$ of the stated value (or range of values), $\pm 2\%$ of the stated value (or range of values), $\pm 5\%$ of the stated value (or range of values), $\pm 10\%$ of the stated value (or range of values), etc. Any numerical values given herein should also be understood to include about or approximately that value, unless the context indicates otherwise. For example, if the value “10” is disclosed, then “about 10” is also disclosed. Any numerical range recited herein is intended to include all sub-ranges subsumed therein. It is also understood that when a value is disclosed that “less than or equal to” the value, “greater than or equal to the value” and possible ranges between values are also disclosed, as appropriately understood by the skilled artisan. For example, if the value “X” is disclosed the “less than or equal to X” as well as “greater than or equal to X” (e.g., where X is a numerical value) is also disclosed. It is also understood that the throughout the application, data is provided in a number of different formats, and that this data, represents endpoints and starting points, and ranges for any combination of the data points. For example, if a particular data point “10” and a particular data point “15” are disclosed, it is understood that greater than, greater than or equal to, less than, less than or equal to, and equal to 10 and 15 are considered disclosed as well as between 10 and 15. It is also understood that each unit between two particular units are also disclosed. For example, if 10 and 15 are disclosed, then 11, 12, 13, and 14 are also disclosed.

(81) Although various illustrative embodiments are described above, any of a number of changes can be made to various embodiments without departing from the teachings herein. For example, the order in which various described method steps are performed may often be changed in alternative embodiments, and in other alternative embodiments, one or more method steps may be skipped altogether. Optional features of various device and system embodiments may be included in some embodiments and not in others. Therefore, the foregoing description is provided primarily for exemplary purposes and should not be interpreted to limit the scope of the claims.

(82) One or more aspects or features of the subject matter described herein can be realized in digital electronic circuitry, integrated circuitry, specially designed application specific integrated circuits (ASICs), field programmable gate arrays (FPGAs) computer hardware, firmware, software, and/or combinations thereof. These various aspects or features can include implementation in one or more computer programs that are executable and/or interpretable on a programmable system including at least one programmable processor, which can be special or general purpose, coupled to receive data and instructions from, and to transmit data and instructions to, a storage system, at least one input device, and at least one output device. The programmable system or computing system can include clients and servers. A client and server are generally remote from each other and typically interact through a communication network. The relationship of client and server

arises by virtue of computer programs running on the respective computers and having a client-server relationship to each other.

(83) These computer programs, which can also be referred to programs, software, software applications, applications, components, or code, include machine instructions for a programmable processor, and can be implemented in a high-level procedural language, an object-oriented programming language, a functional programming language, a logical programming language, and/or in assembly/machine language. As used herein, the term “machine-readable medium” refers to any computer program product, apparatus and/or device, such as for example magnetic discs, optical disks, memory, and Programmable Logic Devices (PLDs), used to provide machine instructions and/or data to a programmable processor, including a machine-readable medium that receives machine instructions as a machine-readable signal. The term “machine-readable signal” refers to any signal used to provide machine instructions and/or data to a programmable processor. The machine-readable medium can store such machine instructions non-transitorily, such as for example as would a non-transient solid-state memory or a magnetic hard drive or any equivalent storage medium. The machine-readable medium can alternatively or additionally store such machine instructions in a transient manner, such as for example, as would a processor cache or other random access memory associated with one or more physical processor cores.

(84) The examples and illustrations included herein show, by way of illustration and not of limitation, specific embodiments in which the subject matter may be practiced. As mentioned, other embodiments may be utilized and derived there from, such that structural and logical substitutions and changes may be made without departing from the scope of this disclosure. Such embodiments of the inventive subject matter may be referred to herein individually or collectively by the term “invention” merely for convenience and without intending to voluntarily limit the scope of this application to any single invention or inventive concept, if more than one is, in fact, disclosed. Thus, although specific embodiments have been illustrated and described herein, any arrangement calculated to achieve the same purpose may be substituted for the specific embodiments shown. This disclosure is intended to cover any and all adaptations or variations of various embodiments. Combinations of the above embodiments, and other embodiments not specifically described herein, will be apparent to those of skill in the art upon reviewing the above description. Use of the term “based on,” herein and in the claims is intended to mean, “based at least in part on,” such that an unrecited feature or element is also permissible.

(85) The subject matter described herein can be embodied in systems, apparatus, methods, and/or articles depending on the desired configuration. The implementations set forth in the foregoing description do not represent all implementations consistent with the subject matter described herein. Instead, they are merely some examples consistent with aspects related to the described subject matter. Although a few variations have been described in detail herein, other modifications or additions are possible. In particular, further features and/or variations can be provided in addition to those set forth herein. For example, the implementations described herein can be directed to various combinations and subcombinations of the disclosed features and/or combinations and subcombinations of several further features disclosed herein. In addition, the logic flows depicted in the accompanying figures and/or described herein do not necessarily require the particular order shown, or sequential order, to achieve desirable results. Other implementations may be within the scope of the following claims.

Claims

1. A hybrid gel-fiber wick comprising: a plurality of fibers bundled together to form a fiber core, the fiber core having a first end portion, a second end portion, and a middle portion therebetween; a gel coating a portion of the fiber core; and a heating element, wherein the gel is in contact with the heating element.

2. The hybrid gel-fiber wick of claim 1, wherein the middle portion of the fiber core is coated by the gel coating.
 3. The hybrid gel-fiber wick of claim 1, wherein at least one of the first end portion or the second end portion of the fiber core is not coated by the gel coating.
 4. The hybrid gel-fiber wick of claim 1, wherein at least a portion of the heating element is disposed between the fiber core and the gel coating.
 5. The hybrid gel-fiber wick of claim 1, wherein the heating element comprises a nichrome wire.
 6. The hybrid gel-fiber wick of claim 1, wherein the heating element is spirally wound around the fiber core.
 7. The hybrid gel-fiber wick of claim 1, wherein the fiber core comprises a cotton material.
 8. The hybrid gel-fiber wick of claim 1, wherein the fiber core comprises a silica material.
 9. The hybrid gel-fiber wick of claim 1, wherein the gel comprises a polymer.
 10. The hybrid gel-fiber wick of claim 1, wherein the gel comprises at least one of a silicon, silane, silicate, or tetraethoxysilane.
 11. The hybrid gel-fiber wick of claim 1, wherein the gel coating is 250 microns to 500 microns in thickness.
 12. A cartridge comprising the hybrid gel-fiber wick of claim 1.
 13. The cartridge of claim 12, wherein the cartridge further comprises a reservoir configured to contain a vaporizable material, and a portion of the hybrid gel-fiber wick is disposed within the reservoir.
 14. The cartridge of claim 13, wherein at least one of the first end portion or the second end portion of the fiber core are disposed within the reservoir.
 15. The cartridge of claim 13, wherein the cartridge further comprises an atomizer configured to vaporize the vaporizable material.
 16. The cartridge of claim 15, wherein the middle portion of the fiber core is disposed within the atomizer.
 17. A device comprising the cartridge of claim 12 and a receptacle configured to receive the cartridge.
-