

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12388592
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Takata; Tomohumi et al.

Base station, terminal, and communication method

Abstract

A base station (**100, 300**) is provided with a transmitter and a receiver. The transmitter (**109**) transmits a downlink signal in a downlink transmission region, in a time unit that includes the downlink transmission region, an uplink transmission region, and a gap period that is a switching point between the downlink transmission region and the uplink transmission region. The receiver (**111**) receives an uplink signal in the uplink transmission region, in the time unit. Furthermore, a delay tolerant signal for which a delay is tolerated more than for the downlink signal and the uplink signal is mapped to within the gap period.

Inventors: Takata; Tomohumi (Ishikawa, JP), Iwai; Takashi (Ishikawa, JP), Suzuki; Hidetoshi (Kanagawa, JP), Horiuchi; Ayako (Kanagawa, JP), Loehr; Joachim (Hessen, DE), Yamamoto; Tetsuya (Kanagawa, JP)

Applicant: Panasonic Intellectual Property Corporation of America (Torrance, CA)

Family ID: 61074143

Assignee: Panasonic Intellectual Property Corporation of America (Torrance, CA)

Appl. No.: 18/516337

Filed: November 21, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240089052 A1	Mar. 14, 2024

Foreign Application Priority Data

JP	2016-154864	Aug. 05, 2016
----	-------------	---------------

Related U.S. Application Data

Publication Classification

Int. Cl.: **H04L5/00** (20060101); **H04L5/14** (20060101); **H04L27/00** (20060101); **H04L27/26** (20060101)

U.S. Cl.:

CPC **H04L5/0048** (20130101); **H04L5/0053** (20130101); **H04L5/143** (20130101);
H04L27/0006 (20130101); **H04L27/2607** (20130101);

Field of Classification Search

CPC: H04L (5/0048)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
10200992	12/2018	Dinan	N/A	N/A
11012208	12/2020	Takata	N/A	H04L 5/0055
2010/0273494	12/2009	Iwai	455/450	H04W 74/00
2013/0039233	12/2012	Dai et al.	N/A	N/A
2015/0043392	12/2014	Susitaival et al.	N/A	N/A
2015/0085721	12/2014	Meng	N/A	N/A
2015/0103704	12/2014	Skov et al.	N/A	N/A
2015/0341150	12/2014	Seo et al.	N/A	N/A
2015/0341910	12/2014	Hayashi et al.	N/A	N/A
2017/0086207	12/2016	Yokomakura et al.	N/A	N/A
2017/0222787	12/2016	Suzuki et al.	N/A	N/A
2017/0288841	12/2016	Park	N/A	H04L 1/1887
2018/0242372	12/2017	Yang et al.	N/A	N/A
2019/0089506	12/2018	Takeda et al.	N/A	N/A
2019/0150170	12/2018	Park et al.	N/A	N/A
2020/0322187	12/2019	He et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2015518667	12/2014	JP	N/A
WO 2014080744	12/2013	WO	N/A
WO 2015174504	12/2014	WO	N/A
WO 2016021580	12/2015	WO	N/A

OTHER PUBLICATIONS

International Search Report of PCT application No. PCT/JP2017/021088 dated Aug. 15, 2017.
cited by applicant
R1-164013, 3GPP TSG RAN WG1 #85, “Framework for beamformed access”, May 23, 2016.
cited by applicant
R1-165662, 3GPP TSG RAN WG1 #85, “WF on NR frame structure”, May 23, 2016. cited by
applicant
R1-165872, 3GPP TSG RAN WG1 #85, “WF on minimum HARQ Timing”, May 23, 2016. cited
by applicant
R1-165886, 3GPP TSG RAN WG1 #85, “WF on Scalable Numerology Symbol Boundary
Alignment”, May 23, 2016. cited by applicant
R1-165887, 3GPP TSG RAN WG1 #85, “WF on minimum HARQ Timing”, May 23, 2016. cited
by applicant
R1-166027, 3GPP TSG RAN WG1 #85, “WF on Frame Structure and Evaluation”, May 23, 2016.
cited by applicant

Primary Examiner: Mattis; Jason E

Attorney, Agent or Firm: Seed IP Law Group LLP

Background/Summary

TECHNICAL FIELD

(1) The present disclosure relates to a base station, a terminal, and a communication method.

BACKGROUND ART

(2) In downlink communication in mobile communication, generally, a base station (sometimes also referred to as an “eNB” or a “gNB”) transmits, to a terminal (sometimes also referred to as “UE (user equipment)”), a control signal for the terminal to receive data. The terminal decodes control information transmitted by the received control signal, and obtains information relating to frequency assignment, adaptive control, or the like required to receive data. The base station transmits, to the terminal, downlink data (a PDSCH: physical downlink shared channel) based on adaptive control, broadcast information (a BCH: broadcast channel) for notifying cell-specific information, a reference signal for estimating a downlink propagation path (for example, a CRS: cell-specific reference signal), an MBMS (multimedia broadcast and multicast service), or the like in frequency positions notified by the control information.

(3) Furthermore, in uplink communication in the mobile communication, generally, the base station transmits, to the terminal, a control signal for the terminal to transmit data. The terminal decodes control information transmitted by the received control signal, and obtains information relating to frequency assignment, adaptive control, or the like required to transmit data. The terminal generates data in accordance with the decoded control information, and transmits, to the base station, uplink data (a PUSCH: physical uplink shared channel), a response signal (an ACK/NACK) indicating an error detection result for downlink data, channel quality information (channel state information), an SRS (sounding reference signal) that is a reference signal for estimating an uplink propagation path, an SR (scheduling request) that requests the assignment of an uplink resource, or the like using an instructed radio resource. It should be noted that there is a possibility that a signal transmitted on the PUSCH includes not only voice and application data but also a higher layer control signal such as a TCP ACK/SYC (high layer signaling) or a BSR (buffer status report) or the like.

(4) In this regard, with the spread of services using mobile broadband in recent years, data traffic in mobile communication has continued to increase exponentially, and there is a pressing need to expand data transmission capacities. Furthermore, in the future, dramatic developments are anticipated for the IoT (Internet of Things) in which all “things” are connected via the Internet. To support the diversification of services by means of the IoT, dramatic advancements are needed not only for data transmission capacities but also for various requirements such as low delay properties and communication areas (coverage). With this background, progress is being made in the technical development/standardization of the fifth-generation mobile communication system (5G), which considerably improves performance and function compared to the fourth-generation mobile communication system (4G).

(5) LTE-Advanced which has been standardized by the 3GPP is one type of radio access technology (RAT) of 4G. In the 3GPP, in the standardization of 5G, progress is being made in the technical development of new radio access technology (NR: new RAT) that does not always have backward compatibility with LTE-Advanced.

(6) In NR, high frequency bands are also used, and therefore consideration is being given to applying analog or digital beamforming in order to compensate for the effect of propagation path attenuation. In beamforming, in order to select an optimum beam, control has been considered in which the transmitting side continuously transmits beams having different beam directions (also referred to as beam patterns), and the receiving side feeds back information regarding the optimum beam (for example, see NPL 1).

(7) Furthermore, in NR, as a time unit configuration (frame configuration) that realizes low delay, which is one of the required conditions of 5G, consideration is being given to a time unit of a fixed time interval (for example, one subframe, an NR subframe, or a time length that includes a fixed time length (for example, 1 ms) or a predetermined number of OFDM symbols) that includes one or more of a “downlink transmission region (DL transmission region)”, a “guard region (sometimes also referred to as a non-transmission period or a gap period)”, and an “uplink transmission region (UL transmission region)” (for example, see NPL 2). An operation that is carried out during this time unit is referred to as a “self-contained operation”.

CITATION LIST

Patent Literature

(8) NPL 1: R1-164013, Samsung, “Framework for Beamformed Access,” 3GPP TSG RAN WG1 #85, May 2016 NPL 2: R1-166027, Qualcomm, Panasonic, NTT DOCOMO, KT Corp, MediaTek, Intel, “WF on Frame Structure and Evaluation,” 3GPP TSG RAN WG1 #85, May 2016 NPL 3: R1-165887, LG Electronics, Panasonic, Qualcomm, NTT DOCOMO, “WF on Minimum HARQ Timing,” 3GPP TSG RAN WG1 #85, May 2016 NPL 4: R1-165886, Panasonic, Intel, Samsung, NTT DOCOMO, Qualcomm, Huawei, MediaTek, “WF on Scalable Numerology Symbol Boundary Alignment,” 3GPP TSG RAN WG1 #85, May 2016 NPL 5: R1-165662, Samsung et al., “WF on NR Frame Structure”, 3GPP TSG RAN WG1 #85, May 2016

SUMMARY OF INVENTION

(9) A gap period (a gap) that is a switching point between a downlink transmission region and an uplink transmission region is provided within a time unit configuration used for a self-contained operation. The gap period is set with consideration being given to the processing time of a base station or a terminal. Thus, it is necessary to set the gap period longer as the processing times by the base station and the terminal increase, and the utilization efficiency of radio resources deteriorates.

(10) Thus, an aspect of the present disclosure provides a base station, a terminal, and a communication method with which it is possible to suppress a decline in the utilization efficiency of radio resources caused by gap periods within a time unit in which a self-contained operation is carried out.

(11) A base station according to an aspect of the present disclosure is provided with: a transmitter

that transmits a downlink signal in a downlink transmission region, in a time unit that includes the downlink transmission region, an uplink transmission region, and a gap period that is a switching point between the downlink transmission region and the uplink transmission region; and a receiver that receives an uplink signal in the uplink transmission region, in the time unit, in which a delay tolerant signal for which a delay is tolerated more than for the downlink signal and the uplink signal is mapped to within the gap period.

(12) A terminal according to an aspect of the present disclosure is provided with: a receiver that receives a downlink signal in a downlink transmission region, in a time unit that includes the downlink transmission region, an uplink transmission region, and a gap period that is a switching point between the downlink transmission region and the uplink transmission region; and a transmitter that transmits an uplink signal in the uplink transmission region, in the time unit, in which a delay tolerant signal for which a delay is tolerated more than for the downlink signal and the uplink signal is mapped to within the gap period.

(13) It should be noted that general or specific aspects hereof may be realized by a system, a method, an integrated circuit, a computer program, or a recording medium, and may be realized by an arbitrary combination of a system, a device, a method, an integrated circuit, a computer program, and a recording medium.

(14) According to an aspect of the present disclosure, it is possible to suppress a decline in the utilization efficiency of radio resources caused by gap periods within a time unit in which a self-contained operation is carried out.

(15) Additional benefits and advantages in an aspect of the present disclosure will be made apparent from the specification and figures. The benefits and/or advantages may each be provided by several of the embodiments and the features disclosed in the specification and figures, and need not all be provided in order to obtain one or more of the same features.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1A is a drawing depicting an exemplary time unit configuration during a DL data self-contained operation.

(2) FIG. 1B is a drawing depicting an exemplary time unit configuration during a UL data self-contained operation.

(3) FIG. 2 is a block diagram depicting a main configuration of a base station according to embodiment 1.

(4) FIG. 3 is a block diagram depicting a main configuration of a terminal according to embodiment 1.

(5) FIG. 4 is a block diagram depicting a configuration of a base station during a DL data self-contained operation according to embodiment 1.

(6) FIG. 5 is a block diagram depicting a configuration of a terminal during a DL data self-contained operation according to embodiment 1.

(7) FIG. 6 is a block diagram depicting a configuration of a base station during a UL data self-contained operation according to embodiment 1.

(8) FIG. 7 is a block diagram depicting a configuration of a terminal during a UL data self-contained operation according to embodiment 1.

(9) FIG. 8 is a drawing depicting an example of a transmission sequence in a base station and a terminal during a DL data self-contained operation.

(10) FIG. 9 is a drawing depicting an example of a transmission sequence in a base station and a terminal during a DL data self-contained operation according to embodiment 1.

(11) FIG. 10 is a drawing depicting an example of a transmission sequence in a case where a delay

tolerant signal is a response signal according to embodiment 1.

(12) FIG. 11 is a drawing depicting an example of delay tolerant signal instruction information according to embodiment 1.

(13) FIG. 12 is a drawing depicting an example of delay tolerant signal instruction information according to embodiment 1.

(14) FIG. 13 is a drawing depicting an example of delay tolerant signal instruction information according to embodiment 1.

(15) FIG. 14 is a drawing depicting an example of delay tolerant signal instruction information according to embodiment 1.

(16) FIG. 15 is a drawing depicting an example of delay tolerant signal instruction information according to embodiment 1.

(17) FIG. 16 is a drawing depicting an example of a transmission sequence in a base station and a terminal during a UL data self-contained operation according to embodiment 1.

(18) FIG. 17 is a drawing depicting an example of a transmission sequence in a base station and a terminal during a UL data self-contained operation according to embodiment 1.

(19) FIG. 18 is a drawing depicting an example of a resource assignment method for a delay tolerant signal according to embodiment 2.

(20) FIG. 19 is a drawing depicting an example of a resource assignment method for a delay tolerant signal according to embodiment 2.

(21) FIG. 20 is a drawing depicting an example of a resource assignment method for a delay tolerant signal according to embodiment 2.

(22) FIG. 21 is a drawing depicting an example of a resource assignment method for a delay tolerant signal according to embodiment 2.

(23) FIG. 22 is a block diagram depicting the configuration of a base station during a DL data self-contained operation according to embodiment 3.

(24) FIG. 23 is a drawing depicting an example of delay tolerant signal instruction information according to embodiment 3.

(25) FIG. 24 is a block diagram depicting a configuration of a terminal during a DL data self-contained operation according to embodiment 3.

(26) FIG. 25 is a block diagram depicting a configuration of a base station during a UL data self-contained operation according to embodiment 3.

(27) FIG. 26 is a block diagram depicting a configuration of a terminal during a UL data self-contained operation according to embodiment 3.

(28) FIG. 27 is a drawing depicting an example of a transmission sequence in a base station and a terminal during a DL data self-contained operation.

(29) FIG. 28 is a drawing depicting an example of a transmission sequence in a base station and a terminal during a DL data self-contained operation according to embodiment 3.

(30) FIG. 29 is a drawing depicting an example of a resource assignment method for a delay tolerant signal according to embodiment 4.

(31) FIG. 30 is a drawing depicting an example of a resource assignment method for a delay tolerant signal according to embodiment 4.

(32) FIG. 31 is a drawing depicting an example of a resource assignment method for a delay tolerant signal according to embodiment 4.

DESCRIPTION OF EMBODIMENTS

(33) [Circumstances Leading to the Present Disclosure]

(34) First, the circumstances leading to the present disclosure will be described.

(35) Consideration is being given to a “DL data self-contained” operation for realizing low delay in downlink communication, and a “UL data self-contained” operation for realizing low delay in uplink communication, using the aforementioned time unit.

(36) In a DL data self-contained operation, a base station transmits a control signal (a DL

assignment or a DL grant) that is required for a terminal to receive downlink data, and downlink data (DL data) assigned by means of the control signal, in a downlink transmission region. The terminal then transmits a response signal for the downlink data and an uplink control signal (a UCI: uplink control indicator) in an uplink transmission region.

(37) Furthermore, in a UL data self-contained operation, the base station transmits a control signal (a UL assignment or a UL grant) that is required for the terminal to transmit uplink data, in a downlink transmission region. The terminal then transmits uplink data (UL data) assigned by means of the control signal and a UCI, in an uplink transmission region.

(38) Furthermore, in NR, as a time unit configuration that realizes low delay, it is necessary for the time interval from the transmission of a response signal to the transmission of retransmission data to also be reduced as much as possible (for example, see NPL 3).

(39) Furthermore, in NR, similar to a subframe of LTE, it has been agreed that a time unit configuration that includes 14 symbols (OFDM symbols) per 1 ms with a subcarrier interval of 15 kHz is to be considered as a basis (for example, see NPL 4).

(40) As a time unit configuration that enables a self-contained operation in a TDD (time division duplex) system, consideration is being given to the configurations depicted in FIG. 1A and FIG. 1B (for example, see NPL 3). FIG. 1A depicts a time unit configuration that enables a DL data self-contained operation, and FIG. 1B depicts a time unit configuration that enables a UL data self-contained operation.

(41) A gap period (the gap arranged first within each time unit of 1 ms in FIG. 1A and FIG. 1B; hereinafter, referred to as “gap #1”) between a downlink transmission region (the period depicted as “DL” in FIG. 1A and FIG. 1B) and an uplink transmission region (the period depicted as “UL” in FIG. 1A and FIG. 1B) is set with consideration being given to a propagation delay time between the base station and the terminal and the processing time of the terminal (UE processing time). It should be noted that there is a possibility of the length of the gap period changing in a dynamic or semi-static manner (for example, see NPL 5). Here, the processing time of the terminal indicates the processing time for the terminal to decode downlink data (DL data) and generate a response signal (an ACK in FIG. 1A and FIG. 1B) in the case of a DL data self-contained operation, and indicates the processing time for the terminal to decode a control signal (a UL assignment) and generate UL data in the case of a UL data self-contained operation.

(42) Furthermore, a gap period (the gap arranged second within each time unit of 1 ms in FIG. 1A and FIG. 1B; hereinafter referred to as “gap #2”) at the end of a time unit, after the uplink transmission region, is set with consideration being given to the processing time of the base station (eNB processing time). Here, the processing time of the base station indicates the processing time for the base station to decode a response signal and generate scheduling for the next time unit and a control signal (a DL assignment) in the case of a DL data self-contained operation, and indicates the processing time for the base station to decode UL data and generate scheduling for the next time unit and a control signal (a UL assignment) in the case of a UL data self-contained operation.

(43) In the time unit configurations of FIG. 1A and FIG. 1B, a gap period for which consideration has been given to the processing time of the base station is provided at the end of a time unit, thereby enabling data retransmission in the next time unit, and therefore a delay in data communication can be reduced.

(44) However, in the time unit configurations for the self-contained operations depicted in FIG. 1A and FIG. 1B, there are a plurality of gap periods. Therefore, it is necessary to set the gap periods to increase as the processing times of the base station and the terminal increase, and therefore the utilization efficiency of radio resources deteriorates.

(45) Thus, an aspect of the present disclosure provides a base station that can suppress a decline in the utilization efficiency of radio resources caused by gap periods, by transmitting a signal/channel for which a delay is tolerated (hereinafter, referred to as a “delay tolerant signal”), at the end of a downlink transmission region or an uplink transmission region within a time unit, in a case where a

self-contained operation is employed.

(46) Hereinafter, embodiments of the present disclosure will be described in detail with reference to the drawings.

Embodiment 1

(47) [Overview of Communication System]

(48) A communication system that carries out a DL data self-contained operation according to the present embodiment is provided with a base station **100** and a terminal **200**. Furthermore, a communication system that carries out a UL data self-contained operation according to each embodiment of the present disclosure is provided with a base station **300** and a terminal **400**.

(49) It should be noted that, hereinafter, a description will be given based on the premise of a TDD system. However, an aspect of the present disclosure can be similarly applied also as an FDD system as described hereinafter.

(50) Furthermore, one base station may have the configurations of both the base station **100** and the base station **300**, or may have the configuration of either one. Similarly, one terminal may have the configurations of both the terminal **200** and the terminal **400**, or may have the configuration of either one.

(51) FIG. 2 is a block diagram depicting a main configuration of the base stations **100** and **300** according to each embodiment of the present disclosure. In the base stations **100** and **300** depicted in FIG. 2, a transmitter **109** transmits a downlink signal in a downlink transmission region, in a time unit that includes the downlink transmission region, an uplink transmission region, and a gap period that is a switching point between the downlink transmission region and the uplink transmission region. A receiver **111** receives an uplink signal in the uplink transmission region, in the time unit. Furthermore, a delay tolerant signal for which a delay is tolerated more than for the downlink signal and the uplink signal is mapped to within the gap period.

(52) FIG. 3 is a block diagram depicting a main configuration of the terminals **200** and **400** according to each embodiment of the present disclosure. In the terminals **200** and **400** depicted in FIG. 3, a receiver **202** receives a downlink signal in a downlink transmission region, in a time unit that includes a downlink transmission region, an uplink transmission region, and a gap period that is a switching point between the downlink transmission region and the uplink transmission region. A transmitter **213** transmits an uplink signal in the uplink transmission region, in the time unit. A delay tolerant signal for which a delay is tolerated more than for the downlink signal and the uplink signal is mapped to within the gap period.

(53) [Configuration of Base Station (During DL Data Self-Contained Operation)]

(54) FIG. 4 is a block diagram depicting a configuration of the base station **100** that carries out a DL data self-contained operation according to the present embodiment. In FIG. 4, the base station **100** has a scheduler **101**, a delay tolerant signal controller **102**, a control signal generator **103**, a control signal encoder/modulator **104**, a data encoder **105**, a retransmission controller **106**, a data modulator **107**, a signal assignment unit **108**, the transmitter **109**, an antenna **110**, the receiver **111**, a signal extraction unit **112**, a delay tolerant signal demodulator/decoder **113**, a delay tolerant signal determination unit **114**, a demodulator/decoder **115**, and a determination unit **116**.

(55) The base station **100** depicted in FIG. 4 transmits a downlink signal that includes a control signal (a DL assignment) or downlink data (DL data) in a downlink transmission region of a time unit (DL data self-contained time unit) that includes the “downlink transmission region”, an “uplink transmission region”, and a “gap period”. Furthermore, the base station **100** receives an uplink signal that includes a response signal (and may also include a delay tolerant signal or a UCI) that is transmitted from the terminal **200** in the uplink transmission region of the time unit.

(56) In the base station **100**, the scheduler **101** determines scheduling information (for example, the ID of an assigned terminal, assigned resource information for the terminal **200** (a frequency, a time, and a coding resource), data demodulation reference signal information, a modulation/encoding scheme, assigned resource information for a response signal (a frequency, a time, and a coding

resource), or the like) relating to a delay tolerant signal (described hereinafter), a control signal (a DL assignment), and downlink data (DL data) in the time unit, with respect to the terminal **200**. The scheduler **101** outputs the determined scheduling information to the control signal generator **103**, the data encoder **105**, and the signal assignment unit **108**.

(57) The delay tolerant signal controller **102** determines information regarding a signal (for example, the signal type) that is generated as a delay tolerant signal, which is a signal or a channel that is transmitted from the terminal **200** at the end of an uplink transmission region within a time unit, and outputs information indicating the determined content to the control signal generator **103**. The delay tolerant signal is, for example, a signal or a channel for which a delay is tolerated more than for a downlink signal that is transmitted in a downlink transmission region and an uplink signal that is transmitted in an uplink transmission region within a time unit. Furthermore, a signal for which a delay is tolerated is, for example, a signal for which it is not necessary to carry out reception/decoding processing or the like by the time unit that is subsequent to the time unit in which the signal has been transmitted. It should be noted that the details of the delay tolerant signal that is transmitted at the end of an uplink transmission region within a time unit will be described hereinafter.

(58) Furthermore, the delay tolerant signal controller **102** outputs information indicating that the transmission of the delay tolerant signal is a retransmission, to the control signal generator **103** in a case where the delay tolerant signal is a retransmission signal, on the basis of information indicating a delay tolerant signal reception error, which is input from the delay tolerant signal determination unit **114**.

(59) The control signal generator **103** generates a control signal (a DL assignment) for the terminal **200** on the basis of information that is input from each of the scheduler **101** and the delay tolerant signal controller **102**. Control signals include a signal of a cell-specific higher layer, a signal of a group or RAT-specific higher layer, a signal of a terminal-specific higher layer, assigned resource information for downlink data, assigned resource information for a delay tolerant signal, information instructing the transmission of a delay tolerant signal (hereinafter, referred to as “delay tolerant signal instruction information”), assigned resource information for a response signal, or the like. An assigned resource for a delay tolerant signal is assumed to be at the end of an uplink transmission region within a time unit (namely, the gap period at the end of a time unit). Furthermore, in a case where the base station **100** requests the terminal **200** for the retransmission of a delay tolerant signal, the control signal generator **103** may include retransmission request information for a delay tolerant signal in the delay tolerant signal instruction information. The control signal generator **103** generates a control information bit string using such control information, and outputs the generated control information bit string to the control signal encoder/modulator **104**. It should be noted that the details of the delay tolerant signal instruction information will be described hereinafter.

(60) It should be noted that assigned resource information for a delay tolerant signal may be notified in advance by means of a higher layer notification from the base station **100** to the terminal **200**. In this case, assigned resource information for a delay tolerant signal is not included in a control signal (a DL assignment).

(61) The control signal encoder/modulator **104** encodes and modulates the control signal (a bit string) received from the control signal generator **103**, and outputs a modulated control signal to the signal assignment unit **108**.

(62) The data encoder **105** carries out error correction encoding on transmission data (downlink data) in accordance with an encoding scheme received from the scheduler **101**, and outputs an encoded data signal to the retransmission controller **106**.

(63) The retransmission controller **106**, at the time of the first transmission, retains the encoded data signal received from the data encoder **105** and also outputs the encoded data signal to the data modulator **107**. Furthermore, the retransmission controller **106**, at the time of a retransmission,

controls the retained data on the basis of a determination result (an ACK/NACK) from the determination unit **116**. Specifically, the retransmission controller **106**, upon receiving a NACK with respect to the data signal, outputs the corresponding retained data to the data modulator **107**. Furthermore, the retransmission controller **106**, upon receiving an ACK with respect to the data signal, discards the corresponding retained data and ends the transmission of downlink data.

(64) The data modulator **107** modulates a data signal received from the retransmission controller **106**, and outputs a modulated data signal (symbol string) to the signal assignment unit **108**.

(65) The signal assignment unit **108** maps a control signal received from the control signal encoder/modulator **104** and a data signal received from the data modulator **107** to a radio resource instructed from the scheduler **101**. The signal assignment unit **108** outputs a downlink signal for which signal mapping has been carried out, to the transmitter **109**.

(66) The transmitter **109** carries out RF (radio frequency) processing such as D/A (digital-to-analog) conversion and up-conversion on the signal received from the signal assignment unit **108**, and transmits a radio signal to the terminal **200** via the antenna **110**.

(67) The receiver **111** carries out RF processing such as down-conversion or A/D (analog-to-digital) conversion with respect to the signal waveform of an uplink from the terminal **200** received via the antenna **110**, and outputs an obtained reception signal to the signal extraction unit **112**.

(68) The signal extraction unit **112** extracts a radio resource portion in which an uplink response signal from the terminal **200** has been transmitted, from the reception signal, and outputs a reception response signal to the demodulator/decoder **115**. Furthermore, the signal extraction unit **112** extracts a radio resource portion in which a delay tolerant signal from the terminal **200** has been transmitted, from the reception signal, and outputs the delay tolerant signal to the delay tolerant signal demodulator/decoder **113**.

(69) The delay tolerant signal demodulator/decoder **113** carries out equalization, demodulation, and error correction decoding for the delay tolerant signal that is input from the signal extraction unit **112**, and outputs a decoded bit sequence to the determination unit **116** and the delay tolerant signal determination unit **114**.

(70) The delay tolerant signal determination unit **114** determines whether or not the delay tolerant signal (a bit sequence) that is input from the delay tolerant signal demodulator/decoder **113** has been correctly received. The delay tolerant signal determination unit **114**, when having determined that the delay tolerant signal has been correctly received, outputs the delay tolerant signal. However, the delay tolerant signal determination unit **114**, when having determined that the delay tolerant signal has not been correctly received and is a signal for which it is necessary to request a retransmission of the delay tolerant signal, outputs information indicating a reception error for the delay tolerant signal to the delay tolerant signal controller **102**.

(71) The demodulator/decoder **115** carries out equalization, demodulation, and decoding on the reception response signal that is received from the signal extraction unit **112**, and outputs a decoded bit sequence to the determination unit **116**.

(72) The determination unit **116** determines whether a response signal for downlink data, transmitted from the terminal **200**, indicates an ACK or NACK with respect to the downlink data, on the basis of the bit sequence that is input from the demodulator/decoder **115**. It should be noted that the determination unit **116** may carry out the determination for the response signal with consideration also being given to a bit sequence (for example, some or all of the response signal) that is input from the delay tolerant signal demodulator/decoder **113**. The determination unit **116** outputs a determination result (an ACK or NACK) to the retransmission controller **106**.

(73) [Configuration of Terminal (During DL Data Self-Contained Operation)]

(74) FIG. 5 is a block diagram depicting a configuration of the terminal **200** that carries out a DL data self-contained operation according to the present embodiment. In FIG. 5, the terminal **200** has an antenna **201**, the receiver **202**, a signal extraction unit **203**, a control signal demodulator/decoder **204**, a data demodulator **205**, a data decoder **206**, an error detector **207**, a response signal generator

208, an encoder/modulator **209**, a delay tolerant signal generator **210**, a delay tolerant signal encoder/modulator **211**, a signal assignment unit **212**, and the transmitter **213**.

(75) The terminal **200** depicted in FIG. 5 receives a downlink signal that includes a control signal (a DL assignment) or downlink data (DL data) transmitted from the base station **100** in a downlink transmission region of a time unit (self-contained time unit) that includes the “downlink transmission region”, a “gap period”, and an “uplink transmission region”. Furthermore, the terminal **200** transmits an uplink signal that includes a response signal for downlink data (and may also include a delay tolerant signal or a UCI), in the uplink transmission region of the time unit.

(76) In the terminal **200**, the receiver **202** receives, via the antenna **201**, a control signal and downlink data transmitted from the base station **100**, carries out RF processing such as down-conversion or AD conversion with respect to a radio reception signal, and obtains a baseband signal. The receiver **202** outputs the baseband signal to the signal extraction unit **203**.

(77) The signal extraction unit **203** extracts a signal portion that includes the control signal, from the baseband signal received from the receiver **202**, and outputs the signal portion to the control signal demodulator/decoder **204**. Furthermore, the signal extraction unit **203** extracts a signal portion that includes the downlink data from the baseband signal, and outputs the signal portion to the data demodulator **205**.

(78) The control signal demodulator/decoder **204** carries out blind decoding on the control signal received from the signal extraction unit **203**, and attempts decoding for a control signal addressed thereto. The control signal demodulator/decoder **204**, when having determined as a result of the blind decoding that the control signal is a control signal addressed thereto, outputs assigned resource information for downlink data included in the control signal (the ID of an assigned terminal, assigned resource information (a frequency, a time, and a coding resource), data demodulation reference signal information, a modulation/encoding scheme, or the like) to the data demodulator **205**, outputs assigned resource information for a response signal and assigned resource information for a delay tolerant signal to the signal assignment unit **212**, and outputs delay tolerant signal instruction information to the delay tolerant signal generator **210**.

(79) The data demodulator **205** demodulates downlink data received from the signal extraction unit **203**, on the basis of the assigned resource information for downlink data, received from the control signal demodulator/decoder **204**, and outputs demodulated downlink data to the data decoder **206**.

(80) The data decoder **206** decodes the downlink data received from the data demodulator **205**, and outputs decoded downlink data to the error detector **207**.

(81) The error detector **207** carries out error detection by means of a CRC, for example, with respect to the downlink data received from the data decoder **206**, and outputs an error detection result (an ACK or NACK) to the response signal generator **208**. Furthermore, the error detector **207** outputs, as reception data, downlink data determined as having no errors as a result of the error detection.

(82) The response signal generator **208**, using the error detection result (an ACK or NACK) received from the error detector **207**, generates a response signal (a bit sequence) for the received downlink data, and outputs the response signal to the encoder/modulator **209**.

(83) The encoder/modulator **209** carries out error correction encoding on the response signal (a bit sequence) received from the response signal generator **208**, modulates an encoded bit sequence, and outputs a modulated symbol sequence to the signal assignment unit **212**.

(84) The delay tolerant signal generator **210** generates a delay tolerant signal on the basis of delay tolerant signal instruction information that has been input from the control signal demodulator/decoder **204**, information that is predetermined by the system, information that is preset in the terminal **200** by means of a higher layer notification from the base station **100**, or the like. The delay tolerant signal generator **210** outputs the generated delay tolerant signal (a bit sequence) to the delay tolerant signal encoder/modulator **211**. Furthermore, the delay tolerant signal generator **210** determines whether the transmission of the delay tolerant signal is the first

transmission or a retransmission on the basis of whether or not retransmission request information is included in the delay tolerant signal instruction information that is input from the control signal demodulator/decoder **204**. The delay tolerant signal generator **210** retains the delay tolerant signal at the time of the first transmission, and outputs a corresponding retained signal to the delay tolerant signal encoder/modulator **211** at the time of a retransmission.

(85) The delay tolerant signal encoder/modulator **211** carries out encoding processing and modulation processing on the bit sequence that is input from the delay tolerant signal generator **210**, and outputs a modulated delay tolerant signal to the signal assignment unit **212**.

(86) The signal assignment unit **212** maps a signal received from the encoder/modulator **209** and a signal received from the delay tolerant signal encoder/modulator **211** to a resource (a time, a frequency, and a coding resource) within a time unit for a self-contained operation, instructed from the control signal demodulator/decoder **204**. It should be noted that a radio resource to which a delay tolerant signal is mapped may be notified in advance by means of a higher layer notification from the base station **100** to the terminal **200** without notification being performed by means of a control signal (a DL assignment).

(87) The transmitter **213** carries out RF processing such as D/A conversion and up-conversion on the signal received from the signal assignment unit **212**, and transmits a radio signal to the base station **100** via the antenna **201**.

(88) [Configuration of Base Station (During UL Data Self-Contained Operation)]

(89) FIG. **6** is a block diagram depicting a configuration of the base station **300** that carries out a UL data self-contained operation according to the present embodiment. In FIG. **6**, the base station **300** has a scheduler **301**, a delay tolerant signal controller **302**, a control signal generator **303**, a control signal encoder/modulator **304**, a signal assignment unit **305**, the transmitter **109**, the antenna **110**, the receiver **111**, a signal extraction unit **306**, a delay tolerant signal demodulator/decoder **307**, a delay tolerant signal determination unit **308**, a data demodulator **309**, a retransmission synthesis decoder **310**, and an error detector **311**.

(90) The base station **300** depicted in FIG. **6** transmits a downlink signal that includes a UL assignment in a downlink transmission region of a time unit (UL data self-contained time unit) that includes the “downlink transmission region”, a “gap period”, and an “uplink transmission region”. Furthermore, the base station **300** receives an uplink signal that includes uplink data (and may also include a delay tolerant signal or a UCI) that has been transmitted from the terminal **400** in the uplink transmission region of the time unit.

(91) In the base station **300**, the scheduler **301** schedules the retransmission of uplink data in a case where an error detection result indicating that there is an error in the previous uplink data is input from the error detector **311**. Furthermore, the scheduler **301** schedules a new packet for the terminal **400** in a case where an error detection result indicating that there are no errors in the previous uplink data is input from the error detector **311**.

(92) For example, the scheduler **301** determines scheduling information (for example, the ID of an assigned terminal, assigned resource information for the terminal **400** (a frequency, a time, and a coding resource), data demodulation reference signal information, a modulation/encoding scheme for uplink data, or the like) relating to a delay tolerant signal, a control signal (a UL assignment), and uplink data (UL data) in a time unit, with respect to the terminal **400**. The scheduler **301** outputs the determined scheduling information to the control signal generator **303** and the signal assignment unit **305**.

(93) The delay tolerant signal controller **302** determines information (for example, the type of delay tolerant signal) relating to a signal that is generated as a delay tolerant signal, which is a signal or a channel that is transmitted from the terminal **400** at the end of an uplink transmission region within a time unit, and outputs information indicating the determined content to the control signal generator **303**. It should be noted that the details of the delay tolerant signal that is transmitted at the end of an uplink transmission region within a time unit will be described hereinafter.

- (94) Furthermore, the delay tolerant signal controller **302** outputs information indicating that the transmission of the delay tolerant signal is a retransmission, to the control signal generator **303** in a case where the delay tolerant signal is a retransmission signal, on the basis of information indicating a delay tolerant signal reception error, which is input from the delay tolerant signal determination unit **308**.
- (95) The control signal generator **303** generates a control signal (a UL assignment) for the terminal **400** on the basis of information that is input from each of the scheduler **301** and the delay tolerant signal controller **302**. Control signals include a signal of a cell-specific higher layer, a signal of a group or RAT-specific higher layer, a signal of a terminal-specific higher layer, assigned resource information for uplink data, information instructing a retransmission or a new transmission of uplink data, assigned resource information for a delay tolerant signal, delay tolerant signal instruction information, or the like. Furthermore, in a case where the base station **300** requests the terminal **400** for the retransmission of a delay tolerant signal, the control signal generator **303** may include retransmission request information for a delay tolerant signal in the delay tolerant signal instruction information. The control signal generator **303** generates a control information bit string using such control information, and outputs the control information bit string to the control signal encoder/modulator **304**. It should be noted that the details of the delay tolerant signal instruction information will be described hereinafter.
- (96) It should be noted that assigned resource information for a delay tolerant signal may be notified in advance by means of a higher layer notification from the base station **300** to the terminal **400**. In this case, assigned resource information for a delay tolerant signal is not included in a control signal (a UL assignment).
- (97) The control signal encoder/modulator **304** encodes and modulates a control signal received from the control signal generator **303**, and outputs a modulated control signal to the signal assignment unit **305**.
- (98) The signal assignment unit **305** maps a control signal received from the control signal encoder/modulator **304** to a radio resource (an assigned time/frequency/coding resource) instructed from the scheduler **301**. The signal assignment unit **305** outputs a downlink signal for which signal mapping has been carried out, to the transmitter **109**.
- (99) The transmitter **109**, the antenna **110**, and the receiver **111** operate in a manner similar to the transmitter **109**, the antenna **110**, and the receiver **111** provided in the base station **100**.
- (100) The signal extraction unit **306** extracts a radio resource portion in which uplink data from the terminal **400** has been transmitted, from a reception signal that is input from the receiver **111**, and outputs the radio resource portion to the data demodulator **309**. Furthermore, the signal extraction unit **306** extracts a radio resource portion in which a delay tolerant signal from the terminal **400** has been transmitted, from the reception signal, and outputs the delay tolerant signal to the delay tolerant signal demodulator/decoder **307**.
- (101) The delay tolerant signal demodulator/decoder **307** carries out equalization, demodulation, and error correction decoding for the delay tolerant signal that is input from the signal extraction unit **306**, and outputs a decoded bit sequence to the delay tolerant signal determination unit **308** and the retransmission synthesis decoder **310**.
- (102) The delay tolerant signal determination unit **308** determines whether or not the delay tolerant signal (a bit sequence) that is input from the delay tolerant signal demodulator/decoder **307** has been correctly received. The delay tolerant signal determination unit **308**, when having determined that the delay tolerant signal has been correctly received, outputs the delay tolerant signal. However, the delay tolerant signal determination unit **308**, when having determined that the delay tolerant signal has not been correctly received and is a signal for which it is necessary to request a retransmission of the delay tolerant signal, outputs information indicating a reception error for the delay tolerant signal, to the delay tolerant signal controller **302**.
- (103) The data demodulator **309** carries out equalization and demodulation processing on uplink

data received from the signal extraction unit **306**, and outputs demodulated uplink data (a bit sequence) to the retransmission synthesis decoder **310**.

(104) The retransmission synthesis decoder **310**, in a case where uplink data to be decoded of the terminal **400** is retained (a case where the uplink data is retransmission data), synthesizes the retained uplink data and uplink data that has been output from the data demodulator **309**, and carries out decoding processing on the synthesized uplink data. The retransmission synthesis decoder **310**, in a case where uplink data of the terminal **400** is not retained (a case where the uplink data is the first packet), carries out decoding processing without carrying out synthesis processing for uplink data. It should be noted that the retransmission synthesis decoder **310** may carry out retransmission synthesis and decoding processing with consideration also being given to a bit sequence (for example, some or all of the uplink data) that is input from the delay tolerant signal demodulator/decoder **307**. The retransmission synthesis decoder **310** then outputs decoded uplink data to the error detector **311**. Furthermore, the retransmission synthesis decoder **310**, in a case where a detection result from the error detector **311** indicates that there are no errors, deletes the retained uplink data of the terminal **400**.

(105) The error detector **311** carries out error detection by means of a CRC, for example, with respect to uplink data received from the retransmission synthesis decoder **310**, and outputs an error detection result (an ACK or NACK) to the scheduler **301** and the retransmission synthesis decoder **310**. Furthermore, the error detector **311** outputs, as reception data, uplink data determined as having no errors as a result of the error detection.

(106) [Configuration of Terminal (During UL Data Self-Contained Operation)]

(107) FIG. 7 is a block diagram depicting a configuration of the terminal **400** that carries out a UL data self-contained operation according to the present embodiment. In FIG. 7, the terminal **400** has the antenna **201**, the receiver **202**, a signal extraction unit **401**, a control signal demodulator/decoder **402**, a data encoder **403**, a retransmission controller **404**, a data modulator **405**, a delay tolerant signal generator **406**, a delay tolerant signal encoder/modulator **407**, a signal assignment unit **408**, and the transmitter **213**.

(108) The terminal **400** depicted in FIG. 7 receives a downlink signal that includes a control signal (a UL assignment) transmitted from the base station **300** in a downlink transmission region of a time unit (UL data self-contained time unit) that includes the “downlink transmission region”, a “gap period”, and an “uplink transmission region”. Furthermore, the terminal **400** transmits an uplink signal that includes uplink data (and may also include a delay tolerant signal or a UCI) in the uplink transmission region of the time unit.

(109) In the terminal **400**, the antenna **201** and the receiver **202** operate in a manner similar to the antenna **201** and the receiver **202** provided in the terminal **200**.

(110) The signal extraction unit **401** extracts a control signal from a baseband signal received from the receiver **202**, and outputs the control signal to the control signal demodulator/decoder **402**.

(111) The control signal demodulator/decoder **402** carries out blind decoding on the control signal received from the signal extraction unit **401**, and attempts decoding for a control signal addressed thereto. The control signal demodulator/decoder **402**, when having determined as a result of the blind decoding that the control signal is a control signal addressed thereto, outputs, to the signal assignment unit **408**, assigned resource information for uplink data (the ID of an assigned terminal, assigned resource information (a frequency, a time, and a coding resource), data demodulation reference signal information, a modulation/encoding scheme, or the like) and assigned resource information for a delay tolerant signal, included in the control signal, outputs information instructing a retransmission or a new transmission of uplink data to the retransmission controller **404**, and outputs delay tolerant signal instruction information to the delay tolerant signal generator **406**.

(112) The data encoder **403** carries out error correction encoding on transmission data (uplink data), and outputs an encoded data signal to the retransmission controller **404**.

(113) The retransmission controller **404** determines whether or not the uplink data is the first packet or a retransmission packet on the basis of information received from the control signal demodulator/decoder **402**. In the case of the first packet, the retransmission controller **404** retains the encoded uplink data received from the data encoder **403** and also outputs the encoded uplink data to the data modulator **405**. Furthermore, in the case of the first packet, the retransmission controller **404** determines that the transmission and reception of the previous transmission packet has been successful and discards the retained data. However, in the case of a retransmission packet, the retransmission controller **404** outputs the corresponding retained data to the data modulator **405**.

(114) The data modulator **405** modulates the uplink data received from the retransmission controller **404**, and outputs modulated uplink data to the signal assignment unit **408**.

(115) The delay tolerant signal generator **406** generates a delay tolerant signal on the basis of delay tolerant signal instruction information that has been input from the control signal demodulator/decoder **402**, information that is predetermined by the system, information that is preset in the terminal **400** by means of a higher layer notification from the base station **300**, or the like. The delay tolerant signal generator **406** outputs the generated delay tolerant signal (a bit sequence) to the delay tolerant signal encoder/modulator **407**. Furthermore, the delay tolerant signal generator **406** determines whether the transmission of the delay tolerant signal is the first transmission or a retransmission on the basis of whether or not retransmission request information is included in the delay tolerant signal instruction information that is input from the control signal demodulator/decoder **402**. The delay tolerant signal generator **406** retains the delay tolerant signal at the time of the first transmission, and outputs a corresponding retained signal to the delay tolerant signal encoder/modulator **407** at the time of a retransmission.

(116) The delay tolerant signal encoder/modulator **407** carries out encoding processing and modulation processing on the bit sequence that is input from the delay tolerant signal generator **406**, and outputs a modulated delay tolerant signal to the signal assignment unit **408**.

(117) The signal assignment unit **408** maps uplink data received from the data modulator **405** and a delay tolerant signal received from the delay tolerant signal encoder/modulator **407** to a resource (a time, a frequency, and a coding resource) within a time unit for a self-contained operation, instructed from the control signal demodulator/decoder **402**. The signal assignment unit **408** outputs an uplink signal for which signal mapping has been carried out, to the transmitter **213**.

(118) The transmitter **213** operates in a manner similar to the transmitter **213** provided in the terminal **200**.

(119) [Operation of Base Stations **100** and **300** and Terminals **200** and **400**]

(120) A detailed description will be given regarding an operation in the base stations **100** and **300** and the terminals **200** and **400** having the above configurations.

(121) FIG. **8** depicts an example of a transmission sequence in each of a base station (eNB) and a terminal (UE) during the DL data self-contained operation of FIG. **1A**. Furthermore, FIG. **9** depicts an example of a transmission sequence in each of the base station **100** and the terminal **200** during the DL data self-contained operation according to the present embodiment.

(122) In FIG. **8**, in each time unit, gap #1 that takes into consideration a propagation delay time and the processing time of the terminal is arranged between a downlink transmission region and an uplink transmission region (at the end of the downlink transmission region), and gap #2 that takes into consideration the processing time of the base station is arranged after the uplink transmission region (at the end of the uplink transmission region). For example, the base station schedules downlink data that is transmitted in the downlink transmission region of the next time unit, on the basis of a determination result for a response signal (depicted as an ACK in FIG. **8**) received in the uplink transmission region, in the period of gap #2 depicted in FIG. **8**.

(123) However, in the present embodiment, as depicted in FIG. **9**, in a DL data self-contained operation, a delay tolerant signal, for which a delay can be tolerated more than for a response signal

(uplink signal) or uplink data (UL data) that is mapped in the uplink transmission region, is mapped to within gap #2 that is arranged at the end of the uplink transmission region depicted in FIG. 8, that is, within a period that takes into consideration the processing time of the base station 100. (124) That is, the terminal 200 transmits a delay tolerant signal that has been mapped to a period corresponding to gap #2 arranged after the uplink transmission region, and the base station 100 receives the delay tolerant signal that has been mapped to the period corresponding to gap #2 arranged after the uplink transmission region.

(125) In this case also, the base station 100, upon receiving the response signal (ACK) in the uplink transmission region, can schedule downlink data that is transmitted in the downlink transmission region of the next time unit, on the basis of a determination result for the response signal, in a transmission period for a delay tolerant signal (corresponding to gap #2 in FIG. 8).

(126) Furthermore, the base station 100, upon receiving the delay tolerant signal transmitted from the terminal 200 at the end of the uplink transmission region, carries out predetermined processing (demodulation/decoding processing or the like) on the delay tolerant signal. However, as mentioned above, a delay tolerant signal is a signal for which it is not always necessary to carry out reception/decoding processing or the like by the time unit that is subsequent to the time unit in which the delay tolerant signal has been received by the base station 100. That is, since a delay is tolerated for a delay tolerant signal, the base station 100, for example, can carry out demodulation/decoding processing for a delay tolerant signal in a period corresponding to the next time unit.

(127) It should be noted that, although FIG. 9 relates to during a DL data self-contained operation, in a UL data self-contained operation it is also sufficient to similarly configure a time unit in which a delay tolerant signal is mapped to a period corresponding to gap #2 depicted in FIG. 1B.

(128) It is thereby possible to reduce the overhead for gaps while maintaining the average delay time from a transmission buffer for the base station 100 being generated to the base station 100 receiving a response signal to downlink data from the terminal 200, and the average delay time from a transmission buffer for the terminal 400 being generated to the terminal 400 completing transmission of the first uplink data.

(129) It should be noted that it is not always necessary for the terminals 200 and 400 to transmit a delay tolerant signal in each time unit. In a case where the terminal 200 does not transmit a delay tolerant signal, the time resource for a delay tolerant signal (the end of an uplink transmission region) becomes a gap period as in FIG. 1A and FIG. 1B. It is thereby possible to reduce power consumption by not carrying out excessive transmissions.

(130) [Types of Delay Tolerant Times]

(131) Next, the types of delay tolerant times that are generated in the delay tolerant signal generators 210 and 406 of the terminals 200 and 400 will be described in detail.

(132) Hereinafter, descriptions will be given regarding the types of delay tolerant signals common to the DL data self-contained operation and the UL data self-contained operation (common delay tolerant signal types), the type of delay tolerant signal that is generated in only the DL data self-contained operation (a DL data self-contained operation delay tolerant signal type), and the type of delay tolerant signal that is generated in only the UL data self-contained operation (a UL data self-contained operation delay tolerant signal type).

(133) First, common delay tolerant signal types 1 to 6 will be described.

(134) <Common Delay Tolerant Signal Type 1>

(135) A delay tolerant signal in common delay tolerant signal type 1 is a reference signal (an SRS: sounding reference signal) for estimating a propagation path for an uplink.

(136) An SRS has no effect on the retransmission control of downlink data or uplink data even if the base stations 100 and 300 do not complete reception/decoding processing by the next time unit. That is, an SRS is a signal for which a delay can be tolerated compared to a response signal or uplink data transmitted in an uplink transmission region.

(137) In this way, due to the terminals **200** and **400** transmitting an SRS in a gap period (gap #2) at the end of an uplink transmission region, in addition to the aforementioned effects, it is possible to increase the opportunities for the base stations **100** and **300** to estimate a propagation path for an uplink. Therefore, channel estimation accuracy for an uplink improves, and uplink throughput can be improved. It should be noted that, in the case of a TDD system, a channel estimation value estimated from a propagation path for an uplink using an SRS can be applied also to a downlink, and therefore downlink throughput can also be improved.

(138) <Common Delay Tolerant Signal Type 2>

(139) A delay tolerant signal in common delay tolerant signal type 2 is information indicating a plurality of beam patterns.

(140) Specifically, the terminals **200** and **400** transmit a reference signal including at least one of a plurality of beam patterns as a delay tolerant signal. The base stations **100** and **300** then detect the optimum beam pattern in an uplink from among the beam patterns corresponding to the reference signals transmitted from the terminals **200** and **400**.

(141) A beam pattern has no effect on the retransmission control of downlink data or uplink data even if the base stations **100** and **300** do not complete reception/decoding processing by the next time unit. That is, a beam pattern is a signal for which a delay can be tolerated compared to a response signal or uplink data transmitted in an uplink transmission region.

(142) In this way, due to the terminals **200** and **400** transmitting a reference signal for a predetermined beam pattern in a gap period (gap #2) at the end of an uplink transmission region, in addition to the aforementioned effects, it is possible to increase the opportunities for the base stations **100** and **300** to estimate the optimum beam pattern for an uplink. Therefore, beam pattern estimation accuracy for an uplink improves, and uplink throughput can be improved.

(143) <Common Delay Tolerant Signal Type 3>

(144) A delay tolerant signal in common delay tolerant signal type 3 is CSI, which is channel quality information of a downlink.

(145) CSI includes one or more out of a CQI (channel quality indicator), a PMI (precoding matrix indicator), an RI (rank indicator), and a CRI (CSI-RS resource indicator).

(146) CSI has no effect on the retransmission control of downlink data or uplink data even if the base stations **100** and **300** do not complete reception/decoding processing by the next time unit. That is, CSI is a signal for which a delay can be tolerated compared to a response signal or uplink data transmitted in an uplink transmission region.

(147) In this way, due to the terminals **200** and **400** transmitting CSI in a gap period (gap #2) at the end of an uplink transmission region, in addition to the aforementioned effects, it is possible to increase the opportunities for the terminals **200** and **400** to notify quality information of a downlink to the base stations **100** and **300**. Therefore, the accuracy of adaptive modulation for a downlink improves, and downlink throughput can be improved.

(148) <Common Delay Tolerant Signal Type 4>

(149) A delay tolerant signal in common delay tolerant signal type 4 is a scheduling request (SR) with which the assignment of a radio resource for an uplink is requested.

(150) An SR has no effect on the retransmission control of downlink data or uplink data even if the base stations **100** and **300** do not complete reception/decoding processing by the next time unit. That is, an SR is a signal for which a delay can be tolerated compared to a response signal or uplink data transmitted in an uplink transmission region.

(151) In this way, due to the terminals **200** and **400** transmitting an SR in a gap period (gap #2) at the end of an uplink transmission region, in addition to the aforementioned effects, it becomes possible for the terminals **200** and **400** to notify a resource assignment request for an uplink to the base stations **100** and **300** at an early timing. Uplink throughput therefore improves.

(152) <Common Delay Tolerant Signal Type 5>

(153) A delay tolerant signal in common delay tolerant signal type 5 is a BSR (buffer status report)

that notifies a buffer state of the terminals **200** and **400**.

(154) A BSR is any of a regular BSR that is notified when data is generated, a periodic BSR that is transmitted periodically, and a padding BSR that is transmitted in a case where the number of redundant bits of a MAC PDU (medium access control protocol data unit) is greater than the number of bits required for storage.

(155) A BSR has no effect on the retransmission control of downlink data or uplink data even if the base stations **100** and **300** do not complete reception/decoding processing by the next time unit. That is, a BSR is a signal for which a delay can be tolerated compared to a response signal or uplink data transmitted in an uplink transmission region.

(156) In this way, due to the terminals **200** and **400** transmitting a BSR in a gap period (gap #2) at the end of an uplink transmission region, in addition to the aforementioned effects, the terminals **200** and **400** can notify a buffer state to the base stations **100** and **300** at an early timing. Therefore, the timing at which scheduling for uplink data is carried out becomes earlier, and uplink throughput improves.

(157) <Common Delay Tolerant Signal Type 6>

(158) A delay tolerant signal in common delay tolerant signal type 6 is a TCP ACK/SYC.

(159) A TCP ACK is a higher layer notification for notifying a base station that the reception of a signal of a TCP (transmission control protocol) layer has been completed. Furthermore, a TCP SYC is a higher layer notification for a terminal to notify a base station when a connection is established with a TCP layer.

(160) A TCP ACK/SYC has no effect on the retransmission control of downlink data or uplink data even if the base stations **100** and **300** do not complete reception/decoding processing by the next time unit. That is, a TCP ACK/SYC is a signal for which a delay can be tolerated compared to a response signal or uplink data transmitted in an uplink transmission region.

(161) It should be noted that since a TCP ACK/SYC is a higher layer notification, there is a possibility of the terminals **200** and **400** not being able to determine whether or not the signal in question is a TCP ACK/SYC in a MAC/PHY layer. In this case, the terminals **200** and **400** may determine that the signal in question is a TCP ACK/SYC in a case where the size of the signal in question is small (for example, a case where the signal size is less than a predetermined value).

(162) Furthermore, a retransmission for a TCP ACK/SYC transmitted as a delay tolerant signal may be carried out or may not be carried out. In a case where a TCP ACK/SYC is to be retransmitted, the terminals **200** and **400** are not able to retransmit the TCP ACK/SYC in the next time unit, but a problem does not arise since the TCP ACK/SYC is a signal for which a delay is tolerated as mentioned above.

(163) In this way, the terminals **200** and **400** transmit a TCP ACK in a gap period (gap #2) at the end of an uplink transmission region. Thus, in addition to the aforementioned effects, it becomes possible for a TCP ACK to be fed back at an early timing, in a slow start phase in which the number of TCP segments in TCP congestion control is increased exponentially. The TCP layer throughput can therefore be improved. Furthermore, by transmitting a TCP SYC, a TCP connection can be established at an early timing, and TCP layer throughput can be improved.

(164) Hereinabove, common delay tolerant signal types 1 to 6 have been described.

(165) <DL Data Self-Contained Delay Tolerant Signal Type>

(166) Next, a description will be given regarding a DL data self-contained delay tolerant signal type with which a performance improvement or the like can be expected due to a transmission being carried out in a DL data self-contained operation.

(167) A delay tolerant signal in the DL data self-contained delay tolerant signal type is some or all of the delay tolerant signal and a response signal (ACK) that has already been transmitted in the same time unit.

(168) FIG. **10** is a drawing depicting an example of a transmission sequence in a case where the terminal **200** transmits a response signal as a delay tolerant signal.

(169) A response signal (ACK #2 depicted in FIG. 10) that is transmitted as a delay tolerant signal is transmitted in a period (the processing time of the base station) corresponding to gap #2 in FIG. 1A. Therefore, there is a high possibility of it being difficult to demodulate/decode ACK #2 within the processing time of the base station 100 (that is, by the next time unit).

(170) Meanwhile, a response signal (ACK #1 depicted in FIG. 10) that is transmitted in an uplink transmission region can be demodulated/decoded within the processing time of the base station 100. However, in a case where the base station 100 makes an error in the determination of the receiving of ACK #1 and determines a NACK as an ACK, a retransmission packet is not transmitted to the terminal 200, and therefore a packet timeout occurs and a large delay occurs.

(171) In order to prevent this determination error, the base station 100 (the determination unit 116 depicted in FIG. 4) synthesizes ACK #2 transmitted as a delay tolerant signal and ACK #1 transmitted in the same time unit. The base station 100 (determination unit 116) then determines whether or not there is a determination error for the response signal on the basis of the synthesized response signal. In this way, the reception quality for a response signal improves due to the synthesizing, and therefore the reception determination accuracy for a response signal can be improved. For example, as depicted in FIG. 10, the processing of the base station 100 is carried out in the period of the time unit that is subsequent to the time unit in which a response signal (ACK #1 or ACK #2) has been transmitted. Then, the base station 100, when having determined that there has been a determination error for the response signal, additionally transmits retransmission data in the next time unit. Thus, a delay for a retransmission packet can be suppressed to one time unit, and a large delay occurring can be prevented.

(172) As mentioned above, some or all of a response signal transmitted as a delay tolerant signal has no effect on the retransmission control of downlink data or uplink data even if the base station 100 does not complete reception/decoding processing by the next time unit. That is, some or all of a response signal transmitted as a delay tolerant signal is a signal for which a delay can be tolerated compared to a response signal that is transmitted in another uplink transmission region.

(173) In this way, the terminal 200 transmits some or all of a response signal transmitted in the same time unit in a gap period (gap #2) at the end of an uplink transmission region. Thus, in addition to the aforementioned effects, the possibility of a determination error for a response signal occurring in the base station 100 can be reduced, and downlink throughput can be improved.

(174) <UL Data Self-Contained Delay Tolerant Signal Type>

(175) Next, a description will be given regarding a UL data self-contained delay tolerant signal type with which a performance improvement or the like can be expected due to a transmission being carried out in a UL data self-contained operation.

(176) A delay tolerant signal in the UL data self-contained delay tolerant signal type is the delay tolerant signal and uplink data that has already been transmitted in the same time unit.

(177) In a case where an IR (incremental redundancy) scheme is applied in retransmission control, uplink data is transmitted with an RV (redundancy version), which indicates a transmission start position in an encoded data sequence, being altered in accordance with the number of times transmission has been carried out. Some of the uplink data transmitted as a delay tolerant signal may be some of a data sequence having the same RV as uplink data that has already been transmitted in the same time unit, or may be some of a data sequence having a different RV.

(178) Some of the uplink data that is transmitted as a delay tolerant signal is transmitted in a period (the processing time of the base station) corresponding to gap #2 in FIG. 1B. Therefore, there is a high possibility of it being difficult to demodulate/decode within the processing time of the base station 300 (that is, by the next time unit). Therefore, uplink data that is transmitted as a delay tolerant signal is used when uplink data that is retransmitted in the next time unit is received. That is, the base station 300 (the retransmission synthesis decoder 310 depicted in FIG. 6) synthesizes retransmission data of the uplink data, and some of the uplink data that has been received in the previous time unit as a delay tolerant signal, and decodes the synthesized data. It should be noted

that the delay tolerant signal is discarded in a case where a retransmission does not occur.

(179) Some of the uplink data transmitted as a delay tolerant signal has no effect on the retransmission control of downlink data or uplink data even if the base station **300** does not complete reception/decoding processing by the next time unit. That is, some of the uplink data transmitted as a delay tolerant signal is a signal for which a delay can be tolerated compared to uplink data that is transmitted in another uplink transmission region.

(180) In this way, the terminal **400** transmits some of the uplink data transmitted in the same time unit in a gap period (gap #2) at the end of an uplink transmission region. Thus, in addition to the aforementioned effects, it is possible to improve the reception success probability for the next item of uplink data in the base station **300**, when a retransmission has occurred.

(181) Hereinabove, the types of delay tolerant signals have been described in detail. It should be noted that the types of delay tolerant signals are not restricted to the aforementioned signals, and it is sufficient for the types of delay tolerant signals to be signals for which a delay is tolerated in communication using a time unit configuration.

(182) [Delay Tolerant Signal Selection Methods]

(183) Next, methods for selecting a delay tolerant signal to be generated in the aforementioned delay tolerant signal controllers **102** and **302** of the base stations **100** and **300** will be described.

(184) <Selection Method 1>

(185) In selection method 1, the base stations **100** and **300** signal the type of delay tolerant signal to be generated by the terminals **200** and **400**, using delay tolerant signal instruction information and using a downlink control signal (a PDCCH including a DL assignment or a UL assignment).

(186) FIG. **11** depicts an example of delay tolerant signal instruction information during a DL data self-contained operation, and FIG. **12** depicts an example of delay tolerant signal instruction information during a UL data self-contained operation.

(187) It should be noted that in a case where a delay tolerant signal to be transmitted does not fit within the resource that has been set, such as in a case where the size of the processing time (gap #2) of the base stations **100** and **300** is small, the base stations **100** and **300** may notify that there is no delay tolerant signal (delay tolerant signal instruction information=0).

(188) In the terminals **200** and **400**, the control signal demodulator/decoders **204** and **402** acquire notified delay tolerant signal instruction information, and the delay tolerant signal generators **210** and **406**, on the basis of the delay tolerant signal instruction information, determine which delay tolerant signal is to be generated, and generate the delay tolerant signal.

(189) In this way, the base stations **100** and **300** signal the type of delay tolerant signal to be generated, to the terminals **200** and **400** by means of a downlink control signal, and it is thereby possible to dynamically switch the information that is transmitted as a delay tolerant signal.

(190) <Selection Method 2>

(191) In selection method 2, similar to selection method 1, the base station **100** signals the type of delay tolerant signal to be generated by the terminal **200**, using a downlink control signal. In selection method 2, in addition, the type of delay tolerant signal to be transmitted by the terminal **200** is altered in accordance with the size of the radio resource (the frequency domain or the time domain) used to transmit the delay tolerant signal.

(192) FIG. **13** and FIG. **14** depict an example of delay tolerant signal instruction information during a DL data self-contained operation.

(193) The delay tolerant signal instruction information depicted in FIG. **13** is an example in which, in accordance with the resource size, the type of the delay tolerant signal does not change but the content of the information that is transmitted as a delay tolerant signal changes. For example, in a case where the delay tolerant signal instruction information indicates “3” in FIG. **13**, a CQI, a PMI, and an RI are transmitted as CSI constituting a delay tolerant signal when the resource size is large, whereas only a CQI is transmitted as CSI constituting a delay tolerant signal when the resource size is small.

(194) Similarly, in a case where the delay tolerant signal instruction information indicates “5” in FIG. 13, a long BSR is transmitted as a delay tolerant signal when the resource size is large, and a short BSR is transmitted as a delay tolerant signal when the resource size is small. It should be noted that a long BSR is information that notifies the amount of data in a plurality of logical channel groups, and a short BSR is information that notifies the amount of data in one logical channel group.

(195) Meanwhile, the delay tolerant signal instruction information depicted in FIG. 14 is an example in which the type of delay tolerant signal changes in accordance with the resource size. As depicted in FIG. 14, in a case where the resource size is small, an SR, an ACK, a TCP ACK/SYC, no delay tolerant signal, or the like constituting information having a comparatively low number of transmission bits is transmitted as a delay tolerant signal, and in a case where the resource size is large, an SRS, CSI, a transmission beam pattern, a BSR, or the like constituting information having a comparatively high number of transmission bits is transmitted as a delay tolerant signal.

(196) It should be noted that a configuration may be adopted in which the delay tolerant signal instruction information is instructed from a higher layer, and the terminal **200** changes the delay tolerant signal to be transmitted in accordance with the resource size.

(197) In this way, by changing the type or content of the delay tolerant signal to be transmitted, in accordance with the resource size, it becomes possible for the terminal **200** to select the type or content of a large number of delay tolerant signals with a small amount of signaling.

(198) <Selection Method 3>

(199) In selection method 3, the base stations **100** and **300** signal delay tolerant signal instruction information that is similar to delay tolerant signal instruction information **1** to the terminals **200** and **400** by means of a higher layer.

(200) In this way, the base stations **100** and **300** notify the type of delay tolerant signal to be generated, to the terminals **200** and **400** by means of a higher layer notification, and it is thereby possible to reduce the overhead caused by signaling in a downlink.

(201) <Selection Method 4>

(202) In selection method 4, the base stations **100** and **300** notify delay tolerant signal instruction information that indicates the priority levels of delay tolerant signals to be generated, to the terminals **200** and **400** by means of a higher layer.

(203) The terminals **200** and **400** transmit one or more transmittable delay tolerant signals on the basis of the priority levels instructed by the delay tolerant signal instruction information.

(204) FIG. 15 depicts an example of delay tolerant signal instruction information that indicates the priority levels of delay tolerant signals to be generated by the terminals **200** and **400**. For example, in a case where the delay tolerant signal instruction information indicates “0”, the terminals **200** and **400** preferentially select signals to be transmitted as delay tolerant signals, in the order of an SR, CSI, and a BSR.

(205) In this way, the base stations **100** and **300** notify the priority levels of delay tolerant signals to be generated, to the terminals **200** and **400** by means of a higher layer, and it thereby becomes possible for the terminals **200** and **400** to select the types of a large number of delay tolerant signals with a small amount of signaling. Furthermore, even in a case where a signal having a high priority level instructed by the delay tolerant signal instruction information cannot be transmitted as a delay tolerant signal, the terminals **200** and **400** can once again select a signal having a lower priority level, and can therefore select transmission signals in a flexible manner.

(206) It should be noted that a configuration may be adopted in which the terminals **200** and **400** transmit delay tolerant signals according to priority levels that are stipulated as a specification in advance, rather than the base stations **100** and **300** notifying the priority levels of generated signals.

(207) Hereinabove, methods for selecting delay tolerant signals have been described.

(208) In this way, in the present embodiment, a delay tolerant signal that has no effect on the processing time of the base station is mapped to a gap period that is arranged after an uplink

transmission region in a time unit (a gap period that is arranged at the end of a time unit). It is thereby possible to reduce the overhead for gap periods while ensuring the processing times of the base stations **100** and **300** in gap periods. For example, even in a case where gap periods increase in length in consideration of the processing times of the base stations **100** and **300**, more assigned resources for delay tolerant signals can be ensured in proportion to the amount by which the gap periods have increased in length.

(209) Based on the above, according to the present embodiment, it is possible to suppress a decline in the utilization efficiency of radio resources caused by gap periods within time units.

(210) It should be noted that, in the present embodiment, in a case where the size of a resource used to transmit a delay tolerant signal is large, the base stations **100** and **300** may transmit a plurality of items of delay tolerant signal instruction information, and instruct the terminals **200** and **400** to transmit a plurality of delay tolerant signals.

(211) Furthermore, a similar effect can be obtained even if the definition of a time unit is different from the arrangement in the exemplary time unit configuration depicted in FIG. **9**, as long as the arrangement of the signals (a DL assignment, DL data, a gap, an ACK, a delay tolerant signal) within a time unit is the same. For example, the definition of a time unit may be a period from the reception of a delay tolerant signal in a base station to the reception of a response signal (an ACK), as depicted in FIG. **16**. In this case, delay tolerant signals are transmitted from the terminals **200** and **400** to the base stations **100** and **300** at the beginning (an uplink transmission region) of a time unit. Thus, an effect that is similar to that of embodiment 1 (the configuration of FIG. **9**) can be obtained.

(212) Furthermore, a delay tolerant signal is not restricted to an uplink signal transmitted by the terminals **200** and **400**, and may be a downlink signal transmitted by the base stations **100** and **300**. For example, the base station **100** may transmit a delay tolerant signal at the beginning of a downlink transmission region, as depicted in FIG. **17**. Thus, an effect that is similar to that of 1 can be obtained. It should be noted that the details of a downlink signal that is transmitted as a delay tolerant signal will be described in embodiment 3.

Embodiment 2

(213) As described in embodiment 1, in a case where a self-contained operation is used, performance can be improved by transmitting a delay tolerant signal that has no effect on the processing time of a base station or a terminal, at the end of an uplink transmission region within a time unit. However, in embodiment 1, it is necessary for a frequency resource (assigned resource information) used to transmit the delay tolerant signal, to be notified from the base station to the terminal. Therefore, the amount of downlink control signals increases, and the overhead for control signals increases.

(214) Thus, in the present embodiment, a method will be described in which a delay tolerant signal is transmitted without the frequency resource used to transmit the delay tolerant signal being notified by means of a downlink control signal.

(215) It should be noted that the base station and the terminal according to the present embodiment have a basic configuration that is common to the base stations **100** and **300** and the terminals **200** and **400** according to embodiment 1, and will therefore be described with reference to FIG. **4** to FIG. **7**.

(216) In the present embodiment, the processing of the control signal generators **103** and **303** of the base stations **100** and **300** in FIG. **4** and FIG. **6** and the processing of the signal assignment units **212** and **408** of the terminals **200** and **400** in FIG. **5** and FIG. **7** are different from in embodiment 1.

(217) Specifically, the control signal generators **103** and **303** do not generate control information that indicates a frequency resource to which a delay tolerant signal is assigned. That is, the control signal generators **103** and **303** generate assigned resource information for downlink data, uplink data, or a response signal as control information relating to a frequency resource assigned to the terminals **200** and **400**.

(218) The signal assignment units **212** and **408** determine a frequency resource (assigned band) to which a delay tolerant signal is assigned, in accordance with a frequency band (assigned band) to which a downlink control signal, downlink data, uplink data, or a response signal, transmitted in the same time unit as the delay tolerant signal, has been assigned.

(219) Hereinafter, resource assignment methods for a delay tolerant signal in the aforementioned signal assignment units **212** and **408** of the terminals **200** and **400** will be described in detail.

(220) First, a resource assignment method that is common to a DL data self-contained operation and a UL data self-contained operation (common resource assignment method) will be described.

(221) <Common Resource Assignment Method>

(222) The base stations **100** and **300** and the terminals **200** and **400** determine a frequency assignment position for a delay tolerant signal on the basis of a CCE (control channel element) index to which a downlink control signal (for example, a PDCCH that includes a DL assignment or a UL assignment) has been assigned.

(223) FIG. **18** depicts an example of the assignment of a frequency resource for a delay tolerant signal (the delay tolerant signal of FIG. **18**) that is based on a CCE according to the common resource assignment method.

(224) In the example depicted in FIG. **18**, during a DL data self-contained operation, an index of a CCE (downlink resource) to which a DL assignment is assigned and a frequency resource (uplink resource) to which a response signal is assigned are associated on a one-to-one basis.

(225) In FIG. **18**, in addition, the index of the CCE to which the DL assignment is assigned and a frequency resource (uplink resource) to which a delay tolerant signal is assigned are associated on a one-to-one basis.

(226) Here, the number of CCEs, for example, is a value obtained by dividing the number of REs (resource elements) forming a downlink control signal (PDCCH) by 36 (1 CCE=36 REs). Thus, for instance, as an example of the association between CCEs and frequency assignment positions, a usable bandwidth is divided by the number of CCEs, and a usable frequency band is associated with each CCE.

(227) The terminal **200** then transmits the delay tolerant signal which is mapped to all or some of a frequency band that is a resource associated on a one-to-one basis in relation to the delay tolerant signal with the index of the CCE (CCE #X in FIG. **18**) used to transmit the DL assignment addressed thereto.

(228) It should be noted that, although FIG. **18** depicts a DL data self-contained operation, similarly also for a UL data self-contained operation, it is sufficient for the index of a CCE used to transmit a UL assignment and a resource used to transmit a delay tolerant signal to be associated on a one-to-one basis.

(229) In this way, a delay tolerant signal is mapped to a resource associated on a one-to-one basis with a resource (CCE index) used to transmit assignment information (a DL assignment or a UL assignment) indicating a resource assignment for data transmitted in the same time unit as the delay tolerant signal. By associating a CCE index and a resource for a delay tolerant signal, signaling for notifying a frequency resource used to transmit the delay tolerant signal is not necessary. Thus, the base stations **100** and **300** can control the frequency assignment position of a delay tolerant signal while reducing the amount of downlink control information. Furthermore, due to the base stations **100** and **300** controlling the assignment of CCEs, it becomes possible for a radio resource for a delay tolerant signal to be changed by the base stations **100** and **300**.

(230) Next, resource assignment methods during a DL data self-contained operation (DL data self-contained resource assignment methods) will be described.

(231) <DL Data Self-Contained Resource Assignment Method 1>

(232) The terminal **200** transmits a delay tolerant signal within a frequency band having assigned thereto a response signal, which is transmitted within the same time unit.

(233) FIG. **19** depicts an example of the assignment of a frequency resource for a response signal

(ACK) and a delay tolerant signal according to DL data self-contained resource assignment method 1. In FIG. 19, the terminal 200 specifies an assigned resource (ACK resource) for a response signal associated with a CCE (CCE #X in FIG. 19) to which a DL assignment addressed thereto is associated. The terminal 200 then specifies a resource within the same frequency band as the ACK resource as the assigned resource for a delay tolerant signal.

(234) It should be noted that, although FIG. 19 depicts an example in which the assigned resource for a delay tolerant signal is the same as for a response signal, the assigned resource for the delay tolerant signal may not be the same as long as it is within the band to which the response signal is assigned.

(235) Furthermore, in a case where a response signal and a delay tolerant signal are mapped to a code region (OCC (orthogonal cover code) number or cyclic shift number) in a manner similar to a response signal in LTE, a configuration may be adopted in which a delay tolerant signal is transmitted in the same radio resource as an ACK code region.

(236) In this way, a delay tolerant signal is mapped to within the same frequency band as the frequency band having assigned thereto a response signal for downlink data transmitted in the same time unit as the delay tolerant signal. By associating the frequency assignment position of the delay tolerant signal with the response signal, the amount of downlink control information can be reduced. Furthermore, since the frequency assignment position of the delay tolerant signal is the same as for the response signal, scheduling in the base station 100 becomes easy.

(237) <DL Data Self-Contained Resource Assignment Method 2>

(238) The terminal 200 transmits a delay tolerant signal within a frequency band having assigned thereto downlink data, which is transmitted within the same time unit.

(239) FIG. 20 depicts an example of the assignment of a frequency resource for downlink data and a delay tolerant signal according to DL data self-contained resource assignment method 2. In FIG. 20, the terminal 200 specifies an assigned resource for the downlink data (DL data) by means of a DL assignment addressed thereto. The terminal 200 then specifies a resource within the same frequency band as the frequency band assigned to the downlink data, as the assigned resource for a delay tolerant signal.

(240) It should be noted that, although FIG. 20 depicts an example in which the assigned resource for a delay tolerant signal is the same as for downlink data, the assigned resource for the delay tolerant signal may not be the same as long as it is within the band to which the downlink data is assigned.

(241) Furthermore, in a case where downlink data is mapped to non-contiguous bands, the terminal 200 may select one or more bands in descending order of bandwidth from among the non-contiguous bands.

(242) Furthermore, in a case where downlink data is transmitted by means of MU-MIMO, delay tolerant signals of a plurality of terminals 200 are assigned to the same band. In this case, a method is feasible in which delay tolerant signals are also transmitted by means of MU-MIMO in a manner similar to the downlink data. Furthermore, a method may be adopted in which the assigned band for downlink data is divided by the number of terminals multiplexed by means of MU-MIMO, and, for example, a port number for a reference signal (also referred to as a demodulation reference signal: DMRS) for demodulating downlink data and a divided frequency band are associated.

(243) In this way, a delay tolerant signal is mapped to within the same frequency band as the frequency band having assigned thereto downlink data transmitted in the same time unit as the delay tolerant signal. By associating the frequency assignment position of the delay tolerant signal with the downlink data, the amount of downlink control information can be reduced.

(244) Furthermore, as depicted in FIG. 19, in a case where the assigned bandwidth for a response signal (ACK) is narrow when the assigned resource for a delay tolerant signal is associated with the assigned resource for the response signal, the bandwidth for the delay tolerant signal also becomes small. In contrast, as depicted in FIG. 20, by associating the assigned resource for a delay tolerant

signal with an assigned resource for downlink data, it is possible to prevent the assigned bandwidth for the delay tolerant signal becoming narrow.

(245) Furthermore, downlink data is scheduled and therefore there is a high possibility of downlink data being assigned to a frequency band having a high SINR. Thus, in the case of a TDD system, a scheduling gain can be obtained by a delay tolerant signal being transmitted in the same band as downlink data.

(246) <UL Data Self-Contained Resource Assignment Method>

(247) Next, a resource assignment method during a UL data self-contained operation (UL data self-contained resource assignment method) will be described.

(248) The terminal **400** transmits a delay tolerant signal within a frequency band having assigned thereto uplink data, which is transmitted within the same time unit.

(249) FIG. **21** depicts an example of the assignment of a frequency resource for uplink data and a delay tolerant signal according to a UL data self-contained resource assignment method. In FIG. **21**, the terminal **400** specifies an assigned resource for the uplink data (UL data) by means of a UL assignment addressed thereto. The terminal **400** then specifies a resource within the same frequency resource as the frequency resource to which the uplink data has been assigned, as the assigned resource for a delay tolerant signal.

(250) It should be noted that, although FIG. **21** depicts an example in which the assigned resource for a delay tolerant signal is the same as for uplink data, the assigned resource for the delay tolerant signal may not be the same as long as it is within the band to which the uplink data is assigned.

(251) Furthermore, in a case where uplink data is transmitted by means of MU-MIMO, delay tolerant signals of a plurality of terminals **400** are assigned to the same band. In this case, a method is feasible in which delay tolerant signals are also transmitted by means of MU-MIMO in a manner similar to uplink data. Furthermore, a method may be adopted in which the assigned band for uplink data is divided by the number of terminals multiplexed by means of MU-MIMO, and, for example, a port number for a reference signal (DMRS) for demodulating uplink data and a divided frequency band are associated.

(252) In this way, a delay tolerant signal is mapped to within the same frequency band as the frequency band having assigned thereto uplink data transmitted in the same time unit as the delay tolerant signal. By associating the frequency assignment position of the delay tolerant signal with the uplink data, the amount of downlink control information can be reduced. Furthermore, since the frequency assignment position of the uplink data is the same as for the delay tolerant signal, scheduling in the base station **300** becomes easy. Furthermore, since the uplink data is scheduled, there is a high possibility of a signal being assigned to a frequency band having a high SINR. Thus, a scheduling gain can be obtained by the delay tolerant signal being transmitted in the same band as the uplink data.

(253) Hereinabove, the details of resource assignment methods for a delay tolerant signal have been described.

(254) In this way, in the present embodiment, it is not necessary to notify a frequency resource (assigned resource information) used to transmit a delay tolerant signal, from the base stations **100** and **300** to the terminals **200** and **400** using a downlink control signal, and therefore it is possible to prevent an increase in the overhead for control signals.

Embodiment 3

(255) In embodiments 1 and 2, methods have been described in which performance is improved by, in a case where a self-contained operation is used, mapping a delay tolerant signal to the end of an uplink transmission region, that is, a gap period (gap #2) that takes into consideration the processing time of a base station.

(256) However, in a case where the processing time for receiving/decoding downlink data in a terminal is long, it is necessary to increase a gap period (gap #1) that is a switching point between a downlink transmission region and an uplink transmission region, and therefore the overhead for

gap #1 becomes large.

(257) Thus, in the present embodiment, a method will be described in which the overhead for gap #1 is reduced by mapping a delay tolerant signal to within a gap period (gap #1) that is subsequent to a downlink transmission region, that is, a period that is provided with consideration being given to the processing time of a terminal.

(258) [Overview of Communication System]

(259) A communication system that carries out a DL data self-contained operation according to the present embodiment is provided with a base station **500** and a terminal **600**. Furthermore, a communication system that carries out a UL data self-contained operation according to each embodiment of the present disclosure is provided with a base station **700** and a terminal **800**.

(260) [Configuration of Base Station (During DL Data Self-Contained Operation)]

(261) FIG. **22** is a block diagram depicting a configuration of the base station **500** that carries out a DL data self-contained operation according to the present embodiment. In FIG. **22**, the base station **500** has a scheduler **501**, a delay tolerant signal controller **502**, a delay tolerant signal generator **503**, a delay tolerant signal encoder/modulator **504**, a control signal generator **505**, a control signal encoder/modulator **506**, a data encoder **507**, a retransmission controller **508**, a data modulator **509**, a signal assignment unit **510**, the transmitter **109**, the antenna **110**, the receiver **111**, a signal extraction unit **511**, a demodulator/decoder **512**, and a determination unit **513**.

(262) The base station **500** depicted in FIG. **22** transmits a downlink signal that includes a control signal (a DL assignment), downlink data (DL data), or a delay tolerant signal in a downlink transmission region, in a time unit (DL data self-contained time unit) that includes the “downlink transmission region”, an “uplink transmission region”, and a “gap period”. Furthermore, the base station **500** receives an uplink signal that includes a response signal (and may also include a UCI) that is transmitted from the terminal **600** in the uplink transmission region, in the time unit.

(263) In the base station **500**, the scheduler **501** determines scheduling information (for example, the ID of an assigned terminal, assigned resource information for the terminal **600** (a frequency, a time, and a coding resource), data demodulation reference signal information, a modulation/encoding scheme, assigned resource information for a response signal (a frequency, a time, and a coding resource), or the like) relating to a delay tolerant signal, a control signal (a DL assignment), and downlink data (DL data) in the time unit, with respect to the terminal **600**. The scheduler **501** outputs the determined scheduling information to the delay tolerant signal generator **503**, the control signal generator **505**, the data encoder **507**, and the signal assignment unit **510**.

(264) The delay tolerant signal controller **502** determines information regarding a signal (for example, the signal type) that is generated as a delay tolerant signal, which is a signal or a channel that is transmitted from the base station **500** at the end of the downlink transmission region within the time unit, and outputs information indicating the determined content to the delay tolerant signal generator **503** and the control signal generator **505**. It should be noted that the details of a delay tolerant signal determined in the delay tolerant signal controller **502** will be described hereinafter.

(265) The delay tolerant signal generator **503** generates a delay tolerant signal on the basis of information that is input from the delay tolerant signal controller **502** and scheduling information that is instructed from the scheduler **501**, and outputs the generated delay tolerant signal to the delay tolerant signal encoder/modulator **504**.

(266) The delay tolerant signal encoder/modulator **504** encodes and modulates the delay tolerant signal (a bit sequence) that is input from the delay tolerant signal generator **503**, and outputs a modulated delay tolerant signal (symbol string) to the signal assignment unit **510**.

(267) The control signal generator **505** generates a control signal (a DL assignment) for the terminal **600** on the basis of information that is input from each of the scheduler **501** and the delay tolerant signal controller **502**. Control signals include a signal of a cell-specific higher layer, a signal of a group or RAT-specific higher layer, a signal of a terminal-specific higher layer, assigned resource information for downlink data, assigned resource information for a delay tolerant signal,

information instructing the type of delay tolerant signal (hereinafter, referred to as delay tolerant signal type information), assigned resource information for a response signal, and the like. The control signal generator **505** generates a control information bit string using such control information, and outputs the generated control information bit string to the control signal encoder/modulator **506**.

(268) It should be noted that assigned resource information for a delay tolerant signal or the delay tolerant signal type information may be notified in advance by means of a higher layer notification from the base station **500** to the terminal **600**. In this case, the assigned resource information for a delay tolerant signal or the delay tolerant signal type information is not included in a control signal (a DL assignment).

(269) FIG. **23** depicts an example of the delay tolerant signal type information. In FIG. **23**, delay tolerant signal type information (an index) and the types of delay tolerant signals transmitted from the base station **500** are associated.

(270) The control signal encoder/modulator **506** encodes and modulates the control signal (a bit string) received from the control signal generator **505**, and outputs a modulated control signal to the signal assignment unit **510**.

(271) The data encoder **507** carries out error correction encoding on transmission data (downlink data) in accordance with an encoding scheme received from the scheduler **501**, and outputs an encoded data signal to the retransmission controller **508**.

(272) The retransmission controller **508**, at the time of the first transmission, retains the encoded data signal received from the data encoder **507** and also outputs the encoded data signal to the data modulator **509**. Furthermore, the retransmission controller **508**, at the time of a retransmission, controls the retained data on the basis of a determination result (an ACK/NACK) from the determination unit **513**. Specifically, the retransmission controller **508**, upon receiving a NACK with respect to the data signal, outputs the corresponding retained data to the data modulator **509**. Furthermore, the retransmission controller **508**, upon receiving an ACK with respect to the data signal, discards the corresponding retained data and ends the transmission of downlink data.

(273) The data modulator **509** modulates a data signal received from the retransmission controller **508**, and outputs the modulated data signal (symbol string) to the signal assignment unit **510**.

(274) The signal assignment unit **510** maps a delay tolerant signal received from the delay tolerant signal encoder/modulator **504**, a control signal received from the control signal encoder/modulator **506**, and a data signal received from the data modulator **509** to a radio resource instructed from the scheduler **501**. The signal assignment unit **510** outputs a downlink signal for which signal mapping has been carried out, to the transmitter **109**.

(275) The transmitter **109**, the antenna **110**, and the receiver **111** operate in a manner similar to the transmitter **109**, the antenna **110**, and the receiver **111** provided in the base station **100**.

(276) The signal extraction unit **511** extracts a radio resource portion in which an uplink response signal from the terminal **600** has been transmitted, from the reception signal, and outputs a reception response signal to the demodulator/decoder **512**.

(277) The demodulator/decoder **512** carries out equalization, demodulation, and decoding on the reception response signal that is received from the signal extraction unit **511**, and outputs a decoded bit sequence to the determination unit **513**.

(278) The determination unit **513** determines whether a response signal for downlink data, transmitted from the terminal **600**, indicates an ACK or NACK with respect to the downlink data, on the basis of the bit sequence that is input from the demodulator/decoder **512**. The determination unit **513** outputs a determination result (an ACK or NACK) to the retransmission controller **508**.

(279) [Configuration of Terminal (During DL Data Self-Contained Operation)]

(280) FIG. **24** is a block diagram depicting a configuration of the terminal **600** that carries out a DL data self-contained operation according to the present embodiment. In FIG. **24**, the terminal **600** has the antenna **201**, the receiver **202**, a signal extraction unit **601**, a control signal

demodulator/decoder **602**, a delay tolerant signal demodulator/decoder **603**, a delay tolerant signal determination unit **604**, a data demodulator **605**, a data decoder **606**, an error detector **607**, a response signal generator **608**, an encoder/modulator **609**, a signal assignment unit **610**, and the transmitter **213**.

(281) The terminal **600** depicted in FIG. **24** receives a downlink signal that includes a delay tolerant signal, a control signal (a DL assignment), or downlink data (DL data) transmitted from the base station **500** in a downlink transmission region, in a time unit (DL data self-contained time unit) that includes the “downlink transmission region”, a “gap period”, and an “uplink transmission region”. Furthermore, the terminal **600** transmits an uplink signal that includes a response signal for downlink data (and may also include a UCI) in the uplink transmission region in the time unit.

(282) In the terminal **600**, the antenna **201** and the receiver **202** operate in a manner similar to the antenna **201** and the receiver **202** provided in the terminal **200**.

(283) The signal extraction unit **601** extracts a signal portion that includes a control signal from a baseband signal received from the receiver **202**, and outputs the signal portion to the control signal demodulator/decoder **602**. Furthermore, the signal extraction unit **601** extracts a signal portion that includes downlink data from the baseband signal, and outputs the signal portion to the data demodulator **605**. Furthermore, the signal extraction unit **601** extracts a signal portion that includes a delay tolerant signal from the baseband signal, and outputs the signal portion to the delay tolerant signal demodulator/decoder **603**.

(284) The control signal demodulator/decoder **602** carries out blind decoding on a control signal received from the signal extraction unit **601**, and attempts decoding for a control signal addressed thereto. The control signal demodulator/decoder **602**, when having determined as a result of the blind decoding that the control signal is a control signal addressed thereto, outputs, to the data demodulator **605**, assigned resource information for downlink data included in the control signal (the ID of an assigned terminal, assigned resource information (a frequency, a time, and a coding resource), data demodulation reference signal information, a modulation/encoding scheme, or the like), outputs assigned resource information (a frequency, a time, and a coding resource) for a response signal to the signal assignment unit **610**, and outputs assigned resource information for a delay tolerant signal and delay tolerant signal type information to the delay tolerant signal demodulator/decoder **603**.

(285) The delay tolerant signal demodulator/decoder **603** carries out equalization, demodulation, and error correction decoding for a delay tolerant signal that is input from the signal extraction unit **601**, on the basis of the assigned resource information for the delay tolerant signal and the delay tolerant signal type that are input from the control signal demodulator/decoder **602**, and outputs a decoded bit sequence to the delay tolerant signal determination unit **604**.

(286) The delay tolerant signal determination unit **604** determines whether or not the delay tolerant signal (a bit sequence) that is input from the delay tolerant signal demodulator/decoder **603** has been correctly received. The delay tolerant signal determination unit **604**, when having determined that the delay tolerant signal has been correctly received, outputs the delay tolerant signal.

(287) The data demodulator **605** demodulates downlink data received from the signal extraction unit **601**, on the basis of assigned resource information for downlink data, received from the control signal demodulator/decoder **602**, and outputs demodulated downlink data to the data decoder **606**.

(288) The data decoder **606** decodes the downlink data received from the data demodulator **605**, and outputs decoded downlink data to the error detector **607**.

(289) The error detector **607** carries out error detection by means of a CRC, for example, with respect to the downlink data received from the data decoder **606**, and outputs an error detection result (an ACK or NACK) to the response signal generator **608**. Furthermore, the error detector **607** outputs, as reception data, downlink data determined as having no errors as a result of the error detection.

(290) The response signal generator **608**, using the error detection result (an ACK or NACK)

received from the error detector **607**, generates a response signal (a bit sequence) for the received downlink data, and outputs the response signal to the encoder/modulator **609**.

(291) The encoder/modulator **609** carries out error correction encoding on the response signal (a bit sequence) received from the response signal generator **608**, modulates an encoded bit sequence, and outputs a modulated symbol sequence to the signal assignment unit **610**.

(292) The signal assignment unit **610** maps a signal received from the encoder/modulator **609** to a resource (a time, a frequency, and a coding resource) within a time unit for a self-contained operation, instructed from the control signal demodulator/decoder **602**.

(293) The transmitter **213** operates in a manner similar to the transmitter **213** provided in the terminal **200**.

(294) [Configuration of Base Station (During UL Data Self-Contained Operation)]

(295) FIG. **25** is a block diagram depicting a configuration of the base station **700** that carries out a UL data self-contained operation according to the present embodiment. In FIG. **25**, the base station **700** has a scheduler **701**, a delay tolerant signal controller **702**, a delay tolerant signal generator **703**, a delay tolerant signal encoder/modulator **704**, a control signal generator **705**, a control signal encoder/modulator **706**, a signal assignment unit **707**, the transmitter **109**, the antenna **110**, the receiver **111**, a signal extraction unit **708**, a data demodulator **709**, a retransmission synthesis decoder **710**, and an error detector **711**.

(296) The base station **700** depicted in FIG. **25** transmits a downlink signal that includes a delay tolerant signal and a UL assignment in a downlink transmission region of a time unit (UL data self-contained time unit) that includes the “downlink transmission region”, a “gap period”, and an “uplink transmission region”. Furthermore, the base station **700** receives an uplink signal that includes uplink data (and may also include a UCI) that is transmitted from the terminal **800** in the uplink transmission region of the time unit.

(297) In the base station **700**, the scheduler **701** schedules the retransmission of uplink data in a case where an error detection result indicating that there is an error in the previous uplink data is input from the error detector **711**. Furthermore, the scheduler **701** schedules a new packet for the terminal **800** in a case where an error detection result indicating that there are no errors in the previous uplink data is input from the error detector **711**.

(298) For example, the scheduler **701** determines scheduling information (for example, the ID of an assigned terminal, assigned resource information for the terminal **800** (a frequency, a time, and a coding resource), data demodulation reference signal information, a modulation/encoding scheme for uplink data, or the like) relating to a delay tolerant signal, a control signal (a UL assignment), and uplink data (UL data) in a time unit, with respect to the terminal **800**. The scheduler **701** outputs the determined scheduling information to the delay tolerant signal generator **703**, the control signal generator **705**, and the signal assignment unit **707**.

(299) The delay tolerant signal controller **702** determines information (for example, the type of delay tolerant signal) relating to a signal that is generated as a delay tolerant signal, which is a signal or a channel that is transmitted from the base station **700** at the end of the downlink transmission region within the time unit, and outputs information indicating the determined content to the delay tolerant signal generator **703** and the control signal generator **705**. It should be noted that the details of the signal types determined in the delay tolerant signal controller **702** will be described hereinafter.

(300) The delay tolerant signal generator **703** generates a delay tolerant signal on the basis of information that is input from the delay tolerant signal controller **702** and scheduling information that is instructed from the scheduler **701**, and outputs the generated delay tolerant signal to the delay tolerant signal encoder/modulator **704**.

(301) The delay tolerant signal encoder/modulator **704** encodes and modulates the delay tolerant signal (a bit sequence) that is input from the delay tolerant signal generator **703**, and outputs a modulated delay tolerant signal (symbol string) to the signal assignment unit **707**.

(302) The control signal generator **705** generates a control signal (a UL assignment) for the terminal **800** on the basis of information that is input from each of the scheduler **701** and the delay tolerant signal controller **702**. Control signals include a signal of a cell-specific higher layer, a signal of a group or RAT-specific higher layer, a signal of a terminal-specific higher layer, assigned resource information for uplink data, information instructing a retransmission or a new transmission of uplink data, assigned resource information for a delay tolerant signal, information indicating the type of delay tolerant signal (delay tolerant signal type information), or the like. The control signal generator **705** generates a control information bit string using such control information, encodes the generated control information bit string, and outputs the encoded control signal to the control signal encoder/modulator **706**.

(303) It should be noted that assigned resource information for a delay tolerant signal or the delay tolerant signal type information may be notified in advance by means of a higher layer notification from the base station **700** to the terminal **800**. In this case, the assigned resource information for a delay tolerant signal or the delay tolerant signal type information is not included in a control signal (a DL assignment).

(304) The control signal encoder/modulator **706** encodes and modulates a control signal received from the control signal generator **705**, and outputs a modulated control signal to the signal assignment unit **707**.

(305) The signal assignment unit **707** maps a delay tolerant signal received from the delay tolerant signal encoder/modulator **704** and a control signal received from the control signal encoder/modulator **706** to a radio resource (an assigned time/frequency/coding resource) instructed from the scheduler **701**. The signal assignment unit **707** outputs a downlink signal for which signal mapping has been carried out, to the transmitter **109**.

(306) The transmitter **109**, the antenna **110**, and the receiver **111** operate in a manner similar to the transmitter **109**, the antenna **110**, and the receiver **111** provided in the base station **100**.

(307) The signal extraction unit **708** extracts a radio resource portion in which uplink data from the terminal **800** has been transmitted, from a reception signal that is input from the receiver **111**, and outputs the radio resource portion to the data demodulator **709**.

(308) The data demodulator **709** carries out equalization and demodulation processing on uplink data received from the signal extraction unit **708**, and outputs demodulated uplink data (a bit sequence) to the retransmission synthesis decoder **710**.

(309) The retransmission synthesis decoder **710**, in a case where uplink data to be decoded of the terminal **800** is retained (a case where the uplink data is retransmission data), synthesizes the uplink data retained and uplink data that has been output from the data demodulator **709**, and carries out decoding processing on the synthesized uplink data. The retransmission synthesis decoder **710**, in a case where uplink data of the terminal **800** is not retained (a case where the uplink data is the first packet), carries out decoding processing without carrying out synthesis processing for uplink data. The retransmission synthesis decoder **710** then outputs decoded uplink data to the error detector **711**. Furthermore, the retransmission synthesis decoder **710**, in a case where a detection result from the error detector **711** indicates that there are no errors, deletes the retained uplink data of the terminal **800**.

(310) The error detector **711** carries out error detection by means of a CRC, for example, with respect to uplink data received from the retransmission synthesis decoder **710**, and outputs an error detection result (an ACK or NACK) to the scheduler **701** and the retransmission synthesis decoder **710**. Furthermore, the error detector **711** outputs, as reception data, uplink data determined as having no errors as a result of the error detection.

(311) [Configuration of Terminal (During UL Data Self-Contained Operation)]

(312) FIG. **26** is a block diagram depicting a configuration of the terminal **800** that carries out a UL data self-contained operation according to the present embodiment. In FIG. **26**, the terminal **800** has the antenna **201**, the receiver **202**, a signal extraction unit **801**, a control signal

demodulator/decoder **802**, a delay tolerant signal demodulator/decoder **803**, a delay tolerant signal determination unit **804**, a data encoder **805**, a retransmission controller **806**, a data modulator **807**, a signal assignment unit **808**, and the transmitter **213**.

(313) The terminal **800** depicted in FIG. **26** receives a downlink signal that includes a delay tolerant signal or a control signal (a UL assignment) transmitted from the base station **700** in a downlink transmission region of a time unit (UL data self-contained time unit) that includes the “downlink transmission region”, a “gap period”, and an “uplink transmission region”. Furthermore, the terminal **800** transmits an uplink signal that includes uplink data (and may also include a UCI) in the uplink transmission region of the time unit.

(314) In the terminal **800**, the antenna **201** and the receiver **202** operate in a manner similar to the antenna **201** and the receiver **202** provided in the terminal **200**.

(315) The signal extraction unit **801** extracts a control signal from a baseband signal received from the receiver **202**, and outputs the control signal to the control signal demodulator/decoder **802**. Furthermore, the signal extraction unit **801** extracts a signal portion that includes a delay tolerant signal from the baseband signal, and outputs the delay tolerant signal to the delay tolerant signal demodulator/decoder **803**.

(316) The control signal demodulator/decoder **802** carries out blind decoding on a control signal received from the signal extraction unit **801**, and attempts decoding for a control signal addressed thereto. The control signal demodulator/decoder **802**, when having determined as a result of the blind decoding that the control signal is a control signal addressed thereto, outputs, to the signal assignment unit **808**, assigned resource information for uplink data (the ID of an assigned terminal, assigned resource information (a frequency, a time, and a coding resource), data demodulation reference signal information, a modulation/encoding scheme, or the like), included in the control signal, outputs information instructing a retransmission or a new transmission of uplink data to the retransmission controller **806**, and outputs assigned resource information for a delay tolerant signal and delay tolerant signal type information to the delay tolerant signal demodulator/decoder **803**.

(317) The delay tolerant signal demodulator/decoder **803** carries out equalization, demodulation, and error correction decoding for a delay tolerant signal that is input from the signal extraction unit **801**, on the basis of the assigned resource information for the delay tolerant signal and the delay tolerant signal type information that are input from the control signal demodulator/decoder **802**, and outputs a decoded bit sequence to the delay tolerant signal determination unit **804**.

(318) The delay tolerant signal determination unit **804** determines whether or not the delay tolerant signal (a bit sequence) that is input from the delay tolerant signal demodulator/decoder **803** has been correctly received. The delay tolerant signal determination unit **804**, when having determined that the delay tolerant signal has been correctly received, outputs the delay tolerant signal.

(319) The data encoder **805** carries out error correction encoding on transmission data (uplink data), and outputs an encoded data signal to the retransmission controller **806**.

(320) The retransmission controller **806** determines whether or not the uplink data is the first packet or a retransmission packet on the basis of information received from the control signal demodulator/decoder **802**. In the case of the first packet, the retransmission controller **806** retains the encoded uplink data received from the data encoder **805** and also outputs the encoded uplink data to the data modulator **807**. Furthermore, in the case of the first packet, the retransmission controller **806** determines that the transmission and reception of the previous transmission packet has been successful and discards the retained data. However, in the case of a retransmission packet, the retransmission controller **806** outputs the corresponding retained data to the data modulator **807**.

(321) The data modulator **807** modulates the uplink data received from the retransmission controller **806**, and outputs the modulated uplink data to the signal assignment unit **808**.

(322) The signal assignment unit **808** maps the uplink data received from the data modulator **807** to a resource (a time, a frequency, and a coding resource) within a time unit for a self-contained

operation, instructed from the control signal demodulator/decoder **802**. The signal assignment unit **808** outputs an uplink signal for which signal mapping has been carried out, to the transmitter **213**. (323) The transmitter **213** operates in a manner similar to the transmitter **213** provided in the terminal **200**.

(324) [Operation of Base Stations **500** and **700** and Terminals **600** and **800**]

(325) A detailed description will be given regarding an operation in the base stations **500** and **700** and the terminals **600** and **800** having the above configurations.

(326) FIG. **27** depicts an example of a transmission sequence in each of a base station (eNB) and a terminal (UE) during the DL data self-contained operation of FIG. **1A**. Furthermore, FIG. **28** depicts an example of a transmission sequence in each of the base station **500** and the terminal **600** during the DL data self-contained operation according to the present embodiment.

(327) In FIG. **27**, in each time unit, gap #1 that takes into consideration the propagation delay time and the processing time of the terminal is arranged between a downlink transmission region and an uplink transmission region (at the end of the downlink transmission region), and gap #2 that takes into consideration the processing time of the base station is arranged after the uplink transmission region (at the end of the uplink transmission region). For example, the terminal carries out reception processing for downlink data received in the downlink transmission region, in the period of gap #1 depicted in FIG. **27**, and transmits a response signal (ACK) for the downlink data in the uplink transmission region.

(328) However, in the present embodiment, as depicted in FIG. **28**, in a DL data self-contained operation, a delay tolerant signal, for which a delay can be tolerated more than for a control signal or downlink data (DL data) that is mapped to the downlink transmission region, is mapped to a period that takes into consideration the processing time of terminal **600** within gap #1 arranged between the downlink transmission region and the uplink transmission region depicted in FIG. **27**.

(329) That is, the base station **500** transmits a delay tolerant signal that has been mapped to a period corresponding to gap #1 between the downlink transmission region and the uplink transmission region, and the terminal **600** receives the delay tolerant signal that has been mapped to the period corresponding to gap #1.

(330) It should be noted that, as depicted in FIG. **28**, in the base station **500**, out of the period corresponding to gap #1, the length of the period in which the delay tolerant signal is arranged corresponds to the processing time of the terminal **600**, and the remaining period remains as a gap period that takes into consideration a propagation delay between the base station **500** and the terminal **600**.

(331) In this case also, the terminal **600**, upon receiving downlink data in the downlink transmission region, is able to carry out reception processing for downlink data in the transmission period for the delay tolerant signal (corresponding to gap #1), and transmit a response signal for the downlink data in the uplink transmission region.

(332) Furthermore, the terminal **600**, upon receiving a delay tolerant signal transmitted from the base station **500** at the end of the downlink transmission region, carries out predetermined processing (demodulation/decoding processing or the like) on the delay tolerant signal. As mentioned above, a delay tolerant signal is a signal for which it is not always necessary to carry out reception/decoding processing or the like by the time unit that is subsequent to the time unit in which the delay tolerant signal has been received by the terminal **600**. That is, since a delay is tolerated for a delay tolerant signal, the terminal **600**, for example, can carry out demodulation/decoding processing for a delay tolerant signal in a period corresponding to the next time unit.

(333) It should be noted that, although FIG. **28** relates to during a DL data self-contained operation, in a UL data self-contained operation it is also sufficient to similarly configure a time unit in which a delay tolerant signal is mapped to a period corresponding to the processing time of the terminal **600** within gap #1 depicted in FIG. **1B**.

(334) It is thereby possible to reduce the overhead for gaps while maintaining the average delay time from a transmission buffer for the base station **500** being generated to the base station **500** receiving a response signal to downlink data from the terminal **600**, and the average delay time from a transmission buffer for the terminal **800** being generated to the terminal **800** completing transmission of the first uplink data.

(335) It should be noted that it is not always necessary for the base stations **500** and **700** to transmit a delay tolerant signal in each time unit. In a case where the base stations **500** and **700** do not transmit a delay tolerant signal, the time resource for a delay tolerant signal (the end of a downlink transmission region) becomes a gap period as in FIG. **1A** and FIG. **1B**. It is thereby possible to reduce power consumption by not carrying out excessive transmissions.

(336) [Types of Delay Tolerant Times]

(337) Next, the types of delay tolerant times that are generated in the delay tolerant signal generators **503** and **703** of the base stations **500** and **700** will be described in detail.

(338) Hereinafter, the types of delay tolerant signals (common delay tolerant signal types) with which a performance improvement can be expected due to being transmitted in both a DL data self-contained operation and a UL data self-contained operation will be described.

(339) <Common Delay Tolerant Signal Type 1>

(340) A delay tolerant signal in common delay tolerant signal type 1 is system information (a MIB: master information block) of the base stations **500** and **700** constituting broadcast information.

(341) A system bandwidth, the number of transmission antennas, and the like are included in a MIB.

(342) A MIB has no effect on the retransmission control of downlink data or uplink data even if the terminals **600** and **800** do not complete reception/decoding processing by the next time unit. That is, a MIB is a signal for which a delay can be tolerated compared to a control signal (a DL assignment or a UL assignment) or downlink data transmitted in a downlink transmission region.

(343) In this way, due to the base stations **500** and **700** transmitting a MIB in a gap period (part of gap #1) at the end of a downlink transmission region, in addition to the aforementioned effects, it is possible to increase the opportunities for the terminals **600** and **800** to receive system information of the base stations **500** and **700**. Therefore, it is possible to shorten the time required for the terminals **600** and **800** to connect to the base stations **500** and **700**.

(344) <Common Delay Tolerant Signal Type 2>

(345) A delay tolerant signal in common delay tolerant signal type 2 is system information (a SIB: system information block) of the base stations **500** and **700** constituting broadcast information.

(346) A SIB includes parameters relating to access to the base stations **500** and **700**, settings for common/shared channels (configuration), and the like. It should be noted that, in an LTE system, there are SIB **1** to SIB **11** as SIBs, and the content and period for transmission by each SIB are determined. One or more from among SIB **1** to SIB **11** may be SIBs that are transmitted as delay tolerant signals.

(347) A SIB has no effect on the retransmission control of downlink data or uplink data even if the terminals **600** and **800** do not complete reception/decoding processing by the next time unit. That is, a SIB is a signal for which a delay can be tolerated compared to a control signal (a DL assignment or a UL assignment) or downlink data transmitted in a downlink transmission region.

(348) In this way, due to the base stations **500** and **700** transmitting a SIB in a gap period (part of gap #1) at the end of a downlink transmission region, in addition to the aforementioned effects, it is possible to increase the opportunities for the terminals **600** and **800** to receive system information of the base stations **500** and **700**. Therefore, it is possible to shorten the time required for the terminals **600** and **800** to connect to the base stations **500** and **700**.

(349) <Common Delay Tolerant Signal Type 3>

(350) A delay tolerant signal in common delay tolerant signal type 3 is MBMS data, which is broadcast distribution data that is multicast/broadcast.

(351) MBMS data has no effect on the retransmission control of downlink data or uplink data even if the terminals **600** and **800** do not complete reception/decoding processing by the next time unit. That is, MBMS data is a signal for which a delay can be tolerated compared to a control signal (a DL assignment or a UL assignment) or downlink data transmitted in a downlink transmission region.

(352) In this way, due to the base stations **500** and **700** transmitting MBMS data in a gap period (part of gap #1) at the end of a downlink transmission region, in addition to the aforementioned effects, it is possible to increase the opportunities for the terminals **600** and **800** to receive broadcast distribution data that is multicast/broadcast.

(353) <Common Delay Tolerant Signal Type 4>

(354) A delay tolerant signal in common delay tolerant signal type 4 is information instructing a time unit or symbol configuration that can be transmitted in a downlink and an uplink within a certain time period (sometimes also referred to as a DL/UL usage configuration).

(355) A DL/UL usage configuration has no effect on the retransmission control of downlink data or uplink data even if the terminals **600** and **800** do not complete reception/decoding processing by the next time unit. That is, a DL/UL usage configuration is a signal for which a delay can be tolerated compared to a control signal (a DL assignment or a UL assignment) or downlink data transmitted in a downlink transmission region.

(356) In this way, due to the base stations **500** and **700** transmitting a DL/UL usage configuration in a gap period (part of gap #1) at the end of a downlink transmission region, in addition to the aforementioned effects, it is possible to increase the opportunities for the terminals **600** and **800** to switch the time unit or symbol configuration for a downlink and an uplink within a certain time period. Therefore, the configuration of a frame can be altered more dynamically in accordance with the amount of downlink traffic and the amount of uplink traffic, and system throughput can be improved.

(357) Hereinabove, common delay tolerant signal types 1 to 4 have been described.

(358) In this way, in the present embodiment, a delay tolerant signal having no effect on the processing time of the terminal is mapped to a gap period that is a switching point from a downlink transmission region to an uplink transmission region in a time unit (a gap period that is arranged at the end of the downlink transmission region). It is thereby possible to reduce the overhead for gap periods while ensuring the processing times of the terminals **600** and **800** in gap periods. For example, even in a case where gap periods increase in length in consideration of the processing times of the terminals **600** and **800**, more assigned resources for delay tolerant signals can be ensured in proportion to the amount by which the gap periods have increased in length.

(359) Based on the above, according to the present embodiment, it is possible to suppress a decline in the utilization efficiency of radio resources caused by gap periods within time units.

Embodiment 4

(360) As described in embodiment 3, in a case where a self-contained operation is used, performance can be improved by transmitting a delay tolerant signal that has no effect on the processing time of the base station or the terminal, at the end of a downlink transmission region within a time unit (that is, a period for the processing time of the terminal within gap #1 in FIG. 1A and FIG. 1B). However, in embodiment 3, it is necessary to notify a frequency resource (assigned resource information) used to transmit a delay tolerant signal, from the base station to the terminal. Therefore, the amount of downlink control signals increases, and the overhead for control signals increases.

(361) Thus, in the present embodiment, a method will be described in which a delay tolerant signal is transmitted without the frequency resource used to transmit the delay tolerant signal being notified by means of a downlink control signal.

(362) It should be noted that the base station and the terminal according to the present embodiment have a basic configuration that is common to the base stations **500** and **700** and the terminals **600**

and **800** according to embodiment 3, and will therefore be described with reference to FIG. 22 and FIG. 24 to FIG. 26.

(363) In the present embodiment, the processing of the control signal generators **505** and **705** and the processing of the signal assignment units **510** and **707** of the base stations **500** and **700** in FIG. 22 and FIG. 25 are different from in embodiment 3.

(364) Specifically, the control signal generators **505** and **705** do not generate control information that indicates a frequency resource to which a delay tolerant signal is assigned. That is, the control signal generators **505** and **705** generate assigned resource information for downlink data, uplink data, or a response signal as control information relating to a frequency resource assigned to the terminals **600** and **800**.

(365) The signal assignment units **510** and **707** determine a frequency resource (assigned band) to which a delay tolerant signal is assigned, in accordance with a frequency band (assigned band) to which a downlink control signal, downlink data, or uplink data, transmitted in the same time unit as the delay tolerant signal, has been assigned.

(366) Hereinafter, a resource assignment method for a delay tolerant signal in the aforementioned signal assignment units **510** and **707** of the base stations **500** and **700** will be described in detail.

(367) First, resource assignment methods that are common to a DL data self-contained operation and a UL data self-contained operation (common resource assignment method) will be described.

(368) <Common Resource Assignment Method 1>

(369) The terminals **600** and **800** receive a delay tolerant signal in a frequency band notified by means of a higher layer. In this way, by notifying a transmission band for a delay tolerant signal by means of a higher layer notification, the amount of downlink control information can be reduced. Furthermore, data transmitted to both the terminals **600** and **800** such as broadcast information can be received by both the terminals **600** and **800** due to being arranged in a radio resource instructed by means of a higher layer notification.

(370) <Common Resource Assignment Method 2>

(371) The terminals **600** and **800** specify a frequency assignment position for a delay tolerant signal on the basis of a CCE index to which a downlink control signal (for example, a PDCCH that includes a DL assignment or a UL assignment) has been assigned.

(372) FIG. 29 depicts an example of the assignment of a frequency resource for a delay tolerant signal (the delay tolerant signal of FIG. 29) that is based on a CCE according to common resource assignment method 2.

(373) In the example depicted in FIG. 29, during a DL data self-contained operation, an index of a CCE (downlink resource) to which a DL assignment is assigned and a frequency resource (uplink resource) to which a response signal is assigned are associated on a one-to-one basis.

(374) In FIG. 29, in addition, the CCE index to which the DL assignment is assigned and a frequency resource (uplink resource) to which a delay tolerant signal is assigned are associated on a one-to-one basis.

(375) Here, the number of CCEs, for example, is a value obtained by dividing the number of REs forming a downlink control signal (PDCCH) by 36 (1 CCE=36 REs). Thus, for instance, as an example of the association between CCEs and frequency assignment positions, a usable bandwidth is divided by the number of CCEs, and a usable frequency band is associated with each CCE.

(376) The base station **500** then transmits the delay tolerant signal which is mapped to all or some of a frequency band that is a resource associated on a one-to-one basis in relation to the delay tolerant signal with the index of the CCE (CCE #X in FIG. 29) used to transmit the DL assignment for the corresponding terminal **600**. Furthermore, the terminal **600** specifies, as an assigned resource for the delay tolerant signal, all or some of a frequency band that is a resource associated on a one-to-one basis in relation to the delay tolerant signal with the index of the CCE to which the DL assignment addressed thereto has been assigned.

(377) It should be noted that, although FIG. 29 depicts a DL data self-contained operation,

similarly also for a UL data self-contained operation, it is sufficient for the index of a CCE used to transmit a UL assignment and a resource used to transmit a delay tolerant signal to be associated on a one-to-one basis.

(378) In this way, a delay tolerant signal is mapped to a resource associated on a one-to-one basis with a resource (CCE index) used to transmit assignment information (a DL assignment or a UL assignment) indicating a resource assignment for data transmitted in the same time unit as the delay tolerant signal. By associating a CCE index and a resource for a delay tolerant signal, signaling for notifying a frequency resource used to transmit the delay tolerant signal is not necessary. Thus, the base stations **500** and **700** can control the frequency assignment position of a delay tolerant signal while reducing the amount of downlink control information. Furthermore, due to the base stations **500** and **700** controlling the assignment of CCEs, it becomes possible for a radio resource for a delay tolerant signal to be changed by the base stations **500** and **700**.

(379) <DL Data Self-Contained Resource Assignment Method>

(380) Next, a resource assignment method during a DL data self-contained operation (DL data self-contained resource assignment methods) will be described.

(381) The terminal **600** receives a delay tolerant signal within a frequency band having assigned thereto downlink data, which is transmitted within the same time unit.

(382) FIG. **30** depicts an example of the assignment of a frequency resource for downlink data and a delay tolerant signal according to a DL data self-contained resource assignment method. In FIG. **30**, the base station **500** transmits a delay tolerant signal which is mapped to a resource within the same frequency band as the frequency band used to transmit downlink data for the corresponding terminal **600**. The terminal **600** specifies an assigned resource for the downlink data (DL data) by means of the DL assignment addressed thereto. The terminal **600** then specifies a resource within the same frequency band as the frequency band assigned to the downlink data, as the assigned resource for the delay tolerant signal.

(383) It should be noted that, although FIG. **30** depicts an example in which the assigned resource for a delay tolerant signal is the same as for downlink data, the assigned resource for the delay tolerant signal may not be the same as long as it is within the band to which the downlink data is assigned.

(384) Furthermore, in a case where downlink data is transmitted by means of MU-MIMO, delay tolerant signals of a plurality of terminals **600** are assigned to the same band. In this case, a method is feasible in which delay tolerant signals are also transmitted by means of MU-MIMO in a manner similar to downlink data. Furthermore, a method may be adopted in which the assigned band for downlink data is divided by the number of terminals multiplexed by means of MU-MIMO, and, for example, a port number for a reference signal (DMRS) for demodulating downlink data and a divided frequency band are associated.

(385) Furthermore, in a case where a delay tolerant signal is a multicast/broadcast signal, a method may be adopted in which the base station **500** transmits a delay tolerant signal within a frequency band to which downlink data is assigned, irrespective of the downlink data transmission method.

(386) In this way, a delay tolerant signal is mapped to within the same frequency band as the frequency band having assigned thereto downlink data transmitted in the same time unit as the delay tolerant signal. By associating the frequency assignment position of the delay tolerant signal with the downlink data, the amount of downlink control information can be reduced. Furthermore, since the frequency assignment position of the downlink data is the same as for the delay tolerant signal, scheduling in the base station **500** becomes easy. Furthermore, since the downlink data is scheduled, there is a high possibility of a signal being assigned to a frequency band having a high SINR. Thus, a scheduling gain can be obtained by the delay tolerant signal being transmitted in the same band as the downlink data.

(387) <UL Data Self-Contained Resource Assignment Method>

(388) Next, a resource assignment method during a UL data self-contained operation (UL data self-

contained resource assignment method) will be described.

(389) The terminal **800** receives a delay tolerant signal within a frequency band having assigned thereto uplink data, which is transmitted within the same time unit.

(390) FIG. **31** depicts an example of the assignment of a frequency resource for uplink data and a delay tolerant signal according to a UL data self-contained resource assignment method. In FIG. **31**, the base station **700** transmits a delay tolerant signal which is mapped to a resource within the same frequency band as the frequency band used to transmit uplink data (UL data) for the corresponding terminal **800**. The terminal **800** specifies an assigned resource for the uplink data by means of a UL assignment addressed thereto. The terminal **800** then specifies a resource within the same frequency band as the frequency band assigned to the uplink data, as the assigned resource for a delay tolerant signal.

(391) It should be noted that, although FIG. **31** depicts an example in which the assigned resource for a delay tolerant signal is the same as for uplink data, the assigned resource for the delay tolerant signal may not be the same as long as it is within the band to which the uplink data is assigned.

(392) Furthermore, in a case where uplink data is transmitted by means of MU-MIMO, delay tolerant signals of a plurality of terminals **800** are assigned to the same band. In this case, a method is feasible in which delay tolerant signals are also transmitted by means of MU-MIMO in a manner similar to uplink data. Furthermore, a method may be adopted in which the assigned band for uplink data is divided by the number of terminals multiplexed by means of MU-MIMO, and, for example, a port number for a reference signal (DMRS) for demodulating uplink data and a divided frequency band are associated.

(393) In this way, a delay tolerant signal is mapped to within the same frequency band as the frequency band having assigned thereto uplink data transmitted in the same time unit as the delay tolerant signal. By associating the frequency assignment position of the delay tolerant signal with the uplink data, the amount of downlink control information can be reduced. Furthermore, since the frequency assignment position of the uplink data is the same as for the delay tolerant signal, scheduling in the base station **700** becomes easy. Furthermore, since the uplink data is scheduled, there is a high possibility of a signal being assigned to a frequency band having a high SINR. Thus, in the case of a TDD system, a scheduling gain can be obtained by the delay tolerant signal being transmitted in the same band as the uplink data.

(394) Hereinabove, the details of resource assignment methods for a delay tolerant signal have been described.

(395) In this way, in the present embodiment, it is not necessary to notify a frequency resource (assigned resource information) used to transmit a delay tolerant signal, from the base stations **500** and **700** to the terminals **600** and **800** using a downlink control signal, and therefore it is possible to prevent an increase in the overhead for control signals.

(396) Hereinabove, embodiments of the present disclosure have been described.

(397) It should be noted that embodiment 1 and embodiment 2 may be combined and implemented.

(398) Furthermore, the aforementioned embodiments describe examples of cases where an aspect of the present disclosure is configured by means of hardware; however, it is also possible for the present disclosure to be realized by means of software in cooperation with hardware.

(399) Furthermore, each functional block used in the description of the aforementioned embodiments is typically realized as an LSI, which is an integrated circuit. The integrated circuits may control the functional blocks used in the descriptions of the aforementioned embodiments, and may be provided with input and output. These may be implemented separately as single chips or may be implemented as a single chip in such a way as to include some or all of the functional blocks. LSIs have been mentioned here; however, the functional blocks are sometimes also referred to as ICs, system LSIs, super LSIs, or ultra LSIs depending on differences in the degree of integration.

(400) Furthermore, the circuit integration technique is not limited to that of an LSI, and a functional

block may be realized using a dedicated circuit or a general-purpose processor. After an LSI has been manufactured, an FPGA (field-programmable gate array) that can be programmed, or a reconfigurable processor with which the connections and settings of circuit cells within the LSI can be reconfigured, may be used.

(401) In addition, if circuit integration technology that replaces LSI appears as a result of another technology that is an advancement in semiconductor technology or is derived therefrom, naturally, the other technology may be used to carry out the integration of functional blocks. Biotechnology applications and the like are also a possibility.

(402) A base station of the present disclosure is provided with: a transmitter that transmits a downlink signal in a downlink transmission region, in a time unit that includes the downlink transmission region, an uplink transmission region, and a gap period that is a switching point between the downlink transmission region and the uplink transmission region; and a receiver that receives an uplink signal in the uplink transmission region, in the time unit, in which a delay tolerant signal for which a delay is tolerated more than for the downlink signal and the uplink signal is mapped to within the gap period.

(403) In the base station of the present disclosure, the transmitter transmits the delay tolerant signal mapped to the gap period arranged between the downlink transmission region and the uplink transmission region within the time unit.

(404) In the base station of the present disclosure, the delay tolerant signal is at least one downlink signal from among a MIB (master information block), a SIB (system information block), MBMS (multimedia broadcast and multicast service) data, information indicating a time unit configuration of a downlink and an uplink, or downlink data.

(405) In the base station of the present disclosure, the receiver receives the delay tolerant signal mapped to the gap period arranged after the uplink transmission region.

(406) In the base station of the present disclosure, the delay tolerant signal is at least one uplink signal from among an SRS (sounding reference signal), information indicating a transmission beam pattern, CSI (channel state information), an SR (scheduling request), a BSR (buffer status report), a TCP ACK/SYC, a response signal that is transmitted in the same time unit as the delay tolerant signal, or uplink data that is transmitted in the same time unit as the delay tolerant signal.

(407) In the base station of the present disclosure, the delay tolerant signal is mapped to a resource associated on a one-to-one basis with a resource used to transmit assignment information indicating a resource assignment for data transmitted in the same time unit as the delay tolerant signal.

(408) In the base station of the present disclosure, the delay tolerant signal is mapped to within the same frequency band as a frequency band having assigned thereto a response signal for downlink data transmitted in the same time unit as the delay tolerant signal.

(409) In the base station of the present disclosure, the delay tolerant signal is mapped to within the same frequency band as a frequency band having assigned thereto data transmitted in the same time unit as the delay tolerant signal.

(410) A terminal of the present disclosure is provided with: a receiver that receives a downlink signal in a downlink transmission region, in a time unit that includes the downlink transmission region, an uplink transmission region, and a gap period that is a switching point between the downlink transmission region and the uplink transmission region; and a transmitter that transmits an uplink signal in the uplink transmission region, in the time unit, in which a delay tolerant signal for which a delay is tolerated more than for the downlink signal and the uplink signal is mapped to within the gap period.

(411) A communication method of the present disclosure includes: transmitting a downlink signal in a downlink transmission region, in a time unit that includes the downlink transmission region, an uplink transmission region, and a gap period that is a switching point between the downlink transmission region and the uplink transmission region; and receiving an uplink signal in the uplink transmission region, in the time unit, in which a delay tolerant signal for which a delay is tolerated

more than for the downlink signal and the uplink signal is mapped to within the gap period.
(412) A communication method of the present disclosure includes: receiving a downlink signal in a downlink transmission region, in a time unit that includes the downlink transmission region, an uplink transmission region, and a gap period that is a switching point between the downlink transmission region and the uplink transmission region; and transmitting an uplink signal in the uplink transmission region, in the time unit, in which a delay tolerant signal for which a delay is tolerated more than for the downlink signal and the uplink signal is mapped to within the gap period.

INDUSTRIAL APPLICABILITY

(413) An aspect of the present disclosure is useful in a mobile communication system.

REFERENCE SIGNS LIST

(414) **100, 300, 500, 700** Base station **101, 301, 501, 701** Scheduler **102, 302, 502, 702** Delay tolerant signal controller **103, 303, 505, 705** Control signal generator **104, 304, 506, 706** Control signal encoder/modulator **105, 403, 507, 805** Data encoder **106, 404, 508, 806** Retransmission controller **107, 405, 509, 807** Data modulator **108, 212, 305, 408, 510, 610, 707, 808** Signal assignment unit **109, 213** Transmitter **110, 201** Antenna **111, 202** Receiver **112, 203, 306, 401, 511, 601, 708, 801** Signal extraction unit **113, 307, 603, 803** Delay tolerant signal demodulator/decoder **114, 308, 604, 804** Delay tolerant signal determination unit **115, 512** Demodulator/decoder **116, 513** Determination unit **200, 400, 600, 800** Terminal **204, 402, 602, 802** Control signal demodulator/decoder **205, 309, 605, 709** Data demodulator **206, 606** Data decoder **207, 311, 607, 711** Error detector **208, 608** Response signal generator **209, 609** Encoder/modulator **210, 406, 503, 703** Delay tolerant signal generator **211, 407, 504, 704** Delay tolerant signal encoder/modulator **310, 710** Retransmission synthesis decoder

Claims

1. A terminal, comprising: a receiver, which, in operation, receives, based on time unit configuration information, a downlink signal in a downlink transmission region, in a subcarrier subframe, the subcarrier subframe including the downlink transmission region, an uplink transmission region, and a gap period between the downlink transmission region and the uplink transmission region, wherein the time unit configuration is dynamically indicated by Downlink Control Information (DCI); and a transmitter, which, in operation, transmits an uplink signal in the uplink transmission region, in the subcarrier subframe, wherein a delay tolerant signal for which a delay is tolerated more than for the downlink signal and the uplink signal is mapped to within the gap period in the subcarrier subframe, and the delay tolerant signal is a sounding reference signal (SRS).
2. The terminal according to the claim 1, wherein the subcarrier subframe is a Time Division Duplex (TDD) subframe.
3. The terminal according to the claim 1, wherein the transmitter in operation transmits the delay tolerant signal in the gap period.
4. A communication method for a terminal, the communication method comprising: receiving, based on time unit configuration information, a downlink signal in a downlink transmission region, in a subcarrier subframe, the subcarrier subframe including the downlink transmission region, an uplink transmission region, and a gap period between the downlink transmission region and the uplink transmission region wherein the time unit configuration is dynamically indicated by Downlink Control Information (DCI); and transmitting an uplink signal in the uplink transmission region, in the subcarrier subframe, wherein a delay tolerant signal for which a delay is tolerated more than for the downlink signal and the uplink signal is mapped to within the gap period in the subcarrier subframe, and the delay tolerant signal is a sounding reference signal (SRS).
5. The communication method according to the claim 4, wherein the subcarrier subframe is a Time

Division Duplex (TDD) subframe.

6. The communication method according to the claim 4, comprising: transmitting the delay tolerant signal in the gap period.
 7. A base station comprising: a transmitter, which, in operation, transmits, based on time unit configuration information, a downlink signal in a downlink transmission region, in a subcarrier subframe, the subcarrier subframe including the downlink transmission region, an uplink transmission region, and a gap period between the downlink transmission region and the uplink transmission region wherein the time unit configuration is dynamically indicated by Downlink Control Information (DCI); and a receiver, which, in operation, receives an uplink signal in the uplink transmission region, in the subcarrier subframe, wherein a delay tolerant signal for which a delay is tolerated more than for the downlink signal and the uplink signal is mapped to within the gap period in the subcarrier subframe, and the delay tolerant signal is a sounding reference signal (SRS).
 8. The base station according to the claim 7, wherein the subcarrier subframe is a Time Division Duplex (TDD) subframe.
 9. The base station according to the claim 7, wherein the receiver, in operation, receives the delay tolerant signal in the gap period.
 10. A terminal, comprising: a receiver, which, in operation, receives, control information relating to a time resource of a delay tolerant signal by a higher layer signaling; and a transmitter, which, in operation, transmits the delay tolerant signal in a time unit based on the control information, the time unit including a downlink transmission region, an uplink transmission region, and a gap period between the downlink transmission region and the uplink transmission region in a subcarrier, wherein a length of the gap period of the time unit is configured by a base station, wherein the delay tolerant signal is mapped to within the gap period of the time unit, and the delay tolerant signal is a sounding reference signal (SRS), which is different from a downlink data signal transmitted in the downlink region and an uplink data signal transmitted in the uplink region.
-