

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250267289

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

PANUSOPONE; Krit et al.

REDUCING MOTION VECTOR INFORMATION TRANSMISSION IN BI-DIRECTIONAL TEMPORAL PREDICTION

Abstract

A method for inter-coding video is provided in which transmission bandwidth requirements associated with second motion vectors for bi-directional temporal prediction is reduced. In the method motion vector information for only one of the two motion vectors for bi-directional temporal prediction can be transmitted together with information on how to derive or construct the second motion vector. Thus, rather than sending express information regarding two motion vectors, express information related to only one motion vector along with information related to reconstruction/derivation of the second motion vector is transmitted, thus reducing bandwidth requirements and increasing coding efficiency.

Inventors: PANUSOPONE; Krit (San Diego, CA), YU; Yue (San Diego, CA), WANG; Limin (San Diego, CA)

Applicant: ARRIS Enterprises LLC (Horsham, PA)

Family ID: 1000008589339

Assignee: ARRIS Enterprises LLC (Horsham, PA)

Appl. No.: 19/202897

Filed: May 08, 2025

Related U.S. Application Data

parent US continuation 18502954 20240119 parent-grant-document US 12323601 child US 19202897

parent US continuation 17983301 20221108 ABANDONED child US 18502954

parent US continuation 17163059 20210129 parent-grant-document US 11533492 child US 17983301

parent US continuation 16377833 20190408 parent-grant-document US 11146796 child US 17163059

Publication Classification

Int. Cl.: **H04N19/159** (20140101); **H04N19/137** (20140101); **H04N19/174** (20140101);
H04N19/30 (20140101)

U.S. Cl.:

CPC **H04N19/159** (20141101); **H04N19/137** (20141101); **H04N19/174** (20141101);
H04N19/30 (20141101);

Background/Summary

CLAIM OF PRIORITY [0001] This Application is a continuation of U.S. patent application Ser. No. 18/502,954 filed Jan. 19, 2024, which is a continuation of U.S. patent application Ser. No. 17/983,301 filed Nov. 8, 2022, which is a continuation of U.S. patent application Ser. No. 17/163,059 filed Jan. 29, 2021, now U.S. Pat. No. 11,533,492 which is a continuation of U.S. patent application Ser. No. 16/377,833, filed Apr. 8, 2019, now U.S. Pat. No. 11,146,796, which claims priority under 35 U.S.C. § 119 (e) from earlier filed U.S. Provisional Application No. 62/654,073, filed Apr. 6, 2018, and U.S. Provisional Patent Application No. 62/656,114, filed Apr. 11, 2018, the entireties of each of which are hereby incorporated herein by reference.

TECHNICAL FIELD

[0002] The present disclosure relates to the field of video coding, particularly coding efficiency increases associated with reduction in transmission of motion vector information for Bi-directional temporal prediction.

BACKGROUND

[0003] The technical improvements in evolving video coding standards illustrate the trend of increasing coding efficiency to enable higher bit-rates, higher resolutions, and better video quality. The Joint Video Exploration Team developed a new video coding scheme referred to as JVET and is developing a newer video coding scheme referred to a Versatile Video Coding (VVC)-the complete contents of the VVC 7th edition of draft 2 of the standard titled Versatile Video Coding (Draft 2) by JVET published Oct. 1, 2018 is hereby incorporated herein by reference. Similar to other video coding schemes like HEVC (High Efficiency Video Coding), both JVET and VVC are block-based hybrid spatial and temporal predictive coding schemes. However, relative to HEVC, JVET and VVC include many modifications to bitstream structure, syntax, constraints, and mapping for the generation of decoded pictures. JVET has been implemented in Joint Exploration Model (JEM) encoders and decoders, but VVC is not anticipated to be implemented until early 2020.

[0004] Various coding techniques require that two motion vectors be using in the reconstruction of a coding unit. Transmission of complete information related to the two motion vectors is inefficient and consumes unnecessary bandwidth. What is needed is a system and method of reducing overhead and burden associated with coding involving multiple Motion Vectors (MVs).

SUMMARY

[0005] A system of one or more computers can be configured to perform particular operations or actions by virtue of having software, firmware, hardware, or a combination of them installed on the system that in operation causes or cause the system to perform the actions. One or more computer

programs can be configured to perform particular operations or actions by virtue of including instructions that, when executed by data processing apparatus, cause the apparatus to perform the actions. One general aspect comprises receiving information regarding a coding unit; determining motion information associated with said coding unit; determining whether more than one motion vector is associated with said motion information; determining a relationship between a first motion vector and a second motion vector if it is determined that said motion information is associated with more than one motion vector; and encoding said coding unit, where said coding unit includes information related to said first motion vector and information related to said relationship between said first motion vector and said second motion vector. Other embodiments of this aspect include corresponding computer systems, apparatus, and computer programs recorded on one or more computer storage devices, each configured to perform the actions of the methods. [0006] Implementations can comprise one or more of the following features: The method of inter-coding where said information related to said relationship between said first motion vector and said second motion vector includes information sufficient to reconstruct an MVP index and an MVD of said second motion vector; the method of inter-coding where said information related to said relationship between said first motion vector and said second motion vector includes a scaling factor; the method of inter-coding where said information related to said relationship between said first motion vector and said second motion vector includes information sufficient to reconstruct an MVP index and an MVD of said second motion vector; the method of inter-coding where said information related to said relationship between said first motion vector and said second motion vector includes information regarding a reference slice; the method of inter-coding where said information related to said relationship between said first motion vector and said second motion vector indicates said second motion vector is a mirror image of said first motion vector; the method of inter-coding where said information related to said relationship between said first motion vector and said second motion vector includes reference index information; the method of inter-coding where said information related to said relationship between said first motion vector and said second motion vector includes a control point for said second motion vector. Implementations of the described techniques can comprise hardware, a method or process, or computer software on a computer-accessible medium.

[0007] Some embodiments can include a system of inter-coding comprising: receiving in a first memory information regarding a coding unit, determining motion information associated with said coding unit, determining whether more than one motion vector is associated with said motion information, determining a relationship between a first motion vector and a second motion vector if it is determined that said motion information is associated with more than one motion vector, and encoding said coding unit, where said coding unit includes information related to said first motion vector and information related to said relationship between said first motion vector and said second motion vector. Other embodiments of this aspect include corresponding computer systems, apparatus, and computer programs recorded on one or more computer storage devices, each configured to perform the actions of the methods.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0008] Further details of the present invention are explained with the help of the attached drawings in which:

[0009] FIG. 1 depicts division of a frame into a plurality of Coding Tree Units (CTUs).

[0010] FIG. 2a-2c depict exemplary partitioning of a CTU into Coding Units (CUs).

[0011] FIG. 3 depicts a quadtree plus binary tree (QTBT) representation of FIG. 2's CU

[0012] partitioning.

[0013] FIG. 4 depicts a simplified block diagram for CU coding in a JVET or VVC encoder.
[0014] FIG. 5 depicts possible intra prediction modes for luma components in JVET of VVC.
[0015] FIG. 6 depicts a simplified block diagram for CU coding in a JVET of VVC decoder.
[0016] FIG. 7 depicts a block diagram of a reduced-overhead encoding method for use in encoding video.
[0017] FIG. 8 depicts a block diagram of a reduced-overhead decoding method for use in decoding video.
[0018] FIG. 9 depicts an embodiment of a computer system adapted and configured to provide for variable template size for template matching.
[0019] FIG. 10 depicts an embodiment of video encoder/decoder adapted and configured to provide for variable template size for template matching.

DETAILED DESCRIPTION

[0020] FIG. 1 depicts division of a frame into a plurality of Coding Tree Units (CTUs) **100**. A frame can be an image in a video sequence. A frame can include a matrix, or set of matrices, with pixel values representing intensity measures in the image. Thus, a set of these matrices can generate a video sequence. Pixel values can be defined to represent color and brightness in full color video coding, where pixels are divided into three channels. For example, in a Y CbCr color space pixels can have a luma value, Y, that represents gray level intensity in the image, and two chrominance values, Cb and Cr, that represent the extent to which color differs from gray to blue and red. In other embodiments, pixel values can be represented with values in different color spaces or models. The resolution of the video can determine the number of pixels in a frame. A higher resolution can mean more pixels and a better definition of the image, but can also lead to higher bandwidth, storage, and transmission requirements.

[0021] Frames of a video sequence can be encoded and decoded using JVET. JVET is a video coding scheme being developed by the Joint Video Exploration Team. Versions of JVET have been implemented in JEM (Joint Exploration Model) encoders and decoders. Similar to other video coding schemes like HEVC (High Efficiency Video Coding), JVET is a block-based hybrid spatial and temporal predictive coding scheme. During coding with JVET, a frame is first divided into square blocks called CTUs **100**, as shown in FIG. 1. For example, CTUs **100** can be blocks of 128×128 pixels.

[0022] FIG. 2a depicts an exemplary partitioning of a CTU **100** into CUs **102**. Each CTU **100** in a frame can be partitioned into one or more CUs (Coding Units) **102**. CUs **102** can be used for prediction and transform as described below. Unlike HEVC, in JVET the CUs **102** can be rectangular or square and can be coded without further partitioning into prediction units or transform units. The CUs **102** can be as large as their root CTUs **100**, or be smaller subdivisions of a root CTU **100** as small as 4×4 blocks.

[0023] In JVET, a CTU **100** can be partitioned into CUs **102** according to a quadtree plus binary tree (QTBT) scheme in which the CTU **100** can be recursively split into square blocks according to a quadtree, and those square blocks can then be recursively split horizontally or vertically according to binary trees. Parameters can be set to control splitting according to the QTBT, such as the CTU size, the minimum sizes for the quadtree and binary tree leaf nodes, the maximum size for the binary tree root node, and the maximum depth for the binary trees. In VVC, a CTU **100** can be partitioned into CUs utilizing ternary splitting also.

[0024] By way of a non-limiting example, FIG. 2a shows a CTU **100** partitioned into CUs **102**, with solid lines indicating quadtree splitting and dashed lines indicating binary tree splitting. As illustrated, the binary splitting allows horizontal splitting and vertical splitting to define the structure of the CTU and its subdivision into CUs. FIGS. 2b & 2c depict alternate, non-limiting examples of ternary splitting of a CU wherein subdivisions of the CUs are non-equal.

[0025] FIG. 3 depicts a QTBT representation of FIG. 2's partitioning. A quadtree root node represents the CTU **100**, with each child node in the quadtree portion representing one of four

square blocks split from a parent square block. The square blocks represented by the quadtree leaf nodes can then be divided zero or more times using binary trees, with the quadtree leaf nodes being root nodes of the binary trees. At each level of the binary tree portion, a block can be divided either vertically or horizontally. A flag set to “0” indicates that the block is split horizontally, while a flag set to “1” indicates that the block is split vertically.

[0026] After quadtree splitting and binary tree splitting, the blocks represented by the QTBT's leaf nodes represent the final CUs **102** to be coded, such as coding using inter prediction or intra prediction. For slices or full frames coded with inter prediction, different partitioning structures can be used for luma and chroma components. For example, for an inter slice a CU **102** can have Coding Blocks (CBs) for different color components, such as such as one luma CB and two chroma CBs. For slices or full frames coded with intra prediction, the partitioning structure can be the same for luma and chroma components.

[0027] FIG. **4** depicts a simplified block diagram for CU coding in a JVET encoder. The main stages of video coding include partitioning to identify CUs **102** as described above, followed by encoding CUs **102** using prediction at **404** or **406**, generation of a residual CU **410** at **408**, transformation at **412**, quantization at **416**, and entropy coding at **420**. The encoder and encoding process illustrated in FIG. **4** also includes a decoding process that is described in more detail below.

[0028] Given a current CU **102**, the encoder can obtain a prediction CU **402** either spatially using intra prediction at **404** or temporally using inter prediction at **406**. The basic idea of prediction coding is to transmit a differential, or residual, signal between the original signal and a prediction for the original signal. At the receiver side, the original signal can be reconstructed by adding the residual and the prediction, as will be described below. Because the differential signal has a lower correlation than the original signal, fewer bits are needed for its transmission.

[0029] A slice, such as an entire picture or a portion of a picture, coded entirely with intra-predicted CUs can be an I slice that can be decoded without reference to other slices, and as such can be a possible point where decoding can begin. A slice coded with at least some inter-predicted CUs can be a predictive (P) or bi-predictive (B) slice that can be decoded based on one or more reference pictures. P slices may use intra-prediction and inter-prediction with previously coded slices. For example, P slices may be compressed further than the I-slices by the use of inter-prediction, but need the coding of a previously coded slice to code them. B slices can use data from previous and/or subsequent slices for its coding, using intra-prediction or inter-prediction using an interpolated prediction from two different frames, thus increasing the accuracy of the motion estimation process. In some cases P slices and B slices can also or alternately be encoded using intra block copy, in which data from other portions of the same slice is used.

[0030] As will be discussed below, intra prediction or inter prediction can be performed based on reconstructed CUs **434** from previously coded CUs **102**, such as neighboring CUs **102** or CUs **102** in reference pictures.

[0031] When a CU **102** is coded spatially with intra prediction at **404**, an intra prediction mode can be found that best predicts pixel values of the CU **102** based on samples from neighboring CUs **102** in the picture.

[0032] When coding a CU's luma component, the encoder can generate a list of candidate intra prediction modes. While HEVC had 35 possible intra prediction modes for luma components, in JVET there are 67 possible intra prediction modes for luma components and in VVC there are 85 prediction modes. These include a planar mode that uses a three dimensional plane of values generated from neighboring pixels, a DC mode that uses values averaged from neighboring pixels, the 65 directional modes shown in FIG. **5** that use values copied from neighboring pixels along the solid-line indicated directions and 18 wide-angle prediction modes that can be used with non-square blocks.

[0033] When generating a list of candidate intra prediction modes for a CU's luma component, the number of candidate modes on the list can depend on the CU's size. The candidate list can include:

a subset of HEVC's 35 modes with the lowest SATD (Sum of Absolute Transform Difference) costs; new directional modes added for J VET that neighbor the candidates found from the HEVC modes; and modes from a set of six most probable modes (MPMs) for the CU **102** that are identified based on intra prediction modes used for previously coded neighboring blocks as well as a list of default modes.

[0034] When coding a CU's chroma components, a list of candidate intra prediction modes can also be generated. The list of candidate modes can include modes generated with cross-component linear model projection from luma samples, intra prediction modes found for luma CBs in particular collocated positions in the chroma block, and chroma prediction modes previously found for neighboring blocks. The encoder can find the candidate modes on the lists with the lowest rate distortion costs, and use those intra prediction modes when coding the CU's luma and chroma components. Syntax can be coded in the bitstream that indicates the intra prediction modes used to code each CU **102**.

[0035] After the best intra prediction modes for a CU **102** have been selected, the encoder can generate a prediction CU **402** using those modes. When the selected modes are directional modes, a 4-tap filter can be used to improve the directional accuracy. Columns or rows at the top or left side of the prediction block can be adjusted with boundary prediction filters, such as 2-tap or 3-tap filters.

[0036] The prediction CU **402** can be smoothed further with a position dependent intra prediction combination (PDPC) process that adjusts a prediction CU **402** generated based on filtered samples of neighboring blocks using unfiltered samples of neighboring blocks, or adaptive reference sample smoothing using 3-tap or 5-tap low pass filters to process reference samples.

[0037] When a CU **102** is coded temporally with inter prediction at **406**, a set of motion vectors (MVs) can be found that points to samples in reference pictures that best predict pixel values of the CU **102**. Inter prediction exploits temporal redundancy between slices by representing a displacement of a block of pixels in a slice. The displacement is determined according to the value of pixels in previous or following slices through a process called motion compensation. Motion vectors and associated reference indices that indicate pixel displacement relative to a particular reference picture can be provided in the bitstream to a decoder, along with the residual between the original pixels and the motion compensated pixels. The decoder can use the residual and signaled motion vectors and reference indices to reconstruct a block of pixels in a reconstructed slice.

[0038] In JVET, motion vector accuracy can be stored at 1/16 pel, and the difference between a motion vector and a CU's predicted motion vector can be coded with either quarter-pel resolution or integer-pel resolution.

[0039] In JVET motion vectors can be found for multiple sub-CUs within a CU **102**, using techniques such as advanced temporal motion vector prediction (ATMVP), spatial-temporal motion vector prediction (STMVP), affine motion compensation prediction, pattern matched motion vector derivation (PMMVD), and/or bi-directional optical flow (BIO).

[0040] Using ATMVP, the encoder can find a temporal vector for the CU **102** that points to a corresponding block in a reference picture. The temporal vector can be found based on motion vectors and reference pictures found for previously coded neighboring CUs **102**. Using the reference block pointed to by a temporal vector for the entire CU **102**, a motion vector can be found for each sub-CU within the CU **102**.

[0041] STM VP can find motion vectors for sub-CUs by scaling and averaging motion vectors found for neighboring blocks previously coded with inter prediction, together with a temporal vector.

[0042] Affine motion compensation prediction can be used to predict a field of motion vectors for each sub-CU in a block, based on two control motion vectors found for the top corners of the block. For example, motion vectors for sub-CUs can be derived based on top corner motion vectors found for each 4×4 block within the CU **102**.

[0043] PMMVD can find an initial motion vector for the current CU **102** using bilateral matching or template matching. Bilateral matching can look at the current CU **102** and reference blocks in two different reference pictures along a motion trajectory, while template matching can look at corresponding blocks in the current CU **102** and a reference picture identified by a template. The initial motion vector found for the CU **102** can then be refined individually for each sub-CU.

[0044] BIO can be used when inter prediction is performed with bi-prediction based on earlier and later reference pictures, and allows motion vectors to be found for sub-CUs based on the gradient of the difference between the two reference pictures.

[0045] In some situations local illumination compensation (LIC) can be used at the CU level to find values for a scaling factor parameter and an offset parameter, based on samples neighboring the current CU **102** and corresponding samples neighboring a reference block identified by a candidate motion vector. In JVET, the LIC parameters can change and be signaled at the CU level.

[0046] For some of the above methods the motion vectors found for each of a CU's sub-CUs can be signaled to decoders at the CU level. For other methods, such as PM MVD and BIO, motion information is not signaled in the bitstream to save overhead, and decoders can derive the motion vectors through the same processes.

[0047] After the motion vectors for a CU **102** have been found, the encoder can generate a prediction CU **402** using those motion vectors. In some cases, when motion vectors have been found for individual sub-CUs, Overlapped Block Motion Compensation (OBMC) can be used when generating a prediction CU **402** by combining those motion vectors with motion vectors previously found for one or more neighboring sub-CUs.

[0048] When bi-prediction is used, JVET can use decoder-side motion vector refinement (DMVR) to find motion vectors. DMVR allows a motion vector to be found based on two motion vectors found for bi-prediction using a bilateral template matching process. In DMVR, a weighted combination of prediction CUs **402** generated with each of the two motion vectors can be found, and the two motion vectors can be refined by replacing them with new motion vectors that best point to the combined prediction CU **402**. The two refined motion vectors can be used to generate the final prediction CU **402**.

[0049] At **408**, once a prediction CU **402** has been found with intra prediction at **404** or inter prediction at **406** as described above, the encoder can subtract the prediction CU **402** from the current CU **102** find a residual CU **410**.

[0050] The encoder can use one or more transform operations at **412** to convert the residual CU **410** into transform coefficients **414** that express the residual CU **410** in a transform domain, such as using a discrete cosine block transform (DCT-transform) to convert data into the transform domain. JVET allows more types of transform operations than HEVC, including DCT-II, DST-VII, DST-VII, DCT-VIII, DST-I, and DCT-V operations. The allowed transform operations can be grouped into sub-sets, and an indication of which sub-sets and which specific operations in those sub-sets were used can be signaled by the encoder. In some cases, large block-size transforms can be used to zero out high frequency transform coefficients in CUs **102** larger than a certain size, such that only lower-frequency transform coefficients are maintained for those CUs **102**.

[0051] In some cases a mode dependent non-separable secondary transform (MDNSST) can be applied to low frequency transform coefficients **414** after a forward core transform. The MDNSST operation can use a Hypercube-Givens Transform (HyGT) based on rotation data. When used, an index value identifying a particular MDNSST operation can be signaled by the encoder.

[0052] At **416**, the encoder can quantize the transform coefficients **414** into quantized transform coefficients **416**. The quantization of each coefficient may be computed by dividing a value of the coefficient by a quantization step, which is derived from a quantization parameter (QP). In some embodiments, the Qstep is defined as $2^{\text{sup}(\text{QP}-4)/6}$. Because high precision transform coefficients **414** can be converted into quantized transform coefficients **416** with a finite number of possible values, quantization can assist with data compression. Thus, quantization of the transform

coefficients may limit an amount of bits generated and sent by the transformation process.

However, while quantization is a lossy operation, and the loss by quantization cannot be recovered, the quantization process presents a trade-off between quality of the reconstructed sequence and an amount of information needed to represent the sequence. For example, a lower QP value can result in better quality decoded video, although a higher amount of data may be required for representation and transmission. In contrast, a high QP value can result in lower quality reconstructed video sequences but with lower data and bandwidth needs.

[0053] JVET can utilize variance-based adaptive quantization techniques, which allows every CU **102** to use a different quantization parameter for its coding process (instead of using the same frame QP in the coding of every CU **102** of the frame). The variance-based adaptive quantization techniques adaptively lowers the quantization parameter of certain blocks while increasing it in others. To select a specific QP for a CU **102**, the CU's variance is computed. In brief, if a CU's variance is higher than the average variance of the frame, a higher QP than the frame's QP may be set for the CU **102**. If the CU **102** presents a lower variance than the average variance of the frame, a lower QP may be assigned.

[0054] At **420**, the encoder can find final compression bits **422** by entropy coding the quantized transform coefficients **418**. Entropy coding aims to remove statistical redundancies of the information to be transmitted. In JVET, CABAC (Context Adaptive Binary Arithmetic Coding) can be used to code the quantized transform coefficients **418**, which uses probability measures to remove the statistical redundancies. For CUs **102** with non-zero quantized transform coefficients **418**, the quantized transform coefficients **418** can be converted into binary. Each bit ("bin") of the binary representation can then be encoded using a context model. A CU **102** can be broken up into three regions, each with its own set of context models to use for pixels within that region.

[0055] Multiple scan passes can be performed to encode the bins. During passes to encode the first three bins (bin0, bin1, and bin2), an index value that indicates which context model to use for the bin can be found by finding the sum of that bin position in up to five previously coded neighboring quantized transform coefficients **418** identified by a template.

[0056] A context model can be based on probabilities of a bin's value being '0' or '1'. As values are coded, the probabilities in the context model can be updated based on the actual number of '0' and '1' values encountered. While HEVC used fixed tables to re-initialize context models for each new picture, in JVET the probabilities of context models for new inter-predicted pictures can be initialized based on context models developed for previously coded inter-predicted pictures.

[0057] The encoder can produce a bitstream that contains entropy encoded bits **422** of residual CUs **410**, prediction information such as selected intra prediction modes or motion vectors, indicators of how the CUs **102** were partitioned from a CTU **100** according to the QTBT structure, and/or other information about the encoded video. The bitstream can be decoded by a decoder as discussed below.

[0058] In addition to using the quantized transform coefficients **418** to find the final compression bits **422**, the encoder can also use the quantized transform coefficients **418** to generate reconstructed CUs **434** by following the same decoding process that a decoder would use to generate reconstructed CUs **434**. Thus, once the transformation coefficients have been computed and quantized by the encoder, the quantized transform coefficients **418** may be transmitted to the decoding loop in the encoder. After quantization of a CU's transform coefficients, a decoding loop allows the encoder to generate a reconstructed CU **434** identical to the one the decoder generates in the decoding process. Accordingly, the encoder can use the same reconstructed CUs **434** that a decoder would use for neighboring CUs **102** or reference pictures when performing intra prediction or inter prediction for a new CU **102**. Reconstructed CUs **102**, reconstructed slices, or full reconstructed frames may serve as references for further prediction stages.

[0059] At the encoder's decoding loop (and see below, for the same operations in the decoder) to obtain pixel values for the reconstructed image, a dequantization process may be performed. To

dequantize a frame, for example, a quantized value for each pixel of a frame is multiplied by the quantization step, e.g., (Qstep) described above, to obtain reconstructed dequantized transform coefficients **426**. For example, in the decoding process shown in FIG. **4** in the encoder, the quantized transform coefficients **418** of a residual CU **410** can be dequantized at **424** to find dequantized transform coefficients **426**. If an M DNSST operation was performed during encoding, that operation can be reversed after dequantization.

[0060] At **428**, the dequantized transform coefficients **426** can be inverse transformed to find a reconstructed residual CU **430**, such as by applying a DCT to the values to obtain the reconstructed image. At **432** the reconstructed residual CU **430** can be added to a corresponding prediction CU **402** found with intra prediction at **404** or inter prediction at **406**, in order to find a reconstructed CU **434**.

[0061] At **436**, one or more filters can be applied to the reconstructed data during the decoding process (in the encoder or, as described below, in the decoder), at either a picture level or CU level. For example, the encoder can apply a deblocking filter, a sample adaptive offset (SAO) filter, and/or an adaptive loop filter (ALF). The encoder's decoding process may implement filters to estimate and transmit to a decoder the optimal filter parameters that can address potential artifacts in the reconstructed image. Such improvements increase the objective and subjective quality of the reconstructed video. In deblocking filtering, pixels near a sub-CU boundary may be modified, whereas in SAO, pixels in a CTU **100** may be modified using either an edge offset or band offset classification. JVET's ALF can use filters with circularly symmetric shapes for each 2×2 block. An indication of the size and identity of the filter used for each 2×2 block can be signaled.

[0062] If reconstructed pictures are reference pictures, they can be stored in a reference buffer **438** for inter prediction of future CUs **102** at **406**.

[0063] During the above steps, JVET allows a content adaptive clipping operations to be used to adjust color values to fit between lower and upper clipping bounds. The clipping bounds can change for each slice, and parameters identifying the bounds can be signaled in the bitstream.

[0064] FIG. **6** depicts a simplified block diagram for CU coding in a JVET decoder. A JVET decoder can receive a bitstream containing information about encoded CUs **102**. The bitstream can indicate how CUs **102** of a picture were partitioned from a CTU **100** according to a QTBT structure, prediction information for the CUs **102** such as intra prediction modes or motion vectors, and bits **602** representing entropy encoded residual CUs.

[0065] At **604** the decoder can decode the entropy encoded bits **602** using the CABAC context models signaled in the bitstream by the encoder. The decoder can use parameters signaled by the encoder to update the context models' probabilities in the same way they were updated during encoding.

[0066] After reversing the entropy encoding at **604** to find quantized transform coefficients **606**, the decoder can dequantize them at **608** to find dequantized transform coefficients **610**. If an M DNSST operation was performed during encoding, that operation can be reversed by the decoder after dequantization.

[0067] At **612**, the dequantized transform coefficients **610** can be inverse transformed to find a reconstructed residual CU **614**. At **616**, the reconstructed residual CU **614** can be added to a corresponding prediction CU **626** found with intra prediction at **622** or inter prediction at **624**, in order to find a reconstructed CU **618**.

[0068] At **620**, one or more filters can be applied to the reconstructed data, at either a picture level or CU level. For example, the decoder can apply a deblocking filter, a sample adaptive offset (SAO) filter, and/or an adaptive loop filter (ALF). As described above, the in-loop filters located in the decoding loop of the encoder may be used to estimate optimal filter parameters to increase the objective and subjective quality of a frame. These parameters are transmitted to the decoder to filter the reconstructed frame at **620** to match the filtered reconstructed frame in the encoder.

[0069] After reconstructed pictures have been generated by finding reconstructed CUs **618** and

applying signaled filters, the decoder can output the reconstructed pictures as output video **628**. If reconstructed pictures are to be used as reference pictures, they can be stored in a reference buffer **630** for inter prediction of future CUs **102** at **624**.

[0070] Bi-directional temporal prediction employs two MVs referring to reference slices in two reference lists to determine two prediction blocks. These two prediction blocks are then combined to form final prediction block. In JVET and VVC, several inter coding modes (skip, merge, FRUC, AMVP, AFFINE) include bi-directional temporal prediction to increased prediction accuracy.

Signaling for the two MVs varies by the coding mode. AMVP (Advanced MV Predictor) utilizes the most flexible signaling for the two MVs. Specifically, three information types are required to generate MV; reference index, MVP index, and MVD. Hence, a coding block using AMVP with bi-directional temporal prediction must send two reference indices, two MVP indices, and two MVDs.

[0071] The affine motion model describes motion between two frames in a more flexible way, such as rotation, shear and scale. The affine model employs an affine transformation to describe motion based on model parameters. In JVET and VVC, four or six parameter models can be employed.

Instead of using affine motion model to compute motion field for each pixel in coding block, JVET and VVC can compute MV at a coarser granularity, such as a block of size 4×4. Moreover, JVET and VVC describe an affine motion model of a coding block through control point motion vectors. That is, MV for each block coding using affine mode can be determined based on control point motion vectors.

[0072] Control point MVs can be coded using predictive coding in a similar fashion as normal MV in JVET and VVC. MV predictors for each control point MV are first determined and then MV a difference between the MV predictor and the control point MV can then be coded and signaled in the bitstream. That is, two control point MVs can be used for a four-parameter Affine model and three control point MVs can be used for a six-parameter Affine model.

[0073] Bi-directional temporal prediction using Affine motion model requires additional overhead to signal additional control point MV. For four parameter Affine model, two MVDs are signaled for each list, instead of one. Similarly, three MVDs are signaled for each list, instead of one, when size parameter Affine model is used. Hence, a coding block using Affine model for AMVP with bi-directional temporal prediction must send two reference indices, two MVP indices, and either four or six MVDs, based on Affine motion model.

[0074] Disclosed is a system and method of reducing overhead of Bi-directional temporal prediction. The current approach in JVET and VVC signals MV information overhead twice resulting in two MVs that are independent from each other. The overhead or signaling two independent MVs can be reduced if the two MVs for bi-directional temporal prediction are related. When the two MVs are related (or paired), the second MV can be fully or partially derived from the first MV and thus reducing the overhead for the second MV.

[0075] The relationship between the MV pair (first MV and second MV) can be significant for achieving high coding efficiency. There are many possible ways to define a MV pair relationship. In some embodiments, optical flow can be assumed and/or that the first MV and second MV can have similar trajectories can be assumed. In such an embodiment, the second MV can be considered a scaled version of the first MV and the relationship can be defined as follows:

$$MV2=((POC_Cur-POC_L1)/(POC_Cur-POC_L0))*MV1$$

[0076] Wherein:

[0077] MV1 and MV2 are MV of the first and second MV, respectively;

[0078] POC Cur is the POC index of the current slice; and

[0079] POC_L0 and POC_L1 are the POC indices of the reference used by MV1 and MV2, respectively.

[0080] This equation shows an example of a derivation of the second MV in which the first MV of the MV pair uses a reference slice stored in one of reference lists, such as reference list 0 (and or

any other known, convenient and/or desired reference) and the second MV of the MV pair uses a reference slice stored in another list of reference lists (and or any other known, convenient and/or desired reference).

[0081] Additionally, there are many ways to signal the second MV with reduced overhead based on the system in which the second MV is derived from the first MV. In some embodiments, the signaling scheme may not send a reference index, MVP index and MVD of the second MV. In such embodiments, a reference slice in list 1 can be determined to be used for the second MV—by way of non-limiting example, reference index 0 of list 1 can be used. MV2 can thus be computed based on the equation provided.

[0082] In some alternate embodiments, MV2 can be configured as the mirror of MV1 and thus be derived or constructed from MV1.

[0083] In still further alternate embodiments, a reference index, absent sending an MVP index and MVD of the second MV can be established from the MV1 and MV2 information. In such alternate embodiments, the system can first determine a reference slice in list 1 of the second MV using the signaled reference index which can be literally signaled, then compute MV2 according to the provided equation.

[0084] There are a few possible ways to utilize MV pair concept when the affine motion model is employed. In some embodiments, a control point MV of the second list can be determined by scaling a corresponding control point MV of the first list in accordance with the equation provided above. A MV of the second list for each sub-block within a coding block can then be computed based on the derived control point MV. In some alternate embodiments, a MV of the first list for each sub-block can be determined using signaled control point MVs, then a scaled MV of the first list can be used to determine the MV of the second list for each sub-block.

[0085] In still further alternate embodiments, MVD2 can be related to MVD1 where MVD1 and MVD2 are difference between motion vectors interrelated in accordance with the following equation:

$$MVD2 = ((POC_Cur - POC_L1) / (POC_Cur - POC_L0)) * MVD1$$

[0086] Thus, MVD2 can be derived or determined from MVD1 and the system can send reference index information and an MVP index, but the MVD of the second MV need not be transmitted as it can be directly determined from MVD1.

[0087] Furthermore, there are also many ways to add an MV pair (interrelated MV1 and MV2) concept to the existing AMVP and affine bi-directional temporal prediction systems. In some embodiments, a new flag at CU level can be introduced to indicate whether an MV pair with reduced MV2 overhead or the existing full MV2 overhead signaling is used. In embodiments in which full MV2 overhead signaling is used, reference index, MVP index and MVD can be signaled as in current JVET and VVC systems. In alternate embodiments, an MV pair option can be signaled as a special index of list 1—by way of non-limiting example, reference index 1 can be considered M V pair option with a reference slice set to index 0 of list 1. Additionally, in some embodiments, this option can be disabled for Generalized P/B (GPB) slice, where all reference slices in list 0 are identical to list 1, since MV1 and MV2 are identical based on the provided equation.

[0088] FIG. 7 depicts a block diagram of a reduced-overhead encoding method **700** for use in encoding video. In step **702** information related to a CU can be received then in step **704** the information can be evaluated to determine whether more than one MV is to be used in the coding process. If in step **704** it is determined that more than one MV is to be used in the coding process, then the system can proceed to step **706** in which MV1 (the first motion vector) and MV2 (the second motion vector) are determined. Then in step **708**, a relationship between MV1 and MV2 can be determined, using any one or more of the previously described techniques and/or any other known convenient and/or desired method and/or technique. However, in some embodiments, step

708 can precede step **706** and the second motion vector can be defined directly by reference to the first motion vector. In step **710**, signaling related to the relationship between MV1 and MV2 can be determined, using any one or more of the previously described techniques and/or any other known convenient and/or desired method and/or technique and then the CU can be encoded with the relevant information related to MV1 and the relationship to MV2 in step **712** and the encoded bitstream can be transmitted in step **714**. If in step **704** it is determined that fewer than two MVs are desired for encoding, then the process can proceed directly from step **704** to the encoding step **712** and then to transmission in step **714**.

[0089] FIG. **8** depicts a block diagram of a reduced-overhead decoding method **800** for use in decoding video. In step **802** a signal is received and then a CU is decoded in step **804**. The in step **806** is determined whether more than one M V is indicated in the received signal. If in step **806** it is determined that more than one MV is indicated in the received signal, then in step **808** MV1 is determined from signal and information regarding MV2 is determined from the signal. MV2 is then constructed from MV1 and the information regarding MV2 in step **810**. The reconstruction of MV2 can be performed in accordance with any of the techniques and methods described herein and/or any other know, convenient and/or desired technique and/or method. In step **812** the video can be reconstructed and then can be displayed in step **814**. If in step **806** is determined that one or fewer MVs are indicated in the received signal, then the system can proceed from step **806** to reconstruction of the video in step **812** and display in step **814**.

[0090] The execution of the sequences of instructions required to practice the embodiments can be performed by a computer system **900** as shown in FIG. **9**. In an embodiment, execution of the sequences of instructions is performed by a single computer system **900**. According to other embodiments, two or more computer systems **900** coupled by a communication link **915** can perform the sequence of instructions in coordination with one another. Although a description of only one computer system **900** will be presented below, however, it should be understood that any number of computer systems **900** can be employed to practice the embodiments.

[0091] A computer system **900** according to an embodiment will now be described with reference to FIG. **9**, which is a block diagram of the functional components of a computer system **900**. As used herein, the term computer system **900** is broadly used to describe any computing device that can store and independently run one or more programs.

[0092] Each computer system **900** can include a communication interface **914** coupled to the bus **906**. The communication interface **914** provides two-way communication between computer systems **900**. The communication interface **914** of a respective computer system **900** transmits and receives electrical, electromagnetic or optical signals, that include data streams representing various types of signal information, e.g., instructions, messages and data. A communication link **915** links one computer system **900** with another computer system **900**. For example, the communication link **915** can be a LAN, in which case the communication interface **914** can be a LAN card, or the communication link **915** can be a PSTN, in which case the communication interface **914** can be an integrated services digital network (ISDN) card or a modem, or the communication link **915** can be the Internet, in which case the communication interface **914** can be a dial-up, cable or wireless modem.

[0093] A computer system **900** can transmit and receive messages, data, and instructions, including program, i.e., application, code, through its respective communication link **915** and communication interface **914**. Received program code can be executed by the respective processor(s) **907** as it is received, and/or stored in the storage device **910**, or other associated non-volatile media, for later execution.

[0094] In an embodiment, the computer system **900** operates in conjunction with a data storage system **931**, e.g., a data storage system **931** that contains a database **932** that is readily accessible by the computer system **900**. The computer system **900** communicates with the data storage system **931** through a data interface **933**. A data interface **933**, which is coupled to the bus **906**, transmits

and receives electrical, electromagnetic or optical signals, that include data streams representing various types of signal information, e.g., instructions, messages and data. In embodiments, the functions of the data interface **933** can be performed by the communication interface **914**.

[0095] Computer system **900** includes a bus **906** or other communication mechanism for communicating instructions, messages and data, collectively, information, and one or more processors **907** coupled with the bus **906** for processing information. Computer system **900** also includes a main memory **908**, such as a random access memory (RAM) or other dynamic storage device, coupled to the bus **906** for storing dynamic data and instructions to be executed by the processor(s) **907**. The main memory **908** also can be used for storing temporary data, i.e., variables, or other intermediate information during execution of instructions by the processor(s) **907**.

[0096] The computer system **900** can further include a read only memory (ROM) **909** or other static storage device coupled to the bus **906** for storing static data and instructions for the processor(s) **907**. A storage device **910**, such as a magnetic disk or optical disk, can also be provided and coupled to the bus **906** for storing data and instructions for the processor(s) **907**.

[0097] A computer system **900** can be coupled via the bus **906** to a display device **911**, such as, but not limited to, a cathode ray tube (CRT) or a liquid-crystal display (LCD) monitor, for displaying information to a user. An input device **912**, e.g., alphanumeric and other keys, is coupled to the bus **906** for communicating information and command selections to the processor(s) **907**.

[0098] According to one embodiment, an individual computer system **900** performs specific operations by their respective processor(s) **907** executing one or more sequences of one or more instructions contained in the main memory **908**. Such instructions can be read into the main memory **908** from another computer-usable medium, such as the ROM **909** or the storage device **910**. Execution of the sequences of instructions contained in the main memory **908** causes the processor(s) **907** to perform the processes described herein. In alternative embodiments, hard-wired circuitry can be used in place of or in combination with software instructions. Thus, embodiments are not limited to any specific combination of hardware circuitry and/or software.

[0099] The term “computer-usable medium,” as used herein, refers to any medium that provides information or is usable by the processor(s) **907**. Such a medium can take many forms, including, but not limited to, non-volatile, volatile and transmission media. Non-volatile media, i.e., media that can retain information in the absence of power, includes the ROM **909**, CD ROM, magnetic tape, and magnetic discs. Volatile media, i.e., media that can not retain information in the absence of power, includes the main memory **908**. Transmission media includes coaxial cables, copper wire and fiber optics, including the wires that comprise the bus **906**. Transmission media can also take the form of carrier waves; i.e., electromagnetic waves that can be modulated, as in frequency, amplitude or phase, to transmit information signals. Additionally, transmission media can take the form of acoustic or light waves, such as those generated during radio wave and infrared data communications.

[0100] In the foregoing specification, the embodiments have been described with reference to specific elements thereof. It will, however, be evident that various modifications and changes can be made thereto without departing from the broader spirit and scope of the embodiments. For example, the reader is to understand that the specific ordering and combination of process actions shown in the process flow diagrams described herein is merely illustrative, and that using different or additional process actions, or a different combination or ordering of process actions can be used to enact the embodiments. The specification and drawings are, accordingly, to be regarded in an illustrative rather than restrictive sense.

[0101] It should also be noted that the present invention can be implemented in a variety of computer systems. The various techniques described herein can be implemented in hardware or software, or a combination of both. Preferably, the techniques are implemented in computer programs executing on programmable computers that each include a processor, a storage medium readable by the processor (including volatile and non-volatile memory and/or storage elements), at

least one input device, and at least one output device. Program code is applied to data entered using the input device to perform the functions described above and to generate output information. The output information is applied to one or more output devices. Each program is preferably implemented in a high level procedural or object oriented programming language to communicate with a computer system. However, the programs can be implemented in assembly or machine language, if desired. In any case, the language can be a compiled or interpreted language. Each such computer program is preferably stored on a storage medium or device (e.g., ROM or magnetic disk) that is readable by a general or special purpose programmable computer for configuring and operating the computer when the storage medium or device is read by the computer to perform the procedures described above. The system can also be considered to be implemented as a computer-readable storage medium, configured with a computer program, where the storage medium so configured causes a computer to operate in a specific and predefined manner. Further, the storage elements of the exemplary computing applications can be relational or sequential (flat file) type computing databases that are capable of storing data in various combinations and configurations.

[0102] FIG. 10 is a high level view of a source device 1012 and destination device 1010 that may incorporate features of the systems and devices described herein. As shown in FIG. 10, example video coding system 1010 includes a source device 1012 and a destination device 1014 where, in this example, the source device 1012 generates encoded video data. Accordingly, source device 1012 may be referred to as a video encoding device. Destination device 1014 may decode the encoded video data generated by source device 1012. Accordingly, destination device 1014 may be referred to as a video decoding device. Source device 1012 and destination device 1014 may be examples of video coding devices.

[0103] Destination device 1014 may receive encoded video data from source device 1012 via a channel 1016. Channel 1016 may comprise a type of medium or device capable of moving the encoded video data from source device 1012 to destination device 1014. In one example, channel 1016 may comprise a communication medium that enables source device 1012 to transmit encoded video data directly to destination device 1014 in real-time.

[0104] In this example, source device 1012 may modulate the encoded video data according to a communication standard, such as a wireless communication protocol, and may transmit the modulated video data to destination device 1014. The communication medium may comprise a wireless or wired communication medium, such as a radio frequency (RF) spectrum or one or more physical transmission lines. The communication medium may form part of a packet-based network, such as a local area network, a wide-area network, or a global network such as the Internet. The communication medium may include routers, switches, base stations, or other equipment that facilitates communication from source device 1012 to destination device 1014. In another example, channel 1016 may correspond to a storage medium that stores the encoded video data generated by source device 1012.

[0105] In the example of FIG. 10, source device 1012 includes a video source 1018, video encoder 1020, and an output interface 1022. In some cases, output interface 1028 may include a modulator/demodulator (modem) and/or a transmitter. In source device 1012, video source 1018 may include a source such as a video capture device, e.g., a video camera, a video archive containing previously captured video data, a video feed interface to receive video data from a video content provider, and/or a computer graphics system for generating video data, or a combination of such sources.

[0106] Video encoder 1020 may encode the captured, pre-captured, or computer-generated video data. An input image may be received by the video encoder 1020 and stored in the input frame memory 1021. The general purpose processor 1023 may load information from here and perform encoding. The program for driving the general purpose processor may be loaded from a storage device, such as the example memory modules depicted in FIG. 10. The general purpose processor may use processing memory 1022 to perform the encoding, and the output of the encoding

information by the general processor may be stored in a buffer, such as output buffer **1026**.

[0107] The video encoder **1020** may include a resampling module **1025** which may be configured to code (e.g., encode) video data in a scalable video coding scheme that defines at least one base layer and at least one enhancement layer. Resampling module **1025** may resample at least some video data as part of an encoding process, wherein resampling may be performed in an adaptive manner using resampling filters.

[0108] The encoded video data, e.g., a coded bit stream, may be transmitted directly to destination device **1014** via output interface **1028** of source device **1012**. In the example of FIG. **10**, destination device **1014** includes an input interface **1038**, a video decoder **1030**, and a display device **1032**. In some cases, input interface **1028** may include a receiver and/or a modem. Input interface **1038** of destination device **1014** receives encoded video data over channel **1016**. The encoded video data may include a variety of syntax elements generated by video encoder **1020** that represent the video data. Such syntax elements may be included with the encoded video data transmitted on a communication medium, stored on a storage medium, or stored a file server.

[0109] The encoded video data may also be stored onto a storage medium or a file server for later access by destination device **1014** for decoding and/or playback. For example, the coded bitstream may be temporarily stored in the input buffer **1031**, then loaded in to the general purpose processor **1033**. The program for driving the general purpose processor may be loaded from a storage device or memory. The general purpose processor may use a process memory **1032** to perform the decoding. The video decoder **1030** may also include a resampling module **1035** similar to the resampling module **1025** employed in the video encoder **1020**.

[0110] FIG. **10** depicts the resampling module **1035** separately from the general purpose processor **1033**, but it would be appreciated by one of skill in the art that the resampling function may be performed by a program executed by the general purpose processor, and the processing in the video encoder may be accomplished using one or more processors. The decoded image(s) may be stored in the output frame buffer **1036** and then sent out to the input

[0111] interface **1038**. Display device **1038** may be integrated with or may be external to destination device **1014**. In some examples, destination device **1014** may include an integrated display device and may also be configured to interface with an external display device. In other examples, destination device **1014** may be a display device. In general, display device **1038** displays the decoded video data to a user.

[0112] Video encoder **1020** and video decoder **1030** may operate according to a video compression standard. ITU-T VCEG (Q6/16) and ISO/IEC MPEG (JTC 1/SC 29/WG 11) are studying the potential need for standardization of future video coding technology with a compression capability that significantly exceeds that of the current High Efficiency Video Coding HEVC standard (including its current extensions and near-term extensions for screen content coding and high-dynamic-range coding). The groups are working together on this exploration activity in a joint collaboration effort known as the Joint Video Exploration Team (JVET) to evaluate compression technology designs proposed by their experts in this area. A recent capture of JVET development is described in the “Algorithm Description of Joint Exploration Test Model 5 (JEM 5)”, JVET-E1001-V2, authored by J. Chen, E. Alshina, G. Sullivan, J. Ohm, J. Boyce.

[0113] Additionally or alternatively, video encoder **1020** and video decoder **1030** may operate according to other proprietary or industry standards that function with the disclosed JVET features. Thus, other standards such as the ITU-T H.264 standard, alternatively referred to as MPEG-4, Part 10, Advanced Video Coding (AVC), or extensions of such standards. Thus, while newly developed for JVET, techniques of this disclosure are not limited to any particular coding standard or technique. Other examples of video compression standards and techniques include MPEG-2, ITU-T H.263 and proprietary or open source compression formats and related formats.

[0114] Video encoder **1020** and video decoder **1030** may be implemented in hardware, software, firmware or any combination thereof. For example, the video encoder **1020** and decoder **1030** may

employ one or more processors, digital signal processors (DSPs), application specific integrated circuits (ASICs), field programmable gate arrays (FPGAs), discrete logic, or any combinations thereof. When the video encoder **1020** and decoder **1030** are implemented partially in software, a device may store instructions for the software in a suitable, non-transitory computer-readable storage medium and may execute the instructions in hardware using one or more processors to perform the techniques of this disclosure. Each of video encoder **1020** and video decoder **1030** may be included in one or more encoders or decoders, either of which may be integrated as part of a combined encoder/decoder (CODEC) in a respective device.

[0115] Aspects of the subject matter described herein may be described in the general context of computer-executable instructions, such as program modules, being executed by a computer, such as the general-purpose processors **1023** and **1033** described above. Generally, program modules include routines, programs, objects, components, data structures, and so forth, which perform particular tasks or implement particular abstract data types. Aspects of the subject matter described herein may also be practiced in distributed computing environments where tasks are performed by remote processing devices that are linked through a communications network. In a distributed computing environment, program modules may be located in both local and remote computer storage media including memory storage devices.

[0116] Examples of memory include random access memory (RAM), read only memory (ROM), or both. Memory may store instructions, such as source code or binary code, for performing the techniques described above. Memory may also be used for storing variables or other intermediate information during execution of instructions to be executed by a processor, such as processor **1023** and **1033**.

[0117] A storage device may also store instructions, instructions, such as source code or binary code, for performing the techniques described above. A storage device may additionally store data used and manipulated by the computer processor. For example, a storage device in a video encoder **1020** or a video decoder **1030** may be a database that is accessed by computer system **1023** or **1033**. Other examples of storage device include random access memory (RAM), read only memory (ROM), a hard drive, a magnetic disk, an optical disk, a CD-ROM, a DVD, a flash memory, a USB memory card, or any other medium from which a computer can read.

[0118] A memory or storage device may be an example of a non-transitory computer-readable storage medium for use by or in connection with the video encoder and/or decoder. The non-transitory computer-readable storage medium contains instructions for controlling a computer system to be configured to perform functions described by particular embodiments. The instructions, when executed by one or more computer processors, may be configured to perform that which is described in particular embodiments.

[0119] Also, it is noted that some embodiments have been described as a process which can be depicted as a flow diagram or block diagram. Although each may describe the operations as a sequential process, many of the operations can be performed in parallel or concurrently. In addition, the order of the operations may be rearranged. A process may have additional steps not included in the figures.

[0120] Particular embodiments may be implemented in a non-transitory computer-readable storage medium for use by or in connection with the instruction execution system, apparatus, system, or machine. The computer-readable storage medium contains instructions for controlling a computer system to perform a method described by particular embodiments. The computer system may include one or more computing devices. The instructions, when executed by one or more computer processors, may be configured to perform that which is described in particular embodiments.

[0121] As used in the description herein and throughout the claims that follow, “a”, “an”, and “the” includes plural references unless the context clearly dictates otherwise. Also, as used in the description herein and throughout the claims that follow, the meaning of “in” includes “in” and “on” unless the context clearly dictates otherwise.

[0122] Although exemplary embodiments of the invention have been described in detail and in language specific to structural features and/or methodological acts above, it is to be understood that those skilled in the art will readily appreciate that many additional modifications are possible in the exemplary embodiments without materially departing from the novel teachings and advantages of the invention. Moreover, it is to be understood that the subject matter defined in the appended claims is not necessarily limited to the specific features or acts described above. Accordingly, these and all such modifications are intended to be included within the scope of this invention construed in breadth and scope in accordance with the appended claims.

Claims

1-12. (canceled)

13. A method of decoding a video with a decoder that includes a processor included in a bitstream comprising: (a) receiving a rectangular coding unit of a coding tree unit of samples included in a bi-predictive B-slice of a current frame of said video; (b) receiving a first motion vector associated with said coding unit of said bi-predictive B-slice of said current frame of said video referencing a temporally previous reference slice of a temporally previous reference frame relative to said current frame of said coding unit; (c) receiving a second motion vector associated with said coding unit of said bi-predictive B-slice of said current frame of said video referencing a temporally future reference slice of a temporally future reference frame relative to said current frame of said coding unit; (d) applying an optical flow between said temporally previous reference slice and said temporally future reference slice to perform a sample based motion modification using a corrective motion vector applied to predicted arrays based upon at least one of said first motion vector and said second motion vector; and (e) decoding said coding unit based upon said sample based motion modification as a result of said applying said optical flow between said temporally previous reference slice and said temporally future reference slice.

14. The method of decoding of claim 13 wherein said modifying comprises information sufficient to reconstruct an MVP index and an MVD of said second motion vector.

15. The method of decoding of claim 13 wherein said modifying comprises a scaling factor.

16. The method of decoding of claim 13 wherein said modifying comprises said second motion vector is a mirror image of said first motion vector.

17. The method of decoding of claim 13 wherein said coding unit is greater than a predefined size.

18. The method of decoding of claim 13 wherein said second motion vector is partially derived based upon said first motion vector.

19. The method of decoding of claim 13 wherein said second motion vector is fully derived based upon said first motion vector.

20. The method of decoding of claim 13 wherein said second motion vector is a scaled version of said first motion vector.

21. The method of decoding of claim 13 wherein said first motion vector is stored in a reference list.

22. The method of decoding of claim 21 wherein said second motion vector is stored in a reference list.

23. A bitstream of compressed video for decoding by a decoder that includes a processor, including a non-transitory computer readable storage medium storing the compressed video, the method comprising: (a) said bitstream containing data indicating a rectangular coding unit of a coding tree unit of samples included in a bi-predictive B-slice of a current frame of said video; (b) said bitstream containing data indicating a first motion vector associated with said coding unit of said bi-predictive B-slice of said current frame of said video referencing a temporally previous reference slice of a temporally previous reference frame relative to said current frame of said coding unit; (c) said bitstream containing data indicating a second motion vector associated with

said coding unit of said bi-predictive B-slice of said current frame of said video referencing a temporally future reference slice of a temporally future reference frame relative to said current frame of said coding unit; (d) said bitstream containing data indicating an optical flow between said temporally previous reference slice and said temporally future reference slice to perform a sample based motion modification using a corrective motion vector applied to predicted arrays based upon at least one of said first motion vector and said second motion vector; and (e) said bitstream containing data indicating said coding unit based upon said sample based motion modification as a result of said applying said optical flow between said temporally previous reference slice and said temporally future reference slice.

24. A method of encoding a video included in a bitstream by an encoder that includes a processor comprising: (a) providing an encoded bitstream including a rectangular coding unit of a coding tree unit of samples included in a bi-predictive B-slice of a current frame of said video; (b) providing an encoded bitstream including a first motion vector associated with said coding unit of said bi-predictive B-slice of said current frame of said video referencing a temporally previous reference slice of a temporally previous reference frame relative to said current frame of said coding unit; (c) providing an encoded bitstream including a second motion vector associated with said coding unit of said bi-predictive B-slice of said current frame of said video referencing a temporally future reference slice of a temporally future reference frame relative to said current frame of said coding unit; (d) providing an encoded bitstream including an optical flow between said temporally previous reference slice and said temporally future reference slice to perform a sample based motion modification using a corrective motion vector applied to predicted arrays based upon at least one of said first motion vector and said second motion vector; and (e) providing an encoded bitstream including said coding unit based upon said sample based motion modification as a result of said applying said optical flow between said temporally previous reference slice and said temporally future reference slice.
