

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent	12392280
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Pixton; Stephen G. et al.

---

### Gas turbine engine with high low spool power extraction ratio

---

#### Abstract

A gear reduction drives a fan rotor at a speed slower than a fan drive turbine. The turbine section further includes a high pressure turbine driving a high pressure compressor. The fan drive turbine and low pressure compressor are connected by a shaft and the low pressure turbine. The shaft and the low pressure compressor define a low pressure spool, the low pressure spool has a torque at maximum takeoff defined in ft-lbs and also having a low pressure spool power defined in horsepower and at maximum takeoff, and a ratio of the low pressure spool torque to the low pressure spool power being defined, with the low pressure spool power being defined in horsepower, and the ratio of the low pressure spool torque to the low pressure spool power being greater than or equal to 0.6 ft-lb/hp and less than or equal to 1.2 ft-lb/hp.

---

**Inventors:** Pixton; Stephen G. (South Windsor, CT), Hasel; Karl L (Manchester, CT)

**Applicant:** Raytheon Technologies Corporation (Farmington, CT)

**Family ID:** 1000008765665

**Assignee:** RTX Corporation (Farmington, CT)

**Appl. No.:** 17/379244

**Filed:** July 19, 2021

#### Prior Publication Data

<b>Document Identifier</b>	<b>Publication Date</b>
US 20230029308 A1	Jan. 26, 2023

---

#### Publication Classification

**Int. Cl.:** F02C3/06 (20060101); F02C7/36 (20060101)

**U.S. Cl.:**

CPC      **F02C3/06** (20130101); **F02C7/36** (20130101); F05D2220/32 (20130101);  
F05D2260/4031 (20130101)

## Field of Classification Search

**CPC:**      F02C (3/06); F02C (7/36); F05D (2220/32); F05D (2260/4031); F05D (2260/40311)

---

## References Cited

### U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2258792	12/1940	New	N/A	N/A
2936655	12/1959	Peterson et al.	N/A	N/A
3021731	12/1961	Stoeckicht	N/A	N/A
3194487	12/1964	Tyler et al.	N/A	N/A
3352178	12/1966	Lindgren et al.	N/A	N/A
3412560	12/1967	Gaubatz	N/A	N/A
3664612	12/1971	Skidmore et al.	N/A	N/A
3747343	12/1972	Rosen	N/A	N/A
3754484	12/1972	Roberts	N/A	N/A
3765623	12/1972	Donelson et al.	N/A	N/A
3820719	12/1973	Clark et al.	N/A	N/A
3843277	12/1973	Ehrich	N/A	N/A
3892358	12/1974	Gisslen	N/A	N/A
3932058	12/1975	Harner et al.	N/A	N/A
3935558	12/1975	Miller et al.	N/A	N/A
3988889	12/1975	Chamay et al.	N/A	N/A
4130872	12/1977	Haloff	N/A	N/A
4220171	12/1979	Ruehr et al.	N/A	N/A
4240250	12/1979	Harris	N/A	N/A
4284174	12/1980	Salvana et al.	N/A	N/A
4289360	12/1980	Zirin	N/A	N/A
4478551	12/1983	Honeycutt, Jr. et al.	N/A	N/A
4649114	12/1986	Miltenburger et al.	N/A	N/A
4696156	12/1986	Burr et al.	N/A	N/A
4722357	12/1987	Wynosky	N/A	N/A
4979362	12/1989	Vershure, Jr.	N/A	N/A
5058617	12/1990	Stockman et al.	N/A	N/A
5102379	12/1991	Pagluica et al.	N/A	N/A
5141400	12/1991	Murphy et al.	N/A	N/A
5317877	12/1993	Stuart	N/A	N/A
5361580	12/1993	Ciokajlo et al.	N/A	N/A
5433674	12/1994	Sheridan et al.	N/A	N/A
5447411	12/1994	Curley et al.	N/A	N/A
5466198	12/1994	McKibbin et al.	N/A	N/A
5524847	12/1995	Brodell et al.	N/A	N/A
5634767	12/1996	Dawson	N/A	N/A
5677060	12/1996	Terentieva et al.	N/A	N/A
5778659	12/1997	Duesler et al.	N/A	N/A

5857836	12/1998	Stickler et al.	N/A	N/A
5915917	12/1998	Eveker et al.	N/A	N/A
5975841	12/1998	Lindemuth et al.	N/A	N/A
5985470	12/1998	Spitsberg et al.	N/A	N/A
6223616	12/2000	Sheridan	N/A	N/A
6315815	12/2000	Spadaccini et al.	N/A	N/A
6318070	12/2000	Rey et al.	N/A	N/A
6387456	12/2001	Eaton, Jr. et al.	N/A	N/A
6517341	12/2002	Brun et al.	N/A	N/A
6607165	12/2002	Manteiga et al.	N/A	N/A
6709492	12/2003	Spadaccini et al.	N/A	N/A
6814541	12/2003	Evans et al.	N/A	N/A
6883303	12/2004	Seda	N/A	N/A
7021042	12/2005	Law	N/A	N/A
7219490	12/2006	Dev	N/A	N/A
7328580	12/2007	Lee et al.	N/A	N/A
7374403	12/2007	Decker et al.	N/A	N/A
7591754	12/2008	Duong et al.	N/A	N/A
7632064	12/2008	Somanath et al.	N/A	N/A
7662059	12/2009	McCune	N/A	N/A
7806651	12/2009	Kennepohl et al.	N/A	N/A
7824305	12/2009	Duong et al.	N/A	N/A
7828682	12/2009	Smook	N/A	N/A
7926260	12/2010	Sheridan et al.	N/A	N/A
7997868	12/2010	Liang	N/A	N/A
8205432	12/2011	Sheridan	N/A	N/A
10641182	12/2019	Bemment	N/A	N/A
10859001	12/2019	Spruce	N/A	N/A
10961918	12/2020	Spruce	N/A	N/A
2004/0238654	12/2003	Hagen	237/12.1	F23C 6/02
2006/0228206	12/2005	Decker et al.	N/A	N/A
2007/0234702	12/2006	Hagen	60/39.01	F01K 23/12
2008/0003096	12/2007	Kohli et al.	N/A	N/A
2008/0116009	12/2007	Sheridan et al.	N/A	N/A
2008/0317588	12/2007	Grabowski et al.	N/A	N/A
2009/0056343	12/2008	Suciu et al.	N/A	N/A
2009/0304518	12/2008	Kodama et al.	N/A	N/A
2009/0314881	12/2008	Suciu et al.	N/A	N/A
2010/0105516	12/2009	Sheridan et al.	N/A	N/A
2010/0148396	12/2009	Xie et al.	N/A	N/A
2010/0212281	12/2009	Sheridan	N/A	N/A
2010/0218483	12/2009	Smith	N/A	N/A
2010/0331139	12/2009	McCune	N/A	N/A
2011/0159797	12/2010	Beltman et al.	N/A	N/A
2011/0293423	12/2010	Bunker et al.	N/A	N/A
2012/0124964	12/2011	Hasel et al.	N/A	N/A
2013/0104522	12/2012	Kupratis	N/A	N/A
2014/0283500	12/2013	Sabnis	N/A	N/A
2015/0121844	12/2014	Kupratis et al.	N/A	N/A
2017/0191548	12/2016	Fisher et al.	N/A	N/A

2017/0335774	12/2016	Moniz et al.	N/A	N/A
2018/0230912	12/2017	Hasel et al.	N/A	N/A
2020/0200093	12/2019	Moore	N/A	F02K 3/06

## FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
0791383	12/1996	EP	N/A
1142850	12/2000	EP	N/A
3546737	12/2018	EP	N/A
1516041	12/1977	GB	N/A
2041090	12/1979	GB	N/A
2426792	12/2005	GB	N/A
2007038674	12/2006	WO	N/A

## OTHER PUBLICATIONS

Sforza, Pasquale; Theory of Aerospace Propulsion, 2012, Todd Green, Second Edition, p. 442 (Year: 2012). cited by examiner

Howe, D.C., and Wynosky, T.A. (1985). Energy efficient engine program advanced turbofan nacelle definition study. NASA-CR-174942. May 1985. pp. 1-60. cited by applicant

Howe, D.C., and Wynosky, T.A. (1985). Energy efficient engine program advanced turbofan nacelle definition study. NASA-CR-174942. May 1985. University of Washington dated Dec. 13, 1990. pp. 1-14. cited by applicant

Huang, H., Sobel, D.R., and Spadaccini, L.J. (2002). Endothermic heat-sink of hydrocarbon fuels for scramjet cooling. AIAA/ASME/SAE/ASEE, Jul. 2002. pp. 1-7. cited by applicant

Hughes, C. (2002). Aerodynamic performance of scale-model turbofan outlet guide vanes designed for low noise. Prepared for the 40th Aerospace Sciences Meeting and Exhibit. Reno, NV. NASA/TM-2001-211352. Jan. 14-17, 2002. pp. 1-38. cited by applicant

Hughes, C. (2010). Geared turbofan technology. NASA Environmentally Responsible Aviation Project. Green Aviation Summit. NASA Ames Research Center. Sep. 8-9, 2010. pp. 1-8. cited by applicant

Ivchenko-Progress AI-727M. Jane's Aero-engines, Aero-engines—Turbofan. Nov. 27, 2011. cited by applicant

Ivchenko-Progress D-436. Jane's Aero-engines, Aero-engines—Turbofan. Feb. 8, 2012. cited by applicant

Ivchenko-Progress D-727. Jane's Aero-engines, Aero-engines—Turbofan. Feb. 7, 2007. cited by applicant

Jacobson, N.S. (1993). Corrosion of silicon-based ceramics in combustion environments. J. Am. Ceram. Soc. 76(1). pp. 3-28. cited by applicant

Jeng, Y.-L., Lavernia, E.J. (1994). Processing of molybdenum disilicide. J. of Mat. Sci. vol. 29. 1994. pp. 2557-2571. cited by applicant

Johnston, R.P. and Hemsworth, M.C. (1978). Energy efficient engine preliminary design and integration studies. Jun. 1, 1978. pp. 1-28. cited by applicant

Johnston, R.P., Hirschkron, R., Koch, C.C., Neitzel, R.E., and Vinson, P.W. (1978). Energy efficient engine: Preliminary design and integration study—final report. NASA CR-135444. Sep. 1978. pp. 1-401. cited by applicant

Jorgensen, P.J., Wadsworth, M.E., and Cutler, I.B. (1961). Effects of water vapor on oxidation of silicon carbide. J. Am. Ceram. Soc. 44(6). pp. 248-261. cited by applicant

Kahn, H., Tayebi, N., Ballarini, R., Mullen, R.L., Heuer, A.H. (2000). Fracture toughness of polysilicon MEMS devices. Sensors and Actuators vol. 82. 2000. pp. 274-280. cited by applicant

Kandebo, S.W. (1998). Geared-Turbofan engine design targets cost, complexity. Aviation Week &

Space Technology, 148(8). p. 34-5. cited by applicant

Kaplan, B., Nicke, E., Voss, C. (2006), Design of a highly efficient low-noise fan for ultra-high bypass engines. Proceedings of GT2006 for ASME Turbo Expo 2006: Power for Land, Sea and Air. Barcelona, SP. May 8-11, 2006. pp. 1-10. cited by applicant

Kasuba, R. and August, R. (1984). Gear mesh stiffness and load sharing in planetary gearing. American Society of Mechanical Engineers, Design Engineering Technical Conference, Cambridge, MA. Oct. 7-10, 1984. pp. 1-6. cited by applicant

Kerrebrock, J.L. (1977). Aircraft engines and gas turbines. Cambridge, MA: The MIT Press. p. 11. cited by applicant

Knip, Jr., G. (1987). Analysis of an advanced technology subsonic turbofan incorporating revolutionary materials. NASA Technical Memorandum. May 1987. pp. 1-23. cited by applicant

Kojima, Y., Usuki, A. Kawasumi, M., Okada, A., Fukushima, Y., Kurauchi, T., and Kamigaito, O. (1992). Mechanical properties of nylon 6-clay hybrid. Journal of Materials Research, 8(5), 1185-1189. cited by applicant

Kollar, L.P. and Springer, G.S. (2003). Mechanics of composite structures. Cambridge, UK: Cambridge University Press. p. 465. cited by applicant

Krantz, T.L. (1990). Experimental and analytical evaluation of efficiency of helicopter planetary stage. NASA Technical Paper. Nov. 1990. pp. 1-19. cited by applicant

Krenkel, W., Naslain, R., and Schneider, H. Eds. (2001). High temperature ceramic matrix composites pp. 224-229. Weinheim, DE: Wiley-VCH Verlag GmbH. cited by applicant

Kurzke, J. (2001). GasTurb 9: A program to calculate design and off-design performance of gas turbines. Retrieved from: <https://www.scribd.com/document/92384867/GasTurb9Manual>. cited by applicant

Kurzke, J. (2012). GasTurb 12: Design and off-design performance of gas turbines. Retrieved from: <https://www.scribd.com/document/153900429/GasTurb-12>. cited by applicant

Kurzke, J. (2008). Preliminary Design, Aero-engine design: From state of the art turbofans towards innovative architectures. pp. 1-72. cited by applicant

Kurzke, J. (2009). Fundamental differences between conventional and geared turbofans. Proceedings of ASME Turbo Expo: Power for Land, Sea, and Air. 2009, Orlando, Florida. pp. 145-153. cited by applicant

Langston, L. and Faghri, A. Heat pipe turbine vane cooling. Prepared for Advanced Turbine Systems Annual Program Review. Morgantown, West Virginia. Oct. 17-19, 1995. pp. 3-9. cited by applicant

Lau, K., Gu, C., and Hui, D. (2005). A critical review on nanotube and nanotube/nanoclay related polymer composite materials. Composites: Part B 37(2006) 425-436. cited by applicant

Leckie, F.A. and Dal Bello, D.J. (2009). Strength and stiffness of engineering systems. Mechanical Engineering Series. Springer. pp. 1-10, 48-51. cited by applicant

Lee, K.N. (2000). Current status of environmental barrier coatings for Si-Based ceramics. Surface and Coatings Technology 133-134, 2000. pp. 1-7. cited by applicant

Levintan, R.M. (1975). Q-Fan demonstrator engine. Journal of Aircraft. vol. 12( 8). Aug. 1975. pp. 658-663. cited by applicant

Lewicki, D.G., Black, J.D., Savage, M., and Coy, J.J. (1985). Fatigue life analysis of a turboprop reduction gearbox. NASA Technical Memorandum. Prepared for the Design Technical Conference (ASME). Sep. 11-13, 1985. pp. 1-26. cited by applicant

Liebeck, R.H., Andrastek, D.A., Chau, J., Girvin, R., Lyon, R., Rawdon, B.K., Scott, P.W. et al. (1995). Advanced subsonic airplane design & economics studies. NASA CR-195443. Apr. 1995. pp. 1-187. cited by applicant

Lord, W.K., Macmartin, D.G., and Tillman, T.G. (2000). Flow control opportunities in gas turbine engines. American Institute of Aeronautics and Astronautics. pp. 1-15. cited by applicant

Lynwander, P. (1983). Gear drive systems: Design and application. New York, New York: Marcel

Dekker, Inc. pp. 145, 355-358. cited by applicant

Macisaac, B. and Langston, R. (2011). Gas turbine propulsion systems. Chichester, West Sussex: John Wiley & Sons, Ltd. pp. 260-5. cited by applicant

Mancuso, J.R. and Corcoran, J.P. (2003). What are the differences in high performance flexible couplings for turbomachinery? Proceedings of the Thirty-Second Turbomachinery Symposium. 2003. pp. 189-207. cited by applicant

Manual. Student's Guide to Learning SolidWorks Software. Dassault Systemes—SolidWorks Corporation. pp. 1-156. cited by applicant

Matsumoto, T., Toshiro, U., Kishida, A., Tsutomu, F., Maruyama, I., and Akashi, M. (1996). Novel functional polymers: Poly (dimethylsiloxane)-polyamide multiblock copolymer. VII. Oxygen permeability of aramid-silicone membranes in a gas-membrane-liquid system. Journal of Applied Polymer Science, vol. 64(6). May 9, 1997. pp. 1153-1159. cited by applicant

Mattingly, J.D. (1996). Elements of gas turbine propulsion. New York, New York: McGraw-Hill, Inc. pp. 1-18, 60-62, 223-234, 462-479, 517-520, 757-767, and 862-864. cited by applicant

Mattingly, J.D. (1996). Elements of gas turbine propulsion. New York, New York: McGraw-Hill, Inc. pp. 1-18, 60-62, 85-87, 95-104, 121-123, 223-234, 242-245, 278-285, 303-309, 323-326, 462-479, 517-520, 563-565, 630-632, 668-670, 673-675, 682-685, 697-705, 726-727, 731-732, 802-805, 828-830 and appendices. cited by applicant

Mattingly, J.D. (1996). Elements of gas turbine propulsion. New York, New York: McGraw-Hill, Inc. pp. 1-18, 60-62, 85-87, 95-104, 121-123, 223-234, 242-245, 278-285, 303-309, 323-326, 462-479, 517-520, 563-565, 630-632, 673-675, 682-685, 697-699, 703-705, 802-805, 862-864, and 923-925. cited by applicant

Mattingly, J.D. (1996). Elements of gas turbine propulsion. New York, New York: McGraw-Hill, Inc. pp. 8-15. cited by applicant

Mcardle, J.G. and Moore, A.S. (1979). Static test-stand performance of the YF-102 turbofan engine with several exhaust configurations for the Quiet Short-Haul Research Aircraft (QSRA). Prepared for NASA. NASA-TP-1556. Nov. 1979. pp. 1-68. cited by applicant

Mccune, M.E. (1993). Initial test results of 40,000 horsepower fan drive gear system for advanced ducted propulsion systems. AIAA 29th Joint Conference and Exhibit. Jun. 28-30, 1993. pp. 1-10. cited by applicant

Mcmillan, A. (2008) Material development for fan blade containment casing. Abstract. p. 1. Conference on Engineering and Physics: Synergy for Success 2006. Journal of Physics: Conference Series vol. 105. London, UK. Oct. 5, 2006. cited by applicant

Merriam-Webster's collegiate dictionary, 10th Ed. (2001). p. 1125-1126. cited by applicant

Merriam-Webster's collegiate dictionary, 11th Ed. (2009). p. 824. cited by applicant

Dudley, D.W., Ed. (1954). Handbook of practical gear design. Lancaster, PA: Technomic Publishing Company, Inc. pp. 3.96-102 and 8.12-18. cited by applicant

Dudley, D.W., Ed. (1962). Gear handbook. New York, NY: McGraw-Hill. pp. 14-17 (TOC, Preface, and Index). cited by applicant

Dudley, D.W., Ed. (1962). Gear handbook. New York, NY: McGraw-Hill. pp. 3.14-18 and 12.7-12.21. cited by applicant

Dudley, D.W., Ed. (1994). Practical gear design. New York, NY: McGraw-Hill. pp. 119-124. cited by applicant

Edkins, D.P., Hirschcron, R., and Lee, R. (1972). TF34 turbofan quiet engine study. Final Report prepared for NASA. NASA-CR-120914. Jan. 1, 1972. pp. 1-99. cited by applicant

Edwards, T. and Zabarnick, S. (1993). Supercritical fuel deposition mechanisms. Ind. Eng. Chem. Res. vol. 32. 1993. pp. 3117-22. cited by applicant

El-Sayad, A.F. (2008). Aircraft propulsion and gas turbine engines. Boca Raton, FL: CRC Press. pp. 215-9 and 855-60 . cited by applicant

Faghri, A. (1995). Heat pipe and science technology. Washington, D.C.: Taylor & Francis. pp. 1-60.

cited by applicant

Falchetti, F., Quiniou, H., and Verdier, L. (1994). Aerodynamic design and 3D Navier-Stokes analysis of a high specific flow fan. ASME. Presented at the International Gas Turbine and Aeroengine Congress and Exposition. The Hague, Netherlands. Jun. 13-16, 1994. pp. 1-10. cited by applicant

File History for U.S. Appl. No. 12/131,876. cited by applicant

Fledderjohn, K.R. (1983). The TFE731-5: Evolution of a decade of business jet service. SAE Technical Paper Series. Business Aircraft Meeting & Exposition. Wichita, Kansas. Apr. 12-15, 1983. pp. 1-12. cited by applicant

Frankenfeld, J.W. and Taylor, W.F. (1980). Deposit formation from deoxygenated hydrocarbons. 4. Studies in pure compound systems. Ind. Eng. Chem., Prod. Res. Dev., vol. 19(1). 1978. pp. 65-70. cited by applicant

Garret TFE731 Turbofan Engine (CAT C). Chapter 79: Lubrication System. TTFE731 Issue 2. 2010. pp. 1-24. cited by applicant

Gates, D. Bombardier flies at higher market. Seattle Times. Jul. 13, 2008. pp. C6. cited by applicant

Gibala, R., Ghosh, A.K., Van Aken, D.C., Srolovitz, D.J., Basu, A., Chang, H., . . . Yang, W. (1992). Mechanical behavior and interface design of MoSi<sub>2</sub>-based alloys and composites. Materials Science and Engineering, A155, 1992. pp. 147-158. cited by applicant

Gliebe, P.R. and Janardan, B.A. (2003). Ultra-high bypass engine aeroacoustic study. NASA/CR-2003-21252. GE Aircraft Engines, Cincinnati, Ohio. Oct. 2003. pp. 1-103. cited by applicant

Gliebe, P.R., Ho, P.Y., and Mani, R. (1995). UHB engine fan and broadband noise reduction study. NASA CR-198357. Jun. 1995. pp. 1-48. cited by applicant

Grady, J.E., Weir, D.S., Lamoureux, M.C., and Martinez, M.M. (2007). Engine noise research in NASA's quiet aircraft technology project. Papers from the International Symposium on Air Breathing Engines (ISABE). 2007. cited by applicant

Gray, D.E. (1978). Energy efficient engine preliminary design and integration studies. Prepared for NASA. NASA CR-135396. Nov. 1978. pp. 1-366. cited by applicant

Gray, D.E. and Gardner, W.B. (1983). Energy efficient engine program technology benefit/cost study—vol. 2. NASA CR-174766. Oct. 1983. pp. 1-118. cited by applicant

Griffiths, B. (2005). Composite fan blade containment case. Modern Machine Shop. Retrieved from: <http://www.mmsonline.com/articles/composite-fan-blade-containment-case> pp. 1-4. cited by applicant

Growneweg, J.F. (1994). Fan noise research at NASA. NASA-TM-106512. Prepared for the 1994 National Conference on Noise Control Engineering. Fort Lauderdale, FL. May 1-4, 1994. pp. 1-10. cited by applicant

Growneweg, J.F. (1994). Fan noise research at NASA. Noise-CON 94. Fort Lauderdale, FL. May 1-4, 1994. pp. 1-10. cited by applicant

Gunston, B. (Ed.) (2000). Jane's aero-engines, Issue seven. Coulsdon, Surrey, UK: Jane's Information Group Limited. pp. 510-512. cited by applicant

Guynn, M. D., Berton, J.J., Fisher, K. L., Haller, W.J., Tong, M. T., and Thurman, D.R. (2011). Refined exploration of turbofan design options for an advanced single-aisle transport. NASA/TM-2011-216883. pp. 1-27. cited by applicant

Haldenbrand, R. and Norgren, W.M. (1979). Airsearch QCGAT program [quiet clean general aviation turbofan engines]. NASA-CR-159758. pp. 1-199. cited by applicant

Hall, C.A. and Crichton, D. (2007). Engine design studies for a silent aircraft. Journal of Turbomachinery, 129, 479-487. cited by applicant

Han, J., Dutta, S., and Ekkad, S.V. (2000). Gas turbine heat transfer and cooling technology. New York, NY: Taylor & Francis. pp. 1-25, 129-157, and 160-249. cited by applicant

Haque, A. and Shamsuzzoha, M., Hussain, F., and Dean, D. (2003). S20-glass/epoxy polymer nanocomposites: Manufacturing, structures, thermal and mechanical properties. Journal of

Composite Materials, 37 (20), 1821-1837. cited by applicant

Hazlett, R.N. (1991). Thermal oxidation stability of aviation turbine fuels. Philadelphia, PA: ASTM. pp. 1-163. cited by applicant

Heidelberg, L.J., and Hall, D.G. (1992). Acoustic mode measurements in the inlet of a model turbofan using a continuously rotating rake. AIAA-93-0598. 31st Aerospace Sciences Meeting. Reno, NV. Jan. 11-14, 1993. pp. 1-30. cited by applicant

Heidelberg, L.J., and Hall, D.G. (1992). Acoustic mode measurements in the inlet of a model turbofan using a continuously rotating rake. NASA-TM-105989. Prepared for the 31st Aerospace Sciences Meeting. Reno, NV. Jan. 11-14, 1993. pp. 1-30. cited by applicant

Heingartner, P., Mba, D., Brown, D. (2003). Determining power losses in the helical gear mesh; Case Study. ASME 2003 Design Engineering Technical Conferences. Chicago, IL. Sep. 2-6, 2003. pp. 1-7. cited by applicant

Hemighaus, G., Boval, T., Bacha, J., Barnes, F., Franklin, M., Gibbs, L., . . . Morris, J. (2007). Aviation fuels: Technical review. Chevron Products Company. pp. 1-94. Retrieved from: [https://www.cgabusinessdesk.com/document/aviation\\_tech\\_review.pdf](https://www.cgabusinessdesk.com/document/aviation_tech_review.pdf). cited by applicant

Hendricks, E.S. and Tong, M.T. (2012). Performance and weight estimates for an advanced open rotor engine. NASA/TM-2012-217710. pp. 1-13. cited by applicant

Hess, C. (1998). Pratt & Whitney develops geared turbofan. Flug Revue 43(7). Oct. 1998. cited by applicant

Hill, P.G., Peterson, C.R. (1965). Mechanics and thermodynamics of propulsion. Addison-Wesley Publishing Company, Inc. pp. 307-8. cited by applicant

Hill, P.G., Peterson, C.R. (1992). Mechanics and thermodynamics of propulsion, 2nd Edition. Addison-Wesley Publishing Company, Inc. pp. 400-6. cited by applicant

Holcombe, V. (2003). Aero-Propulsion Technology (APT) task V low noise ADP engine definition study. NASA CR-2003-212521. Oct. 1, 2003. pp. 1-73. cited by applicant

Honeywell Learjet 31 and 35/36 TFE731-2 to 2C Engine Upgrade Program. Sep. 2005. pp. 1-4. cited by applicant

Honeywell LF502. Jane's Aero-engines, Aero-engines—Turbofan. Feb. 9, 2012. cited by applicant

Honeywell LF502. Jane's Aero-engines, Aero-engines—Turbofan. Aug. 17, 2016. cited by applicant

Honeywell LF507. Jane's Aero-engines, Aero-engines—Turbofan. Feb. 9, 2012. cited by applicant

Honeywell Sabreliner 65 TFE731-3 to -3D Engine Upgrade Program. Oct. 2005. pp. 1-4. cited by applicant

Honeywell TFE731. Jane's Aero-engines, Aero-engines—Turbofan. Jul. 18, 2012. cited by applicant

Honeywell TFE731 Pilot Tips. pp. 1-143. cited by applicant

Honeywell TFE731-5AR to -5BR Engine Conversion Program. Sep. 2005. pp. 1-4. cited by applicant

Horikoshi, S. and Serpone, N. (2013). Introduction to nanoparticles. Microwaves in nanoparticle synthesis. Wiley-VCH Verlag GmbH & Co. KGaA. pp. 1-24. cited by applicant

Howe, D.C. and Marchant R.D. (1988). Energy Efficient Engine. High-Pressure Compressor Test Hardware Detailed Design Report. NASA CR-180850. Mar. 1988. pp. 1-295. cited by applicant

Howe, D.C. and Wynosky, T.A. (1985). Energy efficient engine program advanced turbofan nacelle definition study. NASA CR-174942. May 1, 1985. pp. 174. cited by applicant

About GasTurb. Retrieved Jun. 26, 2018 from: <http://gasturb.de/about-gasturb.html>. cited by applicant

Adamson, A.P. (1975). Quiet Clean Short-Haul Experimental Engine (QCSEE) design rationale. Society of Automotive Engineers. Air Transportation Meeting. Hartford, CT. May 6-8, 1975. pp. 1-9. cited by applicant

Aerospace Information Report. (2008). Advanced ducted propulsor in-flight thrust determination.



SAE International AIR5450. Aug. 2008. p. 1-392. cited by applicant

Agarwal, B.D and Broutman, L.J. (1990). Analysis and performance of fiber composites, 2nd Edition. John Wiley & Sons, Inc. New York: New York. pp. 1-30, 50-1, 56-8, 60-1, 64-71, 87-9, 324-9, 436-7. cited by applicant

AGMA Standard (1997). Design and selection of components for enclosed gear drives. Alexandria, VA: American Gear Manufacturers Association. pp. 1-48. cited by applicant

AGMA Standard (1999). Flexible couplings—Mass elastic properties and other characteristics. Alexandria, VA: American Gear Manufacturers Association. pp. 1-46. cited by applicant

AGMA Standard (2006). Design manual for enclosed epicyclic gear drives. Alexandria, VA: American Gear Manufacturers Association. pp. 1-104. cited by applicant

Ahmad, F. and Mizramoghadam, A.V. (1999). Single v. two stage high pressure turbine design of modern aero engines. ASME. Prestand at the International Gas Turbine & Aeroengine Congress & Exhibition. Indianapolis, Indiana. Jun. 7-10, 1999. pp. 1-9. cited by applicant

Amezket, M., Iriarte, X., Ros, J., and Pintor, J. (2009). Dynamic model of a helical gear pair with backlash and angle-varying mesh stiffness. Multibody Dynamics 2009, ECCOMAS Thematic Conference. 2009. pp. 1-36. cited by applicant

Anderson, N.E., Loewenthal, S.H., and Black, J.D. (1984). An analytical method to predict efficiency of aircraft gearboxes. NASA Technical Memorandum prepared for the Twentieth Joint Propulsion Conference. Cincinnati, OH. Jun. 11-13, 1984. pp. 1-25. cited by applicant

Anderson, R.D. (1985). Advanced Propfan Engine Technology (APET) definition study, single and counter-rotation gearbox/pitch change mechanism design. NASA CR-168115. Jul. 1, 1985. pp. 1-289. cited by applicant

Avco Lycoming Division. ALF 502L Maintenance Manual. Apr. 1981. pp. 1-118. cited by applicant

Aviadvigatel D-110. Jane's Aero-engines, Aero-engines—Turboprop. Jun. 1, 2010. cited by applicant

Awker, R.W. (1986). Evaluation of propfan propulsion applied to general aviation. NASA CR-175020. Mar. 1, 1986. pp. 1-140. cited by applicant

Baker, R.W. (2000). Membrane technology and applications. New York, NY: McGraw-Hill. pp. 87-153. cited by applicant

Bessarabov, D.G., Jacobs, E.P., Sanderson, R.D., and Beckman, I.N. (1996). Use of nonporous polymeric flat-sheet gas-separation membranes in a membrane-liquid contactor: experimental studies. Journal of Membrane Sciences, vol. 113. 1996. pp. 275-84. cited by applicant

Bornstein, N. (1993). Oxidation of advanced intermetallic compounds. Journal de Physique IV, 1993, 03 (C9), pp. C9-367-C9-373. cited by applicant

Brennan, P.J. and Krolczek, E.J. (1979). Heat pipe design handbook. Prepared for National Aeronautics and Space Administration by B & K Engineering, Inc. Jun. 1979. pp. 1-348. cited by applicant

Brines, G.L. (1990). The turboprop of tomorrow. Mechanical Engineering: The Journal of the American Society of Mechanical Engineers, 108(8), 65-67. cited by applicant

Bucknell, R.L. (1973). Influence of fuels and lubricants on turbine engine design and performance, fuel and lubricant analyses. Final Technical Report, Mar. 1971-Mar. 1973. pp. 1-252. cited by applicant

Bunker, R.S. (2005). A review of shaped hole turbine film-cooling technology. Journal of Heat Transfer vol. 127. Apr. 2005. pp. 441-453. cited by applicant

Carney, K., Pereira, M., Revilock, and Matheny, P. (2003). Jet engine fan blade containment using two alternate geometries. 4th European LS-DYNA Users Conference. pp. 1-10. cited by applicant

Cheryan, M. (1998). Ultrafiltration and microfiltration handbook. Lancaster, PA: Technomic Publishing Company, Inc. pp. 171-236. cited by applicant

Ciepluch, C. (1977). Quiet clean short-haul experimental engine (QCSEE) under-the-wing (UTW) final design report. Prepared for NASA. NASA-CP-134847. Retrieved from: <https://ntrs.nasa.gov/archive/nasa/casi.ntrs.nasa.gov/19800075257.pdf>. cited by applicant

Clarke, D.R. and Levi, C.G. (2003). Materials design for the next generation thermal barrier coatings. Annual. Rev. Mater. Res. vol. 33. 2003. pp. 383-417. cited by applicant

Cramoisi, G. Ed. (2012). Death in the Potomac: The crash of Air Florida Flight 90. Air Crash Investigations. Accident Report NTSB/AAR-82-8. p. 45-47. cited by applicant

Cusick, M. (1981). Avco Lycoming's ALF 502 high bypass fan engine. Society of Automotive Engineers, Inc. Business Aircraft Meeting & Exposition. Wichita, Kansas. Apr. 7-10, 1981. pp. 1-9. cited by applicant

Daggett, D.L., Brown, S.T., and Kawai, R.T. (2003). Ultra-efficient engine diameter study. NASA/CR-2003-212309. May 2003. pp. 1-52. cited by applicant

Daly, M. Ed. (2008). Jane's Aero-Engine. Issue Twenty-three. Mar. 2008. p. 707-12. cited by applicant

Daly, M. Ed. (2010). Jane's Aero-Engine. Issue Twenty-seven. Mar. 2010. p. 633-636. cited by applicant

Damerau, J. (2014) What is the mesh stiffness of gears? Screen shot of query submitted by Vahid Dabbagh, answered by Dr. Jochan Damerau, Research General Manager at Bosch Corp., Japan. Retrieved from: [https://www.researchgate.net/post/What\\_is\\_the\\_mesh\\_stiffness\\_of\\_gears](https://www.researchgate.net/post/What_is_the_mesh_stiffness_of_gears). cited by applicant

Darrah, S. (1987). Jet fuel deoxygenation. Interim Report for Period Mar. 1987-Jul. 1988. pp. 1-22. cited by applicant

Dassault Falcon 900EX Easy Systems Summary. Retrieved from: <http://www.smartcockpit.com/docs/F900EX-Engines.pdf> pp. 1-31. cited by applicant

Datasheet. CF6-80C2 high-bypass turbofan engines. Retrieved from <https://geaviation.com/sites/default/files/datasheet-CF6-80C2.pdf>. cited by applicant

Datasheet. CFM56-5B For the Airbus A320ceo family and CFM56-7B for the Boeing 737 family. <https://www.cfmaeroengines.com/>. cited by applicant

Datasheet. Genx™ high bypass turbofan engines. Retrieved from: <https://www.geaviation.com/sites/default/files/datasheet-genx.pdf>. cited by applicant

Davies, D. and Miller, D.C. (1971). A variable pitch fan for an ultra quiet demonstrator engine. 1976 Spring Convention: Seeds for Success in Civil Aircraft Design in the Next Two Decades. pp. 1-18. cited by applicant

Davis, D.G.M. (1973). Variable-pitch fans: Progress in Britain. Flight International. Apr. 19, 1973. pp. 615-7. cited by applicant

Decker, S. and Clough, R. (2016). GE wins shot at voiding pratt patent in jet-engine clash. Bloomberg Technology. Retrieved from: <https://www.bloomberg.com/news/articles/2016-06-30/ge-wins-shot-to-invalidate-pratt-airplane-engine-patent-in-u-s>. cited by applicant

Declaration of Dr. Magdy Attia, In re U.S. Pat. No. 8,313,280, Executed Oct. 21, 2016, pp. 1-88. cited by applicant

Declaration of Dr. Magdy Attia, In re U.S. Pat. No. 8,517,668, Executed Dec. 8, 2016, pp. 1-81. cited by applicant

Declaration of John Eaton, Ph.D. In re U.S. Pat. No. 8,869,568, Executed Mar. 28, 2016, pp. 1-87. cited by applicant

Declaration of Reza Abhari, In re U.S. Pat. No. 8,448,895, Executed Nov. 28, 2016, pp. 1-81. cited by applicant

Declaration of Reza Abhari. In re U.S. Pat. No. 8,695,920, claims 1-4, 7-14, 17 and 19, Executed Nov. 29, 2016, pp. 1-102. cited by applicant

Declaration of Reza Abhari. In re U.S. Pat. No. 8,695,920. Executed Nov. 30, 2016, pp. 1-67. cited by applicant

Declaration of Reza Abhari, Ph.D. In re U.S. Pat. No. 8,844,265, Executed Jun. 28, 2016, pp. 1-91. cited by applicant

Defeo, A. and Kulina, M. (1977). Quiet clean short-haul experimental engine (QCSEE) main

reduction gears detailed design final report. Prepared for NASA. NASA-CR-134872. Jul. 1977. pp. 1-221. cited by applicant

Dickey, T.A. and Dobak, E.R. (1972). The evolution and development status of ALF 502 turbofan engine. National Aerospace Engineering and Manufacturing Meeting. San Diego, California. Oct. 2-5, 1972. pp. 1-12. cited by applicant

Drago, R.J. (1974). Heavy-lift helicopter brings up drive ideas. Power Transmission Design. Mar. 1987. pp. 1-15. cited by applicant

Drago, R.J. and Margasahayam, R.N. (1987). Stress analysis of planet gears with integral bearings; 3D finite-element model development and test validation. 1987 MSC Nastran World Users Conference. Los Angeles, CA. Mar. 1987. pp. 1-14. cited by applicant

Tummers, B. (2006). DataThief III. Retrieved from: <https://datathief.org/DatathiefManual.pdf> pp. 1-52. cited by applicant

Turbomeca Aubisque. Jane's Aero-engines, Aero-engines—Turbofan. Nov. 2, 2009. cited by applicant

Turner, M. G., Norris, A., and Veres, J.P. (2004). High-fidelity three-dimensional simulation of the GE90. NASA/TM-2004-212981. pp. 1-18. cited by applicant

Type Certificate Data Sheet No. E6NE. Department of Transportation Federal Aviation Administration. Jun. 7, 2002. pp. 1-10. cited by applicant

U.S. Department of Transportation: Federal Aviation Administration Advisory Circular, Runway overrun prevention, dated: Nov. 6, 2007, p. 1-8 and Appendix 1 pp. 1-15, Appendix 2 pp. 1-6, Appendix 3 pp. 1-3, and Appendix 4 pp. 1-5. cited by applicant

U.S. Department of Transportation: Federal Aviation Administration Advisory Circular. Standard operating procedures for flight deck crewmembers, Dated: Feb. 27, 2003, p. 1-6 and Appendices. cited by applicant

U.S. Department of Transportation: Federal Aviation Administration Type Certificate Data Sheet No. E6WE. Dated: May 9, 2000. p. 1-9. cited by applicant

Vasudevan, A.K. and Petrovic, J.J. (1992). A comparative overview of molybdenum disilicide composites. Materials Science and Engineering, A155, 1992. pp. 1-17. cited by applicant

Waters, M.H. and Schairer, E.T. (1977). Analysis of turbofan propulsion system weight and dimensions. NASA Technical Memorandum. Jan. 1977. pp. 1-65. cited by applicant

Webster, J.D., Westwood, M.E., Hayes, F.H., Day, R.J., Taylor, R., Duran, A., . . . Vogel, W.D. (1998). Oxidation protection coatings for C/SiC based on yttrium silicate. Journal of European Ceramic Society vol. 18. 1998. pp. 2345-2350. cited by applicant

Wendus, B.E., Stark, D.F., Holler, R.P., and Funkhouse, M.E. (2003). Follow-on technology requirement study for advanced subsonic transport. Technical Report prepared for NASA. NASA/CR-2003-212467. Aug. 1, 2003. pp. 1-47. cited by applicant

Whitaker, R. (1982). ALF 502: plugging the turbofan gap. Flight International, p. 237-241, Jan. 30, 1982. cited by applicant

Wie, Y.S., Collier, F.S., Wagner, R.D., Viken, J.K., and Pfenniger, W. (1992). Design of a hybrid laminar flow control engine nacelle. AIAA-92-0400. 30th Aerospace Sciences Meeting & Exhibit. Jan. 6-9, 1992. pp. 1-14. cited by applicant

Wikipedia. Stiffness. Retrieved Jun. 28, 2018 from: <https://en.wikipedia.org/wiki/Stiffness>. cited by applicant

Wikipedia. Torsion spring. Retrieved Jun. 29, 2018 from: [https://en.wikipedia.org/wiki/Torsion\\_spring](https://en.wikipedia.org/wiki/Torsion_spring). cited by applicant

Wilfert, G. (2008). Geared fan. Aero-Engine Design: From State of the Art Turbofans Towards Innovative Architectures, von Karman Institute for Fluid Dynamics, Belgium, Mar. 3-7, 2008. pp. 1-26. cited by applicant

Willis, W.S. (1979). Quiet clean short-haul experimental engine (QCSEE) final report. NASA/CR-159473 pp. 1-289. cited by applicant

Winn, A. (Ed). (1990). Wide Chord Fan Club. Flight International, 4217(137). May 23-29, 1990. pp. 34-38. cited by applicant

Wright, G.H. and Russell, J.G. (1990). The M.45SD-02 variable pitch geared fan engine demonstrator test and evaluation experience. Aeronautical Journal., vol. 84(836). Sep. 1980. pp. 268-277. cited by applicant

Xie, M. (2008). Intelligent engine systems: Smart case system. NASA/CR-2008-215233. pp. 1-31. cited by applicant

Xu, Y., Cheng, L., Zhang, L., Ying, H., and Zhou, W. (1999). Oxidation behavior and mechanical properties of C/SiC composites with Si-MoSi<sub>2</sub> oxidation protection coating. J. of Mat. Sci. vol. 34. 1999. pp. 6009-6014. cited by applicant

Zalud, T. (1998). Gears put a new spin on turbofan performance. Machine Design, 70(20), p. 104. cited by applicant

Zamboni, G. and Xu, L. (2009). Fan root aerodynamics for large bypass gas turbine engines: Influence on the engine performance and 3D design. Proceedings of ASME Turbo Expo 2009: Power for Land, Sea and Air. Jun. 8-12, 2009, Orlando, Florida, USA. pp. 1-12. cited by applicant

Zhao, J.C. and Westbrook, J.H. (2003). Ultrahigh-temperature materials for jet engines. MRS Bulletin. vol. 28(9). Sep. 2003. pp. 622-630. cited by applicant

Meyer, A.G. (1988). Transmission development of TEXTRON Lycoming's geared fan engine. Technical Paper. Oct. 1988. pp. 1-12. cited by applicant

Middleton, P. (1971). 614: VFW's jet feederliner. Flight International, Nov. 4, 1971. p. 725, 729-732. cited by applicant

Moxon, J. How to save fuel in tomorrow's engines. Flight International. Jul. 30, 1983. 3873(124). pp. 272-273. cited by applicant

Muhlstein, C.L., Stach, E.A., and Ritchie, R.O. (2002). A reaction-layer mechanism for the delayed failure of micron-scale polycrystalline silicon structural films subjected to high-cycle fatigue loading. Acta Materialia vol. 50. 2002. pp. 3579-3595. cited by applicant

Munt, R. (1981). Aircraft technology assessment: Progress in low emissions engine. Technical Report. May 1981. pp. 1-171. cited by applicant

Nanacor Technical Data for Epoxy Nanocomposites using Nanomer 1.30E Nanoclay. Nnacor, Inc. Oct. 2004. cited by applicant

NASA Conference Publication. (1978). CTOL transport technology. NASA-CP-2036-PT-1. Jun. 1, 1978. pp. 1-531. cited by applicant

NASA Conference Publication. Quiet, powered-lift propulsion. Cleveland, Ohio. Nov. 14-15, 1978. pp. 1-420. cited by applicant

Newton, F.C., Liebeck, R.H., Mitchell, G.H., Mooiweer, M.A., Platte, M.M., Toogood, T.L., and Wright, R.A. (1986). Multiple Application Propfan Study (MAPS): Advanced tactical transport. NASA CR-175003. Mar. 1, 1986. pp. 1-101. cited by applicant

Norton, M. and Karczub, D. (2003). Fundamentals of noise and vibration analysis for engineers. Press Syndicate of the University of Cambridge. New York: New York. p. 524. cited by applicant

Oates, G.C. (Ed). (1989). Aircraft propulsion systems and technology and design. Washington, D.C.: American Institute of Aeronautics, Inc. pp. 341-344. cited by applicant

Parker, R.G. and Lin, J. (2001). Modeling, modal properties, and mesh stiffness variation instabilities of planetary gears. Prepared for NASA. NASA/CR-2001-210939. May 2001. pp. 1-111. cited by applicant

Petrovic, J.J., Castro, R.G., Vaidya, R.U., Peters, M.I., Mendoza, D., Hoover, R.C., and Gallegos, D. E. (2001). Molybdenum disilicide materials for glass melting sensor sheaths. Ceramic Engineering and Science Proceedings. vol. 22(3). 2001. pp. 59-64. cited by applicant

Press release. The GE90 engine. Retrieved from:  
<https://www.geaviation.com/commercial/engines/ge90-engine>; <https://www.geaviation.com/press-release/ge90-engine-family/ge90-115b-fan-completing-blade-testing-schedule-first-engine-test>; and

<https://www.geaviation.com/press-release/ge90-engine-family/ge'scomposite-fan-blade-revolution-turns-20-years-old>. cited by applicant

Product Brochure. Garrett TFE731. Allied Signal. Copyright 1987. pp. 1-24. cited by applicant

Pyrograf-III Carbon Nanofiber. Product guide. Retrieved Dec. 1, 2015 from: [http://pyrografproducts.com/Merchant5/merchant.mvc?Screen=cp\\_nanofiber](http://pyrografproducts.com/Merchant5/merchant.mvc?Screen=cp_nanofiber). cited by applicant

Ramsden, J.M. (Ed). (1978). The new European airliner. Flight International, 113(3590). Jan. 7, 1978. pp. 39-43. cited by applicant

Ratna, D. (2009). Handbook of thermoset resins. Shawbury, UK: iSmithers. pp. 187-216. cited by applicant

Rauch, D. (1972). Design study of an air pump and integral lift engine ALF-504 using the Lycoming 502 core. Prepare for NASA. Jul. 1972. pp. 1-182. cited by applicant

Reshotko, M., Karchmer, A., Penko, P.F. (1977). Core noise measurements on a YF-102 turbofan engine. NASA TM X-73587. Prepared for Aerospace Sciences Meeting sponsored by the American Institute of Aeronautics and Astronautics. Jan. 24-26, 2977. cited by applicant

Reynolds, C.N. (1985). Advanced prop-fan engine technology (APET) single- and counter-rotation gearbox/pitch change mechanism. Prepared for NASA. NASA CR-168114 (vol. I). Jul. 1985. pp. 1-295. cited by applicant

Riegler, C., and Bichlmaier, C. (2007). The geared turbofan technology- Opportunities, challenges and readiness status. Porceedings CEAS. Sep. 10-13, 2007. Berlin, Germany. pp. 1-12. cited by applicant

Rolls-Royce M45H. Jane's Aero-engines, Aero-engines—Turbofan. Feb. 24, 2010. cited by applicant

Roux, E. (2007). Turbofan and turbojet engines database handbook. Editions Elodie Roux. Blagnac: France. pp. 1-595. cited by applicant

Salemme, C.T. and Murphy, G.C. (1979). Metal spar/superhybrid shell composite fan blades. Prepared for NASA. NASA-CR-159594. Aug. 1979. pp. 1-127. cited by applicant

Savelle, S.A. and Garrard, G.D. (1996). Application of transient and dynamic simulations to the U.S. Army T55-L-712 helicopter engine. The American Society of Mechanical Engineers. Presented Jun. 10-13, 1996. pp. 1-8. cited by applicant

Schaefer, J.W., Sagerser, D.R., and Stakolich, E.G. (1977). Dynamics of high-bypass-engine thrust reversal using a variable-pitch fan. Technical Report prepared for NASA. NASA-TM-X-3524. May 1, 1977. pp. 1-33. cited by applicant

Seader, J.D. and Henley, E.J. (1998). Separation process principles. New York, NY: John Wiley & Sons, Inc. pp. 722-6 and 764-71. cited by applicant

Seventh Semiannual Status Report vol. I. Apr. 1, 1981-Sep. 30, 1981. Energy Efficient Engine Component Development and Integration Program. Contract NAS3-20646. Prepared for National Aeronautics and Space Administration. PWA-5594-179. United Technologies Pratt & Whitney Aircraft. Oct. 30, 1981. pp. 1-232. cited by applicant

Shah, D.M. (1992). MoSi2 and other silicides as high temperature structural materials. Superalloys 1992. The Minerals, Metals, & Materials Society. pp. 409-422. cited by applicant

Shorter Oxford English Dictionary, 6th Edition. (2007), vol. 2, N-Z, p. 1888. cited by applicant

Silverstein, C.C., Gottschlich, J.M., and Meininger, M. The feasibility of heat pipe turbine vane cooling. Presented at the International Gas Turbine and Aeroengine Congress and Exposition, The Hague, Netherlands. Jun. 13-16, 1994. pp. 1-7. cited by applicant

Singh, A. (2005). Application of a system level model to study the planetary load sharing behavior. Jounal of Mechanical Design. vol. 127. May 2005. pp. 469-76. cited by applicant

Singh, B. (1986). Small engine component technology (SECT) study. NASA CR-175079. Mar. 1, 1986. pp. 1-102. cited by applicant

Smith-Boyd, L. and Pike, J. (1986). Expansion of epicyclic gear dynamic analysis program. Prepared for NASA. NASA CR-179563. Aug. 1986. pp. 1-98. cited by applicant

Spadaccini, L.J., and Huang, H. (2002). On-line fuel deoxygenation for coke suppression. ASME, Jun. 2002. pp. 1-7. cited by applicant

Spadaccini, L.J., Sobel, D.R., and Huang, H. (2001). Deposit formation and mitigation in aircraft fuels. Journal of Eng. For Gas Turbine and Power, vol. 123. Oct. 2001. pp. 741-746. cited by applicant

Sundaram, S.K., Hsu, J-Y., Speyer, R.F. (1994). Molten glass corrosion resistance of immersed combustion- heating tube materials in soda-lime-silicate glass. J. Am. Ceram. Soc. 77(6). pp. 1613-23. cited by applicant

Sundaram, S.K., Hsu, J-Y., Speyer, R.F. (1995). Molten glass corrosion resistance of immersed combustion-heating tube materials in e-glass. J. Am. Ceram. Soc. 78(7). pp. 1940-46. cited by applicant

Sutliff, D. (2005). Rotating rake turbofan duct mode measurement system. NASA TM-2005-213828. Oct. 1, 2005. pp. 1-34. cited by applicant

Suzuki, Y., Morgan, P.E.D., and Niihara, K. (1998). Improvement in mechanical properties of powder-processed MoSi<sub>2</sub> by the addition of Sc<sub>2</sub>O<sub>3</sub> and Y<sub>2</sub>O<sub>3</sub>. J. Am. Ceram. Soci. 81(12). pp. 3141-49. cited by applicant

Sweetman, B. and Sutton, O. (1998). Pratt & Whitney's surprise leap. Interavia Business & Technology, 53.621, p. 25. cited by applicant

Taylor, W.F. (1974). Deposit formation from deoxygenated hydrocarbons. I. General features. Ind. Eng. Chem., Prod. Res. Develop., vol. 13(2). 1974. pp. 133-38. cited by applicant

Taylor, W.F. (1974). Deposit formation from deoxygenated hydrocarbons. II. Effect of trace sulfur compounds. Ind. Eng. Chem., Prod. Res. Dev., vol. 15(1). 1974. pp. 64-8. cited by applicant

Taylor, W.F. and Frankenfeld, J.W. (1978). Deposit formation from deoxygenated hydrocarbons. 3. Effects of trace nitrogen and oxygen compounds. Ind. Eng. Chem., Prod. Res. Dev., vol. 17(1). 1978. pp. 86-90. cited by applicant

Technical Data. Teflon. WS Hampshire Inc. Retrieved from: [http://catalog.wshampshire.com/Asset/psg\\_teflon\\_ptfe.pdf](http://catalog.wshampshire.com/Asset/psg_teflon_ptfe.pdf). cited by applicant

Technical Report. (1975). Quiet Clean Short-haul Experimental Engine (QCSEE) UTW fan preliminary design. NASA-CR-134842. Feb. 1, 1975. pp. 1-98. cited by applicant

Thulin, R.D., Howe, D.C., and Singer, I.D. (1982). Energy efficient engine: High pressure turbine detailed design report. Prepared for NASA. NASA CR-165608. Received Aug. 9, 1984. pp. 1-178. cited by applicant

Trembley, Jr., H.F. (1977). Determination of effects of ambient conditions on aircraft engine emissions. ALF 502 combustor rig testing and engine verification test. Prepared for Environmental Protection Agency. Sep. 1977. pp. 1-256. cited by applicant

Tsirlin, M., Pronin, Y.E., Florina, E.K., Mukhametov, S. Kh., Khatsernov, M.A., Yun, H.M., . . . Kroke, E. (2001). Experimental investigation of multifunctional interphase coatings on SiC fibers for non-oxide high temperature resistant CMCs. High Temperature Ceramic Matrix Composites. 4th Int'l Conf. on High Temp. Ceramic Matrix Composites. Oct. 1-3, 2001. pp. 149-156. cited by applicant

European Search Report for EP Application No. 22185711.3 dated Dec. 6, 2022. cited by applicant

European Search Report for EP Application No. 22185719.6 dated Dec. 15, 2022. cited by applicant

---

*Primary Examiner:* Sutherland; Steven M

*Attorney, Agent or Firm:* Carlson, Gaskey & Olds, P.C.

---

## Background/Summary

### BACKGROUND

(1) This application relates to a gas turbine engine with a gear reduction between a low pressure compressor and a fan, and where a ratio of low spool torque to low spool power is higher than has been the case in gas turbine engines with a gear reduction.

(2) Gas turbine engines are known, and typically include a fan delivering air into a bypass duct as bypass air. The air is also delivered into a compressor. The compressed air is delivered into a combustor where it is mixed with fuel and ignited. Products of this combustion pass downstream over turbine rotors, driving them to rotate.

(3) The turbine rotors drive the fan and compressor. Typically, there are two turbine rotors and two compressors. A lower pressure turbine rotor drives a lower pressure compressor. Historically the low pressure compressor was fixed to a fan shaft to drive the shaft. However, more recently a gear reduction has been placed between the low pressure compressor and the fan.

### SUMMARY

(4) In a featured embodiment, a gas turbine engine includes a fan rotor surrounded by a fan case and delivering air into a bypass duct defined between the fan and an inner core housing. The fan rotor also delivers air into the inner core housing and into a compressor section. The compressor section includes a low pressure compressor and a high pressure compressor. The high pressure compressor delivers air into a combustor where it is mixed with fuel and ignited, and products of the combustion pass downstream into a turbine section. The turbine section includes a fan drive turbine driving the low pressure compressor, and driving a gear reduction to in turn drive the fan rotor at a speed slower than the fan drive turbine. The turbine section further includes a high pressure turbine driving the high pressure compressor. The fan drive turbine and low pressure compressor are connected by a shaft and the fan drive turbine. The shaft and the low pressure compressor define a low pressure spool. The low pressure spool has a torque at maximum takeoff defined in ft-lbs and also having a low pressure spool power defined in horsepower and at maximum takeoff, and a ratio of the low pressure spool torque to the low pressure spool power being defined, with the low pressure spool power being defined in horsepower, and the ratio of the low pressure spool torque to the low pressure spool power being greater than or equal to 0.6 ft-lb/hp and less than or equal to 1.2 ft-lb/hp.

(5) In another embodiment according to the previous embodiment, a gear ratio of the gear reduction is greater than or equal to 3.2 and less than or equal to 4.0.

(6) In another embodiment according to any of the previous embodiments, the gear ratio of the gear ratio is greater than or equal to 3.4.

(7) In another embodiment according to any of the previous embodiments, the power extraction ratio is greater than or equal to 0.70 ft-lb/hp.

(8) In another embodiment according to any of the previous embodiments, the power extraction ratio is less than or equal to 1.0 ft-lb/hp.

(9) In another embodiment according to any of the previous embodiments, the power extraction ratio is greater than or equal to 0.70 ft-lb/hp.

(10) In another embodiment according to any of the previous embodiments, a pressure ratio at cruise condition can be defined across the fan rotor and the low pressure compressor. The pressure ratio is greater than or equal to 3.5 and less than or equal to 6.0.

(11) In another embodiment according to any of the previous embodiments, the pressure ratio is greater than or equal to 4.0.

(12) In another embodiment according to any of the previous embodiments, a pressure ratio at cruise condition can be defined across the fan rotor and the low pressure compressor. The pressure

ratio is greater than or equal to 3.5 and less than or equal to 6.0.

(13) In another embodiment according to any of the previous embodiments, the pressure ratio is greater than or equal to 4.0.

(14) A gas turbine engine includes a fan rotor surrounded by a fan case and delivering air into a bypass duct defined between the fan and an inner core housing. The fan rotor also delivers air into the inner core housing and into a compressor section. The compressor section includes a low pressure compressor and a high pressure compressor. The high pressure compressor delivers air into a combustor where it is mixed with fuel and ignited, and products of the combustion passing downstream into a turbine section. The turbine section includes a fan drive turbine driving the low pressure compressor, and driving a gear reduction to in turn drive the fan rotor at a speed slower than the fan drive turbine. The turbine section further includes a high pressure turbine driving the high pressure compressor. The fan drive turbine and low pressure compressor are connected by a shaft and the fan drive turbine. The low pressure shaft and the low pressure compressor define a low pressure spool. The low pressure spool has a torque at maximum takeoff defined in ft-lbs and also has a low pressure spool power, and a ratio of the low pressure spool torque to the low pressure spool power being defined, with the low pressure spool power being defined in horsepower, and the ratio of the low pressure spool torque to the low pressure spool power being greater than or equal to 0.5 ft-lb/hp and less than or equal to 1.2 ft-lb/hp. A pressure ratio at cruise condition is defined across the fan and the low pressure compressor. The pressure ratio is greater than or equal to 3.5 and less than or equal to 6.0.

(15) In another embodiment according to any of the previous embodiments, a gear ratio of the gear reduction is greater than or equal to 3.2 and less than or equal to 4.0.

(16) In another embodiment according to any of the previous embodiments, the gear ratio of the gear ratio is greater than or equal to 3.4.

(17) In another embodiment according to any of the previous embodiments, the power extraction ratio is greater than or equal to 0.70 ft-lb/hp.

(18) In another embodiment according to any of the previous embodiments, power extraction ratio is less than or equal to 1.0 ft-lb/hp.

(19) In another embodiment according to any of the previous embodiments, the power extraction ratio is greater than or equal to 0.90 ft-lb/hp.

(20) In another embodiment according to any of the previous embodiments, the pressure ratio is greater than or equal to 4.0.

(21) In another embodiment according to any of the previous embodiments, the pressure ratio is greater than or equal to 4.0.

(22) In another embodiment according to any of the previous embodiments, the power extraction ratio is greater than or equal to 0.70 ft-lb/hp.

(23) In another embodiment according to any of the previous embodiments, the power extraction ratio is greater than or equal to 0.90 ft-lb/hp.

(24) The present disclosure may include any one or more of the individual features disclosed above and/or below alone or in any combination thereof.

(25) These and other features of the present invention can be best understood from the following specification and drawings, the following of which is a brief description.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 shows a gas turbine engine according to this disclosure.

(2) FIG. 2 schematically shows a low spool.

### DETAILED DESCRIPTION



(3) FIG. 1 schematically illustrates a gas turbine engine 20. The gas turbine engine 20 is disclosed herein as a two-spool turbofan that generally incorporates a fan section 22, a compressor section 24, a combustor section 26 and a turbine section 28. The fan section 22 may include a single-stage fan 42 having a plurality of fan blades 43. The fan blades 43 may have a fixed stagger angle or may have a variable pitch to direct incoming airflow from an engine inlet. The fan 42 drives air along a bypass flow path B in a bypass duct 13 defined within a housing 15 such as a fan case or nacelle, and also drives air along a core flow path C for compression and communication into the combustor section 26 then expansion through the turbine section 28. A splitter 29 aft of the fan 42 divides the air between the bypass flow path B and the core flow path C. The housing 15 may surround the fan 42 to establish an outer diameter of the bypass duct 13. The splitter 29 may establish an inner diameter of the bypass duct 13. Although depicted as a two-spool turbofan gas turbine engine in the disclosed non-limiting embodiment, it should be understood that the concepts described herein are not limited to use with two-spool turbofans as the teachings may be applied to other types of turbine engines including three-spool architectures. The engine 20 may incorporate a variable area nozzle for varying an exit area of the bypass flow path B and/or a thrust reverser for generating reverse thrust.

(4) The exemplary engine 20 generally includes a low speed spool 30 and a high speed spool 32 mounted for rotation about an engine central longitudinal axis A relative to an engine static structure 36 via several bearing systems 38. It should be understood that various bearing systems 38 at various locations may alternatively or additionally be provided, and the location of bearing systems 38 may be varied as appropriate to the application.

(5) The low speed spool 30 generally includes an inner shaft 40 that interconnects, a first (or low) pressure compressor 44 and a first (or low) pressure turbine 46. The inner shaft 40 is connected to the fan 42 through a speed change mechanism, which in the exemplary gas turbine engine 20 is illustrated as a geared architecture 48 to drive the fan 42 at a lower speed than the low speed spool 30. The inner shaft 40 may interconnect the low pressure compressor 44 and low pressure turbine 46 such that the low pressure compressor 44 and low pressure turbine 46 are rotatable at a common speed and in a common direction. In other embodiments, the low pressure turbine 46 drives both the fan 42 and low pressure compressor 44 through the geared architecture 48 such that the fan 42 and low pressure compressor 44 are rotatable at a common speed. Although this application discloses geared architecture 48, its teaching may benefit direct drive engines having no geared architecture. The high speed spool 32 includes an outer shaft 50 that interconnects a second (or high) pressure compressor 52 and a second (or high) pressure turbine 54. A combustor 56 is arranged in the exemplary gas turbine 20 between the high pressure compressor 52 and the high pressure turbine 54. A mid-turbine frame 57 of the engine static structure 36 may be arranged generally between the high pressure turbine 54 and the low pressure turbine 46. The mid-turbine frame 57 further supports bearing systems 38 in the turbine section 28. The inner shaft 40 and the outer shaft 50 are concentric and rotate via bearing systems 38 about the engine central longitudinal axis A which is collinear with their longitudinal axes.

(6) Airflow in the core flow path C is compressed by the low pressure compressor 44 then the high pressure compressor 52, mixed and burned with fuel in the combustor 56, then expanded through the high pressure turbine 54 and low pressure turbine 46. The mid-turbine frame 57 includes airfoils 59 which are in the core flow path C. The turbines 46, 54 rotationally drive the respective low speed spool 30 and high speed spool 32 in response to the expansion. It will be appreciated that each of the positions of the fan section 22, compressor section 24, combustor section 26, turbine section 28, and fan drive gear system 48 may be varied. For example, gear system 48 may be located aft of the low pressure compressor, or aft of the combustor section 26 or even aft of turbine section 28, and fan 42 may be positioned forward or aft of the location of gear system 48.

(7) The fan 42 may have at least 10 fan blades 43 but no more than 20 or 24 fan blades 43. In examples, the fan 42 may have between 12 and 18 fan blades 43, such as 14 fan blades 43. An

exemplary fan size measurement is a maximum radius between the tips of the fan blades **43** and the engine central longitudinal axis A. The maximum radius of the fan blades **43** can be at least 38 inches, or more narrowly no more than 75 inches. For example, the maximum radius of the fan blades **43** can be between 45 inches and 60 inches, such as between 50 inches and 55 inches. Another exemplary fan size measurement is a hub radius, which is defined as distance between a hub of the fan **42** at a location of the leading edges of the fan blades **43** and the engine central longitudinal axis A. The fan blades **43** may establish a fan hub-to-tip ratio, which is defined as a ratio of the hub radius divided by the maximum radius of the fan **42**. The fan hub-to-tip ratio can be less than or equal to 0.35, or more narrowly greater than or equal to 0.20, such as between 0.25 and 0.30. The combination of fan blade counts and fan hub-to-tip ratios disclosed herein can provide the engine **20** with a relatively compact fan arrangement.

(8) The low pressure compressor **44**, high pressure compressor **52**, high pressure turbine **54** and low pressure turbine **46** each include one or more stages having a row of rotatable airfoils. Each stage may include a row of vanes adjacent the rotatable airfoils. The rotatable airfoils are schematically indicated at **47**, and the vanes are schematically indicated at **49**.

(9) The low pressure compressor **44** and low pressure turbine **46** can include an equal number of stages. For example, the engine **20** can include a three-stage low pressure compressor **44**, an eight-stage high pressure compressor **52**, a two-stage high pressure turbine **54**, and a three-stage low pressure turbine **46** to provide a total of sixteen stages. In other examples, the low pressure compressor **44** includes a different (e.g., greater) number of stages than the low pressure turbine **46**. For example, the engine **20** can include a five-stage low pressure compressor **44**, a nine-stage high pressure compressor **52**, a two-stage high pressure turbine **54**, and a four-stage low pressure turbine **46** to provide a total of twenty stages. In other embodiments, the engine **20** includes a four-stage low pressure compressor **44**, a nine-stage high pressure compressor **52**, a two-stage high pressure turbine **54**, and a three-stage low pressure turbine **46** to provide a total of eighteen stages. It should be understood that the engine **20** can incorporate other compressor and turbine stage counts, including any combination of stages disclosed herein.

(10) The engine **20** may be a high-bypass geared aircraft engine. The bypass ratio can be greater than or equal to 10.0 and less than or equal to about 18.0, or more narrowly can be less than or equal to 16.0. The geared architecture **48** may be an epicyclic gear train, such as a planetary gear system or a star gear system. The epicyclic gear train may include a sun gear, a ring gear, a plurality of intermediate gears meshing with the sun gear and ring gear, and a carrier that supports the intermediate gears. The sun gear may provide an input to the gear train. The ring gear (e.g., star gear system) or carrier (e.g., planetary gear system) may provide an output of the gear train to drive the fan **42**. A gear reduction ratio may be greater than or equal to 2.3, or more narrowly greater than or equal to 3.0, and in some embodiments the gear reduction ratio is greater than or equal to 3.4. The gear reduction ratio may be less than or equal to 4.0. The fan diameter is significantly larger than that of the low pressure compressor **44**. The low pressure turbine **46** can have a pressure ratio that is greater than or equal to 8.0 and in some embodiments is greater than or equal to 10.0. The low pressure turbine pressure ratio can be less than or equal to 13.0, or more narrowly less than or equal to 12.0. Low pressure turbine **46** pressure ratio is pressure measured prior to an inlet of low pressure turbine **46** as related to the pressure at the outlet of the low pressure turbine **46** prior to an exhaust nozzle. It should be understood, however, that the above parameters are only exemplary of one embodiment of a geared architecture engine and that the present invention is applicable to other gas turbine engines including direct drive turbfans. All of these parameters are measured at the cruise condition described below.

(11) A significant amount of thrust is provided by the bypass flow B due to the high bypass ratio. The fan section **22** of the engine **20** is designed for a particular flight condition—typically cruise at about 0.8 Mach and about 35,000 feet (10,668 meters). The flight condition of 0.8 Mach and 35,000 ft (10,668 meters), with the engine at its best fuel consumption—also known as “bucket

cruise Thrust Specific Fuel Consumption ("TSFC")—is the industry standard parameter of lbfm of fuel being burned divided by lbf of thrust the engine produces at that minimum point. The engine parameters described above, and those in the next paragraph are measured at this condition unless otherwise specified.

(12) "Fan pressure ratio" is the pressure ratio across the fan blade **43** alone, without a Fan Exit Guide Vane ("FEGV") system. A distance is established in a radial direction between the inner and outer diameters of the bypass duct **13** at an axial position corresponding to a leading edge of the splitter **29** relative to the engine central longitudinal axis A. The fan pressure ratio is a spanwise average of the pressure ratios measured across the fan blade **43** alone over radial positions corresponding to the distance. The fan pressure ratio can be less than or equal to 1.45, or more narrowly greater than or equal to 1.25, such as between 1.30 and 1.40. "Corrected fan tip speed" is the actual fan tip speed in ft/sec divided by an industry standard temperature correction of  $[(T_{\text{Tram}} / 518.7) / (T_{\text{R}} / 518.7)]^{0.5}$ . The corrected fan tip speed can be less than or equal to 1150.0 ft/second (350.5 meters/second), and can be greater than or equal to 1000.0 ft/second (304.8 meters/second).

(13) The fan **42**, low pressure compressor **44** and high pressure compressor **52** can provide different amounts of compression of the incoming airflow that is delivered downstream to the turbine section **28** and cooperate to establish an overall pressure ratio (OPR). The OPR is a product of the fan pressure ratio across a root (i.e., 0% span) of the fan blade **43** alone, a pressure ratio across the low pressure compressor **44** and a pressure ratio across the high pressure compressor **52**. The pressure ratio of the low pressure compressor **44** is measured as the pressure at the exit of the low pressure compressor **44** divided by the pressure at the inlet of the low pressure compressor **44**. In examples, a product of the pressure ratio of the low pressure compressor **44** and the fan pressure ratio is between 3.0 and 6.0, or more narrowly is between 4.0 and 5.5. The pressure ratio of the high pressure compressor ratio **52** is measured as the pressure at the exit of the high pressure compressor **52** divided by the pressure at the inlet of the high pressure compressor **52**. In examples, the pressure ratio of the high pressure compressor **52** is between 7.0 and 12.0, or more narrowly is between 10.0 and 11.5. The OPR can be equal to or greater than 44.0, and can be less than or equal to 70.0, such as between 50.0 and 60.0. The overall and compressor pressure ratios disclosed herein are measured at the cruise condition described above, and can be utilized in two-spool architectures such as the engine **20** as well as three-spool engine architectures.

(14) The engine **20** establishes a turbine entry temperature (TET). The TET is defined as a maximum temperature of combustion products communicated to an inlet of the turbine section **28** at a maximum takeoff (MTO) condition. The inlet is established at the leading edges of the axially forwardmost row of airfoils of the turbine section **28**, and MTO is measured at maximum thrust of the engine **20** at static sea-level and 86 degrees Fahrenheit ( $^{\circ}\text{F}$ ). The TET may be greater than or equal to 2700.0 $^{\circ}\text{F}$ ., or more narrowly less than or equal to 3500.0 $^{\circ}\text{F}$ ., such as between 2750.0 $^{\circ}\text{F}$  and 3350.0 $^{\circ}\text{F}$ . The relatively high TET can be utilized in combination with the other techniques disclosed herein to provide a compact turbine arrangement.

(15) The engine **20** establishes an exhaust gas temperature (EGT). The EGT is defined as a maximum temperature of combustion products in the core flow path C communicated to at the trailing edges of the axially aftmost row of airfoils of the turbine section **28** at the MTO condition. The EGT may be less than or equal to 1000.0 $^{\circ}\text{F}$ ., or more narrowly greater than or equal to 800.0 $^{\circ}\text{F}$ ., such as between 900.0 $^{\circ}\text{F}$  and 975.0 $^{\circ}\text{F}$ . The relatively low EGT can be utilized in combination with the other techniques disclosed herein to reduce fuel consumption.

(16) Applicant previously designed, manufactured and flew a gas turbine engine with a gear reduction between the low pressure compressor and the fan rotor. A gear ratio of the gear reduction in those engines was 3.06, or lower. This disclosure relates to gas turbine engines with a gear reduction, but also in embodiments with a gear ratio greater than or equal to 3.2, and also in embodiments greater than or equal to 3.4, and less than 4.0.

(17) The low spool **30** is illustrated in FIG. 2 including a low pressure (or fan drive) turbine **46**, and

a shaft **40** driving a low pressure compressor **44**. A gear reduction **48** drives the fan rotor **42**. The low spool is defined as turbine **46**, shaft **40** and compressor **44**.

(18) In this disclosure, the low speed spool **30** has its torque reduced and speed is increased. This will enable a smaller shaft **40** to transfer the required torque. This is at least partially due to the higher gear ratio. Even so, a ratio of low speed spool torque at maximum takeoff to maximum takeoff thrust is higher than has been the case in the prior art. As an example, the following example engines would come within the scope of this disclosure.

(19) TABLE-US-00001

Engine 1	Engine 2	Engine 3	Engine 4	Low spool torque	89512 ft-lb	21027 ft-lb	19727 ft-lb	21061 ft-lb	MTO thrust	94027 lbf	25360 lbf	24240 lbf	32980 lbf	LST/MTO thrust
0.95 ft-lb/lbf	0.83 ft-lb/lbf	0.81 ft-lb/lbf	0.64 ft-lb/lbf											

(20) The ratios as disclosed above could be called a low spool torque-to-thrust ratio.

(21) In the first generation gas turbine engines with a gear reduction developed by Applicant, the ratios were on the order of 0.18 ft-lb/lbf in one engine, 0.52 ft-lb/lbf in another engine, 0.61 ft-lb/lbf in yet another engine, and 0.65 ft-lb/lbf in yet another engine.

(22) The disclosed low spool thrust ratios being higher provides more efficient operation by providing greater energy via the highly efficient low pressure turbine. In embodiments, the ratio may be greater than or equal 0.60 ft-lb/lbf, and in other embodiments greater than or equal to 0.70 ft-lb/lbf, 0.8 ft-lb/lbf and greater than or equal to 0.9 ft-lb/lbf in other embodiments. The ratio is preferably less than 1.2 ft-lb/lbf, and in embodiments less than or equal to 1.0 ft-lb/lbf.

(23) Engines coming under this disclosure may shift more of the work from the high speed spool and compressor to the low speed spool and compressor compared to the first generation engines. As an example, in the first generation engine mentioned above where the low spool thrust ratio is 0.65, the corresponding low pressure compressor pressure ratio including the fan pressure ratio was 3.0. In the engine designed under this disclosure having the low spool thrust ratio of 0.64, the corresponding low pressure compressor pressure ratio with the fan was 4.1. Engines coming under this disclosure could also be said to include the pressure ratio across the low pressure compressor including the fan pressure ratio is greater than or equal to 3.5, and in embodiments greater than or equal to 4.0, and less than or equal to 6.5. Further details of the low spool thrust ratio may found in co-pending U.S. patent application Ser. No. 17/379,233, filed on even date herewith, and entitled "GAS TURBINE ENGINE WITH HIGHER LOW SPOOL TORQUE-TO-THRUST RATIO." The disclosure of which is incorporated by reference here.

(24) The disclosed engine may also benefit from a power extraction ratio that relates the low spool torque to the low spool power, both measured at maximum takeoff. Low spool power is measured in horsepower.

(25) TABLE-US-00002

Engine 1	Engine 2	Engine 3	Engine 4	Low spool torque	89512 ft-lb	21027 ft-lb	19727 ft-lb	21061 ft-lb	Low spool power	98190 hp	37639 hp	35924 hp	34834 hp	LST/MTO thrust
0.912 ft-lb/hp	0.559 ft-lb/hp	0.549 ft-lb/hp	0.605 ft-lb/hp											

(26) In engines made according to Applicant's first generation gas turbine engine with a gear reduction the corresponding ratios were 0.558 ft-lb/hp, 0.551 ft-lb/hp, 0.534 ft-lb/hp, and 0.449 ft-lb/hp.

(27) Engines according to this disclosure benefit from higher power extraction ratios by providing greater energy via the highly efficient low pressure turbine. In embodiments the power extraction ratio may be greater than or equal to 0.50 ft-lb/hp, and in other embodiments greater than or equal to 0.60 ft-lb/hp, and in further embodiments greater than or equal to 0.70 ft-lb/hp, in further embodiments it may be greater than or equal to 0.80 ft-lb/hp, and in further embodiments it may be greater than or equal to 0.90 ft-lb/hp. In embodiments it is preferably less than or equal 1.2 ft-lb/hp, and in further embodiments less than or equal to 1.1 ft-lb/hp, in other embodiments it may be less than or equal to 1.0 ft-lb/hp.

(28) Engines coming under this disclosure may shift more of the work from a high speed spool and compressor to the low speed spool and compressor compared to the first generation engine. As an

example, in the first generation engines mentioned above wherein the power extraction ratio was 0.558, 0.551 and 0.534, the corresponding low pressure compressor ratio including the fan pressure ratio was 2.9, 3.1 and 3.1, respectively. In the engines designed under this disclosure having the power extraction ratio of 0.559 and 0.549, the corresponding pressure ratio across the low pressure compressor including the fan pressure ratio was 5.0 for both. Engines coming under this disclosure could also be said to include the pressure ratio across the low pressure compressor including the fan is greater than or equal to 3.5, and embodiments greater than or equal to 4.0, and less than or equal to 6.5.

(29) The combination of the two ratios disclosed above also results in a synergistic benefit with regard to the efficient operation of the associated engine.

(30) The disclosures here can be said to provide efficient operation, with each disclosed ratio, but the combination of the two is particularly powerful. As the gear ratio goes up, the necessary torque on the low spool drops. Power has a relationship with thrust, and for a given thrust there is a given power. However, since this disclosure relates to gas turbine engines wherein a speed increase is provided to the low spool, one can reach the given power and thrust with less torque on the low spool.

(31) A gas turbine engine under this disclosure could be said to include a fan rotor surrounded by a fan case and delivering air into a bypass duct defined between the fan and an inner core housing. The fan rotor also delivering air into the inner core housing and into a compressor section. The compressor section includes a low pressure compressor and a high pressure compressor. The high pressure compressor delivers air into a combustor where it is mixed with fuel and ignited, and products of the combustion pass downstream into a turbine section. The turbine section includes a low pressure turbine driving the low pressure compressor, and driving a gear reduction to in turn drive the fan rotor at a speed slower than the fan drive turbine. The turbine section further includes a high pressure turbine driving the high pressure compressor. The low pressure turbine and low pressure compressor are connected by a shaft. The low pressure turbine, the shaft and the low pressure compressor define a low pressure spool. The low pressure spool has a torque at maximum takeoff defined in ft-lbs and also having a low pressure spool power defined in horsepower and at maximum takeoff. The low pressure spool power is defined in horsepower. A ratio of the low pressure spool torque to the low pressure spool power being greater than or equal to 0.6 ft-lb/hp and less than or equal to 1.2 ft-lb/hp.

(32) In another embodiment, the ratio is greater than or equal to 0.5 ft-lb/hp and less than or equal to 1.2 ft-lb/hp and a power ratio at cruise condition is defined across the fan and the low pressure compressor. The pressure ratio being greater than or equal to 3.5 and less than or equal to 6.0.

(33) Although preferred embodiments of this invention have been disclosed, a worker of ordinary skill in this art would recognize that certain modifications would come within the scope of this invention. For that reason, the following claims should be studied to determine the true scope and content of this invention.

## Claims

1. A gas turbine engine comprising: a fan rotor surrounded by a fan case and delivering air into a bypass duct defined between said fan and an inner core housing, said fan rotor also delivering air into said inner core housing and into a compressor section, and a bypass ratio being defined as a volume of air delivered into said bypass duct divided by a volume of air delivered into said inner core housing, and said bypass ratio being greater than or equal to 10.0 and less than or equal to 16.0, said compressor section including a low pressure compressor and a high pressure compressor, said high pressure compressor delivering air into a combustor where it is mixed with fuel and ignited, and products of the combustion passing downstream into a turbine section, said turbine section including a fan drive turbine driving said low pressure compressor, and driving a gear

reduction to in turn drive said fan rotor at a speed slower than said fan drive turbine, said turbine section further including a high pressure turbine driving said high pressure compressor, said fan drive turbine and low pressure compressor connected by a shaft and said fan drive turbine, said shaft and said low pressure compressor defining a low pressure spool; wherein said low pressure spool has a torque at maximum takeoff defined in ft-lbs and also having a low pressure spool power defined in horsepower and at maximum takeoff, and a ratio of said low pressure spool torque to said low pressure spool power being defined, and said ratio of said low pressure spool torque to said low pressure spool power being greater than or equal to 0.9 ft-lb/hp and less than or equal to 1.2 ft-lb/hp; wherein a pressure ratio at cruise condition is defined across said fan rotor and said low pressure compressor, and said pressure ratio being greater than or equal to 3.5 and less than or equal to 6.0; and wherein a low pressure turbine pressure ratio is defined as a pressure measured prior to an inlet of the low pressure turbine as related to the pressure at the outlet of the low pressure turbine prior to any exhaust nozzle, and said low pressure turbine pressure ratio being greater than or equal to 8.0 and less than or equal to 13.0.

2. A gas turbine engine comprising: a fan rotor surrounded by a fan case and delivering air into a bypass duct defined between said fan and an inner core housing, said fan rotor also delivering air into said inner core housing and into a compressor section, and a bypass ratio being defined as a volume of air delivered into said bypass duct divided by a volume of air delivered into said inner core housing, and said bypass ratio being greater than or equal to 10.0 and less than or equal to 16.0, said compressor section including a low pressure compressor and a high pressure compressor, said high pressure compressor delivering air into a combustor where it is mixed with fuel and ignited, and products of the combustion passing downstream into a turbine section, said turbine section including a fan drive turbine driving said low pressure compressor, and driving a gear reduction to in turn drive said fan rotor at a speed slower than said fan drive turbine, a gear ratio of said gear reduction being greater than or equal to 3.4 and less than or equal to 4.0, said turbine section further including a high pressure turbine driving said high pressure compressor, said fan drive turbine and low pressure compressor connected by a shaft and said fan drive turbine, said low pressure shaft and said low pressure compressor defining a low pressure spool; wherein said low pressure spool has a torque at maximum takeoff defined in ft-lbs and also having a low pressure spool power, and a ratio of said low pressure spool torque to said low pressure spool power being defined, with said low pressure spool power being defined in horsepower, and said ratio of said low pressure spool torque to said low pressure spool power being greater than or equal to 0.6 ft-lb/hp and less than or equal to 1.2 ft-lb/hp; a pressure ratio at cruise condition defined across said fan and said low pressure compressor, and said pressure ratio being greater than or equal to 3.5 and less than or equal to 6.0; and wherein a low pressure turbine pressure ratio is defined as a pressure measured prior to an inlet of the low pressure turbine as related to the pressure at the outlet of the low pressure turbine prior to any exhaust nozzle, and said low pressure turbine pressure ratio being greater than or equal to 8.0 and less than or equal to 13.0.

---