

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent	12383424
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Thomas; Jonathan Moulton et al.

---

### Heating devices

---

#### Abstract

A heating device includes a heating unit and device electronics. The heating unit is configured to deliver heat to a user's body. The heating unit includes a substrate and a heating element supported by the substrate. The device electronics are coupled to the heating element and are configured to store a first heating profile that includes data indicating how power should be delivered to the heating element over a first period of time. The device electronics are configured to deliver power to the heating element according to the first heating profile. The device electronics are configured to wirelessly receive a second heating profile from an external computing device. The second heating profile includes data indicating how power should be delivered to the heating element over a second period of time. The device electronics are configured to deliver power to the heating element according to the second heating profile.

---

**Inventors:** Thomas; Jonathan Moulton (San Francisco, CA), Krieger; Brian James (San Francisco, CA), Caligaris; Richard Thomas (Los Altos, CA), Miracle; Elizabeth Ann (San Francisco, CA), Lee; Grace Hina (San Francisco, CA)

**Applicant:** Relief Technologies, Inc. (San Francisco, CA)

**Family ID:** 62782014

**Assignee:** Relief Technologies, Inc. (San Francisco, CA)

**Appl. No.:** 18/504460

**Filed:** November 08, 2023

#### Prior Publication Data

<b>Document Identifier</b>	<b>Publication Date</b>
US 20250082495 A1	Mar. 13, 2025

#### Related U.S. Application Data

continuation parent-doc US 17959659 20221004 US 11839569 child-doc US 18504460  
continuation parent-doc US 17220586 20210401 US 11504267 child-doc US 18504460  
continuation parent-doc US 15863296 20180105 US 11000406 child-doc US 17959659  
us-provisional-application US 62443041 20170106

---

## Publication Classification

**Int. Cl.:** **A61F7/00** (20060101); **A61F7/02** (20060101); **H05B1/02** (20060101); **H05B3/34** (20060101)

**U.S. Cl.:**

**CPC** **A61F7/007** (20130101); **A61F7/02** (20130101); **H05B1/025** (20130101); **H05B3/34** (20130101); A61F2007/0022 (20130101); A61F2007/0023 (20130101); A61F2007/0027 (20130101); A61F2007/003 (20130101); A61F2007/0071 (20130101); A61F2007/0078 (20130101); A61F2007/0086 (20130101); A61F2007/0093 (20130101); A61F2007/0096 (20130101); A61F2007/0228 (20130101); A61F2007/0236 (20130101); H05B2203/003 (20130101); H05B2203/013 (20130101)

## Field of Classification Search

**CPC:** A61F (7/007); A61F (7/02); A61F (2007/0022); A61F (2007/0023); A61F (2007/0027); A61F (2007/003); A61F (2007/0071); A61F (2007/0078); A61F (2007/0086); A61F (2007/0093); A61F (2007/0096); A61F (2007/0228); A61F (2007/0236); H05B (1/025); H05B (3/34); H05B (2203/003); H05B (2203/013)

---

## References Cited

### U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3634655	12/1971	Jordan	N/A	N/A
4243041	12/1980	Paul	N/A	N/A
6068606	12/1999	Castel et al.	N/A	N/A
9795502	12/2016	Kopes	N/A	N/A
11504267	12/2021	Thomas	N/A	H05B 1/025
11839569	12/2022	Thomas	N/A	H05B 3/34
2002/0190059	12/2001	Lam	N/A	N/A
2006/0060576	12/2005	Haas et al.	N/A	N/A
2006/0195168	12/2005	Dunbar et al.	N/A	N/A
2007/0016271	12/2006	Hammond	N/A	N/A
2011/0220634	12/2010	Yeh	N/A	N/A
2012/0228279	12/2011	Haas	219/211	H05B 1/02
2013/0036549	12/2012	Mcklarney	N/A	N/A
2014/0209594	12/2013	Besner	N/A	N/A
2014/0350645	12/2013	Diller et al.	N/A	N/A
2015/0083705	12/2014	Cronn et al.	N/A	N/A

2015/0227245	12/2014	Inagaki	345/173	G06F 3/0412
2016/0066716	12/2015	Rao	600/26	A61B 5/6814
2016/0178251	12/2015	Johnson et al.	N/A	N/A
2016/0262924	12/2015	Abreu	N/A	A61F 7/007
2016/0299526	12/2015	Inagaki	N/A	G06F 3/0443
2016/0374411	12/2015	Brooks et al.	N/A	N/A
2017/0028196	12/2016	Stopperan	N/A	N/A
2017/0258629	12/2016	Awasthi	N/A	N/A
2017/0265533	12/2016	Gueritee	N/A	H05B 3/342
2020/0008973	12/2019	Dunbar et al.	N/A	N/A

#### **FOREIGN PATENT DOCUMENTS**

<b>Patent No.</b>	<b>Application Date</b>	<b>Country</b>	<b>CPC</b>
202015102703	12/2014	DE	H05B 1/0275
WO-2016009202	12/2015	WO	A24F 15/18

#### **OTHER PUBLICATIONS**

Brookstone Shiatsu Neck and Back Massager with Heat.pdf—copyright 2016, 2 pages. cited by applicant

Palm NRG—Cordless heat pads—accessed on Jan. 2, 2018, <https://web.archive.org/web/20160311234727/https://shop.palnmrg.net/products/cordless-heat-pads>. The site is dated Mar. 11, 2016, 3 pages. cited by applicant

SoftHeat Soothing Therapy Mobile PowerWrap Manual.pdf—copyright 2013, 24 pages. cited by applicant

Sunbeam Heating Pad Instruction Manual—copyright 2008, 2 pages. cited by applicant

Versatile Body Wrap.pdf—The website <http://qfiber.com/products/versatile-body-wrap.php> was accessed Jan. 2, 2018 and is copyright 2015, 1 page. cited by applicant

U.S. Appl. No. 15/863,296, filed Jan. 5, 2018, Thomas et al. cited by applicant

U.S. Appl. No. 17/220,586, filed Apr. 1, 2021, Thomas et al. cited by applicant

*Primary Examiner:* Zadeh; Bob

*Attorney, Agent or Firm:* RMCK Law Group, PLC

#### **Background/Summary**

**CROSS-REFERENCE TO RELATED APPLICATIONS** (1) This application is a continuation of U.S. application Ser. No. 17/959,659, filed on Oct. 4, 2022, which is a continuation of U.S. application Ser. No. 17/220,586, filed on Apr. 1, 2021, which is a continuation of U.S. application Ser. No. 15/863,296, filed on Jan. 5, 2018, which claims the benefit of U.S. Provisional Application No. 62/443,041, filed on Jan. 6, 2017. The disclosure of each of the above applications is incorporated herein by reference in their entirety.

## FIELD

(1) The present disclosure relates to heating devices that provide heat to a user's body.

## BACKGROUND

(2) Heating therapy can be used to provide relief/rehabilitation for a variety of ailments, such as muscle ailments (e.g., soreness, tightness, or spasms), joint ailments (e.g., stiffness or arthritis), or other tissue ailments (e.g., tissue injuries). Heating therapy can be applied in a variety of manners, such as via direct contact with the skin (e.g., a hot cloth, pad, or hot water bath) or via infrared radiation. Heat therapy may increase tissue temperature, which may produce vasodilation that causes increased blood flow to affected areas, thereby increasing the supply of oxygen and nutrients to the affected areas. The therapeutic effects of heat may include a reduction in pain, stiffness, and inflammation in the affected areas.

## SUMMARY

(3) In one example, the present disclosure is directed to a heating device comprising a heating unit and device electronics. The heating unit is configured to deliver heat to a user's body. The heating unit comprises a substrate and a heating element supported by the substrate. The device electronics are coupled to the heating element. The device electronics are configured to store a first heating profile that includes data indicating how power should be delivered to the heating element over a first period of time. The device electronics are configured to deliver power to the heating element according to the first heating profile. The device electronics are configured to wirelessly receive a second heating profile from an external computing device. The second heating profile includes data indicating how power should be delivered to the heating element over a second period of time. The device electronics are configured to deliver power to the heating element according to the second heating profile.

(4) In another example, the present disclosure is directed to a heating device comprising a first heating element, a second heating element, and device electronics. The first heating element is configured to deliver heat to a first portion of a user's body. The second heating element is configured to deliver heat to a second portion of the user's body. The device electronics are coupled to the first and second heating elements and configured to wirelessly communicate with an external computing device. The device electronics are configured to wirelessly receive a first user-input instruction from the external computing device, the first user-input instruction indicating a first amount of power to deliver to each of the first and second heating elements. The device electronics are configured to deliver power to the first and second heating elements based on the first user-input instruction. The device electronics are configured to wirelessly receive a second user-input instruction from the external computing device, the second user-input instruction indicating a second amount of power to deliver to the first heating element. The device electronics are configured to modify the delivery of power to the first heating element based on the second user-input instruction.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

(1) The present disclosure will become more fully understood from the detailed description and the accompanying drawings.

(2) FIGS. 1A-1C illustrate a first example heating device.

(3) FIGS. 2A-2F illustrate example heating units.

(4) FIGS. 3A-3D illustrate example heating units connected to heating device electronics.

(5) FIG. 4 is a functional block diagram of an example heating device.

(6) FIGS. 5A-5E are example current versus time graphs for a heating device.

(7) FIGS. 6A-6C are flow diagrams that illustrate different modes of heating device operation.

- (8) FIGS. 7A-7C are directed to techniques for immediately heating a user.
- (9) FIG. 8 illustrates communication between a plurality of heating devices and a remote server.
- (10) FIGS. 9A-9K illustrate example graphical user interfaces (GUIs) on a user device in communication with a heating device.
- (11) FIGS. 10A-15 illustrate additional example heating devices.
- (12) FIGS. 16A-16E illustrate example sleeves and garments that hold heating devices.
- (13) In the drawings, reference numbers may be reused to identify similar and/or identical elements.

#### DETAILED DESCRIPTION

- (14) A heating device of the present disclosure (e.g., FIG. 1A) may be used to provide relief for a variety of different conditions including, but not limited to, muscle soreness, headaches, joint pain, and arthritis. The heating device may also be used to provide relief for pelvic pain conditions, such as chronic pelvic pain, dyspareunia, vulvodynia, endometriosis, and dysmenorrhea (menstrual pain). A variety of example heating devices **100-1**, **100-2**, . . . , **100-6** are illustrated and described herein (e.g., FIGS. 1A-1C and FIGS. 10A-15). A heating device **100** may generally refer to any of the example heating devices.
- (15) A heating device **100** (e.g., a heating pad) includes one or more heating units (e.g., heating unit **202-1** of FIG. 2B) that can generate heat for application to one or more areas of a user's body. The heating device **100** can include a device package (e.g., encapsulation **1006** of FIG. 10B) that houses the one or more heating units. A user can control the heating device manually. For example, the heating device **100** may include user input devices (e.g., manual controls) and/or be controlled via an external computing device **102**, such as a user's phone (e.g., see FIG. 1C). In one specific example, the heating device **100-1** of FIG. 1B includes a user input button **106**. The heating device **100** may also automatically run heating device profiles (e.g., FIGS. 5A-5E) that include data indicating how the heating device **100** should operate over time.
- (16) A heating unit can include a heating element and a substrate. Example heating units **202-1**, **202-2**, . . . , **202-13** (generally "heating unit **202**") are illustrated herein (e.g., FIGS. 2C-2F). Example heating elements **204-1**, **204-2**, . . . , **204-8** (generally "heating element **204**") are illustrated herein (e.g., FIGS. 2B-2F). Example substrates **200-1**, **200-2**, **200-3**, **200-4** (generally "substrate **200**") are illustrated herein (e.g., FIG. 2A).
- (17) The heating element **204** can generate heat that is applied to a user's body (e.g., via resistive heating). For example, the heating element **204** may include a metallic wire that generates heat when power is delivered to the heating element **204**. The substrate **200** can provide support to the heating element **204** (e.g., to maintain shape) so that the heating element **204** can be positioned near the user's body. For example, the heating element **204** can be attached to the substrate **200** and/or formed on the substrate **200** (e.g., etched on the substrate). The substrate **200** can be composed of a flexible material and/or a rigid material.
- (18) The heating device **100** includes device electronics (e.g., device electronics **300** in FIGS. 3A-3D) that control the amount of heat generated by the heating elements **204**. For example, the device electronics may control heat by controlling power (e.g., current or voltage) delivered to the heating elements **204**. In some implementations, the heating device **100** may include one or more sensors (e.g., temperature, orientation, motion, and/or pressure sensors). In these implementations, the device electronics may control the amount of heat generated by the heating elements **204** based on data acquired from the one or more sensors. In some implementations, the heating device **100** may include a battery, such as battery **302** in FIGS. 3B-3D, FIG. 10B, and FIG. 13C. In these implementations, the device electronics can manage charging/discharging of the battery and control heating based on a variety of conditions, such as a state of charge of the battery, the currently running heating device profile, and/or a target device run time indicated by the user.
- (19) In some implementations, the heating device **100** may include user interface devices that allow the user to interact with the heating device **100**. For example, the heating device **100** may include

buttons, switches, touch sensitive controls, and/or a display that allow the user to control/monitor the amount of heat being generated by the heating device **100**. The device electronics may communicate with the user interface devices in order to control heating of the heating elements **204** and provide output to the user. In some implementations, the device electronics may include electronics that can communicate with an external wired/wireless computing device **102**, such as a user's cell phone (e.g., see FIG. **1C**). In these implementations, the user may control/monitor the heat being generated by the heating device **100** using the external computing device **102**. The external computing device **102** may be referred to herein as a “user device **102**.”

(20) The heating device **100** can be powered in a variety of different ways. In some implementations, the heating device **100** can be configured to receive a battery **302** (e.g., rechargeable/non-rechargeable battery) from the user. The battery **302** may be removable by hand and/or fixed within the heating device **100** (e.g., accessible using tools). Additionally, or alternatively, the heating device **100** can be plugged into an external power source (e.g., via a power input port **104**) that may power the heating device and/or charge the battery **302**.

(21) The arrangement of the one or more heating elements **204** may create one or more heating zones. A heating zone refers to an area of the heating device **100** in which heat is delivered to the user. A user may control the heat generated in a heating zone by controlling power delivered to the heating element(s) **204** making up the heating zone. In some cases, heating zones can be surrounded by cooler areas of the heating device **100** (e.g., areas not including heating elements **204**). Put another way, if a heating device **100** has multiple heating zones, the heating zones can be separated from one another. In other cases, the heating zones may not be separated, but instead, some of the heating zones may merge together such that the two heating zones are bridged by a heated area instead of a cooler area.

(22) The heating device **100** can be configured to operate in one or more of three modes, which may be referred to herein as a manual mode, an automatic mode, or a mixed mode. The heating device **100** can operate in a manual mode in which the heating device is configured to generate heat in response to a user's manual input. For example, while operating in the manual mode, a user can control heating using manual controls on the heating device **100** and/or using the user device **102**. In a more specific example, the user can incrementally increase/decrease heating in different heating zones using manual controls and/or graphical controls rendered on a graphical user interface (GUI) of the user device **102**. In the manual mode, the user may control one or more of the heating zones. If the heating device **100** has multiple heating zones, the user may manually control the heating zones independently or together.

(23) The heating device **100** can operate in an automatic mode in which the heating device **100** generates heat according to a heating profile, or sequence of profiles, loaded on the heating device **100**. The heating profile can include data indicating how the heating device **100** should heat the one or more heating zones. For example, if a heating device **100** includes a single heating element **204**, the heating profile may include data that indicates how to heat the heating element **204**. In this example, the heating profile may include data indicating the amount of power (e.g., voltage or current) to be delivered to the heating element **204** over a period of time. FIGS. **5A-5E** illustrate example heating profiles that may be used by the heating device **100**. In heating devices **100** including multiple heating elements **204**, a heating profile can include data indicating the amount of power (e.g., voltage or current) to be delivered to each of the multiple heating elements **204**. A heating profile may also indicate how the heating device **100** should operate in response to data acquired from one or more sensors included on the heating device **100**. For example, the heating profile may indicate whether to increase/decrease the delivery of power based on a detected temperature.

(24) The heating device **100** can store one or more heating profiles. In some implementations, the heating profiles may be stored permanently in memory (e.g., in a ROM), and the user can select from the heating profiles using manual controls and/or a GUI. In some implementations, the user

can load different heating profiles onto the heating device **100** (e.g., from the user device **102**) and then select from the loaded heating profiles.

(25) The heating device **100** may operate in a mixed mode during which the user can modify/update a heating profile while the heating device **100** is controlling heat according to the heating profile. Modification of the heating profile may refer to a situation where any portion of the heating profile is changed by the user. The user can modify the heating profile in a variety of different ways. For example, the user may modify a heating profile by: 1) adjusting the amount of heat generated (e.g., the voltage or current) by one or more heating elements **204**, 2) adjusting the frequency of the heat generated (e.g., frequency of heating pulses) in one or more heating elements **204**, 3) adjusting timing delays between the one or more heating elements **204**, and/or 4) loading a new heating profile for one or more of the heating elements **204**. In some mixed mode implementations, the heating device **100** may memorize a heating profile generated by the user. For example, the user may modify the amplitude of heat generated by the heating device **100** (e.g., using the user device **102** and/or manual controls) in one or more heating elements **204** and the heating device **100** may store a heating profile that corresponds to the user's heating pattern.

(26) In some implementations, the heating device **100** can be configured to operate in any of the three modes. For example, the heating device **100** can be configured to allow the user to select the mode (e.g., using a button or GUI). In some implementations, the heating device **100** can have more limited functionality. For example, the heating device **100** may be configured to operate in one or two of the modes, but not the other mode(s). For example, the heating device **100** may be configured to operate in the manual mode, but not the automatic or mixed modes.

(27) The user can generate new heating profiles in a variety of different ways. In some implementations, the user can create a new heating profile using a computing device other than the heating device **100**, such as a cell phone or laptop computer. The user can then load the newly created heating profile onto the heating device **100** (e.g., using the user device **102**). In some implementations, the user can create a new heating profile from scratch (e.g., without using another existing heating profile). In other implementations, the user can create a new heating profile by modifying an existing heating profile. For example, the user can modify an existing heating profile running on the heating device **100** (e.g., in the mixed mode) and then save the modified heating profile as a new heating profile. As another example, the user may load an existing heating profile on an external computing device, modify the loaded heating profile, and then save the modified heating profile on the heating device **100** as a new heating profile. The user may also use the heating device **100** (e.g., a user input device such as a touchscreen) to generate new heating profiles and/or modify existing heating profiles.

(28) The heating device **100** can store one or more heating profiles in memory (e.g., memory **420** of FIG. 4). The heating device **100** can update the stored heating profiles over time. For example, the heating device **100** can delete stored heating profiles and add additional heating profiles to memory. The heating device **100** can acquire heating profiles from different sources. For example, if the heating device **100** includes wired/wireless communication technology (e.g., WiFi, Bluetooth, etc.), the heating device **100** can retrieve heating profiles via the internet (e.g., from the remote server **802** of FIG. 8) and/or the user device **102**.

(29) In some implementations, the heating device **100** can include one or more sensors. The sensors may include, but are not limited to, a temperature sensor (e.g., FIG. 4), a motion sensor, an orientation sensor, and a pressure/force sensor. A temperature sensor may indicate the temperature of an area of the heating device **100** in the location of the temperature sensor. Example temperature sensors may include, but are not limited to, thermocouples, thermistors, resistance temperature detectors, and semiconductor based temperature sensors. A motion sensor may generate a motion signal that indicates an amount of motion of the heating device **100** (e.g., rotation/translation). Example motion sensors may include, but are not limited to, linear or angular accelerometers, gyroscopes, magnetometers, or integrated inertial measurement units. An orientation sensor may

generate an orientation signal that indicates the orientation of the heating device **100** (e.g., indicating a user's posture). Example orientation sensors may include, but are not limited to, linear or angular accelerometers, gyroscopes, magnetometers, or integrated inertial measurement units. A pressure/force sensor may indicate an amount of pressure/force in an area of the heating device **100**.

(30) One or more sensors may be located on or within the substrate **200**. The temperature sensors may be positioned near heating elements **204** so that the temperature indicated by the temperature sensors reflect the temperature near one or more heating elements **204**. Integrating the temperature sensors onto the substrate **200** may be beneficial in some implementations. For example, integrating a temperature sensor onto the substrate (e.g., **310** in FIG. 3C) may provide for more accurate temperature sensing at the location where heat is being delivered to the user. Additionally, or alternatively, the temperature sensors may be located farther from the heating elements, such as along with the device electronics on the substrate or off the substrate. In some implementations, a temperature sensor can be placed in contact with a user's body. For example, a temperature sensor may be embedded in the substrate or device package in contact with the user's body. As another example, a temperature sensor may be attached externally to the heating device via a wire and sandwiched between the user and the heating device during use.

(31) The orientation/motion sensors may also be included on the substrate **200** and/or along with the device electronics **300** in order to detect the orientation/motion of the heating device **100** (i.e., the user). In some implementations, an orientation/motion sensor may be included on the user device **102** (e.g., a cell phone) which may be carried by the user (e.g., in their hand or pocket) and, therefore, detect the orientation/motion of the user. In these implementations, the user device **102** may communicate with the heating device **100** so that the heating device **100** can modify heating based on the user's orientation/motion as determined by the user device **102**.

(32) The device electronics **300** may control heating based on data acquired from the sensors. For example, with respect to a temperature sensor, the device electronics **300** may control the heating device **100** to maintain a target temperature. As another example, the device electronics **300** may control the heating device **100** to maintain a temperature that is less than a threshold temperature (e.g., a maximum user comfort temperature and/or a maximum heating device temperature). With respect to the orientation/motion sensors, the device electronics **300** may change heating profiles/intensity based on a user's orientation and/or amount of motion. In a specific example, if a motion sensor detects changes indicative of user movement, the device electronics **300** may be configured to generate a greater amount of heat to alleviate discomfort resulting from movement. In a different specific example, the device electronics **300** may be configured to generate a greater amount of heat when a user is seated (e.g., as detected by the orientation/motion sensors) in order to alleviate discomfort resulting from sitting for long periods of time.

(33) The heating device **100** can determine a user status based on data acquired from one or more sensors. The heating device **100** may load different heating profiles corresponding to the different user statuses. For example, the heating device **100** may include a seated heating profile, a standing heating profile, a walking heating profile, and a running heating profile that may be loaded in response to the heating device **100** detecting a corresponding user status. In a specific example, if the heating device **100** determines that a user is seated (e.g., upright posture with little motion), the heating device **100** may load a seated heating profile. At a later time, if the heating device **100** detects that a user transitions from a seated position to walking, the heating device **100** may load the walking heating profile. The user may configure the different heating profiles for different statuses. In some cases, the user may configure the heating device **100** to cease heating during some user activities and provide heating during other activities. For example, the heating device **100** may be configured to remain in a standby state (e.g., where heating is turned off) when the user is seated, and then provide heating when the user is standing. A user may configure the heating device **100** in such a manner when the user feels little or no discomfort when seated, but then feels



discomfort when standing. Additional user statuses can include user posture, such as whether the user is upright or leaning to one side. In some implementations, instead of loading a different profile for a different status, the heating device **100** can be configured to adjust parameters of the heating profile, such as the amplitude of the heating, the frequency of heating pulses, or the phase difference between different heating zones.

(34) The heating device **100** can be configured to operate with varying degrees of autonomy with respect to a user device **102**. In some implementations, the heating device **100** can be configured to operate without any communication with the user device **102**. For example, the heating device **100** may not include wired/wireless communication technology for communicating with a user device **102**. In other implementations, the heating device **100** may be configured to communicate with the user device **102**, but operate autonomously without further communication with the user device **102**. For example, the heating device **100** may be configured to receive heating profiles from the user device **102** and then operate according to the heating profiles without additional communication with the user device **102**. In other implementations, the heating device **100** may be configured to make intermittent communication with the user device **102** and operate according to instructions and/or heating profiles received from the user device **102**. In these examples, the heating device **100** may intermittently communicate with the user device **102** to receive instructions, such as instructions for increasing/decreasing the amount of heat to be generated. Accordingly, in some cases, the user device **102** can adjust operation of the heating device **100** over time while the heating device **100** is operating (e.g., in the automatic and/or mixed mode).

(35) In some examples, the user device **102** may generate instructions based on user input received on the user device **102**, such as user input received from a GUI in FIGS. **9A-9K**. The user device **102** may then wirelessly transmit the user-input instructions to the heating device **100**. The heating device **100** may control the amount of power to the heating elements **204** based on the received user-input instructions (e.g., to increase/decrease heating).

(36) The user device **102** and heating device **100** can communicate using a variety of different communication protocols. In some implementations, communication between the user device **102** and the heating device **100** may involve pairing followed by periodic polling/updating of data. The connection between the user device **102** and the heating device **100** may be continuous (e.g., streaming data and/or control). Alternatively, the connection between the user device **102** and the heating device **100** may be intermittent (e.g. downloading of a profile and/or instructions).

(37) FIGS. **1A-16E** illustrate features of example heating devices **100**. FIGS. **1A-1C** and **10A-15** illustrate different example heating device form factors. FIGS. **2A-2F** illustrate example heating units. FIGS. **3A-3D** illustrate example heating units connected to other components, such as device electronics, a battery, and a sensor. FIG. **4** is an example functional block diagram of a heating device. FIGS. **5A-5E** illustrate example heating profiles that may run on a heating device **100**. FIGS. **6A-6C** illustrate example methods describing different heating device modes of operation. FIGS. **7A-7C** are directed to providing immediate heating. FIG. **8** illustrates a plurality of heating devices in communication with a remote server via a plurality of user devices. FIGS. **9A-9K** illustrate example GUIs on a user device that the user may interact with in order to control/monitor the heating device. FIGS. **16A-16E** illustrate example sleeves and garments that may hold the heating device.

(38) FIGS. **2A-2F** illustrate a variety of different substrates **200** having different shapes and arrangements of heating elements **204**. FIG. **2A** illustrates a variety of different substrate shapes and features, such as rectangular substrates **200-1**, a substrate including cutouts **200-2**, substrates including protrusions **200-3** (e.g., lobes), and a substrate **200-4** including strips. Although not illustrated, the substrates **200** of FIG. **2A** may include heating elements **204** (e.g., in the substrate or on one surface of the substrate).

(39) A substrate **200** may be flexible or rigid. In some implementations, the entire substrate may be flexible. Although some of the substrates **200** in FIGS. **2A-2F** are illustrated as being flexed, any of

the substrates in FIGS. 2A-2F may be flexible. Flexibility may allow the substrate to conform to the user's body during use. In other implementations, the entire substrate may be rigid. In still other implementations, the substrate may include portions that are rigid and portions that are flexible. The entire substrate may be formed from the same material in some cases. In other cases, the substrate may include portions that are formed from different materials. A flexible portion of substrate may be made rigid by reinforcing a portion of the substrate with additional material and/or different material. FIGS. 3A-3B illustrate a substrate that is partially rigid and partially flexible. The rigid portion of the substrate in FIGS. 3A-3B includes device electronics **300**.

(40) A substrate **200** can be formed from any material that is tolerant to the levels of heat generated by the heating element(s) **204** and other processing steps used to fabricate the heating unit **202** (e.g., oven reflow or wave flow soldering). Example materials may include, but are not limited to, polyester, polyimide, and silicone. In some implementations, the substrate may include a single layer of material. In other implementations, the substrate may include multiple layers of material that are bonded to one another.

(41) A single substrate **200** can include one or more heating elements **204**. The combination of substrate **200** and one or more heating elements **204** may be referred to herein as a "heating unit **202**." A heating device **100** may include one or more heating units **202**. For example, a heating device **100** may include a heating device package (e.g., FIGS. 1A, 10B, and 13C) that includes one or more heating units **202**.

(42) In some implementations, a heating element **204** may be formed from an electrical conductor that can provide resistive heating. The heating element **204** may be formed from a metallic material. Example metallic materials may include, but are not limited to, nichrome, FeCrAl alloy, cupronickel, and platinum. In implementations in which the substrate **200** includes a metallic layer, the heating element **204** may be formed by removing (e.g., etching) excess portions of the metallic layer from the substrate **200**. In these implementations, the remaining metallic layer may form the heating element **204**. In other implementations, the heating element **204** may be formed from wires that are connected to the substrate **200**. For example, the wire heating elements may be embedded in the substrate or sandwiched between two layers of the substrate. In one specific example, a heating unit **202** may include a polyimide or polyester sheet with etched metal heating elements. In another specific example, a heating unit **202** may include a wire sandwiched between two silicone layers that are vulcanized together (e.g., ½ mm thickness total). In another specific example, a heating unit **202** may include an etched metal layer sandwiched between silicone layers.

(43) The substrate **200** can include one or more heating elements **204** that can be arranged in a variety of different ways. In some implementations, a substrate **200** can include a single heating element **204** (e.g., FIG. 2B). In other implementations, a substrate **200** can include multiple heating elements **204** (e.g., FIG. 2C). The multiple heating elements **204** may be separate from one another. In other cases, any number of heating elements **204** may be connected in series and/or parallel.

(44) The heating elements **204** may have a linear and/or curved shape. Some of the heating elements **204** illustrated in the figures (e.g., FIG. 2C) are laid out in a tortuous shape in order to distribute heat along the surface of the substrate **200** that delivers heat to the user's body. In other examples, the heating elements **204** can be laid out in a circular shape (e.g., FIG. 2E) to generate a circular heating zone. It is contemplated that the heating elements **204** may be laid out in other shapes in addition to those illustrated herein.

(45) If the heating unit **202** includes multiple heating elements **204**, the multiple heating elements **204** can be arranged in a variety of different ways. In some implementations, the heating elements **204** can be arranged next to one another (e.g., FIG. 2C). In other implementations, the heating elements **204** may be arranged such that one heating element **204** surrounds another heating element **204**. In still other implementations, a heating element **204** may be intertwined with another heating element **204** in a different manner.

(46) Referring to FIG. 2B, the heating units **202** may include heating element contacts **206**. The

heating element contacts **206** are electrically coupled to the heating elements **204**. In some examples, the heating element contacts **206** may be formed from the same material as the heating element **204**. For example, the heating element contacts **206** may be the ends of wires used for heating elements **204** or etched areas fabricated along with etched heating elements **204**.

(47) The heating element contacts **206** may provide points where electrical contact (e.g., a low resistance contact) can be made with the heating element **204**. For example, the device electronics **300** may electrically couple to the heating elements **204** via heating element contacts **206**. A heating element **204** may include two or more heating element contacts **206**. In some implementations, a single heating element **204** may include heating element contacts **206** at each end of the heating element **204** (e.g., FIG. 2B). Additionally, or alternatively, a heating element **204** may include multiple heating element contacts **206** along the heating element **204** (e.g., FIG. 2D). Although the device electronics **300** may be coupled to the heating elements **204** via heating element contacts **206** and wires **208**, the device electronics **300** may be coupled to the heating elements **204** via other types of electrical coupling. For example, in some implementations, the device electronics **300** may be included on the substrate **200** and may be connected to the heating elements **204** via a continuous connection, such as a set of metal traces between the device electronics **300** and the heating elements **204**.

(48) The device electronics **300** deliver power to a heating element **204** via heating element contacts **206** for the heating elements **204**. For example, the device electronics **300** may deliver power to a single heating element **204** having two heating element contacts **206** by delivering power to the heating element **204** between the two contacts **206**. As another example, if the heating element **204** includes three contacts (e.g., FIG. 2D and FIG. 2F), the device electronics **300** may deliver power to a first portion of the heating element **204** between a first pair of heating element contacts **206** on opposite sides of the first portion of the heating element **204**. Additionally, in this example, the device electronics **300** may deliver power to a second portion of the heating element **204** between a second pair of heating element contacts **206** on opposite sides of the second portion of the heating element **204**. In this example, one of the three heating element contacts **206** is included in both the first and second pairs of heating element contacts **206**.

(49) The device electronics **300** control heat generated by the heating elements **204** by controlling the delivery of power to the heating elements **204**. For example, the device electronics **300** may control power delivered to a heating element **204** by controlling the voltage applied across the heating element **204** (i.e., between two contacts **206**). As another example, the device electronics **300** may control the power delivered to a heating element **204** by controlling the current through the heating element **204**. In some implementations, the heating device **100** (e.g., the device electronics **300**) may include maximum power delivery values, such as a threshold power/current/voltage level at which the heating device **100** may limit the delivery of power to one or more heating elements **204**.

(50) The layout of the heating elements **204** defines the heating zones. In some implementations, the shape of the substrates **200** can be configured to match the heating zones. For example, with respect to the substrate **200-3** of FIG. 2A that includes a plurality of lobes **210**, each of the lobes **210** can include one or more heating elements **204**. In this example, each of the lobes **210** may include a heating zone.

(51) In some implementations, the substrate **200** may include an adhesive layer (not illustrated). The adhesive layer can attach to the substrate **200** on one surface and adhere to the user's skin on the other surface. The skin adhesive layer may include, but is not limited to, silicone gels, acrylic adhesives, polyurethane gels, and hydrogels. The adhesive layer may include a removable cover layer that can be peeled from the adhesive layer to expose the adhesive layer. The removable cover layer may be a smooth layer that adheres to the underlying adhesive but does not adhere to the user. In some implementations (e.g., FIG. 10D), the adhesive layer and removable cover layer may be attached to the device package instead of the substrate **200** of the heating unit **202**. In some

implementations, the adhesive layer may be removable. For example, the adhesive layer may include an adhesive or other type of attachment for connecting to the substrate/package. In some implementations, the heating device **100** may include other types of adhesive layers (not shown) used in construction of the heating device **100**, such as adhesive layers that adhere different packaging components to one another.

(52) The device electronics **300** can control heat generated by the heating elements **204** based on a heating profile, user input, and/or sensor data (e.g., in the manual/automatic/mixed mode). The device electronics **300** may also perform a variety of other functions described herein. For example, the device electronics **300** can provide communication with the user device **102**, control charging of the battery **302**, and control interactions with user interface devices.

(53) The device electronics **300** can be mounted in a variety of different locations. In some implementations, the device electronics **300** can be mounted (e.g., soldered) to the substrate **200** (e.g., FIG. 3A). In FIG. 3A, the device electronics **300** are included on a portion of the substrate **304** that is more rigid than the rest of the substrate. In other implementations, the device electronics **300** may be attached to a flexible portion of the substrate.

(54) Although the device electronics **300** can be mounted to a substrate **200**, in some implementations, at least a portion of the device electronics **300** can be mounted in another location. For example, with respect to FIG. 3B, the device electronics **300** can be mounted to a printed circuit board (PCB) **306** that is external to the substrate **200**, but included in the device package. In these implementations, the PCB **306** including the device electronics **300** can be electrically coupled to the heating elements **204** via the heating element contacts **206**.

(55) In some implementations, an external PCB **306** can be wired (e.g., permanently) to the heating element contacts **206**. For example, the external PCB **306** can be soldered or otherwise connected to the heating element contacts **206** (e.g., via wires). In other implementations, as illustrated in FIGS. 3B-3D, the heating device **100** can include a heating unit connector **308** that can electrically couple the external PCB **306** to the heating elements **204**. The heating unit connector **308** can include two connection components that can be disconnected from one another so that the external PCB **306** and the heating elements **204** can be disconnected from one another. The heating unit connector **308** can include an electronics side and a heating unit side. The two sides of the connector can be connected to electrically couple the device electronics **300** and the heating elements **204**. The illustrated connector **308** is a low-profile connector, such as a Molex 36877-0004 connector. The connector **308** may have a positive-latching connector design so that the connector **308** does not become detached during use. Additionally, the connector **308** may be water-proof to allow for easy cleaning or moisture exposure during use. In some implementations, the PCB **306** can be connected to the heating elements **204** with other types of detachable connectors than those illustrated. For example, the external PCB **306** may include a socket into which the heating unit can be inserted, such as a Universal Serial Bus (USB) connection or other low profile power connector. As an additional example, the heating unit **202** may include a socket into which the external PCB wires/connectors can be inserted.

(56) The heating unit **100** may also include a battery connector **309**. The battery connector **309** can include two connection components that can be disconnected from one another so that the external PCB **306** and the battery **302** can be disconnected from one another. The battery connector **309** may include similar connectors as described with respect to the heating unit connector **308**.

(57) In implementations where the device electronics **300** are detachable from the heating unit(s) **202** (e.g., via the heating unit connector **308**), different heating units **202** having different arrangements of heating elements **204** (e.g., layout/number of heating elements) and sensors may be interchangeable with the same device electronics **300**. In other cases, a new heating unit **202** having the same arrangements as the old heating unit **202** could be swapped out (e.g., in the case the old heating unit is broken or worn out).

(58) FIGS. 3C-3D illustrate how different heating units **202** having different heating element and

sensor arrangements can be connected to the device electronics **300** via the heating unit connector **308**. In FIG. **3C**, the device electronics **300** can connect to two heating element contacts **206** for a single heating element **204**. The device electronics **300** in FIG. **3C** can also connect to a temperature sensor **310** included on the substrate **200**. In FIG. **3C**, the device electronics **300** can deliver power to the heating element **204** via the heating element contacts **206** and also determine the temperature indicated by the temperature sensor **310**.

(59) In FIG. **3D**, the device electronics **300** are connected to a heating unit **200-5** that is different than the heating unit **202-9** of FIG. **3C**. In FIG. **3D**, the heating unit **202-5** includes three heating element contacts for a single heating element, whereas the heating unit **202-9** of FIG. **3C** includes a heating element and a temperature sensor **310**. Although the heating element and sensor arrangement are different, the device electronics **300** may be configured to operate the heating units **200** of FIG. **3C** and FIG. **3D**. For example, the device electronics **300** can be configured to deliver power to the heating element of FIG. **3C** and determine the temperature indicated by the temperature sensor **310**. The device electronics **300** can then be reconfigured to deliver power to the heating element of FIG. **3D** via the three heating element contacts.

(60) In some implementations, the device electronics can deliver power to the heating elements **204** and measure temperature using the same circuits. For example, if the temperature sensor **310** is a resistive temperature sensor (e.g., a thermistor or resistance temperature detector), the device electronics **300** may include circuits that deliver power to the sensor **310** in a manner similar to the heating elements **204**, determine the resistance of the sensor **310**, and determine temperature based on the determined resistance. In other implementations, the device electronics **300** may include additional components that interface with the temperature sensor **310**, such as circuits that interface with a thermocouple or a digital temperature sensor. The device electronics **300** may include switches (e.g., discrete switches and/or switches included on a microcontroller) that may be used to reconfigure the functionality for each of the contacts. Although the figures of **3C-3D** illustrate reconfiguration of the device electronics **300** to operate with three different types of connections (e.g., heating element and sensor connections), device electronics **300** may be configured to operate while connected to any number of connections.

(61) As described with respect to FIGS. **3C-3D**, the device electronics **300** can be configured (e.g., using switches) to couple to sensors and/or heating elements **204** using the same contacts. In some implementations, the device electronics **300** may be configured to operate with a variety of different heating units **202** having a different number of contacts, a different number of heating elements **204**, different arrangements of heating elements **204**, and/or different types of sensors. The device electronics **300** may determine how to operate with different heating units **202** in a variety of different ways. In some implementations, a user may manually configure the device electronics **300** (e.g., using a GUI on the user device **102**) to operate with a specific heating unit **202**. For example, the user may enter a model number of the heating unit **202** into the GUI that indicates to the user device **102** and/or heating device **100** how to configure the device electronics **300** for operating the specific heating unit **202**. In some implementations, the device electronics **300** may automatically detect the specific heating unit **202** attached to the device electronics **300** and then correctly operate the specific heating unit **202**. The device electronics **300** may automatically detect the heating unit **202** in a variety of ways, such as via applying test voltage/current to determine heating element arrangement/resistance and whether a sensor is attached. In some cases, a heating unit **202** may include an identification circuit (e.g., a ROM) that indicates details of the heating unit **202** to the device electronics **300**, such as the number of heating elements **204**, the arrangement of heating elements **204**, and the number/arrangement of sensors. The device electronics **300** may determine the configuration of the heating unit **202** and how to operate the heating unit based on communication with the identification circuit (e.g., by reading the ROM).

(62) FIG. **1C** and FIG. **4** illustrate a heating device in communication with a user device (e.g., a cell

phone). The device electronics **300** can include wireless/wired communication technology that communicates with the user device **102**. As described herein with respect to FIG. **8**, the user device **102** can communicate with remote computing devices **802** via a network **804**, such as the internet. The user device **102** can also provide a variety of functionality with respect to the heating device **100**. In some implementations, the user device **102** may generate a GUI (e.g., FIGS. **9A-9K**) that the user may use to perform a variety of different operations with respect to the heating device **100**. For example, the user may interact with the GUI to control heating of the heating device **100**. In some examples, the user may interact with GUI element controls to control heating. In other examples, the user may select a heating profile and upload the heating profile to the heating device **100** using the GUI. The user may select a profile on the heating device **100** to run, select a heating profile from the user device **102** to load onto the heating device **100**, and/or retrieve a heating profile from a remote server **802** to run on the heating device **100**. The user may also monitor various heating device parameters, such as the battery status, the currently running heating profile (e.g., a heating map), and the remaining time for which the heating device **100** may run the heating profile. Additional features of the user device **102**, heating device **100**, and aspects of communication between the devices **100**, **102** are described herein.

(63) FIG. **4** is a functional block diagram of an example heating device **400**. The various modules included in the heating device **400** represent functionality (e.g., circuits and other components) included in the heating devices **100**. Modules of the present disclosure may include any discrete and/or integrated electronic circuit components that implement analog and/or digital circuits capable of producing the functions attributed to the modules herein. For example, the modules may include analog circuits (e.g., amplification circuits, filtering circuits, analog/digital conversion circuits, and/or other signal conditioning circuits). The modules may also include digital circuits (e.g., combinational or sequential logic circuits, memory circuits, etc.). Memory may include any volatile, non-volatile, magnetic, or electrical media, such as a random access memory (RAM), read-only memory (ROM), non-volatile RAM (NVRAM), electrically-erasable programmable ROM (EEPROM), Flash memory, or any other memory device. Furthermore, memory may include instructions that, when executed by one or more processing circuits, cause the modules to perform various functions attributed to the modules herein. The device electronics **300** of the heating devices **100**, **400** described herein are only example device electronics. As such, the types of electronic components used to implement the device electronics may vary based on design considerations.

(64) The functions attributed to the modules herein may be embodied as one or more processors, hardware, firmware, software, or any combination thereof. Depiction of different features as modules is intended to highlight different functional aspects and does not necessarily imply that such modules must be realized by separate hardware or software components. Rather, functionality associated with one or more modules may be performed by separate hardware or software components, or integrated within common or separate hardware or software components.

(65) The heating device **400** includes a processing module **402** (e.g., a processor and/or microcontroller), a communication module **404**, an interface module **406**, a power module **408**, a heating control module **410**, and a temperature sensing module **412**. The heating device **400** may also include a battery **414**, heating elements **416-1**, **416-2**, . . . , **416-N**, and one or more sensors (e.g., a temperature sensor **418**). The processing module **402** communicates with the modules included in the heating device **400**. For example, the processing module **402** may transmit/receive data to/from the modules and other components of the heating device **400**. As described herein, the modules may be implemented by various circuit components. Accordingly, the modules may also be referred to as circuits (e.g., a communication circuit, temperature sensing circuit, heating control circuit, interface circuit, and power circuit).

(66) The processing module **402** may communicate with the memory **420**. The memory **420** may include computer-readable instructions that, when executed by the processing module **402**, cause

the processing module **402** to perform the various functions attributed to the processing module **402** herein. The memory **420** may include any volatile, non-volatile, magnetic, or electrical media, such as RAM, ROM, NVRAM, EEPROM, Flash memory, or any other digital media. In some implementations, the processing module **402** may include a microcontroller which may include additional features associated with other modules, such as an integrated Bluetooth Low Energy transceiver.

(67) The temperature sensing module **412** is electrically coupled to the temperature sensor **418**. The temperature sensor **418** indicates the temperature in the area in which the temperature sensor **418** is located. The temperature sensing module **412** may determine the temperature in the location of the temperature sensor **418**. In some implementations, the temperature sensor **418** may generate a temperature signal that indicates the temperature in the area. For example, the temperature sensor **418** may generate a digital signal that the temperature sensing module **412** may use to determine the temperature. As another example, if the temperature sensor **418** is a passive thermistor, the temperature sensing module **412** may measure a current/voltage generated by the temperature sensor **418** and determine the temperature based on the measured current/voltage.

(68) The interface devices **422** may include user-feedback devices and/or user input devices. For example, user-feedback devices may include, but are not limited to, a display (e.g., a touchscreen display), vibration devices, lighting devices (e.g., LEDs), and a speaker. The interface module **406** can control the user-feedback devices. For example, the interface module **406** may include display control/driver circuits, vibration control circuits, LED control circuits, speaker control circuits, and/or other control circuits. In some implementations, the processing module **402** may control the interface devices **422** via the interface module **406**. For example, the processing module **402** may generate control signals that the interface module **406** uses to control the interface devices **422**. For example, the interface module **406** may include circuits that deliver power/data to the display/vibration/lighting devices, while the processing module **402** controls the delivery of power/data to the display/vibration/lighting devices.

(69) Example user input devices include, but are not limited to, buttons (e.g., manual buttons and/or capacitive touch sensors), switches, and a touchscreen. The interface module **406** may include circuits for receiving user input signals from the user input devices. The processing module **402** may receive the user input signals from the interface module **406** and take a variety of actions based on the user input signals. For example, the processing module **402** may detect a user pushing an on/off button and then power on (i.e., turn on) the heating device **100** in response to detection of the button push. As another example, the processing module **402** may detect a user pushing an on/off button while the heating device **100** is powered on. In this example, the processing module **402** may power off (i.e., turn off) the heating device **100** in response to detection of the button push. As another example, the processing module **402** may detect a user pushing a heating control button (e.g., +/- buttons) and then increment/decrement the heat generated by the heating elements **416** (or temperature setting) based on detection of the button push.

(70) The communication module **404** can include circuits that provide wired and/or wireless communication with the user device **102**. In some implementations, the communication module **404** can include wired communication circuits, such as USB communication circuits. In some implementations, the communication module **404** can include wireless communication circuits, such as Bluetooth circuits and/or WiFi circuits.

(71) Using the communication module **404**, the heating device **400** and the user device **102** can communicate with each other. The processing module **402** can transmit/receive data to/from the user device **102** via the communication module **404**. Example data may include heating profiles and other information requests, such as status updates (e.g., charging status, battery charge level, and/or heating device configuration settings). The processing module **402** can also receive instructions/commands from the user device **102** (e.g., user-input instructions), such as instructions to increase/decrease heating. In some implementations, the processing module **402** can receive

instructions/commands from the user device **102** to power on or power off the heating device **100**. For example, the user device **102** may transmit a power-on/power-off instruction to power on/off the heating device **100**. In some implementations, the processing module **402** (e.g., a microcontroller) may include circuits that provide wired/wireless communication (e.g., USB/Bluetooth). In some implementations, the user device **102** can transfer update data to the heating device **400** to update the software/firmware of the heating device **400**.

(72) The heating device **400** may include a battery **414** (e.g., a rechargeable or non-rechargeable battery). An example battery may include a Lithium-Ion or Lithium-Polymer type battery, although a variety of battery options are possible. A power source (e.g., a wall adapter power cord or USB power plug) can be plugged into the power input port (e.g., FIG. **1A**) of the heating device **400** to charge the battery **414**. The heating device **400** includes a power module **408** that may control charging of the battery **414**, regulate voltage(s) of the device electronics **300**, regulate power output to the device electronics **300**, and monitor the state of charge of the battery **414**. In some implementations, the battery itself may contain a protection circuit module (PCM) that protects the battery from high current discharge, over voltage during charging, and under voltage during discharge. In some implementations, the power module **408** may include circuits configured to modulate the voltage and current into the battery **414** during charging. For example, the power module **408** may include a Microchip MCP73832 charge control IC and supporting passive components. The power module **408** may also include electro-static discharge (ESD) protection.

(73) In some implementations, the power module **408** may control charging of the heating device **400** from the user device **102**. For example, the heating device **400** may draw power from the user device **102** (e.g., a laptop or tablet), which may allow the heating device **400** to run longer. In some implementations, the power module **408** may control charging of the user device **102** from the heating device **400**. For example, the heating device **400** can deliver power to the user device **102** (e.g., a phone or tablet) to extend the battery life of the user device **102**, which the user may be using to control the heating device **400**. In some cases, if the user device **102** is in communication with the heating device **400** and the battery is running low on the user device **102**, the user device **102** may prompt the user to plug into the heating device **400** in order to charge the battery of the user device **102**. In other cases, if the user device **102** is in communication with the heating device **400** and the battery **414** is running low on the heating device **400**, the heating device **400** may prompt the user to plug the heating device **400** into the user device **102** in order to charge the battery **414** of the heating device **400** (e.g., prompt via a GUI on the user device **102**).

(74) The processing module **402** along with the heating control module **410** can control the amount of heat generated by the heating elements **416**. For example, the heating control module **410** can include electronics that control the amount of power delivered to the heating elements **416**. In one example, the heating control module **410** can include electronics that switch on/off the delivery of power to the individual heating elements **416**. As another example, the heating control module **410** can include electronics that can incrementally adjust the power delivery to the heating elements **416** (e.g., adjust current and/or voltage).

(75) The processing module **402** may control the heating control module **410** to deliver power to the heating elements **416** according to user input and/or a heating profile. In some implementations, the heating control module **410** may include metal-oxide semiconductor field-effect transistor devices (MOSFETs) (e.g., power MOSFETs) that are controlled by a gate voltage generated by the processing module **402** (e.g., a microcontroller). In implementations where MOSFET devices are used to control current through the heating elements **416**, the MOSFETs may be controlled via pulse-width modulation (PWM) signals or on/off commands generated by the processing module **402** (e.g., microcontroller).

(76) The processing module **402** may control the heating control module **410** in a variety of different modes (e.g., a manual mode, automatic mode, and mixed mode). In the manual mode, the processing module **402** may control the heating control module **410** to deliver power based on user



input received via the user input devices on the heating device **400** and/or based on user input received from the user device **102** (e.g., via wireless communication). In the automatic mode, the processing module **402** may control the heating control module **410** to deliver power according to a heating profile. In the mixed mode, the processing module **402** may control the heating control module **410** to deliver power according to a heating profile and/or user input.

(77) The heating device **400** (e.g., memory **420**) may store heating profiles that include data indicating how to deliver power to one or more heating elements **416**. For example, the heating profiles may include data indicating the voltage (e.g., analog voltage level and/or digital average with PWM) to apply to one or more heating elements **416** over time. As another example, the heating profiles may include data indicating the current to deliver to one or more heating elements **416** over time. A heating profile may include one or more heating element profiles. A heating element profile may include data indicating how to deliver power to a single heating element **416** (e.g., between two heating element contacts). In one example, if the heating device **400** includes two heating elements **416**, the heating profile may include two heating element profiles.

(78) The heating profile (e.g., including multiple heating element profiles) can be stored in a variety of ways. In general, the data stored in the heating profile indicates to the processing module **402** and heating control module **410** how to deliver power to the heating element(s) **416**. In some implementations, the heating profile may include a plurality of digital values indicating current/voltage to be delivered to the heating element(s) **416** over time. In other examples, the heating profile may be stored as a function that yields current/voltage over time. Note that in some cases, the values stored in the heating profiles may not be voltage or current values over time, but instead may be digital values (e.g., PWM control values) used by the processing module **402** and/or the heating control module **410** to cause power to be delivered to the heating element(s) **416** over time.

(79) FIGS. 5A-5E illustrate example current versus time curves that the heating device **100** may generate according to heating profiles stored on the heating device **100**. The time values associated with the curves may vary, depending on the implementation. As such, the units of time are not explicitly noted on the graphs. In some implementations, the graphs may represent a duration on the order of seconds (e.g., 10-30 seconds in duration). In other implementations, the graphs may represent a duration on the order of minutes (e.g., 1-5 minutes). Although the Y-axis is labeled as current (i), the curves may also represent voltage/power delivered to heating elements.

(80) FIGS. 5A-5B illustrate current versus time for a single heating element. FIG. 5A illustrates delivering power to a heating element in a repetitive pattern. FIG. 5B illustrates delivering power to the heating element in a more irregular pattern. The pattern in FIG. 5B may be repeated (e.g., periodic) or non-repetitive.

(81) FIGS. 5C-5D illustrate current versus time for multiple heating elements. FIG. 5C illustrates a first and second current delivered to first and second heating elements. The first curve (solid line) may be stored as a first heating element profile for the first heating element. The second curve (broken line) may be stored as a second heating element profile for a second heating element. The heating profile for FIG. 5C may include both the first and second heating element profiles. Note that the two heating element profiles of FIG. 5C store the same current curve, but the current curves are offset in time from one another. FIG. 5D illustrates three current curves for three separate heating elements. The three curves include one solid curve and two broken curves. The three current curves are similar in shape, but offset in time from one another.

(82) In some implementations, the user may perceive the offsetting of similar curves as a wave of heat that passes across the heating device **100**. For example, if a heating device **100** has first and second heating elements next to one another and operates according to FIG. 5C, the user may first feel the heat generated by the first heating element and then feel a similar heating in the adjacent second heating element as though the heat is flowing across the heating device from one heating element to the next. In some implementations, the heating device **100** and/or user device **102** may

include controls (e.g., buttons and/or GUI elements) that the user can use to cause the time offset between two or more heating elements.

(83) FIG. 5E illustrates two different current curves for two separate heating elements. Each of the current curves in FIG. 5E may be repeated or non-repetitive. The current curves of FIG. 5E may provide an irregular pattern of heating that the user may perceive as unpredictable.

(84) FIGS. 5A-5E illustrate a variety of different heating patterns. Heating profiles may include patterns similar to, or different from, the illustrated heating patterns (e.g., regular/irregular/repetitive/non-repetitive). Additionally, a heating profile may include heating patterns that transition from repetitive to non-repetitive and/or from regular to irregular (or vice versa) over time. As described herein, a user may create new heating patterns or modify existing heating patterns while using the heating device or working offline.

(85) The duration of heating pulses (e.g., as illustrated in FIG. 5D) deliverable by the heating device may vary depending on a variety of parameters. In some implementations, the duration of heating pulses may be selected based on response times of the heating device **100** and/or the user's ability to perceive the delivered heat. For example, response times of the heating device **100** (e.g., heating elements **204**) affecting the time required to deliver heat to a user may determine the minimum duration of heating pulses. As another example, a user's ability to perceive the changes in heating being delivered may determine the minimum duration of heating pulses. For example, if a user is unable to differentiate heating pulses having a duration of less than one second from heating pulses having a duration of one second, then the minimum pulse duration may be set to one second. The ability of a user to perceive changes in heating may depend on the region of the body to which the heating device **100** is applied. Accordingly, the minimum duration of heating pulses may also depend on where the heating device **100** is to be applied. In some implementations, the pulses illustrated in FIG. 5D may have a duration on the order of a second or more, although the pulses may be set to a duration of less than a second if perceptible by the user.

(86) In some implementations, the heating device **100** can control power delivered to the heating elements **204** based on a sensed and/or estimated temperature. For example, the heating device **100** may control the delivery of power to meet a target temperature that is adjustable by the user. As another example, the heating device **100** may control the delivery of power such that the temperature remains less than a threshold temperature, such as a temperature threshold set by a user or a maximum allowable temperature (e.g., in factory settings).

(87) The heating device **100** can control the delivery of heat to the user based on the temperature of the heating device **100** in proximity to the user (e.g., the temperature of a heating zone). In some implementations, the heating device **100** can include one or more temperature sensors (e.g., **310** in FIG. 3C and **1124** in FIG. 11B) that sense temperatures in one or more heating zones. In implementations where the heating device **100** includes one or more temperature sensors, the heating device **100** can control heating based on temperature indicated by the temperature sensor.

(88) In implementations where the heating device **100** does not include a temperature sensor, the processing module **402** may estimate the temperature and control heating based on the estimated temperature. The processing module **402** may estimate the temperature based on one or more factors, such as the amount of power delivered to the heating elements **204** (e.g., voltage or current) and the amount of time over which the power has been delivered. In some implementations, the memory **420** may include temperature estimation models and/or tables that the processing module **402** may use in order to estimate temperature. For example, the models/tables may indicate an estimated temperature for power values and/or a heating profile over time. The processing module **402** may also determine the temperature based on a combination of temperature indicated by the temperature sensors and the estimated temperature. In some implementations, the memory **420** may include models/tables that use sensed temperatures to estimate additional temperatures.

(89) Although the heating device **100** can control heating based on temperature (e.g., a target temperature), in some implementations, the heating device **100** can control heating based on

alternative and/or additional parameters, such as an amount of energy/heat delivered to a user. For example, the heating device **100** may control the delivery of heat to reach a target amount or rate of energy/heat delivery. The heating device **100** may determine the amount of energy/heat delivered based on a variety of parameters, such as the delivered current/voltage and the amount of time over which the current/voltage was delivered.

(90) In some implementations, the heating device **100** may include components that indicate an amount of pressure placed on the heating device **100** (e.g., a pressure sensor). Such components may be embedded in and/or attached to the substrate **200** or device packaging. In these implementations, the heating device **100** may control heating based on the indicated pressure (e.g., as indicated by the pressure sensor). In one example, the heating device **100** may decrease an amount of heat being delivered to the user if the pressure sensing components indicate that the heating device **100** is pressed more firmly against the user, as the pressure may be indicative of a close contact and better heat transfer to the user. In another example, the heating device **100** may be configured to increase heating in response to increased pressure placed on the heating device **100**. In this example, if a user presses their hand on top of the heating device to increase pressure on the heating device **100**, the heating device **100** may respond by delivering more heat to the area.

(91) FIGS. **6A-6C** illustrate example methods describing operation of the heating device **100** in different modes of operation. FIG. **6A** illustrates an example method describing operation of the heating device **100** in the manual mode. In FIG. **6A**, the heating device **100** is initially started (e.g., using an on/off button) at block **602**. At block **604**, the heating device **100** (e.g., the device electronics **300**) sets an initial power delivery to the one or more heating elements **204**. At block **606**, the heating device **100** then waits for user input, which may include user interaction with manual controls (e.g., user input buttons) on the heating device **100** and/or user interaction with a GUI on the user device **102**. Example user input may include incrementing/decrementing heat (e.g., power delivery) to be delivered to the user. If the heating device **100** receives user input, the heating device **100** may modify power delivery to the one or more heating elements **204** according to the user input at block **608**.

(92) FIG. **6B** illustrates an example method describing operation of the heating device **100** in the automatic mode. In FIG. **6B**, the heating device is initially started at block **610**. Upon starting, the heating device **100** may load a heating profile at block **612**. For example, the heating device **100** may load a stored heating profile or may receive a heating profile from the user device **102**. At block **614**, the heating device **100** controls heat (e.g., power delivery) for one or more heating elements **204** according to the loaded heating profile.

(93) FIG. **6C** illustrates an example method describing operation of the heating device **100** in the mixed mode. In blocks **620-624** of FIG. **6C**, the heating device **100** is initially started, loads a heating profile, and controls heat according to the heating profile, as described with respect to FIG. **6B**. In the mixed mode, at block **626**, the user may modify the heating profile and/or load another heating profile onto the heating device **100**. For example, the user may provide user input that modifies the currently running heating profile via manual controls on the heating device **100** and/or GUI controls on the user device **102**. The user may also load new heating profiles to run on the heating device **100**. For example, the user may select a new heating profile stored on the heating device **100** or download a heating profile from the user device **102** to the heating device **100**. In block **628**, the heating device **100** may run the new profile until the user modifies the new profile and/or loads another heating profile.

(94) A positive heating experience for the user may include the immediate delivery of heat to the user's body at the user-desired heating level. However, the ability of the heating device **100** to deliver immediate heat may be limited due to various power delivery limitations associated with the battery and/or other device electronics. For example, limited power output from the battery may prevent the heating device **100** from immediately reaching a desired temperature and/or heat output. As another example, initial power provided to the heating elements **204** may be absorbed by

materials in the heating device **100**, which may prevent immediate heat transfer to the user. FIGS. 7A-7C are directed to techniques for operating a heating device **100** in a manner that may provide the user with a perception of immediate heat delivery without exceeding power limitations of the battery.

(95) FIG. 7A illustrates an example heating unit **202-10** including four heating elements arranged symmetrically on the substrate. The first heating element **204-7** and the second heating element **204-8** are associated with first and second heating zones, respectively. The first heating element **204-7** covers a first heating zone having a smaller area than the second heating zone covered by the second heating element **204-8**. In the example of FIG. 7A, the first heating zone is centrally located on the right side of the substrate. The second heating zone is located around the periphery of the first heating zone.

(96) In order to provide immediate heat delivery to a user, the heating device **100** may be configured to first provide an excess of power to the heating element associated with the smaller area (e.g., the first heating element **204-7**). Excess power may refer to an amount of power per area of heating zone that is greater than that desired by the user over the long term in either the first or second heating zones. The provision of excess power may rapidly heat the smaller heating zone. In some cases, the power delivery limitations of the heating device **100** may limit the ability of the heating device **100** to deliver enough power to immediately heat more heating zones, but may allow for immediate heating of a smaller heating zone. Providing the user with immediate heating in such a manner may provide a pleasing user experience. Additionally, depending on positioning of the heating device **100** on the user's body, the user may not be able to immediately perceive that only a smaller portion of the heating unit is being heated. In this case, the immediate heating may be perceived as being provided across the additional heating zones. The user may perceive immediate heating on the order of seconds (e.g., 3-5 seconds).

(97) After heating the smaller heating zone for a period of time, the heating device **100** may begin providing more power to the larger heating zone (e.g., the second heating zone) to bring the larger heating zone to the user's desired power level. The heating device **100** may also decrease power to the smaller heating zone toward the user's desired power level. After decreasing/increasing power to the smaller/larger heating zones, the smaller and larger heating zones may level out at the user's desired power level(s) for the zones.

(98) In some implementations, the heating device **100** may control the initial power delivery to the smaller heating zone based on a detected temperature associated with the smaller heating zone. For example, the heating device **100** may ramp the power delivery up to a threshold temperature (e.g., a user-specified maximum temperature) and then limit the power delivery such that the threshold temperature is not exceeded.

(99) Implementation of immediate heating may vary based on a variety of factors. Example factors that may affect implementation of immediate heating include, but are not limited to, the area of the heating zones, the amount of heating element material in the heating zones (e.g., length/diameter of wire), heating element geometry within the heating zone, the resistivity of the heating elements, and the voltage/current applied to the heating elements. Although substantially concentric heating zones are illustrated in FIG. 7A, other heating devices may include other arrangements of heating elements/zones. Although immediate heating may be implemented using two heating elements defining two heating zones, immediate heating may be implemented using other numbers of heating elements and heating zones.

(100) FIG. 7B illustrates power delivery per area of heating zone for the first heating element **204-7** and the second heating element **204-8** of FIG. 7A. In FIG. 7B, the first heating element **204-7** receives excess power to provide immediate heating to the user. The first heating element **204-7** delivers power to the user for a period of time before the second heating element **204-8** begins delivering power. Power delivered to the first heating element **204-7** is decreased upon ramping power to the second heating element **204-8**. In some implementations, the power delivery per area

can be operated as a step function (e.g., the first heating element **204-7**). The power delivery per area may also be operated in another manner (e.g., a ramp function as illustrated with respect to the second heating element **204-8**). FIG. 7B illustrates a single set of traces for two heating elements. In other implementations, the traces may converge to the same power level or cross one another. (101) FIG. 7C illustrates a method for providing immediate heating to a user. The heating device **100** may provide immediate heating in a variety of scenarios, such as when the heating device **100** is being turned on or when any burst of heat is desired. In some implementations, the user may manually set the desired power level (e.g., using the GUI). In other implementations, the desired power level may be set according to the heating profile. The method of FIG. 7C is described with respect to FIGS. 7A-7B.

(102) Initially, in block **700**, the heating device **100** delivers excess power to the first heating element **204-7** in the first heating zone. After a period of time, in block **702**, the heating device **100** starts delivery of power to the second heating element **204-8** in the second zone. In block **704**, the heating device **100** increases power to the second heating element **204-8** and decreases power to the first heating element **204-7**. In some implementations, the heating device **100** may start increasing power to the second heating element **204-8** at approximately the same time as the heating device **100** starts decreasing power to the first heating element **204-7**. In block **706**, the heating device **100** maintains the delivery of power to the first and second heating elements **204-7**, **204-8**.

(103) FIG. 8 illustrates a plurality of user devices **800-1**, **800-2**, . . . , **800-N** in communication with a remote server **802** via a network **804**. Each of the user devices **800** is in communication with a different heating device **806-1**, **806-2**, . . . , **806-N**. In FIG. 8, different users may each own/operate one of the user devices **800** and one of the heating devices **806**. The remote server **802** may be owned/operated by a party other than the users. For example, the remote server **802** may be operated by the developer/manufacturer of the heating devices **806**. In these examples, the developer/manufacturer of the heating devices **806** can provide data and programs to the remote server **802** for download by the user devices **800**.

(104) In some implementations, the remote server **802** can provide one or more programs (e.g., applications) to the user devices **800**. The one or more programs may be executed by the user devices **800** to interact with the heating devices **806**. For example, the one or more programs may generate GUIs on the user device **800** which the user may use to interact with the heating device **806** (e.g., see FIGS. 9A-9K). The user devices **800** may download and execute the one or more programs in order to interact with the heating device **806** (e.g., after the user purchases the heating device).

(105) In some implementations, the remote server **802** may store data that can be accessed by the user devices **800**. For example, the remote server **802** can store heating profiles. In some implementations, the heating profiles may be created by the owner/operator of the remote server **802** and uploaded to the remote server **802**. In another example, the heating profiles may be created by one or more of the users and uploaded to the remote server **802**. Users may download the heating profiles and load the heating profiles on their heating devices **806**. Providing the heating profiles for download may help new and existing users conveniently acquire and try new heating profiles.

(106) A heating profile may also include associated data. The associated data may include heating device information that indicates the type of heating device and/or heating unit with which the heating profile may be used. In one example, the associated data may include heating device identification numbers (e.g., model numbers) indicating the type of heating device with which the heating profile is compatible. As another example, the associated data may indicate that the heating profile should be used with a certain device/unit having a certain configuration of heating elements and/or sensors.

(107) In some implementations, the users can store user data on the remote server **802**. Example

user data may include the types of conditions for which the user uses the heating device **806** along with data indicating how effective various heating profiles are in alleviating the condition. For example, the user may upload a heating profile and additional data along with the heating profile indicating the condition for which the heating profile is used and how effective the heating profile is in alleviating the condition (e.g., a score from 1-10). The remote server **802** can make recommendations to users based on uploaded user data. For example, the remote server **802** can recommend heating profiles to users with a condition if the heating profiles are indicated as effective by other users for the same/similar conditions.

(108) FIGS. **9A-9K** illustrate example GUIs that can be displayed on the user devices. Users may use the example GUIs to: 1) control the heating device, 2) transfer data to the heating device, 3) retrieve data from the heating device, 4) transfer data to the remote server, 5) retrieve data from the remote server, and perform other operations, such as creating and modifying heating profiles. In FIGS. **9A-9K**, the user devices **900-1**, **900-2**, **900-11** include a touchscreen that overlays the GUIs. A user can interact with the GUI by interacting with the touchscreen display (e.g., touching/swiping the touchscreen display). In other implementations, a user device may include additional user inputs, such as buttons, that the user may use to control the heating device **100**. The GUIs of FIGS. **9A-9K** are only example GUIs used to illustrate various example features of the user device, and as such, do not represent an exhaustive set of features that may be provided by the user device.

(109) FIG. **9A** illustrates a GUI that the user may use to control the heating device **100** (e.g., in the manual mode). In FIG. **9A**, the GUI controls a heating device **100** having two heating zones, where each heating zone includes one or more heating elements **204**. The user can interact with two different GUI elements **902-1**, **902-2** (e.g., sliders), each of which controls heating to the different heating zones. For example, the user may slide (e.g., swipe) the slider icons **902-1**, **902-2** in the high/low direction to increase/decrease the amount of heating in the heating zones. Although sliding GUI elements are illustrated, in other implementations, other GUI elements may be used to control heating, such as graphical buttons (e.g., +/- buttons) or dials. Although GUI elements for incrementing/decrementing heat are illustrated in FIG. **9A**, other GUIs may include other controls, such as controls that control both heating zones at the same time or controls that can be used to offset the timing of different heating zones (e.g., to create a wave of heat).

(110) FIGS. **9B-9C** illustrate GUIs that provide information to the user, provide controls for the user, and acquire feedback from the user. The GUI in FIG. **9B** indicates that the user device **900-2** is connected to a heating device **100**. The GUI also gives the user various controls for the heating device **100**. For example, the user can: 1) update the active heating profile running on the heating device **100**, 2) view the active heating profile in real-time in another GUI, and 3) put the heating device **100** to sleep. Additionally, the GUI prompts the user for feedback indicating how effective the heating profile is for the user.

(111) FIG. **9C** illustrates a GUI that allows the user to select a new heating profile to run on the heating device **100** and/or modify a current heating profile. The user can select a new heating profile from other users (e.g., from the remote server **802**), select a profile saved on the user device **900-3** or remote server **802**, or select a random profile. The user can also create a new profile. In some implementations, the heating profiles can be assigned names (e.g., by the user/creator) so that the user can identify the heating profile.

(112) Additionally, the user may use motion sensors or music to generate a profile. In the case of generating profiles based on motion, the heating device **100** may detect motion patterns from the motion sensor (such as a walking motion) and/or may respond to real-time changes in the user's motion. For example, the heating device **100** may detect a regular periodic frequency within the user's motion. In response to this detected frequency, the heating device **100** can deliver pulses of heat to coincide with the user's motion. Further, in order to have the pulse of heat arrive at the user's body in-phase with his/her periodic motion, the heating device may delay/offset the pulse of heat by a given amount (based on the thermodynamic properties of the device package). In the case

of generating profiles based on music, the user may choose an audio stream on the user device **900-3** (either downloaded onto the user device **900-3** or streaming on the internet). The audio stream's contents can be processed (e.g., by an external computing device and/or the heating device **100**) to find underlying rhythms and frequency patterns, which can then be converted to heat delivery profiles. For example, if an audio stream has a melody that rises and falls at a given rate, then a profile can be created to match it. A benefit of using music as a seed for generating new profiles is that it allows for varied and diverse profiles without the need for a high degree of user input. Another example benefit of using music to generate profiles is that the user may listen to the music while experiencing the music-generated profile, so that the effect of the heating device **100** is combined with the effect of hearing the music stream.

(113) FIG. **9D** illustrates a GUI that allows a user to create a custom heating profile. In the GUI, the user may draw a heating pattern (e.g., with their finger or stylus). The user may then save the heating pattern (i.e., heating profile) and upload the heating pattern to the heating device **100**. The user can retrieve and modify the saved heating pattern at a later time.

(114) FIGS. **9E-9F** illustrate GUIs that allow a user to specify their desires for a heating profile, which may then be generated automatically by the user devices **900-5**, **900-6**. In FIG. **9E**, the user can adjust a slider left or right to indicate that they would like maximum heat or maximum heating device operating time. In general, a greater amount of heat may yield a shorter operating time when the heating device **100** is running on a battery. The GUI provides the user with the choice of whether to increase heat or increase operating time. The heating device **100** may adjust the amplitude of the current heating pattern according to the user's selection and/or select another heating pattern based on the selected operating time and/or heating.

(115) The GUI of FIG. **9F** illustrates a graph with four quadrants and a point that the user may position within the quadrants to control the intensity of heat and whether the heating is steady or in pulses. The user may drag the dot in the X direction to increase/decrease the amount of heat delivered to the user. The user may drag the dot in the Y direction to modify the rate of pulses delivered to the user. For example, dragging the dot toward the pulses portion of the Y axis may cause an increase in pulse frequency, whereas dragging the dot toward the steady portion of the Y axis may cause the pulse frequency to decrease (e.g., steady=no pulses).

(116) FIG. **9G** illustrates a GUI that conveys heating device information to the user, including: 1) the connection status between the user device **900-7** and the heating device, 2) the battery status of the heating device, and 3) the remaining operating time for the heating device at the current settings (e.g., the current heating profile). The GUI also illustrates a thermal map of the heating device that indicates the heat in different heating zones. Additionally, the GUI illustrates the heating profile running in zone **1** of the heating device. Over time, the illustrated heating profile may scroll from left to right as the heating device executes the heating profile. This allows the user to visualize the past/present/future behavior of the heating profile. The user may pause the heating device by pressing the "PAUSE HEAT" button in the GUI.

(117) FIG. **9H** illustrates a GUI that allows the user to select a desired usage (operation) time for the heating device **100**. For example, the user may slide the slider to the right/left to increase/decrease the usage time. The user device **900-8** and/or the heating device **100** may then update the current heating profile or generate a new heating profile based on the selected usage time.

(118) FIG. **9I** illustrates a GUI that allows the user to control how long a heating profile is run, how long a heating profile is turned off, and the strength of the heating profile. For example, the user may use a slider GUI element to set an on time that sets how long the heating profile should run. The user may also use a slider GUI element to set an off time that sets how long the heating device **100** should cease heating (e.g., pause) after running for the on time. The heating device **100** may then repeat the on/off behavior for the selected on/off times. The user can use a slider GUI element to set the strength (e.g., the power) associated with the heating profile, where a greater strength

may increase the power delivery for a given heating profile. The user device **900-9** may then calculate the estimated usage time for the heating device **100** according to the present battery level, the on/off times, and the strength. The GUI displays the estimated usage time to the user (e.g., 3 hours, 10 min). Modifying the on time and off time can extend/reduce the battery life (i.e., the estimated usage time) of the heating device **100**.

(119) FIG. **9J** illustrates a GUI that allows a user to tailor the motion response of the heating device **100**. As described herein, the heating device **100** can determine the motion of the user based on a motion sensor included in the heating device **100** and/or a motion sensor included in the user device **900-10**. The user may move the slider GUI element to the left or right to adjust whether the heating device **100** provides more heat while the user is stationary or moving.

(120) FIG. **9K** illustrates a GUI that acquires user information. The GUI prompts the user to describe their pain based on whether the user is stationary/moving. The GUI also prompts the user to describe their pain in terms of whether it is consistent/steady or shooting. Additionally, the GUI prompts the user to indicate their source of pain. The user information acquired via the GUI may be stored on the user device **900-11** and/or the remote server **802**. At a later time, the user may indicate which heating profile(s) are most effective in comforting the pain described in the GUI. The effectiveness of one or more heating profiles with respect to the reduction/elimination of pain described in the GUI may be stored at the remote server **802** and/or user device **900-11** and be used to make recommendations to the user or other users, as described herein.

(121) The heating device **100** can include a device package that can house one or more heating units **202**, device electronics **300**, and other components (e.g., a battery). The device package may include flexible portions that conform to a user's body. FIGS. **1A-1C** and **11A-15B** illustrate different example heating devices having different packages.

(122) FIGS. **1A-1C** and FIGS. **10A-10D** illustrate a first heating device **100-1**. The first heating device package can include one or more heating elements **204** arranged in any manner throughout the package. The first heating device **100-1** can be applied to different parts of the user's body, such as the user's back (FIG. **1C**). The first device package can include one or more belt loops **1002** that receive a belt **1004** used to hold the heating device **100-1** to a user's body. The belt **1004** is fastened together using a clasp **1005**. With respect to FIG. **10A**, the first heating device **100-1** can include a user input button **106** (e.g., an on/off button) and a power input port **104**. In FIG. **10A**, the first heating device **100-1** may have approximate dimensions of 220 mm by 90 mm, with an approximate thickness of 5 mm. Note that the dimensions included in the figures for the various heating devices **100** are only example dimensions. Heating devices having other dimensions may be fabricated.

(123) FIG. **10B** illustrates an exploded view of the first heating device **100-1**. The first heating device **100-1** includes an encapsulation **1006**. The encapsulation **1006** is formed from an encapsulation top cover **1006-1** and an encapsulation bottom cover **1006-2**. The encapsulation **1006** encapsulates components of the heating device **100-1**, such as the heating unit **202-11**, battery **302**, and device electronics (not illustrated in FIG. **10B**). The top/bottom covers **1006** in FIG. **10B** can be flexible material that can be adhered together or connected in another manner, such as fused, vulcanized, ultrasonically welded, or thermally welded. In some implementations, the encapsulation **1006** may not entirely cover the heating unit **202-11**. In these implementations, the heating unit **202-11**, or other body contact layer (e.g., a thermally conductive layer) may contact the user (e.g., body or clothing). The encapsulation **1006** may be formed from materials including, but not limited to, cloth-based or fabric materials, molded flexible plastics/rubbers, foams, and synthetic fleece material. In some implementations, the heating device **100-1** may include material/structure that imparts some rigidity to the heating device **100-1**. FIG. **10D** illustrates an additional skin adhesive layer **1008** that may be attached to the encapsulation bottom cover **1006-2**. A removable cover layer **1010** can be peeled from the adhesive layer **1008** to expose the adhesive layer **1008**.



(124) The first heating device **100-1** includes an insulation layer **1012** (e.g., an insulating foam) that may help increase the thermal efficiency of the heating device **100-1**. The insulation layer **1012** may minimize heat flowing away from the body and away from the heating device **100-1**. The insulation layer **1012** may include a thermally insulating material, such as a closed cell foam. In some implementations, the insulation layer **1012** may include material that reflects heat back toward the body. The insulation layer **1012** may also provide comfort to the user. For example, the insulation layer **1012** may include a material (e.g., a foam) that may provide a cushioning layer that conforms to the user's body and other components of the heating device **100-1**. The insulation layer **1012** may rebound after conforming during use.

(125) FIGS. **11A-11F** illustrate a second example heating device **100-2**. The heating device **100-2** includes a heating unit **202-12**. The heating unit **202-12** includes a substrate and one or more heating elements (not illustrated) embedded within the substrate. For example, the heating elements may be resistive heating elements embedded within a polymer substrate. In a more specific example, the heating unit may be a flexible circuit board including resistive heating traces. The heating elements of the heating device **100-2** may be arranged in any manner described herein.

(126) The heating device **100-2** includes a removable battery housing **1100**. The battery housing **1100** includes a battery (not shown). In some implementations, the battery housing **1100** may also include device electronics. Accordingly, the battery housing **1100** may also be referred to as a “battery and electronics housing **1100**.” The user may remove/replace the battery housing **1100**. For example, the user may replace the battery housing **1100** with other battery housings including fully charged batteries and/or batteries with different capacities. In some implementations, the battery housing **1100** may have a different geometry than that illustrated in FIGS. **11A-11F**. For example, a battery housing including a battery with a larger capacity may have a larger volume and/or different shape than that illustrated in FIGS. **11A-11F**.

(127) The battery housing **1100** mates with a receptacle **1102**. In the example of FIG. **11C**, the battery housing **1100** defines indentations **1104** that mate with retention clips **1106** included on the receptacle **1102**. The user can slide the battery housing **1100** into the receptacle **1102** along rails **1108** defined by the receptacle. The battery housing **1100** is seated and retained in position by the mating between the retention clips **1106** and indentations **1104**. When the battery housing **1100** is seated in the receptacle **1102**, the user can apply a force to the battery housing **1100** to unseat the battery housing **1100** from the receptacle **1102**. For example, the user can apply a force to the battery housing **1100** that causes the indentations **1104** to spread the retention clips **1106** and then causes the battery housing **1100** to slide out of the receptacle **1102** along the rails **1108**. The illustrated battery housing **1100** and receptacle **1102** are only one example retention mechanism for a removable battery housing. The battery housing may be attached and retained by other retention mechanisms, such as an electrical connector (e.g., friction between electrical contacts), a magnetic latch, a push/push mechanism (e.g., such as on a ballpoint pen), and/or a mechanical hook/latch (e.g., a user actuated connector).

(128) The heating device **100-2** includes an insulating foam padding **1110**. The insulating foam **1110** may be formed from a flexible insulating material, such as a closed cell foam. The insulating foam **1110** is attached to the heating unit **202-12** on the side of the heating unit **202-12** facing away from the user's body during use. The insulating foam **1110** may increase the thermal efficiency of the heating device **100-2** by minimizing heat flowing away from the body. The insulating foam **1110** may also provide comfort to the user during use. For example, the insulating foam **1110** may even out the pressure against the user if the heating device **100-2** is sandwiched between the user and an object (e.g., a chair back). Specifically, in FIG. **11A**, the insulating foam **1110** can help distribute pressure along the entire heating unit **202-12**, which may otherwise be focused under the battery housing **1100** and receptacle **1102**.

(129) The heating device **100-2** includes multiple flexible and rigid PCBs. With respect to FIG. **11D** and FIG. **11F**, the battery housing **1100** includes a first rigid PCB **1112** and a first flexible PCB

**1114** that are connected to one another. The first rigid PCB **1112** includes a power input port **104** and a battery indicator **1116**. The battery indicator **1116** may indicate a variety of statuses associated with the battery, such as the charge level of the battery and whether the battery is being charged. The first flexible PCB **1114** includes electrical traces that connect the battery to the electronics included on the first rigid PCB **1112**. The first flexible PCB **1114** also includes electrical traces that connect to the electrical contacts on the second flexible PCB **1118** (e.g., FIG. **11D**). The first rigid PCB **1112**, the first flexible PCB **1114**, and/or the battery may also include circuits similar to those included in the power module **408** of FIG. **4**.

(130) The heating device **100-2** includes a second rigid PCB **1120** and a second flexible PCB **1118** that are connected to one another. The second rigid PCB **1120** includes device electronics described herein, such as electronics included in the communication module **404**, processing module **402**, memory **420**, temperature sensing module **412**, heating control module **410**, and interface module **406**. The LED on the heating device **1122** may indicate if the heating device **100-2** is turned on, if it is connected to a user device **102** (e.g., via Bluetooth), if it is heating, and/or the state of the battery.

(131) The second flexible PCB **1118** can be attached to the heating unit **202-12** in a variety of ways. For example, the second flexible PCB **1118** can be bonded to the heating unit **202-12** using adhesive bonding, heat welding, ultrasonic welding, mechanical attachments, or other technique. The second flexible PCB **1118** includes temperature sensors **1124** that extend through openings **1126** defined in the heating unit **202-12**. The temperature sensors **1126** are positioned between the heating unit **202-12** and the user during use. The second flexible PCB **1118** also includes electrical contacts **1128** that solder to the heating elements included in the heating unit **202-12**.

(132) The second flexible PCB **1118** includes electrical contacts **1130** (e.g., 6 illustrated contacts) that electrically couple the battery and electronics included in the battery housing **1100** to the device electronics included on the second flexible PCB **1118** and the second rigid PCB **1120**. For example, the contacts **1130** may deliver power from the battery to the second flexible PCB **1118** and the second rigid PCB **1120**. The electrical contacts **1130** may also provide for communication between components included in the battery housing **1100** and components on the receptacle side of the heating device **100-2**. For example, the contacts **1130** may allow electronics on the second rigid PCB **1120** to determine the battery serial number/ID, the battery size, the state of charge, the battery temperature, the battery usage time, and other data.

(133) The arrangement of PCBs and device electronics described with respect to FIGS. **11A-11F** is only one example arrangement of PCBs and device electronics. In other examples, the heating device **100-2** may include other arrangements of PCBs and device electronics. For example, the heating device **100-2** may include other arrangements of flexible and/or rigid PCBs. As another example, the battery housing **1100** may include additional device electronics, such as device electronics included in the communication module **404**, processing module **402**, memory **420**, temperature sensing module **412**, heating control module **410**, and interface module **406**.

(134) Note that the heating device **100-2** does not include a manual user input button. For example, the heating device **100-2** does not include an on/off button for turning the heating device **100-2** on/off. Instead of controlling the heating device **100-2** using manual buttons included on the heating device **100-2**, the user may control the heating device **100-2** via the user device **102**. For example, the user may interact with a GUI on the user device **102** to turn the heating device **100-2** on/off or place the heating device in a standby/sleep mode.

(135) FIGS. **12A-12C** illustrate a third heating device **100-3**. The third heating device package can include one or more heating elements **204** arranged in any manner throughout the package. The third heating device **100-3** can be applied to different parts of the user's body, such as the user's back (FIG. **12C**). The third device package can include one or more connectors **1200** (device connectors) that are configured to connect to a belt loop **1202** having connectors **1204** (belt connectors) that mate with the device connectors **1200** of the third device package (see FIG. **12B**).

With respect to FIG. 12A, the third heating device **100-3** can include a user input button **106** (e.g., an on/off button) and a power input port **104**. The third heating device **100-3** may have approximate dimensions of 220 mm by 90 mm, with a thickness of approximately 5 mm.

(136) The third heating device **100-3** of FIGS. 12A-12C may include similar layers as the first heating device **100-1**, such as the encapsulation layers, heating unit, and insulation layer. The arrangement of the components within the third heating device **100-3** may be different than the arrangement of components within the first heating device **100-1**. For example, the battery, user input button, and power input port of the third heating device **100-3** may be offset to one side, whereas these components are centrally located in the first heating device **100-1**. In some implementations, the third heating device **100-3** may also include an adhesive layer (not illustrated) that may be attached to the encapsulation bottom cover.

(137) FIGS. 13A-13D illustrate a fourth heating device **100-4**. The fourth heating device package can include one or more heating elements **204** arranged in any manner throughout the package. The fourth heating device **100-4** can be applied to different parts of the user's body (e.g., see FIG. 13D). The fourth device package can include one or more belt loops **1300** for receiving a belt **1301**. The belt loops **1300** of the fourth device package, which are located at the edges of the fourth device package, may be integrated with the encapsulation top cover **1302**. The fourth heating device **100-4** can include a user input button **106** (e.g., an on/off button) and a power input port. In FIG. 13B, the fourth heating device **100-4** may have approximate dimensions of 220 mm by 90 mm, with a thickness of approximately 10 mm.

(138) Referring to FIG. 13C, the fourth heating device **100-4** may include similar layers as the first heating device **100-1**, such as the encapsulation layers **1302**, **1304** and the heating unit **202-13**. The fourth heating device **100-4** also includes a shape retention element **1306** (e.g., a moldable wire or plastically deformable material) that the user can use to form the fourth heating device **100-4** into a shape that is maintained by the shape retention element **1306**. The shape retention element **1306** may be used to shape and fix the fourth heating device **100-4** to the user's body (e.g., around the shoulder in FIG. 13D, waist, arm, hand, leg, foot, neck, or head). For example, the shape retention element **1306** (e.g., the wire) may be pressed to conform to the user's body and maintain its shape so that the heating device **100-4** conforms to the user's body when the user removes their hand from the heating device **100-4**. Since the belt loops **1300** are integrated into the perimeter of the fourth heating device **100-4**, the belt loops **1300** may also conform to whatever shape the fourth heating device **100-4** takes. Although the shape retention element **1306** is included around the perimeter of the fourth heating device **100-4**, a heating device may include shape retention elements along one or more axes of the heating device.

(139) FIGS. 14A-14C illustrate a fifth heating device **100-5** having a fifth device package. The fifth device package separates different components into different pods **1400**. The pods **1400** may include different components. In some examples, one or more pods **1400** may include the battery and device electronics. In these examples, the remaining pods may include heating units. In some implementations, the heating units may be distributed throughout the full surface of the heating device **100-5** or beneath some or all of the pods **1400**. The fifth heating device **100-5** may include similar layers as the other heating devices, such as encapsulation layers, heating units, and an adhesive layer. Separation of the components into different pods **1400** may allow the heating device **100-5** to easily fold/roll in one direction. The flexibility of the fifth heating device **100-5** may help it conform to the user's body (e.g., a user's shoulder) as illustrated in FIG. 14C.

(140) FIG. 15 illustrates a sixth heating device **100-6** having a sixth device package. The sixth heating device **100-6** is shaped to conform to a female's pelvic region. The sixth heating device **100-6** may include similar layers and components as the other heating devices, such as user input buttons, device electronics, a battery, encapsulation layers, heating units, and an adhesive layer. The sixth heating device **100-6** may be flexible so that it conforms to the user's body. In some implementations, the sixth heating device **100-6** (or any other heating device) may be made from

water repellent materials.

(141) FIGS. **16A-16E** illustrate various sleeves and garments that may be configured to hold the heating devices **100** described herein. FIG. **16A** illustrates an example sleeve **1600** that holds the sixth heating device **100-6**. The sleeve **1600** of FIG. **16A** may be fabricated from a cloth material (e.g., cotton or other fabric). In some implementations, the sleeve **1600** may be fabricated from a material that spreads heat. In some implementations, the sleeve **1600** may be fabricated from a breathable material. FIG. **16B** illustrates another sleeve **1602**. The sleeve **1602** of FIG. **16B** is a weighted sleeve configured to hold the first heating device **100-1**. The weighted sleeve **1602** may apply pressure to the heating device **100-1** during use (e.g., while resting on the user).

(142) FIGS. **16C-16E** illustrate garments that are configured to hold the heating devices **100**. FIG. **16C** is a female underwear garment **1606** including a device pouch **1604** that is shaped to hold the sixth heating device **100-6** in the pelvic region. FIG. **16D** is another underwear garment **1608** including a device pouch **1610** for holding a heating device. Specifically, the garment **1608** of FIG. **16D** includes a device pouch **1610** that holds the first heating device **100-1** above the pubic region. FIG. **16E** illustrates an additional example underwear garment **1612** for a woman that includes a device pouch **1614** for holding the first heating device **100-1** in the user's lower back.

(143) Various examples have been described. These and other examples are within the scope of the following claims.

## Claims

1. A heating device comprising: a first heating element configured to deliver heat to a first portion of a user's body; a second heating element configured to deliver heat to a second portion of the user's body; one or more substrates that support the first and second heating elements; device electronics coupled to the first and second heating elements, the device electronics configured to: receive a heating profile from an external computing device, wherein the heating profile includes data indicating how power should be delivered to the first and second heating elements over a period of time; and power the first and second heating elements according to the heating profile; and a device package comprising: a motion sensor that generates a motion signal that indicates user motion; the first and second heating elements; the one or more substrates; the device electronics; a battery that provides power to the device electronics, wherein the device electronics and the battery are centrally located between the first and second heating elements; and a belt configured to wrap around the user's body.
2. The heating device of claim 1, wherein the motion sensor includes at least one of a linear accelerometer, an angular accelerometer, a gyroscope, a magnetometer, and an integrated inertial measurement unit.
3. The heating device of claim 1, wherein the device electronics are configured to power the first and second heating elements based on the user motion indicated by the motion signal.
4. The heating device of claim 1, wherein the motion signal indicates at least one of acceleration and rotation.
5. The heating device of claim 1, wherein the motion signal indicates that the user is stationary.
6. The heating device of claim 1, wherein the device electronics are configured to determine an orientation of the user based on the motion signal.
7. The heating device of claim 6, wherein the motion signal indicates the user's posture.
8. The heating device of claim 6, wherein the motion signal indicates the user's orientation is upright.
9. The heating device of claim 6, wherein the motion signal indicates the user's orientation is leaning.
10. The heating device of claim 1, wherein the motion signal indicates a type of user activity.
11. The heating device of claim 1, wherein the device electronics are configured to send data

acquired from the motion signal to the external computing device.

12. A system comprising: a non-transitory computer-readable medium comprising computer-readable instructions configured to cause an external computing device to store a heating profile; and a heating device comprising: a first heating element configured to deliver heat to a first portion of a user's body; a second heating element configured to deliver heat to a second portion of the user's body; one or more substrates that support the first and second heating elements; device electronics coupled to the first and second heating elements, the device electronics configured to: receive the heating profile from the external computing device, wherein the heating profile includes data indicating how power should be delivered to the first and second heating elements over a period of time; and power the first and second heating elements according to the heating profile; and a device package comprising: a motion sensor that generates a motion signal that indicates user motion; the first and second heating elements; the one or more substrates; the device electronics; a battery that provides power to the device electronics, wherein the device electronics and the battery are centrally located between the first and second heating elements; and a belt configured to wrap around the user's body.

13. The system of claim 12, wherein the motion sensor includes at least one of a linear accelerometer, an angular accelerometer, a gyroscope, a magnetometer, and an integrated inertial measurement unit.

14. The system of claim 12, wherein the device electronics are configured to power the first and second heating elements based on the user motion indicated by the motion signal.

15. The system of claim 12, wherein the motion signal indicates at least one of acceleration and rotation.

16. The system of claim 12, wherein the motion signal indicates that the user is stationary.

17. The system of claim 12, wherein the device electronics are configured to determine an orientation of the user based on the motion signal.

18. The system of claim 17, wherein the motion signal indicates the user's posture.

19. The system of claim 17, wherein the motion signal indicates the user's orientation is upright.

20. The system of claim 17, wherein the motion signal indicates the user's orientation is leaning.

21. The system of claim 12, wherein the motion signal indicates a type of user activity.

22. The system of claim 12, wherein the computer-readable instructions are configured to cause the external computing device to send data acquired from the motion signal to a remote server.

23. The system of claim 22, wherein the computer-readable instructions are configured to cause the external computing device to receive recommended actions for the user from the remote server, wherein the recommended actions are based on the data sent to the remote server.

---