

# US Patent & Trademark Office

## Patent Public Search | Text View

United States Patent Application Publication

20250266736

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

YANG; Hae Jun et al.

### COOLING MECHANISM FOR DRIVING MOTOR

#### Abstract

Provided is a driving motor having a cooling mechanism for directly cooling the driving motor by using cooling oil, and more particularly, a cooling mechanism for a driving motor that sprays the cooling oil onto a stator by using a snap ring to secure the stator to a motor housing.

**Inventors:** YANG; Hae Jun (Yongin-si, KR), KIM; Sang Jin (Yongin-si, KR)

**Applicant:** HYUNDAI MOBIS CO., LTD. (Seoul, KR)

**Family ID:** 1000008480122

**Assignee:** HYUNDAI MOBIS CO., LTD. (Seoul, KR)

**Appl. No.:** 19/058605

**Filed:** February 20, 2025

#### Foreign Application Priority Data

KR 10-2024-0025178

Feb. 21, 2024

#### Publication Classification

**Int. Cl.:** H02K5/20 (20060101); H02K1/16 (20060101)

**U.S. Cl.:**

**CPC** H02K5/203 (20210101); H02K1/16 (20130101);

#### Background/Summary

## CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application claims priority under 35 U.S.C. § 119 to Korean Patent Application No. 10-2024-0025178, filed on Feb. 21, 2024, in the Korean Intellectual Property Office, the disclosure of which is incorporated herein by reference in its entirety.

## TECHNICAL FIELD

[0002] The following disclosure relates to a driving motor having a cooling mechanism for directly cooling the driving motor by using cooling oil, and more particularly, to a cooling mechanism for a driving motor that sprays the cooling oil onto a stator by using a snap ring to secure the stator to a motor housing.

## BACKGROUND

[0003] A driving motor applied to an electric vehicle (EV) or a hybrid vehicle (HEV) may improve fuel efficiency from a vehicle perspective if the motor has higher output while having the same weight and size. However, in order for the driving motor to have the higher output, a current, that is, the input, may be required to be increased. However, if the current flows through a coil inside the motor, heat may occur due to coil resistance. Therefore, it is necessary to lower heat occurring in the driving motor.

[0004] Methods for cooling the coil inside the driving motor may be broadly classified into three types. A first method may be an air cooling method of using a cooling fin exposed to the outside, and a second method may be a water cooling method of indirectly cooling the coil by forming a water path in a housing or the like. A third method may be an oil-cooling method of using oil, which is an insulating material, to directly cool the coil inside the motor.

[0005] Recently, the number of cases applying a driving motor that uses a direct cooling method of using the cooling oil has increased in accordance with the continuously increasing demand for a high-efficiency and high-output driving motor for the development of a high-performance electric vehicle.

[0006] There are two types of methods for directly cooling the inside of the motor. One method is a churning-type that injects an appropriate amount of oil into the motor and pumps the oil by using a rotating body, and the other method is a spray-type that flows or sprays the oil from the top to the bottom.

[0007] As shown in FIG. 1, the spray-type may supply the oil to a cooling oil pipe **11** in order to intensively spray the cooling oil onto a stator assembly **10**, and form an oil spray hole **13** at an end of the pipe **11** to spray the oil onto a target. The sprayed oil may flow through a coil **15** of the stator assembly **10**. In this case, the sprayed oil may fall downwards because the oil flows by gravity under a condition where the motor is mounted on the vehicle.

[0008] Meanwhile, the stator assembly **10** of the driving motor may have a circular shape, and the oil sprayed from the top may thus flow only downwards, staying adjacent to the spray hole **13**, thus limiting a cooling range.

[0009] To improve this limitation/problem, a conventional technology has been publicly disclosed to include an oil guide to spray the oil by dividing the oil into several paths, thus allowing the oil flowing into the oil guide to be evenly sprayed onto the stator assembly **10**.

[0010] A conventional cooling structure of the driving motor including the oil guide as described above may further include the oil guide configuration, which acts as resistance to an oil flow, thus causing an insufficient effect on increasing cooling efficiency, and may require additional processes for manufacturing and assembling the oil guide, thereby increasing both its manufacturing cost and process cost.

## SUMMARY

[0011] An embodiment of the present disclosure is directed to providing a cooling mechanism for a driving motor, in which an oil path and a spray hole are formed in a snap ring for securing a stator inserted into a motor housing, and an oil supply groove is formed between the motor housing and

the stator for an end of the groove to communicate with the oil path of the snap ring, thereby supplying cooling oil to the stator by using the snap ring.

[0012] In one general aspect, provided is a cooling mechanism for a driving motor, the mechanism including: a cylindrical stator wound with a coil; a cylindrical motor housing having one side sealed, the other side open, and accommodating the stator; a snap ring fitted into an inner circumferential surface of the other side of the motor housing to have a radial inner side protruding inward from the inner circumferential surface of the motor housing, and securing the other side of the stator by having one surface protruding and in contact with a circumference of the other surface of the stator; and an oil supply path formed between an outer circumferential surface of the stator and the inner circumferential surface of the motor housing to supply oil to the snap ring, wherein the snap ring includes an oil spray path having an upstream side fluidically communicating with the oil supply path and a downstream side passing through an inner circumferential surface of the snap ring and exposed to the other side of the stator.

[0013] The oil supply path may be formed in an axial direction, have a predetermined width in a circumferential direction, and be recessed radially inward from the outer circumferential surface of the stator.

[0014] The oil supply path may be formed in an axial direction, have a predetermined width in a circumferential direction, and be recessed radially outward from the inner circumferential surface of the motor housing.

[0015] The oil spray path may include an inflow path recessed circumferentially upward from a lower surface of the snap ring, an outflow path passing through the snap ring radially inward from the other end of the inflow path, and a spray hole formed in a downstream end of the outflow path.

[0016] The inflow path may be formed in a closed curve in a circumferential direction, or the one or more inflow paths may each have a predetermined width in the circumferential direction and be disposed to be spaced apart from each other in the circumferential direction.

[0017] The oil spray path may include an outflow path recessed upward from a radially inner lower surface of the snap ring, and a spray hole formed in a radially inner end of the outflow path.

[0018] The plurality of outflow paths may have equal spacing in a circumferential direction or have variable spacing based on a region of the stator, where heat occurs.

[0019] The outflow path may have an upstream end fluidically communicating with the inflow path, have a predetermined width in a circumferential direction, and be recessed upward from the lower surface of the snap ring.

[0020] The outflow path may have a longer recessed length toward its radial inner side.

[0021] The outflow path may have a smaller circumferential width toward its radial inner side.

[0022] Other features and aspects will be apparent from the following detailed description, the drawings, and the claims.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

[0023] FIG. 1 is a view showing the inside of a driving motor using a spray cooling method.

[0024] FIG. 2 is a partial cross-sectional perspective view of a driving motor having a cooling mechanism for a driving motor according to an embodiment of the present disclosure.

[0025] FIG. 3 is a partial enlarged perspective view showing a snap ring according to an embodiment of the present disclosure.

[0026] FIG. 4 is a partial enlarged perspective view showing a cooling mechanism for a driving motor according to a first embodiment of the present disclosure.

[0027] FIG. 5 is a partial enlarged perspective view showing an oil path of the snap ring according to the first embodiment of the present disclosure.

[0028] FIG. 6 is a partial enlarged perspective view showing an oil supply path according to a second embodiment of the present disclosure.

[0029] FIG. 7 is a partial enlarged cross-sectional perspective view showing an oil path of the snap ring according to the second embodiment of the present disclosure.

[0030] FIG. 8 is a partial enlarged perspective view showing the oil flow path of the snap ring according to the second embodiment of the present disclosure.

[0031] FIG. 9 is a partial enlarged perspective view showing the snap ring and a stator according to the second embodiment of the present disclosure.

[0032] FIG. 10 is a partial enlarged cross-sectional perspective view showing an oil path of the snap ring according to a third embodiment of the present disclosure.

[0033] FIG. 11 is a partial enlarged perspective view showing the oil path of the snap ring according to the third embodiment of the present disclosure.

#### DETAILED DESCRIPTION OF EMBODIMENTS

[0034] Hereinafter, an embodiment of the present disclosure is described in detail with reference to the accompanying drawings.

[0035] FIG. 2 shows a partial cross-sectional perspective view of a driving motor having a cooling mechanism for a driving motor according to an embodiment of the present disclosure. In addition, FIG. 3 shows a partial enlarged perspective view of a snap ring **300** according to an embodiment of the present disclosure.

[0036] As shown in the drawings, a cooling mechanism **1000** for a driving motor may include a cylindrical stator **100** wound with a coil, a cylindrical motor housing **200** accommodating the stator **100**, the snap ring **300** fitted into an upper inner surface of the motor housing **200** to secure an upper side of the stator **100** accommodated in the motor housing **200**, and an oil supply means for supplying oil to the snap ring **300**, although not shown in the drawings. The oil supply means may be, for example, an oil pump for circulating the oil. Therefore, the oil pumped from the oil pump may flow through a gap between the stator **100** and the motor housing **200** along a path formed in the motor housing **200** and supply the oil to the snap ring **300**.

[0037] The cylindrical motor housing **200** may have a sealed bottom and an open top.

[0038] The cylindrical stator **100** having a predetermined thickness may have the coil wound on an inner circumferential surface, and apply a current to the coil to thus rotate a rotor (not shown) disposed on an inner side of the stator **100**.

[0039] The snap ring **300** may be formed in a shape of a ring having a predetermined width in a radial direction. The snap ring **300** may have a radial inner side protruding inward from an inner circumferential surface of the motor housing **200** as its radial outer circumference fitted into a snap ring securing groove **210** recessed radially outward from the inner circumferential surface of an upper side of the motor housing **200**. In addition, the snap ring **300** may have a radially inner lower surface protruding and in contact with a circumference of an upper surface of the stator **100**.

Therefore, the stator **100** may be secured to the motor housing **200** by limiting an upward movement of the stator **100** while the stator **100** is seated on the motor housing **200**.

[0040] Here, the snap ring **300** may include an oil spray path **310** formed therein to thus receive the oil supplied to an oil supply path **400** formed between an outer circumferential surface of the stator **100** and the inner circumferential surface of the motor housing **200** to spray the oil onto a coil end part **110** on the upper side of the stator **100**.

[0041] The cooling mechanism **1000** having the above configuration is described in detail with reference to the drawings.

[0042] FIG. 4 shows a partial enlarged perspective view of the cooling mechanism **1000** for a driving motor according to a first embodiment of the present disclosure, and FIG. 5 shows a partial enlarged perspective view of the oil spray path **310** of the snap ring according to the first embodiment of the present disclosure.

[0043] As shown in the drawings, the oil supply path **400** may be formed between the inner

circumferential surface of the motor housing **200** and the outer circumferential surface of the stator **100**. The oil supply path **400** may have a predetermined width in a circumferential direction and be radially recessed inward from the outer circumferential surface of the stator **100**. Although not shown in the drawings, in another embodiment, the oil supply path may be recessed radially outward from the inner circumferential surface of the motor housing **200**.

[0044] Here, an upper end of the oil supply path **400** may be in contact with the lower surface of the snap ring **300**, and the oil spray path **310** may include an inflow path **311** recessed circumferentially upward from the lower surface of the snap ring **300**, and an outflow path **312** passing through the snap ring **300** radially inward from a downstream end of the inflow path **311**, that is, the upper end. An upstream side of the inflow path **311** may communicate with the oil supply path **400**, and distribute the oil supplied from the oil supply path **400** in the circumferential direction of the snap ring **300**. The plurality of outflow paths **312** may be disposed to be spaced apart from each other in the circumferential direction of the snap ring **300**, and may have a spray hole **315** formed in a downstream end to evenly spray the oil supplied through the inflow path **311** onto the coil end part **110** on the upper side of the stator **100**.

[0045] The outflow paths **312** may be spaced apart from each other while having equal spacing, or may be disposed more densely in a region where relatively high heat occurs, if necessary.

[0046] With the above configuration, the oil may be sprayed evenly onto the coil end part **110** on the upper side of the stator **100**, or intensively onto a specific region on the coil end part **110**, by using only the snap ring **300** without any separate oil guide.

[0047] FIG. **6** shows a partial enlarged perspective view of an oil supply path **410** according to a second embodiment of the present disclosure. In addition, FIG. **7** shows a partial enlarged cross-sectional perspective view of an oil spray path **320** of the snap ring **300** according to the second embodiment of the present disclosure, and FIG. **8** shows a partial enlarged perspective view of the oil spray path **320** of the snap ring **300** according to the second embodiment of the present disclosure. In addition, FIG. **9** shows a partial enlarged perspective view of the stator **100** and the snap ring **300** according to the second embodiment of the present disclosure.

[0048] Referring to FIG. **6**, the plurality of oil supply path **410** may be formed in a vertical longitudinal direction, recessed inward from the outer circumferential surface of the stator **100**, and disposed to be spaced apart from each other in the circumferential direction. As shown in the drawings, the plurality of oil supply paths **410** may have narrower spacing, particularly in a region where a relatively large amount of heat occurs.

[0049] In addition, referring to FIGS. **7** to **9**, the oil spray path **320** may include an inflow path **321** recessed circumferentially upward from the lower surface of the snap ring **300** and an outflow path **322** passing radially inward through the snap ring **300** from a downstream end of the inflow path **321**, that is, the upper end. The outflow path **322** disposed on the densely disposed plurality of oil supply paths **410** may have the following configuration to increase a spray flow rate and a spray distance. The outflow path **322** may have an upstream end fluidically communicating with the inflow path **321**, may have a predetermined width in the circumferential direction, and may be recessed upward from the lower surface of the snap ring **300**. In particular, the outflow path **322** may have a longer recessed length toward its radial inner side, i.e., its downstream side. That is, the outflow path **322** may have an increased vertical width toward its downstream side. Therefore, a large amount of oil supplied from the oil supply path **410** may be smoothly sprayed as a spray hole **325** formed in a downstream end of the outflow path **322** has an increased area. In addition, the outflow path **322** may have the top sloping upward toward its downstream side to thus increase the spray distance.

[0050] FIG. **10** shows a partial enlarged cross-sectional perspective view of an oil spray path **330** of the snap ring **300** according to a third embodiment of the present disclosure, and FIG. **11** shows a partial enlarged perspective view of the oil spray path **330** of the snap ring **300** according to the third embodiment of the present disclosure.

[0051] Meanwhile, the oil spray path **330** according to the second embodiment described above may have an oil flow rate reduced as the path has an increased cross-sectional area toward its downstream side. To solve this problem, the oil spray path **330** of the snap ring **300** according to the third embodiment may be configured as follows.

[0052] The oil spray path **330** may include an outflow path **332** fluidically communicating with the oil supply path **410**. Here, the outflow path **332** disposed on the densely disposed plurality of oil supply paths **410** may have the following configuration to maintain an oil spray velocity while increasing the spray flow rate and the spray distance.

[0053] The outflow path **332** may be formed on the radial inner side of the snap ring **300** and recessed upward from the lower surface of the snap ring **300**. In addition, the outflow path **332** may have a longer recessed length toward its radial inner side, i.e., its downstream side. In addition, the outflow path **322** may have a smaller circumferential width toward its downstream side. Therefore, the oil spray path **330** may directly receive the oil from the oil supply path **410** to the outflow path **332**, and maintain a cross-sectional area of the outflow path **322** to thus maintain or increase the oil spray velocity. In addition, the outflow path **322** may have a width increased again near a spray hole **335** to thus increase an oil spray area.

[0054] The cooling mechanism for a driving motor according to the present disclosure configured as above may reduce the manufacturing cost or process cost for forming the cooling mechanism by spraying the cooling oil onto the stator using the snap ring for securing the stator to the motor housing without any separate configuration for spraying the oil onto the stator.

[0055] The cooling mechanism for a driving motor according to the present disclosure may be applied to the motors having various specifications that require intensive cooling at a specific location at a low cost, as the spray location of the cooling oil or a supply flow rate may be easily adjusted by modifying a design of the snap ring.

[0056] The spirit of the present disclosure should not be limited to an embodiment described above. The present disclosure may be applied to various fields and may be variously modified by those skilled in the art without departing from the scope of the present disclosure claimed in the claims. Therefore, it is obvious to those skilled in the art that these alterations and modifications fall within the scope of the present disclosure.

## Claims

1. A cooling mechanism for a driving motor, the mechanism comprising: a cylindrical stator wound with a coil and including a first side and a second side; a cylindrical motor housing having a first side sealed, a second side open, and accommodating the stator therein; a snap ring fitted into an inner circumferential surface of the second side of the motor housing to have a radial inner side protruding inward from the inner circumferential surface of the motor housing, and securing the second side of the stator by having a surface protruding and in contact with a circumference of a surface of the stator; and an oil supply path formed between an outer circumferential surface of the stator and the inner circumferential surface of the motor housing to supply oil to the snap ring through the oil supply path, wherein the snap ring includes an oil spray path having an upstream side fluidically communicating with the oil supply path and a downstream side passing through an inner circumferential surface of the snap ring and exposed to the second side of the stator.
2. The mechanism of claim 1, wherein the oil supply path is formed in an axial direction of the stator, has a predetermined width in a circumferential direction of the stator, and is recessed radially inward from the outer circumferential surface of the stator.
3. The mechanism of claim 1, wherein the oil supply path is formed in an axial direction of the stator, has a predetermined width in a circumferential direction of the stator, and is recessed radially outward from the inner circumferential surface of the motor housing.
4. The mechanism of claim 1, wherein the oil spray path includes an inflow path recessed

circumferentially upward from a lower surface of the snap ring and include first and second ends, an outflow path passing through the snap ring radially inward from the second end of the inflow path, and a spray hole formed in a downstream end of the outflow path.

**5.** The mechanism of claim 4, wherein the inflow path is formed in a closed curve in a circumferential direction of the stator.

**6.** The mechanism of claim 4, wherein the inflow path is in plural, and wherein the plurality of inflow paths each have a predetermined width in the circumferential direction and are disposed to be spaced apart from each other in the circumferential direction.

**7.** The mechanism of claim 4, wherein the outflow path is in plural, and wherein the plurality of outflow paths have equal spacing in a circumferential direction of the stator or have variable spacing based on a region of the stator, where heat occurs.

**8.** The mechanism of claim 4, wherein the outflow path has an upstream end fluidically communicating with the inflow path, has a predetermined width in a circumferential direction of the stator, and is recessed upward from the lower surface of the snap ring.

**9.** The mechanism of claim 8, wherein the outflow path has a longer recessed length toward a radial inner side of the snap ring.

**10.** The mechanism of claim 9, wherein the outflow path has a smaller circumferential width toward a radial inner side of the snap ring.

**11.** The mechanism of claim 9, wherein the outflow path includes a width increased near the spray hole.

**12.** The mechanism of claim 1, wherein the oil spray path includes: an outflow path recessed upward from a radially inner lower surface of the snap ring, and a spray hole formed in a radially inner end of the outflow path.

**13.** The mechanism of claim 12, wherein the oil spray path includes a sloping upward toward a downstream side thereof to thus increase spray distance.

**14.** The mechanism of claim 12, wherein the outflow path is in plural, and wherein the plurality of outflow paths have equal spacing in a circumferential direction of the stator or have variable spacing based on a region of the stator, where heat occurs.

---