

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250261829

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

UBBESEN; Line Sandahl et al.

VIDEO PROCESSING DEVICE

Abstract

A video processing apparatus includes a housing defining an interior space, the housing having first, second, third, and fourth sides and a back side extending between the first, second, third and fourth sides, the back side including a back wall having a main portion laying on a back plane, a recessed portion recessed from the back plane and defining a video connection recess, and a recessed wall extending from the main portion to the recessed portion, the recessed wall having a video connector opening, and the recessed portion having an angled surface lying at an angle of at least 5 degrees relative to the back plane; and a video output socket in the interior space and aligned with the video connector opening of the recessed wall, whereby the angled surface facilitates insertion of a video connector into the video output socket.

Inventors: UBBESEN; Line Sandahl (Holte, DK), NIELSEN; Brian (Næstved, DK), FRENGLER; Henrik (Værløse, DK), JAKOBSEN; Kasper Rieland (Roskilde, DK), CHEN; Nai-Hua (Kaohsiung City, TW)

Applicant: AMBU A/S (Ballerup, DK)

Family ID: 1000008589733

Assignee: AMBU A/S (Ballerup, DK)

Appl. No.: 19/202947

Filed: May 08, 2025

Foreign Application Priority Data

DK

PA 2020 70117

Feb. 21, 2020

Related U.S. Application Data

parent US continuation 18206929 20230607 parent-grant-document US 12324562 child US 19202947

parent US continuation 17234368 20210419 parent-grant-document US 11707181 child US

Publication Classification

Int. Cl.: **A61B1/00** (20060101); **G06F1/16** (20060101); **H04N23/50** (20230101)

U.S. Cl.:

CPC **A61B1/0005** (20130101); **A61B1/00006** (20130101); **A61B1/00018** (20130101); **G06F1/1601** (20130101); **A61B1/00009** (20130101); **H04N23/555** (20230101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation of U.S. patent application Ser. No. 18/206,929, filed Jun. 7, 2023, which is a continuation of U.S. patent application Ser. No. 17/234,368, filed Apr. 19, 2021 and issued as U.S. Pat. No. 11,707,181 on Jul. 25, 2023, which is a continuation U.S. patent application Ser. No. 16/905,859, filed Jun. 18, 2020 and issued as U.S. Pat. No. 10,980,397 on Apr. 20, 2021, which claims priority from Danish Patent Application No. PA 2020 20117, filed Feb. 21, 2020; said applications are incorporated by reference herein in their entirety. **[0002]** U.S. patent application Ser. No. 17/097,739, filed Nov. 13, 2020 and issued as U.S. Pat. No. 11,266,297 on Mar. 8, 2022, and U.S. patent application Ser. No. 16/904,245, filed Jun. 17, 2020 and issued as U.S. Pat. No. 10,835,106 on Apr. 20, 2021, claim priority from Danish Patent Application No. PA 2020 70116, filed Feb. 21, 2020, and claim related subject matter.

TECHNICAL FIELD

[0003] The disclosure relates to a video processing device operable to generate video output signals based on images obtained with a videoscope.

BACKGROUND OF THE DISCLOSURE

[0004] Medical videoscopes comprise endoscopes, colonoscopes, ear-nose-throat scopes, duodenoscopes, and any other medical device having an image sensor configured to obtain images of views of a patient. The term “patient” herein includes humans and animals. Portable medical monitors can be communicatively coupled to the medical videoscopes to receive image data therefrom and present images corresponding to the image data on a display module of the monitor.

[0005] FIG. 1A is a perspective view of a videoscope **1** comprising a handle **2** with an articulation lever **4** and an insertion tube **3** having a proximal end **3a** and a distal end **3b**. An articulation tube **5** having an image sensor **6** is disposed at distal end **3b**. The image sensor captures optical images and transmits image data corresponding to the images via a cable **12** to a connector **13**. Connector **13** is insertable into a connector port of a monitor to present graphical images corresponding to the optical images with a display module of the monitor. Movement of articulation lever **4** reorients the field of view of image sensor **6**.

[0006] Videoscopes are made for various procedures and may have different technical characteristics suited for the procedure they are designed to perform, based on the age of the device, or for other reasons. The technical characteristics, or technology, may comprise the type of image sensor included with the image sensor, whether the videoscope includes on-board data processing capabilities, whether the videoscope includes additional sensor which provide information to the monitor, potentially including more than one image sensor. The type of image

sensor may provide different capabilities, including various controls such as image inversion, image rotation, contrast, and exposure.

[0007] An endoscope is a type of a videoscope. An endoscope described in commonly owned U.S. Patent Application No. 2019/0223694 has an insertion tube with an internal working channel and a connector at the handle adapted for the attachment of a syringe. A recess is adapted to accommodate a cylindrical body of the syringe when the syringe is attached to the connector. The endoscope is adapted to perform bronchoalveolar lavage, a procedure for obtaining samples, through the working channel, of organic material from a lung segment of a patient. Commonly owned U.S. Pat. No. 10,321,804 describes an articulated tip of an endoscope. Commonly owned U.S. Pat. No. 9,220,400 describes a camera housing arranged at the distal end of the insertion tube. The camera housing is molded and contains an image sensor and a light source, e.g. LED, embedded in the material of the camera housing. The foregoing application and patents describe technical characteristics of respective videoscopes described therein and are incorporated herein by reference in their entirety.

[0008] Furthermore, portable medical monitors are used in various settings including hospital, clinics, emergency response vehicles and in the field. These settings offer differing lighting conditions which might not be optimal for a predetermined monitor position.

[0009] Based on the foregoing it is evident that a need exists for a video processing apparatus suitable for use with a variety of videoscopes and videoscope technologies in a variety of settings.

SUMMARY OF THE DISCLOSURE

[0010] The present disclosure relates to a video processing apparatus, such as a portable medical monitor.

[0011] It is an object of the present disclosure to provide a solution which at least improves the solutions of the prior art. Particularly, it is an object of the present disclosure to provide a video processing apparatus that facilitates connectivity to external devices.

[0012] In a first aspect of the disclosure, a video processing apparatus (VPA) is provided. In some embodiments according to the first aspect, the VPA comprises a housing defining an interior space of the VPA, the housing having a first side and a second side opposite the first side, a third side and a fourth side opposite the third side and orthogonal to the first side, and a back side extending between the first side, the second side, the third side and the fourth side, the back side including a back wall comprising a main portion laying on a back plane, a recessed portion recessed from the back plane and defining a video connection recess, and a recessed wall extending from the main portion to the recessed portion, the recessed wall having a video connector opening, and the recessed portion having an angled surface lying at an angle of at least 5 degrees relative to the back plane; and a video output socket in the interior space and aligned with the video connector opening of the recessed wall, whereby the angled surface facilitates insertion of a video connector into the video output socket.

[0013] In some embodiments according to the first aspect, the VPA further comprises a video output card and the video output socket is mounted on the video output card.

[0014] In some embodiments according to the first aspect, the video output card is supported by the housing parallel to the angled surface of the recessed portion of the back wall.

[0015] In some embodiments according to the first aspect, the VPA extends parallel to the first side.

[0016] In some variations of the present embodiment, the recessed portion extends from the recessed wall toward the first side of the VPA. In one example, a distance from the recessed portion to the back plane decreases in a direction from the recessed wall toward the first side of the VPA.

[0017] In some embodiments according to the first aspect, the VPA includes a handle pivotally affixed to the back wall and operable to pivot about a rotation axis, wherein the recessed wall is positioned between the rotation axis and the first side of the VPA.

[0018] In some embodiments according to the first aspect, the VPA includes a handle and the main portion of the back wall comprises grooves, the handle including arms having first ends opposite

second ends and a bar extending between and connected to the second ends of arms, wherein the grooves are sized and shaped to receive the arms of the handle, wherein the video connection recess is positioned between the grooves.

[0019] In some variations of the present embodiment, the handle is pivotally affixed to the back wall and operable to pivot about a rotation axis passing through the grooves to define first sections of the grooves on one side of the rotation axis and second sections of the grooves on an opposite side of the rotation axis, wherein the handle is pivotable about the rotation axis to a plurality of positions including a first position, in which the arms are received by the first sections of the grooves, a second position, in which the arms are received by the second sections of the grooves, and intermediate positions between the first position and the second position.

[0020] In some embodiments according to the first aspect, the video connection recess is positioned between the second sections of the grooves on the opposite side of the rotation axis.

[0021] In some embodiments according to the first aspect, the VPA further comprises an external heat sink positioned between the second sections of the grooves on the opposite side of the rotation axis and adjacent the video connection recess.

[0022] In some embodiments according to the first aspect, the recessed wall extends parallel to the first side of the VPA, and a distance from the recessed portion to the back plane decreases in a direction from the recessed wall toward the first side of the VPA.

[0023] In some embodiments according to the first aspect, the VPA comprises an external heat sink outside the internal space, an internal heat sink within the internal space, and a heat transfer bridge thermally connecting the internal heat sink and the external heat sink.

[0024] In some variations of the present embodiment, the VPA is devoid of a fan.

[0025] In some embodiments according to the first aspect, the VPA comprises a display module supported by the housing and having a display screen opposite the back plane.

[0026] In some embodiments according to the first aspect, the VPA is operable in a first orientation and in a second orientation, and the VPA includes a graphical user interface to present image data with the display module in the first orientation or the second orientation.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0027] The above-mentioned embodiments and additional variations, features and advantages thereof will be further elucidated by the following illustrative and nonlimiting detailed description of embodiments disclosed herein with reference to the appended drawings, wherein:

[0028] FIG. 1A is a perspective view of an embodiment of a videoscope;

[0029] FIG. 1B is a perspective view of an embodiment of a portable medical monitor;

[0030] FIGS. 2A-C are top, front, and bottom views of the embodiment of the portable medical monitor of FIG. 1B in a first orientation;

[0031] FIGS. 3A and 3B are perspective and side views of the embodiment of the portable medical monitor of FIG. 1B;

[0032] FIGS. 4A, 4B, and 4C are side and back views of the embodiment of the portable medical monitor of FIG. 1B;

[0033] FIGS. 5A, 5B, and 5C are back, cross-section, and expanded cross-section views of the embodiment of the portable medical monitor of FIG. 1B;

[0034] FIG. 6 is a perspective exploded view of the portable medical monitor of FIG. 1B;

[0035] FIG. 7 is a perspective view of an embodiment of a housing of the portable medical monitor of FIG. 1B supported by a support bracket;

[0036] FIGS. 8A and 8B are perspective and side views of an embodiment of a support bracket for the portable medical monitor of FIG. 1B;

[0037] FIG. **9A** is a top view of the embodiment of the support bracket of FIG. **6A**;
[0038] FIG. **9B** is a perspective view of the embodiment of the support bracket of FIG. **6A** supporting the portable medical monitor of FIG. **1B**;
[0039] FIG. **10** is a perspective view of an embodiment of a component of the support bracket of FIG. **8A**;
[0040] FIG. **11** is schematic view of a cross-section of the component of the support bracket of FIG. **10**;
[0041] FIGS. **12A** and **12B** are views of the portable medical monitor of FIG. **1B** in a first orientation and a second orientation;
[0042] FIGS. **13A**, **13B**, and **13C** are side views of an embodiment of a cable connector of a videoscope operable with the portable medical monitor of FIG. **1B**;
[0043] FIGS. **14A** and **14B** are partial views of components of the portable medical monitor of FIG. **1A**;
[0044] FIG. **15** is a perspective view of the portable medical monitor of FIG. **1B** in a partially disassembled state;
[0045] FIGS. **16A**, **16B**, and **16C** are perspective views of an embodiment of a connector ring of the portable medical monitor of FIG. **1B**;
[0046] FIG. **17** is a perspective view of the connector ring of FIGS. **16A-C** in the process of removal from the housing of the portable medical monitor;
[0047] FIGS. **18** and **19** are perspective and diagrammatic views of an embodiment of a handle position brake of the portable medical monitor of FIG. **1B**;
[0048] FIGS. **20A**, **20B**, and **20C** are perspective views of an embodiment of a video output housing recess;
[0049] FIG. **21** is a perspective view of the portable medical monitor of FIG. **1Bb** in a partially disassembled state;
[0050] FIG. **22** is a block diagram of an embodiment of portable medical video monitor module;
[0051] FIG. **23** is a block diagram of an embodiment of the portable medical video monitor of FIG. **1B** connected to three videoscopes and an external video display; and
[0052] FIG. **24** is a block diagram of another embodiment of a portable medical video monitor connected to three videoscopes and an external video display.
[0053] In the drawings, corresponding reference characters indicate corresponding parts, functions, and features throughout the several views. The drawings are not necessarily to scale and certain features may be exaggerated in order to better illustrate and explain the disclosed embodiments.

DETAILED DESCRIPTION

[0054] For the purposes of promoting an understanding of the principles of the disclosure, reference will now be made to the embodiments illustrated in the drawings, which are described below. The embodiments disclosed below are not intended to be exhaustive or limit the disclosure to the precise form disclosed in the following detailed description.

[0055] FIG. **1B** is a perspective view of an embodiment of a portable medical monitor **20** (also referred to as “monitor **20**”) in a first orientation. FIGS. **2A-C** are top, front, and bottom views of monitor **20**. As shown, monitor **20** comprises a housing **22**, a display module **24** supported by housing **22**, a handle **26**, a power button **28**, an output interface **30**, and connector ports **32**, **34**, and **36**. Monitor **20** has front and back sides. Display module **24** includes a display screen that defines the front side and electronic circuits operable to receive, and then output to the display screen, video data. The display screen may be a touch sensitive screen that also functions as a user input sensor, in which case the electronic circuits also include circuits to sense the position of the user's fingers or input device, e.g. touch screen pencil, and to output signals including indicia indicative of the location touched on the display screen.

[0056] As shown in FIG. **2C**, housing **22** includes a front housing component **57** removably attached to a back housing component **54**. A securement cover **56** is removably attached to back

housing component **54**. Securement cover **56** can be removed to expose and provide access to a number of fasteners provided to removably attach front housing component **57** to back housing component **54**. Example fasteners include screws and snap-fits.

[0057] FIGS. **3A** and **3B** are a back perspective and a side view of monitor **20**. Monitor **20** comprises support features including at least handle **26** and a latching structure **82**, described with reference to FIGS. **5A-5C**, including a pair of bracket latch receivers. Handle **26**, described with reference to FIGS. **3A-4C**, can be used to carry monitor **20** and can function as a table stand. Latching structure **82** is configured to support monitor **20** from a monitor bracket which can be clamped to an IV stand. Advantageously, the support features are positioned in a middle section of the monitor to facilitate operation of the monitor in the first and second orientations.

[0058] Rotating the monitor to place the connector ports on the right or left side may be desirable in enclosed settings, for example, which may provide limited accessibility to one or the other side. Advantageously, connector rings are provided on one side of the monitor that distinguish the right and left sides and allow a user to quickly determine which orientation the monitor is in.

[0059] Handle **26** comprises handle axles **51**, **52** pivotally securing arms **46**, **48** to housing **22**. Each handle axle is connected to the first end of one of the arms. Each handle axle traverses, at least partially, one of the grooves **42**, **44** to define a first section of the groove on one side of the handle axle and a second section of the groove on an opposite side of the handle axle. The handle is pivotable about the handle axles to a plurality of positions including a first position, in which the arms are received by the first sections of the grooves, a second position, in which the arms are received by the second sections of the grooves, and intermediate positions between the first position and the second position. Monitor **20** further includes handle position brakes (described with reference to FIGS. **18** and **19**), including the handle axles, to hold the handle in one of the positions. Housing **22** includes a body **54** and a cover **56**. Cover **56** can be removed from body **54** to provide access to fasteners which can be removed to separate body **54** from display module **24** and provide access to various internal components.

[0060] The back side, **65**, of the housing includes grooves **42**, **44** sized and shaped to receive, respectively, arms **46**, **48** of handle **26**. The back side of the housing also includes a middle section **50** (shown in FIG. **4B**) extending between the third side and the fourth side equidistantly between the first side and the second side, the middle section having a height “H” less than 4.0 centimeters, preferably less than 3.0 centimeters. A central plane C.sub.P passes through middle section **50**. Each of the arms has a first end pivotally attached via a handle axle **51**, **52** to the middle section of the housing, as described further below, and a second end opposite the first end and connected to the bar. Handle axles **51**, **52** are shown on central plane C.sub.P. Grooves **42**, **44** each have a portion **42a**, **44a** on one side of a handle axle and another portion **42b**, **44b** on the other side of the handle axle. The portions of grooves **42**, **44** are sized and shaped to receive the arms of the handle. In FIGS. **3A** and **3B** the arms of the handle are not drawn to scale.

[0061] Housing **22** also includes a video output housing recess **400** (described with reference to FIGS. **20A-C**) and a power receptacle assembly **500** (described with reference to FIGS. **14A** and **21**). Additionally, housing **22** includes an external heat sink **70**.

[0062] Housing **22** has a first side **61** and a second side **62** opposite the first side, a third side **63** and a fourth side **64** opposite the third side and orthogonal to the first side, a front side, and a back side opposite the front side. Advantageously, monitor **20** can be rotated 180 degrees from a first orientation to a second orientation. The first orientation may be referred to as the “default” orientation and the second orientation may be referred to as the “inverted” orientation. In the default, or first, orientation the external heat sink is below a ventilation grid and first side **61** is below second side **62**. In the inverted, or second, orientation first side **61** is above the second side **62**. The connector ports are on the third side. In the first orientation the third side is the left side and in the second orientation the third side is the right side. The terms “right” and “left” correspond to the sides of a viewer facing display module **24**. Accordingly, in FIGS. **3A** and **3B** the top side is the

side opposite the support structure onto which monitor **20** rests because monitor **20** is in the first orientation with connector ports **32**, **34**, and **36** on the left side.

[0063] Portable medical monitor **20** includes sensors configured to determine a change in the orientation of monitor **20** (e.g. between the first and second orientations) and a controller configured to rotate the images presented with display module **24** responsive to such rotation. The sensors and controller are described with reference to FIGS. **22** and **23**.

[0064] Referring to FIG. **3B**, monitor **20** has rounded edges. A rounded first edge **66** connects first side **61** to back side **65** and a rounded second edge **68** connects second side **62** to back side **65**. The bar of the handle is operable to support the monitor at an angle to a horizontal plane, as shown in FIG. **3B**, ranging at least between 15-75 degrees, permitting the monitor to rest on the rounded first edge in the first orientation and on the rounded second edge in the second orientation. Handle brakes, described with reference to FIGS. **18** and **19**, maintain a position of the handle to support monitor **20** at a plurality of angles relative to the support structure onto which monitor **20** lays.

[0065] In some embodiments, rounded first edge **66** has a curvature radius equal to a curvature radius of rounded second edge **68**. The curvature radius may be greater than 2.0 centimeters, and preferably greater than 2.5 centimeters.

[0066] FIGS. **4A**, **4B**, **4C**, **5A**, **5B**, and **5C** depict support features of monitor **20** including latching structure **82**, including bracket latch receivers operable to receive latches of a monitor support bracket described with reference to FIGS. **8A-9B**. FIG. **4B** illustrates the back side of monitor **20** showing the arms of handle **26** in the grooves. A ventilation grid **80** is positioned between the grooves and also between second side **62** and central plane C.sub.P.

[0067] Referring to FIG. **4B**, a heatsink **70** extends downward from middle section **50** toward first side **61**. Heat sink **70** includes a plurality of fins **72** with slots therebetween configured to extend the external surface area of heat sink **70** and thereby increase cooling capacity, as is known in the art. An aperture **74** of heat sink **70** is positioned on the middle section of the monitor. Central plane C.sub.P is equidistant between first side **61** and second side **62** and divides middle section **50** such that a first side of the middle section has a height equal to $H/2$ and a second side of the middle section has a height equal to $H/2$. As shown, an edge of heat sink **70** is aligned with an edge of middle section **50**. Generally, the latching structure comprises latch retainers **85a**, **85b** and recesses **86a**, **86b**. In one variation, the latching structure is part of heat sink **70** and is therefore secured to housing **22** when heat sink **70** is secured to housing **22**. In another variation, a portion of latching structure **82**, e.g. a centering portion, is formed with the back wall of housing **22**. Aperture **74** surrounds the portion of the latching structure **82** formed with the back wall of housing **22**. In a further embodiment, the portion of the latching structure **82** is formed in a separate device that fits between the back wall of housing **22** and heat sink **70**, as described with reference to FIG. **6**.

[0068] FIG. **5B** is a cross-sectional view of monitor **20** at central plane C.sub.P showing latching structure **82**. The handle axles comprise rotation axes lying in the center plane. FIG. **5C** is an expanded view of the cross-sectional view of latching structure **82**. As shown, heat sink **70** is positioned within a recess **83** formed in the back side of the monitor by lateral walls **81c** extending from a wall **81a** (which forms back side **65** of housing **22**) and a recessed heat sink wall **81b** connecting lateral walls **81c**. Heat sink recess **83** is sized to receive heat sink **70** therein. Heat sink **70** includes two vertical, parallel, support walls **75a**, **75b**. Support walls **75a**, **75b** include a securement portion **84a**, **84b**, and extending from the securement portions toward the center of the heat sink, a first latch retainer **85a** and a second latch retainer **85b**. A plurality of screws **76** pass through the securement portions to secure heat sink **70** to housing **22**. Between first and second latch retainers **85a**, **85b** and recessed heat sink wall **81b** of housing **22**, are a first recess **86a** and a second recess **86b**. The latch retainers **85a**, **85b** cause latches of the support bracket to retreat until the latches enter the recesses, at which time the latches are retained by the latch retainers. As shown, latching structure **82** includes a centering structure **87** comprising two vertical walls defining a cavity **88**. Cavity **88** is sized to receive a centering protrusion **168** (shown in FIGS. **8A**

and **8B**) from the monitor support bracket, which facilitates latching of the monitor onto the monitor support bracket.

[0069] FIG. **6** is a perspective exploded back view of monitor **20** illustrating a variation of the latching structure described above and FIG. **7** is a perspective view of housing **22** supported by a monitor support bracket **100**, depicted in FIGS. **8A** and **8B**. Referring to FIG. **6**, housing **22** includes video output housing recess **400** and a heat sink recess **90** defined by a plurality of walls including lateral walls **81c** extending from a back wall **81a** of housing **22** toward the internal space of monitor **20**, and a recessed heat sink wall **81b** connecting lateral walls **81c**. Recessed heat sink wall **81b** includes a through-hole **91** through which heat sink **70** is thermally connected to a heat generator located in the internal space. A latching structure centering portion **92** is shown extending from recessed heat sink wall **81b**. A heat generator can be any packaged integrated circuit that generates heat. In particular, a heat generator may be a packaged integrated circuit which may suffer a reduced life or performance unless heat is removed from it. Examples of heat generators include processors including central processing units, graphical processing units, FPGAs, other packaged circuits capable of executing processing instructions, and the like.

[0070] The handle axles comprise rotation axes lying in the center plane. In use, latches **166**, **170** from the monitor support bracket (shown in FIGS. **8A** and **8B**) pass through aperture **74**. The latches are movable between a first position and a second position and are biased to the first position. The latches include angled surfaces that contact first and second latch retainers **85a**, **85b**. During insertion the monitor is pressed toward the monitor support bracket and the latches pass through the aperture. The first latch retainer and the second latch retainer cause the two latches to temporarily move to the second position and after insertion the latches return to the first position with portions of the latches positioned in the bracket latch receivers intermediate the first latch retainer and the display module and intermediate the second latch retainer and the display module to secure the monitor to the monitor support bracket. The latches move away from each other and into first and second recesses **86a**, **86b** by operation of a biasing force.

[0071] Advantageously, heat sink **70** is manufactured from a material that is stronger than the material from which housing **22** is made, therefore heat sink **70** supports or provides support for hanging monitor **20** from the monitor support bracket. For example, heat sink **70** can be made from aluminum or other heat conductive metals, and housing **22** can be made from polymers. Additionally, placing latching structure **82** in the middle section of the monitor allows hanging the monitor in the first orientation or the second orientation with the first or second sides supported by the cradle of the support frame.

[0072] FIGS. **8A**, **8B**, **9A**, **9B**, **10**, and **11** are views of an embodiment of a support bracket **100** for monitor **20** including an articulating arm **101** and a longitudinal frame **130**. FIG. **9B** shows monitor **20** mounted on support bracket **100**. FIGS. **10** and **11** show details of longitudinal frame **130**. Articulating arm **101** includes a clamp **102** hinged to a horizontally articulating link **104** which is hinged to a vertically articulating link **106**. A knob **108** can be rotated to tighten a hinge between horizontally articulating link **104** and vertically articulating link **106** in a known manner. Clamp **102** also includes a threaded rod connected to a knob **109** which can be rotated to tightly secure clamp **102** to a support rod passing through an aperture of the clamp, in a known manner. The support rod can be an IV stand, for example.

[0073] A cable holster **110** is removably attached to clamp **102** and comprises a support wall **111** attached to the clamp, side walls **112a**, **112b** extending from the support wall, a bottom wall **113**, and an exterior wall **114** opposite the support wall and connected to the lateral walls and the bottom wall, the support wall, the side walls, the bottom wall, and the exterior wall defining a volume **118** in which a power cable of the monitor may be held. Exterior wall **114** has a slot **115** along a length thereof sized and configured to pass therethrough a portion of the power cable. A cable clip **120** and clip retainer **122** are also shown.

[0074] Longitudinal frame **130** includes a first end **131a** having a first opening **132a**, a second end

131b having a second opening **132b**, a monitor facing side **160** between the first opening and the second opening, and at least one aperture **135** disposed in the monitor facing side. A first actuator **134a** at the first end of the longitudinal frame translates through the first opening and a second actuator **134b** at the second end of the longitudinal frame translates through the second opening. Referring to FIG. 10, first and second actuators **134a**, **134b** include internal portions **134c**, **134d** which extend to contact a pair of longitudinally aligned latches **166**, **170** movable between a first position and a second position and biased to the first position. The biasing force may be provided by springs **134g** (shown in FIG. 11), for example, connecting internal portions **134e**, **134f** of the latches to the walls of the elongate member and compressible by operation of first and second actuators **134a**, **134b** to overcome the biasing force. A gap between the pair of latches is greater in the first position than the second position. Each of the pair of latches includes an internal portion **134e**, **134f** disposed within the longitudinal frame, a protruding portion **171b** (shown in FIG. 8B) connected to the internal portion and extending through the at least one aperture, and a latching portion **172b** connected to the protruding portion distally of the monitor facing side and including an angled surface **173a**, **173b**. The angled surfaces of the pair of latches are operable to move the pair of latches from the first position to the second position. The first actuator and the second actuator are also operable to move the pair of latches from the first position to the second position. The biasing member, for example a spring, moves the pair of latches from the second position to the first position.

[0075] In one variation, internal portions **134e**, **134f** of the latches are attached to internal portions **134c**, **134d** of the actuators. In another variation, internal portions **134c**, **134d** press against but are not attached to internal portions **134e**, **134f**. Internal portions **134e**, **134f** may be inserted through the opening on the monitor facing side of longitudinal frame **130**. Internal portions **134c**, **134d** may be inserted through first and second openings **132a**, **132b** or through the opening on the monitor facing side of longitudinal frame **130**. In some embodiments, internal portions **134c**, **134d** are inserted through the opening on the monitor facing side of longitudinal frame **130** and include one or more circumferential ridges provided to retain internal portions **134c**, **134d** by abutting with an internal surface of longitudinal frame **130**. The circumferential ridges do not permit insertion of internal portions **134c**, **134d** through first and second openings **132a**, **132b** in the first and second ends **131a**, **131b**.

[0076] Returning to FIGS. 8A-B and 9, a monitor cradle **180** is sized and configured to receive monitor **20**. Monitor cradle **180** includes a hanger **182** connected to the longitudinal frame and extending downwardly therefrom, a bottom wall **190** connected to the hanger and extending forwardly therefrom, and a front wall **194** extending upwardly from the bottom wall. The bottom wall has a bottom surface **192** configured to the shapes of the first and second sides of the monitor. A curved surface **193** is contiguous with bottom surface **192** and curved to match the curvature of the rounded first edge and the rounded second edge so that the monitor can be positioned in the cradle in the first orientation or the second orientation.

[0077] As described above, heat sink **70** of monitor **20** includes centering structure **87** comprising two vertical walls defining cavity **88**. Cavity **88** is sized to receive centering protrusion **168** extending from monitor facing side **160**. Centering protrusion **168** extends between latches **166** and **170** to facilitate latching of the monitor onto the monitor support bracket.

[0078] As shown, hanger **182** is affixed to monitor facing side **160** of longitudinal frame **130**. On the opposite side of monitor facing side **160** longitudinal frame **130** is affixed to articulating link **106**. A wall opening on monitor facing side **160** may be provided in longitudinal frame **130** to provide access to the latching mechanism (e.g. spring, internal portion, latches), and potentially to enable securement of vertically articulating link **106** to a rear wall of longitudinal frame **130**. Longitudinal frame **130** and monitor cradle **180** may be molded from polymeric materials.

[0079] In a variation of the present embodiment, longitudinal frame **130** is formed together with hanger **182**. For example, hanger **182** may be molded with monitor facing side **160**.

[0080] FIGS. **12A** and **12B** illustrate monitor **20** positioned in the first, or default, orientation (FIG. **12A**) and in the second, or inverted, orientation (FIG. **12B**), in both cases with connector ports **32**, **34**, **36** extending from third side **63**. A graphical image **200** corresponding to an optical image captured by the image sensor of a videoscope is presented with display module **24**. The orientation of the monitor does not change the orientation of the graphical image because the monitor senses the change in orientation and rotates the graphical image in a corresponding manner. Of course, in an alternative embodiment, connector ports **32**, **34**, **36** can be positioned to extend from fourth side **64**.

[0081] Cable connectors **202** and **204** are shown inserted into, respectively, connector ports **32** and **34**. Cable connector **202** is attached to a cable of a videoscope and cable connector **204** is attached to a cable of another videoscope, as described further with reference to FIG. **23**. In some embodiments, each cable connector and matching connector port has a visual technology indicator to ensure the technology of the videoscope is compatible with the technology of the respective connector port.

[0082] In some embodiments, alignment indicators **210**, **211**, visual and tactile, are also provided to facilitate connection of the cable connector with the connector port. The connector port may include communication lines and power conductors to provide power to energize the image sensor of the respective videoscope. The visual technology indicators and alignment indicators are described in additional detail with reference to FIGS. **15** to **17**.

[0083] In some embodiments, each cable connector and matching connector port has a visual technology indicator and alignment indicators.

[0084] Cable connectors may comprise standard cable connectors or may include technology and/or alignment indicators as shown in FIGS. **13A**, **13B**, and **13C**, which illustrate features of cable connector **204**. The features are the same in cable connector **202**. Cable connector **204** includes a connection section **220**, a middle section **230**, and a grip section **240**. Middle section **230** is positioned between connection section **220** and grip section **240**. Cable **12** extends from grip

[0085] Connection section **220** includes opposing tabs **222** provided to mate with corresponding recesses and retain cable connector **204** in place once inserted into a connector port. Middle section **230** comprises a visual alignment indicator **210**, illustratively a triangle, and a visual technology indicator **230**, illustratively a color-coded ring. Visual alignment indicator **210** and visual technology indicator **230** may have the same color. The cross-section of middle section **230** is substantially circular. Grip section **240** comprises tactile orientation indicators **242** and **244**. Tactile alignment indicator **242**, illustratively a flat surface, enables a user to place its thumb on the surface, and thereby feel the orientation of the cable connector and be able to align it with the monitor's connector ports. Tactile orientation indicator **244**, illustratively a textured surface, also allows the user to feel the texture to determine, without looking, how to hold cable connector **202** in the proper orientation relative to the monitor to thereby align the cable connector with the connector ports. As shown, the textured surface comprises a plurality of parallel grooves.

[0086] Up to this point several features of monitor **20** were described, including support features pertaining to the orientation of the monitor, and features pertaining to cable connectors and connector ports. Several components of monitor **20** can be characterized as being part of a video processing apparatus **520**, described in additional detail with reference to FIGS. **22-24**, which may but does not require the same support features because it does not include a display module. Therefore, video processing apparatus **520** includes the components of monitor **20** related to communication and manipulation of image data but not necessarily a handle or latching structure, although the handle and/or latching structure may be provided for convenience of the user. Accordingly, monitor **20** is a particular embodiment of video processing apparatus **520**.

[0087] Referring to FIGS. **14A** and **14B**, components of monitor **20** are depicted which may also be comprised by video processing apparatus **520**. These components may include a circuit board **250** and, mounted on circuit board **250**, an internal heat sink **252** thermally coupled to a first heat

generator circuit **254**, a battery **251**, a second heat generator circuit **255**, and a heat transfer bridge **256** thermally coupling internal heat sink **252** with external heat sink **70**. Heat transfer bridge **256** may comprise a sheet of copper physically attached to internal heat sink **252** with external heat sink **70**. As shown, heat transfer bridge **256** comprises a first portion positioned between internal heat sink **252** and the first heat generator circuit **254**, which may be a memory (see memory **512** in FIG. **22**), and a second portion positioned between external heat sink **70** and the second heat generator circuit, which may be an FPGA (see FPGA **514** in FIG. **22**). In another example, the first portion of heat transfer bridge **256** is sized and shaped to match, and is attached to, the finned surface of internal heat sink **252** instead of being positioned between internal heat sink **252** and the first heat generator circuit **254**. A fan **253** circulates air through the fins of heat sink **252**. Hot air may exit the internal space via ventilation grid **80**. The heat generator circuits may comprise the FPGA, a processor or central processing unit, a video graphics integrated circuit, and any other circuit integrated in a single semiconductor package and capable to processing a large number of instructions and thus generate heat. A heat generator circuit may also comprise a power regulator and/or power converter, including a DC-DC converter. A surface **258** of heat sink **70** contacts heat transfer bridge **256** which in turn contacts second heat generator circuit **255**. Thermally conductive paste or a layer of thermally conductive material may be placed between the heat generators and the heat sinks to improve thermal transfer, as is well known in the art. A plate **257** is placed on the inside of the back wall of the housing. Plate **257** has a through-hole, matching the location of through-hole **91**, through which surface **258** is accessible. Plate **257** also provides support to mount heat sink **70** since fasteners **76** pass through heat sink recess wall **81b** and are secured within the internal space of the housing through plate **257**.

[0088] In a variation of the present embodiment, fan **253** is omitted and the internal space is passively cooled by transferring some of the heat produced by the first heat generator circuit through the heat transfer bridge to the external heat sink, where the heat is dissipated. A portion of the heat is also ventilated through the ventilation grid.

[0089] In another variation of the present embodiment, fan **253** is provided and the heat transfer bridge is omitted.

[0090] In another variation of the present embodiment, only an external heat sink is provided.

[0091] Monitor **20** and video processing apparatus **520** comprise one or more connector port. The connector port may include a flexible plug hood, as described below. The flexible plug hood extends from a side of the housing of monitor **20** or video processing apparatus **520**. The flexible plug hood may, but does not have to, include an alignment indicator and/or a technology indicator.

[0092] Referring to FIGS. **15-17**, each connector port **32, 34, 36** includes a connector **263, 265** mounted on a medical device interface **262, 264**. Connectors **263** and **265** are shown mounted on, respectively, medical device interfaces **262** and **264**, and more specifically on a circuit board of each medical device interface. The medical device interfaces are removable. Each connector port **32, 34, 36** also includes a connector ring **282, 284** which, in the present embodiment, is associated with the technology of the respective medical device interface. The technology for receiving and outputting image data and for outputting power for the image sensor, lighting device, and other components of a respective videoscope can vary based on the purpose or procedure for which the videoscope is designed, the image sensor model, etc. The videoscopes may be single-use videoscopes, in which case the monitor may be the most expensive component of the video system. Providing removable medical device interfaces and providing technology indicators in the connector port and videoscope cable connectors enables use of different videoscope technologies with the same monitor and updating of the medical device interfaces to match additional or newer versions of videoscopes as they become available, therefore allowing an owner of the monitor to extend its effectiveness and useful life and to increase its value.

[0093] Referring to FIGS. **16A-16C** and **17**, connector ring **282** comprises a plug hood **282a**, an intermediate portion **282b**, and a retention portion **282d** including an alignment cavity **282d**. The

connector ring mounted on an opening in a wall of the housing. The retention portion and the plug hood are larger in cross-section than the opening in the wall of the housing in at least one radial extent, and the intermediate portion is smaller in cross-section than the opening in the wall of the housing in the at least one extent, therefore the flexible material of the connector ring can be bent to pass the connector ring through the opening until the intermediate portion traverses the opening, at which time the plug hood and the retention portion secure the connector ring in the opening. In another example the retention portion may be threaded to secure the connector ring to a threaded opening in the housing, while still including a flexible plug hood.

[0094] As shown, alignment cavity **282d** is a notch that fits over a protrusion inside the housing. The protrusion and alignment cavity cause connector ring **282** to fit within an aperture on the side of the monitor with the alignment indicator **287** in the correct radial orientation. Plug hood **282a** includes alignment indicator **287**, which may be, as shown, a notch shaped as the letter V. At least plug hood **282a** is made from a flexible material. In the present embodiment, the connector ring is made from the flexible material, for example silicone or an elastomeric polymer. The connector ring may be molded or machined. Flexibility facilitates insertion of the cable connector, or plug, through the plug hood into the connector of the medical device interface. Additionally, flexibility prevents damage to the plug hood in case the monitor or VMM is accidentally dropped or hit. Thus, because the plug hood will not be damaged by contact, it can extend further than prior art plug hoods. Additionally, flexibility facilitates “blind” (by feel, without looking) insertion of a cable connector through plug hood **282a** for coupling with a connector **263**, **265**. Altogether, the tactile and visual alignment indicators facilitate visual and blind connections, as desired, which can be made more quickly than without the indicators.

[0095] The notch of alignment indicator **287** may be surrounded by a frame **288** of material of a color different than the color of the remainder of the connector ring to highlight the position of the notch. For example, frame **288** may be white while connector ring **282** may be blue, green, or another color.

[0096] Turning attention now to the handle of monitor **20**, as described with reference to FIGS. 2A-5C, the handle can be maintained in one of many positions by a handle position brake. Referring now to FIGS. **18** and **19**, the monitor includes a handle position brake on each side. FIG. **18** illustrates an embodiment of a handle position brake **300** viewed from inside housing **22** and therefore showing the internal surface of the wall portion forming groove **42**, denoted by numeral **330** in FIG. **18**. Handle position brake **300** includes a threaded nut **302** secured to handle axle **51**, a first disk **304**, a second disk **306**, and a spring **308** between threaded nut **302** and first disk **304**, spring **308** causing a surface of the first disk to press against a surface of the second disk to create a braking force to maintain handle **26** in one of the plurality of positions as described above. An additional disk **310** is shown between spring **308** and threaded nut **302**. The surface of the first disk can be grooved and the surface of the second disk can also be grooved to increase the braking force relative to ungrooved, or flat, disk surfaces. Grooves provide one form of texturing. Other textures may be applied to increase friction between the disk's surfaces. The grooves can be distributed evenly radially, for example every 10-20 degrees, so that protrusions between each pair of grooves can fit in grooves of the opposing disk to provide a discrete position. Thus, for example, if the grooves are spaced 15 degrees apart, the brakes will have different handle positions at 15 degree intervals.

[0097] Second disk **306** comprises two keys protruding parallel to handle axle **51**. One key penetrates an aperture of a right-hand rotation stop **320** and the other penetrates an aperture of a left-hand rotation stop **322**. Each rotation stop comprises a circular portion through which handle axle **51** passes and extending from the circular portion a first arm perpendicular to handle axle **51** and a second arm extending therefrom in parallel to handle axle **51**. The rotation stops prevent rotation of second disk **306**.

[0098] A reinforcement block **332** is affixed to housing **22** on the opposite side of which handle

position brake **300** is mounted. A portion of reinforcement block **332** extends over wall **330** and between wall **330** and left-hand rotation stop **322** to reinforce wall **330**.

[0099] FIG. **19** depicts an external view of a portion of monitor **22** overlapping handle position brake **300**. A distal end of handle axle **51** opposite threaded nut **302** has a through-hole. The first end of arm **46** fits in the through-hole and is secured therein by a screw **334**. Thus, pivoting movement of arm **46** causes handle axle **51** to pivot only when the friction between the surfaces of the first and second disks **304** and **306** is overcome by the force applied to arm **46**. Otherwise, the friction holds arm **46** in its position. A distal end of the handle axle may be supported by a bushing **311**.

[0100] In some variations of the present embodiment, monitor **20** does not include a handle or a handle position brake.

[0101] In some variations of the present embodiment, monitor **20** includes a handle and a handle position brake, and the handle is not pivotally coupled to the housing of the monitor at a middle section thereof.

[0102] Turning attention now to the video output by monitor **20** or video processing apparatus **520**, a video output housing recess facilitates connection of video cables while retaining the connectors of the video cable substantially within the recess to enhance retention and prevent accidental disconnection thereof. Referring to FIGS. **20A**, **20B**, and **20C**, video output housing recess **400** is formed by lateral walls **401**, **402**, **404** and **405**, and a bottom wall **403** having an external surface **403a** and an internal surface **403b**. Connectors **420a**, **420b**, and **420c** are accessible through wall **402**. Bottom wall **403** is disposed at an angle beta which is at least 4 degrees relative to the surface of the display screen. Preferably, beta is at least and including 5-25 degrees, and even more preferably beta is at least and including 6-25 degrees. Connector **420a**, for example an HDMI connector, is also aligned at angle beta. Connector **420a** is mounted on a video output board **410**. Optionally, video output board **410** is also supported inside housing **22** at angle beta. A video plug **421** is shown in FIG. **20C** plugged into output connector **420a**. Advantageously, aligning the connector and the bottom wall of the video output housing recess enables a user to more easily connect the plugs with the connectors of the video output board. Optionally, wall **404** is curved to further facilitate manipulation of plugs with the connectors of the video output board. Wall **404** is opposite **402**. The connectors can, but do not have to be, video output connectors. Connectors can be for ethernet, coaxial, and other types of cables and the cables can provide bi-directional communications and/or power.

[0103] Another feature of monitor **20** or video processing apparatus **520** is a power receptacle assembly. Referring to FIG. **21**, a power receptacle assembly **500** comprises a power socket **501** mounted on circuit board **250** and a corresponding hole **502** in the back wall of housing **22**. A power cord plug passes through hole **502** to enter power socket **501** and through power socket **501** provides power to the circuits on circuit board **250** and the medical device interfaces.

Advantageously, this design requires or causes removal of the power cord plug before the back portion of housing **22** is removed from the front portion to, for example, swap, remove, or add, medical device interfaces, which ensures the circuits are powered down before the back portion of housing **22** is removed to provide access to the medical device interfaces. Additionally, aligning hole **502** with power socket **501** mounted on the circuit board, which can be referred to as a motherboard, eliminates additional cables in the internal space that would be required if, for example, power socket **501** were mounted on a side of the housing.

[0104] As described above, monitor **20** is advantageously operable in default and inverted orientations and can be connected to one or more medical devices, which may, but do not have to, be videoscopes. Thus, monitor **20** includes video processing circuits operable to receive image data, present a graphical user interface to allow a user to manipulate image data with a touch screen, and, optionally, output a video signal to allow remote viewing of the images presented with the touch screen.

[0105] Variations of monitor **20** can be provided with various features of monitor **20** but including other features. For example, it might not be desirable to provide a touch screen, or it might be desirable to omit a display module altogether. Omission of the display module might be beneficial to take advantage of evolving video display technologies which improve resolution and reduce cost. Provision of exchangeable medical device interfaces allows for adoption of evolving image sensor and videoscope technologies, thus use of existing or future-developed external video displays could allow presentation of higher resolution or otherwise improved video. Use of external video displays could also leverage existing capital investments. Use of wall-mounted video displays could also reduce reliance on IV poles and, generally, clutter.

[0106] Video processing circuits and other components will now be described with reference to FIGS. **22-24**. FIG. **22** depicts example components of monitor **20**. Several components are part of a VMM **21**. It should be understood that VMM **21** can, but does not have to be, a physical module independent of other components. Instead, VMM **21** is described in terms of its function to simplify description, and the components that perform the functions can be arranged in any convenient manner. Accordingly, monitor **20** includes VMM **21**, display module **24**, and, optionally, an orientation sensor **518**. The functionality of orientation sensors was described above. VMM **21**, display module **24**, and an orientation sensor **518** are supported by housing **22**, as described above. As shown, VMM **21** includes medical device interfaces **262**, **264**, and **266**. VMM **21** could include fewer medical interfaces and might include a medical device interface that is not removably coupled.

[0107] VMM **21** also includes a processor **510**, memory **512** including graphical user interface (GUI) logic **513**, a field-programmable gate array (FP GA) **514**, video output board **410**, a user interface **516**, and a microphone **517**. User interface **516** may comprise a wireless interface operable to receive user inputs via a mouse, keyboard, or other physical user input devices. Example wireless interfaces include Bluetooth and Zigbee controllers. User interface **516** may also comprise a USB port to receive a USB connector including the wireless interface or a USB connector of a wired user input device. Thus, VMM **21** provides for flexibility in receiving user inputs via various user input devices, regardless whether a display module is integrated therewith.

[0108] FPGA **514** is optionally provided because it is capable of rapid power-up (i.e. short boot-up time) and thus is useful in emergency situations. FPGAs may also be provided in the medical device interfaces for the same reasons. FPGAs process data very fast compared to other memory/instruction combinations and are re-programmable. Therefore FPGAs facilitate presentation of a live view of the images captured by the videoscope in real-time with minimal latency so that the physician observing the live view can take immediate actions even in emergency situations. As technology evolves, the functionality of FP GA **514** may be combined with processor **510**. VMM **21** is therefore not limited to the precise packaged integrated circuits described with reference to FIG. **22** but can be constructed to take advantage of design and cost targets and future video processing technologies. For example, faster/more costly memory may be used to increase graphics processing speed. Graphics processing may be provided in the FPGA or a processor that incorporates graphics processing logic may be used instead.

[0109] FIG. **23** illustrates a system including monitor **20** and three videoscopes **1a**, **1b**, **1c** communicatively coupled to monitor **20** via cables **12a**, **12b**, and **12c**. The videoscopes may comprise, for example, an endotracheal tube with an image sensor at the distal end thereof, a video laryngoscope, an endoscope, a duodenoscope, a colonoscope, an ENT scope, and any other medical device adapted for insertion into a living body and having an image sensor to capture views of body tissues. An external display device **524** is communicatively coupled to monitor **20**, for example via video output board **410** and an HDMI cable.

[0110] FIG. **24** illustrates a system including a video processing apparatus **520** including a housing **522**, VMM **21**, and ports **32**, **34**, and **36**. As described above, more or less ports can be included. Video processing apparatus **520** is communicatively coupled to external display device **524**. The

connector port(s) may include a flexible plug hood, as described above. The flexible plug hood may extend from a side of housing **522**. Any of the above-described connector port configurations may be used, including those comprising various indicators technology and orientation indicators.

[0111] In some embodiments, PVA **520** is devoid of a display module.

[0112] In some embodiments, PVA **520** is devoid of a handle pivotally attached to the back wall of the housing and of grooves sized and shaped to receive the arms of the handle.

[0113] In some embodiments, PVA **520** includes the internal and external heat sinks. In some variations of the present embodiment PVA **520** includes the heat transfer bridge. In other variations PVA **520** excludes the heat transfer bridge.

[0114] In some embodiments, PVA **520** includes the flexible connector hoods. In some variations of the present embodiments, PVA **520** includes the technology and orientation indicators referred to above. In some variations of the present embodiments, PVA **520** the connector hoods are unmarked by technology and orientation indicators.

[0115] The term “logic” as used in this patent application includes software and/or firmware executing on one or more programmable processing devices, application-specific integrated circuits, field-programmable gate arrays, digital signal processors, hardwired logic, or combinations thereof. Therefore, in accordance with the embodiments, various logic may be implemented in any appropriate fashion and would remain in accordance with the embodiments herein disclosed. Logic may comprise processing instructions embedded in non-transitory machine-readable media (e.g. memory).

[0116] GUI logic **513** comprises processing instructions to generate a GUI presented with display module **24** and/or external display device **524**. The GUI can be responsive to user inputs received via the touch screen or other user inputs. GUI logic **513** may process an output signal from orientation sensor **518** indicative of an orientation of monitor **20**, and to present the GUI in an orientation based on the signal from orientation sensor **518**.

[0117] Processor **510** receives image data from medical device interfaces **262**, **264**, and **266** and outputs video signals incorporating the GUI and image data. Image data may be referred to “live images” or “live video” if they are received substantially in real-time from the videoscopes. The video signals may be received by a memory buffer and the buffer may be read by the display module or video output card to present the GUI and images. Techniques for presenting images are well known, including techniques using buffers or mapped memory.

[0118] GUI logic **513** may present the GUI depending on the orientation signal from the orientation sensor or a user instruction to invert the view. A view corresponds to the display area of a display screen. The GUI may comprise first and second panels provided side-by-side in the view. The second panel presents live images and is positioned on the right side of the view, with the first panel positioned on the left side of the view. Even when the monitor orientation changes, the first panel remains on the left of the second panel.

[0119] The GUI may present in the first panel a small version of live images provided by a second videoscope and the user may use the GUI to switch the live images from the first and second videoscopes so that the images from the second videoscope are presented in the second panel while the images from the first videoscope are reduced and presented in the first panel. The last videoscope connected to a connector port may be shown in the second panel by default. However the views from the different videoscopes can be selected by the user with the GUI for presentation in the first or second panel or not displayed at all.

[0120] The GUI may present various icons corresponding to actions selectable by the user with any of the above-described user input devices, to for example store a copy of a live image, store a portion of video corresponding to live images, invert the views, apply correction curves to the image data to reduce overexposure, etc.

[0121] Additional examples within the scope of the disclosure are listed below.

SUPPORT BRACKET EXAMPLES

[0122] 1. A support bracket for a portable monitor, the support bracket comprising: [0123] a longitudinal frame having a first end opposite a second end, a first opening in the first end and a second opening in the second end, the longitudinal frame also including a monitor facing wall having at least one opening between the first end and the second end; [0124] a first actuator accessible through the first opening and sized and shaped to translate in the first end; [0125] a second actuator accessible through the second opening and sized and shaped to translate in the second end; [0126] a first latch extending through the at least one opening and including a slanted surface, the first latch biased to a first position in which the first latch is nearer the first end than in a second position, wherein force applied to the first actuator causes the first actuator to translate the first latch to the second position, and wherein force applied to the slanted surface perpendicularly to the monitor facing wall translates the first latch to the second position; [0127] a second latch extending through the at least one opening and including a slanted surface, the second latch biased to a first position in which the first latch is nearer the second end than in a second position, wherein force applied to the second actuator causes the second actuator to translate the second latch to the second position, and wherein force applied to the slanted surface perpendicularly to the monitor facing wall translates the second latch to the second position.

[0128] 2. The support bracket of example 1, wherein each of the first latch and the second latch includes an internal portion disposed within the longitudinal frame.

[0129] 3. The support bracket of example 2, wherein the internal portion of the first latch is connected to the first actuator and the internal portion of the second latch is connected to the second actuator.

[0130] 4. The support bracket of any one of examples 1 to 3, further comprising a spring connected to the internal portion of the first latch to bias the first latch to the first position.

[0131] 5. The support bracket of example 1, further comprising a hanger connected to the longitudinal frame and extending downwardly therefrom, a bottom wall connected to the hanger, and a front wall extending upwardly from the bottom wall, wherein the hanger, the bottom wall, and the front wall define a cradle sized and shaped to receive the portable monitor.

[0132] 6. The support bracket of example 5, wherein the hanger has a top portion including a first opening and a second opening, wherein the at least one opening is sized and shaped to receive the top portion of the hanger, and wherein the first latch extends through the first opening and the second latch extends through the second opening when the hanger is attached to the longitudinal frame.

[0133] 7. The support bracket of example 6, wherein the top portion of the hanger includes a centering protrusion positioned between the first opening and the second opening.

[0134] 8. A support bracket and monitor arrangement, comprising: [0135] the support bracket of any one of examples 1 to 7; and [0136] a monitor operable in a first orientation and a second orientation, the monitor comprising a display, a housing supporting the display, and a latching structure including a first latch retainer, a first recess, a second latch retainer, and a second recess, [0137] wherein the first latch retainer is sized and shaped to apply force upon the slanted surface of the first latch when the monitor is moved toward the support bracket to move the first latch from the first position to the second position and to retain the first latch once the first latch is received by the first recess and returns to the first position, and [0138] wherein the second latch retainer is sized and shaped to apply force upon the slanted surface of the second latch when the monitor is moved toward the support bracket to move the second latch from the first position to the second position and to retain the second latch once the second latch is received by the second recess and returns to the first position.

[0139] 9. The support bracket and portable monitor arrangement of example 8, wherein the monitor comprises an external heat sink and the external heat sink includes the latching structure.

[0140] 10. The support bracket and portable monitor arrangement of any one of examples 8 and 9, wherein the monitor comprises a handle having arms, handle axles connected to the arms to

pivotaly connect the handle to the housing, the handle axles defining a rotation axis, and wherein the latching structure is on a plane perpendicular to the display and traversing the rotation axis.

[0141] 11. The support bracket and portable monitor arrangement of any one of examples 8 to 10, wherein the monitor has a first side opposite a second side, wherein in the first orientation the first side is below the second side, wherein the monitor has a third side opposite a fourth side, a distance from the third side to the fourth side defining a length of the monitor, wherein a length of the longitudinal frame is at least 65% of the length of the portable monitor.

[0142] 12. The support bracket and portable monitor arrangement of any one of examples 8 to 10, wherein the monitor has a first lateral side and a second, opposite, lateral side, wherein a length of the longitudinal frame is sufficient to enable a user holding the monitor with the right and left hands positioned on the first lateral side and the second lateral side to apply force to the first actuator and the second actuator with the left hand and the right hand to release the monitor from the support bracket.

[0143] 13. The support bracket and portable monitor arrangement of any one of examples 8 to 10, wherein the monitor has a first side opposite a second side, wherein in the first orientation the first side is below the second side, a distance from the first side to the second side defining a width of the monitor, wherein a distance from a plane bisecting the first latch horizontally to the bottom wall is substantially equal to $\frac{1}{2}$ of the width of the monitor.

[0144] 14. The support bracket and portable monitor arrangement of any one of examples 8 to 10, wherein the monitor has a first side opposite a second side, wherein in the first orientation the first side is below the second side, wherein the cradle is sized and shaped to permit latching of the latching structure onto the first latch and the second latch with the monitor supported by the cradle, in the first orientation and also with the monitor in the second orientation.

[0145] 15. The support bracket and portable monitor arrangement of any one of the preceeding examples, the monitor further comprising a circuit board mounted inside the housing and a power socket mounted on the circuit board and sized and shaped to receive therein a power plug, wherein the housing includes a front portion removably attached to a back portion, the back portion including a through-hole aligned with the power socket, the through-hole sized and shaped to receive therethrough the power plug, wherein removal of the back portion removes the power plug from the power socket.

[0146] 16. The support bracket and portable monitor arrangement of any one of the preceeding examples, the monitor further comprising an internal heat sink within the internal space defined by the housing, and an external heat sink mounted on an outer surface of the housing.

[0147] 17. The support bracket and portable monitor arrangement of example 16, the monitor further comprising a heat transfer bridge thermally connecting the internal heat sink and the external heat sink.

[0148] 18. The support bracket and portable monitor arrangement of example 17, wherein the monitor is devoid of an internal fan.

[0149] 19. A support bracket and video processing apparatus (VPA) arrangement, comprising:

[0150] the support bracket of any one of examples 1 to 7; and [0151] a PVA comprising a housing and a latching structure including a first latch retainer, a first recess, a second latch retainer, and a second recess, [0152] wherein the first latch retainer is sized and shaped to apply force upon the slanted surface of the first latch when the PVA is moved toward the support bracket to move the first latch from the first position to the second position and to retain the first latch once the first latch is received by the first recess and returns to the first position, and [0153] wherein the second latch retainer is sized and shaped to apply force upon the slanted surface of the second latch when the PVA is moved toward the support bracket to move the second latch from the first position to the second position and to retain the second latch once the second latch is received by the second recess and returns to the first position.

[0154] 20. The support bracket and PVA arrangement of example 19, wherein the PVA comprises

an external heat sink and the external heat sink includes the latching structure.

[0155] 21. The support bracket and PVA arrangement of any one of examples 19 or 20, wherein the PVA has a first lateral side and a second, opposite, lateral side, wherein a length of the longitudinal frame is sufficient to enable a user holding the PVA with the right and left hands positioned on the first lateral side and the second lateral side to apply force to the first actuator and the second actuator with the left hand and the right hand to release the PVA from the support bracket.

[0156] 22. The support bracket and PVA arrangement of any one of examples 19 to 21, wherein the PVA has a first side opposite a second side, wherein in the first orientation the first side is below the second side, a distance from the first side to the second side defining a width of the PVA, wherein a distance from a plane bisecting the first latch horizontally to the bottom wall is substantially equal to $\frac{1}{2}$ of the width of the PVA.

[0157] 23. The support bracket and PVA arrangement of any one of the preceding examples, the PVA further comprising a circuit board mounted inside the housing and a power socket mounted on the circuit board and sized and shaped to receive therein a power plug, wherein the housing includes a front portion removably attached to a back portion, the back portion including a through-hole aligned with the power socket, the through-hole sized and shaped to receive therethrough the power plug, wherein removal of the back portion removes the power plug from the power socket.

[0158] 24. The support bracket and PVA arrangement of any one of the preceding examples, the PVA further comprising an internal heat sink within the internal space defined by the housing, and an external heat sink mounted on an outer surface of the housing.

[0159] 25. The support bracket and PVA arrangement of example 24, the PVA further comprising a heat transfer bridge thermally connecting the internal heat sink and the external heat sink.

[0160] 26. The support bracket and PVA arrangement of any one of the preceding examples, wherein the PVA is devoid of an internal fan.

[0161] 27. The support bracket and PVA arrangement of any one of examples 19 to 26, wherein the VPA is devoid of a display module.

[0162] 28. The support bracket and PVA arrangement of any one of examples 19 to 26, wherein the VPA is devoid of a handle pivotally attached to the back wall.

CONNECTOR RING EXAMPLES

[0163] 1. A connector ring for a video processing apparatus (VPA), the connector ring comprising: [0164] a retention portion; [0165] an intermediate portion; and [0166] a plug hood made of a flexible material, the intermediate portion connecting the retention portion to the plug hood, [0167] wherein the retention portion and the plug hood are larger in cross-section than the intermediate portion in at least one radial extent.

[0168] 2. The connector ring of example 1, wherein the plug hood comprises a visual technology indicator associated with a technology of a medical device interface of the VPA and a plug alignment indicator, wherein the retention portion includes an alignment feature corresponding with the alignment indicator.

[0169] 3. The connector ring of examples 1 or 2, wherein the plug hood comprises a cylindrical wall including the visual technology indicator and the plug alignment indicator.

[0170] 4. The connector ring of examples 1, 2, or 3, wherein the visual technology indicator comprises a color associated with the technology of the medical device interface, and the plug alignment indicator comprises a notch in the cylindrical wall, and wherein the plug hood further comprises an alignment indicia of a color different than the color associated with the technology of the medical device interface.

[0171] 5. The connector ring of any one of examples 1-4, wherein the retention portion of the connector ring comprises an arcuate wall including the alignment feature, and the alignment feature is sized and shaped to radially align the connector ring with a medical device connector of the medical device interface of the VPA.

[0172] 6. The connector ring of any one of examples 1-5, wherein the alignment feature comprises

an opening in the arcuate wall.

[0173] 7. The connector ring of any one of examples 1-6, wherein the flexible material is selected to adopt a bent state under application of force and an unbent state upon release of the force, and wherein the connector hood consists substantially of the flexible material.

[0174] 8. The connector ring of any one of examples 1-7, wherein the VPA comprises a housing and a display module supported by the housing and including a display screen.

[0175] 9. A video processing apparatus (VPA), comprising: [0176] a housing defining an interior space of the VPA and including a wall having an opening; [0177] a medical device interface including a medical device connector axially aligned with the opening on the wall of the housing; and [0178] a connector ring as in any one of examples 1-8.

[0179] 10. The VPA of example 9, wherein the connector ring comprises a retention portion located in the interior space and radially aligned with the medical device connector, an intermediate portion traversing the opening, and a plug hood made of flexible material and extending outwardly from the intermediate portion, wherein the retention portion and the plug hood are larger in cross-section than the opening in the wall of the housing in at least one radial extent, and wherein the intermediate portion is smaller in cross-section than the opening in the wall of the housing in the at least one extent.

[0180] 11. The VPA of example 10, wherein the retention portion of the connector ring comprises an arcuate wall including an alignment feature sized and shaped to radially align the connector ring with the medical device connector.

[0181] 12. The VPA of example 11, wherein the alignment feature comprises a notch in the arcuate wall.

[0182] 13. The VPA of example 11, wherein the plug hood of the connector ring comprises a visual technology indicator.

[0183] 14. The VPA of example 10, wherein the plug hood of the connector ring comprises a plug alignment indicator.

[0184] 15. The VPA of example 14, wherein the plug hood comprises a cylindrical wall and the plug alignment indicator comprises a notch in the cylindrical wall.

[0185] 16. The VPA of example 9, wherein the plug hood comprises a cylindrical wall and the plug alignment indicator comprises a notch in the cylindrical wall.

[0186] 17. The VPA of example 9, wherein the plug hood of the connector ring comprises a cylindrical wall including a visual technology indicator and a plug alignment indicator.

[0187] 18. The VPA of example 17, wherein the visual technology indicator comprises a color associated with a technology of the medical device interface, and the plug alignment indicator comprises a notch in the cylindrical wall, and wherein the plug hood further comprises an alignment indicia of a color different than the color associated with the technology of the medical device interface.

[0188] 19. The VPA of any one of examples 8-18, wherein the VPA further comprises a display module supported by the housing and including a display screen.

[0189] 20. A method of assembling a video processing apparatus (VPA), comprising: [0190] providing a housing including a wall having an opening; [0191] removably connecting a medical device interface to a circuit board located in an internal space of the VPA, the medical device interface including a connector axially aligned with the opening on the wall of the housing when the medical device interface is connected to the circuit board; [0192] providing a connector ring including a retention portion, an intermediate portion, and a plug hood, the intermediate portion connecting the retention portion to the plug hood, the connector ring having a flexible portion capable of adopting a bent state and an unbent state, in the unbent state the flexible portion having a cross-section larger than the opening and thus not being insertable through the opening, and in the bent state the flexible portion having a cross-section smaller than the opening and thus being insertable through the opening; [0193] bending the flexible portion into the bent state; [0194] while

in the bent state, inserting the portion of the connector ring through the opening until the opening surrounds the intermediate portion; and [0195] releasing the connector ring to allow the flexible portion to adopt the unbent state.

[0196] 21. The method of example 20, further comprising radially aligning the connector ring with the connector of the medical device interface.

[0197] 22. The method of example 20, wherein the connector hood comprises the flexible portion.

[0198] 23. The method of example 20, wherein the flexible portion comprises a flexible polymeric material selected to adopt the bent state and the unbent state, and wherein the connector hood consists substantially of the flexible polymeric material.

[0199] 24. The method of any one of examples 20 to 23, wherein wherein the VPA comprises a display module supported by the housing and including a display screen.

INDICATOR EXAMPLES

[0200] 1. A video processing apparatus (VPA) comprising: [0201] a housing defining an interior space of the VPA; [0202] a first medical device interface located in the interior space and including a connector adapted to removably connect a cable associated with first medical device having an image sensor; [0203] a first visual technology indicator corresponding to the first medical device interface and positioned adjacent the first medical device interface; and [0204] a second medical device interface located in the interior space and including a second connector adapted to removably connect a cable associated with a second medical device having an image sensor, the second medical device interface being operably different than the first medical device interface; [0205] a second visual technology indicator corresponding to the second medical device interface and positioned adjacent the second medical device interface, [0206] wherein the first technology indicator is different from the second technology indicator to thereby facilitate connection of the first medical device with the first medical device interface and of the second medical device with the second medical device interface.

[0207] 2. The VPA of example 1, wherein the first medical device interface is located adjacent the second medical device interface.

[0208] 3. The VPA of example 1, wherein the housing comprises a first opening and the first visual technology indicator comprises or is comprised by a ring removably positioned in the first opening, and wherein the housing comprises a second opening and the second visual technology indicator comprises or is comprised by a ring removably positioned in the second opening.

[0209] 4. The VPA of example 3, wherein the first opening is permanently aligned with the first interface socket and the second opening is permanently aligned with the second interface socket.

[0210] 5. The VPA of example 4, wherein the first visual technology indicator can be moved from the first opening to the second opening and the first medical device interface can be moved from the first interface socket to the second interface socket.

[0211] 6. The VPA of example 3, wherein the ring corresponding to the first visual technology indicator surrounds the connector of the first medical device interface.

[0212] 7. The VPA of example 3, wherein the first visual technology indicator comprises a first color and the second visual technology indicator comprises a second color different than the first color, to thereby color-code the first medical device interface and the second medical device interface.

[0213] 8. The VPA of any one of examples 1 to 7, further comprising a first interface socket and a second interface socket, the first interface socket and the second interface socket sized and shaped to removably and interchangeably receive the first medical device interface and the second medical device interface.

[0214] 9. The VPA of example 8, wherein the first interface socket and the second interface socket are identical.

[0215] 10. The VPA of example 1, wherein the first visual technology indicator is comprised by the first connector and the second visual technology indicator is comprised by the second connector.

[0216] 11. The VPA of any one of examples 1 to 10, wherein the VPA further comprises a display module supported by the housing and including a display screen.

[0217] 12. The VPA of any one of the preceeding examples, further comprising a circuit board mounted inside the housing and a power socket mounted on the circuit board and sized and shaped to receive therein a power plug, wherein the housing includes a front portion removably attached to a back portion, the back portion including a through-hole aligned with the power socket, the through-hole sized and shaped to receive therethrough the power plug, wherein removal of the back portion removes the power plug from the power socket.

[0218] 13. The VPA of any one of the preceeding examples, further comprising an internal heat sink within the internal space defined by the housing, and an external heat sink mounted on an outer surface of the housing.

[0219] 14. The VPA of example 3, further comprising a heat transfer bridge thermally connecting the internal heat sink and the external heat sink.

[0220] 15. The VPA of example 14, wherein the VPA is devoid of an internal fan.

[0221] 16. A visualization system comprising: [0222] the VPA of any one of examples 1 to 15; [0223] the first medical device, the first medical device including a connector plug including a first visual indicator corresponding to the first visual technology indicator; and [0224] the second medical device, the second medical device including a connector plug having a second visual indicator corresponding to the second visual technology indicator.

[0225] 16. The visualization system of example 16, wherein the first visual technology indicator and the first visual indicator comprise a first color, and wherein the second visual technology indicator and the second visual indicator comprise a second color different than the first color, to thereby color-code the first medical device with the first medical device interface and the second medical device with the second medical device interface.

[0226] 17. A method of making a video processing apparatus (VPA), comprising: [0227] providing a housing having a first opening adjacent a second opening; [0228] providing a motherboard including a first interface socket and a second interface socket, the first interface socket sized and shaped as the second interface socket, the first interface socket aligned with the first opening when the VPA is assembled, and the second interface socket aligned with the second opening when the VPA is assembled; [0229] removably connecting a first medical device interface to the first interface socket, the first medical device interface adapted to removably connect a first medical device having an image sensor; [0230] removably connecting a second medical device interface to the second interface socket, the second medical device interface adapted to removably connect a second medical device having an image sensor, the second medical device being different than the first medical device; [0231] removably positioning a first ring comprising a first visual technology indicator in the first opening; and [0232] removably positioning a second ring comprising a second visual technology indicator in the second opening, the second visual technology indicator being different than the first visual technology indicator, [0233] wherein the first technology indicator is different from the second technology indicator to thereby facilitate connection of a first medical device with the first medical device interface and of a second medical device with the second medical device interface.

SUPPORT FEATURES EXAMPLES

[0234] 1. A portable monitor operable in a first orientation and a second orientation, the monitor comprising: [0235] a display module; [0236] a housing supporting the display module, the housing having a first side and a second side opposite the first side, a third side and a fourth side opposite the third side and orthogonal to the first side, and a back side opposite the display module, wherein in the first orientation the first side is below the second side and, and wherein in the second orientation the first side is above the second side; and [0237] a handle having arms and a bar extending between the arms, [0238] wherein the back side of the housing includes a middle section extending between the third side and the fourth side equidistantly between the first side and the

second side, the middle section having a height less than 4.0 centimeters, and [0239] wherein each of the arms has a first end pivotally attached to the middle section of the housing and a second end opposite the first end and connected to the bar.

[0240] 2. The monitor of example 1, wherein the middle section has a height less than 3.0 centimeters.

[0241] 3. The monitor of example 1, wherein a center plane bisects the housing in equal parts, and wherein the handle axles comprise rotation axes lying in the center plane.

[0242] 4. The monitor of any one of examples 1 to 3, wherein the housing comprises a rounded first edge connecting the first side to the back side and a rounded second edge connecting the second side to the back side, wherein the bar of the handle is operable to support the monitor at an angle to a horizontal plane ranging at least between 15-75 degrees, permitting the monitor to rest on the rounded first edge in the first orientation and on the rounded second edge in the second orientation.

[0243] 5. The monitor of any one of examples 1 to 4, wherein the back side of the housing includes grooves sized and shaped to receive, respectively, the arms of the handle.

[0244] 6. The monitor of any one of examples 1 to 4, further comprising a handle axle connected to the first end of one of the arms, the handle axle traversing one of the grooves to define a first section of the groove on one side of the handle axle and a second section of the groove on an opposite side of the handle axle, wherein the handle is pivotable about the handle axle to a plurality of positions including a first position, in which the one of the arms is received by the first section of the groove, a second position, in which the one of the arms is received by the second section of the groove, and intermediate positions between the first position and the second position.

[0245] 7. The monitor of example 6, further including a handle position brake including one of the handle axles, a first disk having a surface including grooves defining protrusions therebetween, and a second disk having a surface including grooves defining protrusions therebetween, wherein the grooves of the first disk are shaped to match the protrusions of the second disk to thereby define the intermediate positions.

[0246] 8. The monitor of example 6, further including a handle position brake including the handle axle, a first disk, a second disk, and a spring, the handle axle passing through the first disk, the second disk, and the spring, and the spring causing a surface of the first disk to press against a surface of the second disk to create a braking force to maintain the handle in one of the plurality of positions.

[0247] 9. The monitor of example 8, wherein the surface of at least one of the first disk and the second disk comprises grooves to increase the braking force relative to disk surfaces without grooves.

[0248] 10. The monitor of examples 7 or 9, wherein the grooves of the first disk extend radially and are evenly distributed.

[0249] 11. The monitor of example 10, wherein the grooves are evenly distributed at between 5 and 20 degrees from each other.

[0250] 12. The monitor of any one of the preceding examples, wherein the housing comprises a rounded first edge connecting the first side to the back side and a rounded second edge connecting the second side to the back side, and wherein the rounded first edge has a curvature radius equal to a curvature radius of the rounded second edge.

[0251] 13. The monitor of example 12, wherein the curvature radius of the rounded first edge is greater than 2.0 centimeters.

[0252] 14. A portable monitor operable in a first orientation and a second orientation, the monitor comprising: [0253] a display module; [0254] a housing supporting the display module, the housing having a first side and a second side opposite the first side, a third side and a fourth side opposite the third side and orthogonal to the first side, and a back side opposite the display module, wherein in the first orientation the first side is below the second side and, and wherein in the second

orientation the first side is above the second side; [0255] a handle having arms, the arms having first ends opposite second ends, and a bar extending between and connected to the second ends of arms; and [0256] handle axles connected to the first ends of the arms to pivotally connect the handle to the housing, [0257] wherein the back side of the housing includes grooves sized and shaped to receive, respectively, the arms of the handle, and [0258] wherein the handle axles traverse, at least partially, the grooves to define first sections of the grooves on one side of the handle axles and second sections of the grooves on opposite sides of the handle axles, wherein the handle is pivotable about the handle axles to a plurality of positions including a first position, in which the arms are received by the first sections of the grooves, a second position, in which the arms are received by the second sections of the grooves, and intermediate positions between the first position and the second position.

[0259] 15. The monitor of example 14, further including a handle position brake including one of the handle axles, a first disk having a surface including grooves defining protrusions therebetween, and a second disk having a surface including grooves defining protrusions therebetween, wherein the grooves of the first disk are shaped to match the protrusions of the second disk to thereby define the intermediate positions.

[0260] 16. The monitor of example 15, wherein the grooves of the first disk are evenly distributed at between 5 and 20 degrees.

[0261] 17. The monitor of any one of examples 14 to 16, wherein the housing comprises a rounded first edge connecting the first side to the back side and a rounded second edge connecting the second side to the back side, and wherein the rounded first edge has a curvature radius equal to a curvature radius of the rounded second edge.

[0262] 18. The monitor of any one of examples 14 to 17, wherein the monitor has a weight, wherein between 40-60% of the weight is between the handle axles and the first side of the monitor, and wherein between 40-60% of the weight is between the handle axles and the second side of the monitor.

[0263] 19. A method of using a monitor as in any one of examples 1 to 18, the method comprising: [0264] placing the monitor in the first orientation on a support structure with the handle in a first of the plurality of intermediate positions; [0265] pivoting the handle to a second of the plurality of positions; and [0266] prior to or after pivoting the handle to the second of the plurality of positions, placing the monitor in the second orientation on the support structure.

VIDEO OUT EXAMPLES

[0267] 1. A video processing apparatus (VPA) comprising: [0268] a housing defining an interior space of the VPA, the housing having a first side and a second side opposite the first side, a third side and a fourth side opposite the third side and orthogonal to the first side, and a back wall opposite the display module, the back wall comprising a main portion laying on a back plane, a recessed portion recessed from the back plane and defining a video connection recess, and a recessed wall extending from the main portion to the recessed portion, the recessed wall having a video connector opening, and the recessed portion having an angled surface lying at an angle of at least 5 degrees relative to the back plane; and [0269] a video output socket in the interior space and aligned with the video connector opening of the recessed wall, whereby the angled surface facilitates insertion of a video connector into the video output socket.

[0270] 2. The VPA of example 1, further comprising a video output card, wherein the video output socket is mounted on the video output card.

[0271] 3. The VPA of example 2, wherein the video output card is supported by the housing parallel to the angled surface of the recessed portion of the back wall.

[0272] 4. The VPA of any one of examples 1 to 3, wherein the recessed wall extends parallel to the first side.

[0273] 5. The VPA of example 4, wherein the recessed portion extends from the recessed wall toward the first side of the VPA.

[0274] 6. The VPA of example 5, wherein a distance from the recessed portion to the back plane decreases in a direction from the recessed wall toward the first side of the VPA.

[0275] 7. The VPA of example 1, wherein the VPA includes a handle pivotally affixed to the back wall and operable to pivot about a rotation axis, wherein the recessed wall is positioned between the rotation axis and the first side of the VPA.

[0276] 8. The VPA of example 1, wherein the VPA includes a handle and the main portion of the back wall comprises grooves, the handle including arms having first ends opposite second ends and a bar extending between and connected to the second ends of arms, wherein the grooves are sized and shaped to receive the arms of the handle, wherein the video connection recess is positioned between the grooves.

[0277] 9. The VPA of example 8, wherein the handle is pivotally affixed to the back wall and operable to pivot about a rotation axis passing through the grooves to define first sections of the grooves on one side of the rotation axis and second sections of the grooves on an opposite side of the rotation axis, wherein the handle is pivotable about the rotation axis to a plurality of positions including a first position, in which the arms are received by the first sections of the grooves, a second position, in which the arms are received by the second sections of the grooves, and intermediate positions between the first position and the second position.

[0278] 10. The VPA of example 9, wherein the video connection recess is positioned between the second sections of the grooves on the opposite side of the rotation axis.

[0279] 11. The VPA of example 9, further comprising an external heat sink positioned between the second sections of the grooves on the opposite side of the rotation axis and adjacent the video connection recess.

[0280] 12. The VPA of any one of examples 8 to 11, wherein the recessed wall extends parallel to the first side of the VPA, and wherein a distance from the recessed portion to the back plane decreases in a direction from the recessed wall toward the first side of the VPA.

[0281] 13. The VPA of any one of examples 1 to 12, further comprising a display module supported by the housing and including a display screen.

[0282] 14. A video processing apparatus (VPA) comprising: [0283] a housing defining an interior space of the VPA, the housing having a front side opposite a back side, and a back wall opposite comprising a main portion laying on a back plane, a recessed portion recessed from the back plane and defining a video connection recess, and a recessed wall extending from the main portion to the recessed portion, the recessed wall having a video connector opening, and the recessed portion having an angled surface lying at an angle of at least 5 degrees relative to the back plane; and [0284] a video output socket in the interior space and aligned with the video connector opening of the recessed wall, whereby the angled surface facilitates insertion of a video connector into the video output socket.

[0285] 15. The VPA of example 14, wherein the VPA comprises a display module on the front side.

[0286] 16. The VPA of example 15, wherein the VPA includes a handle and the main portion of the back wall comprises grooves, the handle including arms having first ends opposite second ends and a bar extending between and connected to the second ends of arms, wherein the grooves are sized and shaped to receive the arms of the handle, and wherein the video connection recess is positioned between the grooves.

[0287] 17. The VPA of example 15, wherein the VPA includes a handle pivotally affixed to the back wall and operable to pivot about a rotation axis, wherein the recessed wall is positioned between the rotation axis and the first side of the VPA.

[0288] 18. The VPA of example 15, wherein the VPA includes a handle and the main portion of the back wall comprises grooves, the handle including arms having first ends opposite second ends and a bar extending between and connected to the second ends of arms, wherein the grooves are sized and shaped to receive the arms of the handle, wherein the video connection recess is positioned between the grooves.

[0289] 19. The VPA of any one of examples 16 to 18, wherein the handle is pivotally affixed to the back wall and operable to pivot about a rotation axis passing through the grooves to define first sections of the grooves on one side of the rotation axis and second sections of the grooves on an opposite side of the rotation axis, wherein the handle is pivotable about the rotation axis to a plurality of positions including a first position, in which the arms are received by the first sections of the grooves, a second position, in which the arms are received by the second sections of the grooves, and intermediate positions between the first position and the second position.

[0290] 20. The VPA of example 19, wherein the VPA includes a handle position brake operable to maintain the handle in the intermediate positions.

[0291] 21. The VPA of example 14, wherein the VPA is devoid of a display module and is devoid of a handle pivotally attached to the back wall.

[0292] 22. The VPA of any one of examples 14 to 21, wherein the video output card is supported by the housing parallel to the angled surface of the recessed portion of the back wall.

[0293] In the detailed description herein, references to “one embodiment,” “an embodiment,” “an example embodiment,” etc., indicate that the embodiment described may include a particular feature, structure, or characteristic, but every embodiment may not necessarily include the particular feature, structure, or characteristic. Moreover, such phrases are not necessarily referring to the same embodiment.

[0294] As used herein, the terms “comprises,” “comprising,” or any other variation thereof, are intended to cover a non-exclusive inclusion, such that a process, method, article, or apparatus that comprises a list of elements does not include only those elements but may include other elements not expressly listed or inherent to such process, method, article, or apparatus.

[0295] The scope of the invention is to be limited by nothing other than the appended claims, in which reference to an element in the singular is not intended to mean “one and only one” unless explicitly so stated, but rather “one or more.” Moreover, where a phrase similar to “at least one of A, B, or C” is used in the claims, it is intended that the phrase be interpreted to mean that A alone may be present in an embodiment, B alone may be present in an embodiment, C alone may be present in an embodiment, or that any combination of the elements A, B or C may be present in a single embodiment; for example, A and B, A and C, B and C, or A and B and C.

Claims

1. A video processing apparatus (VPA) comprising: a display screen; a housing enclosing an interior space of the VPA and comprising a back wall, a recessed wall, a ventilation grid, a first side, a second side, a third side, a fourth side, and a back side opposite to the display screen, the back side comprising a middle section and grooves, the middle section extending between the third side and the fourth side equidistantly between the first side and the second side, the grooves extending at least from the middle section toward the first side, the recessed wall located between the middle section and the first side and being connected to, and extending from the back wall toward the interior space, the recessed wall comprising a video connector opening, and the ventilation grid located between the middle section and the second side and extending between the third side and the fourth side; and a handle including arms having first ends, second ends opposite to the first ends, and a bar extending between and connected to the second ends of the arms, the first ends being pivotally affixed to the middle section of the back wall and operable to pivot about a rotation axis from a first position, in which the arms are received by the grooves, and an intermediate position, in which the arms are not received by the grooves.

2. The VPA of claim 1, wherein the back wall comprises a main portion laying on a back plane and a recessed portion recessed from the back plane, the recessed wall extending from the main portion to the recessed portion.

3. The VPA of claim 2, further comprising a video output card comprising a video output socket,

the video output socket being accessible through the video connector opening.

4. The VPA of claim 3, wherein the recessed portion comprises an angled surface lying at an angle of at least 5 degrees relative to the back plane; and wherein the video output card is supported by the housing parallel to the angled surface.

5. The VPA of claim 3, wherein the recessed wall extends parallel to the first side.

6. The VPA of claim 3, wherein the recessed portion extends from the recessed wall toward the first side of the housing.

7. The VPA of claim 6, wherein a distance from the recessed portion to the back plane decreases in a direction from the recessed wall toward the first side of the housing.

8. The VPA of claim 1, wherein the grooves comprise first sections on one side of the rotation axis and second sections of an opposite side of the rotation axis, wherein the handle is pivotable about the rotation axis to a second position, in which the arms are received by the second sections, and wherein the intermediate position is between the first position and the second position.

9. The VPA of claim 1, further comprising a heat sink positioned in the internal space between the grooves and between the middle section and the first side.

10. The VPA of claim 1, wherein the VPA is devoid of a fan.

11. The VPA of claim 1, further comprising a display module supported by the housing and comprising the display screen.

12. The VPA of claim 1, wherein the VPA is operable in a first orientation and in a second orientation, and where the VPA includes a graphical user interface to present image data with the display module in the first orientation or the second orientation, a view of the image data presented in the first orientation being the same as a view of the image data presented in the second orientation.

13. The VPA of claim 1, wherein the VPA comprises four curved corners at which the first side is connected to the third side and at which the second side is connected to the third side and to the fourth side.

14. The VPA of claim 1, the VPA further comprising hinges, each of the hinges including a shaft, a locking nut and a spring, the locking nut and the spring traversed by the shaft, the shafts connected to the first ends of the handle.
