

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250265091

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

Hush; Glen E. et al.

APPARATUSES AND METHODS FOR ORDERING BITS IN A MEMORY DEVICE

Abstract

Systems, apparatuses, and methods for organizing bits in a memory device are described. In a number of embodiments, an apparatus can include an array of memory cells, a data interface, a multiplexer coupled between the array of memory cells and the data interface, and a controller coupled to the array of memory cells, the controller configured to cause the apparatus to latch bits associated with a row of memory cells in the array in a number of sense amplifiers in a prefetch operation and send the bits from the sense amplifiers, through a multiplexer, to a data interface, which may include or be referred to as DQs. The bits may be sent to the DQs in a particular order that may correspond to a particular matrix configuration and may thus facilitate or reduce the complexity of arithmetic operations performed on the data.

Inventors: Hush; Glen E. (Boise, ID), Boehm; Aaron P. (Boise, ID), Luo; Fa-Long (San Jose, CA)

Applicant: Lodestar Licensing Group LLC (Evanston, IL)

Family ID: 1000008586802

Appl. No.: 19/202459

Filed: May 08, 2025

Related U.S. Application Data

parent US continuation 18378044 20231009 parent-grant-document US 12314723 child US 19202459

parent US continuation 17680538 20220225 parent-grant-document US 11782721 child US 18378044

parent US continuation 17065749 20201008 parent-grant-document US 11269648 child US 17680538

Publication Classification

Int. Cl.: **G06F9/38** (20180101); **G06F9/30** (20180101); **G11C7/08** (20060101); **G11C7/10** (20060101)

U.S. Cl.:

CPC **G06F9/3856** (20230801); **G06F9/3001** (20130101); **G06F9/30018** (20130101); **G11C7/08** (20130101); **G11C7/1006** (20130101); G06F9/30032 (20130101)

Background/Summary

PRIORITY INFORMATION [0001] This application is a Continuation of U.S. application Ser. No. 18/378,044, filed Oct. 9, 2023, which is a Continuation of U.S. application Ser. No. 17/680,538, filed on Feb. 25, 2022, which issued as U.S. Pat. No. 11,782,712, which is a Continuation of U.S. application Ser. No. 17/065,749, filed on Oct. 8, 2020, which issued as U.S. Pat. No. 11,269,648 on Mar. 8, 2022, which is a Continuation of U.S. application Ser. No. 16/231,106, filed on Dec. 21, 2018, which issued as U.S. Pat. No. 10,838,732 on Nov. 17, 2020, the contents of which are incorporated herein by reference.

TECHNICAL FIELD

[0002] The present disclosure relates generally to semiconductor memory and methods, and more particularly, to apparatuses and methods for ordering bits in a memory device.

BACKGROUND

[0003] Memory devices are typically provided as internal, semiconductor, integrated circuits in computers or other electronic systems. There are many different types of memory including volatile and non-volatile memory. Volatile memory can require power to maintain its data (e.g., host data, error data, etc.) and includes random access memory (RAM), dynamic random access memory (DRAM), static random access memory (SRAM), synchronous dynamic random access memory (SDRAM), and thyristor random access memory (TRAM), among others. Non-volatile memory can provide persistent data by retaining stored data when not powered and can include NAND flash memory, NOR flash memory, and resistance variable memory such as phase change random access memory (PCRAM), resistive random access memory (RRAM), and magnetoresistive random access memory (MRAM), such as spin torque transfer random access memory (STT RAM), among others.

[0004] Electronic systems often include a number of processing resources (e.g., one or more processors), which may retrieve and execute instructions and store the results of the executed instructions to a suitable location. A processor can include a number of functional units such as arithmetic logic unit (ALU) circuitry, floating point unit (FPU) circuitry, and a combinatorial logic block, for example, which can be used to execute instructions by performing logical operations such as AND, OR, NOT, NAND, NOR, and XOR, and invert (e.g., inversion) logical operations on data (e.g., one or more operands). For example, functional unit circuitry may be used to perform arithmetic operations such as addition, subtraction, multiplication, and division on operands via a number of operations. Memory devices without logic for ordering information may contribute to increased latency, or may not ameliorate latency issues, associated with such arithmetic operations.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0005] FIG. 1 is a block diagram of an apparatus in the form of a computing system including a memory device in accordance with a number of embodiments of the present disclosure.

[0006] FIG. 2 is a block diagram of an array of memory cells of the memory device and a controller of the memory device in accordance with a number of embodiments of the present disclosure.

[0007] FIG. 3 is a schematic diagram illustrating a row of an array of memory cells in accordance with a number of embodiments of the present disclosure.

[0008] FIG. 4 is a block diagram illustrating an apparatus and method for transferring bits between sense amplifiers and I/O circuitry via column decode circuitry in a particular order in accordance with a number of embodiments of the present disclosure.

[0009] FIG. 5 is a flow diagram of an example method to perform a read operation in accordance with a number of embodiments of the present disclosure.

[0010] FIG. 6 is a flow diagram of an example method to perform a write operation in accordance with a number of embodiments of the present disclosure.

DETAILED DESCRIPTION

[0011] The present disclosure includes systems, apparatuses and methods for organizing bits in a memory device. In a number of embodiments, an apparatus can include an array of memory cells, a data interface, column decode circuitry coupled between the array of memory cells and the data interface, and a controller coupled to the array of memory cells, the controller configured to cause the apparatus to latch bits associated with a row of memory cells in the array in a number of sense amplifiers and send the bits from the sense amplifiers, through column decode circuitry, to a data interface, which may include or be referred to as DQs. The bits may be sent to the DQs in a particular order that may correspond to a particular matrix configuration and may thus facilitate or reduce the complexity of arithmetic operations performed on the data.

[0012] A number of components in a computing system may be involved in providing instructions to the functional unit circuitry for execution. The instructions may be executed, for instance, by a processing resource such as a controller and/or host processor. Data (e.g., the operands on which the instructions will be executed) may be written to and/or stored in an array of memory cells that is accessible by the functional unit circuitry. In many instances, the processing resources (e.g., processor and/or associated functional unit circuitry) may be external to the array of memory cells, and data is accessed via a bus between the processing resources and the array of memory cells to execute a set of instructions.

[0013] In some instances, data is transferred from memory cells by the processing resources in the order that the data is stored in the array of memory cells. Accessing the data in this manner may reduce throughput (e.g., rate and/or efficiency) from the array of memory cells to the processing resources because the processing resources may need to reorder, organize, or otherwise manipulate the data before instructions can be executed on the data. The reduced throughput to the processing resources may reduce the overall performance of the computing system.

[0014] In a number of embodiments of the present disclosure, bits of data can be ordered by circuitry coupled to an array of memory cells prior to the processing resources executing instructions on the data. In some cases, a controller coupled to the array of memory cells directs the circuitry to send the bits of data to the DQs in a particular order for transfer to the processing resources. The particular order that the bits of data are sent to the DQs and transferred to the processing resource can be requested via a command from the processing resource and can configure the data in a particular matrix configuration for processing by the processing resource. In some embodiments, the circuitry can include column decode circuitry, that includes a multiplexer,

for example, that selects and sends data from sense amplifiers to the DQs in a particular order. The particular order can be based on a command from a processing resource and/or a controller on a memory system. For example, data transferred from the array of memory cells to sense amplifiers may be sent from the sense amplifiers to the DQs via column decode circuitry (e.g., a multiplexer) in a particular order. The particular order may include bits sent from groups of adjacent sense amplifiers or may include bits sent from groups of sense amplifiers that are separated from each other by a particular number of sense amplifiers.

[0015] Also, bits of data received by the DQs may be written to the sense amplifiers via the column decode circuitry in a particular order. The particular order may include writing bits of data to groups of adjacent sense amplifiers or may include writing bits of data to groups of sense amplifiers that are separated from each other by a particular number of sense amplifiers. The bits of data sent from the sense amplifiers to the DQs via the column decode circuitry and/or sent from the DQs to the sense amplifiers via the column decode circuitry in a particular order can correspond to rows, columns, and/or diagonals of a matrix. In a number of embodiments, the particular order in which bits of data are sent by the column decode circuitry to the DQs and/or sense amplifiers can be based on the number DQs on a memory system and/or a burst length of a memory system which can be variable.

[0016] Transferring data from the array of memory cells to and/or writing data to the array of memory cells in the manner described above may reduce the number of steps typically carried out by the processing resource. Thus, a number of embodiments of the present disclosure may provide various benefits including improved throughput (e.g., increased speed, rate, and/or efficiency) associated with accessing (e.g., reading, writing, etc.) data values stored in the array of memory cells.

[0017] In the following detailed description of the present disclosure, reference is made to the accompanying drawings that form a part hereof, and in which is shown by way of illustration how a number of embodiments of the disclosure may be practiced. These embodiments are described in sufficient detail to enable those of ordinary skill in the art to practice the embodiments of this disclosure, and it is to be understood that other embodiments may be utilized and that process, electrical, and/or structural changes may be made without departing from the scope of the present disclosure.

[0018] As used herein, “a number of” something can refer to one or more of such things. For example, a number of memory devices can refer to one or more of memory devices. Additionally, designators such as “M”, “N”, “X”, and “Y”, as used herein, particularly with respect to reference numerals in the drawings, indicates that a number of the particular feature so designated can be included with a number of embodiments of the present disclosure.

[0019] The figures herein follow a numbering convention in which the first digit or digits of a reference number correspond to the figure number and the remaining digits identify an element or component in the figure. Similar elements or components between different figures may be identified by the use of similar digits. For example, **130** may reference element “30” in FIG. **1**, and a similar element may be referenced as **230** in FIG. **2**. As will be appreciated, elements shown in the various embodiments herein can be added, exchanged, and/or eliminated so as to provide a number of additional embodiments of the present disclosure. In addition, the proportion and the relative scale of the elements provided in the figures are intended to illustrate various embodiments of the present disclosure and are not to be used in a limiting sense.

[0020] FIG. **1** is a block diagram of an apparatus in the form of a computing system **100** including a memory device **120** in accordance with a number of embodiments of the present disclosure. The system **100** may be a laptop computer, tablet computer, personal computer, digital camera, digital recording and playback device, mobile telephone, personal digital assistant (PDA), memory card reader, interface hub, sensor, autonomous or semi-autonomous motor vehicle, autonomous or semi-autonomous manufacturing robot, or an Internet-of-Things (IoT) enabled device, among other

systems.

[0021] In a number of embodiments, reading and/or writing data and associated commands may utilize a data path and timing in a DRAM device based upon pre-existing protocols (e.g., DDR3, DDR4, LPDDR4, etc.). As used herein, data movement is an inclusive term that includes, for instance, copying, transferring, and/or transporting data values from a source location to a destination location, such as from an array of memory cells to processing resources or vice versa. As the reader will appreciate, while a DRAM-style memory device is discussed with regard to examples presented herein, embodiments are not limited to a DRAM implementation.

[0022] In a number of embodiments, a row (e.g., as shown at **219** in FIG. **2** and at corresponding reference numbers elsewhere herein) of virtual address space in a memory device (e.g., as shown at **120** in FIG. **1**) may have a bit length of 16K bits (e.g., corresponding to 16,384 memory cells or complementary pairs of memory cells in a DRAM configuration). Read/latch circuitry (e.g., as shown at **150** in FIG. **1** and at corresponding reference numbers elsewhere herein) for such a 16K bit row may include a corresponding 16K sense amplifiers (e.g., as shown at **306** in FIG. **3** and at corresponding reference numbers elsewhere herein) and associated circuitry formed on pitch with the sense lines selectably coupled to corresponding memory cells in the 16K bit row. A sense amplifier in the memory device may operate as a cache for a single data value (bit) from the row of memory cells sensed by the read/latch circuitry **150**. More generally, a number of embodiments of the present disclosure includes read/latch circuitry **150** (e.g., sense amplifiers **306** and associated circuitry), which may be formed on pitch with sense lines of an array of memory cells. The read/latch circuitry and other data storage components described herein are capable of performing data sensing and/or storage (e.g., caching, latching, buffering etc.) of data local to the array of memory cells.

[0023] In order to appreciate the improved data movement techniques that are based on ordering bit using column decode circuitry, a discussion of an apparatus for implementing such techniques (e.g., a memory device **120** having these capabilities and an associated host **110**) follows.

[0024] As shown in FIG. **1**, the system **100** may include a host **110** coupled (e.g., connected) to a memory device **120**. The memory device **120** includes an array of memory cells **130** and a controller **140**, among the various other circuitry for organizing data in a matrix configuration and transforming data from a matrix configuration to a linear configuration, as shown and described herein. The host **110** may be responsible for execution of an operating system (OS) and/or various applications that may be loaded thereto (e.g., from the memory device **120** via the controller **140**). The host **110** may include a system motherboard and backplane and may include a number of processing resources (e.g., one or more processors **145**, microprocessors, or some other type of controlling circuitry) capable of accessing the memory device **120** (e.g., via controller **140**) to perform operations on data values organized in a matrix configuration. The controller **140** also may, in a number of embodiments, include a number of processing resources for performance of processing operations. As further shown in FIG. **1**, the controller **140** may include or may be coupled to a mode register **141**. The mode register **141** may be directed by the controller **140** to be set in a particular setting that corresponds to a particular order in which bits of data are read from the sense amplifiers and/or written to the sense amplifiers. The system **100** may include separate integrated circuits or both the host **110** and the memory device **120** may be on the same integrated circuit. The system **100** may, for instance, be a server system and a high performance computing (HPC) system or a portion thereof. Although the example shown in FIG. **1** illustrates a system having a V on Neumann architecture, embodiments of the present disclosure may be implemented in non-V on Neumann architectures, which may not include one or more components (e.g., CPU, ALU, etc.) often associated with a V on Neumann architecture.

[0025] The controller **140** (e.g., control logic and sequencer) may include control circuitry, in the form of hardware, firmware, or software, or combinations thereof. As an example, the controller **140** may include a state machine, a sequencer, and/or some other types of control circuitry, which

may be implemented in the form of an application specific integrated circuit (ASIC) coupled to a printed circuit board. In a number of embodiments, the controller **140** may be co-located with the host **110** (e.g., in a system-on-chip (SOC) configuration).

[0026] For clarity, description of the system **100** has been simplified to focus on features with particular relevance to the present disclosure. For example, the array of memory cells **130** may be a DRAM array, SRAM array, STT RAM array, PCRAM array, TRAM array, RRAM array, FeRAM array, phase-change array of memory cells, 3D X point™ array, NAND flash array, and/or NOR flash array. The array of memory cells **130** may include memory cells arranged in rows (e.g., in a plurality of subarrays) and columns. The memory cells may be coupled to one another by access lines (which may be referred to herein as word lines or select lines) to form rows. Additionally, the memory cells may be coupled to one another by sense lines (which may be referred to herein as data lines or digit lines) to form columns. Although a single array of memory cells **130** is shown in FIG. **1**, embodiments are not so limited. For instance, memory device **120** may represent a plurality of array of memory cells **130** (e.g., array of memory cells included in a number of banks of DRAM cells, NAND flash cells, etc.) in addition to a plurality of subarrays, as described herein. Accordingly, descriptions in the present disclosure may be made with regard to DRAM architectures by way of example and/or clarity. However, unless explicitly stated otherwise, the scope of the present disclosure and claims is not limited to DRAM architectures.

[0027] As further shown in FIG. **1**, the memory device **120** may include address circuitry **142** to latch address signals provided over a data bus **156** (e.g., an I/O bus from host **110**) by I/O circuitry **144** (e.g., provided to external ALU circuitry and to DRAM DQs via local I/O lines and global I/O lines) included within the memory device **120**. As further shown in FIG. **1**, the host **110** may include a channel controller **143**. Status and exception information may be provided from the controller **140** of the memory device **120** to the channel controller **143**, for example, through a control bus **154**, which in turn may be provided from the channel controller **143** to host **110**. Address signals may be received (e.g., from channel controller **143** or another host component) through address circuitry **142** and may be decoded via a row decoder **146** and/or a column decoder **152** to access the array of memory cells **130**. Data may be sensed from the array of memory cells **130** by sensing voltage and/or current changes on sense lines (digit lines) using sense amplifiers (e.g., shown as read/latch circuitry **150** in FIG. **1**). Data may be sensed from the array of memory cells **130** in sizes of 256 bits, 128 bits, 64 bits, among other possibilities. The read/latch circuitry **150** may include a number of sense amplifiers, as described herein, to latch a page (e.g., a row or a portion of a row) of data from the array of memory cells **130**. The input-output (I/O) circuitry **144** may include data I/O pins to be used for bi-directional data communication with host **110** over the data bus **156** (e.g., a 64 bit wide data bus, a 128 bit wide data bus, a 256 bit wide data bus, etc.). The memory device **120** may further include write circuitry **148** that may be used to write data to the array of memory cells **130**.

[0028] The controller **140** may decode signals (e.g., commands) provided by control bus **154** from host **110**. The controller **140** may be configured to receive a command from the host **110** regarding ordering data sensed from the array of memory cells **130**. For example, the controller **140** may receive a command to order the bits of data based on a matrix configuration and/or size. The controller **140** may control operations by issuing signals determined from the decoded commands from host **110**. These signals may include chip enable signals, write enable signals, address signals (e.g., subarray address signals, row address signals, and/or latch address signals) that may be used to control operations performed on the array of memory cells **130**, including data sense, data store, subarray addressing, row addressing, latch addressing, data move, data write, and data erase operations, among other operations. In various embodiments, the controller **140** may be responsible for executing instructions from host **110** and accessing the sense amplifiers for a prefetch operation or a write operation.

[0029] As further shown in FIG. **1**, the memory device **120** includes a column decode

circuitry/multiplexer **152**. The controller **140** may be capable of directing circuitry such as the read/latch circuitry **150** to transfer data from the array of memory cells **130**. In a number of embodiments, the controller **140** may direct the column decode circuitry **152** to send the data in a prefetch operation from the number of sense amplifiers to DQs via column decode circuitry **152** in a particular order. Additionally or alternatively, the controller may direct the column decode circuitry **152** to write data received by the I/O circuitry **144** to the read/latch circuitry **150** via column decode circuitry **152** in a particular order. The data may be received by the I/O circuitry **144** via the data bus **156** from the host **110**. The data can be written to the read/latch circuitry **150** in the particular order to prepare the data for a subsequent read operation that will request the data in a matrix configuration that corresponds to the particular order which the data was written to the read/latch circuitry.

[0030] FIG. 2 is a block diagram of an array of memory cells **230** of the memory device and a controller **240** of the memory device in accordance with a number of embodiments of the present disclosure. The architecture of the array of memory cells **230** may include a plurality of columns (e.g., “X” columns **222** as shown in FIG. 2). Additionally, the array **230** may be divided into a plurality of subarrays **225-0** (SUBARRAY 0), **225-1** (SUBARRAY 1), . . . , **225-N-1** (SUBARRAY **225-N-1**), which may be separated by respective amplification regions that may include groups (e.g., sets) of sense amplifiers. The groups of sense amplifiers may be referred to as sense amplifier stripes or read/latch stripes. For example, as shown in FIG. 2, each of the subarrays **225-0**, **225-1**, . . . , **225-N-1** has an associated read/latch stripe associated therewith (e.g., **224-0**, **224-1**, . . . , **224-N-1**, respectively).

[0031] The array of memory cells **230** may include 64 subarrays, 128 subarrays, 256 subarrays, 512 subarrays, among various other possible numbers of subarrays. However, embodiments are not so limited, and some embodiments of an array of memory cells may have a different number of subarrays than just presented. In a number of embodiments, the subarrays **225** may have the same number of rows in each subarray (e.g., 256 rows, 512 rows, 1024 rows, 2048 rows, among various other possible numbers of rows). However, embodiments are not so limited, and at least some of a plurality of subarrays within the array of memory cells **230** may have different numbers of rows.

[0032] Each column **222** is configured to be coupled to read/latch circuitry (e.g., read/latch circuitry **150** as described in connection with FIG. 1 and elsewhere herein). As such, each column in a subarray may be coupled individually to a sense amplifier that contributes to a set of sense amplifiers (e.g., a read/latch stripe) for that subarray. For example, as shown in FIG. 2, the array of memory cells **230** may include read/latch stripe **0**, read/latch stripe **1**, . . . , read/latch stripe **N-1**, shown at **224-0**, **224-1**, . . . , **224-N-1**, that each have read/latch circuitry with a set of sense amplifiers that may, in various embodiments, be used as registers, cache, and data buffering. The sense amplifiers (e.g., as shown at **306** and described in connection with FIG. 3) may be coupled to each column **222** in the subarrays **225-0**, **225-1**, . . . , **225-N-1**. Each of the subarrays **225-0**, **225-1**, . . . , **225-N-1** may include a respective plurality of rows (e.g., a respective group of “Y” rows **219**). Each read/latch stripe **224-0**, **224-1**, . . . , **224-N-1** can be coupled to column decode circuitry/multiplexer (e.g., column decode circuitry/multiplexer **152** in FIGS. 1 and **352** in FIG. 3) which can be coupled to an I/O component (e.g., I/O component circuitry **144** in FIG. 1 and I/O component **344** in FIG. 3) to send data from the read/latch stripes to apparatus coupled to the array of memory cells **230**.

[0033] FIG. 2 is a schematic diagram of a portion of a memory device in accordance with a number of embodiments of the present disclosure. FIG. 2 illustrates an example that includes 1T1C memory cells, in a folded DRAM configuration, that are each coupled to a sense amplifier **206**. However, embodiments are not so limited, such that some embodiments may have memory cells in a 2T2C DRAM configuration.

[0034] FIGS. 3 is a schematic diagram illustrating a row of an array of memory cells in accordance with a number of embodiments of the present disclosure. As shown in FIG. 3, a portion of the

subarray **325** includes a row **319-1** that may include a plurality of X memory cells **308-0 . . . 308-X-1**. The memory cells **308-0 . . . 308-X-1** may be located at the intersection of a plurality of X digit lines **305-0 . . . 305-X-1** with the row **319-1**. The plurality of digit lines **305-0 . . . 305-X-1** are referred to as DIGIT LINE 1. . . . DIGIT LINE X-1 in the illustration. The number X corresponds to a number of columns (e.g., the number of columns **222** shown in FIG. 2). As further shown in FIG. 3, the memory cells **308-0 . . . 308-X-1** may each be connected to associated read/latch circuitry **350-0 . . . 350-X-1**, respectively. Each of the read/latch circuitry **350-0 . . . 350-X-1** includes a respective sense amplifier **306-0 . . . 306-X-1**. The sense amplifiers **306-1 . . . 306-X-1** are referred to as sense amplifiers **1 . . . X-1** in the illustration. As illustrated, a sense amplifier associated with a memory cell is disposed between the memory cell and the column decode circuitry **352**. The sense amplifier may be operated to determine a data value (e.g., logic state) stored in a selected memory cell. The sense amplifier **306** may include a cross coupled latch (not shown). The sense amplifier **306** may be coupled to equilibration circuitry (not shown), which may be configured to equilibrate the sense lines **305-1** and **305-2**.

[0035] Each memory cell of the plurality of memory cells may include a transistor serving as an access element and a capacitor serving as a storage element. The number of data values (e.g., voltages) sensed from the memory cells (e.g., in activate operations) may correspond to the number of columns of memory cells that intersect a row of a subarray, such as row **319-1** of FIG. 3. For example, a total of X number of data values may be stored by the plurality of memory cells **308-0 . . . 308-X-1**.

[0036] As further shown, the portion of the subarray **325** illustrated in FIG. 3 is connected to column decode circuitry **352**. In particular, each memory cell is connected to the column decode circuitry **352** via a digit line associated with the memory cell and via a sense amplifier connected to the digit line, as shown. The column decode circuitry **352**, in turn, is connected to an input-output component **344** that includes the DQs that transfer data from the memory system to a requesting device such as a processing resource and/or host. The I/O component **344** may be referred to as a data interface because it provides an interface or connection point to other components or device to facilitate an exchange of data. An architecture such as that shown in FIG. 3 allows the column decode circuitry **352** to read data stored in each memory cell and organize the data independent of reading data stored in other memory cells.

[0037] A controller (e.g., the controller **140** in FIG. 1) may be configured to receive (e.g., from host **110**) coded instructions for performance of a data movement operation from the selected row of a subarray of the array of memory cells (e.g., a read, write, erase operation, etc.) and/or a compute operation (e.g., a logical operation, such as a Boolean operation, among other logical operations performed by a processor, such as processor **145** in FIG. 1) on a data value stored by a memory cell of the selected row. For example, the controller may be configured to receive a command for an operation that includes a request for performance of a DRAM operation (e.g., a DRAM activate, read, and/or write operation). The controller may be further configured to sequence or organize the data values of a row in a matrix configuration between the sense amplifier and an I/O component (e.g., the I/O circuitry **144** in FIG. 1) via column decode circuitry **352**. The controller may direct column decode circuitry **352** and/or column select circuitry to organize the data values of the row in the matrix configuration. As such, the sense amplifiers described herein are configured to enable performance of memory operations and/or compute operations in connection with the selected row.

[0038] In a number of embodiments, bits of data corresponding from memory cells **308-0, . . . , 308-X-1** on row **319-1** can be latched in (e.g., temporarily stored in) sense amplifiers **306-1, . . . , 306-X-1**. The bits of data can be transferred from sense amplifiers **306-1, . . . , 306-X-1** to I/O component **344** via column decode circuitry **352**. Column decode circuitry **352** can transfer the bits of data from sense amplifiers **306-1, . . . , 306-X-1** in a particular order. For example, column decode circuitry **352** can transfer the bits of data in sequential order starting with the bit of data in sense amplifier **306-0** and ending with the bit of data in sense amplifier **306-X-1**. The column

decode circuitry **352** can transfer the bits of data corresponding to a matrix configuration. For example, column decode circuitry **352** can transfer 8 bits of data corresponding to a row, column, and or diagonal of matrix from corresponding sense amplifiers. The bits of data corresponding to a row of a matrix can correspond to every eighth sense amplifier of the sense amplifiers **306-0**, . . . , **306-63**.

[0039] FIG. **4** is a block diagram illustrating an apparatus and method for transferring bits between sense amplifiers and I/O circuitry via column decode circuitry in a particular order in accordance with a number of embodiments of the present disclosure. In FIG. **4**, sense amplifiers **406-0**, . . . , **406-X-1** can store bits of data from a row of memory cells in an array of memory cells. The bits of data can be transferred from the row of memory cells and stored in sense amplifiers **406-0**, . . . , **406-X-1** in response to an activate request. The column decode circuitry **452** can select bits of data from sense amplifiers **406-0**, . . . , **406-X-1** to send the bits of data in a particular order to the I/O component **444** (e.g., a read operation). In the example depicted in FIG. **4**, the column decode circuitry **452** can be configured to send 8 bits at time to the I/O component **444**. Although, embodiments are not limited to 8 bits and any number of bits can be sent to the I/O component **444** at a time as part of a prefetch operation. For example, 8, 32, 64, and/or 128 bits, among other numbers of bits, can be sent to I/O component **444** at a time as part of a prefetch operation. The number of bits sent at a time during a prefetch operation can be based on a number of DQs in I/O component **444** and a burst length of the memory system.

[0040] In a number of embodiments, column decode circuitry **452** can select the 8 bits stored in group **407-1** of sense amplifiers **407-1** including sense amplifiers **406-0**, . . . , **406-7** and send those 8 bits to I/O component **444**. After sending bits from group **407-1** to I/O component **444**, multiplexer **460** can select the 8 bits stored in group **407-2** of sense amplifiers **407-1** including sense amplifiers **406-8**, . . . , **406-15** and send those 8 bits to I/O component **444**. After sending bits from group **407-2** to I/O component **444**, column decode circuitry **452** can continue select groups of sense amplifiers until bits from group **407-M** including sense amplifiers **406-X-8**, . . . , **406-X-1** are sent to I/O component **444**.

[0041] In a number of embodiments, column decode circuitry **452** can select 8 bits stored in sense amplifiers with each of the 8 bits stored in different groups to first send to I/O component **444**. For example, a first bit of the 8 bits can be from a first sense amplifier of a first group (e.g., sense amplifier **406-0** of group **407-1**), a second bit of the 8 bits can be from a first sense amplifier of a second group (e.g., sense amplifier **406-8** of group **407-8**), and so on until a final bit of the 8 bits is from a first sense amplifier of an eight group (not shown). After sending the bits from a first sense amplifier of 8 groups of sense amplifiers, column decode circuitry **452** can continue to select 8 bits from a second sense amplifier of the 8 groups of sense amplifiers.

[0042] In FIG. **4**, I/O component **444** can receive bits of data and the bits of data can be written to sense amplifiers **406-0**, . . . , **406-X-1** in a particular order. The column decode circuitry **452** can receive bits of data from I/O component **444** select the sense amplifiers **406-0**, . . . , **406-X-1** such that data is written to the sense amplifiers **406-0**, . . . , **406-X-1** in a particular order. In FIG. **4**, the column decode circuitry **452** can be configured to send 8 bits at time from the I/O component **444** to sense amplifiers **406-0**, . . . , **406-X-1**. Although, embodiments are not limited to 8 bits and any number of bits can be sent from the I/O component **444** to sense amplifiers **406-0**, . . . , **406-X-1** at a time as part of a write operation. For example, 8, 32, 64, and/or 128 bits, among other numbers of bits, can be sent to I/O component **444** at a time as part of a write operation. The number of bits sent at a time during a write operation can be based on a number of DQs in I/O component **444** and a burst length of the memory system.

[0043] In a number of embodiments, column decode circuitry **452** can select the sense amplifiers in group **407-1** include sense amplifiers **406-0**, . . . , **406-7** and to receive the first 8 bits of data and the first 8 bits can be written to group **407-1**. After writing the first 8 bits to the sense amplifiers in group **407-1**, column decode circuitry **452** can select the sense amplifiers in group **407-2** include

sense amplifiers **406-8**, . . . , **406-15** and to receive the second 8 bits of data and the second 8 bits can be written to group **407-2**. After sending bits to the sense amplifiers in group **407-2**, column decode circuitry **452** can continue select groups of sense amplifiers to receive bits until bits from group **407-M** including sense amplifiers **406-X-8**, . . . , **406-X-1** have received 8 bits of data, which may correspond to the final 8 bits in a write command.

[0044] In a number of embodiments, column decode circuitry **452** can select 8 sense amplifiers with each of the sense amplifiers in different groups. For example, a first sense amplifier of the first group (e.g., sense amplifier **406-0** of group **407-1**) can receive a first bit of 8 bits, a first sense amplifier of the second group (e.g., sense amplifier **406-8** of group **407-2**) can receive a second bit of 8 bits, and so on until a first sense amplifier of an eight group (not shown) receive an eight bit of 8 bits. After sending the bits to a first sense amplifier of 8 groups of sense amplifiers, column decode circuitry **452** can continue to select second sense amplifiers from the 8 groups of sense amplifiers and/or select another 8 groups of sense amplifiers and select sense amplifiers from those 8 groups to send bits of data. The column decode circuitry **452**, according to embodiments of the present disclosure, can select the sense amplifiers to receive the bits of data in any order and can select any number of sense amplifiers at a given time to receive bits of data.

[0045] FIG. **5** is a flow diagram of an example method to perform a read operation in accordance with a number of embodiments of the present disclosure. FIG. **5** is a flow diagram of an example method **560** to perform a read operation. Method **560** can be performed by the apparatuses and system described above in association with FIGS. **1-4**. Although the method is shown in a particular sequence or order, unless otherwise specified, the order of the processes can be modified. Thus, the illustrated implementations should be understood only as examples, and the illustrated processes can be performed in a different order, and some processes can be performed in parallel. Additionally, one or more processes can be omitted in various embodiments. Thus, not all processes are required in every implementation. Other process flows are possible.

[0046] At block **562**, the method **560** may include latching bits of data from a row of memory cells in a number of sense amplifiers

[0047] At block **564**, the method **560** may include sending the bits of data from the number of sense amplifiers to a data interface of a memory device via column decode circuitry in a particular order, wherein the column decode circuitry is configured to request bits of data from the number of sense amplifiers and send the bits of data to the data interface in the particular order.

[0048] FIG. **6** is a flow diagram of an example method to perform a write operation in accordance with a number of embodiments of the present disclosure. FIG. **6** is a flow diagram of an example method **670** to perform a write operation. Method **670** can be performed by the apparatuses and system described above in association with FIGS. **1-4**. Although the method is shown in a particular sequence or order, unless otherwise specified, the order of the processes can be modified. Thus, the illustrated implementations should be understood only as examples, and the illustrated processes can be performed in a different order, and some processes can be performed in parallel. Additionally, one or more processes can be omitted in various embodiments. Thus, not all processes are required in every implementation. Other process flows are possible.

[0049] At block **672**, the method **670** may include receiving a number of bits of data from a host.

[0050] At block **674**, the method **670** may include sending the number of bits of data from a data interface to a number of sense amplifiers through column decode circuitry, wherein the bits are sent to the number of sense amplifiers in a particular order.

[0051] Although specific embodiments have been illustrated and described herein, those of ordinary skill in the art will appreciate that an arrangement calculated to achieve the same results can be substituted for the specific embodiments shown. This disclosure is intended to cover adaptations or variations of various embodiments of the present disclosure. It is to be understood that the above description has been made in an illustrative fashion, and not a restrictive one. Combination of the above embodiments, and other embodiments not specifically described herein

will be apparent to those of skill in the art upon reviewing the above description. The scope of the various embodiments of the present disclosure includes other applications in which the above structures and methods are used. Therefore, the scope of various embodiments of the present disclosure should be determined with reference to the appended claims, along with the full range of equivalents to which such claims are entitled.

[0052] In the foregoing Detailed Description, various features are grouped together in a single embodiment for the purpose of streamlining the disclosure. This method of disclosure is not to be interpreted as reflecting an intention that the disclosed embodiments of the present disclosure have to use more features than are expressly recited in each claim. Rather, as the following claims reflect, inventive subject matter lies in less than all features of a single disclosed embodiment. Thus, the following claims are hereby incorporated into the Detailed Description, with each claim standing on its own as a separate embodiment.

Claims

1. An apparatus, comprising: an array of memory cells; a data interface; a column decode circuitry coupled between the array of memory cells and the data interface; and a controller coupled to the array of memory cells, the controller configured to cause the apparatus to: transfer data from an array of memory cells, wherein the data is organized in a linear configuration and is an amount of data in a matrix, wherein the matrix has a matrix configuration; and select a first portion of the data that corresponds to a first portion of the matrix configuration to transfer to a processing resource.
2. The apparatus of claim 1, wherein the first portion of the data corresponds to a row of the matrix configuration.
3. The apparatus of claim 1, wherein the column decode circuitry is configured to send the first portion of data to the processing resource.
4. The apparatus of claim 1, wherein the controller is further configured to cause the column code circuitry to select the first portion of data.
5. The apparatus of claim 1, wherein a read operation transfers the data from the array of memory cells.
6. The apparatus of claim 1, wherein a prefetch operation transfers the data from the array of memory cells.
7. The apparatus of claim 1, wherein the controller configured to cause the apparatus to select a second portion of the data that corresponds to a second portion of the matrix configuration to transfer to the processing resource.
8. The apparatus of claim 7, wherein the second portion of the data corresponds to a second row of the matrix configuration.
9. The apparatus of claim 7, wherein the second portion of the data corresponds to a first column of the matrix configuration.
10. An apparatus, comprising: an array of memory cells; a data interface; a column decode circuitry coupled between the array of memory cells and the data interface; and a controller coupled to the array of memory cells, the controller configured to cause the apparatus to: transfer data from the array of memory cells, wherein the data is organized in a linear configuration and corresponds to at least a portion of a matrix having a matrix configuration; and selecting a first portion of the data that corresponds to a first portion of the matrix configuration to transfer to a processing resource.
11. The apparatus of claim 10, wherein the first portion of the data corresponds to a first row of the matrix configuration.
12. The apparatus of claim 10, wherein the first portion of the data corresponds to a column row of the matrix configuration.
13. The apparatus of claim 10, wherein the first portion of the data was transferred from adjacent memory cells in the array of memory cells.

- 14.** The apparatus of claim 10, wherein the first portion of the data was transferred from non-adjacent memory cells in the array of memory cells.
- 15.** A method, comprising: transferring data from an array of memory cells, wherein the data is organized in a linear configuration and is an amount of data in a matrix, wherein the matrix has a matrix configuration; and selecting a first portion of the data that corresponds to a first portion of the matrix configuration to transfer to a processing resource.
- 16.** The method of claim 15, further including selecting the first portion of the data to correspond to a first row of the matrix configuration.
- 17.** The method of claim 15, further including transferring the data from the array of memory cells via a read operation.
- 18.** The method of claim 15, further including transferring the data from the array of memory cells via a prefetch operation.
- 19.** The method of claim 15, further including selecting a second portion of the data that corresponds to a second portion of the matrix configuration to transfer to the processing resource.
- 20.** The method of claim 19, wherein the second portion of the data corresponds to a second row of the matrix configuration.
-