

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250267643

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

ZENG; Wei et al.

WAVEFORM SELECTION IN WIRELESS COMMUNICATIONS

Abstract

Techniques are described that provide for waveform selection for uplink (UL) and/or downlink (DL) wireless transmissions based on one or more factors associated with the wireless transmission, a transmitter that is to transmit the wireless transmission, or combinations thereof. UL and DL transmissions may use one of a number of different waveforms, such as single-carrier waveforms that use a single carrier for information transmission of a wireless channel, and multi-carrier waveforms that use multiple carriers at different frequencies to transmit some of the bits on each channel. Multi-carrier transmission waveforms or single-carrier waveforms may be selected for wireless transmissions based on a bandwidth allocated for the transmissions, a capability of a transmitter that is to transmit the transmissions, or combinations thereof.

Inventors: ZENG; Wei (Saratoga, CA), CHEN; Wanshi (San Diego, CA), JI; Tingfang (San Diego, CA), GAAL; Peter (San Diego, CA)

Applicant: QUALCOMM Incorporated (San Diego, CA)

Family ID: 1000008589296

Appl. No.: 19/204249

Filed: May 09, 2025

Related U.S. Application Data

parent US continuation 17810432 20220701 parent-grant-document US 12302300 child US 19204249

parent US division 15612762 20170602 parent-grant-document US 11405914 child US 17810432
us-provisional-application US 62400086 20160926

Publication Classification

Int. Cl.: H04W72/0453 (20230101); **H04L5/00** (20060101); **H04L5/14** (20060101); **H04L27/00** (20060101); **H04L27/26** (20060101); **H04W72/23** (20230101); **H04W88/06** (20090101)

U.S. Cl.:

CPC H04W72/0453 (20130101); **H04L5/0007** (20130101); **H04L5/001** (20130101); **H04L5/0064** (20130101); **H04L5/0091** (20130101); **H04L5/1453** (20130101); **H04L27/0012** (20130101); **H04L27/2646** (20130101); **H04L27/2666** (20130101); **H04W72/23** (20230101); **H04W88/06** (20130101); H04L27/2636 (20130101)

Background/Summary

CROSS REFERENCES [0001] The present Application for Patent is a continuation of U.S. patent application Ser. No. 17/810,432 by ZENG et al., entitled “WAVEFORM SELECTION IN WIRELESS COMMUNICATIONS,” filed Jul. 1, 2022, which is a divisional of U.S. patent application Ser. No. 15/612,762 by ZENG et al., entitled “WAVEFORM SELECTION IN WIRELESS COMMUNICATIONS,” filed Jun. 2, 2017, which claims priority to and the benefit of U.S. Provisional Application Ser. No. 62/400,086, entitled “WAVEFORM SELECTION IN WIRELESS COMMUNICATIONS,” filed Sep. 26, 2016. All of said applications are assigned to the assignee hereof, and are expressly incorporated by reference herein as if fully set forth and for all applicable purposes.

INTRODUCTION

[0002] The following relates generally to wireless communication, and more specifically to waveform selection in wireless communications based on user equipment (UE) capability, transmission bandwidth, or combinations thereof.

[0003] Wireless communication systems are widely deployed to provide various types of communication content such as voice, video, packet data, messaging, broadcast, and so on. These systems may be multiple-access systems capable of supporting communication with multiple users by sharing the available system resources (e.g., time, frequency, and power). Examples of such multiple-access systems include code-division multiple access (CDMA) systems, time-division multiple access (TDMA) systems, frequency-division multiple access (FDMA) systems, and orthogonal frequency-division multiple access (OFDMA) systems.

[0004] In some examples, a wireless multiple-access communication system may include a number of base stations, each simultaneously supporting communication for multiple communication devices, otherwise known as UEs. In a Long-Term Evolution (LTE) or LTE-Advanced (LTE-A) network, a set of one or more base stations may define an eNodeB (eNB). In other examples (e.g., in a next generation new radio (NR) or 5G network), a wireless multiple access communication system may include a number of smart radio heads (radio heads (RHs)) in communication with a number of access node controllers (ANCs), where a set of one or more RHs, in communication with an ANC, defines a base station (e.g., an eNB). A base station may communicate with a set of UEs on downlink (DL) channels (e.g., for transmissions from a base station to a UE) and uplink (UL) channels (e.g., for transmissions from a UE to a base station).

[0005] As communications providers continue to increase the capacity of wireless networks, and as demand for such capacity grows, efficient use of wireless resources becomes increasingly important for high quality and relatively low cost wireless communications. Efficient use of wireless resources may include providing available wireless resources and coordinating communications in a manner that allows each UE being served to efficiently utilize network resources and enhance user experience.

SUMMARY

[0006] A method of wireless communication is described. The method may include receiving a radio frequency (RF) capability indication from a UE, selecting a multi-carrier waveform or a single-carrier waveform for a wireless transmission between the UE and the base station, and transmitting an indication of the selected waveform to the UE.

[0007] An apparatus for wireless communication is described. The apparatus may include means for receiving a RF capability indication from a UE, means for selecting a multi-carrier waveform or a single-carrier waveform for a wireless transmission between the UE and the base station, and means for transmitting an indication of the selected waveform to the UE.

[0008] Another apparatus for wireless communication is described. The apparatus may include a processor, memory in electronic communication with the processor, and instructions stored in the memory. The instructions may be operable to cause the processor to receive a RF capability indication from a UE, select a multi-carrier waveform or a single-carrier waveform for a wireless transmission between the UE and the base station, and transmit an indication of the selected waveform to the UE.

[0009] A non-transitory computer readable medium for wireless communication is described. The non-transitory computer-readable medium may include instructions operable to cause a processor to receive a RF capability indication from a UE, select a multi-carrier waveform or a single-carrier waveform for a wireless transmission between the UE and the base station, and transmit an indication of the selected waveform to the UE.

[0010] A method of wireless communication at a base station is described. The method may include receiving a RF capability indication from a UE, identifying a bandwidth for a wireless transmission between the UE and the base station, selecting a waveform for the wireless transmission between the UE and the base station based at least in part on the RF capability indication or the bandwidth, or both, and transmitting an indication of the selected waveform to the UE.

[0011] Another apparatus for wireless communication is described. The apparatus may include a processor, memory in electronic communication with the processor. The processor and memory configured to receive a RF capability indication from a UE, identify a bandwidth for a wireless transmission between the UE and the apparatus, select a waveform for the wireless transmission between the UE and the apparatus based at least in part on the RF capability indication or the bandwidth, or both, and transmit an indication of the selected waveform to the UE.

[0012] In some examples of the method, apparatus, and non-transitory computer-readable medium described above, the waveform comprises a multi-carrier waveform or a single-carrier waveform. In some examples of the method, apparatus, and non-transitory computer-readable medium described above, the wireless transmission is an UL transmission and the waveform selection is performed independently of a waveform of a DL transmission.

[0013] Some examples of the method, apparatus, and non-transitory computer-readable medium described above may further include processes, features, means, or instructions for receiving the wireless transmission from the UE using the selected waveform. Some examples of the method, apparatus, and non-transitory computer-readable medium described above may further include processes, features, means, or instructions for transmitting the wireless transmission to the UE using the selected waveform.

[0014] In some examples of the method, apparatus, and non-transitory computer-readable medium described above, the RF capability indication indicates a single-carrier bandwidth capability of the UE. Some examples of the method, apparatus, and non-transitory computer-readable medium described above may further include processes, features, means, or instructions for identifying a bandwidth for the wireless transmission. Some examples of the method, apparatus, and non-transitory computer-readable medium described above may further include processes, features, means, or instructions for determining that the bandwidth for the wireless transmission exceeds the single-carrier bandwidth capability of the UE, and selecting the multi-carrier waveform responsive

to the determining.

[0015] In some examples of the method, apparatus, and non-transitory computer-readable medium described above, the RF capability indication indicates that the UE is to use carrier aggregation (CA) for transmission of the wireless transmission, and wherein the multi-carrier waveform may be selected based at least in part on the indication of CA.

[0016] Some examples of the method, apparatus, and non-transitory computer-readable medium described above may further include processes, features, means, or instructions for identifying a bandwidth for the wireless transmission, selecting the multi-carrier waveform when the bandwidth for the wireless transmission exceeds a threshold value, and selecting the single-carrier waveform when the bandwidth for the wireless transmission does not exceed the threshold value.

[0017] Some examples of the method, apparatus, and non-transitory computer-readable medium described above may further include processes, features, means, or instructions for identifying one or more of a signal-to-noise ratio (SNR) for the UE, a transmission mode (TM) of the wireless transmission, or a modulation-and-coding scheme (MCS) of the wireless transmission, and selecting the multi-carrier waveform based at least in part on the SNR, TM, MCS, or any combination thereof.

[0018] In some examples of the method, apparatus, and non-transitory computer-readable medium described above, the single-carrier waveform comprises a discrete Fourier transform (DFT) spread orthogonal frequency division multiplexing (DFT-s-OFDM) waveform, or any non-IFFT-based single carrier waveform. In some examples of the method, apparatus, and non-transitory computer-readable medium described above, the multi-carrier waveform comprises an orthogonal frequency division multiplexing (OFDM) waveform.

[0019] A method of wireless communication is described. The method may include transmitting a RF capability indication to a base station, receiving an indication of whether an UL transmission to the base station is to be transmitted using a multi-carrier waveform or a single-carrier waveform, and transmitting the wireless transmission using the indicated multi-carrier waveform or single carrier waveform.

[0020] Another method of wireless communication at a UE is described. The method may include transmitting a RF capability indication to a base station, receiving in response to the RF capability indication, from the base station, an indication of a waveform or a bandwidth, or both for a wireless transmission between the UE and the base station, identifying a waveform for the wireless transmission based at least in part on the indication of the waveform or the bandwidth, or both, and performing the wireless transmission using the identified waveform.

[0021] An apparatus for wireless communication is described. The apparatus may include means for transmitting a RF capability indication to a base station, means for receiving an indication of whether an UL transmission to the base station is to be transmitted using a multi-carrier waveform or a single-carrier waveform, and means for transmitting the UL transmission using the indicated multi-carrier waveform or single carrier waveform.

[0022] Another apparatus for wireless communication is described. The apparatus may include a processor, memory in electronic communication with the processor, and instructions stored in the memory. The instructions may be operable to cause the processor to transmit a RF capability indication to a base station, receive an indication of whether an UL transmission to the base station is to be transmitted using a multi-carrier waveform or a single-carrier waveform, and performing the wireless transmission using the identified waveform.

[0023] Another apparatus for wireless communication is described. The apparatus may include a processor, memory in electronic communication with the processor. The processor and memory configured to transmit a RF capability indication to a base station, receive in response to the RF capability indication, from the base station, an indication of a waveform or a bandwidth, or both for a wireless transmission between the apparatus and the base station, identify a waveform for the wireless transmission based at least in part on the indication of the waveform or the bandwidth, or

both, and transmit the wireless transmission using the identified waveform.

[0024] A non-transitory computer readable medium for wireless communication is described. The non-transitory computer-readable medium may include instructions operable to cause a processor to transmit a RF capability indication to a base station, receive an indication of whether an UL transmission to the base station is to be transmitted using a multi-carrier waveform or a single-carrier waveform, and transmit a UL transmission using the indicated multi-carrier waveform or single carrier waveform.

[0025] In some examples of the method, apparatus, and non-transitory computer-readable medium described above, the waveform comprises a multi-carrier waveform or a single-carrier waveform. In some examples of the method, apparatus, and non-transitory computer-readable medium described above, the waveform is based at least in part on the RF capability indication.

[0026] Some examples of the method, apparatus, and non-transitory computer-readable medium described above may further include processes, features, means, or instructions for receiving the wireless transmission from the base station using the identified waveform or transmitting the wireless transmission to the base station using the identified waveform. In some examples of the method, apparatus, and non-transitory computer-readable medium described above, the RF capability indication indicates a single-carrier bandwidth capability of the UE, or a capability of the UE to use carrier aggregation for transmission of an uplink transmission, or a combination thereof.

[0027] In some examples of the method, apparatus, and non-transitory computer-readable medium described above, the RF capability indication indicates a single-carrier bandwidth capability of the UE. In some examples of the method, apparatus, and non-transitory computer-readable medium described above, the RF capability indication indicates that the UE is to use CA for transmission of the UL transmission.

[0028] Some examples of the method, apparatus, and non-transitory computer-readable medium described above may further include processes, features, means, or instructions for identifying one or more of a SNR for the UE, a TM of the UL transmission, or a MCS of the UL transmission. Some examples of the method, apparatus, and non-transitory computer-readable medium described above may further include processes, features, means, or instructions for transmitting the identified SNR, TM, or MCS to the base station.

[0029] In some examples of the method, apparatus, and non-transitory computer-readable medium described above, the single-carrier waveform comprises a DFT-s-OFDM waveform or any non-IFFT-based single carrier waveform. In some examples of the method, apparatus, and non-transitory computer-readable medium described above, the multi-carrier waveform comprises an OFDM waveform.

[0030] A method of wireless communication is described. The method may include identifying a bandwidth for a wireless transmission between a UE and the base station, selecting a multi-carrier waveform or a single-carrier waveform for the wireless transmission based at least in part on the identified bandwidth for the wireless transmission, and transmitting an indication of the selected waveform to the UE.

[0031] An apparatus for wireless communication is described. The apparatus may include means for identifying a bandwidth for a wireless transmission between a UE and the base station, means for selecting a multi-carrier waveform or a single-carrier waveform for the wireless transmission based at least in part on the identified bandwidth for the wireless transmission, and means for transmitting an indication of the selected waveform to the UE.

[0032] Another apparatus for wireless communication is described. The apparatus may include a processor, memory in electronic communication with the processor, and instructions stored in the memory. The instructions may be operable to cause the processor to identify a bandwidth for a wireless transmission between a UE and the base station, select a multi-carrier waveform or a single-carrier waveform for the wireless transmission based at least in part on the identified bandwidth for the wireless transmission, and transmit an indication of the selected waveform to the

UE.

[0033] A non-transitory computer readable medium for wireless communication is described. The non-transitory computer-readable medium may include instructions operable to cause a processor to identify a bandwidth for a wireless transmission between a UE and the base station, select a multi-carrier waveform or a single-carrier waveform for the wireless transmission based at least in part on the identified bandwidth for the wireless transmission, and transmit an indication of the selected waveform to the UE.

[0034] In some examples of the method, apparatus, and non-transitory computer-readable medium described above, the wireless transmission is an UL transmission and the waveform selection is performed independently of a waveform of a DL transmission. Some examples of the method, apparatus, and non-transitory computer-readable medium described above may further include processes, features, means, or instructions for receiving the wireless transmission from the UE using the selected waveform. Some examples of the method, apparatus, and non-transitory computer-readable medium described above may further include processes, features, means, or instructions for transmitting the wireless transmission to the UE using the selected waveform.

[0035] In some examples of the method, apparatus, and non-transitory computer-readable medium described above, the RF capability indication indicates a single-carrier bandwidth capability of the UE, or a capability of the UE to use CA for transmission of the UL transmission, or a combination thereof.

[0036] Some examples of the method, apparatus, and non-transitory computer-readable medium described above may further include processes, features, means, or instructions for determining that the bandwidth comprises two or more component carriers (CCs), and identifying a multi-carrier waveform based at least in part on the determining. Some examples of the method, apparatus, and non-transitory computer-readable medium described above may further include processes, features, means, or instructions for identifying a multi-carrier waveform based at least in part on the bandwidth exceeding a threshold. Some examples of the method, apparatus, and non-transitory computer-readable medium described above may further include processes, features, means, or instructions for identifying a multi-carrier waveform based at least in part on the bandwidth exceeding the RF capability.

[0037] Some examples of the method, apparatus, and non-transitory computer-readable medium described above may further include processes, features, means, or instructions for receiving a RF capability indication from the UE, and wherein the selecting the multi-carrier waveform or a single-carrier waveform may be based at least in part on the RF capability indication.

[0038] In some examples of the method, apparatus, and non-transitory computer-readable medium described above, the RF capability indication indicates a single-carrier bandwidth capability of the UE, it is determined whether the bandwidth for the wireless transmission exceeds the single-carrier bandwidth capability of the UE, and the multi-carrier waveform or single-carrier waveform is selected responsive to the determination.

[0039] In some examples of the method, apparatus, and non-transitory computer-readable medium described above, the RF capability indication indicates that the UE is to use CA for transmission of the wireless transmission, and the multi-carrier waveform may be selected based at least in part on the indication of CA.

[0040] A method of wireless communication is described. The method may include receiving, from a base station, an indication of a bandwidth for a wireless transmission between the UE and the base station and identifying a multi-carrier waveform or a single-carrier waveform for the wireless transmission based at least in part on the indication of the bandwidth for the wireless transmission.

[0041] An apparatus for wireless communication is described. The apparatus may include means for receiving, from a base station, an indication of a bandwidth for a wireless transmission between the UE and the base station and means for identifying a multi-carrier waveform or a single-carrier waveform for the wireless transmission based at least in part on the indication of the bandwidth for

the wireless transmission.

[0042] Another apparatus for wireless communication is described. The apparatus may include a processor, memory in electronic communication with the processor, and instructions stored in the memory. The instructions may be operable to cause the processor to receive, from a base station, an indication of a bandwidth for a wireless transmission between the UE and the base station and identify a multi-carrier waveform or a single-carrier waveform for the wireless transmission based at least in part on the indication of the bandwidth for the wireless transmission.

[0043] A non-transitory computer readable medium for wireless communication is described. The non-transitory computer-readable medium may include instructions operable to cause a processor to receive, from a base station, an indication of a bandwidth for a wireless transmission between the UE and the base station and identify a multi-carrier waveform or a single-carrier waveform for the wireless transmission based at least in part on the indication of the bandwidth for the wireless transmission.

[0044] Some examples of the method, apparatus, and non-transitory computer-readable medium described above may further include processes, features, means, or instructions for transmitting a RF capability indication to the base station, and the identification of the multi-carrier waveform or a single-carrier waveform may be based at least in part on the RF capability indication. In some examples of the method, apparatus, and non-transitory computer-readable medium described above, the RF capability indication indicates one or more of a single-carrier bandwidth capability of the UE, or that the UE may be to use CA for transmission of the wireless transmission.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0045] FIG. 1 illustrates an example of a system for wireless communication that supports waveform selection in wireless communications, in accordance with one or more aspects of the present disclosure.

[0046] FIG. 2 illustrates an example of a portion of a wireless communication system that supports waveform selection in wireless communications, in accordance with one or more aspects of the present disclosure.

[0047] FIG. 3 illustrates an example of a system bandwidth and UE component carriers that support waveform selection in wireless communications, in accordance with one or more aspects of the present disclosure.

[0048] FIG. 4 illustrates an example of a process flow that supports waveform selection in wireless communications, in accordance with one or more aspects of the present disclosure.

[0049] FIGS. 5 through 7 show block diagrams of a device that supports waveform selection in wireless communications, in accordance with one or more aspects of the present disclosure.

[0050] FIG. 8 illustrates a block diagram of a system including a base station that supports waveform selection in wireless communications, in accordance with one or more aspects of the present disclosure.

[0051] FIGS. 9 through 11 show block diagrams of a device that supports waveform selection in wireless communications, in accordance with one or more aspects of the present disclosure.

[0052] FIG. 12 illustrates a block diagram of a system including a UE that supports waveform selection in wireless communications, in accordance with one or more aspects of the present disclosure.

[0053] FIGS. 13 through 18 illustrate methods for waveform selection in wireless communications, in accordance with one or more aspects of the present disclosure.

DETAILED DESCRIPTION

[0054] Techniques are described that provide for waveform selection for UL and/or DL wireless

transmissions based on one or more factors associated with the wireless transmission, a transmitter that is to transmit the wireless transmission, or combinations thereof. UL and DL transmissions may use one of a number of different waveforms, such as single-carrier waveforms (e.g., single-carrier frequency division multiplexing (SC-FDM) waveforms, DFT spread OFDM (DFT-s-OFDM) waveforms, or CDMA waveforms) that use a single carrier for information transmission of a wireless channel, and multi-carrier waveforms (e.g., OFDM waveforms) that use multiple carriers at different frequencies to transmit some of the bits on each channel. When referring to a single-carrier waveform, such a waveform may be any non-IFFT-based single carrier waveform.

[0055] According to various aspects of the disclosure, multi-carrier transmission waveforms or single-carrier waveforms may be selected for wireless transmissions based on a bandwidth allocated for the transmissions, a capability of a transmitter that is to transmit the transmissions, or combinations thereof. In some examples, a UE may provide an indication of the UE RF capability. Such a capability indication may include, for example, an indication of a bandwidth over which the UE can transmit at relatively high efficiency. A base station may receive such an RF capability indication, determine wireless resources associated with a wireless transmission, and select a multi-carrier waveform or a single-carrier waveform for the wireless transmission. The base station may provide an indication of the selected waveform to the UE for use in transmitting or receiving the wireless transmission. In some cases, a multi-carrier waveform may be selected when it is determined that the UE is not capable of transmitting over an entire allocated bandwidth with a single RF chain and would otherwise use CA to synthesize a single-carrier transmission over the entire allocated bandwidth. In some cases, a multi-carrier waveform may be selected based on the allocated bandwidth being above a threshold value, and a single-carrier waveform may be selected based on the allocated bandwidth being at or below the threshold value.

[0056] The present disclosure describes various techniques with reference to next generation networks (e.g., 5G or NR networks) that are being designed to support features such as high bandwidth operations, more dynamic subframe types, and self-contained subframe types (in which hybrid automatic repeat request (HARQ) feedback for a subframe may be transmitted before the end of the subframe). However, such techniques may be used for any system in which multi-carrier or single-carrier waveforms may be used for UL or DL transmissions.

[0057] Aspects of the disclosure are initially described in the context of a wireless communications system. Aspects of the disclosure are further illustrated by and described with reference to diagrams, system diagrams, and flowcharts that relate to query-based UE capability determination for coordination across multiple radio access technologies.

[0058] FIG. 1 illustrates an example of a wireless communication system **100**, in accordance with various aspects of the disclosure. The wireless communication system **100** may include network devices **105** (e.g., gNodeBs (gNBs), and/or RHs), UEs **115**, and a core network **130**. Wireless communication system **100** may support waveform selection for UL or DL transmissions. For example, wireless communication system **100** may support a capability report by a UE **115**, and selection of a multi-carrier or single-carrier waveform for a subsequent wireless transmission based at least in part on the capability reported by the UE **115** (e.g., whether the UE **115** is to use CA to use an allocated bandwidth for transmission), a bandwidth allocated for a wireless transmission, or any combination thereof.

[0059] A core network **130** may provide user authentication, access authorization, tracking, Internet Protocol (IP) connectivity, and other access, routing, or mobility functions. At least some of the network devices **105** (e.g., network device **105-a**, which may be an example of a LTE eNB, an eLTE eNB, an NR gNB, an NR Node-B, an NR access node or a base station, network device **105-b**, which may be an example of a gNB, an ANC, or a centralized unit) may interface with the core network **130** through backhaul links **132** (e.g., S1, S2, NG-1, NG-2, NG-3, NG-C, NG-U etc.) and may perform radio configuration and scheduling for communication with the UEs **115**. In various examples, the network devices **105-b** may communicate, either directly or indirectly (e.g., through

core network **130**), with each other over backhaul links **134** (e.g., X1, X2, Xn etc.), which may be wired or wireless communication links. A UE **115** may communicate with the core network **130** through communication link **135**.

[0060] Each network device **105-b** may also communicate with a number of UEs **115** through a number of other network devices **105-c**, where network device **105-c** may be an example of a transmission reception point (TRP), a distributed unit (DU), a radio head (RH), a remote radio head (RRH), or a smart RH. In alternative configurations, various functions of each network device **105** may be distributed across various network devices **105** (e.g., RHs/distributed units and access network controllers/centralized units) or consolidated into a single network device **105** (e.g., a base station/an access node).

[0061] The wireless communication system **100** may support synchronous or asynchronous operation. For synchronous operation, the network devices **105-a** and/or network devices **105-c** may have similar frame timing, and transmissions from different network devices **105-a** and/or network devices **105-c** may be approximately aligned in time. For asynchronous operation, the network devices **105-a** and/or network devices **105-c** may have different frame timings, and transmissions from different network devices **105-a** and/or network devices **105-c** may not be aligned in time. The techniques described herein may be used for either synchronous or asynchronous operations.

[0062] The communication networks that may accommodate some of the various disclosed examples may be packet-based networks that operate according to a layered protocol stack. In the user plane, communications at the bearer or one of the layer 2 protocol stack (e.g. Packet Data Convergence Protocol (PDCP)) may be IP-based. One of the layer 2 protocol stack (e.g. PDCP, Radio Link Control (RLC) or Medium Access Control (MAC)) may in some cases perform packet segmentation and reassembly to communicate over logical channels. One of the layer 2 protocol stack (e.g. A Medium Access Control (MAC)) may perform priority handling and multiplexing of logical channels into transport channels. The MAC layer may also use Hybrid ARQ (HARQ) to provide retransmission at the MAC layer to improve link efficiency. In the control plane, the Radio Resource Control (RRC) protocol layer may provide establishment, configuration, and maintenance of an RRC connection between a UE **115** and a network device **105-c**, network device **105-b**, or core network **130** supporting radio bearers for user plane data. At the Physical (PHY) layer, transport channels may be mapped to physical channels.

[0063] The UEs **115** may be dispersed throughout the wireless communication system **100**, and each UE **115** may be stationary or mobile. A UE **115** may also include or be referred to by those skilled in the art as a mobile station, a subscriber station, a mobile unit, a subscriber unit, a wireless unit, a remote unit, a mobile device, a wireless device, a wireless communications device, a remote device, a mobile subscriber station, an access terminal, a mobile terminal, a wireless terminal, a remote terminal, a handset, a user agent, a mobile client, a client, or some other suitable terminology. A UE **115** may be a cellular phone, a personal digital assistant (PDA), a wireless modem, a wireless communication device, a handheld device, a tablet computer, a laptop computer, a cordless phone, a wireless local loop (WLL) station, a IoE device, a smart phone, a smart watch, a customer premises equipment (CPE) or the like. A UE may be able to communicate with various types of network devices **105-a**, network devices **105-c**, base stations, access points, or other network devices, including macro eNBs, small cell eNBs, relay base stations, and the like. A UE may also be able to communicate directly with other UEs (e.g., using a peer-to-peer (P2P) protocol).

[0064] The communication link **125** and **135** shown in wireless communication system **100** may include UL channels from a UE **115** to a network device **105**, and/or DL channels, from a network device **105** to a UE **115**. The DL channels may also be called forward link channels, while the UL channels may also be called reverse link channels. Control information and data may be multiplexed on an UL channel or DL according to various techniques. Control information and data

may be multiplexed on a DL channel, for example, using time-division-multiplexing (TDM) techniques, frequency-division-multiplexing (FDM) techniques, or hybrid TDM-FDM techniques. In some examples, the control information transmitted during a transmission time interval (TTI) of a DL channel may be distributed between different control regions in a cascaded manner (e.g., between a common control region and one or more UE-specific control regions).

[0065] Wireless communication system **100** may support operation on multiple cells or carriers, a feature which may be referred to as CA or multi-carrier operation. A carrier may also be referred to as a CC, a layer, a channel, etc. The terms “carrier,” “component carrier,” “cell,” and “channel” may be used interchangeably herein. A UE **115** may be configured with multiple DL CCs and one or more UL CCs for carrier aggregation. Carrier aggregation may be used with both frequency-division-duplexing (FDD) and time-division-duplexing (TDD) CCs. Wireless communication system **100** may also support multiple-input multiple-output (MIMO) operation in which multiple concurrent transmissions may share time and frequency resources, and may uniquely modulate a transmission stream with space-time orthogonal codes, such as spatial frequency block codes (SFBC). These spatial resources may be called transmission layers, and the same or different streams of data may be transmitted over different transmission layers. For single-user MIMO (SU-MIMO), multiple transmission layers may be transmitted to the same UE, while in multiple user (MU-MIMO), multiple transmission layers may be transmitted to different UEs. A capability reported by a UE **115** may take into account the RF chains available at the UE **115** based on such multi-carrier or MIMO operation.

[0066] In some cases, wireless communication system **100** may utilize enhanced component carriers (eCCs). An eCC may be characterized by one or more features including: wider bandwidth, shorter symbol duration, and shorter transmission time interval (TTIs). In some cases, an eCC may be associated with a carrier aggregation configuration or a dual connectivity configuration (e.g., when multiple serving cells have a suboptimal or non-ideal backhaul link). An eCC may also be configured for use in unlicensed spectrum or shared spectrum (where more than one operator is allowed to use the spectrum).

[0067] In some cases, an eCC may utilize a different symbol duration than other CCs, which may include use of a reduced symbol duration as compared with symbol durations of the other CCs. A shorter symbol duration is associated with increased subcarrier spacing. A device, such as a UE **115** or base station **105**, utilizing eCCs may transmit wideband signals (e.g., 20, 40, 60, 80 MHz, etc.) at reduced symbol durations (e.g., 16.67 microseconds). A TTI in eCC may consist of one or multiple symbols. In some cases, the TTI duration (that is, the number of symbols in a TTI) may be variable. A 5G or NR carrier may be considered an eCC.

[0068] Wireless communication system **100** may operate in an ultra-high frequency (UHF) frequency region using frequency bands from 700 MHz to 2600 MHz (2.6 GHz), although in some cases wireless local area network (WLAN) networks may use frequencies as high as 4 GHz. This region may also be known as the decimeter band, since the wavelengths range from approximately one decimeter to one meter in length. UHF waves may propagate mainly by line of sight, and may be blocked by buildings and environmental features. However, the waves may penetrate walls sufficiently to provide service to UEs **115** located indoors. Transmission of UHF waves is characterized by smaller antennas and shorter range (e.g., less than 100 km) compared to transmission using the smaller frequencies (and longer waves) of the high frequency (HF) or very high frequency (VHF) portion of the spectrum. In some cases, wireless communication system **100** may also utilize extremely high frequency (EHF) portions of the spectrum (e.g., from 30 GHz to 300 GHz). This region may also be known as the millimeter band, since the wavelengths range from approximately one millimeter to one centimeter in length, and systems that use this region may be referred to as millimeter wave (mmWave) systems. Thus, EHF antennas may be even smaller and more closely spaced than UHF antennas. In some cases, this may facilitate use of antenna arrays within a UE **115** (e.g., for directional beamforming). However, EHF transmissions

may be subject to even greater atmospheric attenuation and shorter range than UHF transmissions. Techniques disclosed herein may be employed across transmissions that use one or more different frequency regions.

[0069] As indicated above, UL and DL transmissions may use one of a number of different waveforms, such as single-carrier waveforms (e.g., SC-FDM waveforms, DFT-s-OFDM waveforms, or CDMA waveforms) that use a single carrier for information transmission of a wireless channel, and multi-carrier waveforms (e.g., OFDM waveforms) that use multiple carriers at different frequencies to transmit some of the bits on each channel. In some examples, the UL waveform for use by a UE **115** may be selected based on one or more factors, such as power amplifier (PA) efficiency, battery life, demodulation performance, and the like. Single-carrier waveforms (e.g., DFT-s-OFDM) may provide a lower peak-to-average power ratio (PAPR) than a multicarrier waveform, which may provide good PA efficiency at a UE **115** and thereby enable relatively good cell coverage with efficient power utilization that may be beneficial for a battery-powered UE **115**.

[0070] Such single-carrier waveforms, however, may have relatively poor demodulation performance compared to a multi-carrier waveform (e.g., OFDM), depending on the MCS used for the transmission. For example, at relatively high modulation orders (e.g., 64 QAM) demodulation performance may be negatively impacted relative to a multi-carrier UL waveform, and thus a multi-carrier waveform may be more efficient in such cases. Additionally, in cases where a UE **115** has relatively good channel conditions, such a higher modulation order may be supportable for an UL transmission, and thus using such a MCS may enhance network efficiency. Accordingly, in such cases, a multi-carrier waveform may be desirable even though such a waveform may have a higher PAPR, less PA efficiency, and smaller cell coverage. Various examples provided herein provide that a multi-carrier or single-carrier waveform may be selected based on one or more factors to increase overall network efficiency and provide efficient use of UE **115** power.

[0071] In the example of FIG. **1**, base station **105-a** may include a network communications manager **101**, which may receive an indication of UE **115** RF capability, determine wireless resources associated with a wireless transmission, and select a multi-carrier waveform or a single-carrier waveform for the wireless transmission. The base station **105-a** may provide an indication of the selected waveform to the UE **115** for use in transmitting or receiving the wireless transmission. In some cases, a multi-carrier waveform may be selected when it is determined that the UE **115** is not capable of transmitting over an entire allocated bandwidth with a single RF chain and would otherwise use CA to synthesize a single-carrier transmission over the entire allocated bandwidth. In some cases, a multi-carrier waveform may be selected based on the allocated bandwidth being above a threshold value, and a single-carrier waveform may be selected based on the allocated bandwidth being at or below the threshold value. The network communications manager **101** may be an example of a base station communications manager **815** as described below with reference to FIG. **8**.

[0072] UEs **115** may include a UE communications manager **102**, which may provide a RF capability indication to a base station **105-a**, receive an indication of whether an UL transmission to the base station **105-a** is to be transmitted using a multi-carrier waveform or a single-carrier waveform, and transmit the UL transmission using the indicated multi-carrier waveform or single carrier waveform. In some cases, a UE **115** may identify that a multi-carrier waveform or a single-carrier waveform is to be used for a transmission based on a bandwidth for the wireless transmission. The UE communications manager **102** may be an example of a UE communications manager **1215** as described below with reference to FIG. **12**.

[0073] FIG. **2** illustrates an example of a portion of a wireless communication system **200** for waveform selection in wireless communications in accordance with various aspects of the present disclosure. Wireless communication system **200** may include a base station **105-d**, a first UE **115-a**, and a second UE **115-b**, which may be examples of the corresponding devices described with

reference to FIG. 1. In the example of FIG. 2, the base station **105-d** may establish a first connection **210** with the first UE **115-a**, which may be a wideband connection that covers a system bandwidth, and that an RF chain at the first UE **115-a** is capable of supporting relatively efficiently. The base station **105-d** may also establish a second connection **215** with the second UE **115-b**, which may include a number of CCs that are used to occupy the system bandwidth. In the example of FIG. 2, the wireless communication system may operate according to a first radio access technology (RAT), such as a 5G or NR RAT, although techniques described herein may be applied to any RAT and to systems that may concurrently use two or more different RATs.

[0074] In some examples, the first base station **105-d** may include a base station communications manager **201**, which may be an example of network communications manager **101** of FIG. 1, and may be used to receive an indication of RF capability from the first UE **115-a**, the second UE **115-b**, or both. The base station communications manager **201** may determine wireless resources associated with the first connection **210** and the second connection **215**, which may include, for example, bandwidth resources for each of the first connection **210** and the second connection **215**. The base station **105-d** may provide an indication of the selected waveform to the first UE **115-a** for use in transmitting or receiving wireless transmissions over the first connection **210**. In some cases, a single-carrier waveform may be selected for the first connection **210** when it is determined that the first UE **115-a** is capable of transmitting over an entire allocated bandwidth with a single RF chain.

[0075] In some cases, the second UE **115-b** may provide an indication to the base station **105-d** of an RF capability that would not enable the second UE **115-b** to transmit over the entire allocated bandwidth, and that a single-carrier waveform would have to be synthesized using CA over two or more CCs that form the second connection **215**. In such a case, the base station **105-d** may select a multi-carrier waveform for the second connection **215**. In some examples, the base station communications manager **201** may select a single-carrier or multi-carrier waveform based on the allocated bandwidth being above or below a threshold value, either based on the allocated bandwidth alone or in combination with one or more other factors associated with the UE **115** or associated channel conditions. The base station communications manager **201** may be an example of a base station communications manager **815** as described below with reference to FIG. 8.

[0076] The UE **115-a** may include a UE communications manager **202**, and the UE **115-b** may include a UE communications manager **203** which may be examples of UE communications manager **102** of FIG. 1, and each of which may be used to provide a RF capability indication to base station **105-d**, receive in response to the RF capability indication, from the base station, an indication of a waveform or a bandwidth, or both for a wireless transmission between the UE and the base station, and identify a waveform for the wireless transmission based at least in part on the indication of the waveform or the bandwidth, or both. In some examples, UE communications manager **202** and UE communications manager **203** may determine that the bandwidth includes two or more component carriers, and identify a multi-carrier waveform based on the determination. Additionally or alternatively, UE communications manager **202** and UE communications manager **203** may identify a multi-carrier waveform based on the bandwidth exceeding a threshold or identify a multi-carrier waveform based at least in part on the bandwidth exceeding the RF capability.

[0077] UE communications manager **202** and UE communications manager **203** may also receive an indication of whether transmissions with the base station **105-d** are to use a multi-carrier waveform or a single-carrier waveform, and transmit/receive the transmissions using the indicated multi-carrier waveform or single carrier waveform. In some cases, UE communications manager **202** or UE communications manager **203** may identify that a multi-carrier waveform or a single-carrier waveform is to be used for a transmission based on a bandwidth for the wireless transmission. The UE communications manager **202** and the UE communications manager **203** may be examples of a UE communications manager **1215** as described below with reference to

FIG. 12.

[0078] As indicated above, in some examples the wireless communication system **200** may be a portion of a NR or 5G network. Based on growing demand for data and throughput anticipated for 5G, more RF spectrum may be necessary to support communications. In some cases, such a wireless communication system **200** may operate using relatively high frequency bands (e.g., mmWave) in order to have access to additional unpaired spectrum available at such frequency bands, which may be less expensive than paired spectrum at lower frequency bands such as 2 GHz and below. Additionally, such relatively high frequency bands may potentially provide relatively large bandwidth for UL and DL channels, such as bandwidths of hundreds of MHz per channel. As indicated above, such high frequencies may have a relatively small coverage area, and may be supported when a UE **115** is relatively close to a base station **105-e**, which may also indicate that a connection may support higher modulation orders, which may be more efficiently transmitted using multi-carrier waveforms to provide enhanced demodulation performance.

[0079] According to some examples, the selection of a multi-carrier waveform or a single-carrier waveform may be based on a number of different factors. For example, base station **105-d** may consider the SNR associated with a UE **115**. For example, the first UE **115-a** may only achieve a low SNR, which may be typical of a cell edge user, and should be assigned single carrier waveform (e.g., a DFT-s-OFDM waveform), while the second UE **115-b** may have a relatively high SNR and may use a multi-carrier waveform (e.g., an OFDM waveform). Additionally or alternatively, a TM indicated by a UE **115** may be considered, where an indication of a capability to transmit multiple streams (i.e., MIMO) may indicate that the UE **115** is not power limited, and may thus be assigned multi-carrier waveforms (e.g., OFDM), and an indication of a rank one transmission (i.e., single stream capability) may be assigned a single-carrier waveform (e.g., DFT-s-OFDM). A further alternative may be an MCS-related consideration in which, for example, second UE **115-b** may indicate in channel quality information (CQI) provided to the base station **105-d** that it can transmit with a relatively high modulation order MCS, and may be assigned to use a multi-carrier waveform. Likewise, if the first UE **115-a** indicates a relatively low MCS in CQI, a single-carrier waveform may be assigned. Of course, any combination of the above-described factors may be used in making a determination of whether to use a multi-carrier or single-carrier waveform.

[0080] FIG. 3 illustrates an examples of a wireless communications bandwidth supported by different UEs in accordance with various aspects of the present disclosure. In the example of FIG. 3 a first UE **115-c** and a second UE **115-d** may use different techniques to provide a transmission that covers an entire system bandwidth **305**. The first UE **115-c** and second UE **115-d** may be examples of the corresponding devices described with reference to FIGS. 1-2.

[0081] In the example of FIG. 3, the first UE **115-c** may establish a first connection using a first component carrier (CC) **310** that spans the entire system bandwidth **305**. The second UE **115-d** may establish a second connection using a second CC **315** and a third CC **320**, that may collectively span the system bandwidth **305**. In some cases, the system bandwidth **305** may be a relatively wideband allocation (e.g., hundreds of MHz), and a single RF chain at the second UE **115-d** may not be able to cover the whole bandwidth, and thus carrier aggregation may be needed from the second UE **115-d** to cover the whole system bandwidth **305**. Multiple carriers from carrier aggregation will, at least partially, result in at least a partial degradation of the various properties of a single-carrier waveform that were discussed above, even if each of the second CC **315** and the third CC **320** are single carrier waveforms (e.g., DFT-s-OFDM). Thus, in some examples, if a wideband single-carrier transmission is to be synthesized from multiple narrower-band transmissions, a multi-carrier waveform may be considered for the transmission. In such cases, a demodulation performance advantage may favor a multi-carrier waveform, as well as potential degradation of PAPR resulting from multiple CCs.

[0082] Additionally, when system bandwidth **305** becomes relatively large, the system bandwidth **305** may become more frequency selective, and some parts of the channel may have more fading

relative to other parts of the channel, which may have a negative impact on demodulation performance. In such cases, the demodulation performance advantage of a multi-carrier waveform may favor such a multi-carrier waveform over a single-carrier waveform. Thus, another factor that may be considered in selecting a waveform for a transmission may include channel characteristics such as frequency selectivity of a channel.

[0083] FIG. 4 illustrates an example of a process flow **400** for waveform selection in wireless communications in accordance with various aspects of the present disclosure. Process flow **400** may include a base station **105-e** and a UE **115-e**, which may be examples of the corresponding devices described with reference to FIGS. 1-3. The UE **115-e** may, at block **405**, identify a UE capability of the UE **115-e**. Such a UE capability may be, for example, an indication of a UE category that may be used to identify UE capability (e.g., a number of RF chains of the UE **115-e**, a bandwidth capability of the UE **115-e**, a multiple carrier capability of the UE **115-e**, etc.). The UE capability **410** may be transmitted from the UE **115-e** to the base station **105-e**. In some cases, the UE capability **410** may be provided during the establishment of an RRC connection.

[0084] At block **415**, the UE **115-e** may determine CQI associated with a channel that may be used for communications. Such CQI may include, for example, CQI (e.g., SNR, MCS), a precoding matrix indicator (PMI), and a rank indicator (RI) for the UE. The UE **115-e** may transmit the CQI **420** to the base station **105-e**. At block **425**, the base station **105-e** may identify wireless resources for one or more wireless transmission(s). The identification of wireless resources may include determining UL or DL resources for the wireless transmission(s), and may include a determination of one or more channels and associated bandwidths for the transmission(s).

[0085] The base station **105-e** may, at block **430**, select a waveform to use for the wireless transmission(s). The selection of the waveform may include selection of a single-carrier or multi-carrier waveform based at least in part on one or more of the factors as discussed above. The base station **105-e** may then transmit DL control information (DCI) to the UE **115-e**, that may include information on the resources for the wireless transmission(s), and an indication of the waveform to use for the transmission(s).

[0086] The UE **115-e** may receive the DCI and identify the transmission resources and the selected waveform for the transmission(s). At block **440**, when the wireless transmission(s) include UL transmissions, the UE **115-e** may format the UL transmission according to the DCI and indicated waveform. For example, the UE **115-e** may format a single-carrier or a multi-carrier waveform for UL transmission **445** using the allocated resources from the DCI, and transmit the UL transmission **445** to the base station **105-e**.

[0087] At optional block **450**, the base station **105-e** may format one or more DL transmissions according to the DCI and indicated waveform, and transmit the associated DL transmission **455** to the UE **115-e**. The DL transmission **455** may be transmitted using a single-carrier waveform or a multi-carrier waveform, which may be selected based at least in part on one or more of the factors as discussed above.

[0088] FIG. 5 shows a block diagram **500** of a device **505** that supports waveform selection in wireless communications in accordance with various aspects of the present disclosure. Device **505** may be an example of aspects of a base station **105** as described with reference to FIGS. 1-4. Device **505** may include receiver **510**, base station communications manager **515**, and transmitter **520**. Device **505** may also include a processor. Each of these components may be in communication with one another (e.g., via one or more buses).

[0089] Receiver **510** may receive information such as packets, user data, or control information associated with various information channels (e.g., control channels, data channels, and information related to waveform selection in wireless communications, etc.). Information may be passed on to other components of the device. The receiver **510** may be an example of aspects of the transceiver **835** described with reference to FIG. 8.

[0090] Receiver **510** may receive the wireless transmission from the UE using the selected

waveform. Base station communications manager **515** may be an example of aspects of the network communications manager **101**, base station communications manager **201**, or base station communications manager **815** described with reference to FIGS. **1**, **2**, and **8**.

[0091] Base station communications manager **515** may receive a RF capability indication from a UE, select a multi-carrier waveform or a single-carrier waveform for a wireless transmission between the UE and the base station, and transmit an indication of the selected waveform to the UE. The base station communications manager **515** may, in some cases, identify a bandwidth for a wireless transmission between a UE and the base station, select a multi-carrier waveform or a single-carrier waveform for the wireless transmission based on the identified bandwidth for the wireless transmission, and transmit an indication of the selected waveform to the UE.

[0092] Transmitter **520** may transmit signals generated by other components of the device. In some examples, the transmitter **520** may be collocated with a receiver **510** in a transceiver module. For example, the transmitter **520** may be an example of aspects of the transceiver **835** described with reference to FIG. **8**. The transmitter **520** may include a single antenna, or it may include a set of antennas. Transmitter **520** may transmit wireless transmissions to a UE using the selected single-carrier or multi-carrier waveform.

[0093] FIG. **6** shows a block diagram **600** of a device **605** that supports waveform selection in wireless communications in accordance with various aspects of the present disclosure. Device **605** may be an example of aspects of a device **505** or a base station **105** as described with reference to FIGS. **1-5**. Device **605** may include receiver **610**, base station communications manager **615**, and transmitter **620**. Device **605** may also include a processor. Each of these components may be in communication with one another (e.g., via one or more buses).

[0094] Receiver **610** may receive information such as packets, user data, or control information associated with various information channels (e.g., control channels, data channels, and information related to waveform selection in wireless communications, etc.). Information may be passed on to other components of the device. The receiver **610** may be an example of aspects of the transceiver **835** described with reference to FIG. **8**.

[0095] Base station communications manager **615** may be an example of aspects of the network communications manager **101**, base station communications manager **201**, or the base station communications manager **815** described with reference to FIGS. **1**, **2**, and **8**. Base station communications manager **615** may also include RF capability component **625**, waveform selection component **630**, waveform indication component **635**, and bandwidth identification component **640**.

[0096] RF capability component **625** may receive a RF capability indication from a UE, and the selecting the multi-carrier waveform or single-carrier waveform may be based on the RF capability indication. In some cases, the RF capability indication indicates a single-carrier bandwidth capability of the UE.

[0097] Waveform selection component **630** may select a multi-carrier waveform or a single-carrier waveform for a wireless transmission between the UE and the base station. In some cases, waveform selection component **630** may select the multi-carrier waveform when the bandwidth for the wireless transmission exceeds a threshold value, select the multi-carrier waveform based on the SNR, TM, MCS, or any combination thereof, select the multi-carrier waveform responsive to determining a UE capability, select a multi-carrier waveform or a single-carrier waveform for the wireless transmission based on an identified bandwidth for the wireless transmission, or any combination thereof. In some cases, the multi-carrier waveform includes an OFDM waveform. In some cases, the RF capability indication indicates that the UE is to use carrier aggregation for transmission of the wireless transmission, and the multi-carrier waveform is selected based on the indication of carrier aggregation. In some cases, the single-carrier waveform includes a DFT-s-OFDM waveform. In some cases, the RF capability indication indicates that the UE is to use carrier aggregation for transmission of the wireless transmission, and where the multi-carrier waveform is

selected based on the indication of carrier aggregation. In some cases, the single-carrier waveform includes a DFT-s OFDM waveform. In some cases, the multi-carrier waveform includes an OFDM waveform. Waveform indication component **635** may transmit an indication of the selected waveform to the UE (e.g., in DCI transmitted to the UE).

[0098] Bandwidth identification component **640** may identify a bandwidth for the wireless transmission, and determine that the bandwidth for the wireless transmission exceeds a single-carrier bandwidth capability of the UE. In some cases, the RF capability indication indicates a single-carrier bandwidth capability of the UE, and it may be determined that the bandwidth for the wireless transmission exceeds the single-carrier bandwidth capability of the UE.

[0099] Transmitter **620** may transmit signals generated by other components of the device. In some examples, the transmitter **620** may be collocated with a receiver **610** in a transceiver module. For example, the transmitter **620** may be an example of aspects of the transceiver **835** described with reference to FIG. 8. The transmitter **620** may include a single antenna, or it may include a set of antennas.

[0100] FIG. 7 shows a block diagram **700** of a base station communications manager **715** that supports waveform selection in wireless communications in accordance with various aspects of the present disclosure. The base station communications manager **715** may be an example of aspects of a network communications manager **101**, a base station communications manager **201**, a base station communications manager **515**, a base station communications manager **615**, or a base station communications manager **815** described with reference to FIGS. 1, 2, 5, 6, and 8. The base station communications manager **715** may include RF capability component **720**, waveform selection component **725**, waveform indication component **730**, bandwidth identification component **735**, and CQI component **740**. Each of these modules may communicate, directly or indirectly, with one another (e.g., via one or more buses).

[0101] RF capability component **720** may receive a RF capability indication from a UE and receive a RF capability indication from the UE. In some cases, the selecting the multi-carrier waveform or a single-carrier waveform is based on the RF capability indication. In some cases, the RF capability indication indicates a single-carrier bandwidth capability of the UE.

[0102] Waveform selection component **725** may select a multi-carrier waveform or a single-carrier waveform for a wireless transmission between the UE and the base station. In some cases, the waveform selection component **725** may select the multi-carrier waveform when the bandwidth for the wireless transmission exceeds a threshold value, select the multi-carrier waveform based on the SNR, TM, MCS, or any combination thereof, of a UE, select the multi-carrier waveform responsive to the determining UE bandwidth capability, select a multi-carrier waveform for the wireless transmission based on the identified bandwidth for the wireless transmission, or any combination thereof. In some cases, the multi-carrier waveform includes an OFDM waveform.

[0103] In some cases, the RF capability indication indicates that the UE is to use carrier aggregation for transmission of the wireless transmission, and the multi-carrier waveform may be selected based on the indication of carrier aggregation. In some cases, the single-carrier waveform includes a DFT-s-OFDM waveform. In some cases, the multi-carrier waveform includes an OFDM waveform.

[0104] Waveform indication component **730** may transmit an indication of the selected waveform to the UE. Bandwidth identification component **735** may identify a bandwidth for the wireless transmission, and may determine that the bandwidth for the wireless transmission exceeds the single-carrier bandwidth capability of the UE. CQI component **740** may identify one or more of a SNR for the UE, a TM of the wireless transmission, a MCS of the wireless transmission, a RI, a PMI, or any combination thereof.

[0105] FIG. 8 shows a diagram of a system **800** including a device **805** that supports waveform selection in wireless communications in accordance with various aspects of the present disclosure. Device **805** may be an example of or include the components of device **505**, device **605**, or a base

station **105** as described above, e.g., with reference to FIGS. **1**, **5** and **6**. Device **805** may include components for bi-directional voice and data communications including components for transmitting and receiving communications, including base station communications manager **815**, processor **820**, memory **825**, software **830**, transceiver **835**, antenna **840**, network communications manager **845**, and base station coordination manager **850**. These components may be in electronic communication via one or more busses (e.g., bus **810**). Base station communications manager **815** may be an example of aspects of a network communications manager **101**, a base station communications manager **201**, a base station communications manager **515**, a base station communications manager **615**, or a base station communications manager **715** described with reference to FIGS. **1**, **2**, **5**, **6**, and **7**. Device **805** may communicate wirelessly with one or more UEs **115**.

[0106] Base station coordination manager **850** may manage communications with other base station **105**, and may include a controller or scheduler for controlling communications with UEs **115** in cooperation with other base stations **105**. For example, the base station coordination manager **850** may coordinate scheduling for transmissions to UEs **115** for various interference mitigation techniques such as beamforming or joint transmission. In some examples, base station coordination manager **850** may provide an interface within a wireless communication network technology to provide communication between base stations **105**.

[0107] Processor **820** may include an intelligent hardware device, (e.g., a general-purpose processor, a digital signal processor (DSP), a central processing unit (CPU), a microcontroller, an application-specific integrated circuit (ASIC), an field-programmable gate array (FPGA), a programmable logic device, a discrete gate or transistor logic component, a discrete hardware component, or any combination thereof). In some cases, processor **820** may be configured to operate a memory array using a memory controller. In other cases, a memory controller may be integrated into processor **820**. Processor **820** may be configured to execute computer-readable instructions stored in a memory to perform various functions (e.g., functions or tasks supporting waveform selection in wireless communications).

[0108] Memory **825** may include random access memory (RAM) and read only memory (ROM). The memory **825** may store computer-readable, computer-executable software **830** including instructions that, when executed, cause the processor to perform various functions described herein. In some cases, the memory **825** may contain, among other things, a basic input/output system (BIOS) which may control basic hardware and/or software operation such as the interaction with peripheral components or devices.

[0109] Software **830** may include code to implement aspects of the present disclosure, including code to support waveform selection in wireless communications. Software **830** may be stored in a non-transitory computer-readable medium such as system memory or other memory. In some cases, the software **830** may not be directly executable by the processor but may cause a computer (e.g., when compiled and executed) to perform functions described herein.

[0110] Transceiver **835** may communicate bi-directionally, via one or more antennas, wired, or wireless links as described above. For example, the transceiver **835** may represent a wireless transceiver and may communicate bi-directionally with another wireless transceiver. The transceiver **835** may also include a modem to modulate the packets and provide the modulated packets to the antennas for transmission, and to demodulate packets received from the antennas.

[0111] In some cases, the wireless device may include a single antenna **840**. However, in some cases the device may have more than one antenna **840**, which may be capable of concurrently transmitting or receiving multiple wireless transmissions.

[0112] Network communications manager **845** may manage communications with the core network (e.g., via one or more wired backhaul links). For example, the network communications manager **845** may manage the transfer of data communications for client devices, such as one or more UEs **115**.

[0113] FIG. 9 shows a block diagram **900** of a device **905** that supports waveform selection in wireless communications in accordance with various aspects of the present disclosure. Device **905** may be an example of aspects of a UE **115** as described with reference to FIG. 1. Device **905** may include receiver **910**, UE communications manager **915**, and transmitter **920**. Device **905** may also include a processor. Each of these components may be in communication with one another (e.g., via one or more buses).

[0114] Receiver **910** may receive information such as packets, user data, or control information associated with various information channels (e.g., control channels, data channels, and information related to waveform selection in wireless communications, etc.). Information may be passed on to other components of the device. The receiver **910** may be an example of aspects of the transceiver **1235** described with reference to FIG. 12. Receiver **910** may receive wireless transmissions from a base station using a single-carrier or multi-carrier waveform.

[0115] UE communications manager **915** may be an example of aspects of the UE communications manager **102**, UE communications manager **202**, UE communications manager **203**, or UE communications manager **1215** described with reference to FIGS. 1, 2, and 12.

[0116] UE communications manager **915** may transmit a RF capability indication to a base station and receive an indication of whether an UL transmission to the base station is to be transmitted using a multi-carrier waveform or a single-carrier waveform. The UE communications manager **915** may also receive, from a base station, an indication of a bandwidth for a wireless transmission between the UE and the base station and identify a multi-carrier waveform or a single-carrier waveform for the wireless transmission based on the indication of the bandwidth for the wireless transmission.

[0117] Transmitter **920** may transmit signals generated by other components of the device. In some examples, the transmitter **920** may be collocated with a receiver **910** in a transceiver module. For example, the transmitter **920** may be an example of aspects of the transceiver **1235** described with reference to FIG. 12. The transmitter **920** may include a single antenna, or it may include a set of antennas. Transmitter **920** may transmit UL transmissions using the indicated multi-carrier waveform or single carrier waveform, and in some cases, may transmit an identified SNR, TM, or MCS to the base station.

[0118] FIG. 10 shows a block diagram **1000** of a device **1005** that supports waveform selection in wireless communications in accordance with various aspects of the present disclosure. Device **1005** may be an example of aspects of a device **905** or a UE **115** as described with reference to FIGS. 1 and 9. Device **1005** may include receiver **1010**, UE communications manager **1015**, and transmitter **1020**. Device **1005** may also include a processor. Each of these components may be in communication with one another (e.g., via one or more buses).

[0119] Receiver **1010** may receive information such as packets, user data, or control information associated with various information channels (e.g., control channels, data channels, and information related to waveform selection in wireless communications, etc.). Information may be passed on to other components of the device. The receiver **1010** may be an example of aspects of the transceiver **1235** described with reference to FIG. 12.

[0120] UE communications manager **1015** may be an example of aspects of the UE communications manager **102**, UE communications manager **202**, UE communications manager **203**, the UE communications manager **915**, or the UE communications manager **1215** described with reference to FIGS. 1, 2, 9, and 12.

[0121] UE communications manager **1015** may also include UE RF capability component **1025**, waveform indication component **1030**, bandwidth identification component **1035**, and waveform selection component **1040**.

[0122] UE RF capability component **1025** may transmit a RF capability indication to a base station, and the identifying the multi-carrier waveform or a single-carrier waveform may be based on the RF capability indication. In some cases, the RF capability indication indicates a single-carrier

bandwidth capability of the UE. In some cases, the RF capability indication indicates that the UE is to use carrier aggregation for transmission of an UL transmission.

[0123] Waveform indication component **1030** may receive an indication of whether an UL transmission to the base station is to be transmitted using a multi-carrier waveform or a single-carrier waveform. Bandwidth identification component **1035** may receive, from a base station, an indication of a bandwidth for a wireless transmission between the UE and the base station.

[0124] Waveform selection component **1040** may identify a multi-carrier waveform or a single-carrier waveform for the wireless transmission based on the indication of the bandwidth for the wireless transmission. In some cases, the single-carrier waveform includes a DFT-s-OFDM waveform. In some cases, the multi-carrier waveform includes an OFDM waveform.

[0125] Transmitter **1020** may transmit signals generated by other components of the device. In some examples, the transmitter **1020** may be collocated with a receiver **1010** in a transceiver module. For example, the transmitter **1020** may be an example of aspects of the transceiver **1235** described with reference to FIG. **12**. The transmitter **1020** may include a single antenna, or it may include a set of antennas.

[0126] FIG. **11** shows a block diagram **1100** of a UE communications manager **1115** that supports waveform selection in wireless communications in accordance with various aspects of the present disclosure. The UE communications manager **1115** may be an example of aspects of a UE communications manager described with reference to FIGS. **1**, **2**, **9**, **10**, and **12**. The UE communications manager **1115** may include UE RF capability component **1120**, waveform indication component **1125**, bandwidth identification component **1130**, waveform selection component **1135**, and UE CQI component **1140**. Each of these modules may communicate, directly or indirectly, with one another (e.g., via one or more buses).

[0127] UE RF capability component **1120** may transmit a RF capability indication to a base station, and the identifying the multi-carrier waveform or a single-carrier waveform may be based on the RF capability indication. In some cases, the RF capability indication indicates a single-carrier bandwidth capability of the UE. In some cases, the RF capability indication indicates that the UE is to use carrier aggregation for transmission of the UL transmission.

[0128] Waveform indication component **1125** may receive an indication of whether an UL transmission to the base station is to be transmitted using a multi-carrier waveform or a single-carrier waveform. Bandwidth identification component **1130** may receive, from a base station, an indication of a bandwidth for a wireless transmission between the UE and the base station.

[0129] Waveform selection component **1135** may identify a multi-carrier waveform or a single-carrier waveform for the wireless transmission based on the indication of the bandwidth for the wireless transmission. UE CQI component **1140** may identify one or more of a SNR for the UE, a TM of the UL transmission, or a MCS of the UL transmission.

[0130] FIG. **12** shows a diagram of a system **1200** including a device **1205** that supports waveform selection in wireless communications in accordance with various aspects of the present disclosure. Device **1205** may be an example of or include the components of UE **115** as described above, e.g., with reference to FIG. **1**. Device **1205** may include components for bi-directional voice and data communications including components for transmitting and receiving communications, including UE communications manager **1215**, processor **1220**, memory **1225**, software **1230**, transceiver **1235**, antenna **1240**, and I/O controller **1245**. These components may be in electronic communication via one or more busses (e.g., bus **1210**). Device **1205** may communicate wirelessly with one or more base stations **105**. UE communications manager **1215** may be an example of aspects of the UE communications manager discussed with respect to FIG. **1**, **2**, **9**, **10**, or **11**.

[0131] Processor **1220** may include an intelligent hardware device, (e.g., a general-purpose processor, a DSP, a CPU, a microcontroller, an ASIC, an FPGA, a programmable logic device, a discrete gate or transistor logic component, a discrete hardware component, or any combination thereof). In some cases, processor **1220** may be configured to operate a memory array using a

memory controller. In other cases, a memory controller may be integrated into processor **1220**. Processor **1220** may be configured to execute computer-readable instructions stored in a memory to perform various functions (e.g., functions or tasks supporting waveform selection in wireless communications).

[0132] Memory **1225** may include RAM and ROM. The memory **1225** may store computer-readable, computer-executable software **1230** including instructions that, when executed, cause the processor to perform various functions described herein. In some cases, the memory **1225** may contain, among other things, a BIOS which may control basic hardware and/or software operation such as the interaction with peripheral components or devices.

[0133] Software **1230** may include code to implement aspects of the present disclosure, including code to support waveform selection in wireless communications. Software **1230** may be stored in a non-transitory computer-readable medium such as system memory or other memory. In some cases, the software **1230** may not be directly executable by the processor but may cause a computer (e.g., when compiled and executed) to perform functions described herein.

[0134] Transceiver **1235** may communicate bi-directionally, via one or more antennas, wired, or wireless links as described above. For example, the transceiver **1235** may represent a wireless transceiver and may communicate bi-directionally with another wireless transceiver. The transceiver **1235** may also include a modem to modulate the packets and provide the modulated packets to the antennas for transmission, and to demodulate packets received from the antennas.

[0135] In some cases, the wireless device may include a single antenna **1240**. However, in some cases the device may have more than one antenna **1240**, which may be capable of concurrently transmitting or receiving multiple wireless transmissions.

[0136] I/O controller **1245** may manage input and output signals for device **1205**. I/O controller **1245** may also manage peripherals not integrated into device **1205**. In some cases, I/O controller **1245** may represent a physical connection or port to an external peripheral. In some cases, I/O controller **1245** may utilize an operating system such as iOS®, ANDROID® MS-DOS®, MS-WINDOWS®, OS/2®, UNIX®, LINUX®, or another known operating system.

[0137] FIG. **13** shows a flowchart illustrating a method **1300** for waveform selection in wireless communications in accordance with various aspects of the present disclosure. The operations of method **1300** may be implemented by a base station **105** or its components as described herein. For example, the operations of method **1300** may be performed by a base station communications manager as described with reference to FIGS. **5** through **8**. In some examples, a base station **105** may execute a set of codes to control the functional elements of the device to perform the functions described below. Additionally or alternatively, the base station **105** may perform aspects the functions described below using special-purpose hardware.

[0138] At block **1305** the base station **105** may receive a RF capability indication from a UE. The operations of block **1305** may be performed according to the methods described with reference to FIGS. **1** through **4**. In certain examples, aspects of the operations of block **1305** may be performed by a RF capability component as described with reference to FIGS. **5** through **8**.

[0139] At block **1310** the base station **105** may identify a bandwidth for a wireless transmission between the UE and the base station **105**. The operations of block **1310** may be performed according to the methods described with reference to FIGS. **1** through **4**. In certain examples, aspects of the operations of block **1310** may be performed by a bandwidth identification component as described with reference to FIGS. **5** through **8**.

[0140] At block **1315** the base station **105** may select a waveform for the wireless transmission between the UE and the base station based on the RF capability indication or the bandwidth, or both. The operations of block **1315** may be performed according to the methods described with reference to FIGS. **1** through **4**. In certain examples, aspects of the operations of block **1315** may be performed by a waveform selection component as described with reference to FIGS. **5** through **8**.

[0141] At block **1320** the base station **105** may transmit an indication of the selected waveform to

the UE. The operations of block **1320** may be performed according to the methods described with reference to FIGS. **1** through **4**. In certain examples, aspects of the operations of block **1320** may be performed by a waveform indication component as described with reference to FIGS. **5** through **8**. [0142] FIG. **14** shows a flowchart illustrating a method **1400** for waveform selection in wireless communications in accordance with various aspects of the present disclosure. The operations of method **1400** may be implemented by a base station **105** or its components as described herein. For example, the operations of method **1400** may be performed by a base station communications manager as described with reference to FIGS. **5** through **8**. In some examples, a base station **105** may execute a set of codes to control the functional elements of the device to perform the functions described below. Additionally or alternatively, the base station **105** may perform aspects the functions described below using special-purpose hardware.

[0143] At block **1405** the base station **105** may identify a bandwidth for the wireless transmission. The operations of block **1405** may be performed according to the methods described with reference to FIGS. **1** through **4**. In certain examples, aspects of the operations of block **1405** may be performed by a bandwidth identification component as described with reference to FIGS. **5** through **8**.

[0144] At block **1410** the base station **105** may determine that the bandwidth for the wireless transmission exceeds the single-carrier bandwidth capability of the UE. The operations of block **1410** may be performed according to the methods described with reference to FIGS. **1** through **4**. In certain examples, aspects of the operations of block **1410** may be performed by a bandwidth identification component as described with reference to FIGS. **5** through **8**.

[0145] At block **1415** the base station **105** may select the multi-carrier waveform responsive to the determining. The operations of block **1415** may be performed according to the methods described with reference to FIGS. **1** through **4**. In certain examples, aspects of the operations of block **1415** may be performed by a waveform selection component as described with reference to FIGS. **5** through **8**.

[0146] FIG. **15** shows a flowchart illustrating a method **1500** for waveform selection in wireless communications in accordance with various aspects of the present disclosure. The operations of method **1500** may be implemented by a base station **105** or its components as described herein. For example, the operations of method **1500** may be performed by a base station communications manager as described with reference to FIGS. **5** through **8**. In some examples, a base station **105** may execute a set of codes to control the functional elements of the device to perform the functions described below. Additionally or alternatively, the base station **105** may perform aspects the functions described below using special-purpose hardware.

[0147] At block **1505** the base station **105** may identify one or more of a SNR for the UE, a TM of the wireless transmission, or a MCS of the wireless transmission. The operations of block **1505** may be performed according to the methods described with reference to FIGS. **1** through **4**. In certain examples, aspects of the operations of block **1505** may be performed by a CQI component as described with reference to FIGS. **5** through **8**.

[0148] At block **1510** the base station **105** may select the multi-carrier waveform based at least in part on the SNR, TM, MCS, or any combination thereof. The operations of block **1510** may be performed according to the methods described with reference to FIGS. **1** through **4**. In certain examples, aspects of the operations of block **1510** may be performed by a waveform selection component as described with reference to FIGS. **5** through **8**.

[0149] FIG. **16** shows a flowchart illustrating a method **1600** for waveform selection in wireless communications in accordance with various aspects of the present disclosure. The operations of method **1600** may be implemented by a UE **115** or its components as described herein. For example, the operations of method **1600** may be performed by a UE communications manager as described with reference to FIGS. **9** through **12**. In some examples, a UE **115** may execute a set of codes to control the functional elements of the device to perform the functions described below.

Additionally or alternatively, the UE **115** may perform aspects the functions described below using special-purpose hardware.

[0150] At block **1605** the UE **115** may transmit a RF capability indication to a base station. The operations of block **1605** may be performed according to the methods described with reference to FIGS. **1** through **4**. In certain examples, aspects of the operations of block **1605** may be performed by a UE RF capability component as described with reference to FIGS. **9** through **12**.

[0151] At block **1610** the UE **115** may receive in response to the RF capability indication, from the base station, an indication of a waveform or a bandwidth, or both for a wireless transmission between the UE **115** and base station. The operations of block **1610** may be performed according to the methods described with reference to FIGS. **1** through **4**. In certain examples, aspects of the operations of block **1610** may be performed by a waveform indication component as described with reference to FIGS. **9** through **12**.

[0152] At block **1615** the UE **115** may identify a waveform for the wireless transmission based on the indication of the waveform or the bandwidth, or both. The operations of block **1615** may be performed according to the methods described with reference to FIGS. **1** through **4**. In certain examples, aspects of the operations of block **1615** may be performed by a bandwidth identification component as described with reference to FIGS. **9** through **12**.

[0153] At block **1620** the UE **115** may perform the wireless transmission using the identified waveform. In some examples, performing the wireless transmission using the identified waveform may include transmitting using the identified waveform (e.g., via UL) or receiving using the identified waveform (e.g., via DL). The operations of block **1620** may be performed according to the methods described with reference to FIGS. **1** through **4**. In certain examples, aspects of the operations of block **1620** may be performed by a transmitter as described with reference to FIGS. **9** through **12**.

[0154] FIG. **17** shows a flowchart illustrating a method **1700** for waveform selection in wireless communications in accordance with various aspects of the present disclosure. The operations of method **1700** may be implemented by a base station **105** or its components as described herein. For example, the operations of method **1700** may be performed by a base station communications manager as described with reference to FIGS. **5** through **8**. In some examples, a base station **105** may execute a set of codes to control the functional elements of the device to perform the functions described below. Additionally or alternatively, the base station **105** may perform aspects the functions described below using special-purpose hardware.

[0155] At block **1705** the base station **105** may identify a bandwidth for a wireless transmission between a UE and the base station. The operations of block **1705** may be performed according to the methods described with reference to FIGS. **1** through **4**. In certain examples, aspects of the operations of block **1705** may be performed by a bandwidth identification component as described with reference to FIGS. **5** through **8**.

[0156] At block **1710** the base station **105** may select a multi-carrier waveform or a single-carrier waveform for the wireless transmission based at least in part on the identified bandwidth for the wireless transmission. The operations of block **1710** may be performed according to the methods described with reference to FIGS. **1** through **4**. In certain examples, aspects of the operations of block **1710** may be performed by a waveform selection component as described with reference to FIGS. **5** through **8**.

[0157] At block **1715** the base station **105** may transmit an indication of the selected waveform to the UE. The operations of block **1715** may be performed according to the methods described with reference to FIGS. **1** through **4**. In certain examples, aspects of the operations of block **1715** may be performed by a waveform indication component as described with reference to FIGS. **5** through **8**.

[0158] FIG. **18** shows a flowchart illustrating a method **1800** for waveform selection in wireless communications in accordance with various aspects of the present disclosure. The operations of method **1800** may be implemented by a UE **115** or its components as described herein. For

example, the operations of method **1800** may be performed by a UE communications manager as described with reference to FIGS. **9** through **12**. In some examples, a UE **115** may execute a set of codes to control the functional elements of the device to perform the functions described below. Additionally or alternatively, the UE **115** may perform aspects the functions described below using special-purpose hardware.

[0159] At block **1805** the UE **115** may receive, from a base station, an indication of a bandwidth for a wireless transmission between the UE and the base station. The operations of block **1805** may be performed according to the methods described with reference to FIGS. **1** through **4**. In certain examples, aspects of the operations of block **1805** may be performed by a bandwidth identification component as described with reference to FIGS. **9** through **12**.

[0160] At block **1810** the UE **115** may identify a multi-carrier waveform or a single-carrier waveform for the wireless transmission based at least in part on the indication of the bandwidth for the wireless transmission. The operations of block **1810** may be performed according to the methods described with reference to FIGS. **1** through **4**. In certain examples, aspects of the operations of block **1810** may be performed by a waveform selection component as described with reference to FIGS. **9** through **12**.

[0161] It should be noted that the methods described above describe possible implementations, and that the operations may be rearranged or otherwise modified and that other implementations are possible. Furthermore, aspects from two or more of the methods may be combined.

[0162] Techniques described herein may be used for various wireless communications systems such as code division multiple access (CDMA), time division multiple access (TDMA), frequency division multiple access (FDMA), orthogonal frequency division multiple access (OFDMA), single carrier frequency division multiple access (SC-FDMA), and other systems. The terms “system” and “network” are often used interchangeably. A code division multiple access (CDMA) system may implement a radio technology such as CDMA2000, Universal Terrestrial Radio Access (UTRA), etc. CDMA2000 covers IS-2000, IS-95, and IS-856 standards. IS-2000 Releases may be commonly referred to as CDMA2000 1X, 1X, etc. IS-856 (TIA-856) is commonly referred to as CDMA2000 1×EV-DO, High Rate Packet Data (HRPD), etc. UTRA includes Wideband CDMA (WCDMA) and other variants of CDMA. A time division multiple access (TDMA) system may implement a radio technology such as Global System for Mobile Communications (GSM).

[0163] An orthogonal frequency division multiple access (OFDMA) system may implement a radio technology such as Ultra Mobile Broadband (UMB), Evolved UTRA (E-UTRA), Institute of Electrical and Electronics Engineers (IEEE) 802.11 (Wi-Fi), IEEE 802.16 (WiMAX), IEEE 802.20, Flash-OFDM, etc. UTRA and E-UTRA are part of Universal Mobile Telecommunications system (UMTS). 3GPP Long Term Evolution (LTE) and LTE-A are releases of Universal Mobile Telecommunications System (UMTS) that use E-UTRA. UTRA, E-UTRA, UMTS, LTE, LTE-A, and Global System for Mobile communications (GSM) are described in documents from the organization named “3rd Generation Partnership Project” (3GPP). CDMA2000 and UMB are described in documents from an organization named “3rd Generation Partnership Project 2” (3GPP2). The techniques described herein may be used for the systems and radio technologies mentioned above as well as other systems and radio technologies. While aspects an LTE system may be described for purposes of example, and LTE terminology may be used in much of the description, the techniques described herein are applicable beyond LTE applications.

[0164] In LTE/LTE-A networks, including such networks described herein, the term evolved node B (eNB) may be generally used to describe the base stations. The wireless communications system or systems described herein may include a heterogeneous LTE/LTE-A network in which different types of evolved node B (eNBs) provide coverage for various geographical regions. For example, each eNB or base station may provide communication coverage for a macro cell, a small cell, or other types of cell. The term “cell” may be used to describe a base station, a carrier or component carrier associated with a base station, or a coverage area (e.g., sector, etc.) of a carrier or base

station, depending on context.

[0165] Base stations may include or may be referred to by those skilled in the art as a base transceiver station, a radio base station, an access point, a radio transceiver, a NodeB, eNB, Home NodeB, a Home eNodeB, or some other suitable terminology. The geographic coverage area for a base station may be divided into sectors making up only a portion of the coverage area. The wireless communications system or systems described herein may include base stations of different types (e.g., macro or small cell base stations). The UEs described herein may be able to communicate with various types of base stations and network equipment including macro eNBs, small cell eNBs, relay base stations, and the like. There may be overlapping geographic coverage areas for different technologies.

[0166] A macro cell generally covers a relatively large geographic area (e.g., several kilometers in radius) and may allow unrestricted access by UEs with service subscriptions with the network provider. A small cell is a lower-powered base station, as compared with a macro cell, that may operate in the same or different (e.g., licensed, unlicensed, etc.) frequency bands as macro cells. Small cells may include pico cells, femto cells, and micro cells according to various examples. A pico cell, for example, may cover a small geographic area and may allow unrestricted access by UEs with service subscriptions with the network provider. A femto cell may also cover a small geographic area (e.g., a home) and may provide restricted access by UEs having an association with the femto cell (e.g., UEs in a closed subscriber group (CSG), UEs for users in the home, and the like). An eNB for a macro cell may be referred to as a macro eNB. An eNB for a small cell may be referred to as a small cell eNB, a pico eNB, a femto eNB, or a home eNB. An eNB may support one or multiple (e.g., two, three, four, and the like) cells (e.g., component carriers). A gNB for a macro cell may be referred to as a macro gNB. A gNB for a small cell may be referred to as a small cell gNB, a pico gNB, a femto gNB, or a home gNB. A gNB may support one or multiple (e.g., two, three, four, and the like) cells (e.g., component carriers). A UE may be able to communicate with various types of base stations and network equipment including macro eNBs, small cell eNBs, relay base stations, and the like.

[0167] The wireless communications system or systems described herein may support synchronous or asynchronous operation. For synchronous operation, the base stations may have similar frame timing, and transmissions from different base stations may be approximately aligned in time. For asynchronous operation, the base stations may have different frame timing, and transmissions from different base stations may not be aligned in time. The techniques described herein may be used for either synchronous or asynchronous operations.

[0168] The DL transmissions described herein may also be called forward link transmissions while the UL transmissions may also be called reverse link transmissions. Each communication link described herein—including, for example, wireless communication system **100** and **200** of FIGS. **1** and **2**—may include one or more carriers, where each carrier may be a signal made up of multiple sub-carriers (e.g., waveform signals of different frequencies).

[0169] The description set forth herein, in connection with the appended drawings, describes example configurations and does not represent all the examples that may be implemented or that are within the scope of the claims. The term “exemplary” used herein means “serving as an example, instance, or illustration,” and not “preferred” or “advantageous over other examples.” The detailed description includes specific details for the purpose of providing an understanding of the described techniques. These techniques, however, may be practiced without these specific details. In some instances, well-known structures and devices are shown in block diagram form in order to avoid obscuring the concepts of the described examples.

[0170] In the appended figures, similar components or features may have the same reference label. Further, various components of the same type may be distinguished by following the reference label by a dash and a second label that distinguishes among the similar components. If just the first reference label is used in the specification, the description is applicable to any one of the similar

components having the same first reference label irrespective of the second reference label.

[0171] Information and signals described herein may be represented using any of a variety of different technologies and techniques. For example, data, instructions, commands, information, signals, bits, symbols, and chips that may be referenced throughout the above description may be represented by voltages, currents, electromagnetic waves, magnetic fields or particles, optical fields or particles, or any combination thereof.

[0172] The various illustrative blocks and modules described in connection with the disclosure herein may be implemented or performed with a general-purpose processor, a DSP, an ASIC, an FPGA or other programmable logic device, discrete gate or transistor logic, discrete hardware components, or any combination thereof designed to perform the functions described herein. A general-purpose processor may be a microprocessor, but in the alternative, the processor may be any conventional processor, controller, microcontroller, or state machine. A processor may also be implemented as a combination of computing devices (e.g., a combination of a DSP and a microprocessor, multiple microprocessors, one or more microprocessors in conjunction with a DSP core, or any other such configuration).

[0173] The functions described herein may be implemented in hardware, software executed by a processor, firmware, or any combination thereof. If implemented in software executed by a processor, the functions may be stored on or transmitted over as one or more instructions or code on a computer-readable medium. Other examples and implementations are within the scope of the disclosure and appended claims. For example, due to the nature of software, functions described above can be implemented using software executed by a processor, hardware, firmware, hardwiring, or combinations of any of these. Features implementing functions may also be physically located at various positions, including being distributed such that portions of functions are implemented at different physical locations. Also, as used herein, including in the claims, “or” as used in a list of items (for example, a list of items prefaced by a phrase such as “at least one of” or “one or more of”) indicates an inclusive list such that, for example, a list of at least one of A, B, or C means A or B or C or AB or AC or BC or ABC (i.e., A and B and C). Also, as used herein, the phrase “based on” shall not be construed as a reference to a closed set of conditions. For example, an exemplary operation that is described as “based on condition A” may be based on both a condition A and a condition B without departing from the scope of the present disclosure. In other words, as used herein, the phrase “based on” shall be construed in the same manner as the phrase “based at least in part on.”

[0174] Computer-readable media includes both non-transitory computer storage media and communication media including any medium that facilitates transfer of a computer program from one place to another. A non-transitory storage medium may be any available medium that can be accessed by a general purpose or special purpose computer. By way of example, and not limitation, non-transitory computer-readable media may comprise RAM, ROM, electrically erasable programmable read only memory (EEPROM), compact disk (CD) ROM or other optical disk storage, magnetic disk storage or other magnetic storage devices, or any other non-transitory medium that can be used to carry or store desired program code means in the form of instructions or data structures and that can be accessed by a general-purpose or special-purpose computer, or a general-purpose or special-purpose processor. Also, any connection is properly termed a computer-readable medium. For example, if the software is transmitted from a website, server, or other remote source using a coaxial cable, fiber optic cable, twisted pair, digital subscriber line (DSL), or wireless technologies such as infrared, radio, and microwave, then the coaxial cable, fiber optic cable, twisted pair, digital subscriber line (DSL), or wireless technologies such as infrared, radio, and microwave are included in the definition of medium. Disk and disc, as used herein, include CD, laser disc, optical disc, digital versatile disc (DVD), floppy disk and Blu-ray disc where disks usually reproduce data magnetically, while discs reproduce data optically with lasers. Combinations of the above are also included within the scope of computer-readable media.

[0175] The description herein is provided to enable a person skilled in the art to make or use the disclosure. Various modifications to the disclosure will be readily apparent to those skilled in the art, and the generic principles defined herein may be applied to other variations without departing from the scope of the disclosure. Thus, the disclosure is not limited to the examples and designs described herein, but is to be accorded the broadest scope consistent with the principles and novel features disclosed herein.

Claims

1. A method for wireless communication at a user equipment (UE), comprising: transmitting a radio frequency (RF) capability indication to a base station; receiving, from the base station based on the RF capability indication, downlink control information indicative of a waveform and a bandwidth to use for a first uplink transmission between the UE and the base station; and transmitting the first uplink transmission using the waveform and via the bandwidth indicated via the downlink control information.
2. The method of claim 1, further comprising: transmitting a second uplink transmission using the waveform, wherein the waveform comprises a single-carrier waveform or a multi-carrier waveform.
3. The method of claim 2, wherein the single-carrier waveform comprises a discrete Fourier transform (DFT) spread orthogonal frequency division multiplexing (OFDM) waveform and the multi-carrier waveform comprises an OFDM waveform.
4. The method of claim 1, further comprising: receiving second downlink control information indicative of a second waveform different from the waveform to use for a second uplink transmission; and transmitting the second uplink transmission using the second waveform indicated via the second downlink control information, wherein the waveform is one of a single-carrier waveform or a multi-carrier waveform and the second waveform is another of the single-carrier waveform or the multi-carrier waveform.
5. The method of claim 4, wherein the first uplink transmission is associated with one or more first channel quality measurements, the waveform used for the first uplink transmission being based at least in part on the one or more first channel quality measurements, and the second uplink transmission is associated with one or more second channel quality measurements, the second waveform used for the second uplink transmission being based at least in part on the one or more second channel quality measurements.
6. The method of claim 4, wherein the first uplink transmission is associated with a multi-stream capability of the UE, the waveform used for the first uplink transmission being based at least in part on the multi-stream capability, and the second uplink transmission is associated with a single stream capability of the UE, the second waveform used for the second uplink transmission being based at least in part on the single stream capability.
7. The method of claim 4, wherein the first uplink transmission is associated with a first modulation and coding scheme, the waveform used for the first uplink transmission being based at least in part on the first modulation and coding scheme, and the second uplink transmission is associated with a second modulation and coding scheme, the second waveform used for the second uplink transmission being based at least in part on the second modulation and coding scheme.
8. The method of claim 1, wherein the RF capability indication indicates a single-carrier bandwidth capability of the UE, or a carrier aggregation capability of the UE for transmission of the first uplink transmission, or a combination thereof.
9. An apparatus for wireless communication, comprising: one or more processors; and one or more memories coupled with the one or more processors, the one or more processors configured to: transmit a radio frequency (RF) capability indication to a base station; receive, from the base station based on the RF capability indication, downlink control information indicative of a

waveform and a bandwidth to use for a first uplink transmission between a user equipment (UE) and the base station; and transmit the first uplink transmission using the waveform and via the bandwidth indicated via the downlink control information.

10. The apparatus of claim 9, wherein the one or more processors are further configured to: transmit a second uplink transmission using the waveform, wherein the waveform comprises a single-carrier waveform or a multi-carrier waveform.

11. The apparatus of claim 10, wherein the single-carrier waveform comprises a discrete Fourier transform (DFT) spread orthogonal frequency division multiplexing (OFDM) waveform and the multi-carrier waveform comprises an OFDM waveform.

12. The apparatus of claim 9, wherein the one or more processors are further configured to: receive second downlink control information indicative of a second waveform different from the waveform to use for a second uplink transmission; and transmit the second uplink transmission using the second waveform indicated via the second downlink control information, wherein the waveform is one of a single-carrier waveform or a multi-carrier waveform and the second waveform is the another of the single-carrier waveform or the multi-carrier waveform.

13. The apparatus of claim 12, wherein the first uplink transmission is associated with one or more first channel quality measurements, the waveform used for the first uplink transmission being based at least in part on the one or more first channel quality measurements, and the second uplink transmission is associated with one or more second channel quality measurements, the second waveform used for the second uplink transmission being based at least in part on the one or more second channel quality measurements.

14. The apparatus of claim 12, wherein the first uplink transmission is associated with a multi-stream capability of the UE, the waveform used for the first uplink transmission being based at least in part on the multi-stream capability, and the second uplink transmission is associated with a single stream capability of the UE, the second waveform used for the second uplink transmission being based at least in part on the single stream capability.

15. The apparatus of claim 12, wherein the first uplink transmission is associated with a first modulation and coding scheme, the waveform used for the first uplink transmission being based at least in part on the first modulation and coding scheme, and the second uplink transmission is associated with a second modulation and coding scheme, the second waveform used for the second uplink transmission being based at least in part on the second modulation and coding scheme.

16. The apparatus of claim 9, wherein the RF capability indication indicates a single-carrier bandwidth capability of the UE, or a carrier aggregation capability of the UE for transmission of the first uplink transmission, or a combination thereof.

17. A non-transitory computer-readable medium comprising instructions operable to cause one or more processors to: transmit a radio frequency (RF) capability indication to a base station; receive, from the base station based on the RF capability indication, downlink control information indicative of a waveform and a bandwidth to use for a first uplink transmission between a user equipment (UE) and the base station; and transmit the first uplink transmission using the waveform and via the bandwidth indicated via the downlink control information.

18. The non-transitory computer-readable medium of claim 17, wherein the instructions are further operable to cause the one or more processors to: transmit a second uplink transmission using the waveform, wherein the waveform comprises a single-carrier waveform or a multi-carrier waveform.

19. The non-transitory computer-readable medium of claim 18, wherein the single-carrier waveform comprises a discrete Fourier transform (DFT) spread orthogonal frequency division multiplexing (OFDM) waveform and the multi-carrier waveform comprises an OFDM waveform.

20. The non-transitory computer-readable medium of claim 17, wherein the instructions are further operable to cause the one or more processors to: receive second downlink control information indicative of a second waveform different from the waveform to use for a second uplink

transmission; and transmit the second uplink transmission using the second waveform indicated via the second downlink control information, wherein the waveform is one of a single-carrier waveform or a multi-carrier waveform and the second waveform is another of the single-carrier waveform or the multi-carrier waveform.
