

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent Application Publication

20250265876

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

Marcinkowski; Dave et al.

---

### SMART THERMOSTAT HUB

---

#### Abstract

A smart thermostat hub and a management platform for controlling and securing smart devices in a multi-family residential property are disclosed. Smart thermostat hubs may bi-directionally communicate with the management platform using a LoRaWAN communication link and communicate with smart devices present within an apartment of the multi-family residential property via a non-LoRaWAN communication link. Smart thermostat hub may provide a gateway or bridge between the management platform and an offline door lock, thereby enabling access credentials for an offline door lock to be disabled from the management platform, and may serve to facilitate remote configuration of other smart devices, such as thermostats and smart light fixtures, for example.

---

**Inventors:** Marcinkowski; Dave (Lubbock, TX), Mandry; Thomas (Lubbock, TX), Massie; Shawn (Lubbock, TX), Gilles; David (Lubbock, TX), Lafreniere; Larry (Lubbock, TX), Johnson; Tray (Lubbock, TX)

**Applicant:** EDST, LLC (Lubbock, TX)

**Family ID:** 1000008578291

**Appl. No.:** 19/200311

**Filed:** May 06, 2025

#### Related U.S. Application Data

parent US continuation 18822751 20240903 PENDING child US 19200311

parent US continuation 17512577 20211027 parent-grant-document US 12080115 child US 18822751

parent US continuation 16912370 20200625 parent-grant-document US 11189118 child US 17512577

parent US continuation 16162262 20181016 parent-grant-document US 10825273 child US 16912370

---

## Publication Classification

**Int. Cl.:** **G07C9/00** (20200101); **G06F3/0484** (20220101); **H04L12/28** (20060101); **H04W12/04** (20210101)

**U.S. Cl.:**

**CPC** **G07C9/00182** (20130101); **G06F3/0484** (20130101); **G07C9/00904** (20130101); **H04L12/283** (20130101); **H04W12/04** (20130101); G07C2009/00198 (20130101); G07C9/00309 (20130101); G07C2009/00333 (20130101); G07C2009/00357 (20130101); G07C2009/00507 (20130101); G07C2009/00769 (20130101); G07C2009/00825 (20130101)

---

## Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS [0001] The present application is a continuation of U.S. patent application Ser. No. 18/822,751 filed Sep. 3, 2024, entitled “SMART THERMOSTAT HUB” (Attorney Docket No. MDRA.P0003US.C2C1C6); which is a continuation of U.S. patent application Ser. No. 17/512,577 filed Oct. 27, 2021, and issued as U.S. Pat. No. 12,080,115 on Sep. 3, 2024, entitled “SMART THERMOSTAT HUB” (Attorney Docket No. MDRA.P0003US.C2C1); which is a continuation of U.S. patent application Ser. No. 16/912,370 filed Jun. 25, 2020, and issued as U.S. Pat. No. 11,189,118 on Nov. 30, 2021, entitled “SMART THERMOSTAT HUB” (Attorney Docket No. MDRA.P0003US.C2); which is a continuation of U.S. patent application Ser. No. 16/162,262 filed Oct. 16, 2018, and issued as U.S. Pat. No. 10,825,273 on Nov. 3, 2020, entitled “SMART THERMOSTAT HUB” (Attorney Docket No. MDRA.P0003US); the disclosures of which are incorporated by reference herein in their entirety.

### TECHNICAL FIELD

[0002] The present disclosure is directed to an intelligent thermostat. In particular, the present disclosure is directed to an intelligent thermostat that can function as a hub having multi-band/multi-radio communication capabilities and can be implemented in a system for controlling and securing offline door locks and other smart devices within a multi-family property.

### BACKGROUND

[0003] Technology and the benefits it provides often plays an important role with respect to how many consumers make decisions. This has become increasingly so in the real-estate industry, and more specifically in the multi-family residential property market. To illustrate, Class A multi-family residential properties (e.g., apartments, etc.) may have keyless entry systems installed that allow residents to gain entry into their respective apartments by placing a fob, smartphone, or smartcard in proximity to a door lock. As another example, these Class A multi-family residential properties may have been constructed with infrastructure, such as Wireless Fidelity (Wi-Fi) access points and/or wired networks (e.g., Ethernet), for providing Internet access to residents. While the security and convenience these technologies provide are attractive to residents, deploying such technologies in older multi-family residential properties, such as Class B and C multi-family residential properties, can be cost prohibitive and/or present challenges with respect to the security of residents of the multi-family residential property.

[0004] For example, keyless entry systems may utilize online door locks or offline door locks. Online door locks may be controlled (e.g., locked and unlocked) remotely through an Internet-accessible network connection and locally by a device (e.g., a fob, smartphone, smartcard, etc.) that is placed in proximity to a sensor of the online door lock, while offline door locks can only be

controlled (e.g., locked and unlocked) by a device (e.g., a fob, smartphone, smartcard, etc.) that is placed in proximity to a sensor of the offline door lock. The cost to deploy an online door lock-based keyless entry system in a multi-family residential property can be significantly higher than offline door lock-based keyless entry systems due to the requirement that network communication infrastructure (e.g., a mesh network, a Wi-Fi network, etc.) be provided to facilitate network-based control of the door lock.

[0005] While less expensive to deploy, the offline door lock-based keyless entry systems present challenges with respect to security. For example, in addition to being controlled remotely, online door locks can be managed remotely, such as to authorize and disable new access credentials. For offline door locks, new access credentials for controlling an offline door lock may be created via a network-based application (e.g., a cloud-based application or website); however, offline door locks require an individual, such as a property manager or property maintenance personnel, to connect (e.g., via a universal serial bus (USB) connection) an external device (e.g., a laptop, tablet, or other electronic device) to the offline door lock and then use software or another utility provided by the external device to disable access credentials. The requirement that access credentials for offline door locks be disabled in person presents risks with respect to the security of residents of a multi-family residential property. For example, if a resident's access credential (e.g., fob, smartcard, etc.) is lost or stolen, the access device may be used to gain entry into the resident's apartment before the appropriate personnel can visit the resident's apartment and use an external device to disable the lost or stolen access credential. As another example, if a resident gives an access credential to a non-resident and then has a falling out with the non-resident, the resident cannot prevent the non-resident from using access credential to gain entry into the resident's apartment and must wait until the appropriate personnel can visit the resident's apartment to disable the access credential provided to the non-resident.

## SUMMARY

[0006] Embodiments described herein provide a system that comprises smart thermostat hubs and a management platform for controlling and securing smart devices in a multi-family residential property. Smart thermostat hubs may comprise a first communication interface that facilitates bi-directional communication between smart thermostat hub and the management platform and a second communication interface that facilitates bi-directional communication between the thermostat smart hub and the smart devices present within a unit of the multi-family residential property. Smart thermostat hub may provide a gateway or bridge between the management platform and an offline door lock, thereby enabling access credentials for an offline door lock to be disabled from the management platform via the bi-directional communication links provided by the first and second communication interfaces of smart thermostat hub.

[0007] In addition to providing enhanced the security for offline door lock-based keyless entry systems, smart thermostat hub may also provide functionality for automating and improving various property management tasks. For example, the management platform may be configured to automatically detect (e.g., based on a database) when a unit of a multi-family residential property becomes vacant and may transmit control information to smart thermostat hub of the vacant unit. The control information may include information that identifies various smart devices within the unit, as well as parameters for configuring the identified smart devices. Upon receiving the control information via first communication interface, smart thermostat hub may transmit commands to each of the identified smart devices via second communication interface, where the commands configure the identified smart devices in accordance with parameters specified in the control information. Similar operations may be performed when the management platform detects that a resident is scheduled to move in to a vacant unit of the multi-family residential property.

[0008] The foregoing has outlined rather broadly the features and technical advantages of the present invention in order that the detailed description of the invention that follows may be better understood. Additional features and advantages of the invention will be described hereinafter which

form the subject of the claims of the invention. It should be appreciated by those skilled in the art that the conception and specific embodiment disclosed may be readily utilized as a basis for modifying or designing other structures for carrying out the same purposes of the present invention. It should also be realized by those skilled in the art that such equivalent constructions do not depart from the spirit and scope of the invention as set forth in the appended claims. The novel features which are believed to be characteristic of the invention, both as to its organization and method of operation, together with further objects and advantages will be better understood from the following description when considered in connection with the accompanying figures. It is to be expressly understood, however, that each of the figures is provided for the purpose of illustration and description only and is not intended as a definition of the limits of the present invention.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

[0009] For a more complete understanding of the disclosed methods and apparatuses, reference should be made to the embodiments illustrated in greater detail in the accompanying drawings, wherein:

[0010] FIG. 1 is a block diagram of an exemplary system for managing and securing access credentials for accessing a multi-family residential property using smart devices in accordance with aspects of the present disclosure;

[0011] FIG. 2 is a block diagram of a smart thermostat hub in accordance with embodiments of the present disclosure;

[0012] FIG. 3 is a block diagram of another smart hub in accordance with embodiments of the present disclosure;

[0013] FIG. 4 is a block diagram of a modular smart thermostat hub in accordance with embodiments of the present disclosure;

[0014] FIG. 5 is a block diagram illustrating aspects of an intelligent property management system configured in accordance with embodiments of the present disclosure;

[0015] FIG. 6 is a block diagram illustrating additional aspects of an intelligent property management system configured in accordance with embodiments of the present disclosure;

[0016] FIG. 7 is a block diagram illustrating additional aspects of an intelligent property management system configured in accordance with embodiments of the present disclosure;

[0017] FIG. 8 is a flow diagram illustrating an exemplary method for securing smart devices within an apartment of a multi-family residential property in accordance with embodiments of the present disclosure;

[0018] FIG. 9 is a flow diagram of an exemplary method for retrieving access log data from an offline door lock in accordance with embodiments of the present disclosure;

[0019] FIG. 10 is a flow diagram illustrating an exemplary method for securing an offline door lock of an apartment of a multi-family residential property in accordance with embodiments of the present disclosure;

[0020] FIG. 11 is a flow diagram illustrating an exemplary method for securing an offline door lock of an apartment of a multi-family residential property in accordance with embodiments of the present disclosure;

[0021] FIG. 12 is a block diagram illustrating exemplary features of an offline door lock configured in accordance with embodiments of the present disclosure; and

[0022] FIG. 13 is a block diagram illustrating an embodiment of a smart thermostat in accordance with embodiments of the present disclosure.

[0023] It should be understood that the drawings are not necessarily to scale and that the disclosed embodiments are sometimes illustrated diagrammatically and in partial views. In certain instances,

details which are not necessary for an understanding of the disclosed methods and apparatuses or which render other details difficult to perceive may have been omitted. It should be understood, of course, that this disclosure is not limited to the particular embodiments illustrated herein.

#### DETAILED DESCRIPTION

[0024] Referring to FIG. 1, a block diagram of an exemplary system for managing and securing access credentials for accessing a multi-family residential property using smart devices in accordance with aspects of the present disclosure is shown as a system **100**. As described in more detail below, system **100** provides functionality that improves the manner in which access to multi-family residential properties is managed and secured. Additionally, system **100** may reduce the cost of deploying various technologies in a multi-family residential property, thereby enabling such technologies to be utilized in certain multi-family residential properties for which previous technologies were deemed cost prohibitive, such as Class B and Class C properties.

[0025] In FIG. 1, system **100** is illustrated as comprising smart hub **110**, one or more smart devices **120**, and server **130**. As shown in FIG. 1, server **130** may include one or more processors **132**, memory **133**, credential management module **137**, and one or more communication interfaces **138**. Memory **133** may include random access memory (RAM), read only memory (ROM), hard disk drives(s) (HDDs), solid state drive(s) (SSDs), network attached storage (NAS) devices, or other types of memory devices for storing data in a persistent or non-persistent state. Memory **133** may store instructions **134** that, when executed by the one or more processors **132**, cause the one or more processors **132** to perform the operations of server **130** described with reference to FIGS. 1-6. Additionally, one or more databases **135** may be stored at memory **133**. Exemplary types of information that may be stored at the one or more databases **135** are described in more detail below. It is noted that although FIG. 1 illustrates server **130** as a standalone device, it is to be understood that server **130** and the functionality described herein with respect to the server **130**, may be implemented using more than one server or via a collection of computing resources (e.g., processors, memory, communication interfaces, and the like) deployed in the cloud.

[0026] Credential management interface **137** may be configured to manage (e.g., create and disable) access credentials provided to residents of a multi-family residential property. For example, credential management interface **137** may be configured to generate access credentials that enable a resident to access one or more areas of a multi-family residential property, such as the resident's apartment, a workout facility, a pool, a parking garage, and the like. Access credentials may be stored on a device, such as a fob, a smartcard, or a resident's smartphone and may be used to control (e.g., lock and unlock) an offline door lock installed on a door of the resident's apartment. In an embodiment, each of the offline door locks of the multi-family residential property may comprise logic configured to process access credentials presented for authentication. For example, when a resident places a device having the resident's access credential in proximity to a sensor (e.g., a near field communication (NFC) device, a Bluetooth device, etc.) of the offline door lock, access credential may be received by the logic for processing, which may include applying a hash function or other data processing technique. If the processing is successful (e.g., a result of the hash function or other processing technique satisfies a criterion), a lock control mechanism may be engaged, thereby enabling the resident to turn a knob that controls a deadbolt or other form of locking device to either lock or unlock the offline door lock. If the processing is not successful (e.g., the result of the hash function or other processing technique does not satisfy the criterion), the lock control mechanism may not be engaged. When the lock control mechanism is not engaged, the knob that controls the deadbolt may spin freely (or not move at all), thereby preventing the deadbolt from being placed in a locked state or an unlocked state. Additional features provided by an offline door lock in accordance with embodiments are described in more detail below with respect to FIG. 12.

[0027] In an embodiment, rather than generating access credentials, the credential management interface **137** may interface with a system of a third party service provider that is configured to

generate access credentials. In such an embodiment, the credential management interface **137** may enable property management personnel and/or a resident to request an additional access credential that may be utilized to unlock an offline door lock be generated by the system of the third party service provider. As a result of the request, the system of the third party service provider may generate the requested access credential (assuming appropriate authentication of the request and/or requestor has been performed). Where the access credential is to be utilized by a user device, such as a smart phone, the system of the third party may provide the newly generated access credential to the user device directly, such as by downloading the access credential to the user device via an access credential management application installed on the user device, or indirectly, such via a message (e.g., a text message, e-mail message, etc.) provided to the user device that includes information that enables the user device to retrieve or otherwise obtain or download the newly generated access credential, or via another technique. In an embodiment, if an access credential that is to be disabled corresponds to an access credential that was generated by the system of the third party and that is stored on a user device, such as a smart phone, the server **130** may be configured to interact with the system of the third party to disable such access credentials, such as by providing information the user device to disable further use of the access credential. If, however, the access credential is stored on a third party device **160**, such as a fob or smartcard, disabling of the access credential may be accomplished via communication of control information to smart hub **110**, as described in more detail below.

[0028] In an embodiment, one or more databases **135** may include a credential database storing information associated with the offline door locks installed at the multi-family residential property. When an access credential for a particular offline door lock is to be generated, credential management module **137** may access the credential database to obtain information associated with the particular offline door lock, and then use the obtained information to create access credential. For example, the information stored in access credential database **135** may comprise information that may be used to generate access credentials that, when processed by the logic of the designated offline door lock, produce a successful result. Additionally, when new access credentials are generated, access credential management module **137** may update one or more records stored at the credential database (or another database), such as to record information that identifies the resident or individual access credential was provided to.

[0029] The one or more communication interfaces **138** may include a first communication interface configured to communicatively couple server **130** to smart hubs deployed within the multi-family residential property, such as smart hub **110**, and may include a second communication interface configured to communicatively couple server **130** to one or more communication networks. First communication interface of server **130** may be configured to communicate with smart hub **110** via Long Range (LoRa) wide area network (LoRaWAN) communication link **112** and second communication interface of server **130** may be configured to communicate with the one or more communication networks via a non-LoRaWAN communication link, such as a Institute of Electrical and Electronics Engineers (IEEE) 802.11 communication link, an Ethernet communication link, and the like. In an embodiment, the first communication interface may communicatively couple the server **130** to a LoRa gateway **136**, as shown in FIG. **1**. The LoRa gateway **136** may be configured to relay information received from the server **130** to one or more smart hubs using the LoRaWAN communication link **112** and to relay information received from one or more smart hubs via the LoRaWAN communication link **112** to the server **130**. It is noted that although communication link **112** may be described herein as a LoRaWAN communication link or LoRa-based communication link, it should be understood that communication link **112** may be a communication link within a low-power, wide area network (LPWAN) or another type of network topology utilizing low power-or LoRa-based communication links. For example, in an embodiment, communication link **112** may utilize narrowband-Internet of Things (NB-IoT) communication links, Sigfox-based communication links, Weightless communication links, and the

like.

[0030] Smart hub **110** may include a first communication interface and one or more additional communication interfaces. First communication interface may communicatively couple smart hub **110** to server **130** via LoRaWAN communication link **112** and one or more additional communication interfaces may communicatively couple smart hub **110** to one or more smart devices **120** via non-LoRaWAN communication links **114**, such as a Wi-Fi communication link, a ZigBee communication link, a Bluetooth communication link (e.g., a Bluetooth low energy (BLE) communication link), and the like. As described in more detail below, smart hub **110** may be deployed within an area of a multi-family residential property, such as an apartment, a gym, a game room, etc. and may be utilized to facilitate remote access to, and control of, smart devices in proximity to smart hub **110**.

[0031] In an embodiment, smart hub **110** may be a smart thermostat hub. For example, in FIG. 2, a block diagram of a smart thermostat hub in accordance with embodiments of the present disclosure is shown as a smart thermostat hub **200**. As shown in FIG. 2, smart thermostat hub **200** includes a smart hub controller **210** and a heating, ventilation, and air conditioning (HVAC) controller **220**. Smart hub controller **210** may include one or more processors **212**, a memory **213**, communication interfaces **215**, and one or more input/output (I/O) devices **216**. Memory **213** may include RAM, ROM, one or more HDDs, one or more SSDs, or other types of memory devices for storing data in a persistent or non-persistent state. Memory **213** may store instructions **214** that, when executed by the one or more processors **212**, cause the one or more processors **212** to perform operations of smart hub devices described with reference to FIGS. 1-6. As explained with reference to smart hub **110** of FIG. 1, communication interfaces **215** may include a first communication interface configured to communicatively couple smart hub controller **210** to a remote server (e.g., server **130** of FIG. 1) via a LoRaWAN communication link (e.g., LoRaWAN communication link **112** of FIG. 1) and one or more additional communication interfaces configured to communicatively couple smart hub controller **210** to one or more smart devices (e.g., the one or more smart devices **120** of FIG. 1) via non-LoRaWAN communication links (e.g., non-LoRaWAN communication links **114** of FIG. 1), such as Wi-Fi communication links, ZigBee communication links, a Bluetooth communication links, and the like.

[0032] The one or more I/O devices **216** may be configured to facilitate user interaction with smart hub controller **210**. For example, a user (e.g., employee, contractor, or agent of the multi-family residential property) may periodically couple an external device (e.g., third party devices **160** of FIG. 1) to smart hub controller **210** to perform software upgrades, diagnostics, etc. It is noted, however, that the communication link between smart hub controller and server may be utilized for these purposes in some embodiments. The one or more I/O devices **216** may include a USB interface, a serial port interface, or other type of wired or wireless interface suitable for exchanging information with, obtaining information from, or providing information to smart hub control **210**. Additionally, I/O devices **216** may include a display device, which may provide information regarding an operational status of smart hub controller **210**. For example, the display device may present information associated with a status of various communication links between smart hub controller **210** and smart devices and/or the remote server. It is noted that the specific I/O devices described above have been provided for purposes of illustration, rather than by way of limitation and that I/O devices **216** may include other types of I/O devices that facilitate interaction with smart hub controller **210**.

[0033] As shown in FIG. 2, HVAC controller **220** may include one or more processors **222**, a memory **223**, and one or more I/O devices **225**. Memory **223** may include RAM, ROM, one or more HDDs, one or more SSDs, or other types of memory devices for storing data in a persistent or non-persistent state. Memory **223** may store instructions **224** that, when executed by the one or more processors **222**, cause the one or more processors **222** to perform operations for modifying an ambient setting of an environment, such as heating or cooling an apartment of a multi-family

residential property to a desired temperature. One or more I/O devices **225** may include buttons, display devices, a touch screen, speakers, microphones, and/or other devices that facilitate interaction with HVAC controller **220**. For example, a user may interact with the one or more I/O devices **225** to adjust a temperature of the thermostat. In response to such interaction, HVAC controller **220** may initiate operations to heat or cool an ambient environment specified by the user interaction. As shown in FIG. 2, one or more I/O devices **225** may also include measurement devices **226**, such as a temperature sensor, which may be used to determine whether the temperature of the ambient environment is within a threshold tolerance (e.g., 0.5 degree, 1 degree, 2 degrees, etc.) of the target temperature specified by the user interaction.

[0034] Referring to FIG. 3, a block diagram of another smart hub in accordance with embodiments of the present disclosure is shown as a smart hub **300**. As shown in FIG. 3, smart hub **300** includes smart hub controller **210**, one or more processors **212**, memory **213**, instructions **214**, communication interfaces **215**, and I/O devices **216** described above with reference to FIG. 2. However, smart hub **300** of FIG. 3 also includes power interface **302**. Power interface **302** may comprise one or more components (e.g., a plug configured to interface with a power outlet, a power coupling configured to couple smart hub **300** to a power source via electrical wiring of a structure, a battery interface, and the like) configured to provide operational power to smart hub **300**. Therefore, as compared to smart thermostat hub **200** of FIG. 2, smart hub **300** of FIG. 3 illustrates an embodiment of smart hub as standalone device.

[0035] It is noted that, as compared to smart hub **300** of FIG. 3, smart thermostat hub **200** of FIG. 2 may provide several advantages for multi-family residential properties, such as Class B and C properties in particular. For example, a common problem when deploying new technologies in Class B and C properties is the lack of necessary infrastructure needed to support the new technology. To install the standalone smart hub illustrated in FIG. 3, an electrician would need to find or create a suitable source for tapping into existing electrical wiring of an apartment in order to hard wire smart hub **300** into the apartment's electrical power infrastructure. This may include hardwiring smart hub **300** to electrical wiring of a power outlet, which would result in loss of an existing power outlet of the apartment. Alternatively, an electrician may install smart hub **300** on a wall of the apartment by tapping into or splicing the existing electrical wiring of the apartment, but this option would create a significant cost if performed for many apartments of a multi-family residential property. An additional option would be to plug smart hub **300** into an electrical outlet of the apartment. This option may be problematic as the resident could easily unplug smart hub **300** from the electrical outlet, thereby preventing operation of smart hub **300** and the various features it provides with respect to certain smart devices of the apartment, such as managing and controlling an offline door lock and enhanced property management functionalities (e.g., controlling a thermostat, light fixtures, etc.).

[0036] In contrast, smart thermostat hub **200** of FIG. 2 is designed to be installed as a replacement to existing thermostats that may be present in a multi-family residential property. Even for Class B and Class C residential properties, the existing thermostats would be coupled to existing electrical wiring of the structure thereby enabling installation of smart thermostat hub **200** by simply removing the existing thermostat and coupling smart thermostat hub **200** to the existing electrical wiring. Such an installation can be performed with minimal effort and cost, thereby significantly reducing the cost to deploy smart thermostat hubs in a multi-family residential property. Additionally, because smart thermostat hub **200** may be enclosed within a single housing, the likelihood that a resident would tamper with or remove smart thermostat hub **200**, and thereby inhibit the benefits that smart thermostat hub **200** provides with respect to security and property management functionality would be minimized. A further advantage of smart thermostat hub **200** is that thermostats may be centrally located within a structure for which they provide control of an HVAC system, such as a central location within an apartment of a multi-family residential property. This may be advantageous as it enables smart hub functionality to be centralized with respect to the



apartment, thereby increasing the likelihood that smart hub's one or more second communication interfaces (e.g., communication interfaces for interacting with smart devices), which may utilize communication links having short range communication capabilities, are within communication range of smart devices present in the apartment, such as an offline door lock.

[0037] Referring to FIG. 4, a block diagram of a modular smart thermostat hub in accordance with embodiments of the present disclosure is shown as modular smart thermostat hub **400**. As shown in FIG. 4, the modular smart thermostat hub may comprise a thermostat component **410** and a smart hub component **420**. Thermostat component **410** may comprise the components of smart thermostat hub **200** that provide control over an HVAC system of a structure, such as HVAC controller **222** (including the one or more processors **222** and memory **223** storing instructions **224**) and I/O devices **225** (including the measurement devices **226**). Smart hub component **420** may include components of smart thermostat hub **200** of FIG. 2 and/or smart hub **300** of FIG. 3 that provide the above-described improvements with respect to security and property management through utilization of smart devices, such as an offline door lock, a thermostat, lights fixtures, and the like. For example, as illustrated in FIG. 4, smart hub component **420** may comprise smart hub controller **210** (including the one or more processors **212** and memory **213** storing instructions **214**), communication interfaces **215**, and I/O devices **216**.

[0038] Additionally, thermostat component **410** may comprise a smart hub interface **412** and smart hub component **420** may comprise a thermostat interface **422**. The modular smart thermostat hub **400** may be formed by coupling smart hub interface **412** and the thermostat interface **422**, as shown at arrow **402**. For example, smart hub interface **412** may comprise one or more pins and the thermostat interface **422** may comprise a connector configured to couple the one or more pins of smart hub interface **412**. Alternatively, the thermostat interface **422** may comprise one or more pins and smart hub interface **412** may comprise a connector configured to couple the one or more pins of the thermostat interface **422**. It is noted that although smart hub interface **412** and the thermostat interface **422** have been described as being coupled via one or more pins and a connector, this exemplary technique for interfacing smart hub component **420** and thermostat component **410** has been provided for purposes of illustration, rather than by way of limitation and that other techniques and components may be used to couple smart hub component **420** and thermostat component **410**.

[0039] As shown above, the modular smart thermostat hub **400** may comprise separate components (e.g., thermostat component **410** and smart hub **420**) that, when coupled, facilitate the operations for providing the enhanced security features for managing and securing offline door locks and the improved property management functionality, as described herein. The modular design of the modular smart thermostat hub **400** may provide various advantages over smart thermostat hub **200** and smart hub **300** described above. For example, due to the modular design, a multi-family residential property may be incrementally upgraded to provide the various features described herein, such as installing thermostat component **410** at a first point in time and then installing smart hub component **420** at a second point in time that is later than the first point in time. This may allow a multi-family residential property to be upgraded over time using components (e.g., thermostat component **410** and smart hub component **420**) that may be cheaper (individually) than smart thermostat hub **200**, enabling the upgrades to be performed as a budget of the multi-family residential facility allows. The modular smart thermostat hub may also provide additional advantages regardless of whether the components (e.g., thermostat component **410** and smart hub component **420**) of the modular smart thermostat hub are installed at the same point in time or at different points in time. For example, if thermostat component **410** of the modular smart thermostat hub **400** fails, thermostat component **410** may be replaced without replacing smart hub component **420** and if smart hub component **420** of the modular smart thermostat hub **400** fails, smart hub component **420** may be replaced without replacing thermostat component **410**. Therefore, the cost of maintaining the modular smart thermostat hub **400** in an operational state over time may be less

than smart thermostat hub **200** of FIG. 2. It is noted that the components of the modular smart thermostat hub **400** may be provided within a single housing. For example, thermostat component **410** may comprise a housing that includes a cavity or space within which smart hub component **420** may be provided. The cavity or space within the housing may be accessible through an access panel of the housing.

[0040] It is noted that each of the different smart hub configurations illustrated in FIGS. 2-4, which are configured to utilize LoRa-based communication links (e.g., communication link **112** of FIG. 1), provide the additional advantage of not requiring network infrastructure, such as a Wi-Fi network, to be deployed in concert with the deployment of the smart hub devices in order to facilitate operations in accordance with embodiments of the present disclosure. This significantly reduces the costs to deploy the smart hubs in a multi-family residential property. However, it is noted that even in situations where such network infrastructure is present, the LoRa-based smart hubs illustrated in FIGS. 2-4 still provide certain advantages, as described in more detail below with reference to FIG. 7.

[0041] Referring back to FIG. 1, during operation of system **100**, residents of a multi-family residential property may be provided with access credentials, as described with reference to credential management module **137**. Access credentials may be provided to the residents via user devices **140** or third party devices **160**. Exemplary user devices **140** may include a resident's smartphone, tablet computing device, smartwatch, or other electronic devices having appropriate functionality for interacting with an offline door lock, such as functionality enabling communication via NFC, Bluetooth, ZigBee, Zwave, and the like. Exemplary third party devices **160** may include fobs or smartcards provided by the multi-family residential property, such as by an employee or property manager associated with the multi-family residential facility.

[0042] In an embodiment, access credentials may also be provided to the user devices **140** via a cloud-based service **152** accessible via a network **150**, such as the Internet. For example, a property management entity associated with a multi-family residential facility may provide a website and/or mobile application that residents may utilize to obtain access credentials. The website and/or the mobile application may enable residents to interact with the cloud-based service **152** to request access credentials. The cloud-based service **152** may be configured to generate access credentials in a manner similar to the techniques described above with respect to credential management module **137** of server **130**. For example, after authenticating a resident, the cloud-based service **152** may generate an access credential based on information stored in a database, such as the credential database described above. Once generated, the cloud-based service **152** may provide access credential to the resident's user device.

[0043] As described above, generation of credentials may not require interaction with an offline door lock. Instead, access credential may be generated such that when access credential is presented to the offline door lock (e.g., via placing a device loaded with access credential in proximity to the offline door lock), a result (e.g., a hash value or other information) generated by the credential processing logic of the offline door satisfies an access authorization criterion. The access authorization criterion may comprise a pre-determined value (e.g., a pre-determined hash value or other information) or may comprise a range of pre-determined values. Utilizing access authorization criteria comprised of a range of pre-determined values may facilitate various advantageous features of system **100**.

[0044] For example, as access credentials are generated, by either the cloud-based service **152** or credential management module **137**, each access credential may be configured to result in a different value within the pre-determined range of values of the corresponding offline door lock, and information that identifies each individual to which an access credential is provided may be recorded (e.g., at the credentials database or another database). The offline door lock may comprise a memory configured to log information associated with each access credential presented to the offline door lock, such as the result generated by the processing logic of the offline door lock in

response to presentation of an access credential and timestamp information associated with a time when access credential was presented. The logged information may also include information associated with a state of the offline door lock at the time access credential is present. For example, the state of the offline door lock may be configurable to change between a locked state and an unlocked state, as described above. Each time the state of the offline door lock changes, information indicating the current state of the offline door lock and the time of the state change may be recorded in memory of the offline door lock.

[0045] The log of information recorded by the offline door lock may be subsequently retrieved to audit access of the offline door lock. To illustrate, smart hub **110** may be configured to periodically generate and transmit an audit log request that may be transmitted to the offline door lock via a communication link provided by the one or more second communication interfaces of smart hub **110**. In response to the request, the offline door lock may transmit the log of information to smart hub **110** via the communication link. Upon receiving the log of information, smart hub **110** may transmit the log of information to server **130** via a communication link provided by first communication interface (e.g., the LoRaWAN communication interface) and server **130** may store the log of information in the one or more database **135**, such as at an access audit log database. Smart hub **110** may be configured to preform retrieval of the log of information from the offline door lock and transmission of the log of information to server **130** according to scheduling information provided by server **130** via LoRaWAN communication link. For example, the data transmission bandwidth provided by LoRaWAN communication links is lower than other types of wireless communication links, such as Wi-Fi, and therefore, transmission of the log of information may take appreciable time. By scheduling transmission of the log of information to server **130** at specific times, which may correspond to off-peak hours (e.g., overnight), interference with other smart hubs of a multi-family residential property may be minimized, which may ensure more reliable communication with smart hubs of the multi-family residential property in an emergency or priority situation, such as if a credential for an offline door lock needs to be disabled.

[0046] Additionally or alternatively, server **130** may transmit control information to smart hub **110**, where the control information comprises information that identifies the offline door lock and instructs smart hub **110** to obtain at least a portion of the log of information (e.g., information associated with all access credentials presented to the offline door lock, invalid (denied) access credentials presented to the offline door lock, valid access credentials presented to the offline door lock; information associated with changes in the state (actuation events) of the offline door lock; a current state of the offline door lock; and the like), where the portion of the log of information may be specified temporally (e.g., a portion of the log information corresponding to a particular period of time, such as a specified hour, range of hours, day, number of days, a week, and the like), by event type (e.g., state changes, received valid and/or invalid access credentials, disablement of access credentials, authorization of new access credentials, and the like), or both temporally and by event type (e.g., occurrences of one or more particular event types during one or more defined periods of time). It is noted that temporal portions of the retrieved log information may include consecutive time units, such as portions of the log information captured during a consecutive number of hours, days, weeks, and the like. Additionally, the temporal portions of the retrieved log information may include disjoint time units, such as portions of the log information captured on a first day in a week and a third day of the week, a first number of hours in the morning of a particular day and a second number of hours during the evening of the particular day or another day, and the like. The retrieved access log information may include information that identifies particular access credentials associated the retrieved portion(s) of the information logged by the offline door lock. The ability to probe the offline door lock via control information transmitted by server **130** may improve the security of a multi-family residential property. For example, if a resident is unsure of whether his/her apartment was locked when they left, the resident may contact property management personnel to inquire about the status of the offline door lock, and the

property management personnel may utilize a property management platform provided by server **130** to transmit control information to smart hub **110** associated with the resident's apartment. In this example, the control information may identify the offline door lock associated with the resident's apartment and may specify that smart hub **110** is to retrieve only the current status of the offline door lock (e.g., whether the offline door lock is in the locked state or the unlocked state), rather than the entire log of information stored at memory of the offline door lock. By only retrieving the current state of the offline door lock, the requested information may be returned to server **130** more quickly. If the status of the offline door lock is determined to be unlocked, the property management personnel may visit the resident's apartment and secure the offline door lock (e.g., place the offline door lock in the locked state).

[0047] In an embodiment, a resident may initiate a status check of the offline door lock via cloud-based service **152**. For example, the resident may access the website or mobile application providing a graphical user interface that facilitates interaction with the cloud-based service **152**. The graphical user interface may provide functionality that enables the resident to view the log of information associated with the offline door lock of the resident's apartment, as well as initiate a status check request to determine a current state of the offline door lock. When a status check request is initiated via the graphical user interface provided by the website or mobile application, the cloud-based service **152** may initiate transmission of a status check request message to server **130** via the network **150**. The status check request message may include information identifying the offline door lock for which the status check has been request, such as information that identifies the resident, the resident's apartment number, an offline door lock identifier corresponding to the offline door lock of the resident's apartment, or other information that may be used to identify smart hub located at the resident's apartment. Upon receiving the status check request message, server **130** may obtain information indicating the current status of the offline door lock of the resident's apartment by transmitting control information to smart hub located at the resident's apartment via a LoRaWAN communication link, as described above.

[0048] Upon receiving the status information from smart hub, server **130** may provide the status information to the cloud-based service **152**, which may present information associated with the current status of the offline door lock to the resident via the graphical user interface. The status information may be provided from server **130** to the cloud-based service **152** in a variety of ways. For example, server **130** may store the status information at the access audit log database and then transmit a message to the cloud-based service **152** that indicates the status check request is complete. The cloud-based service **152** may then retrieve the status information from the access audit log database for presentation to the resident via the graphical user interface. Additionally or alternatively, server **130** may include information that indicates the current status of the offline door lock in the response message, which eliminates the need for the cloud-based service **152** to access the access audit log database.

[0049] If the status of the offline door lock is determined to be unlocked, the resident may contact property management personnel to request that they visit the resident's apartment and secure the offline door lock (e.g., place the offline door lock in the locked state). The resident may contact the property management personnel to request that the resident's offline door lock be secured via a phone call, a text message (e.g., a text message sent to a number associated with the multi-family residential property for reporting maintenance requests, door security verification requests, and the like), an e-mail message, an instant message (e.g., an instant message created using functionality of the graphical user interface) provided to a device associated with property management personnel, or another method. In an embodiment, a confirmation notification may be provided to the resident once the offline door lock has been secured by the property management personnel.

[0050] It is noted that smart hub **110** may also be configured to maintain one or more activity logs, which may be periodically retrieved, in whole or in part, via the LoRa-based communication link **112** and LoRa-gateway **136** by the property management platform. Such activity logs may include

information associated with various smart devices such as information that provides historical information associated with how a resident's thermostat is configured (e.g., preferred temperatures, etc.), whether various smart devices, such as lights, were left on for prolonged periods of time, etc. Such information may provide insights into the preferences of the residents of a multi-family residential property, which may be used to automatically customize other experiences of the resident. For example, a resident may gain access to a particular area of the multi-family residential property, such as a game room, a media room, and the like, by presenting the resident's access credential. Such access may be detected (e.g., via periodic probing of offline door locks associated with common areas of the multi-family residential property by one or more smart hubs associated with the common areas or via automatic transmission of access information to the one or more smart hubs by the offline door lock via a non-LoRa-based communication link) and utilized to configure the particular area to perceived preferences of the resident (e.g., a preferred temperature, etc.), where the perceived preferences are derived from the activity log maintained by the smart hub associated with the resident's apartment.

[0051] As briefly described above, server **130** may provide a property management platform that may be utilized to manage various aspects of a multi-family residential property. The property management platform may provide one or more graphical user interfaces that facilitate interaction with smart hubs installed at apartments of the multi-family residential property. To illustrate, the property management platform (e.g., server **130** or a cloud-based implementation of the functionality provided by server **130**) may provide a graphical user interface that enables access credentials associated with an offline door lock to be disabled remotely. Via this graphical user interface, a property management user may view access credentials authorized for a particular offline door lock and select one or more access credentials that are to be disabled. Upon confirming which access credential(s) is to be disabled, server **130** may identify one or more smart hubs of the multi-family residential property associated with offline door locks for which the access credential(s) has been authorized (e.g., may be used to lock or unlock the offline door lock(s)), and may transmit control information to the identified smart hubs. For each of the identified smart hubs, the control information may identify the offline door lock and the access credential(s) that is to be disabled for the identified offline door lock.

[0052] As explained above, control information provided to a smart hub may include information that identifies one or more smart devices to which the control information pertains and information associated with one or more actions or parameters for modifying a configuration of the one or more smart devices. Continuing with this example, upon receiving the control information from server **130**, smart hub(s) may identify one or more smart devices (e.g., one or more offline door locks) and may derive one or more commands for controlling the one or more identified smart devices in accordance with the control information, such as commands to disable access credentials specified in the control information at the identified offline door lock. Having determined the one or more smart devices to which the received control information pertains and deriving appropriate commands for controlling the one or more smart devices in accordance with the control information, smart hub(s) may initiate transmission of the derived commands to the smart devices via communication links provided by second communication interface (e.g., the non-LoRaWAN communication interface), and the smart devices may execute the commands. For example, upon receiving the commands, an offline door lock may disable the identified access credentials. In an embodiment, the offline door lock may disable an access credential by configuring a flag associated with the access authorization criteria used by the processing logic of the offline door lock to authenticate presented access credentials. A first value of the flag may indicate access credential is authorized to configure the offline door lock to the locked state and the unlocked state and a second flag value may indicate that access credential has been disabled. Once disabled, access credential may not be used to configure the offline door lock to the unlocked state or the locked state. In an embodiment, offline door locks may comprise an automatic locking mechanism

that automatically configures the offline door lock to the locked state when a disable access credential is present. This may further enhance security since an offline lock that is in the unlocked state may be automatically transitioned to the locked state when a disable access credential is presented.

[0053] In addition to remotely disabling access credentials, property management personnel may manually disable access credentials associated with offline door locks of system **100**, such as by coupling an external device (e.g., a laptop computing device, a tablet computing device, etc.) to the offline door lock and then using an application or utility provided by the external device to manage access credentials. In an embodiment, server **130** may be configured such that access credentials that have been disabled may not be re-enabled via smart hub **110**. In this embodiment, a disable access credential may only be re-enabled by coupling the external device to the offline door lock, as described above. In an embodiment, disable access credentials may be re-enabled via control information provided to smart hub **110** by server **130**. However, if such capability is provided, system **100** may be configured to require one or more users to authorize the re-enablement of access credential. For example, a manager, supervisor, or other member of property management personnel may need to provide a password in order to re-enable access credential via server **130** and smart hub **110**. As another example, remotely re-enabling an access credential via server **130** and smart hub **110** may require authorization from a member of the property management personnel and the resident associated with the offline door lock where access credential is disabled. Requiring the resident to participate in the authorization to remotely enable an access credential may prevent a nefarious individual from gaining entry into the resident's apartment.

[0054] In an embodiment, access credentials may also be created (e.g., by either the credential management interface **130** or the system of the third party) that comprise information designed to disable another access credential when used. For example, suppose that a first access credential is to be disabled. A second access credential may be generated and configured to include information that is configured to disable the first access credential when the second access credential is presented to a particular offline door lock. The information for disabling the first access credential may include information that identifies the first access credential and other information that specifies an operation associated with the first access credential, such as to disable the first access credential. When the second access credential is presented to the offline door lock, the information for disabling the first access credential may be detected by the offline door lock in addition to detecting the second access credential, thereby enabling the second access credential to be used to change a state of the offline door lock while also disabling the first access credential. It is noted that such techniques may be utilized to disable multiple access credentials, rather than a single access credential, and may also be utilized to disable one or more access credentials at multiple different offline door locks (e.g., by presenting the second access credential carrying the information for disabling the first access credential at multiple offline door locks where the first access credential has been previously authorized for use). Additionally, access credentials carrying information configured to disable one or more other access credentials may be presented to offline door locks via a user device (e.g., a smartphone, etc.) or via a third party device (e.g., a fob, a smartcard, etc.).

[0055] In addition to providing functionality for managing access credential, the property management platform provided by server **130** may also provide graphical user interfaces and features that facilitate intelligent management of a multi-family residential property. For example, the one or more database **135** may include a resident database that includes information associated with vacant apartments of the multi-family residential property, move-in dates associated with new residents, and move-out dates associated with departing residents. The property management platform may utilize this information to control and automate various property management tasks. For example, the property management platform may periodically (e.g., daily, weekly, monthly, etc.) analyze the resident database to identify move out dates. When a move out date occurs, the property management platform may transmit control information to a smart hub **110** of the vacated

apartment via the first communication link (e.g., LoRaWAN communication link) to place various smart devices of the apartment into a vacant mode. To illustrate, the control information may identify the thermostat (e.g., the thermostat of smart thermostat hub **200** of FIG. 2 or thermostat component **410** of FIG. 4) of the vacated apartment and may include parameters specifying a temperature that the thermostat should be configured to while vacant. Smart hub **110** may receive the control information, detect that the control information is associated with the thermostat (e.g., based on device identification information included in the control information, and transmit one or more commands to the thermostat via the second communication link (e.g., a non-LoRaWAN communication link) to modify one or more operational settings of the thermostat in accordance with the control information. The one or more operational settings control at least one of a temperature setting of the thermostat and an operating mode of the thermostat, the operating mode configurable to change between a heating mode, a cooling mode, and an off mode (e.g., to turn the thermostat off).

[0056] In an embodiment, the control information may include scheduling information that specifies periods of time during which the thermostat is to be placed in a particular operating mode. For example, the thermostat scheduling information may specify first information that specifies the thermostat is to be configured to a first operating mode (e.g., the heating mode, the cooling mode, or the off mode) for a first period of time and second information that specifies the thermostat is to be configured to a second operating mode (e.g., the heating mode, the cooling mode, or the off mode) that is different from the first operating mode for a second period of time. The first information may be utilized to at least partially heat the vacant apartment during at least a portion of the night during winter months or cool the apartment during at least a portion of the day during summer months. The particular temperatures associated with the first information and the second information may be determined to mitigate potential damage caused by seasonal temperatures, such as to prevent freezing of water pipes, etc. or prevent damage to paint or other potentially heat sensitive surfaces of the apartment. The second information may configure the thermostat to the off mode to minimize the operating costs associated with the vacant apartment. In an embodiment, the thermostat scheduling information may be dynamically generated. For example, the property management platform may be configured to receive weather data (e.g., via an RSS feed or from another third party source of weather information), and may generate commands to control the configuration of the thermostat based on the weather information, such as to place the thermostat in the heating mode if the weather data indicates severely cold temperatures are expected. As the weather data changes, updates thermostat configuration information may be generated and provided to the thermostat via the smart hub **110**, as described herein.

[0057] As another example, the control information may identify one or more smart light fixtures of the vacated apartment and may include information that indicates the light fixtures are to be turned off. Smart hub **110** may receive the control information, detect that the control information is associated with the one or more smart light fixtures, and transmit one or more commands to the one or more smart light fixtures via the second communication link (e.g., the non-LoRaWAN communication link) to turn the one or more smart light fixtures off. Alternatively, the control information may specify that one or more of the smart light fixtures of the vacant apartment are to be, at least periodically, turned on. In such instances, smart hub **110** may transmit additional commands to turn on any smart light fixtures based on the control information, which may include scheduling information that indicates times and dates for turning each applicable light fixture on and/or off.

[0058] By using server **130** and smart hub **110** to place vacated apartments into the vacant mode, operating costs associated with the multi-family residential property may be significantly reduced. For example, if a thermostat in a vacated apartment is configured to cool the vacated apartment to a low temperature, the thermostat may remain configured in that state until a new resident moves into the apartment. Operating an HVAC system to cool a vacant apartment for a potentially long period

of time may result in significant costs, which are avoided using the above-described techniques.

[0059] To illustrate, suppose that a resident prefers a “cold” apartment and configures the thermostat to maintain the apartment at a particular temperature (e.g., <75° F.). If, during a walkthrough performed in connection with the resident vacating the apartment, the thermostat setting is not noticed, the apartment may continue to be cooled in accordance with the settings configured by the resident, thus maintaining the now vacated apartment at the temperature preferred by the former resident. This may cause the property owner (or property management company) to incur significant unnecessary costs associated with cooling a vacant apartment. However, as described herein, a property management platform in accordance with embodiments of the present disclosure may automatically detect (e.g., based on information stored in the one or more databases **135**) the apartment has been vacated and via the smart hub **110**, may configure the thermostat to the vacant mode, which configures the thermostat's temperature setting to maintain the vacant apartment at a temperature specified by the property management company. This temperature may be higher than temperatures typically configured by residents, such as 80° F. Thus, while the apartment is vacant, the thermostat may maintain the apartment at a higher temperature, resulting in reduced costs during the duration of the vacancy. In an embodiment, the vacant mode may further be configured to turn the thermostat off, at least periodically, such that the HVAC system is not operated at all, which may further reduce the costs associated with the vacant apartment.

[0060] Similarly, the above-described techniques for placing a vacant apartment into vacant mode may also eliminate costs associated with light fixtures being allowed to remain on in a vacant apartment. It is noted that in addition to facilitating control of smart devices within apartments of a multi-family residential property, the property management platform may also be utilized to control smart devices associated with public areas of a multi-family residential property, such as gyms, conference rooms, game rooms, parking lots/garages, walking paths, and other common spaces maintained by the property management personnel. For example, the above-described techniques may be utilized to transmit control information to smart hubs communicatively coupled to smart light fixtures and/or thermostats associated with such areas of the multi-family residential property to minimize power consumption and associated costs, such as turning the smart light fixtures off at a particular time (e.g., when a common space is deemed closed), turning the smart light fixtures on at a particular time, such as to light up pathways at night, or increasing the temperature of thermostats at a particular time (e.g., when the leasing office or other area is closed). Further, the property management platform may utilize the above-described techniques to verify whether any offline door locks associated with the areas of the multi-family residential property maintained by the property management personnel were left unlocked, and transmit a notification to a member of the property management if any offline door locks are detected to be in the unlocked state, such as an offline door lock associated with the leasing office.

[0061] From the foregoing, it is to be appreciated that the various devices illustrated in FIG. 1, as well as the features they provide, represent a significant improvement to technologies for managing aspects of a multi-family residential property. For example, system **100** utilizes LoRaWAN communication links to provide backhaul communication between a central location, such as a leasing office, and smart hubs located at the various apartments of the multi-family residential property, system **100** does not require a mesh network or Wi-Fi network to be deployed. This significantly reduces the costs associated with deploying an intelligent property management system, such as system **100** described above, and makes it feasible to deploy intelligent property management systems in certain types of multi-family residential properties for which previous technologies requiring mesh or Wi-Fi networks were cost prohibitive, such as Class B and Class C properties. System **100** also provides features that improve the security of multi-family residential properties, such as by enabling credentials for offline door locks to be remotely disabled via smart hub **110** and allowing offline door locks to be probed for information associated with a state of the



offline door lock or to obtain access log information. Additionally, system **100** provides features that improve property management capabilities, such as by automatically placing vacant apartments into a vacant mode designed to improve the energy efficiency and reduce the operating costs of the multi-family residential property.

[0062] Referring to FIG. 5, a block diagram illustrating aspects of an intelligent property management system configured in accordance with embodiments of the present disclosure is shown. As shown in FIG. 5, a building **500** of a multi-family residential property may include a plurality of apartments **510, 520, 530, 540**. The apartments **510, 520, 530, 540** may include smart hubs **512, 522, 532, 542**, respectively, which may comprise smart thermostat hub **200** of FIG. 2, smart hub **300** of FIG. 3, or the modular smart thermostat hub **400** of FIG. 4. Additionally, each of the apartments **510, 520, 530, 540** may include an offline door lock, illustrated in FIG. 5 as offline door locks **514, 524, 534, 544**. Each of smart hubs **512, 522, 532, 542** may communicate with server **130** via a first communication link (e.g., a LoRaWAN communication link) and may communicate with one or more smart devices, such as thermostat or the offline door locks **514, 524, 534, 544**, via a second communication link (e.g., a non-LoRaWAN communication link).

[0063] As described above, smart hubs **514, 524, 534, 544** may be utilized to control various smart devices present within the respective apartments of the building **500**. For example, suppose that a resident of the apartment **510** left for work and was not sure whether he locked the offline door lock **514** on his way out. As described above with reference to FIG. 1, the resident may utilize a user device **140**, such as a smartphone, to access a cloud-based service (e.g., the cloud-based service **152** of FIG. 1) to obtain the current status of the offline door lock **514**. If the resident discovers that he did forget to lock the offline door lock **514**, the resident may request that property management personnel visit the apartment **510** and secure (e.g., lock) the offline door lock **514**. Once secured, the resident may be notified.

[0064] As another example, suppose that two residents live in apartment **530** and each of the residents have an access credential loaded onto a third party device **160**, such as a fob or smartcard. If one of the residents living in apartment **530** becomes violent toward the other resident, it may be necessary to prevent the aggressor resident from gaining access to apartment **530**. As described above, previous systems that utilized offline door locks would require property management personnel to physically visit the apartment **530** and connect an external device to the offline door lock **534** in order to disable the aggressors access credential. Depending on the urgency with which the credential needs to be disabled, the property management personnel may not arrive in time to prevent the aggressor resident from gaining entry to the apartment **530** and causing harm to the other resident. However, utilizing the property management platform provided by server **130**, property management personnel may remotely disable the aggressor resident's access credential by transmitting control information to smart hub **532**, where the control information causes smart hub **532** to communicate with the offline door lock **534** to disable access credential. As can be appreciated, this functionality enables access credentials to be disabled quickly, significantly enhancing the security services that may be provided to the residents of the multi-family residential property.

[0065] In yet another example, suppose that a resident of apartment **520** has moved out and apartment **520** is now vacant. As described above, the property management platform provided by server **130** may detect the status of the apartment **520** is now vacant and may automatically transmit control information to smart hub **522** to place various smart devices into vacant mode. For example, based on the control information, smart hub **522** may turn off one or more smart lights **526** within the apartment **520** and may configure a thermostat (not shown in FIG. 5) of the apartment **520** to a predetermined temperature. This capability may significantly reduce the power consumption of the multi-family residential facility, resulting in significant cost savings. Additionally, the control information provided to smart hub **522** may instruct smart hub **522** to communicate with the offline door lock **524** to disable the former resident's access credentials. This

may prevent the former resident or someone possessing the former resident's access credentials from gaining unauthorized access to the apartment after resident has moved out.

[0066] Now suppose that apartment **540** is currently vacant, but a new resident is scheduled to move in soon. On the day the new resident is to move in, the property management platform provided by server **130** may transmit control information to smart hub **542** that instructs smart hub **452** to adjust a temperature setting of the thermostat for the apartment **540** in advance of the resident moving in. For example, the control information may be configured to cause the thermostat to start cooling the apartment an hour ahead of a scheduled move in time or at some pre-determined time of day so that the apartment is cooler (relative to the vacant mode) when the resident moves in.

[0067] Referring to FIG. **6**, a block diagram illustrating additional aspects of an intelligent property management system configured in accordance with embodiments of the present disclosure is shown. As shown in FIG. **6**, a multi-family residential property **610** may include a plurality of buildings **611**, **612**, **613**, **614**, **615**, **616**, **617**, **618**, each building having one or more floors and each floor having at least one apartment. As described and illustrated with respect to FIG. **5**, each of the apartments may include a smart hub (e.g., smart thermostat hub **200** of FIG. **2**, smart hub **300** of FIG. **3**, or the modular smart thermostat hub **400** of FIG. **4**), an offline door lock, and other smart devices. Each of smart hubs associated with the apartments of the buildings **611**, **612**, **613**, **614**, **615**, **616**, **617**, **618** may communicate with a server providing a management platform that provides various advantageous features for managing a multi-family residential property.

[0068] As illustrated in FIG. **6**, intelligent property management systems in accordance with embodiments of the present disclosure may include a one or more LoRa gateways **620** in conjunction with server **130**. The one or more LoRa gateways **620** may be configured to communicatively couple one or more smart hubs to server **130** and/or to provide overlapping coverage areas for failover purposes. For example, the communication capabilities of LoRa-based communication links may degrade in some environments or conditions, such as environments with many buildings. In such cases, providing the one or more LoRa gateways **620** may ensure that all smart hubs deployed in a multi-family residential property are communicatively coupled to server **130**. In an embodiment, the LoRa gateway(s) **620** may be communicatively coupled to server **130** via a wired communication link (e.g., an Ethernet communication link) or wireless communication link (e.g., a hotspot or other wireless access point providing the LoRa gateway with network-based access to server **130**). In an embodiment, utilizing the one or more LoRa gateways **620** may enable server **130** to be located at a location other than the multi-family residential property, such as at a corporate office of an entity that owns the multi-family residential property or at another location, or to enable the functionality provided by the server **130** to be accessed from the cloud. In such instances, access to the property management platform provided by server **130** may be facilitated through a web-based interface, which may be provided by the cloud-based service **152** of FIG. **1**.

[0069] Referring to FIG. **7**, a block diagram illustrating additional aspects of an intelligent property management system configured in accordance with embodiments of the present disclosure is shown. As shown in FIG. **7**, a multi-family residential property **700** may include a plurality of buildings **710**, **720**, **730**, **740**, **750**, **760**, each building having one or more floors and each floor having at least one apartment. As described and illustrated with respect to FIG. **5**, each of the apartments may include a smart hub (e.g., smart thermostat hub **200** of FIG. **2**, smart hub **300** of FIG. **3**, or the modular smart thermostat hub **400** of FIG. **4**), an offline door lock, and other smart devices. Each of smart hubs associated with the apartments of the buildings **710**, **720**, **730**, **740**, **750**, **760** may communicate with server **130**, which provides a property management platform that provides various features for managing a multi-family residential property, as described above with reference to FIGS. **1-4**.

[0070] Although not wired and/or wireless communication infrastructure, such as Wi-Fi is not necessary to facilitate operation of intelligent property management systems in accordance with the

embodiments disclosed herein, such features may provide additional capabilities when present. For example, as illustrated in FIG. 7, a plurality of access points **712, 722, 732, 742, 752, 762** may be communicatively coupled to server **130** via wired communication links (e.g., Ethernet, etc.) and/or wireless communication links (e.g., Wi-Fi communication links). The bandwidth capabilities provided by the access points **712, 722, 732, 742, 752, 762** may enable the intelligent property management system to provide video capabilities. For example, in FIG. 7, each of the buildings **710, 720, 730, 740, 750, 760** may be equipped with one or more video cameras **714, 724, 734, 742, 752, 762**, respectively. The video cameras **714, 724, 734, 742, 752, 762** may be communicatively coupled to server **130** via the access points **712, 722, 732, 742, 752, 762** to facilitate video monitoring of areas of the multi-family residential property **700**.

[0071] Referring to FIG. 8, a flow diagram illustrating an exemplary method for securing smart devices within an apartment of a multi-family residential property in accordance with embodiments of the present disclosure is shown as method **800**. In an embodiment, steps of the method **800** may be stored as instructions that, when executed by one or more processors, cause the one or more processors to perform operations for securing smart devices within an apartment of a multi-family residential property, as described above with reference to FIGS. 1-7. It is noted that the method **800** may be performed by smart hub **110** of FIG. 1, smart thermostat hub **200** of FIG. 2, smart hub **300** of FIG. 3, and the modular smart thermostat hub **400** of FIG. 4.

[0072] As shown in FIG. 8, the method **800** may include, at step **810**, receiving, by one or more processors of a smart thermostat hub, control information associated with an offline door lock from a property management platform via a LoRa-based communication link where the control information identifies one or more access credentials to be disabled with respect to the offline door lock. At a step **820**, the method **800** may include generating, by the one or more processors of smart thermostat hub, a command configured to disable the one or more access credentials identified in the control information. In a step **830**, the method **800** may include transmitting, by the one or more processors, the command to the offline door lock via a non-LoRa-based communication link. As described above with reference to FIGS. 1-7, by using a smart thermostat hub in accordance with embodiments of the present disclosure, the method **800** may provide improved security for residents of a multi-family residential property, such as by facilitating access credentials for an offline door lock to be disabled remotely, rather than requiring property management personnel to visit the apartment and couple an external device to the offline door lock.

[0073] It is noted that the concepts of method **800** may further facilitate additional advantageous operations. For example, instead of receiving control information for disabling access credentials of the offline door lock, smart thermostat hub may receive control information configured to control operations of a thermostat, a light fixture, or another smart device present in an apartment where smart thermostat hub is located, or may receive control information configured to retrieve status information from a memory of the offline door lock. In a manner similar to steps **810** and **820**, this additional control information may be received via a LoRa-based communication link and may cause smart thermostat hub to generate one or more commands for controlling operation of smart devices identified by the control information, as described above with reference to FIGS. 1-7. After the one or more commands associated with the additional control information are generated, the smart thermostat hub may transmit the one or more additional commands to the appropriate smart devices via a non-LoRa-based communication link. Utilizing a smart thermostat hub and LoRa-based communication links to provide control information to smart devices may reduce the cost of deploying an intelligent property management system, such as the intelligent property management system described above with reference to FIG. 1. In aspects, the method **800** may also be utilized to create access credentials for one or more offline door locks, remotely unlock an offline door lock, or other operations described above with reference to FIGS. 1-7.

[0074] Referring to FIG. 9, a flow diagram of an exemplary method for retrieving access log data from an offline door lock is shown as a method **900**. In an embodiment, steps of the method **900**

may be stored as instructions that, when executed by one or more processors, cause the one or more processors to perform operations for securing smart devices within an apartment of a multi-family residential property, as described above with reference to FIGS. **1-7**. It is noted that the method **900** may be performed by smart hub **110** of FIG. **1**, smart thermostat hub **200** of FIG. **2**, smart hub **300** of FIG. **3**, and the modular smart thermostat hub **400** of FIG. **4**.

[0075] At step **910**, the method **900** includes transmitting, by one or more processors of a smart thermostat hub, an access log request to an offline door lock via a non-LoRa-based communication link. The access log request may be configured to retrieve at least a portion of access log information stored at a memory of the offline door lock. As described above with reference to FIG. **1**, smart thermostat hub may be configured to transmit the access log request to the offline door lock in response to control information received from a property management platform (e.g., the property management platform provided by server **130** of FIGS. **1, 5, 6, and 7**) and the control information may specify the portion of the access log to be retrieved. At step **920**, the method **900** may include receiving, by the one or more processors of smart thermostat hub, at least the portion of the access log information from a lock processor of the offline door lock via the non-LoRa-based communication link and at step **930**, the method **900** may include transmitting, by the one or more processors of smart thermostat hub, at least the portion of the access log information to the property management platform via a LoRa-based communication link. As described above, transmission of at least the portion of the access log information to the property management platform may be performed periodically, and may also be performed based on scheduling information received from the property management platform.

[0076] It is noted that operations of the method **900** may improve the security of residents of a multi-family residential property. For example, as described above with reference to FIGS. **1 and 5**, if residents are not sure they locked the door to their apartment after they leave, the residents may access a cloud-based service (e.g., the cloud-based service **152** of FIG. **1**) to determine whether they locked the door or not. The cloud-based service may be configured to communicate with the property management platform to initiate operations of the method **900** to obtain a current status of the offline door lock and provide that status to the resident(s). If the door was found to be unlocked, the resident may contact the property management office to request that property management personnel visit the apartment and secure the offline door lock.

[0077] Referring to FIG. **10**, a flow diagram illustrating an exemplary method for securing an offline door lock of an apartment of a multi-family residential property in accordance with embodiments of the present disclosure is shown as method **1000**. In an embodiment, steps of the method **1000** may be stored as instructions that, when executed by one or more processors, cause the one or more processors to perform operations for securing an offline door lock of an apartment of a multi-family residential property, as described above with reference to FIGS. **1-5**. In an embodiment, the method **1000** may be performed by an offline door lock, such as the offline door lock **1200** of FIG. **12**.

[0078] The method **1000** may include, at step **1010**, receiving, by a lock processor of an offline door lock, a command via a non-LoRa-based communication link. As described above with reference to FIGS. **1 and 5**, as well as FIG. **8**, the command may be received from a smart thermostat hub, and may include information for disabling one or more access credentials associated with the offline door lock. At step **1020**, the method **1000** may include modifying, by the lock processor, access credential validation information stored at a memory of the offline door lock to disable the one or more access credentials based on the command. As disclosed herein, modifying access credential validation information may include deleting a portion of access credential validation information corresponding to the one or more access credentials identified in the control information. Additionally or alternatively, modifying access credential validation information may include configuring one or more flags corresponding to the one or more access credentials identified in the control information to have a particular flag value. The one or more

flags may be stored with access credential validation information and the particular flag value may indicate a corresponding access credential is disabled.

[0079] At step **1030**, the method **1000** may include receiving, by a sensor of the offline door lock, access credential information from a credential device placed in proximity to the sensor. As described herein, the credential device may include a smartphone, a fob, a smartcard or another type of device provided with an access credential. At step **1040**, the method **100** may include determining, by the lock processor, a validity of access credential information based on whether access credential validation information indicates access credential information is valid or disabled and at step **1050**, the method **1000** may include engaging, in response to a determination that access credential is valid, a locking mechanism of the offline door lock such that the locking mechanism is configurable to change between locked state and an unlocked state. It is noted that the method **1000** may provide functionality that is complimentary to the functionality provided by the method **800**. Additionally, as described above with reference to FIGS. **1-6**, providing an intelligent property management system that includes a smart thermostat hub to enable access credentials for offline locks to be remotely disabled in accordance with the method **1000** provides improved security for residents of a multi-family residential property, such as by facilitating access credentials for an offline door lock to be disabled remotely, rather than requiring property management personnel to visit the apartment and couple an external device to the offline door lock. Further, it is noted that although the method **1000** is described as providing functionality for disabling access credentials, the method **1000** may also be utilized to provide other functionality described herein with respect to operations of an offline door lock in accordance with aspects of the present disclosure, such as authorize new credentials.

[0080] Referring to FIG. **11**, a flow diagram illustrating an exemplary method for securing an offline door lock of an apartment of a multi-family residential property in accordance with embodiments of the present disclosure is shown as method **1100**. In an embodiment, steps of the method **1100** may be stored as instructions that, when executed by one or more processors, cause the one or more processors to perform operations for securing an offline door lock of an apartment of a multi-family residential property, as described above with reference to FIGS. **1** and **5**. In an embodiment, the method **1100** may be performed by an offline door lock, such as the offline door lock **1200** of FIG. **12**.

[0081] At step **1110**, the method **1100** may include storing, by a lock processor of an offline door lock, access log information at a memory of the offline door lock. As disclosed herein, the access log may comprise access credential information associated with access credentials presented to the sensor and/or status information identifying changes to a state of a locking mechanism of the offline door lock. Additionally, the access log information may comprise time stamps associated with the time that particular information was recorded to the access log. At step **1120**, the method **100** may include receiving, by the lock processor, an access log request via a non-LoRa-based communication link. At step **1130**, the method **1100** may include transmitting, by the lock processor, at least the portion of the access log information to a smart thermostat hub via the non-LoRa-based communication link. As described above with respect to FIGS. **1** and **5**, the access log request may be received by the lock processor from a smart thermostat hub that is in communication with a property management platform, and the request for access log information may ultimately be provided to the property management platform or another destination, such as a graphical user interface associated with the cloud-based service **152** of FIG. **1**.

[0082] It is noted that the method **1100** provides functionality that is complimentary to, and may be used on coordination with, the functionality provided by the method **900**. For example, as described above with reference to FIGS. **1** and **5**, if residents are not sure they locked the door to their apartment after they leave, the residents may access a cloud-based service (e.g., the cloud-based service **152** of FIG. **1**) to determine whether they locked the door or not. The cloud-based service may be configured to communicate with the property management platform to initiate

operations of the method **900** to obtain a current status of the offline door lock and provide that status to the resident(s). If the door was found to be unlocked, the resident may contact the property management office to request that property management personnel visit the apartment and secure the offline door lock. Thus, it is to be appreciated that the operations of the method **1100**, individually or in coordination with other processes, such as the method **900** described with reference to FIG. **9**, may improve the security of residents of a multi-family residential property. [0083] Referring to FIG. **12**, a block diagram illustrating exemplary features of an offline door lock configured in accordance with embodiments of the present disclosure is shown as an offline door lock **1200**. As shown in FIG. **12**, the offline door lock **1200** may include a processor **1210**, a sensor **1212**, a communication interface **1214**, a memory **1220**, a locking mechanism **1230**, and a lock control mechanism **1240**. The sensor **1212** may be configured to receive access credential information from a credential device placed in proximity to the sensor **1212**. For example, the sensor **1212** may be configured to utilize near field communication (NFC) or Bluetooth communication to receive access credentials from an credential device (e.g., a resident's smartphone, a fob, a smartcard, and the like). Communication interface **1214** may be configured to communicatively couple the offline door lock **1200** to smart hub **110** via a non-LoRaWAN communication link, such as a Bluetooth communication link, for example. In an embodiment, the sensor **1212** may be omitted and the communication interface **1214** may be configured to utilize one or more non-LoRa-based communication links, such as a Bluetooth communication link, a ZigBee communication link, and/or other types of non-LoRa communication links, to communicate with a smart thermostat hub and/or to receive, disable, or otherwise manage access credentials, as described herein.

[0084] In an embodiment, communication interface **1214** may include one or more LoRa-based communication interfaces configured to communicatively couple the offline door lock **1200** directly to a remote system, such as a property management platform configured in accordance with embodiments of the present disclosure. In such an embodiment, rather than communicating with a smart hub to perform various operations with respect to the offline door lock **1200**, as described above, the property management platform, which may be provided via server **130** of FIG. **1**, may communicate control information directly to offline door lock **1200** via a LoRa-gateway (e.g., LoRa-gateway **136** of FIG. **1**), such as to retrieve at least a portion of the log information maintained by offline door lock **1200**, manage access credentials associated with offline door lock **1200**, or other operations described herein. Because offline door lock **1200** includes, at least in the embodiment described in this example, a LoRa-based communication interface, offline door lock **1200** may be able to bi-directionally communicate with the property management platform, such as to transmit a requested portion of the access log information to the property management platform via a LoRa-gateway using LoRa-based communication links, as described above.

[0085] As shown in FIG. **12**, memory **1220** of the offline door lock **1200** may store access credential validation information **1222** and access log data **1224**. Additional aspects of access credential validation information **1222** and the access log data are described in more detail above with reference to FIGS. **1-6**. As described above, the lock processor **1210** may be configured to determine a validity of access credential information presented to the sensor **1212** (or the communication interface **1214**) based on the access credential validation information **1222**. Additionally, the lock processor **1210** may be configured to selectively engage the lock control mechanism **1240** based on whether access credential is valid.

[0086] In an embodiment, the locking mechanism **1230** comprises a deadbolt **1232** and the lock control mechanism **1240** may comprise a rotatable member **1242**. The locking mechanism **1230** may be configurable to change between the locked state and the unlocked state via rotation of the rotatable member. For example, in response to successful authentication of access credentials presented to the sensor **1212** (e.g., the presented access credential information is determined to be valid), the lock processor **1210** may engage the lock control mechanism **1240**, and the engagement

of the lock control mechanism **1240** may facilitate interaction between the lock control mechanism **1240** and the locking mechanism **1230**. For example, engagement of the lock control mechanism **1240** may configure the rotatable member **1242** such that rotation of the rotatable member **1242** in a first direction drives the deadbolt **1232** to a first position corresponding to the locked state, as shown at **1202**, and rotation of the rotatable member **1242** in a second direction drives the deadbolt **1232** to a second position corresponding to the unlocked state, as shown at **1204**. The lock processor **1210** may be configured to ignore invalid or disabled credentials. In such instances, interaction between the lock control mechanism **1240** and the locking mechanism **1230** may be prohibited. For example, when an invalid or disabled credential is presented, the lock control mechanism **1240** may not be engaged by the lock processor **1210** in response to receipt of an invalid access credential and the locking mechanism **1230** may be maintained in a current state (e.g., either the locked state or the unlocked state). In such instances, the rotatable member **1242** may freely rotate without impacting the locking mechanism **1232**. As another example, rotation of the rotatable member **1242** may be prevented, thereby causing the lock control mechanism to maintain a current state (e.g., either the locked state or the unlocked state). Thus, in the absence of engagement of the locking mechanism **1240**, the locking mechanism **1230** may remain in the locked state or the unlocked state (e.g., until a valid credential is presented).

[0087] In an embodiment, the lock control mechanism **1240** may include one or more electro-mechanical components **1244**, such as one or more circuits, motors, actuators, gears, or other components, configured to electrically, mechanically, or electro-mechanically configure the locking mechanism **1230** to change between the locked state and the unlocked state. For example, in response to presentation of a valid access credential, the one or more electro-mechanical components **1244** may be activated to automatically drive the deadbolt **1232** to the first position or the second position. In response to presentation of an invalid access credential, the one or more electro-mechanical components may be configured to maintain the locking mechanism **1230** in a current state (e.g., the deadbolt **1232** may be maintained at the first position or the second position). In embodiments comprising an offline door lock **1200** that includes electro-mechanical components **1244**, the offline door lock **1200** may further include a power supply, such as a battery or other power source, configured to supply operational power to the electro-mechanical components **1244**.

[0088] In addition to controlling the electro-mechanical components **1244** in response to valid access credentials, in an embodiment, the lock processor **1210** may be configured to activate or otherwise control the electro-mechanical components **1244** to configure the locking mechanism **1230** to change between the locked state and the unlocked state in response to commands received via a non-LoRa-based communication link, such as commands received from a smart hub configured in accordance with embodiments of the present disclosure. As described above, the smart hub may be configured to generate such commands (e.g., lock commands and/or unlock commands) responsive to control information provided by a property management platform (e.g., the system **100** of FIG. **1**) via a LoRa-based communication link (e.g., via server **130** and LoRa-gateway **136** of FIG. **1**). Additionally, the control information received at the smart hub may be generated by the property management platform in response to information received via a user interface, such as the user interface described above that allows a resident (or property management personnel) to verify a status of the offline door lock as locked or unlocked. For example, if a status check indicates the offline door lock is unlocked, a request may be initiated from the user interface to property management platform to lock the offline door lock. In response to such a request, control information identifying the offline door lock and including an instruction to configure the offline door lock to the locked state may be communicated to the appropriate smart hub via the LoRa-based communication link and then the commands may be provided from the smart hub to the offline door lock via a non-LoRa-based communication link, such as a Bluetooth low energy (BLE) communication link, a ZigBee communication link, a Zwave communication link, etc.

[0089] In an embodiment, the offline door lock **1200** may not be configured to facilitate the use of

remote unlock commands irrespective of whether the offline door lock **1200** includes the electro-mechanical components **1244**. For example, although access credentials may be disabled or enabled/provided via commands received from a smart hub in response to control information transmitted to the smart hub by a property management platform, the offline door lock **1200** may be prevented from enabling the locking mechanism to change between the locked state and the unlocked state via commands received from the smart hub. In this example, the offline door lock **1200** may only enable the locking mechanism to change between the locked state and the unlocked state when a valid access credential is received (e.g., via the sensor **1212** or the communication interface **1214**) from a user device (e.g., smartphone, etc.) or third party device (e.g., a fob, a smartcard, etc.).

[0090] Referring to FIG. **13**, a block diagram illustrating an embodiment of a smart thermostat in accordance with embodiments of the present disclosure is shown as a smart thermostat **1300**. As shown in FIG. **13**, the smart thermostat **1300** may include the components illustrated with respect to the thermostat component **410** of FIG. **4**, however, rather than including the smart hub interface **412**, the smart thermostat **1300** may include a LoRa-based communication interface. In such an embodiment, the smart thermostat **1300** may be communicatively coupled to a property management platform (e.g., the system **100** of FIG. **1**) via a LoRa-based communication link, and may receive control information from the property management platform directly, as opposed to receiving commands derived from control information by a smart hub. Such a direct communication link may enable operational aspects of the smart thermostat **1300** to be configured, such as temperature settings, operating modes, and the like as described above, to be configured via control information provided by the property management platform (e.g., via server **130** and gateway **136** of FIG. **1**) without requiring a smart hub to be provided in proximity to or in connection with the smart thermostat **1300**. In this manner, the advantages provided by utilizing a smart hub to control a thermostat, such as to place the thermostat into vacant mode or other advantageous operations, may be provided by the smart thermostat **1300** directly, thereby providing a more cost effective solution for situations where the additional functionality provided by the smart hub (e.g., short-range communication with offline door locks and other smart devices) may not be desired or practical.

[0091] Although the embodiments of the present disclosure and their advantages have been described in detail, it should be understood that various changes, substitutions and alterations can be made herein without departing from the spirit and scope of the disclosure as defined by the appended claims. It should be noted that although the descriptions provided above with respect to FIGS. **1-13** have been described with reference to multi-family residential properties, embodiments of the present disclosure may be readily applied to other types of properties, such as commercial properties (e.g., office spaces, warehouses, storage units, malls, and the like). Accordingly, it is to be understood that embodiments of the present disclosure are not limited to use with multi-family residential properties. Moreover, the scope of the present application is not intended to be limited to the particular embodiments of the process, machine, manufacture, composition of matter, means, methods and steps described in the specification. As one of ordinary skill in the art will readily appreciate from the present disclosure, processes, machines, manufacture, compositions of matter, means, methods, or steps, presently existing or later to be developed that perform substantially the same function or achieve substantially the same result as the corresponding embodiments described herein may be utilized according to the present disclosure. Accordingly, the appended claims are intended to include within their scope such processes, machines, manufacture, compositions of matter, means, methods, or steps.

## Claims



- 1.** A system for controlling a plurality of smart devices of a unit of a multi-family residential or commercial property, the system comprising: a property management platform configured to provide property management and security functionality, the property management platform configured for accessibility by a user associated with the unit of the multi-family residential or commercial property and by a representative associated with the multi-family residential or commercial property, the property management platform configured to reside at a location other than the multi-family residential or commercial property; and a smart thermostat hub associated with the unit, the smart thermostat hub comprising: a housing; one or more processors in the housing and configured to implement a smart hub controller and a heating, ventilation, and air conditioning (HVAC) controller within the housing; a first bi-directional low-power wide area network (LPWAN) communication interface in the housing and configured to communicatively couple the one or more processors to the property management platform via a LPWAN communication link; and a second bi-directional non-LPWAN communication interface in the housing and configured to communicatively couple the one or more processors to the plurality of smart devices via a non-LPWAN communication link, where the one or more processors are configured to: receive, from the property management platform via the LPWAN communication link, a request for status of a smart device of the plurality of smart devices, request status of the smart device via the non-LPWAN communication link, and transmit, in response to the received request for status, the status of the smart device to the property management platform via the LPWAN communication link.
- 2.** The system of claim 1, where the one or more processors are further configured to: receive, from the property management platform via the LPWAN communication link, a request for status of another smart device of the plurality of smart devices that comprises another type of smart device; request status of the another smart device via the non-LPWAN communication link; and transmit, in response to the received request for status of the another smart device, the status of the another smart device via the LPWAN communication link.
- 3.** The system of claim 1, where the first LPWAN communication interface is a long-range wide area network (LoRaWAN) interface.
- 4.** The system of claim 1, further comprising: a gateway, where the first bi-directional LPWAN communication interface of the smart thermostat hub is configured to communicatively couple the one or more processors to the gateway via the LPWAN communication link and where the gateway is configured to communicatively couple to the property management platform via a non-LPWAN communication link.
- 5.** The system of claim 1, where the property management platform is configured to communicate with a system of a third party service provider.
- 6.** The system of claim 1, where the property management platform is configured to communicate the status of the smart device to a cloud-based service via the Internet.
- 7.** The system of claim 1, where the smart device comprises an electronic door lock, and where the property management platform is configured to: determine the unit is vacant; and signal, in response to determining the unit is vacant, the smart thermostat hub to disable access credentials of the electronic door lock associated with a former resident of the unit and to adjust another one or more smart devices of the plurality of smart devices.
- 8.** The system of claim 7, where the property management platform is configured to automatically determine the unit is vacant based on a database comprising move-out dates.
- 9.** The system of claim 8, where the property management platform is configured to automatically signal the smart thermostat hub in response to determining the unit is vacant.
- 10.** The system of claim 8, where the database comprising move-out dates is a third-party database separate from the property management platform and communicatively coupled to the property management platform.

- 11.** The system of claim 7, where the property management platform is configured to, in response to determining the unit is vacant, signal the smart thermostat hub to adjust a thermostat of the unit to a predetermined temperature.
- 12.** The system of claim 1, where the property management platform is configured to: determine a new resident is scheduled to move into the unit based on a database of move-in dates; and in response to determining a new resident is scheduled to move in, signal the smart thermostat hub to adjust one or more smart devices of the plurality of smart devices associated with the unit.
- 13.** The system of claim 12, where the database of move-in dates is a third-party database separate from the property management platform and communicatively coupled to the property management platform.
- 14.** The system of claim 12, where the database of move-in dates is stored at the property management platform.
- 15.** The system of claim 1, where the one or more processors are configured to: receive, from the property management platform via the LPWAN communication link, one or more requests for activity associated with one or more of the plurality of smart devices, and transmit, at a specified time of day, one or more received activity entries to the property management platform via the LPWAN communication link.
- 16.** The system of claim 1, where the smart device comprises an electronic door lock, a smart thermostat, a second smart thermostat hub, a smart light bulb or a leak detection device.
- 17.** A method for controlling a plurality of smart devices of a multi-family residential or commercial property, the method comprising: receiving, by one or more processors of a smart thermostat hub at a unit of the multi-family residential or commercial property, a request for status of a smart device of the plurality of smart devices via a first bi-directional low-power wide area network (LPWAN) communication link from a property management platform residing at a location other than the multi-family residential or commercial property, the property management platform configured to provide property management and security functionality and configured to be accessed by a user associated with the unit and a representative associated with the multi-family residential or commercial property; requesting, by the one or more processors, status of the smart device via a second bi-directional non-LPWAN communication link; and transmitting, by the one or more processors and in response to the received request for status, the status of the smart device to the property management platform via the first LPWAN communication link.
- 18.** The method of claim 17, where the smart device comprises an electronic door lock, a smart thermostat, a smart thermostat hub, a smart light bulb or a leak detection device.
- 19.** The method of claim 17, where the LPWAN communication link comprises a long-range wide area network (LoRaWAN) communication link.
- 20.** The method of claim 17, where the LPWAN communication link is between the smart thermostat hub and a gateway.
- 21.** The method of claim 20, where receiving via the LPWAN communication link comprises receiving from one or more of a plurality of gateways residing at the multi-family residential or commercial property, where the plurality of gateways includes the gateway.
- 22.** The method of claim 17, further comprising: transmitting, by the one or more processors and via the Internet, the status of the smart device to a cloud-based service.
- 23.** A smart thermostat hub for controlling a plurality of smart devices of a unit of a multi-family residential or commercial property, the smart thermostat hub comprising: a housing; one or more processors in the housing and configured to implement a smart hub controller and a heating, ventilation, and air conditioning (HVAC) controller within the housing; a first bi-directional low-power wide area network (LPWAN) communication interface in the housing and configured to communicatively couple the one or more processors to a property management platform via a LPWAN communication link, the property management platform configured for accessibility by a user associated with the unit of the multi-family residential or commercial property and a

representative associated with the multi-family residential or commercial property, the property management platform configured to reside at a location other than the multi-family residential or commercial property; and a second bi-directional non-LPWAN communication interface in the housing and configured to communicatively couple the one or more processors to the plurality of smart devices via a non-LPWAN communication link, where the one or more processors are configured to: receive, from the property management platform via the LPWAN communication link, a request for status of a smart device of the plurality of smart devices, request status of the smart device via the non-LPWAN communication link, and transmit, in response to the received request for status, the status of the smart device to the property management platform via the LPWAN communication link.

**24.** The smart thermostat hub of claim 23, where the smart thermostat hub is configured to reside in the unit and is coupled to an HVAC device associated with the unit.

**25.** The smart thermostat hub of claim 23, where the smart thermostat hub is part of a system for controlling the plurality of smart devices, including the smart device, associated with the unit of the multi-family residential or commercial property, and where the smart device comprises an electronic door lock, a smart thermostat, a smart thermostat hub, a smart light bulb or a leak detection device.

**26.** The smart thermostat hub of claim 23, where the LPWAN communication link comprises a long-range wide area network (LoRaWAN) communication link.

**27.** The smart thermostat hub of claim 23, where the non-LPWAN communication link comprises at least one of a Wireless Fidelity (Wi-Fi) communication link, a ZigBee communication link, a Bluetooth communication link, and a Bluetooth Low Energy (BLE) communication link.

**28.** The smart thermostat hub of claim 23, where the smart thermostat hub is configured to be communicatively coupled to the plurality of smart devices via the non-LPWAN communication link, the plurality of smart devices including the smart device and a second smart device, where the smart device comprises an electronic door lock and the second smart device comprises a smart thermostat.

**29.** The smart thermostat hub of claim 23, where the smart device comprises smart thermostat, and where the one or more processors are further configured to: receive additional control information from the property management platform via the LPWAN communication link, the additional control information including one or more thermostat parameters; and transmit one or more thermostat commands to the smart thermostat via the non-LPWAN communication link to instruct the HVAC controller based on the one or more thermostat parameters.

**30.** The smart thermostat hub of claim 29, where: the one or more thermostat parameters control a temperature setting, a thermostat operating mode, or both; and the thermostat operating mode is configurable to change between a heating mode, a cooling mode, and an off mode.

**31.** The smart thermostat hub of claim 23, where the one or more processors are further configured to: receive additional control information from the property management platform via the LPWAN communication link, the additional control information identifying a smart light fixture of the plurality of smart devices and including information indicating to turn off the smart light fixture or turn on the smart light fixture; generate one or more light fixture commands configured to turn off the smart light fixture or turn on the smart light fixture based on the additional control information; and transmit the one or more light fixture commands to the smart light fixture via the non-LPWAN communication link.

**32.** The smart thermostat hub of claim 31, where: the additional control information comprises scheduling information that identifies a first time and a second time that is different from the first time; the first time corresponds to a time to turn on the smart light fixture and the second time corresponds to a time to turn off the smart light fixture; and the one or more light fixture commands comprise a first light fixture command to turn on the smart light fixture at the first time and a second light fixture command to turn off the smart light fixture at the second time.

