

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12384006
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Wang; Huisun et al.

Surgical device having changeable elements

Abstract

An electrosurgical device kit includes an elongate first member, an elongate second member disposed adjacent to the first member, the second member being at least movably coupled to the first member, a first electrode head removably attachable to the first member, a second electrode head removably attachable to the first member, and a third electrode head coupled to the second member. The first, second, and third electrode heads are configured to apply a current to a tissue, the first and second electrode heads being non-identical.

Inventors: Wang; Huisun (Maple Grove, MN), Batchelor; Kester Julian (Mound, MN)

Applicant: GYRUS ACMI, INC. (Southborough, MA)

Family ID: 52463145

Assignee: Gyrus ACMI, Inc. (Westborough, MA)

Appl. No.: 16/919233

Filed: July 02, 2020

Prior Publication Data

Document Identifier	Publication Date
US 20200330151 A1	Oct. 22, 2020

Related U.S. Application Data

division parent-doc US 15817707 20171120 US 10702331 child-doc US 16919233
division parent-doc US 14595484 20150113 US 9855091 child-doc US 15817707
us-provisional-application US 61974407 20140402

Publication Classification

Int. Cl.: B25B7/00 (20060101); **A61B17/00** (20060101); **A61B17/29** (20060101); **A61B18/00** (20060101); **A61B18/14** (20060101); **B25B7/04** (20060101); **B25B9/02** (20060101)

U.S. Cl.:

CPC **B25B7/00** (20130101); **A61B17/29** (20130101); **A61B18/1442** (20130101); **A61B18/1445** (20130101); **B25B7/04** (20130101); **B25B9/02** (20130101); A61B2017/00473 (20130101); A61B2017/2929 (20130101); A61B2017/2943 (20130101); A61B2018/00107 (20130101); A61B2018/00589 (20130101); A61B2018/0063 (20130101); A61B2018/1452 (20130101); A61B2018/1462 (20130101); A61B2018/1495 (20130101)

Field of Classification Search

CPC: A61B (17/28-295); A61B (18/1442); A61B (17/30); A61B (17/128); B25B (7/04); B25B (9/02); B25B (7/00)

USPC: 606/205; 606/206; 606/207; 294/99.2

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2010493	12/1934	La	N/A	N/A
2109147	12/1937	Grosso	N/A	N/A
2406393	12/1945	Neugass	N/A	N/A
3044081	12/1961	Robinson, Jr.	N/A	N/A
3484924	12/1968	Dahl	N/A	N/A
3818784	12/1973	McClure	N/A	N/A
4074718	12/1977	Morrison, Jr.	N/A	N/A
4389912	12/1982	Dallons et al.	N/A	N/A
4478221	12/1983	Heiss	N/A	N/A
4634165	12/1986	Russell. et al.	N/A	N/A
4657016	12/1986	Ellman et al.	N/A	N/A
4903696	12/1989	Stasz et al.	N/A	N/A
5047046	12/1990	Bodoia	N/A	N/A
5057016	12/1990	Lukase et al.	N/A	N/A
5190335	12/1992	Rommerdale	N/A	N/A
5334215	12/1993	Chen	N/A	N/A
5342381	12/1993	Tidemand	N/A	N/A
5445638	12/1994	Rydell et al.	N/A	N/A
5462546	12/1994	Rydell	N/A	N/A
5496317	12/1995	Goble et al.	N/A	N/A
5542167	12/1995	Nakamoto	N/A	N/A
5649938	12/1996	Allen	606/151	A61B 17/1114
5797959	12/1997	Castro et al.	N/A	N/A
5810805	12/1997	Sutcu et al.	N/A	N/A
5899513	12/1998	Grisoni	N/A	N/A
5902301	12/1998	Olig	N/A	N/A

6007552	12/1998	Fogarty	606/157	A61B 17/122
6050996	12/1999	Schmaltz et al.	N/A	N/A
6096037	12/1999	Mulier et al.	N/A	N/A
6099539	12/1999	Howell	606/151	A61B 17/122
6110171	12/1999	Rydell	N/A	N/A
6152924	12/1999	Parins	N/A	N/A
6174309	12/2000	Wrublewski et al.	N/A	N/A
6190386	12/2000	Rydell	N/A	N/A
6257105	12/2000	Lin	29/229	B25B 27/205
6293954	12/2000	Fogarty et al.	N/A	N/A
6786117	12/2003	Tseng	N/A	N/A
7229111	12/2006	Cohen et al.	N/A	N/A
7235073	12/2006	Levine et al.	N/A	N/A
7641248	12/2009	Cho	N/A	N/A
7931668	12/2010	Sloat	N/A	N/A
7938469	12/2010	Ait-mani	N/A	N/A
7938779	12/2010	Sakurai et al.	N/A	N/A
8048107	12/2010	Chen	N/A	N/A
8152212	12/2011	Sugiyama	N/A	N/A
9452011	12/2015	Batchelor et al.	N/A	N/A
9855091	12/2017	Wang et al.	N/A	N/A
10702331	12/2019	Wang et al.	N/A	N/A
11266407	12/2021	Bagley	N/A	A61B 17/1285
2002/0023524	12/2001	Lowe	81/427.5	B25F 1/003
2003/0181904	12/2002	Levine et al.	N/A	N/A
2004/0158241	12/2003	Battles et al.	N/A	N/A
2005/0021025	12/2004	Buyse et al.	N/A	N/A
2005/0119650	12/2004	Sanders et al.	N/A	N/A
2006/0047278	12/2005	Christian et al.	N/A	N/A
2006/0271042	12/2005	Latterell et al.	N/A	N/A
2007/0244480	12/2006	Suzuki	N/A	N/A
2008/0065021	12/2007	Jenkins et al.	N/A	N/A
2010/0035564	12/2009	Lee	N/A	N/A
2010/0057084	12/2009	Hanna	606/51	A61B 18/1445
2010/0145335	12/2009	Johnson et al.	N/A	N/A
2010/0198248	12/2009	Vakharia	N/A	N/A
2011/0071519	12/2010	Rothstein et al.	N/A	N/A
2011/0087219	12/2010	Batross et al.	N/A	N/A
2012/0059375	12/2011	Couture et al.	N/A	N/A
2012/0296172	12/2011	Raven, III	600/231	A61B 17/0206
2013/0116682	12/2012	Koo et al.	N/A	N/A
2013/0197516	12/2012	Kappel	606/46	A61B 17/29
2013/0226200	12/2012	Kappel	606/142	A61B 17/128
2013/0253489	12/2012	Nau, Jr. et al.	N/A	N/A
2013/0274740	12/2012	Dickson et al.	N/A	N/A
2014/0094801	12/2013	Boudreaux et al.	N/A	N/A
2015/0282871	12/2014	Wang et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
101277654	12/2007	CN	N/A
203042442	12/2012	CN	N/A
106535801	12/2016	CN	N/A
106535801	12/2019	CN	N/A
0904738	12/1998	EP	N/A
1336384	12/2002	EP	N/A
3110358	12/2016	EP	N/A
3110358	12/2022	EP	N/A
S5167783	12/1975	JP	N/A
05029444	12/1992	JP	N/A
2004237105	12/2003	JP	N/A
2009056291	12/2008	JP	N/A
2010005464	12/2009	JP	N/A
2012516716	12/2011	JP	N/A
2017513574	12/2016	JP	N/A
6333406	12/2017	JP	N/A
2018138192	12/2017	JP	N/A
6589007	12/2018	JP	N/A
2020006213	12/2019	JP	N/A
WO-2005020834	12/2004	WO	N/A
WO-2015152979	12/2015	WO	N/A

OTHER PUBLICATIONS

U.S. Appl. No. 14/595,484 U.S. Pat. No. 9,855,091, filed Jan. 13, 2015, Surgical Device Having Changeable Elements. cited by applicant

U.S. Appl. No. 15/817,707 U.S. Pat. No. 10,702,331, filed Nov. 20, 2017, Surgical Device Having Changeable Elements. cited by applicant

“Japanese Application Serial No. 2019-166831, Notification of Reasons for Refusal mailed Aug. 21, 2020”, w/ English translation, 6 pgs. cited by applicant

“Japanese Application Serial No. 2019-166831, Response filed Jan. 21, 2021 to Notification of Reasons for Refusal mailed Aug. 21, 2020”, with English claims, 7 pgs. cited by applicant

“U.S. Appl. No. 14/595,484, Corrected Notice of Allowability mailed Nov. 21, 2017”, 2 pgs. cited by applicant

“U.S. Appl. No. 14/595,484, Non Final Office Action mailed Jul. 6, 2017”, 12 pgs. cited by applicant

“U.S. Appl. No. 14/595,484, Notice of Allowance mailed Oct. 12, 2017”, 8 pgs. cited by applicant

“U.S. Appl. No. 14/595,484, Response filed Sep. 22, 2017 to Non Final Office Action mailed Jul. 6, 2017”, 15 pgs. cited by applicant

“U.S. Appl. No. 15/817,707, Advisory Action mailed Jan. 31, 2020”, 4 pgs. cited by applicant

“U.S. Appl. No. 15/817,707, Corrected Notice of Allowability mailed Apr. 20, 2020”, 2 pgs. cited by applicant

“U.S. Appl. No. 15/817,707, Final Office Action mailed Oct. 21, 2019”, 11 pgs. cited by applicant

“U.S. Appl. No. 15/817,707, Non Final Office Action mailed Jun. 26, 2019”, 11 pgs. cited by applicant

“U.S. Appl. No. 15/817,707, Notice of Allowance mailed Mar. 2, 2020”, 10 pgs. cited by applicant

“U.S. Appl. No. 15/817,707, Response filed Jan. 21, 2020 to Final Office Action mailed Oct. 21, 2019”, 10 pgs. cited by applicant
“U.S. Appl. No. 15/817,707, Response filed Feb. 12, 2020 to Advisory Action mailed Jan. 31, 2020”, 10 pgs. cited by applicant
“U.S. Appl. No. 15/817,707, Response filed Jun. 6, 2019 to Restriction Requirement mailed Apr. 23, 2019”, 5 pgs. cited by applicant
“U.S. Appl. No. 15/817,707, Response filed Sep. 25, 2019 to Non Final Office Action mailed Jun. 26, 2019”, 9 pgs. cited by applicant
“U.S. Appl. No. 15/817,707, Restriction Requirement mailed Apr. 23, 2019”, 6 pgs. cited by applicant
“Chinese Application Serial No. 201680018044.X, Office Action mailed Mar. 15, 2019”, W/English Translation, 13 pgs. cited by applicant
“Chinese Application Serial No. 201580018044.X, Office Action mailed Jul. 19, 2018”, W/English Translation, 14 pgs. cited by applicant
“Chinese Application Serial No. 201580018044.X, Request for Reexamination filed Feb. 13, 2020”, w/ English Claims, 18 pgs. cited by applicant
“International Application Serial No. PCT/US2015/011120, International Preliminary Report on Patentability mailed Oct. 13, 2016”, 9 pgs. cited by applicant
“International Application Serial No. PCT/US2016/011120, International Search Report mailed Apr. 2, 2015”, 4 pgs. cited by applicant
“International Application Serial No. PCT/US2015/011120, Written Opinion mailed Apr. 2, 2015”, 7 pgs. cited by applicant
“Japanese Application Serial No. 2016-560413, Notice of Reasons for Refusal mailed Sep. 19, 2017”, with English translation of claims, 8 pgs. cited by applicant
“Japanese Application Serial No. 2016-560413, Response filed Jan. 22, 2018 to Notice of Reasons for Refusal mailed Sep. 19, 2017”, 11 pgs. cited by applicant
“Japanese Application Serial No. 2018-082839, Notice of Reasons for Refusal mailed Mar. 1, 2019”, 14 pgs. cited by applicant
“Japanese Application Serial No. 2018-082839, Response filed Jun. 4, 2019 to Notice of Reasons for Refusal mailed Mar. 1, 2019”, with English translation of claims, 13 pgs. cited by applicant
“European Application Serial No. 15703347.3, Response Filed Nov. 30, 2021 to Communication Pursuant to Article 94(3) EPC mailed May 25, 2021”, 39 pgs. cited by applicant
“European Application Serial No. 15703347.3, Communication Pursuant to Article 94(3) EPC mailed May 25, 2021”, 4 pgs. cited by applicant

Primary Examiner: Holwerda; Kathleen S

Assistant Examiner: Miller; Serenity A

Attorney, Agent or Firm: Schwegman Lundberg & Woessner, P.A.

Background/Summary

RELATED APPLICATION (1) This application is a divisional of U.S. patent application Ser. No. 15/817,707, filed on Nov. 20, 2017, which is a divisional of U.S. application Ser. No. 14/595,484, filed on Jan. 13, 2015 and issued on Jan. 2, 2018 as U.S. Pat. No. 9,855,091, which claims the benefit of U.S. Provisional Patent Application No. 61/974,407, filed on Apr. 2, 2014. (2) The entire contents of the above applications are incorporated herein by reference in their entireties.

FIELD

(1) The present disclosure relates to surgical devices, and more particular, surgical devices having opposed members that may be used for gripping or applying a current.

BACKGROUND

(2) The statements in this section merely provide background information related to the present disclosure and may or may not constitute prior art.

(3) Surgical forceps or tweezers are used in various applications during medical therapy procedures. Such devices are commonly used for holding or gripping objects.

(4) Recently, medical practitioners have also used bipolar forceps and tweezers during surgical procedures. Bipolar forceps and tweezers may be used to seal vessels by delivering pulsed bipolar energy to coagulate nearby tissue, which may replace or minimize the need for sutures and staples.

(5) Bipolar forceps and tweezers have a fixed size, and one device is used in a finite number of applications for which the device is properly sized. In addition, the devices have other fixed characteristics, which make them useful in only a limited number of applications. The same is true for regular, non-energized forceps and tweezers.

(6) Accordingly, there is a need for more universally useful surgical devices, such as tweezers and forceps.

SUMMARY

(7) The present disclosure provides a surgical device that has at least one end which may be changeable to fit the needs of various different or same procedures.

(8) Accordingly, pursuant to one aspect of the invention, an electrosurgical device kit includes an elongate first member, an elongate second member disposed adjacent to the first member, the second member being at least movably coupled to the first member, a first electrode head removably attachable to the first member, a second electrode head removably attachable to the first member, and a third electrode head coupled to the second member. The first, second, and third electrode heads are configured to apply a current to a tissue, the first and second electrode heads being non-identical.

(9) Accordingly, pursuant to another aspect of the invention, a device includes an elongate first member, an elongate second member disposed adjacent to the first member, the second member being at least movably coupled to the first member, and a forceps end coupled to the first member, at least a portion of the forceps end being movable with respect to the first member into a forceps end first position and a forceps end second position, the forceps end having a first portion and a second portion, the first portion having first set of teeth and the second portion having a second set of teeth.

(10) The invention may be further characterized by one or any combination of the features described herein, such as: the first electrode is identical to the third electrode; the first electrode is sharper than the second electrode; the first electrode has a first coating disposed thereon and the second electrode has one of: no coating and a second coating disposed thereon, the first and second coatings being non-identical; the first electrode has a first electrode thermal capability and the second electrode has a second electrode thermal capability, the first electrode thermal capability being different than the second electrode thermal capability; the first electrode has a first electrode electrical capability and the second electrode has a second electrode electrical capability, the first electrode electrical capability being different than the second electrode electrical capability; the first electrode is formed of a first material and the second electrode is formed of a second material, the first and second materials being non-identical; the first electrode is formed of a conductive material and the second electrode is formed of an insulating material; the device or kit also includes a fourth electrode head removably attachable to the second member, the third electrode head being removably coupled to the second member, the fourth electrode head being configured to apply a current to a tissue, the third and fourth electrode heads being non-identical.

(11) Further aspects, advantages and areas of applicability will become apparent from the description provided herein. It should be understood that the description and specific examples are intended for purposes of illustration only and are not intended to limit the scope of the present disclosure.

Description

DRAWINGS

- (1) The drawings described herein are for illustration purposes only and are not intended to limit the scope of the present disclosure in any way.
- (2) FIG. 1A is a side perspective view of a surgical device having device ends in first positions, in accordance with the principles of the present disclosure;
- (3) FIG. 1B is a side perspective view of the surgical device of FIG. 1A with the device ends in second positions, according to the principles of the present disclosure;
- (4) FIG. 2A is a side schematic view of a portion of another surgical device having device ends in first positions, in accordance with the principles of the present disclosure;
- (5) FIG. 2B is a side schematic view of the portion of the surgical device of FIG. 2A with the device ends in second positions, according to the principles of the present disclosure;
- (6) FIG. 3A is a side schematic view of a portion of yet another surgical device having device ends in first positions, in accordance with the principles of the present disclosure;
- (7) FIG. 3B is a side schematic view of the portion of the surgical device of FIG. 3A with the device ends in second positions, according to the principles of the present disclosure;
- (8) FIG. 3C is a side schematic view of a portion of still another surgical device having device ends in first positions, in accordance with the principles of the present disclosure;
- (9) FIG. 3D is a side schematic view of the portion of the surgical device of FIG. 3C with the device ends in second positions, according to the principles of the present disclosure;
- (10) FIG. 3E is a plan view of the portion of the surgical device of FIGS. 3C-3D taken along the lines 3E-3E in FIG. 3D, according to the principles of the present disclosure;
- (11) FIG. 4A is a side schematic view of a portion of still another surgical device having a device end in a first position, in accordance with the principles of the present disclosure;
- (12) FIG. 4B is a side schematic view of the portion of the surgical device of FIG. 4A with the device end in a second position, according to the principles of the present disclosure;
- (13) FIG. 4C is a perspective view of a portion of the surgical device of FIGS. 4A-4B, with two device ends in the second position, according to the principles of the present disclosure;
- (14) FIG. 5A is a side schematic view of a portion of still another surgical device having a device end in a first position, in accordance with the principles of the present disclosure;
- (15) FIG. 5B is a side schematic view of the portion of the surgical device of FIG. 5A with the device end in a second position, according to the principles of the present disclosure;
- (16) FIG. 6A is a side schematic view of a portion of still another surgical device having device ends in first positions, in accordance with the principles of the present disclosure;
- (17) FIG. 6B is a side schematic view of the portion of the surgical device of FIG. 6A with the device ends in second positions, according to the principles of the present disclosure;
- (18) FIG. 7A is a perspective view of a portion of still another surgical device having device ends in first positions, in accordance with the principles of the present disclosure;
- (19) FIG. 7B is a side schematic view of the portion of the surgical device of FIG. 7A with the device ends in second positions, according to the principles of the present disclosure;
- (20) FIG. 8 is a side perspective view of a surgical device kit having interchangeable device ends, in accordance with the principles of the present disclosure;
- (21) FIG. 9A is a side schematic view of another set of interchangeable device ends for the surgical

device kit of FIG. 8, according to the principles of the present disclosure; and (22) FIG. 9B is a side schematic view of yet another set of interchangeable device ends for the surgical device kit of FIG. 8, in accordance with the principles of the present disclosure.

DETAILED DESCRIPTION

(23) The following description is merely exemplary in nature and is not intended to limit the present disclosure, application, or uses.

(24) The present disclosure provides a surgical device that has at least one end which may be changeable to fit the needs of various different or same procedures.

(25) For example, referring to FIG. 1, a surgical forceps is illustrated and generally designated at 20. The surgical forceps 20 may be of the electrosurgical type or the non-energized type, by way of example. For example, if of the non-energized type, the forceps 20 are used for gripping and no energy is applied through the forceps 20. However, if the forceps 20 are of the electrosurgical type, they may be used as a bipolar device, for example, to apply pulsed or non-pulsed energy to coagulate a tissue.

(26) For the forceps 20 of the electrosurgical type, the forceps 20 include a proximal end 22 that may be connected to an energy source via first and second leads 24, 26. The forceps 20 may include a first elongate member 28 and a second elongate member 30, which are connected together at the proximal end 22 of the forceps device 20. The first member 28 is disposed adjacent to the second member 30. In this example, a band 32 surrounds proximal ends 34, 36 of the first and second members 28, 30 to couple the proximal ends 34, 36 together. Thus, the proximal ends 34, 36 may be fixed together by the band 32 as shown. In this example, the first and second members 28, 30 are movably coupled together. The first and second members 28, 30 may be moved toward each other by exerting pressure on their outer sides 38, 40; for example, an operator can pinch the first and second members 28, 30 together and toward each other by gripping and exerting pressure on gripping sections 42 disposed on the outer sides 38, 40. (Though not shown, it should be understood that an identical gripping section 42 is disposed on the outer side 40, as shown on the outer side 38.)

(27) The band 32 and the first and second members 28, 30 may be formed of an insulating material, such as a plastic or rubber. In other configurations, the first and second members 28, 30 may each have an inner portion formed of a conductive material, such as a metal, and an outer casing formed of an insulating material, where the outer casing surrounds the inner portion. In still other configurations, such as with non-electrosurgical devices, the first and second members 28, 30 may be formed entirely of a conductive material, such as a metal. This paragraph provides merely examples of materials that may be used for the first and second members 28, 30; other variations not described in this paragraph are also contemplated.

(28) A first end piece 44 is coupled to the distal end 48 of the first member 28, and a second end piece 46 may be coupled to the distal end 50 of the second member 30. In the alternative, the second member 30 may not have a separate end piece 46, but instead, the second member 30 may simply have a non-movable end that may be unitarily formed with the rest of the second member 30. The end pieces 44, 46 may be identical to each other, or the end pieces 44, 46 may be different from each other. The end pieces 44, 46 may take on various configurations, which will be described below.

(29) In the illustrated example of FIGS. 1A-1B, each end piece 44, 46 has a semi-rectangular shape with rounded edges. Each end piece 44, 46 has a joint, such as a pivot pin 52, connecting the end piece 44, 46 to the distal end 48, 50 of the respective member 28, 30.

(30) In FIG. 1A, the first and second end pieces 44, 46 are illustrated in first positions on the first and second members 28, 30, wherein long sides 54, 56 of the end pieces 44, 46 are disposed at the distal end 58 of the device 20. A short side 60 of the first end piece 44 is disposed on an opposite side of the pivot pin 52 from the long side 54. In the first position of the first end piece 44, the short side 60 of the first end piece 44 is disposed closer to the proximal end 22 of the device 20 than the

long side **54** is disposed with respect to the proximal end **22**. The second end piece **46** may also have a short side **62** that is disposed closer to the proximal end **22** than the long side **56** is disposed with respect to the proximal end **22**, in the first position of the second end piece **46**.

(31) In FIG. **1B**, the first and second end pieces **44**, **46** are illustrated in second positions on the first and second members **28**, **30**, wherein the short sides **60**, **62** of the end pieces **44**, **46** are disposed at the distal end **58** of the device **20**. In the second position of the first member **28**, the long side **54** of the first end piece **44** is disposed closer to the proximal end **22** of the device **20** than the short side **60** is disposed with respect to the proximal end **22**. The long side **56** of the second end piece **46** is disposed closer to the proximal end **22** than the short side **62** is disposed with respect to the proximal end **22**, in the second position of the second member **30**. Accordingly, each of the end pieces **44**, **46** has a long side **54**, **56** and a short side **60**, **62**, wherein the long and short sides **56**, **60** of the first end piece **44** are not identical to each other, and the long and short sides **56**, **62** of the second end piece **46** are not identical to each other, since they have different lengths.

(32) The end pieces **44**, **46** are movable with respect to the first and second members **28**, **30**. In the illustrated example, the end pieces **44**, **46** are rotatable about the pivot pins **52**. In the alternative, another type of joint or connection may be provided. Thus, each end piece **44**, **46** may be rotated into their first positions (shown in FIG. **1A**) and into their second positions (shown in FIG. **1B**). In the example of FIGS. **1A-1B**, the first and second end pieces **44**, **46** are movable between their first and second positions without being detached from the first and second members **28**, **30**, respectively, because the end pieces **44**, **46** are pivoted around the pivot pins **52**, but not detached. Thus, the first end piece **44** is rotatably attached to the first member **28**, and the second end piece **46** is rotatably attached to the second member **30**. An operator may desire to rotate the end pieces **44**, **46** between the first and second positions depending on whether the operator would like to use the long sides **54**, **56** or the short sides **60**, **62** at the distal end of the device **58**. In some examples, each end piece **44**, **46** and/or the distal ends **48**, **50** of each of the members **28**, **30** may have a detent or other feature to aid in positioning the end pieces **44**, **46** into the first and second positions.

(33) In some variations, one or more of the end pieces **44**, **46** is an electrode. For example, both of the first and second end pieces **44**, **46** may be electrodes that are configured to apply a current to a tissue when energized. The first and second end pieces **44**, **46** may be active bipolar electrodes that are configured to be coupled with and energized by an electrode energy source. In the illustrated example, the current may be provided through the lead ends **24**, **26** and through the pivot pins **52** to each of the end pieces **44**, **46**.

(34) Referring now to FIGS. **2A-2B**, another example of a portion of a surgical forceps is illustrated and generally designated at **120**. The proximal end of the forceps **120** is not shown, however, all details may be the same as shown in FIG. **1A-1B**, or the proximal end may take on any other acceptable configuration as known or desired in the art. As in the example of FIGS. **1A-1B**, the forceps **120** may be of the electrosurgical type or the non-energized type, by way of example. For example, if of the non-energized type, the forceps **120** are used for gripping and no energy is applied through the forceps **120**. However, if the forceps **120** are of the electrosurgical type, they may be used as a bipolar device, for example, to apply pulsed or non-pulsed energy to coagulate a tissue.

(35) The forceps **120** may include a first elongate member **128** and a second elongate member **130**, which are connected together at the proximal end (not shown, but may be same or similar as shown in FIGS. **1A-1B**). The first member **128** is disposed adjacent to the second member **130**. As described above with respect to FIGS. **1A-1B**, the first and second members **128**, **130** may be moved toward each other by exerting pressure on their outer sides; for example, an operator can pinch the first and second members **128**, **130** together and toward each other and bring the end pieces **144**, **146** together.

(36) As described above, the first and second members **128**, **130** may be formed of an insulating material, such as a plastic or rubber. In other configurations, the first and second members **128**, **130**

may each have an inner portion formed of a conductive material, such as a metal, and an outer casing formed of an insulating material, where the outer casing surrounds the inner portion. In still other configurations, such as non electrosurgical devices, the first and second members **128**, **130** may be formed entirely of a conductive material, such as a metal.

(37) The first end piece **144** is coupled to the distal end **148** of the first member **128**, and the second end piece **146** may be coupled to the distal end **150** of the second member **130**. In the alternative, the second member may not have a separate end piece **146**. The end pieces **144**, **146** may be identical to each other, or the end pieces **144**, **146** may be different from each other.

(38) In the illustrated example of FIGS. 2A-2B, each end piece **144**, **146** has a semi-rectangular shape with rounded edges. Each end piece **144**, **146** has a joint, such as a pivot pin **152**, connecting the end piece **144**, **146** to the distal end **148**, **150** of the respective member **128**, **130**.

(39) In FIG. 2A, the first and second end pieces **144**, **146** are illustrated in first positions on the first and second members **128**, **130**, wherein a first side **154**, **156** of each of the end pieces **144**, **146** is disposed at the distal end **158** of the device **120**. A second side **160** of the first end piece **144** is disposed on an opposite side of the pivot pin **152** from the first side **154**. In the first position of the first end piece **144**, the second side **160** of the first end piece **144** is disposed closer to the proximal end (not shown) of the device **120** than the first side **154** is disposed with respect to the proximal end. The second end piece **146** may also have a second side **162** that is disposed closer to the proximal end than the first side **156** is disposed with respect to the proximal end, in the first position of the second end piece **146**.

(40) In FIG. 2, the first and second end pieces **144**, **146** are illustrated in second positions on the first and second members **128**, **130**, wherein the second sides **160**, **162** of the end pieces **144**, **146** are disposed at the distal end **158** of the device **120**. In the second position of the first end piece **144**, the first side **154** of the first end piece **144** is disposed closer to the proximal end (not shown) of the device **120** than the second side **160** is disposed with respect to the proximal end. The first side **156** of the second end piece **146** is disposed closer to the proximal end than the second side **162** is disposed with respect to the proximal end, in the second position of the second end piece **146**.

(41) The first and second sides **154**, **160** of the first end piece **144** are identical to each other, each being disposed on opposite sides of the pivot pin **152**. Likewise, the first and second sides **156**, **162** of the second end piece **146** are identical to each other, each being disposed on opposite sides of the pivot pin **152**.

(42) The end pieces **144**, **146** are movable with respect to the first and second members **128**, **130**. In the illustrated example, the end pieces **144**, **146** are rotatable about the pivot pins **152**. Thus, each end piece **144**, **146** may be rotated into their first positions (shown in FIG. 2A) and into their second positions (shown in FIG. 2B). In the example of FIGS. 2A-2B, the first and second end pieces **144**, **146** are movable between their first and second positions without being detached from the first and second members **128**, **130**, respectively, because the end pieces **144**, **146** are pivoted around the pivot pins **152**. Thus, the first end piece **144** is rotatably attached to the first member **128**, and the second end piece **146** is rotatably attached to the second member **130**. An operator may desire to rotate the end pieces **144**, **146** between the first and second positions if one of the sides **154**, **156**, **160**, **162** has become dirty or damaged. Thus, the operator could continue to use the forceps device **120** even if one side **154**, **156**, **160**, **162** of an end piece **144**, **146** becomes undesirable for use.

(43) As in the example of FIGS. 1A-1B, one or more of the end pieces **144**, **146** could be provided as an electrode. For example, both of the first and second end pieces **144**, **146** may serve as electrodes that are configured to apply a current to a tissue when energized. The first and second end pieces **144**, **146** may be active bipolar electrodes that are configured to be coupled with and energized by an electrode energy source. In the illustrated example, the current may be provided through lead ends (such as lead ends **24**, **26** shown in FIGS. 1A-1B) and through the pivot pins **152**

to each of the end pieces **144**, **146**.

(44) Referring now to FIGS. **3A-3B**, another example of a portion of a surgical forceps is illustrated and generally designated at **220**. The proximal end of the forceps **220** is not shown, however, all details may be the same as shown in FIG. **1A-1B**, or the proximal end may take on any other acceptable configuration as known in the art. As in the examples of FIGS. **1A-1B** and **2A-2B**, the forceps **220** may be of the electrosurgical type or the non-energized type, by way of example. For example, if of the non-energized type, the forceps **220** are used for gripping and no energy is applied through the forceps **220**. However, if the forceps **220** are of the electrosurgical type, they may be used as a bipolar device, for example, to apply pulsed or non-pulsed energy to coagulate a tissue.

(45) The forceps **220** may include a first elongate member **228** and a second elongate member **230**, which are connected together at a proximal end (not shown). The first member **228** is disposed adjacent to the second member **230**. As described above with respect to FIGS. **1A-1B**, the first and second members **228**, **230** may be moved toward each other by exerting pressure on their outer sides; for example, an operator can pinch the first and second members **228**, **230** together and toward each other and bring the end pieces **244**, **246** together.

(46) As described above, the first and second members **228**, **230** may be formed of an insulating material, such as a plastic or rubber. In other configurations, the first and second members **228**, **230** may each have an inner portion formed of a conductive material, such as a metal, and an outer casing formed of an insulating material, where the outer casing surrounds the inner portion. In still other configurations, such as non electrosurgical devices, the first and second members **228**, **230** may be formed entirely of a conductive material, such as a metal, by way of example.

(47) The first end piece **244** is coupled to the distal end **248** of the first member **228**, and the second end piece **246** may be coupled to the distal end **250** of the second member **230**. In the alternative, the second member **230** may not have a separate end piece **246**, as described above. The end pieces **244**, **246** may be identical to each other, or the end pieces **244**, **246** may be different from each other.

(48) In the illustrated example of FIGS. **3A-3B**, each end piece **244**, **246** has a first set of teeth **264**, **266** disposed on a first side **268**, **270** and a second set of teeth **272**, **274** disposed on a second side **276**, **278**. The first sides **268**, **270** are disposed on opposite elongate faces of the end pieces **244**, **246** from the second sides **276**, **278**. Each end piece **244**, **246** has a joint, such as a pivot pin **252**, connecting the end piece **244**, **246** to the distal end **248**, **250** of the respective member **228**, **230**.

(49) In FIG. **3A**, the first and second end pieces **244**, **246** are illustrated in first positions on the first and second members **228**, **230**, wherein the first sets of teeth **264**, **266** of each of the end pieces **244**, **246** are disposed facing each other and facing toward a central axis C of the device **220**, the central axis C being disposed between inner sides **280**, **282** of each of the first and second members **228**, **230**. In the first positions, the second sets of teeth **272**, **274** are facing outwardly and away from the central axis C. In other examples, one of the members **228**, **230** or end pieces **244**, **246** may be plain without a set of teeth, so that the teeth only appear on the end **248**, **250** of one of the members **228**, **230**.

(50) In FIG. **3B**, the first and second end pieces **244**, **246** are illustrated in second positions on the first and second members **228**, **230**, wherein the second sets of teeth **272**, **274** of each of the end pieces **244**, **246** are disposed facing each other and facing toward a central axis C of the device **220**. In the second positions, the first sets of teeth **264**, **266** are facing outwardly and away from the central axis C.

(51) In some variations, the first and second sets of teeth **264**, **272**, of the first end piece **244** may be identical to each other, each being disposed on opposite sides of the pivot pin **252**. Likewise, the first and second sets of teeth **266**, **274** of the second end piece **246** may be identical to each other, each being disposed on opposite sides of the pivot pin **252**. However, as illustrated in FIGS. **3A-3B**, the first sets of teeth **264**, **266** in this example have a larger number and smaller teeth than the

second sets of teeth **272, 274**. The second sets of teeth **272, 274** have a smaller number and are larger than the first sets of teeth **264, 266**.

(52) The end pieces **244, 246** are movable with respect to the first and second members **228, 230**. In the illustrated example, the end pieces **244, 246** are rotatable about the pivot pins **252**. Thus, each end piece **244, 246** may be rotated into their first positions (shown in FIG. 3A) and into their second positions (shown in FIG. 3B). In the example of FIGS. 3A-3B, the first and second end pieces **244, 246** are movable between their first and second positions without being detached from the first and second members **228, 230**, respectively, because the end pieces **244, 246** are pivoted around the pivot pins **252**. Thus, the first end piece **244** is rotatably attached to the first member **228**, and the second end piece **246** is rotatably attached to the second member **230**.

(53) An operator may desire to rotate the end pieces **244, 246** between the first and second positions if one of the sets of teeth **264, 266, 272, 274** has become dirty or damaged. Furthermore, the operator may desire to rotate the end pieces **244, 246** to use either the smaller or larger sets of teeth **264, 266, 272, 274**, depending on the application, without having to use a different set of forceps.

(54) As in the examples of FIGS. 1A-2B, one or more of the end pieces **244, 246** could be provided as an electrode. For example, both of the first and second end pieces **244, 246** may serve as electrodes that are configured to apply a current to a tissue when energized. The first and second end pieces **244, 246** may be active bipolar electrodes that are configured to be coupled with and energized by an electrode energy source. In the illustrated example, the current may be provided through lead ends (such as lead ends **24, 26** shown in FIGS. 1A-1B) and through the pivot pins **252** to each of the end pieces **244, 246**.

(55) Referring now to FIGS. 3C-3E, another example of a portion of a surgical forceps is illustrated and generally designated at **1220**. The proximal end of the forceps **1220** is not shown, however, all details may be the same as shown in FIG. 1A-1B, or the proximal end may take on any other acceptable configuration as known in the art. The forceps **1220** may be essentially the same as the forceps **220** described above with respect to FIGS. 3A-3B, except for the orientation of the teeth **1264, 1266, 1272, 1274**, which will be described below. For example, the forceps **1220** may include a first elongate member **1228**, a second elongate member **1230**, and pins **1252** holding the rotatable device ends **1244, 1246** to the distal ends **1248, 1250** of the first and second members **1228, 1230**. In addition, the device ends **1244, 1246** may or may not be provided as energizable electrodes.

(56) In the illustrated example of FIGS. 3C-3E, each end piece **1244, 1246** has a first set of teeth **1264, 1266** disposed on a first end **1269, 1271** and a second set of teeth **1272, 1274** disposed on a second end **1277, 1279** of the device ends **1244, 1246**. Each of the sets of teeth **1264, 1266, 1272, 1274** is disposed on a first face **1268, 1270** of each device end **1244, 1246**. Second faces **1276, 1278** of the end pieces **1244, 1246** are disposed on opposite sides of the end pieces **1244, 1246** from the first faces **1268, 1270**. The second faces **1276, 1278** are flat and have no teeth, in this example.

(57) In FIG. 3C, the first and second end pieces **1244, 1246** are illustrated in first positions on the first and second members **1228, 1230**, wherein the first sets of teeth **1264, 1266** are disposed facing each other and facing toward a central axis C of the device **1220**, the central axis C being disposed between inner sides **1280, 1282** of each of the first and second members **1228, 1230**. In the first positions, the first sets of teeth **1264, 1266** and the first ends **1269, 1271** of the device ends **1244, 1246** are disposed at the distal end **1258** of the forceps **1220**. The second sets of teeth **1272, 1274** are not facing directly toward to the central axis C, as the second sets of teeth **1272, 1274** are oriented on angle in the first positions. More particularly, the distal ends **1248, 1250** of the first and second members **1228, 1230** are angled inward toward the central axis C. As such, in the first positions, the first sets of teeth **1264, 1266** are aligned along parallel planes and are configured to compress tissue therebetween when the first and second members **1228, 1230** are pressed toward

each other and toward the central axis C. The second sets of teeth **1272**, **1274** are disposed along non-parallel planes in the first positions, and the second sets of teeth **1272**, **1274** are configured to be spaced farther from each other than the first sets of teeth **1264**, **1266** are spaced with respect to each other. As such, the second sets of teeth **1272**, **1274** are configured to remain apart from each other and not grasp tissue in the first positions, even when the first and second members **1228**, **1230** are pressed toward each other.

(58) In FIGS. 3D-3E, the first and second end pieces **1244**, **1246** are illustrated in second positions on the first and second members **1228**, **1230**. The second sets of teeth **1272**, **1274** and the second ends **1277**, **1279** of the device ends **1244**, **1246** are disposed at the distal end **1258** of the forceps **1220**. In the second positions, the second sets of teeth **1272**, **1274** are directly facing each other and facing toward the central axis C of the device **1220**. In the second positions, the second sets of teeth **1272**, **1274** are aligned along parallel planes and are configured to compress tissue therebetween when the first and second members **1228**, **1230** are pressed toward each other. The first sets of teeth **1264**, **1266** are disposed along non-parallel planes in the second positions, and the first sets of teeth **1264**, **1266** are configured to be spaced farther from each other than the second sets of teeth **1272**, **1274** are spaced with respect to each other. As such, the first sets of teeth **1264**, **1266** are configured to remain apart from each other and not grasp tissue in the second positions, even when the first and second members **1228**, **1230** are pressed toward each other.

(59) In some variations, the first and second sets of teeth **1264**, **1272**, of the first end piece **1244** may be identical to each other, each being disposed on opposite sides of the pivot pin **1252**. Likewise, the first and second sets of teeth **1266**, **1274** of the second end piece **1246** may be identical to each other, each being disposed on opposite sides of the pivot pin **1252**. However, as illustrated in FIGS. 3C-3E, the first sets of teeth **1264**, **1266** in this example have a larger number and smaller teeth than the second sets of teeth **1272**, **1274**. The second sets of teeth **1272**, **1274** have a smaller number and are larger than the first sets of teeth **1264**, **1266**.

(60) The end pieces **1244**, **1246** are movable with respect to the first and second members **1228**, **1230**. In the illustrated example, the end pieces **1244**, **1246** are rotatable about the pivot pins **1252**. Thus, each end piece **1244**, **1246** may be rotated into their first positions (shown in FIG. 3C) and into their second positions (shown in FIGS. 3D-3E). In FIGS. 3A-3B, the end pieces **244**, **246** are pivotable along a first plane that is perpendicular to the central axis C, while in FIGS. 3C-3E, the end pieces **1244**, **1246** are pivotable along a second plane that is not perpendicular to the central axis C. Because the distal ends **1248**, **1250** of the first and second members **1228**, **1230** are angled with respect to the central axis C, the second plane is not parallel to the central axis C, but the second plane is disposed at an acute angle with respect to the central axis C.

(61) An operator may desire to rotate the end pieces **1244**, **1246** between the first and second positions if one of the sets of teeth **1264**, **1266**, **1272**, **1274** has become dirty or damaged. Furthermore, the operator may desire to rotate the end pieces **1244**, **1246** to use either the smaller or larger sets of teeth **1264**, **1266**, **1272**, **1274**, depending on the application, without having to use a different set of forceps.

(62) Referring now to FIGS. 4A-4C, another example of a portion of a surgical forceps is illustrated and generally designated at **320**. The proximal end of the forceps **320** is not shown, however, all details may be the same as shown in FIG. 1A-1B, or the proximal end may take on any other acceptable configuration as known in the art. As in the examples of FIGS. 1A-3B, the forceps **320** may be of the electrosurgical type or the non-energized type, by way of example. For example, if of the non-energized type, the forceps **320** are used for gripping and no energy is applied through the forceps **320**. However, if the forceps **320** are of the electrosurgical type, they may be used as a bipolar device, for example, to apply pulsed or non-pulsed energy to coagulate a tissue.

(63) The forceps **320** may include a first elongate member **328** and a second elongate member **330** (shown in FIG. 4C). The second elongate member **330** may be understood to be either identical to

the first elongate member **328**, or the second elongate member **330** may be plain without a pivotable end piece **346**; however, preferably, the second elongate member **330** has a pivotable end piece **346**. The first member **328** and the second member **330** may be connected together at the proximal end (not shown). The first member **328** is disposed adjacent to the second member **330**. As described above with respect to FIGS. **1A-1B**, the first member **328** and the second member **330** may be moved toward each other by exerting pressure on their outer sides; for example, an operator can pinch the first member **328** and the second member **330** together and toward each other and bring the first end piece **344** and the end of the second member **330** together (whether the second member **330** has an end piece **346** or no end piece).

(64) As described above, the first member **328** and the second member **330** may be formed of an insulating material, such as a plastic or rubber. In other configurations, the first member **328** and the second member **330** may each have an inner portion formed of a conductive material, such as a metal, and an outer casing formed of an insulating material, where the outer casing surrounds the inner portion. In still other configurations, such as non-electrosurgical devices, the first member **328** and the second member **330** may be formed entirely of a conductive material, such as a metal.

(65) The first end piece **344** is coupled to the distal end **348** of the first member **328**. The second member **330** may also have an end piece **346** identical or different from the first end piece **344**, which may be coupled to the distal end **350** of the second member **330**.

(66) Each end piece **344**, **346** has a joint, such as a pivot pin **352**, connecting the end piece **344**, **346** to the distal end **348**, **350** of the respective member **328**, **330**. The end pieces **344**, **346** may be rotated around the pivot pins **352** to move the end pieces **344**, **346** into various positions, such as first and second positions. FIGS. **4A-4B** illustrate first and second positions of the first end piece **344**, and it should be understood that the second end piece **346** may also be rotated into first and second positions, as is shown with respect to the first end piece **344**.

(67) In FIG. **4A**, the first end piece **344** is illustrated in a first position on the first member **328**, wherein the first end piece has a first part **354** that extends at an angle **A** with respect to a longitudinal axis **L** defined by the distal end **348** of the first member **328**. In the first position, a second part **360** of the first end piece **344** is disposed along the longitudinal axis **L**, in this example.

(68) In FIG. **3B**, the first end piece **344** is illustrated in a second position on the first member **328**, wherein the second part **360** of the first end piece **344** extends at an angle **B** with respect to the longitudinal axis **L**. In the second position, the first part **354** of the first end piece **344** is disposed along the longitudinal axis **L**.

(69) The angle **B** may be equal or different from the angle **A**, in either or both of magnitude and direction. For example, the angle **A** may be defined as extending in a positive direction from the axis **L**. Accordingly, it can be seen that the angle **A** is a positive acute angle in FIG. **4A**. As such, the angle **B** is shown as extending in the opposite direction from the longitudinal axis **L**, in a negative direction, as shown in FIG. **4B**. Thus, if the angles were instead both measured in a positive direction, then the second part **360** would extend at an angle **C** from the longitudinal axis **L**, and the angle **C** would clearly be an obtuse angle much larger than the angle **A**.

(70) FIG. **4C** shows both first and second pieces **344**, **346** in the second positions. Thus, the second part **360** of the first end piece **344** extends at the angle **B** or **C** from the longitudinal axis **L** in the second position as shown in FIG. **4C**, and the second part **362** of the second end piece **346** extends at an angle, such as **B** or **C**, from a longitudinal axis **L.sub.2** defined by the distal end **350** of the second member **330** in the second position as shown in FIG. **4C**. It should be noted that in the second positions of both the first and second end pieces **344**, **346**, both the second parts **360**, **362** extend at the same angle, such as **B**, from their respective longitudinal axes **L**, **L.sub.2**, in the illustrated example. As such, the second parts **360**, **362** are disposed alongside each other and can be used to grip a piece of tissue.

(71) The end pieces **344**, **346** are movable with respect to the first and second members **328**, **330**. In the illustrated example, the end pieces **344**, **346** are rotatable about the pivot pins **352**. Thus,

each end piece **344**, **346** may be rotated into their first positions (the first position of the first end piece **344** is shown in FIG. **4A**; the second end piece may have an identical first position) and into their second positions (shown in FIGS. **4B-4C**). In the example of FIGS. **4A-4C**, the first and second end pieces **344**, **346** are movable between their first and second positions without being detached from the first and second members **328**, **330**, respectively, because the end pieces **344**, **346** are pivoted around the pivot pins **352**. Thus, the first end piece **344** is rotatably attached to the first member **328**, and the second end piece **346** is rotatably attached to the second member **330**.

(72) An operator may desire to rotate the end pieces **344**, **346** between the first and second positions if one of the parts **354**, **360**, **356**, **362** has become dirty or damaged. Furthermore, the operator may desire to rotate the end pieces **344**, **346** so that the end pieces **344**, **346** have parts extending at a desired angle or in a desired direction from the axis **L**, depending on the application, without having to use a different set of forceps.

(73) As in the examples of FIGS. **1A-3B**, one or more of the end pieces **344**, **346** could be provided as an electrode. For example, both of the first and second end pieces **344**, **346** may serve as electrodes that are configured to apply a current to a tissue when energized. The first and second end pieces **344**, **346** may be active bipolar electrodes that are configured to be coupled with and energized by an electrode energy source. In the illustrated example, the current may be provided through lead ends (such as lead ends **24**, **26** shown in FIGS. **1A-1B**) and through the pivot pins **352** to each of the end pieces **344**, **346**.

(74) Referring now to FIGS. **5A-5B**, another example of a portion of a surgical forceps is illustrated and generally designated at **420**. The proximal end of the forceps **420** is not shown, however, all details may be the same as shown in FIG. **1A-1B**, or the proximal end may take on any other acceptable configuration as known in the art. As in the example of FIGS. **1A-1B**, the forceps **420** may be of the electrosurgical type or the non-energized type, by way of example. For example, if of the non-energized type, the forceps **420** are used for gripping and no energy is applied through the forceps **420**. However, if the forceps **420** are of the electrosurgical type, they may be used as a bipolar device, for example, to apply pulsed or non-pulsed energy to coagulate a tissue.

(75) The forceps **420** may include a first elongate member **428** and a second elongate member (not shown), which are connected together at the proximal end (not shown). Though the second member is not shown, it may be the same as or similar to the first member **428** and connected as shown in FIGS. **1A-1B**, by way of example. The first member **428** is disposed adjacent to the second member. As described above with respect to FIGS. **1A-1B**, the first member **428** and the second member may be moved toward each other by exerting pressure on their outer sides; for example, an operator can pinch the first member **428** and the second member together and toward each other and bring the first end piece **444** and the end of the second member together. The second member may have an identical end piece **444**, another end piece, or no end piece.

(76) As described above, the first member **428** and the second member may be formed of an insulating material, such as a plastic or rubber. In other configurations, the first member **428** and the second member may each have an inner portion formed of a conductive material, such as a metal, and an outer casing formed of an insulating material, where the outer casing surrounds the inner portion. In still other configurations, such as non-electrosurgical devices, the first member **428** and the second member may be formed entirely of a conductive material, such as a metal, by way of example.

(77) The first end piece **444** is coupled to the distal end **448** of the first member **428**. A similar end may be coupled to the second member. In the alternative, the second member may not have a separate end piece. The first end piece **444** and the second end piece may be identical to each other, or the first end piece **444** and the second end piece may be different from each other.

(78) In the illustrated example of FIGS. **5A-5B**, the end piece **444** has a first wide part **454** and a second part **460** that has a narrow projection **484**. In this example, the narrow projection **484** has a

width **w** that is half the width of the first part **454**. Thus, the width of the first part **454** is $2w$. In other examples, the narrow projection width **w** could be smaller than the width of the first part, but not as small as half the width of the first part. In still other examples, the width of the narrow projection **484** could be less than half as wide as the width of the first part **454**. The end piece **444** has a joint, such as a pivot pin **452**, connecting the end piece **444** to the distal end **448** of the first member **428**.

(79) In FIG. 5A, the end piece **444** is illustrated in a first position on the first members **428**, wherein the projection **484** of the end piece **444** is disposed at the distal end **458** of the device **420**. The first side **454** of the end piece **444** is disposed on an opposite side of the pivot pin **452** from the second side **460** and the projection **484**. In the first position of the end piece **444**, the first side **454** of the end piece **444** is disposed closer to the proximal end (not shown) of the device **420** than the second side **460** is disposed with respect to the proximal end. The second member and end piece (not shown), may also have a similar first position.

(80) In FIG. 5B, the end piece **444** is illustrated in a second position on the first member **428**, wherein the first side **454** of the end piece **444** is disposed at the distal end **458** of the device **420**. In the second position of the end piece **444**, the second side **460** of the end piece **444** is disposed closer to the proximal end (not shown) of the device **420** than the first side **454** is disposed with respect to the proximal end. The second member and end piece (not shown), may also have a similar second position.

(81) The end piece **444** is movable with respect to the first member **428**. In the illustrated example, the end piece **444** is rotatable about the pivot pin **452**. Thus, the end piece **444** may be rotated into the first position (shown in FIG. 5A) and into the second position (shown in FIG. 5B). In the example of FIGS. 5A-5B, the end piece **444** is movable between the first and second positions without being detached from the first member **428**, because the end piece **444** is pivoted around the pivot pin **452**. Thus, the end piece **444** is rotatably attached to the first member **428**. Likewise, an identical second end piece (not shown) may be rotatably attached to the second member (not shown).

(82) An operator may desire to rotate the end pieces **444** between the first and second positions if one of the sides **454**, **460** has become dirty or damaged. Thus, the operator could continue to use the forceps device **420** even if one side **454**, **460** has become undesirable for use. Furthermore, the first and second sides **454**, **460** of the end piece **444** are of different sizes, they have different widths (as described above), and they have different surface areas. The operator may desire to use the wider side **454** or the narrower side **460** for different applications, without having to use a different forceps.

(83) As in the example of FIGS. 1A-1B, the end piece **444** could be provided as an electrode. For example, both of the first and second end pieces **444** (second end piece not shown), may serve as electrodes that are configured to apply a current to a tissue when energized. The first and second end pieces **444** (second end piece not shown) may be active bipolar electrodes that are configured to be coupled with and energized by an electrode energy source. In the illustrated example, the current may be provided through lead ends (such as lead ends **24**, **26** shown in FIGS. 1A-1B) and through pivot pins **452** to each of the end pieces **444** (second end piece not shown).

(84) Referring now to FIGS. 6A-6B, another example of a portion of a surgical forceps is illustrated and generally designated at **520**. The proximal end of the forceps **520** is not shown, however, all details may be the same as shown in FIG. 1A-1B, or the proximal end may take on any other acceptable configuration as known in the art. As in the examples of FIGS. 1A-5B, the forceps **520** may be of the electrosurgical type or the non-energized type, by way of example. For example, if of the non-energized type, the forceps **520** are used for gripping and no energy is applied through the forceps **520**. However, if the forceps **520** are of the electrosurgical type, they may be used as a bipolar device, for example, to apply pulsed or non-pulsed energy to coagulate a tissue.

(85) The forceps **520** may include a first elongate member **528** and a second elongate member **530**, which are connected together at the proximal end (not shown). The first member **528** is disposed adjacent to the second member **530**. As described above with respect to FIGS. **1A-1B**, the first and second members **528**, **530** may be moved toward each other by exerting pressure on their outer sides; for example, an operator can pinch the first and second members **528**, **530** together and toward each other and bring the end pieces **544**, **546** together.

(86) As described above, the first and second members **528**, **530** may be formed of an insulating material, such as a plastic or rubber. In other configurations, the first and second members **528**, **530** may each have an inner portion formed of a conductive material, such as a metal, and an outer casing formed of an insulating material, where the outer casing surrounds the inner portion. In still other configurations, such as non-electrosurgical devices, the first and second members **528**, **530** may be formed entirely of a conductive material, such as a metal, by way of example.

(87) The first end piece **544** is coupled to the distal end **548** of the first member **528**, and the second end piece **546** may be coupled to the distal end **550** of the second member **530**. In the alternative, the second member **530** may not have a separate end piece **546**. The end pieces **544**, **546** may be identical to each other, as shown, or the end pieces **544**, **546** may be different from each other.

(88) In the illustrated example of FIGS. **6A-6B**, each end piece **544**, **546** has a sharp edge **586**, **588** disposed on a first part **554**, **556** and a dull edge **590**, **592** disposed on a second part **560**, **562**. Each end piece **544**, **546** has a joint, such as a pivot pin **552**, connecting the end piece **544**, **546** to the distal end **548**, **550** of the respective member **528**, **530**.

(89) In FIG. **6A**, the first and second end pieces **544**, **546** are illustrated in first positions on the first and second members **528**, **530**, wherein the first parts **454**, **456** of the end pieces **544**, **546** having the sharp edges **586**, **588** are disposed at the distal end **558** of the device **520**. The second part **560** of the first end piece **544** is disposed on an opposite side of the pivot pin **552** from the first part **554**. In the first position of the first end piece **544**, the second part **560** of the first end piece **544** is disposed closer to the proximal end (not shown) of the device **520** than the first part **554** is disposed with respect to the proximal end. Likewise, the second part **562** of the second end piece **546** is disposed on an opposite side of the pivot pin **552** from the first part **556**. In the first position of the second end piece **544**, the second part **562** of the second end piece **546** is disposed closer to the proximal end (not shown) of the device **520** than the first part **556** is disposed with respect to the proximal end.

(90) In FIG. **6B**, the first and second end pieces **544**, **546** are illustrated in second positions on the first and second members **528**, **530**, wherein the second parts **560**, **562** of the end pieces **544**, **546** having the dull sides **590**, **592** are disposed at the distal end **558** of the device **520**. In the second position of the first member **528**, the first part **554** of the first end piece **544** is disposed closer to the proximal end (not shown) of the device **520** than the second part **560** is disposed with respect to the proximal end. The first part **556** of the second end piece **546** is disposed closer to the proximal end than the second part **562** is disposed with respect to the proximal end, in the second position of the second member **530**.

(91) Accordingly, each of the end pieces **544**, **546** have a sharp edge **586**, **588** and a dull edge **590**, **592**, wherein the sharp and dull edges **586**, **590** of the first end piece **544** are not identical to each other, the sharp edge **586** being sharper than the dull edge **590**. Likewise, the sharp and dull edges **588**, **592** of the second end piece **546** are not identical to each other, the sharp edge **588** being sharper than the dull edge **592**.

(92) The end pieces **544**, **546** are movable with respect to the first and second members **528**, **530**. In the illustrated example, the end pieces **544**, **546** are rotatable about the pivot pins **552**. Thus, each end piece **544**, **546** may be rotated into their first positions (shown in FIG. **6A**) and into their second positions (shown in FIG. **6B**). In the example of FIGS. **6A-6B**, the first and second end pieces **544**, **546** are movable between their first and second positions without being detached from

the first and second members **528**, **530**, respectively, because the end pieces **544**, **546** are pivoted around the pivot pins **552**. Thus, the first end piece **544** is rotatably attached to the first member **528**, and the second end piece **546** is rotatably attached to the second member **530**.

(93) An operator may desire to rotate the end pieces **544**, **546** between the first and second positions if one of the parts **554**, **556**, **560**, **562** has become dirty or damaged. Furthermore, the operator may desire to rotate the end pieces **544**, **546** to use either the sharp edges **586**, **588** or the parts **560**, **562** having dull edges **590**, **592** on a particular application, without having to use a different set of forceps for different tasks.

(94) As in the examples of FIGS. **1A-5B**, one or more of the end pieces **544**, **546** could be provided as an electrode. For example, both of the first and second end pieces **544**, **546** may serve as electrodes that are configured to apply a current to a tissue when energized. The first and second end pieces **544**, **546** may be active bipolar electrodes that are configured to be coupled with and energized by an electrode energy source. In the illustrated example, the current may be provided through lead ends (such as lead ends **24**, **26** shown in FIGS. **1A-1B**) and through the pivot pins **552** to each of the end pieces **544**, **546**.

(95) Referring now to FIGS. **7A-7B**, another example of a portion of a surgical forceps is illustrated and generally designated at **620**. The proximal end of the forceps **620** is not shown, however, all details may be the same as shown in FIG. **1A-1B**, or the proximal end may take on any other acceptable configuration as known in the art. As in the examples of FIGS. **1A-6B**, the forceps **620** may be of the electrosurgical type or the non-energized type, by way of example. For example, if of the non-energized type, the forceps **620** are used for gripping and no energy is applied through the forceps **620**. However, if the forceps **620** are of the electrosurgical type, they may be used as a bipolar device, for example, to apply pulsed or non-pulsed energy to coagulate a tissue.

(96) The forceps **620** may include a first elongate member **628** and a second elongate member **630**, which are connected together at the proximal end (not shown). The first member **628** is disposed adjacent to the second member **630**. As described above with respect to FIGS. **1A-1B**, the first and second members **628**, **630** may be moved toward each other by exerting pressure on their outer sides; for example, an operator can pinch the first and second members **628**, **630** together and toward each other and bring the end pieces **644**, **646** together.

(97) As described above, the first and second members **628**, **630** may be formed of an insulating material, such as a plastic or rubber. In other configurations, the first and second members **628**, **630** may each have an inner portion formed of a conductive material, such as a metal, and an outer casing formed of an insulating material, where the outer casing surrounds the inner portion. In still other configurations, such as non-electrosurgical devices, the first and second members **628**, **630** may be formed entirely of a conductive material, such as a metal, by way of example.

(98) The first end piece **644** is coupled to the distal end **648** of the first member **628**, and the second end piece **646** may be coupled to the distal end **650** of the second member **630**. In the alternative, the second member **630** may not have a separate end piece **646**, as described above. The end pieces **644**, **646** may be identical to each other, as shown, or the end pieces **644**, **646** may be different from each other.

(99) Each end piece **644**, **646** has a first part **654**, **656** that is fixedly attached to the distal ends **648**, **650** of the first and second members **628**, **630**, respectively. In some examples, the first parts **654**, **656** may be formed unitarily with the distal ends **648**, **650**, respectively. A second part **660** of the first end piece **644** is movable with respect to the first part **654** and the first member **628**. Likewise, a second part **662** of the second end piece **646** is movable with respect to the first part **656** and the second member **630**. For example, the first parts **654**, **656** may each define a bore **694**, **696** therein, the first parts **654**, **656** defining an opening **698**, **699** in distal ends **700**, **701** of the first parts **654**, **656**, the openings **698**, **699** forming a distal end of the bores **694**, **696**. The second parts **660**, **662** may be retractable or slidable into and out of the openings **698**, **699** of the bores **694**, **696**. Thus,

the second parts **660**, **662** are axially movable with respect to the first parts **654**, **656**.

(100) In FIG. 7A, the first and second end pieces **644**, **646** are illustrated in first positions, wherein the second parts **660**, **662** are fully retracted into the bores **694**, **696** of the first parts **654**, **656**, so that the second parts **660**, **662** are fully disposed on a proximal side of the distal ends **700**, **701** and the openings **698**, **699**, the second parts **660** being fully disposed within one of: the first parts **654**, **656**, the members **628**, **630**, or a combination of the first parts **654**, **656** and the members **628**, **630**.

(101) In FIG. 7B, the first and second end pieces **644**, **646** are illustrated in second positions, wherein the second parts **660**, **662** extend distally from the openings **698**, **699** of the first parts **654**, **656**. In the second positions, the second parts **660**, **662** are partially located on distal sides of the openings **698**, **699** and the distal ends **700**, **701** of the first parts **654**, **656**, the second parts **660**, **662** also being located partially on proximal sides of the openings **698**, **699** and the distal ends **700**, **701** of the first parts **654**, **656**. Thus, the second parts **660**, **662** are partially located in the bores **694**, **696** in the second positions.

(102) The second parts **660**, **662** of the end pieces **644**, **646** are axially movable with respect to the first and second members **628**, **630**. Each second part **660**, **662** may be axially moved to put the end pieces **644**, **646** into their first positions (shown in FIG. 7A) and their second positions (shown in FIG. 7B). In the example of FIGS. 7A-7B, the second parts **660**, **662** of the first and second end pieces **644**, **646** are axially movable between their first and second positions without being detached from the first and second members **628**, **630**, respectively.

(103) As in the examples of FIGS. 1A-6B, one or more of the end pieces **644**, **646** could be provided as an electrode. For example, both of the first and second end pieces **644**, **646** may serve electrodes that are configured to apply a current to a tissue when energized. The first and second end pieces **644**, **646** may be active bipolar electrodes that are configured to be coupled with and energized by an electrode energy source. In the illustrated example, the current may be provided through lead ends (such as lead ends **24**, **26** shown in FIGS. 1A-1B) to each of the end pieces **644**, **646**.

(104) In some examples, either the first parts **654**, **656** or second parts **660**, **662** may be energizable as the electrode, and the other first parts **654**, **656** or second parts **660**, **662** may be an insulated or non-energized part. For example, the first parts **654**, **656** could be insulated like the first and second members **628**, **630** and the second parts **660**, **662** could be provided as energizable electrodes.

(105) An operator may desire to move the second parts **660**, **662** out of the first parts **654**, **656** of the end pieces **644**, **646** if the operator desires to use a narrower part of the end pieces **644**, **646**. Similarly, the operator may retract the second parts **660**, **662** into the first parts **654**, **656** if the operator desires wider ends of the forceps **620**. In the example where only the second parts **660**, **662** are energizable electrodes, the operator may move the end pieces **644**, **646** into their second positions if the operator desires to use the electrodes, and the operator may move the end piece into their first positions, wherein the second parts **660**, **662** are fully retracted into the first parts **654**, **656**, when the operator desires to use the forceps **420** as a non-energized gripper or tweezers.

(106) Like the various examples described above, the first and second parts **654**, **656**, **660**, **662** may have various characteristics that have been hereinbefore described. For example, one of the first and second parts **654**, **656**, **660**, **662** may be sharper than the other or have a larger surface area, by way of example.

(107) Similarly, any of the movable forceps **20**, **120**, **220**, **320**, **420**, **520**, **620** described herein, or other configurations, could also have other variations between the first and second parts or sides.

(108) For example, the first parts or sides could have a first coating disposed thereon, and a second parts or sides could have either no coating, or a second coating disposed thereon. In some examples, the first coating could be different than the second coating. Thus, the operator may desire to move the end pieces between the first and second positions to use the sides with either the first coating, no coating, or the second coating.

(109) In another example, a first portion of the first end piece could have a first end piece first

thermal capability, and a second portion of the first end piece could have a first end piece second thermal capability, wherein the first end piece first and second thermal capabilities are non-identical. The thermal capabilities could include conductivity, specific heat, heating upon application of power (related to electrical resistance), and/or thermal capacitance, by way of example. Likewise, a first portion of the second end piece could have a second end piece first thermal capability, and a second portion of the second end piece could have a second end piece second thermal capability, wherein the second end piece first and second thermal capabilities are non-identical. These thermal capabilities could differ from each other, such that the operator could move the end pieces between their first and second positions to use a part of the end piece having the desired thermal capability.

(110) In yet another example, a first portion of the first end piece could have a first end piece first electrical capability, and a second portion of the first end piece could have a first end piece second electrical capability, wherein the first end piece first and second electrical capabilities are non-identical—differing from each other. The electrical capabilities could include, for example, resistance and/or current density (conduction contact area). Likewise, a first portion of the second end piece could have a second end piece first electrical capability, and a second portion of the second end piece could have a second end piece second electrical capability, wherein the second end piece first and second electrical capabilities are non-identical. These electrical capabilities could differ from each other, such that the operator could move the end pieces between their first and second positions to use a part of the end piece having the desired electrical capability.

(111) In still another example, a first portion of the first end piece could have a first end piece first electrical polarity, and a second portion of the first end piece could have a first end piece second electrical polarity, particularly when the end pieces are electrodes or have electrodes. The first end piece first and second electrical polarities are non-identical—differing from each other. The electrical polarities could include energy passage, by way of example. Likewise, a first portion of the second end piece could have a second end piece first electrical polarity, and a second portion of the second end piece could have a second end piece second electrical polarity, wherein the second end piece first and second electrical polarities are non-identical. These electrical polarities could differ from each other, such that the operator could move the end pieces between their first and second positions to use a part of the end piece having the desired electrical polarity.

(112) In still another example, the first portions of the end pieces may be formed of a first material, and the second portions may be formed of a second material that is different than the first material. In some variations, one of the materials is conductive, while the other is insulating.

(113) Referring now to FIG. 8, a portion of an electrosurgical device kit is illustrated and generally designated at **718**. The kit **718** includes a surgical forceps **720** and at least two different attachable and detachable end pieces **744**, **745**.

(114) The surgical forceps **720** may be of the electrosurgical type or the non-energized type, by way of example. For example, if of the non-energized type, the forceps **720** are used for gripping and no energy is applied through the forceps **720**. However, if the forceps **720** are of the electrosurgical type, they may be used as a bipolar device, for example, to apply pulsed or non-pulsed energy to coagulate a tissue.

(115) For the forceps **720** of the electrosurgical type, the forceps **720** include a proximal end **722** that may be connected to an energy source via first and second leads **724**, **726**. The forceps **720** may include a first elongate member **728** and a second elongate member **730**, which are connected together at the proximal end **722** of the forceps device **720**. The first member **728** is disposed adjacent to the second member **730**. In this example, a band **732** surrounds proximal ends **734**, **736** of the first and second members **728**, **730** to couple the proximal ends **734**, **736** together. Thus, the proximal ends **734**, **736** may be fixed together by the band **732** as shown. In this example, the first and second members **728**, **730** are movably coupled together. As described with respect to FIGS. **1A-1B**, the first and second members **728**, **730** may be moved toward each other by exerting

pressure on their outer sides **738, 740**; for example, an operator can pinch the first and second members **728, 730** together and toward each other by gripping and exerting pressure on gripping sections **742** disposed on the outer sides **738, 740**. (Though not shown, it should be understood that an identical gripping section **742** is disposed on the outer side **740**, as shown on the outer side **738**.) (116) The band **732** and the first and second members **728, 730** may be formed of an insulating material, such as a plastic or rubber. In other configurations, the first and second members **728, 730** may each have an inner portion formed of a conductive material, such as a metal, and an outer casing formed of an insulating material, where the outer casing surrounds the inner portion. In still other configurations, such as non-electrosurgical devices, the first and second members **728, 730** may be formed entirely of a conductive material, such as a metal, by way of example.

(117) The first end piece **744** may be temporarily or removably attached to the distal end **748** of the first member **728**. The second member **730** may have a similar second end piece **746** that is removably attached to the distal end **750** of the second member **730**. In the alternative, the second member **730** may not have a separate end piece **746**; instead, the second member **730** may have a fixed end that is not interchangeable. The end pieces **744, 746** may be identical to each other, as shown, or the end pieces **744, 746** may be different from each other. The end pieces **744, 746** may take on various configurations, which will be described below.

(118) In the illustrated example of FIG. 8, each end piece **744, 746** has an arrow-like shape with a pointed end **749, 751**. The ends pieces **744, 746** form a cavity **753, 755** for attaching the end pieces **744, 746** to projections **757, 759** extending from the distal ends **748, 750** of the first and second members **728, 730**.

(119) The first type of end pieces **744, 746** may be detached from the first and second members **728, 730**, and the second type of end pieces **745, 747** may be attached. Thus, the end pieces **745, 747** are also removably attachable to the first and second members **728, 730**. The second type of end piece **745, 747**, in this example, is a rounded, blunt end piece **745, 747**. Each of the rounded end pieces **745, 747** also form a cavity **761, 763** therein for attaching the rounded end pieces **745, 747** to the projections **757, 759** of the first and second members **728, 730**. In the illustrated example, the first type of end pieces **744, 746** are sharper than the second type of end pieces **745, 747**. Thus, an operator can use whichever type of end pieces **744, 746, 745, 747** is more suitable for the particular task at hand and attach the desired end pieces **744, 746, 745, 747** to the first and/or second members **728, 730**.

(120) In some variations, one or more of the end pieces **744, 746, 745, 747** is an electrode head. For example, both of the types of end pieces **744, 746, 745, 747** may serve as electrode heads for the forceps device **720**. The electrode heads **744, 746, 745, 747** are configured to apply a current to a tissue when connected to one of the first and second members **728, 730** and energized. The end pieces **744, 746, 745, 747** may be active bipolar electrodes that are configured to be coupled with and energized by an electrode energy source when attached to one of the first and second members **728, 730**. In the illustrated example, the current may be provided through the lead ends **724, 726** to whichever of the end pieces **744, 746, 745, 747** is attached.

(121) Additional interchangeable electrode heads or end pieces may also be provided. For example, referring to FIG. 9A, a set of toothed end pieces **844, 846** (which may be electrode heads, as described above) are provided. Each of the toothed end pieces **844, 846** has a set of teeth **864, 866** for gripping a tissue. Furthermore, referring to FIG. 9B, another set of toothed end pieces **845, 847** (which may be electrode heads, as described above) are provided. The toothed end pieces **845, 847** also have sets of teeth **872, 874**. However, the sets of teeth **872, 874** on the end pieces **845, 847** in FIG. 9B have much larger teeth than the sets of teeth **864, 866** of the end pieces **844, 846** shown in FIG. 9A.

(122) As with the forceps **20, 120, 220, 320, 420, 520, 620** described above, the forceps **720** and end pieces **744, 745, 746, 747, 844, 845, 846, 847** may also be provided with various shapes, and having differing materials, coatings, polarities, electrical capabilities, and thermal capabilities.

(123) When used as an electrosurgical device, the forceps 20, 120, 220, 320, 420, 520, 620, 720 is configured to emit an electric signal for ablation, coagulation, or other treatment of nearby tissue. The forceps 20, 120, 220, 320, 420, 520, 620 720 may be of the bipolar type, wherein current is passed through one of the end pieces, through the patient's tissue, and received through the other end piece. In some examples, both end pieces are energized electrodes, which are energized with opposite polarity. For example, a first source signal may be delivered from the first end piece electrode, and a second source signal may be delivered from the second end piece electrode. Each of the first and second signals travel through tissue and return to the other of the two electrodes—the one that did not generate the signal. The electrons flow in a single direction at a time. As the signals oscillate between each electrode, the electrons race toward whichever electrode has a more positive terminal.

(124) The description of the invention is merely exemplary in nature and variations that do not depart from the gist of the invention are intended to be within the scope of the invention. Such variations are not to be regarded as a departure from the spirit and scope of the invention. For example, variations in the various figures can be combined with each without departing from the spirit and scope of the present disclosure.

(125) The preferred embodiment of the present invention has been disclosed. A person of ordinary skill in the art would realize, however, that certain modifications would come within the teachings of this invention. Therefore, the following claims should be studied to determine the true scope and content of the invention.

(126) Any numerical values recited in the above application include all values from the lower value to the upper value in increments of one unit provided that there is a separation of at least 2 units between any lower value and any higher value. As an example, if it is stated that the amount of a component or a value of a process variable such as, for example, temperature, pressure, time and the like is, for example, from 1 to 90, preferably from 20 to 80, more preferably from 30 to 70, it is intended that values such as 15 to 85, 22 to 68, 43 to 51, 30 to 32 etc. are expressly enumerated in this specification. For values which are less than one, one unit is considered to be 0.0001, 0.001, 0.01 or 0.1 as appropriate. These are only examples of what is specifically intended and all possible combinations of numerical values between the lowest value and the highest value enumerated are to be considered to be expressly stated in this application in a similar manner.

(127) Unless otherwise stated, all ranges include both endpoints and all numbers between the endpoints, the use of “about” or “approximately” in connection with a range apply to both ends of the range. Thus, “about 20 to 30” is intended to cover “about 20 to about 30”, inclusive of at least the specified endpoints.

(128) The disclosures of all articles and references, including patent applications and publications, are incorporated by reference for all purposes.

(129) The term “consisting essentially of” to describe a combination shall include the elements, ingredients, components or steps identified, and such other elements ingredients, components or steps that do not materially affect the basic and novel characteristics of the combination.

(130) The use of the terms “comprising” or “including” describing combinations of elements, ingredients, components or steps herein also contemplates embodiments that consist essentially of the elements, ingredients, components or steps.

Claims

1. A device, comprising: an elongate first member; an elongate second member disposed adjacent to the elongate first member, the elongate second member movably coupled to the elongate first member; wherein a central axis extends from a distal end portion of the device to a proximal end portion of the device and between the elongate first member and the elongate second member; and a forceps end coupled to the elongate first member, at least a portion of the forceps end being

movable with respect to the elongate first member into a forceps end first position and a forceps end second position, the forceps end having a first face surface and a second face surface and a perimeter edge extending around each of the first face surface and the second face surface; wherein at least one of the first face surface or the second face surface face the central axis; wherein the first face surface includes a first set of teeth extending towards the central axis from the first face surface within the perimeter edge of the first face surface and the second face surface includes a second set of teeth extending from the second face surface; wherein the elongate first member and the elongate second member are configured to have a separated position, and a first gripping position, and a second gripping position; wherein in the first gripping position the first set of teeth is disposed closer to the central axis than the second set of teeth, and in the second gripping position the second set of teeth is disposed closer to the central axis than the first set of teeth.

2. The device of claim 1, wherein the first set of teeth is non-identical to the second set of teeth.

3. The device of claim 1, wherein the forceps end is movable between the forceps end first position and the forceps end second position without being detached from the elongate first member.

4. The device of claim 1, wherein the forceps end is rotatably attached to the elongate first member.

5. The device of claim 1, wherein the device includes a first device distal end and a second device distal end, the first set of teeth forming the first device distal end when the forceps end is in the forceps end first position, and the second set of teeth forming the second device distal end when the forceps end is in the forceps end second position.

6. The device of claim 5, wherein in the forceps end first position, the second set of teeth is disposed closer to the device proximal end portion than the first set of teeth is disposed with respect to the device proximal end portion.

7. The device of claim 1, wherein the device is an electrosurgical device, the device includes: a second forceps end coupled to the elongate second member, at least a portion of the second forceps end being movable with respect to the elongate second member into a second forceps end first position and a second forceps end second position, the second forceps end having a third forceps portion and a fourth forceps portion, the third forceps portion having a third set of teeth and the fourth portion having a fourth set of teeth.

8. The device of claim 1, wherein a second forceps end coupled to the elongate second member includes a third face surface and a fourth face surface; wherein the first face surface is identical to the second face surface and the third face surface is identical to the fourth face surface.

9. The device of claim 8, wherein the first face surface is movable between the first forceps end first position and the first forceps end second position without being detached from the elongate first member, and wherein the third face surface is movable with respect to the elongate second member between a second forceps end third position and a second forceps end fourth position where the third face surface is closer to the central axis than the fourth face surface without being detached from the elongate second member.

10. The device of claim 8, wherein in the first forceps end first position, the second face surface of the first forceps end is disposed closer to the device proximal end portion than the first face surface, and wherein in a second forceps end third position, the third face surface is disposed closer to the device proximal end portion than the fourth face surface.

11. The device of claim 8, wherein in the first forceps end first position, the first face surface is disposed closer to the central axis of the device than the second face surface, and in a second forceps end third position, the third face surface is disposed closer to the central axis of the device than the fourth face surface.

12. The device of claim 1, wherein a second forceps end coupled to the elongate second member includes a third face surface and a fourth face surface, the third face surface includes a third set of teeth and the fourth face surface includes a fourth set of teeth; wherein the first set of teeth of the first forceps end forms a first device distal end when the first forceps end is in the first forceps end first position, and the second set of teeth of the first forceps end forms the first device distal end

when the first forceps end is in the first forceps end second position, and wherein the third set of teeth of the second forceps end and forms a second device distal end when the second forceps end is in a second forceps end third position, and the fourth set of teeth of the second forceps end forms the second device distal end when the second forceps end is in a second forceps end fourth position.

13. A device, comprising: an elongate first member; an elongate second member disposed adjacent to the elongate first member, the elongate second member being at least movably coupled to the elongate first member; wherein the elongate first member and the elongate second member are configured to be movable between a separated position and a gripping position; a first forceps end coupled to the elongate first member, at least a portion of the first forceps end being movable with respect to the elongate first member into a first forceps end first position and a first forceps end second position, the first forceps end having a first face surface and a second face surface, the first face surface having a first set of teeth and the second face surface having a second set of teeth; wherein at least one of first set of teeth or the second set of teeth extend toward a central axis of the device in the first forceps end first position; and a second forceps end coupled to the elongate second member, at least a portion of the second forceps end being movable with respect to the elongate second member into a second forceps end third position and a second forceps end fourth position, the second forceps end having a third face surface and a fourth face surface, the third face surface having a third set of teeth and the fourth face surface having a fourth set of teeth; wherein at least one of the third set of teeth or the fourth set of teeth extend toward the central axis of the device in the second forceps end third position; wherein in a first gripping position of the gripping position, the first set of teeth and the third set of teeth are positioned closer to the central axis than the second set of teeth and the fourth set of teeth, and in a second gripping position of the gripping position, the second set of teeth and fourth set of teeth are positioned closer to the central axis than the first set of teeth and the third set of teeth.

14. The device of claim 13, wherein the first forceps end and the second forceps end are identical.

15. The device of claim 13, wherein the first set of teeth of the first and the second set of teeth are non-identical to the third set of teeth and the fourth set of teeth.

16. The device of claim 13, wherein the first forceps end is rotatably attached to the elongate first member and the second forceps end is rotatably attached to the elongate second member; wherein one or more of the first forceps end and the second forceps end are electrodes that are configured to apply a current to a tissue when energized.
