

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18

MEDICAL DEVICE DOCKING STATION

CROSS-REFERENCE TO RELATED APPLICATION

[0001] This application is a continuation of U.S. patent application Ser. No. 18/422,894, filed on Jan. 25, 2024, which claims benefit of U.S. patent application Ser. No. 17/214,211, filed on Mar. 26, 2021, which issued as U.S. Pat. No. 11,920,361 on Mar. 5, 2024, which claims benefit of U.S. Provisional Application No. 63/001,109, filed on Mar. 27, 2020, titled “Medical Device Docking Station”, which are incorporated by reference herein in their entirety.

BACKGROUND

[0002] A monitor-defibrillator is a portable, life-saving piece of equipment that is brought to a patient to monitor and treat the patient during an emergency medical event. As the patient is transported from the site of the emergency medical event, such as in an ambulance, the monitor-defibrillator often remains with the patient to continue monitoring and treatment during transport, until the patient arrives at a care facility. However, an unsecured monitor-defibrillator used within a moving vehicle can present a hazard or nuisance to the patient, rescuers, or others caring for the patient.

[0003] Additionally, portable medical devices, such as monitor-defibrillators, typically include a direct current (DC) power source, such as batteries, to provide power to electronic components of the medical device. Some DC batteries are configured to be recharged by coupling the medical device to an external power source, such as an alternating current (AC) power source. In a vehicle, such as an ambulance, a connection to an external power source may not be positioned near the patient, making it difficult to have the portable medical device connected to the external power source while positioned in a convenient manner for treating the patient. For example, if the medical device is not positioned near the patient due to its connection to an external power source, the rescuers’ treatment of the patient may be hindered because the rescuers may have to break their concentration on the patient to interact with the portable medical device. Additionally, should the portable medical device be operating on battery power and the batteries become depleted during care of the patient, further delays may occur as the rescuers interrupt patient care to connect the portable medical device to the external power source. The disclosure made herein is presented with respect to these and other considerations.

BRIEF DESCRIPTION OF THE DRAWINGS

[0004] FIG. 1 illustrates a front perspective view of an example medical device docking station.

[0005] FIG. 2 illustrates a top plan view of the example docking station depicted in FIG. 1.

[0006] FIG. 3 illustrates a bottom plan view of the example docking station depicted in FIG. 1.

[0007] FIG. 4 illustrates a front plan view of the example docking station depicted in FIG. 1.

[0008] FIG. 5 illustrates a rear plan view of the example docking station depicted in FIG. 1.

[0009] FIG. 6 illustrates a side plan view of the example docking station depicted in FIG. 1.

[0010] FIG. 7 illustrates a front perspective view of a medical device docked to the example docking station depicted in FIG. 1.

[0011] FIG. 8 illustrates a rear perspective view of the example medical device and docking station depicted in FIG. 7.

[0012] FIG. 9 illustrates a front perspective view of the example medical device and docking station depicted in FIG. 7 with example storage bags coupled to the medical device.

[0013] FIG. 10 illustrates a rear perspective view of the example medical device and docking station depicted in FIG. 9.

[0014] FIG. 11 illustrates a front plan view of the example medical device and docking station depicted in FIG. 7.

[0015] FIG. 12 illustrates a rear plan view of the example medical device and docking station depicted in FIG. 7.

[0016] FIG. 13 illustrates a side plan view of the example medical device and docking station depicted in FIG. 7.

[0017] FIG. 14 illustrates a front plan view of an example base plate of a docking station.

[0018] FIG. 15 illustrates a top plan view of the example base plate depicted in FIG. 14.

[0019] FIG. 16 illustrates a perspective view of a portion of the base plate depicted in FIG. 14.

[0020] FIG. 17 illustrates a top view of an example integrated connector of the example base plate depicted in FIG. 14.

[0021] FIG. 18 illustrates a cutaway view of an example docking mechanism of a docking station.

DETAILED DESCRIPTION

[0022] Portable medical devices provide life-saving monitoring and treatment capabilities that assist a rescuer who is attending to a patient. A “rescuer,” as used herein, is the person operating the disclosed medical devices and treating the patient; however, the term “rescuer” includes any user, such as a bystander or other user, whether trained or untrained to use such medical devices. The portability of a medical device allows the medical device to be positioned near a patient, as needed by the rescuer, both while treating the patient at the scene of an emergency medical event or treating the patient within a moving vehicle during patient transport from the emergency medical event. Unsecured medical devices (e.g., those that are not retained or otherwise secured to a surface) within a moving vehicle, such as an ambulance, can pose a hazard and/or a nuisance for the vehicle occupants. However, retaining the medical device using ad hoc equipment (e.g., straps, etc.) can make it difficult to both connect the medical device to an external power source and have the medical device positioned conveniently for the rescuer.

[0023] The disclosure provides examples of a medical device docking station that is configured to, among other things, securely retain a medical device. When the docking station is securely positioned within a vehicle, the docking station prevents unintentional movement of the medical device relative to the vehicle. The docking station allows for efficient docking of the medical device to the docking station and for efficient removal of the medical device from the docking station. As used herein, “docking” the medical device to the docking station means coupling the medical device to the docking station in any suitable fashion, such as placing the medical device on or in the docking station,

whereby the medical device is retained by the docking station once it is docked to the docking station. Furthermore, the docking station allows for positioning the medical device to maximize rescuer ease and comfort during use of the medical device, and to minimize delays in patient care. In certain examples, docking the medical device to the docking station also electrically connects the medical device to an external power source, which provides electrical power to the docked medical device. In some examples, the electrical connection that is established upon docking the medical device to the docking station connects the medical device to an external device(s), network(s), and/or system, such as remote computing device(s), network(s), and/or system(s), which allows the medical device to communicate with the external device(s), network(s), and/or system(s).

[0024] In some examples, the medical device that is configured to dock at the disclosed docking station is a defibrillator, such as a monitor-defibrillator used by emergency medical services (EMS) teams to monitor and treat patients during emergency medical events. Such monitor-defibrillators are portable devices that are physically moved to a position near the patient experiencing the emergency medical event and then transported with the patient to a medical facility, such as a hospital. For example, a patient experiencing a cardiac event undergoes monitoring and potentially treatment, such as cardiopulmonary resuscitation (CPR), defibrillation therapy, drug therapy, and/or other therapies until the patient is in a condition deemed sufficient to transport the patient to a hospital for further care. To perform this monitoring and treatment, EMS teams often connect the patient to a portable monitor-defibrillator upon arrival at the emergency scene. Once the patient's condition is approved for transport, the patient and the monitor-defibrillator are moved together into an ambulance with the monitor-defibrillator still connected to the patient to facilitate continued monitoring and possibly further treatment. Once the patient and the monitor-defibrillator are inside the ambulance, the EMS team continues to monitor and possibly administer treatment to the patient during transport.

[0025] The portable monitor-defibrillator in this cardiac event example is secured within the ambulance using the disclosed docking station to avoid the danger of the monitor-defibrillator colliding with the patient or an EMS team member, and to allow the EMS team to easily use the monitor-defibrillator during continued monitoring and treatment of the patient during transport. The medical device disclosed herein may be any suitable medical device or a combination of medical devices, such as an automated external defibrillator (AED), a manual defibrillator, a monitor-defibrillator, other medical devices that couple to the monitor-defibrillator (through wireless or through wired connections), other portable medical devices, or the like. It is to be appreciated that the disclosed docking station is configured to be used with any suitable type of medical devices, and that the docking station may be utilized in any suitable environment, such as within an ambulance or other types of vehicles.

[0026] To secure a medical device within a vehicle, such as an ambulance, the medical device is configured to be docked to a docking station disclosed herein. The rescuer docks the medical device to the docking station, and a docking mechanism automatically engages to retain the medical device in or on the docking station. To remove the medical device from the docking station, the rescuer can

actuate a handle that, when actuated, disengages the docking mechanism. In some examples, the handle is configured to be actuated using a single hand, which allows the rescuer to easily disengage the docking mechanism and remove the medical device from the docking station. The automatic engagement of the docking mechanism and the disengagement using the handle allows the rescuer to quickly and easily dock the medical device to the docking station and to efficiently remove the medical device from the docking station.

[0027] In some examples, the docking station includes an electronic connector that couples the medical device to an external power source and optionally establishes a communications connection that allows the medical device to communicate with an external device(s), network(s), and/or system. In some examples, the medical device includes a mating electronic connector that interfaces with the electronic connector of the docking station. The docking of the medical device to the docking station causes the mating electronic connector of the medical device to couple to the electronic connector of the docking station. The removal of the medical device from the docking station decouples the mating electronic connector of the medical device from the electronic connector of the docking station. As used herein, the term “couple” may refer to an indirect coupling or a direct coupling between elements. The term “couple,” as used herein, may also refer to a removable coupling or a permanent coupling between the elements. Elements are removably coupled if a user or another entity is able to decouple the elements. Elements are permanently coupled if a user or another entity is unable to decouple the elements without destroying or significantly damaging the elements, or without undue effort to disassemble the elements using tools or machinery. As used herein, the term “couple” can be interpreted as connect, attach, join, engage, interface, link, fasten, or bind. Unless otherwise specified herein, the term “couple” is to be interpreted as coupling elements in a mechanical sense, rather than in an electrical sense, for example. Nevertheless, it is to be appreciated that a mechanical coupling of elements may result in an electrical coupling(s) between multiple elements of the system.

[0028] In some examples, the coupling between the mating electronic connector of the medical device and the electronic connector of the docking station causes power to be provided to the medical device from an external power source, and optionally establishes other electronic connections, such as communication between the medical device and other external device(s), network(s), or system(s), including other nearby or remote medical device(s), caregiver device(s), computer network(s) or system(s), communication platforms such as Bluetooth®, WiFi, or WiGig or other electronic coupling(s) or communication(s).

[0029] FIGS. 1-13 illustrate various views of an example docking station 100. FIGS. 1-6 illustrate views of the docking station 100 without a medical device 150 docked to the docking station 100. FIGS. 7-13 illustrate views of the docking station 100 with a medical device 150 docked to the docking station 100. The example medical device 150 shown in these figures is a defibrillator (e.g., a monitor-defibrillator).

[0030] The docking station 100 of FIGS. 1-13 includes a docking mechanism 110 and a base plate 120. The base plate 120 is configured to interface with (e.g., contact, support, etc.) a medical device mounted therein, such as the medical

device **150** of FIGS. 7-13. In these examples, the medical device **150** is inserted into or placed onto the docking station **100**, and the docking mechanism **110** automatically engages (e.g., grabs, grasps, hooks, etc.) a portion of the medical device **150** to dock the medical device **150** to the docking station **100** and retain the medical device **150**. In some examples, the docking mechanism **110** is disposed at an upper portion of the docking station **100** (e.g., at the distal ends of two arms **102b**) to engage a top portion of the medical device **150**. To remove the medical device **150** from the docking station **100**, the rescuer actuates the docking mechanism **110** with an actuator, such as a handle **112**. Actuation of the handle **112** causes the docking mechanism **110** to disengage from the portion of the medical device **150**. The disengagement of the docking mechanism **110** allows the medical device **150** to be removed from the docking station **100**. The docking mechanism **110** is discussed in more detail below with reference to FIG. 18.

[0031] In some examples, the docking station **100** includes a base plate **120** that is configured to interface with (e.g., contact, support, etc.) a bottom surface (or base) of the medical device **150** when the medical device **150** is docked to the docking station **100**. The example base plate **120** includes positioning guides **122**, **124** and an electronic connector **126** that is disposed on (e.g., integrated with) the base plate **120**. The positioning guides **122**, **124** are each configured to mate with corresponding cavity defined in the bottom surface (or base) of the medical device **150**. As the medical device **150** is docked to the docking station **100**, the positioning guides **122**, **124** engage (e.g., insert into) the corresponding cavities defined in the bottom surface of the medical device **150** to assist with positioning the medical device **150** on the base plate **120**. When the medical device **150** is docked to the docking station **100**, a mating electronic connector of the medical device **150** engages the electronic connector **126** of the docking station **100** to establish one or more electrical connection(s) between them. Through this or these connection(s), the medical device **150** is connected to an external power source that is configured to supply power to the medical device **150** originating from the external power source, and the medical device **150** optionally establishes a communication connection to transmit data to, and/or receive data from an external device(s), network(s), and/or system(s).

[0032] In some examples, the docking station **100** includes the docking mechanism **110**, a frame **102**, a front plate **104**, and a back plate **106**. In the example shown in FIGS. 1-13, the frame **102** is substantially C-shaped to fit around the exterior of the medical device **150** or a portion of the medical device **150**, such as the back **150b** of the medical device **150**. For example, the C-shaped frame **102** is configured to fit around the medical device **150** from the rear of the medical device **150**. It is to be appreciated that the frame **102** can be any other suitable shape, and the frame **102** may be curved and/or angled to fit around the medical device **150** or a portion thereof. The frame **102** shown in FIGS. 1-13 includes two C-shaped members that are vertically-oriented and spaced apart from each other, each C-shaped member including a post **102a** that is vertically-oriented when the docking station **100** is upright (as shown in FIG. 1), an arm **102b** extending orthogonally from a top (e.g., a first, top end) of the post **102a**, and a leg **102c** extending orthogonally from a bottom (e.g., a second, bottom end) of the post **102a**. In some examples, the two posts **102a** are

both vertical and straight, and, therefore, parallel with each other. Similarly, the arms **102b** and the legs **102c**, in some examples, are parallel with each other. The posts **102a** of the frame **102** are shown in a vertical orientation and spaced apart by roughly the same width as the medical device **150**. It is to be appreciated however, that the posts **102a** may be in an orientation other than vertical, in some examples. Further, in some examples, the posts **102a** are not parallel. In some examples, the posts **102a** are angled relative to each other, or the posts **102a** may include some curvature. In some examples, the posts **102a** are a single integrated member. In other examples, the posts **102a** include more than two parallel (or non-parallel) members. Likewise, the arms **102b** and the legs **102c**, in some examples, are single integrated pieces, or they are separated into multiple arm(s) **102b** and multiple leg(s) **102c**, including more than two arms **102b** and more than two legs **102c**. Further, the cross-sectional shape of the posts **102a**, the arms **102b**, and the legs **102c** is shown in a generally rectangular shape, and the corners at the junction between the posts **102a** and the arms **102b** and legs **102c** are depicted as curved corners in FIGS. 1-13. It is to be appreciated, however, that the cross-sectional shape of the posts **102a**, the arms **102b**, and the legs **102c** may be another shape, such as circular (e.g., a circular tube), triangular, square, pentagonal, hexagonal, etc., and the corners where the posts **102a** meet the arms **102b** and legs **102c** may be sharp corners without curvature.

[0033] Referring to FIG. 1, the arms **102b** of the frame **102** are positioned at first (e.g., top) ends of the posts **102a**, and at least a portion of the docking mechanism **110** is positioned between the arms **102b** at distal ends of the arms **102b**. The legs **102c** of the frame **102** are positioned at the second (e.g., bottom) ends of the posts **102a**. The second ends of the posts **102a** are opposite their first ends. The posts **102a** shown in FIGS. 1-13 are each integrated with a portion of the two arms **102b** and the two legs **102c**, which are linked or joined by a curved portion **102d** of the frame **102** to each of the posts **102a**. In other examples, the portions of the frame **102** are individual elements that are joined together, and/or the joint(s) or junction(s) between elements of the frame **102** have various profiles other than the curved profile shown, such as a square or angular profile.

[0034] In the example of FIGS. 1-13, the frame **102** has two sides that mirror each other. The frame **102** includes a first side and a second side that each have a post **102a**, an arm **102b**, and a leg **102c**. The two sides of the frame **102** are connected together by the handle **112**, the front plate **104**, the base plate **120**, and/or the back plate **106**. In some examples, the handle **112** is positioned at or near distal ends of the arms **102b** (e.g., the free ends of the arms **102b** that are opposite the proximal ends adjoined with the posts **102a** from which the arms **102b** extend). The handle **112** extends between the arms **102b** of the frame **102** to connect the arms **102b** of the two sides of the frame **102**. Accordingly, the handle **112** is oriented horizontally to span the distance that the two arms **102b** are spaced apart. The back plate **106** is positioned on rear surfaces of the posts **102a**. The rear surfaces of the posts **102a** are opposite front surfaces of the posts **102a** from which the arms **102b** and legs **102c** extend. The back plate **106** is coupled to the posts **102a** to connect the posts **102a** of the two sides of the frame **102**. The front plate **104** is positioned at the distal ends of the legs **102c** (e.g., the ends of the legs **102c** that are opposite the proximal ends adjoined to the posts **102a** from which the legs **102c**

extend). The front plate **104** is coupled to the distal ends of the legs **102c** to connect the legs **102c** of the two sides of the frame **102**. In some examples, the two sides of the frame **102** are connected in other manners. For example, other features or elements can join the two sides of the frame **102**. These other features or elements that join the two sides of the frame **102** can be in addition to or in place of the handle **112**, front plate **104**, base plate **120**, back plate **106**, or a combination thereof.

[0035] In some examples, the frame **102** has alternative arrangements to those described in reference to FIGS. 1-13, such as a sectional frame **102** formed with an upper section, a middle section, and a lower section. The upper section of this alternative frame **102** includes the arms **102b** and the docking mechanism **110** shown in FIGS. 1-13. The middle section of this alternative frame **102** includes the posts **102a**, also shown in FIGS. 1-13. The lower section of this alternative frame **102** includes the legs **102c** and a front plate **104**, also shown in FIGS. 1-13. In this example, the upper, middle and lower sections are connected or joined together to form the frame **102**. It is to be appreciated that, even if the C-shaped members of the frame **102** do not include multiple sections that are coupled together (e.g., if the C-shaped members are monolithic parts), the C-shaped frame **102** can be considered to include a middle portion (e.g., the posts **102a**), an upper portion (e.g., the arms **102b**), and a lower portion (e.g., the legs **102c**).

[0036] Referring again to FIG. 1, the docking station **100** is configured to be mounted to a surface, such as a counter or shelf within a vehicle. Such mounting of the docking station **100** to a surface secures the docking station **100** during movement of the vehicle and from unintentional impact. The legs **102c** of the frame **102** include openings, such as through holes, through which a faster(s) like a screw(s) or a bolt(s) is configured to be inserted to couple the docking station **100** to the surface. Mounting the docking station **100** to the surface secures the docking station **100** to the surface and prevents movement of the docking station **100** with respect to the surface to which it is coupled, such as preventing the unwanted movement of the docking station **100** within the moving vehicle or by unintentional impact.

[0037] In some examples, the docking station **100** is configured to be mounted from above so that the docking station **100** hangs below a surface, such as the underside of a cabinet, a ceiling, etc. To secure the docking station **100** in such a manner, the arms **102b** of the docking station **100** are configured to be secured to the surface, or an intervening element(s) is used to couple the arms **102b** or another portion of the docking station **100** to the surface.

[0038] In some examples, the docking station **100** is configured to be releasably mounted to a surface to allow the docking station **100** to be decoupled and removed from the surface or to be repositioned on the same or another surface, as desired. Releasable mounting elements secure the docking station **100** to the surface in a releasable manner. For example, releasable mounting elements include screws, bolts, temporary adhesives, or other releasable mounting elements or systems.

[0039] In some examples, an underside or bottom surface of the legs **102c** of the frame **102** include features, such as protrusions or openings that engage complementary features of the surface to further secure the docking station **100** to the surface. In an example, openings on the underside of the legs **102c** are configured to engage with (e.g., receive) protrusions,

such as pins or dowels extending from the surface to position the docking station **100** on the surface and prevent movement of the docking station **100** along the surface. In some examples, the protrusions extending from the surface include locking features, such as a spring-driven catch, to engage with the docking station **100** and secure the docking station **100** to the protrusions on the surface. In some examples, the protrusions extending from the surface are configured to engage (e.g., insert into) the openings defined in the underside of the legs **102c** in a non-locking manner to prevent lateral motion of the docking station **100** across the surface while not impeding vertical motion of the docking station **100** from the surface, such as to facilitate quick and easy removal of the docking station **100** from the surface.

[0040] In an example, the docking station **100** includes a turntable **130** that is integrated with or coupled to an underside of the frame **102**. FIG. 10 shows an example turntable **130** that is coupled to an underside of the legs **102c** of the frame **102** and disposed beneath the legs **102c**. In some examples, the turntable **130** is coupled to an underside of the base plate **120**. In some examples, the turntable **130** includes openings **132** (e.g., through holes) or other attachment elements to allow the turntable **130** to be coupled to the surface on which the docking station **100** rests. In an example, the turntable **130** of the docking station **100** is configured to be coupled to a surface within a vehicle, such as a shelf, cabinet, or countertop, using the openings **132** defined in the turntable **130**. To secure the docking station **100** to the surface, fasteners (e.g., screws) are passed through the openings **132** defined in the turntable **130** to engage the surface and couple the turntable **130** and the docking station **100** to the surface.

[0041] The turntable **130** allows the docking station **100** to rotate relative to the surface. The rescuer is able to rotate or swivel the docking station **100** so that the retained medical device **150** is viewable in different positions and adjusted, as desired. In some examples, the rotation of the docking station **100** is a clockwise or a counterclockwise rotation about an imaginary vertical axis running through a center of the docking station **100** from top-to-bottom. In some examples, the example turntable **130** includes an element, such as a mechanical stopper or a detent, that limits or prevents unintended rotation of the turntable **130** caused by movement of the vehicle or unintentional impact with the medical device **150** and/or the docking station **100**. In an example, the turntable **130** includes a lock that the rescuer engages to prevent further rotation of the turntable **130** and/or the docking station **100** after the turntable **130** and/or docking station **100** is positioned in the desired position or orientation. In another example, the turntable **130** includes multiple, fixed orientations to which the docking station **100** is configured to be rotated. When rotated, the docking station **100** locks into one of the fixed orientations to prevent further rotation beyond the selected fixed orientation. In some examples, an application of force is required to rotate the turntable **130** and/or the docking station **100** from the selected fixed orientation. The force needed to rotate the turntable **130** from the selected fixed orientation can be sufficiently large so that force created by routine movement of the vehicle does not overcome the needed force to cause rotation of the turntable **130** and/or the docking station **100**. In an example, the turntable **130** includes one or more detents that are each associated with one of the fixed

orientations and require a predetermined amount of force to release the turntable from the fixed orientation associated with one of the detents.

[0042] In some examples, the turntable **130** includes a tilt feature to allow the docking station **100** to be tilted relative to the surface on which the turntable **130** rests. In this manner, the rescuer is able to move the medical device **150** in three dimensions by rotating the docking station **100** (e.g., clockwise or counterclockwise) with the turntable **130** and tilting the docking station **100** with the tilt feature of the turntable **130**. In an example, the rescuer is able to tilt the docking station **100** to adjust the inclination of the medical device **150** so the medical device **150** is positioned at an angle relative to the surface (e.g., in a reclined or an inclined orientation). This tilt motion allows the rescuer to look downward at the medical device **150** to more easily view a display on the front of the medical device **150**. Similarly, the medical device **150** is configured to be tilted to position the display of the medical device **150** at an opposing angle to the inclined position, which is useful if the rescuer is positioned below the level of the display of the medical device **150**, such as when the rescuer is sitting down or kneeling next to a patient.

[0043] In some examples, the docking station **100** is configured to be mounted to a wall, cabinet, or other surface (e.g., a vertically-oriented surface) using the back plate **106**. The back plate **106** include openings, such as the through holes **107a** to allow the docking station **100** to be coupled to a vertical surface like a wall of an ambulance. In FIG. 5, for example, four through holes **107a** defined in the back plate **106** are shown—an upper left through hole **107a**, an upper right through hole **107a**, a lower left through hole **107a**, and a lower right through hole **107a**. The through holes **107a** defined in the back plate **106** are configured to receive fasteners, such as screws, nails, bolts, or other fasteners, and the fasteners pass through the through holes **107a** to engage (e.g., fasten into) a vertical surface behind the docking station **100** to couple the docking station **100** to the vertical surface. In some examples, the vertical surface to which the docking station **100** is mounted includes mounting hardware, such as threaded openings to allow the fasteners to be passed through the through holes **107a** and mounted to the mounting hardware of the vertical surface. In an example, the back plate **106** is configured to be coupled to the vertical surface, and then the frame **102** of the docking station **100** is configured to be coupled to the back plate **106**. In another example, the back plate **106** is configured to be coupled to the frame **102** of the docking station **100**, and then the docking station **100** is configured to be coupled to the vertical surface using the back plate **106**.

[0044] In some examples, the back plate **106** includes features that engage complementary features of the vertical surface to couple the docking station **100** to the vertical surface. In an example, the vertical surface includes pins that protrude from the vertical surface, and the through holes **107a** of the back plate **106** are configured to be placed onto the pins to mount the docking station **100** to the vertical surface. In another example, the vertical surface includes hooks onto which the back plate **106** is configured to be rested to mount the docking station **100** to the vertical surface.

[0045] In some examples, the through holes **107a**, or other openings **107b**, of the back plate **106** are configured to be used to couple accessories or modules, such as the accessory

160 shown in FIGS. 12 and 13, to the docking station **100**. The accessory **160** is configured to be coupled to the back plate **106** using fasteners that engage or interface with the openings of the back plate **106**. In some examples, the accessory **160** includes a communication module, a data transfer module, a power module, and/or another accessory, or a combination thereof. In some examples, the coupling of the accessory **160** to the back plate **106** is removable to allow the accessory **160** to be removed from the docking station **100**. In some examples, the accessory **160** is configured to be coupled to the back plate **106** by means other than the openings **107a** and/or **107b** of the back plate **106**. In some examples, the accessory **160** is configured to be coupled to a portion of the docking station **100** other than the back plate **106**.

[0046] In the examples shown in FIGS. 1-13, the back plate **106** is coupled to the posts **102a** of the frame **102**. In some examples, the back plate **106** is configured to be coupled to one of the posts **102a** of the frame **102**, but not both of the posts **102a**. In some examples, the frame **102** includes a single or multiple posts **102a**, and the back plate **106** is configured to be coupled to some or all of the posts **102a** of the frame **102**. In these examples, the back plate **106** is also configured to be used to secure the docking station **100** to a surface, such as a vertical surface (e.g., a wall, a cabinet, etc.).

[0047] In some examples, rather than being coupled to a surface, the docking station **100** is configured to be portable or moveable. The docking station **100** is configured to rest on a surface and is movable or repositionable, as desired. In some examples, the legs **102c** of the frame **102** of the docking station **100** include high-friction material (e.g., rubber) on their bottom surfaces to prevent movement, such as sliding, of the docking station **100** along or across the surface on which the docking station **100** rests.

[0048] At least a portion of the base plate **120** is positioned between the legs **102c** of the frame **102** of the docking station **100**, as shown in FIG. 3. In some examples, the base plate **120** is configured to be coupled to the frame **102** by sliding the base plate **120** into slots defined in each of the legs **102c** of the frame **102**. In some examples, the slots are defined in the inner side surfaces, the top surfaces, and/or the bottom surfaces of the legs **102c** to accommodate the base plate **120** and position the base plate **120** between the legs of the frame **102**. The front plate **104** is configured to be coupled to the legs **102c** of the frame **102** using fasteners, such as screws. In some examples, the front plate **104** is configured to be removably coupled to the legs **102c** to retain the base plate **120** within the docking station **100**. Removing the front plate **104** allows a rescuer to access to the base plate **120** so that the base plate **120** is accessible to be removed from the docking station **100**. For example, removing the front plate **104** in FIG. 3 allows the rescuer to slide or manipulate the base plate **120** from between the legs **102c** of the frame **102** of the docking station **100**.

[0049] FIGS. 1, 4-6, and 14-16 show the base plate **120** with an external connector **127** to allow the electronic connector **126** to be electrically connected to an external device or system, such as a power source, communications system, or both (either by the same or two separate electrical connections). In this manner, when the medical device **150** is docked to the docking station **100**, the medical device **150** is electrically connected to the electronic connector **126**, and to the external device(s), network(s), or system(s) that are

electrically connected to the base plate **120** by the external connector **127**. The electrical connection of the medical device **150** to the external device(s), network(s), or system(s) allows the medical device **150** to receive power from an external source and/or to facilitate data communication and sharing of information and data between the medical device **150** and the external device(s), network(s), or system(s).

[0050] In an example, the docking station **100** is mounted within an ambulance or another type of emergency vehicle. A cable is electrically coupled to the external connector **127** of the base plate **120** at one end of the cable and is coupled to a power, data, or combined power and data connector within the vehicle on the other end of the cable. Since the docking station **100** is fixed in place, or is allowed to rotate on a turntable **130** that is fixed in place, this affixation of the docking station **100** to the vehicle acts as a strain relief on the cable that is connected to the vehicle and to the external connector **127** of the base plate **120**, thereby preventing unintentional decoupling of the cable from the external connector **127** and/or the power and/or data connection within the vehicle so that the medical device **150** remains connected to the external device(s), network(s), or system(s). While the medical device **150** is docked to the docking station **100**, there is an electronic connection between the medical device **150** and the electronic connector **126** of the base plate **120**. This electrical connection allows the medical device **150** to receive electrical power from an external power source (e.g., a power source of the vehicle) and/or to communicate with the vehicle or another computing system(s) or network(s), such as the Internet.

[0051] To electrically connect the medical device **150** to the electronic connector **126** of the base plate **120**, the rescuer docks the medical device **150** to the docking station **100**. In some examples, to help position and orient the medical device **150** on the base plate **120**, the base plate **120** includes positioning guides **122** and **124**, such as shown in FIGS. **1**, **4-6**, and **14-16**. The positioning guides **122** and **124** are shaped and sized to be engaged by (e.g., received within) complimentary shaped and sized cavities defined in the bottom surface of the medical device **150**.

[0052] In the example shown in FIGS. **1**, **4-6**, and **14-16**, the positioning guide **122** is substantially oblong, is disposed on a top of the base plate, and is positioned along a first edge or side of the base plate **120** (e.g., left of the center of the base plate **120**). The positioning guide **124** is substantially circular, is disposed on the top of the base plate, and is positioned along a second edge or side of the base plate **120** (e.g., right of the center of the base plate **120**), which is opposite the first side. In some examples, both positioning guides **122** and **124** taper inwards from a base of each of the positioning guides **122**, **124** towards a top surface of each of the positioning guides **122**, **124**. The inward taper of the positioning guides **122**, **124** from the base to the top of the positioning guides **122**, **124** helps align the complimentary cavities defined in the bottom surface (or base) of the medical device **150** with the positioning guides **122**, **124**. In doing so, the medical device **150** is easily oriented and positioned on the base plate **120** in the proper position and/or orientation as the medical device **150** is docked to the docking station **100**. The ease and efficiency of placing the medical device **150** into or onto the docking station **100**, at which point the medical device **150** is coupled to external power and/or communications, reduces the amount of time spent connecting the medical device **150** to power and/or to

an external device(s) and/or system(s). In emergency situations, this docking efficiency allows the rescuer to more quickly return to focusing on the patient, because the rescuer does not have to separately connect the medical device **150** to external power and/or device(s) and/or system(s).

[0053] In some examples, the base plate **120** includes a different number of positioning guides, such as one positioning guide, or more than two positioning guides. In some examples, the positioning guides **122**, **124** have different shapes or profiles, and/or the location(s) of the positioning guides **122**, **124** on the base plate **120** differ from what is shown, or a combination thereof. In some examples, the base plate **120** does not include the positioning guides **122**, **124**.

[0054] FIGS. **7-13** illustrate various views of the medical device **150** docked to the docking station **100**. The docking mechanism **110** of the docking station **100** engages a portion of the medical device **150**, such as protrusions **152** extending from a top of the medical device **150** to dock the medical device **150** to the docking station **100**. The protrusions **152** of the medical device **150** are located on the top surface of the medical device **150** and are sized, shaped and positioned on the top surface of the medical device **150** to be engaged (e.g., grasped, hooked, etc.) by hooks **116** of the docking mechanism **110**. The handle **112** is configured to be actuated (e.g., rotated, pivoted, etc.) to raise the hooks **116** upwards and over the protrusions **152** of the medical device **150**, which disengages the docking mechanism **110** from the medical device **150** and allows the rescuer to remove the medical device **150** from the docking station **100**.

[0055] To use the docking station **100**, the rescuer inserts the medical device **150** into, or places the medical device **150** onto, the docking station **100** in an arc trajectory. For examples, the rescuer initially positions the medical device **150** at an angled orientation with respect to the base plate **120** of the docking station **100**, so that the base (or bottom surface) of the medical device **150** is positioned in the space between the arms **102b** and the legs **102c** of the frame **102**. In this orientation, a front **150a** of the medical device **150** is oriented towards the base plate **120** and/or the legs **102c**, and a rear portion **150b** of the medical device **150** is oriented towards the arms **102b** of the frame **102**. As the medical device **150** is further inserted into the docking station **100**, the base (or bottom surface) of the medical device **150** contacts the base plate **120** along the front **150a** of the medical device **150**. The medical device **150** is then tilted backwards (or towards an upright orientation) so that the medical device **150** is brought into alignment with the posts **102a** of the frame **102**. As the medical device **150** is tilted along an arc pathway backwards, the base (or bottom surface) of the medical device **150** contacts a greater area of the base plate **120**. By the rescuer continuing to rotate the medical device **150** backwards along the arc pathway, the base (or bottom surface) of the medical device **150** seats onto the positioning guides **122**, **124** of the base plate **120**, and the electronic connector **126** engages the mating electronic connector of the medical device **150**.

[0056] In some examples, as the rescuer tilts the medical device **150** backwards along the arc pathway while docking the medical device **150**, the protrusions **152** of the medical device **150** come into contact the hooks **116** disposed at the distal ends of a pair of docking arms **115** of the docking mechanism **110**. This contact between the hooks **116** and the protrusions **152** of the medical device **150** forces the docking mechanism **110** into an open position, and it forces the

hooks 116 of the docking arms 115 to be moved upwards and over the protrusion 152 of the medical device 150. The docking mechanism 110 is biased (e.g., by springs 114) to return to an engaged position once the medical device 150 is docked to the docking station 100, and this causes the docking mechanism 110 to engage (e.g., grasp, hook onto, etc.) the protrusions 152 of the medical device 150 when the hooks 116 moved past an edge (or ledge) of the protrusions 152. When the rescuer actuates (e.g., rotates, pivots, etc.) the handle 112 towards the medical device 150, the docking mechanism 110 moves into the open position and disengages from the protrusions 152 of the medical device 150 by the hooks 116 moving upwards and over the protrusions 152 of the medical device 150. When the docking mechanism 110 is in the open position, the medical device 150 is removable from the docking station 100.

[0057] FIGS. 9 and 10 show the medical device 150 with storage bags 170 and 172 coupled to the medical device 150. The storage bags 170, 172 are configured to store various accessories, sensors, consumables, and/or other items that are configured to be used with the medical device 150 to assist with monitoring or treating the patient. The docking station 100 is shaped to allow the medical device 150 to be docked to the docking station 100 with the storage bags 170, 172 coupled to respective portions of the medical device 150 because there is sufficient space to accommodate the storage bags 170, 172 while the medical device 150 is docked to the docking station 100. For example, the arms 102b and legs 102c of the frame 102 of the docking station 100 extend orthogonally from the posts 102a of the frame 102 so that the medical device 150 and the rear storage bag 172 coupled to the back of the medical device 150 fits within the space between the arms 102b, the legs 102c, and the posts 102a of the frame 102 when the medical device 150 is docked to the docking station 100. Meanwhile, the side storage bag 170 coupled to a side of the medical device 150 is disposed outside of the C-shaped frame 102 and does not interfere with any portion of the frame 102 when the medical device 150 is docked to the docking station 100. Accordingly, the rescuer does not have to remove the storage bags 170, 172 from the medical device 150 prior to docking the medical device 150 to the docking station 100, which allows the rescuer to efficiently dock the medical device 150 to the docking station 100 and remove the medical device 150 from the docking station 100 with the storage bags 170, 172 coupled to the medical device 150. In this manner, supplies and accessories are easily and efficiently transported with the medical device 150 to a patient needing care.

[0058] As shown in FIGS. 15-17, the base plate 120 includes the positioning guides 122, 124 and the electronic connector 126. The electronic connector 126 has multiple slots 128 that defined in the top and front surfaces of the electronic connector 126. The slots 128 are open and continuous across both a portion of the top surface and the front surface of the electronic connector 126. The slots 128 are evenly spaced apart in this example, although the spacing between the slots 128 can vary in alternative examples. Each of the slots 128 include spring-like electrical contacts 129 that each have two sides which are biased towards the center of a slot due to the spring-like nature. This allows the electrical contacts 129 to engage and form an electrical connection with portions of an electronic connector of the medical device 150 that are inserted within the slots 128. In other examples, some, but not all, of the slots 128 include an

electrical contact 129. In still other examples, the electrical contacts 129 are contacts for the same electrical connection, such as the power supply, or the electrical contacts 129 include electrical connections for two or more different electronic connections, such as a combination of the power supply, a communication connection, and/or other types of connections.

[0059] In some examples, the electronic connector 126 of the base plate 120 is configured to be coupled to an external device or system, such as a power source, a communication system, or both, by a cable coupled to the external connector 127 of the electronic connector 126. This coupling via the external connector 127 allows the medical device 150 to draw power from an external source, transfer data to/from an external device(s) and/or system(s), or both when the medical device 150 is docked to the docking station 100 and thereby electrically connected to the electronic connector 126 of the base plate 120. In an example, when the medical device 150 is electrically connected to the electronic connector 126, the medical device 150 automatically draws power from an external source to power the medical device 150 to charge one or more batteries of the medical device 150. In this manner, the one or more batteries of the medical device 150 are automatically charged and maintained in a substantially charged state so that the medical device 150 is ready for use as a portable device by removing the medical device 150 from the docking station 100. In some examples, the medical device 150 is configured to communicate information to the external device(s), network(s), or system(s), such as operating data, historical patient treatment data, status information, physiological data of the patient being monitored, and/or other data using the cable connected to the external connector 127 of the electronic connector 126. In some examples, the external device(s), network(s), or system(s) are configured to transfer data to the medical device 150 when the medical device 150 is docked to the docking station 100. For example, an external device(s), network(s), or system(s) are configured to provide software updates to the medical device 150, communicate information to the rescuer operating the medical device 150 (e.g., by outputting information via an output device of the medical device 150, such as a display, speakers, a printer, etc.), or other information or data to the medical device 150.

[0060] The mating electronic connector of the medical device 150 that is configured to couple to the electronic connector 126 of the base plate 120 is positioned on the back 150b of the medical device 150, such as near the lower-right corner of the back 150b of the medical device 150. The positioning of the mating electronic connector of the medical device 150 allows the mating electronic connector to engage the electronic connector 126 of the base plate 120 when the medical device 150 is docked to the docking station 100. The mating electronic connector of the medical device 150 includes blade-or planar-shaped electrical contacts that are sized, spaced, and positioned to engage (e.g., insert into) the slots 128 of the electronic connector 126 of the base plate 120. When the medical device 150 is docked to the docking station 100, the blade-shaped electrical contacts of the mating electronic connector are inserted into the slots 128 and physically contact the electrical contacts 129 of the electronic connector 126 to complete one or more electrical connections between the medical device 150 and the electronic connector 126 of the docking station 100.

[0061] In some examples, the mating electronic connector of the medical device 150 is configured to be positioned anywhere on the medical device 150 (e.g., at the top of the back 150b, at a bottom left corner of the back 150b, etc.). Accordingly, the electronic connector 126 is configured to be positioned on the docking station 100 at a position where the electronic connector 126 engages the mating electronic connector of the medical device 150 when the medical device 150 is docked to the docking station 100. In some examples, the interface between the electronic connector 126 of the docking station 100 and the mating electronic connector of the medical device 150 is different than the described blade-shaped electrical contacts. In an example, the mating electronic connector of the medical device 150 includes one or more circular conductors that interface with an electronic connector 126 having complimentary shaped circular receptacles, or vice versa.

[0062] In the configuration where the mating electronic connector of the medical device 150 includes blade-shaped electrical contacts and the electronic connector 126 includes slots 128, an electrical connection is able to be established or broken quickly, without the rescuer having to perform a complex or difficult task other than docking the medical device 150 to or removing the medical device 150 from the docking station 100. The efficiency of the electronic connection between the medical device 150 and the electronic connector 126 helps minimize delays in patient monitoring and/or treatment using the medical device 150.

[0063] In some examples, the medical device 150 is removed from the docking station 100 using a similar arc trajectory used to dock the medical device 150 to the docking station 100, but in reverse. It is to be appreciated that a sudden interruption of the electrical connection between the medical device 150 and the electronic connector 126 can cause the medical device 150 to have operating inefficiencies, such as errors caused by the sudden interruption of communication and/or power connection between the medical device 150 and an external device(s), network(s), or system(s). To minimize such inefficiencies, the medical device 150, in some examples, is configured to detect an imminent disconnection of the medical device 150 from the electronic connector 126.

[0064] In an example, one of the blade-shaped electrical contacts of the mating electronic connector of the medical device 150 is shorter and/or smaller than the other, remaining blade-shaped electrical contacts of the mating electronic connector. During decoupling of the medical device 150 from the docking station 100, the electrical connection between the shorter and/or smaller blade-shaped contact and an associated electrical contact 129 of the electronic connector 126 is broken before the electrical connections between the other, remaining blade-shaped electrical contacts and the associated electrical contacts 129 of the electronic connector 126. The interruption of the electrical connection between the smaller blade-shaped contact and the corresponding electrical contact 129 of the electronic connector 126 is sensed or detected by the medical device 150 as an indication that the electrical connection between the medical device 150 and the electronic connector 126 is about to be interrupted. The interruption of the electrical connection between the smaller blade-shaped contact and the corresponding electrical contact 129 occurs before the interruption of the electrical connection between the longer and/or larger, remaining blade-shaped contacts and the

remaining electrical contacts 129 because the medical device 150 is removed along an arced pathway, which forces the disconnection of the smaller-blade connection before the longer-blade connections are disconnected. Thus, the medical device 150 detects that one of the electrical contacts 129 is no longer coupled to a corresponding blade-shaped contact of the mating electronic connector, the medical device 150 determines that the electrical connection is about to be interrupted, and the medical device 150 performs one or more operations to prepare for the interruption of the electrical connection, and the electrical connection between the other, larger blade-shaped contacts of the mating electronic connector and the remaining electrical contacts 129 of the electronic connector 126 are usable until the interruption of the electrical connection due to the removal of the medical device 150 from the docking station 100. For example, the medical device 150 completes a data transfer and/or provides an indication that the data transfer is about to be interrupted so that the recipient of data being transferred is able to properly process or interpret the transferred data and prepare for an impending interruption (e.g., by saving data to memory, saving a progress point of the data transfer process, etc.). In some examples, in response to the imminent data interruption, the medical device 150 stores the data in memory for later transfer and prevents the data from being overwritten until the data is able to be transferred for processing, storage or both.

[0065] In another example, the medical device 150 alters or changes its configuration in response to detecting the imminent disconnection from the power connection, data connection, or both. In this example, the medical device 150 includes a touchscreen 154, such as shown in FIG. 7, which is configured to display a user interface that includes various information regarding the patient and allows the rescuer to access various functions of the medical device 150 (e.g., by interacting through touching user interface elements on the touchscreen 154). The touchscreen 154 is configured to display different user interfaces depending on the situation, such as a docked user interface and an undocked user interface, depending on whether the medical device 150 is docked to the docking station 100 or is removed therefrom. The medical device 150 is configured to automatically switch between the docked and undocked user interfaces, such as switching to the undocked user interface in response to detecting the imminent disconnection from the electronic connector 126. The docked user interface is catered to monitoring or treating the patient while the patient is being transported (e.g., in an emergency vehicle), and the undocked user interface is catered to monitoring or treating a patient at a location, such as a rescue scene or operation. The various user interface configurations are customizable, and/or the user interface configuration is automatically selected and used in response to the imminent disconnection from the electronic connector 126. This allows the rescuer to configure the docked and undocked user interfaces of the medical device 150 according to user preferences, such as allowing the rescuer to position patient information on the touchscreen 154 and to access the functions of the medical device 150 by positioning user interface elements on the touchscreen 154 at the rescuer's preferred positions. In some examples, the docked and undocked user interfaces of the medical device 150 are different depending on the type of medical device. For example, the docked and undocked user interfaces of the medical device 150 display different infor-

mation or provide the rescuer different capabilities than the docked and undocked user interfaces of a different type of medical, such as an AED or other medical device. By being able to detect the imminent disconnection of the medical device 150 from the electronic connector 126, the medical device 150 is able to configure itself automatically to better assist the rescuer and also minimize or prevent inefficiencies, such as incomplete data transfers, loss of generated data that had not yet been stored and/or transferred, and the like that otherwise affects the usability of the medical device 150.

[0066] FIG. 18 is a cutaway view of a portion of the frame 102 of the docking station 100. The cutaway view shows various components of the docking mechanism 110 within one of the arms 102b of the frame 102. The other arm 102b of the frame 102 includes similar components in a similar and mirrored arrangement. The docking arm 115 is positioned substantially along the center of the arm 102b of the frame 102. The docking arm 115 includes a hook 116 that extends beyond the arm 102b of the frame 102 at a distal end of the arm 102b. The docking arm 115 also includes a retained portion 117 that is received and/or disposed within a recess 103 defined in the rear of the post 102a of the frame 102. The retained portion 117 of the docking arm 115 is movable into and out of the recess 103, which allows the docking arm 115 to rotate and move the hook 116 upwards. The handle 112 is positioned between the arms 102b of the frame 102 and includes an axle 111 at either end of the handle 112. The axle 111 extends into the arm 102b of the frame 102 and engages a cam 113 within the arm of the frame 102. A free end 113a of the cam 113 is rounded and contacts an underside of the docking arm 115 within the arm 102b of the frame 102. When a rescuer rotates the handle 112 towards the front of the docking station 100, the free end 113a of the cam 113 is rotated upwards within the arm 102b of the frame 102, which lifts or raises the docking arm 115. The upward movement of the docking arm 115 causes the hook 116 to move upwards, and the retained portion 117 to rotate within and move further into the recess 103. The upward movement of the hook 116 caused by the rotation of the handle 112 disengages the hook 116 from the protrusions 152 of the medical device 150 to allow the medical device 150 to be removed from the docking station 100.

[0067] FIG. 18 shows a spring 114 that is coupled to the underside of the docking arm 115 and configured to bias the docking arm 115 to return to a resting position within the arm 102b of the frame 102. In some examples, the spring 114 is disposed around a stud of the docking arm 115 to counter the motion of the stud and bias the docking arm 115 towards the resting position. In the resting position, the hook 116 is in its lowermost position and engages (e.g., grasps, hooks, grabs, etc.) one of the protrusions 152 of the medical device 150 when the medical device 150 is docked to the docking station 100. When the hook 116 engages one of the protrusions 152, the medical device 150 is docked to the docking station 100.

[0068] The hook 116 of the docking arm 115 includes a sloped face 116a that tapers to a point 116b of the hook 116. The sloped face 116a of the hook 116 is configured to contact a protrusion 152 of the medical device 150 and to move upwards when the medical device 150 is docked to the docking station 100. This is due to the sloped face 116a sliding along and over the protrusion 152 as the medical device 150 is docking. Once the protrusion 152 passes

beyond the point 116b of the hook 116, the hook 116 is no longer sliding along the protrusion 152 and the hook 116 moves downwards to engage the protrusion 152 due to the bias of the spring 114 that causes the docking arm 115 to return to the resting position. In this manner, the rescuer does not have to rotate the handle 112 when placing the medical device 150 into the docking station 100 and, instead, pushes the protrusions 152 of the medical device 150 under and beyond the hooks 116 of the docking mechanism 110 to dock the medical device 150 to the docking station 100.

EXAMPLE CLAUSES

- [0069] 1. A docking station for a defibrillator, the docking station including: a frame including: a first C-shaped member including: a first post that is vertically-oriented when the docking station is upright; a first arm extending orthogonally from a top of the first post; and a first leg extending orthogonally from a bottom of the first post; and a second C-shaped member including: a second post that is vertically-oriented when the docking station is upright; a second arm extending orthogonally from a top of the first post; and a second leg extending orthogonally from a bottom of the first post; and a base plate coupled to the frame, wherein at least a portion of the base plate is positioned between the first leg and the second leg, and wherein the base plate is configured to contact a base of the defibrillator and to support the defibrillator when the defibrillator is docked to the docking station.
- [0070] 2. The docking station of clause 1, further including an electronic connector integrated with the base plate and configured to couple to the defibrillator and to provide power originating from an external power source to the defibrillator when the defibrillator is docked to the docking station.
- [0071] 3. The docking station of clause 2, wherein the electronic connector is further configured to couple the defibrillator to an external device for allowing transmission of data between the defibrillator and the external device.
- [0072] 4. The docking station of any one of clauses 1 to 3, further including a docking mechanism coupled to the frame, wherein at least a portion of the docking mechanism is positioned between the first arm and the second arm, the docking mechanism including a pair of hooks that are configured to engage a pair of protrusions disposed on a top of the defibrillator when the defibrillator is docked to the docking station.
- [0073] 5. The docking station of clause 4, wherein the docking mechanism includes a handle that is configured to be actuated, wherein actuation of the handle causes the pair of hooks to disengage from the pair of protrusions to remove the defibrillator from the docking station.
- [0074] 6. The docking station of any one of clauses 1 to 5, further including a back plate coupled to the first post and the second post, the back plate being usable to mount the docking station to a vertical surface or to couple an accessory to the backplate.
- [0075] 7. The docking station of any one of clauses 1 to 6, further including a turntable coupled to the base plate or to the first leg and the second leg, the turntable configured to allow the docking station to rotate relative to a surface on which the docking station rests.

- [0076]** 8. A docking station for a defibrillator, the docking station including: a frame including: a pair of posts that are vertically-oriented when the docking station is upright; and a pair of legs extending orthogonally from bottoms of the pair of posts; and a base plate coupled to the frame, wherein at least a portion of the base plate is positioned between the pair of legs, and wherein the base plate is configured to contact a base of the defibrillator and to support the defibrillator when the defibrillator is docked to the docking station.
- [0077]** 9. The docking station of clause 8, further including an electronic connector disposed on the base plate and configured to couple to the defibrillator and to provide power originating from an external power source to the defibrillator when the defibrillator is docked to the docking station.
- [0078]** 10. The docking station of clause 9, wherein the electronic connector is further configured to couple to a cable that supplies the power originating from the external power source.
- [0079]** 11. The docking station of any one of clauses 8 to 10, further including a docking mechanism coupled to the frame, wherein the frame further includes a pair of arms extending orthogonally from tops of the pair of posts, and wherein at least a portion of the docking mechanism is positioned between the pair of arms at distal ends of the pair of arms, the docking mechanism including a pair of hooks that are configured to engage a pair of protrusions disposed on a top of the defibrillator when the defibrillator is docked to the docking station.
- [0080]** 12. The docking station of clause 11, wherein the docking mechanism includes a handle that is configured to be actuated, wherein actuation of the handle causes the pair of hooks to disengage from the pair of protrusions to remove the defibrillator from the docking station.
- [0081]** 13. The docking station of any one of clauses 8 to 12, further including a back plate coupled to the pair of posts, the back plate being usable to mount the docking station to a vertical surface or to couple an accessory to the backplate.
- [0082]** 14. The docking station of any one of clauses 8 to 13, further including a turntable coupled to the base plate or to the pair of legs, the turntable configured to allow the docking station to rotate relative to a surface on which the docking station rests.
- [0083]** 15. A docking station for a defibrillator, the docking station including: a frame including: a middle portion that is vertically-oriented when the docking station is upright; an upper portion disposed at a top of the middle portion; and a lower portion disposed at a bottom of the middle portion; and a base plate coupled to the frame at the lower portion, the base plate configured to contact a base of the defibrillator and to support the defibrillator when the defibrillator is docked to the docking station.
- [0084]** 16. The docking station of clause 15, further including an electronic connector disposed on the base plate and configured to couple to the defibrillator and to provide power originating from an external power source to the defibrillator when the defibrillator is docked to the docking station.
- [0085]** 17. The docking station of clause 15 or 16, further including a docking mechanism coupled to the upper portion of the frame, the docking mechanism including a pair of hooks that are configured to engage a pair of protrusions disposed on a top of the defibrillator when the defibrillator is docked to the docking station.
- [0086]** 18. The docking station of clause 17, wherein the docking mechanism includes a handle that is configured to be actuated, wherein actuation of the handle causes the pair of hooks to disengage from the pair of protrusions to remove the defibrillator from the docking station.
- [0087]** 19. The docking station of any one of clauses 15 to 18, further including a back plate coupled to the middle portion of the frame, the back plate being usable to mount the docking station to a vertical surface or to couple an accessory to the backplate.
- [0088]** 20. The docking station of any one of clauses 15 to 19, further including a turntable coupled to the base plate or to the lower portion of the frame, the turntable configured to allow the docking station to rotate relative to a surface on which the docking station rests.
- [0089]** The features disclosed in the foregoing description, or the following claims, or the accompanying drawings, expressed in their specific forms or in terms of a means for performing the disclosed function, or a method or process for attaining the disclosed result, as appropriate, may, separately, or in any combination of such features, be used for realizing implementations of the disclosure in diverse forms thereof.
- [0090]** As will be understood by one of ordinary skill in the art, each implementation disclosed herein can comprise, consist essentially of or consist of its particular stated element, step, or component. Thus, the terms “include” or “including” should be interpreted to recite: “comprise, consist of, or consist essentially of.” The transition term “comprise” or “comprises” means has, but is not limited to, and allows for the inclusion of unspecified elements, steps, ingredients, or components, even in major amounts. The transitional phrase “consisting of” excludes any element, step, ingredient or component not specified. The transition phrase “consisting essentially of” limits the scope of the implementation to the specified elements, steps, ingredients or components and to those that do not materially affect the implementation. As used herein, the term “based on” is equivalent to “based at least partly on,” unless otherwise specified.
- [0091]** The terms “a,” “an,” “the” and similar referents used in the context of describing implementations (especially in the context of the following claims) are to be construed to cover both the singular and the plural, unless otherwise indicated herein or clearly contradicted by context. Recitation of ranges of values herein is merely intended to serve as a shorthand method of referring individually to each separate value falling within the range. Unless otherwise indicated herein, each individual value is incorporated into the specification as if it were individually recited herein. All methods described herein can be performed in any suitable order unless otherwise indicated herein or otherwise clearly contradicted by context. The use of any and all examples, or exemplary language (e.g., “such as”) provided herein is intended merely to better illuminate implementations of the disclosure and does not pose a limitation on the

scope of the disclosure. No language in the specification should be construed as indicating any non-claimed element essential to the practice of implementations of the disclosure.

[0092] Groupings of alternative elements or implementations disclosed herein are not to be construed as limitations. Each group member may be referred to and claimed individually or in any combination with other members of the group or other elements found herein. It is anticipated that one or more members of a group may be included in, or deleted from, a group for reasons of convenience and/or patentability. When any such inclusion or deletion occurs, the specification is deemed to contain the group as modified thus fulfilling the written description of all Markush groups used in the appended claims.

[0093] Certain implementations are described herein, including the best mode known to the inventors for carrying out implementations of the disclosure. Of course, variations on these described implementations will become apparent to those of ordinary skill in the art upon reading the foregoing description. The inventor expects skilled artisans to employ such variations as appropriate, and the inventors intend for implementations to be practiced otherwise than specifically described herein. Accordingly, the scope of this disclosure includes all modifications and equivalents of the subject matter recited in the claims appended hereto as permitted by applicable law. Moreover, any combination of the above-described elements in all possible variations thereof is encompassed by implementations of the disclosure unless otherwise indicated herein or otherwise clearly contradicted by context.

1. A system comprising:
 - a defibrillator; and
 - a docking station for the defibrillator, the docking station comprising:
 - a frame comprising:
 - a middle portion that is vertically-oriented when the docking station is upright;
 - an upper portion disposed at a top of the middle portion; and
 - a lower portion disposed at a bottom of the middle portion;
 - a base plate configured to contact a base of the defibrillator and to support the defibrillator when the defibrillator is docked to the docking station; and
 - a turntable configured to allow the docking station to rotate relative to a surface on which the turntable is disposed, the turntable being coupled to:
 - the base plate or the lower portion of the frame; and
 - the surface.
2. The system of claim 1, wherein the surface comprises a shelf, a cabinet, or a countertop.
3. The system of claim 1, wherein the turntable is permanently coupled to the surface.
4. The system of claim 1, wherein the turntable is permanently coupled to the base plate.
5. The system of claim 1, wherein the turntable comprises a locking mechanism configured to block rotation of the docking station relative to the surface.
6. The system of claim 5, wherein the locking mechanism comprises a detent corresponding to an orientation of the docking station relative to the turntable.
7. The system of claim 1, wherein the turntable is configured to allow the base plate to tilt relative to the turntable.

8. The system of claim 1, wherein the docking station further comprises:

- an electronic connector integrated with the base plate, wherein, when the defibrillator is docked to the docking station, a mating electronic connector of the defibrillator connects to the electronic connector to establish an electrical connection.

9. The system of claim 1, wherein the docking station further comprises:

- a back plate coupled to the middle portion of the frame, the back plate being usable to mount the docking station to a vertical surface or to couple an accessory to the back plate.

10. A docking station for a defibrillator, the docking station comprising:

- a base plate configured to contact a base of the defibrillator and to support the defibrillator when the defibrillator is docked to the docking station; and

- a turntable configured to:

- couple to the base plate and to a surface; and
 - allow the docking station to rotate relative to the surface.

11. The docking station of claim 10, wherein the surface comprises a shelf, cabinet, or countertop.

12. The docking station of claim 10, wherein the turntable is configured to permanently couple to the base plate and/or to the surface.

13. The docking station of claim 10, wherein the turntable comprises a locking mechanism configured to block rotation of the docking station relative to the surface.

14. The docking station of claim 13, wherein the locking mechanism comprises a detent corresponding to an orientation of the docking station relative to the turntable.

15. The docking station of claim 10, wherein the turntable is configured to allow the base plate to tilt relative to the turntable.

16. The docking station of claim 10, further comprising:

- an electronic connector integrated with the base plate, wherein, when the defibrillator is docked to the docking station, a mating electronic connector of the defibrillator connects to the electronic connector to establish an electrical connection.

17. The docking station of claim 10, further comprising:

- a lock that is configured to be actuated, wherein actuation of the lock causes the turntable to maintain an orientation of the base plate relative to the turntable.

18. A method comprising:

- receiving, at a base plate of a docking station, a base of a defibrillator, the base plate being coupled to a turntable that is coupled to a surface, the turntable being configured to allow the docking station to rotate relative to the surface;

- receiving, at the defibrillator, a force, thereby causing a rotation of the docking station relative to the surface; and

- stopping the rotation of the docking station relative to the surface by a mechanical stopper of the turntable.

19. The method of claim 18, the force being a first force, further comprising:

- receiving, at the defibrillator, a second force corresponding to a motion of a vehicle, the docking station being disposed inside the vehicle; and

- preventing the rotation of the docking station relative to the surface by a detent of the docking station.

20. The method of claim **18**, further comprising:
in response to receiving the base of the defibrillator at the
base plate of the docking station, establishing, by the
defibrillator, an electrical connection based on a con-
nection between an electronic connector of a docking
station and a mating electronic connector of the defi-
brillator.

* * * * *