

US Patent & Trademark Office

Patent Public Search | Text View

| | |
|--|------------------------------|
| United States Patent Application Publication | 20250258665 |
| Kind Code | A1 |
| Publication Date | August 14, 2025 |
| Inventor(s) | McFarland, Jr.; Stephen Paul |

TRANSPORT SENSOR DATA UPDATE

Abstract

An example operation includes one or more of detecting, by a transport, a difference between sensor data associated with a location outside the transport and data stored on the transport and updating, by the transport, the data stored on the transport with the difference.

| | |
|-------------------|---|
| Inventors: | McFarland, Jr.; Stephen Paul (Allen, TX) |
| Applicant: | TOYOTA MOTOR NORTH AMERICA, INC. (Plano, TX) |
| Family ID: | 77464350 |
| Assignee: | TOYOTA MOTOR NORTH AMERICA, INC. (Plano, TX) |
| Appl. No.: | 19/194016 |
| Filed: | April 30, 2025 |

Related U.S. Application Data

parent US continuation 17898310 20220829 parent-grant-document US 12327103 child US 19194016
parent US continuation 16805310 20200228 parent-grant-document US 11461087 child US 17898310

Publication Classification

Int. Cl.: G06F8/65 (20180101); H04L67/00 (20220101)

U.S. Cl.:

CPC G06F8/65 (20130101); H04L67/34 (20130101);

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation of U.S. patent application Ser. No. 17/898,310, filed on Aug. 29, 2022, which is a continuation of U.S. patent application Ser. No. 16/805,310, filed on Feb. 28, 2020, now U.S. Pat. No. 11,461,087, issued on Oct. 4, 2022, the entire disclosures of which are incorporated by reference herein.

TECHNICAL FIELD

[0002] This application generally relates to software updates to a transport, and more particularly, to transport sensor data updates.

BACKGROUND

[0003] Vehicles or transports, such as cars, motorcycles, trucks, planes, trains, etc., generally provide transportation needs to occupants and/or goods in a variety of ways. Functions related to transports may be identified and utilized by various computing devices, such as a smartphone or a computer.

[0004] Transports may include stored data for many purposes. In some cases, stored data may reflect operator or user configuration parameters that optimally configure various parameters for specific users. These parameters may include seat settings, temperature or environmental settings, mirror positions, entertainment preferences, or navigation parameters. Stored data may also reflect street signs/street names, detours, traffic restrictions, and normal traffic flow.

[0005] Transports may include various sensors that continually observe areas outside the transport and in proximity to the transport. These areas may include road construction, accidents, traffic re-routing/detours, or other conditions that may differ from the stored data.

SUMMARY

[0006] One example embodiment provides a method that includes one or more of receiving, by a memory on a transport, a first portion of a software update from a server, and in response to at least one device associated with the transport is proximate to the transport, receiving, by the memory, a second portion from the at least one device, performing, by a processor on the transport, the software update, and providing, by the transport, a notification of a completion of the software update to the at least one device.

[0007] Another example embodiment provides a transport that includes a processor and a memory, coupled to the processor. The memory includes instructions that when executed by the processor are configured to perform one or more of receive, by the memory, a first portion of a software update from a server. In response to at least one device associated with the transport is proximate to the transport, the memory receives a second portion from the at least one device, the processor performs the software update, and the transport provides a notification of a completion of the software update to the at least one device.

[0008] A further example embodiment provides a non-transitory computer readable medium comprising instructions, that when read by a processor, cause the processor to perform one or more of receiving, by a memory on a transport, a first portion of a software update from a server, in response to at least one device associated with the transport is proximate to the transport, receiving, by the memory, a second portion from the at least one device, performing, by a processor on the transport, the software update, and providing, by the transport, a notification of a completion of the software update to the at least one device.

[0009] One example embodiment provides a method that includes one or more of detecting, by a transport, a difference between sensor data associated with a location outside the transport and data stored on the transport and updating, by the transport, the data stored on the transport with the difference.

[0010] Another example embodiment provides a transport that includes a processor and a memory,

coupled to the processor. The memory includes instructions that when executed by the processor are configured to perform one or more of detect, by the transport, a difference between sensor data associated with a location outside the transport and data stored on the transport and update, by the transport, the data stored on the transport with the difference.

[0011] A further example embodiment provides a non-transitory computer readable medium comprising instructions, that when read by a processor, cause the processor to perform one or more of detecting, by a transport, a difference between sensor data associated with a location outside the transport and data stored on the transport and updating, by the transport, the data stored on the transport with the difference.

[0012] One example embodiment provides a method that includes one or more of receiving indications from a plurality of transports, by a server, of another transport in proximity to the plurality of transports, forming a consensus, by the server, from the indications from the plurality of transports, and transmitting, by the server, a notification to one or more of the other transport and a device associated with the other transport, in response to the consensus. Each indication includes an identifier of the other transport and an identification of one or more ways the other transport is being operated in a different manner than intended.

[0013] Another example embodiment provides a transport that includes a processor and a memory, coupled to the processor. The memory includes instructions that when executed by the processor are configured to perform one or more of receive indications from a plurality of transports of another transport in proximity to the plurality of transports, form a consensus from the indications from the plurality of transports, and transmit a notification to one or more of the other transport and a device associated with the other transport, in response to the consensus. Each indication includes an identifier of the other transport and an identification of one or more ways the other transport is being operated in a different manner than intended.

[0014] A further example embodiment provides a non-transitory computer readable medium comprising instructions, that when read by a processor, cause the processor to perform one or more of receiving indications from a plurality of transports, by a server, of another transport in proximity to the plurality of transports, forming a consensus, by the server, from the indications from the plurality of transports, and transmitting, by the server, a notification to one or more of the other transport and a device associated with the other transport. In response to the consensus, each indication includes an identifier of the other transport and an identification of one or more ways the other transport is being operated in a different manner than intended.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0015] FIG. 1A illustrates an example diagram of a transport software update, according to example embodiments.

[0016] FIG. 1B illustrates an example diagram of data discrepancy resolution for a transport, according to example embodiments.

[0017] FIG. 1C illustrates an example diagram of transport behavior observation, according to example embodiments.

[0018] FIG. 2A illustrates a transport network diagram, according to example embodiments.

[0019] FIG. 2B illustrates another transport network diagram, according to example embodiments.

[0020] FIG. 2C illustrates yet another transport network diagram, according to example embodiments.

[0021] FIG. 2D illustrates a further transport network diagram, according to example embodiments.

[0022] FIG. 2E illustrates a yet further transport network diagram, according to example embodiments.

[0023] FIG. 3A illustrates a flow diagram, according to example embodiments.
[0024] FIG. 3B illustrates another flow diagram, according to example embodiments.
[0025] FIG. 3C illustrates yet another flow diagram, according to example embodiments.
[0026] FIG. 4 illustrates a machine learning transport network diagram, according to example embodiments.
[0027] FIG. 5A illustrates an example vehicle configuration for managing database transactions associated with a vehicle, according to example embodiments.
[0028] FIG. 5B illustrates another example vehicle configuration for managing database transactions conducted among various vehicles, according to example embodiments
[0029] FIG. 6A illustrates a blockchain architecture configuration, according to example embodiments.
[0030] FIG. 6B illustrates another blockchain configuration, according to example embodiments.
[0031] FIG. 6C illustrates a blockchain configuration for storing blockchain transaction data, according to example embodiments.
[0032] FIG. 6D illustrates example data blocks, according to example embodiments.
[0033] FIG. 7 illustrates an example system that supports one or more of the example embodiments.

DETAILED DESCRIPTION

[0034] It will be readily understood that the instant components, as generally described and illustrated in the figures herein, may be arranged and designed in a wide variety of different configurations. Thus, the following detailed description of the embodiments of at least one of a method, apparatus, non-transitory computer readable medium and system, as represented in the attached figures, is not intended to limit the scope of the application as claimed but is merely representative of selected embodiments.

[0035] The instant features, structures, or characteristics as described throughout this specification may be combined in any suitable manner in one or more embodiments. For example, the usage of the phrases “example embodiments”, “some embodiments”, or other similar language, throughout least this specification refers to the fact that a particular feature, structure, or characteristic described in connection with the embodiment may be included in at one embodiment. Thus, appearances of the phrases “example embodiments”, “in some embodiments”, “in other embodiments”, or other similar language, throughout this specification do not necessarily all refer to the same group of embodiments, and the described features, structures, or characteristics may be combined in any suitable manner in one or more embodiments. In the diagrams, any connection between elements can permit one-way and/or two-way communication even if the depicted connection is a one-way or two-way arrow. In the current application, a transport may include one or more of cars, trucks, motorcycles, scooters, bicycles, boats, recreational vehicles, planes, and any object that may be used to transport people and or goods from one location to another.

[0036] In addition, while the term “message” may have been used in the description of embodiments, the application may be applied to many types of network data, such as, a packet, frame, datagram, etc. The term “message” also includes packet, frame, datagram, and any equivalents thereof. Furthermore, while certain types of messages and signaling may be depicted in exemplary embodiments they are not limited to a certain type of message, and the application is not limited to a certain type of signaling.

[0037] Example embodiments provide methods, systems, components, non-transitory computer readable media, devices, and/or networks, which provide at least one of: a transport (also referred to as a vehicle herein) a data collection system, a data monitoring system, a verification system, an authorization system and a vehicle data distribution system. The vehicle status condition data, received in the form of communication update messages, such as wireless data network communications and/or wired communication messages, may be received and processed to identify vehicle/transport status conditions and provide feedback as to the condition changes of a transport.

In one example, a user profile may be applied to a particular transport/vehicle to authorize a current vehicle event, service stops at service stations, and to authorize subsequent vehicle rental services. [0038] Within the communication infrastructure, a decentralized database is a distributed storage system, which includes multiple nodes that communicate with each other. A blockchain is an example of a decentralized database which includes an append-only immutable data structure (i.e. a distributed ledger) capable of maintaining records between untrusted parties. The untrusted parties are referred to herein as peers, nodes or peer nodes. Each peer maintains a copy of the database records and no single peer can modify the database records without a consensus being reached among the distributed peers. For example, the peers may execute a consensus protocol to validate blockchain storage entries, group the storage entries into blocks, and build a hash chain via the blocks. This process forms the ledger by ordering the storage entries, as is necessary, for consistency. In a public or permissionless blockchain, anyone can participate without a specific identity. Public blockchains can involve cryptocurrencies and use consensus based on various protocols such as proof of work (PoW). On the other hand, a permissioned blockchain database provides a system, which can secure interactions among a group of entities which share a common goal, but which do not or cannot fully trust one another, such as businesses that exchange funds, goods, information, and the like. The instant application can function in a permissioned and/or a permissionless blockchain setting.

[0039] Smart contracts are trusted distributed applications which leverage tamper-proof properties of the shared or distributed ledger (i.e., which may be in the form of a blockchain) database and an underlying agreement between member nodes which is referred to as an endorsement or endorsement policy. In general, blockchain entries are “endorsed” before being committed to the blockchain while entries, which are not endorsed are disregarded. A typical endorsement policy allows smart contract executable code to specify endorsers for an entry in the form of a set of peer nodes that are necessary for endorsement. When a client sends the entry to the peers specified in the endorsement policy, the entry is executed to validate the entry. After validation, the entries enter an ordering phase in which a consensus protocol is used to produce an ordered sequence of endorsed entries grouped into blocks.

[0040] Nodes are the communication entities of the blockchain system. A “node” may perform a logical function in the sense that multiple nodes of different types can run on the same physical server. Nodes are grouped in trust domains and are associated with logical entities that control them in various ways. Nodes may include different types, such as a client or submitting-client node which submits an entry-invocation to an endorser (e.g., peer), and broadcasts entry-proposals to an ordering service (e.g., ordering node). Another type of node is a peer node which can receive client submitted entries, commit the entries and maintain a state and a copy of the ledger of blockchain entries. Peers can also have the role of an endorser, although it is not a requirement. An ordering-service-node or orderer is a node running the communication service for all nodes, and which implements a delivery guarantee, such as a broadcast to each of the peer nodes in the system when committing entries and modifying a world state of the blockchain, which is another name for the initial blockchain entry, which normally includes control and setup information.

[0041] A ledger is a sequenced, tamper-resistant record of all state transitions of a blockchain. State transitions may result from smart contract executable code invocations (i.e., entries) submitted by participating parties (e.g., client nodes, ordering nodes, endorser nodes, peer nodes, etc.). An entry may result in a set of asset key-value pairs being committed to the ledger as one or more operands, such as creates, updates, deletes, and the like. The ledger includes a blockchain (also referred to as a chain) which is used to store an immutable, sequenced record in blocks. The ledger also includes a state database, which maintains a current state of the blockchain. There is typically one ledger per channel. Each peer node maintains a copy of the ledger for each channel of which they are a member.

[0042] A chain is an entry log, which is structured as hash-linked blocks, and each block contains a

sequence of N entries where N is equal to or greater than one. The block header includes a hash of the block's entries, as well as a hash of the prior block's header. In this way, all entries on the ledger may be sequenced and cryptographically linked together. Accordingly, it is not possible to tamper with the ledger data without breaking the hash links. A hash of a most recently added blockchain block represents every entry on the chain that has come before it, making it possible to ensure that all peer nodes are in a consistent and trusted state. The chain may be stored on a peer node file system (i.e., local, attached storage, cloud, etc.), efficiently supporting the append-only nature of the blockchain workload.

[0043] The current state of the immutable ledger represents the latest values for all keys that are included in the chain entry log. Because the current state represents the latest key values known to a channel, it is sometimes referred to as a world state. Smart contract executable code invocations execute entries against the current state data of the ledger. To make these smart contract executable code interactions efficient, the latest values of the keys may be stored in a state database. The state database may be simply an indexed view into the chain's entry log, it can therefore be regenerated from the chain at any time. The state database may automatically be recovered (or generated if needed) upon peer node startup, and before entries are accepted.

[0044] A blockchain is different from a traditional database in that the blockchain is not a central storage but rather a decentralized, immutable, and secure storage, where nodes must share in changes to records in the storage. Some properties that are inherent in blockchain and which help implement the blockchain include, but are not limited to, an immutable ledger, smart contracts, security, privacy, decentralization, consensus, endorsement, accessibility, and the like.

[0045] Example embodiments provide a way for providing a vehicle service to a particular vehicle and/or requesting user associated with a user profile that is applied to the vehicle. For example, a user may be the owner of a vehicle or the operator of a vehicle owned by another party. The vehicle may require service at certain intervals and the service needs may require authorization prior to permitting the services to be received. Also, service centers may offer services to vehicles in a nearby area based on the vehicle's current route plan and a relative level of service requirements (e.g., immediate, severe, intermediate, minor, etc.). The vehicle needs may be monitored via one or more sensors which report sensed data to a central controller computer device in the vehicle, which in turn, is forwarded to a management server for review and action.

[0046] A sensor may be located on one or more of the interior of the transport, the exterior of the transport, on a fixed object apart from the transport, and on another transport near to the transport. The sensor may also be associated with the transport's speed, the transport's braking, the transport's acceleration, fuel levels, service needs, the gear-shifting of the transport, the transport's steering, and the like. The notion of a sensor may also be a device, such as a mobile device. Also, sensor information may be used to identify whether the vehicle is operating safely and whether the occupant user has engaged in any unexpected vehicle conditions, such as during the vehicle access period. Vehicle information collected before, during and/or after a vehicle's operation may be identified and stored in a transaction on a shared/distributed ledger, which may be generated and committed to the immutable ledger as determined by a permission granting consortium, and thus in a “decentralized” manner, such as via a blockchain membership group.

[0047] Each interested party (i.e., company, agency, etc.) may want to limit the exposure of private information, and therefore the blockchain and its immutability can limit the exposure and manage permissions for each particular user vehicle profile. A smart contract may be used to provide compensation, quantify a user profile score/rating/review, apply vehicle event permissions, determine when service is needed, identify a collision and/or degradation event, identify a safety concern event, identify parties to the event and provide distribution to registered entities seeking access to such vehicle event data. Also, the results may be identified, and the necessary information can be shared among the registered companies and/or individuals based on a “consensus” approach associated with the blockchain. Such an approach could not be implemented on a traditional

centralized database.

[0048] Every autonomous driving system is built on a whole suite of software and an array of sensors. Machine learning, lidar projectors, radar, and ultrasonic sensors all work together to create a living map of the world that a self-driving car can navigate. Most companies in the race to full autonomy are relying on the same basic technological foundations of lidar+radar+cameras+ultrasonic, with a few notable exceptions.

[0049] In another embodiment, GPS, maps and other cameras and sensors are used in autonomous vehicles without lidar as lidar is often viewed as being expensive and unnecessary. Researchers have determined that stereo cameras are a low-cost alternative to the more expensive lidar functionality.

[0050] The instant application includes, in certain embodiments, authorizing a vehicle for service via an automated and quick authentication scheme. For example, driving up to a charging station or fuel pump may be performed by a vehicle operator and the authorization to receive charge or fuel may be performed without any delays provided the authorization is received by the service station. A vehicle may provide a communication signal that provides an identification of a vehicle that has a currently active profile linked to an account that is authorized to accept a service which can be later rectified by compensation. Additional measures may be used to provide further authentication, such as another identifier may be sent from the user's device wirelessly to the service center to replace or supplement the first authorization effort between the transport and the service center with an additional authorization effort.

[0051] Data shared and received may be stored in a database, which maintains data in one single database (e.g., database server) and generally at one particular location. This location is often a central computer, for example, a desktop central processing unit (CPU), a server CPU, or a mainframe computer. Information stored on a centralized database is typically accessible from multiple different points. A centralized database is easy to manage, maintain, and control, especially for purposes of security because of its single location. Within a centralized database, data redundancy is minimized as a single storing place of all data also implies that a given set of data only has one primary record.

[0052] FIG. 1A illustrates an example diagram of a transport software update **100**, according to example embodiments. The present application discloses a software update for a transport or vehicle **104**. The software update may include a first portion **116** for the transport **104** and a second portion **120A/120B** through one or more occupant devices **124** of the transport **104**. The second portion **120B** may be transferred to the transport **104** from the one or more occupant devices **124** in response to the one or more occupant devices **124** being in proximity to the transport **104**. In response to the software update completed, a notification may be sent to the one or more occupant devices **124**.

[0053] The application solves a potential security problem with transport **104** software updates by allocating a portion **120A/120B** of a software update to a user device **124** associated with a transport **104**. When the user device **124** moves within proximity of the transport **104**, the portion **120B** on the user device **124** may be transferred to the transport **104**, which may then install the complete software update **116/120B**. This also puts the user of the user device **124** in the loop and may allow human approval to perform the software update. By dividing the software update into multiple parts **116/120A/120B**, any one part being compromised or corrupted may not alter, invalidate, or change the entire software update.

[0054] A software update may be divided into multiple parts, including at least a first portion software update **116** and a second portion software update **120A/120B**. The first portion software update **116** may be related to different function software application(s), data structure(s), and metadata for the transport **104**. For example, in one embodiment the first portion software update **116** may include engine and emission controls while the second portion software update **120A/120B** may include new programming choices for a satellite-based entertainment system. A

server **112** transmits the first portion of a software update **116** to a transport or vehicle **104**. The first portion software update **116** may be transmitted over any wireless communication technology including but not limited to BLUETOOTH, WI-FI, or a cellular data connection such as 3G/4G/5G or LTE. In some embodiments, the first portion software update **116** may be communicated to the transport **104** through a hardware means such as an SD card or USB dongle. The transport or vehicle **104** may include several processors, and the software update may run on a single processor, two or more processors, or all processors. The software update includes at least two portions, with the first portion being transferred directly to the transport **104**. The transport **104** may also include one or more memories, transceivers, receivers, and sensors to allow for the software update to be received.

[0055] The server **112** also transfers, either at the same time as the first portion **116** or at a later time, a second portion of the software update **120A** to a user device **124** associated with the transport **124**. The user device **124** may be associated with a user, who may also be associated with the transport **104**. In other embodiments, a third or more software update (not shown) may be transmitted to other user devices (not shown), which either do or do not cooperate to transfer those portions to the transport **104**. In other embodiments, the third or more software update may also be transferred to the user device **124**, so that the user device **124** receives multiple portions of the software update. In other embodiments, the transport **104** may determine one or more (other) compatible transports in proximity to the transport **104** and transfer one or more portions to the one or more compatible transports. This may allow portions to be distributed to other transports that may use all or part of the software update. The transport **104**, in some embodiments, may determine that the transport **104** uses a same or newer version of the first portion software update **116**. In response, the transport **104** may notify the server **112** that the first portion software update **116** may not be installed.

[0056] When the user device **124** moves within proximity to the transport **128**, the user device **124** transfers the second portion of the software update **120B** to the transport or vehicle **104**. The proximity **128** may be related to a wireless communication range between the user device **124** and the transport **104**. In one embodiment, after the user device **124** receives the second portion of the software update **120A**, the user device **124** wirelessly emits a beacon signal on a random, one-time, or continuous basis. The user device **124** monitors for a response from the transport **104**. After receiving the response from the transport **104**, the user device **124** wirelessly transmits the second portion of the software update **120B** to the transport **104**. In other embodiments, the user device **124** may transmit an SMS message, an email, or make a call to a phone device associated with the transport **104**. The transport **104** then responds in similar or different fashion to the user device **124**, when enables the user device **124** to wirelessly transmit the second portion of the software update **120B** to the transport **104**.

[0057] In another embodiment, the proximity **128** may be related to a geofence. In another embodiment, the proximity **128** may be related to a location either the user device **124** or transport **104** is at. In other embodiments, a third or more software update (not shown) may be transmitted from other user devices (not shown), which either do or do not cooperate to transfer those portions to the transport **104**. In other embodiments, a third or more software update **120** may also be transferred from the user device **124**, so that the user device transfers multiple portions of the software update to the transport or vehicle **104**. In some embodiments, a master software update to the transport **104** may include first, second, and third portions, where the third portion updates one or more occupant devices of a different type than occupant device(s) **124** receiving the second portion of software update **120A**. This may allow different types of occupant devices such as iPhones, Android devices, and tablets or notebook computers running different operating systems to be concurrently updated. In some embodiments, the second portion received by the one or more devices may include a second portion of the software update itself. In one embodiment, a user device **124** may receive second **120A/120B** and third portions of a software update. One of the

second **120A/120B** and third portions of the software update may be usable by the user device **124**, while the other of the second and third portions are intended for a different device. In that case, the user device **124** may first determine it can communicate with the different device. After making that determination, the user device **124** may then transfer the other of the second and third portions to the different device. Communication may be determined by any known methods including a beacon or other wireless signal, sending a SMS message, email, or making a cellular phone call. [0058] In one embodiment, the transport **104** may validate one or more portions of the software update after the transport **104** has received them, in order to ensure the integrity of the software update and a reliable update process. Received portions of software updates may be stored in one or more memory devices of the transport **104**. In one embodiment, a transport **104** may have several computers or processors for different functions, and each computer or processor may have one or more associated memory devices. Each received portion of a software update may include an identifier that the transport **104** reads in order to determine which memory device to store the portion to. The identifier may also include a memory range that specifies a location in the memory for storing the software update portion. In another embodiment, the transport **104** validates the entire software update after all portions have been received. Validation may include any of integrity checking, combining, compiling, version checking, storing, or any other action performed on the software update or software update portions by one or more computers of the transport **104**. [0059] In one embodiment, the transport **104** may install the complete software update after all portions have been received. Installation may include parsing the complete software update into portions, associating each portion with a memory device and/or a location in a memory, and storing each portion into an appropriate memory device and/or location. In another embodiment, the transport **104** installs at least the first portion **116** when it receives it, and may store one or more other portions until all portions of the software update have been received. In another embodiment, the transport **104** installs each portion (regardless of how many portions) when it receives it. Once the user device **124** has transferred the second (or third, etc) portion(s) of the software update **120** to the transport **104**, the transport **104** provides a completion notification **132** to the user device **124**. In another embodiment, the transport **104** may provide a completion notification **132** to acknowledge receipt of all portions and/or successful installation of the complete software update (all portions). The completion notification **132** may include an SMS message, an email, an image, or a video that informs the user of the user device **124** that the software update has been completed. In another embodiment, the transport **104** may display a notification of completion of the software update on a display associated with the transport **104** and/or provide an audio notification of completion of the software update.

[0060] FIG. **1B** illustrates an example diagram of data discrepancy resolution for a transport **140**, according to example embodiments. Transports or vehicles **104** may include sensors including cameras, radar, lidar, or other items that sense location areas outside and in proximity to the transport **104**. Sensors obtain sensor data **144** of these outside items. Sensor data **144** may include camera images of a traffic accident, construction, one or more signs, and/or a road or traffic condition. The transport **104** may identify one or more objects at the location from the sensor data **144**. It may identify the objects using image interpretation software, pattern matching, optical character recognition (OCR), and comparison to satellite or other data. In one embodiment, the sensor data **144** may include one or more of a camera image, a notification from a transport entertainment system, and drivetrain sensor data.

[0061] In some cases, transports **104** have stored sensor data that is stored on the transport **104**. Stored sensor data may include text, images, video, or various data items. When the transport **104** receives new sensor data **144** at a location, it checks to see if the received sensor data **144** is the same as stored sensor data. Identified objects are compared to stored data on the transport **104**. If the received sensor data **144** is the same as the stored sensor data, the transport **104** continues to receive and evaluate sensor data **144**. However, in some cases, the transport **104** may detect a

difference between the stored and received **144** sensor data. In that case, the transport **104** may update the data stored on the transport **104** with the received sensor data **144**, and transmits a request including the received sensor data **144** or the difference **148** to a server **112**. Differences **148** may include camera images of a traffic accident, construction, one or more signs, and/or a road or traffic condition. In one embodiment, the transport **104** may determine the stored data includes one or more elements that correspond to the difference **148** between the stored data and the sensor data **144**, and updates the one or more elements with the difference **148**. The request may include an identification of the transport **104**, a current software level of the transport **104**, and a difference between the current software level and the latest software update. The latest software update may include a software application and one or more of release notes for the latest software update and an installation application.

[0062] In one embodiment, providing a request including the sensor data **144** or difference **148** to a server **112** may include generating, by the transport **104**, a blockchain transaction to the server **112**. The server **112**, the transport **104**, and/or the other transports **108A**, **108B** may be one of nodes or peers of a blockchain network. The server **112** may also store any of the sensor data **144**, the difference **148**, and/or the patch **152** to a shared ledger of the blockchain network.

[0063] The server **112** receives the request, and creates a patch **152** including the sensor data **144** or the difference **148**. The patch **152** may be used to update the stored sensor data in transports. The server **112** transmits the patch **152** to other transports **108** in proximity to the location where the difference was first identified. Any number of transports **108** may receive the patch **152**, and FIG. **1B** illustrates two transports **108A** and **108B** that receive the patch **152**. In another embodiment, the transport **104** that identified the difference may also receive the patch **152**. In some embodiments, a patch **152** may include other stored data updates, including permanent changes or differences reported by other transports **108**. In some embodiments, a transport **104**, **108A**, **108B** may display information related to a received patch **152**. The displayed information may include one or more of a patch **152** name, a version number, a date, a compatible transports list, a size of the patch **152**, or the contents of the patch **152** itself. The contents may include one or more images, videos, text items, or data items.

[0064] In one embodiment, updating the transport **104** with the latest software update may include identifying one or modules within the latest software update; associating the one or more modules with the sensor data **144**; and updating one or more of an application and a data structure with the one or more modules. In one embodiment, the server **112** may provide the patch **152** live to other transports **108** that enter proximity range to the location, for example within a mile of the location.

[0065] In another embodiment, the sensor data **144** and differences **148** may reflect reverse cases such as a cleared traffic accident, a pothole or other road damage repaired, road barriers removed—in other words a temporary condition that becomes cleared. The stored data in such cases may be immediately updated to reflect the cleared condition, possibly without generating the request and a patch **152** being issued.

[0066] In another embodiment, a transport **104** or a server **112** may determine the differences **148** between the sensor data **144** and the stored data as before, but is able to estimate a time to clear based on the differences **148**. The time to clear may be determined by comparing the sensor data **144** to a series of stored images that display different traffic accidents or road repair of varying “severity”, each with an associated repair time. By matching a closest stored image/repair time to the sensor data **144**, a most likely repair time may be determined. In one embodiment, the transport **104** may provide the estimated repair time to the server **112** or other transports **108A**, **108B** in proximity to the location. The other transports **108A**, **108B** may be able to take advantage of this information by delaying starting out until the repair or accident is cleared, or taking a different route that bypasses the location.

[0067] For example, one or more sensor(s) of a transport **104** may detect a new street sign in a new neighborhood. The street sign may have been just recently installed, and may reflect a new street

name. The transport **104** may include a navigation computer that includes various maps including streets and street names. When the sensor(s) observe the new street name ("Main Street"), the transport **104** may check its' stored data to see if the street name is present. Because the stored data was installed to the transport **104** before the street name was assigned, the new street name is not found in the stored data. Therefore, the street name at the location becomes a difference **148** that the transport **104** sends to the server **112**. The server **112** then creates a patch **152** that includes the new street name (and possibly other differences **148** received since a previous patch **152** was issued), and distributes the patch **152** including the new street name to other transports **108A**, **108B** that are in proximity to the transport **104** when it first observed the street name. The other transports **108A**, **108B**, in response, update their own stored data to include the patch **152** and the new street name.

[0068] FIG. **1C** illustrates an example diagram of transport behavior observation **160**, according to example embodiments. Transports **104** include various sensors, including cameras, that may observe other transports **108** in proximity. In most embodiments, "in proximity" means within a line of sight of the transport **104**, and preferably close enough to observe details of the other transport **108** and how it is being operated. A transport's behavior relates to how it is being operated, and includes a transport's speed, acceleration, traction in weather, handling, seating capacity, load carrying capacity, towing capacity, and the like. Transports have performance characteristics that depend on the design of a transport, its intended use, price, and region where purchased. A transport's performance may also be related to characteristics of a driver-such as a driver's eyesight, reaction time, confidence, and driving ability. Thus, a transport's actual performance is a combination of both a transport's automotive characteristics and performance and a driver's characteristics. In some embodiments, the performance of a transport is limited by automotive characteristics of the transport itself, while in other embodiments, the performance of a transport is limited by limitations of the driver. In yet other embodiments, the performance of a transport may be limited by both automotive characteristics of the transport and by limitations of the driver.

[0069] Multiple transports **104**, identified as transport or vehicle **104A** and transport or vehicle **104B**, are in proximity to another transport **108**. Each of the transports **104A**, **104B**, **108** may be a same or different type. In FIG. **1C**, transports **104** are passenger vehicles while transport **108** is a pickup truck towing a large 5th-wheel trailer. Each of the transports **104A**, **104B** includes side-vision cameras that observe the transport **108**. Transport **104A** observes the other transport **164A** and transport **104B** observes the other transport **164B**.

[0070] Each transport **104A**, **104B** independently observes **164A**, **164B** how the other transport **108** is being operated, as described previously, and makes a determination the other transport **108** is not being operated as intended. The determination may be that the other transport **108** is overloaded in some fashion, the other transport **108** is in obvious need of repair (emitting a very excessive amount of exhaust smoke, for example), the other transport **108** is being accelerated too slowly, has improper tire pressure in one or more tires, has one or more blocked mirrors, or is being operated in any other fashion that may be not as the other transport **108** was intended to operate. Once the transport **104A**, **104B** makes this determination, the transport **104A**, **104B** provides an indication or transaction **168** to a server **112**. In one embodiment, each transport **104A**, **104B** examines itself using the same behavior criteria as the other transport **108**, and provides a notification to itself or a device associated with the transport **104** similar to what would be provided to the other transport **108**, as described herein.

[0071] The indication or transaction **168** (i.e. indication or transaction **168A** from transport **104A** and indication or transaction **168B** from transport **104B**) provides an identification of the other transport **108** as well as a behavior of the other transport **108** not as intended. The identification of the other transport **108** may include a camera image, a Vehicle ID Number (VIN Number), a license plate number, a state of registration (either the US state where the vehicle is registered as

well as an indication if the registration is current), and/or a physical description (i.e. model year, manufacturer, model, color, etc) of an exterior of the other transport **108**. The identification allows the server **112** to uniquely identify the other transport **108** from all other transports **104**, **108** so that a notification **172** may be sent to the other transport **108** or a device associated with the other transport **108**.

[0072] In one embodiment, indications **168A**, **168B** are blockchain transactions, where a blockchain network includes the transports **104A**, **104B** and the server **112**. The blockchain transactions **168A**, **168B** provide information to the server **112** and are stored to a shared ledger associated with the blockchain network.

[0073] In another embodiment, a transport **104** may identify one or more other transports **108** that use a software module, and obtain a current software level for the software module from one or more other transports **108**. In response to determining the current software level from another transport **108** is more recent than a current software level for the other transport **108**, the transport **104** may request the more recent software update from another transport **108**, install the more recent software update, and in response to the transport **104** determines the current software level from another transport **108** is older than the current software level for the other transport **108**, the transport **104** transfers a software update corresponding to the current software level for the other transport **108** to another transport **108** that includes an older software level.

[0074] The server **112** receives the indications or transactions **168** from multiple transports or vehicles **104**. Although two such transports or vehicles **104A**, **104B** are shown in FIG. **1C**, there may be any number of transports **104** providing such information as long as two or more transports **104** are involved. The server **112** forms a consensus after receiving indications or transactions **168** from multiple transports **104**. In one embodiment, the server **112** forms a first consensus after receiving multiple indications or transactions **168**, and performs additional consensus after receiving a next following indication or transaction **168**. Each of the received indications or transactions **168** used for a consensus must apply to a same other transport **108**. In one embodiment, a consensus may be formed if a majority of the received indications or transactions **168** apply to a same other transport **108**. In another embodiment, a consensus may be formed if a majority of the received indications or transactions **168** apply to a same other transport **108**, and a same behavior is identified. In another embodiment, a same behavior may be identified by multiple transports **104** prior to forming the consensus. In one embodiment, the server **112** matches a behavior pattern associated with the other transport **108** to a different type of transport than the other transport **108** and/or a different way of operating the other transport **108**. For a blockchain network, a consensus may be performed by a majority of validating nodes or peers.

[0075] Once a consensus has been performed by the server **112**, the server **112** transmits a notification **172** to the other transport **108** and/or one or more devices (such as cell phones/smart phones) associated with the other transport **108**. The notification **172** may provide information about the behavior not as intended, how to correct the behavior not as intended, a new other transport **108** type or description, or a proposed change or modification to the other transport **108**. In one embodiment, the notification **172** may include a different type of transport than the other transport **108** and/or a different way of operating the other transport **108**. For example, the notification **172** may indicate the other transport **108** may be overloaded, encourage a driver of the other transport **108** to remove cargo or passengers from the other transport **108**, recommend and upgrade to a newer or different transport **108** type with higher load capacity, or recommend the other transport **108** driver to select a different transmission gear ratio on a control of the other transport **108**. In one embodiment, the notification **172** may include an upgrade recommendation for the other transport **108**, including a feature or software upgrade. In another embodiment, the notification **172** may include a downgrade recommendation for the other transport **108**, including a feature or software downgrade.

[0076] FIG. **2A** illustrates a transport network diagram **200**, according to example embodiments.

The network comprises elements including a transport node **202** including a processor **204**, as well as a transport node **202'** including a processor **204'**. The transport nodes **202**, **202'** communicate with one another via the processors **204**, **204'**, as well as other elements (not shown) including transceivers, transmitters, receivers, storage, sensors and other elements capable of providing communication. The communication between the transport nodes **202**, **202'** can occur directly, via a private and/or a public network (not shown) or via other transport nodes and elements comprising one or more of a processor, memory, and software. Although depicted as single transport nodes and processors, a plurality of transport nodes and processors may be present. One or more of the applications, features, steps, solutions, etc., described and/or depicted herein may be utilized and/or provided by the instant elements.

[0077] FIG. 2B illustrates another transport network diagram **210**, according to example embodiments. The network comprises elements including a transport node **202** including a processor **204**, as well as a transport node **202'** including a processor **204'**. The transport nodes **202**, **202'** communicate with one another via the processors **204**, **204'**, as well as other elements (not shown) including transceivers, transmitters, receivers, storage, sensors and other elements capable of providing communication. The communication between the transport nodes **202**, **202'** can occur directly, via a private and/or a public network (not shown) or via other transport nodes and elements comprising one or more of a processor, memory, and software. The processors **204**, **204'** can further communicate with one or more elements **230** including sensor **212**, wired device **214**, wireless device **216**, database **218**, mobile phone **220**, transport node **222**, computer **224**, I/O device **226** and voice application **228**. The processors **204**, **204'** can further communicate with elements comprising one or more of a processor, memory, and software.

[0078] Although depicted as single transport nodes, processors and elements, a plurality of transport nodes, processors and elements may be present. Information or communication can occur to and/or from any of the processors **204**, **204'** and elements **230**. For example, the mobile phone **220** may provide information to the processor **204** which may initiate the transport node **202** to take an action, may further provide the information or additional information to the processor **204'** which may initiate the transport node **202'** to take an action, may further provide the information or additional information to the mobile phone **220**, the transport node **222**, and/or the computer **224**. One or more of the applications, features, steps, solutions, etc., described and/or depicted herein may be utilized and/or provided by the instant elements.

[0079] FIG. 2C illustrates yet another transport network diagram **240**, according to example embodiments. The network comprises elements including a transport node **202** including a processor **204** and a non-transitory computer readable medium **242C**. The processor **204** is communicably coupled to the computer readable medium **242C** and elements **230** (which were depicted in FIG. 2B).

[0080] The processor **204** performs one or more of the following steps. At step **244C**, the transport memory receives a first portion of a software update from a server. The software update includes at least two portions. The first portion is transferred to the transport by the server, and a second portion is provided to a user device. At step **246C**, the transport memory receives a second portion of the software update from a user device in proximity to the transport. At step **248C**, a transport processor performs the software update. Finally, at step **250C**, the transport provides notification of completion of the software update.

[0081] FIG. 2D illustrates yet another transport network diagram **260**, according to example embodiments. The network comprises elements including a transport node **202** including a processor **204** and a non-transitory computer readable medium **242D**. The processor **204** is communicably coupled to the computer readable medium **242D** and elements **230** (which were depicted in FIG. 2B).

[0082] The processor **204** performs one or more of the following steps. At step **244D**, the transport detects a difference between inside and outside sensor data. The inside data is data stored on the

transport, while the outside data is sensor data reflecting the environment outside the transport. At step **246D**, the transport updates the data stored on the transport with the difference. In one embodiment, the transport transmits a request including the sensor data to a server. The server then creates a patch including the sensor data, and transmits the patch to other transports in proximity to a location outside the transport.

[0083] FIG. **2E** illustrates yet another transport network diagram **270**, according to example embodiments. The network comprises elements including a transport node **202** including a processor **204** and a non-transitory computer readable medium **242E**. The processor **204** is communicably coupled to the computer readable medium **242E** and elements **230** (which were depicted in FIG. **2B**).

[0084] The processor **204** performs one or more of the following steps. At step **244E**, a server receives one or more indications of another transport operated in a different manner than intended. The indications include an identifier of the other transport and an identification of one or more ways the other transport is being operated in a different manner than intended. At step **246E**, the server forms a consensus from the received indications. At step **248E**, the server transmits a notification to other transports and a device associated with the other transport. The notification may provide a recommendation or suggestion of an alternate type of transport.

[0085] The processors and/or computer readable media may fully or partially reside in the interior or exterior of the transport nodes. The steps or features stored in the computer readable media may be fully or partially performed by any of the processors and/or elements in any order. Additionally, one or more steps or features may be added, omitted, combined, performed at a later time, etc.

[0086] FIG. **3A** illustrates a flow diagram **300**, according to example embodiments. Referring to FIG. **3A**, at block **302**, the transport memory receives a first portion of a software update from a server. The software update includes at least two portions. The first portion is transferred to the transport by the server, and a second portion is provided to a user device. At block **304**, the transport memory receives a second portion of the software update from a user device in proximity to the transport. At block **306**, a transport processor performs the software update. Finally, at block **308**, the transport provides notification of completion of the software update.

[0087] FIG. **3B** illustrates another flow diagram **320**, according to example embodiments.

[0088] Referring to FIG. **3B**, at block **322**, the transport detects a difference between inside and outside sensor data. The inside data is data stored on the transport, while the outside data is sensor data reflecting the environment outside the transport. At block **324**, the transport updates the data stored on the transport with the difference. In one embodiment, the transport transmits a request including the sensor data to a server. The server then creates a patch including the sensor data, and transmits the patch to other transports in proximity to a location outside the transport.

[0089] FIG. **3C** illustrates yet another flow diagram **340**, according to example embodiments. Referring to FIG. **3C**, at block **342**, a server receives one or more indications of another transport operated in a different manner than intended. The indications include an identifier of the other transport and an identification of one or more ways the other transport is being operated in a different manner than intended. At block **344**, the server forms a consensus from the received indications. Finally, at block **346**, the server transmits a notification to other transports and a device associated with the other transport. The notification may provide a recommendation or suggestion of an alternate type of transport.

[0090] FIG. **4** illustrates a machine learning transport network diagram **400**, according to example embodiments. The network **400** includes a transport node **402** that interfaces with a machine learning subsystem **406**. The transport node includes one or more sensors **404**.

[0091] The machine learning subsystem **406** contains a learning model **408** which is a mathematical artifact created by a machine learning training system **410** that generates predictions by finding patterns in one or more training data sets. In some embodiments, the machine learning subsystem **406** resides in the transport node **402**. In other embodiments, the machine learning

subsystem **406** resides outside of the transport node **402**.

[0092] The transport node **402** sends data from the one or more sensors **404** to the machine learning subsystem **406**. The machine learning subsystem **406** provides the one or more sensor **404** data to the learning model **408** which returns one or more predictions. The machine learning subsystem **406** sends one or more instructions to the transport node **402** based on the predictions from the learning model **408**.

[0093] In a further embodiment, the transport node **402** may send the one or more sensor **404** data to the machine learning training system **410**. In yet another embodiment, the machine learning subsystem **406** may sent the sensor **404** data to the machine learning subsystem **410**. One or more of the applications, features, steps, solutions, etc., described and/or depicted herein may utilize the machine learning network **400** as described herein.

[0094] FIG. 5A illustrates an example vehicle configuration **500** for managing database transactions associated with a vehicle, according to example embodiments. Referring to FIG. 5A, as a particular transport/vehicle **525** is engaged in transactions (e.g., vehicle service, dealer transactions, delivery/pickup, transportation services, etc.), the vehicle may receive assets **510** and/or expel/transfer assets **512** according to a transaction(s). A transport processor **526** resides in the vehicle **525** and communication exists between the transport processor **526**, a database **530**, a transport processor **526** and the transaction module **520**. The transaction module **520** may record information, such as assets, parties, credits, service descriptions, date, time, location, results, notifications, unexpected events, etc. Those transactions in the transaction module **520** may be replicated into a database **530**. The database **530** can be one of a SQL database, an RDBMS, a relational database, a non-relational database, a blockchain, a distributed ledger, and may be on board the transport, may be off board the transport, may be accessible directly and/or through a network, or be accessible to the transport.

[0095] FIG. 5B illustrates an example vehicle configuration **550** for managing database transactions conducted among various vehicles, according to example embodiments. The vehicle **525** may engage with another vehicle **508** to perform various actions such as to share, transfer, acquire service calls, etc. when the vehicle has reached a status where the services need to be shared with another vehicle. For example, the vehicle **508** may be due for a battery charge and/or may have an issue with a tire and may be in route to pick up a package for delivery. A transport processor **528** resides in the vehicle **508** and communication exists between the transport processor **528**, a database **554**, a transport processor **528** and the transaction module **552**. The vehicle **508** may notify another vehicle **525** which is in its network and which operates on its blockchain member service. A transport processor **526** resides in the vehicle **525** and communication exists between the transport processor **526**, a database **530**, the transport processor **526** and a transaction module **520**. The vehicle **525** may then receive the information via a wireless communication request to perform the package pickup from the vehicle **508** and/or from a server (not shown). The transactions are logged in the transaction modules **552** and **520** of both vehicles. The credits are transferred from vehicle **508** to vehicle **525** and the record of the transferred service is logged in the database **530/554** assuming that the blockchains are different from one another, or, are logged in the same blockchain used by all members. The database **554** can be one of a SQL database, an RDBMS, a relational database, a non-relational database, a blockchain, a distributed ledger, and may be on board the transport, may be off board the transport, may be accessible directly and/or through a network.

[0096] FIG. 6A illustrates a blockchain architecture configuration **600**, according to example embodiments. Referring to FIG. 6A, the blockchain architecture **600** may include certain blockchain elements, for example, a group of blockchain member nodes **602-606** as part of a blockchain group **610**. In one example embodiment, a permissioned blockchain is not accessible to all parties but only to those members with permissioned access to the blockchain data. The blockchain nodes participate in a number of activities, such as blockchain entry addition and

validation process (consensus). One or more of the blockchain nodes may endorse entries based on an endorsement policy and may provide an ordering service for all blockchain nodes. A blockchain node may initiate a blockchain action (such as an authentication) and seek to write to a blockchain immutable ledger stored in the blockchain, a copy of which may also be stored on the underpinning physical infrastructure.

[0097] The blockchain transactions **620** are stored in memory of computers as the transactions are received and approved by the consensus model dictated by the members' nodes. Approved transactions **626** are stored in current blocks of the blockchain and committed to the blockchain via a committal procedure which includes performing a hash of the data contents of the transactions in a current block and referencing a previous hash of a previous block. Within the blockchain, one or more smart contracts **630** may exist that define the terms of transaction agreements and actions included in smart contract executable application code **632**, such as registered recipients, vehicle features, requirements, permissions, sensor thresholds, etc. The code may be configured to identify whether requesting entities are registered to receive vehicle services, what service features they are entitled/required to receive given their profile statuses and whether to monitor their actions in subsequent events. For example, when a service event occurs and a user is riding in the vehicle, the sensor data monitoring may be triggered, and a certain parameter, such as a vehicle charge level, may be identified as being above/below a particular threshold for a particular period of time, then the result may be a change to a current status which requires an alert to be sent to the managing party (i.e., vehicle owner, vehicle operator, server, etc.) so the service can be identified and stored for reference. The vehicle sensor data collected may be based on types of sensor data used to collect information about vehicle's status. The sensor data may also be the basis for the vehicle event data **634**, such as a location(s) to be traveled, an average speed, a top speed, acceleration rates, whether there were any collisions, was the expected route taken, what is the next destination, whether safety measures are in place, whether the vehicle has enough charge/fuel, etc. All such information may be the basis of smart contract terms **630**, which are then stored in a blockchain. For example, sensor thresholds stored in the smart contract can be used as the basis for whether a detected service is necessary and when and where the service should be performed.

[0098] FIG. **6B** illustrates a shared ledger configuration, according to example embodiments. Referring to FIG. **6B**, the blockchain logic example **640** includes a blockchain application interface **642** as an API or plug-in application that links to the computing device and execution platform for a particular transaction. The blockchain configuration **640** may include one or more applications which are linked to application programming interfaces (APIs) to access and execute stored program/application code (e.g., smart contract executable code, smart contracts, etc.) which can be created according to a customized configuration sought by participants and can maintain their own state, control their own assets, and receive external information. This can be deployed as an entry and installed, via appending to the distributed ledger, on all blockchain nodes.

[0099] The smart contract application code **644** provides a basis for the blockchain transactions by establishing application code which when executed causes the transaction terms and conditions to become active. The smart contract **630**, when executed, causes certain approved transactions **626** to be generated, which are then forwarded to the blockchain platform **652**. The platform includes a security/authorization **658**, computing devices which execute the transaction management **656** and a storage portion **654** as a memory that stores transactions and smart contracts in the blockchain.

[0100] The blockchain platform may include various layers of blockchain data, services (e.g., cryptographic trust services, virtual execution environment, etc.), and underpinning physical computer infrastructure that may be used to receive and store new entries and provide access to auditors which are seeking to access data entries. The blockchain may expose an interface that provides access to the virtual execution environment necessary to process the program code and engage the physical infrastructure. Cryptographic trust services may be used to verify entries such as asset exchange entries and keep information private.

[0101] The blockchain architecture configuration of FIGS. 6A and 6B may process and execute program/application code via one or more interfaces exposed, and services provided, by the blockchain platform. As a non-limiting example, smart contracts may be created to execute reminders, updates, and/or other notifications subject to the changes, updates, etc. The smart contracts can themselves be used to identify rules associated with authorization and access requirements and usage of the ledger. For example, the information may include a new entry, which may be processed by one or more processing entities (e.g., processors, virtual machines, etc.) included in the blockchain layer. The result may include a decision to reject or approve the new entry based on the criteria defined in the smart contract and/or a consensus of the peers. The physical infrastructure may be utilized to retrieve any of the data or information described herein.

[0102] Within smart contract executable code, a smart contract may be created via a high-level application and programming language, and then written to a block in the blockchain. The smart contract may include executable code which is registered, stored, and/or replicated with a blockchain (e.g., distributed network of blockchain peers). An entry is an execution of the smart contract code which can be performed in response to conditions associated with the smart contract being satisfied. The executing of the smart contract may trigger a trusted modification(s) to a state of a digital blockchain ledger. The modification(s) to the blockchain ledger caused by the smart contract execution may be automatically replicated throughout the distributed network of blockchain peers through one or more consensus protocols.

[0103] The smart contract may write data to the blockchain in the format of key-value pairs. Furthermore, the smart contract code can read the values stored in a blockchain and use them in application operations. The smart contract code can write the output of various logic operations into the blockchain. The code may be used to create a temporary data structure in a virtual machine or other computing platform. Data written to the blockchain can be public and/or can be encrypted and maintained as private. The temporary data that is used/generated by the smart contract is held in memory by the supplied execution environment, then deleted once the data needed for the blockchain is identified.

[0104] A smart contract executable code may include the code interpretation of a smart contract, with additional features. As described herein, the smart contract executable code may be program code deployed on a computing network, where it is executed and validated by chain validators together during a consensus process. The smart contract executable code receives a hash and retrieves from the blockchain a hash associated with the data template created by use of a previously stored feature extractor. If the hashes of the hash identifier and the hash created from the stored identifier template data match, then the smart contract executable code sends an authorization key to the requested service. The smart contract executable code may write to the blockchain data associated with the cryptographic details.

[0105] FIG. 6C illustrates a blockchain configuration for storing blockchain transaction data, according to example embodiments. Referring to FIG. 6C, the example configuration **660** provides for the vehicle **662**, the user device **664** and a server **666** sharing information with a distributed ledger (i.e., blockchain) **668**. The server may represent a service provider entity inquiring with a vehicle service provider to share user profile rating information in the event that a known and established user profile is attempting to rent a vehicle with an established rated profile. The server **666** may be receiving and processing data related to a vehicle's service requirements. As the service events occur, such as the vehicle sensor data indicates a need for fuel/charge, a maintenance service, etc., a smart contract may be used to invoke rules, thresholds, sensor information gathering, etc., which may be used to invoke the vehicle service event. The blockchain transaction data **670** is saved for each transaction, such as the access event, the subsequent updates to a vehicle's service status, event updates, etc. The transactions may include the parties, the requirements (e.g., 18 years of age, service eligible candidate, valid driver's license, etc.), compensation levels, the distance traveled during the event, the registered recipients permitted to

access the event and host a vehicle service, rights/permissions, sensor data retrieved during the vehicle event operation to log details of the next service event and identify a vehicle's condition status, and thresholds used to make determinations about whether the service event was completed and whether the vehicle's condition status has changed.

[0106] FIG. 6D illustrates blockchain blocks **680** that can be added to a distributed ledger, according to example embodiments, and contents of block structures **682A** to **682n**. Referring to FIG. 6D, clients (not shown) may submit entries to blockchain nodes to enact activity on the blockchain. As an example, clients may be applications that act on behalf of a requester, such as a device, person or entity to propose entries for the blockchain. The plurality of blockchain peers (e.g., blockchain nodes) may maintain a state of the blockchain network and a copy of the distributed ledger. Different types of blockchain nodes/peers may be present in the blockchain network including endorsing peers which simulate and endorse entries proposed by clients and committing peers which verify endorsements, validate entries, and commit entries to the distributed ledger. In this example, the blockchain nodes may perform the role of endorser node, committer node, or both.

[0107] The instant system includes a blockchain which stores immutable, sequenced records in blocks, and a state database (current world state) maintaining a current state of the blockchain. One distributed ledger may exist per channel and each peer maintains its own copy of the distributed ledger for each channel of which they are a member. The instant blockchain is an entry log, structured as hash-linked blocks where each block contains a sequence of N entries. Blocks may include various components such as those shown in FIG. 6D. The linking of the blocks may be generated by adding a hash of a prior block's header within a block header of a current block. In this way, all entries on the blockchain are sequenced and cryptographically linked together preventing tampering with blockchain data without breaking the hash links. Furthermore, because of the links, the latest block in the blockchain represents every entry that has come before it. The instant blockchain may be stored on a peer file system (local or attached storage), which supports an append-only blockchain workload.

[0108] The current state of the blockchain and the distributed ledger may be stored in the state database. Here, the current state data represents the latest values for all keys ever included in the chain entry log of the blockchain. Smart contract executable code invocations execute entries against the current state in the state database. To make these smart contract executable code interactions extremely efficient, the latest values of all keys are stored in the state database. The state database may include an indexed view into the entry log of the blockchain, it can therefore be regenerated from the chain at any time. The state database may automatically get recovered (or generated if needed) upon peer startup, before entries are accepted.

[0109] Endorsing nodes receive entries from clients and endorse the entry based on simulated results. Endorsing nodes hold smart contracts which simulate the entry proposals. When an endorsing node endorses an entry, the endorsing nodes creates an entry endorsement which is a signed response from the endorsing node to the client application indicating the endorsement of the simulated entry. The method of endorsing an entry depends on an endorsement policy which may be specified within smart contract executable code. An example of an endorsement policy is “the majority of endorsing peers must endorse the entry.” Different channels may have different endorsement policies. Endorsed entries are forward by the client application to an ordering service.

[0110] The ordering service accepts endorsed entries, orders them into a block, and delivers the blocks to the committing peers. For example, the ordering service may initiate a new block when a threshold of entries has been reached, a timer times out, or another condition. In this example, blockchain node is a committing peer that has received a data block **682A** for storage on the blockchain. The ordering service may be made up of a cluster of orderers. The ordering service does not process entries, smart contracts, or maintain the shared ledger. Rather, the ordering service may accept the endorsed entries and specifies the order in which those entries are committed to the

distributed ledger. The architecture of the blockchain network may be designed such that the specific implementation of 'ordering' (e.g., Solo, Kafka, BFT, etc.) becomes a pluggable component.

[0111] Entries are written to the distributed ledger in a consistent order. The order of entries is established to ensure that the updates to the state database are valid when they are committed to the network. Unlike a cryptocurrency blockchain system (e.g., Bitcoin, etc.) where ordering occurs through the solving of a cryptographic puzzle, or mining, in this example the parties of the distributed ledger may choose the ordering mechanism that best suits that network.

[0112]] Referring to FIG. 6D, a block **682A** (also referred to as a data block) that is stored on the blockchain and/or the distributed ledger may include multiple data segments such as a block header **684A** to **684n**, transaction specific data **686A** to **686n**, and block metadata **688A** to **688n**. It should be appreciated that the various depicted blocks and their contents, such as block **682A** and its contents are merely for purposes of an example and are not meant to limit the scope of the example embodiments. In some cases, both the block header **684A** and the block metadata **688A** may be smaller than the transaction specific data **686A** which stores entry data; however, this is not a requirement. The block **682A** may store transactional information of N entries (e.g., **100**, **500**, **1000**, **2000**, **3000**, etc.) within the block data **690A** to **690n**. The block **682A** may also include a link to a previous block (e.g., on the blockchain) within the block header **684A**. In particular, the block header **684A** may include a hash of a previous block's header. The block header **684A** may also include a unique block number, a hash of the block data **690A** of the current block **682A**, and the like. The block number of the block **682A** may be unique and assigned in an incremental/sequential order starting from zero. The first block in the blockchain may be referred to as a genesis block which includes information about the blockchain, its members, the data stored therein, etc.

[0113] The block data **690A** may store entry information of each entry that is recorded within the block. For example, the entry data may include one or more of a type of the entry, a version, a timestamp, a channel ID of the distributed ledger, an entry ID, an epoch, a payload visibility, a smart contract executable code path (deploy tx), a smart contract executable code name, a smart contract executable code version, input (smart contract executable code and functions), a client (creator) identify such as a public key and certificate, a signature of the client, identities of endorsers, endorser signatures, a proposal hash, smart contract executable code events, response status, namespace, a read set (list of key and version read by the entry, etc.), a write set (list of key and value, etc.), a start key, an end key, a list of keys, a Merkel tree query summary, and the like. The entry data may be stored for each of the N entries.

[0114] In some embodiments, the block data **690A** may also store transaction specific data **686A** which adds additional information to the hash-linked chain of blocks in the blockchain. Accordingly, the data **686A** can be stored in an immutable log of blocks on the distributed ledger. Some of the benefits of storing such data **686A** are reflected in the various embodiments disclosed and depicted herein. The block metadata **688A** may store multiple fields of metadata (e.g., as a byte array, etc.). Metadata fields may include signature on block creation, a reference to a last configuration block, an entry filter identifying valid and invalid entries within the block, last offset persisted of an ordering service that ordered the block, and the like. The signature, the last configuration block, and the orderer metadata may be added by the ordering service. Meanwhile, a committer of the block (such as a blockchain node) may add validity/invalidity information based on an endorsement policy, verification of read/write sets, and the like. The entry filter may include a byte array of a size equal to the number of entries in the block data **690A** and a validation code identifying whether an entry was valid/invalid.

[0115] The other blocks **682B** to **682n** in the blockchain also have headers, files, and values. However, unlike the first block **682A**, each of the headers **684A** to **684n** in the other blocks includes the hash value of an immediately preceding block. The hash value of the immediately

preceding block may be just the hash of the header of the previous block or may be the hash value of the entire previous block. By including the hash value of a preceding block in each of the remaining blocks, a trace can be performed from the Nth block back to the genesis block (and the associated original file) on a block-by-block basis, as indicated by arrows **692**, to establish an auditable and immutable chain-of-custody.

[0116] The above embodiments may be implemented in hardware, in a computer program executed by a processor, in firmware, or in a combination of the above. A computer program may be embodied on a computer readable medium, such as a storage medium. For example, a computer program may reside in random access memory (“RAM”), flash memory, read-only memory (“ROM”), erasable programmable read-only memory (“EPROM”), electrically erasable programmable read-only memory (“EEPROM”), registers, hard disk, a removable disk, a compact disk read-only memory (“CD-ROM”), or any other form of storage medium known in the art.

[0117] An exemplary storage medium may be coupled to the processor such that the processor may read information from, and write information to, the storage medium. In the alternative, the storage medium may be integral to the processor. The processor and the storage medium may reside in an application specific integrated circuit (“ASIC”). In the alternative, the processor and the storage medium may reside as discrete components. For example, FIG. 7 illustrates an example computer system architecture **700**, which may represent or be integrated in any of the above-described components, etc.

[0118] FIG. 7 is not intended to suggest any limitation as to the scope of use or functionality of embodiments of the application described herein. Regardless, the computing node **700** is capable of being implemented and/or performing any of the functionality set forth hereinabove.

[0119] In computing node **700** there is a computer system/server **702**, which is operational with numerous other general purpose or special purpose computing system environments or configurations. Examples of well-known computing systems, environments, and/or configurations that may be suitable for use with computer system/server **702** include, but are not limited to, personal computer systems, server computer systems, thin clients, thick clients, hand-held or laptop devices, multiprocessor systems, microprocessor-based systems, set top boxes, programmable consumer electronics, network PCs, minicomputer systems, mainframe computer systems, and distributed cloud computing environments that include any of the above systems or devices, and the like.

[0120] Computer system/server **702** may be described in the general context of computer system-executable instructions, such as program modules, being executed by a computer system. Generally, program modules may include routines, programs, objects, components, logic, data structures, and so on that perform particular tasks or implement particular abstract data types. Computer system/server **702** may be practiced in distributed cloud computing environments where tasks are performed by remote processing devices that are linked through a communications network. In a distributed cloud computing environment, program modules may be located in both local and remote computer system storage media including memory storage devices.

[0121] As shown in FIG. 7, computer system/server **702** in cloud computing node **700** is shown in the form of a general-purpose computing device. The components of computer system/server **702** may include, but are not limited to, one or more processors or processing units **704**, a system memory **706**, and a bus that couples various system components including system memory **706** to processor **704**.

[0122] The bus represents one or more of any of several types of bus structures, including a memory bus or memory controller, a peripheral bus, an accelerated graphics port, and a processor or local bus using any of a variety of bus architectures. By way of example, and not limitation, such architectures include Industry Standard Architecture (ISA) bus, Micro Channel Architecture (MCA) bus, Enhanced ISA (EISA) bus, Video Electronics Standards Association (VESA) local bus, and Peripheral Component Interconnects (PCI) bus.

[0123] Computer system/server **702** typically includes a variety of computer system readable media. Such media may be any available media that is accessible by computer system/server **702**, and it includes both volatile and non-volatile media, removable and non-removable media. System memory **706**, in one embodiment, implements the flow diagrams of the other figures. The system memory **706** can include computer system readable media in the form of volatile memory, such as random-access memory (RAM) **708** and/or cache memory **710**. Computer system/server **702** may further include other removable/non-removable, volatile/non-volatile computer system storage media. By way of example only, memory **706** can be provided for reading from and writing to a non-removable, non-volatile magnetic media (not shown and typically called a “hard drive”). Although not shown, a magnetic disk drive for reading from and writing to a removable, non-volatile magnetic disk (e.g., a “floppy disk”), and an optical disk drive for reading from or writing to a removable, non-volatile optical disk such as a CD-ROM, DVD-ROM or other optical media can be provided. In such instances, each can be connected to the bus by one or more data media interfaces. As will be further depicted and described below, memory **706** may include at least one program product having a set (e.g., at least one) of program modules that are configured to carry out the functions of various embodiments of the application.

[0124] Program/utility, having a set (at least one) of program modules, may be stored in memory **706** by way of example, and not limitation, as well as an operating system, one or more application programs, other program modules, and program data. Each of the operating system, one or more application programs, other program modules, and program data or some combination thereof, may include an implementation of a networking environment. Program modules generally carry out the functions and/or methodologies of various embodiments of the application as described herein.

[0125] As will be appreciated by one skilled in the art, aspects of the present application may be embodied as a system, method, or computer program product. Accordingly, aspects of the present application may take the form of an entirely hardware embodiment, an entirely software embodiment (including firmware, resident software, micro-code, etc.) or an embodiment combining software and hardware aspects that may all generally be referred to herein as a “circuit,” “module” or “system.” Furthermore, aspects of the present application may take the form of a computer program product embodied in one or more computer readable medium(s) having computer readable program code embodied thereon.

[0126] Computer system/server **702** may also communicate with one or more external devices via an I/O device **712** (such as an I/O adapter), which may include a keyboard, a pointing device, a display, a voice recognition module, etc., one or more devices that enable a user to interact with computer system/server **702**, and/or any devices (e.g., network card, modem, etc.) that enable computer system/server **702** to communicate with one or more other computing devices. Such communication can occur via I/O interfaces of the device **712**. Still yet, computer system/server **702** can communicate with one or more networks such as a local area network (LAN), a general wide area network (WAN), and/or a public network (e.g., the Internet) via a network adapter. As depicted, device **712** communicates with the other components of computer system/server **702** via a bus. It should be understood that although not shown, other hardware and/or software components could be used in conjunction with computer system/server **702**. Examples, include, but are not limited to: microcode, device drivers, redundant processing units, external disk drive arrays, RAID systems, tape drives, and data archival storage systems, etc.

[0127] Although an exemplary embodiment of at least one of a system, method, and non-transitory computer readable medium has been illustrated in the accompanied drawings and described in the foregoing detailed description, it will be understood that the application is not limited to the embodiments disclosed, but is capable of numerous rearrangements, modifications, and substitutions as set forth and defined by the following claims. For example, the capabilities of the system of the various figures can be performed by one or more of the modules or components described herein or in a distributed architecture and may include a transmitter, receiver or pair of

both. For example, all or part of the functionality performed by the individual modules, may be performed by one or more of these modules. Further, the functionality described herein may be performed at various times and in relation to various events, internal or external to the modules or components. Also, the information sent between various modules can be sent between the modules via at least one of: a data network, the Internet, a voice network, an Internet Protocol network, a wireless device, a wired device and/or via plurality of protocols. Also, the messages sent or received by any of the modules may be sent or received directly and/or via one or more of the other modules.

[0128] One skilled in the art will appreciate that a “system” could be embodied as a personal computer, a server, a console, a personal digital assistant (PDA), a cell phone, a tablet computing device, a smartphone or any other suitable computing device, or combination of devices. Presenting the above-described functions as being performed by a “system” is not intended to limit the scope of the present application in any way but is intended to provide one example of many embodiments. Indeed, methods, systems and apparatuses disclosed herein may be implemented in localized and distributed forms consistent with computing technology.

[0129] It should be noted that some of the system features described in this specification have been presented as modules, in order to more particularly emphasize their implementation independence. For example, a module may be implemented as a hardware circuit comprising custom very large-scale integration (VLSI) circuits or gate arrays, off-the-shelf semiconductors such as logic chips, transistors, or other discrete components. A module may also be implemented in programmable hardware devices such as field programmable gate arrays, programmable array logic, programmable logic devices, graphics processing units, or the like.

[0130] A module may also be at least partially implemented in software for execution by various types of processors. An identified unit of executable code may, for instance, comprise one or more physical or logical blocks of computer instructions that may, for instance, be organized as an object, procedure, or function. Nevertheless, the executables of an identified module need not be physically located together but may comprise disparate instructions stored in different locations which, when joined logically together, comprise the module and achieve the stated purpose for the module. Further, modules may be stored on a computer-readable medium, which may be, for instance, a hard disk drive, flash device, random access memory (RAM), tape, or any other such medium used to store data.

[0131] Indeed, a module of executable code could be a single instruction, or many instructions, and may even be distributed over several different code segments, among different programs, and across several memory devices. Similarly, operational data may be identified and illustrated herein within modules and may be embodied in any suitable form and organized within any suitable type of data structure. The operational data may be collected as a single data set or may be distributed over different locations including over different storage devices, and may exist, at least partially, merely as electronic signals on a system or network.

[0132] It will be readily understood that the components of the application, as generally described and illustrated in the figures herein, may be arranged and designed in a wide variety of different configurations. Thus, the detailed description of the embodiments is not intended to limit the scope of the application as claimed but is merely representative of selected embodiments of the application.

[0133] One having ordinary skill in the art will readily understand that the above may be practiced with steps in a different order, and/or with hardware elements in configurations that are different than those which are disclosed. Therefore, although the application has been described based upon these preferred embodiments, it would be apparent to those of skill in the art that certain modifications, variations, and alternative constructions would be apparent.

[0134] While preferred embodiments of the present application have been described, it is to be understood that the embodiments described are illustrative only and the scope of the application is

to be defined solely by the appended claims when considered with a full range of equivalents and modifications (e.g., protocols, hardware devices, software platforms etc.) thereto.

Claims

1. A method, comprising: generating, by a server, a patch including an estimated time when a condition affecting travel of a transport will be cleared based on new sensor data; transmitting, by the server, the patch to the transport and other transports to update sensor data previously stored by the transport, wherein the other transports are in proximity the transport; receiving the patch at the transport and the other transports; and downloading the patch on the transport to replace the sensor data previously stored with the new sensor data.
2. The method of claim 1, comprising: creating the patch by the server.
3. The method of claim 1, wherein the new sensor data and the sensor data previously stored by the transport each comprise camera images of one or more of a traffic accident, construction, one or more signs, or a road or traffic condition.
4. The method of claim 1, comprising: displaying information associated with the patch by a display of the transport.
5. The method of claim 1, wherein a difference between the new sensor data and the sensor data previously stored by the transport comprises information related to one or more of: a traffic accident, construction, one or more signs, or a road or traffic condition.
6. The method of claim 1, wherein the patch further comprises additional differences received from the other transports.
7. The method of claim 1, wherein the sensor data previously stored by the transport indicates an impediment to traffic and the new sensor data indicates removal of the impediment.
8. A computer device, comprising: a processor that, when executing instructions stored in an associated memory, is configured to: generate a patch that includes an estimated time when a condition affecting travel of a transport will be cleared based on new sensor data; transmit the patch to the transport and other transports to update sensor data previously stored by the transport, wherein the other transports are in proximity the transport; receive the patch at the transport and the other transports; and download the patch on the transport to replace the sensor data previously stored with the new sensor data.
9. The computer device of claim 8, wherein the patch is created by a server.
10. The computer device of claim 8, wherein the new sensor data and the sensor data previously stored by the transport each comprise camera images of one or more of a traffic accident, construction, one or more signs, or a road or traffic condition.
11. The computer device of claim 8, wherein the transport is configured to display information associated with the patch by a display of the transport.
12. The computer device of claim 8, wherein a difference between the new sensor data and the sensor data previously stored by the transport comprises information related to one or more of: a traffic accident, construction, one or more signs, or a road or traffic condition.
13. The computer device of claim 8, wherein the patch further comprises additional differences received from the other transports.
14. The computer device of claim 8, wherein the sensor data previously stored by the transport indicates an impediment to traffic and the new sensor data indicates removal of the impediment.
15. A non-transitory computer-readable medium comprising instructions that, when executed by a processor, cause the processor to perform: generating, by a server, a patch including an estimated time when a condition affecting travel of a transport will be cleared based on new sensor data; transmitting, by the server, the patch to the transport and other transports to update sensor data previously stored by the transport, wherein the other transports are in proximity the transport; receiving the patch at the transport and the other transports; and downloading the patch on the

transport to replace the sensor data previously stored with the new sensor data.

16. The non-transitory computer-readable medium of claim 15, wherein the instructions further cause the processor to perform: creating the patch by the server.

17. The non-transitory computer-readable medium of claim 15, wherein the new sensor data and the sensor data previously stored by the transport each comprise camera images of one or more of a traffic accident, construction, one or more signs, or a road or traffic condition.

18. The non-transitory computer-readable medium of claim 15, wherein the instructions further cause the processor to perform: displaying information associated with the patch by a display of the transport, wherein a difference between the new sensor data and the sensor data previously stored by the transport comprises information related to one or more of: a traffic accident, construction, one or more signs, or a road or traffic condition.

19. The non-transitory computer-readable medium of claim 15, wherein the patch further comprises additional differences received from the other transports.

20. The non-transitory computer-readable medium of claim 15, wherein the sensor data previously stored by the transport indicates an impediment to traffic and the new sensor data indicates removal of the impediment.
