

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent	12393233
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Calatayud; Thomas et al.

---

### Wireless antenna sensing in a playback device

---

#### Abstract

An example embodiment includes a playback device comprising a wireless communications interface including a wireless (e.g., a radio frequency (RF) antenna), a capacitive sensor comprising an electrode that is coupled to the RF antenna, one or more processors, and a data storage having stored therein instructions executable by the one or more processors to cause the playback device to perform operations. The operations include operating the playback device in a first power state, detecting that an object is in proximity to the capacitive sensor, and in response to detecting the object, adjusting operation of the playback device from the first power state to a second power state.

---

**Inventors:** Calatayud; Thomas (Cambridge, MA), Reilly; Jonathon (Cambridge, MA)

**Applicant:** Sonos, Inc. (Santa Barbara, CA)

**Family ID:** 1000008762892

**Assignee:** Sonos, Inc. (Goleta, CA)

**Appl. No.:** 18/352346

**Filed:** July 14, 2023

#### Prior Publication Data

Document Identifier	Publication Date
US 20230359249 A1	Nov. 09, 2023

#### Related U.S. Application Data

continuation parent-doc US 17473212 20210913 US 11747863 child-doc US 18352346  
continuation parent-doc US 15645121 20170710 US 11119540 20210914 child-doc US 17473212  
continuation parent-doc US 14799323 20150714 US 9703324 20170711 child-doc US 15645121  
continuation parent-doc US 14041115 20130930 US 9223353 20151229 child-doc US 14799323

---

## Publication Classification

**Int. Cl.:** **G06F1/16** (20060101); **G06F1/18** (20060101); **G06F1/3231** (20190101); **G06F1/3234** (20190101); **G06F3/03** (20060101); **G06F3/16** (20060101); **H04S7/00** (20060101); **H03K17/94** (20060101); **H03K17/955** (20060101); **H04N21/442** (20110101)

**U.S. Cl.:**

**CPC** **G06F1/1656** (20130101); **G06F1/1684** (20130101); **G06F1/1688** (20130101); **G06F1/1698** (20130101); **G06F1/182** (20130101); **G06F1/3231** (20130101); **G06F1/3265** (20130101); **G06F3/0304** (20130101); **G06F3/162** (20130101); **H04S7/303** (20130101); **H03K17/941** (20130101); **H03K17/955** (20130101); **H03K2217/94106** (20130101); **H04N21/44218** (20130101); **H04R2227/003** (20130101); **H04R2227/005** (20130101); **H04R2430/01** (20130101); **Y02D10/00** (20180101)

## Field of Classification Search

**CPC:** G06F (1/1656); G06F (1/1684); G06F (1/1688); G06F (1/1698); G06F (1/182); G06F (1/3231); G06F (1/3265); G06F (3/0304); G06F (3/162); H04S (7/303); Y02D (10/00); H03K (17/955); H03K (2217/94106); H04N (21/44218); H04R (2227/003); H04R (2227/005); H04R (2430/01)

---

## References Cited

### U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5440644	12/1994	Farinelli et al.	N/A	N/A
5761320	12/1997	Farinelli et al.	N/A	N/A
5923902	12/1998	Inagaki	N/A	N/A
6032202	12/1999	Lea et al.	N/A	N/A
6044632	12/1999	Schmalz et al.	N/A	N/A
6256554	12/2000	DiLorenzo	N/A	N/A
6404811	12/2001	Cvetko et al.	N/A	N/A
6469633	12/2001	Wachter	N/A	N/A
6522886	12/2002	Youngs et al.	N/A	N/A
6611537	12/2002	Edens et al.	N/A	N/A
6631410	12/2002	Kowalski et al.	N/A	N/A
6643744	12/2002	Cheng	N/A	N/A
6757517	12/2003	Chang	N/A	N/A
6778869	12/2003	Champion	N/A	N/A
7114399	12/2005	Mallory	N/A	N/A
7130608	12/2005	Hollstrom et al.	N/A	N/A
7130616	12/2005	Janik	N/A	N/A
7143939	12/2005	Henzerling	N/A	N/A
7236773	12/2006	Thomas	N/A	N/A
7295548	12/2006	Blank et al.	N/A	N/A
7483538	12/2008	McCarty et al.	N/A	N/A
7571014	12/2008	Lambourne et al.	N/A	N/A
7621441	12/2008	Milford et al.	N/A	N/A

7630501	12/2008	Blank et al.	N/A	N/A
7643894	12/2009	Braithwaite et al.	N/A	N/A
7657910	12/2009	McAulay et al.	N/A	N/A
7728316	12/2009	Fadell et al.	N/A	N/A
7840740	12/2009	Minoo	N/A	N/A
7853341	12/2009	McCarty et al.	N/A	N/A
7868778	12/2010	Kenwright	N/A	N/A
7949707	12/2010	McDowall et al.	N/A	N/A
7957762	12/2010	Herz et al.	N/A	N/A
7987294	12/2010	Bryce et al.	N/A	N/A
8014423	12/2010	Thaler et al.	N/A	N/A
8030914	12/2010	Alameh et al.	N/A	N/A
8045952	12/2010	Qureshey et al.	N/A	N/A
8103009	12/2011	McCarty et al.	N/A	N/A
8234395	12/2011	Millington	N/A	N/A
8269178	12/2011	Blom et al.	N/A	N/A
8332414	12/2011	Nguyen et al.	N/A	N/A
8381135	12/2012	Hotelling et al.	N/A	N/A
8452020	12/2012	Gregg et al.	N/A	N/A
8483853	12/2012	Lambourne	N/A	N/A
8577289	12/2012	Schlub et al.	N/A	N/A
8649833	12/2013	Lee et al.	N/A	N/A
9195432	12/2014	Reilly	N/A	N/A
9225307	12/2014	Reilly et al.	N/A	N/A
9454256	12/2015	Fisher et al.	N/A	N/A
9490885	12/2015	Zheng et al.	N/A	N/A
9494683	12/2015	Sadek	N/A	N/A
9881058	12/2017	Liu	N/A	N/A
11119540	12/2020	Calatayud	N/A	G06F 1/1698
11747863	12/2022	Calatayud	250/208.4	G06F 3/0304
2001/0042107	12/2000	Palm	N/A	N/A
2001/0043592	12/2000	Jimenez et al.	N/A	N/A
2002/0022453	12/2001	Balog et al.	N/A	N/A
2002/0026442	12/2001	Lipscomb et al.	N/A	N/A
2002/0124097	12/2001	Isely et al.	N/A	N/A
2003/0004690	12/2002	Maeda et al.	N/A	N/A
2003/0157951	12/2002	Hasty, Jr.	N/A	N/A
2004/0024478	12/2003	Hans et al.	N/A	N/A
2005/0219228	12/2004	Alameh et al.	N/A	N/A
2005/0227702	12/2004	Nishimura et al.	N/A	N/A
2006/0132447	12/2005	Conrad	N/A	N/A
2007/0116264	12/2006	Lucey	N/A	N/A
2007/0142944	12/2006	Goldberg et al.	N/A	N/A
2008/0109956	12/2007	Bayley et al.	N/A	N/A
2008/0284738	12/2007	Hovden et al.	N/A	N/A
2009/0027068	12/2008	Philipp et al.	N/A	N/A
2009/0139778	12/2008	Butler et al.	N/A	N/A
2010/0046766	12/2009	Gregg et al.	N/A	N/A
2010/0103098	12/2009	Gear et al.	N/A	N/A
2010/0171027	12/2009	Yun	N/A	N/A

2011/0087842	12/2010	Lu et al.	N/A	N/A
2011/0241907	12/2010	Cordeiro	N/A	N/A
2012/0019165	12/2011	Igaki et al.	N/A	N/A
2012/0044199	12/2011	Karpin et al.	N/A	N/A
2012/0050189	12/2011	Choboter et al.	N/A	N/A
2012/0143357	12/2011	Chemel et al.	N/A	N/A
2012/0145932	12/2011	Yao et al.	N/A	N/A
2012/0214412	12/2011	Schlub et al.	N/A	N/A
2012/0268145	12/2011	Chandra et al.	N/A	N/A
2012/0318364	12/2011	Sawaski et al.	N/A	N/A
2013/0094659	12/2012	Liu	N/A	N/A
2013/0095885	12/2012	Liu et al.	N/A	N/A
2013/0202132	12/2012	Zurek et al.	N/A	N/A
2013/0273869	12/2012	Parker et al.	N/A	N/A
2014/0002305	12/2013	Hsu et al.	N/A	N/A
2014/0179239	12/2013	Nickel et al.	N/A	N/A
2014/0280450	12/2013	Luna	709/202	H04L 67/12
2014/0333494	12/2013	Huang	N/A	N/A
2015/0044977	12/2014	Ramasamy et al.	N/A	N/A
2015/0162943	12/2014	Peter	N/A	N/A
2015/0199042	12/2014	Standing et al.	N/A	N/A

#### **FOREIGN PATENT DOCUMENTS**

<b>Patent No.</b>	<b>Application Date</b>	<b>Country</b>	<b>CPC</b>
1389853	12/2003	EP	N/A
2194471	12/2009	EP	N/A
200153994	12/2000	WO	N/A
2003093950	12/2002	WO	N/A

#### **OTHER PUBLICATIONS**

AudioTron Quick Start Guide, Version 1.0, Mar. 2001, 24 pages. cited by applicant

AudioTron Reference Manual, Version 3.0, May 2002, 70 pages. cited by applicant

AudioTron Setup Guide, Version 3.0, May 2002, 38 pages. cited by applicant

Bluetooth. "Specification of the Bluetooth System: The ad hoc Scatternet for affordable and highly functional wireless connectivity," Core, Version 1.0 A, Jul. 26, 1999, 1068 pages. cited by applicant

Bluetooth. "Specification of the Bluetooth System: Wireless connections made easy," Core, Version 1.0 B, Dec. 1, 1999, 1076 pages. cited by applicant

Camacho et al., "Designing Touch Sensing Electrodes: Electrical Considerations and Recommended Layout Patterns," Freescale Semiconductor, 2010, 28 pages. cited by applicant

Dell, Inc. "Dell Digital Audio Receiver: Reference Guide," Jun. 2000, 70 pages. cited by applicant

Dell, Inc. "Start Here," Jun. 2000, 2 pages. cited by applicant

"Denon 2003-2004 Product Catalog," Denon, 2003-2004, 44 pages. cited by applicant

"Extended Range Proximity with SMSC RightTouch Capacitive Sensors", SMSC, Revision 1.0, Nov. 7, 2012, 11 pages. cited by applicant

Final Office Action mailed on Feb. 3, 2020, issued in connection with U.S. Appl. No. 15/269,700, filed Sep. 19, 2016, 31 pages. cited by applicant

Gao, Xiang, "Microchip Capacitive Proximity Design Guide," Microchip Technology Inc., 2013, pp. 1-8. cited by applicant

"Si114X Designer's Guide", Silicon Labs, 2012, 58 pages. cited by applicant

Jo et al., "Synchronized One-to-many Media Streaming with Adaptive Payout Control,"

Proceedings of SPIE, 2002, pp. 71-82, vol. 4861. cited by applicant

Jones, Stephen, "Dell Digital Audio Receiver: Digital upgrade for your analog stereo," Analog Stereo, Jun. 24, 2000 <http://www.reviewsonline.com/articles/961906864.htm> retrieved Jun. 18, 2014, 2 pages. cited by applicant

Louderback, Jim, "Affordable Audio Receiver Furnishes Homes With MP3," TechTV Vault. Jun. 28, 2000 retrieved Jul. 10, 2014, 2 pages. cited by applicant

Non-Final Office Action mailed on May 6, 2015, issued in connection with U.S. Appl. No. 14/041,115, filed Sep. 30, 2013, 14 pages. cited by applicant

Non-Final Office Action mailed on Jan. 21, 2021, issued in connection with U.S. Appl. No. 15/645,121, filed Jul. 10, 2017, 12 pages. cited by applicant

Non-Final Office Action mailed on Jul. 22, 2020, issued in connection with U.S. Appl. No. 15/645,121, filed Jul. 10, 2017, 12 pages. cited by applicant

Non-Final Office Action mailed on Sep. 24, 2019, issued in connection with U.S. Appl. No. 15/269,700, filed Sep. 19, 2016, 42 pages. cited by applicant

Non-Final Office Action mailed on May 30, 2019, issued in connection with U.S. Appl. No. 15/645,121, filed Jul. 10, 2017, 12 pages. cited by applicant

Non-Final Office Action mailed on Jan. 6, 2023, issued in connection with U.S. Appl. No. 17/473,212, filed Sep. 13, 2021, 7 pages. cited by applicant

Non-Final Office Action mailed on Jan. 7, 2020, issued in connection with U.S. Appl. No. 15/645,121, filed Jul. 10, 2017, 12 pages. cited by applicant

Notice of Allowance mailed on May 12, 2021, issued in connection with U.S. Appl. No. 15/645,121, filed Jul. 10, 2017, 8 pages. cited by applicant

Notice of Allowance mailed on Jun. 15, 2015, issued in connection with U.S. Appl. No. 14/041,308, filed Sep. 30, 2013, 8 pages. cited by applicant

Notice of Allowance mailed on Apr. 17, 2023, issued in connection with U.S. Appl. No. 17/473,212, filed Sep. 13, 2021, 8 pages. cited by applicant

Notice of Allowance mailed on Jun. 21, 2016, issued in connection with U.S. Appl. No. 14/806,922, filed Jul. 23, 2015, 13 pages. cited by applicant

Notice of Allowance mailed on Oct. 21, 2015, issued in connection with U.S. Appl. No. 14/041,115, filed Sep. 30, 2013, 8 pages. cited by applicant

Notice of Allowance mailed on Apr. 23, 2020, issued in connection with U.S. Appl. No. 15/269,700, filed Sep. 19, 2016, 18 pages. cited by applicant

Notice of Allowance mailed on Mar. 30, 2017, issued in connection with U.S. Appl. No. 14/799,323, filed Jul. 14, 2015, 11 pages. cited by applicant

Palm, Inc., "Handbook for the Palm VII Handheld," May 2000, 311 pages. cited by applicant

Presentations at WinHEC 2000, May 2000, 138 pages. cited by applicant

U.S. Appl. No. 60/490,768, filed Jul. 28, 2003, entitled "Method for synchronizing audio playback between multiple networked devices," 13 pages. cited by applicant

U.S. Appl. No. 60/825,407, filed Sep. 12, 2006, entitled "Controlling and manipulating groupings in a multi-zone music or media system," 82 pages. cited by applicant

UPnP; "Universal Plug and Play Device Architecture," Jun. 8, 2000; version 1.0; Microsoft Corporation; pp. 1-54. cited by applicant

Yamaha DME 64 Owner's Manual; copyright 2004, 80 pages. cited by applicant

Yamaha DME Designer 3.0 Owner's Manual; Copyright 2008, 501 pages. cited by applicant

Yamaha DME Designer 3.5 setup manual guide; copyright 2004, 16 pages. cited by applicant

Yamaha DME Designer 3.5 User Manual; Copyright 2004, 507 pages. cited by applicant

## Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 17/473,212 (filed 13 Sep. 2021), which is a continuation of U.S. patent application Ser. No. 15/645,121 (filed 10 Jul. 2017; now U.S. Pat. No. 11,119,540), which is a continuation of U.S. patent application Ser. No. 14/799,323 (filed 14 Jul. 2015; now U.S. Pat. No. 9,703,324), which is a continuation of U.S. patent application Ser. No. 14/041,115 (filed 30 Sep. 2013; now U.S. Pat. No. 9,223,353). All of the foregoing priority applications are incorporated herein by reference in their entirety.

### FIELD OF THE DISCLOSURE

(1) The disclosure is related to consumer goods and, more particularly, to methods, systems, products, features, services, and other items directed to media playback or some aspect thereof.

### BACKGROUND

(2) Digital music has become readily available due in part to the development of consumer level technology that has allowed people to listen to digital music on a personal audio device. The consumer's increasing preference for digital audio has also resulted in the integration of personal audio devices into PDAs, cellular phones, and other mobile devices. The portability of these mobile devices has enabled people to take the music listening experience with them and outside of the home. People have become able to consume digital music, like digital music files or even Internet radio, in the home through the use of their computer or similar devices. Now there are many different ways to consume digital music, in addition to other digital content including digital video and photos, stimulated in many ways by high-speed Internet access at home, mobile broadband Internet access, and the consumer's hunger for digital media.

(3) Until recently, options for accessing and listening to digital audio in an out-loud setting were severely limited. In 2005, Sonos offered for sale its first digital audio system that enabled people to, among many other things, access virtually unlimited sources of audio via one or more networked connected zone players, dynamically group or ungroup zone players upon command, wirelessly send the audio over a local network amongst zone players, and play the digital audio out loud across multiple zone players in synchrony. The Sonos system can be controlled by software applications running on network capable mobile devices and computers.

(4) Given the insatiable appetite of consumers towards digital media, there continues to be a need to develop consumer technology that revolutionizes the way people access and consume digital media.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

(1) Features, aspects, and advantages of the presently disclosed technology may be better understood with regard to the following description, appended claims, and accompanying drawings where:

(2) FIG. 1 shows an example configuration in which certain embodiments may be practiced;

(3) FIG. 2A shows an illustration of an example zone player having a built-in amplifier and transducers;

(4) FIG. 2B shows an illustration of an example zone player having a built-in amplifier and

connected to external speakers;

(5) FIG. 2C shows an illustration of an example zone player connected to an AN receiver and speakers;

(6) FIG. 3 shows an illustration of an example controller;

(7) FIG. 4 shows an internal functional block diagram of an example zone player;

(8) FIG. 5 shows an internal functional block diagram of an example controller;

(9) FIG. 6 shows an example playback queue configuration for a network media system;

(10) FIG. 7 shows an example ad-hoc playback network;

(11) FIG. 8 shows a system including a plurality of networks including a cloud-based network and at least one local playback network;

(12) FIG. 9 shows an example flow diagram for configuring a proximity sensor module on a playback device;

(13) FIG. 10 shows an example playback device with a control panel;

(14) FIG. 11 shows an example configuration of an infrared (IR) sensor and a capacitive sensor implemented along a control panel;

(15) FIG. 12A shows a first example configuration of a capacitive sensor implemented along a control panel of a playback device; and

(16) FIG. 12B shows a second example configuration of a capacitive sensor implemented along a control panel of a playback device.

(17) In addition, the drawings are for the purpose of illustrating example embodiments, but it is understood that the inventions are not limited to the arrangements and instrumentality shown in the drawings.

## DETAILED DESCRIPTION

### I. Overview

(18) Embodiments described herein involve intelligently revealing selectable icons on a control panel of a playback device based on proximity detection, and further involve configurations of capacitive proximity sensors for detecting physical movement within a wider proximal range of the playback device.

(19) In one example, the control panel of the playback device may include one or more back-lit icons or buttons selectable by a user to control functions of the playback device. In some cases, such as for purposes of energy conservation or room-ambience preservation, the icons may be configured to remain dark or dimmed by default, and illuminated when a determination has been made that a user may wish to view and potentially select the icon. As such, illumination of the icons may be based on a proximity detection of the user approaching the playback device.

(20) A proximity sensor module of the playback device may be configured to detect physical movement or presence such as that of the user, within a proximal range of the playback device. The icons may then be illuminated based on a detection of the physical movement or presence. The proximity sensor module may include one or more different types of sensors, such as a capacitive sensors, infrared (IR) sensors, and photo-sensors. Other types of sensors are also possible.

(21) In one example, the proximity sensor module may include a capacitive sensor configured to detect a change in capacitance near the control panel of the playback device. In some cases however, such as if the playback device is located near a plasma television, the capacitive sensor may be falsely triggered while the plasma television is on. In one example, a gain of the capacitive sensor may be reduced in the presence of the plasma television to reduce false triggers. However, a reduced capacitive sensor gain may result in signals indicating the physical movement becoming indistinguishable from a baseline noise signal for the capacitive sensor. Additional signal processing may be performed to better distinguish the signals, but may result in slower response times.

(22) In another example, the proximity sensor module may include an IR sensor configured to detect reflected infrared light pulses. In some cases however, if the ambient light level of the

playback device is high, the IR sensor may be flooded by the high ambient light level such that the IR sensor may not be able to reliably discern the reflected light pulses from the baseline ambient light.

(23) In one embodiment of the present application, the proximity sensor module may include both a capacitive sensor and an IR sensor configured to complementarily detect physical movement or presence, with reduced false triggers and improved detection. In one example, respective sensitivities of the capacitive sensor and the IR sensor may be adjusted based on the ambient light level around the playback device. For instance, an ambient light sensor, which may be the IR sensor and/or another type of sensor, may be configured to determine the ambient light level.

(24) For the IR sensor, if the ambient light level is high, a dynamic range of the IR sensor may be reduced, and a pulse width of infrared light pulses generated from the IR sensor may be lengthened. On the other hand, if the ambient light level is low, the dynamic range of the IR sensor may be increased, and the pulse width of infrared light pulses may be shortened. For the capacitive sensor, if the ambient light level is high, a gain of the capacitive sensor may be increased, and if the ambient light level is low, the gain of the capacitive sensor may be reduced. In one example, different combinations of IR sensor dynamic ranges and infrared light pulse widths may be configured for different levels of ambient light, and different capacitive sensor gain levels may be configured for different levels of ambient light.

(25) In combination, when the ambient light level is high, the capacitive sensor may become more sensitive due to the increased gain level, while the IR sensor may become less sensitive due to the reduced dynamic range and increased infrared light pulse width. On the other hand, when the ambient light level is low, the capacitive sensor may become less sensitive due to the decreased gain level, while the IR sensor may become more sensitive due to the increased dynamic range and shorted infrared light pulse widths. As indicated above, different configurations of IR sensor and capacitive sensor sensitivities may be implemented for different levels of ambient light. Based on this example embodiment, the back-lit icons on the control panel of the playback device may be illuminated when either the IR sensor or the capacitive sensor detects the physical movement or presence of the user within the proximal range of the playback device.

(26) The capacitive sensor may also complement the IR sensor by providing additional off-axis detections. For instance, the IR sensor may be positioned along a top side of the playback device and accordingly, may have a detection range limited to space above the playback device. In this case, an approach of the user from the front side of the playback device may not be detected by the IR sensor. The capacitive sensor however, may be less directional and may provide detection of physical movement from the front side of the playback device, even if the capacitive sensor is positioned along the top side of the playback device as well.

(27) In some embodiments of the present application, the off-axis, or zero-degree approach detection by capacitive sensors may further be improved by coupling an antenna of the capacitive sensor to other components of the playback device. In one example, the playback device may be configured to communicate via wireless communication and may include an RF antenna component. In one case, an RF antenna ground plane of the RF antenna component may be oriented orthogonally to the capacitive sensor, and coupling the antenna of the capacitive sensor to the RF antenna ground plane may provide detection in an axial direction orthogonal to the axial direction of the capacitive sensor. In the case the capacitive sensor is positioned along the top surface of the playback device, the axial direction of the capacitive sensor may be directed to the space above the playback device. In this case, if the RF antenna ground is along the front surface of the playback device, the orthogonal axial direction provided by coupling the antenna of the capacitive sensor to the RF antenna ground may be directed to the space in front of the playback device. Accordingly, the capacitive sensor may provide improved detection of physical movement in the space in front of the playback device.

(28) In some cases, the playback device may include a speaker grille covering the front surface of



the playback device. Similar to the RF antenna component, the speaker grille may also be coupled to the antenna of the capacitive sensor, thereby providing improved detection of physical movement in the space in front of the playback device. In some cases however, playback of audio by the playback device may generate sufficient change in capacitance detected by the speaker grille and cause false triggers. As such, in one embodiment, the speaker grille and the antenna of the capacitive sensor may be coupled when the playback device is not playing audio content, and decoupled when the playback device is playing audio content.

(29) While the discussions above are directed to proximity detection for the purposes of revealing icons or buttons on the control panel of the playback device, one having ordinary skill in the art will appreciate that proximity detection may be utilized in other capacities as well. For instance, a playback device may pre-cache audio content in anticipation of a user providing input via the control panel to cause the playback device to playback audio content. In another instance, the playback device may be in an in-active state such that an amplifier of the playback device may be turned off to reduce power consumption while the playback device is not playing audio content. In this instance, the amplifier of the playback device may be turned on in anticipation of a user providing input via the control panel to cause the playback device to playback audio content based on proximity detection. Other examples are also possible.

(30) As indicated above, the present application involves intelligently revealing selectable icons on a control panel of a playback device based on proximity detection. In one aspect, a method is provided. The method involves determining an ambient light level based on a detection by a light sensor of ambient light of a control area for a playback device, and adjusting, based on the ambient light level, a sensitivity of an infrared (IR) proximity sensor. The IR proximity sensor is configured to detect physical movement. The method further involves adjusting, based on the ambient light level, a sensitivity of a capacitive proximity sensor. The capacitive proximity sensor is configured to detect a physical movement. The method also involves determining a physical approach of an entity towards the playback device based on the detection of the physical movement by at least one of the IR proximity sensor and the capacitive proximity sensor, and responsively causing a control area of the playback device to be illuminated.

(31) In another aspect, a device is provided. The device includes a processor, an infrared (IR) proximity sensor, a capacitive proximity sensor, and memory having stored thereon instructions executable by the processor to cause the playback device to perform functions. The functions include determining an ambient light level of a control area for a playback device based on a detection by a light sensor, and adjusting, based on the ambient light level, a sensitivity of an infrared (IR) proximity sensor. The IR proximity sensor is configured to detect physical movement. The functions further include adjusting, based on the ambient light level, a sensitivity of a capacitive proximity sensor. The capacitive proximity sensor is configured to detect a physical movement. The functions further include determining a physical approach of an entity towards the playback device based on the detection of the physical movement by at least one of the IR proximity sensor and the capacitive proximity sensor, and responsively causing a control area of the playback device to be illuminated.

(32) In yet another aspect, a non-transitory computer readable memory is provided. The non-transitory computer readable memory has stored thereon instructions executable by a computing device to cause the computing device to perform functions. The functions include determining an ambient light level of a control area for a playback device based on a detection by a light sensor, and adjusting, based on the ambient light level, a sensitivity of an infrared (IR) proximity sensor. The IR proximity sensor is configured to detect physical movement. The functions also include adjusting, based on the ambient light level, a sensitivity of a capacitive proximity sensor. The capacitive proximity sensor is configured to detect a physical movement. The functions further include determining a physical approach of an entity towards the playback device based on the detection of the physical movement by at least one of the IR proximity sensor and the capacitive

proximity sensor, and responsively causing a control area of the playback device to be illuminated.

(33) Other embodiments, as those discussed in the following and others as can be appreciated by one having ordinary skill in the art are also possible.

## II. Example Operating Environment

(34) Referring now to the drawings, in which like numerals can refer to like parts throughout the figures, FIG. 1 shows an example media system configuration **100** in which one or more embodiments disclosed herein can be practiced or implemented.

(35) By way of illustration, the media system configuration **100** is associated with a home having multiple zones, although it should be understood that the home could be configured with only one zone. Additionally, one or more zones can be added to the configuration **100** over time. Each zone may be assigned by a user to a different room or space, such as, for example, an office, bathroom, bedroom, kitchen, dining room, family room, home theater room, utility or laundry room, and patio. A single zone might also include multiple rooms or spaces if so configured. With respect to FIG. 1, one or more of zone players **102-124** are shown in each respective zone. Zone players **102-124**, also referred to herein as playback devices, multimedia units, speakers, players, and so on, provide audio, video, and/or audiovisual output. A controller **130** (e.g., shown in the kitchen for purposes of this illustration) provides control to the media system configuration **100**. Controller **130** may be fixed to a zone, or alternatively, mobile such that it can be moved about the zones. The media system configuration **100** may also include more than one controller **130**, and additional controllers may be added to the system over time.

(36) The media system configuration **100** illustrates an example whole house media system, though it is understood that the technology described herein is not limited to, among other things, its particular place of application or to an expansive system like a whole house media system **100** of FIG. 1.

### (37) a. Example Zone Players

(38) FIGS. 2A, 2B, and 2C show example types of zone players. Zone players **200**, **202**, and **204** of FIGS. 2A, 2B, and 2C, respectively, can correspond to any of the zone players **102-124** of FIG. 1, for example. In some embodiments, audio is reproduced using only a single zone player, such as by a full-range player. In some embodiments, audio is reproduced using two or more zone players, such as by using a combination of full-range players or a combination of full-range and specialized players. In some embodiments, zone players **200-204** may also be referred to as a “smart speaker,” because they contain processing capabilities beyond the reproduction of audio, more of which is described below.

(39) FIG. 2A illustrates a zone player **200** that includes sound producing equipment **208** capable of reproducing full-range sound. The sound may come from an audio signal that is received and processed by zone player **200** over a wired or wireless data network. Sound producing equipment **208** includes one or more built-in amplifiers and one or more acoustic transducers (e.g., speakers). A built-in amplifier is described more below with respect to FIG. 4. A speaker or acoustic transducer can include, for example, any of a tweeter, a mid-range driver, a low-range driver, and a subwoofer. In some embodiments, zone player **200** can be statically or dynamically configured to play stereophonic audio, monaural audio, or both. In some embodiments, zone player **200** may be dynamically configured to reproduce a subset of full-range sound, such as when zone player **200** is grouped with other zone players to play stereophonic audio, monaural audio, and/or surround audio or when the media content received by zone player **200** is less than full-range.

(40) FIG. 2B illustrates zone player **202** that includes a built-in amplifier to power a set of detached speakers **210**. A detached speaker can include, for example, any type of loudspeaker. Zone player **202** may be configured to power one, two, or more separate loudspeakers. Zone player **202** may be configured to communicate an audio signal (e.g., right and left channel audio or more channels depending on its configuration) to the detached speakers **210** via a wired path.

(41) FIG. 2C illustrates zone player **204** that does not include a built-in amplifier, but is configured

to communicate an audio signal, received over a data network, to an audio (or “audio/video”) receiver **214** with built-in amplification.

(42) Referring back to FIG. **1**, in some embodiments, one, some, or all of the zone players **102** to **124** can retrieve audio directly from a source. For example, a particular zone player in a zone or zone group may be assigned to a playback queue (or “queue”). The playback queue contains information corresponding to zero or more audio items for playback by the associated zone or zone group. The playback queue may be stored in memory on a zone player or some other designated device. Each item contained in the playback queue may comprise a uniform resource identifier (URI) or some other identifier that can be used by the zone player(s) to seek out and/or retrieve the audio items from the identified audio source(s). Depending on the item, the audio source might be found on the Internet (e.g., the cloud), locally from another device over the data network **128** (described further below), from the controller **130**, stored on the zone player itself, or from an audio source communicating directly to the zone player. In some embodiments, the zone player can reproduce the audio itself (e.g., play the audio), send the audio to another zone player for reproduction, or both where the audio is reproduced by the zone player as well as one or more additional zone players (possibly in synchrony). In some embodiments, the zone player may play a first audio content (or alternatively, may not play the content at all), while sending a second, different audio content to another zone player(s) for reproduction. To the user, each item in a playback queue is represented on an interface of a controller by an element such as a track name, album name, radio station name, playlist, or other some other representation. A user can populate the playback queue with audio items of interest. The user may also modify and clear the playback queue, if so desired.

(43) By way of illustration, SONOS, Inc. of Santa Barbara, California presently offers for sale zone players referred to as a “PLAY:5,” “PLAY:3,” “PLAYBAR,” “CONNECT:AMP,” “CONNECT,” and “SUB.” Any other past, present, and/or future zone players can additionally or alternatively be used to implement the zone players of example embodiments disclosed herein. Additionally, it is understood that a zone player is not limited to the particular examples illustrated in FIGS. **2A**, **2B**, and **2C** or to the SONOS product offerings. For example, a zone player may include a wired or wireless headphone. In yet another example, a zone player might include a sound bar for television. In yet another example, a zone player may include or interact with a docking station for an Apple iPod™ or similar device.

(44) b. Example Controllers

(45) FIG. **3** illustrates an example wireless controller **300** in docking station **302**. By way of illustration, controller **300** may correspond to controlling device **130** of FIG. **1**. Docking station **302**, if provided or used, may provide power to the controller **300** and additionally may charge a battery of controller **300**. In some embodiments, controller **300** may be provided with a touch screen **304** that allows a user to interact through touch with the controller **300**, for example, to retrieve and navigate a playlist of audio items, modify and/or clear the playback queue of one or more zone players, control other operations of one or more zone players, and provide overall control of the system configuration **100**. In other embodiments, other input mechanisms such as voice control may be used to interact with the controller **300**. In certain embodiments, any number of controllers can be used to control the system configuration **100**. In some embodiments, there may be a limit set on the number of controllers that can control the system configuration **100**. The controllers might be wireless like wireless controller **300** or wired to data network **128**.

(46) In some embodiments, if more than one controller is used in system **100** of FIG. **1**, each controller may be coordinated to display common content, and may all be dynamically updated to indicate changes made to the system **100** from a single controller. Coordination can occur, for instance, by a controller periodically requesting a state variable directly or indirectly from one or more of the zone players; the state variable may provide information about system **100**, such as current zone group configuration, what is playing in one or more zones, volume levels, and other

items of interest. The state variable may be passed around on data network **128** between zone players (and controllers, if so desired) as needed or as often as programmed.

(47) In addition, an application running on any network-enabled portable device, such as an iPhone™, iPad™, Android™ powered phone or tablet, or any other smart phone or network-enabled device can be used as controller **130**. An application running on a laptop or desktop personal computer (PC) or Mac™ can also be used as controller **130**. Such controllers may connect to system **100** through an interface with data network **128**, a zone player, a wireless router, or using some other configured connection path. Example controllers offered by Sonos, Inc. of Santa Barbara, California include a “Controller **200**,” “SONOS® CONTROL,” “SONOS® Controller for iPhone™,” “SON OS® Controller for iPad™,” “SONOS® Controller for Android™,” “SONOS® Controller for Mac™ or PC.”

(48) c. Example Data Connection

(49) Zone players **102-124** of FIG. **1** are coupled directly or indirectly to a data network, such as data network **128**. Controller **130** may also be coupled directly or indirectly to data network **128** or individual zone players. Data network **128** is represented by an octagon in the figure to stand out from other representative components. While data network **128** is shown in a single location, it is understood that such a network is distributed in and around system **100**. Particularly, data network **128** can be a wired network, a wireless network, or a combination of both wired and wireless networks. In some embodiments, one or more of the zone players **102-124** are wirelessly coupled to data network **128** based on a proprietary mesh network. In some embodiments, one or more of the zone players are coupled to data network **128** using a centralized access point such as a wired or wireless router. In some embodiments, one or more of the zone players **102-124** are coupled via a wire to data network **128** using Ethernet or similar technology. In addition to the one or more zone players **102-124** connecting to data network **128**, data network **128** can further allow access to a wide area network, such as the Internet.

(50) In some embodiments, connecting any of the zone players **102-124**, or some other connecting device, to a broadband router, can create data network **128**. Other zone players **102-124** can then be added wired or wirelessly to the data network **128**. For example, a zone player (e.g., any of zone players **102-124**) can be added to the system configuration **100** by simply pressing a button on the zone player itself (or perform some other action), which enables a connection to be made to data network **128**. The broadband router can be connected to an Internet Service Provider (ISP), for example. The broadband router can be used to form another data network within the system configuration **100**, which can be used in other applications (e.g., web surfing). Data network **128** can also be used in other applications, if so programmed. An example, second network may implement SONOSNET™ protocol, developed by SONOS, Inc. of Santa Barbara. SONOSNET™ represents a secure, AES-encrypted, peer-to-peer wireless mesh network. Alternatively, in certain embodiments, the data network **128** is the same network, such as a traditional wired or wireless network, used for other applications in the household.

(51) d. Example Zone Configurations

(52) A particular zone can contain one or more zone players. For example, the family room of FIG. **1** contains two zone players **106** and **108**, while the kitchen is shown with one zone player **102**. In another example, the home theater room contains additional zone players to play audio from a 5.1 channel or greater audio source (e.g., a movie encoded with 5.1 or greater audio channels). In some embodiments, one can position a zone player in a room or space and assign the zone player to a new or existing zone via controller **130**. As such, zones may be created, combined with another zone, removed, and given a specific name (e.g., “Kitchen”), if so desired and programmed to do so with controller **130**. Moreover, in some embodiments, zone configurations may be dynamically changed even after being configured using controller **130** or some other mechanism.

(53) In some embodiments, a “bonded zone” is a zone that contains two or more zone players, such as the two zone players **106** and **108** in the family room whereby the two zone players **106** and **108**

can be configured to play the same audio source in synchrony. In one example, the two zone players **106** and **108** can be paired to play two separate sounds in left and right channels, for example. In other words, the stereo effects of a sound can be reproduced or enhanced through the two zone players **106** and **108**, one for the left sound and the other for the right sound. In another example two or more zone players can be sonically consolidated to form a single, consolidated zone player. A consolidated zone player (though made up of multiple, separate devices) can be configured to process and reproduce sound differently than an unconsolidated zone player or zone players that are paired, because a consolidated zone player has additional speaker drivers from which sound can be passed. The consolidated zone player can further be paired with a single zone player or yet another consolidated zone player. Each playback device of a consolidated playback device can be set in a consolidated mode, for example.

(54) In certain embodiments, paired or consolidated zone players (also referred to as “bonded zone players”) can play audio in synchrony with other zone players in the same or different zones.

(55) According to some embodiments, one can continue to do any of: group, consolidate, and pair zone players, for example, until a desired configuration is complete. The actions of grouping, consolidation, and pairing are preferably performed through a control interface, such as using controller **130**, and not by physically connecting and re-connecting speaker wire, for example, to individual, discrete speakers to create different configurations. As such, certain embodiments described herein provide a more flexible and dynamic platform through which sound reproduction can be offered to the end-user.

(56) e. Example Audio Sources

(57) In some embodiments, each zone can play from the same audio source as another zone or each zone can play from a different audio source. For example, someone can be grilling on the patio and listening to jazz music via zone player **124**, while someone is preparing food in the kitchen and listening to classical music via zone player **102**. Further, someone can be in the office listening to the same jazz music via zone player **110** that is playing on the patio via zone player **124**. In some embodiments, the jazz music played via zone players **110** and **124** is played in synchrony. Synchronizing playback amongst zones allows for an individual to pass through zones while seamlessly (or substantially seamlessly) listening to the audio. Further, zones can be put into a “party mode” such that all associated zones will play audio in synchrony.

(58) Sources of audio content to be played by zone players **102-124** are numerous. In some embodiments, audio on a zone player itself may be accessed and played. In some embodiments, audio on a controller may be accessed via the data network **128** and played. In some embodiments, music from a personal library stored on a computer or networked-attached storage (NAS) may be accessed via the data network **128** and played. In some embodiments, Internet radio stations, shows, and podcasts may be accessed via the data network **128** and played. Music or cloud services that let a user stream and/or download music and audio content may be accessed via the data network **128** and played. Further, music may be obtained from traditional sources, such as a turntable or CD player, via a line-in connection to a zone player, for example. Audio content may also be accessed using a different protocol, such as Airplay™, which is a wireless technology by Apple, Inc., for example. Audio content received from one or more sources can be shared amongst the zone players **102** to **124** via data network **128** and/or controller **130**. The above-disclosed sources of audio content are referred to herein as network-based audio information sources. However, network-based audio information sources are not limited thereto.

(59) In some embodiments, the example home theater zone players **116**, **118**, **120** are coupled to an audio information source such as a television **132**. In some examples, the television **132** is used as a source of audio for the home theater zone players **116**, **118**, **120**, while in other examples audio information from the television **132** may be shared with any of the zone players **102-124** in the audio system **100**.

III. Example Zone Players

(60) Referring now to FIG. 4, there is shown an example block diagram of a zone player **400** in accordance with an embodiment. Zone player **400** includes a network interface **402**, a processor **408**, a memory **410**, an audio processing component **412**, one or more modules **414**, an audio amplifier **416**, and a speaker unit **418** coupled to the audio amplifier **416**. FIG. 2A shows an example illustration of such a zone player. Other types of zone players may not include the speaker unit **418** (e.g., such as shown in FIG. 2B) or the audio amplifier **416** (e.g., such as shown in FIG. 2C). Further, it is contemplated that the zone player **400** can be integrated into another component. For example, the zone player **400** could be constructed as part of a television, lighting, or some other device for indoor or outdoor use.

(61) In some embodiments, network interface **402** facilitates a data flow between zone player **400** and other devices on a data network **128**. In some embodiments, in addition to getting audio from another zone player or device on data network **128**, zone player **400** may access audio directly from the audio source, such as over a wide area network or on the local network. In some embodiments, the network interface **402** can further handle the address part of each packet so that it gets to the right destination or intercepts packets destined for the zone player **400**. Accordingly, in certain embodiments, each of the packets includes an Internet Protocol (IP)-based source address as well as an IP-based destination address.

(62) In some embodiments, network interface **402** can include one or both of a wireless interface **404** and a wired interface **406**. The wireless interface **404**, also referred to as a radio frequency (RF) interface, provides network interface functions for the zone player **400** to wirelessly communicate with other devices (e.g., other zone player(s), speaker(s), receiver(s), component(s) associated with the data network **128**, and so on) in accordance with a communication protocol (e.g., any wireless standard including IEEE 802.11a, 802.11b, 802.11g, 802.11n, 802.11ac, 802.15, 4G mobile communication standard, and so on). Wireless interface **404** may include one or more radios. To receive wireless signals and to provide the wireless signals to the wireless interface **404** and to transmit wireless signals, the zone player **400** includes one or more antennas **420**. The wired interface **406** provides network interface functions for the zone player **400** to communicate over a wire with other devices in accordance with a communication protocol (e.g., IEEE 802.3). In some embodiments, a zone player includes multiple wireless **404** interfaces. In some embodiments, a zone player includes multiple wired **406** interfaces. In some embodiments, a zone player includes both of the interfaces **404** and **406**. In some embodiments, a zone player **400** includes only the wireless interface **404** or the wired interface **406**.

(63) In some embodiments, the processor **408** is a clock-driven electronic device that is configured to process input data according to instructions stored in memory **410**. The memory **410** is data storage that can be loaded with one or more software module(s) **414**, which can be executed by the processor **408** to achieve certain tasks. In the illustrated embodiment, the memory **410** is a tangible machine-readable medium storing instructions that can be executed by the processor **408**. In some embodiments, a task might be for the zone player **400** to retrieve audio data from another zone player or a device on a network (e.g., using a uniform resource locator (URL) or some other identifier). In some embodiments, a task may be for the zone player **400** to send audio data to another zone player or device on a network. In some embodiments, a task may be for the zone player **400** to synchronize playback of audio with one or more additional zone players. In some embodiments, a task may be to pair the zone player **400** with one or more zone players to create a multi-channel audio environment. Additional or alternative tasks can be achieved via the one or more software module(s) **414** and the processor **408**.

(64) The audio processing component **412** can include one or more digital-to-analog converters (DAC), an audio preprocessing component, an audio enhancement component or a digital signal processor, and so on. In some embodiments, the audio processing component **412** may be part of processor **408**. In some embodiments, the audio that is retrieved via the network interface **402** is processed and/or intentionally altered by the audio processing component **412**. Further, the audio

processing component **412** can produce analog audio signals. The processed analog audio signals are then provided to the audio amplifier **416** for playback through speakers **418**. In addition, the audio processing component **412** can include circuitry to process analog or digital signals as inputs to play from zone player **400**, send to another zone player on a network, or both play and send to another zone player on the network. An example input includes a line-in connection (e.g., an auto-detecting 3.5 mm audio line-in connection).

(65) The audio amplifier **416** is a device(s) that amplifies audio signals to a level for driving one or more speakers **418**. The one or more speakers **418** can include an individual transducer (e.g., a “driver”) or a complete speaker system that includes an enclosure including one or more drivers. A particular driver can be a subwoofer (e.g., for low frequencies), a mid-range driver (e.g., for middle frequencies), and a tweeter (e.g., for high frequencies), for example. An enclosure can be sealed or ported, for example. Each transducer may be driven by its own individual amplifier.

(66) A commercial example, presently known as the PLAY:5™, is a zone player with a built-in amplifier and speakers that is capable of retrieving audio directly from the source, such as on the Internet or on the local network, for example. In particular, the PLAY:5™ is a five-amp, five-driver speaker system that includes two tweeters, two mid-range drivers, and one woofer. When playing audio content via the PLAY:5, the left audio data of a track is sent out of the left tweeter and left mid-range driver, the right audio data of a track is sent out of the right tweeter and the right mid-range driver, and mono bass is sent out of the subwoofer. Further, both mid-range drivers and both tweeters have the same equalization (or substantially the same equalization). That is, they are both sent the same frequencies but from different channels of audio. Audio from Internet radio stations, online music and video services, downloaded music, analog audio inputs, television, DVD, and so on, can be played from the PLAY:5™.

#### IV. Example Controller

(67) Referring now to FIG. 5, there is shown an example block diagram for controller **500**, which can correspond to the controlling device **130** in FIG. 1. Controller **500** can be used to facilitate the control of multi-media applications, automation and others in a system. In particular, the controller **500** may be configured to facilitate a selection of a plurality of audio sources available on the network and enable control of one or more zone players (e.g., the zone players **102-124** in FIG. 1) through a wireless or wired network interface **508**. According to one embodiment, the wireless communications is based on an industry standard (e.g., infrared, radio, wireless standards including IEEE 802.11a, 802.11b, 802.11g, 802.11n, 802.11ac, 802.15, 4G mobile communication standard, and so on). Further, when a particular audio is being accessed via the controller **500** or being played via a zone player, a picture (e.g., album art) or any other data, associated with the audio and/or audio source can be transmitted from a zone player or other electronic device to controller **500** for display.

(68) Controller **500** is provided with a screen **502** and an input interface **514** that allows a user to interact with the controller **500**, for example, to navigate a playlist of many multimedia items and to control operations of one or more zone players. The screen **502** on the controller **500** can be an LCD screen, for example. The screen **500** communicates with and is commanded by a screen driver **504** that is controlled by a microcontroller (e.g., a processor) **506**. The memory **510** can be loaded with one or more application modules **512** that can be executed by the microcontroller **506** with or without a user input via the user interface **514** to achieve certain tasks. In some embodiments, an application module **512** is configured to facilitate grouping a number of selected zone players into a zone group to facilitate synchronized playback amongst the zone players in the zone group. In some embodiments, an application module **512** is configured to control the audio sounds (e.g., volume) of the zone players in a zone group. In operation, when the microcontroller **506** executes one or more of the application modules **512**, the screen driver **504** generates control signals to drive the screen **502** to display an application specific user interface accordingly.

(69) The controller **500** includes a network interface **508** that facilitates wired or wireless

communication with a zone player. In some embodiments, the commands such as volume control and audio playback synchronization are sent via the network interface **508**. In some embodiments, a saved zone group configuration is transmitted between a zone player and a controller via the network interface **508**. The controller **500** can control one or more zone players, such as **102-124** of FIG. **1**. There can be more than one controller for a particular system, and each controller may share common information with another controller, or retrieve the common information from a zone player, if such a zone player stores configuration data (e.g., such as a state variable). Further, a controller can be integrated into a zone player.

(70) It should be noted that other network-enabled devices such as an iPhone™, iPad™ or any other smart phone or network-enabled device (e.g., a networked computer such as a PC or Mac™) can also be used as a controller to interact or control zone players in a particular environment. In some embodiments, a software application or upgrade can be downloaded onto a network-enabled device to perform the functions described herein.

(71) In certain embodiments, a user can create a zone group (also referred to as a bonded zone) including at least two zone players from the controller **500**. The zone players in the zone group can play audio in a synchronized fashion, such that all of the zone players in the zone group playback an identical audio source or a list of identical audio sources in a synchronized manner such that no (or substantially no) audible delays or hiccups are to be heard. Similarly, in some embodiments, when a user increases the audio volume of the group from the controller **500**, the signals or data of increasing the audio volume for the group are sent to one of the zone players and causes other zone players in the group to be increased together in volume.

(72) A user via the controller **500** can group zone players into a zone group by activating a “Link Zones” or “Add Zone” soft button, or de-grouping a zone group by activating an “Unlink Zones” or “Drop Zone” button. For example, one mechanism for ‘joining’ zone players together for audio playback is to link a number of zone players together to form a group. To link a number of zone players together, a user can manually link each zone player or room one after the other. For example, assume that there is a multi-zone system that includes the following zones: Bathroom, Bedroom, Den, Dining Room, Family Room, and Foyer. In certain embodiments, a user can link any number of the six zone players, for example, by starting with a single zone and then manually linking each zone to that zone.

(73) In certain embodiments, a set of zones can be dynamically linked together using a command to create a zone scene or theme (subsequent to first creating the zone scene). For instance, a “Morning” zone scene command can link the Bedroom, Office, and Kitchen zones together in one action. Without this single command, the user would manually and individually link each zone. The single command may include a mouse click, a double mouse click, a button press, a gesture, or some other programmed or learned action. Other kinds of zone scenes can be programmed or learned by the system over time.

(74) In certain embodiments, a zone scene can be triggered based on time (e.g., an alarm clock function). For instance, a zone scene can be set to apply at 8:00 am. The system can link appropriate zones automatically, set specific music to play, and then stop the music after a defined duration and revert the zones to their prior configuration. Although any particular zone can be triggered to an “On” or “Off” state based on time, for example, a zone scene enables any zone(s) linked to the scene to play a predefined audio (e.g., a favorable song, a predefined playlist) at a specific time and/or for a specific duration. If, for any reason, the scheduled music failed to be played (e.g., an empty playlist, no connection to a share, failed Universal Plug and Play (UPnP), no Internet connection for an Internet Radio station, and so on), a backup buzzer can be programmed to sound. The buzzer can include a sound file that is stored in a zone player, for example.

## V. Playback Queue

(75) As discussed above, in some embodiments, a zone player may be assigned to a playback queue identifying zero or more media items for playback by the zone player. The media items identified



in a playback queue may be represented to the user via an interface on a controller. For instance, the representation may show the user (or users if more than one controller is connected to the system) how the zone player is traversing the playback queue, such as by highlighting the “now playing” item, graying out the previously played item(s), highlighting the to-be-played item(s), and so on.

(76) In some embodiments, a single zone player is assigned to a playback queue. For example, zone player **114** in the bathroom of FIG. **1** may be linked or assigned to a “Bathroom” playback queue. In an embodiment, the “Bathroom” playback queue might have been established by the system as a result of the user naming the zone player **114** to the bathroom. As such, contents populated and identified in the “Bathroom” playback queue can be played via the zone player **114** (the bathroom zone).

(77) In some embodiments, a zone or zone group is assigned to a playback queue. For example, zone players **106** and **108** in the family room of FIG. **1** may be linked or assigned to a “Family room” playback queue. In another example, if family room and dining room zones were grouped, then the new group would be linked or assigned to a family room+dining room playback queue. In some embodiments, the family room+dining room playback queue would be established based upon the creation of the group. In some embodiments, upon establishment of the new group, the family room+dining room playback queue can automatically include the contents of one (or both) of the playback queues associated with either the family room or dining room or both. In one instance, if the user started with the family room and added the dining room, then the contents of the family room playback queue would become the contents of the family room+dining room playback queue. In another instance, if the user started with the family room and added the dining room, then the family room playback queue would be renamed to the family room+dining room playback queue. If the new group was “ungrouped,” then the family room+dining room playback queue may be removed from the system and/or renamed to one of the zones (e.g., renamed to “family room” or “dining room”). After ungrouping, each of the family room and the dining room will be assigned to a separate playback queue. One or more of the zone players in the zone or zone group may store in memory the associated playback queue.

(78) As such, when zones or zone groups are “grouped” or “ungrouped” dynamically by the user via a controller, the system will, in some embodiments, establish or remove/rename playback queues respectively, as each zone or zone group is to be assigned to a playback queue. In other words, the playback queue operates as a container that can be populated with media items for playback by the assigned zone. In some embodiments, the media items identified in a playback queue can be manipulated (e.g., re-arranged, added to, deleted from, and so on).

(79) By way of illustration, FIG. **6** shows an example network **600** for media content playback. As shown, the example network **600** includes example zone players **612** and **614**, example audio sources **662** and **664**, and example media items **620**. The example media items **620** may include playlist **622**, music track **624**, favorite Internet radio station **626**, playlists **628** and **630**, and album **632**. In one embodiment, the zone players **612** and **614** may be any of the zone players shown in FIGS. **1**, **2**, and **4**. For instance, zone players **612** and **614** may be the zone players **106** and **108** in the Family Room.

(80) In one example, the example audio sources **662** and **664**, and example media items **620** may be partially stored on a cloud network, discussed more below in connection to FIG. **8**. In some cases, the portions of the audio sources **662**, **664**, and example media items **620** may be stored locally on one or both of the zone players **612** and **614**. In one embodiment, playlist **622**, favorite Internet radio station **626**, and playlist **630** may be stored locally, and music track **624**, playlist **628**, and album **632** may be stored on the cloud network.

(81) Each of the example media items **620** may be a list of media items playable by a zone player(s). In one embodiment, the example media items may be a collection of links or pointers (i.e., URI) to the underlying data for media items that are stored elsewhere, such as the audio

sources **662** and **664**. In another embodiment, the media items may include pointers to media content stored on the local zone player, another zone player over a local network, or a controller device connected to the local network.

(82) As shown, the example network **600** may also include an example queue **602** associated with the zone player **612**, and an example queue **604** associated with the zone player **614**. Queue **606** may be associated with a group, when in existence, comprising zone players **612** and **614**. Queue **606** might comprise a new queue or exist as a renamed version of queue **602** or **604**. In some embodiments, in a group, the zone players **612** and **614** would be assigned to queue **606** and queue **602** and **604** would not be available at that time. In some embodiments, when the group is no longer in existence, queue **606** is no longer available. Each zone player and each combination of zone players in a network of zone players, such as those shown in FIG. 1 or that of example zone players **612**, **614**, and example combination **616**, may be uniquely assigned to a corresponding playback queue.

(83) A playback queue, such as playback queues **602-606**, may include identification of media content to be played by the corresponding zone player or combination of zone players. As such, media items added to the playback queue are to be played by the corresponding zone player or combination of zone players. The zone player may be configured to play items in the queue according to a specific order (such as an order in which the items were added), in a random order, or in some other order.

(84) The playback queue may include a combination of playlists and other media items added to the queue. In one embodiment, the items in playback queue **602** to be played by the zone player **612** may include items from the audio sources **662**, **664**, or any of the media items **622-632**. The playback queue **602** may also include items stored locally on the zone player **612**, or items accessible from the zone player **614**. For instance, the playback queue **602** may include Internet radio **626** and album **632** items from audio source **662**, and items stored on the zone player **612**.

(85) When a media item is added to the queue via an interface of a controller, a link to the item may be added to the queue. In a case of adding a playlist to the queue, links to the media items in the playlist may be provided to the queue. For example, the playback queue **602** may include pointers from the Internet radio **626** and album **632**, pointers to items on the audio source **662**, and pointers to items on the zone player **612**. In another case, a link to the playlist, for example, rather than a link to the media items in the playlist may be provided to the queue, and the zone player or combination of zone players may play the media items in the playlist by accessing the media items via the playlist. For example, the album **632** may include pointers to items stored on audio source **662**. Rather than adding links to the items on audio source **662**, a link to the album **632** may be added to the playback queue **602**, such that the zone player **612** may play the items on the audio source **662** by accessing the items via pointers in the album **632**.

(86) In some cases, contents as they exist at a point in time within a playback queue may be stored as a playlist, and subsequently added to the same queue later or added to another queue. For example, contents of the playback queue **602**, at a particular point in time, may be saved as a playlist, stored locally on the zone player **612** and/or on the cloud network. The saved playlist may then be added to playback queue **604** to be played by zone player **614**.

## VI. Example Ad-Hoc Network

(87) Particular examples are now provided in connection with FIG. 7 to describe, for purposes of illustration, certain embodiments to provide and facilitate connection to a playback network. FIG. 7 shows that there are three zone players **702**, **704** and **706** and a controller **708** that form a network branch that is also referred to as an Ad-Hoc network **710**. The network **710** may be wireless, wired, or a combination of wired and wireless technologies. In general, an Ad-Hoc (or “spontaneous”) network is a local area network or other small network in which there is generally no one access point for all traffic. With an established Ad-Hoc network **710**, the devices **702**, **704**, **706** and **708** can all communicate with each other in a “peer-to-peer” style of communication, for example.

Furthermore, devices may join and/or leave from the network **710**, and the network **710** will automatically reconfigure itself without needing the user to reconfigure the network **710**. While an Ad-Hoc network is referenced in FIG. 7, it is understood that a playback network may be based on a type of network that is completely or partially different from an Ad-Hoc network.

(88) Using the Ad-Hoc network **710**, the devices **702**, **704**, **706**, and **708** can share or exchange one or more audio sources and be dynamically grouped (or ungrouped) to play the same or different audio sources. For example, the devices **702** and **704** are grouped to playback one piece of music, and at the same time, the device **706** plays back another piece of music. In other words, the devices **702**, **704**, **706** and **708**, as shown in FIG. 7, form a HOUSEHOLD that distributes audio and/or reproduces sound. As used herein, the term HOUSEHOLD (provided in uppercase letters to disambiguate from the user's domicile) is used to represent a collection of networked devices that are cooperating to provide an application or service. An instance of a HOUSEHOLD is identified with a household **710** (or household identifier), though a HOUSEHOLD may be identified with a different area or place.

(89) In certain embodiments, a household identifier (HHID) is a short string or an identifier that is computer-generated to help ensure that it is unique. Accordingly, the network **710** can be characterized by a unique HHID and a unique set of configuration variables or parameters, such as channels (e.g., respective frequency bands), service set identifier (SSID) (a sequence of alphanumeric characters as a name of a wireless network), and WEP keys (wired equivalent privacy) or other security keys. In certain embodiments, SSID is set to be the same as HHID.

(90) In certain embodiments, each HOUSEHOLD includes two types of network nodes: a control point (CP) and a zone player (ZP). The control point controls an overall network setup process and sequencing, including an automatic generation of required network parameters (e.g., security keys). In an embodiment, the CP also provides the user with a HOUSEHOLD configuration user interface. The CP function can be provided by a computer running a CP application module, or by a handheld controller (e.g., the controller **308**) also running a CP application module, for example. The zone player is any other device on the network that is placed to participate in the automatic configuration process. The ZP, as a notation used herein, includes the controller **308** or a computing device, for example. In some embodiments, the functionality, or certain parts of the functionality, in both the CP and the ZP are combined at a single node (e.g., a ZP contains a CP or vice-versa).

(91) In certain embodiments, configuration of a HOUSEHOLD involves multiple CPs and ZPs that rendezvous and establish a known configuration such that they can use a standard networking protocol (e.g., IP over Wired or Wireless Ethernet) for communication. In an embodiment, two types of networks/protocols are employed: Ethernet 802.3 and Wireless 802.11g. Interconnections between a CP and a ZP can use either of the networks/protocols. A device in the system as a member of a HOUSEHOLD can connect to both networks simultaneously.

(92) In an environment that has both networks in use, it is assumed that at least one device in a system is connected to both as a bridging device, thus providing bridging services between wired/wireless networks for others. The zone player **706** in FIG. 7 is shown to be connected to both networks, for example. The connectivity to the network **712** is based on Ethernet and/or Wireless, while the connectivity to other devices **702**, **704** and **708** is based on Wireless and Ethernet if so desired.

(93) It is understood, however, that in some embodiments each zone player **706**, **704**, **702** may access the Internet when retrieving media from the cloud (e.g., the Internet) via the bridging device. For example, zone player **702** may contain a uniform resource locator (URL) that specifies an address to a particular audio track in the cloud. Using the URL, the zone player **702** may retrieve the audio track from the cloud, and ultimately play the audio out of one or more zone players.

## VII. Another Example System Configuration

(94) FIG. 8 shows a system **800** including a plurality of interconnected networks including a cloud-based network and at least one local playback network. A local playback network includes a

plurality of playback devices or players, though it is understood that the playback network may contain only one playback device. In certain embodiments, each player has an ability to retrieve its content for playback. Control and content retrieval can be distributed or centralized, for example. Input can include streaming content provider input, third party application input, mobile device input, user input, and/or other playback network input into the cloud for local distribution and playback.

(95) As illustrated by the example system **800** of FIG. **8**, a plurality of content providers **820-850** can be connected to one or more local playback networks **860-870** via a cloud and/or other network **810**. Using the cloud **810**, a multimedia audio system server **820** (e.g., Sonos™), a mobile device **830**, a third party application **840**, a content provider **850** and so on can provide multimedia content (requested or otherwise) to local playback networks **860, 870**. Within each local playback network **860, 870**, a controller **862, 872** and a playback device **864, 874** can be used to playback audio content.

## VIII. Example Proximity Sensing Configuration

(96) As discussed above, embodiments described herein involve intelligently revealing selectable icons on a control panel of a playback device based on proximity detection. As indicated previously, a proximity sensor module may be configured to detect physical movement within a proximal range of the playback device, and based on the detected physical movement cause the selectable icons on the control panel to be illuminated and revealed. In some embodiments, the detection of physical movement within the proximal range of the playback device may indicate a user approaching the playback device, and accordingly, the selectable icons may be revealed for the user to view and potentially select.

(97) FIG. **9** shows an example flow diagram for configuring a proximity sensor module on a playback device, in accordance with at least some embodiments described herein. Method **900** shown in FIG. **9** presents an embodiment of a method that could be used in the environments **100, 600, 700**, and **800** with the systems **200, 202, 204, 300, 400**, and **500** for example, in communication with one or more devices, such as those illustrated in FIGS. **2-5**. Method **900** may include one or more operations, functions, or actions as illustrated by one or more of blocks **902-910**. Although the blocks are illustrated in sequential order, these blocks may also be performed in parallel, and/or in a different order than those described herein. Also, the various blocks may be combined into fewer blocks, divided into additional blocks, and/or removed based upon the desired implementation.

(98) In addition, for the method **900** and other processes and methods disclosed herein, the flowchart shows functionality and operation of one possible implementation of present embodiments. In this regard, each block may represent a module, a segment, or a portion of program code, which includes one or more instructions executable by a processor for implementing specific logical functions or steps in the process. The program code may be stored on any type of computer readable medium, for example, such as a storage device including a disk or hard drive. The computer readable medium may include non-transitory computer readable medium, for example, such as computer-readable media that stores data for short periods of time like register memory, processor cache and Random Access Memory (RAM). The computer readable medium may also include non-transitory media, such as secondary or persistent long term storage, like read only memory (ROM), optical or magnetic disks, compact-disc read only memory (CD-ROM), for example. The computer readable media may also be any other volatile or non-volatile storage systems. The computer readable medium may be considered a computer readable storage medium, for example, or a tangible storage device. In addition, for the method **900** and other processes and methods disclosed herein, each block in FIG. **9** may represent circuitry that is wired to perform the specific logical functions in the process.

(99) At block **902**, the method **900** may involve determining an ambient light level based on a detection by a light sensor of ambient light of a control area for a playback device. The control area

might allow, for example, playback control for the playback device, such as “play,” “pause,” “volume up/down,” and so on. FIG. 10 shows an example playback device **1000** that may be configured to intelligently reveal selectable icons on proximity detection. As shown, the playback device **1000** may include a control area **1002** around where proximity detecting capabilities may be implemented. The control area **1002** may include a control strip having selectable icons or buttons on a top portion **1004** of the control area **1002**. In one example, the selectable icons may be capacitive buttons presented as back-lit icons. In some cases, if the top portion **1004** is a dark color, the icons may be effectively invisible when the icons are not illuminated. Also as shown, the control area **1002** further includes a front portion **1006** where a logo, such as a SONOS® may be provided. Further as shown, the playback device **1000** may include a speaker grille **1008**.

(100) In one example, a light sensor may be implemented on the playback device **1000** and configured to detect an ambient light level around the playback device **1000**. More particularly, the light sensor may be configured to detect an ambient light level around the control area **1002** of the playback device **1000**. In one case, the light sensor may be positioned within or adjacent to the control area **1002**. The determined ambient light level, as will be further discussed below, may be based upon to refine the proximity detection capabilities of the playback device **1000** for the purposes of intelligently revealing the selectable icons on the top portion **1004** of the control area **1002**.

(101) FIG. 11 shows an example embodiment of the playback device **1000** with proximity sensing capabilities, including an IR sensor **1102** and a capacitive sensor **1104** implemented along the top portion **1004** of the control area **1002**. The capacitive sensor **1104**, as shown may have a capacitive grounding plane **1106**. In discussions herein, the capacitive grounding plane **1106** may also be referred to as an electrode or metal electrode of the capacitive sensor **1104**. In one case, the capacitive grounding plane **1106** may also be referred to as an antenna of the capacitive sensor **1104**.

(102) Both the IR proximity sensor and the capacitive sensor may be configured to detect physical movement, albeit via different mechanisms. As previously discussed, the capacitive sensor **1104** may be configured to detect a change in capacitance within a range of the capacitive grounding plane **1106**, which in this case may be a range within a proximal vicinity above the control area **1002** of the playback device **1000**. The IR sensor **1102** on the other hand, may be configured to emit infrared light pulses and detect reflected infrared light pulses to determine physical movement. In some embodiments, the IR sensor **1102** may further be configured as the light sensor for determining the ambient light level, as discussed above in connection to block **902**.

(103) As indicated above, if the playback device **1000** is located near a plasma television, the capacitive sensor **1104** may be falsely triggered while the plasma television is on, and a gain of the capacitive sensor **1104** may be reduced in the presence of the plasma television to reduce false triggers. However, reduced capacitive sensor gain may result in signals indicating the physical movement that are indistinguishable from a baseline noise signal for the capacitive sensor. Additional signal processing may be performed to better distinguish the signals, but may result in slower response times.

(104) On the other hand, if the ambient light level of the playback device is high, the IR sensor may be flooded by the high ambient light level such that the IR sensor may not be able to reliably discern the reflected light pulses from the baseline ambient light. Accordingly, at block **904**, the method **900** may involve adjusting, based on the ambient light level, a sensitivity of an infrared (IR) proximity sensor, and at block **906**, the method **900** may involve adjusting, based on the ambient light level, a sensitivity of a capacitive proximity sensor.

(105) In one example, adjusting the sensitivity of the capacitive proximity sensor may involve adjusting a gain level of the capacitive proximity sensor, and adjusting the sensitivity of the IR proximity sensor may involve adjusting a pulse width of the IR proximity sensor. In one instance, if the ambient light level is high, a gain of the capacitive sensor may be increased, and if the ambient

light level is low, the gain of the capacitive sensor may be reduced. For the IR proximity sensor if the ambient light level is high, a dynamic range of the IR sensor may be reduced, and a pulse width of infrared light pulses generated from the IR sensor may be lengthened. Analogously, if the ambient light level is low, the dynamic range of the IR sensor may be increased, and the pulse width of infrared light pulses may be shortened.

(106) As one having ordinary skill in the art may appreciate, different combinations of IR sensor dynamic ranges and infrared light pulse widths may be configured for different levels of ambient light, and different capacitive sensor gain levels may be configured for different levels of ambient light. In combination, when the ambient light level is high, the capacitive sensor may become more sensitive due to the increased gain level, while the IR sensor may become less sensitive due to the reduced dynamic range and increased infrared light pulse width. On the other hand, when the ambient light level is low, the capacitive sensor may become less sensitive due to the decreased gain level, while the IR sensor may become more sensitive due to the increased dynamic range and shorted infrared light pulse widths. As indicated above, different configurations of IR sensor and capacitive sensor sensitivities may be implemented for different levels of ambient light.

(107) In an illustrative example, six combinations of capacitive sensor and IR sensor sensitivities may be implemented and configured depending on the determined ambient light level. In this example, the capacitive sensor **1104** may have three gain settings. The lowest gain settings, or “cap gain 1” may be configured such that false triggers are unlikely as long as the capacitive sensor **1104** is at least six inches away from a plasma display, as referred to above. In this setting, the capacitive sensor **1104** may have a range of about two to three inches. The next gain settings, or “cap gain 2” may be configured such that the capacitive sensor **1104** may have an additional inch or two of range. In this setting however, false triggers from the plasma display may occur if the plasma display is within six to eight inches away. The third gain setting, or “cap gain 3” may be configured such that the capacitive sensor **1104** may have a range up to about four inches, but may result in yet higher susceptibility to false triggers from the plasma display.

(108) Further in this example, the IR sensor **1102** may have six settings. The first setting, or “IR setting 1,” may have a minimal IR pulse width and short pulse integration time. In some cases, the IR sensor **1102** may have a high sensitivity mode and a low sensitivity mode, and at “IR setting 1” the IR sensor **1102** may be in high sensitivity mode. This setting may be suitable for a dark environment. Depending on the ambient light conditions, IR setting 1 may provide a range of about seven inches. As the settings progress to “IR setting 2,” “IR setting 3,” “IR setting 4,” “IR setting 5,” and “IR setting 6,” the IR pulse width may increase incrementally, and the pulse integration time may increase accordingly. In one example, the IR sensor **1102** may be configured to be in the high sensitivity mode up to “IR setting 3,” and at “IR setting 4,” the IR sensor **1102** may be configured to switch to the low sensitivity mode, to accommodate the higher ambient light levels. As one having ordinary skill in the art will appreciate, higher ambient light levels may also include higher infrared light levels that may swamp the IR sensor **1102**. In one case, an additional IR sensor, or IR sensor component of the IR sensor **1102** having a smaller receiving component for further reduced sensitivity may be provided to accommodate high ambient light levels. In such a case, settings, such as “IR setting 6” or even “IR setting 5” may involve switching to the IR sensor having the smaller receiving component. Other examples may also be possible.

(109) In this illustrative example, “cap gain 1” may be paired with “IR setting 1,” “IR setting 2,” “IR setting 3,” and “IR setting 4,” “cap gain 2” may be paired with “IR setting 5,” and “cap gain 3” may be paired with “IR setting 6.” In other words, as previously suggested, as the capacitive sensor gain increases, the IR sensitivity decreases and the IR pulse widths and integration times increase. In some embodiments, the pairing of “cap gain 2” and “IR setting 5,” and the pairing of “cap gain 3” and “IR setting 6” may be configured for when the playback device **1000** is operating outdoors during the day. Other examples are also possible.

(110) Referring back to the method **900**, block **908** may involve determining a physical approach of

an entity towards the playback device based on the detection of the physical movement by at least one of the IR proximity sensor and the capacitive proximity sensor. In other words, if either the IR sensor **1102** or capacitive sensor **1104** detects physical movement within the proximal range of the playback device **1000**, a determination may be made that a user **1112** may be approaching the playback device and may wish to view the selectable icons before potentially selecting one or more of the selectable icons. To implement block **908**, outputs from the IR sensor **1102** and the capacitive sensor **1104** may be processed through an “OR” function, and a physical approach of the entity towards the playback device may be determined based on the output of the “OR” function. Other examples are also possible.

(111) At block **910**, the method **900** may involve responsively causing a control area of the playback device to be illuminated. As suggested above, the back-lit icons on the control area **1002** of the playback device **1000** may be illuminated when either the IR sensor or the capacitive sensor detects the physical movement or presence of the user **1112** within the proximal range of the playback device. As such, responsive to the determination of the physical approach of the entity towards the playback device **1000**, the selectable icons on the control area **1002** may be revealed.

(112) In another embodiment, the selectable icons on the control area **1002** may be revealed after a presence of the user **1112** has been present within a distance of the control area for a predetermined period of time. For example, the control area **1002** may be configured to reveal the selectable icons if the user **1112** or a hand or finger of the user **1112** is within an inch or less from the control area for at least half a second. In some cases, such an implementation may reduce false triggers when the user **1112**, or a pet of the user **1112** simply moves by the playback device **1000** within a proximal range from the control area **1002**.

(113) A similar approach may be implemented if any of the selectable icons on the control area **1002** represent a subset of additional icons selectable for the playback device to perform related functions. In such a case, if the user **1112** hovers over the selectable icon representative of the group of functions, the control area **1002** may, in response, reveal the subset of additional icons within the group. Other examples are also possible.

(114) While the discussions above are directed to proximity detection for the purposes of revealing icons or buttons on the control panel of the playback device, one having ordinary skill in the art will appreciate that proximity detection may be utilized in other capacities as well. For instance, a playback device may pre-cache audio content in anticipation of a user providing input via the control panel to cause the playback device to playback audio content. In another instance, the playback device may be in an in-active state such that an amplifier of the playback device may be turned off to reduce power consumption while the playback device is not playing audio content. In this instance, the amplifier of the playback device may be turned on in anticipation of a user providing input via the control panel to cause the playback device to playback audio content based on proximity detection. Other examples are also possible.

(115) As discussed above, embodiments described herein further involve configurations for improved off-axis or zero-degree approach detection of physical movement by the capacitive sensor. In addition to offering alternative proximity sensing capabilities in high ambient light conditions, the capacitive sensor may also complement the IR sensor by providing additional off-axis detection. For instance, as shown in FIG. **11**, the IR sensor **1102** may be positioned along the top portion **1004** of the control area **1002** of the playback device **1000** and accordingly, may have a detection range **1108** in a first direction directed to a space above the playback device **1000**. In this case, an approach of the user **1112** from the front side of the playback device **1000** may not be as easily detected by the IR sensor. The capacitive sensor on the other hand, depending on the configuration of the capacitive grounding plane **1106**, may be less directional and may have a detection range **1110** directed to the space above the playback device **1000**, as well as, to perhaps a lesser extent, spaces around the playback device **1000**, even if the capacitive sensor **1104** is positioned along the top side of the playback device as well.

(116) In some embodiments of the present application, the off-axis, or zero-degree approach detection by the capacitive sensor **1104** may further be improved by coupling the capacitive grounding plane **1106**, or an electrode of the capacitive sensor **1104** to other components of the playback device **1000**. In one example, the playback device **1000** may be configured to communicate via wireless communication and may include an RF antenna component. FIG. **12A** shows a first example configuration of the capacitive sensor **1104** implemented along the control panel **1002** of a playback device **1000**. As shown, the capacitive sensor **1104** may be coupled to an RF antenna **1202** that is oriented orthogonally to the capacitive grounding plane **1106** of the capacitive sensor **1104**. In one example, the RF antenna ground plane may be a copper pour in a printed circuit board.

(117) In effect, coupling the ground plane of the RF antenna **1202** to the capacitive grounding plane **1106** of the capacitive sensor **1104** may provide an additional, second capacitive grounding plane for the capacitive sensor **1104**. As such, in addition to the detection range **1110** as provided by the capacitive grounding plane **1106**, the capacitive sensor **1104** may also have a detection range **1204**. In this case, because the RF antenna **1202** may be oriented orthogonally to the capacitive grounding plane **1106**, the detection range **1204** may be in a direction orthogonal, or 90 degrees to the direction of the detection range **1110**. As shown, the detection range **1204** may be towards the front side of the playback device **1000**. In other words, coupling the capacitive grounding plane **1106**, or an electrode of the capacitive sensor **1104** to the ground plane of the RF antenna **1202** as described may improve the detection of physical movement in front of the playback device **1000** by the capacitive sensor **1104**. Further in this case, the capacitive grounding plane **1106** may be capacitively coupled to the ground plane of the RF antenna **1202**, such that performance of the RF antenna **1202** may be enhanced because the capacitive grounding plane **1106** may act as an RF ground for additional noise isolation for the RF antenna **1202**.

(118) In other embodiments, the RF antenna **1202** may be oriented at any relative angle to the capacitive grounding plane **1106**. In such cases, the detection of physical movement by the capacitive sensor **1104** may be improved in a direction at the relative angle to the detection direction of the capacitive grounding plane **1106**. Other examples are also possible.

(119) In addition to the RF antenna **1202**, the off-axis, or zero-degree approach detection by the capacitive sensor **1104** may further be improved by coupling the capacitive grounding plane **1106**, or an electrode of the capacitive sensor **1104** to the speaker grille **1008** of the playback device **1000**. FIG. **12B** shows a second example configuration of the capacitive sensor **1104** implemented along the control panel **1002** of the playback device **1000**, and coupled to the speaker grille **1008**. In one example, the speaker grille **1008** may be a metal speaker grille. Similar to the case described above in connection to the RF antenna **1202**, the speaker grille **1008** may provide the capacitive sensor **1104** a second capacitive grounding plane, which in this case, may also be substantially orthogonal to the capacitive grounding plane **1106**, on the front side of the playback device **1000**. In this case, the second capacitive grounding plane may provide the capacitive sensor **1104** with a detection range **1206**, substantially orthogonal to the detection range **1110**. Accordingly, coupling the capacitive grounding plane **1106**, or an electrode of the capacitive sensor **1104** to the speaker grille may also improve the detection of physical movement in front of the playback device **1000** by the capacitive sensor **1104**.

(120) In such a configuration, however, playback of audio by the playback device **1000** may generate sufficient change in capacitance detectable by the speaker grille and cause false triggers in the capacitive sensor **1104**. This may occur, for example, if the diaphragm of the speaker is metal. As such, in one embodiment, the speaker grille and the capacitive grounding plane **1106** may be coupled when the playback device is not playing audio content, and decoupled when the playback device is playing audio content.

(121) In implementation, the playback device **1000** may be configured to determine that the playback device is not rendering audio content, and responsively cause the capacitive grounding



plane **1106** of the capacitive sensor **1104** to be coupled to the speaker grille **1008** of the playback device **1000**. On the other hand, the playback device **1000** may be configured to determine that the playback device **1000** is or will be rendering audio content, and responsively, cause the capacitive grounding plane **1106** of the capacitive sensor **1104** to be decoupled from the speaker grille **1008** of the playback device **1000**, if the capacitive grounding plane **1106** and the speaker grille **1008** was previously coupled.

(122) In some embodiments, the capacitive grounding plane **1106** may be coupled to both the RF antenna **1202** and the speaker grille **1008** such that the capacitive sensor **1104** has three capacitive grounding planes. In one case, the capacitive grounding plane **1106** may be coupled to the RF antenna **1202** and not to the speaker grille **1008** when audio content is being played by the playback device **1000**, while the capacitive grounding plane **1106** may be coupled to both the RF antenna **1202** and the speaker grille **1008** when audio content is not being played by the playback device **1000**. Other examples and configurations may also be possible.

(123) As discussed previously, proximity detection may be utilized in other capacities as well, in addition to the intelligent revealing of selectable icons. Depending on the application of proximity detection, various combinations of coupling or decoupling between the capacitive grounding plane **1106** and the RF antenna **1202** and speaker grille **1008** may be implemented as applicable.

## IX. Conclusion

(124) The descriptions above disclose various example systems, methods, apparatus, and articles of manufacture including, among other components, firmware and/or software executed on hardware. However, such examples are merely illustrative and should not be considered as limiting. For example, it is contemplated that any or all of these firmware, hardware, and/or software components can be embodied exclusively in hardware, exclusively in software, exclusively in firmware, or in any combination of hardware, software, and/or firmware. Accordingly, while the following describes example systems, methods, apparatus, and/or articles of manufacture, the examples provided are not the only way(s) to implement such systems, methods, apparatus, and/or articles of manufacture.

(125) As indicated above, the present application involves intelligently revealing selectable icons on a control panel of a playback device based on proximity detection. In one aspect, a method is provided. The method involves determining an ambient light level based on a detection by a light sensor of ambient light of a control area for a playback device, and adjusting, based on the ambient light level, a sensitivity of an infrared (IR) proximity sensor. The IR proximity sensor is configured to detect physical movement. The method further involves adjusting, based on the ambient light level, a sensitivity of a capacitive proximity sensor. The capacitive proximity sensor is configured to detect a physical movement. The method also involves determining a physical approach of an entity towards the playback device based on the detection of the physical movement by at least one of the IR proximity sensor and the capacitive proximity sensor, and responsively causing a control area of the playback device to be illuminated.

(126) In another aspect, a device is provided. The device includes a processor, an infrared (IR) proximity sensor, a capacitive proximity sensor, and memory having stored thereon instructions executable by the processor to cause the playback device to perform functions. The functions include determining an ambient light level of a control area for a playback device based on a detection by a light sensor, and adjusting, based on the ambient light level, a sensitivity of an infrared (IR) proximity sensor. The IR proximity sensor is configured to detect physical movement. The functions further include adjusting, based on the ambient light level, a sensitivity of a capacitive proximity sensor. The capacitive proximity sensor is configured to detect a physical movement. The functions further include determining a physical approach of an entity towards the playback device based on the detection of the physical movement by at least one of the IR proximity sensor and the capacitive proximity sensor, and responsively causing a control area of the playback device to be illuminated.

(127) In yet another aspect, a non-transitory computer readable memory is provided. The non-transitory computer readable memory has stored thereon instructions executable by a computing device to cause the computing device to perform functions. The functions include determining an ambient light level of a control area for a playback device based on a detection by a light sensor, and adjusting, based on the ambient light level, a sensitivity of an infrared (IR) proximity sensor. The IR proximity sensor is configured to detect physical movement. The functions also include adjusting, based on the ambient light level, a sensitivity of a capacitive proximity sensor. The capacitive proximity sensor is configured to detect a physical movement. The functions further include determining a physical approach of an entity towards the playback device based on the detection of the physical movement by at least one of the IR proximity sensor and the capacitive proximity sensor, and responsively causing a control area of the playback device to be illuminated.

(128) Additionally, references herein to “embodiment” means that a particular feature, structure, or characteristic described in connection with the embodiment can be included in at least one example embodiment of the invention. The appearances of this phrase in various places in the specification are not necessarily all referring to the same embodiment, nor are separate or alternative embodiments mutually exclusive of other embodiments. As such, the embodiments described herein, explicitly and implicitly understood by one skilled in the art, can be combined with other embodiments.

(129) The specification is presented largely in terms of illustrative environments, systems, procedures, steps, logic blocks, processing, and other symbolic representations that directly or indirectly resemble the operations of data processing devices coupled to networks. These process descriptions and representations are typically used by those skilled in the art to most effectively convey the substance of their work to others skilled in the art. Numerous specific details are set forth to provide a thorough understanding of the present disclosure. However, it is understood to those skilled in the art that certain embodiments of the present disclosure can be practiced without certain, specific details. In other instances, well known methods, procedures, components, and circuitry have not been described in detail to avoid unnecessarily obscuring aspects of the embodiments. Accordingly, the scope of the present disclosure is defined by the appended claims rather than the foregoing description of embodiments.

(130) When any of the appended claims are read to cover a purely software and/or firmware implementation, at least one of the elements in at least one example is hereby expressly defined to include a tangible medium such as a memory, DVD, CD, Blu-ray, and so on, storing the software and/or firmware.

## Claims

1. A wireless headphone device comprising: a wireless communications interface including a wireless antenna; an infrared proximity sensor that is configured to detect physical movement; at least one processor; and at least one non-transitory computer-readable medium comprising program instructions that are executable by the at least one processor such that the wireless headphone device is configured to: operate in a first power state; detect that an object is in proximity to the infrared proximity sensor; and after detection of the object, adjust operation of the wireless headphone device from the first power state to a second power state.
2. The wireless headphone device of claim 1, further comprising a control area that includes a capacitive button that is coupled to a capacitive sensor that is configured to detect a touch-based user input, wherein actuation of the capacitive button causes playback control of the wireless headphone device.
3. The wireless headphone device of claim 1, wherein a power consumption of the wireless headphone device in the second power state is greater than a power consumption of the wireless headphone device in the first power state.

4. The wireless headphone device of claim 1, wherein the at least one non-transitory computer readable medium further comprises program instructions that are executable by the at least one processor such that the wireless headphone device is further configured to prepare to play back audio after detecting the object.
5. The wireless headphone device of claim 1, wherein the at least one non-transitory computer readable medium further comprises program instructions that are executable by the at least one processor such that the wireless headphone device is further configured to cause a component of the wireless headphone device to be illuminated after detecting the object.
6. The wireless headphone device of claim 1, further comprising an audio amplifier, wherein electrical power is not provided to the audio amplifier in the first power state, and wherein electrical power is provided to the audio amplifier in the second power state.
7. The wireless headphone device of claim 1, wherein the at least one non-transitory computer readable medium further comprises program instructions that are executable by the at least one processor such that the wireless headphone device is further configured to, while in the second power state: stream, via the wireless antenna, data representing audio content; and play back the audio content via at least one audio amplifier.
8. The wireless headphone device of claim 1, wherein the wireless communications interface is configured for data communication in accordance an IEEE 802.15 communication standard.
9. The wireless headphone device of claim 8, wherein the wireless communications interface comprises a Bluetooth interface.
10. A playback device comprising: one or more processors; an infrared proximity sensor that is configured to detect physical movement; and at least one non-transitory computer-readable medium having stored thereon instructions executable by the one or more processors to cause the playback device to perform functions comprising: operate in a first power state; detect that an object is in proximity to the infrared proximity sensor; and after detection of the object, adjust operation of the playback device from the first power state to a second power state.
11. The playback device of claim 10, wherein the instructions are executable by the one or more processors to cause the playback device to perform additional functions comprising: determining an ambient light level around the playback device based on a detection by a light sensor; and adjusting, based on the ambient light level, a sensitivity of the infrared proximity sensor.
12. The playback device of claim 11, wherein the light sensor is the infrared proximity sensor.
13. The playback device of claim 11, wherein the light sensor is a distinct optical sensor from the infrared proximity sensor.
14. The playback device of claim 10, further comprising an audio amplifier, wherein electrical power is not provided to the audio amplifier in the first power state, and wherein electrical power is provided to the audio amplifier in the second power state.
15. The playback device of claim 10, further comprising a wireless communications interface including a wireless antenna, wherein the instructions are executable by the one or more processors to cause the playback device to perform additional functions comprising: stream, via the wireless antenna, data representing audio content; and play back the audio content via at least one audio amplifier.
16. The playback device of claim 15, wherein the wireless communications interface is configured for data communication in accordance an IEEE 802.15 communication standard.
17. The playback device of claim 16, wherein the wireless communications interface comprises a Bluetooth interface.
18. A method comprising: determining an ambient light level around a wireless headphone device based on a detection by a light sensor; receiving user input to the wireless headphone device via actuation of a capacitive button that is coupled to a capacitive sensor; detecting, via an infrared proximity sensor, physical movement of an object that is nearby the wireless headphone device; adjusting, based on the ambient light level, a sensitivity of the capacitive sensor; operating the

wireless headphone device in a first power state; detecting the object using the infrared proximity sensor; and after detecting the object, adjusting operation of the wireless headphone device from the first power state to a second power state.

19. The method of claim 18, wherein actuation of the capacitive button causes playback control of the wireless headphone device.

20. The method of claim 18, further comprising: streaming, via an antenna that is included in the wireless headphone device, data representing audio content; and playing back the audio content via an audio amplifier; wherein electrical power is not provided to the audio amplifier in the first power state, and wherein electrical power is provided to the audio amplifier in the second power state.

---