

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent Application Publication

20250263893

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

Reardon; Mike et al.

---

### Selectively Frictionally Engaged Hole Cover

---

#### Abstract

A selectively frictionally engaged hole cover for a bore hole cored from a paved surface that includes a cover plate configured to cover the bore hole and support vehicular traffic. An engagement mechanism is attached to the cover plate and extends down into the bore hole. The engagement mechanism is configured to be actuated by a user torque input that causes an engagement plate selectively shiftable relative to the cover plate to thereby shift an engagement member along a engagement member stop and thus radially outwardly or inwardly, causing the engagement mechanism to selectively engage or disengage the wall of the bore hole. When the engagement member is in frictional contact with the hole, unintentional extraction of the engagement mechanism is prevented. The selectively frictionally engaged hole cover effectively provides a temporary cover for a bore hole in a road, parking lot, or other paved surface.

---

**Inventors:** Reardon; Mike (Yorba Linda, CA), Reardon; Kevin (Anaheim Hills, CA)

**Applicant:** Clover Equipment, LLC (Anaheim, CA)

**Family ID:** 1000008586620

**Assignee:** Clover Equipment, LLC (Anaheim, CA)

**Appl. No.:** 19/201425

**Filed:** May 07, 2025

#### Related U.S. Application Data

parent US continuation 18917488 20241016 parent-grant-document US 12297608 child US 19201425

parent US continuation-in-part 18487680 20231016 PENDING child US 18917488

---

#### Publication Classification

**Int. Cl.:** E01C9/08 (20060101)

**U.S. Cl.:**

**CPC** E01C9/083 (20130101);

---

## **Background/Summary**

[0001] This application is a continuation of that claims the benefit of priority and is entitled to the filing date pursuant to 35 U.S.C. § 120 of U.S. Non-Provisional patent application Ser. No. 18/917,488, filed Oct. 16, 2024, a continuation-in-part that claims the benefit of priority and is entitled to the filing date pursuant to 35 U.S.C. § 120 of U.S. Non-Provisional patent application Ser. No. 18/487,680, filed Oct. 16, 2023, the content of each of which is hereby incorporated by reference in its entirety.

### **BACKGROUND**

[0002] The subject of this patent application relates generally to temporary covers for covering holes in paved surfaces so that vehicular traffic can safely travel thereover.

[0003] By way of background, when locating and verifying subsurface utilities (e.g., water, power, gas, telephone, sewer, cable, oil lines, reclaimed water, and so on) it is common practice to core approximately a 6-inch to 12-inch diameter hole through the asphalt or concrete. Once the asphalt or concrete core is removed, the field crew will then hydro excavate down to the utility to positively identify the line. Thereafter, the core is left open with the utility exposed to allow for survey crews, inspection crews, digging crews, drilling crews, etc. to visually identify the line they are working with and/or around.

[0004] During non-working hours, a cover (often called a “graduation cap” due to its appearance) is placed over the core hole to permit safe passage of pedestrians and vehicular traffic. Many current graduation caps are made from heavy-duty steel materials, with a large diameter steel pipe having a steel plate welded to the top end. The pipe portion is dropped into the bore hole, with the plate resting atop the rim of the hole, with only the weight of the graduation cap holding it within the hole. As high-speed vehicles drive over the plate, the graduation caps have issues with becoming dislodged from the core and ejected onto the street. This causes great damage to vehicles due to impact with the dislodged graduation cap and/or the open bore hole itself. What is needed is a bore hole cover that can withstand the stresses of vehicular traffic without becoming dislodged.

[0005] Aspects of the present invention fulfill these needs and provide further related advantages as described in the following summary.

### **SUMMARY**

[0006] Aspects of the present invention teach certain benefits in construction and use which give rise to the exemplary advantages described below.

[0007] The present specification discloses a selectively frictionally engaged hole cover generally comprising a cover plate coupled to an engagement mechanism. The cover plate includes a top surface and a bottom surface opposite the top surface. The engagement mechanism includes an engagement plate selectively shiftable relative to the cover plate and configured to thereby shift an engagement member along a engagement member stop and thus radially outwardly or inwardly. The engagement mechanism is coupled with the cover plate and extends from the bottom surface of the cover plate. During an insertion procedure, the engagement mechanism is configured to be positioned within the bore hole and supported at least initially therein by the cover plate that is configured to rest upon the paved surface and substantially cover the bore hole. And, during an engagement procedure, the engagement mechanism is configured to be actuated to cause a first

movement of the engagement plate so as to shift the engagement member along the engagement member stop radially outwardly to move the engagement member into frictional contact with the bore hole and to substantially prevent extraction of the engagement mechanism from the bore hole and substantially prevent lifting of the cover plate due to forces exerted by vehicular traffic thereupon.

[0008] Other features and advantages of aspects of the present invention will become apparent from the following more detailed description, taken in conjunction with the accompanying drawings, which illustrate, by way of example, the principles of aspects of the invention.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

[0009] The accompanying drawings, which are incorporated in and constitute a part of this specification, illustrate aspects of the disclosed subject matter in at least one of its exemplary embodiments, which are further defined in detail in the following description. Features, elements, and aspects of the disclosure are referenced by numerals with like numerals in different drawings representing the same, equivalent, or similar features, elements, or aspects, in accordance with one or more embodiments. The drawings are not necessarily to scale, emphasis instead being placed upon illustrating the principles herein described and provided by exemplary embodiments of the invention. In such drawings:

[0010] FIG. 1 is an assembled top perspective view of an exemplary embodiment of a selectively frictionally engaged hole cover disclosed herein;

[0011] FIG. 2 is an assembled bottom perspective view of the selectively frictionally engaged hole cover of FIG. 1;

[0012] FIG. 3 is an enlarged side cross-sectional view of the selectively frictionally engaged hole cover of FIG. 1 taken from line 3-3 of FIG. 2;

[0013] FIG. 4 is a reduced scale side view of the selectively frictionally engaged hole cover of FIG. 1, showing the selectively frictionally engaged hole cover inserted within a bore hole formed through a paved surface in the unengaged configuration;

[0014] FIG. 5 is a reduced scale side view of the selectively frictionally engaged hole cover of FIG. 1, showing the selectively frictionally engaged hole cover inserted within a bore hole formed through a paved surface in the engaged configuration;

[0015] FIG. 6 is an assembled top perspective view of another exemplary embodiment of a selectively frictionally engaged hole cover disclosed herein;

[0016] FIG. 7 is an assembled bottom perspective view of the anchored hole cover of FIG. 6;

[0017] FIG. 8 is an enlarged side cross-sectional view of the selectively frictionally engaged hole cover of FIG. 6 taken from line 8-8 of FIG. 7;

[0018] FIG. 9 is a reduced scale side view of the selectively frictionally engaged hole cover of FIG. 6, showing the selectively frictionally engaged hole cover inserted within a bore hole formed through a paved surface in the unengaged configuration;

[0019] FIG. 10 is a reduced scale side view of the selectively frictionally engaged hole cover of FIG. 6, showing the selectively frictionally engaged hole cover inserted within a bore hole formed through a paved surface in the engaged configuration.

[0020] FIG. 11 is an assembled top perspective view of an exemplary embodiment of a selectively frictionally engaged hole cover disclosed herein;

[0021] FIG. 12 is an assembled bottom perspective view of the selectively frictionally engaged hole cover of FIG. 11;

[0022] FIG. 13 is an exploded top perspective view of of a selectively frictionally engaged hole cover of FIG. 11;

[0023] FIG. **14** is an exploded bottom perspective view of the selectively frictionally engaged hole cover of FIG. **11**;

[0024] FIG. **15** is an enlarged side cross-sectional view of the selectively frictionally engaged hole cover of FIG. **11** taken from line **15-15**;

[0025] FIG. **16** is a reduced scale side view of the selectively frictionally engaged hole cover of FIG. **11**, showing the selectively frictionally engaged hole cover inserted within a bore hole formed through a paved surface in the unengaged configuration; and

[0026] FIG. **17** is a reduced scale side view of the selectively frictionally engaged hole cover of FIG. **11**, showing the selectively frictionally engaged hole cover inserted within a bore hole formed through a paved surface in the engaged configuration.

TABLE-US-00001 Listing of Reference Numbers Associated with Drawings Ref. No. Element 20 Selectively frictionally engaged hole cover 30 Cover plate 32 Top surface 34 Bottom surface 36 Access hole 38 Cover plate skirt 39 Slots 40 Engagement mechanism 50 Engagement support bracket 52 Bracket sidewall 54 Support plate 56 Support plate hole 58 Bracing rib 60 Engagement screw 62 Head 64 Shank 66 Threaded portion 70 Engagement member stop 80 Engagement plate 82 Top surface 84 Bottom surface 86 Through-hole 87 Boss 88 Perimeter lip 89 Through hole 90 Engagement member 100 Stand-off 106 Through-hole 110 Retainer plate 112 Top surface 114 Bottom surface 116 Retainer plate hole 118 Retainer plate skirt 120 Bracket housing 122 Bottom portion 124 Angled portion 126 Skirt portion 128 Through-hole 130 Reinforcement plate 132 Top surface 134 Bottom surface 136 Nut seat 140 Nut 142 Threaded through-hole H Bore hole W Bore hole wall P Paved surface C Course B Base S Sub-grade U Utility

#### DETAILED DESCRIPTION

[0027] The present specification discloses a selectively frictionally engaged hole cover for a bore hole cored from a paved surface that includes a cover plate and an engagement mechanism. A cover plate disclosed herein is configured to cover the bore hole and support vehicular traffic. An engagement mechanism disclosed herein is operably attached to the cover plate and extends down into the bore hole and comprises an engagement support bracket, an engagement screw, an engagement plate, and an engagement member. The engagement mechanism is configured to be actuated by a user torque input that is transmitted through the engagement screw threadably connected with the engagement plate to selectively raise or lower the engagement plate and thereby cause the engagement member to selectively engage or disengage a wall of the bore hole as the engagement member moves up and against or down and away from an engagement member stop and so selectively shifts the engagement member radially outwardly or inwardly. When the engagement mechanism is engaged with the bore wall via the engagement member as urged radially outwardly under the influence of the engagement plate upon rotation of the engagement screw by the user, the selectively frictionally engaged hole cover is prevented from being unintentionally extracted from the bore hole. The selectively frictionally engaged hole cover effectively provides a temporary cover for a bore hole in a road, parking lot, or other paved surface that supports vehicular traffic, that prevents extraction due to vibrations of passing traffic, and that thus prevents damage to cars and their occupants.

[0028] The present selectively frictionally engaged hole cover **20** is illustrated in FIGS. **1-17** and generally includes a cover plate **30** with an engagement mechanism **40**. Cover plate **30** has a central access hole **36** that communicates between a top surface **32** and a bottom surface **34** of cover plate **30**. Cover plate **30** has a diameter that is greater than that of engagement mechanism as well as a bore hole H itself so as to span and seat over bore hole H even as engagement mechanism **40** is seated within bore hole H. Engagement mechanism **40** is coupled to and extends from bottom surface **34** of cover plate **30** and substantially conforms to or is slightly clear of or inset from the respective bore hole wall W. Engagement mechanism **40** generally includes an engagement support bracket **50**, an engagement screw **60**, an engagement plate **80**, and an engagement member **90**.

Engagement mechanism **40** can have a variety of configurations that convert a user torque input into radial or lateral expansion to grip or frictionally engage a wall **W** of a bore hole **H** (as exemplified in FIGS. **5**, **10**, and **17**). Generally, engagement plate **80** is operably spaced from and configured to shift up and down relative to bottom surface **34** of cover plate **30** so as to thereby cause an engagement member **90** in contact with engagement plate **80** to selectively move up and against or down and away along an engagement member stop **70** and thus shift outwardly or inwardly radially or laterally. An engagement screw **60** operably installed between cover plate **30** and engagement plate **80** selectively raises or lowers engagement plate **80** as rotation or torque is applied to the engagement screw **60**, which is, in one or more embodiments, accessed by an appropriate tool (e.g., a socket wrench, a T-handle wrench, a speed or crack handle wrench, an impact wrench, and numerous other hand or power tools that can be used to impart a torque on engagement screw **60**) through access hole **36**. Thus, upon actuation (applied through a user torque input), engagement screw **60** rotates and amplifies the magnitude of the torque and/or converts the torque to generally radial or lateral movement of engagement member **90** (e.g., movement toward/from the bore hole wall **W**).

[0029] While a particular configuration of the exemplary selectively frictionally engaged hole cover **20** and thus of cover plate **30** and engagement mechanism **40** is shown and described, it will be appreciated by those skilled in the art that the invention is not so limited and other configurations and related assembly and operability arrangements are possible according to aspects of the present invention without departing from its spirit and scope. By way of illustration and not limitation, the sizes and shapes of the various components can vary, and particularly engagement member **90**, while shown and described as an annular gasket or o-ring, may take other forms; or engagement member **90** may be sized and configured to itself not frictionally engage bore hole wall **W** but instead to support other operably coupled engagement members configured, for example, as curved tabs or pads or other surfaces that in cooperation with the gasket-like portion of engagement member **90** are selectively forced radially or laterally outwardly and into frictional contact or engagement with bore hole wall **W** as they are lifted along engagement member stop **70** of the engagement mechanism **40** by upward movement of engagement plate **80**, which tabs or pads or the like may be configured to grip the wall and include a radius similar to bore hole **H** radius. Regardless, those skilled in the art will appreciate that the selectively frictionally engaged hole cover **20** according to aspects of the present invention is a relatively simple mechanical arrangement with fewer mechanical or moving components, thereby reducing or eliminating potential failure points, and also a relatively more compact design for better storage efficiency. Of course, hole cover apparatus **20** can be easily scaled for use with larger or smaller bore hole **H** sizes (e.g., 6-inch or 12-inch diameter hole).

[0030] Referring now to FIGS. **1-3**, an example embodiment of the present selectively frictionally engaged hole cover **20** is illustrated and generally includes a cover plate **30** with an engagement mechanism **40** coupled thereto and extending from bottom surface **34** of cover plate **30**.

[0031] Cover plate **30** is a circular plate having a diameter that is greater than engagement mechanism **40** and is sized larger than bore hole **H** so as to span and seat over bore hole **H** even as engagement mechanism **40** is seated within bore hole **H**. Cover plate **30** has a central access hole **36** that communicates between a top surface **32** and a bottom surface **34** of cover plate **30**. As best seen in FIG. **3**, cover plate **30** further compresses a cover plate skirt **38** including engagement member stop **70**. Positioned radially outwardly of central engagement support bracket **50**, cover plate skirt **38** extends downwardly and distally from bottom surface **34** of cover plate **30** (i.e., facing into the bore hole **H** when installed) which may again be integral with or connected to cover plate **30** as by welding or otherwise. Engagement member stop **70** spans between an outer surface of cover plate skirt **38** and bottom surface **34** to form an annular angled or sloped wall. Engagement member stop **70** can be integral with or connected to bottom surface **34** of cover plate **30** and cover plate skirt **38** as by welding or otherwise.

[0032] With continued reference to the illustrated example embodiment of FIGS. 1-3, engagement mechanism **40** is coupled to and extends from bottom surface **34** of cover plate **30** and comprises engagement support bracket **50**, engagement screw **60**, engagement plate **80**, and engagement member **90**.

[0033] Engagement support bracket **50** extends from bottom surface **34** (i.e., facing into the bore hole H when installed) substantially centered about access hole **36**, the engagement support bracket **50** having an annular bracket sidewall **52** terminating in a support plate **54** spaced from bottom surface **34** of cover plate **30** and having a support plate hole **56** formed therein offset from and substantially aligned with access hole **36** of cover plate **30**. Bracket sidewall **52** may be attached to bottom surface **34** of cover plate **30** at its top edge, for example, as by welding the top edge to bottom surface **34**, and similarly support plate **54** may be integral with or connected to bracket sidewall **52** by welding or other appropriate means now known or later developed.

[0034] As best seen in FIG. 3, engagement screw **60** has a head **62** configured to pass through access hole **36** and seat on support plate **54** and a shank **64** configured to pass through support plate hole **56** with a distal threaded portion **66** configured to threadably engage a threaded hole **86** formed centrally in the offset engagement plate **80**. Rotation of engagement screw **60** as by operably engaging head **62** via access hole **36** with an appropriate tool thereby selectively raises or lowers engagement plate **80** relative to cover plate **30** as rotation or torque is applied to engagement screw **60**. In one or more embodiments, an appropriate tool includes, without limitation, a socket wrench, a T-handle wrench, a speed or crack handle wrench, an impact wrench, and numerous other hand or power tools that can be used to impart a torque. Thus, upon actuation (applied through a user torque input), engagement screw **60** rotates and amplifies the magnitude of the torque and/or converts the torque to generally radial or lateral movement of engagement member **90** (e.g., movement toward/from bore hole wall W).

[0035] Engagement plate **80** is a circular plate having a diameter and includes centrally located threaded hole **86** that communicates between a top surface **82** and a bottom surface **84** of engagement plate **80** and a perimeter lip **88** extending substantially perpendicular from top surface **82** and surrounding an outer perimeter edge of engagement plate **80**. A raised boss **87** may be formed about threaded hole **86** simply to provide for more material thickness where threaded hole **86** is formed in engagement plate **80**. Perimeter lip **88** and may be integral with or connected to engagement plate **80** as by welding, adhesives or with the use fasteners, such as, e.g., screws or rivets. Perimeter lip **88** supports engagement member **90** vertically or from beneath and selectively shift engagement member **90** upwardly along engagement member stop **70** and thus radially outwardly as engagement plate **80** is shifted upwardly due to rotation of engagement screw **60**. Engagement plate **80** and thus the annular position of perimeter lip **88** is substantially vertically aligned with the center of engagement member **90** and the midline of engagement member stop **70**. which outer annular alignment or general profile of engagement mechanism **40** substantially conforms to or is slightly clear of or inset from the respective bore hole wall W. In addition, the outer diameters of cover plate skirt **38** and engagement member **90** are approximately equal, As such, the outer annular alignment or general profile of engagement mechanism **40** substantially conforms to or is slightly smaller than or insets from the respective bore hole wall W.

[0036] Engagement member **90** may be formed as an annular gasket or o-ring having a nominal or "at rest" diameter approximately the same as or slightly larger than that of cover plate skirt **38** and having a degree of elasticity so as to stretch and expand as engagement member **90** transitions along engagement member stop **70** that effectively provides an expanding or increasing diameter on which engagement member **90** seats. Engagement member **90** has a diameter configured to align with the midline of engagement member stop **70**.

[0037] As shown in FIGS. 4 & 5, the insertion and engagement procedures, respectively, of selectively frictionally engaged hole cover **20** can be seen. Bore hole H is formed by coring through a paved surface P (e.g., asphalt, concrete, or other form of paved surface appropriate for

supporting vehicular traffic on a roadway, parking lot, or other area). Bore hole H is further dug through any other layers beneath paved surface P, such as the illustrated base B or subgrade S layers, until a utility U is sufficiently exposed.

[0038] Referring to FIG. 4, selectively frictionally engaged hole cover **20** is positioned over bore hole H, with engagement mechanism **40** inserted within bore hole H and cover plate **30** resting on top of paved surface P. Once selectively frictionally engaged hole cover **20** is properly positioned, engagement member **90** is inserted within bore hole B and positioned adjacent to bore hole wall W here in the vicinity of or at the level of paved surface P.

[0039] Turning to FIG. 5, head **62** of engagement screw **60** is rotated in a clockwise direction using an appropriate tool to provide the required torque, from the point of view of the user standing on top of paved surface P. This clockwise rotation causes engagement plate **80** to move upward on engagement screw **60**, thus lifting engagement member **90** up and against engagement member stop **70** of cover plate **30** and so shifting engagement member **90** radially or laterally outwardly into contact with bore hole wall W of bore hole H. In this way, the frictional engagement between engagement member **90** and bore hole wall W creates a mechanical interference that prohibits extraction of selectively frictionally engaged hole cover **20** from bore hole H, even under maximum expected vehicular traffic conditions, such as class one vehicles (under 6,000 pounds) up to and exceeding class eight vehicles (over 33,000 pounds) traveling at highway speeds. To remove selectively frictionally engaged hole cover **20**, a user simply rotates head **62** of engagement screw **60** in the counterclockwise direction to shift engagement plate **80** downwardly and thus allow engagement member **90** to shift downwardly and away from inwardly sloped engagement member stop **70** and thus radially or laterally inwardly so as to disengage from or come out of contact with bore hole wall W as shown in FIG. 4.

[0040] While a particular configuration of selectively frictionally engaged hole cover **20** and thus of cover plate **30** and engagement mechanism **40** is shown and described, it will be appreciated by those skilled in the art that the invention is not so limited and other configurations and related assembly and operability arrangements are possible according to aspects of the present invention without departing from its spirit and scope. By way of illustration and not limitation, the sizes and shapes of the various components can vary, and particularly engagement member **90**, while shown and described as an annular gasket or o-ring, may take other forms; or gasket-type member **90** may be sized and configured to itself not frictionally engage bore hole wall W but instead to support other operably coupled engagement members configured, for example, as curved tabs or pads or other surfaces that in cooperation with engagement member **90** are selectively forced radially or laterally outwardly and into frictional contact or engagement with bore hole wall W as they are lifted along engagement member stop **70** of engagement mechanism **40** by upward movement of engagement plate **80**, which tabs or pads or the like may be configured to grip bore hole wall W and include a radius similar to bore hole H radius. Regardless, those skilled in the art will appreciate that selectively frictionally engaged hole cover **20** according to aspects of the present invention is a relatively simple mechanical arrangement with fewer mechanical or moving components, thereby reducing or eliminating potential failure points, and also a relatively more compact design for better storage efficiency.

[0041] It will be appreciated by those skilled in the art that by having contact about all or substantially all the circumference or between the perimeter of engagement mechanism **40** and specifically engagement member **90** and bore hole wall W, selectively frictionally engaged hole cover **20** according to aspects of the present invention is less susceptible to shifting and maintains its orientation in bore hole H, versus other designs that might tend to get point loaded when cars and trucks drive over. Relatedly, the present invention by making perimeter contact or frictionally engaging bore hole wall W at numerous points of contact does not dig into bore hole wall W even while sufficiently engaging bore hole wall W to prevent unwanted dislodging or removal of selectively frictionally engaged hole cover **20**, thereby not compromising the integrity of bore hole

H even as selectively frictionally engaged hole cover **20** is inserted and removed. It will be further appreciated that even at a relatively shallow depth within bore hole H, selectively frictionally engaged hole cover **20** is substantially secured within bore hole H even pre-actuation based on the close clearance between engagement member **90** and bore hole wall W.

[0042] Referring now to FIGS. **6-10**, another example embodiment of the present selectively frictionally engaged hole cover **20** is disclosed, and again generally includes cover plate **30** with engagement mechanism **40** coupled thereto and extending from bottom surface **34** of cover plate **30**.

[0043] Cover plate **30** is a circular plate having a diameter that is greater than engagement mechanism **40** and is sized larger than bore hole H so as to span and seat over bore hole H even as engagement mechanism **40** is seated within bore hole H. Cover plate **30** includes access hole **36** centrally located therein that communicates between top surface **32** and bottom surface **34** of cover plate **30**. As best seen in FIGS. **7 & 8**, cover plate **30** further compress cover plate skirt **38** which extends downwardly from bottom surface **34** of cover plate **30** and may be integral with or connected to cover plate **30** as by welding or otherwise. Positioned radially outwardly of central engagement support bracket **50**, cover plate skirt **38** does not serve as a support for engagement member stop **70** but instead just as an upper or proximal retention or guide for selectively frictionally engaged hole cover **20** as the entire assembly is positioned within bore hole H. This configuration ensures that the relatively longer or taller selectively frictionally engaged hole cover **20** does not get cocked as it is being inserted within bore hole H and that cover plate **30** is substantially centered over bore hole H as cover plate **30** rests on paved surface P.

[0044] As shown in FIGS. **6-8**, engagement mechanism **40** again comprises engagement support bracket **50**, engagement screw **60**, engagement plate **80**, and engagement member **90**. Engagement mechanism **40** once again generally includes engagement plate **80** operably spaced from and configured to shift up and down relative to bottom surface **34** of cover plate **30** so as to thereby cause engagement member **90** in contact with engagement plate **80** to selectively move up and down along engagement member stop **70** offset from engagement plate **80** and thus shift outwardly or inwardly radially or laterally.

[0045] Engagement support bracket **50** extends from bottom surface **34** (i.e., facing into the bore hole H when installed) substantially centered about access hole **36**, the engagement support bracket **50** having an annular bracket sidewall **52** terminating in a support plate **54** spaced from bottom surface **34** of cover plate **30** and having a support plate hole **56** formed therein offset from and substantially aligned with access hole **36** of cover plate **30**. Bracket sidewall **52** may be attached to bottom surface **34** of cover plate **30** at its top edge, for example, as by welding the top edge to bottom surface **34**, and similarly support plate **54** may be integral with or connected to bracket sidewall **52** by welding or other appropriate means now known or later developed.

[0046] As shown in FIGS. **7 & 8**, in this alternative embodiment, a stand-off **100** is provided between cover plate **30** and engagement plate **80** so as to space the two further apart. Stand-off **100** is aligned with and adjacent to support plate **54** and extends downwardly or distally therefrom. Stand-off **100** has its own through-hole **106** aligned with support plate hole **56**. Opposite of support plate **54**, stand-off **100** engages a retainer plate **110** that is substantially parallel to cover plate **30** and support plate **80**, with retainer plate **110** again joined to stand-off **100** via welding or any other appropriate attachment technique now known or later developed.

[0047] As best seen in FIGS. **7 & 8**, retainer plate **110** is a circular plate having a diameter and includes centrally located access hole **116** that communicates between a top surface **112** and a bottom surface **114** of retainer plate **110**. Retainer plate **110** further comprises retainer plate skirt **118** and engagement member **90**. Retainer plate skirt **118** extends downward or distally from bottom surface **114** of retainer plate **110** (i.e., facing into bore hole H when installed), and may be integral with or connected to retainer plate **110** as by welding or otherwise. Engagement member stop **70** spans between an outer surface of retainer plate skirt **118** and bottom surface **114** of retainer



plate **110** to form an annular angled or sloped wall. Engagement member stop **70** can be integral with or connected to bottom surface **114** of retainer plate **110** and retainer plate skirt **118** as by welding or otherwise.

[0048] Engagement screw **60** is still operably installed between cover plate **30** and engagement plate **80**. As best seen in FIG. **8**, engagement screw **60** again has head **62** configured to pass through access hole **36** and seat on support plate **54** and here has a relatively longer shank **64** configured to pass through support plate hole **56** as well as through-hole **106** of stand-off **100** and axially aligned retainer plate hole **116** to enable distal threaded portion **66** to threadably engage threaded hole **86** of engagement plate **80**. Rotation of engagement screw **60** as by operably engaging head **62** via access hole **36** with an appropriate tool thereby selectively raises or lowers engagement plate **80** relative to retainer plate **110** as rotation or torque is applied to engagement screw **60**. In one or more embodiments, an appropriate tool includes, without limitation, a socket wrench, a T-handle wrench, a speed or crack handle wrench, an impact wrench, and numerous other hand or power tools that can be used to impart a torque. Thus, upon actuation (applied through a user torque input), engagement screw **60** rotates and amplifies the magnitude of the torque and/or converts the torque to generally radial or lateral movement of engagement member **90** (e.g., movement toward/from bore hole wall **W**).

[0049] Engagement plate **80** is a circular plate having a diameter and includes centrally located threaded hole **86** that communicates between a top surface **82** and a bottom surface **84** of engagement plate **80** and perimeter lip **88** extending substantially perpendicular from top surface **82** and surrounding an outer perimeter edge of engagement plate **80**. A raised boss **87** may be formed about threaded hole **86** simply to provide for more material thickness where threaded hole **86** is formed in engagement plate **80**. Perimeter lip **88** and may be integral with or connected to engagement plate **80** as by welding, adhesives or with the use fasteners, such as, e.g., screws or rivets. Perimeter lip **88** supports engagement member **90** vertically or from beneath and selectively shift engagement member **90** upwardly along engagement member stop **70** of retainer plate **110** and thus radially outwardly as engagement plate **80** is shifted upwardly due to rotation of engagement screw **60**. Engagement plate **80** and thus the annular position of perimeter lip **88** is substantially vertically aligned with the center of engagement member **90** and the midline of engagement member stop **70**. In addition, the outer diameters of cover plate skirt **38**, retainer plate **110**, and engagement member **90** are approximately equal, As such, the outer annular alignment or general profile of engagement mechanism **40** substantially conforms to or is slightly smaller than or insets from the respective bore hole wall **W**.

[0050] Engagement member **90** may be formed as an annular gasket or o-ring having a nominal or “at rest” diameter approximately the same as or slightly larger than that of retainer plate skirt **118** and having a degree of elasticity so as to stretch and expand as engagement member **90** transitions along engagement member stop **70** that effectively provides an expanding or increasing diameter on which engagement member **90** seats. Engagement member **90** has a diameter configured to align with the midline of engagement member stop **70**.

[0051] As shown in FIGS. **9** & **10**, the insertion and engagement procedures, respectively, of selectively frictionally engaged hole cover **20** can be seen. Bore hole **H** is again formed by coring through paved surface **P** (e.g., asphalt, concrete, or other form of paved surface appropriate for supporting vehicular traffic on a roadway, parking lot, or other area). Bore hole **H** is further dug through any other layers beneath paved surface **P**, such as illustrated intermediate course **C** and base **B** or subgrade **S** layers, until utility **U** is sufficiently exposed. Notably, as illustrated, uppermost paved surface **P** may in some cases be a concrete or aggregate or other material that is relatively coarse beneath which may be intermediate layer or course **C** that is relatively finer and so may provide a relatively smoother bore hole wall **W** for engagement mechanism **40** and specifically engagement member **90** to selectively seat against and frictionally engage. In use, selectively frictionally engaged hole cover **20** with stand-off **100** for increased height or increased

depth of positioning engagement mechanism **40** and engagement member **90** specifically within bore hole H. More generally, it will be appreciated that the deeper engagement mechanism **40** is inserted within bore hole H, the better the retention of hole cover **20**, regardless of the layers and the characteristics of bore hole wall W at various depths.

[0052] Referring to FIG. **9**, selectively frictionally engaged hole cover **20** is positioned over bore hole H with engagement mechanism **40** inserted within bore hole H and the cover plate **30** resting on top of paved surface P. Once selectively frictionally engaged hole cover **20** is properly positioned, engagement member **90** is inserted within bore hole B and positioned adjacent to bore hole wall W here in the vicinity of or at the level of intermediate course C.

[0053] Turning to FIG. **10**, head **62** of engagement screw **60** is rotated in a clockwise direction using an appropriate tool to provide the required torque, from the point of view of a user standing on top of paved surface P. This clockwise rotation causes engagement plate **80** to move upward on engagement screw **60**, thus lifting engagement member **90** up and against engagement member stop **70** of retaining plate **110** and so shifting engagement member **90** radially or laterally outwardly into contact with bore hole wall W of bore hole H. In this way, the frictional engagement between engagement member **90** and bore hole wall W creates a mechanical interference that prohibits extraction of selectively frictionally engaged hole cover **20** from bore hole H, even under maximum expected vehicular traffic conditions, such as class one vehicles (under 6,000 pounds) up to and exceeding class eight vehicles (over 33,000 pounds) traveling at highway speeds. To remove selectively frictionally engaged hole cover **20**, a user simply rotates head **62** of engagement screw **60** in the counterclockwise direction to shift engagement plate **80** downwardly and thus allow engagement member **90** to shift downwardly and away from inwardly sloped engagement member stop **70** and thus radially or laterally inwardly so as to disengage from or come out of contact with bore hole wall W as shown in FIG. **9**.

[0054] It will again be appreciated by those skilled in the art that by having contact about all or substantially all the circumference or between the perimeter of the engagement mechanism **40** and specifically engagement member **90** and bore hole wall W, selectively frictionally engaged hole cover **20** according to aspects of the present invention is less susceptible to shifting and maintains its orientation in bore hole H, versus other designs that might tend to get point loaded when cars and trucks drive over. Relatedly, the present invention by making perimeter contact or frictionally engaging bore hole wall W at numerous points of contact does not dig into it even while sufficiently engaging bore hole wall W to prevent unwanted dislodging or removal of selectively frictionally engaged hole cover **20**, thereby not compromising the integrity of bore hole H even as selectively frictionally engaged hole cover **20** is inserted and removed. It will be further appreciated that even at a relatively shallow depth within bore hole H, and certainly even more so at increased depth as in the alternative exemplary embodiment, selectively frictionally engaged hole cover **20** is substantially secured within bore hole H even pre-actuation based on the close clearance between engagement member **90** and bore hole wall W. Indeed, selectively frictionally engaged hole cover **20** according to aspects of the present invention, whether short (FIGS. **1-5**) or long (FIGS. **6-10**), is well suited to capping or covering a variety of other holes, such as in walls and other support structures and not just horizontal surfaces such as roads and the like.

[0055] While a particular configuration of selectively frictionally engaged hole cover **20** and thus of cover plate **30** and engagement mechanism **40** is shown and described, it will be appreciated by those skilled in the art that the invention is not so limited and other configurations and related assembly and operability arrangements are possible according to aspects of the present invention without departing from its spirit and scope. By way of illustration and not limitation, the sizes and shapes of the various components can vary, and particularly engagement member **90**, while shown and described as an annular gasket or o-ring, may take other forms; or gasket-type member **90** may be sized and configured to itself not frictionally engage bore hole wall W but instead to support other operably coupled engagement members configured, for example, as curved tabs or pads or

other surfaces that in cooperation with engagement member **90** are selectively forced radially or laterally outwardly and into frictional contact or engagement with bore hole wall **W** as they are lifted along engagement member stop **70** of engagement mechanism **40** by upward movement of engagement plate **80**, which tabs or pads or the like may be configured to grip bore hole wall **W** and include a radius similar to bore hole **H** radius. Regardless, those skilled in the art will appreciate that selectively frictionally engaged hole cover **20** according to aspects of the present invention is a relatively simple mechanical arrangement with fewer mechanical or moving components, thereby reducing or eliminating potential failure points, and also a relatively more compact design for better storage efficiency.

[0056] Referring now to FIGS. **11-17**, another example embodiment of the present selectively frictionally engaged hole cover **20** is disclosed, and again generally includes cover plate **30** with engagement mechanism **40** coupled thereto and extending from bottom surface **34** of cover plate **30**.

[0057] As shown in FIGS. **11-15**, cover plate **30** is a circular plate having a diameter that is greater than engagement mechanism **40** and is sized larger than bore hole **H** so as to span and seat over bore hole **H** even as engagement mechanism **40** is seated within bore hole **H**. Cover plate **30** includes access hole **36** centrally located therein that communicates between top surface **32** and bottom surface **34** of cover plate **30**. Cover plate **30** further includes slots **39**.

[0058] As shown in FIGS. **11-15**, engagement mechanism **40** again comprises engagement support bracket **50**, engagement screw **60**, engagement plate **80**, and engagement member **90**. Engagement mechanism **40** once again has engagement plate **80** operably spaced from and configured to shift up and down relative to bottom surface **34** of cover plate **30** so as to thereby cause engagement member **90** in contact with engagement plate **80** to selectively move up and down along engagement member stop **70** offset from engagement plate **80** and thus shift outwardly or inwardly radially or laterally.

[0059] Engagement support bracket **50** extends from bottom surface **34** (i.e., facing into the bore hole **H** when installed) substantially centered about access hole **36**, engagement support bracket **50** having an annular bracket sidewall **52** terminating in a support plate **54** spaced from bottom surface **34** of cover plate **30** and having a support plate hole **56** formed therein offset from and substantially aligned with access hole **36** of cover plate **30**. Bracket sidewall **52** may be attached to bottom surface **34** of cover plate **30** at its top edge, for example, as by welding the top edge to bottom surface **34**, and similarly support plate **54** may be integral with or connected to bracket sidewall **52** by welding or other appropriate means now known or later developed. Engagement support bracket **50** further comprises one or more bracing ribs **58** (with six illustrated in FIG. **13**) extending radially from bracket sidewall **52**. Bracing ribs **58** are used to provide additional stability to engagement mechanism **40** and may be integral with or connected to bracket sidewall **52** by welding or other appropriate means now known or later developed.

[0060] As shown in FIGS. **13-15**, in this alternative embodiment, a bracket housing **120** is provided between cover plate **30** and engagement plate **80** so as to space the two further apart. Bracket housing **120** is bowl-shaped having a flat bottom portion **122**, an angular angled portion **124** that extends at an upward and outward angle from bottom portion **122** to form a sloped wall, and a skirt portion **126** that extends from angled portion **124** and is substantially perpendicular to bottom portion **122**. A through-hole **128** is centrally positioned on bottom portion **122**. Angled portion **124** of bracket housing **120** functions as and is equivalent to engagement member stop **70** whereas skirt portion **126** of bracket housing **120** functions as and is equivalent to cover plate skirt **38** and serves as an upper or proximal retention or guide for selectively frictionally engaged hole cover **20** as the entire assembly is positioned within bore hole **H**.

[0061] As best seen in FIG. **15**, engagement support bracket **50** is contained within bracket housing **120** in a manner that aligned support plate hole **56** to through-hole **128**. Bracket housing **120** may be attached to bottom surface **34** of cover plate **30** at its top edge, for example, as by welding or

other appropriate means now known or later developed, that centrally positions bracket housing **120** to cover plate **30** at in a manner that encases engagement support bracket **50** within bracket housing **120** and aligns access hole **36**, support plate hole **56**, and through-hole **128**. Additionally, bracket sidewall **52** can be attached to an inner surface of bottom portion **122** at its bottom edge, for example, as by welding the top edge to inner surface of bottom portion **122**. Furthermore, one or more bracing ribs **58** can be attached to an inner surface of bottom portion **122** at a bottom edge of each bracing rib **58**, and to an inner surface of angled portion **124** and skirt portion **126** at a side edge of each bracing rib **58**.

[0062] Engagement screw **60** is still operably installed between cover plate **30** and engagement plate **80**. As best seen in FIG. **15**, engagement screw **60** again has head **62** configured to pass through access hole **36** and seat on support plate **54** and here has shank **64** configured to pass through support plate hole **56** as well as through-hole **128** of bracket housing **120** and axially aligned through-hole **86** of engagement plate **80** to enable distal threaded portion **66** to threadably engage a threaded through-hole **142** of a nut **140**. Rotation of engagement screw **60** as by operably engaging head **62** via access hole **36** with an appropriate tool thereby selectively raises or lowers engagement plate **80** relative to bracket housing **120** as rotation or torque is applied to engagement screw **60**. In one or more embodiments, an appropriate tool includes, without limitation, a socket wrench, a T-handle wrench, a speed or crack handle wrench, an impact wrench, and numerous other hand or power tools that can be used to impart a torque. Thus, upon actuation (applied through a user torque input), engagement screw **60** rotates and amplifies the magnitude of the torque and/or converts the torque to generally radial or lateral movement of engagement member **90** (e.g., movement toward/from bore hole wall **W**).

[0063] Engagement plate **80** is a circular plate having a diameter and includes centrally located through-hole **86** that communicates between a top surface **82** and a bottom surface **84** of engagement plate **80** and perimeter lip **88** extending substantially perpendicular from top surface **82** and surrounding an outer perimeter edge of engagement plate **80**. Perimeter lip **88** includes one or more through-holes **89** (with four illustrated in FIG. **13**). Perimeter lip **88** may be integral with or connected to engagement plate **80** as by welding, adhesives or with the use fasteners, such as, e.g., screws or rivets, inserted through through-hole **89** of engagement plate **80** and into a blind-hole on a bottom surface of perimeter lip **88**. Perimeter lip **88** supports engagement member **90** vertically or from beneath and selectively shift engagement member **90** upwardly along engagement member stop **70** of retainer plate **110** and thus radially outwardly as engagement plate **80** is shifted upwardly due to rotation of engagement screw **60**. Engagement plate **80** further comprises a reinforcement plate **130** and nut **140** having threaded through-hole **142**. Reinforcement plate **130** is a circular plate having a diameter smaller than engagement plate **80** and includes centrally located nut seat **136** that communicates between a top surface **132** and a bottom surface **134** of reinforcement plate **130**. Reinforcement plate **130** functions to increase the thickness of engagement plate **80** and spread the load outward toward engagement member **90**. Nut seat **136** is sized to receive and hold nut **140** in place to prevent nut **140** from turning when engagement screw **60** is rotated. Engagement plate **80** and thus the annular position of perimeter lip **88** is substantially vertically aligned with the center of engagement member **90** and the midline of engagement member stop **70**. In addition, the outer diameters of bracket housing **120** and engagement member **90** are approximately equal, As such, the outer annular alignment or general profile of engagement mechanism **40** substantially conforms to or is slightly smaller than or insets from the respective bore hole wall **W**.

[0064] Engagement member **90** may be formed as an annular gasket or o-ring having a nominal or “at rest” diameter approximately the same as or slightly larger than that of bracket housing **120** and having a degree of elasticity so as to stretch and expand as engagement member **90** transitions along engagement member stop **72** that effectively provides an expanding or increasing diameter on which engagement member **90** seats. Engagement member **90** has a diameter configured to align

with the midline of engagement member stop **72**.

[0065] As shown in FIGS. **16** & **17**, the insertion and engagement procedures, respectively, of selectively frictionally engaged hole cover **20** can be seen. Bore hole H is again formed by coring through paved surface P (e.g., asphalt, concrete, or other form of paved surface appropriate for supporting vehicular traffic on a roadway, parking lot, or other area). Bore hole H is further dug through any other layers beneath paved surface P, such as illustrated intermediate course C and base B or subgrade S layers, until utility U is sufficiently exposed. Notably, as illustrated, uppermost paved surface P may in some cases be a concrete or aggregate or other material that is relatively coarse beneath which may be intermediate layer or course C that is relatively finer and so may provide a relatively smoother bore hole wall W for engagement mechanism **40** and specifically engagement member **90** to selectively seat against and frictionally engage. In use, selectively frictionally engaged hole cover **20** with bracket housing **120** increases height or depth of positioning engagement mechanism **40** and engagement member **90** specifically within bore hole H. More generally, it will be appreciated that the deeper engagement mechanism **40** is inserted within bore hole H, the better the retention of hole cover **20**, regardless of the layers and the characteristics of bore hole wall W at various depths.

[0066] Referring to FIG. **16**, selectively frictionally engaged hole cover **20** is positioned over bore hole H with engagement mechanism **40** inserted within bore hole H and the cover plate **30** resting on top of paved surface P. Once selectively frictionally engaged hole cover **20** is properly positioned, engagement member **90** is inserted within bore hole B and positioned adjacent to bore hole wall W here in the vicinity of or at the level of intermediate course C.

[0067] Turning to FIG. **17**, head **62** of engagement screw **60** is rotated in a clockwise direction using an appropriate tool to provide the required torque, from the point of view of a user standing on top of paved surface P. This clockwise rotation causes engagement plate **80** to move upward on engagement screw **60**, thus lifting engagement member **90** up and against engagement member stop **72** of retaining plate **110** and so shifting engagement member **90** radially or laterally outwardly into contact with bore hole wall W of bore hole H. In this way, the frictional engagement between engagement member **90** and bore hole wall W creates a mechanical interference that prohibits extraction of selectively frictionally engaged hole cover **20** from bore hole H, even under maximum expected vehicular traffic conditions, such as class one vehicles (under 6,000 pounds) up to and exceeding class eight vehicles (over 33,000 pounds) traveling at highway speeds. To remove selectively frictionally engaged hole cover **20**, a user simply rotates head **62** of engagement screw **60** in the counterclockwise direction to shift engagement plate **80** downwardly and thus allow engagement member **90** to shift downwardly and away from inwardly sloped engagement member stop **72** and thus radially or laterally inwardly so as to disengage from or come out of contact with bore hole wall W as shown in FIG. **16**.

[0068] It will again be appreciated by those skilled in the art that by having contact about all or substantially all the circumference or between the perimeter of the engagement mechanism **40** and specifically engagement member **90** and bore hole wall W, selectively frictionally engaged hole cover **20** according to aspects of the present invention is less susceptible to shifting and maintains its orientation in bore hole H, versus other designs that might tend to get point loaded when cars and trucks drive over. Relatedly, the present invention by making perimeter contact or frictionally engaging bore hole wall W at numerous points of contact does not dig into it even while sufficiently engaging bore hole wall W to prevent unwanted dislodging or removal of selectively frictionally engaged hole cover **20**, thereby not compromising the integrity of bore hole H even as selectively frictionally engaged hole cover **20** is inserted and removed. It will be further appreciated that even at a relatively shallow depth within bore hole H, and certainly even more so at increased depth as in the alternative exemplary embodiment, selectively frictionally engaged hole cover **20** is substantially secured within bore hole H even pre-actuation based on the close clearance between engagement member **90** and bore hole wall W. Indeed, selectively frictionally

engaged hole cover **20** according to aspects of the present invention, whether short (FIGS. 1-5) or long (FIGS. 6-10), is well suited to capping or covering a variety of other holes, such as in walls and other support structures and not just horizontal surfaces such as roads and the like.

[0069] While a particular configuration of selectively frictionally engaged hole cover **20** and thus of cover plate **30** and engagement mechanism **40** is shown and described, it will be appreciated by those skilled in the art that the invention is not so limited and other configurations and related assembly and operability arrangements are possible according to aspects of the present invention without departing from its spirit and scope. By way of illustration and not limitation, the sizes and shapes of the various components can vary, and particularly engagement member **90**, while shown and described as an annular gasket or o-ring, may take other forms; or gasket-type member **90** may be sized and configured to itself not frictionally engage bore hole wall W but instead to support other operably coupled engagement members configured, for example, as curved tabs or pads or other surfaces that in cooperation with engagement member **90** are selectively forced radially or laterally outwardly and into frictional contact or engagement with bore hole wall W as they are lifted along engagement member stop **72** of engagement mechanism **40** by upward movement of engagement plate **80**, which tabs or pads or the like may be configured to grip bore hole wall W and include a radius similar to bore hole H radius. Regardless, those skilled in the art will appreciate that selectively frictionally engaged hole cover **20** according to aspects of the present invention is a relatively simple mechanical arrangement with fewer mechanical or moving components, thereby reducing or eliminating potential failure points, and also a relatively more compact design for better storage efficiency.

[0070] In one or more example embodiments, the cover plate **30** is made of steel plate material sufficiently strong and thick to support heavy vehicular traffic thereupon. The weight bearing capacity of the cover plate **30** is up to 10,000 pounds, or up to 20,000 pounds, or up to 30,000 pounds, or up to 40,000 pounds, or up to 50,000 pounds, or up to 60,000 pounds, or up to 70,000 pounds, or up to 80,000 pounds, or up to 90,000 pounds, or up to or exceeding 100,000 pounds.

[0071] In one or more example embodiments, the engagement mechanism **40** is sufficiently strong to resist an extraction force up to 1,000 pounds, or up to 3,000 pounds, or up to 5,000 pounds, or up to 7,000 pounds, or up to or exceeding 10,000 pounds.

[0072] Aspects of the present specification may also be described by the following numbered embodiments: [0073] 1. A selectively frictionally engaged hole cover for covering a bore hole formed through a paved surface, the selectively frictionally engaged hole cover comprising: a cover plate having a top surface and a bottom surface opposite the top surface, the top surface being configured to support safe passage of pedestrians and vehicular traffic across the selectively frictionally engaged hole cover; and an engagement mechanism coupled with the cover plate and extending from the bottom surface of the cover plate, the engagement mechanism having an engagement plate selectively shiftable relative to the cover plate and configured to thereby shift an engagement member along a engagement member stop and thus radially outwardly or inwardly; wherein, during an insertion procedure, the engagement mechanism is configured to be positioned within the bore hole and supported at least initially therein by the cover plate that is configured to rest upon the paved surface and substantially cover the bore hole; and wherein, during an engagement procedure, the engagement mechanism is configured to be actuated to cause a first movement of the engagement plate so as to shift the engagement member along the engagement member stop radially outwardly to move the engagement member into frictional contact with the bore hole to substantially prevent extraction of the engagement mechanism from the bore hole and to substantially prevent lifting of the cover plate due to forces exerted by vehicular traffic thereupon. [0074] 2. The selectively frictionally engaged hole cover of embodiment 1, wherein, during a disengagement procedure, the engagement mechanism is configured to be actuated to cause a second movement of the engagement plate so as to shift the engagement member along the engagement member stop radially inwardly to allow the engagement member to move out of

frictional contact with the bore hole and permit extraction of the engagement mechanism from the bore hole. [0075] 3. The selectively frictionally engaged hole cover of embodiments 1 or 2, wherein the engagement mechanism further comprises a screw operably installed between the cover plate and the engagement plate, the screw having a head and a shank extending from the head, the shank having a threaded portion formed thereon opposite the head. [0076] 4. The selectively frictionally engaged hole cover of embodiment 3, wherein actuation of the engagement mechanism comprises rotation of the screw in a first rotational direction to cause the first movement and rotation of the screw in a second rotational direction opposite the first rotational direction to cause the second movement. [0077] 5. The selectively frictionally engaged hole cover of embodiments 3 or 4, wherein the cover plate further comprises an access hole, the head of the screw being situated substantially flush or below the top surface of the cover plate and sufficiently aligned with the access hole to permit actuation of the screw through the access hole. [0078] 6. The selectively frictionally engaged hole cover of embodiment 5, wherein the cover plate further comprises an engagement mechanism support bracket having a sidewall extending from the bottom surface of the cover plate about the access hole and further having a support plate coupled with the sidewall opposite of the cover plate, the support plate having a support plate hole sufficiently aligned with the access hole for receipt therethrough of a shank of the screw while the head of the screw seats on the support plate. [0079] 7. The selectively frictionally engaged hole cover of embodiment 6, wherein a stand-off is installed adjacent to the support plate of the engagement mechanism support bracket, the stand-off having a through-hole for receipt therethrough of the shank of the screw, the shank having sufficient length to pass out of the through-hole of the stand-off. [0080] 8. The selectively frictionally engaged hole cover of embodiment 7, wherein a retainer plate is installed adjacent to the stand-off opposite the support plate of the engagement mechanism support bracket, the retainer plate having a retainer plate hole sufficiently aligned with the through-hole of the stand-off for receipt therethrough of the shank of the screw. [0081] 9. The selectively frictionally engaged hole cover of embodiment 8, wherein the engagement member stop is installed so as to extend downwardly and inwardly from the retainer plate, whereby the engagement member shifts up and down along the engagement member stop and thus radially outwardly and inwardly as the engagement plate shifts up and down relative to the retainer plate. [0082] 10. The selectively frictionally engaged hole cover of embodiment 9, wherein a retainer plate skirt is formed extending downwardly from the retainer plate, and further wherein the engagement member stop is configured at an angle spanning between the retainer plate and the retainer plate skirt. [0083] 11. The selectively frictionally engaged hole cover of any of embodiments 8-10, wherein the outer edge of the retainer plate and the outer edge of the engagement member are substantially vertically aligned. [0084] 12. The selectively frictionally engaged hole cover of any one of embodiments 3-11, wherein the engagement plate comprises a substantially central threaded hole for selective receipt of the threaded portion of the screw. [0085] 13. The selectively frictionally engaged hole cover of embodiment 12, wherein the engagement plate further comprises a boss in which the threaded hole is formed. [0086] 14. The selectively frictionally engaged hole cover of any one of embodiments 1-13, wherein a cover plate skirt is formed extending downwardly from the bottom surface of the cover plate. [0087] 15. The selectively frictionally engaged hole cover of embodiment 14, wherein the engagement member stop is configured at an angle spanning between the cover plate and the cover plate skirt. [0088] 16. The selectively frictionally engaged hole cover of embodiment 14, wherein the cover plate skirt and the outer edge of the engagement member are substantially vertically aligned. [0089] 17. The selectively frictionally engaged hole cover of any one of embodiments 1-16, wherein the engagement plate comprises a perimeter lip oriented to contact the engagement member in shifting the engagement member along the engagement member stop as the engagement plate is shifted relative to the cover plate. [0090] 18. A selectively frictionally engaged hole cover for covering a bore hole formed through a paved surface, the selectively frictionally engaged hole cover comprising: a cover plate having a top surface and a

bottom surface opposite the top surface, the top surface being configured to support safe passage of pedestrians and vehicular traffic across the selectively frictionally engaged hole cover, the cover plate further having a cover plate skirt formed extending downwardly from the bottom surface of the cover plate; and an engagement mechanism coupled with the cover plate and extending from the bottom surface of the cover plate, the engagement mechanism having an engagement plate selectively shiftable relative to the cover plate, the engagement mechanism further having a screw operably installed between the cover plate and the engagement plate, the screw having a head and a shank extending from the head, the shank having a threaded portion formed thereon opposite the head, the engagement plate having a substantially central threaded hole for selective receipt of the threaded portion of the screw, the engagement mechanism further having an engagement member stop configured at an angle spanning between the cover plate and the cover plate skirt, the engagement mechanism further having an engagement member in contact with both the engagement plate and the engagement member stop, the engagement plate configured to thereby shift the engagement member along the engagement member stop and thus radially outwardly or inwardly as the engagement plate shifts relative to the cover plate; wherein, during an insertion procedure, the engagement mechanism is configured to be positioned within the bore hole and supported at least initially therein by the cover plate that is configured to rest upon the paved surface and substantially cover the bore hole; and wherein, during an engagement procedure, the engagement mechanism is configured to be actuated as by rotation of the screw in a first rotational direction to cause a first movement of the engagement plate so as to shift the engagement member along the engagement member stop radially outwardly to move the engagement member into frictional contact with the bore hole to substantially prevent extraction of the engagement mechanism from the bore hole and to substantially prevent lifting of the cover plate due to forces exerted by vehicular traffic thereupon; and further wherein, during a disengagement procedure, the engagement mechanism is configured to be actuated as by rotation of the screw in a second rotational direction opposite the first rotational direction to cause a second movement of the engagement plate so as to shift the engagement member along the engagement member stop radially inwardly to allow the engagement member to move out of frictional contact with the bore hole and permit extraction of the engagement mechanism from the bore hole. [0091] 19. A selectively frictionally engaged hole cover for covering a bore hole formed through a paved surface, the selectively frictionally engaged hole cover comprising: a cover plate having a top surface and a bottom surface opposite the top surface, the top surface being configured to support safe passage of pedestrians and vehicular traffic across the selectively frictionally engaged hole cover, the cover plate further having a cover plate skirt formed extending downwardly from the bottom surface of the cover plate; and an engagement mechanism coupled with the cover plate and extending from the bottom surface of the cover plate, the engagement mechanism having an engagement plate selectively shiftable relative to the cover plate, the engagement mechanism further having a screw operably installed between the cover plate and the engagement plate, the screw having a head and a shank extending from the head, the shank having a threaded portion formed thereon opposite the head, the engagement plate having a substantially central threaded hole for selective receipt of the threaded portion of the screw, the engagement mechanism further having a retainer plate spaced from the cover plate, wherein a stand-off couples the retainer plate to the cover plate, the stand-off having a through-hole for receipt therethrough of the shank of the screw, the shank having sufficient length to pass out of the through-hole of the stand-off, the engagement mechanism further having an engagement member stop extending downwardly and inwardly from the retainer plate, the engagement mechanism further having an engagement member in contact with both the engagement plate and the engagement member stop, the engagement plate configured to thereby shift the engagement member along the engagement member stop and thus radially outwardly or inwardly as the engagement plate shifts relative to the cover plate; wherein, during an insertion procedure, the engagement mechanism is configured to be



positioned within the bore hole and supported at least initially therein by the cover plate that is configured to rest upon the paved surface and substantially cover the bore hole; and wherein, during an engagement procedure, the engagement mechanism is configured to be actuated as by rotation of the screw in a first rotational direction to cause a first movement of the engagement plate so as to shift the engagement member along the engagement member stop radially outwardly to move the engagement member into frictional contact with the bore hole to substantially prevent extraction of the engagement mechanism from the bore hole and to substantially prevent lifting of the cover plate due to forces exerted by vehicular traffic thereupon; and further wherein, during a disengagement procedure, the engagement mechanism is configured to be actuated as by rotation of the screw in a second rotational direction opposite the first rotational direction to cause a second movement of the engagement plate so as to shift the engagement member along the engagement member stop radially inwardly to allow the engagement member to move out of frictional contact with the bore hole and permit extraction of the engagement mechanism from the bore hole.

[0092] Aspects of the present specification may also be described by the following numbered embodiments: [0093] 1. A selectively frictionally engaged hole cover comprising a cover plate and an engagement mechanism: the cover plate having a top surface and a bottom surface opposite the top surface, the top surface being configured to support safe passage of pedestrians and vehicular traffic across the selectively frictionally engaged hole cover; and the engagement mechanism being coupled with the cover plate and extending from the bottom surface of the cover plate, the engagement mechanism comprising an engagement screw, an engagement plate, an engagement member, and an engagement member stop; the engagement screw operably installed between the cover plate and the engagement plate thereby attaching the cover plate to the engagement mechanism, the engagement screw having a head and a shank extending from the head, the shank having a threaded portion formed thereon opposite the head; and the engagement plate being selectively shiftable relative to the cover plate and configured to thereby shift the engagement member up and against the engagement member stop and thus radially outwardly or down and away from the engagement member stop and thus radially inwardly; wherein the selectively frictionally engaged hole cover is configured to cover a bore hole formed through a paved surface with engagement mechanism positioned within the bore hole and supported at least initially therein by the cover plate that rests upon the paved surface and substantially covers the bore hole. [0094] 2. The selectively frictionally engaged hole cover of embodiment 1, wherein actuation of the engagement mechanism comprises rotation of the engagement screw in a first rotational direction to cause the first movement and rotation of the engagement screw in a second rotational direction opposite the first rotational direction to cause the second movement. [0095] 3. The selectively frictionally engaged hole cover of embodiment 1 or 2, wherein, during an engagement procedure, the engagement mechanism is configured to be actuated to cause a first movement of the engagement plate so as to shift the engagement member up and against the engagement member stop to move the engagement member radially outwardly and into frictional contact with the bore hole to substantially prevent extraction of the engagement mechanism from the bore hole and to substantially prevent lifting of the cover plate due to forces exerted by vehicular traffic thereupon. [0096] 4. The selectively frictionally engaged hole cover of any one of embodiments 1-3, wherein, during a disengagement procedure, the engagement mechanism is configured to be actuated to cause a second movement of the engagement plate so as to shift the engagement member down and away from the engagement member stop to allow the engagement member to move radially inwardly and out of frictional contact with the bore hole and permit extraction of the engagement mechanism from the bore hole. [0097] 5. The selectively frictionally engaged hole cover of any one of embodiments 1-4, wherein the cover plate further comprises an access hole, the head of the engagement screw being situated substantially flush or below the top surface of the cover plate and sufficiently aligned with the access hole to permit actuation of the engagement screw through the access hole. [0098] 6. The selectively frictionally engaged hole cover of any one of embodiments

1-5, wherein the engagement plate comprises a substantially central threaded hole for selective receipt of the threaded portion of the engagement screw. [0099] 7. The selectively frictionally engaged hole cover of any one of embodiments 1-6, wherein the engagement plate comprises a perimeter lip oriented to contact the engagement member in shifting the engagement member along the engagement member stop as the engagement plate is shifted relative to the cover plate. [0100] 8. The selectively frictionally engaged hole cover of any one of embodiments 1-7, wherein the cover plate further comprises an engagement support bracket having a sidewall extending from the bottom surface of the cover plate about the access hole and further having a support plate coupled with the sidewall opposite of the cover plate, the support plate having a support plate hole sufficiently aligned with the access hole for receipt therethrough of a shank of the engagement screw while the head of the engagement screw seats on the support plate. [0101] 9. The selectively frictionally engaged hole cover of embodiment 8, wherein a bracket housing is installed on the bottom surface of the cover plate thereby encasing the engagement support bracket. [0102] 10. The selectively frictionally engaged hole cover of embodiment 8 or 9, wherein the bracket housing is bowl-shaped has a flat bottom portion, an angular angled portion that extends at an upward and outward angle from bottom portion to form a sloped wall, and a skirt portion that extends from angled portion and is substantially perpendicular to bottom portion, wherein the angled portion functions as the engagement member stop. [0103] 11. The selectively frictionally engaged hole cover of any one of embodiments 8-10, wherein engagement support bracket further comprises one or more bracing ribs. [0104] 12. The selectively frictionally engaged hole cover of any one of embodiments 1-7, wherein a stand-off is installed adjacent to the support plate of the engagement support bracket, the stand-off having a through-hole for receipt therethrough of the shank of the engagement screw, the shank having sufficient length to pass out of the through-hole of the stand-off. [0105] 13. The selectively frictionally engaged hole cover of embodiment 12, wherein a retainer plate is installed adjacent to the stand-off opposite the support plate of the engagement support bracket, the retainer plate having a retainer plate hole sufficiently aligned with the through-hole of the stand-off for receipt therethrough of the shank of the engagement screw. [0106] 14. The selectively frictionally engaged hole cover of embodiment 12 or 13, wherein the engagement member stop is installed so as to extend downwardly and inwardly from the retainer plate, whereby the engagement member shifts up and down along the engagement member stop and thus radially outwardly and inwardly as the engagement plate shifts up and down relative to the retainer plate. [0107] 15. The selectively frictionally engaged hole cover of any one of embodiments 12-14, wherein a retainer plate skirt is formed extending downwardly from the retainer plate, and further wherein the engagement member stop is configured at an angle spanning between the retainer plate and the retainer plate skirt. [0108] 16. The selectively frictionally engaged hole cover of any one of embodiments 12-15, wherein the outer edge of the retainer plate and the outer edge of the engagement member are substantially vertically aligned. [0109] 17. The selectively frictionally engaged hole cover of any one of embodiments 1-7, wherein a cover plate skirt is formed extending downwardly from the bottom surface of the cover plate. [0110] 18. The selectively frictionally engaged hole cover of embodiment 17, wherein the engagement member stop is configured at an angle spanning between the cover plate and the cover plate skirt. [0111] 19. The selectively frictionally engaged hole cover of embodiment 17 or 18, wherein the cover plate skirt and the outer edge of the engagement member are substantially vertically aligned. [0112] 20. A selectively frictionally engaged hole cover comprising a cover plate, a bracket housing, and an engagement mechanism: the cover plate having a top surface and a bottom surface opposite the top surface, the top surface being configured to support safe passage of pedestrians and vehicular traffic across the selectively frictionally engaged hole cover; the bracket housing installed on the bottom surface of the cover plate and encasing an engagement support bracket, the bracket housing being bowl-shaped with a flat bottom portion, an angular angled portion that extends at an upward and outward angle from bottom portion to form a sloped wall, and a skirt portion that extends from angled portion and

is substantially perpendicular to bottom portion, wherein the angled portion functions as an engagement member stop; and the engagement mechanism coupled with the cover plate and extending from the bottom surface of the cover plate, the engagement mechanism comprising an engagement screw, an engagement plate, and an engagement member; the engagement screw operably installed between the cover plate and the engagement plate thereby attaching the cover plate to the engagement mechanism, the engagement screw having a head and a shank extending from the head, the shank having a threaded portion formed thereon opposite the head; and the engagement plate having a substantially central threaded hole for selective receipt of the threaded portion of the engagement screw that enables selective shifting of the engagement plate relative to the cover plate and configured to thereby shift the engagement member up and against the engagement member stop and thus radially outwardly or down and away from the engagement member stop and thus radially inwardly; wherein the selectively frictionally engaged hole cover is configured to cover a bore hole formed through a paved surface with engagement mechanism positioned within the bore hole and supported at least initially therein by the cover plate that rests upon the paved surface and substantially covers the bore hole. [0113] 21. A selectively frictionally engaged hole cover comprising a cover plate and an engagement mechanism: the cover plate having a top surface and a bottom surface opposite the top surface, the top surface being configured to support safe passage of pedestrians and vehicular traffic across the selectively frictionally engaged hole cover and the cover plate comprising a cover plate skirt extending downwardly from the bottom surface of the cover plate and an engagement member stop configured at an angle spanning between the bottom surface of the cover plate and an outer surface of the cover plate skirt; and the engagement mechanism coupled with the cover plate and extending from the bottom surface of the cover plate, the engagement mechanism comprising an engagement screw, an engagement plate, and an engagement member; the engagement screw operably installed between the cover plate and the engagement plate thereby attaching the cover plate to the engagement mechanism, the engagement screw having a head and a shank extending from the head, the shank having a threaded portion formed thereon opposite the head; and the engagement plate having a substantially central threaded hole for selective receipt of the threaded portion of the engagement screw that enables selective shifting of the engagement plate relative to the cover plate and configured to thereby shift the engagement member up and against the engagement member stop and thus radially outwardly or down and away from the engagement member stop and thus radially inwardly; wherein the selectively frictionally engaged hole cover is configured to cover a bore hole formed through a paved surface with engagement mechanism positioned within the bore hole and supported at least initially therein by the cover plate that rests upon the paved surface and substantially covers the bore hole. [0114] 22. A selectively frictionally engaged hole cover comprising a cover plate and an engagement mechanism: the cover plate having a top surface and a bottom surface opposite the top surface, the top surface being configured to support safe passage of pedestrians and vehicular traffic across the selectively frictionally engaged hole cover; the engagement mechanism coupled with the cover plate and extending from the bottom surface of the cover plate, the engagement mechanism comprising an engagement screw, an engagement plate, an engagement member, a retainer plate, and a stand-off; the engagement screw operably installed between the cover plate and the engagement plate thereby attaching the cover plate to the engagement mechanism, the engagement screw having a head and a shank extending from the head, the shank having a threaded portion formed thereon opposite the head; and the retainer plate spaced from the cover plate, the retainer plate comprising a retainer plate skirt extending downwardly from the bottom surface of the retainer plate and an engagement member stop configured at an angle spanning between the bottom surface of the retainer plate and an outer surface of the retainer plate skirt; the stand-off couples the retainer plate to the cover plate, the stand-off having a through-hole for receipt therethrough of the shank of the engagement screw, the shank having sufficient length to pass out of the through-hole of the stand-off; and the engagement

plate having a substantially central threaded hole for selective receipt of the threaded portion of the engagement screw that enables selective shifting of the engagement plate relative to the retainer plate and configured to thereby shift the engagement member up and against the engagement member stop and thus radially outwardly or down and away from the engagement member stop and thus radially inwardly; wherein the selectively frictionally engaged hole cover is configured to cover a bore hole formed through a paved surface with engagement mechanism positioned within the bore hole and supported at least initially therein by the cover plate that rests upon the paved surface and substantially covers the bore hole.

[0115] In closing, the foregoing descriptions of embodiments of the present invention have been presented for the purposes of illustration and description. It is to be understood that, although aspects of the present invention are highlighted by referring to specific embodiments, one skilled in the art will readily appreciate that these described embodiments are only illustrative of the principles comprising the present invention. As such, the specific embodiments are not intended to be exhaustive or to limit the invention to the precise forms disclosed. Therefore, it should be understood that embodiments of the disclosed subject matter are in no way limited to a particular element, compound, composition, component, article, apparatus, methodology, use, protocol, step, and/or limitation described herein, unless expressly stated as such.

[0116] In addition, groupings of alternative embodiments, elements, steps and/or limitations of the present invention are not to be construed as limitations. Each such grouping may be referred to and claimed individually or in any combination with other groupings disclosed herein. It is anticipated that one or more alternative embodiments, elements, steps and/or limitations of a grouping may be included in, or deleted from, the grouping for reasons of convenience and/or patentability. When any such inclusion or deletion occurs, the specification is deemed to contain the grouping as modified, thus fulfilling the written description of all Markush groups used in the appended claims.

[0117] Furthermore, those of ordinary skill in the art will recognize that certain changes, modifications, permutations, alterations, additions, subtractions, and sub-combinations thereof can be made in accordance with the teachings herein without departing from the spirit of the present invention. Furthermore, it is intended that the following appended claims and claims hereafter introduced are interpreted to include all such changes, modifications, permutations, alterations, additions, subtractions, and sub-combinations as are within their true spirit and scope. Accordingly, the scope of the present invention is not to be limited to that precisely as shown and described by this specification.

[0118] Certain embodiments of the present invention are described herein, including the best mode known to the inventors for carrying out the invention. Of course, variations on these described embodiments will become apparent to those of ordinary skill in the art upon reading the foregoing description. The inventor expects skilled artisans to employ such variations as appropriate, and the inventors intend for the present invention to be practiced otherwise than specifically described herein. Accordingly, this invention includes all modifications and equivalents of the subject matter recited in the claims appended hereto as permitted by applicable law. Moreover, any combination of the above-described embodiments in all possible variations thereof is encompassed by the invention unless otherwise indicated herein or otherwise clearly contradicted by context.

[0119] The words, language, and terminology used in this specification is for the purpose of describing particular embodiments, elements, steps and/or limitations only and is not intended to limit the scope of the present invention, which is defined solely by the claims. In addition, such words, language, and terminology are to be understood not only in the sense of their commonly defined meanings, but to include by special definition in this specification structure, material or acts beyond the scope of the commonly defined meanings. Thus, if an element, step, or limitation can be understood in the context of this specification as including more than one meaning, then its use in a claim must be understood as being generic to all possible meanings supported by the specification and by the word itself.

[0120] The definitions and meanings of the elements, steps or limitations recited in a claim set forth below are, therefore, defined in this specification to include not only the combination of elements, steps or limitations which are literally set forth, but all equivalent structure, material or acts for performing substantially the same function in substantially the same way to obtain substantially the same result. In this sense it is therefore contemplated that an equivalent substitution of two or more elements, steps or limitations may be made for any one of the elements, steps or limitations in a claim set forth below or that a single element, step, or limitation may be substituted for two or more elements, steps, or limitations in such a claim. Although elements, steps or limitations may be described above as acting in certain combinations and even initially claimed as such, it is to be expressly understood that one or more elements, steps or limitations from a claimed combination can in some cases be excised from the combination and that the claimed combination may be directed to a sub-combination or variation of a sub-combination. As such, notwithstanding the fact that the elements, steps and/or limitations of a claim are set forth below in a certain combination, it must be expressly understood that the invention includes other combinations of fewer, more, or different elements, steps and/or limitations, which are disclosed in above even when not initially claimed in such combinations. Furthermore, insubstantial changes from the claimed subject matter as viewed by a person with ordinary skill in the art, now known or later devised, are expressly contemplated as being equivalently within the scope of the claims. Therefore, obvious substitutions now or later known to one with ordinary skill in the art are defined to be within the scope of the defined elements. Accordingly, the claims are thus to be understood to include what is specifically illustrated and described above, what is conceptually equivalent, what can be obviously substituted and also what essentially incorporates the essential idea of the invention.

[0121] Unless otherwise indicated, all numbers expressing a characteristic, item, quantity, parameter, property, term, and so forth used in the present specification and claims are to be understood as being modified in all instances by the term “about.” As used herein, the term “about” means that the characteristic, item, quantity, parameter, property, or term so qualified encompasses a range of plus or minus ten percent above and below the value of the stated characteristic, item, quantity, parameter, property, or term. Accordingly, unless indicated to the contrary, the numerical parameters set forth in the specification and attached claims are approximations that may vary. For instance, as mass spectrometry instruments can vary slightly in determining the mass of a given analyte, the term “about” in the context of the mass of an ion or the mass/charge ratio of an ion refers to  $\pm 0.50$  atomic mass unit. At the very least, and not as an attempt to limit the application of the doctrine of equivalents to the scope of the claims, each numerical indication should at least be construed in light of the number of reported significant digits and by applying ordinary rounding techniques.

[0122] Notwithstanding that the numerical ranges and values setting forth the broad scope of the invention are approximations, the numerical ranges and values set forth in the specific examples are reported as precisely as possible. Any numerical range or value, however, inherently contains certain errors necessarily resulting from the standard deviation found in their respective testing measurements. Recitation of numerical ranges of values herein is merely intended to serve as a shorthand method of referring individually to each separate numerical value falling within the range. Unless otherwise indicated herein, each individual value of a numerical range is incorporated into the present specification as if it were individually recited herein.

[0123] Use of the terms “may” or “can” in reference to an embodiment or aspect of an embodiment also carries with it the alternative meaning of “may not” or “cannot.” As such, if the present specification discloses that an embodiment or an aspect of an embodiment may be or can be included as part of the inventive subject matter, then the negative limitation or exclusionary proviso is also explicitly meant, meaning that an embodiment or an aspect of an embodiment may not be or cannot be included as part of the inventive subject matter. In a similar manner, use of the term

“optionally” in reference to an embodiment or aspect of an embodiment means that such embodiment or aspect of the embodiment may be included as part of the inventive subject matter or may not be included as part of the inventive subject matter. Whether such a negative limitation or exclusionary proviso applies will be based on whether the negative limitation or exclusionary proviso is recited in the claimed subject matter.

[0124] The terms “a,” “an,” “the” and similar references used in the context of describing the present invention (especially in the context of the following claims) are to be construed to cover both the singular and the plural, unless otherwise indicated herein or clearly contradicted by context. Further, ordinal indicators—such as, e.g., “first,” “second,” “third,” etc.—for identified elements are used to distinguish between the elements, and do not indicate or imply a required or limited number of such elements, and do not indicate a particular position or order of such elements unless otherwise specifically stated. All methods described herein can be performed in any suitable order unless otherwise indicated herein or otherwise clearly contradicted by context. The use of any and all examples or exemplary language (e.g., “such as”) provided herein is intended merely to better illuminate the present invention and does not pose a limitation on the scope of the invention otherwise claimed. No language in the present specification should be construed as indicating any non-claimed element essential to the practice of the invention.

[0125] When used in the claims, whether as filed or added per amendment, the open-ended transitional term “comprising”, variations thereof such as, e.g., “comprise” and “comprises”, and equivalent open-ended transitional phrases thereof like “including,” “containing” and “having”, encompass all the expressly recited elements, limitations, steps, integers, and/or features alone or in combination with unrecited subject matter; the named elements, limitations, steps, integers, and/or features are essential, but other unnamed elements, limitations, steps, integers, and/or features may be added and still form a construct within the scope of the claim. Specific embodiments disclosed herein may be further limited in the claims using the closed-ended transitional phrases “consisting of” or “consisting essentially of” (or variations thereof such as, e.g., “consist of”, “consists of”, “consist essentially of”, and “consists essentially of”) in lieu of or as an amendment for “comprising.” When used in the claims, whether as filed or added per amendment, the closed-ended transitional phrase “consisting of” excludes any element, limitation, step, integer, or feature not expressly recited in the claims. The closed-ended transitional phrase “consisting essentially of” limits the scope of a claim to the expressly recited elements, limitations, steps, integers, and/or features and any other elements, limitations, steps, integers, and/or features that do not materially affect the basic and novel characteristic(s) of the claimed subject matter. Thus, the meaning of the open-ended transitional phrase “comprising” is being defined as encompassing all the specifically recited elements, limitations, steps and/or features as well as any optional, additional unspecified ones. The meaning of the closed-ended transitional phrase “consisting of” is being defined as only including those elements, limitations, steps, integers, and/or features specifically recited in the claim, whereas the meaning of the closed-ended transitional phrase “consisting essentially of” is being defined as only including those elements, limitations, steps, integers, and/or features specifically recited in the claim and those elements, limitations, steps, integers, and/or features that do not materially affect the basic and novel characteristic(s) of the claimed subject matter. Therefore, the open-ended transitional phrase “comprising” (and equivalent open-ended transitional phrases thereof) includes within its meaning, as a limiting case, claimed subject matter specified by the closed-ended transitional phrases “consisting of” or “consisting essentially of.” As such, the embodiments described herein or so claimed with the phrase “comprising” expressly and unambiguously provide description, enablement, and support for the phrases “consisting essentially of” and “consisting of.”

[0126] Lastly, all patents, patent publications, and other references cited and identified in the present specification are individually and expressly incorporated herein by reference in their entirety for the purpose of describing and disclosing, for example, the compositions and

methodologies described in such publications that might be used in connection with the present invention. These publications are provided solely for their disclosure prior to the filing date of the present application. Nothing in this regard is or should be construed as an admission that the inventors are not entitled to antedate such disclosure by virtue of prior invention or for any other reason. All statements as to the date or representation as to the contents of these documents are based on the information available to the applicant and do not constitute any admission as to the correctness of the dates or contents of these documents.

## Claims

1. A selectively frictionally engaged hole cover comprising a cover plate, engagement support bracket, a bracket housing, and an engagement mechanism: the cover plate having a top surface and a bottom surface opposite the top surface, the cover plate having an access hole centrally located therethrough, the top surface sized to cover a bore hole formed through a paved surface; the engagement support bracket comprising a sidewall extending from the bottom surface of the cover plate and ending in a support plate, the support plate having a support plate hole centrally located therethrough, the support plate hole sufficiently aligned with the access hole of the cover plate, the bracket housing comprising a sloped wall and a skirt portion, the skirt portion affixed to the bottom surface of the cover plate thereby encasing the engagement support bracket, the engagement mechanism comprising an engagement screw, an engagement plate, and an engagement member, the engagement screw operably installed between the cover plate and the engagement plate thereby coupling the cover plate to the engagement mechanism; and the engagement plate being selectively shiftable to enable a first movement of the engagement member relative to the cover plate or a second movement of the engagement member relative to the cover plate.
2. The selectively frictionally engaged hole cover of claim 1, wherein actuation of the engagement mechanism comprises rotation of the engagement screw in a first rotational direction to cause the first movement and rotation of the engagement screw in a second rotational direction opposite the first rotational direction to cause the second movement.
3. The selectively frictionally engaged hole cover of claim 1, wherein, during an engagement procedure, the engagement mechanism is actuated to cause the first movement of the engagement plate to shift the engagement member up and against the sloped wall of the bracket housing, thereby causing radially outward movement of the engagement member.
4. The selectively frictionally engaged hole cover of claim 3, wherein the radially outward movement of the engagement member provides frictional contact with the bore hole to substantially prevent removal of the selectively frictionally engaged hole cover from the bore hole.
5. The selectively frictionally engaged hole cover of claim 1, wherein, during a disengagement procedure, the engagement mechanism is actuated to cause the second movement of the engagement plate to shift the engagement member down and away from the sloped wall of the bracket housing, thereby causing radially inward movement of the engagement member.
6. The selectively frictionally engaged hole cover of claim 5, wherein the radially outward movement of the engagement member provides frictional contact release with the bore hole to permit extraction of the selectively frictionally engaged hole cover from the bore hole.
7. The selectively frictionally engaged hole cover of claim 1, wherein the bracket housing comprises a flat bottom portion, flat bottom portion having a bracket housing hole centrally located therethrough, the bracket housing hole sufficiently aligned with the support plate hole of the engagement support bracket and the access hole of the cover plate.
8. The selectively frictionally engaged hole cover of claim 7, wherein the bracket housing is bowl-shaped where the sloped wall is an angular portion that extends at an upward and outward angle from the bottom portion, and the skirt portion extends from the sloped portion and is substantially perpendicular to the bottom portion.

9. The selectively frictionally engaged hole cover of claim 1, wherein the engagement support bracket further comprises one or more bracing ribs extending radially from the sidewall.
10. The selectively frictionally engaged hole cover of claim 9, wherein the one or more bracing ribs is six bracing ribs.
11. The selectively frictionally engaged hole cover of claim 9, wherein a bottom edge of each of the one or more bracing ribs is attached to an inner surface of the bracket housing and wherein a side edge of each of the one or more bracing ribs is attached to an inner surface of the sloped wall and the skirt portion of the bracket housing.
12. The selectively frictionally engaged hole cover of claim 1, wherein the engagement screw comprises a head and a shank extending from the head, the shank having a threaded portion formed thereon opposite the head.
13. The selectively frictionally engaged hole cover of claim 12, wherein the head of the engagement screw is situated substantially flush or below the top surface of the cover plate and sufficiently aligned with the access hole to permit actuation of the engagement screw through the access hole.
14. The selectively frictionally engaged hole cover of claim 12, wherein the engagement plate comprises a substantially central threaded hole for selective receipt of the threaded portion of the engagement screw.
15. The selectively frictionally engaged hole cover of claim 12, wherein the access hole and the support plate hole receive therethrough the shank of the engagement screw while the head of the engagement screw seats on the support plate.
16. The selectively frictionally engaged hole cover of claim 1, wherein the engagement plate has an engagement plate hole centrally located therethrough, the engagement plate hole sufficiently aligned with the support plate hole of the engagement support bracket and the access hole of the cover plate.
17. The selectively frictionally engaged hole cover of claim 1, wherein the engagement plate further comprises a perimeter lip oriented to contact the engagement member.
18. A selectively frictionally engaged hole cover comprising a cover plate, engagement support bracket, a bracket housing, and an engagement mechanism: the cover plate having a top surface and a bottom surface opposite the top surface, the cover plate having an access hole centrally located therethrough, the top surface sized to cover a bore hole formed through a paved surface; the engagement support bracket comprising a sidewall extending from the bottom surface of the cover plate and ending in a support plate, the support plate having a support plate hole centrally located therethrough, the bracket housing comprising a bottom portion, a sloped wall and a skirt portion, the bottom portion having a bracket housing hole centrally located therethrough, and the skirt portion affixed to the bottom surface of the cover plate thereby encasing the engagement support bracket, the engagement mechanism comprising an engagement screw, an engagement plate, and an engagement member, the engagement screw operably installed between the cover plate and the engagement plate thereby coupling the cover plate to the engagement mechanism; and the engagement plate having an engagement plate hole centrally located therethrough, the engagement plate being selectively shiftable to enable a first movement of the engagement member relative to the cover plate or a second movement of the engagement member relative to the cover plate, wherein the support plate hole of the engagement support bracket, the bracket housing hole of the bracket housing, and the engagement plate hole of the engagement plate are each sufficiently aligned with the access hole of the cover plate.
19. The selectively frictionally engaged hole cover of claim 18, wherein, during an engagement procedure, the engagement mechanism is actuated to rotate the engagement screw in a first rotational direction to cause the first movement of the engagement plate to shift the engagement member up and against the sloped wall of the bracket housing, thereby causing radially outward movement of the engagement member, and wherein, during a disengagement procedure, the



engagement mechanism is actuated to rotate the engagement screw in a second rotational direction to cause the second movement of the engagement plate to shift the engagement member down and away from the sloped wall of the bracket housing, thereby causing radially inward movement of the engagement member.

**20.** The selectively frictionally engaged hole cover of claim 18, wherein the engagement plate further comprising a reinforcement plate, the reinforcement plate having a reinforcement plate hole centrally located therethrough, the reinforcement plate hole sufficiently aligned with the engagement plate hole of the engagement plate.

---