United States Patent Application Publication	20250280906
Kind Code	A1
Publication Date	September 11, 2025
Inventor(s)	Salas; Mike

Insulated Pocket System

Abstract

An insulated pocket system for holding and insulating a beverage container within a pocket of a garment includes a beverage container and a garment with an outer surface. A pocket is coupled to the outer surface of the garment. The pocket has an interior space. The interior space has a size that is complementary to a size of the beverage container such that the beverage container is positionable within the pocket. A liner is positioned in the interior space. The liner covers an interior surface of the pocket. The liner includes an insulated material that can insulate the contents of the beverage container from outside temperatures when the beverage container is positioned within the pocket.

Inventors:	**Salas; Mike (Nacogdoches, TX)**
Applicant:	**Salas; Mike** (Nacogdoches, TX)
Family ID:	**96948217**
Appl. No.:	**18/601736**
Filed:	**March 11, 2024**

Publication Classification

Int. Cl.: **A41D27/20** (20060101); **A41D1/04** (20060101); **A41D27/02** (20060101)

U.S. Cl.:

CPC **A41D27/20** (20130101); **A41D1/04** (20130101); **A41D27/02** (20130101);

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS
[0001] Not Applicable
STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT
[0002] Not Applicable
THE NAMES OF THE PARTIES TO A JOINT RESEARCH AGREEMENT
[0003] Not Applicable
INCORPORATION-BY-REFERENCE OF MATERIAL SUBMITTED ON A COMPACT DISC OR AS A TEXT FILE VIA THE OFFICE ELECTRONIC FILING SYSTEM
[0004] Not Applicable
STATEMENT REGARDING PRIOR DISCLOSURES BY THE INVENTOR OR JOINT INVENTOR
[0005] Not Applicable
BACKGROUND OF THE INVENTION
(1) Field of the Invention
[0006] The disclosure relates to beverage insulators and more particularly pertains to a new beverage insulator for holding and insulating a beverage container within a pocket of a garment.
(2) Description of Related Art Including Information Disclosed under 37 CFR 1.97 and 1.98
[0007] The prior art relates to beverage insulators. For example, the prior art relates to koozies, or cozies, that generally comprise fabric or foam sleeves for insulating beverage containers to keep them cool. People may use these beverage insulators when working or relaxing outdoors in warm temperatures. Having a cool, refreshing beverage can provide the user with increased energy. When working in very warm temperatures, having a cool beverage can also help the user to avoid heat exhaustion. However, the prior art koozies do not facilitate the user in carrying the beverage along with them. Thus, particularly when working outdoors with their hands, the user may set the beverage down and walk away from the beverage. Being physically separated from the beverage can make it harder for the user to drink the beverage and use the cooled contents to avoid heat exhaustion. Thus, there is a need in the art for a beverage insulating system that can facilitate the user in keeping the beverage on their person as the user moves or walks around a space.
BRIEF SUMMARY OF THE INVENTION
[0008] An embodiment of the disclosure meets the needs presented above by generally comprising a beverage container. A garment has an outer surface. A pocket is coupled to the outer surface of the garment. The pocket has an interior space. The interior space has a size that is complementary to a size of the beverage container wherein the beverage container is positionable within the pocket. A liner is positioned in the interior space. The liner covers an interior surface of the pocket. The liner comprises an insulated material that is configured to insulate contents of the beverage container from outside temperatures when the beverage container is positioned within the pocket.
[0009] There has thus been outlined, rather broadly, the more important features of the disclosure in order that the detailed description thereof that follows may be better understood, and in order that the present contribution to the art may be better appreciated. There are additional features of the disclosure that will be described hereinafter and which will form the subject matter of the claims appended hereto.
[0010] The objects of the disclosure, along with the various features of novelty which characterize the disclosure, are pointed out with particularity in the claims annexed to and forming a part of this disclosure.

Description

BRIEF DESCRIPTION OF SEVERAL VIEWS OF THE DRAWING(S)
[0011] The disclosure will be better understood and objects other than those set forth above will

become apparent when consideration is given to the following detailed description thereof. Such description makes reference to the annexed drawings wherein:

[0012] FIG. **1** is an isometric in-use view of an insulated pocket system according to an embodiment of the disclosure.

[0013] FIG. **2** is a front view of an embodiment of the disclosure.

[0014] FIG. **3** is a top view of an embodiment of the disclosure.

[0015] FIG. **4** is a cross-sectional view of an embodiment of the disclosure.

[0016] FIG. **5** is an isometric view of an embodiment of the disclosure.

[0017] FIG. **6** is a side view of an embodiment of the disclosure.

[0018] FIG. **7** is a detail view of an embodiment of the disclosure.

[0019] FIG. **8** is a front view of an embodiment of the disclosure.

[0020] FIG. **9** is an isometric view of an embodiment of the disclosure.

[0021] FIG. **10** is a detail view of an embodiment of the disclosure.

[0022] FIG. **11** is a detail view of an embodiment of the disclosure.

DETAILED DESCRIPTION OF THE INVENTION

[0023] With reference now to the drawings, and in particular to FIGS. **1** through **9** thereof, a new beverage insulator embodying the principles and concepts of an embodiment of the disclosure and generally designated by the reference numeral **10** will be described.

[0024] As best illustrated in FIGS. **1** through **9**, the insulated pocket system **10** generally comprises a beverage container **12**. The beverage container **12** may include one of a bottle **14** and a can **16**.

[0025] A garment **18** has an outer surface **20**. The garment **18** may also have a front side **22**. For example, the garment **18** may comprise a shirt, as shown in FIGS. **1-3** and **8**. The shirt may be sleeveless wherein the shirt comprises a vest. The shirt may alternatively comprise a tank top. As shown in FIG. **8**, the shirt may have sleeves, for example comprising a jacket or sweatshirt. Alternatively, the garment may comprise a pair of pants, such as the cargo shorts shown in FIG. **5**, or a bag, such as the backpack shown in FIG. **6** or the tote bag shown in FIG. **9**.

[0026] A pocket **24** is coupled to the outer surface **20** of the garment **18**. The pocket **24** has an interior space **30**. The interior space **30** has a size that is complementary to a size of the beverage container **12** wherein the beverage container **12** is positionable within the interior space **30** of the pocket **24**.

[0027] For example, the pocket **24** may comprise a bottom wall **26** and a peripheral wall **28** that is coupled to and extends upwardly from the bottom wall **26** to define the interior space **30**. The peripheral wall **28** may have an upper edge **32** defining an opening **34** that is distal to the bottom wall **26**. The opening **34** facilitates access to the interior space **30**. The bottom wall **26** may extend perpendicularly outward from the outer surface **20** of the garment **18**. The peripheral wall **28** may extend perpendicularly upward from the bottom wall **26**. The bottom wall **26** may have a quadrilateral shape that is configured to receive a base surface **36** of the beverage container **12**. The peripheral wall **28** may have a height **38** exceeding a length **40** of the bottom wall **26**.

[0028] Alternatively, the pocket **24** may comprise a panel having a bottom edge and opposing side edges that are each coupled to the garment **18** to define the interior space **30**. Free ends of the opposing side edges may define the opening **34** that is distal to the bottom edge.

[0029] A liner **42** is positioned in the interior space **30**. The liner **42** comprises an insulated material that is configured to insulate contents of the beverage container **12** from outside temperatures when the beverage container **12** is positioned within the pocket **24**. The liner **42** may cover an interior surface **44** of the bottom wall **26** and the peripheral wall **28** of the pocket **24**. The liner **42** may also cover a portion **46** of the outer surface **20** of the garment **18**. The portion **46** of the outer surface **20** of the garment **18** is generally positioned within the interior space **30**. The liner **42** may be coupled to the outer surface **20** of garment **18**, to the interior surface **44** of the bottom wall **26** and/or the peripheral wall **28** of the pocket **24**, or to both the garment **18** and the pocket **24**.

[0030] The pocket **24** may be positioned on the front side **22** of the garment **18** such that the beverage container **12** is configured to be accessible to a user **52** when the user **52** is wearing the garment **18**. Alternatively, the pocket **24** may be positioned on a lateral side of the garment **18**. In such alternative embodiments, the beverage container **12** may still be configured to be accessible to the user **52** when the user **52** is wearing the garment **18**.

[0031] A band **50** may be coupled to at least one of the pocket **24** and the liner **42**. The band **50** is generally positioned between the pocket **24** and the liner **42**. The band **50** may be positioned between the bottom wall **26** and the opening **34** of the pocket **24**. The band **50** may comprise a resiliently compressible material that is configured to secure the beverage container **12** within the pocket **24**. For example, the band **50** may expand to accommodate the beverage container **12** that is positioned within the pocket **12** and contract around the beverage container **12** once the beverage container is inserted within the pocket **12**. The band **50** may be thereby configured to inhibit the beverage container **12** from tipping within the pocket **24** and to inhibit contents of the beverage container **12** from spilling out of the beverage container **12**.

[0032] The peripheral wall **28** of the pocket **24** may further comprise a front surface **54**, and a pair of opposing lateral surfaces that are coupled to and extend between the front surface and the outer surface **20** of the garment **18**. Each of the pair of opposing lateral surfaces **58** may have a side fold **60** that extends from the bottom wall **26** to the upper edge **32** of the peripheral wall **28** thereby facilitating each of the pair of opposing lateral surfaces **58** to be collapsible along the side fold **60**. The bottom wall **26** may have a bottom fold **62** that extends along the length **40** of the bottom wall, for example from a first surface of the pair of opposing lateral surfaces **58** to a second surface of the pair of opposing lateral surfaces **58**, thereby facilitating the bottom wall **26** to be collapsible along the bottom fold **62**.

[0033] As shown in FIGS. **6** and **7**, the garment **18** may comprise the backpack **64**. The backpack **64** generally includes a shoulder strap **66**. The pocket **24** may be coupled to, or releasably securable to, the shoulder strap **66**. The peripheral wall **28** of the pocket **24** may include the front surface **54**, a back surface **56**, and the pair of opposing lateral surfaces **58** that are coupled to and extend between the front surface **54** and the back surface **56**.

[0034] The pocket **24** may comprise a flap **68** that is coupled to the back surface **56** of the peripheral wall **28**. Alternatively, the flap **68** may be coupled to the outer surface **20** of the garment **18** and positioned adjacent to the upper edge **32** of the pocket **24**. The flap **68** is generally foldable over the upper edge **32** for selectively closing the opening **34**. The flap **68** may be releasably couplable to an exterior surface the front surface **54** of the peripheral wall **28** when the flap **68** is folded over the upper edge **32**.

[0035] A flap coupler **70** may releasably fasten the flap **68** to the exterior surface of the front surface **54** of the peripheral wall **28**. For example, the flap coupler **70** may comprise a first mating member **72** that is attached to the exterior surface of the front surface **54** of the peripheral wall **28**. A second mating member **74** may be releasably engageable with the first mating member **72**. The second mating member **74** may be attached to an inner surface of the flap **68** and is generally alignable with the first mating member **72** when the flap **68** is folded over the upper edge **32**. Each of the first mating member **72** and the second mating member **74** may comprise a hook and loop material, or another suitable fastener such as a snap, a button, or a magnet.

[0036] A handle **76** may be coupled to the back surface **56** of the peripheral wall **28**. The handle **76** may extend between the upper edge **32** and the bottom wall **26**. The handle **76** may be removably couplable to the shoulder strap **66** of the backpack **64** to releasably secure the pocket **24** to the shoulder strap **66**.

[0037] A handle fastener **78** may releasably couple the handle **76** to the shoulder strap **66**. For example, the handle fastener **78** may comprise a primary coupling piece **80** that is attached to the handle **76**. A secondary coupling piece **82** may be releasably engageable with the primary coupling piece **80**. The secondary coupling piece **82** may be attached to the shoulder strap **66**. The secondary coupling piece **82** is generally alignable with the primary coupling piece **80** when the pocket **24** is coupled to the shoulder strap **66**. Each of the primary coupling piece **80** and the secondary coupling piece **82** may comprise a hook and loop material, or another suitable fastener such as a snap, a button, or a magnet.

[0038] FIGS. **10** and **11** show an alternative embodiment wherein the pocket **24** is configured to hold two beverage containers **12**. As shown, the pocket **24** may include an interior wall **84** that separates the interior space **30** into a first chamber **86** and a second chamber **88**. For example, the interior wall **84** may be coupled to and extend upwardly from the bottom wall **26**. The interior wall **84** may also be coupled to and extend between opposing edges of the peripheral wall **28**. The interior wall **84** may have a top edge **90** that is spaced from the bottom wall **26**. The top edge **90** may be offset from the upper edge **32** of the peripheral wall **28**, as shown in FIG. **10**. Alternatively, the top edge **90** may be aligned or coplanar with the upper edge **32** of the peripheral wall **28**. The flap **68** may be folded over both the top edge **90** of the interior wall **84** and upper edge **32** of the peripheral wall **28** to selectively close the opening **34**. The flap coupler **70** may releasably fasten the flap **68** to the front surface **54** of the peripheral wall **28** to keep the flap **68** closed over the opening **34**.

[0039] In use, the user **52** can position the beverage container **12** within the interior space **30** of the pocket **24**. With the embodiments shown in FIGS. **10** and **11**, the user **52** may position a first beverage container **12** within the first chamber **86** and a second beverage container **12** within the second chamber **88**. The pocket **24** may be positioned on any garment **18**, so that the user **52** can easily carry the beverage container **12** along with them in the pocket **24**. The insulated material of the liner **42** will insulate contents of the beverage container **12** from outside temperatures, for example so that the contents of the beverage container **12** remain cool when the user **52** is working outdoors in warm temperatures. The band **50** can retain the beverage container **12** within the pocket **24**, inhibiting the beverage container **12** from tipping over or falling out of the pocket **24** as the user **52** works. The flap **68** can be folded over the upper edge **32** of the peripheral wall **28** of the pocket **24** to provide further insulation and to further inhibit the beverage container **12** from falling out of the pocket **24** as the user **52** works.

[0040] With respect to the above description then, it is to be realized that the optimum dimensional relationships for the parts of an embodiment enabled by the disclosure, to include variations in size, materials, shape, form, function and manner of operation, assembly and use, are deemed readily apparent and obvious to one skilled in the art, and all equivalent relationships to those illustrated in the drawings and described in the specification are intended to be encompassed by an embodiment of the disclosure.

[0041] Therefore, the foregoing is considered as illustrative only of the principles of the disclosure. Further, since numerous modifications and changes will readily occur to those skilled in the art, it is not desired to limit the disclosure to the exact construction and operation shown and described, and accordingly, all suitable modifications and equivalents may be resorted to, falling within the scope of the disclosure. In this patent document, the word “comprising” is used in its non-limiting sense to mean that items following the word are included, but items not specifically mentioned are not excluded. A reference to an element by the indefinite article “a” does not exclude the possibility that more than one of the element is present, unless the context clearly requires that there be only one of the elements.

Claims

1. A beverage insulating system comprising: a beverage container; a garment having an outer surface; a pocket being coupled to the outer surface of the garment, the pocket having an interior space, the interior space having a size being complementary to a size of the beverage container wherein the beverage container is positionable within the pocket, the pocket including a bottom wall and a peripheral wall being coupled to and extending upwardly from the bottom wall to define

the interior space, the peripheral wall having an upper edge defining an opening distal to the bottom wall to facilitate access to the interior space; a liner being positioned in the interior space, the liner covering an interior surface of the pocket, the liner comprising an insulated material being configured to insulate contents of the beverage container from outside temperatures when the beverage container is positioned within the pocket; and a band being positioned between the pocket and the liner, the band comprising a resiliently compressible material being configured to secure the beverage container within the pocket, the band being positioned between the bottom wall and the opening of the pocket wherein a distance between the bottom wall and the band is less than a distance between the opening and the band.
2. The beverage insulating system of claim 1, the garment further comprising a front side, wherein the pocket is positioned on the front side of the garment such that the beverage container is configured to be accessible to a user when the user is wearing the garment.
3. (canceled)
4. (canceled)
5. The beverage insulating system of claim 1, wherein the bottom wall extends perpendicularly outward from the outer surface of the garment.
6. The beverage insulating system of claim 1, wherein the peripheral wall extends perpendicularly upward from the bottom wall.
7. The beverage insulating system of claim 1, wherein the peripheral wall has a height exceeding a length of the bottom wall.
8. The beverage insulating system of claim 1, wherein the bottom wall has a shape with a pair of straight sides and a pair of curved sides extending between the pair of straight sides, each curved side of the pair of curved sides being elongated relative to the pair of straight sides wherein the shape is configured to receive a base surface of the beverage container.
9. The beverage insulating system of claim 1, wherein the liner covers an interior surface of the bottom wall and the peripheral wall of the pocket.
10. The beverage insulating system of claim 1, wherein the liner covers an interior surface of the peripheral wall of the pocket.
11. The beverage insulating system of claim 1, wherein the liner covers an interior surface of the bottom wall of the pocket.
12. The beverage insulation system of claim 1, wherein the liner covers a portion of the outer surface of the garment being positioned within the interior space.
13. (canceled)
14. The beverage insulation system of claim 1, wherein the band is coupled to the pocket and the liner.
15. The beverage insulation system of claim 1, wherein the band is coupled to the pocket.
16. The beverage insulation system of claim 1, wherein the band is coupled to the liner.
17. A beverage insulating system comprising: a beverage container, the beverage container including one of a bottle and a can; a garment having an outer surface, the garment having a front side, the garment comprising a shirt, the shirt being sleeveless wherein the shirt comprises a vest; a pocket being coupled to the outer surface of the garment, the pocket comprising a bottom wall and a peripheral wall being coupled to and extending upwardly from the bottom wall to define an interior space, the peripheral wall having an upper edge defining an opening distal to the bottom wall to facilitate access to the interior space, the interior space having a size being complementary to a size of the beverage container wherein the beverage container is positionable within the pocket, the bottom wall extending perpendicularly outward from the outer surface of the garment, the peripheral wall extending perpendicularly upward from the bottom wall, the peripheral wall having a height exceeding a length of the bottom wall; a liner being positioned in the interior space, the liner covering an interior surface of the bottom wall and the peripheral wall of the pocket, the liner covering a portion of the outer surface of the garment wherein the portion of the outer surface of

the garment is positioned within the interior space, the liner comprising an insulated material being configured to insulate contents of the beverage container from outside temperatures when the beverage container is positioned within the pocket; wherein the pocket is positioned on the front side of the garment such that the beverage container is configured to be accessible to a user when the user is wearing the garment; and a band being coupled to at least one of the pocket and the liner, the band being positioned between the pocket and the liner, the band comprising a resiliently compressible material being configured to secure the beverage container within the pocket, the band being positioned between the bottom wall and the opening of the pocket wherein a distance between the bottom wall and the band is less than a distance between the opening and the band.