US Patent & Trademark Office Patent Public Search | Text View

United States Patent

Kind Code

Date of Patent

Inventor(s)

12391437

August 19, 2025

Prinz; Michael et al.

Suction lance

Abstract

A suction lance comprising at least one tube and a guide body made from an elastomer material axially displaceable on this tube is provided. The suction lance comprises a retaining section for a connecting body, a conical section axially adjoining the retaining section, the radially largest section whereof lies axially closer to the retaining section than the radially smallest section thereof, and a connecting body for the detachable connection of the suction lance to a removal opening of a container. The connecting body is fastened to the retaining section of the guide body, and the conical section of the guide body, by reason of its material, its radial size and the shape of its external contour, is designed to act in case of use as a sealing body in a removal opening of a container.

Inventors: Prinz; Michael (Leutkirch, DE), Hildebrand; Nadine (Leutkirch, DE)

Applicant: elobau Gmbh & Co. KG (Leutkirch, DE)

Family ID: 1000008766316

Assignee: LOBAU GMBH & CO. KG (Leutkirch, DE)

Appl. No.: 18/093983

Filed: January 06, 2023

Prior Publication Data

Document IdentifierUS 20230312190 A1

Publication Date
Oct. 05, 2023

Foreign Application Priority Data

DE 10 2022 100 407.4 Jan. 10, 2022 DE 20 2022 104 599.2 Aug. 12, 2022

Publication Classification

Int. Cl.: B65D47/06 (20060101)

U.S. Cl.:

CPC **B65D47/06** (20130101);

Field of Classification Search

CPC: B65D (47/06)

USPC: 222/514; 16/2.3; 16/2.4

References Cited

U.S. PATENT DOCUMENTS

Issued Date	Patentee Name	U.S. Cl.	CPC
12/1925	Polk	215/309	G01F 11/084
12/1933	Gabel	217/111	B67D 3/04
12/1935	Rice	217/113	B65D 39/082
12/1936	Joh	222/545	B67D 1/0829
12/1952	Gray	222/400.7	B65D 39/082
12/1954	Aneshansley	222/215	G01N 1/14
12/1955	Beutel	222/464.2	B67D 1/0456
12/1957	Potash	222/402.18	B65D 83/425
12/1958	Bull	277/606	B60R
12/1050	Toulan III	222/500	16/0222
	5		B65D 47/148
			B67D 1/0829
			B67D 1/0829
	·		B67D 1/0829
	<u> </u>		B65D 51/20
			H02G 3/088
			B65D 39/08
			B67D 3/0048
			A61J 15/0026
			B01L 3/565
12/1993		16/2.2	F16L 5/10
12/1997	_	16/2.2	H02G 3/083
12/1998	Henderson	215/319	B67D 7/0288
12/1999	Murray	222/542	A01K 7/06
12/2001	Murray	222/542	A01K 7/06
12/2003	Ver Hage	119/72	A01K 7/06
12/2008	Anderson	222/105	B67D 1/0462
12/2013	Cayzac	277/606	F16L 5/10
12/2015	Grittmann	N/A	B65D 39/12
12/2002	Ver Hage	119/72	A01K 7/06
	12/1925 12/1933 12/1935 12/1936 12/1952 12/1954 12/1955 12/1957 12/1958 12/1958 12/1965 12/1966 12/1969 12/1975 12/1976 12/1976 12/1985 12/1986 12/1989 12/1990 12/1993 12/1993 12/1997 12/1998 12/1999 12/2001 12/2003 12/2008 12/2015	12/1925 Polk 12/1933 Gabel 12/1935 Rice 12/1936 Joh 12/1952 Gray 12/1954 Aneshansley 12/1955 Beutel 12/1957 Potash 12/1958 Bull 12/1958 Taylor, III 12/1965 Nicko 12/1966 Nicko 12/1975 Haag 12/1976 Olmstead 12/1985 Grittmann 12/1986 Neward 12/1999 Justal 12/1990 Freidel 12/1993 Benda 12/1999 Murray 12/1999 Murray 12/2001 Murray 12/2003 Ver Hage 12/2013 Cayzac 12/2015 Grittmann	12/1925 Polk 215/309 12/1933 Gabel 217/111 12/1935 Rice 217/113 12/1936 Joh 222/545 12/1952 Gray 222/400.7 12/1954 Aneshansley 222/215 12/1955 Beutel 222/464.2 12/1957 Potash 222/402.18 12/1958 Bull 277/606 12/1958 Taylor, III 222/569 12/1958 Taylor, III 222/569 12/1965 Nicko 285/364 12/1965 Nicko 285/364 12/1966 Nicko 222/400.7 12/1969 Johnson, Jr. 137/212 12/1975 Haag 220/254.1 12/1976 Olmstead 277/627 12/1985 Grittmann 217/111 12/1986 Neward 141/46 12/1989 Justal 215/250 12/1990 Freidel 215/276 12/1998 Henderson <t< td=""></t<>

2010/0133227	12/2009	Ver Hage	215/354	A01K
		vei Hage		39/0213
2015/0108080	12/2014	Grittmann	215/359	B65D 45/32

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
1815006	12/1969	DE	N/A
2343232	12/1974	DE	N/A
102019102033	12/2019	DE	N/A

OTHER PUBLICATIONS

European Search Report for European Patent Application No. EP22217087 mailed May 31, 2023 (1 page). cited by applicant

Primary Examiner: Durand; Paul R

Assistant Examiner: Melaragno; Michael J.

Attorney, Agent or Firm: Dickinson Wright PLLC

Background/Summary

(1) This U.S. patent application claims priority to German patent application no. 10 2022 100 407.4, filed Jan. 10, 2022, and German utility model patent application no. 20 2022 104 599.2, filed Aug. 12, 2022, the entire contents of which are incorporated herein by reference in their entirety.

BACKGROUND

- 1. Technical Field
- (2) The present invention relates to a suction lance.
- 2. Related Art
- (3) Suction lances are used for the removal of liquids (fluid media) from containers, in particular fuels, operating resources, agents for the reduction of exhaust gas constituents, disinfection and cleaning agents and other fluid media. They can be fastened reversibly to a container.
- (4) Suction lances as a rule comprise a head part fastened in the operating state to the outer side of the container and one or more tubes projecting into the container and thus into the fluid media (liquid) and conducting medium in the operating state, which are held as applicable in a foot part. The foot part can stand on the bottom of the container, but often hangs freely in the container and has no contact with the bottom thereof or is completely absent. Insofar as present, it comprises one or more inlet openings for the fluid, so that the latter can penetrate into the tube or tubes and can be passed through the latter. The tubes are connected media-tight to the foot and head part, wherein a second tube possibly present serves as a return line. Suction lances can also comprise a float or in general a sensor, by means of which the liquid level in the container or other properties of the liquid such as its temperature, etc. can be detected. The head part usually has connections for the onward transfer of the liquid removed from the container (the removed fluid medium) to downline pump metering systems.
- (5) Suction lances are intended to enable a reliable removal of the fluid medium present in the container. This applies in particular when the container changes in its spatial orientation during the removal, in particular is tilted or placed upside down or subjected to vibrations or is shaken.
- (6) Different containers comprise the most varied connection options at their respective removal

openings, for example a nozzle with an external thread or one with a smooth wall. In addition, the diameter of the respective removal openings differ from one another with different containers.

- (7) Suction lances are thus known from the prior art which are designed for containers with specific connection arrangements and cannot be assembled operationally reliable on containers with other connection arrangements.
- (8) DE 10 2019 102 033 A1 discloses a suction lance, in which a tube is housed in a sleeve element made of a rigid material which is displaceable thereon, which for its part passes through a coaxial opening of a cap cover with an inner retaining contour, wherein the cap cover with the retaining contour can be screwed/pushed onto an external thread of a container opening in the manner of an internal thread and the snap-in projections of the retaining contour engage into the external thread of the container. For this purpose, this known cap cover is formed from an elastically deformable material. It also comprises a vent opening. By replacing a cap cover for another one, this suction lance can be adapted to different containers.

SUMMARY

- (9) The invention has the problem of specifying a suction lance which can be fastened in a straightforward manner to different containers.
- (10) This problem is solved by a suction lance, comprising at least one tube and a guide body made from an elastomer material axially displaceable on this tube, comprising a retaining section for a connecting body, further comprising a conical section axially adjoining the retaining section, the radially largest section whereof lies axially closer to the retaining section than the radially smallest section thereof, further comprising a connecting body for the detachable connection of the suction lance to a removal opening of a container, wherein the connecting body is fastened to the retaining section of the guide body, wherein the conical section of the guide body, by reason of its material, its radial size and the shape of its external contour, is designed to act in case of use as a sealing body in a removal opening of the container.
- (11) To great advantage, the invention enables the use of the guide body of the tube at the same time also as a sealing body at a removal opening of the container and thus very advantageously extends the types of container for which the suction lance according to the invention can be used. The latter can be fastened to the container both by different connection bodies and also by the guide body itself. According to the invention, therefore, both these two bodies are available in each case alone for the fastening as well as jointly, which leads to a particularly operationally reliable fastening of the suction lance to the container.
- (12) For this purpose, the guide body is in the first place formed from an elastomer, soft material deformable with little effort, which can abut in a sealing manner against the inner wall or the edge of a removal opening. In addition, the guide body is constituted with a conical section with in particular a smooth outer contour in the manner of a lateral surface of a truncated cone, which thus provides different diameters for sealing along its axial extension, as a result of which both narrow and also further removal openings up to the maximum radial size of the conical section can be closed in a sealing manner with this guide body.
- (13) The possibility according to the invention of being able to fasten the suction lance both by means of the connecting body at the outer side of the removal opening and also by the conical section at the inner side is a particularly great advantage.
- (14) In an embodiment of the invention, provision is made such that, in its interior, the guide body comprises two retaining collars axially spaced apart from one another for contact with the tube, in particular retaining collars which are adapted to the outer contour of a rounded rectangular tube. These retaining collars serve to guide the tube and seal its outer side, so that any fluid creeping along there cannot escape to the outside and thus to the user of the suction lance.
- (15) In a development of the invention, provision is made to particularly great advantage that the retaining section is constituted roughly u-shaped in the cross section of the guide body, wherein the base of the U lies radially inwards relative to the radially largest section of the conical section. This

enables a particularly reliable and firm connection between the guide and connecting body, since the latter is encompassed by the legs of the U.

- (16) In an embodiment of the invention, provision is made such that a first end of the guide body is formed by one of the two retaining collars and a second end of the guide body lying axially opposite is formed by a gripping and displacement collar, which is constituted in particular radially larger than the radially largest section of the conical section of the guide body and which preferably comprises a radial recess, in such a way that an accommodation for a welding seam on the tube is formed. The gripping collar enables the axial movement of the guide body along the longitudinal axis of the tube accommodating it by a simple grip. The axially running radial recess forms an accommodation open at one side at the second end of the guide body, so that the latter as it were can be pushed up to the stop at the end of the tube, where the latter is usually connected to further components of the suction lance by means of an, in particular, bulge-like welding seam or a connection piece, as explained at the outset. This in turn enables a particularly deep immersion of the tube into the container, since the components of the suction lance according to the invention serving for the fastening to the container are arranged virtually completely at the end of the tube. (17) If a retaining collar comprises one or more radially inwardly springing sealing lips and/or an axial groove, in particular a venting groove, a particularly tight contact at the outer wall of the tube is very advantageously enabled, so that no fluid can escape that is creeping along the tube. A venting groove admittedly prevents this function, but advantageously permits a structurally simple ventilation, that is to say a simple compensation for the removed liquid volume by external air flowing into the container.
- (18) In a development of the invention, provision is made such that the guide body comprises a connecting nozzle for the media return flow or for the container venting. This alternative to the venting groove is preferred, since both the tube is thus sealed and also a volume compensation is enabled.
- (19) In an embodiment of the invention, provision is made such that the guide body is formed from one of the materials of the group formed by silicon, EPDM, TPE, TPU, FKM, NBR, rubber, natural rubber, and/or have a Shore-A hardness between 40 and 60, limits included. These materials are particularly well suited in order on the one hand to enable the sealing function of the guide body desired according to the invention and are also particularly resistant or inert with respect to the fluid/media to be removed.
- (20) In particular, the guide body is constituted as a hollow body, in the hollow space whereof at least one retaining collar is constituted axially projecting. A hollow body is again better suited for performing a sealing function on account of its deformability.
- (21) Finally, provision is also made in an embodiment of the invention such that the connecting body is a screw cover, a snap-on cover, a snap-on cap or a disc-like insert. The invention very advantageously enables a replacement of a connecting body by one of the others stated, which are all fastened to the retaining section. This retaining section is constituted such that this cover/cap can be pulled onto the guide body without dismantling any float of the suction lance that might be present.
- (22) In a development of the suction lance, provision is made such that the guide body has an elliptical cross-section, in particular over the axial length of the conical section. Such an elliptical cross-section of the conical section, especially between its largest and smallest radial extension, displays a better clamping behaviour with a simultaneously facilitated introduction into the opening of the container. This elliptical cross-section is deformed into a round cross-section by pressing in and thus reliably abuts against the opening wall. In other words, an improved clamping behaviour thus results with markedly reduced insertion force.
- (23) The development is particularly advantageous, according to which the radially largest section of the conical section comprises a thickening. This additional thickening again improves the retaining force in the elliptical region and facilitates the insertion. The connecting body according

to the invention such as a screw cover, a snap-on cover, a snap-on cap or an insert can easily be pushed over this thickening and thus held better in the retaining section of the guide body. In an embodiment of the invention, this retaining section is also itself constituted with an elliptical cross-section.

(24) If a recess is provided in the displacement collar for the ventilation, good aeration and venting of the container is thus guaranteed in a straightforward manner.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The invention is explained in greater detail below with the aid of the figures of the drawing, wherein identical components are provided with the same reference numbers. In the figures:
- (2) FIGS. **1**A, **1**B and **1**C are partial figures each showing a diagrammatic cross-section through part of an embodiment of the suction lance with different connecting bodies,
- (3) FIGS. **2**A and **2**B are partial figures each showing an arrangement of the embodiment in two removal openings of differing width,
- (4) FIG. **3**A is a side view through a guide body of a first embodiment and
- (5) FIG. **3**B is a perspective cross-sectional view through a guide body of a second embodiment, and
- (6) FIG. **4**A is a side view of an embodiment of a guide body with an elliptical cross-section of the conical section, and FIG. **4**B is a perspective view of the embodiment of the guide body with the elliptical cross-section of the conical section.

DETAILED DESCRIPTION OF EXAMPLE EMBODIMENTS

- (7) FIG. **1**A is an axial partial section of an embodiment of suction lance **1** with tube **2**, which is accommodated in a guide body **3**. A connecting body **5** is fastened in a retaining section **4**, which here is constituted as a snap-on cap **24** and is snapped onto a nozzle in a removal opening of a container. In the same way, partial FIG. **1**B shows a connecting body **5** as a screw cover **22**, which is screwed onto an external thread of a removal opening of a container and partial FIG. **1**C shows a connecting body **5** as a snap-on cover **24**, which is clipped onto a nozzle on a removal opening of a container.
- (8) On account of the embodiment of retaining section **4** as a roughly u-shaped region lying in cross-section, the latter offers fastening and holding possibilities for different connecting bodies **5**. Thus, the snap-on cap **24** usually made of flexible, in particular rubbery material, clamps with its rounded end against both sides of the U, whereas the other two connecting bodies **5** either compress the base of the U **12** together and/or widen the sides of the U, so that the latter press against it on account of their material properties and thus hold it in a force-fit and also a slightly form-fit manner. Since, as will be described further below, guide body **3** can itself also function according to the invention as a sealing body in a removal opening, a coloured insert in the form of a disc penetrated by guide body **3** is also a form of a connecting body according to the invention, even if this insert does not produce any connection to a container. By selecting the colour, however, it can indicate the contents of a container in a rapidly detectable manner.
- (9) FIG. **2**A shows an arrangement of a guide body **3** according to the invention in a removal opening **25** of a container **26**, wherein removal opening is understood to mean the actual opening as well as associated nozzle **18** with an external thread. Connecting body **5** has been omitted in this representation. With the represented arrangement, guide body **3**, by means of its outer contour **9**—a truncated cone lateral surface, seals at the edge of the neck of container **26** on account of its elastomer material, its shape and its axial extension with its conical section **6**. As can easily be seen, this kind of seal is possible for all removal openings **25** which have an opening diameter smaller than or equal to the different diameters of conical section **6**. In combination with a snap-on

- cap **24** according to FIG. **1**A as a connecting body **5**, the otherwise usual equipment of the suction lance with additional weight against floating can thus advantageously be dispensed with, and also no fluid can run out when the container tilts. In other words, only the elastomer, large-diameter and conically running guide body according to the invention enables a reliable and simple use of snapon caps as connecting bodies and with removal openings of differing width.
- (10) Soft, elastomer guide body **3** can also be arranged in this clamping and sealing manner with very large opening widths of a removal opening **25**, as partial FIG. **2**B shows. Here, it is not the truncated cone lateral surface or conical section **6** that are compressed, but the base of the truncated cone itself. On account of the large contact area, this represents a particularly tight and firm connection of suction lance and container.
- (11) The arrangements according to these two partial figures enable in each case a double connection between suction lance and container, i.e. simultaneously by connecting body 5 and guide body 3 not represented for the sake of clarity.
- (12) FIG. 3A shows a cross-sectional view through a first embodiment of a guide body 3 according to the invention. The latter is constituted as a hollow body with an interior 10, through which tube 2 not represented here penetrates. This tube is axially spaced apart at two retaining collars 11, of which one is arranged at first end 13 of guide body 3 and which also serves for the stabilisation of the tube guidance. Second retaining collar 11 comprises two sealing lips 19, which abut against the external wall of the tube and prevent fluid from leaking out between the tube and the guide body. A possibly present axial groove penetrating through the two sealing lips 19 serves for the ventilation of the container interior and thus facilitates the removal of liquid, even though the fluid density is somewhat reduced as a result. The passage opening area of the two retaining collars 11 is constituted in this embodiment as a rounded rectangle and is therefore suited for rectangular tubes, as can be seen in particular from partial FIG. 3B. Other passage opening areas are also according to the invention, in particular circular or oval, depending on the nature of the tube.
- (13) Retaining collar **11** lying in the direction of second end **14** transforms on the one hand into a displacement collar **15**, at which the relative axial position of guide body **3** to a tube can be changed. On account of the soft material of guide body **3**, a frequent axial adjustment is possible, without it no longer abutting firmly against the tube due to wear. This is in particular the case with the known guide bodies made of a hard material such as PVC, which permit only very few axial position changes. With the latter, inevitable hard mounting of the connecting body rapidly wears away, so that the latter can no longer be connected firmly to the hard guide bodies.
- (14) The base of the U **12** and sides **27** branching off from the latter serve to clamp a connecting body, just as the base of the U **12** itself, as previously described.
- (15) At second end **14**, the displacement collar **15** springs radially inwards in such a way that an axially-radially running accommodation **17** is formed, in particular a conical one, in which for example a welding seam at the end of the tube can be housed, so that the tube can be arranged as deeply as possible in the container, since it is supported at its upper end as far as possible.
- (16) The outer contour of guide body **3** with its conical section **6** and radially largest section **7** as well as radially smallest section **8** can clearly be seen.
- (17) Partial FIG. **3**B shows a perspective cross-sectional view of a second embodiment, in which in particular a connecting nozzle **18** for the ventilation is provided, so that upper retaining collar **11** abuts against the tube wall in a completely sealing manner. According to the invention, this connecting nozzle **18** can also be used for the return flow of removed fluid into the container.
- (18) Very advantageously, the invention of a guide body made of elastomer material such as silicon, EPDM, TPE, TPU, FKM, NBR, rubber, natural rubber, which have a Shore-A hardness between 40 and 60, in a conical shape with a smooth outer contour, or outer surface with the provision of a many-sided retaining section for different connecting bodies, permits a suction lance which is suitable for use with very different containers with removal openings of different sizes and shapes. The complicated adjustment of the insertion depth of the suction lance by for example clamping

rings and nuts can advantageously be dispensed with, since the described connecting body can be displaced axially in an easy and durable manner and in addition also undertakes a sealing and retention function for the suction lance.

(19) FIGS. **4**A and **4**B show a further embodiment of guide body **3**, wherein conical section **6** has an elliptical cross-section, in particular between its radially largest section **7** and its radially smallest section **8**. This leads to an easier insertability of the suction lance into a removal opening **25** (see FIG. **2**A) of a container, since contact with its inner wall over the greatest part of the circumference is avoided and can only take place in the region of the main axis. According to the invention, an elliptical cross-section can also be understood to mean an oval cross-section. The elliptical cross-section extends in this embodiment not up to displacement collar **15**, but is connected to the latter via an axial section of guide body **3**, which has a circular cross-section. In partial FIG. **4**A, a thickening **21** can also be seen, which is arranged in radially largest section **7**. (20) In partial FIG. **4**B, it can be seen that a recess **20** is provided in displacement collar **15** for the ventilation of a container. Such a recess represents the simplest possibility for such ventilation.

Claims

- 1. A suction lance, comprising: at least one tube and a guide body made from an elastomer material axially displaceable on the tube, a retaining section for a connecting body, the connecting body being for a detachable connection of the suction lance to a removal opening of a container, a conical section axially adjoining the retaining section, the radially largest section whereof lies axially closer to the retaining section than the radially smallest section thereof, wherein the connecting body is fastened to the retaining section of the guide body, wherein the conical section of the guide body, by reason of its material, its radial size and the shape of its external contour, is designed to act in case of use as a sealing body in a removal opening of a container, wherein in its interior, the guide body comprises two retaining collars axially spaced apart from one another for contact with the tube, in particular retaining collars which are adapted to the outer contour of a rounded rectangular tube.
- 2. A suction lance, comprising: at least one tube and a guide body made from an elastomer material axially displaceable on the tube, a retaining section for a connecting body, the connecting body being for a detachable connection of the suction lance to a removal opening of a container, a conical section axially adjoining the retaining section, the radially largest section whereof lies axially closer to the retaining section than the radially smallest section thereof, wherein the connecting body is fastened to the retaining section of the guide body, wherein the conical section of the guide body, by reason of its material, its radial size and the shape of its external contour, is designed to act in case of use as a sealing body in a removal opening of a container, wherein the guide body comprises two retaining collars axially spaced apart from one another, wherein a first end of the guide body is formed by one of the retaining collars and a second end of the guide body lying axially opposite is formed by a gripping and displacement collar, which is constituted in particular radially larger than the radially largest section of the conical section of the guide body and which comprises a radial recess, in such a way that an accommodation for a welding seam on the tube is formed.
- 3. A suction lance, comprising: at least one tube and a guide body made from an elastomer material axially displaceable on the tube, a retaining section for a connecting body, the connecting body being for a detachable connection of the suction lance to a removal opening of a container, a conical section axially adjoining the retaining section, the radially largest section whereof lies axially closer to the retaining section than the radially smallest section thereof, wherein the connecting body is fastened to the retaining section of the guide body, wherein the conical section of the guide body, by reason of its material, its radial size and the shape of its external contour, is designed to act in case of use as a sealing body in a removal opening of a container, wherein the

guide body comprises a connecting nozzle for a media return flow or for the container venting.

4. A suction lance, comprising: at least one tube and a guide body made from an elastomer material axially displaceable on the tube, a retaining section for a connecting body, the connecting body being for a detachable connection of the suction lance to a removal opening of a container, a conical section axially adjoining the retaining section, the radially largest section whereof lies axially closer to the retaining section than the radially smallest section thereof, wherein the connecting body is fastened to the retaining section of the guide body, wherein the conical section of the guide body, by reason of its material, its radial size and the shape of its external contour, is designed to act in case of use as a sealing body in a removal opening of a container, wherein an end of the guide body is formed by a displacement collar, and wherein a recess is provided in the displacement collar for ventilation.

- 5. A suction lance, comprising: at least one tube and a guide body made from an elastomer material axially displaceable on the tube, a retaining section for a connecting body, the connecting body being for a detachable connection of the suction lance to a removal opening of a container, a conical section axially adjoining the retaining section, the radially largest section whereof lies axially closer to the retaining section than the radially smallest section thereof, wherein the connecting body is fastened to the retaining section of the guide body, wherein the conical section of the guide body, by reason of its material, its radial size and the shape of its external contour, is designed to act in case of use as a sealing body in a removal opening of a container, thereby having a radial sealing function, and whereby the suction lance can be fastened to the container by the guide body itself.
- 6. The suction lance according to claim 5, wherein the retaining section is constituted roughly ushaped in the cross section of the guide body, wherein the base of the U lies radially inwards relative to the radially largest section of the conical section.
- 7. The suction lance according to claim 5, wherein a retaining collar comprises one or more radially inwardly springing sealing lips and/or an axial groove, in particular a venting groove.
- 8. The suction lance according to claim 5, wherein the guide body is formed from one of the materials of the group silicon, EPDM, TPE, TPU, FKM, NBR, rubber, natural rubber, and/or has a Shore-A hardness between 40 and 60, limits included.
- 9. The suction lance according to claim 5, wherein the guide body is constituted as a hollow body, in the interior whereof at least one retaining collar is constituted axially projecting.
- 10. The suction lance according to claim 5, wherein the connecting body is a screw cover, a snap-on cover, a snap-on cap or a disc-like insert.
- 11. The suction lance according to claim 5, wherein the guide body has an elliptical cross-section over the axial length of the conical section.
- 12. The suction lance according to claim 5, wherein the radially largest section of the conical section has a thickening.