US Patent & Trademark Office
Patent Public Search | Text View

United States Patent	12395416
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Nakamura; Azusa et al.

Vehicle-mounted relay device

Abstract

A vehicle-mounted relay device includes a hardware unit implementing functions of first to third layer of OSI model, and a software unit implementing functions of fourth and upper layers of OSI model. The hardware unit includes a first abnormality recording section in which an abnormal frame detected during data relay is recorded, and a first abnormality recording processing section storing, in response to detection of the abnormal frame, the abnormal frame in the first abnormality recording section. The software unit includes a second vehicle information recording section in which vehicle information sequentially transmitted from an end ECU is stored, and a first diagnostic recording processing section, which reads out the abnormal frame from the first abnormality recording section and reads out the vehicle information from the second vehicle information recording section, and stores the readout abnormal frame and vehicle information in a diagnostic information recording section as diagnostic information.

Inventors: **Nakamura; Azusa (Kariya, JP), Sasaki; Takahiro (Kariya, JP), Mizoguchi; Shota (Kariya, JP), Asano; Masayoshi (Kariya, JP)**

Applicant: **DENSO CORPORATION** (Kariya, JP)

Family ID: **1000008766435**

Assignee: **DENSO CORPORATION (Kariya, JP)**

Appl. No.: **18/173521**

Filed: **February 23, 2023**

Prior Publication Data

Document Identifier	Publication Date
US 20230208733 A1	Jun. 29, 2023

Foreign Application Priority Data

JP	2020-158706	Sep. 23, 2020

Related U.S. Application Data

continuation parent-doc WO PCT/JP2021/030758 20210823 PENDING child-doc US 18173521

Publication Classification

Int. Cl.: **H04L43/0823** (20220101); **B60R16/023** (20060101); **H04L67/12** (20220101)

U.S. Cl.:

CPC   **H04L43/0823** (20130101); **B60R16/023** (20130101); **H04L67/12** (20130101);

Field of Classification Search

CPC: G05B (15/02); G07C (5/0825); G07C (5/0808); H01R (31/06); B60R (16/023); H04L (13/00); H04L (12/28); H04L (12/46)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2014/0119199	12/2013	Watanabe	370/242	H04W 28/0231
2018/0131700	12/2017	Ando	N/A	H04L 63/162
2020/0203906	12/2019	Thürmer	N/A	G05B 15/02
2020/0304340	12/2019	Itoda	N/A	N/A
2023/0308256	12/2022	Kitagawa	N/A	H04L 7/0033

Primary Examiner: Roumi; Mahran Y Abu

Attorney, Agent or Firm: Posz Law Group, PLC

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) The present application is a continuation application of International Patent Application No. PCT/JP2021/030758 filed on Aug. 23, 2021 which designated the U.S. and claims the benefit of priority from Japanese Patent Application No. 2020-158706 filed on Sep. 23, 2020. The entire disclosures of all of the above applications are incorporated herein by reference.

TECHNICAL FIELD
(1) The present disclosure relates to a vehicle-mounted relay device.
BACKGROUND
(2) Conventionally, a relay device is used in a vehicle-mounted communication network. The relay device includes multiple ports. When one port receives an input signal, the input signal is transmitted to a destination terminal that is communicably connected to the same relay device. The destination terminal is identified based on destination identification information included in the input signal.
SUMMARY

(3) The present disclosure provides a vehicle-mounted relay device used in a vehicle. The vehicle-mounted relay device includes: a hardware unit performing a hardware operation; and a software unit performing a software operation. The hardware operation implements functions of a first layer to a third layer of an OSI reference model. The software operation implements functions of a fourth layer and upper layers of the OSI reference model. The hardware unit includes a second layer relay section, which implements a relay function in the second layer of the OSI reference model, and a third layer relay section, which implements a relay function in the third layer of the OSI reference model. The software unit includes a vehicle information recording processing section storing vehicle information, which is sequentially transmitted from another vehicle-mounted device, in a vehicle information recording section. The vehicle information recording section is readable by the software unit. The hardware unit includes a first abnormality recording processing section storing, in response to an abnormal frame being detected during a data relay in the second layer relay section or in the third layer relay section, the detected abnormal frame in a first abnormality recording section. The first abnormality recording section is readable by the software unit. The software unit includes a first diagnostic recording processing section. The first diagnostic recording processing section reads out the abnormal frame from the first abnormality recording section and stores the readout abnormal frame together with the vehicle information, which is read out from the vehicle information recording section, in a diagnostic information recording section as diagnostic information. The diagnostic information recording section is readable by the software unit.

Description

BRIEF DESCRIPTION OF DRAWINGS
(1) Objects, features and advantages of the present disclosure will become apparent from the following detailed description made with reference to the accompanying drawings. In the drawings:
(2) FIG. **1** is a diagram showing an example of a schematic configuration of a vehicle-mounted communication system;
(3) FIG. **2** is a diagram showing an example of a schematic configuration of a vehicle-mounted relay device;
(4) FIG. **3** is a diagram showing an example of a schematic configuration of a FPGA;
(5) FIG. **4** is a diagram showing an example of a schematic configuration of a microcomputer;
(6) FIG. **5** is a flowchart showing an exemplary flow of diagnostic record related process executed by the microcomputer;
(7) FIG. **6** is a diagram showing an exemplary case where an abnormal frame recorded in the FPGA cannot be read correctly;
(8) FIG. **7** is a diagram showing an example of a schematic configuration of a vehicle-mounted relay device;
(9) FIG. **8** is a diagram showing an example of a schematic configuration of a FPGA;
(10) FIG. **9** is a diagram showing an example of a schematic configuration of a microcomputer;
(11) FIG. **10** is a flowchart showing an exemplary flow of diagnostic record related process executed by the microcomputer;
(12) FIG. **11** is a diagram showing an example of a schematic configuration of a vehicle-mounted relay device;
(13) FIG. **12** is a diagram showing an example of a schematic configuration of a FPGA;
(14) FIG. **13** is a diagram showing an example of a schematic configuration of a microcomputer;
(15) FIG. **14** is a flowchart showing an exemplary flow of diagnostic record related process executed by the FPGA;
(16) FIG. **15** is a diagram showing an example of a schematic configuration of a vehicle-mounted relay device;

(17) FIG. **16** is a diagram showing an example of a schematic configuration of a memory;

(18) FIG. **17** is a diagram showing an example of a schematic configuration of a relay circuit;

(19) FIG. **18** is a diagram showing an example of a schematic configuration of a CPU;

(20) FIG. **19** is a diagram showing an example of a schematic configuration of a vehicle-mounted relay device;

(21) FIG. **20** is a diagram showing an example of a schematic configuration of a memory;

(22) FIG. **21** is a diagram showing an example of a schematic configuration of a relay circuit;

(23) FIG. **22** is a diagram showing an example of a schematic configuration of a CPU;

(24) FIG. **23** is a diagram showing an example of a schematic configuration of a vehicle-mounted relay device;

(25) FIG. **24** is a diagram showing an example of a schematic configuration of a memory;

(26) FIG. **25** is a diagram showing an example of a schematic configuration of a relay circuit; and

(27) FIG. **26** is a diagram showing an example of a schematic configuration of a CPU.

DETAILED DESCRIPTION

(28) Conventionally, a vehicle-mounted relay device is provided by a vehicle-mounted ECU having a relay function. The vehicle-mounted ECU may include a physical layer and a data link layer, which are defined in OSI reference model, and the physical layer and the data link layer may be configured by ASIC. The vehicle-mounted ECU may include an upper layer, which is configured by a microcomputer, above the physical layer and the data link layer. In this vehicle-mounted ECU, when the relay function is implemented by a network layer, which corresponds to a third layer, the relay function is implemented by the microcomputer in software manner.

(29) When the relay function is implemented by the network layer, the relay function requires a high processing load since the relay is required to be executed across one or more networks. Therefore, even though a high-performance microcomputer is used for the relay function, a communication delay may occur. Due to the high processing load of relay function, large amount of heat is generated by the relay function. In order to solve the above-described difficulties, in a known vehicle-mounted relay device, the functions of first to third layers are executed by a hardware circuit, while the functions of fourth and higher layers are executed by a microcomputer.

(30) The above known art does not assume a configuration in which other functions are also provided by the second and third layers, which are executed by the hardware circuit. Herein, other functions refer to functions other than the relay function. In the known art, when an abnormal frame is detected during relay operation executed by the second and third layers, the abnormal frame can be recorded. However, information sent from another electronic control device (hereinafter referred to as vehicle information) cannot be recorded together with the abnormal frame as diagnostic information (hereinafter also referred to as diag information).

(31) When a diagnostic tool reads an abnormal frame, since the hardware circuit does not have an application layer, a response to the abnormal frame cannot be made. With consideration of this difficulty, when an application layer is installed in the hardware circuit, the hardware circuit needs to be changed every time the specification of application layer is changed. This will increase a development cost.

(32) According to a first aspect of the present disclosure, a vehicle-mounted relay device used in a vehicle includes: a hardware unit performing a hardware operation; and a software unit performing a software operation. The hardware operation implements functions of a first layer to a third layer of an OSI reference model. The software operation implements functions of a fourth layer and upper layers of the OSI reference model. The hardware unit includes a second layer relay section, which implements a relay function in the second layer of the OSI reference model, and a third layer relay section, which implements a relay function in the third layer of the OSI reference model. The software unit includes a vehicle information recording processing section storing vehicle information, which is sequentially transmitted from another vehicle-mounted device, in a vehicle information recording section. The vehicle information recording section is readable by the

software unit. The hardware unit includes a first abnormality recording processing section storing, in response to an abnormal frame being detected during a data relay in the second layer relay section or in the third layer relay section, the detected abnormal frame in a first abnormality recording section. The first abnormality recording section is readable by the software unit. The software unit includes a first diagnostic recording processing section. The first diagnostic recording processing section reads out the abnormal frame from the first abnormality recording section and stores the readout abnormal frame together with the vehicle information, which is read out from the vehicle information recording section, in a diagnostic information recording section as diagnostic information. The diagnostic information recording section is readable by the software unit.

(33) According to the above configuration, the second layer relay section, which implements the relay function in the second layer of the OSI reference model, and the third layer relay section, which implements the relay function in the third layer of the OSI reference model, are provided by the hardware circuit. Thus, the second layer relay section and the third layer relay section are implemented by the operation of hardware circuit. By implementing the second layer relay section and the third layer relay section with the operation of hardware circuit, the processing speed can be increased. Therefore, communication delay is less likely to occur. In addition, heat generation can be suppressed by implementing the relay function with operation executed by the hardware circuit. The software unit needs to execute only the functions of the fourth layer and higher layers above the fourth layer. Thus, a device that has low software support performance can also be used as the device for operating the software unit.

(34) According to the above configuration, the software unit reads out the abnormal frame, which is recorded by the operation of the hardware unit in the first abnormality recording section, and also reads out the vehicle information, which is recorded by the operation of software unit in the vehicle information recording section. Then, the software unit correlates the readout abnormal frame with the readout vehicle information, and stores as the diagnostic information in the diagnostic information recording section. The diagnostic information can be read out by the software unit. As described above, an abnormal frame is detected by the operation of the hardware unit, and the vehicle information is recorded by the operation of the software unit. Thus, the software unit can read out the diagnostic information, which includes the vehicle information transmitted from other electronic control units and the abnormal frame correlated with the vehicle information. Since the software unit executes the functions of fourth layer and upper layer, the function of application layer is executed by the software unit. Therefore, the diagnostic information recorded in the diagnostic information recording section can be read out by the diagnostic tool. Since the diagnostic information can be read without installing the application layer in the hardware unit, it is possible to easily change the specification of the application layer and reduce the development cost.

(35) As a result, an occurrence of communication delay and heat generation can be suppressed. Further, while enabling reading out of diagnostic information about abnormal frame detected during the relay operation executed by the hardware unit, the development cost can be suppressed.

(36) According to a second aspect of the present disclosure, a vehicle-mounted relay device used in a vehicle, includes: a hardware unit operating a hardware; and a software unit operating a software. The hardware unit implements functions of a first layer to a third layer of an OSI reference model. The software unit implements functions of a fourth layer and upper layers of the OSI reference model. The hardware unit includes a second layer relay section, which implements a relay function in the second layer of the OSI reference model, and a third layer relay section, which implements a relay function in the third layer of the OSI reference model. The software unit includes a vehicle information transmission section that transmits, to the hardware unit, vehicle information sequentially transmitted from another vehicle-mounted device. The hardware unit includes a second abnormality recording processing section. The second abnormality recording processing section stores, in response to an abnormal frame being detected during a data relay in the second layer relay section or in the third layer relay section, the abnormal frame in a second abnormality

recording section. The second abnormality recording processing section stores, in the second abnormality recording section, the abnormal frame by correlating the abnormal frame with the vehicle information, which corresponds to a detection time of the abnormal frame and is transmitted from the vehicle information transmission section. The second abnormality recording section is readable by the software unit. The software unit includes a second diagnostic recording processing section. The second diagnostic recording processing section reads out, from the second abnormality recording section, the abnormal frame together with the vehicle information correlated with the abnormal frame, and stores the readout abnormal frame and the readout vehicle information in a diagnostic information recording section as diagnostic information. The diagnostic information recording section is readable by the software unit.

(37) According to the above configuration, the second layer relay section, which implements the relay function in the second layer of the OSI reference model, and the third layer relay section, which implements the relay function in the third layer of the OSI reference model, are provided by the hardware circuit. Thus, the second layer relay section and the third layer relay section are implemented by the operation of hardware circuit. By implementing the second layer relay section and the third layer relay section with the operation of hardware circuit, the processing speed can be increased. Therefore, communication delay is less likely to occur. In addition, heat generation can be suppressed by implementing the relay function with operation executed by the hardware circuit. The software unit needs to execute only the functions of the fourth layer and higher layers above the fourth layer. Thus, a device that has low software support performance can also be used as the device for operating the software unit.

(38) According to the above configuration, the second diagnostic recording processing section of the software unit reads out the abnormal frame detected during data relay in the second layer relay section or in the third layer relay section. The abnormal frame is stored by the operation of the hardware unit. The second diagnostic recording processing section further reads out the vehicle information, which corresponds to the detection time of abnormal frame and is transmitted from the vehicle information transmission section. Then, the second diagnostic recording processing section stores, as the diagnostic information, the readout abnormal frame and the vehicle information in the diagnostic information recording section, which is readable by the software unit. According to the above configuration, the software unit can read out the stored diagnostic information in which the vehicle information transmitted from another electronic control unit at the detection time of abnormal frame is correlated with the abnormal frame. Since the software unit executes the functions of fourth layer and upper layer, the function of application layer is executed by the software unit. Therefore, the diagnostic information recorded in the diagnostic information recording section can be read out by the diagnostic tool. Since the diagnostic information can be read without installing the application layer in the hardware unit, it is possible to easily change the specification of the application layer and reduce the development cost.

(39) As a result, an occurrence of communication delay and heat generation can be suppressed. Further, while enabling reading out of diagnostic information about abnormal frame detected during the relay operation executed by the hardware unit, the development cost can be suppressed.

(40) The following will describe embodiments of the present disclosure with reference to the accompanying drawings. For convenience of description, among multiple embodiments, a configuration having the same function as a configuration shown in the drawing and described in the previous embodiment may be indicated by the same reference symbol, and the description thereof may be omitted. The description of other embodiments may be referred to with respect to the configurations assigned with the same reference symbols.

First Embodiment

Configuration of Vehicle-Mounted Communication System **1**

(41) The following will describe a first embodiment of the present disclosure with reference to the accompanying drawings. First, a vehicle-mounted communication system **1** will be described with

reference to FIG. **1**. The vehicle-mounted communication system **1** is configured according to an in-vehicle Ethernet standard. Ethernet is registered trademark. The vehicle-mounted communication system **1** is mounted on a vehicle. Hereinafter, the vehicle to which the vehicle-mounted communication system **1** is installed is referred to as a subject vehicle.

(42) As shown in FIG. **1**, the vehicle-mounted communication system **1** includes a vehicle-mounted relay device **10**, an end ECU **20**, and a cable **30**. In the example shown in FIG. **1**, the vehicle-mounted communication system **1** includes six end ECUs **20**. This is only an example. The vehicle-mounted communication system **1** may include any number of end ECUs **20**.

(43) The end ECU **20** corresponds to a node, and is connected to the vehicle-mounted relay device **10** via a cable **30**. The node may include an electronic control unit (that is, an ECU), a sensor or the like. Alternatively, another vehicle-mounted relay device **10** may be connected as the node. Each end ECU **20** directly communicates only with the vehicle-mounted relay device **10**. When transmitting a signal to another node, the end ECU **20** includes an address of destination node in the signal. The end ECU **20** outputs this signal to the vehicle-mounted relay device **10** via the cable **30**. For example, the cable **30** may be a twisted pair cable.

(44) The vehicle-mounted relay device **10** divides multiple nodes connected to the vehicle-mounted relay device **10** into two virtual LANs (VLANs) **40** and **50**. The vehicle-mounted relay device **10** may divide multiple nodes connected to the vehicle-mounted relay device **10** into three or more VLANs.

Configuration of Vehicle-Mounted Relay Device **10**

(45) The following will describe a configuration of the vehicle-mounted relay device **10** with reference to FIG. **2**. As shown in FIG. **2**, the vehicle-mounted relay device **10** includes a power supply circuit **100**, a PHY **110**, an FPGA (field-programmable gate array) **120**, and a microcomputer **140**.

(46) The power supply circuit **100** supplies power to the PHY **110**, the FPGA **120**, and the microcomputer **140**. The PHY **110** has multiple ports P. In FIG. **2**, the PHY includes six ports P as an example. Each port P is connected to one end of the cable **30**. The other end of the cable **30** is connected to the end ECU **20**.

(47) The PHY **110** converts the signal supplied from the FPGA **120** into an electric signal that can be transmitted through the cable **30**. The PHY **110** also converts a signal supplied from the end ECU **20** via the cable **30** into a signal that can be processed by the FPGA **120**. The PHY **110** corresponds to the physical layer (that is, the first layer) L**1** in the OSI reference model. In addition to the signal conversion described above, the PHY **110** performs frame encoding, serial-parallel conversion, signal waveform conversion, or the like.

(48) The PHY **110** is a hardware circuit, and includes an analog circuit or the like. The PHY **110** corresponds to a hardware unit. As an example, the PHY **110** is provided by an IC. In FIG. **2**, as an example, the PHY **110** includes multiple ports P. The configuration of PHY is not necessarily limited to this example. Multiple PHYs **110** may be individually configured such that each PHY corresponds to one port P.

(49) The FPGA **120** is a type of integrated electronic circuit, such as a programmable logic device (PLD). The FPGA **120** corresponds to a hardware circuit and a hardware unit. The FPGA **120** is programmed to perform functions of the second layer L**2** and the third layer L**3** in the OSI reference model.

(50) The second layer L**2** is the data link layer. The FPGA **120** relays the communications in the same VLAN **40**, **50** by the function of the second layer L**2**. The third layer L**3** is the network layer. The FPGA **120** relays the communication between different networks by the function of the third layer L**3**.

(51) The microcomputer **140** is a general purpose computer, and includes a processor, a memory, an I/O, and a bus connecting these elements. The microcomputer **140** executes various processes by executing control programs stored in a memory. The microcomputer **140** performs the functions of

the fourth layer L**4**, the fifth layer L**5**, the sixth layer L**6**, and the seventh layer L**7** by executing the programs stored in the memory. That is, the functions of the fourth layer L**4**, the fifth layer L**5**, the sixth layer L**6**, and the seventh layer L**7** are implemented by software processing. The memory referred to here is a non-transitory tangible storage medium, and stores programs and data that can be read by a computer. The non-transitory tangible storage medium may be provided by a semiconductor memory, a magnetic disk, or the like. The microcomputer **140** corresponds to a software unit.

(52) The fourth layer L**4** is the transport layer. The microcomputer **140** executes an inter-program communication and data transfer guarantee by the function of the fourth layer L**4**. The fifth layer L**5** is the session layer. The sixth layer L**6** is the presentation layer. The seventh layer L**7** is the application layer. The microcomputer **140** performs user authentication using the function of the fifth layer L**5**. The microcomputer **140** performs data encoding and data decoding using the function of the sixth layer L**6**. The microcomputer **140** executes user interface using the function of the seventh layer L**7**. The vehicle-mounted relay device **10** having these functions may also be referred to as a switching hub ECU.

Configuration of FPGA **120**

(53) The following will describe an example of a configuration of the FPGA **120** with reference to FIG. **3**. As shown in FIG. **3**, the FPGA **120** includes a second layer relay section **121**, a third layer relay section **122**, a second layer abnormality detection section **123**, a third layer abnormality detection section **124**, a first abnormality recording processing section **125**, and a first abnormality recording section **126** as functional blocks.

(54) The second layer relay section **121** relays the communication within the same VLAN **40**, **50**. The second layer relay section **121** may determine the node that transmits the signal based on the media access control (MAC) address. The function of second layer implemented by the second layer relay section **121** may be referred to as a switch.

(55) The third layer relay section **122** relays the communication between different networks. The third layer relay section **122** may determine the node that transmits the signal based on internet protocol (IP) address. The function of third layer implemented by the third layer relay section **122** may be referred to as a switch.

(56) The second layer abnormality detection section **123** detects an abnormal frame in the signal relayed by the second layer relay section **121**. The abnormal frame referred to here is a frame that has an abnormality and cannot be relayed due to the abnormality. As an example, the second layer abnormality detection section detects an abnormality in the IP addresses and MAC addresses of transmission source and transmission destination. The abnormalities in the IP address and the MAC address refer to abnormalities in which access is not permitted by an access control list (ACL). The second layer abnormality detection section may detect a communication under unspecified protocol as an abnormal frame. The second layer abnormality detection section **123** may be configured to not relay the detected abnormal frame.

(57) The third layer abnormality detection section **124** detects an abnormal frame in the signal relayed by the third layer relay section **122**. As an example, the third layer abnormality detection section detects an abnormality in the IP addresses of transmission source and transmission destination. The third layer abnormality detection section may detect a communication under unspecified protocol as an abnormal frame. The third layer abnormality detection section **124** may be configured to not relay the detected abnormal frame.

(58) When the second layer abnormality detection section **123** detects an abnormal frame, the first abnormality recording processing section **125** records the detected abnormal frame in the first abnormality recording section **126**. When the third layer abnormality detection section **124** detects an abnormal frame, the first abnormality recording processing section **125** records the detected abnormal frame in the first abnormality recording section **126**. For example, a volatile memory may be used as the first abnormality recording section **126**. That is, the first abnormality recording

section **126** is a buffer. As another example, a non-volatile memory may be used as the first abnormality recording section **126**.

(59) The first abnormality recording processing section **125** may accumulate the detected abnormal frame in the first abnormality recording section **126** each time either the second layer abnormality detecting section **123** or the third layer abnormality detecting section **124** detects abnormal data. When recording the detected abnormal frames in the first abnormality recording section **126**, the first abnormality recording processing section **125** may record the abnormal frames in chronological order. A storage capacity of the first abnormality recording section **126** is limited. When the storage capacity becomes insufficient for the records to be stored, the oldest records may be overwritten in order.

(60) The first abnormality recording processing section **125** records the header of the frame excluding the payload as the abnormal frame in the first abnormality recording section **126** in order to prevent the memory of the first abnormality recording section **126** from being overloaded. As another example, the first abnormality recording processing section **125** may record a part of the frame, which includes the payload and the header, in the first abnormality recording section **126** as the abnormal frame.

Configuration of Microcomputer **140**

(61) The following will describe an example of a configuration of the microcomputer **140** with reference to FIG. **4**. As shown in FIG. **4**, the microcomputer **140** includes a vehicle information recording processing section **141**, a vehicle information recording section **142**, a first diagnostic recording processing section **143**, and a diagnostic information recording section **144** as functional blocks.

(62) The vehicle information recording processing section **141** records vehicle-related information (hereinafter referred to as vehicle information) sequentially transmitted from the end ECU **20** in the vehicle information recording section **142**. That is, the vehicle information sequentially transmitted from other devices mounted on the subject vehicle is recorded in the vehicle information recording section **142**. For example, the vehicle information includes time information, an integrated value of section distances on a trip meter, and an integrated value of accumulated travel distances on an odometer. The vehicle information referred to here may be information correlated with diagnostic information, which is information about abnormalities of the vehicle. The vehicle information recording processing section **141** may be configured to record only one latest vehicle information in the vehicle information recording section **142**.

(63) For example, a volatile memory may be used as the vehicle information recording section **142**. That is, the vehicle information recording section **142** is a buffer. As another example, a non-volatile memory may be used as the vehicle information recording section **142**.

(64) The first diagnostic recording processing section **143** periodically reads out the abnormal frame recorded in the first abnormality recording section **126** of the FPGA **120**. Then, the first diagnostic recording processing section **143** records the read-out abnormal frame together with the vehicle information, which is recorded in the vehicle information recording section **142**, as the diagnostic information in the diagnostic information recording section **144**. The abnormal frame may be correlated with the vehicle information by combining the latest information recorded in the first abnormality recording section **126** with the latest information recorded in the vehicle information recording section **142** in order. As an example, a predetermined number of most recent abnormal frames and a predetermined number of most recent vehicle information records may be read out, and the abnormal frames may be combined with the vehicle information records from the most recent one in order. The predetermined number referred to here may be singular or plural. For example, a volatile memory may be used as the diagnostic information recording section **144**.

Process Related to Diagnostic Recording Executed by Microcomputer **140**

(65) The following will describe an example of a process related to diagnostic recording (hereinafter referred to as a diagnostic recording related process) executed by the microcomputer

140 with reference to the flowchart shown in FIG. **5**. For example, the flowchart shown in FIG. **5** may start when a switch (hereinafter referred to as a power switch) for starting an internal combustion engine or a motor generator of the subject vehicle is turned on. That is, the process may start when an ignition (hereinafter referred to as IG) of the subject vehicle is turned on.

(66) In S**1**, when the microcomputer determines that the vehicle information is transmitted from the end ECU **20** (YES in S**1**), the process proceeds to S**2**. When the vehicle information is not transmitted from the end ECU **20** (NO in S**1**), the process proceeds to S**7**. In S**2**, the vehicle information recording processing section **141** records information (hereinafter referred to as vehicle information) sequentially transmitted from the end ECU **20** in the vehicle information recording section **142**. The vehicle information currently recorded in the vehicle information recording section **142** may be overwritten each time new vehicle-related information is recorded, and only the latest vehicle information is kept in the vehicle information recording section **142**.

(67) In S**3**, when the current time is determined as the readout timing of abnormal frame (YES in S**3**), the process proceeds to S**4**. The abnormal frame is readout from the first abnormality recording section **126** of the FPGA **120** at predetermined abnormal readout cycle. When the current time is not the readout timing determined based on the abnormal readout cycle (NO in S**3**), the process proceeds to S**7**. The readout cycle of abnormal frame may be properly set to a predetermined interval.

(68) In S**4**, when an abnormal frame is recorded in the first abnormality recording section **126**, that is, when an abnormal frame exists (YES in S**4**), the process proceeds to S**5**. In S**4**, when an abnormal frame is not recorded in the first abnormality recording section **126**, that is, when an abnormal frame does not exist (NO in S**4**), the process proceeds to S**7**.

(69) In S**5**, the first diagnostic recording processing section **143** reads out the abnormal frame recorded in the first abnormality recording section **126**. In S**6**, the first diagnostic recording processing section **143** stores, as the diagnostic information, the abnormal frame read out in S**5** together with the vehicle information, which is recorded in the vehicle information recording section **142** and corresponds to the readout time of the abnormal frame in S**5**, in the diagnostic information recording section **144**. For example, the first diagnostic recording processing section **143** may store, as the diagnostic information, the abnormal frame read out in S**5** together with the latest vehicle information, which is most recently recorded in the vehicle information recording section **142**, in the diagnostic information recording section **144**. Note that the FPGA **120** may be configured to delete the abnormal frame from the first abnormality recording section **126** after the abnormal frame is read out from the first abnormality recording section **126**.

(70) In S**7**, when the process determines the current time is an end timing of the process related to diagnostic recording (YES in S**7**), the process related to diagnostic recording is ended. For example, the process related to diagnostic recording may be ended when the power switch of vehicle is turned off. More specifically, the process related to diagnostic recording may be ended when the ignition (IG) of vehicle is turned off. When the current time is not the end timing of the process related to diagnostic recording (NO in S**7**), the process returns to S**1** and repeats the subsequent process.

Overview of First Embodiment

(71) In the first embodiment, the vehicle-mounted relay device **10** includes the second layer L**2** and the third layer L**3**, which are configured by the hardware circuit of FPGA **120**. Thus, the second layer relay section **121** and the third layer relay section **122** are also configured by the hardware circuit. By configuring the second layer relay section **121** and the third layer relay section **122** with hardware circuits, the processing speed can be increased. Therefore, communication delay is less likely to occur. In addition, heat generation can be reduced by using the hardware circuit. The microcomputer **140** only needs to execute the process of the fourth layer L**4** and upper layers, it is possible to use a less sophisticated microcomputer **140**.

(72) Further, according to the first embodiment, it is possible to record, in the microcomputer **140**,

the diagnostic information in which the vehicle information, such as time information transmitted from another electronic control unit is correlated with the abnormal frame. Since the microcomputer **140** executes the functions of the fourth layer and upper higher layers, the application layer is mounted in the microcomputer **140**. Therefore, the diagnostic information recorded in the diagnostic information recording section **144** can be read out by the diagnostic tool. The diagnostic information can be read without installing a dedicated application device in the hardware circuit. Thus, development cost can be suppressed. As a result, an occurrence of communication delay and heat generation can be suppressed. Further, while enabling reading out of diagnostic information about abnormal frame detected during the relay operation executed by the hardware circuit, the development cost can be suppressed.

Second Embodiment

(73) In the first embodiment, the microcomputer **140** periodically reads out the abnormal frame recorded in the FPGA **120**. However, the present disclosure is not limited to this configuration. For example, a configuration that solves potential difficulty existing in the first embodiment may be used as a second embodiment. The following will describe a detailed example of the second embodiment with reference to the accompanying drawings.

(74) First, potential difficulty existing in the first embodiment will be described. When the microcomputer **140** periodically reads out the abnormal frame recorded in the FPGA **120**, the microcomputer **140** may fail to read out correct information in some cases. The following will describe a specific example with reference to FIG. **6**. FIG. **6** is a diagram schematically showing abnormal frames recorded in the first abnormality recording section **126** of the FPGA **120**. In the example of FIG. **6**, it is assumed that four abnormal frames can be recorded in the first abnormality recording section **126**.

(75) When the microcomputer **140** periodically reads out the abnormal frame from the FPGA **120**, the readout timing of the abnormal frame from the FPGA **120** may overlap with the detection timing of abnormal frame by the FPGA **120**. In this case, the reading order of the abnormal frames from the first abnormality recording section **126** may become incorrect. The following will describe a specific example with reference to FIG. **6**. When the fifth abnormal frame is detected during reading of the first abnormal frame, the fifth abnormal frame is recorded in the area where the first abnormal frame was recorded, not after the fourth abnormal frame. In this case, instead of the second abnormal frame, fifth abnormal frame read out after readout of the first abnormal frame. The second embodiment can solve this potential difficulty existing in the first embodiment.

(76) The vehicle-mounted communication system **1** of the second embodiment is the same as the vehicle-mounted communication system **1** of the first embodiment, except that a vehicle-mounted relay device **10***a* is included instead of the vehicle-mounted relay device **10** of the first embodiment.

Configuration of Vehicle-Mounted Relay Device **10***a*

(77) The following will describe a configuration of the vehicle-mounted relay device **10***a* with reference to FIG. **7**. As shown in FIG. **7**, the vehicle-mounted relay device **10***a* includes a power supply circuit **100**, a PHY **110**, an FPGA **120***a*, and a microcomputer **140***a*. In the vehicle-related communication system **1** of the second embodiment, the vehicle-mounted relay device **10***a* is the same as the vehicle-mounted relay device **10** of the first embodiment, except that the FPGA **120***a* and the microcomputer **140***a* are provided instead of the FPGA **120** and the microcomputer **140** of the first embodiment.

Configuration of FPGA **120***a*

(78) The following will describe an example of a configuration of the FPGA **120***a* with reference to FIG. **8**. As shown in FIG. **8**, the FPGA **120** includes a second layer relay section **121**, a third layer relay section **122**, a second layer abnormality detection section **123**, a third layer abnormality detection section **124**, a first abnormality recording processing section **125**, a first abnormality recording section **126**, a counter **127**, a count value recording processing section **128**, and a count

value recording section **132** as functional blocks. The FPGA **120***a* of the second embodiment is the same as the FPGA **120** of the first embodiment except that the FPGA **120***a* includes the counter **127**, the count value recording processing section **128**, and the count value recording section **132**.

(79) The counter **127** counts the occurrence number of abnormal frames in either the second layer relay section **121** or the third layer relay section **122**. The counter **127** may be triggered by detection of an abnormal frame by either the second layer abnormality detection section **123** or the third layer abnormality detection section **124**. When being triggered, the counter **127** increases the count value by one. The count value recording processing section **128** records the count value counted by the counter **127** in the count value recording section **132**.

(80) For example, a volatile memory may be used as the count value recording section **132**. As another example, a non-volatile memory may be used as the count value recording section **132**. The count value recording section **132** may be set as a different area from the first abnormality recording processing section **125** in the same memory.

Configuration of Microcomputer **140***a*

(81) The following will describe an example of a configuration of the microcomputer **140***a* with reference to FIG. **9**. As shown in FIG. **9**, the microcomputer **140** includes a vehicle information recording processing section **141***a*, a first vehicle information recording section **142***a*, a first diagnostic recording processing section **143***a*, a diagnostic information recording section **144**, a difference detection section **145**, a count value recording section **146**, and a second vehicle information recording section **147** as functional blocks. The microcomputer **140***a* of the second embodiment is the same as the microcomputer **140** of the first embodiment except that the microcomputer **140***a* includes the vehicle information recording processing section **141***a*, the first vehicle information recording section **142***a*, the second vehicle information recording section **147**, and the first diagnostic recording processing section **143***a*, instead of the vehicle information recording processing section **141**, the vehicle information recording section **142**, and the first diagnostic recording processing section **143**, and further includes the difference detection section **145** and the count value recording section **146**.

(82) The difference detection section **145** periodically reads out the count value recorded in the count value recording section **132** of the FPGA **120**. That is, the occurrence number of abnormal frames recorded in the count value recording section **132** is periodically read out. The term "periodically" used herein may be defined as a predetermined time interval that is properly set. The difference detection section **145** records the count value, which is read out, in the count value recording section **146**. For example, a volatile memory may be used as the count value recording section **146**. As another example, a non-volatile memory may be used as the count value recording section **146**. Each time the count value is read out from the FPGA, the difference detection section **145** detects a difference between the immediately readout count value and the previous readout count value recorded in the count value recording section **146**.

(83) The vehicle information recording processing section **141***a* is the same as the vehicle information recording processing section **141** of the first embodiment, except that a part of the recording process for recording the vehicle information, which is sequentially transmitted from the end ECU **20**, is different from that of the first embodiment. The vehicle information recording processing section **141***a* records, in the first vehicle information recording section **142***a*, only one record of the latest vehicle information among the multiple records of vehicle information sequentially transmitted from the end ECU **20**. That is, only the latest one vehicle information record is left in the first vehicle information recording section **142***a*. For example, a volatile memory may be used as the first vehicle information recording section **142***a*. As another example, a non-volatile memory may be used as the first vehicle information recording section **142***a*.

(84) When the difference detection section **145** detects one or more differences, the vehicle information recording processing section **141***a* records, in the second vehicle information recording section **147**, the vehicle information corresponding to the number of times detected as the

difference. For example, when the difference detection section **145** detects one or more differences, the vehicle information recording processing section **141***a* may store, in the second vehicle information recording section **147**, the corresponding difference number of latest vehicle information records, which are read out from the first vehicle information recording section **142***a*. The second vehicle information recording section **147** corresponds to the vehicle information recording section.

(85) For example, when the detected difference is one record, the latest one record of vehicle information is recorded in the second vehicle information recording section **147**. For example, when the detected difference is three records, three records of same latest vehicle information are recorded in the second vehicle information recording section **147**. As a result, the number of vehicle information records correspond to the occurrence number of detected abnormal frames, and it is possible to record the vehicle information close to the occurrence time of the abnormal frame. Each time the difference detection section **145** detects one or more differences, the vehicle information recording processing section **141***a* may store, in the second vehicle information recording section **147**, the corresponding difference number of latest vehicle information records in chronological order, which are read out from the first vehicle information recording section **142***a*. For example, a volatile memory may be used as the second vehicle information recording section **147**. As another example, a non-volatile memory may be used as the second vehicle information recording section **147**.

(86) By shortening the cycle of periodically detecting the count value by the difference detection section **145**, detection of two or more differences can be reduced, and the vehicle information, which is more close to the detected occurrence time of abnormal frame, can be transmitted from the end ECU **20** and recorded in the second vehicle information recording section **147**. Therefore, the cycle at which the difference detection section **145** periodically detects the count value may be properly set such that multiple times of detection can be performed in average one trip. The one trip referred to here is the period from turn-on of the power switch to turn-off of the power switch.

(87) The first diagnostic recording processing section **143***a* reads out the abnormal frame, which is recorded in the first abnormality recording section **126** of the FPGA **120**, when the second layer relay section **121** and the third layer relay section **122** are not in the data relaying states. As an example, the first diagnostic recording processing section **143***a* may read out the abnormal frame when the power switch of the own vehicle is turned off. More specifically, the first diagnostic recording processing section **143***a* may read out the abnormal frame when the ignition of vehicle is turned off. When the ignition is in off state, the vehicle-mounted relay device **10***a* may receive power from the backup power supply so that the first diagnostic recording processing section **143***a* can execute the abnormal frame readout process.

(88) Then, the first diagnostic recording processing section **143***a* records the readout abnormal frame together with the vehicle information, which is recorded in the second vehicle information recording section **147**, as the diagnostic information in the diagnostic information recording section **144**. The first diagnostic recording processing section **143***a* may correlate the vehicle information recorded in the second vehicle information recording section **147** with the abnormal frame recorded in the first abnormality recording section **126** in chronological order of recording. Then, the vehicle information correlated with the abnormal frame may be recorded in the diagnostic information recording section **144** as the diagnostic information.

Process Related to Diagnostic Recording Executed by Microcomputer **140***a*

(89) The following will describe an example of a diagnostic record related process executed by the microcomputer **140***a* with reference to FIG. **10**. The flowchart of FIG. **10** may be configured to start when the power switch of the vehicle is turned on, similar to the flowchart shown in FIG. **5**. That is, the process may start when the ignition of vehicle is turned on.

(90) In S**21**, when the microcomputer determines that the vehicle information is transmitted from the end ECU **20** (YES in S**21**), the process proceeds to S**22**. When the vehicle information is not

transmitted from the end ECU **20** (NO in S**21**), the process proceeds to S**28**. In S**22**, the vehicle information recording processing section **141** records the vehicle information sequentially transmitted from the end ECU **20** in the first vehicle information recording section **142***a*. The vehicle information currently recorded in the first vehicle information recording section **142***a* may be overwritten each time new vehicle-related information is recorded, and only the latest vehicle information is kept in the first vehicle information recording section **142***a*.

(91) In S**23**, when the current time is determined as the readout timing of count value (YES in S**23**), the process proceeds to S**24**. The count value is readout from the count value recording section **132** of the FPGA **120** at predetermined readout cycle. When the current time is not the readout timing determined based on the readout cycle (NO in S**23**), the process proceeds to S**28**.

(92) In S**24**, the difference detection section **145** reads out the count value, which is recorded in the count value recording section **132**. In S**25**, the difference detection section **145** calculates the difference between the previously readout count value the currently readout count value. In S**26**, when the count value difference calculated in S**25** is equal to or greater than one, that is, when there exists a difference (YES in S**26**), the process proceeds to S**27**. When the count value different calculated in S**25** is zero, that is, when there is no difference (NO in S**26**), the process proceeds to S**28**.

(93) In S**27**, the vehicle information recording processing section **141***a* stores, in the second vehicle information recording section **147**, one or more latest vehicle information records, which are read out from the first vehicle information recording section **142***a*. The number of one or more latest vehicle information records read out from the first vehicle information recording section **142***a* is set corresponding to the count value different detected in S**25**. In S**28**, when the ignition is turned off (YES in S**28**), the process proceeds to S**29**. In S**28**, when the ignition is not turned off (NO in S**28**), the process returns to S**21** and repeats the subsequent process.

(94) In S**29**, when an abnormal frame is recorded in the first abnormality recording section **126** (YES in S**9**), the process proceeds to S**30**. In S**29**, when no abnormal frame is recorded in the first abnormality recording section **126** (NO in S**29**), the diagnostic recording related process is terminated.

(95) In S**30**, the first diagnostic recording processing section **143***a* reads out the abnormal frame recorded in the first abnormality recording section **126**. In S**31**, the first diagnostic recording processing section **143***a* correlates the abnormal frame read out in S**30** with the vehicle information recorded in the second vehicle information recording section **147** in chronological order of recording. Then, the vehicle information correlated with the abnormal frame is recorded in the diagnostic information recording section **144** as the diagnostic information. Then, the process is ended.

(96) After the vehicle information recording processing section **141***a* records the vehicle information as the diagnostic information, the vehicle information may be deleted from the second vehicle information recording section **147**.

Overview of Second Embodiment

(97) According to the second embodiment, the vehicle-mounted relay device **10***a* includes the second layer L**2** and the third layer L**3**, which are configured by the hardware circuit of FPGA **120***a*. Thus, an occurrence of communication delay and heat generation can be suppressed. The microcomputer **140***a* only needs to execute the process of the fourth layer L**4** and upper layers, it is possible to use a less sophisticated microcomputer **140***a*.

(98) Further, according to the second embodiment, it is possible to record, in the microcomputer **140***a*, the diagnostic information in which the vehicle information transmitted from another electronic control unit is correlated with the abnormal frame. As a result, similar to the first embodiment, an occurrence of communication delay and heat generation can be suppressed. Further, while enabling reading out of diagnostic information about abnormal frame detected during the relay operation executed by the hardware circuit, the development cost can be

suppressed.

(99) In addition, according to the second embodiment, the abnormal frame recorded in the FPGA **120***a* is read out while the second layer relay section **121** and the third layer relay section **122** are not in the relaying operation states. Thus, it is possible to prevent the recording order of the abnormal frames from becoming incorrect in the first abnormality recording section **126**. In the second embodiment, the microcomputer records the vehicle information corresponding to the difference in the periodically readout number of occurrences of the abnormal frames in the second vehicle information recording section **147**. Thus, the number of vehicle information records, which correspond to the number of times the abnormal frames are detected, can be recorded, and the vehicle information that is more close to the occurrence time of abnormal frame can be recorded. As described above, although the abnormal frames recorded in the FPGA **120***a* are read out while the relaying operation of the second layer relay section **121** and the third layer relay section **122** are in relay operation stop states, the vehicle information corresponding to each detected abnormal frame can be recorded as the diagnostic information.

Third Embodiment

(100) In the above-described embodiment, the microcomputer **140**, **140***a* correlates the detected abnormal frame with the vehicle information. The present disclosure is not limited to this configuration. For example, instead of the microcomputer, the hardware circuit may correlate the detected abnormal frame with the vehicle information (hereinafter described as third embodiment). The following will describe a detailed example of the third embodiment with reference to the accompanying drawings. The vehicle-mounted communication system **1** of the third embodiment is the same as the vehicle-mounted communication system **1** of the first embodiment, except that a vehicle-mounted relay device **10***b* is included instead of the vehicle-mounted relay device **10** of the first embodiment.

Configuration of Vehicle-Mounted Relay Device **10***b*

(101) The following will describe a configuration of the vehicle-mounted relay device **10***b* with reference to FIG. **11**. As shown in FIG. **11**, the vehicle-mounted relay device **10***b* includes a power supply circuit **100**, a PHY **110**, an FPGA **120***b*, and a microcomputer **140***b*. In the vehicle-related communication system **1** of the third embodiment, the vehicle-mounted relay device **10***b* is the same as the vehicle-mounted relay device **10** of the first embodiment, except that the FPGA **120***b* and the microcomputer **140***b* are provided instead of the FPGA **120** and the microcomputer **140** of the first embodiment.

Configuration of FPGA **120***b*

(102) The following will describe an example of a configuration of the FPGA **120***b* with reference to FIG. **12**. As shown in FIG. **8**, the FPGA **120***b* includes a second layer relay section **121**, a third layer relay section **122**, a second layer abnormality detection section **123**, a third layer abnormality detection section **124**, a second abnormality recording processing section **125***b*, a second abnormality recording section **126***b*, a vehicle information recording processing section **129**, and a vehicle information recording section **130** as functional blocks. The FPGA **120***b* of the third embodiment is the same as the FPGA **120** of the first embodiment except that the FPGA **120***b* includes the second abnormality recording processing section **125***b* and the second abnormality recording section **126***b* instead of the first abnormality recording processing section **125** and the first abnormality recording section **126**, and further includes the vehicle information recording processing section **129** and the vehicle information recording section **130**.

(103) The vehicle information recording processing section **129** records, in the vehicle information recording section **130**, the above-described vehicle information, which is sequentially transmitted from the end ECU **20** via the microcomputer **140***b*. That is, the vehicle information sequentially transmitted from other devices mounted on the subject vehicle via the microcomputer **140***b* are recorded in the vehicle information recording section **130**. The FPGA **120***b* does not directly acquire and record the vehicle information transmitted from the end ECU **20**. This is because, the

microcomputer **140***b* can determine the content of frame as vehicle information by specifying the content of received communication frame while the FPGA has no ability to determine the content of frame as the vehicle information.

(104) For example, a volatile memory may be used as the vehicle information recording section **130**. As another example, a non-volatile memory may be used as the vehicle information recording section **130**. Each time the vehicle information is transmitted from the microcomputer, the vehicle information recording processing section **129** may record only one latest vehicle information in the vehicle information recording section **130** by overwriting the currently recorded vehicle information.

(105) When the second layer abnormality detection section **123** or the third layer abnormality detection section **124** detects an abnormal frame, the second abnormality recording processing section **125***b* records, in the second abnormality recording section **126***b*, the abnormal frame and the vehicle information by correlating one with one another. The vehicle information is transmitted from a vehicle information transmission section **148** of the microcomputer **140***b*, which will be described later, at the detection time of the abnormal frame. As an example, when the second layer abnormality detection section **123** or the third layer abnormality detection section **124** detects an abnormal frame, the detected abnormal frame is correlated with the latest vehicle information recorded in the vehicle information recording section **130**. Then the abnormal frame correlated with the latest vehicle information is recorded in the second abnormality recording section **126***b*. With this configuration, it becomes possible to correlate the vehicle information, which is more close to the detection time of the abnormal frame, with the detected abnormal frame. For example, as the second abnormality recording section **126***b*, a volatile memory or a non-volatile memory may be used.

Configuration of Microcomputer **140***b*

(106) The following will describe an example of a configuration of the microcomputer **140***b* with reference to FIG. **13**. As shown in FIG. **13**, the microcomputer **140***b* includes a vehicle information transmission section **148**, a second diagnostic recording processing section **143***b*, and a diagnostic information recording section **144** as functional blocks. The microcomputer **140***b* of the third embodiment is the same as the microcomputer **140** of the first embodiment except that the microcomputer **140***b* does not include the vehicle information recording processing section **141** and the vehicle information recording section **142**, includes the second diagnostic recording processing section **143***b* instead of the first diagnostic recording processing section **143**, and further includes the vehicle information transmission section **148**.

(107) The vehicle information transmission section **148** transmits, to the FPGA **120***b*, the vehicle information sequentially transmitted from the end ECU **20**.

(108) The second diagnostic recording processing section **143***b* reads out, from the second abnormality recording section **126***b* of the FPGA **120***b*, the abnormal frame and the vehicle information correlated with one another. Then, the second diagnostic recording processing section **143***b* stores the readout abnormal frame and the correlated vehicle information in the diagnostic information recording section **144** as the diagnostic information. The second diagnostic recording processing section **143***b* may periodically read out the abnormal frame and the correlated vehicle information from the FPGA **120***b*, and may read out the abnormal frame and the correlated vehicle information from the FPGA **120** in response to a predetermined event occurrence. One example of the predetermined event is turning off the power switch, such as turning off the ignition.

(109) The second abnormality recording processing section **125***b* of the FPGA **120***b* may delete the abnormal frame and correlated vehicle information from the second abnormality recording section **126***b* after the abnormal frame and the correlated vehicle information are read out by the microcomputer **140***b*.

Process Related to Diagnostic Recording Executed by FPGA **120***b*

(110) The following will describe an example of a diagnostic record related process executed by

the FPGA **120***b* with reference to FIG. **14**. The flowchart of FIG. **14** may be configured to be started when, for example, the power switch is turned on. That is, the process may start when the ignition of vehicle is turned on.

(111) In S**41**, when the FPGA determines that the vehicle information is transmitted from the microcomputer **140***b* (YES in S**41**), the process proceeds to S**42**. When the FPGA determines that vehicle information is not transmitted from the microcomputer **140***b* (NO in S**41**), the process proceeds to S**45**. In S**42**, the vehicle information recording processing section **129** records the vehicle information transmitted from the microcomputer **140***b* in the vehicle information recording section **130**. The vehicle information currently recorded in the vehicle information recording section **130** may be overwritten each time new vehicle-related information is recorded, and only the latest vehicle information is kept in the vehicle information recording section **142**.

(112) In S**43**, when an abnormal frame is detected by the second layer abnormality detection section **123** or the third layer abnormality detection section **124** (YES in S**43**), the process proceeds to S**44**. When the second layer abnormality detection section **123** nor the third layer abnormality detection section **124** does not detect an abnormal frame (NO in S**43**), the process proceeds to S**45**.

(113) In S**44**, the second abnormality recording processing section **125***b* correlates the abnormal frame detected in S**43** with the latest vehicle information recorded in the vehicle information recording section **130**, and records the correlated abnormal frame and vehicle information in the second abnormality recording section **126***b*.

(114) In S**45**, when the process determines the current time is an end timing of the process related to diagnostic recording (YES in S**45**), the process related to diagnostic recording is ended. For example, the process related to diagnostic recording may be ended when the power switch of vehicle is turned off. More specifically, the process related to diagnostic recording may be ended when the ignition of vehicle is turned off. When the current time is not the end timing of the process related to diagnostic recording (NO in S**45**), the process returns to S**41** and repeats the subsequent process.

Overview of Third Embodiment

(115) According to the third embodiment, the vehicle-mounted relay device **10***b* includes the second layer L**2** and the third layer L**3**, which are configured by the hardware circuit of FPGA **120***b*. Thus, an occurrence of communication delay and heat generation can be suppressed. The microcomputer **140***b* only needs to execute the process of the fourth layer L**4** and upper layers, it is possible to use a less sophisticated microcomputer **140***b*.

(116) Further, according to the third embodiment, it is possible to record, in the microcomputer **140***b*, the diagnostic information in which the vehicle information transmitted from another electronic control unit at the detection time of abnormal frame is correlated with the abnormal frame. As a result, an occurrence of communication delay and heat generation can be suppressed. Further, while enabling reading out of diagnostic information about abnormal frame detected during the relay operation executed by the hardware circuit, the development cost can be suppressed.

Fourth Embodiment

(117) In the above-described embodiments, the PHY **110** is provided separately from the FPGA **120**, **120***a*, and **120***b*. The present disclosure is not limited to this configuration. For example, the FPGA **120**, **120***a*, and **120***b* may have the function of PHY **110**.

Fifth Embodiment

(118) The hardware circuit may be provided by a hardware circuit equipped with a processor such as a CPU.

Sixth Embodiment

(119) In the first embodiment, the software unit, which executes the functions of the fourth layer L**4** to the seventh layer L**7**, is configured separately from the hardware circuit. The present disclosure is not limited to this configuration. For example, software unit that executes the

functions of the fourth layer L**4** to the seventh layer L**7** may be mounted on the hardware circuit as one component (hereinafter referred to as sixth embodiment). The following will describe a detailed example of the sixth embodiment with reference to the accompanying drawings.

(120) The vehicle-mounted communication system **1** of the third embodiment is the same as the vehicle-mounted communication system **1** of the first embodiment, except that the vehicle-mounted relay device **10***c* is included instead of the vehicle-mounted relay device **10** of the first embodiment.

Configuration of Vehicle-Mounted Relay Device **10***c*

(121) The following will describe a configuration of the vehicle-mounted relay device **10** with reference to FIG. **15**. As shown in FIG. **15**, the vehicle-mounted relay device **10***c* includes a power supply circuit **100** and a FPGA **200**.

(122) The power supply circuit **100** is similar to the power supply circuit of the first embodiment, and supplies power to the FPGA **200**. The FPGA **200** is a type of integrated electronic circuit, such as a well-known PLD. The FPGA **200** corresponds to a hardware circuit. The FPGA **200** is programmed to perform functions of the first layer L**1** to the third layer L**3** in the OSI reference model.

(123) The FPGA **200** converts, by using the function of the first layer L**1**, a signal supplied from the end ECU **20** via the cable **30** into a signal that can be processed by the FPGA **200**. The FPGA **200** converts, by using the function of the first layer L**1**, the signal supplied from the FPGA **200** into an electric signal that can be transmitted through the cable **30**. The FPGA **200** performs signal conversion, frame coding, serial-parallel conversion, signal waveform conversion, and the like. The FPGA **200** relays the communications in the same VLAN **40**, **50** by the function of the second layer L**2**. The FPGA **200** relays the communication between different networks by the function of the third layer L**3**.

Configuration of FPGA **200**

(124) The following will describe an example of a configuration of the FPGA **200** with reference to FIG. **15**. As shown in FIG. **15**, the FPGA **200** includes a PHY **210**, a memory **220**, a relay circuit **230**, and a CPU **240**.

(125) The PHY **210** may be the same as the PHY **110** of the first embodiment except that the PHY is included in the FPGA **200**. The PHY **210** corresponds to the physical layer (that is, the first layer) L**1** in the OSI reference model. The PHY **210** corresponds to a hardware unit.

(126) The memory **220** is shared by the relay circuit **230** and the CPU **240**, and is also referred to as a common memory. The CPU **240** can read out information, from the memory **220**, information recorded by the relay circuit **230** in the memory and information recorded by the CPU **240** in the memory. For example, the memory **220** may be provided by a volatile memory. As another example, the memory **220** may be provided by a RAM. As another example, the memory **220** may be provided by a register. As another example, the memory **220** may be provided by a non-volatile memory. Hereinafter, a case where a RAM is used as the memory **220** will be described as an example.

(127) The relay circuit **230** can relay a communication. The relay circuit **230** is a logic circuit that performs communication relay function of the second layer L**2** and the third layer L**3** with hardware without using software. The relay circuit **230** may be referred to as a logic circuit designed by a hardware language. The relay circuit **230** corresponds to a hardware unit.

(128) The CPU **240** is a processor that operates software to perform corresponding function of software. The CPU **240** performs various processes by executing control programs. The control program may be configured to be stored in the non-volatile memory of FPGA **200**. The CPU **240** implements the functions of the fourth layer L**4**, the fifth layer L**5**, the sixth layer L**6**, and the seventh layer L**7** by software process. The CPU **240** corresponds to a software unit.

Configuration of Memory **220**

(129) The following will describe an example of a configuration of the memory **220** with reference

to FIG. **16**. As shown in FIG. **16**, the memory **220** includes a first abnormality recording section **221**, a vehicle information recording section **222**, and a diagnostic information recording section **223** as functional blocks.

(130) A first abnormality recording processing section **235**, which will be described later, stores, in the first abnormality recording section **221**, an abnormal frame. A vehicle information recording processing section **241**, which will be described later, stores vehicle information in the vehicle information recording section **222**. A first diagnostic recording processing section **242**, which will be described later, stores, in the diagnostic information recording section **223**, diagnostic information including the vehicle information and the abnormal frame.

Configuration of Relay Circuit **230**

(131) The following will describe an example of a configuration of the relay circuit **230** with reference to FIG. **17**. As shown in FIG. **17**, the relay circuit **230** includes a second layer relay section **231**, a third layer relay section **232**, a second layer abnormality detection section **233**, a third layer abnormality detection section **234**, and a first abnormality recording processing section **235** as functional blocks.

(132) The second layer relay section **231** relays the communication within the same VLAN **40**, **50** in the same manner as the second layer relay section **121** of the first embodiment. The third layer relay section **232** relays the communication between different networks in the same manner as the third layer relay section **122** of the first embodiment. The second layer abnormality detection section **233** detects an abnormal frame in the signal relayed by the second layer relay section **231** in the same manner as the second layer abnormality detection section **123** of the first embodiment. The third layer abnormality detection section **234** detects an abnormal frame in the signal relayed by the third layer relay section **232** in the same manner as the third layer abnormality detection section **124** of the first embodiment.

(133) When the second layer abnormality detection section **233** detects an abnormal frame, the first abnormality recording processing section **235** stores the detected abnormal frame in the first abnormality recording section **221** of the memory **220** similar to the first abnormality recording processing section **125** of the first embodiment. When the third layer abnormality detection section **234** detects an abnormal frame, the first abnormality recording processing section **235** records the detected abnormal frame in the first abnormality recording section **221** of the memory **220** similar to the first abnormality recording processing section **125** of the first embodiment.

Configuration of CPU **240**

(134) The following will describe an example of a configuration of the CPU **240** with reference to FIG. **18**. As shown in FIG. **18**, the CPU **240** includes a vehicle information recording processing section **241** and a first diagnostic recording processing section **242** as functional blocks.

(135) Similar to the vehicle information recording processing section **141** of the first embodiment, the vehicle information recording processing section **241** records, in the vehicle information recording section **222** of the memory **220**, the vehicle information sequentially transmitted from the end ECU **20**. The vehicle information recording processing section **241** may be configured to record only one latest vehicle information in the vehicle information recording section **222**.

(136) The first diagnostic recording processing section **242** periodically reads out the abnormal frame recorded in the first abnormality recording section **221** of the memory **220**. Then, the first diagnostic recording processing section **242** records the readout abnormal frame together with the vehicle information, which is recorded in the vehicle information recording section **222** of the memory **220** at the detection time of the abnormal frame, as the diagnostic information in the diagnostic information recording section **223** of the memory **220**. When correlating the abnormal frame with the vehicle information, the first diagnostic recording processing section **242** may correlate the latest information recorded in the first abnormality recording section **221** with the latest information recorded in the vehicle information recording section **222** in order. As an example, a predetermined number of most recent abnormal frames and a predetermined number of

most recent vehicle information records may be read out, and the abnormal frames may be combined with the vehicle information records from the most recent one in order. The predetermined number referred to here may be singular or plural.

(137) The process related to the diagnostic recording by the CPU **240** may be performed in the same manner as the diagnostic recording related process shown in the flowchart of FIG. **5**.

Overview of Sixth Embodiment

(138) According to the sixth embodiment, the vehicle-mounted relay device **10**c includes the second layer L**2** and the third layer L**3**, which are implemented by the operation of hardware circuit. Thus, an occurrence of communication delay and heat generation can be suppressed. The CPU **240** only needs to execute the process of the fourth layer L**4** and upper layers, it is possible to use a less sophisticated CPU **240**.

(139) According to the configuration of the sixth embodiment, the CPU **240** reads out the abnormal frame, which is recorded in the first abnormality recording section **221** by the relay circuit **230**, and also reads out the vehicle information, which is recorded in the vehicle information recording section **222** by the CPU **240**. Then, the CPU **240** stores correlates the abnormal frame with the vehicle information, and stores, as the diagnostic information, in the diagnostic information recording section **223**. The diagnostic information stored in the diagnostic information recording section **223** can be read out by the CPU **240**. As described above, an abnormal frame is detected by the operation of the relay circuit **230**, which is the hardware unit, and the vehicle information is recorded by the operation of the CPU **240**, which is the software unit. Thus, the CPU **240**, which corresponds to the software unit, can read out the diagnostic information, which includes the vehicle information transmitted from other electronic control units and the abnormal frame correlated with the vehicle information. Since the function of application layer is executed by the CPU **240**, the diagnostic information recorded in the diagnostic information recording section **223** can be read by a diagnostic tool. Since the diagnostic information can be read without installing the application layer in the hardware unit, it is possible to easily change the specification of the application layer and reduce the development cost.

Seventh Embodiment

(140) In the second embodiment, the software unit, which executes the functions of the fourth layer L**4** to the seventh layer L**7**, is configured separately from the hardware circuit. The present disclosure is not limited to this configuration. For example, software unit that executes the functions of the fourth layer L**4** to the seventh layer L**7** may be mounted on the hardware circuit as one component (hereinafter referred to as seventh embodiment). The following will describe a detailed example of the seventh embodiment with reference to the accompanying drawings.

(141) In the sixth embodiment, the CPU **240** periodically reads out the abnormal frame from the memory **220**. In this configuration, the readout timing of the abnormal frame from the memory **220** may overlap with the detection timing of abnormal frame similar to the first embodiment. In this case, the reading order of the abnormal frames from the first abnormality recording section **221** may become incorrect. The seventh embodiment can solve this potential difficulty.

(142) The vehicle-mounted communication system **1**d of the seventh embodiment is the same as the vehicle-mounted communication system **1**a of the second embodiment, except that a vehicle-mounted relay device **10**d is included instead of the vehicle-mounted relay device **10**a of the second embodiment.

Configuration of Vehicle-Mounted Relay Device **10**d

(143) The following will describe a configuration of the vehicle-mounted relay device **10**d with reference to FIG. **19**. As shown in FIG. **19**, the vehicle-mounted relay device **10**d includes a power supply circuit **100** and a FPGA **300**.

(144) The power supply circuit **100** is similar to the power supply circuit of the sixth embodiment, and supplies power to the FPGA **300**. The FPGA **300** is the same as the FPGA **200** of the sixth embodiment except that a part of process is different from that of the sixth embodiment.

Configuration of FPGA **300**

(145) The following will describe an example of a configuration of the FPGA **300** with reference to FIG. **19**. As shown in FIG. **19**, the FPGA **300** includes a PHY **210**, a memory **320**, a relay circuit **330**, and a CPU **340**.

(146) The memory **320** is similar to the memory **220** of the sixth embodiment except that some functional blocks are different from those of the sixth embodiment. The relay circuit **330** and the CPU **340** can read out information, from the memory **320**, information recorded by the relay circuit **330** in the memory and information recorded by the CPU **340** in the memory.

(147) The relay circuit **330** is the same as the relay circuit **230** of the sixth embodiment except that some functional blocks are different from those of the sixth embodiment. The relay circuit **330** is a logic circuit that performs communication relay function of the second layer L**2** and the third layer L**3** with hardware without using software. The relay circuit **330** may be referred to as a logic circuit designed by a hardware language. The relay circuit **330** corresponds to a hardware unit. The CPU **340** is a processor similar to the CPU **240** of the sixth embodiment, except that some functional blocks are different from those of eighth embodiment. The CPU **340** corresponds to a software unit.

Configuration of Memory **320**

(148) The following will describe an example of a configuration of the memory **320** with reference to FIG. **20**. As shown in FIG. **20**, the memory **320** includes a first abnormality recording section **221**, a diagnostic information recording section **223**, a count value recording section **321**, a first vehicle information recording section **322**, and a second vehicle information recording section **323** as functional blocks. The memory **320** of the present embodiment is same as the memory **220** of the sixth embodiment except that the memory **320** further includes the count value recording section **321**, and includes the first vehicle information recording section **322** and the second vehicle information recording section **323** instead of the vehicle information recording section **222**.

(149) A count value recording processing section **332**, which will be described later, counts the number of occurrence times of abnormal frames in either the second layer relay section **231** or the third layer relay section **232** as a count value, and the count value recording section **321** records the count value counted by the count value recording processing section. A vehicle information recording processing section **342**, which will be described later, records, in the first vehicle information recording section **322**, only one record of the latest vehicle information among the multiple records of vehicle information sequentially transmitted from the end ECU **20**. The vehicle information recording processing section **342** reads out, from the first vehicle information recording section **322**, predetermined number of latest vehicle information records, and stores the readout vehicle information records in the second vehicle information recording section **323**. The predetermined number of latest vehicle information records corresponds to the difference value detected by a difference detection section **341**, which will be described later.

Configuration of Relay Circuit **330**

(150) The following will describe an example of a configuration of the relay circuit **330** with reference to FIG. **21**. As shown in FIG. **21**, the relay circuit **330** includes a second layer relay section **231**, a third layer relay section **232**, a second layer abnormality detection section **233**, a third layer abnormality detection section **234**, a first abnormality recording processing section **235**, a counter **331**, and a count value recording processing section **332** as functional blocks. The first abnormality recording processing section **235** of the present embodiment is the same as the first abnormality recording processing section **235** of the sixth embodiment, except that the first abnormality recording processing section **235** of the present embodiment records the abnormal frame in the memory **320**.

(151) Similar to the counter **127** of the second embodiment, the counter **331** counts the occurrence number of abnormal frames in either the second layer relay section **231** or the third layer relay section **232**. The count value recording processing section **332** records the count value counted by the counter **331** in the count value recording section **321** of the memory **320**.

Configuration of CPU **340**

(152) The following will describe an example of a configuration of the CPU **340** with reference to FIG. **22**. As shown in FIG. **22**, the CPU **340** includes a difference detection section **341**, a vehicle information recording processing section **342**, and a first diagnostic recording processing section **343** as functional blocks.

(153) The difference detection section **341** periodically reads out the count value recorded in the count value recording section **321** of the memory **320**. That is, the occurrence number of abnormal frames recorded in the count value recording section **321** is periodically read out. The term "periodically" used herein may be defined as a predetermined time interval that is properly set. The difference detection section **341** records the count value, which is read out, in the count value recording section **321**. Each time the count value is read out, the difference detection section **341** detects a difference between the immediately readout count value and the previous readout count value recorded in the count value recording section **321**.

(154) The vehicle information recording processing section **342** records, in the first vehicle information recording section **322**, only one record of the latest vehicle information among the multiple records of vehicle information sequentially transmitted from the end ECU **20**. That is, only the latest one vehicle information record is left in the first vehicle information recording section **322**.

(155) Similar to the vehicle information recording processing section **141***a* of the second embodiment, when the difference detection section **341** detects one or more differences, the vehicle information recording processing section **342** of the present embodiment records, in the second vehicle information recording section **323**, the vehicle information corresponding to the number of times detected as the difference. The second vehicle information recording section **323** corresponds to the vehicle information recording section. Each time the difference detection section **341** detects one or more differences, the vehicle information recording processing section **342** may store, in the second vehicle information recording section **323**, the corresponding difference number of latest vehicle information records in chronological order, which are read out from the first vehicle information recording section **322**.

(156) Similar to the first diagnostic recording processing section **143***a* of the second embodiment, the first diagnostic recording processing section **343** of the present embodiment reads out the abnormal frame, which is recorded in the first abnormality recording section **221** of the memory **320**, when the second layer relay section **231** and the third layer relay section **232** are not in the data relaying states. Similar to the first diagnostic recording processing section **143***a* of the second embodiment, the first diagnostic recording processing section **343** then records the readout abnormal frame together with the vehicle information, which is read out from the second vehicle information recording section **323**, as the diagnostic information in the diagnostic information recording section **223**.

(157) The process related to the diagnostic recording by the CPU **340** may be performed in the same manner as the diagnostic recording related process shown in the flowchart of FIG. **10**.

Overview of Seventh Embodiment

(158) According to the seventh embodiment, the vehicle-mounted relay device **10***d* includes the second layer L**2** and the third layer L**3**, which are implemented by the operation of hardware circuit. Thus, an occurrence of communication delay and heat generation can be suppressed. The CPU **340** only needs to execute the process of the fourth layer L**4** and upper layers, it is possible to use a less sophisticated CPU **340**.

(159) According to the seventh embodiment, the CPU **340**, which corresponds to the software unit, can read out, by executing a process, the diagnostic information in which the vehicle information transmitted from another electronic control unit is correlated with the abnormal frame. As a result, similar to the first embodiment, an occurrence of communication delay and heat generation can be suppressed. Further, while enabling reading out of diagnostic information about abnormal frame

detected during the relay operation executed by the hardware circuit, the development cost can be suppressed.

(160) In addition, according to the seventh embodiment, the abnormal frame recorded in the memory **220** is read out while the second layer relay section **231** and the third layer relay section **232** are not in the relaying operation states. Thus, when reading out the abnormal frames from the first abnormality recording section **221**, it is possible to prevent the recording order of the abnormal frames from becoming incorrect in the first abnormality recording section **221**. In the seventh embodiment, the microcomputer records the vehicle information corresponding to the difference in the periodically readout number of occurrences of the abnormal frames in the second vehicle information recording section **323**. Thus, the number of vehicle information records, which correspond to the number of times the abnormal frames are detected, can be recorded, and the vehicle information that is more close to the occurrence time of abnormal frame can be recorded. As described above, although the abnormal frames recorded in the memory **220** are read out while the relaying operation of the second layer relay section **231** and the third layer relay section **232** are in relay operation stop states, the vehicle information corresponding to each detected abnormal frame can be recorded as the diagnostic information.

Eighth Embodiment

(161) In the third embodiment, the software unit, which executes the functions of the fourth layer L**4** to the seventh layer L**7**, is configured separately from the hardware circuit. The present disclosure is not limited to this configuration. For example, software unit that executes the functions of the fourth layer L**4** to the seventh layer L**7** may be mounted on the hardware circuit as one component (hereinafter referred to as eighth embodiment). The following will describe a detailed example of the eighth embodiment with reference to the accompanying drawings.

(162) The vehicle-mounted communication system **1**b of the third embodiment is the same as the vehicle-mounted communication system **1**d of the eighth embodiment, except that a vehicle-mounted relay device **10**e is included instead of the vehicle-mounted relay device **10**b of the third embodiment.

Configuration of Vehicle-Mounted Relay Device **10**e

(163) The following will describe a configuration of the vehicle-mounted relay device **10**e with reference to FIG. **23**. As shown in FIG. **23**, the vehicle-mounted relay device **10**e includes a power supply circuit **100** and a FPGA **400**.

(164) The power supply circuit **100** is similar to the power supply circuit of the sixth embodiment, and supplies power to the FPGA **400**. The FPGA **400** is the same as the FPGA **200** of the sixth embodiment except that a part of process is different from that of the sixth embodiment.

Configuration of FPGA **400**

(165) The following will describe an example of a configuration of the FPGA **400** with reference to FIG. **23**. As shown in FIG. **23**, the FPGA **400** includes a PHY **210**, a memory **420**, a relay circuit **430**, and a CPU **440**.

(166) The memory **420** is similar to the memory **220** of the sixth embodiment except that some functional blocks are different from those of the sixth embodiment. The relay circuit **430** and the CPU **440** can read out information, from the memory **420**, information recorded by the relay circuit **430** in the memory and information recorded by the CPU **440** in the memory. The relay circuit **430** is the same as the relay circuit **230** of the sixth embodiment except that some functional blocks are different from those of the sixth embodiment. The relay circuit **430** corresponds to a hardware unit. The CPU **440** is a processor similar to the CPU **240** of the sixth embodiment, except that some functional blocks are different from those of eighth embodiment. The CPU **440** corresponds to a software unit.

Configuration of Memory **420**

(167) The following will describe an example of a configuration of the memory **420** with reference to FIG. **24**. As shown in FIG. **24**, the memory **420** includes a vehicle information recording section

421, a second abnormality recording section **422**, and a diagnostic information recording section **223** as functional blocks. The memory **420** of the present embodiment is same as the memory **220** of the sixth embodiment except that the memory **420** includes the second abnormality recording section **422** instead of the first abnormality recording section **221**, and includes the vehicle information recording section **421** instead of the vehicle information recording section **222**.

(168) A vehicle information transmission section **441**, which will be described later, records, in the vehicle information recording section **421**, only one record of the latest vehicle information among the multiple records of vehicle information sequentially transmitted from the end ECU **20**. A second abnormality recording processing section **431**, which will be described later, stores, in the second abnormality recording section **422**, an abnormal frame and vehicle information correlated with one another. A second diagnostic recording processing section **442**, which will be described later, stores, in the diagnostic information recording section **223**, diagnostic information including the vehicle information and the abnormal frame correlated with one another.

Configuration of Relay Circuit **430**

(169) The following will describe an example of a configuration of the relay circuit **430** with reference to FIG. **25**. As shown in FIG. **25**, the relay circuit **430** includes a second layer relay section **231**, a third layer relay section **232**, a second layer abnormality detection section **233**, a third layer abnormality detection section **234**, and a second abnormality recording processing section **431** as functional blocks.

(170) When the second layer abnormality detection section **233** or the third layer abnormality detection section **234** detects an abnormal frame, the second abnormality recording processing section **431** records, in the second abnormality recording section **422**, the abnormal frame and the vehicle information by correlating one with one another. The vehicle information is transmitted from the vehicle information transmission section **441** of the CPU **440** after the vehicle information is recorded in the vehicle information recording section **421** at the detection time of the abnormal frame. The vehicle information recording section **421** can also read out the vehicle information from the relay circuit **430**, which is a hardware unit. Thus, after the vehicle information is recorded in the vehicle information recording section **421**, the vehicle information transmission section **441** of the CPU **440** can transmit the vehicle information to the relay circuit **430**. For example, the second abnormality recording processing section **431** may store, in the second abnormality recording section **422**, the abnormal frame together with the latest vehicle information in correlated manner. The latest vehicle information is recorded in the vehicle information recording section **421** of the memory **420** by the vehicle information transmission section **441**. With this configuration, it becomes possible to correlate the vehicle information, which is more close to the detection time of the abnormal frame, with the detected abnormal frame.

Configuration of CPU **440**

(171) The following will describe an example of a configuration of the CPU **440** with reference to FIG. **26**. As shown in FIG. **26**, the CPU **440** includes a vehicle information transmission section **441**, a second diagnostic recording processing section **442** as functional blocks.

(172) The vehicle information transmission section **441** records, in the vehicle information recording section **421** of the memory **420**, only one record of the latest vehicle information among the multiple records of vehicle information sequentially transmitted from the end ECU **20**.

(173) The second diagnostic recording processing section **442** reads out the correlated abnormal frame and the vehicle information recorded in the second abnormality recording section **422** of the memory **420**, and stores the readout data in the diagnostic information recording section **223** of the memory **420** as the diagnostic information. After the correlated abnormal frame and the vehicle information are read out by the second diagnostic recording processing section **442**, the correlated abnormal frame and the vehicle information may be deleted from the second abnormality recording section **422**.

(174) The process related to the diagnostic recording by the CPU **440** may be performed in the

same manner as the diagnostic recording related process shown in the flowchart of FIG. **14**.

Overview of Eighth Embodiment

(175) According to the eighth embodiment, the vehicle-mounted relay device **10***e* includes the second layer L**2** and the third layer L**3**, which are implemented by the operation of hardware circuit. Thus, an occurrence of communication delay and heat generation can be suppressed. The CPU **440** only needs to execute the process of the fourth layer L**4** and upper layers, it is possible to use a less sophisticated CPU **440**.

(176) According to the eighth embodiment, the CPU **440**, which corresponds to the software unit, can read out, by executing a process, the diagnostic information in which the vehicle information transmitted from another electronic control unit is correlated with the abnormal frame. As a result, similar to the first embodiment, an occurrence of communication delay and heat generation can be suppressed. Further, while enabling reading out of diagnostic information about abnormal frame detected during the relay operation executed by the hardware circuit, the development cost can be suppressed.

Ninth Embodiment

(177) In the sixth to eighth embodiments described above, the functions of the PHY **210** are provided by the FPGA **200**, **300**, **400**. The present disclosure is not limited to this configuration. For example, the PHY **210** may be provided separately from the FPGA **200**, **300**, **400**.

Tenth Embodiment

(178) In the above-described embodiments, an example of using the FPGA as the hardware circuit is described. The present disclosure is not limited to this configuration. As the hardware circuit, any structure or component other than the FPGA may be used. For example, instead of FPGA, ASIC or the like may be used as the hardware circuit.

Eleventh Embodiment

(179) A hardware circuit having the functions of the first layer L**1** and the second layer L**2** may be configured separately from a hardware circuit having the function of the third layer L**3**.

(180) It should be noted that the present disclosure is not limited to the embodiments described above, and various modifications are possible within the scope indicated in the claims, and embodiments obtained by appropriately combining technical means disclosed in different embodiments are also included in the technical scope of the present disclosure.

Claims

1. A vehicle-mounted relay device used in a vehicle, the vehicle-mounted relay device comprising: a hardware unit performing a hardware operation; and a software unit performing a software operation, wherein the hardware operation implements functions of a first layer to a third layer of an open systems interconnection (OSI) reference model, the software operation implements functions of a fourth layer and upper layers of the OSI reference model, the hardware unit includes a second layer relay section, which implements a relay function in the second layer of the OSI reference model, and a third layer relay section, which implements a relay function in the third layer of the OSI reference model, the software unit includes a vehicle information recording processing section storing vehicle information, which is sequentially transmitted from another vehicle-mounted device, in a vehicle information recording section, the vehicle information recording section is readable by the software unit, the hardware unit includes a first abnormality recording processing section storing, in response to an abnormal frame being detected during a data relay in the second layer relay section or in the third layer relay section, the detected abnormal frame in a first abnormality recording section, the first abnormality recording section is readable by the software unit, the software unit includes a first diagnostic recording processing section, the first diagnostic recording processing section reads out the abnormal frame from the first abnormality recording section and stores the readout abnormal frame together with the vehicle information,

which is read out from the vehicle information recording section, in a diagnostic information recording section as diagnostic information, and the diagnostic information recording section is readable by the software unit.

2. The vehicle-mounted relay device according to claim 1, wherein the first diagnostic recording processing section periodically reads out, from the first abnormality recording section, the abnormal frame, and the first diagnostic recording processing section correlates the readout abnormal frame with the vehicle information, which is recorded in the vehicle information recording section and corresponds to a readout time of the abnormal frame, and then stores the correlated abnormal frame and the vehicle information in the diagnostic information recording section as the diagnostic information.

3. The vehicle-mounted relay device according to claim 1, wherein the hardware unit includes: a counter that counts occurrence times of the abnormal frame in the second layer relay section or in the third layer relay section; and a count value recording processing section recording, in a count value recording section, the occurrence times of the abnormal frame counted by the counter, the count value recording section is readable by the software unit, the software unit includes a difference detection section, the difference detection section periodically reads out, from the count value recording section, the occurrence times of the abnormal frame and detects a difference between a currently readout occurrence times and a previously readout occurrence times, the vehicle information recording processing section stores, in response to the detected difference between the currently readout occurrence times and the previously readout occurrence times being equal to or greater than one, a same record number of the vehicle information as the detected difference in the vehicle information recording section, the vehicle information recording section is readable by the software unit, the first diagnostic recording processing section reads out the abnormal frame from the first abnormality recording section during when the second layer relay section and the third layer relay section are in stop states of data relay, and stores the readout abnormal frame together with the vehicle information, which is read out from the vehicle information recording section, in the diagnostic information recording section as the diagnostic information, and the diagnostic information recording section is readable by the software unit.

4. The vehicle-mounted relay device according to claim 1, wherein the hardware unit is a hardware circuit, the software unit is a microcomputer, the hardware circuit executes the functions of the first layer to the third layer of the OSI reference model, and the microcomputer executes the functions of the fourth layer and upper layers of the OSI reference model.

5. The vehicle-mounted relay device according to claim 4, wherein the microcomputer includes the vehicle information recording section and the diagnostic information recording section, and the hardware circuit includes the first abnormality recording section.

6. The vehicle-mounted relay device according to claim 1, wherein the hardware unit is a logic circuit that performs the hardware operation in a hardware circuit, the software unit is a processor mounted on the hardware circuit, the functions of the first layer to the third layer of the OSI reference model are implemented by the logic circuit, and the functions of the fourth layer and upper layers are implemented by the processor.

7. The vehicle-mounted relay device according to claim 6, further comprising a memory mounted on the hardware circuit and shared by the logic circuit and the processor, wherein the memory includes the vehicle information recording section, the diagnostic information recording section, and the first abnormality recording section.

8. A vehicle-mounted relay device used in a vehicle, the vehicle-mounted relay device comprising: a hardware unit operating a hardware; and a software unit operating a software, wherein the hardware unit implements functions of a first layer to a third layer of an OSI reference model, the software unit implements functions of a fourth layer and upper layers of the OSI reference model, the hardware unit includes a second layer relay section, which implements a relay function in the second layer of the OSI reference model, and a third layer relay section, which implements a relay

function in the third layer of the OSI reference model, the software unit includes a vehicle information transmission section that transmits, to the hardware unit, vehicle information sequentially transmitted from another vehicle-mounted device, the hardware unit includes a second abnormality recording processing section, the second abnormality recording processing section stores, in response to an abnormal frame being detected during a data relay in the second layer relay section or in the third layer relay section, the abnormal frame in a second abnormality recording section, the second abnormality recording processing section stores, in the second abnormality recording section, the abnormal frame by correlating the abnormal frame with the vehicle information, which corresponds to a detection time of the abnormal frame and is transmitted from the vehicle information transmission section, the second abnormality recording section is readable by the software unit, the software unit includes a second diagnostic recording processing section, the second diagnostic recording processing section reads out, from the second abnormality recording section, the abnormal frame together with the vehicle information correlated with the abnormal frame, and stores the readout abnormal frame and the readout vehicle information in a diagnostic information recording section as diagnostic information, and the diagnostic information recording section is readable by the software unit.

9. The vehicle-mounted relay device according to claim 8, wherein the hardware unit is a hardware circuit, the software unit is a microcomputer, the hardware circuit executes the functions of the first layer to the third layer of the OSI reference model, and the microcomputer executes the functions of the fourth layer and upper layers of the OSI reference model.

10. The vehicle-mounted relay device according to claim 9, wherein the microcomputer includes the diagnostic information recording section, and the hardware circuit includes the second abnormality recording section.

11. The vehicle-mounted relay device according to claim 8, wherein the hardware unit is a logic circuit that operates the hardware in a hardware circuit, the software unit is a processor mounted on the hardware circuit, the functions of the first layer to the third layer of the OSI reference model are implemented by the logic circuit, and the functions of the fourth layer and upper layers are implemented by the processor.

12. The vehicle-mounted relay device according to claim 11, further comprising a memory mounted on the hardware circuit and shared by the logic circuit and the processor, wherein the memory includes a vehicle information recording section, the diagnostic information recording section, and the second abnormality recording section, and the vehicle information recording section records the vehicle information transmitted from the vehicle information transmission section.