

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250255292

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

FLEMING; Ian Yuta Oki et al.

RODENT TRAPPING APPARATUS

Abstract

Embodiments of the present invention disclose a rodent trapping apparatus. The rodent trapping apparatus includes a lid including a top surface, wherein the lid comprises a longitudinal slot having two opposing longitudinal edges. Further, the rodent trapping apparatus includes two sidewalls provided on the top surface, with one sidewall along each longitudinal edge of the longitudinal slot. The rodent trapping apparatus further includes a transverse connecting member connecting the two sidewalls thereby forming a tunnel over the longitudinal slot, a proximal end of the tunnel being located at the edge of the lid. The rodent trapping apparatus further includes a bait compartment located at a distal end of the tunnel. The rodent trapping apparatus includes a swivel platform located within the longitudinal slot. The swivel platform is configured to swivel about a pivot axis, the pivot axis being located between the distal end and the proximal end of the tunnel.

Inventors: FLEMING; Ian Yuta Oki (Los Gatos, CA), ROGERS; Jay N. (Los Gatos, CA)

Applicant: e-Thrive LLC (Los Gatos, CA)

Family ID: 96661757

Appl. No.: 18/436964

Filed: February 08, 2024

Publication Classification

Int. Cl.: A01M23/06 (20060101)

U.S. Cl.:

CPC A01M23/06 (20130101);

Background/Summary

TECHNICAL FIELD

[0001] The present invention generally relates to animal traps and, more particularly, the present invention relates to traps for catching rodents that are comparatively larger in size, such as full-grown rats.

BACKGROUND ART

[0002] In general, bucket lid traps function by placing bait at an end of a tunnel. A mouse walks up the ladder and moves toward the bait. The weight of the mouse triggers a swivel platform to fall forward. As the swivel platform rotates, the mouse has nothing to support or hold onto, because it is inside the tunnel. As the swivel platform moves from being horizontal to angled downwards, the mouse slides down the platform. The further it slides in the horizontal direction, the further the weight of the mouse is from the pivot, resulting in an increasing moment on the falling side, and accelerated fall. The mouse falls into the bucket. The platform resets itself.

[0003] U.S. Pat. No. 11,166,448B2 issued to RICKEY MOUSE COMPANY LLC discloses an animal trap apparatus having a collection of individual components mounted onto a rim of a bucket and including a plank having a bait receiving end and a mounting end, with a fulcrum feature therebetween. In use, the plank is configured to pivot about the fulcrum feature in a forward direction when an animal approaches the bait receiving end thereby placing the animal trap apparatus in a tripped condition whereby the bait receiving extends downwardly toward the closed bottom of the bucket and the animal falls into the cavity.

[0004] Such traps work very well for mice. However, when it comes to rats or larger rodents, the rats or larger rodents can hold on to the edge of the entrance of the tunnel, reach for the bait in the tunnel, and acquire the bait without falling into the bucket. This is because rats are larger than mice, and tend to be more agile and skittish or cautious in nature.

[0005] Therefore, there exists a technological need for an apparatus that overcomes the disadvantages and limitations associated with the prior art and provides a more satisfactory solution.

SUMMARY OF THE INVENTION

[0006] According to an aspect of the present invention, there is provided a rodent trapping apparatus for trapping rodents. The rodent trapping apparatus includes a lid configured to be disposed on a bucket, the lid including a top surface, wherein the lid comprises a longitudinal slot having two opposing longitudinal edges. Further, the rodent trapping apparatus includes two sidewalls provided on the top surface, with one sidewall along each longitudinal edge of the longitudinal slot, wherein the two sidewalls extend up to an edge of the lid. The rodent trapping apparatus further includes a transverse connecting member connecting the two sidewalls thereby forming a tunnel over the longitudinal slot, a proximal end of the tunnel being located at the edge of the lid due to the two sidewalls extending up to the edge of the lid. The rodent trapping apparatus further includes a bait compartment located at a distal end of the tunnel, the distal end of the tunnel being formed by a distal connecting portion of the transverse connecting member and two distal segments of the two sidewalls. The rodent trapping apparatus also includes a swivel platform located within and along the longitudinal slot, wherein the swivel platform is configured to swivel about a pivot axis, wherein the pivot axis is located between the distal end and the proximal end of the tunnel.

[0007] In one embodiment of the invention, the bait compartment is disposed at a distance from the pivot axis, wherein the distance between the bait compartment and the pivot axis lies in the range of 3 to 12 inches.

[0008] In one embodiment of the invention, the swivel platform is inclined at an angle with respect to the horizontal, the angle of incline of the swivel platform, with respect to the horizontal lies in the range of 0 to 45 degrees.

[0009] In one embodiment of the invention, the proximal end of the tunnel is disposed at a distance

from the pivot axis lies in the range of 3 to 10 inches.

[0010] In one embodiment of the invention, the bait compartment includes a cover and a material of the cover is stainless steel.

[0011] In one embodiment of the invention, the rodent trapping apparatus includes at least one first securing member and at least one second securing member. The first securing member is mounted to the swivel platform and adapted to disable movement of the swivel platform during a disabled state of the rodent trapping apparatus. The second securing member mounted to the cover and the bucket and adapted to lock the cover with the bucket, during an enabled state of the rodent trapping apparatus.

[0012] In one embodiment of the invention, the rodent trapping apparatus further includes a ramp configured to be provided between the ground and the top surface of the lid, wherein the ramp connects the ground level with the top surface of the lid at the proximal end of the tunnel.

[0013] In one embodiment of the invention, the transverse connecting member further includes an inclined connecting portion connecting the two sidewalls and providing an inclined section to the tunnel.

[0014] In one embodiment of the invention, the bucket is a five-gallon bucket and the lid includes an overhang portion that extends beyond the edge of the bucket.

[0015] In one embodiment of the invention, the lid comprises a portion extending downwards to a predetermined depth to create a rim structure, wherein in use, the rim structure is adapted to run along an inner surface of a peripheral wall of the bucket, while maintaining a minimum predetermined distance from the inner surface.

[0016] In one embodiment of the invention, the lid, the two sidewalls, the transverse connecting member, the bait compartment, and the swivel platform are modular units and are connected to form the rodent trapping apparatus using one or more securing members.

[0017] In one embodiment of the invention, the swivel platform includes a first portion positioned below the distal end of the tunnel. The first portion includes the one or more securing members. The one or more securing members have one or more magnets of varying magnetic strength, adapted to increase a distance between the pivot axis and center of gravity of the rodent.

[0018] In one embodiment of the invention, the swivel platform includes a second portion positioned below the distal end of the tunnel. The second portion includes a loading element configured to reset the swivel platform after the rodent is trapped inside the bucket.

[0019] According to another aspect of the invention, there is provided a rodent trapping apparatus for trapping rodents. The rodent trapping apparatus includes a lid configured to be disposed on a bucket, the lid including a top surface, wherein the lid comprises a longitudinal slot having two opposing longitudinal edges. Further, the rodent trapping apparatus includes two sidewalls provided on the top surface, with one sidewall along each longitudinal edge of the longitudinal slot, wherein the two sidewalls extend up to an edge of the lid. The rodent trapping apparatus further includes a transverse connecting member connecting the two sidewalls thereby forming a tunnel over the longitudinal slot, a proximal end of the tunnel being located at the edge of the lid due to the two sidewalls extending up to the edge of the lid. The rodent trapping apparatus further includes a bait compartment located at a distal end of the tunnel, the distal end of the tunnel being formed by a distal connecting portion of the transverse connecting member and two distal segments of the two sidewalls. The rodent trapping apparatus also includes a swivel platform located within and along the longitudinal slot, wherein the swivel platform is configured to swivel about a pivot axis, wherein the pivot axis is located between the distal end and the proximal end of the tunnel. The proximal end of the tunnel comprises one or more securing members for connecting the swivel platform with the lid, the one or more securing members are one or more magnets of varying magnetic strength adapted to increase a distance between the pivot axis and center of gravity of the rodent.

[0020] According to another aspect of the present invention, there is provided a rodent trapping

apparatus for trapping rodents. The rodent trapping apparatus includes a lid configured to be disposed on a bucket, the lid including a top surface, wherein the lid comprises a longitudinal slot having two opposing longitudinal edges. Further, the rodent trapping apparatus includes two sidewalls provided on the top surface, with one sidewall along each longitudinal edge of the longitudinal slot, wherein the two sidewalls extend up to an edge of the lid. The rodent trapping apparatus further includes a transverse connecting member connecting the two sidewalls thereby forming a tunnel over the longitudinal slot, a proximal end of the tunnel being located at the edge of the lid due to the two sidewalls extending up to the edge of the lid. The rodent trapping apparatus further includes a bait compartment located at a distal end of the tunnel, the distal end of the tunnel being formed by a distal connecting portion of the transverse connecting member and two distal segments of the two sidewalls. The rodent trapping apparatus also includes a swivel platform located within and along the longitudinal slot, wherein the swivel platform is configured to swivel about a pivot axis, wherein the pivot axis is located between the distal end and the proximal end of the tunnel. The lid, the two sidewalls, the transverse connecting member, the bait compartment, and the swivel platform are modular units and are connected to form the rodent trapping apparatus using one or more securing members.

Description

BRIEF DESCRIPTION OF THE ACCOMPANYING DRAWINGS

[0021] The following detailed description of illustrative embodiments is better understood when read in conjunction with the appended drawings. To illustrate the present disclosure, exemplary constructions of the disclosure are shown in the drawings. However, the present disclosure is not limited to a specific device, or a tool and instrumentalities disclosed herein. Moreover, those in the art will understand that the drawings are not to scale.

[0022] FIG. 1A illustrates a side view of a rodent trapping apparatus installed with a bucket, for trapping rodents, in accordance with an embodiment of the present invention;

[0023] FIG. 1B illustrates a bottom view of the rodent trapping apparatus of FIG. 1A;

[0024] FIG. 2A illustrates a side perspective view of the rodent trapping apparatus for trapping rodents, in accordance with an embodiment of the present invention;

[0025] FIG. 2B illustrates a front perspective view of the rodent trapping apparatus of FIG. 2A;

[0026] FIG. 3 illustrates a left sectional view of the rodent trapping apparatus, in accordance with an embodiment of the present invention;

[0027] FIG. 4 illustrates a left sectional view of the rodent trapping apparatus with a rodent reaching out to the bait compartment, in accordance with an embodiment of the present invention;

[0028] FIG. 5 illustrates a left sectional view of the rodent trapping apparatus with a rodent reaching out to the bait compartment, in accordance with another embodiment of the present invention;

[0029] FIG. 6A illustrates a partial perspective view of the rodent trapping apparatus with the bucket, in accordance with another embodiment of the present invention;

[0030] FIG. 6B illustrates a partial sectional view of the rodent trapping apparatus of FIG. 6A, in accordance with another embodiment of the present invention;

[0031] FIG. 7 illustrates a left sectional view of the rodent trapping apparatus of a modular design, in accordance with another embodiment of the present invention;

[0032] FIG. 8 illustrates a left sectional view of a lid and a swivel platform of the rodent trapping apparatus of FIG. 7 connected using one or more securing members, in accordance with another embodiment of the present invention;

[0033] FIG. 9 illustrates a left sectional view of the rodent trapping apparatus of FIG. 7 with at least one first securing member and at least one second securing member, for enabling and

disabling the rodent trapping apparatus, in accordance with an embodiment of the present invention;

[0034] FIG. **10A** illustrates a left sectional view of the second securing structure for locking a cover of the bait compartment of the rodent trapping apparatus of FIG. **9**, in accordance with an embodiment of the present invention; and

[0035] FIG. **10B** illustrates a left sectional view of the first securing structure, for enabling and disabling the rodent trapping apparatus of FIG. **9**, in accordance with an embodiment of the present invention.

DETAILED DESCRIPTION

[0036] In the following description, for purposes of explanation, numerous specific details are set forth in order to provide a thorough understanding of the present disclosure. It will be apparent, however, to one skilled in the art that the present disclosure can be practiced without these specific details. Descriptions of well-known components and processing techniques are omitted to not unnecessarily obscure the embodiments herein. The examples used herein are intended merely to facilitate an understanding of ways in which the embodiments herein may be practiced and to further enable those of skill in the art to practice the embodiments herein. Accordingly, the examples should not be construed as limiting the scope of the embodiments herein.

[0037] Reference in this specification to “one embodiment” or “an embodiment” means that a particular feature, structure, or characteristic described in connection with the embodiment is included in at least one embodiment of the present disclosure. The appearances of the phrase “in an embodiment” in various places in the specification are not necessarily all referring to the same embodiment, nor are separate or alternative embodiments mutually exclusive of other embodiments. Moreover, various features are described which may be exhibited by some embodiments and not by others. Similarly, various requirements are described which may be requirements for some embodiments but not for other embodiments.

[0038] Moreover, although the following description contains many specifics for the purposes of illustration, anyone skilled in the art will appreciate that many variations and/or alterations to said details are within the scope of the present disclosure. Similarly, although many of the features of the present disclosure are described in terms of each other, or in conjunction with each other, one skilled in the art will appreciate that many of these features can be provided independently of other features. Accordingly, this description of the present disclosure is set forth without any loss of generality to, and without imposing limitations upon, the present disclosure.

[0039] Various embodiments of the present invention provide a rodent trapping apparatus for trapping rodents that is suitable for catching large rodents. In that regard, a lid configured to be disposed on a bucket is provided. A longitudinal slot has been provided in the lid and a swivel platform has been disposed within and along the longitudinal slot. The swivel platform is configured to swivel about a pivot axis. Further, a tunnel has been provided over the longitudinal slot in a manner that a distal end of the tunnel includes a bait compartment for receiving bait for the rodents. Moreover, the tunnel has been so designed that the pivot axis lies between the distal end and a proximal end of the tunnel. To further make the design of the rodent trapping apparatus more effective, the swivel platform has been made inclined with respect to the horizontal. The lengths of the tunnel and the swivel platform have been selected so that the distance between the bait compartment and the pivot axis is greater than the distance between the nose and center of gravity of the rodent, and the distance between the pivot axis and the proximal end of the tunnel is greater than the distance between hind legs stretched out and the center of gravity of the rodent.

[0040] Various example embodiments of the present invention are described hereinafter with reference to FIG. **1A-1B** to FIG. **5**.

[0041] FIG. **1A** illustrates a side view of a rodent trapping apparatus **100** installed with a bucket **150**, for trapping rodents, in accordance with an embodiment of the present invention. FIG. **1B** illustrates a bottom view of the rodent trapping apparatus of FIG. **1A**. Referring to FIGS. **1A** and

1B, a lid **102** is configured to be disposed onto a bucket **150**. The lid **102** may be made up of a polymer material such as Polyvinyl Chloride (PVC), High-Density Polyethylene (HDPE), Low-Density Polyethylene (LDPE), Acrylonitrile Butadiene Styrene (ABS) and the like. The lid **102** may be disposed of on top of the bucket **150**, along the rim of the bucket **150** using snap-fit fasteners. In several embodiments of the invention, the bucket **150** is a five-gallon bucket. The advantage of using a five-gallon bucket as the bucket **150** is that five-gallon buckets are readily available in the market at low costs through several brands such as, but not limited to, Lowes, Ace Hardware, and Home Depot, etc. In the embodiments, where the bucket **150** is the five-gallon bucket, the lid **102** extends beyond the outer perimeter of the bucket **150** forming an overhang portion **115** that extends beyond the edge of the bucket **150**. A five-gallon bucket generally has a diameter in the range of 11.8 to 12 inches. A standard circular lid for the five-gallon bucket would not allow the rodent trapping apparatus **100** to assume relatively larger dimensions required for trapping larger rodents such as large rats. The overhang portion **115** increases the overall size of the lid and allows several components, such as a swivel platform and a tunnel (See FIG. 2), of the rodent trapping apparatus **100** to assume larger dimensions that would allow the trapping of relatively larger rodents. The overhang portion **115** allows several components of the rodent trapping apparatus **100** to assume larger dimensions that would allow the trapping of relatively larger rodents. In several alternate embodiments of the invention, the size of the bucket **150** may be selected from a group of sizes consisting of twenty gallons, thirty-two gallons, and forty-four gallons. In the alternative embodiments, where the bucket **150** assumes relatively larger sizes, the lid **102** may not extend beyond the edge of the bucket **150**, since the larger sizes of the bucket **150** would be adequate to incorporate the larger dimensions of the rodent trapping apparatus **100** that may be required to trap relatively larger rodents. The lid **102** includes a top surface **104**. The lid **102** also includes a longitudinal slot **106**. In several embodiments, the longitudinal slot **106** may be provided along the diameter of the lid **102**. In several alternate embodiments, the longitudinal slot **106** may be provided parallel to the diameter of the lid **102** and may be shorter in length compared to the diameter of the lid **102**.

[0042] The longitudinal slot **106** has two opposing longitudinal edges **108** and two transverse edges **107**. In several embodiments, the longitudinal slot **106** may be rectangular in shape. In that regard, the two opposing longitudinal edges **108** may be parallel to each other. In several alternate embodiments, the longitudinal slot **106** may not be rectangular and the two opposing longitudinal edges **108** may be convergent or divergent in nature. In several embodiments of the invention, the two opposing longitudinal edges **108** and thus the longitudinal slot **106** may be inclined with respect to the horizontal. Two sidewalls **114** have been provided on the top surface **104**. One sidewall **114** has been provided along each one of the two opposing longitudinal edges **108**. Each one of the two sidewalls **114** includes a distal segment **116**. A swivel platform **110** has been disposed of within and along the longitudinal slot **106**. The swivel platform **110** has been balanced on two pivot points **109** provided on the two opposing longitudinal edges **108**. Each longitudinal edge **108** has one pivot point **109**. A pivot axis **112** connects the two pivot points **109**. The swivel platform **110** is configured to swivel about the pivot axis **112**.

[0043] FIG. 2A illustrates a side perspective view of the rodent trapping apparatus **100** for trapping rodents, in accordance with an embodiment of the present invention. FIG. 2B illustrates a front perspective view of the rodent trapping apparatus of FIG. 2A. In reference to FIGS. 2A and 2B, a transverse connecting member **210** connects the two sidewalls **114**. The transverse connecting member **210** and the two sidewalls **114** together form a tunnel **220** over the longitudinal slot **106** and the swivel platform **110**. The transverse connecting member **210** has a distal connecting portion **212**. The distal connecting portion **212** connects the two distal segments **116** of the two sidewalls **114** at a distal end **222** of the tunnel **220**. The tunnel **220** also has a proximal end **224** at the mouth of the tunnel **220**. Moreover, the two sidewalls **114** and consequently the tunnel **220** extend up to the edge of the lid **102**. In that manner, the proximal end of the tunnel **220** is located at the edge of

the lid **102** due to the two sidewalls **114c** extending up to the edge of the lid **102**.

[0044] Extending the tunnel **220** up to the edge of the lid **102** ensures that the rodents are not able to circumvent the tunnel **220** as they climb up to the lid **102** using a ramp **230**. It also prevents the rodents from chewing their way through to the bait from other parts of the rodent trapping apparatus **100**. The transverse connecting member **210** also has an inclined connecting portion **214**. The inclined connecting portion **214** along with the two sidewalls **114** provide the tunnel **220** its characteristic inclined shape. The ramp **230** is configured to be provided between the ground level and the top surface **104** of the lid **102**. The ramp **230** connects the ground level with the top surface **104** of the lid **102** at the proximal end **224** of the tunnel **220**. The connection of the ramp **230** at the proximal end **224** of the tunnel **220** forces the rodents directly into the tunnel **220**, without allowing them to circumvent the tunnel **220** as the rodents climb up the ramp **230**. The ramp **230** of the present invention has been made strong and broad enough to support large rodents as they climb from the level ground to the top surface **104** of the lid **102**.

[0045] FIG. **3** illustrates a left sectional view of the rodent trapping apparatus **100**, in accordance with an embodiment of the present invention. A bait compartment **310** is located at the distal end **222** of the tunnel **220**. The bait compartment **310** has the function of receiving bait to lure the rodents into the tunnel **220**. The bait compartment **310** includes a cover **312** for direct access to the bait compartment **310** without lifting the lid **102** from the bucket **150**. The material of the cover **312** of the bait compartment **310** is stainless steel. In several embodiments of the invention, the distal connecting portion **212** of the transverse connecting member **210** and the two distal segments **116** of the two sidewalls **114** are also made from stainless steel. In several alternate embodiments, the entire transverse connecting member **210** is made up of stainless steel. Using stainless steel as a material ensures that the rodents are not able to chew through the polymeric material surrounding the bait compartment **310**, since the bait compartment **310** is located at the distal end **222** of the tunnel **220**. FIG. **3** also illustrates that the pivot axis **112** of the swivel platform **110** is disposed between the distal end **222** and the proximal end **224** of the tunnel **220**. Locating the pivot axis **112** between the distal end **222** and the proximal end **224** ensures that rodents lured into the rodent trapping apparatus **100** are not able to reach backward and hold onto the entrance of the tunnel **220** as the swivel platform **110** swivels or pivots about the pivot axis **112**.

[0046] FIG. **4** illustrates a left sectional view of the rodent trapping apparatus **100** with a rodent reaching out to the bait compartment **310**, in accordance with an embodiment of the present invention. To ensure that the rodent is not able to balance itself on the swivel platform **110**, the distance (a) between the bait compartment **310** and the pivot axis **112** should be greater than the distance (b) between the nose of a target rodent and its center of gravity. An average large rodent measures 10 inches. Assuming that the shape of the tunnel **220** and the location of the bait compartment **310** forces the rodent into crawling thereby shifting the center of gravity closer to the middle portion of the rodent, (a) should be greater than 5 inches. Therefore, in several embodiments of the invention, the distance (a) between the bait compartment **310** and the pivot axis **112** has been designed to be greater than 5 inches, preferably lie in the range of 6-12 inches, and most preferably lie in the range of 7 to 10 inches.

[0047] Also, it is to be noted that larger rodents such as rats are very agile and can balance their center of gravity over the pivot axis **112** when the swivel platform **110** is horizontal. Moreover, in some cases, larger rodents can reverse the rotation motion of the swivel platform **110** much more easily, if the swivel platform **110** is horizontally oriented. To ensure that the larger rodents are not able to balance themselves over the pivot axis **112**, or reverse the rotation motion of the swivel platform **110**, the swivel platform **110** is inclined at an angle with respect to the horizontal, along the longitudinal slot **106**. The angle of incline of the swivel platform **110** has been designed to lie in the range of 2.5 to 45 degrees, more preferably lie in the range of 6 to 30 degrees, and most preferably lie in the range of 10 to 20 degrees. In one example embodiment of the invention, the angle of incline of the swivel platform **110** has been designed to be 15.4 degrees. The swivel

platform **110** that is inclined ensures that the time between the starting of the rotary motion of the swivel platform **110** and the sliding motion of the rodent is reduced considerably.

[0048] The rotary motion of the swivel platform **110** is initiated as the rodent moves towards the bait and tips the balance of the swivel platform **110**. As the swivel platform **110** rotates, the frictional force holding the rodent on the swivel platform **110** becomes less than the gravitational force pulling the rodent along the swivel platform **110** thereby initiating the sliding of the rodent. The sliding motion causes a greater moment (force (weight of the rodent)×distance (distance of the rodent from the pivot axis **112** achieved due to sliding of the rodent)) to be exerted about the pivot axis **112** thereby accelerating the rotation of the swivel platform **110**. The accelerated rotation further accelerates the sliding which further accelerates the rotation and so on and so forth, and the rodent is trapped inside the bucket **150**. Therefore, the chances of the rodent getting trapped are increased considerably if the sliding motion of the rodent follows the rotation of the swivel platform sooner rather than later. However, in the time between the beginning of the rotation motion and the eventual beginning of the sliding motion, the rodent has some friction on the swivel platform **110** that may prevent the rodent from sliding. The friction may allow the rodent to shift its center of gravity backward or maneuver in such a manner that reverses the rotation of the swivel platform **110**. The swivel platform **110** being inclined therefore reduces the time between the rotation motion of the swivel platform **110** and the eventual sliding motion of the rodent. In other words, if the swivel platform **110** is inclined, the rodent starts sliding much sooner after the initiation of rotation, compared to the swivel platform **110** being horizontal, providing less time for the rodent to reverse the rotation of the swivel platform **110**.

[0049] FIG. 5 illustrates a left sectional view of the rodent trapping apparatus **100** with a rodent reaching out to the bait compartment **310**, in accordance with another embodiment of the present invention. To ensure that the rodent does not hold onto the walls of the tunnel **220** as the swivel platform **110** rotates, the distance (c) between the pivot axis **112** and the proximal end **224** of the tunnel **220** should be greater than the distance (d) between the center of gravity of the target rodent and the end of target rodent's hind legs stretched out. Assuming that the average length of the rodent is 10 inches and because of the shape of tunnel **220**, the center of gravity of the rodent is closer to the middle portion of the rodent, (c) should be greater than 5 inches. Therefore, in several embodiments of the invention, the distance between the proximal end **224** of the tunnel **220** and the pivot axis **112** has been designed to be greater than 5 inches, preferably lie in the range of 5 to 8 inches.

[0050] FIG. 6A illustrates a partial perspective view of the rodent trapping apparatus **100** with the bucket **150**, in accordance with another embodiment of the present invention. FIG. 6A illustrates the inclined connecting portion **214** of the tunnel **220** provided over the lid **102**. The swivel platform **110** is disposed longitudinally along the lid **102**. The volume of the bucket **150** is defined by a peripheral wall **510**. The peripheral wall **510** may have a straight profile, a tapered, an inclined profile, or a stepped profile. The peripheral wall **510** illustrated in FIG. 6A has a combination of the tapered and the stepped profile. FIG. 6B illustrates a partial sectional view of the rodent trapping apparatus **100** of FIG. 6A. The partial sectional view illustrates the bucket **150** with the peripheral wall **510**. Further, a portion **514** of the lid **102** extends downwards into the bucket **150** to a predetermined depth.

[0051] The lid **102** extends downwards to create a rim structure **512** at a predetermined distance from an inner surface of the peripheral wall **510**. In the case of the peripheral wall **510** having a tapered profile, the predetermined distance will vary along the depth of the rim structure **512**, while having a minimum clearance between the peripheral wall **510** and the rim structure **512**. Moreover, the entire rim structure **512** runs along the inner surface of the peripheral wall **510**. The rim structure **512** is particularly beneficial in the case of five-gallon buckets, because comparatively larger rodents such as rats are sometimes able to wedge themselves between the bucket **150** and the lid **102**, thereby forcing open the lid **102** and escaping, by holding on to the edge of the bucket **150**.

The rim structure **512** prevents the larger rodents from accessing the edge of the bucket **150**. While the rim structure **512** is particularly useful for five-gallon buckets owing to the small size of the five-gallon buckets, the rim structure **512** is not limited to five-gallon buckets only and may be used with other sizes of buckets as per the specific application.

[0052] In use, the bait is kept in the bait compartment **310** by opening the cover **312** of the bait compartment **310**. The bait has a strong smell which lures the rodents to the bait. The rodent climbs up the bucket **150** through the ramp **230**. As the rodent crawls into the tunnel **220** entering from the proximal end **224** and towards the bait compartment **310** at the distal end **222**, a moment is exerted on the swivel platform **110** about the pivot axis **112**. Due to the moment exerted, the swivel platform **110** rotates and the rodent falls into the bucket **150**. In several embodiments of the invention, the distance between the bait compartment **310** and the pivot axis **112** is chosen to ensure that the rodent is not able to balance itself on the swivel platform **110**. Further, in several embodiments, the distance between the proximal end **224** of the tunnel **220** and the pivot axis **112** is chosen to ensure that the rodent is not able to hold onto the tunnel entrance with its hind legs. Moreover, in several embodiments, the swivel platform **110** is kept inclined with the horizontal to prevent the rodent from balancing itself on the swivel platform **110** and to prevent the rodent from reversing the rotation of the swivel platform **110**. The swivel platform **110** is kept inclined with the horizontal, also to initiate the sliding of the rodent relatively sooner rather than later, thereby reducing the time between initiation of the rotation of the swivel platform **110** about the pivot axis **112** and the eventual sliding motion of the rodent.

[0053] In one embodiment of the invention, the rodent trapping apparatus **100** is made of modular design. The apparatus **100** can be shipped in a compact form with multiple components that are then assembled by the consumer (i.e., end-user) once the rodent trapping apparatus **100** has been purchased. The compact design provides massive savings in shipping costs because the assembled rodent trapping apparatus **100** is much larger in volume compared to the disassembled rodent trapping apparatus **100**. As the rodent trapping apparatus **100** is shipped in a compact design, more than one rodent trapping apparatus **100** can be shipped together. Further, as the rodent trapping apparatus **100** is of compact design, the rodent trapping apparatus can be easily stored as individual units in the warehouse.

[0054] The various components of the rodent trapping apparatus **100** such as the lid **102**, the sidewalls **114**, the ramp **230**, and the swivel platform **110**, etc., can be made into modular units. The various components of the rodent trapping apparatus **100** are designed to be easily assembled using one or more securing members. The one or more securing members are not limited to at least one or a combination of guiding pins, double-sided adhesive tape, magnets, snap-fit design, self-tapping screws, fasteners, etc. The double-sided adhesive tape is not limited to 3M's Very High Bond (VHB) tape, etc. In some embodiments of the invention, in addition to the guiding pins, the side walls **114** of the rodent trapping apparatus **100** have one or more flanges that prevent the side walls **114** from leaning inward and causing interference with the swivel platform **110**.

[0055] FIG. 7 illustrates a left sectional view of the rodent trapping apparatus **100** of a modular design, in accordance with another embodiment of the present invention. The various components of the rodent trapping apparatus **100** such as the lid **102**, the sidewalls **114**, the ramp **230**, the bait compartment **310**, and the swivel platform **110**, etc., are made into modular units and are assembled together at the end user using one or more securing members **702**. It should be noted that once the modular type rodent trapping apparatus **100** (see FIGS. 7 to 10B) is installed, and the various elements and their function for trapping the rodent will be the same as described in FIG. 1A to FIG. 6B, hence only elements that differ from the rodent trapping apparatus **100** of FIG. 1A to FIG. 6B are described in the description of FIGS. 7 to 10B.

[0056] In one embodiment of the invention, one or more magnets are used as one or more securing members **702**. It should be noted that one or more securing members **702** are not limited to one or more magnets, other securing members either alone or in combination can be used to connect the

modular components of the rodent trapping apparatus **100**.

[0057] FIG. **8** illustrates a left sectional view of the lid **102** and the swivel platform **110** of the rodent trapping apparatus **100** of FIG. **7** connected using one or more securing members **702** (e.g., one or more magnets **802**), in accordance with another embodiment of the present invention. The pivot axis **112** of the rodent trapping apparatus **100** is shown in FIG. **7**. As shown in FIG. **7**, “d_mag” represents a distance from the pivot axis **112** to the one or more magnets **802**, “F_mag” represents a pull force exerted by the one or more magnets **802** on the rodent trapping apparatus **100**, “F_rat” represents a force of rodent at which the rodent falls into the bucket **150**, and “d_rat” represents a distance from the pivot axis **112** to the center of gravity of the rodent.

[0058] Some rodents are more agile and wary, such as the brown rat (species name, *Rattus Norvegicus*). The brown rats are good at finding a balance point of the swivel platform **110** compared to other rodent species. Sometimes brown rats can come back without getting trapped in the rodent trapping apparatus **100** by shifting their weight and maneuvering effectively. In order to more reliably catch such rodents that are more agile and wary, one or more magnets **802** are embedded between the swivel platform **110** and/or the lid **102** of the rodent trapping apparatus **100**. In one embodiment of the invention, as shown in FIG. **8**, the one or more magnets **802** are embedded in the swivel platform **110**, while the lid **102** has the metal plate **804**. The metal plate **804** can be made of steel material and can be attached to the lid **102** using the adhesive **806**.

[0059] Other embodiments of the invention include, the one or more magnets **802** are embedded in the lid **102**, while the swivel platform **110** has a metal plate **804**. The metal plate **804** can be made of steel material and can be attached to the bucket **150** as shown in FIG. **8** using an adhesive **806**. During the installation of modular units, the lid **102** can be mounted over the bucket **150**, by allowing the one or more magnets **802** in the lid **102** to get attracted to the metal plate **804** of the bucket **150**. In some embodiments, both the swivel platform **110** and the lid **102** can have magnets. Further, the number of magnets used in the rodent trapping apparatus **100** is not limited to a specific number, size, shape, and type of magnets, it varies based on the rodent type, shape, etc.

[0060] In one embodiment of the invention, the one or more magnets **802** are molded into the swivel platform **110** using an injection mold process. The metal plate **804** can be affixed to the lid **102**, using the adhesive **806**. In another embodiment of the invention, the one or more magnets **802** are molded into the lid **102** using an injection mold process. The metal plate **804** can be affixed to the swivel platform **110**, using the adhesive **806**.

[0061] In some embodiments of the invention, the magnet strength of the one or more magnets **802** can be varied, depending on the type of rodent intended to be caught. By increasing the magnetic strength, the distance from the pivot axis **112** to the center of gravity of the rodent can be increased, thereby more effective rodent trapping apparatus **100** can be achieved. The rodent can pass the pivoting axis **112** and move toward the bait compartment **310**. The one or more magnets **802** serves for two purposes. Firstly, the one or more magnets **802** increases the distance from the pivot axis **112** to the center of gravity of the rodent, and secondly, the one or more magnets **802** prevent the swivel platform **110** from rotating earlier. The swivel platform **110** may rotate earlier, if no magnets are used, in such an arrangement, the rodents (e.g., brown rats) may escape without getting trapped in the rodent trapping apparatus **100**. While using one or more magnets **802**, the rodent trapping apparatus **100** is designed in such a manner that until trapping is activated, the one or more magnets **802** do not release from the metal plate **804** of the lid **102**.

[0062] It should be noted that the magnet should have a pull force such that the smallest target rodent can be caught. For instance, a grown brown rat typically weighs between 140 g to 500 g. Using basic see-saw physics calculations, the one or more magnets **804** that will release a 140 g rodent is 6 inches from the pivot axis **112**. In the above scenario, a magnet pull force (F_mag) of 1.39 N can be selected. The force calculation used in the rodent trapping apparatus **100** is as follows:

$$F_mag*d_mag=F_rat*d_rat, \text{ where } F_rat=m_rat*g \quad \text{Equation (1)}$$

$$\text{Therefore, } F_mag*d_mag=(m_rat*g)*d_rat \quad \text{Equation (2)}$$

[0063] In Equation (2), “F_mag” represents the pull force of the one or more magnets **802**, that is the force required to pull the magnet straight free vertically from the swivel platform **110**, “d_mag” represents a distance from the pivot axis **112** to the one or more magnets **802**, “m_rat” represents mass of the rodent, “g” represents a gravitational acceleration (i.e., 9.8 m/s/s), and “d_rat” represents a distance from the pivot axis **112** to the center of gravity of the rodent.

[0064] It should be noted that the smaller rodents such as mice, rat pups, etc., can be caught using one or more magnets **802** of lesser pull force based on the Equation (2). However, the smaller the magnet strength is, the less effective for catching larger rodents. The very large rodent, for instance of 500 g in mass, if the magnet pull force is very small, the magnet will release when the center of gravity of the rodent is only a few distance (in mm) passed the pivot axis **112**. It has been found that when the distance (d_rat) is just a few millimeters, large rats can pull out of the trap even after the swivel platform **110** starts rotating. For example, the rodent trapping apparatus **100** with one or more magnets **802** will release if a 22 g rodent gets to 6 inches from the pivot axis **112** (0.22N pull strength), whereas a 500 g rodent will be released only at 6 mm after the pivot axis **112**. If the large rodent (e.g., brown rat) is very agile and wary, the rodent is sometimes able to shift its own weight in time to stop the swivel platform **110** from rotating too far, and reverse the rotation, and escape.

[0065] In one embodiment of the invention, to cover trapping of all types of rodents, the one or more magnets **802** as shown in FIG. 9 can be interchanged to obtain different magnetic strength depending on the type and size of the rodents. Rodents of smaller size require, a small magnet pull force, while larger rodents need a larger pull force. In some embodiment of the invention, especially in the modular type of the rodent trapping apparatus **100** as shown in FIG. 8, one or more swivel platforms with one or more magnets **802** of different magnetic strengths can be used. For example, one swivel platform can have one or more magnets **802** of lesser magnetic strength, while another swivel platform can have one or more magnets **802** of greater magnetic strength. The user can interchange the swivel platform based on the requirement of the magnetic strength and type of the rodents.

[0066] In one embodiment of the invention, the ramp **230** can be designed for the bucket **150** of both seven-gallon and five-gallon. The bucket **150** of both seven-gallon and five-gallon has the same diameter while the height of both seven-gallon and five-gallon varies. For example, the height of the five-gallon is typically 14.25 inches, while that of the seven-gallon is typically 19.5 inches. The modular interface that connects the ramp **230** and the lid **102** is designed in such a manner that the same interface can be used to accept the bucket **150** of different gallons, for example, seven-gallon and five-gallon. It should be noted that the lid **102** can be adapted to cover any standard size of commercially available bucket sizes.

[0067] It should be noted that the important function of the swivel platform **110** is that it can automatically reset the rodent trapping apparatus **100**. For example, when the rodent falls into the bucket **150**, the swivel platform **110** will move back to the original position. This is done by designing the plate with a loading element **807** as shown in FIG. 8. When the rodent falls into the trap, the swivel platform **110** will be in a vertical position. Due to center of gravity of the swivel platform **110**, the entrance side of the rodent trapping apparatus **100** is pulled down due to the weight of the loading element **807**, so that the rodent trapping apparatus **100** is automatically reset.

[0068] It should be noted that the swivel platform **110** includes a first portion **808** positioned below the distal end of the tunnel **220**. The first portion **808** includes the one or more securing members **702** for connecting the swivel platform **110** with the lid **102**. The one or more securing members **702** include one or more magnets **802** of varying magnetic strength and are adapted to increase a distance between the pivot axis **112** and center of gravity of the rodent. The swivel platform **110** also includes a second portion **809** positioned below the distal end of the tunnel **220**. The second

portion **809** includes the loading element **807** configured to reset the swivel platform **110** after the rodent is trapped inside the bucket **150**.

[0069] FIG. **9** illustrates a left sectional view of the rodent trapping apparatus of FIG. **7** with at least one first securing structure **902** and at least one second securing structure **908**, for enabling and disabling the rodent trapping apparatus **100**, in accordance with an embodiment of the present invention. The first securing member **902** is mounted to the swivel platform **110** and adapted to disable movement of the swivel platform **110** during a disabled state of the rodent trapping apparatus **100**. The second securing member **908** is mounted to the cover **312** and the bucket **150** and adapted to lock the cover **312** with the bucket **150**, during an enabled state of the rodent trapping apparatus **100**.

[0070] In one embodiment of the invention, the first securing structure **902** has a first receiving member **906A**, and a second receiving member **906B**. The first securing structure **902** is mounted to the swivel platform **110**, such that the first securing structure **902** is positioned below the swivel platform **110**. The rodent trapping apparatus **100** also has a locking member (e.g., locking pin **904**) for locking the rodent trapping apparatus **100** in the enabled state or the disabled state. When the locking pin **904** is inserted into the first receiving member **906A** and the second receiving member **906B**, as shown in FIG. **9**, the swivel platform **110** is locked and hence cannot swivel about the pivot axis **112**. FIG. **9** shows the rodent trapping apparatus **100** in a “disabled state” (not used for trapping the rodents). In the disabled state, the user of the rodent trapping apparatus **100** can place a bait directly on the swivel platform **110** or in the bait compartment **310**, to allow rats and other rodents to feed on the bait. This is done to target rodents or rat colonies to get used to the rodent trapping apparatus **100**.

[0071] The rodent trapping apparatus **100** can be left in the disabled state with bait for a week or more. After the rodents have become used to feeding in the rodent trapping apparatus **100**, locking pin **904** can be removed from the first receiving member **906A** and the second receiving member **906B**. This allows the rodent trapping apparatus **100** ready for trapping the rodents (i.e., “enabled state”). FIG. **9** also shows the second securing structure **908** and the locking pin **904** for locking the cover **312** of the bait compartment **310** of the rodent trapping apparatus **100**.

[0072] FIG. **10A** illustrates a left sectional view of the second securing structure **908** for locking the cover **312** of the bait compartment **310** of the rodent trapping apparatus **100** of FIG. **9**, in accordance with an embodiment of the present invention. After removing the locking pin **904** from the first securing structure **902** (to enable the rodent trapping apparatus **100**, referred to as “enabled state”), the locking pin **904** can be inserted into the second securing structure **908** as shown in FIG. **10A**. As the rodents have become familiar with feeding in the rodent trapping apparatus **100**, rodents can move freely in the used space and get caught in the rodent trapping apparatus **100**.

[0073] When the rodent trapping apparatus **100** is in the disabled state, there is no need to lock the cover **312** of the bait compartment **310** with the bucket **150**. When the rodent trapping apparatus **100** is enabled or activated by removing the locking pin **904** from the first securing structure **902**, the rodent trapping apparatus **100** starts its trapping function and hence it is essential to lock the cover **312** of the bait compartment **310** with the bucket **150** to prevent the cover **312** being removed from the bucket **150** and causing the rodents reaching the bait compartment **310** to escape. At the time of enabled state, the locking pin **904** is secured in the second securing structure **908** to lock the cover **312** of the bait compartment **310** with the bucket **150**.

[0074] FIG. **10B** illustrates a left sectional view of the first securing structure **902**, for enabling and disabling the rodent trapping apparatus **100** of FIG. **9**, in accordance with an embodiment of the present invention. A spring loaded pin is used as locking pin **904**. The spring loaded pin has a retaining ring **1002** and a spring **1004**. The retaining ring **1002** retains the movement of the spring **1004**, thereby retaining the movement of the swivel platform **110**.

[0075] It should be noted that the design, structure, and mechanism of the first securing structure **902**, the second securing structure **908**, and the locking member (e.g., locking pin **904**) as shown in

FIG. 9, FIG. 10A, and FIG. 10B, corresponds to one or more embodiments of the invention. Without limitation, any suitable mechanism, structure, and design of the first securing structure **902**, the second securing structure **908**, and the locking member other than as shown in FIG. 9, FIG. 10A, and FIG. 10B can be used for disabling and enabling the rodent trapping apparatus **100**, depending upon the structure, design, and mechanism of the swivel platform **110**, the bait compartment **310**, the cover **213**, or the bucket **150**. In one embodiment, the first securing structure **902** has only one receiving member (e.g., the first receiving member **906A** or the second receiving member **906B**) positioned at the bottom of the swivel platform **110**. The receiving member extends along the width of the swivel platform **110** and the locking member (e.g., locking pin **904**) can be inserted into the receiving member (e.g., the first receiving member **906A** or a second receiving member **906B**) in order to disable the rodent trapping apparatus **100**. It should be noted that the position of the first securing structure **902**, the second securing structure **908**, and the locking member (e.g., locking pin **904**) are not limited as shown in FIG. 9, FIG. 10A, and FIG. 10B. The first securing structure **902** and/or the second securing structure **908** can also be located near the located at an end of the swivel plate **110** (e.g., at the distal end of the tunnel **220** where bait compartment **310** is located). Thus, the present invention efficiently traps the different types of the rodents. Further, the modular design of the rodent trapping apparatus **100** allows easy transportation and assembling of the rodent trapping apparatus **100** at the end user side.

[0076] Various embodiments of the disclosure, as discussed above, may be practiced with steps and/or operations in a different order, and/or with hardware elements in configurations, which are different from those which are disclosed. Therefore, although the disclosure has been described based on these exemplary embodiments, it is noted that certain modifications, variations, and alternative constructions may be apparent and well within the scope of the disclosure.

[0077] Although various exemplary embodiments of the disclosure are described herein in a language specific to structural features and/or methodological acts, the subject matter defined in the appended claims is not necessarily limited to the specific features or acts described above. Rather, the specific features and acts described above are disclosed as exemplary forms of implementing the claims.

Claims

1. A rodent trapping apparatus for trapping rodents, the rodent trapping apparatus comprising: a lid configured to be disposed on a bucket, the lid including a top surface, wherein the lid comprises a longitudinal slot having two opposing longitudinal edges; two sidewalls provided on the top surface, with one sidewall along each longitudinal edge of the longitudinal slot, wherein the two sidewalls extend up to an edge of the lid; a transverse connecting member connecting the two sidewalls thereby forming a tunnel over the longitudinal slot, a proximal end of the tunnel being located at the edge of the lid due to the two sidewalls extending up to the edge of the lid; a bait compartment located at a distal end of the tunnel, the distal end of the tunnel being formed by a distal connecting portion of the transverse connecting member and two distal segments of the two sidewalls; and a swivel platform located within and along the longitudinal slot, wherein the swivel platform is configured to swivel about a pivot axis, wherein the pivot axis is located between the distal end and the proximal end of the tunnel.
2. The rodent trapping apparatus as claimed in claim 1, wherein the bait compartment is disposed at a distance from the pivot axis, wherein the distance between the bait compartment and the pivot axis lies in the range of 3 to 12 inches.
3. The rodent trapping apparatus as claimed in claim 1, wherein the swivel platform is inclined at an angle with respect to the horizontal, the angle of incline of the swivel platform, with respect to the horizontal, lies in the range of 0 to 45 degrees.
4. The rodent trapping apparatus as claimed in claim 1, wherein the proximal end of the tunnel is

disposed at a distance from the pivot axis lies in the range of 3 to 10 inches.

5. The rodent trapping apparatus as claimed in claim 1, wherein the bait compartment includes a cover and a material of the cover is stainless steel.

6. The rodent trapping apparatus as claimed in claim 5, further comprising: at least one first securing member mounted to the swivel platform and adapted to disable movement of the swivel platform during a disabled state of the rodent trapping apparatus; and at least one second securing member mounted to the cover and the bucket and adapted to lock the cover with the bucket, during an enabled state of the rodent trapping apparatus.

7. The rodent trapping apparatus as claimed in claim 1, further comprising a ramp configured to be provided between ground and the top surface of the lid, wherein the ramp connects the ground level with the top surface of the lid at the proximal end of the tunnel.

8. The rodent trapping apparatus as claimed in claim 1, wherein the transverse connecting member further comprises an inclined connecting portion connecting the two sidewalls and providing an inclined section to the tunnel.

9. The rodent trapping apparatus as claimed in claim 1, wherein the lid includes an overhang portion that extends beyond edge of the bucket.

10. The rodent trapping apparatus as claimed in claim 1, wherein the lid comprises a portion extending downwards to a predetermined depth to create a rim structure, wherein in use, the rim structure is adapted to run along an inner surface of a peripheral wall of the bucket, while maintaining a minimum predetermined distance from the inner surface.

11. The rodent trapping apparatus as claimed in claim 1, wherein the lid, the two sidewalls, the transverse connecting member, the bait compartment and the swivel platform are of modular units and are connected together to form the rodent trapping apparatus using one or more securing members.

12. The rodent trapping apparatus as claimed in claim 11, the swivel platform comprises a first portion positioned below the distal end of the tunnel, the first portion comprises the one or more securing members for connecting the swivel platform with the lid, the one or more securing members comprises one or more magnets of varying magnetic strength, adapted to increase a distance between the pivot axis and center of gravity of the rodent.

13. The rodent trapping apparatus as claimed in claim 1, wherein the swivel platform comprises a second portion positioned below the distal end of the tunnel, the second portion comprises a loading element configured to reset the swivel platform after the rodent is trapped inside the bucket.

14. A rodent trapping apparatus for trapping rodents, the rodent trapping apparatus comprising: a lid configured to be disposed on a bucket, the lid including a top surface, wherein the lid comprises a longitudinal slot having two opposing longitudinal edges; two sidewalls provided on the top surface, with one sidewall along each longitudinal edge of the longitudinal slot, wherein the two sidewalls extend up to an edge of the lid; a transverse connecting member connecting the two sidewalls thereby forming a tunnel over the longitudinal slot, a proximal end of the tunnel being located at the edge of the lid due to the two sidewalls extending up to the edge of the lid; a bait compartment located at a distal end of the tunnel, the distal end of the tunnel being formed by a distal connecting portion of the transverse connecting member and two distal segments of the two sidewalls; and a swivel platform located within and along the longitudinal slot, wherein the swivel platform is configured to swivel about a pivot axis, wherein the pivot axis is located between the distal end and the proximal end of the tunnel; wherein the proximal end of the tunnel comprises one or more securing members for connecting the swivel platform with the lid, the one or more securing members are one or more magnets of varying magnetic strength adapted to increase a distance between the pivot axis and center of gravity of the rodent.

15. The rodent trapping apparatus as claimed in claim 14, wherein the bait compartment is disposed at a distance from the pivot axis, the distance between the bait compartment and the pivot axis is in

the range of 5 to 12 inches.

16. The rodent trapping apparatus as claimed in claim 14, wherein the proximal end of the tunnel is disposed at a distance from the pivot axis lies in the range of 5 to 8 inches.

17. The rodent trapping apparatus as claimed in claim 14, wherein the swivel platform is inclined at an angle with respect to the horizontal, the angle of incline of the swivel platform, with respect to the horizontal lies in the range of 2.5 to 45 degrees.

18. The rodent trapping apparatus as claimed in claim 14, further comprising a ramp configured to be provided between ground and the top surface of the lid, wherein the ramp connects the ground level with the top surface of the lid at the proximal end of the tunnel.

19. The rodent trapping apparatus as claimed in claim 14, wherein the transverse connecting member further comprises an inclined connecting portion connecting the two sidewalls and providing an inclined section to the tunnel.

20. The rodent trapping apparatus as claimed in claim 14, wherein the lid includes an overhang portion that extends beyond the edge of the bucket.

21. The rodent trapping apparatus as claimed in claim 14, wherein the bait compartment includes a cover and a material of the cover is stainless steel.

22. The rodent trapping apparatus as claimed in claim 21, further comprising: at least one first securing member mounted to the swivel platform and adapted to disable movement of the swivel platform during a disabled state of the rodent trapping apparatus; and at least one second securing member mounted to the cover and the bucket and adapted to lock the cover with the bucket, during an enabled state of the rodent trapping apparatus.

23. The rodent trapping apparatus as claimed in claim 14, wherein the lid comprises a portion extending downwards to a predetermined depth to create a rim structure, wherein in use, the rim structure is adapted to run along an inner surface of a peripheral wall of the bucket while maintaining a minimum predetermined distance from the inner surface.

24. A rodent trapping apparatus for trapping rodents, the rodent trapping apparatus comprising: a lid configured to be disposed on a bucket, the lid including a top surface, wherein the lid comprises a longitudinal slot having two opposing longitudinal edges; two sidewalls provided on the top surface, with one sidewall along each longitudinal edge of the longitudinal slot, wherein the two sidewalls extend up to an edge of the lid; a transverse connecting member connecting the two sidewalls thereby forming a tunnel over the longitudinal slot, a proximal end of the tunnel being located at the edge of the lid due to the two sidewalls extending up to the edge of the lid; a bait compartment located at a distal end of the tunnel, the distal end of the tunnel being formed by a distal connecting portion of the transverse connecting member and two distal segments of the two sidewalls; and a swivel platform located within and along the longitudinal slot, wherein the swivel platform is configured to swivel about a pivot axis, wherein the pivot axis is located between the distal end and the proximal end of the tunnel, wherein the lid, the two sidewalls, the transverse connecting member, the bait compartment, and the swivel platform are modular units and are connected together to form the rodent trapping apparatus using one or more securing members.

25. The rodent trapping apparatus as claimed in claim 24, wherein the lid includes an overhang portion that extends beyond the edge of the bucket, the swivel platform is inclined at an angle with respect to the horizontal, along the longitudinal slot, the angle lies in the range of 2.5 to 45 degrees.

26. The rodent trapping apparatus as claimed in claim 24, wherein the bait compartment is disposed at a distance from the pivot axis, the distance lies in the range of 6 to 12 inches.

27. The rodent trapping apparatus as claimed in claim 24, wherein the proximal end of the tunnel is disposed at a distance from the pivot axis, the distance lies in the range of 5 to 8 inches.

28. The rodent trapping apparatus as claimed in claim 24, wherein the transverse connecting member further comprises an inclined connecting portion connecting the two sidewalls and providing an inclined section to the tunnel.

29. The rodent trapping apparatus as claimed in claim 24, wherein the lid comprises a portion

extending downwards to a predetermined depth to create a rim structure, wherein in use, the rim structure is adapted to run along an inner surface of a peripheral wall of the bucket, while maintaining a minimum predetermined distance from the inner surface.

30. The rodent trapping apparatus as claimed in claim 24, wherein the bait compartment includes a cover and a material of the cover is stainless steel.

31. The rodent trapping apparatus as claimed in claim 30, further comprising: at least one first securing member mounted to the swivel platform and adapted to disable movement of the swivel platform during a disabled state of the rodent trapping apparatus; and at least one second securing member mounted to the cover and the bucket and adapted to lock the cover with the bucket, during an enabled state of the rodent trapping apparatus.
