

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Design Patent	D1089051
Kind Code	S
Date of Patent	August 19, 2025
Inventor(s)	Gu; Jinggen

---

### Tire

---

**Inventors:** Gu; Jinggen (Chengdu, CN)

**Applicant:** Sichuan Yuanxing Rubber Co., Ltd. (Chengdu, CN)

**Assignee:** Suchian Yuanxing Rubber Co., Ltd. (Chengdu, CN)

**(\*\*) Term:** 15 Years    **Appl. No.:**

**D/913860**

**Filed:**

**October 10, 2023**

### Foreign Application Priority Data

CN	202330523708.5	Aug. 16, 2023
----	----------------	---------------

### Publication Classification

**LOC Cl.:** 1215

**U.S. Cl.:**

USPC    D12/535

### Field of Classification Search

**CPC:** B60C (2200/10); B60C (11/0302); B60C (11/11); B60C (2200/14); B60C (2011/0374); B60C (11/033); B60C (11/032); B60C (2011/0381); B60C (11/0304); B60C (2011/0372); B60C (9/06); B60C (9/22); B60C (9/2204); B60C (11/0083); B60C (11/1376); B60C (2011/0025); B60C (2011/0376); B60C (11/0058); B60C (11/1369); B60C (11/0311); B60C (11/0332); B60C (3/04); B60C (9/20); B60C (11/0306); B60C (9/08); B60C (19/001); B60C (2011/0365); B60C (2011/0344); B60C (2011/0358); B60C (2011/0379); B60C (9/28); B60C (2009/2022); B60C (2011/0367); B60C (2011/0388); B60C (9/2009); B60C (2011/0334); B60C (9/0007); B60C (11/00); B60C (11/0008); B60C (11/13); B60C (11/1392); B60C (15/0018); B60C (2009/1828); B60C (9/09); B60C (15/0036); B60C (15/0045); B60C (2009/2019); B60C (2009/2252);

B60C (2011/0346); B60C (9/0042); B60C (9/04); B60C (2011/0383); B60C (2200/04); B60C (9/1821); B60C (1/0016); B60C (11/005); B60C (11/03); B60C (11/12); B60C (2009/2214); B60C (2011/0016); B60C (2011/0033); B60C (2011/0369); B60C (11/1353); B60C (13/00); B60C (15/024); B60C (2011/0362); B60C (2015/009); B60C (2015/0614); B60C (5/00); B60C (9/14); B60C (9/18); B60C (11/0041); B60C (11/01); B60C (11/0327); B60C (11/04); B60C (11/1315); B60C (15/06); B60C (2009/0078); B60C (2009/0092); B60C (2009/2276); B60C (2009/2285); B60C (2011/0313); B60C (2011/0353); B60C (15/0603); B60C (2009/2016); B60C (2006/2261); B60C (2011/0339); B60C (2011/0348); B60C (2011/0351); B60C (2011/0355); B60C (2011/1338); B60C (2013/006); B60C (9/02); B60C (9/07); B60C (9/10); B60C (9/2006); B60C (11/1236); B60C (11/1323); B60C (11/18); B60C (15/0027); B60C (15/0072); B60C (15/02); B60C (17/0009); B60C (2009/0035); B60C (2009/0466); B60C (2009/0475); B60C (2009/2025); B60C (2009/2271); B60C (2009/2295); B60C (2011/016); B60C (2011/0341); B60C (2011/1361); B60C (2015/061); B60C (1/0025); B60C (11/0323); B60C (11/1204); B60C (11/1281); B60C (11/1307); B60C (11/1384); B60C (13/001); B60C (15/0242); B60C (15/0632); B60C (15/0635); B60C (2001/0075); B60C (2009/0085); B60C (2009/0276); B60C (2009/0491); B60C (2009/2032); B60C (2009/2093); B60C (2009/2223); B60C (2009/2233); B60C (2009/2238); B60C (2009/2247); B60C (2009/2266); B60C (2009/228); B60C (2011/036); B60C (2011/1209); B60C (2011/1227); B60C (2011/1231); B60C (2011/1254); B60C (2011/1286); B60C (2013/007); B60C (2013/045); B60C (2017/0072); B60C (3/00); B60C (9/0207); B60C (9/023); B60C (9/0238); B60C (9/1835); B60C (9/185); B60C (1/00); B60C (11/0309); B60C (11/1259); B60C (11/1263); B60C (11/24); B60C (15/009); B60C (15/04); B60C (17/06); B60C (19/00); B60C (2011/0083); B60C (2009/0014); B60C (2009/0246); B60C (2009/0284); B60C (2009/0425); B60C (2009/0433); B60C (2009/0441); B60C (2009/0458); B60C (2009/2012); B60C (2009/2029); B60C (2009/209); B60C (2009/2242); B60C (2009/2257); B60C (2009/229); B60C (2011/013); B60C (2011/039); B60C (2011/1213); B60C (2011/129); B60C (2015/0245); B60C (25/132); B60C (29/04); B60C (29/06); B60C (29/064); B60C (9/0057); B60C (9/0292); B60C (9/26)

**USPC:** D12/535

---

## Description

- (1) FIG. 1 is a front, right and top side perspective view of a tire showing the new design;
- (2) FIG. 2 is a rear, left and bottom side perspective view thereof;
- (3) FIG. 3 is a front elevation view thereof;
- (4) FIG. 4 is a rear elevation view thereof;
- (5) FIG. 5 is a left side elevation view thereof;
- (6) FIG. 6 is a right side elevation view thereof;
- (7) FIG. 7 is a top plan view thereof; and,
- (8) FIG. 8 is a bottom plan view thereof.
- (9) The broken lines shown in the drawings represent portions of the tire that form no part of the claimed design.

## Claims

The ornamental design for a tire, as shown and described.

---

