

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12395676
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Filippov; Alexey Konstantinovich et al.

Intra-prediction apparatus for extending a set of predetermined directional intra-prediction modes

Abstract

An intra-prediction apparatus and method are provided for extending a set of predetermined directional intra-prediction modes of a rectangular video coding block. The intra-prediction apparatus determines an aspect ratio of the rectangular video coding block, and determines a complementary angle range based on the aspect ratio. The apparatus then selects a complementary direction within the complementary directional range, and adds an extension directional intra-prediction mode associated with the complementary direction to the set of predetermined directional intra-prediction modes. Based on the extension directional intra-prediction mode, the apparatus intra-predicts pixel values of pixels of the rectangular video coding block.

Inventors: Filippov; Alexey Konstantinovich (Moscow, RU), Rufitskiy; Vasily Alexeevich (Moscow, RU)

Applicant: Huawei Technologies Co., Ltd. (Shenzhen, CN)

Family ID: 1000008765830

Assignee: Huawei Technologies Co., Ltd. (Shenzhen, CN)

Appl. No.: 17/750099

Filed: May 20, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20220279208 A1	Sep. 01, 2022

Related U.S. Application Data

continuation parent-doc US 17097942 20201113 US 11343537 child-doc US 17750099
continuation parent-doc US 16448476 20190621 US 10863197 20201208 child-doc US 17097942
continuation parent-doc WO PCT/RU2016/000916 20161223 PENDING child-doc US 16448476

Publication Classification

Int. Cl.: **H04N19/11** (20140101); **H04N19/157** (20140101); **H04N19/176** (20140101); **H04N19/182** (20140101); **H04N19/593** (20140101); **H04N19/70** (20140101)

U.S. Cl.:

CPC **H04N19/593** (20141101); **H04N19/11** (20141101); **H04N19/157** (20141101); **H04N19/176** (20141101); **H04N19/182** (20141101); **H04N19/70** (20141101);

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9225986	12/2014	Bossen et al.	N/A	N/A
2007/0036215	12/2006	Pan et al.	N/A	N/A
2008/0101707	12/2007	Mukherjee et al.	N/A	N/A
2010/0208799	12/2009	Park et al.	N/A	N/A
2011/0243230	12/2010	Liu et al.	N/A	N/A
2012/0057630	12/2011	Saxena et al.	N/A	N/A
2012/0307894	12/2011	Chien et al.	N/A	N/A
2013/0101036	12/2012	Zhou	N/A	N/A
2013/0107970	12/2012	Wang	375/240.18	H04N 19/186
2013/0114713	12/2012	Bossen et al.	N/A	N/A
2013/0114716	12/2012	Gao et al.	N/A	N/A
2013/0136180	12/2012	Yang et al.	N/A	N/A
2013/0156098	12/2012	Schwartz	375/240.03	H04N 19/115
2013/0163664	12/2012	Guo et al.	N/A	N/A
2013/0287094	12/2012	Song	375/240.02	H04N 19/105
2014/0086333	12/2013	Wang et al.	N/A	N/A
2014/0092983	12/2013	Joshi et al.	N/A	N/A
2014/0140404	12/2013	Liu et al.	N/A	N/A
2014/0198855	12/2013	Sole Rojals et al.	N/A	N/A
2014/0376626	12/2013	Lee	N/A	N/A
2015/0010062	12/2014	Gokhale et al.	N/A	N/A
2015/0016516	12/2014	Saxena et al.	N/A	N/A
2015/0023405	12/2014	Joshi et al.	N/A	N/A
2015/0043641	12/2014	Gamei et al.	N/A	N/A
2015/0063457	12/2014	Gamei et al.	N/A	N/A
2015/0078438	12/2014	Lim et al.	N/A	N/A
2015/0078447	12/2014	Gamei et al.	N/A	N/A
2015/0110201	12/2014	Sasai	375/240.26	H04N 19/119
2015/0117549	12/2014	Matsubara	375/240.01	H04N 19/436
2015/0195566	12/2014	Hinz et al.	N/A	N/A
2015/0365692	12/2014	Liu et al.	N/A	N/A
2015/0373332	12/2014	Kim	375/240.03	H04N 19/122
2016/0134866	12/2015	Budagavi	N/A	N/A
2016/0330255	12/2015	Denoual	N/A	H04N 19/115

2017/0094314	12/2016	Zhao et al.	N/A	N/A
2017/0150186	12/2016	Zhang	N/A	H04N 19/61
2017/0180742	12/2016	Maani et al.	N/A	N/A
2017/0214940	12/2016	Chien et al.	N/A	N/A
2017/0251220	12/2016	Chun	N/A	H04N 19/105
2018/0173118	12/2017	Schmitt-Weaver	N/A	G03F 9/7019
2018/0176601	12/2017	Jeong et al.	N/A	N/A
2018/0241995	12/2017	Son	N/A	H04N 19/11
2018/0255295	12/2017	Lee	N/A	H04N 19/593
2018/0255299	12/2017	Lee	N/A	H04N 19/70
2018/0288446	12/2017	An	N/A	H04N 19/159
2018/0302620	12/2017	Koo	N/A	H04N 19/90
2018/0324441	12/2017	Lim	N/A	H04N 19/17
2019/0058890	12/2018	Maani et al.	N/A	N/A
2019/0065859	12/2018	Togashi	N/A	G06T 7/215

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
101228797	12/2007	CN	N/A
101971631	12/2010	CN	N/A
102907098	12/2012	CN	N/A
102907100	12/2012	CN	N/A
103004210	12/2012	CN	N/A
104255030	12/2013	CN	N/A
104412591	12/2014	CN	N/A
104935925	12/2014	CN	N/A
2587805	12/2012	EP	N/A
2745519	12/2013	EP	N/A
2015515236	12/2014	JP	N/A
2012161445	12/2011	WO	N/A
2012167119	12/2011	WO	N/A
2012170812	12/2011	WO	N/A
2013082291	12/2012	WO	N/A

OTHER PUBLICATIONS

U.S. Appl. No. 17/097,942, filed Nov. 13, 2020. cited by applicant

U.S. Appl. No. 16/448,476, filed Jun. 21, 2019. cited by applicant

“Information technology—High efficiency coding and media delivery in heterogeneous environments—Part 2: High efficiency video coding,” ISO/IEC 23008-2:2013, total 13 pages (Dec. 2013). cited by applicant

Sullivan et al., “Overview of the High Efficiency Video Coding (HEVC) Standard,” in IEEE Transactions on Circuits and Systems for Video Technology, vol. 22, No. 12, pp. 1649-1668 (Dec. 2012). cited by applicant

Sullivan et al., “Future video coding: Joint Exploration Model 1 (JEMI) for future video coding investigation,” ITU-T SG16 Q6, TD 213 (WP 3/16), Geneva, total 20 pages (Oct. 12-23, 2015). cited by applicant

Huang et al., “EE2.1: Quadtree plus binary tree structure integration with JEM tools,” Joint Video Exploration Team (JVET) of ITU-T SG 16 WP 3 and ISO/IEC JTC 1/SC 29/WG 11, JVET-C0024, 3rd Meeting: Geneva, CH, total 5 pages (May 26-Jun. 1, 2016). cited by applicant

“Series H: Audiovisual and Multimedia Systems Infrastructure of audiovisual services—Coding of moving video, Advanced video coding for generic audiovisual services,” ITU-T H.264, total 804 pages (Oct. 2016). cited by applicant

“Series H: Audiovisual and Multimedia Systems Infrastructure of audiovisual services—Coding of

moving video, High efficiency video coding,” ITU-T H.265, total 634 pages (Apr. 2015). cited by applicant

Liu et al., “Rectangular (2NxN and Nx2N) Intra Prediction,” Joint Collaborative Team on Video Coding (JCT-VC) of ITU-T SG16 WP3 and ISO/IEC JTC1/SC29/WG11, 7th Meeting: Geneva, JCTVC-G135, WG11, No. 21687, 7th Meeting: Geneva, total 6 pages, XP030110119 (Nov. 21-30, 2011). cited by applicant

Chen et al., “Algorithm Description of Joint Exploration Test Model 4,” Joint Video Exploration Team (JVET) of ITU-T SG 16 WP 3 and ISO/IEC JTC 1/SC 29/WG 11, JVET-D1001-v1, 4th Meeting: Chengdu, CN, total 38 pages, KP030150460 (Oct. 15-21, 2016). cited by applicant

Search report IP.com. cited by applicant

Grange “Overview of VP-Next, A Next Generation Open Video Codec, Objectives & Progress,” Chrome Media Group, Google, Total 12 pages (2012). cited by applicant

Primary Examiner: Rahman; Mohammad J

Attorney, Agent or Firm: Leydig, Voit & Mayer, Ltd.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 17/097,942, filed on Nov. 13, 2020, which is a continuation of U.S. patent application Ser. No. 16/448,476, filed on Jun. 21, 2019, now U.S. Pat. No. 10,863,197, which is a continuation of International Application No. PCT/RU2016/000916, filed on Dec. 23, 2016. All of the afore-mentioned patent applications are hereby incorporated by reference in their entireties.

TECHNICAL FIELD

(1) Embodiments of the present disclosure relate to the field of video coding. More specifically, embodiments of the present disclosure relate to an apparatus for directional intra-prediction of a video coding block as well as an encoding apparatus and a decoding apparatus comprising such an intra-prediction apparatus.

BACKGROUND

(2) Digital video communication and storage applications are implemented by a wide range of digital devices, e.g. digital cameras, cellular radio telephones, laptops, broadcasting systems, video conferencing systems, etc. One of the most important and challenging tasks of these applications is video compression. The task of video compression is complex and is constrained by two contradicting parameters: compression efficiency and computational complexity. Video coding standards, such as ITU-T H.264/AVC or ITU-T H.265/HEVC, provide a good tradeoff between these parameters. For that reason, support of video coding standards is a mandatory requirement for almost any video compression application.

(3) The state-of-the-art video coding standards are based on partitioning of a source picture into video coding blocks (or short blocks). Processing of these blocks depend on their size, spatial position and a coding mode specified by an encoder. Coding modes can be classified into two groups according to the type of prediction: intra- and inter-prediction modes. Intra-prediction modes use pixels of the same picture (also referred to as frame or image) to generate reference samples to calculate the prediction values for the pixels of the block being reconstructed. Intra-prediction is also referred to as spatial prediction. Inter-prediction modes are designed for temporal prediction and uses reference samples of previous or next pictures to predict pixels of the block of the current picture. After a prediction stage, transform coding is performed for a prediction error that is the difference between an original signal and its prediction. Then, the transform coefficients and side information are encoded using an entropy coder (e.g., CABAC for AVC/H.264 and HEVC/H.265). The recently adopted ITU-T H.265/HEVC standard (ISO/IEC 23008-2:2013, “Information technology—High efficiency coding and media delivery in heterogeneous environments—Part 2: High efficiency video coding”, November 2013) declares a set of

state-of-the-art video coding tools that provide a reasonable tradeoff between coding efficiency and computational complexity. An overview on the ITU-T H.265/HEVC standard has been given by Gary J. Sullivan, "Overview of the High Efficiency Video Coding (HEVC) Standard", in IEEE Transactions on Circuits and Systems for Video Technology, Vol. 22, No. 12, December 2012, the entire content of which is incorporated herein by reference.

(4) Similarly, to the ITU-T H.264/AVC video coding standard, the HEVC/H.265 video coding standard provides for a division of the source picture into blocks, e.g., coding units (CUs). Each of the CUs can be further split into either smaller CUs or prediction units (PUs). A PU can be intra- or inter-predicted according to the type of processing applied for the pixels of PU. In case of inter-prediction, a PU represents an area of pixels that is processed by motion compensation using a motion vector specified for a PU. For intra prediction, the adjacent pixels of neighbor blocks are used as reference samples to predict a current block. A PU specifies a prediction mode that is selected from the set of intra-prediction modes for all the transform units (TUs) contained in this PU. A TU can have different sizes (e.g., 4×4 , 8×8 , 16×16 and 32×32 pixels) and can be processed in different ways. For a TU, transform coding is performed, i.e. the prediction error is transformed with a discrete cosine transform or a discrete sine transform (in the HEVC/H.265 standard, it is applied to intra-coded blocks) and quantized. Hence, reconstructed pixels contain quantization noise (it can become apparent, for examples, as blockiness between units, ringing artifacts along with sharp edges, etc.) that in-loop filters such as Deblocking Filter (DBF), Sample Adaptive Offset (SAO) and Adaptive Loop Filter (ALF) try to suppress. The use of sophisticated prediction coding (such as motion compensation and intra-prediction) and partitioning techniques (e.g., quadtree for CUs and PUs as well as residual quadtree for TUs in the HEVC/H.265 standard and quadtree plus binary tree for the JEM reference software starting from version JEM-3.0) allowed the standardization committee to significantly reduce the redundancy in PUs.

(5) According to the HEVC/H.265 standard, the intra prediction modes as shown in FIG. 5 include a planar mode (the intra-prediction mode index is 0), DC mode (the intra-prediction mode index is 1), and 33 directional modes (the intra-prediction mode index ranges from 2 to 34, indicated by the solid lines). The set of directional intra-prediction modes was extended up to 65 modes (almost doubled) by decreasing a step angle between directional intra-prediction modes by a factor of 2. The dotted lines in FIG. 5 denote the angular modes, which are introduced in the JEM software.

(6) For the JEM-3.0 software, a new partitioning mechanism based on both quad-tree and binary-tree (known as QTBT) was proposed. The fundamental difference between the QT and QTBT partitioning mechanisms is that the latter one enables not only square but also rectangular blocks by using partitioning based on both quad- and binary-tree. FIG. 6 illustrates an example of block partitioning and a corresponding tree structure by using QTBT, wherein solid lines denote quad-tree partitioning and dashed lines denote binary-tree partitioning. In each partitioning node of the binary-tree, the partitioning type is indicated by 0 (horizontal partitioning) or 1 (vertical partitioning).

(7) Some signaling overhead and increased computational complexity at the encoder side are the price of the QTBT partitioning as compared to conventional quad-tree based partitioning used in the HEVC/H.265 standard. Nevertheless, the QTBT-based partitioning is endowed with better segmentation properties and demonstrates significantly higher coding efficiency than the conventional quad-tree ("EE2.1: Quadtree plus binary tree structure integration with JEM tools," Contribution JVET-C00024 to the 3.sup.rd JVET meeting, Geneva, Switzerland, May 2016 by Han Huang, Kai Zhang, Yu-Wen Huang, Shawmin Lei). However, the QTBT partitioning has a critical problem: a set of available directional intra-prediction modes has not been changed accordingly. Thus, the asymmetry nature of rectangular blocks utilized by the QTBT framework has not been taken into account, as shown in FIG. 7, i.e., the same number of reference samples are used along both shorter and longer sides of rectangular blocks. Therefore, the number of directional intra-prediction modes depends on neither aspect ratio of blocks nor actual availability of reference samples in the current implementation of the QTBT framework.

(8) In light of the above, there is a need for apparatuses and methods for video coding, which allow for an efficient handling of rectangular video coding blocks.

SUMMARY

(9) It is an object to provide apparatuses and methods for video coding, which allow for an efficient handling of rectangular video coding blocks in conjunction with a directional intra-prediction

mechanism.

(10) The foregoing and other objects are achieved by the subject matter of the independent claims. Further implementation forms are apparent from the dependent claims, the description and the figures.

(11) The following disclosure employs a plurality of terms which, in embodiments, have the following meaning: Slice—a spatially distinct region of a picture that is independently encoded/decoded. Slice header—Data structure configured to signal information associated with a particular slice. Video coding block (or short block)—an $M \times N$ (M -column by N -row) array of pixels or samples (each pixel/sample being associated with at least one pixel/sample value), or an $M \times N$ array of transform coefficients. Coding Tree Unit (CTU) grid—a grid structure employed to partition blocks of pixels into macro-blocks for video encoding. Coding Unit (CU)—a coding block of luma samples, two corresponding coding blocks of chroma samples of an image that has three sample arrays, or a coding block of samples of a monochrome picture or a picture that is coded using three separate color planes and syntax used to code the samples. Picture Parameter Set (PPS)—a syntax structure containing syntax elements that apply to zero or more entire coded pictures as determined by a syntax element found in each slice segment header. Sequence Parameter Set (SPS)—a syntax structure containing syntax elements that apply to zero or more entire coded video sequences as determined by the content of a syntax element found in the PPS referred to by a syntax element found in each slice segment header. Video Parameter Set (VPS)—a syntax structure containing syntax elements that apply to zero or more entire coded video sequences. Prediction Unit (PU)—a prediction block of luma samples, two corresponding prediction blocks of chroma samples of a picture that has three sample arrays, or a prediction block of samples of a monochrome picture or a picture that is coded using three separate color planes and syntax used to predict the prediction block samples. Transform Unit (TU)—a transform block of luma samples, two corresponding transform blocks of chroma samples of a picture that has three sample arrays, or a transform block of samples of a monochrome picture or a picture that is coded using three separate color planes and syntax used to predict the transform block samples. Supplemental enhancement information (SEI)—extra information that may be inserted into a video bit-stream to enhance the use of the video. Luma—information indicating the brightness of an image sample. Chroma—information indicating the color of an image sample, which may be described in terms of red difference chroma component (Cr) and blue difference chroma component (Cb).

(12) Generally, the present disclosure relates to an apparatus and a method for improving the directional intra-prediction mechanism within the QTBT framework. More specifically, the present disclosure extends a set of available directional intra-prediction modes subject to the aspect ratio of a block to be predicted, enables or disables some directional intra-prediction modes subject to the availability of reference samples, signals directional intra-prediction modes contained in the extended subset via mode mapping and a one-bit flag.

(13) Embodiments of the present disclosure provide, amongst others, the following advantages: additional coding gain after integrating this technique into a codec, extensive applications in hybrid video coding paradigms compatible with the HM software and the VPX video codec family as well as in the state-of-the-art and next-generation video coding frameworks (the JEM software and VPX/AV1 video codec family respectively), low hardware and computational complexities at both encoder and decoder sides, easy implementation in such codecs that use conventional directional intra-prediction mechanisms.

(14) According to a first aspect, the disclosure relates to an intra-prediction apparatus for extending a set of predetermined directional intra-prediction modes of a rectangular video coding block, each predetermined directional intra-prediction mode of the set of predetermined directional intra-prediction modes being associated with a predetermined direction within a predetermined directional range, the intra-prediction apparatus comprising an aspect ratio determining unit configured to determine a width and a height of the video coding block, and to determine an aspect ratio of the rectangular video coding block on the basis of the width and the height, a complementary angle range determining unit configured to determine a complementary angle range (α) upon the basis of the aspect ratio of the rectangular video coding block, the complementary angle range (α) being associated with a complementary directional range different from the predetermined directional range, a directional intra-prediction mode extending unit configured to select a complementary direction within the complementary directional range, and to add an extension directional intra-prediction mode being associated with the complementary direction to

the set of predetermined directional intra-prediction modes, and an intra-prediction unit configured to intra-predict pixel values of pixels of the rectangular video coding block on the basis of the extension directional intra-prediction mode.

(15) In this regard, the term “direction” refers to an orientation within the video coding block to be used for directional intra-prediction within the video coding block. The term “directional range” refers to range covering a plurality of said directions.

(16) In a first implementation form of the intra-prediction apparatus according to the first aspect as such, the complementary angle range determining unit is configured to determine the complementary angle range (α) upon the basis of the following equation:

$$(17) \quad \alpha = \frac{\pi}{4} - \arctan\left(\frac{L_{\text{shorter}}}{L_{\text{longer}}}\right)$$

wherein α denotes the complementary angle range, and $L_{\text{sub.shorter}}/L_{\text{sub.longer}}$ denotes the aspect ratio of the rectangular video coding block.

(18) In a second implementation form of the intra-prediction apparatus according to the first implementation form of the first aspect, $L_{\text{sub.shorter}}$ represents the width of the rectangular video coding block and $L_{\text{sub.longer}}$ represents the height of the rectangular video coding block in a vertical orientation of the rectangular video coding block, or $L_{\text{sub.shorter}}$ represents the height of the rectangular video coding block and $L_{\text{sub.longer}}$ represents the width of the rectangular video coding block in a horizontal orientation of the rectangular video coding block.

(19) In a third implementation form of the intra-prediction apparatus according to the first aspect as such or any preceding implementation form of the first aspect, the directional intra-prediction mode extending unit is further configured to select a further complementary direction within the complementary directional range, and to add a further extension directional intra-prediction mode being associated with the further complementary direction to the set of predetermined directional intra-prediction modes.

(20) In a fourth implementation form of the intra-prediction apparatus according to the third implementation form of the first aspect, the complementary direction of the extension directional intra-prediction mode and the further complementary direction of the further extension directional intra-prediction mode differ by a predetermined angle step (s).

(21) In a fifth implementation form of the intra-prediction apparatus according to the fourth implementation form of the first aspect, the predetermined angle step (s) is given by the following equation:

$$(22) \quad s = \frac{\pi}{64}$$

wherein s denotes the predetermined angle step.

(23) In a sixth implementation form of the intra-prediction apparatus according to the first aspect as such or any preceding implementation form of the first aspect, the intra-prediction apparatus further comprises a directional intra-prediction mode removing unit configured to select a directional intra-prediction mode within the set of predetermined directional intra-prediction modes, the selected directional intra-prediction mode being associated with a direction opposite to the complementary directional range, and to remove the selected directional intra-prediction mode from the set of predetermined directional intra-prediction modes.

(24) In a seventh implementation form of the intra-prediction apparatus according to the first aspect as such or any preceding implementation form of the first aspect, the complementary directional range and the predetermined directional range are adjacent.

(25) In an eighth implementation form of the intra-prediction apparatus according to the first aspect as such or any preceding implementation form of the first aspect, the rectangular video coding block is a coding unit (CU), a prediction unit (PU), or a transform unit (TU).

(26) According to a second aspect, the disclosure relates to an encoding apparatus for encoding a rectangular video coding block, the encoding apparatus comprising an intra-prediction apparatus according to the first aspect as such or any implementation form of the first aspect for providing a predicted rectangular video coding block, and an encoding unit configured to encode the rectangular video coding block on the basis of the predicted rectangular video coding block.

(27) According to a third aspect, the disclosure relates to a decoding apparatus for decoding an encoded rectangular video coding block, the decoding apparatus comprising an intra-prediction apparatus

according to the first aspect as such or any implementation form of the first aspect for providing a predicted rectangular video coding block, and a restoration unit configured to restore a rectangular video coding block on the basis of the encoded rectangular video coding block and the predicted rectangular video coding block.

(28) According to a fourth aspect, the disclosure relates to an intra-prediction method for extending a set of predetermined directional intra-prediction modes of a rectangular video coding block, each predetermined directional intra-prediction mode of the set of predetermined directional intra-prediction modes being associated with a predetermined direction within a predetermined directional range, the intra-prediction method comprising determining a width and a height of the video coding block, determining an aspect ratio of the rectangular video coding block on the basis of the width and the height, determining a complementary angle range (α) upon the basis of the aspect ratio of the rectangular video coding block, the complementary angle range (α) being associated with a complementary directional range different from the predetermined directional range, selecting a complementary direction within the complementary directional range, adding an extension directional intra-prediction mode being associated with the complementary direction to the set of predetermined directional intra-prediction modes, and intra-predicting pixel values of pixels of the rectangular video coding block on the basis of the extension directional intra-prediction mode.

(29) In a first implementation form of the intra-prediction method according to the fourth aspect as such, the intra-prediction method further comprises selecting a directional intra-prediction mode within the set of predetermined directional intra-prediction modes, the selected directional intra-prediction mode being associated with a direction opposite to the complementary directional range, and removing the selected directional intra-prediction mode from the set of predetermined directional intra-prediction modes.

(30) The intra-prediction method can be performed by the intra-prediction apparatus. Further features of the intra-prediction method directly result from the features or the functionality of the intra-prediction apparatus.

(31) According to a fifth aspect, the disclosure relates to a computer program comprising a program code for performing the method of the fourth aspect as such or any implementation form of the fourth aspect when executed on a computer.

(32) The invention can be implemented in hardware and/or software.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Further embodiments of the invention will be described with respect to the following figures, wherein:

(2) FIG. 1 shows a schematic diagram of an intra-prediction apparatus for extending a set of predetermined directional intra-prediction modes of a rectangular video coding block;

(3) FIG. 2 shows a schematic diagram of an encoding apparatus for encoding a rectangular video coding block;

(4) FIG. 3 shows a schematic diagram of a decoding apparatus for decoding an encoded rectangular video coding block;

(5) FIG. 4 shows a schematic diagram of an intra-prediction method for extending a set of predetermined directional intra-prediction modes of a rectangular video coding block;

(6) FIG. 5 shows a schematic diagram of a video coding block illustrating different directional intra-prediction modes;

(7) FIGS. 6(a) and 6(b) illustrate an example of block partitioning and a corresponding tree structure by using quad-tree plus binary-tree (QTBT);

(8) FIGS. 7(a) and 7(b) illustrate implementations of a directional intra-prediction mechanism in quad-tree (QT) and quad-tree plus binary-tree (QTBT) frameworks, respectively;

(9) FIGS. 8(a) and 8(b) illustrate an extension of a set of predetermined directional intra-prediction modes subject to an aspect ratio of a given rectangular video coding block;

(10) FIG. 9 shows a schematic diagram illustrating an extension of a set of predetermined directional

intra-prediction modes subject to an aspect ratio of a given rectangular video coding block;

(11) FIG. **10** shows a schematic diagram illustrating a preservation of a cardinality of directional intra-prediction modes subject to an aspect ratio of a given rectangular video coding block;

(12) FIG. **11** illustrates an example of block partitioning and a corresponding tree structure by using quad-tree plus binary-tree (QTBT), wherein the number of available reference samples along a longer side is less than its double length in a rectangular video coding block;

(13) FIG. **12** illustrates enabling or disabling a set of predetermined directional intra-prediction modes subject to an availability of reference samples of a given rectangular video coding block;

(14) FIG. **13** illustrates a first step of a signaling mechanism for extension of directional intra-prediction modes;

(15) FIG. **14** illustrates a second step of a signaling mechanism for extension of directional intra-prediction modes;

(16) FIG. **15** illustrates a decoding process for a directional intra mode index by applying a signaling mechanism;

(17) FIG. **16** shows a schematic diagram illustrating an implementation of a signaling mechanism applied in an encoding apparatus;

(18) FIG. **17** shows a schematic diagram illustrating an implementation of a signaling mechanism applied in a decoding apparatus;

(19) FIGS. **18(a)** and **18(b)** show schematic diagrams illustrating implementations of a signaling mechanism applied to the Enhanced Intra-Prediction (EIP) mechanism; and

(20) FIG. **19** shows a schematic diagram of an encoding apparatus for encoding a rectangular video coding block comprising an intra-prediction apparatus.

(21) In the various figures, identical reference signs will be used for identical or at least functionally equivalent features.

DETAILED DESCRIPTION OF EMBODIMENTS

(22) In the following description, reference is made to the accompanying drawings, which form part of the disclosure, and in which are shown, by way of illustration, specific aspects in which embodiments of the present invention may be placed. It is understood that other aspects may be utilized and structural or logical changes may be made without departing from the scope of the present invention. The following detailed description, therefore, is not to be taken in a limiting sense, as the scope of the present invention is defined by the appended claims.

(23) For instance, it is understood that a disclosure in connection with a described method may also hold true for a corresponding device or system configured to perform the method and vice versa. For example, if a specific method step is described, a corresponding device may include a unit to perform the described method step, even if such unit is not explicitly described or illustrated in the figures. Further, it is understood that the features of the various exemplary aspects described herein may be combined with each other, unless specifically noted otherwise.

(24) FIG. **1** shows a schematic diagram of an intra-prediction apparatus **100** for extending a set of predetermined directional intra-prediction modes of a rectangular video coding block. Each predetermined directional intra-prediction mode of the set of predetermined directional intra-prediction modes is associated with a predetermined direction within a predetermined directional range. The intra-prediction apparatus **100** comprises an aspect ratio determining unit **101** configured to determine a width and a height of the video coding block, and to determine an aspect ratio of the rectangular video coding block on the basis of the width and the height, a complementary angle range determining unit **103** configured to determine a complementary angle range (α) upon the basis of the aspect ratio of the rectangular video coding block, the complementary angle range (α) being associated with a complementary directional range different from the predetermined directional range, a directional intra-prediction mode extending unit **105** configured to select a complementary direction within the complementary directional range, and to add an extension directional intra-prediction mode being associated with the complementary direction to the set of predetermined directional intra-prediction modes, and an intra-prediction unit **107** configured to intra-predict pixel values of pixels of the rectangular video coding block on the basis of the extension directional intra-prediction mode.

(25) FIG. **2** shows a schematic diagram of an encoding apparatus **200** for encoding a rectangular video

coding block. The decoding apparatus **200** comprises an intra-prediction apparatus **100** for providing a predicted rectangular video coding block, and an encoding unit **201** configured to encode the rectangular video coding block on the basis of the predicted rectangular video coding block.

(26) FIG. **3** shows a schematic diagram of a decoding apparatus **300** for decoding an encoded rectangular video coding block. The decoding apparatus **300** comprises an intra-prediction apparatus **100** for providing a predicted rectangular video coding block, and a restoration unit **301** configured to restore a rectangular video coding block on the basis of the encoded rectangular video coding block and the predicted rectangular video coding block.

(27) FIG. **4** shows a schematic diagram of an intra-prediction method **400** for extending a set of predetermined directional intra-prediction modes of a rectangular video coding block. Each predetermined directional intra-prediction mode of the set of predetermined directional intra-prediction modes is associated with a predetermined direction within a predetermined directional range. The intra-prediction method **400** comprises determining **401** a width and a height of the video coding block, determining **403** an aspect ratio of the rectangular video coding block on the basis of the width and the height, determining **405** a complementary angle range (α) upon the basis of the aspect ratio of the rectangular video coding block, the complementary angle range (α) being associated with a complementary directional range different from the predetermined directional range, selecting **407** a complementary direction within the complementary directional range, adding **409** an extension directional intra-prediction mode being associated with the complementary direction to the set of predetermined directional intra-prediction modes, and intra-predicting **411** pixel values of pixels of the rectangular video coding block on the basis of the extension directional intra-prediction mode.

(28) FIG. **5** shows a schematic diagram of a video coding block illustrating different directional intra-prediction modes. The intra prediction modes as shown in FIG. **5** include a planar mode (the intra-prediction mode index is 0), DC mode (the intra-prediction mode index is 1), and 33 directional modes (the intra-prediction mode index ranges from 2 to 34, indicated by the solid lines). The set of directional intra-prediction modes was extended up to 65 modes (almost doubled) by decreasing a step angle between directional intra-prediction modes by a factor of 2. The dotted lines in FIG. **5** denote the angular modes, which are introduced in the JEM software.

(29) FIGS. **6a** and **6b** illustrate an example of block partitioning and a corresponding tree structure by using quad-tree plus binary-tree (QTBT), wherein solid lines denote quad-tree partitioning and dashed lines denote binary-tree partitioning. In each partitioning node of the binary-tree, the partitioning type is indicated by 0 (horizontal partitioning) or 1 (vertical partitioning).

(30) FIGS. **7a** and **7b** illustrate implementations of a directional intra-prediction mechanism in quad-tree (QT) and quad-tree plus binary-tree (QTBT) frameworks, respectively. Here, the same number of reference samples are used along both shorter and longer sides of rectangular blocks. Therefore, the number of directional intra-prediction modes depends on neither aspect ratio of blocks nor actual availability of reference samples in the current implementation of the QTBT framework.

(31) FIGS. **8a** and **8b** illustrate an extension of a set of predetermined directional intra-prediction modes subject to an aspect ratio of a given rectangular video coding block. As shown in FIG. **8a**, an aspect ratio of a square video coding block is 1:1 and a set of conventional directional intra-prediction modes is used for predicting values of a video coding block being reconstructed. On the other hand, a rectangular video coding block comprises shorter and longer sides, and such asymmetry can be used to improve the current directional intra-prediction mechanism by increasing its prediction accuracy. As illustrated in FIG. **8b**, the number of available directional intra-prediction modes can be increased along a long side.

(32) FIG. **9** shows a schematic diagram illustrating an extension of a set of predetermined directional intra-prediction modes subject to an aspect ratio of a given rectangular video coding block. The corresponding processing steps may be implemented by the intra-prediction apparatus **100** and/or the intra-prediction method **400**. In FIG. **9**, square pixels represent reference samples for intra-prediction, wherein the order of probabilities that the reference samples are available is: reference pixel with dots>reference pixel with stripes>reference pixel with diagonal stripes.

(33) The number of the newly introduced directional intra-prediction modes may depend on the aspect ratio of the rectangular video coding block. The angle that encompasses these new modes is defined by the following formula:

$$(34) \quad = \frac{1}{4} - \arctan\left(\frac{L_{\text{shorter}}}{L_{\text{longer}}}\right)$$

wherein L.sub.shorter and L.sub.longer are the lengths of the shorter and longer sides of the rectangular video coding block, respectively. As illustrated in FIG. 9, L.sub.shorter=width and L.sub.longer=height for a vertical orientation of the rectangular video coding block. The actual number of these modes may depend on the angle between neighbor directional modes and the angle α defined by the above formula.

(35) In the up-to-date version of the JEM software (version JEM-4.0), the average angle step between neighbor directional modes defined by an intra-prediction interpolation filter does not depend on the block size and equals:

$$(36) \quad S = \frac{\pi}{64}$$

(37) Thus, in the case of uniformly spaced directional intra-prediction modes, the number N of the newly introduced modes equals:

$$(38) \quad N = \left\lfloor \frac{\pi}{S} \right\rfloor = 16 - \left\lfloor 64 \arctan\left(\frac{L_{\text{shorter}}}{L_{\text{longer}}}\right) \right\rfloor$$

wherein $\lfloor \cdot \rfloor$ is a floor operation.

(39) In the embodiment shown in FIG. 9, the number of reference samples is extended along the longer side, and it is not reduced for the shorter side. Therefore, the amount of intra-prediction modes that are available along the longer side (the angle that encompasses these modes is marked by a solid line) is increased, but the number of intra-prediction modes that are available along the shorter side (the angle that encompasses these modes is marked by a dashed line) is not decreased. Hence, the cardinality of the intra-prediction mode set is only increased while the aspect ratio

$$(40) \quad R_{\text{asp}} = \frac{L_{\text{shorter}}}{L_{\text{longer}}}$$

is decreasing. On the other hand, another approach to preserve the original number of directional intra-prediction modes is also possible according to another embodiment.

(41) FIG. 10 shows a schematic diagram illustrating a preservation of a cardinality of directional intra-prediction modes subject to an aspect ratio of a given rectangular video coding block. As shown in FIG. 10, the amount of the directional intra-prediction modes added along the longer side (the angle that encompasses these modes is marked by a solid line) may be equal to the amount of the directional intra-prediction modes removed along the shorter side (the angle that encompasses these modes is marked by a dashed line). Thus, the cardinality of the intra-prediction mode set remains the same as for square blocks. According to an embodiment, whether to extend a set of available intra-prediction modes or not can also depend on the availability of reference samples because they are needed to generate an intra-predictor.

(42) FIG. 11 illustrates an example of block partitioning and a corresponding tree structure by using quad-tree plus binary-tree (QTBT), wherein the number of available reference samples along a longer side is less than its double length in a rectangular video coding block. As shown in FIG. 11, the quad-tree plus binary-tree (QTBT) partitioning framework produces a partitioning, wherein the actual number of available reference samples along a longer side is less than its double length as assumed in the above examples in FIGS. 9 and 10. Therefore, the approach for increasing the number of the directional intra-prediction modes in the above examples may need to be adjusted according to an availability of reference samples for the case of FIG. 11.

(43) FIG. 12 illustrates enabling or disabling a set of predetermined directional intra-prediction modes subject to an availability of reference samples of a given rectangular video coding block within the quad-tree plus binary-tree (QTBT) partitioning framework, wherein a grey rectangle area represents a currently processed video coding block, square pixels with diagonal stripes indicate available reference samples, and square pixels with dots indicate unavailable reference samples.

(44) A fractional non-prediction area P of a rectangular video coding block generated using interpolated reference samples may be calculated as follows:

$$(45) \quad P_{\text{area}} = \frac{S_{\text{uncov}}}{S_{\text{block}}} = \frac{S_{\text{uncov}}}{L_{\text{shorter}} \cdot \text{Math.} L_{\text{longer}}} = \frac{L_{\text{shorter}}^2 \cdot \text{Math.} \tan \frac{\alpha}{2}}{2 \cdot \text{Math.} L_{\text{shorter}} \cdot \text{Math.} L_{\text{longer}}} = \frac{L_{\text{shorter}} \cdot \text{Math.} \tan \frac{\alpha}{2}}{2 \cdot \text{Math.} L_{\text{longer}}} = \frac{L_{\text{shorter}}}{L_{\text{longer}}} \cdot \text{Math.} \frac{\tan \frac{\alpha}{2}}{2} = R_{\text{asp}} \cdot \text{Math.} \frac{\tan \frac{\alpha}{2}}{2}$$

wherein L.sub.longer and L.sub.shorter are the lengths of the longer and shorted sides of a rectangular video coding block, respectively, α is the angle of a given directional intra-prediction mode belonging to the extended set, S.sub.block=L.sub.shorter.Math.L.sub.longer is the area of a rectangular video coding

block to be predicted,

$$(46) S_{\text{uncov}} = \frac{L_{\text{shorter}}^2 \cdot \text{Math. tan}}{2}$$

is the non-prediction area, i.e. the area of the video coding block that may not be predicted using non-interpolated reference samples, as marked by stripes.

(47) Therefore, the closer an intra-prediction direction is located to the diagonal marked by a dashed line, the larger part of an area that remains may not be predicted using non-interpolated reference samples. In an example, the set of directional intra-prediction modes is not extended if the length $L_{\text{sub.RSlonger}}$ of non-interpolated reference samples along the longer side is less than the double length of the longer side: $L_{\text{sub.RSlonger}} < 2 L_{\text{sub.longer}}$

(48) If a set of directional intra-prediction modes is extended, it is desirable to signal the newly extended modes, which may not be accomplished using existing conventional mechanisms. For this purpose, a 2-step signaling mechanism for the extension of directional intra-prediction modes is proposed and explained in FIGS. 13 and 14.

(49) FIG. 13 illustrates a first step of a signaling mechanism for extension of directional intra-prediction modes, wherein a set of extended modes is mapped to a conventional set of intra prediction modes using a mirroring procedure.

(50) FIG. 14 illustrates a second step of a signaling mechanism for extension of directional intra-prediction modes, wherein in a one-bit flag is used to distinguish between conventional and extended directional modes. The flag is assigned a value “0” for a conventional mode and “1” for an extended mode. Furthermore, the flag in the signaling mechanism is used only for those directional modes that are reflections of extended ones.

(51) FIG. 15 illustrates a decoding process for a directional intra mode index by applying a signaling mechanism. As shown in FIG. 15, the extended modes of the directional intra-prediction are flagged with “1”, the conventional modes having a mapped mode are flagged with “0”, and the other modes have no additional signaling value.

(52) FIG. 16 shows a schematic diagram illustrating an implementation of a signaling mechanism applied in an encoding apparatus. In a first processing step **1601** the index of the intra-prediction mode $I_{\text{sub.IPM}}$ is parsed from the bitstream. Thereafter, in processing step **1603** a decision is taken depending on whether the decoded intra-prediction mode is a directional intra prediction mode. In the case the signaling scheme is applied in the context of HEVC video coding, the intra-prediction mode is directional when $I_{\text{sub.IPM}}$ is greater than 1. If the intra-prediction mode is directional, in processing step **1605** a decision is taken depending on whether the decoded intra-prediction mode is extended. The decoded intra-prediction mode is extended when $I_{\text{sub.IPM}}$ is greater than $Q[\pi/2 + \arctan(\text{Width}/\text{Height})]$ and smaller than VDIAG_IDX , wherein Width and Height are the lengths of short and long sides of a rectangular video coding block being decoded, and VDIAG_IDX is equal to 66 according to embodiments of the invention. Then, the flag “ext_dir_mode_flag” is assigned to a value of 0 for the conventional modes which can have mapped extended code (see processing steps **1607**, **1609**). A rate-distortion cost (RD-cost) is estimated for the conventional modes in processing step **1611**. The flag “ext_dir_mode_flag” is assigned to a value of 1 for the extended modes (see processing steps **1613**, **1615**). A rate-distortion cost (RD-cost) for the conventional modes is estimated in processing step **1617**. The flag “ext_dir_mode_flag” is determined by finding the lowest rate-distortion cost (RD-cost) between the conventional modes and extended modes in processing step **1619**.

(53) FIG. 17 shows a schematic diagram illustrating an implementation of a signaling mechanism applied in a decoding apparatus. In a first processing step **1701** the index of the intra-prediction mode k_m is parsed from the bitstream. Thereafter, in processing step **1703** a decision is taken depending on whether the decoded intra prediction mode is a directional intra prediction mode. In the case the signaling scheme is applied in the context of HEVC video coding, the intra prediction mode is directional when $I_{\text{sub.IPM}}$ is greater than 1. If the intra-prediction mode is directional, in processing step **1705** a decision is taken depending on whether the decoded intra-prediction mode is extended. The decoded intra-prediction mode is extended when $I_{\text{sub.IPM}}$ is greater than $Q[\pi/2 + \arctan(\text{Width}/\text{Height})]$ and smaller than VDIAG_IDX , wherein Width and Height are the lengths of short and long sides of a rectangular block being decoded, and VDIAG_IDX is equal to 66 according to embodiments of the

invention. For extended directional intra-prediction modes the value of the flag “ext_dir_mode_flag” is parsed from the bitstream in processing step **1707**. According to embodiments of the invention this flag is introduced into the bitstream to code whether to apply the proposed mechanism to the prediction unit. In processing step **1709**, a decision is taken to use either the extended prediction scheme if ext_dir_mode_flag is equal to 1 (processing step **1711a**) or the conventional prediction if ext_dir_mode_flag is not equal to 1 (processing step **1711b**), as provided by embodiments of the invention, for obtaining the predicted signal. The decision in processing step **1709** is taken on the basis of the value of the flag “ext_dir_mode_flag”, which has been determined in processing step **1707**.

(54) The signaling mechanism is applicable to a wider spectrum of cases according to embodiments of the invention. For examples, it can be used to reduce a signaling overhead caused by an extended set of directional intra-prediction modes used in Enhanced Intra-Prediction (EIP) technique proposed by Google for its VPX codec family. This EIP technique is needed to improve the compression efficiency of intra-predicted blocks within inter-predicted pictures. EIP is a two-pass mechanism for increasing the number of available prediction directions, wherein blocks with good inter-prediction modes are initially encoded, and then intra blocks with access to more boundaries are filled in.

(55) FIGS. **18a** and **18b** show schematic diagrams illustrating implementations of a signaling mechanism applied to the Enhanced Intra-Prediction (EIP) mechanism. In the cases shown in FIGS. **18a** and **18b**, 4 (2π) and 3 ($3\pi/2$) sides of a video coding block are available for directional intra-prediction, respectively. Solid lines denote directions from a main angle and dashed lines denote directions from a complimentary angle. In both cases, the set of available intra-prediction modes is more than for a conventional case.

(56) As described above, the same 2-step signaling mechanism can be conducted to signal what angle the selected directional intra-prediction mode belongs to by using a one-bit flag. Firstly, a directional mode can be mapped onto the main angle if the directional mode is selected from the complementary angle. Secondly, the one-bit flag can be set to “ON” if the direction is selected from the complementary angle; otherwise, the flag can be set to “OFF”.

(57) FIG. **19** shows a schematic diagram of an encoding apparatus **200** for encoding a rectangular video coding block comprising an intra-prediction apparatus **100**. A decoding apparatus **300** can be implemented analogously.

(58) While a particular feature or aspect of the disclosure may have been disclosed with respect to only one of several implementations or embodiments, such a feature or aspect may be combined with one or more further features or aspects of the other implementations or embodiments as may be desired or advantageous for any given or particular application. Furthermore, to the extent that the terms “include”, “have”, “with”, or other variants thereof are used in either the detailed description or the claims, such terms are intended to be inclusive in a manner similar to the term “comprise”. Also, the terms “exemplary”, “for example” and “e.g.” are merely meant as an example, rather than the best or optimal. The terms “coupled” and “connected”, along with derivatives thereof may have been used. It should be understood that these terms may have been used to indicate that two elements cooperate or interact with each other regardless whether they are in direct physical or electrical contact, or they are not in direct contact with each other.

(59) Although specific aspects have been illustrated and described herein, it will be appreciated that a variety of alternate and/or equivalent implementations may be substituted for the specific aspects shown and described without departing from the scope of the present disclosure. This application is intended to cover any adaptations or variations of the specific aspects discussed herein.

(60) Although the elements in the following claims are recited in a particular sequence with corresponding labeling, unless the claim recitations otherwise imply a particular sequence for implementing some or all of those elements, those elements are not necessarily intended to be limited to being implemented in that particular sequence.

(61) Many alternatives, modifications, and variations will be apparent to those skilled in the art in light of the above teachings. Of course, those skilled in the art readily recognize that there are numerous applications of the invention beyond those described herein. While the present invention has been described with reference to one or more particular embodiments, those skilled in the art recognize that many changes may be made thereto without departing from the scope of the present invention. It is

therefore to be understood that within the scope of the appended claims and their equivalents, the invention may be practiced otherwise than as specifically described herein.

Claims

1. An intra prediction method for a rectangular video coding block, wherein the method is applied to an intra prediction apparatus and the method comprises: parsing a bitstream to obtain a predetermined directional intra-prediction mode, the predetermined directional intra-prediction modes being associated with a predetermined direction within a predetermined directional range; determining a width and a height of the rectangular video coding block as a coding unit (CU); determining an aspect ratio of the rectangular video coding block based on the width and the height in luma samples, wherein the rectangular video coding block includes a non-square luma coding block; determining an extension directional luma intra-prediction mode based on the aspect ratio of the rectangular video coding block and the predetermined directional intra-prediction mode; and intra-predicting pixel values of luma pixels of the rectangular video coding block based on the extension directional luma intra-prediction mode.
2. The method of claim 1, wherein an index of the extension directional luma intra-prediction mode is different from an index of each predetermined directional intra-prediction mode within the predetermined directional range.
3. The method of claim 1, wherein the extension directional luma intra-prediction mode is within a complementary angle range, and wherein the complementary angle range is different from an angle range corresponding to the predetermined directional range.
4. The method of claim 1, wherein an amount of directional intra-prediction modes is increased along a longer side of the rectangular video coding block.
5. The method of claim 4, wherein the amount of the directional intra-prediction modes added along the longer side is equal to an amount of directional intra-prediction modes removed along a shorter side of the rectangular video coding block.
6. The method of claim 1, wherein $L_{\text{sub.shorter}}/L_{\text{sub.longer}}$ denotes the aspect ratio of the rectangular video coding block in luma samples, wherein $L_{\text{sub.shorter}}$ represents the width of the rectangular video coding block and $L_{\text{sub.longer}}$ represents the height of the rectangular video coding block in a vertical orientation of the rectangular video coding block, or wherein $L_{\text{sub.shorter}}$ represents the height of the rectangular video coding block and $L_{\text{sub.longer}}$ represents the width of the rectangular video coding block in a horizontal orientation of the rectangular video coding block.
7. An intra prediction apparatus for a rectangular video coding block, the intra prediction apparatus comprising: a non-transitory computer-readable storage medium storing instructions; and one or more processors in communication with the medium and, upon execution of the instructions, configured to: parse a bitstream to obtain a predetermined directional intra-prediction mode, the predetermined directional intra-prediction modes being associated with a predetermined direction within a predetermined directional range; determine a width and a height of the rectangular video coding block as a coding unit (CU); determine an aspect ratio of the rectangular video coding block based on the width and the height in luma samples, wherein the rectangular video coding block includes a non-square luma coding block; determine an extension directional luma intra-prediction mode based on the aspect ratio of the rectangular video coding block and the predetermined directional intra-prediction mode; and intra-predict pixel values of luma pixels of the rectangular video coding block based on the extension directional luma intra-prediction mode.
8. The apparatus of claim 7, wherein an index of the extension directional luma intra-prediction mode is different from an index of each predetermined directional intra-prediction mode within the predetermined directional range.
9. The apparatus of claim 7, wherein the extension directional luma intra-prediction mode is within a complementary angle range, and wherein the complementary angle range is different from an angle range corresponding to the predetermined directional range.
10. The apparatus of claim 7, wherein an amount of directional intra-prediction modes is increased along a longer side of the rectangular video coding block.

11. The apparatus of claim 10, wherein the amount of the directional intra-prediction modes added along the longer side is equal to an amount of directional intra-prediction modes removed along a shorter side of the rectangular video coding block.

12. The apparatus of claim 7, wherein $L_{sub.shorter}/L_{sub.longer}$ denotes the aspect ratio of the rectangular video coding block in luma samples, wherein $L_{sub.shorter}$ represents the width of the rectangular video coding block and $L_{sub.longer}$ represents the height of the rectangular video coding block in a vertical orientation of the rectangular video coding block, or wherein $L_{sub.shorter}$ represents the height of the rectangular video coding block and $L_{sub.longer}$ represents the width of the rectangular video coding block in a horizontal orientation of the rectangular video coding block.

13. A non-transitory computer readable medium comprising a program code, which when executed on a computer, cause the computer to carry out operations of: parsing a bitstream to obtain a predetermined directional intra-prediction mode, the predetermined directional intra-prediction modes being associated with a predetermined direction within a predetermined directional range; determining a width and a height of the rectangular video coding block as a coding unit (CU); determining an aspect ratio of the rectangular video coding block based on the width and the height in luma samples, wherein the rectangular video coding block includes a non-square luma coding block; determining an extension directional luma intra-prediction mode based on the aspect ratio of the rectangular video coding block and the predetermined directional intra-prediction mode; and intra-predicting pixel values of luma pixels of the rectangular video coding block based on the extension directional luma intra-prediction mode.

14. The non-transitory computer readable medium of claim 13, wherein an index of the extension directional luma intra-prediction mode is different from an index of each predetermined directional intra-prediction mode within the predetermined directional range.

15. The non-transitory computer readable medium of claim 13, wherein the extension directional luma intra-prediction mode is within a complementary angle range, and wherein the complementary angle range is different from an angle range corresponding to the predetermined directional range.

16. The non-transitory computer readable medium of claim 13, wherein an amount of directional intra-prediction modes is increased along a longer side of the rectangular video coding block.

17. The non-transitory computer readable medium of claim 13, wherein $L_{sub.shorter}/L_{sub.longer}$ denotes the aspect ratio of the rectangular video coding block in luma samples, wherein $L_{sub.shorter}$ represents the width of the rectangular video coding block and $L_{sub.longer}$ represents the height of the rectangular video coding block in a vertical orientation of the rectangular video coding block, or wherein $L_{sub.shorter}$ represents the height of the rectangular video coding block and $L_{sub.longer}$ represents the width of the rectangular video coding block in a horizontal orientation of the rectangular video coding block.
