

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250263290

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

Fieglein; Henry et al.

DYNAMIC TOUCHSCREEN FUEL SELECTION

Abstract

Fuel dispensers, systems, and methods are provided for allowing a user to dynamically create a customized fuel blend, also referred to as a fuel mixture. In an exemplary embodiment, a fuel dispenser is provided having an interactive display, such as a touchscreen display, and a data processor that can perform operations that enable any one or more of replacing PTS buttons, integrating additive pumps to combine fuel mixtures and additives, mixing fuels and additives, calculating fuel mixture prices, and allowing a user to customize fuel mixtures. The application of the interactive display and the control module, as well as other components, can facilitate allowing a user to create customized fuel mixtures, while minimizing changes to standard communication protocol associated with components such as, e.g., a point-of-sale (POS), a forecourt controller, and a fuel controller that can control dispensing of fuel.

Inventors: Fieglein; Henry (Cedar Park, TX), Negley, III; Scott R. (Austin, TX), Morris; John Joseph (Austin, TX), Larsson; Bengt I. (Skivarp, SE), Cerovski; Thomas (Cedar Park, TX), Belt; Steve (Pflugerville, TX)

Applicant: Wayne Fueling Systems LLC (Austin, TX)

Family ID: 1000008576908

Appl. No.: 19/198336

Filed: May 05, 2025

Related U.S. Application Data

parent US continuation 15786421 20171017 ABANDONED child US 19198336
us-provisional-application US 62409076 20161017

Publication Classification

Int. Cl.: B67D7/14 (20100101); **B67D7/04** (20100101); **B67D7/08** (20100101); **B67D7/74** (20100101); **G06F3/041** (20060101); **G06F21/44** (20130101); **G06Q20/20** (20120101); **G07F13/02** (20060101); **G07G1/14** (20060101)

U.S. Cl.:

CPC B67D7/14 (20130101); **G06F3/0412** (20130101); **G06F21/44** (20130101); **G06Q20/204** (20130101); **G07F13/025** (20130101); **G07G1/14** (20130101); B67D2007/0442 (20130101); B67D7/08 (20130101); B67D2007/745 (20130101)

Background/Summary

CROSS-REFERENCE TO RELATED ACTIONS [0001] This application is a continuation application of U.S. patent application Ser. No. 15/786,421, entitled “Dynamic Touchscreen Fuel Selection,” and filed on Oct. 17, 2017 which claims priority to U.S. Provisional Application No. 62/409,076 filed on Oct. 17, 2016 and entitled “Dynamic Touchscreen Fuel Selection,” which are hereby incorporated by reference in their entireties.

FIELD

[0002] Methods, devices, and systems are provided for enabling selection and delivery of customized fuel blends in a fuel dispenser.

BACKGROUND

[0003] Typically, fuel dispensers utilize Push to Select (PTS) buttons to allow a user to select a desired fuel grade to be delivered to a vehicle. Current fuel dispensers that utilize PTS buttons include an electronics compartment and a pump compartment. The pump compartment houses a pump configured to pump fuel from a fuel tank or other reservoir, as well as one or more meters that can be configured to monitor fuel flow. The electronics compartment includes PTS buttons for selecting a desired fuel, a fuel controller for facilitating the dispensing of the fuel, and an output terminal coupled to the fuel controller for displaying a total cost and volume of fuel dispensed. The electronics compartment also includes a payment terminal that interfaces with the user for facilitating payment for fuel and other items. In some cases, the payment terminal can be separate from the fuel dispenser.

[0004] A user can provide payment information (e.g., credit card information) using the payment terminal, and payment information can be delivered via a forecourt controller to a point-of-sale (POS) system for verification. Once the payment information is verified, the POS can notify the fuel controller, which can initiate fueling. The forecourt controller can also deliver data corresponding to unit prices of available fuel grades to the fuel controller via the forecourt controller. The user can select a fuel grade using one of the PTS buttons. The PTS button sends a signal to the fuel controller, which will activate a pump to dispense the desired fuel. As fuel is dispensed, the meter(s) monitor an amount of fuel that has been dispensed, and the fuel controller calculates a running cost of the fuel based on the unit price of the selected fuel grade and the amount of fuel that has been dispensed. The fuel controller delivers data characterizing the running cost and the amount of fuel that has been dispensed to the output terminal to provide the information to the user.

[0005] PTS fuel grade selection buttons on the dispenser have several limitations related to reliability, costs, and versatility. Since PTS buttons are physical mechanical buttons with moving parts, they are subject to failure which tends to result in increased cost. Additionally, because of the physical space that a button occupies, a limited number of buttons can be present on a single fuel dispenser. A typical fuel dispenser will have three PTS buttons on one side of the dispenser for

allowing a user to select from one of three octane grades, regular (usually 87 octane), mid-grade (usually 89 octane), and premium (usually 92 or 93 octane). Some dispensers also contain an additional PTS button for an ethanol blend, and/or one or more PTS buttons for additives. Each PTS button has a static label that indicates the grade, and utilizes an electro-mechanical switch that transmits a signal to the fuel controller for activating fuel delivery. In some cases, pricing information corresponding to each fuel grade can be represented on a display that is on, or near, each PTS button. The number of buttons present on a particular dispenser will limit the selection options for a user, and can limit pricing information that can be displayed for each fuel grade.

[0006] There remains a need for improved systems and methods that enable a user to create customized fuel blends in a fuel dispenser.

SUMMARY

[0007] Fuel dispensers, systems, and methods are provided for allowing a user to dynamically create a customized fuel blend, also referred to as a fuel mixture. In one embodiment, a fuel dispenser is provided that includes a pump compartment having at least one fuel pump disposed therein and configured to dispense fuel, a fuel controller in operative communication with the pump compartment for controlling the at least one fuel pump, and a payment terminal. The payment terminal can include an interactive display that can be configured to receive input thereon to enable a user to create a customized fuel blend. The payment terminal can also include a control module that can be configured to receive data that characterizes the customized fuel blend created by the user, to obtain pricing information relating to components of the customized fuel blend, compute a unit price for the customized fuel blend using the pricing information, generate instructions for creating the customized fuel blend, and transmit the instructions to the fuel controller for dispensing the customized fuel blend.

[0008] The fuel dispenser can vary in a number of ways. For example, the interactive display can include a touchscreen. As another example, the control module can be configured to receive data characterizing payment information from the interactive display, and to deliver the data characterizing payment information to a point-of-sale system for verification. As yet another example, the control module can be configured to deliver data characterizing the unit price to the interactive display to update a graphical element of a graphical user interface rendered on the interactive display to display the unit price. In some implementations, the control module can be configured to obtain the pricing information from a point-of-sale system. In other implementations, the payment terminal can be configured to receive information from the fuel controller during the dispensing of the customized fuel blend, and to display data characterizing a current total price of the customized fuel blend dispensed.

[0009] In another aspect, a method for delivering fuel from a fuel dispenser is provided. The method can include displaying on an interactive display of a fuel dispenser at least one first graphical object for specifying a fuel blend, receiving data characterizing a user input that identifies the fuel blend, and determining instructions for creating the fuel blend based on the received data, wherein the instructions identify at least two components of the fuel blend. The method can also include computing a unit value of the fuel blend using value information related to each of the at least two components of the fuel blend, displaying on the interactive display at least one second graphical object comprising the computed unit value, and transmitting the instructions to a fuel controller of the fuel dispenser for creating the fuel blend. The fuel controller can be configured to control dispensing of the fuel blend from the fuel dispenser.

[0010] The method can vary in a number of ways. For example, the method can include obtaining the value information from a point-of-sale system. As another example, the unit value of the fuel blend can be computed by a control module of a payment terminal of the fuel dispenser. As yet another example, the method can include transmitting data characterizing the unit value of the fuel blend from a control module of a payment terminal of the fuel dispenser to the fuel controller. In some implementations, at least one of the displaying, receiving, determining, and transmitting can

be performed by at least one data processor forming part of at least one computing system. In other implementations, the instructions for creating the fuel blend can include percentages of the at least two components of the fuel blend. As another example, the at least one graphical object can include three graphical objects that represent three different fuel grades, each fuel grade having a different octane level.

[0011] In another aspect, a non-transitory computer program product that includes computer readable instructions is provided. When executed by at least one data processor forming part of at least one computing system, the computer readable instructions can implement operations including displaying on an interactive display of a fuel dispenser at least one first graphical object for specifying a fuel blend, receiving data characterizing a user input that identifies the fuel blend, and determining instructions for creating the fuel blend based on the received data, wherein the instructions identify at least two components of the fuel blend. The operations can also include computing a unit value for the fuel blend using value information related to the at least two components of the fuel blend, displaying on the interactive display at least one second graphical object for accepting the computed unit value, transmitting the instructions to a fuel controller in the fuel dispenser for creating the fuel blend. The fuel controller can be configured to control dispensing of the fuel blend from the fuel dispenser.

[0012] The non-transitory computer program can vary in a number of ways. For example, when executed, the instructions can implement operations that include obtaining the value information a point-of-sale system. As another example, the operations can include comprising transmitting data characterizing the unit value of the fuel blend to the fuel controller. As yet another example, the at least one graphical object can be three graphical objects that represent three different fuel grades, each fuel grade having a different octane level. In some implementations, the instructions for creating the fuel blend can include a percentage of the at least two components of the fuel blend. In other implementations the unit value of the fuel blend can be computed by a control module of a payment terminal of the fuel dispenser.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0013] FIG. 1A is a side perspective view of one embodiment of a fuel dispenser;

[0014] FIG. 1B is a front perspective view of the fuel dispenser shown in FIG. 1A;

[0015] FIG. 2 is a diagram showing internal components of the fuel dispenser of FIGS. 1A and 1B;

[0016] FIG. 3 is a diagram of one embodiment of data flow for dispensing fuel;

[0017] FIG. 4 is a schematic of one embodiment of a graphical user interface (GUI) for enabling a user to create a customized fuel blend;

[0018] FIG. 5 is a schematic of the GUI of FIG. 4 with a customized fuel blend created by a user; and

[0019] FIG. 6 is a schematic of another embodiment of a GUI for enabling a user to create a customized fuel blend.

DETAILED DESCRIPTION

[0020] Certain exemplary embodiments will now be described to provide an overall understanding of the principles of the structure, function, manufacture, and use of the systems, devices, and methods disclosed herein. One or more examples of these embodiments are illustrated in the accompanying drawings. Those skilled in the art will understand that the systems, devices, and methods specifically described herein and illustrated in the accompanying drawings are non-limiting exemplary embodiments and that the scope of the present invention is defined solely by the claims. The features illustrated or described in connection with one exemplary embodiment may be combined with the features of other embodiments. Such modifications and variations are

intended to be included within the scope of the present invention.

[0021] Further, in the present disclosure, like-named components of the embodiments generally have similar features, and thus within a particular embodiment each feature of each like-named component is not necessarily fully elaborated upon. Additionally, to the extent that linear or circular dimensions are used in the description of the disclosed systems, devices, and methods, such dimensions are not intended to limit the types of shapes that can be used in conjunction with such systems, devices, and methods. A person skilled in the art will recognize that an equivalent to such linear and circular dimensions can easily be determined for any geometric shape.

[0022] Fuel dispensers, systems, and methods are provided for allowing a user to dynamically create a customized fuel blend, also referred to as a fuel mixture. In an exemplary embodiment, a fuel dispenser is provided having an interactive display, such as a touchscreen display, and a control module that can perform operations that enable any one or more of replacing PTS buttons, integrating additive pumps to combine fuel mixtures and additives, mixing fuels and additives, calculating fuel mixture prices, and allowing a user to customize fuel mixtures.

[0023] As explained above, current fuel dispensers that utilize Push to Select (PTS) buttons to allow a user to select a desired fuel grade have several limitations related to reliability, costs, and versatility. The PTS buttons operate in conjunction with fuel controller to allow the fuel dispenser to dispense a desired fuel grade. Although current fuel controllers are capable of controlling the dispensing of a wide variety of fuel mixtures, the number of different fuel grades and/or additives that the fuel dispenser can dispense is limited by the number of PTS buttons included on the fuel dispenser. The application of the interactive display and the control module, in conjunction with other components of a fuel dispenser, can facilitate allowing a user to create customized fuel mixtures, while minimizing changes to standard communication protocol associated with components such as, e.g., a point-of-sale (POS) that can be configured to manage certain payment functionality of the fuel dispenser, a forecourt controller that can be configured to manage one or more fuel dispensers, and a fuel controller that can control dispensing of fuel, as discussed in more detail below.

[0024] FIGS. 1A and 1B illustrate one embodiment of a fuel dispenser **100**, and FIG. 2 illustrates components of the fuel dispenser. In general, the fuel dispenser **100** includes an electronics compartment **102** and a pump compartment **104**. The pump compartment **104** houses a pump configured to pump fuel from a fuel tank or other reservoir, as well as one or more meters that can be configured to monitor fuel flow, flow of fuel additives, and/or flow of other components of the fuel. The pump compartment **104** can also include other components to facilitate fuel dispensing and mixing, such as motors and valves, a strainer/filtering system, a vapor recovery system, and the like. The pump compartment **104** is isolated from the electronics compartment **102** within the fuel dispenser **100** to facilitate safety, security, and/or maintenance, as will be appreciated by a person skilled in the art. Fuel is thus not allowed to flow from the pump compartment **104** to the electronics compartment **102** and instead flows from the pump compartment **104** through hoses **106** to nozzles **108** for dispensing. As will be appreciated by a person skilled in the art, the nozzles **108** are each configured to dispense fuel from the fuel dispenser **100** as pumped therefrom by the pump.

[0025] The electronics compartment **102** houses electronics for facilitating payment for fuel and for facilitating the dispensing of the fuel. For example, the electronics compartment **102** can include a fuel controller **119** that, at least in some implementations, includes a data processor, memory, and storage forming part of at least one computing system. The fuel controller **119** is configured to control dispensing of the fuel from the pump compartment **104**. The electronics compartment **102** also includes a payment terminal **105** that is configured to provide a user with one or more options to create a desired fuel mixture, receive instructions characterizing the desired fuel mixture, receive payment information and/or user identification information from a user, transmit and receive the payment information and/or the user identification information with a POS system via a forecourt controller **206**, and deliver fueling instructions to the fuel controller **119** to dispense fuel. The

payment terminal **105** can also be configured to provide a user with information related to a status of fueling. For example, the payment terminal can display an amount of fuel that has been dispensed, and a corresponding fuel cost as the fuel mixture is dispensed.

[0026] The payment terminal **105** can be configured to facilitate communication between a user and the fuel controller **119**, and can include an interactive display **120** and an information module **110**. The information module **110** can, at least in some implementations include a data processor, memory, and storage, forming part of at least one computing system. The payment terminal **105** can also include one or more wired communication modules **116** and/or wireless communication modules **118** and a control module **112** that, at least in some implementations includes a data processor, memory, and storage, forming part of at least one computing system. The communication modules **116**, **118** can function to allow data to be transmitted to and from various components within the payment terminal **105** via wired and/or wireless communication, respectively. For example, the communication modules **116**, **118** can be configured to transmit and receive signals that can characterize, e.g., payment information, user identification information, and/or information regarding a desired fuel selection, via wired and/or wireless communications, respectively. The wireless communication module **118** can include, e.g., a transceiver for communicating via Bluetooth protocol, cellular protocol, WI-FI protocol, near field communication (NFC), and/or a radio frequency identification (RFID) protocol. Wired and/or wireless communication via the communication modules **116**, **118** can be according to any of a variety of communication protocols, e.g., TCP/IP, etc., as will be appreciated by a person skilled in the art.

[0027] The interactive display **120**, which can be, or can include, a touchscreen, can facilitate providing a user with a much broader array of choices than could be provided using PTS buttons. For example, a user can customize the fuel mixture based on octane levels, ethanol blends, additives, and the like, or the user can select a pre-configured mixture. The interactive display **120** can be operably coupled to the control module **112** which can be used to control, dynamically rearrange, and/or update a graphical user interface (GUI) rendered on the display **120**. The display **120** can be configured to show information (e.g., media content, fuel selection options, payment information, user identification information, etc.) in the form of one or more graphical elements, or graphical objects, receive input (e.g., instructions for a desired fuel mixture, user identification information, payment information, etc.) thereon, and can deliver data characterizing the input to the control module **112** to be processed. For example, the control module **112** can receive data characterizing available fuel mixture ingredients including, e.g., additives that are available, octane levels, ethanol blends, etc. from the fuel controller **119**. The control module **112** is discussed in more detail below. As an example, the display **120** can prompt the user with various options and information such as common premixed fuel options, fuel costs, fuel mixture ingredients and additives that are available, octane levels, ethanol blends, an option to input vehicle information for a custom fuel mixture, available payment methods, and the like. Some examples of information that the display **120** can receive from the user are: total cost, desired fuel volume, desired fuel mixture, desired additives, an initiate fueling command, and a terminate fueling command. In some implementations, the user can provide user information, such as user preferences, contact information, etc., and/or information regarding a device that will consume the fuel, such as vehicle make, model, mileage, and the like. The user can also be provided with a recommend fuel blend which they can choose to select.

[0028] To facilitate payment, the information module **110** can be configured to receive input such as, e.g., user identification information and/or payment information, and deliver the information to the control module **112**. For example, the information module **110** can include a card reader such as a magnetic strip card reader, a chip reader, a barcode and/or QR code scanner, and/or a NFC contactless card reader for receiving payment information and/or user identification information. As an example, the card reader can scan a loyalty rewards card and receive a loyalty rewards identifier. The loyalty rewards identifier can be delivered to the control module **112**, which can use

the loyalty rewards identifier to determine or obtain user identification information and/or a pre-set payment method. For example, the control module **112** can use the wired and/or wireless communication modules **116**, **118** to access a loyalty service within a network cloud. The control module **112** can provide data characterizing the loyalty rewards identifier to the loyalty rewards service to access a user account that can include user identification information, user preferences, a loyalty rewards status, and/or a preset payment method. The loyalty service can deliver data to the control module **112** characterizing the user identification information, user preferences, and/or preset payment methods corresponding to the loyalty rewards identifier. For example, user preferences can include default fuel grade selection that the user has set.

[0029] In some embodiments, the information module **110** can include an image sensor for acquiring images of facial features of the user, barcode and/or QR code information (e.g., to scan a loyalty rewards card), vehicle features (e.g., vehicle make, model, color, etc.), license plate number, non-facial body features, and the like, which can be used as user identification information. As another example, the information module can include a palm reader and or/fingerprint reader which can scan a palm and/or finger of the user to obtain user identification information. In some embodiments, the user identification information can be associated with a loyalty rewards identifier automatically. Accordingly, in some embodiments, a pre-determined payment method, and user preferences, can be determined based on user identification information.

[0030] As shown in FIG. 2, the information module **110** can be operably coupled to the wired communication module **116** and/or the wireless communication module **118**. The wired and wireless communication modules **116**, **118** can allow the information module **110** to send and receive payment information and/or user identification information to and from a mobile device such as a smart phone, tablet, laptop, and the like, that is in electronic communication with the information module **110** via the wired and/or wireless communication modules **116**, **118**. For example, in some cases, a loyalty identifier can be transferred to the information module via a NFC and/or Bluetooth communication. Although the wireless communication module **118** is shown to be located within the payment terminal, the wireless communication module **118** can be located elsewhere on, within, or in the vicinity of, the fuel dispenser **100**. For example, the wireless communication module **118** can be mounted on top of the fuel dispenser, which can facilitate retrofitting the wireless communication module **118** to existing fuel dispensers and/or facilitate repair, upgrade, or other maintenance of the communication module **118**, as described in U.S. patent application Ser. No. 15/182,201 filed on Jun. 14, 2016 and entitled “Methods and Devices for Fuel Dispenser Electronic Communication,” which is hereby incorporated by reference in its entirety.

[0031] The addition of the interactive display **120**, which enables customized fuel mixtures to be selected by the user, can present certain challenges regarding payment. In particular, pricing for the customized fuel mixture may not be available prior to identifying the desired fuel mixture. Therefore, in some embodiments, a price of the fuel mixture can be determined when the fuel mixture is identified by a user so that it can be provided to the user prior to delivering the fuel. Additionally, instructions for creating the desired fuel mixture can be communicated to the fuel controller **119** so that appropriate components of the fuel mixture can be mixed and dispensed. Accordingly, the control module **112** can function to determine a price of the desired fuel mixture, and can facilitate communication between the user and the fuel controller **119** such that fuel can be dispensed.

[0032] The control module **112** can receive the instructions for the desired fuel mixture, payment information, and user identification information from the interactive display **120** and/or the information module **110**. The control module **112** can provide a signal characterizing the desired fuel mixture, payment information, and user identification to the forecourt controller **206** via the wired and/or wireless communication modules **116**, **118**. The forecourt controller **206** can deliver the payment information, user identification information, and information characterizing the

desired fuel mixture to a point-of-sale (POS) system **208**. The POS system **208** can verify the payment information and can provide pricing information characterizing a price, or value, of each component of the desired fuel mixture. For example, the POS system **208** can deliver data characterizing a unit price for each component of the desired fuel mixture to the control module **112** via the forecourt controller **206**. Alternatively, in some embodiments, the pricing information can be stored in the forecourt controller **206**, and the forecourt controller **206** can deliver data characterizing a unit price for each component of the desired fuel mixture to the control module **112**. In some embodiments, the pricing information can be delivered from the forecourt controller **206** to the control module **112** via the fuel controller **119**.

[0033] In some embodiments, data characterizing a loyalty rewards identifier can be delivered to the POS system **208**. The POS system **208** can access a loyalty service within a network cloud. The POS system **208** can also provide data characterizing the loyalty rewards identifier to the loyalty rewards service to access a user account that can include user identification information, user preferences, a loyalty rewards status, and/or a preset payment method. The POS system **208** can deliver data to the control module **112** characterizing the user identification information, user preferences, and/or preset payment methods corresponding to the loyalty rewards identifier.

[0034] The control module **112** can use the pricing information from the forecourt controller **206**, or the POS system **208**, in conjunction with the instructions for the desired fuel mixture to determine a unit price for the desired fuel mixture. In some cases, the control module **112** can calculate unit prices corresponding to various payment methods. For example, the control module **112** can calculate a unit price corresponding to cash payments, and a unit price corresponding to credit card payments. All communication regarding pricing within the fuel dispenser **100**, and between the fuel dispenser **100**, the forecourt controller **206**, and the POS system **208** are performed securely. For example, the pricing information from the forecourt controller **206**, or POS system **208**, can be signed for the control module **112** and/or fuel controller to authenticate.

[0035] Once the fuel price has been calculated, the control module **112** can deliver a signal to the display **120** to update graphical elements on the display **120** to show the calculated unit price of the fuel mixture, and to request confirmation to proceed from the user. In some cases, the user can be eligible for a price discount, depending on a current loyalty rewards status. The control module **112** can deliver a signal to the display **120** to update graphical elements on the display **120** to allow the user to apply the discount to the calculated unit price of the fuel mixture. The control module **112** can also translate pricing information, the calculated price of the desired fuel mixture, and instructions for delivering the customized fuel mixture, such as instructions relating to the types of fluids to be delivered, and specific amounts of each component, into commands that can be understood by the fuel controller **119**. For example, the user might select a “high octane” fuel option, and the control module **112** can convert that into amounts of individual components required to create the desired fuel mixture. Once all of the data has been translated, at least some of the data related to fuel mixture and fuel delivery can be provided to the fuel controller **119** in the proper language. In some embodiments, the fuel controller **119** can translate the instructions from the control module **112** into instruction that meters within the pump compartment **104** can understand. For example, the control module **112** might deliver fueling instructions characterizing a desired “98 octane” fuel grade to the fuel controller **119**. The fuel controller **119** can translate the fueling instructions into commands characterizing fuel components required to make the 98 octane fuel mixture. For example, the translated instructions can include types of components, unit price per component, amounts of each component, and/or flow rates of each component such that the desired 98 octane fuel mixture can be dispensed and metered properly.

[0036] The user can confirm, or accept the price of the fuel mixture, which can result in the fuel controller **119** being activated. For example, the control module **112** can receive data characterizing acceptance of unit price of the fuel mixture, and can deliver an activation command to the fuel controller **119** to activate the fuel controller **119**. The fuel controller **119** can deliver a signal to the

forecourt controller **206** to update the status of the transaction, and the provide information regarding fueling so that an attendant can monitor the status of the fuel dispenser **100**. In some embodiments, if the user applies a price discount, the control module **112** can deliver data characterizing the discounted fuel price, or acceptance of the discounted fuel price, along with instructions for delivering the desired fuel mixture, to the POS system **208** via forecourt controller **206**. The forecourt controller **206** can deliver data characterizing the discounted fuel price along with the instructions for delivering the desired fuel mixture to the fuel controller **119**.

[0037] Once the price has been accepted, the user can enter a command to initiate fueling. In some embodiments, the command can be entered on the display **120**. The initiation command can be received by the control module **112**, where it can be translated and sent to the fuel controller **119**. The fuel controller **119** can then activate the pumps within the pump compartment **104** to dispense the desired fuel mixture. Alternatively, the display **120** can provide an indication to the user that they may begin fueling. In some embodiments, the initiation command can be entered as a result of a user action, such as removing the nozzle **108** from the dispenser and/or depressing a lever on the nozzle **108**.

[0038] As shown in FIG. 2, the pump compartment **104** can be coupled to a storage system **204**. The storage system **204** can house components, also referred to as ingredients, which can be used to make the desired fuel mixture. For example, gasoline (also known as petrol) is primarily comprised of processed crude oil, however, there are a number of additives that can be included. Those additives can include fuel stabilizers, detergents, dyes, oxygen-bearing compounds, and the like. Each component can be stored in a separate storage tank for delivery to the dispenser. One or more pumps within the pump compartment **104** can draw specified quantities of the components from the storage system **204**. The components can be mixed and dispensed from the fuel dispenser **100**.

[0039] During fueling, the control module **112** can obtain information from the fuel controller **119** regarding the status of the fueling process. For example, the fuel controller **119** can provide information regarding a volume of fuel dispensed and a total cost of the dispensed fuel to the control module **112**. The control module **112** can translate that information into data that can be understood by the display **120**, and can send it to the display **120** for the user to see.

[0040] FIG. 3 shows a diagram **300** that illustrates exemplary data flow that can occur between the display **120**, the information module **110**, the control module **112**, the forecourt controller **206**, and fuel controller **119**. In the illustrated embodiment, the control module **112** can receive data **303** characterizing available components for creating a fuel mixture from the fuel controller **119**. The information module **110** can deliver data **301** characterizing payment information, user identification information, and/or a loyalty rewards identifier to the control module **112**. Although not illustrated, the control module **112** can deliver data to the display **120** to prompt the user to input supplementary payment information, user identification information, and/or to select components of the desired fuel mixture.

[0041] The display **120** can receive input data **302** from the user, and can send it to the control module **112**. The data **302** can include information regarding a desired fuel mixture, payment information, and/or user identification information. For example, the data **302** can characterize a specified octane grade for the desired fuel mixture. Depending on the selection, the octane grade may require a custom blend of available grades in the storage system **204**. As another example, the data **302** can include supplementary payment information and/or user identification information. In some cases, if the information module **110** does not provide data **301** to the control module **112**, the data **302** can include all of the payment information and/or user identification information.

[0042] The control module **112** can compute **304** a response and can send data **306** characterizing options back to the display **120**. The options can include more fuel mixture choices and/or a prompt input further payment information and/or user identification information.

[0043] The display **120** receives the data **306** from the control module **112**, displays data **308**

characterizing the data **306** from the control module, and receives input data **302** from the user. The user input data **302** is subsequently sent back to the control module **112**.

[0044] The cycle of the user entering data **302** into the display **120**, the display **120** sending the data **302** to the control module **112**, the control module **112** subsequently computing **304** a response and sending data **306** back to the display **120** to update graphical elements, or graphical objects, to display the data **308**, can continue until the desired fuel mixture is identified, or until some predetermined maximum time limit is reached.

[0045] Once the desired fuel mixture has been determined, the control module **112** can deliver data **310** characterizing the desired fuel mixture, payment information, and/or user identification to the forecourt controller **206** via the wired and/or wireless communication modules **116**, **118**. The forecourt controller **206** can deliver the data **310** characterizing the payment information, user identification information, and/or information characterizing the desired fuel mixture to the POS system **208** (shown in FIG. 2). The POS system **208** can authenticate and verify the payment information and/or can provide pricing information characterizing a price, or value, of each component of the desired fuel mixture to the forecourt controller **206**. The forecourt controller **206** can deliver data **312** characterizing the pricing information to the control module **112**. The data **312** can be authenticated between the control module **112** and the POS system **208** via the forecourt controller **206**. Once the payment information has been authenticated, the forecourt controller **206** can send a signal **313** to the control module **112** that allows the control module **112** to active the fuel pumps via the fuel controller **119**. The control module **112** can use the pricing information to calculate a unit price, or value, of the desired fuel mixture.

[0046] The control module **112** can deliver data **314** characterizing the calculated unit price, or value, of the desire fuel mixture to the display **120**, which can update a graphical element, or a graphical object, of GUI to display the unit price and can prompt the user to accept or decline the calculated unit price, and to activate the fuel controller. The user can then input data **316** to accept the displayed price and deliver an activation command to activate the fuel controller **119**. The data **316** can be delivered to the control module **112**. The control module **112** can translate one or more of the calculated unit price of the desired fuel mixture, the activation command, as well as the pricing information previously obtained from the forecourt controller **206**, along with instructions for delivering the desired fuel mixture, such as instructions relating to the types of fluids to be delivered, flow rates for each fluid, and percentages of each fluid, or component, that makes up the desired fuel mixture, into commands that can be understood by the fuel controller **119**. As described above, in some cases, the user can be eligible for a price discount, depending their loyalty rewards status. If the user applies the price discount, the control module **112** can deliver data **318** characterizing the discounted fuel price, or acceptance of the discounted fuel price, along with instructions for delivering the desired fuel mixture, to the forecourt controller **206** and to the POS system **208**. The forecourt controller **206** can deliver data **319** characterizing the discounted fuel price along with the instructions for delivering the desired fuel mixture to the fuel controller **119**. The fuel controller **119** can translate the instructions for delivering the desired fuel mixture into instructions that meters within the pump compartment of the fuel dispenser **100** can understand, as described above.

[0047] Alternatively, if the user has not chosen to apply any price discounts, the control module **112** can deliver the translated data **318'** can then be sent directly to the fuel controller **119**. In some cases, the fuel controller **119** can send data to the forecourt controller **206** to inform the forecourt controller that it has received fueling instructions, and to update the status of the fuel dispenser so that an attendant can monitor and/or control the status of the fuel dispenser **100**.

[0048] Data **320** characterizing the calculated unit price of the desire fuel mixture and/or the pricing information from the forecourt controller **206**, or the POS system **208**, can be authenticated and verified between the fuel controller **119** and the control module **112**. For example, the control module **112** can sign data **320** characterizing the calculated unit price of the fuel mixture, and the

fuel controller **119** can authenticate the signed data **320**.

[0049] In some embodiments, the control module **112** can deliver data **322** to the display to prompt the user to initiate fueling after the calculated unit price of the desired fuel mixture and/or the pricing information from the forecourt controller **206**, or the POS system **208**, has been authenticated and verified between the fuel controller **119** and the control module **112**. The user can enter a fueling initiation command on the display **120** or elsewhere on the dispenser, and data **324** characterizing the initiation command can be delivered to the control module **112**. For example, in some embodiments the initiation command can be entered when a user depresses a lever on the nozzle **108** to begin fueling. The control module **112** can receive the data **324** characterizing the initiation command, translate the data **324**, and send the translated data **326** characterizing the initiation command to the fuel controller **119**.

[0050] The fuel controller **119** can receive the data **326**, compute a response **328**, and begin executing a process to dispense the fuel mixture. The fuel controller **119** can activate the pumps and send commands to the storage system **204** to dispense the desired components necessary to deliver the selected fuel grade.

[0051] During the dispensing process the fuel controller **119** can provide updates regarding a status of the dispensing by periodically sending data **330** characterizing the status of the dispensing to the control module **112**. Alternatively, the control module **112** can fetch the data **330** from the fuel controller **119**. As an example, the data **330** from the fuel controller **119** can characterize a total volume of the desired fuel mixture that has been dispensed and/or volumes of each component of the fuel mixture that have been dispensed, as well as a calculated total cost of dispensed fuel mixture based on the unit price of the fuel mixture and the total volume that has been dispensed. The control module **112** can receive the data **330** from the fuel controller **119**, translate the data **330**, and send data **332** characterizing the volume of fuel dispensed and the corresponding cost to the display **120** to be displayed. The data **332** can be used to update graphical elements, or graphical objects, of a GUI rendered on the display to provide information regarding cost and volume of the fuel mixture that has been dispensed to the user until dispensing is complete. In some embodiments, the fuel controller **119** can deliver data characterizing the volume of the fuel mixture that has been dispensed and/or volumes of each component of the fuel mixture that have been dispensed to the control module **112**, and the control module **112** can calculate the total cost of the dispensed fuel mixture using the calculated unit price.

[0052] The user can send a “termination” command, via the display **120** or elsewhere on the fuel dispenser, at any time during the fueling process to abort fueling. The control module **112** will receive the command, translate it, and send it to the fuel controller **119** to abort fueling. For example, the termination command can be sent when the user releases a lever on the nozzle to stop fueling.

[0053] FIGS. 4-5 illustrate an exemplary interactive GUI **400** that can be rendered on a display such as, e.g., the display **120** described above with regard to FIGS. 1-3, and it can be configured to enable a user to create a customized fuel blend. The GUI **400** can be used to display data and receive user input as described above with regard to FIGS. 1-3. For example, the GUI **400**, shown in FIG. 4, includes first, second, and third graphical elements **402**, **404**, **406** at the top that represent pre-set fuel grades, namely 89 octane, 93 octane, and 97 octane. The user can select any one of the pre-set grades as may be desired. In the illustrated example, the user has selected the 89 octane grade. The interface also includes fourth and fifth graphical elements, illustrated as first and second arrows **408**, **410**, that can be adjacent a sixth graphical element **412** that displays a currently selected octane grade, and can facilitate adjusting the octane grade. For example, a user can touch a portion of the display **120** corresponding to a location of the second arrow **410** to increase an amount of octane in the fuel mixture to a value displayed in a seventh graphical element **412** to the right of the second arrow **410**. Alternatively, the user can touch a portion of the display **120** corresponding to a location to first arrow **408** to decrease the amount of octane in the fuel mixture

to a value displayed in an eighth graphical element **414** to the left of the first arrow **408**. Increases and decreases can occur incrementally allowing the user to select any grade within a range of available octane grades that the dispenser has the ability to provide. The range of available octane grades will be determined based on the minimum and maximum grade of fuel available in the storage tanks. As shown in FIG. 4, the graphical element **414** to the left of the first arrow **408** does not show an octane value because the selected “89” octane grade is the lowest available grade.

[0054] The interface can also be configured to allow a user to select a specified amount of each octane grade. For example, the interface can include ninth, tenth and eleventh graphical elements **418**, **420**, **422** that a user can interact with to adjust percentages of fuel components to create a desired fuel mixture. As shown in FIG. 4, the ninth and tenth graphical elements **418**, **420** can be used to adjust amounts of 89 and 97 octane grade fuel, and the eleventh graphical element **422** can be used to adjust an amount of E85 fuel. As an example, the user can rotate a dial or touch plus and minus buttons of the ninth, tenth and eleventh graphical elements **418**, **420**, **422** to set a percentage for each of three grades to be present in the customized blend. Unit prices corresponding to cash and credit card payment methods are illustrated at the bottom of the GUI **400**. A twelfth graphical element **424** can be used to apply a 10% discount to the unit price of the fuel.

[0055] FIG. 5 illustrates the percentages of each grade adjusted as compared to FIG. 4. For example, in FIG. 5, the octane grade is set at “94,” and the user can press the first arrow **408** to decrease the octane grade, or the second arrow **410** to increase the octane grade.

[0056] FIG. 6 shows another example of a GUI **500** that can be rendered on a display that can be similar to the display **120** described above with regard to FIGS. 1-3. As shown in FIG. 7, the GUI **500** can include graphical elements **502**, **504**, **506** that can be used to select pre-set fuel grades, namely 87 octane, 89 octane, and 92 octane. The GUI **500** shows a currently selected octane grade “87” in a graphical element **512** near the top of the GUI **500**, and includes graphical elements, illustrated as first and second arrows **508**, **510** that can allow the user to switch to other available octane grades “92” and “89,” shown in graphical elements **514**, **516** to the left and right of the first and second arrows **508**, **510**. The GUI **500** also provides options to switch to select E10 standard fuel or ethanol free fuel, shown in graphical elements **524**, **526**, which are below graphical elements **502**, **504**, **506** corresponding to the pre-set fuel grades. Additives such as an engine cleaner and/or a mileage booster can be selected using graphical elements **528**, **530**, respectively.

[0057] Although a few variations have been described in detail above, other modifications or additions are possible. As an example, a fuel dispenser can include in-dispenser payment terminal. Alternatively, the payment terminal can be a standalone outdoor payment terminal (OPT), or it can be a mobile device that can connect to the payment terminal **105** via a wired and/or wireless connection. For example, an outdoor payment terminal (OPT) can be in electronic communication with the fuel controller, but not integral with the fuel dispenser. In some embodiments, a display can be located on a mobile device, such as a smart phone, tablet, laptop, and the like, and can be in electronic communication with a control module such as, e.g., the control module **112**, described above with regard to FIGS. 1-4, of a payment terminal that can be in that is in electronic communication with the fuel controller. As another example, the display can be located within the car itself, where it would function similarly to a smartphone, tablet, laptop, etc. In that event, a computer in the car could use diagnostic information, and send data characterizing the optimal fuel mixture to a control module of a payment terminal.

[0058] Additionally, a control module such as, e.g., the control module **112**, described above, can also communicate with a network to send or receive data, for example, to get updates, transmit information, get information regarding the availability of ingredients, and the like, during, prior to, or after a fuel dispensing process is complete.

[0059] One or more aspects or features of the subject matter described herein can be realized in digital electronic circuitry, integrated circuitry, specially designed application specific integrated circuits (ASICs), field programmable gate arrays (FPGAs) computer hardware, firmware, software,

and/or combinations thereof. These various aspects or features can include implementation in one or more computer programs that are executable and/or interpretable on a programmable system including at least one programmable processor, which can be special or general purpose, coupled to receive data and instructions from, and to transmit data and instructions to, a storage system, at least one input device, and at least one output device. The programmable system or computing system may include clients and servers. A client and server are generally remote from each other and typically interact through a communication network. The relationship of client and server arises by virtue of computer programs running on the respective computers and having a client-server relationship to each other.

[0060] These computer programs, which can also be referred to as programs, software, software applications, applications, components, or code, include machine instructions for a programmable processor, and can be implemented in a high-level procedural language, an object-oriented programming language, a functional programming language, a logical programming language, and/or in assembly/machine language. As used herein, the term “machine-readable medium” refers to any computer program product, apparatus and/or device, such as for example magnetic discs, optical disks, memory, and Programmable Logic Devices (PLDs), used to provide machine instructions and/or data to a programmable processor, including a machine-readable medium that receives machine instructions as a machine-readable signal. The term “machine-readable signal” refers to any signal used to provide machine instructions and/or data to a programmable processor. The machine-readable medium can store such machine instructions non-transitorily, such as for example as would a non-transient solid-state memory or a magnetic hard drive or any equivalent storage medium. The machine-readable medium can alternatively or additionally store such machine instructions in a transient manner, such as for example as would a processor cache or other random access memory associated with one or more physical processor cores.

[0061] To provide for interaction with a user, one or more aspects or features of the subject matter described herein can be implemented on a computer having a display device, such as for example a cathode ray tube (CRT) or a liquid crystal display (LCD) or a light emitting diode (LED) monitor for displaying information to the user and a keyboard and a pointing device, such as for example a mouse or a trackball, by which the user may provide input to the computer. Other kinds of devices can be used to provide for interaction with a user as well. For example, feedback provided to the user can be any form of sensory feedback, such as for example visual feedback, auditory feedback, or tactile feedback; and input from the user may be received in any form, including, but not limited to, acoustic, speech, or tactile input. Other possible input devices include, but are not limited to, touch screens or other touch-sensitive devices such as single or multi-point resistive or capacitive trackpads, voice recognition hardware and software, optical scanners, optical pointers, digital image capture devices and associated interpretation software, and the like.

[0062] Non-transitory computer program products (i.e., physically embodied computer program products) are also described that store instructions, which when executed by one or more data processors of one or more computing systems, causes at least one data processor to perform operations herein. Similarly, computer systems are also described that may include one or more data processors and memory coupled to the one or more data processors. The memory may temporarily or permanently store instructions that cause at least one processor to perform one or more of the operations described herein. In addition, methods can be implemented by one or more data processors either within a single computing system or distributed among two or more computing systems. Such computing systems can be connected and can exchange data and/or commands or other instructions or the like via one or more connections, including but not limited to a connection over a network (e.g. the Internet, a wireless wide area network, a local area network, a wide area network, a wired network, or the like), via a direct connection between one or more of the multiple computing systems, etc.

[0063] In the descriptions above and in the claims, phrases such as “at least one of” or “one or

more of” may occur followed by a conjunctive list of elements or features. The term “and/or” may also occur in a list of two or more elements or features. Unless otherwise implicitly or explicitly contradicted by the context in which it is used, such a phrase is intended to mean any of the listed elements or features individually or any of the recited elements or features in combination with any of the other recited elements or features. For example, the phrases “at least one of A and B;” “one or more of A and B;” and “A and/or B” are each intended to mean “A alone, B alone, or A and B together.” A similar interpretation is also intended for lists including three or more items. For example, the phrases “at least one of A, B, and C;” “one or more of A, B, and C;” and “A, B, and/or C” are each intended to mean “A alone, B alone, C alone, A and B together, A and C together, B and C together, or A and B and C together.” In addition, use of the term “based on,” above and in the claims is intended to mean, “based at least in part on,” such that an unrecited feature or element is also permissible.

[0064] The subject matter described herein can be embodied in systems, apparatus, methods, and/or articles depending on the desired configuration. The implementations set forth in the foregoing description do not represent all implementations consistent with the subject matter described herein. Instead, they are merely some examples consistent with aspects related to the described subject matter. Although a few variations have been described in detail above, other modifications or additions are possible. In particular, further features and/or variations can be provided in addition to those set forth herein. For example, the implementations described above can be directed to various combinations and subcombinations of the disclosed features and/or combinations and sub-combinations of several further features disclosed above. In addition, the logic flows depicted in the accompanying figures and/or described herein do not necessarily require the particular order shown, or sequential order, to achieve desirable results. Other implementations may be within the scope of the following claims.

Claims

1. A product dispenser, comprising: an interactive display; at least one processor; and a memory storing instructions that, when executed by the at least one processor, cause the product dispenser to: present a plurality of graphical elements in a first arrangement on the interactive display, each graphical element in the plurality of graphical elements characterizing a product to be dispensed for a user; responsive to at least one user input received at the interactive display, move the plurality of graphical elements from the first arrangement presented on the interactive display to a second arrangement presented on the interactive display, the second arrangement including at least one additional selectable graphical element corresponding to an additional product; and dispense, in response to at least one user selection of the at least one additional graphical element received at the interactive display, the additional product.
2. The product dispenser of claim 1, wherein the additional product comprises a fuel type.
3. The product dispenser of claim 2, wherein the fuel type has a user-specified octane level.
4. The product dispenser of claim 1, wherein each graphical element in the plurality of graphical elements and the additional graphical elements correspond to fuel types having differing octane levels.
5. The product dispenser of claim 4, wherein the additional selectable graphical element corresponds to a fuel type having a greater octane level than the octane levels of the fuel types represented by the plurality of graphical elements.
6. The product dispenser of claim 4, wherein the additional selectable graphical element corresponds to a fuel type having a lesser octane level than the octane levels of the fuel types represented by the plurality of graphical elements.
7. The product dispenser of claim 1, wherein the interactive display comprises a touchscreen, and wherein the at least one user input comprises a touch of the touchscreen.

8. The product dispenser of claim 1, wherein moving the plurality of graphical elements from the first arrangement to the second arrangement comprises a lateral shift of at least one of the plurality of graphical elements.

9. The product dispenser of claim 1, wherein the instructions, when executed by the at least one processor, further cause the product dispenser to blend a plurality of fuel ingredients together to result in the additional product corresponding to the user-selected, additional graphical element.

10. The product dispenser of claim 9, wherein the instructions, when executed by the at least one processor, further cause the display of a unit price of the additional product on the interactive display.

11. The product dispenser of claim 1, wherein the instructions, when executed by the at least one processor, further cause the product dispenser to: receive, from an image sensor disposed on the product dispenser, data characterizing facial features of a user; identify, based on the received data, a user identity; and associate the user identity with a pre-existing loyalty rewards status.

12. The product dispenser of claim 11, wherein the instructions, when executed by the at least one processor, further cause the product dispenser to update, based on the pre-existing loyalty rewards status, a fuel price of the additional product displayed on the interactive display.

13. A system, comprising: a processor; and a memory storing instructions that, when executed by the at least one processor, cause the processor to: present a plurality of graphical elements in a first arrangement on an interactive display in electronic communication with the processor, each graphical element in the plurality of graphical elements characterizing a product to be dispensed from a product dispenser in electrical communication with the processor; responsive to at least one user input received at the interactive display, move the plurality of graphical elements from the first arrangement presented on the interactive display to a second arrangement presented on the interactive display, the second arrangement including at least one additional selectable graphical element corresponding to an additional product; and dispense, in response to at least one user selection of the at least one additional graphical element received at the interactive display, the additional product.

14. The system of claim 13, wherein the additional product comprises a fuel type.

15. The system of claim 14, wherein the fuel type has a user-specified octane level.

16. The system of claim 13, wherein each graphical element in the plurality of graphical elements and the additional graphical elements correspond to fuel types having differing octane levels.

17. The system of claim 16, wherein the additional selectable graphical element corresponds to a fuel type have a greater octane level than the octane levels of the fuel types represented by the plurality of graphical elements.

18. The system of claim 16, wherein the additional selectable graphical element corresponds to a fuel type have a lesser octane level than the octane levels of the fuel types represented by the plurality of graphical elements.

19. The system of claim 13, wherein the interactive display comprises a touchscreen, and wherein the at least one user input comprises a touch of the touchscreen.

20. The system of claim 13, wherein moving the plurality of graphical elements from the first arrangement to the second arrangement comprises a lateral shift of at least one of the plurality of graphical elements.

21. The system of claim 13, wherein the instructions, when executed by the at least one processor, cause a control module in electronic communication with the processor to blend a plurality of fuel ingredients together to result in the additional product corresponding to the user-selected, additional graphical element.

22. The system of claim 21, wherein the instructions, when executed by the at least one processor, further cause the display of a unit price of the additional product on the interactive display.

23. The system of claim 13, wherein the instructions, when executed by the at least one processor, further cause the processor to: receive, from an image sensor disposed on the product dispenser,

data characterizing facial features of a user; identify, based on the received data, a user identity; and associate the user identity with a pre-existing loyalty rewards status.

24. The system of claim 23, wherein the instructions, when executed by the at least one processor, further cause the processor to update, based on the pre-existing loyalty rewards status, a fuel price of the additional product displayed on the interactive display.

25. A method, comprising: presenting a plurality of graphical elements in a first arrangement on an interactive display, each graphical element in the plurality of graphical elements characterizing a product to be dispensed for a user via a product dispenser in electronic communication with the interactive display; responsive to at least one user input received at the interactive display, moving the plurality of graphical elements from the first arrangement presented on the interactive display to a second arrangement presented on the interactive display, the second arrangement including at least one additional selectable graphical element corresponding to an additional product; and dispensing, via the product dispenser and in response to at least one user selection of the at least one additional graphical element received at the interactive display, the additional product.

26. The method of claim 25, wherein the interactive display comprises a touchscreen, and wherein the at least one user input comprises a touch of the touchscreen.

27. The method of claim 25, moving the plurality of graphical elements from the first arrangement to the second arrangement comprises a lateral shift of the plurality of graphical elements.
