

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent	12391422
Kind Code	B1
Date of Patent	August 19, 2025
Inventor(s)	Robb; Larry Joe et al.

---

### Sealing mechanism with punches and dies for securing packages

---

#### Abstract

Packaging material is folded around an item. First punches are actuated to pierce through the packaging material at a first location, and first dies are actuated to receive a portion of individual first punches of the first punches. Second punches are actuated to pierce through the packaging material at a second location, and second dies are actuated to receive a portion of individual second punches of the second punches. A first press compresses the packaging material at the first location, and a second press compresses the packaging material at the second location.

---

**Inventors:** Robb; Larry Joe (Mount Juliet, TN), Ochs; Garrett (Seattle, WA), Nguyen-Grove; Hang Tran (Kirkland, WA), Lerro; Jacqueline Rose (Newark, DE), Dighe; Anupam (Kirkland, WA)

**Applicant:** Amazon Technologies, Inc. (Seattle, WA)

**Family ID:** 1000006634291

**Assignee:** Amazon Technologies, Inc. (Seattle, WA)

**Appl. No.:** 17/903574

**Filed:** September 06, 2022

---

#### Publication Classification

**Int. Cl.:** B65B61/02 (20060101); B65B5/04 (20060101); B65B7/06 (20060101); B65B41/16 (20060101); B65B67/08 (20060101); B65D77/12 (20060101)

**U.S. Cl.:**

**CPC** B65B61/02 (20130101); B65B5/04 (20130101); B65B7/06 (20130101); B65B41/16 (20130101); B65B67/08 (20130101); B65D77/12 (20130101);

#### Field of Classification Search

## References Cited

### U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3822528	12/1973	Carlsson	53/542	B65B 5/061
3912575	12/1974	Zelnick	493/203	B29C 65/7441
3930350	12/1975	Reid	53/511	B65B 9/06
4000029	12/1975	Michaels	156/510	B29C 65/18
4044524	12/1976	Segale	53/433	B65B 9/06
5177931	12/1992	Latter	493/929	B65B 61/18
5411202	12/1994	Fenini	229/87.05	B65D 75/68
6309104	12/2000	Koch	383/200	B65D 75/58
6993887	12/2005	Dharssi	53/445	B65B 25/16
9718568	12/2016	Vardakostas	N/A	B65B 43/14
11059617	12/2020	Burgess	N/A	B65B 61/16
2005/0276521	12/2004	Price	383/105	B65B 61/16
2009/0241487	12/2008	Actis	53/563	B65B 65/00
2009/0293431	12/2008	Andria	53/436	B65B 31/06
2012/0006718	12/2011	Waldrop	206/557	B65B 25/065
2012/0047850	12/2011	Kemp	53/425	A61L 2/07
2012/0207410	12/2011	Moehlenbrock	383/95	B65B 9/20
2013/0036706	12/2012	Vaccari	53/79	B29C 66/24244
2015/0128525	12/2014	Bartoli	53/410	B65D 85/8061
2015/0191267	12/2014	Mochizuki	53/373.2	B65B 9/04
2015/0259119	12/2014	Duan-Arnold	206/440	A61F 15/001
2016/0304226	12/2015	Rossini	N/A	B29C 66/8412
2017/0129630	12/2016	Weibel	N/A	B65B 31/00
2017/0297312	12/2016	Oyama	N/A	B65B 53/063
2018/0178932	12/2017	Palumbo	N/A	B65B 65/003
2019/0023474	12/2018	Palumbo	N/A	B65D 5/241
2020/0270048	12/2019	Goodrich	N/A	B32B 29/005
2021/0214112	12/2020	Burgess	N/A	B65B 61/16
2021/0292019	12/2020	Chevalier	N/A	B65B 7/164
2022/0267064	12/2021	Gonnering	N/A	G06Q 10/087
2022/0402640	12/2021	Brakkee	N/A	B65B 61/007

---

*Primary Examiner:* Palmer; Lucas E. A.

*Attorney, Agent or Firm:* Eversheds Sutherland (US) LLP

---

## Background/Summary

### BACKGROUND

(1) The rise of online purchases has brought about an increase in order fulfillment, packaging, and processing. To meet these demands, automated machines and systems have been developed that

package items for shipment. In some cases, the automated machines may individually construct boxes for the items being shipped. However, securely manufacturing the boxes around the items remains a challenge. For example, portions of the box may open and the items may spill out. Such occurrences have a negative impact on order fulfillment and throughput.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

(1) The detailed description is described with reference to the accompanying figures. In the figures, the left-most digit(s) of a reference number identifies the figure in which the reference number first appears. The use of the same reference numbers in different figures indicates similar or identical components or features. The systems depicted in the accompanying figures are not to scale and components within the figures may be depicted not to scale with each other.

(2) FIG. 1 illustrates an example environment including an example machine having an example sealing mechanism for sealing portions of a container around an item, according to examples of the present disclosure.

(3) FIG. 2 illustrates select components of the machine and/or the sealing mechanism of FIG. 1, according to examples of the present disclosure.

(4) FIGS. 3A and 3B illustrate an example press and an example punch of the sealing mechanism of FIG. 1, according to examples of the present disclosure.

(5) FIGS. 4A and 4B illustrate an example press and an example die of the sealing mechanism of FIG. 1, according to examples of the present disclosure.

(6) FIGS. 5A-5C illustrate an example process for sealing a container using the sealing mechanism of FIG. 1, according to examples of the present disclosure.

(7) FIG. 6 illustrates an example flow of operations for sealing a container using the sealing mechanism of FIG. 1, according to examples of the present disclosure.

(8) FIGS. 7A-7D illustrate an example process for sealing a container using the sealing mechanism of FIG. 1, according to examples of the present disclosure.

(9) FIG. 8 illustrates an example punch of the sealing mechanism of FIG. 1, according to examples of the present disclosure.

(10) FIG. 9 illustrates an alternative example of a sealing mechanism for sealing portions of a container, according to examples of the present disclosure.

(11) FIGS. 10A-10E illustrate example punches for sealing portions of a container, according to examples of the present disclosure.

(12) FIG. 11 illustrates an example flow of operations for forming a container and sealing portions of the container, according to examples of the present disclosure.

(13) FIGS. 12A-12D illustrate various examples of tabs formed by a sealing mechanism for sealing portions of a container, according to examples of the present disclosure.

(14) FIG. 13 illustrates an example process for sealing a container, according to examples of the present disclosure.

### DETAILED DESCRIPTION

(15) This patent application is directed, at least in part, to a sealing mechanism of a machine that cuts, folds, and seals portions of a container. For example, items being processed for shipment may be placed onto a portion of a material that forms the container. Rollers and folders of the machine may be used to form a number of different container configurations, including inward-facing gussets, outward-facing gussets, bent sidewalls, round sidewalls, flat sidewalls, and so forth. After forming the container, portions of the material may be pinched, folded, cinched, adhered, and/or otherwise secured together using the sealing mechanism. For example, the sealing mechanism may include punches that cut and fold the material over itself, thereby cinching the material together. In

some instances, the material that is cinched together may be disposed at or along seams (e.g., ends) of the container to prevent the seams opening during transport. Additionally, the sealing mechanism may be used to secure the seams of the container together and allow sufficient time for adhesives to cure. As a result, the items may be secured within the container and throughput may be increased.

(16) Initially, as orders are placed, item(s) associated with the order may be picked. The machine, such as via conveyors, robotic elements, chutes, and so forth, may receive the item(s). The item(s) may be placed onto the portion of the material that forms the container around the item(s). The machine is configured to form the container based at least in part on dimensions of the item(s) to be packaged within the container, the number of item(s) packaged within the container, and/or type of the item(s) packaged within the container. In some instances, the containers may be formed of a single sheet of roll-formed material, such as a paper-based material (e.g., unpadded cardboard, chambered corrugate, single-sided or double-sided corrugate, a non-Gaussian material, etc.). Additionally, the container may take any shape, such as being rectangular, square, cylindrical, and so forth.

(17) After forming the container, or as part of forming the container around the item(s), seams of the container may be secured. For example, using the sealing mechanism, one or more ends of the container may be secured to form the container and/or enclose the item(s) within the container. Generally, the sealing mechanism functions to cut and fold portions of the material together to secure seams of the container and prevent the container opening during transport. For example, after the material is folded around the item(s), ends of the container may be pressed and punched together. As referred to herein, punching may involve the process of forming a hole, such as a slit, through the material. As part of forming the hole, a punched out portion, such as a tab, of the material is created. The tab includes an end that remains connected to the material and an opposite end which is free. Thereafter, presses may compact the seams to compress the punched out portion of the material and a remaining portion of the material together. The pressing secures the seam together and prevents separation of the punch out portions from the material disposed along the seam. Common expressions for this type of securing may be referred to as staple-free stapling.

(18) To further illustrate, two pieces of the material, such as an upper piece and a lower piece may be brought together. The sealing mechanism may include dies, cutters, or punches that respectively cut (i.e., punch) through the material to form the holes and the tabs. More particularly, as the punch extends through the upper piece of the material, a first hole may be created along with a first punched out portion (e.g., tab). As the punch extends further, and through the lower piece of the material, a second hole may be created along with a second punch out portion (e.g., tab). The upper piece of the material and the lower piece of the material are then compressed together, and in doing so, the punched out portions of the upper piece of the material and the lower piece of the material secure the seam together. That is, the punched out portions, which are adjoined to the upper piece of the material and the lower piece of the material, extend beyond a perimeter of the hole to prevent separation of the upper piece of the material and the lower piece of the material.

(19) The punches may include any shape or configuration. For example, the punches may include a needle shaped-punch, such as a being circular, square, hexagonal, and so forth. Moreover, a leading end of the punches may include a tip that pierces into the upper piece of the material and the lower piece of the material. In some instances, the punch may taper inward from the leading end of the punch to a trailing end of the punch in order to avoid the trailing end of the punch snagging (e.g., catching) on the hole formed within the upper piece of the material.

(20) As introduced above, the machine may include a press that squeezes the ends of the upper piece of the material and the lower piece of the material together. In some instances, the press may be actuated while or during the punches are actuated. For example, as the punches pierce through the upper piece of the material and the lower piece of the material, the presses may bring the upper piece of the material and the lower piece of the material together. In some instances, the punches are disposed on or within a first press, located adjacent to an exterior surface of the upper piece of

the material, while a die that received the punches are disposed on or within a second press, located adjacent to an exterior of the lower piece of the material. In this manner, as the punches cut through the upper piece of the material and the lower piece of the material, the presses may bring the upper piece of the material and the lower piece of the material together and while the punches remain disposed through the hole. In doing so, the punches prevent the punched out portions of the completely occupying the hole, but rather, the punched out portions extend beyond the holes, adjacent to the exterior surface of the upper piece of the material and/or the lower piece of the material to prevent separation and to secure the upper piece of the material and the lower piece of the material together.

(21) The sealing mechanism may include any number of punches that form the holes along a given length of the material. In some instances, the number of holes may be based on a size of the container, the type of material used to form the container, and/or an amount of material to be secured together. In some instances, the number of holes formed by the punches within the material may be such that a structural integrity of the container is not compromised. For example, in some instances, the number of holes may not exceed eight per ten inches. In some instances, the holes may be spaced apart on twelve millimeter center points. The punched out portions of the material, such as the tabs, may also take any dimensions, but in some instances, may be about six mm in length and four mm in width. In some instances, the size of the tabs may be based at least in part on the size of the container and/or the material used to form the container. However, other sized tabs, and corresponding holes, are envisioned.

(22) The sealing mechanism (or the machine) may include actuators that actuate the punches, dies, and/or the presses. In some instances, biasing members may return the punches and/or the presses to a retracted position. Further, in some instances, the punches and/or the presses may be made up of different sections in order to match a contour of the material being secured together. For example, as ends of the container include overlapping material, such as at/along seams of the container, the end may include different thickness. The different sections may be independently actuatable in order to contour (e.g., shape) to the different thickness. This may, in some instances, assist in further sealing the ends of the container together. For example, a first punch may be disposed within a first press, a second punch may be disposed within a second press, a third punch may be disposed within a third press, and so forth. In some instances, given that the machine may construct differently sized containers, only a predetermined number of the punches may be activated to cinch ends of the container together. For example, the machine may manufacture containers having different widths, and based on the width of the container, certain punches may be activated (via the actuators) and deactivated.

(23) In addition to or alternative from using the sealing mechanism, adhesives may be used to secure the ends of the container. In some instances, adhesives may be applied to surfaces of the material which are brought into contact with one another at the ends of the container, along the upper piece of material and/or the lower piece of the material. The adhesive may be applied prior to the punching and pressing. For example, after the adhesive is applied, the ends of the container may be punched and pressed together. In some instances, this allows for sufficient curing of the adhesive, for example, when the press is released. That is, as the ends of the container are punched together, the punching may prevent the ends of the container disengaging during curing of the adhesive. Punching may therefore assists in holding the ends of the container together to allow for sufficient curing of the adhesive and may reduce the amount of time required for the press to hold ends of the container together.

(24) In some instances, the adhesive may be applied interior to where the ends of the container are punched. In this manner, the punches may not become contaminated (e.g., dirtied) with the adhesive that may adversely impact an operation of the sealing mechanism. Still, in some instances, location of the punches (or the holes formed within the material) may create tear lines to provide assistance during opening of the container. For example, the holes may be arranged along a line and

the container may tear apart along the line to enable a consumer to gain access to the items within the container without the use of tools (e.g., knife, scissors, etc.).

(25) Although the machine is described as performing certain functions, the machine may additionally or alternatively perform other functions. For example, the machine may apply labels to the containers to ready the containers for shipment. Additionally, the machine may include components used to form the container, such as sensors that measure dimensions of the item(s) being packaged in order to size the container appropriately. Further, although the above discussion is with regard to punching ends of the container together, the sealing mechanism described herein may be used to adjoin other seams of the container, such as seams along other sides and surfaces of the container.

(26) The sealing mechanism as disclosed herein may reduce an amount of material used during packaging. For example, adhering and punching ends of the container may eliminate the need for staples or other type-fasteners to secure ends (or other seams) of the package together. Advantageously, the sealing mechanism may reduce waste and/or packaging material consumption. Additionally, the sealing mechanism provides a holding force that resists separation of the material while the adhesive cures.

(27) The present disclosure provides an overall understanding of the principles of the structure, function, device, and system disclosed herein. One or more examples of the present disclosure are illustrated in the accompanying drawings. Those of ordinary skill in the art will understand that the devices and/or the systems specifically described herein and illustrated in the accompanying drawings are non-limiting embodiments. The features illustrated or described in connection with one embodiment may be combined with the features of other embodiments. Such modifications and variations are intended to be included within the scope of the appended claims.

(28) FIG. 1 illustrates an example environment **100** including a machine **102** that functions to form containers for items being processed. In some instances, the environment **100** may include a facility in which the items are processed, categorized, and/or otherwise readied for shipment. For example, the environment **100** may include an inventory field (not shown) in which items are located. In some instances, robotic elements may be used to pick the item(s) from the inventory field and deliver the item(s) to the machine **102**. Additionally, or alternatively, manual labor or a combination thereof may be used to pick the items. Further, in some instances, conveyor belts and/or other conveyance mechanisms (e.g., rollers, chutes, etc.) may be used to process the item(s) to the machine **102**.

(29) The machine **102** includes a plurality of components, stations, or mechanisms for processing the item(s) for shipment. Initially, the item(s) may arrive at the machine **102**. A robotic element **104** may pick an item **106** (e.g., among the item(s)) and place the item **106** onto a first conveyor **108**. As the item **106** traverses along the first conveyor **108**, in a direction of travel **110**, one or more cameras or other sensor(s) **112**, such as LIDAR sensors, depth sensors, and so forth may be used to determine one or more dimensions of the item **106**. For example, the sensor(s) **112** may be used to capture one or more top-down images of the item **106**, one or more side-view images of the item **106**, and so forth. The sensor(s) **112** may generate data that is used to determine one or more dimensions of the item **106**. In some instances, the sensor(s) **112** may be depth cameras or depth sensors used to generate data points that can be processed to determine one or more dimensions of the item **106** (e.g., length, width, height, etc.).

(30) In some instances, the item **106** may traverse along the first conveyor **108** onto a portion of packaging material **114**. The packaging material **114** may be a roll-formed packaging material, such as corrugate (e.g., chambered corrugate, single sided corrugate, etc.), or a different packaging material, such as a non-Gaussian packaging material, an unpadded packaging material, or the like. In some instances, the packaging material **114** may include any material that can be creased or bent, and which is capable of being formed into a roll **116**. Although a single roll of the packaging material **114** is depicted, in some instances, additional rolls of the packaging material **114** may be

included. Additionally, different rolls with different widths may provide flexibility in packaging items of different dimensions.

(31) The packaging material **114** may be cut via a cutting mechanism **140**, which cuts the packaging material **114** according to specifics of the item **106** and based on sensor data generated by the sensor(s) **112**. For example, based at least in part on the dimensions of the item **106**, a length of the packaging material **114** dispensed from the roll **116** may be determined and the cutting mechanism **140** may sever the packaging material **114** accordingly. From the cutting mechanism **140**, the packaging material **114** may flow to a second conveyor **118** using belts, rollers, and so forth. The item **106** may therefore flow seamlessly from the first conveyor **108** onto the packaging material **114** on the second conveyor **118**.

(32) In addition to the length of packaging material **114**, a width between fold lines of the packaging material **114** may be determined. The width between fold lines may correspond to a width of the item **106**. Generally, the fold lines may be creases, score lines, perforations, or other features that facilitate bending of the packaging material **114**. In some instances, the fold lines may be embossed, serrated, perforated, texturized, or otherwise deformed. To form the fold lines onto/into the packaging material **114**, one or more adjustable rollers or dies may be used. Such process may occur as the packaging material **114** and the item **106** traverse along the second conveyor **118**. Additional details of forming the fold lines, or forming a custom container for an item, are discussed in, for example, U.S. patent application Ser. No. 16/871,767, filed May 11, 2020, entitled “Roll-Formed Containers for Shipping,” the entirety of which is herein incorporate by reference for all purposes.

(33) As the packaging material **114** is fed forward, in the direction of travel **110**, an adhesive or sealant, such as a hot melt glue, pressure-sensitive adhesive, tape, glue, thermal sealing component, or other adhesive or sealant may be applied about one or more edges and/or the width of the packaging material **114**. For example, in some embodiments, adhesive may be applied to three sides of the packaging material **114**. The adhesive may be absent on a side that comes into contact or is disposed adjacent to the item **106** once the packaging material **114** is folded. To apply the adhesive, the adhesive may be sprayed, applied in a beaded or spiral pattern, or otherwise distributed along one or more surfaces of the packaging material **114**.

(34) After the adhesive is applied, the packaging material **114** and the item **106** may continue to a folding station **120** whereby a container **122** (via the packaging material) is at least partially formed around the item **106**. For example, the folding station **120** may include one or more folders that are used to fold a first side of the packaging material **114** over the item **106**, and a second side of the packaging material **114** over the first side of the packaging material **114**. This folding creates an overlap between the first side and the second side. After the sides are folded, the sides may be pressed to cause the adhesive to bind the overlap together to form a seal along a top of the item **106**. Additionally, or alternatively, the folders may be used to form inward-facing or outward-facing gussets along sides of the item **106**, or to form sides of the container **122**.

(35) The packaging material **114** may then arrive at a sealing mechanism **124** that functions to enclose the packaging material **114** at longitudinal ends of the container **122**. More specifically, the sealing mechanism **124** serves to enclose longitudinal ends of the container **122** to enclose the item **106**. A detailed view **126** of the container **122**, as formed at least partially by the sealing mechanism **124**, is shown in FIG. 1. The detailed view **126** illustrates a top view of the container **122** and a bottom view of the container **122**.

(36) As will be explained herein, the sealing mechanism **124** includes presses that compress the packaging material **114** at a first longitudinal end **128** and a second longitudinal end **130** of the container **122**. The first longitudinal end **128** may be a leading end (relative to the direction of travel **110**), while second longitudinal end **130** may be a trailing end and spaced apart from the leading end (e.g., in the Z-direction). A first press may press the packaging material **114** together at the first longitudinal end **128**, while a second press may press the packaging material **114** together

at the second longitudinal end **130**.

(37) The sealing mechanism **124** further includes punches that form holes within the packaging material **114**. For example, first punches may form first holes **132** (e.g., slits, openings, voids, etc.) through the packaging material **114** at the first longitudinal end **128** and second punches may form second holes **134** (e.g., slits, openings, voids, etc.) through the packaging material **114** at the second longitudinal end **130**. The first punches and the second punches may vertically actuate (e.g., in the Y-direction) to pierce through the packaging material **114**. During this, the first punches and the second punches form first tabs **136** and second tabs **138**, respectively, from the packaging material **114** (e.g., the punched portions of the packaging material **114**). With continued actuation of the first punches and the second punches, the first tabs **136** and the second tabs **138** are pushed through the first holes **132** and the second holes **134**, respectively, or while the first holes **132** and the second holes **134** are formed. The tabs, however, remain connected to the packaging material **114**. By pressing the packaging material **114** together, at the first longitudinal end **128** and the second longitudinal end **130**, respectively, the packaging material **114** is bound together, and the packaging material **114** at the first longitudinal end **128** and a second longitudinal end **130** resist separation.

(38) In some instances, punching the longitudinal ends of the container **122** together may allow for sufficient curing of the adhesive, for example, when the press is released. That is, as the longitudinal ends of the container **122** are punched together, and held in place at least in part by the first tabs **136** and the second tabs **138**, the first tabs **136** and the second tabs **138** hold the longitudinal ends of the container **122** together to allow for sufficient curing of the adhesive. In some instances, punching of the longitudinal ends may occur while the packaging material **114** is stationary, or the sealing mechanism **124** may be configured to translate with the packaging material **114**.

(39) In some instances, a spacing between the first punches and the second punches may be adjustable to either increase or decrease a spacing between the first holes **132** and the second holes **134**, respectively (e.g., in the Z-direction). Moreover, in some instances, the amount of punches actuated by the sealing mechanism **124** may be based on the width of the container **122** (e.g., in the Z-direction). After punching, the container **122** may be pushed onto or otherwise fed for further processing. For example, the container **122** may be sorted for shipment based on a destination address of the container **122**.

(40) The machine **102** may therefore be configured to retrieve items for packing, and to pack the items into custom sized containers. Given that the container **122** is punched together using portions of the packaging material **114** (e.g., the first tabs **136** and the second tabs), the container **122** may reduce waste and increase throughput by limiting the amount of time the presses are required to hold the packaging material **114** together during curing of the adhesive. Moreover, the machine **102** may improve packing quality, reduce a likelihood of item or container damage, and improve processing efficiencies.

(41) Although a single machine is discussed, it is to be understood that the environment **100** may include any number of machines that process the item(s) for shipment. Any number of the machines are configured to operate independently and perform operations for processing the item(s) for shipment. Further, although FIG. 1 illustrates the container **122** being formed around a single item (e.g., the item **106**), more than one item may be disposed on the packaging material **114** at a time to increase throughput of the machine **102**.

(42) FIG. 2 illustrates example components of the machine **102**. The machine **102** is shown including processor(s) **200** and memory **202**, where the processor(s) **200** may perform various functions and operations associated with sealing the container **122**, and the memory **202** may store instructions executable by the processor(s) **200** to perform the operations described herein.

(43) The machine **102** includes a first press **204** having first punches **206** and first dies **208** for forming the first tabs **136** and sealing the container **122** at the first longitudinal end **128**, for



example. In some instances, the first press **204** may include a first upper press **210** and a first lower press **212**. The first upper press **210** may include the first punches **206**, while the first lower press **212** may include the first dies **208**. In some instances, the first punches **206** may couple to or be disposed on a first upper platform **214** of the first upper press **210**, while the first dies **208** may couple to or be disposed on a first lower platform **216** of the first lower press **212**. Portions of the first upper platform **214** are shown in dashed lines to illustrate the first punches **206**. As shown, the first punches **206** and the first dies **208** may extend from the first upper platform **214** and the first lower platform **216**, respectively, to engage with one another during a sealing of the container **122**. The first dies **208** may be complimentary to receive a corresponding portion of the first punches **206**, respectively, for example, a tip of the first punches **206**. As such, as the first press **204** is brought together (e.g., in the y-direction), the first press **204** presses portions of the packaging material **114** together while the first punches **206** and the first dies **208** create the first tabs **136** to seal the container **122**.

(44) Additionally, the machine **102** includes a second press **220** having second punches **222** and second dies **224** for forming the second tabs **138** and sealing the container **122** at the second longitudinal end **130**, for example. In some instances, the second press **220** may include a second upper press **226** and a second lower press **228**. The second upper press **226** may include the second punches **222**, while the second lower press **228** may include the second dies **224**. In some instances, the first punches **206** may couple to or be disposed on a second upper platform **230** of the second upper press **226**, while the second dies **224** may couple to or be disposed on a second lower platform **232** of the second lower press **228**. Portions of the second upper platform **230** are shown in dashed lines to illustrate the second punches **222**. As shown, the second punches **222** and the second dies **224** may extend from the second upper platform **230** and the second lower platform **232**, respectively, to engage with one another during a sealing of the container **122**. The second dies **224** may be complimentary to receive a corresponding portion of the second punches **222**, respectively, for example, a tip of the second punches **222**. As such, as the second press **220** is brought together (e.g., in the y-direction), the second press **220** presses portions of the packaging material **114** together while the second punches **222** and the second dies **224** create the second tabs **138** to seal the container **122**.

(45) The machine **102** also includes actuator(s) **234** for actuating the first press **204**, the first punches **206**, the first dies **208**, the second press **220**, the second punches **222**, and the second dies **224**, respectively. In some instances, the actuator(s) **234** may independently actuate the first punches **206**, the first press **204**, the first dies **208**, the second punches **222**, the second press **220**, and the second dies **224**, respectively. Example actuator(s) **234** include linear cylinders, whether pneumatic or fluid, screw drives, motors, and so forth.

(46) The actuator(s) **234** actuate the first punches **206** and the second punches **222** for forming the first holes **132** and the second holes **134** through the packaging material **114**. Additionally, actuating the first punches **206** and the second punches **222** creates the first tabs **136** and the second tabs **138**, respectively. In some instances, the first punches **206** and the second punches **222** are actuated substantially simultaneously, or may be actuated at different times.

(47) In some instances, the machine **102** (or the sealing mechanism **124**) may include six first punches **206**, six first dies **208**, six second punches **222**, and six second dies **224**. However, although six first punches **206**, six first dies **208**, six second punches **222**, and six second dies **224** are shown, the machine **102** may include more than or less than six first punches **206**, six first dies **208**, six second punches **222**, and/or six second dies **224** (e.g., four, five, seven, eight, ten, twelve, etc.). Moreover, in some instances, not all of the first punches **206**, the first dies **208**, the second punches **222**, and the second dies **224** may be used to seal the container **122**. For example, depending upon the width of the container **122** to be formed (e.g., in the x-direction), not all of the first punches **206**, the first dies **208**, the second punches **222**, and the second dies **224** may be used. This may, in some instances, include not actuating certain ones of the first punches **206**, the first

dies **208**, the second punches **222**, and the second dies **224**. Alternatively, all of the first punches **206**, the first dies **208**, the second punches **222**, and the second dies **224** may be actuated, but only a portion of the first punches **206**, the first dies **208**, the second punches **222**, and the second dies **224** may contact form the first tabs **136** and the second tabs **138**, respectively. In such instances, on a portion of the first press **204** and the second press **220** may be engage with the packaging material **114** to press the longitudinal ends of the container **122** together.

(48) The first punches **206** and the second punches **222** may be spaced apart by a longitudinal distance **218**. The longitudinal distance **218** may also correspond to a spacing between the first dies **208** and the second dies **224**. In some instances, the longitudinal distance **218** is disposed along a length of the container **122** (e.g., in the Z-direction). In some instances, the longitudinal distance **218** may be in the range of about four inches (+/-¼ inches) to about seventy-two inches (+/-¼ inches). However, other dimensions are envisioned.

(49) In some instances, the first press **204** (as well as the first punches **206** and the first dies **208**) and/or the second press **220** (as well as the second punches **222** and the second dies **224**) may translate in the Z-direction and based on the length of the container **122**. For example, the memory **202** is shown including sensor data **236**, which may be received via the sensor(s) **112** that measure the dimensions of the item **106**. Based at least in part on the sensor data **236**, the machine **102** (or another communicatively coupled computing device), may determine the dimensions of the item **106**. This may, in turn, be used to determine setting(s) **238** of the machine **102**, for example, the longitudinal distance **218**. As such, after determining a length of the item **106**, the first press **204** and/or the second press **220** may translate to reposition the first punches **206**, the first dies **208**, the second punches **222**, and the second dies **224**, respectively, in order to form the container **122**. Such translation may occur via the actuator(s) **234**. Additionally, in some instances, the first upper platform **214**, the first lower platform **216**, the second upper platform **230**, and/or the second lower platform **232** may be disposed on a system of tracks, rails, slides, and so forth for adjusting their longitudinal position.

(50) The first punches **206** and the first dies **208**, as well as the second punches **222** and the second dies **224**, may be spaced apart by a vertical distance **242**. For example, the first punches **206** and the first dies **208** may be separated from one another by the vertical distance **242**, and/or the second punches **222** and the second dies **224** may be separated from one another by the vertical distance **242**. In some instances, the vertical distance **242** represents a spacing prior to the container **122** entering the sealing mechanism **124**. In this manner, the spacing may allow the container **122** to pass within, or enter, the sealing mechanism **124** such that the longitudinal ends may be sealed. In some instances, the first upper platform **214** and/or the second upper platform **230** are disposed on a system of tracks, rails, slides, and so forth for adjusting their vertical position. For example, once the container **122** enters the sealing mechanism **124**, the first upper platform **214** and the second upper platform **230** may descend upon the longitudinal ends of the container **122**. After sealing, the first upper platform **214** and the second upper platform **230** may retract such that the container **122** is permitted to leave the sealing mechanism **124**. Additionally, or alternatively, the first lower platform **216** and/or the second lower platform **232** may function in a similar manner. In some instances, the vertical distance **242** may be up to about forty eight inches (+/-¼ inches). However, other dimensions are envisioned and the sealing mechanism **124** may be positioned based on a height of the item **106** (as determined via the sensor data **236** and/or the setting(s) **238**).

(51) The first punches **206**, the first dies **208**, the second punches **222**, and/or the second dies **224** may also span a lateral length **240**. Individual punches and dies of the first punches **206**, the first dies **208**, the second punches **222**, and/or the second dies **224**, respectively, may be spaced apart from one another along the lateral length **240**. For example, the six first punches **206** may be disposed along the lateral length **240**. In some instances, the lateral length **240** may be up to about forty eight inches (+/-¼ inches). In such instances, and as noted above, more than six first punches **206**, six first dies **208**, six second punches **222**, and six second dies **224** may be included. That is,

the sealing mechanism **124** may be configured to seal containers **122** have a width of up to approximately forty eight inches wide. Moreover, as noted above, depending upon the width of the container **122**, certain ones of the first punches **206**, the first dies **208**, the second punches **222**, and/or the six second dies **224** may nor may not be used. Such determinations may be made using the sensor data **236** and implemented using the setting(s) **238** to control the first punches **206**, the first dies **208**, the second punches **222**, and/or the second dies **224** (e.g., via the actuator(s) **234**).

(52) Although the machine **102** is shown including certain components, other components may be included to effectuate operation of the first punches **206**, the first dies **208**, the second punches **222**, and/or the second dies **224**, the actuator(s) **234**, and so forth. For example, the machine **102** (or the sealing mechanism **124** of the machine **102**), may include other frames, brackets, mounts, and so forth in addition to or alternative from those shown. Further, such components may couple to one another to effectuate their operation and to seal the container **122** as described herein. Moreover, although not shown, the machine **102** may couple to remote computing resource(s) that may, in some instances, control at least part of the operation of the machine **102** (e.g., determining dimensions of the item **106**). Still, the machine **102** may include other features for folding, forming, and creating the container **122**, such as those described in, for example, U.S. patent application Ser. No. 16/871,767, filed May 11, 2020, entitled “Roll-Formed Containers for Shipping,” the entirety of which is herein incorporate by reference for all purposes.

(53) As used herein, a processor, such as the processor(s) **200**, may include multiple processors and/or a processor having multiple cores. Further, the processor(s) may comprise one or more cores of different types. For example, the processor(s) may include application processor units, graphic processing units, and so forth. In one implementation, the processor(s) may comprise a microcontroller and/or a microprocessor. The processor(s) may include a graphics processing unit (GPU), a microprocessor, a digital signal processor or other processing units or components known in the art. Alternatively, or in addition, the functionally described herein can be performed, at least in part, by one or more hardware logic components. For example, and without limitation, illustrative types of hardware logic components that may be used include field-programmable gate arrays (FPGAs), application-specific integrated circuits (ASICs), application-specific standard products (ASSPs), system-on-a-chip systems (SOCs), complex programmable logic devices (CPLDs), etc. Additionally, each of the processor(s) may possess its own local memory, which also may store program components, program data, and/or one or more operating systems.

(54) Memory, such as the memory **202**, may include volatile and nonvolatile memory, removable and non-removable media implemented in any method or technology for storage of information, such as computer-readable instructions, data structures, program component, or other data. Such memory may include, but is not limited to, RAM, ROM, EEPROM, flash memory or other memory technology, CD-ROM, digital versatile disks (DVD) or other optical storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, RAID storage systems, or any other medium which can be used to store the desired information and which can be accessed by a computing device. The memory may be implemented as computer-readable storage media (“CRSM”), which may be any available physical media accessible by the processor(s) to execute instructions stored on the memory. In one basic implementation, CRSM may include random access memory (“RAM”) and Flash memory. In other implementations, CRSM may include, but is not limited to, read-only memory (“ROM”), electrically erasable programmable read-only memory (“EEPROM”), or any other tangible medium which can be used to store the desired information and which can be accessed by the processor(s).

(55) FIGS. **3A** and **3B** illustrate an example press **300** including a punch **302**. In some instances, the punch **302** is representative of individual punches of the first punches **206** and/or the second punches **222**, while the press **300** is representative of individual presses of the first upper press **210** and/or the second upper press **226**.

(56) The punch **302** may be disposed within a housing **304** that couples to a plate **306** of the press

**300**. The housing **304** may include or define a passageway **308** within which the punch **302** translates. For example, a first actuator **234(1)** (e.g., among the actuator(s) **234**) may couple to the punch **302** to extend the punch **302** from and retract the punch **302** within the housing **304**. As such, the first actuator **234(1)** as well as the punch **302** are able to translate in a punch direction **310** (e.g., y-direction) during a sealing of the container **122** to form holes and tabs. For example, the punch **302** may extend through the plate **306** to punch through the packaging material **114**. Corresponding openings in the housing **304** and the plate **306** allow the punch **302** to extend from the housing **304** and/or the plate **306** (e.g., a bottom surface **312** of the plate **306**) and engage the packaging material **114**.

(57) A second actuator **234(2)** and a third actuator **234(3)** may couple to the plate **306** (e.g., a top surface **314**) to press the plate **306** into contact with the packaging material **114**. For example, the second actuator **234(2)** and the third actuator **234(3)** may extend the plate **306** in a press direction **316** (e.g., y-direction). While the plate **306** extends in the press direction **316**, the housing **304**, the first actuator **234(1)**, and the punch **302** may correspondingly move. For example, the first actuator **234(1)**, the second actuator **234(2)**, and/or the third actuator **234(3)** may include a synchronized actuation. The plate **306**, or the bottom surface **312** of the plate **306**, is configured to engage with the packaging material **114** and compress the packaging material **114** against a complimentary plate (e.g., a plate associated with the first lower press **212** and the second lower press **228**).

(58) Opposite ends of the first actuator **234(1)** not coupled to the punch **302**, as well as opposites ends of the second actuator **234(2)** and the third actuator **234(3)** not coupled to the plate **306**, may couple to a platform (e.g., the first upper platform **214**, the second upper platform **230**, etc.). In some instances, the passageway **308** may include or be lined with bushings, bearings, and the like to assist in the translation of the punch **302**.

(59) The punch **302** is shown including a first end **318** and a second end **320**. The first end **318** may represent a piercing end of the punch **302** that pierces into/through the packaging material **114** the first end **318** may include different shapes and contours for forming the first tabs **136** and the second tabs **138**. The second end **320** may represent a trailing end of the punch **302**, opposite the first end **318**. The punch **302** includes a length that extends between the first end **318** and the second end **320**. In some instances, the punch **302** may taper outwards, towards a central axis of the punch **302**, from the first end **318** and the second end **320**. For example, the first end **318** (or adjacent the first end **318**) may include a first cross-sectional dimension, while the second end **320** (or adjacent the second end **320**) may include a second cross-sectional dimension that is larger than the first cross-sectional dimension. This tapering may assist in the punch **302** retreating from the packaging material **114** and/or the hole formed within the packaging material **114** to avoid the punch **302** catching on sidewalls of the hole.

(60) The first end **318** includes a profile for piercing through the packaging material **114**. In some instances, the first end **318** may include a conical shape. However, other shapes are envisioned. For example, the first end may include a square shape, a cylindrical shape, a rectangular shape, and so forth. The shape of the first end **318** may assist in forming tabs of the packaging material **114** (e.g., the first tabs **136** and the second tabs) that are used to secure the longitudinal ends of the container **122** together. For example, as the first end **318** pierces through the packaging material **114**, the shape of the first end **318** may form the tabs that are then used to secure the longitudinal ends of the container **122** during pressing.

(61) In some instances, the plate **306** and/or the housing **304** may include different shapes than shown. For example, the plate **306** may include other shapes (e.g., circular, hexagonal, etc.). In some instances, the housing **304** and/or the plate **306** may be formed of a single piece of material, or may be coupled to one another.

(62) FIGS. 4A and 4B illustrate an example press **400** including an example die **402**. In some instances, the die **402** is representative of individual dies of the first dies **208** and/or the second dies **224**, while the press **400** is representative of individual presses of the first lower press **212** and/or

the second lower press **228**.

(63) The die **402** may be disposed with a housing **404** that couples to a plate **406** of the press **400**. The housing **404** may include or define the die **402**. As shown, the die **402** may represent a channel or other cavity formed within the housing **404** and/or the plate **406**. The die **402** is complimentary to receive a punch, such as the punch **302**, and accordingly, may include shapes and/or contours that are complimentary to the punch **302**. For example, a bottom **408** of the die **402** is shown including a conical feature for receiving a conically-shaped tip of the punch **302** (e.g., in instances where a tip of the punch **302** includes a conical shape). As such, the die **402** may receive the punch **302** (or a portion thereof) such that the punch **302** nests within the die **402**. In instances where the end of the punch **302** includes different shapes and/or contours, the die **402** may include corresponding shapes and contours as well. For example, the die **402** may be square, hexagonal, circular, and so forth. Additionally, the bottom **408** may be complimentary to receive a plurality of differently shaped tips of the punch **302**.

(64) An actuator **234** (e.g., of the actuators **234**) may couple to the housing **404** to press the plate **406** into contact with the packaging material **114** and advance the die **402** (as well as the plate **406**) in a direction towards the press **300**. For example, the actuator **234** may extend the plate **406** in a press direction **410** (e.g., y-direction) that is opposite the press direction **316** and/or the punch direction **310**. While the plate **406** extends in the press direction **410**, the housing **404** and the die **402** may correspondingly move. The plate **406**, or a top surface **412** of the plate **406**, is configured to engage with the packaging material **114** and compress the packaging material **114** against a complimentary plate (e.g., the plate **306** associated with the press **300**). In doing so, the packaging material **114** may be compressed between the plates. Additionally during this occurrence, the punch **302** is received with the die **402**.

(65) Although the die **402** is shown including a particular depth (e.g., in the Y-direction), different depths are envisioned. For example, the depth of the die **402** may be such that the die **402** may receive more than or less than a portion of the length of the punch **302**. Additionally, the actuator **234** may couple to the plate **406** (e.g., a bottom surface), in addition to or alternative from the housing **404**. In some instances, the housing **404** and/or the plate **406** may be formed of a single piece of material, or may be coupled to one another.

(66) FIGS. 5A-5C illustrate a progression of illustrations for securing seams of the container **122** using the sealing mechanism **124**, for example.

(67) In FIG. 5A, the first press **204** and the second press **220** are shown being separated (e.g., in y-direction) such that the sealing mechanism **124** may receive the container **122**. More particularly, the first punches **206** may be spaced apart from the first dies **208**, and the second punches **222** may be spaced apart from the second dies **224**. The first punches **206** and the first dies **208** are arranged to enclose the first longitudinal end **128** of the container **122** via actuation of the first upper press **210** and the first lower press **212**. The second punches **222** and the second dies **224** are arranged to enclose the second longitudinal end **130** of the container **122** via actuation of the second upper press **226** and the second lower press **228**. In FIG. 5A, the container **122** may represent a tube-like structure formed via folding the packaging material **114**, but with the first longitudinal end **128** and the second longitudinal end **130** yet to be secured.

(68) In FIG. 5B, the first press **204** and the second press **220** are shown being brought together to compress the packaging material **114** at the first longitudinal end **128** and the second longitudinal end **130**, respectively. During this instance, the first punches **206** form the first holes **132** and the first tabs **136**, and the first dies **208** receive the first punches **206**, respectively. Additionally, the second punches **222** form the second holes **134** and the second tabs **138**, and the second dies **224** receive the second punches **222**, respectively. Shortly thereafter, the first tabs **136** are compressed via plates of the first upper press **210** and the first lower press **212**. Additionally, the second tabs **136** are compressed via plates via the second upper press **226** and the second lower press **228**.

(69) In FIG. 5C, the first press **204** and the second press **220** are shown being separated (e.g., in y-

direction) such that the container **122** may be released from the sealing mechanism **124**. More particularly, the first punches **206** may be spaced apart from the first dies **208**, and the second punches **222** may be spaced apart from the second dies **224**, to allow the container **122** (now sealed) to be processed for further manufacturing. The first holes **132** and the first tabs **136** (underneath side) may be formed at the first longitudinal end **128**, while the second holes **134** and the second tabs **138** (underneath side) may be formed at the second longitudinal end **130**.

(70) Although the first press **204** and the second press **220** are shown including a certain number of punches and dies, respectively, more punches and dies may be included. In some instances, not all of the punches and/or dies may be used when securing the container **122** at the first longitudinal end **128** and the second longitudinal end **130**. For example, the punches and/or dies may extend beyond lateral edges of the container **122**, for securing containers having a width greater than that shown in FIGS. 5A-5C. Additionally, the positioning of the first punches **206**, the first dies **208**, the second punches **222**, the second dies **224** may be determined and/or set prior to the container **122** arriving at the sealing mechanism **124** in order to properly form the container **122** according to the dimensions of the item **106**. Such movement may be accomplished by moving the first upper press **210** and the first lower press **212**, the second upper press **226**, and the second lower press **228**.

(71) The sealing mechanism **124** may include components different than those described and illustrated. For example, in some instances, the sealing mechanism **124** may include punches that form the tabs from the packaging material **114**, as well as a hole spaced apart from the tab formed by the packaging material **114**. The sealing mechanism **124** may include levers that respectively feed the tabs through the hole in order to bind the packaging material **114** together, such as in the case of stapleless staplers. For example, after the punches form the hole and the tab, the lever may insert (e.g., push) the free end of the tab (e.g., not connected to the packaging material **114**) into the hole. During this process and while the tabs are being fed through the holes, the packaging material may be pressed together via the press in order to prevent separation of the ends of the container **122**. In these instances, the tabs may include an arrow-shape, spade-shape, T-shape, and so forth. However, the tabs may include wings or other tabs that are insertable into the previously cut hole and which prevent the tabs from backing out of the hole.

(72) FIG. 6 illustrates a progression of steps to secure the packaging material **114**, whether at the first longitudinal end **128** or the second longitudinal end **130**. The illustrations in FIG. 6 are simplified to more clearly illustrate the operation of the presses, and specifically, the punches and the dies. For example, the actuators **234** are omitted for clarity. However, it is to be understood that the punches and the dies may operate in accordance with the description herein.

(73) At “1,” the press **300** (e.g., a press of the first upper press **210**) and the press **400** (e.g., a press of the first lower press **212**) are shown being separated and/or spaced apart from one another. The packaging material **114** is disposed between the press **300** and the press **400**, as well as the punch **302** and the die **402**. The packaging material **114** shown is merely exemplary, and differently shaped, sized, etc. pieces of the packaging material **114** may be disposed between the press **300** and the press **400**. Additionally, more layers of the packaging material **114** may be disposed between the press **300** and the press **400** than shown (e.g., three, four, etc.). As shown, the packaging material **114** includes a first piece **600** and a second piece **602**. The first piece **600** and the second piece **602** may be formed from the same piece of packaging material **114**, but at the longitudinal ends of the container **122**, the packaging material **114** may overlap. At “1” the first piece **600** and the second piece **602** are shown being spaced apart and not compressed by the press **300** and the press **400**.

(74) At “2,” the punch **302** is actuated in a direction toward the first piece **600**. In doing so, the punch **302** pierces through the first piece **600**, forming a hole through the first piece **600**, as well as a first flap **604** and a second flap **606**. The first flap **604** and the second flap **606** are formed from the first piece **600**, and the first flap **604** and the second flap **606** may remain coupled to the first piece **600**. However, the first flap **604** and the second flap **606** may be simultaneously pushed in a

direction towards the second piece **602**. More than two flaps, however, may be formed. In some instances, the tapering of the punch **302** may assist in pushing the first flap **604** and the second flap **606**. For example, a body of the punch **302** may taper outward such that as the punch **302** is advanced downward, the first flap **604** and the second flap **606** are pushed by the punch **302**.

(75) At “3,” the punch **302** may be further actuated. In doing so, the punch **302** pierces through the second piece **602**, forming a hole through the second piece **602**, as well as a third flap **608** and a fourth flap **610**. The third flap **608** and the fourth flap **610** are formed from material of the second piece **602**, and the third flap **608** and the fourth flap **610** may remain coupled to the second piece **602**. However, the third flap **608** and the fourth flap **610** may be simultaneously pushed through the hole formed by the punch **302**. Additionally, the first flap **604** and the second flap **606** are pushed through the second piece **602** (e.g., via the tapering of the punch **302**).

(76) As also shown, the first press **300** may press against the first piece **600**, forcing the first piece **600** into contact with the second piece **602**. The tip of the punch **302** (e.g., the first end **318**) is also shown being received with the die **402**, so as to seat or nest the punch **302** within the die **402**.

(77) At “4,” the press **400** may be actuated in a direction towards the press **300**, to compress the first piece **600** and the second piece **602** between the press **300** and the press **400**. During this instance, the punch **302** may remain disposed through the first piece **600** and the second piece **602**. Additionally, during compression of the first piece **600** and the second piece **602**, the first flap **604**, the second flap **606**, the third flap **608**, and/or the fourth flap **610** may fill a space around the punch **302**. A tab **612** is shown being formed adjacent to the second piece **602**, which may be formed at least in part by the first flap **604**, the second flap **606**, the third flap **608**, and/or the fourth flap **610**. In doing so, the first piece **600** and the second piece **602** are prevented from separating when the press **300** and the press **400** release. That is, by forming the tab **612** from the first flap **604**, the second flap **606**, the third flap **608**, and/or the fourth flap **610**, the first piece **600** and the second piece **602** resist separation when the press **300** and the press **400** release. Further, the compression imparted by the press **300** and the press **400** may prevent the tab **612** unbinding.

(78) In some instances, both the press **300** and the press **400** may be actuated to compress the packaging material **114**. In other instances, one of the press **300** or the press **400** may be actuated in a direction towards one another to compress the packaging material **114**. In some instances, as the press **300** moves in the press direction **316**, the punch **302** may at least partially retract into the press **300**. For example, a pressing force of the press **400** may cause the first actuator **234(1)** coupled to the punch **302** to compress, thereby retracting the punch **302** at least partially back into the press **300** (or the housing **304**). However, in some instances, the punch **302** may remain disposed through the first piece **600** and the second piece **602**.

(79) Although the tab **612** is shown being disposed adjacent to the second piece **602**, tabs may additionally or alternatively be disposed adjacent to the first piece **600**. For example, an orientation of the press **300** and the press **400** may be switched. Additionally, or alternatively, a portion of the second piece **602** may be pulled back through the hole formed by the punch **302** and disposed adjacent to the first piece **600**. Thereafter, the press **300** and the press **400** may be actuated to compress the first piece **600** and the second piece **602** to form tabs adjacent to the first piece **600** and the second piece **602**, respectively.

(80) At “5,” the press **300** and the press **400** are shown being separated and/or spaced apart from one another after the first piece **600** and the second piece **602** are secured together via the tab **612**. That is, as the tab **612** is at least partially formed via pieces of the first piece **600** (e.g., the first flap **604** and the second flap **606**), the tab **612** is prevented being pulled through a hole formed by the punch **302**, and therefore, separation of the press **300** and the press **400** is prevented. A hole **614** is shown extending through the first piece **600** and the second piece **602**.

(81) Although certain operations are shown being performed at certain instance in time, or in relation to one another, other embodiments are envisioned. For example, the packaging material **114** at the first longitudinal end **128** may be pressed together and held in place via adhesive.

Thereafter, the punch may actuate to form the tabs to hold the packaging material **114** together while the container **122** is removed from the sealing mechanism **124** and while the adhesive is curing.

(82) In some instances, the first piece **600** and the second piece **602** are single-sided corrugate, which enables the first flap **604**, the second flap **606**, the third flap **608**, and the forth flap **610** to be formed without ripping. That is, given the material of the first piece **600** and the second piece **602**, the first flap **604**, the second flap **606**, the third flap **608**, and the forth flap **610** are formed via the punch **302** but remain connected to the first piece **600** and the second piece **602**, respectively. The single-sided corrugate prevents the first piece **600** and the second piece **602** ripping during actuation of the punch **302**. In doing so, the tabs **612** are formed and prevent separation of the first piece **600** and the second piece **602**.

(83) In some instances, the plate of the press **400** may include features for directing the first flap **604**, the second flap **606**, the third flap **608**, and the forth flap **610** outwards, away from the punch **302**. For example, a surface of the plate may include concave recessed features (e.g., dimples) that directs the first flap **604**, the second flap **606**, the third flap **608**, and the forth flap **610** in a direction outwards. Alternatively, the surface of the plate may include extrusions that direct the first flap **604**, the second flap **606**, the third flap **608**, and the forth flap **610** outwards. Regardless of the specific embodiment, the features may help direct the first flap **604**, the second flap **606**, the third flap **608**, and the forth flap **610** outwards for forming the tab **612**.

(84) FIGS. 7A-7D illustrate a progression of depictions for securing the container **122**, for example, using the sealing mechanism **124**.

(85) Beginning with FIG. 7A, an end view of the container **122** is shown. For example, the end view may represent the first longitudinal end **128** disposed between the first upper press **210** and the first lower press **212**. At the first longitudinal end **128**, the first press **204**, such as the first upper press **210** and the first lower press **212** may seal different thickness of the packaging material **114**. For example, along a first side **700** and a second side **702** of the container **122**, at the first longitudinal end **128**, the packaging material **114** may be folded upon itself to create gussets. This results in overlapping of the packaging material **114**. For example, along a first portion **704** at the first side **700** and/or at the first longitudinal end **128**, four layers of the packaging material **114** may be folded upon themselves. The second side **702** may include five layers of the packaging material **114**, which may result from the seam created along a top of the container **122**. The five layers may be disposed along a second portion **706** at the second side **702** and/or at the first longitudinal end **128**. The second portion **706** is also shown including four layers where the seam does not reside. In some instances, the folding of the sides, as well as the seam along the top of the container **122**, may be formed by the machine **102** at previous stations. A third portion **708**, between the first side **700** and the second side **702**, or between the first portion **704** and the second portion **706**, includes two layers of the packaging material **114**. As such, at the first longitudinal end **128**, different thicknesses of the packaging material **114** may be present.

(86) The first upper press **210** and the first lower press **212** include the first punches **206** and the first dies **208**, respectively. As shown, individual punches of the first punches **206** may be aligned with individual dies of the first dies **208**. The first punches **206** and the first dies **208** are independently actuatable to secure respective portions of the packaging material **114** at the first longitudinal end **128**. For example, as will be explained herein, the first upper press **210** and the first lower press **212** are actuatable to compress these different thicknesses of the packaging material **114** and to secure the first longitudinal end **128** of the container **122**. The individual presses of the first upper press **210** and the first lower press **212** are configured to be actuated from different amounts relative to the first upper platform **214** and the first lower platform **216**.

(87) In FIG. 7B, the first upper press **210** and the first lower press **212** are shown compressing the packaging material **114** at the first longitudinal end **128**. This involves, as explained above in FIG. 6, for example, the first punches **206** to punch through the packaging material **114** and engage with



the first dies **208**. Moreover, the first upper press **210** and the first lower press **212** translate in their respective press directions to compress the packaging material **114** together. Given the different thicknesses of the packaging material **114** at the first longitudinal end **128**, the individual presses of the first upper press **210** and the first lower press **212** may compress the packaging material **114** by different amounts. For example, along the first portion **704**, the first upper press **210** and the first lower press **212** may compress the four layers of the packaging material **114**, along the second portion **706**, the first upper press **210** and the first lower press **212** may compress the five layers of the packaging material **114**, and along the third portion **708**, the first upper press **210** and the first lower press **212** may compress the two layers of the packaging material **114**. However, although a particular number of layers are shown, the sealing mechanism **124** may be used to a different number of layers, or overlapping layers, than shown (e.g., three, six, etc.).

(88) In some instances, the first upper press **210** and the first lower press **212** may be configured to compress to a certain pressure (e.g., PSI). For example, a sensor may indicate the amount of pressure exerted by the first upper press **210** and the first lower press **212**, and such pressure may be used to control a pressing force of the first upper press **210** and the first lower press **212**. As such, because of the different thicknesses, and amount of the packaging material **114** to be compressed, the individual presses of the first upper press **210** and the first lower press **212** may not translate by the same amount.

(89) The independent actuation of the presses of the first upper press **210** and the first lower press **212** permit increased sealing of the packaging material **114**. For example, the first upper press **210** and the first lower press **212** are able to actuate by different amounts according to thickness of the packaging material **114**. Conversely, if a single plate was used across the width of the container **122** at the first longitudinal end **128**, portions of the packaging material **114** may not be adequately compressed together.

(90) In FIG. 7C, the first upper press **210** and the first lower press **212** are shown being opened following actuation of the first upper press **210** and the first lower press **212**. Along a bottom of the container **122**, tabs **710** are shown being formed in order to prevent separation of the packaging material **114** and opening of the container **122**. Each of the tabs **710** may be created by the respective packaging material **114** that the first punches form. That is, along the first portion **704**, the tabs **710** be formed from the four layers of the packaging material **114**, along the second portion **706**, the tabs **710** be formed from the five layers of the packaging material **114**, and along the third portion **708**, the tabs **710** be formed from the two layers of the packaging material **114**. The first punches **206** may include a sufficient stroke in order to pierce through the different layers of the packaging material **114**. Additionally, following compression of the packaging material **114**, a thickness of the packaging material **114** may be reduced.

(91) FIG. 7D illustrates a top view of the first longitudinal end **128** and after the first upper press **210** and the first lower press **212** form the first holes **132**. The first holes **132** are shown being spaced apart by a distance **712**. In some instances, the distance **712** may be between approximately five mm and twenty mm. That is, individual holes of the first holes **132** may be spaced apart between approximately five mm (e.g.,  $\pm\frac{1}{4}$ " ) and twenty mm (e.g.,  $\pm\frac{1}{4}$ " ). In some instances, the first holes **132** may be evenly spaced apart from one another, or may be spaced apart from one another by different distances. In some instances, first punches **206** and the first dies **208** may be adjustable in one or more lateral directions (e.g., X-direction) to increase or decrease separation therebetween.

(92) Although the container **122** is shown including a particular number of first holes **132** and a corresponding number of first tabs **136**, the container **122** may include more than or less than the number of first holes **132** and first tabs **136** than shown. For example, the first upper press **210** and the first lower press **212** may include more than six first punches **206** and six first dies **208**. In some instances, the number of first punches **206** and first dies **208** may not exceed eight per ten inches. This density may ensure an integrity of the container **122** as too many first holes **132** and

first tabs **136** may create a weak point and result in a tearing of the packaging material **114**. Here too, however, the creation of the first holes **132** may create a tear line that allows a consumer to open the container by tearing the packaging material **114** along a line disposed through the first holes **132**. For example, the consumer may grip an end of the packaging material **114** and rip a piece of the packaging material **114** from the container **122** along a line disposed through or between the first holes **132**. The first holes **132** may be equidistantly spaced along the line, and in some instances, the line may be substantially parallel to the first longitudinal end **128**.

(93) The first holes **132** are shown being spaced apart from the first longitudinal end **128** by a first depth **714**. In some instances, the first depth **714** may be between approximately five mm (e.g.,  $\pm 1/4$ " ) and twenty mm (e.g.,  $\pm 1/4$ " ). In some instances, the first holes **132** may even be formed along the first longitudinal end **128** (as shown and discussed in FIG. **12D**). Still, although the first holes **132** are shown including a circular shape, other shapes are envisioned.

(94) FIG. **7D** further shows an adhesive **716** that is applied to the packaging material **114**, which may be within an interior of the container **122** and prior to the packaging material **114** being folded to create the container **122**. For example, the adhesive **716** may be applied to portions of the packaging material **114** that overlap and which are to be sealed upon one another. The adhesive **716** may be applied as a bead, line, drops, and so forth. In some instances, the adhesive **716** is spaced apart from the first longitudinal end **128** by a second depth **718**. The second depth **718** may be greater than the first depth **714** such that the adhesive does not contaminate the first punches **206** and the first dies **208**. As such, the first punches **206** and the first dies **208** may not contact the adhesive **716**, which may increase a longevity of the first punches **206** and/or the first dies **208**, and prevent debris, for example, accumulating on the first punches **206** and/or the first dies **208**.

(95) Although described as sealing longitudinal ends of the container **122**, the first upper press **210** and the first lower press **212** (as well as the other presses described herein), may be used to seal other portions of the container **122**. For example, the presses may be used to seal a seam along a top of the container **122**, or along other sides of the container **122**. In such instances, the presses may be reconfigured to permit their operation and to enclose upon the portions of the container **122** to seal the packaging material **114** together.

(96) FIG. **8** illustrates an example profile of a punch **800**, which may be representative of a punch usable by the first press **204** and/or the second press **220**. The punch **800** may include a first end **802** and a second end **804** spaced apart from the first end **802** (e.g., in the y-direction). The first end **802** may include a pointed tip to pierce through the packaging material **114**.

(97) The punch **800** may include a taper between the first end **802** and the second end **804**. For example, proximate the first end **802**, the punch **800** may include a first cross-sectional dimension **806**, and proximate the second end **804**, the punch **800** may include a second cross-sectional dimension **808**. The second cross-sectional dimension **808** may be greater than the first cross-sectional dimension **806**. In some instances, the taper may assist in pushing the packaging material **114** through holes in the packaging material **114** formed by the punch **800**. Additionally, upon retraction of the punch **800**, the taper may prevent the punch **800** snapping or otherwise catching on sidewalls of the hole.

(98) In some instances, an exterior surface **810** of the punch **800** may include extrusions **812** that spiral along the exterior surface **810**, between the first end **802** and the second end **804**. In some instances, the extrusions **812** may assist in pushing the packaging material **114** to from the tabs. Alternatively, rather than including the extrusions **812**, the punch **800** may include indents that spiral along the exterior surface **810**. Still, in some instances, the punch **800** may include ribs along the exterior surface **810** that assist in piercing through the packaging material **114**, forming the flaps, and/or pushing the flaps through the packaging material **114**.

(99) FIG. **9** illustrates an alternative example of a press **900** that may be used to secure portions of a container **122**. The press **900** may include a "C-shaped" design that is enclosed over/upon longitudinal ends of the container **122**. For example, the press **900** may include a frame **902** to

which punches **904** and dies **906** are operably coupled. In some instances, the punches **904** and the dies **906** translate along the frame **902** (e.g., in the y-direction) to compress the packaging material **114**, pierce through the packaging material **114**, and to form tabs that hold the packaging material **114** together. Operation of the punches **904** and the dies **906** may be otherwise similar to the embodiment described herein. Actuators may control operation of the punches **904** and/or dies **906** to compress the packaging material **114** and seal the container **122**.

(100) FIGS. **10A-10D** illustrate an alternative example of a press **1000** that may be used to secure portions of a container **122**. As shown in FIG. **10A**, in some instances, the press **1000** may include first punches (or dies) **1002** and second punches (or dies) **1004**. The first punches **1002** and the second punches **1004** are configured to actuate in a direction towards one another to pierce through the packaging material **114** while forming the container **122**. Individual punches of the first punches **1002** may include a piercing end **1006** to punch through the packaging material **114**, while individual punches of the second punches **1004** may include a piercing end **1008** to punch through the packaging material **114**.

(101) In some instances, the first punches **1002** may include a channel, receptacle, or trough **1010** in which at least a portion of the second punches **1004** are received. For example, when the first punches **1002** and the second punches **1004** actuate towards one another, and pierce through the packaging material **114**, the piercing end **1008** of the second punches **1004** may reside within the trough **1010**. In this instance, the piercing end **1008** of the second punches **1004** may be at least partially encapsulated within the trough **1010**. Furthermore, the trough **1010** may include a flared section **1012** that directs a tab of the packaging material **114** outward of the trough **1010**.

(102) Although not shown, actuators may couple to the first punches **1002** and the second punches **1004**. Additionally, in some instances, the press **1000** may further include one or more plates that compress the packaging material **114**, either before, after, or simultaneously with the first punches **1002** and the second punches **1004** punching through the packaging material **114**.

(103) Turning to FIG. **10B**, the first punches **1002** and the second punches **1004** are shown being engaged. As introduced above, the piercing end **1008** of the second punches **1004** may be disposed within the trough **1010** of the first punches **1002**. Additionally, the piercing end **1006** of the first punches **1002** may translate along an exterior surface of the second punches **1004**. As the second punches **1004** are actuated upward (e.g., in the y-direction), the packaging material **114** is directed out of the trough **1010** via the flared section **1012**.

(104) FIG. **10C** illustrates a view of one of the second punches **1004**. The second punch **1004** is shown including the piercing end **1008**, and a body **1014** that extends between the piercing end **1008** and a distal end **1016**. A side of the second punch **1004**, such as a back, that is insertable into the trough **1010** may include tapered sidewalls to match a contour of the interior surface of the trough **1010**. For example, the second punch **1004** may include a trapezoidal cross-section (X-Z plane).

(105) FIG. **10D** illustrates a view of one of the first punches **1002**. The first punch **1002** is shown including the piercing end **1006**, and a body **1030** that extends between the piercing end **1006** and a distal end **1018**. The body **1030** forms the trough **1010** in which a portion of the second punch **1004** is received. Additionally, sidewalls **1020** of the trough **1010** may taper outward, from a bottom of the trough **1010** to a top of the trough **1010**, so as to match the contour of the lower press **1000** (e.g., the trapezoidal cross section). The trough **1010** is further shown including the flared section **1012** to direct the packaging material **114** of the trough **1010**.

(106) FIG. **10E** illustrates an operation of the first punch **1002** and the second punch **1004**. The first punch **1002** and the second punch **1004** are shown piercing through a first piece of packaging material **1022** and a second piece of packaging material **1024**. As the first punch **1002** and the second punch **1004** are actuated towards one another, the second punch **1004** creates a first tab **1026** from the first piece of packaging material **1022** and a second tab **1028** from the second piece of packaging material **1024**. The first tab **1026** and the second tab **1028** are channeled within the

trough **1010**, via the sidewalls **1020**, and are advanced towards the flared section **1012** as the first punch **1002** and the second punch **1004** continue to actuate. The flared section **1012** forces the first tab **1026** and the second tab **1028** out of the trough **1010** such that the first piece of packaging material **1022** and the second piece of packaging material **1024** are folded over themselves (e.g., in the z-direction). The first tab **1026** and the second tab **1028** may curl or otherwise fold over an upper portion of the second press **1004** and back in a direction towards the first piece of packaging material **1022** and the second piece of packaging material **1024**. Therein, in some instances, the first tab **1026** and the second tab **1028** may be compressed to secure the first tab **1026** and the second tab **1028** in place and prevent the first tab **1026** and the second tab **1028** separating.

(107) FIG. **11** illustrates a sheet of the packaging material **114** at various stages as the container **122** is formed. At “1,” a first side **1100** of the sheet of the packaging material **114** may be folded over the item **106** to be packed. After the first side **1100** is folded, a second side **1102** may be folded over the first side **1100**. In some instances, the first side **1100** and the second side **1102** may be folded one at a time. In some instances, before the first side **1100** and the second side **1102** are folded, a first set of crease lines **1104** and a second set of crease lines **1106** may be formed on an upper surface of the packaging material **114**. The first set of crease lines **1104** and the second set of crease lines **1106** may be separated by a distance that is equal to or slightly greater than a width of the item **106** to be packed in the container **122**. The first set of crease lines **1104** and the second set of crease lines **1106** may include one or more crease lines formed, for example, using one or more rollers of the machine **102**.

(108) As also shown at “1,” the adhesive **716** may be applied along sides of the packaging material **114** to form a C-pattern. The adhesive **716** may be omitted from portions of the first side **1100** as the packaging material **114** may contact the item **106** once folded. However, in other instances, the adhesive **716** may be disposed in a different pattern about or more, such as all, sides of the packaging material **114**.

(109) At “2,” a first gusset **1108** and a second gusset **1110** may be formed as the first side **1100** and the second side **1102** are folded. Depending on the configuration of the container **122**, the first gusset **1108** and the second gusset **1110** may be folded inward-facing or outward-facing.

(110) At “3,” the sealing mechanism **124**, including the first punches **206**, the first dies **208**, the second punches **222**, and the second dies **224** may secure longitudinal ends of the container **122**. The first tabs **136** and the second tabs **138** formed at the first longitudinal end **128** and the second longitudinal end **130**, respectively, may prevent the container **122** opening prior to the adhesive **716** curing. In this manner, the sealing mechanism **124** serves to provide a redundant hold force during shipping without introducing additional materials.

(111) FIGS. **12A-12D** illustrate different holes and tabs to seal the container **122**. The views shown in FIGS. **12A-12D** may illustrate a bottom of the container **122** with the tabs, at the first longitudinal end **128**. However, it is to be understood that the tabs may be formed on a top of the container **122** at the first longitudinal end **128** and/or at other seams of the container **122**.

(112) In FIG. **12A**, triangular-shaped tabs are shown. The tabs, for example, may be formed from a triangular-shaped punch. The tabs are formed via at least a first piece **1200** of the packaging material **114** and a second piece **1202** of the packaging material **114**. For example, the first piece **1200** of the packaging material **114** may be formed from a piece of the packaging material **114** on a top of the container **122**, while the second piece **1202** of the packaging material **114** may be formed from a piece of the packaging material **114** on a bottom of the container **122**. As shown, the first piece **1200** of the packaging material **114** and the second piece **1202** of the packaging material **114** may be folded to prevent separation of the first piece **1200** of the packaging material **114** and the second piece **1202** of the packaging material **114**. Thereafter, the first piece **1200** of the packaging material **114** and the second piece **1200** of the packaging material **114** may be pressed together.

(113) In FIG. **12B**, circular-shaped tabs are shown. The tabs, for example, may be formed from a circular-shaped punch. The tabs are formed via at least a first piece **1204** of the packaging material

**114** and a second piece **1206** of the packaging material **114**. For example, the first piece **1204** of the packaging material **114** may be formed from a piece of the packaging material **114** on the top of the container **122**, while the second piece **1206** of the packaging material **114** may be formed from a piece of the packaging material **114** on the bottom of the container **122**. Thereafter, the first piece **1204** of the packaging material **114** and the second piece **1206** of the packaging material **114** may be pressed together.

(114) In FIG. **12C**, triangular-shaped tabs are shown. The tabs, for example, may be formed from a diamond-shaped punch. The tabs are formed via at least a first piece **1208** of the packaging material **114** and a second piece **1210** of the packaging material **114**. For example, the first piece **1208** of the packaging material **114** may be formed from a piece of the packaging material **114** on a top of the container **122**, while the second piece **1210** of the packaging material **114** may be formed from a piece of the packaging material **114** on a bottom of the container **122**. As shown, the first piece **1208** of the packaging material **114** and the second piece **1210** of the packaging material **114** may be folded to prevent separation of the first piece **1208** of the packaging material **114** and the second piece **1210** of the packaging material **114**. Thereafter, the first piece **1208** of the packaging material **114** and the second piece **1210** of the packaging material **114** may be pressed together.

(115) In FIG. **12D**, triangular-shaped tabs are shown. As shown, the tabs may be folded over along the first longitudinal end **128** and in a direction into the container **122**. The tabs are formed via at least a first piece **1212** of the packaging material **114** and a second piece **1214** of the packaging material **114**. For example, the first piece **1212** of the packaging material **114** may be formed from a piece of the packaging material **114** on a top of the container **122**, while the second piece **1214** of the packaging material **114** may be formed from a piece of the packaging material **114** on a bottom of the container **122**. As shown, the first piece **1212** of the packaging material **114** and the second piece **1214** of the packaging material **114** may be folded to prevent separation of the first piece **1212** of the packaging material **114** and the second piece **1214** of the packaging material **114**. Thereafter, the first piece **1212** of the packaging material **114** and the second piece **1214** of the packaging material **114** may be pressed together.

(116) Although particular shaped tabs are shown, the punches and/or dies may include other shapes. In some instances, the portions of the tabs that are folded may be between about two mm and about 10 mm. In some instances, the portions of the tabs that are folded may not exceed six mm in length and four mm in width. However, in some instances, the size of the tabs may differ with various corrugate thicknesses and types.

(117) FIG. **11** illustrates a process **1300** for sealing a container. The process **1300** described herein is illustrated as collections of blocks in logical flow diagrams, which represent a sequence of operations, some or all of which may be implemented in hardware, software, or a combination thereof. In the context of software, the blocks may represent computer-executable instructions stored on one or more computer-readable media that, when executed by one or more processors, program the processors to perform the recited operations. Generally, computer-executable instructions include routines, programs, objects, components, data structures and the like that perform particular functions or implement particular data types. The order in which the blocks are described should not be construed as a limitation, unless specifically noted. Any number of the described blocks may be combined in any order and/or in parallel to implement the process, or alternative processes, and not all of the blocks need be executed. For discussion purposes, the process **1300** is described with reference to the environments, architectures, devices, and systems described in the examples herein, such as, for example those described with respect to FIGS. **1-12**, although the process **1300** may be implemented in a wide variety of other environments, architectures, devices, and systems.

(118) At **1302**, the process **1300** may include determining dimensions of an item to be packaged. For example, sensor(s) **112** of the machine **102** may determine the dimensions of the item **106**. As explained herein, the dimensions of the item **106** are usable to appropriately size a container around

the item **106**.

(119) At **1304**, the process **1300** may include causing a container to be formed around the item. For example, folding mechanisms of the machine **102** may fold, crease, or otherwise form the container **122** around the item **106**. In some instances, the container **122** may be formed around the item **106**, but the container **122** itself may not be enclosed (e.g., sealed).

(120) For example, the packaging material **114** may be wrapped around the item **106**, but ends or seams of the packaging material **114** may not be secured.

(121) At **1306**, the process **1300** may include causing punch(es) to be activated to form holes and tabs from packaging material along a seam of the package. For example, press(es) may actuate to form the holes, and correspondingly, the tabs from the packaging material of the first holes, respectively. In some instances, the press(es) include a plurality of punches that pierce through the packaging material **114**, as well as a plurality of dies that receive the plurality of punch(es), respectively. In some instances, the punch(es) and dies may actuate in directions towards one another, so as to pierce through the packaging material **114**.

(122) At **1308**, the process **1300** may include compressing the tabs to seal the seam. For example, plates of the press(es) may be actuated to compress the tabs and prevent separation of the packaging material along the seam.

(123) At **1310**, the process **1300** may include causing the package to be released. In some instances, causing the container to be released may include opening the press(es) of the machine **102** such that the container **122** may be removed from the machine **102** and further processed.

(124) While the foregoing invention is described with respect to the specific examples, it is to be understood that the scope of the invention is not limited to these specific examples. Since other modifications and changes varied to fit particular operating requirements and environments will be apparent to those skilled in the art, the invention is not considered limited to the example chosen for purposes of disclosure, and covers all changes and modifications which do not constitute departures from the true spirit and scope of this invention.

(125) Although the application describes embodiments having specific structural features and/or methodological acts, it is to be understood that the claims are not necessarily limited to the specific features or acts described. Rather, the specific features and acts are merely illustrative some embodiments that fall within the scope of the claims of the application.

## Claims

1. A method comprising: causing packaging material to surround an item; causing one or more first punches to actuate to pierce through the packaging material at a first location, wherein individual first punches of the one or more first punches are independently actuatable; causing one or more first dies to actuate to receive a first portion of the individual first punches of the one or more first punches, wherein individual first dies of the one or more first dies are independently actuatable; causing one or more second punches to actuate to pierce through the packaging material at a second location, wherein individual second punches of the one or more second punches are independently actuatable; causing one or more second dies to actuate to receive a second portion of the individual second punches of the one or more second punches, wherein individual second dies of the one or more second dies are independently actuatable; causing a first press to compress the packaging material at the first location; and causing a second press to compress the packaging material at the second location.

2. The method of claim 1, wherein: the individual first punches create first tabs from the packaging material that are compressed via the first press to secure the packaging material together at the first location; and the individual second punches create second tabs from the packaging material that are compressed via the second press to secure the packaging material together at the second location.

3. The method of claim 2, wherein: at the first location, the packaging material includes a first

segment of a first layer of the packaging material and a second segment of a second layer of the packaging material; the first tabs are created from the first segment of the first layer and the second segment of the second layer; the first tabs are compressed against the second layer of the packaging material; at the second location, the packaging material includes a third segment of the first layer of the packaging material and a fourth segment of the second layer of the packaging material; the second tabs are created from the third segment of the first layer and the fourth segment of the second layer; and the second tabs are compressed against the second layer of the packaging material.

4. The method of claim 1, wherein: the one or more first punches are arranged in a first line; the individual first punches are equidistantly spaced apart from one another along the first line; the one or more second punches are arranged in a second line; and the individual second punches are equidistantly spaced apart from one another along the second line.

5. The method of claim 1, wherein at least one of: the first location corresponds to a first longitudinal end of a container; or the second location corresponds to a second longitudinal end of the container.

6. The method of claim 1, further comprising applying an adhesive adjacent to the first location and the second location.

7. The method of claim 6, wherein: the one or more first punches form one or more first holes in the packaging material; the one or more first holes are spaced apart from a first seam of the packaging material by a first distance; a first section of the adhesive is disposed on the packaging material at a second distance from the first seam, the second distance being greater than the first distance; the one or more second punches form one or more second holes in the packaging material; the one or more second holes are spaced apart from a second seam of the packaging material by a third distance; and a second section of the adhesive is disposed on the packaging material at a fourth distance from the second seam, the fourth distance being greater than the third distance.

8. The method of claim 1, wherein: the one or more first punches are at least partially disposed through the packaging material at the first location during compression of the packaging material via the first press; and the one or more second punches are at least partially disposed through the packaging material at the second location during compression of the packaging material via the second press.

9. The method of claim 1, wherein: the first press includes a plurality of first upper presses and a plurality of first lower presses; individual first presses of the plurality of first upper presses include a first upper plate and the individual first punches of the one or more first punches; individual second presses of the plurality of first lower presses include: a first lower plate that compresses the packaging material between the first upper plate, and individual first dies of the one or more first dies; the second press includes a plurality of second upper presses and a plurality of second lower presses; individual third presses of the plurality of second upper presses include a second upper plate and the individual second punches of the one or more second punches; and individual fourth presses of the plurality of second lower presses include: a second lower plate that compresses the packaging material between the second upper plate, and individual second dies of the one or more second dies.

10. A method comprising: causing a first punch to actuate in a first direction to pierce through a packaging material that is used to form a container, between a top surface of the packaging material and a bottom surface of the packaging material, wherein the first punch forms at least a first tab from the top surface of the packaging material and a second tab from the bottom surface of the packaging material; causing a first die to actuate in a second direction to receive a first portion of the first punch; causing a second punch to actuate in the first direction to pierce through the packaging material, between the top surface and the bottom surface, wherein the second punch forms at least a third tab from the top surface of the packaging material and a fourth tab from the

bottom surface of the packaging material; causing a second die to actuate in the second direction to receive a second portion of the second punch; causing a first upper press and a first lower press to actuate to compress the packaging material at a first end of the container, wherein at least the first tab and the second tab are compressed via the first lower press against the bottom surface of the packaging material; and causing a second upper press and a second lower press to actuate to compress the packaging material at a second end of the container, wherein at least the third tab and the fourth tab are compressed via the second lower press against the bottom surface of the packaging material.

11. The method of claim 10, further comprising: causing a third punch to actuate in the first direction to pierce through the packaging material, between the top surface and the bottom surface, at the first end of the container; causing a third die to actuate in the second direction to receive a third portion of the third punch; causing a fourth punch to actuate in the first direction to pierce through the packaging material, between the top surface and the bottom surface, at the second end of the container; causing a fourth die to actuate in the second direction to receive a fourth portion of the fourth punch; causing a third upper press and a third lower press to actuate to compress the packaging material at the first end of the container; and causing a fourth upper press and a fourth lower press to actuate to compress the packaging material at the second end of the container.

12. The method of claim 11, wherein: the first upper press, the second upper press, the third upper press, and the fourth upper press are independently actuatable; and the first lower press, the second lower press, the third lower press, and the fourth lower press are independently actuatable.

13. A method comprising: causing a packaging material to surround an item; causing one or more first punches to actuate to pierce through the packaging material at a first location to form first tabs, wherein at the first location, the packaging material includes a first segment of a first layer of the packaging material and a second segment of a second layer of the packaging material, and wherein the first tabs are created from the first segment of the first layer and the second segment of the second layer; causing one or more second punches to actuate to pierce through the packaging material at a second location to form second tabs, wherein at the second location, the packaging material includes a third segment of the first layer of the packaging material and a fourth segment of the second layer of the packaging material, and wherein the second tabs are created from the third segment of the first layer and the fourth segment of the second layer; causing a first press to compress the packaging material at the first location to compress the first tabs to secure the packaging material together, wherein the first tabs are compressed against the second layer of the packaging material; and causing a second press to compress the packaging material at the second location to compress the second tabs to secure the packaging material together, wherein the second tabs are compressed against the second layer of the packaging material.

14. The method of claim 13, further comprising: causing one or more first dies to actuate to receive a first portion of individual first punches of the one or more first punches; and causing one or more second dies to actuate to receive a second portion of individual second punches of the one or more second punches.

15. The method of claim 13, wherein at least one of: the first location corresponds to a first longitudinal end of a container; or the second location corresponds to a second longitudinal end of the container.

16. The method of claim 13, further comprising applying an adhesive adjacent to the first location and the second location.

17. The method of claim 13, wherein at least one of: the one or more first punches form first holes that are triangular shaped, circular shaped, diamond shaped, or square shaped; the one or more second punches form second holes that are triangular shaped, circular shaped, diamond shaped, or square shaped; or the first tabs or the second tabs are triangular shaped, circular shaped, diamond shaped, or square shaped.

---



