

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent	12391333
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Riley; Brian Michael et al.

---

### Hydraulic brake system and apparatus

---

#### Abstract

The present invention is directed towards a disk braking system for a bicycle having a rear disk coupled to a rear wheel. A rear brake caliper is coupled to a rear brake lever and the rear brake caliper is also coupled to a hydraulic actuator which has a piston that slides within a cylinder filled with hydraulic fluid and hydraulic tubing coupled to the cylinder and a front brake. When the rear wheel and rear disk are rotating, the rear brake caliper can be actuated which causes compresses rear brake caliper against the rear disk to slow the rotation of the rear wheel. The movement of the rear brake caliper can actuate the hydraulic actuator which causes hydraulic fluid to flow through the hydraulic tubing to actuate a front brake.

---

<b>Inventors:</b>	<b>Riley; Brian Michael (Seymour, IN), Tong; Roger (Berkeley, CA)</b>
<b>Applicant:</b>	<b>Syscend, Inc. (Seymour, IN)</b>
<b>Family ID:</b>	<b>1000008767447</b>
<b>Assignee:</b>	<b>Syscend, Inc. (Seymour, IN)</b>
<b>Appl. No.:</b>	<b>18/581110</b>
<b>Filed:</b>	<b>February 19, 2024</b>

#### Prior Publication Data

Document Identifier	Publication Date
US 20240351662 A1	Oct. 24, 2024

#### Related U.S. Application Data

continuation parent-doc US 16923443 20200708 US 11919605 child-doc US 18581110  
continuation parent-doc US 14612166 20150202 US 10252770 20190409 child-doc US 16379514  
continuation-in-part parent-doc US 16379514 20190409 US 11390355 20220719 child-doc US 16923443

Publication Classification

Int. Cl.: B62L3/08 (20060101); B62L1/10 (20060101); B62L3/02 (20060101)

U.S. Cl.:

CPC B62L3/08 (20130101); B62L3/02 (20130101); B62L1/10 (20130101)

Field of Classification Search

CPC: B62L (1/00); B62L (1/10); B62L (1/12); B62L (1/005); B62L (3/02); B62L (3/08); B60T (1/04); B60T (1/06); B60T (11/046); B60T (11/06); B60T (11/10)

USPC: 188/24.22

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
662602	12/1899	Schmidt et al.	N/A	N/A
2871988	12/1958	Wilkerson	N/A	N/A
3173517	12/1964	Powlas	N/A	N/A
3547229	12/1969	Pollinger et al.	N/A	N/A
3842946	12/1973	Blevens	N/A	N/A
3882971	12/1974	Peckham, Jr.	N/A	N/A
3989124	12/1975	Fujii	N/A	N/A
4015690	12/1976	Armstrong	N/A	N/A
4020925	12/1976	Ryan et al.	N/A	N/A
4061206	12/1976	Wood	N/A	N/A
4102439	12/1977	Calderazzo	N/A	N/A
D281874	12/1984	King	N/A	N/A
D295847	12/1987	Everett	N/A	N/A
D310199	12/1989	Herner	N/A	N/A
5107965	12/1991	Yates	N/A	N/A
5364250	12/1993	Aoki et al.	N/A	N/A
5431257	12/1994	Rocca et al.	N/A	N/A
5501301	12/1995	Nishimura	N/A	N/A
5564531	12/1995	Lumpkin	N/A	N/A
5632362	12/1996	Leitner	N/A	N/A
5775466	12/1997	Banyas et al.	N/A	N/A
5813501	12/1997	Terry, Sr.	N/A	N/A
5927442	12/1998	Liao	N/A	N/A
5997262	12/1998	Finkbeiner et al.	N/A	N/A
6098486	12/1999	Liao	N/A	N/A
6164153	12/1999	Scura	N/A	N/A

D436334	12/2000	Takizawa	N/A	N/A
6386328	12/2001	Chen	N/A	N/A
6615955	12/2002	Jakovljevic	N/A	N/A
6634467	12/2002	Liu	188/24.16	B60T 11/046
D495635	12/2003	Everett	N/A	N/A
6884049	12/2004	Hida et al.	N/A	N/A
6899202	12/2004	McIntyre	N/A	N/A
7537094	12/2008	Kato	N/A	N/A
D603766	12/2008	Huang	N/A	N/A
D603767	12/2008	Crippa et al.	N/A	N/A
8230984	12/2011	Moore	N/A	N/A
8333266	12/2011	Ouellet	N/A	N/A
D688996	12/2012	Arbesman et al.	N/A	N/A
8960378	12/2014	Moore	N/A	N/A
9759277	12/2016	Kobayashi et al.	N/A	N/A
10215243	12/2018	Riley et al.	N/A	N/A
10252770	12/2018	Riley et al.	N/A	N/A
D879687	12/2019	Remy et al.	N/A	N/A
10780736	12/2019	Madhaven	N/A	N/A
11390355	12/2021	Riley et al.	N/A	N/A
11866124	12/2023	Riley et al.	N/A	N/A
11919605	12/2023	Riley et al.	N/A	N/A
2002/0185349	12/2001	Jakovljevic	188/344	B62L 3/08
2005/0000756	12/2004	Biria	N/A	N/A
2007/0227834	12/2006	Mieze	188/2R	B60T 13/02
2007/0284203	12/2006	Tetsuka	188/344	B62L 3/023
2009/0302565	12/2008	Ouellet	N/A	N/A
2010/0007112	12/2009	Ouellet	N/A	N/A
2010/0051394	12/2009	Tsai	N/A	N/A
2010/0230214	12/2009	Tseng	N/A	N/A
2011/0000749	12/2010	Yamashita	411/395	B60T 11/16
2017/0151829	12/2016	Neutsch	N/A	N/A
2017/0283000	12/2016	Huang et al.	N/A	N/A
2021/0394861	12/2020	Riley et al.	N/A	N/A

## FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
26 57 350	12/1976	DE	N/A
41 22 491	12/1992	DE	N/A
42 16 461	12/1992	DE	N/A
20309375	12/2002	DE	B60T 11/046
0 378 009	12/1989	EP	N/A
0 533 950	12/1992	EP	N/A
0 907 023	12/1998	EP	N/A
1 266 820	12/2001	EP	N/A

1 643 127	12/2005	EP	N/A
2 003 563	12/1978	GB	N/A
H08-144964	12/1995	JP	N/A
2005-214140	12/2004	JP	N/A
2007-177735	12/2006	JP	N/A
2009-013832	12/2008	JP	N/A
3159551	12/2009	JP	N/A
WO 2011/075502	12/2010	WO	N/A

## OTHER PUBLICATIONS

English machined translation of DE-4216461 A1, Nov. 25, 1993. cited by examiner  
International Search Report and Written Opinion in Application No. PCT/US2010/060411, mailed Feb. 22, 2011 in 8 pages. cited by applicant

---

*Primary Examiner:* Siconolfi; Robert A.

*Assistant Examiner:* Aung; San M

*Attorney, Agent or Firm:* Knobbe, Martens, Olson & Bear, LLP

---

## Background/Summary

INCORPORATION BY REFERENCE TO ANY PRIORITY APPLICATIONS (1) This patent application is a continuation of U.S. patent application Ser. No. 16/923,443, filed Jul. 8, 2020, which claims priority to U.S. Provisional Patent Application No. 62/871,279, filed Jul. 8, 2019, and is also a continuation in part of U.S. patent application Ser. No. 16/379,514, filed Apr. 9, 2019, now U.S. Pat. No. 11,390,355, which is a continuation of U.S. patent application Ser. No. 14/612,166, filed Feb. 2, 2015, now U.S. Pat. No. 10,252,770, which claims the benefit of U.S. Provisional Patent Application 61/934,538, filed Jan. 31, 2014, all of which are incorporated by reference in their entireties along with all other patent applications and/or patents cited in this application.

### BACKGROUND

(1) A two-wheeled vehicle is equipped with a brake system to slow or stop its moving by applying friction upon its wheels. A rider uses both hands to press two brake levers, fixed on the handlebar, to control a front and rear brake of the two-wheeled vehicle. However, it would be dangerous if the rider presses either one of the brake levers too hard to make the vehicle's wheel to be locked by the front or rear brake. It is uncontrollable and dangerous for a moving two-wheeled vehicle with one of its wheels being locked, e.g. the vehicle may skid on the ground. In the instance of a two-wheeled vehicle's tip over, the two-wheeled vehicle still moves with its front wheel being locked such that the rider may fall over beyond a handlebar of the two-wheeled vehicle when a rear wheel comes off the ground by a sufficient height. For the foregoing reasons, there is a need for preventing a moving two-wheeled vehicle from a tip-over or a wheel being locked.

### SUMMARY

(2) The present invention relates to a brake system and method. More particularly, the present invention relates to a brake system and method for a two-wheeled vehicle such as a bicycle or a scooter which can be human or electric powered. For simplicity, the vehicle can be described as a bicycle, however the described braking system can be used for human and engine or motor powered bicycles, scooters, and other vehicles. A braking system includes a rear and a front hydraulic disk brake. The rear brake may be a disc brake. A first hydraulic line filled with a

hydraulic fluid is coupled to the front brake which is coupled to a hydraulic piston in a cylinder which is connected to the moveable structure coupled to a rear disk brake. When the rear brake is actuated, the moveable structure moves. The movement of the structure compresses the hydraulic piston into the cylinder which results in compressed hydraulic fluid in a second hydraulic line which actuates the front brake. The movement may include a translation, rotation, or both. If the rear wheel loses traction or is moved away from the ground, the rear disk no longer compresses the hydraulic piston in a cylinder which reduces the pressure in the hydraulic fluid in the second hydraulic line which deactivates the front brake which prevents the vehicle from flipping over due to a locked front brake.

(3) In a specific embodiment, an apparatus includes a lever coupled to a rear hydraulic disk brake, a hydraulic lever is coupled an end of a first hydraulic tubing, an opposite end of the rear brake hydraulic tubing being coupled to a rear hydraulic brake, and a first end of a second hydraulic tubing coupled to a moveable portion of the rear brake and an opposite end of the second hydraulic tubing being coupled to a front hydraulic brake, wherein when the rear brake is actuated by the rear brake lever, the hydraulic fluid is forced through the second hydraulic tubing, thereby actuating the front brake.

(4) In another specific embodiment, an apparatus includes a pivot point; a brake mount to attach a rear disc brake; and a lever arm extending away from the pivot point. The lever arm is coupled to a hydraulic piston in a cylinder. A second hydraulic tubing coupled to the cylinder and coupled to a front hydraulic brake, wherein when the rear disc brake is actuated, the lever arm compresses the piston within the cylinder, pressurizing the hydraulic fluid in the second hydraulic tubing to actuate the front brake.

(5) In another specific embodiment, an apparatus includes a first link of a linkage and comprising a first joint, a second joint, and a hydraulic actuator attachment end, wherein the second joint connects to a first tab on a bicycle frame and is between the first joint and the hydraulic actuator attachment end; a second link of the linkage connected to the first joint and comprising a first mount, opposite the first joint, for a disc brake; and a third link of the linkage and comprising a fourth joint and a second mount, opposite the fourth joint, for the disc brake, wherein the fourth joint connects to a second tab on the bicycle frame. Movement of the rear brake linkages results in compression of the hydraulic piston in the cylinder which pressurizes the hydraulic fluid in the second hydraulic tubing to actuate the front brake.

(6) In each of these examples, if the rear wheel loses traction or is moved away from the ground and the braking friction force of the rear tire against the ground decreases or is eliminated. This release of the rear brake force results in the rear disk brake no longer compressing the hydraulic piston in a cylinder which reduces the pressure in the hydraulic fluid in the second hydraulic line which deactivates or reduces the front brake force which prevents the vehicle from flipping over due to a locked front brake.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

(1) The accompanying drawings are included to provide a further understanding of the invention, and are incorporated in and constitute a part of this specification. The drawings illustrate embodiments of the invention and, together with the description, serve to explain the principles of the invention. In the drawings, invention;

(2) FIGS. 1-3 illustrate diagrams of embodiments of the inventive braking system;

(3) FIGS. 4 and 5 illustrate top views of a brake according to an embodiment of the invention;

(4) FIGS. 6 and 7 illustrate hydraulic actuators;

(5) FIG. 8 illustrates a side view of a rear brake system;

- (6) FIG. **9** illustrates a side view of a front brake;
- (7) FIG. **10** illustrates a side view of a rear disk brake system;
- (8) FIG. **11** illustrates a side view of a rear disk brake;
- (9) FIG. **12** illustrate a side view of a rear disk brake system;
- (10) FIG. **13** illustrate a side perspective view of a rear disk brake system;
- (11) FIGS. **14-18** illustrate left side perspective views of rear disk brakes mounted on to rotating linkages;
- (12) FIGS. **19-21** illustrate right side perspective views of rear disk brakes mounted on to rotating linkages;
- (13) FIGS. **22-24** illustrate side perspective views of a rear disk brake on a linear movement track assembly;
- (14) FIG. **25** illustrates a left side perspective view of rear disk brake mounted on an actuate movement assembly;
- (15) FIG. **26** illustrates a left side view of rear disk brake mounted on rotational assembly;
- (16) FIG. **27** illustrates a left side perspective view of rear disk brake mounted on rotational assembly;
- (17) FIG. **28** illustrates a side view of rear disk brake mounted on to movable linkages; and
- (18) FIGS. **29-31** illustrate side views of rear disk brakes mounted lever arms coupled to hydraulic actuators.

#### DETAILED DESCRIPTION

(19) Reference will now be made in detail to the present embodiments of the invention, examples of which are illustrated in the accompanying drawings. Wherever possible, the same reference numbers are used in the drawings and the description to refer to the same or like parts. With reference to FIG. **1**, the present invention is directed towards a brake system **10** that can be used for bicycles and other vehicles supported by multiple wheels. The inventive braking system **10** that can include two or more brake mechanisms **15, 19, 23, 27, 31** that are actuated by one or more brake controls **11**, such as hand brake levers or foot brake pedals. When the user squeezes the one or more brake levers or steps on the foot brake pedal, a first brake actuator **13** actuates the first brake **15**. The friction force of a disk brake caliper pad in the first brake **15** against a rotating disk brake rotor structure then actuates a second brake actuator **17** which can be a hydraulic actuator coupled to the second disk brake **19** so that both brakes **15, 19** are engaged to slow or stop the vehicle. The first brake **15** that is directly controlled by the brake controls **11** and can be mounted on any brake on a vehicle.

(20) It is also possible for the first brake to control multiple brake actuators **17, 25** which can each be hydraulic actuators. For example, a first (rear) brake **15** can be coupled to a second (front left) hydraulic brake actuator **19** can control the second (front left) brake **19** and a third (front right) hydraulic brake actuator **25** can control the third (front right) brake **27** of the vehicle. For example, the brake controls **11** can actuate the first brake actuator **13** which is coupled to the first brake **15**. The braking friction of the first brake **15** can actuate a second brake actuator **17** coupled to the second brake **19**. The braking friction of the second brake **19** can actuate a fourth brake actuator **21** coupled to a fourth brake **23**. Similarly, the braking friction of the third brake **27** can actuate the fifth brake actuator **29** coupled to a fifth brake **31**. This sequential brake actuator configuration can continue to three or more brakes.

(21) The following description is primarily directed towards a two wheeled powered bicycle or scooter. In an embodiment, the first brake is the rear hydraulic disk brake and the second brake is the front hydraulic disk brake. The disclosed designs and operating principles can be applied to any multiple wheeled vehicle and the scope of the application is intended to cover the inventive braking system applied to all multiple wheeled vehicle configurations.

(22) Normal human and motor powered bicycle and scooter brakes can include two hand levers which are used to individually control a front brake and a rear brake. A problem with existing brake

systems is that the bicycle rider must be careful when applying the brakes because if the front brake is actuated to the point that the front wheel is locked and stops rotating, the stopping force can flip the rider off of the bicycle. There are several techniques for efficient braking on a two-brake bicycle. The one most commonly taught is the 25-75 technique. This method entails supplying 75% of the stopping power to the front brake, and about 25% of the power to the rear. Since the bicycle's deceleration causes a transfer of weight to the front wheel, there is much more traction on the front wheel. However, excessive front braking force can cause skidding of the front tire which can cause the bike to flip forward over the front wheel and probably injury to the rider. Excessive rear braking force can cause skidding, but will not result in the bike flipping. The present invention is directed towards a brake system and apparatus which allows the rider to quickly stop the bicycle or other vehicle very quickly, but prevents the front wheel from locking up or being slowed too quickly. The brake system is also compatible with existing brake designs and can be produced in a very economical manner so that bicycle riders will not have to pay a significant amount of money for these very important safety features. In an embodiment, the inventive brake system can be retrofitted onto existing bicycle brakes and in other embodiments, the inventive brake system can be incorporated into the designs of the brakes.

(23) The present invention is directed towards a brake system and apparatus which allows the rider to quickly stop the bicycle or other vehicle very quickly, but prevents the front wheel from locking up or being slowed too quickly. The brake system is also compatible with existing brake designs and can be produced in a very economical manner so that bicycle riders will not have to pay a significant amount of money for these very important safety features. In an embodiment, the inventive brake system can be retrofitted onto existing bicycle brakes and in other embodiments, the inventive brake system can be incorporated into the designs of the brakes.

(24) A bicycle has a frame on which a front wheel and a rear wheel are mounted. In an embodiment, one or two brake levers are fastened on a handlebar and the lever(s) are connected to a rear brake actuator which is coupled to a rear brake. A hydraulic actuator is coupled between the front brake and the rear brake. The rear brake can include one or two disk brake pad assemblies. When the rear brake is actuated by the rear brake lever, a portion of the rotating rear disk brake rotor is compressed between two or more brake pads and the friction generated by the direct contact of the brake pad with the rotating braking surface slows the rotational velocity of the rear wheel which is coupled to the rear disk brake rotor. One or more of the brake pads in the rear brake can include a coupling to a hydraulic actuator. In response to the direct contact between the disk brake pads with the rotating disk brake rotor braking surface. The friction between the rear disk brake caliper and the rotating rear disk brake rotor causes movement of the rear brake caliper and this movement actuates the hydraulic actuator which pressurizes hydraulic fluid in a hydraulic tubing which actuates the front brake and slows the rotation of the front wheel. When the rear brake is released, the disk brake pads are pulled away from the rear disk brake rotor and the hydraulic actuator is no longer compressed which releases the front brake.

(25) If the braking occurs quickly, the weight of the rider can shift forward and the deceleration force applied by the front wheel at the point of contact with the ground can cause the rear wheel to be lifted from the ground. This loss of surface contact will reduce or eliminate the rotational force applied by the ground to the rear wheel. Because the actuation force applied to the front brake is proportional to the rotational force of the rear wheel, the braking force applied to the front wheel will also be reduced until the rear wheel regains contact with the ground. The contact will generate a rotational force to the rear wheel and the rear disk brake pads will be actuated again and apply a force to the hydraulic actuator which will again actuate the front brake. By automatically detecting the rotational force applied to the rear wheel and adjusting the front brake force proportionally, the inventive braking system and brake pad assembly prevents the front wheel from skidding which allows the rider to remain in control of the bicycle even if excessive braking forces are applied. Since the front brake **106** force is controlled to the rear wheel rotational force, a rider can increase

the braking force by moving as much body weight over the rear wheel as possible during braking. However, even if the rider shifts his or her weight forward while riding, hard braking will not cause the bicycle to stop in a manner that would flip the bicycle over the front wheel.

(26) FIG. 2 illustrates a brake system according to one embodiment of this invention. The brake system can include a brake lever(s) **202**, a first brake actuator **203**, a first disk brake **206**, a second brake actuator **250** and a second disk brake **206**. When the brake lever **202** is squeezed, it transfers a braking force to the first brake actuator **203** which applies the first disk brake **206**. The friction force of the disk brake pad assembly in the first brake **206** transmits a compression force to the second brake actuator **250** which can be a hydraulic actuator which actuates the second disk brake **208**.

(27) FIG. 3 illustrates a brake system according to another embodiment of this invention. The brake system may include two brake levers **302a**, **302b**, a first brake actuator **309**, a first disk brake **304**, a second brake actuator **350** and a second disk brake **306**. In this embodiment, two brake levers **302a**, **302b** are used to actuate the first disk brake **304**. In an embodiment, the first brake actuator **309** can be hydraulic that can be split into a first hydraulic tubing **309a** and a second hydraulic tubing **309b** which are pressurized by actuation of a first brake lever **302a** and/or a second brake lever **302b** by a user's hands. In this configuration, a rider may use both hands to apply brake forces on the two brake levers **302a**, **302b** to actuate the rear brake **304**.

(28) With reference to FIGS. 4 and 5, in other embodiments, a top view of a rear hydraulic brake assembly is illustrated. The disk brake **401** can include a slider assembly **403** and a guide **407** that are coupled to an arm **404** of the first brake **401**. The brake pad assembly **414** can include a slider assembly **403** that can slide within the guide **407**. The brake **401** can be mounted around a portion of the first disk brake rotor with the brake pads **402** aligned on opposite sides of a first disk brake rotor **411**. When the vehicle moves forward, the upper portion of the disk brake rotor **411** also moves forward. The brake **401** can have two brake pads **402**. In an embodiment, the brake pad **402** on the right side is coupled to a slider assembly **403** that moves within a guide **407**. The guide **407** can be coupled to a mounting rod **410** which is secured to the brake arm **404**. The slider assembly **403** can include a brake pad **402** which can be compressed against the rotating rim **411**. The brake pad assembly **403** can also include a layer of lubricious material **412** such as Nylatron, Teflon, graphite or other low coefficient of friction and high compression strength materials. Alternatively, the brake assembly **403** components can be made of these low friction materials.

(29) The orientation of the slider assembly **403**, brake pad **402** and guide **407** on the bicycle can depend upon the position of the brake **401** on the wheel. If the brake **401** is located on the upper half of the disk brake rotor **411**, the described and illustrated positions are correct. However, if the brake is on the lower half of the disk brake rotor **411**, the “front” and “back” of the bicycle can be reversed.

(30) The slider assembly **403** can also be coupled to a second brake actuator. In an embodiment, the second brake actuator can be a hydraulic actuator having an end fitting **124** which can have a stepped cylindrical design with a first smaller diameter and a larger end diameter. The fitting **124** can engage an open hole coupling mechanism **132** on the slider **403**. The hole in the coupling mechanism **132** can be slightly larger than the first smaller diameter and smaller than the larger end diameter so that the fitting **124** is securely connected to the coupling mechanism **132**.

(31) The brake pad **402** on the left side of the disk brake rotor **411** can be a normal brake pad. In an embodiment, the brake pad **402** can be coupled to a mount **410** that extends away from the disk brake rotor **411** braking surface. The brake pad **402** can be secured to the brake caliper **404** by a nut **408** that is screwed onto the mounting rod **410**. When the brake **401** is not actuated, the brake pads **402** are pulled away from the disk brake rotor **411** by springs in the brake **401**.

(32) The rear brake **401** is coupled to a brake actuator which can be a brake lever(s). When the lever(s) is actuated, the inventive brake pads **402** is pressed against the disk brake rotor **411** which is coupled to the rear wheel to slow or stop the rear wheel rotation. The slider assembly **403** and



guide **407** are aligned with the brake pad **402** and the disk brake rotor **411** so that the movement of the slider **403** and brake pad **402** are also aligned with the disk brake rotor **411**.

(33) The hydraulic pressure can be proportional to the friction force of the brake pad **402** against the disk brake rotor **411**. A higher braking force applied to the first brake will result in a higher braking force applied to the second brake through the hydraulic tubing **477**.

(34) However, if the rear wheel loses traction with the road, the disk brake rotor **411** may stop rotating and the friction force that creates the hydraulic pressure and the brake force applied to the second brake are reduced until the rear wheel regains traction and begins to rotate the disk brake rotor **411** again. Since the rear wheel may lose traction when excessive braking is applied to the front brake the rear wheel is starting to lift off the ground, this system effectively functions as an anti-locking brake system.

(35) The coefficient of friction of the brake pad **402** sliding against the rim can depend upon the brake pad **402** and disk brake rotor **411** materials. The disk brake rotor **411** can be made of aluminum, carbon fiber, titanium, steel, and other metals or metal alloys. The brake pad **402** can be a plastic, rubber, metal, carbon composites or other high coefficient of friction material or attached in any other suitable manner to a brake support structure. The slider brake support structure and brake pad **402** can also be configured to apply uniform pressure to the contact areas where the brake pads contact the disk brake rotor **411**.

(36) The rear brake assembly can be coupled to a hydraulic cylinder **471** filled with hydraulic fluid **475**. The cylinder **471** can be coupled to the guide **407** and the slide assembly **403** can be coupled to a piston rod **479** that is attached to a piston **473** that can move within the cylinder **471**. One end of the brake hydraulic tubing **477** is coupled to a cylinder **471** and the opposite end is coupled to the second brake. With reference to FIG. 23, a spring in the second brake pressurizes the hydraulic fluid **475** pressing the piston **473** towards the back of the cylinder **471**. The hydraulic brake system can be a disc brake. In the normal position, the brake shoe **402** is not in contact with the disk brake rotor **411**.

(37) With reference to FIG. 5, in the braking position the brake pads **402** are pressed against the moving disk brake rotor **411**. The slider **403** moves forward due to the friction of the brake pad **402** against the rim **411**. The slider **403** pushes the rod **479** and the piston **471** within the cylinder **471** pressuring the hydraulic fluid **475**. The pressurized hydraulic fluid **475** exits the cylinder **471** and flows through the hydraulic tubing **477** to actuate a second hydraulic brake coupled to a front wheel. If the disk brake rotor **411** stops rotating due to the rear wheel's lack of contact with the road, the friction force and the force moving the slider **403** forward will decrease. The forces on the piston **473** will decrease and the hydraulic fluid **475** pressure will also decrease. This reduced hydraulic fluid **475** pressure in the hydraulic tubing **477** will reduce the braking force on the second brake until the rear wheel regains traction on the road and the disk brake rotor **411** starts rotating again.

(38) In many bicycles, hydraulic systems are used with disk brakes. Because the disk brakes use a disk rotor rather than a rim as the braking surface, the brake pad can be any geometric shape that provides sufficient surface area to stop the rotation of the disk rotor. Because the disk brake pad is located much closer to the center of rotation, the radial position of the disk brake pad may shift as the slider moves within the guide if the path is linear. In an embodiment, the slider assembly and guide can be configured with an arched path that matches the disk rotor. This configuration may allow the disk brake pad to maintain a constant radial position against the brake rotor regardless of the position of the slider assembly within the guide. In the disk brake embodiment, the second brake actuator can be a hydraulic system or any other braking mechanism that can be actuated by the movement of the slider assembly in the guide.

(39) The inventive brake system and apparatus are related to an anti-locking system for bicycles and other wheeled vehicles such as motorcycles. As discussed in the applicant's other patents and patent applications, the basic principle of the anti-locking brake system is that the user only

actuates the rear brake and a front brake actuator is coupled directly between the rear brake and the front brake. Thus, the user does not have the ability to independently actuate the front brake. When the rear brake is actuated, the friction force between the rear tire and the ground actuates the front brake actuator which causes the front brake to stop or slow the front wheel.

(40) As discussed, the rear brake can be coupled to a hydraulic actuator. FIGS. 6 and 7 illustrate an embodiment of a hydraulic actuator **501** which has a piston **503** that slides within a cylinder **505** that is filled with a hydraulic fluid. The hydraulic actuator **501** has a first end **511** and a second end **513**. In FIG. 6, the piston **503** is adjacent to one end of the cylinder **505** where the hydraulic actuator **501** is not compressed with substantial pressure or force compressing the first end **511** towards the second end **513**. In this retracted state, the hydraulic fluid does not flow through the hydraulic tubing **507** to a front hydraulic brake which is not shown. In FIG. 7, the first end **511** is pressed towards the second end **513** which moves the piston **503** within the cylinder **505** which results in hydraulic fluid flowing through the hydraulic tubing **507** which can be coupled to the front hydraulic brake. One end **511** of the hydraulic actuator **501** is coupled to a rear brake mechanism or a linkage coupled to the rear brake mechanism and a second end **513** can be coupled to a portion of the frame of the vehicle. A center axis of the hydraulic actuator **501** can be aligned with a plane defined by the rear brake disk rotor. The second end **513** can be coupled to a hinge which can be aligned with a plane defined by the rear brake disk rotor and the rotational axis of the hinge can be perpendicular to the plane defined by the rear brake disk rotor.

(41) FIG. 8 illustrates another embodiment of the rear disk brake system. The rear brake hydraulic tubing **4510** can be placed under the left rear chain stay **4515** and actuates the rear disk brake **4520**. When the rear brake is actuated the friction of the rear wheel **4525** against the ground causes a rear brake lever **4530** coupled to a rotating portion of the rear disk brake **4520** to rotate counter clockwise. In the illustrated embodiment, a hydraulic actuator **501** includes a hydraulic piston **503** and a piston rod **504** coupled to a hydraulic piston **503** that sliding within a hydraulic cylinder **501**. Hydraulic fluid is in the hydraulic cylinder **501** below the piston **503** and air is above the piston **503** in the cylinder **501**. The front brake hydraulic tubing **4540** is coupled to a hydraulic cylinder **505** which is coupled to the left chain stay **4515**. In FIG. 8, the piston **503** is in the unactuated position at the top of the cylinder **505**. When the rear brake **4520** is actuated, the rear brake lever **4530** rotates downward in a counter clockwise direction. The rear brake lever **4530** is coupled to the end of the piston rod **504** of the hydraulic actuator **501** and pulls the hydraulic piston **503** down within the cylinder **505** and the movement of the piston **503** in the cylinder **505** compresses the hydraulic fluid in the lower portion of the cylinder **505**. The hydraulic fluid flows through the front brake tubing **4540** which is coupled to and actuates a front wheel hydraulic brake. The rear brake lever **4530** can have a limited rotational or movement range which stops when or before the piston **503** travels to the bottom end of the cylinder **501** which may be rigidly coupled to a left rear chain stay **4515** of the frame with adjustable fasteners such as bolts. If the rear wheel **4525** loses braking traction, the torque applied to the disk brake rotor **4520** is reduced and the downward force of the brake lever **4530** against the piston rod **504** and piston **503**. This rear brake friction force reduction results in the brake lever **4530** rotating upward which reduces the hydraulic pressure applied by the hydraulic actuator **501** with hydraulic fluid flowing back into the cylinder **501** and the actuation force applied to the front brake is reduced.

(42) In FIG. 8, the hydraulic actuator **501** is actuated by pulling the piston rod **504** from the bottom of the cylinder **505**. In other embodiments, a different hydraulic actuator configuration such as the shown in FIGS. 6 and 7 can be used where the actuator is actuated by pressing the piston rod into the hydraulic cylinder. When the rear brake is actuated, the rear brake lever **4530** can rotate downward and compress the piston rod and piston into the cylinder which causes the hydraulic fluid to flow through the hydraulic tubing coupled to the front hydraulic brake.

(43) FIG. 9 illustrates a front hydraulic brake **4605** which slows and/or stops the rotation of a front disk rotor **4601** and a front wheel **4603**. The front hydraulic tubing **4607** is coupled to the hydraulic

actuator that is actuated by a lever coupled to the rear brake. As discussed, when the hydraulic actuator is actuated by the rear wheel brake, the hydraulic fluid flows through the hydraulic tubing **4607** to actuate the front hydraulic brake **4605**. When the rear wheel loses braking traction and the hydraulic actuator is released, the hydraulic fluid flows back through the hydraulic tubing **4607** to the cylinder in the hydraulic actuator and the hydraulic fluid pressure is reduced and the front hydraulic brake **4605** is released. In the manner described above, the front brake **4605** and front wheel **4603** will not lock up resulting in the vehicle flipping over the front wheel **4603**.

(44) FIG. **10** illustrates another embodiment of an anti-locking disk brake system. A rear portion of a bike is illustrated with a rear disk brake **4705**. The rear disk brake **4705** is mounted on a rear brake assembly **4710** that rotates about a pivot point **4715** which can be aligned with the rear hub axle so that any counter clockwise rotation will keep the pads of the rear brake **4705** can maintain a proper radial alignment with the rear disk **506**. Because the brake surface of the rear disk **506** can be narrow, the alignment of the pads on the rear brake **4705** can be very important. While the rear brake assembly **4710** is shown as being mounted to a pivot point **4715**, in other embodiments, the rear brake assembly **4710** can be mounted to a linkage system which keeps the pads of the rear brake **4705** can maintain a proper radial alignment with the rear disk **506**. The rear brake assembly **4710** can include mounting holes for the rear disk brake **4705** and a lever arm **4725** that can extend forward from the rear wheel axle under the left rear chain stay **4730**.

(45) The hydraulic actuator **501** can be mounted to the left chain stay **4730** with the piston **503** coupled to the lever arm **4725**. FIG. **10** illustrates the actuator in the non-actuated position with the piston **503** in the upper portion of the cylinder **505** with hydraulic fluid under the piston **503** and air above the piston **503**. When the rear brake **4705** is actuated and applies a friction force on the rotating rear disk **506** which causes the rear brake assembly **4710** to rotate with the rear disk **506** in a downward counter clockwise direction. The lever arm **4725** also rotates downward with the rear brake **4705** in a counter clockwise direction and pulls the piston **503** down within the cylinder **505**. The piston **503** movement pressurizes the hydraulic fluid in the cylinder **505** which flows through the hydraulic tubing **4735** to actuate the front hydraulic brake. When the rear brake **4705** is released from the rear disk **506** and/or the rear wheel lifts off of the ground the rotational force of the rear disk **506** is released and the rotational force on the lever arm **4725** from the rotating rear disk **506** is reduced. The lever arm **4725** no longer pulls down on the piston **503** which causes the piston **503** to move up within the cylinder **505** and the hydraulic fluid flows from the front brake into the hydraulic tubing **4735** and into the cylinder **505**. The movement of the hydraulic pressure out of the front brake releases the front brake on the front wheel which prevents the locking up of the front wheel.

(46) FIG. **11** illustrates a view of an embodiment of the rear brake assembly **4805** mounted on a rear hub **4810** of a rear wheel. The rear brake assembly **4805** can include a rear disk brake rotor **4815** and a rear disk brake **4820** mounted on a rear brake arm **4804**. The hydraulic actuator can be coupled to the rear brake arm **4804** and the front brake housing can be coupled to the chain stay or other portion of the frame. When the brakes are not actuated the rear brake arm **4804** the hydraulic actuator used to actuate the front brake may not be in compression or in tension. When the rear brake is actuated, the rear brake assembly **4805** apply a friction force against the rotating rear disk brake rotor **4815** and the rear brake arm **4804** will rotate counter clockwise **4825** (looking at the left side) relative to the frame of the vehicle about a pivot point **4830**. This rotation of the rear brake arm **4804** lever will actuate the hydraulic actuator which will actuate the front brake. If the rear wheel loses contact with the ground or if the rear brake is released, the rear brake assembly **4805** will be able to rotate clockwise and the hydraulic pressure applied to the front brake will be relieved which will prevent the front brake from locking the front wheel.

(47) FIG. **12** illustrates another embodiment of the rear disk brake system. In this embodiment, the rear brake structure assembly **4903** is coupled to a rotational mechanism at a pivot point **4905** on the left chain stay **4910** which is away from the center axis **4915** of the rear hub **4917** and may be a

less complicated rotational bearing. The pivot point **4905** can be a rotational mechanism that may be rigidly attached to the frame by any suitable fastening means such as brazing or welding which allows the rear brake structure assembly **4903** to rotate about the pivot point **4905** around an axis that is parallel with the axis of rotation of the rear brake disk **4916**. The rear hub **4917** is secured in the frame dropouts **4918** which may be horizontal dropouts or vertical dropouts. The rear brake structure **4903** can include threaded mounting holes **4925A** and **4925B** for mounting a standard rear disc brake **4930** and a lever arm **4935** that can extend under the left rear chain stay **4910**. The rear disk brake system can have an adjustable mechanical advantage can be provided based on, for example, a connection point of the actuator **4946** to the lever arm **4935**. The hydraulic actuator **4946** can have a cylinder **505** mounted to the left chain stay **4910** and a piston **503** coupled to the lever arm **4935**. The force is proportional to the distance between the pivot point **4905** and the actuator **4946**. The movement of the lever arm **4935** will generate more force when the hydraulic actuator **4946** is connected to the lever arm **4935** closer to the pivot point **4905** than when the connection is further from the pivot point **4905**. In an embodiment, the

(48) When the rear disc brake **4930** is actuated, the lever **4935** rotates and the hydraulic fluid in the actuator **501** is pressurized to actuate the front disc brake. The rear disc brake **4930** may be a conventional hydraulic or mechanical disc brake. The front brake mechanism and front brake actuation can be substantially the same as described above.

(49) The rear disc brake **4930** can be actuated by increased hydraulic fluid pressure from a rear brake lever or any other suitable rear brake actuation means. Friction between the ground and the rear wheel can result in increased hydraulic pressure generated by the hydraulic actuator **4946** which causes hydraulic fluid to flow into the hydraulic tubing **4945** which can actuate the front brake. However, it is also possible for the rear disc brake **4930** to be coupled to a hydraulic cylinder actuator **4946** so that counter clockwise movement of the rear wheel from the friction between the ground and the rear wheel can increase the front brake hydraulic brake pressure to actuate the front brake. In other embodiments, the rear disk brake can be coupled to a linkage system which can be coupled to a hydraulic actuator **4946** such as those described above. When the rear disk brake is actuated, the rear brake and linkages can move resulting in compression of the hydraulic fluid in the hydraulic actuator.

(50) FIG. 13 illustrates another embodiment of the rear disk brake system. In this embodiment, a rear brake structure assembly **4950** is connected to a center axis of the rear hub. A disc brake caliper **4955** is mounted to the rear brake structure. The rear brake structure assembly **4950** can rotate about the center axis of the rear wheel assembly **4950** or about an axis of rotation that is parallel with the rotation axis of the rear disk **4951**. When the rear brake caliper **4955** is actuated to reduce the bicycle's speed, the rear disc caliper **4955** will produce a friction force with the rear disk **4951** which will slow the rotation of the rear wheel. The rear brake structure assembly **4950** will rotate a short distance in a counter clockwise direction as shown by an arrow **4960**. The rear brake structure assembly **4950** can include a piston that moves within a hydraulic cylinder and the movement of the piston pushes hydraulic fluid out the hydraulic cylinder. An end of a hydraulic actuator may be connected to a portion **4965** of the rear brake structure to actuate the front brake when the rear brake structure assembly **4950** moves with the rear brake disk **4951**. When the rear disc caliper **4955** is actuated and the rear wheel loses traction with the ground, the rear brake structure assembly **4950** returns to a normal position and the force applied to the hydraulic actuator is released which prevents the front brake from locking up the front wheel.

(51) FIGS. 14 and 15 show a sequence of side views of a rear disc braking system having a mechanical linkage **5003**. In an embodiment the linkage can be coupled to a front brake actuator. The mechanical linkage includes an assembly of bodies connected to manage forces and movement. In a specific embodiment, these forces and movements are from the actuation of the rear brake and result in the actuation of the hydraulic actuator and actuation of the front hydraulic brake. FIG. 14 shows the linkage in a released position and FIG. 15 shows the linkage in a second

actuated position. The illustrated linkage system includes a first link **5005A**, a second link **5005B**, and a third link **5005C**. In the illustrated embodiment, the second link **5005B** can include a first disc brake mount **5010A** and the third link **5005C** can include a second disc brake mount **5010B** upon which a disc brake **5015** can be attached. The first link **5005A** and third link **5005C** includes rotational joints **5020A** and **5020B**, respectively, which may be used to secure the linkage system to a bicycle frame. An end **5025** of the first link **5005A** may be connected to an end of a hydraulic actuator. An opposite end **5030** of the first link **5005A** is connected an end of the second link **5005B**.

(52) In a specific embodiment, the actuation of the rear brake **5015** causes the disc caliper grasp and assert a friction force on the rear brake disc. FIG. **14** illustrates the mechanical linkage **5003** in a non-actuated position where the rear brake is not asserting friction on the rotating rear disk or with the rear brake asserting a friction on the rotating rear disk with the rear wheel losing traction with the ground. In FIG. **14**, the brake **5015** is to the left and the end **5025** of the first link **5005A** is moved forward to the left. FIG. **15** shows the mechanical linkage **5003** when the fiction force of the rear brake **5015** against the rotating rear disk causes the rear brake **5015** to move in a counter clockwise direction as indicated by an arrow **5035**. The first link **5005A** rotates **5040** about joint **5020A** and the third link **5005C** rotates **5045** about joint **5020B**. As shown in FIG. **15**, the end **5025** of the first link **5005A** then moves with a force to actuate the hydraulic actuator which can actuate the front brake.

(53) In an embodiment, the linkage system can include a first joint, a second joint, and a hydraulic actuator. The second joint can be connected to a first tab on a bicycle frame and the second joint can be between the first joint and the hydraulic actuator attachment end. There is a second link of the linkage connected to the first joint and including a first mount, opposite the first joint, for a disc brake. There is a third link of the linkage and including a fourth joint and a second mount, opposite the fourth joint, for the disc brake. The fourth joint connects to a second tab on the bicycle frame.

(54) FIGS. **16-18** show side views of an embodiment of a rear brake linkage system during braking. The rear disc braking system can have a mechanical linkage **5103**. In this specific embodiment, the linkage system includes a first link **5105A**, a second link **5105B**, and a third link **5105C**. The second link **5105B** is connected between the first link **5105A** and the third link **5105C**. The third link **5105C** can include disc mounts **5110A** and **5110B** for attaching a disc brake **5115**. A joint **5120A** on the first link **5105A** can connect the linkage system to a first disc tab on the bicycle frame. A joint **5120B** on the third link can connect the linkage system to a second disc tab on the frame. An end of a hydraulic actuator may be connected at a point **5125** on the first link **5105A** and movement of point **5125** actuates the hydraulic actuator.

(55) FIG. **16** shows the linkage in a first position where the rear brake is released and the linkage system is in a relaxed position. The first position can occur when the rear brake is released or if the rear brake is actuated and the rear disc is not moving or if the rear brake is actuated and the rear wheel has lost traction with the ground. In the first position, the hydraulic actuator can be deactivated and the position of the first link **5105A** and point **5125** are retracted and hydraulic pressure is not applied to the front brake. Since the front brake is not actuated the front wheel can rotate freely. FIG. **17** shows the linkage system in a second position where the rear brake is applying a partial braking force on the rotating rear brake disk. The rear brake can move with the rotating rear brake disk counter clockwise and the linkage system is also partially rotated counter clockwise. The actuation of the rear brake causes the disc caliper to move in a counter clockwise direction as indicated by an arrow **5130**. The third link rotates **5135** about joint **5120B** and the first link rotates **5140** about joint **5120A**. The movement of the first link **5105A** and point **5125** are partially rotated and the hydraulic actuator coupled to the point **5125** can be partially actuated. The hydraulic actuator can cause hydraulic pressure to be applied to the front brake. FIG. **18** shows the linkage in a third position where the rear brake is fully applied to the rear brake disk and the first link **5105A** and point **5125** are fully rotated and the hydraulic actuator coupled to the point **5125**

can be fully actuated. Point **5125** on the first link **5105A** at which the end of a hydraulic actuator may be secured moves in a direction **5145** to actuate the hydraulic actuator and actuate the front brake as described above. The hydraulic actuator applies a full braking force to the rear brake disk and the linkage system is fully rotated counter clockwise applying maximum force to the front brake.

(56) In a specific embodiment, a device includes a first link **5205A** that includes a first joint, a second joint, and a hydraulic actuator attachment point. The second joint is between the first joint and the hydraulic actuator attachment end, and connects to a first tab on a bicycle frame. There is a second link of the linkage connected to the first joint. There is a third link of the linkage and including a third joint, a fourth joint, and a set of disc mounts for mounting a disc brake. The third joint is connected to the second link, and the fourth joint connects to a second tab on the bicycle frame.

(57) FIGS. **19-21** show a sequence of right side views of a rear disc braking system having a mechanical linkage **5203** in another specific embodiment of a brake system. As shown in this specific embodiment, the linkage includes a first link **5205A**, a second link **5205B**, and a third link **5205C**. The first link includes a joint **5210A** and a joint **5210B**, opposite joint **5210A**, and including mount for attaching a disc brake caliper **5215**. Joint **5210A** may be connected to the bicycle frame. The second link includes a joint **5210C** and a joint **5210D**, opposite joint **5210C** and connecting the third link. Joint **5210C** may include a mount for attaching the disc brake caliper. The third link includes a joint **5210E** and an end **5220**. Joint **5210E** may be connected to the bicycle frame. End **5220** of the third link **5205C** may be connected to an end of a hydraulic actuator. Movement of the End **5220** of the third link **5205C** actuates the hydraulic actuator which applies or releases hydraulic fluid pressure to the front brake.

(58) FIG. **19** shows the linkage in a first position with the rear brake caliper **5215** is disengaged so there is not friction against the rotating rear brake disk. In an embodiment, a spring may hold the linkage system in a disengaged or relaxed position. The end **5220** at the end of the third link **5205C** can be rotated in a clockwise direction (facing the to a stop which in a lowered right position. The hydraulic actuator coupled to the end **5220** is not compressed or tensioned. In the first position, the hydraulic actuator coupled to the end **5220** can be deactivated. The position of the third link **5205C** and point **5220** are retracted and hydraulic pressure is not applied to the front brake and the front wheel can rotate freely.

(59) FIG. **20** shows the linkage in a second position where the rear brake **5215** is applying a partial braking force on the rotating rear brake disk. The rear brake **5215** can move with the rotating rear brake disk in a clockwise direction with the rear brake disk resulting in a friction force and the linkage system is also partially rotated clockwise. The actuation of the rear brake causes the disc caliper to move in a clockwise direction as indicated by an arrow **5230**. The first link **5205A** rotates in a clockwise direction **5235** about joint **5210A**. The third link **5205C** rotates in a clockwise direction **5240** about joint **5210E**. The movement of the first link **5105A** and point **5220** are partially rotated and the hydraulic actuator coupled to the point **5220** can be partially actuated. The hydraulic actuator can cause hydraulic pressure to be applied to the front brake to partially actuate the front brake.

(60) In FIG. **21**, the brake **5215** is fully actuated and the friction force against the rear brake disk causes the brake **5215** to move to the linkage system to a fully actuated position. The linkages **5205A** and **5205C** have rotated to a full clockwise position and the end **5220** of the third link **5205C** can be attached an end of the hydraulic actuator which fully actuates the front brake which can apply maximum braking force to the front wheel. If the front brake locks the front wheel, the rear wheel can be pulled off the ground releasing the clockwise direction force on the rear brake **5215**. The linkages **5205A**, **5205C** and brake **5215** can rotate in a counter clockwise direction which results in the end **5220** of the third link **5205C** deactivating the actuator which releases the front brake as shown in FIG. **20**.

(61) FIGS. 22-24 show a sequence of left side views of a rear disc braking system having a braking assembly or system that allows the disc brake caliper **5320** to move in a linear direction on a track **5322** against a brake mount **5305** in another specific embodiment. In a specific embodiment, a device includes a first set of mounts for attaching to a bicycle frame, and a carrier including a second set of mounts for attaching a rear disc brake caliper. The braking mount **5305** can include a set of disc mounts **5310A** and **5310B** for attaching the brake mount **5305** to disc tabs of the bicycle frame. The assembly further includes a sliding carrier **5315** upon which a disc brake caliper **5320** is mounted. The sliding carrier **5315** may travel along the track **5322** which is secured to the brake mount **5305**.

(62) FIG. 22 shows the system in a first position with the brake **5320** in a deactivated position where the rear brake is not actuated and does not contact the spinning rear disk. In the deactivated position, the sliding carrier **5315** is on the right side or rear portion of the track **5322**. The carrier translates or slides in linear direction from a first position to a second position to actuate a front brake when the rear disc brake caliper is actuated. FIG. 23 shows the system in a second position where the rear brake **5320** is partially engaged against the rear disc **5321** with the disc brake caliper **5320** partially moved on the track **5322** on the brake mount **5305**. The actuation of the rear brake **5320** while the rear wheel and rear disc **5321** are moving in a counter clockwise direction causes the disc caliper **5320** on the sliding carrier **5313** to move in a linear direction to the left as indicated by arrow **5330**. A hydraulic actuator may be attached a portion of the sliding carrier **5315** so that a compression or tension force can be applied to the hydraulic actuator when the sliding carrier **5315** moves forward with the rotating rear disc **5321**. The compression or tension force on the hydraulic actuator pressurizes the hydraulic fluid in the actuator causing hydraulic fluid to flow through hydraulic tubing to actuate the front hydraulic brake. FIG. 24 shows the system in a third position with the disc brake caliper **5320** fully moved against the brake mount **5305** and the sliding carrier **5313** to move in a linear direction further to the left as indicated by arrow **5330**. The additional movement of the sliding carrier **5313** causes the hydraulic actuator to drive additional hydraulic fluid flow through hydraulic tubing to further actuate the front hydraulic brake.

(63) FIG. 25 shows a left side view of a rear disc braking system that may be referred to as a floating caliper braking assembly. In this specific embodiment, an assembly **5405** includes a first structure **5410** and a second structure **5415**. The first structure includes a set of mounts **5420** to attach the assembly **5405** to a bicycle frame **5421** and adjustable settings **5425**. The second structure **5415** includes a set of mounts **5430** for attaching a disc brake caliper **5435**.

(64) In this specific embodiment, the actuation of the rear brake caliper **5435** causes the rear brake to contact the rotating rear disk which slows the rotation of the rear wheel. The second structure **5415** moves with the rotating rear disk towards the first structure **5410**. The movement of the second structure **5415** may be in an arc which includes translation and rotation. A hydraulic actuator may be secured to a portion of the second structure **5415** and the movement of the second structure **5415** actuates the hydraulic actuator which actuates the front brake. In a specific embodiment, the second structure **5415** on which the caliper **5435** is attached moves into a guide that may be on the first structure **5410**. For example, the guide may include a channel, track, or groove on the first structure through which a portion of the second structure **5415** slides. The shape of the channel helps to direct the movement of the caliper **5435** so that the brake remains in contact with the rear disk throughout the movement of the second structure **5415**. The channel may be an arc curvature or curvilinear. There may be a stop on the first structure **5410** or the second structure **5415** to limit the movement of the second structure **5415**.

(65) FIG. 26 shows a left side view of a rear disc braking system **5505** in another specific embodiment. The illustrated braking system **5505** includes a first structure **5510A** and a second structure **5510B** that rotates towards the first structure **5510A** when the rear brake applies a friction force to the rotating rear disk **5536**. The second structure **5510B** may be rotatably connected to a frame **5514** with the second structure **5510B** rotating about the rear rotational axle

**5507** axis of the rear disk and rear wheel so that the rear brake caliper **5512** remains centered on the rear disk **5536** throughout the movement of the second structure **5510B**. The first structure **5510A** can include a set of mounting holes for attaching the rear disc braking system **5505** to a seat stay **5515** of the bicycle frame **5514**. The second structure can include brake mounts **5520** attached to a disc brake caliper **5512** and a hydraulic actuator attachment point **5525**. When the rear brake caliper **5512** is actuated and it applies a friction force to the rotating rear disk **5536** and the second structure **5510B** rotates counter clockwise with the rear disk **5536** about the rotational axle **5507**. An end **5525** of the second structure **5510B** moves down and counter clockwise in a direction as indicated by an arrow **5530**. The end **5525** of the second structure **5510B** is attached a hydraulic actuator. The movement of the end **5525** of the second structure **5510B** actuates the hydraulic actuator which causes hydraulic fluid to flow out of the hydraulic actuator and through a tube to actuate the front brake.

(66) FIG. **27** shows a left side perspective view of a rear disc braking system **5605** that is similar to the system described above with reference to FIG. **26**. The braking system **5605** is mounted on the frame **5614**. The rear disc braking system **5605** includes a first structure **5610A** and a second structure **5610B** that moves towards the first structure **5610A** when the rear brake caliper **5612** clamps the rear disk **5636** which is rotating counter clockwise. The attachment point **5625** is coupled to a hydraulic actuator and the actuation of the actuators compresses the piston within the cylinder to pressurize the hydraulic fluid which flows from the hydraulic actuator to actuate the front brake.

(67) FIG. **28** shows a left side view of a rear disc braking system in another embodiment. The braking system **5705** includes a rear brake mount **5726** attached to the frame and a linkage system **5710** that includes a first link **5720** and a second link **5725** rotatably coupled to a rear brake mount **5730** at two rotatable couplings **5724** that can be bearings or bushings. A brake caliper **5732** is attached to the rear brake mount **5730**. The first link **5720** and the second link **5725** are attached to the rear brake mount **5726** at rotational couplings **5722**. An end of the first link **5720** includes a hydraulic actuator attachment point **5735**. FIG. **28** shows the brake **5705** in the normal unactuated position where the brake **5732** is released and not contacting the rotating disk **5736** and the first link **5720** and second link **5725** are rotated clockwise. When the rear brake caliper **5732** is actuated, it will create friction against the rotating rear disk **5736** and move counter clockwise with the rotating disk **5736**. The first link **5720** and the second link **5725** will also rotate counter clockwise about the rotational couplings **5722**. The end **5735** will move the hydraulic actuator which will be transmitted to the front brake through a hydraulic tube so the front brake is actuated. When the rear wheel comes off the ground, the rotational force on the rear disk will be relieved and the hydraulic actuator which and the front brake will be deactivated.

(68) With reference to FIGS. **29-31**, embodiments of a rear hydraulic brake system are illustrated. In these embodiments, the rear disk brake **511** is coupled to a lever **521**. One end of the lever **521** can be mounted on a rotational pivot point on the rear wheel dropout **525** and the opposite end of the lever **521** can have a rotational coupling **533** coupled to an end of a hydraulic actuator **501**. When the rear hydraulic disk brake **511** is actuated, a user can actuate a rear brake lever and hydraulic fluid can be pressurized in the rear brake hydraulic tubing **543** which actuates the rear brake **511**. The friction force between the rear brake **511** and the rear disk rotor **513** causes the rear brake **511** on the lever **521** to rotate counter clockwise which compresses the hydraulic actuator **501**. The hydraulic actuator **501** compression pressurizes hydraulic fluid which travels through a hydraulic tubing **541** to a front hydraulic disk brake.

(69) If the rear wheel loses traction or rises off the ground, the rear disk rotor **513** will no longer have the same rotational torque and the hydraulic actuator **501** will not be compressed or be less compressed which relieves the hydraulic pressure applied by the hydraulic actuator **501** to the front brake allowing the front wheel to rotate rather than locking up which can cause the rider to fall off of the vehicle.



(70) With reference to FIG. 29, the hydraulic actuator 501 is coupled to a hinge 531 mounted on middle portion of the left seat stay tube 530 of the frame. The hinge 531 can have an axis of rotation that is perpendicular a plane defined by the rear disk rotor 513. The hinge 531 can also have an axis of rotation which is perpendicular to the plane of the rear disk rotor 513. The brake 511 can be attached to a rotational coupling 525 mounted on the rear dropout which holds the rear axle of the rear wheel. When the rear brake 511 is actuated, the rear brake 511 will rotate counter clockwise with the rotating rear disk 513 about the rotational coupling 525. This movement will compress the hydraulic actuator 501 and hydraulic fluid will flow through the hydraulic tubing 541 to actuate the front hydraulic disk brake.

(71) With reference to FIG. 30, the hydraulic actuator 501 is coupled to a hinge 531 mounted on the left chain stay tube 536 of the frame. The hinge 531 can be aligned with a plane defined by the rear disk rotor 513. The hinge 531 can also have an axis of rotation which is perpendicular to the plane of the rear disk rotor 513. When the rear brake 511 is actuated, the rear brake 511 will rotate counter clockwise with the rotating rear disk 513 about the rotational coupling 525. This movement will compress the hydraulic actuator 501 and hydraulic fluid will flow through the hydraulic tubing 541 to actuate the front hydraulic disk brake.

(72) With reference to FIG. 31, the hydraulic actuator 501 is coupled to a hinge 531 mounted on a cross beam structure 534 mounted between the seat stay tube 536 of the frame. The end of the hydraulic actuator 501 can be attached to a hinge 531 on the cross beam structure 534. The hinge 531 can be aligned with a plane defined by the rear disk rotor 513. The hinge 531 can also have an axis of rotation which is perpendicular to the plane of the rear disk rotor 513. When the rear brake 511 is actuated, the rear brake 511 will rotate counter clockwise with the rotating rear disk 513 about the rotational coupling 525. This movement will compress the hydraulic actuator 501 and hydraulic fluid will flow through the hydraulic tubing 541 to actuate the front hydraulic disk brake.

(73) It should be appreciated that the various braking designs shown in the figures are merely examples of particular implementations of the braking system. In other implementations, other similar and equivalent elements and functions may be used or substituted in place of what is shown. A rotating mechanism or sliding mechanism may include bearings, bushings, pulleys, or combinations of these.

(74) The present disclosure, in various embodiments, includes components, methods, processes, systems and/or apparatus substantially as depicted and described herein, including various embodiments, subcombinations, and subsets thereof. Those of skill in the art will understand how to make and use the present disclosure after understanding the present disclosure. The present disclosure, in various embodiments, includes providing devices and processes in the absence of items not depicted and/or described herein or in various embodiments hereof, including in the absence of such items as may have been used in previous devices or processes, e.g., for improving performance, achieving ease and/or reducing cost of implementation. Rather, as the flowing claims reflect, inventive aspects lie in less than all features of any single foregoing disclosed embodiment.

## Claims

1. A rear hydraulic braking system for a bicycle, the rear hydraulic braking system comprising: a rear brake assembly operatively coupled to a first end of a first hydraulic tubing, the rear brake assembly comprising a first brake pad and a second brake pad, the first brake pad disposed on a first side of a rear brake surface of a rear wheel, and the second brake pad disposed on a second side of the rear brake surface opposite the first side, wherein the first brake pad and the second brake pad are configured to releasably engage the rear brake surface to slow a rotation of the rear wheel; a rear brake lever operatively coupled to a second end of the first hydraulic tubing, wherein actuation of the rear brake lever is configured to actuate the rear brake assembly; a hydraulic actuator comprising a cylinder and a piston rotatably coupled to the rear brake assembly, the

cylinder configured to hold a hydraulic fluid, and the piston configured to slide within the cylinder to compress the hydraulic fluid; and a second hydraulic tubing fluidically coupled to the cylinder, the second hydraulic tubing configured to direct compressed hydraulic fluid from the cylinder to a front brake assembly to actuate the front brake assembly to slow a rotation of a front wheel; wherein the rear brake assembly, when actuated, is configured to move with a rotation of the rear brake surface to move the piston within the cylinder to urge the hydraulic fluid to flow through the second hydraulic tubing to actuate the front brake assembly to slow the rotation of the front wheel.

2. The rear hydraulic braking system of claim 1, wherein the movement of the rear brake assembly comprises translational movement.
3. The rear hydraulic braking system of claim 1, wherein the movement of the rear brake assembly comprises rotational movement.
4. The rear hydraulic braking system of claim 1, wherein the bicycle is an electric powered bicycle.
5. The rear hydraulic braking system of claim 1, wherein the piston is coupled to the rear brake assembly with one or more links.
6. The rear hydraulic braking system of claim 5, wherein the one or more links comprises a rotational coupling.
7. The rear hydraulic braking system of claim 1, wherein the rear brake surface is a rear disc rotor.
8. The rear hydraulic braking system of claim 1, wherein the rear brake surface is a rim of the rear wheel.
9. The rear hydraulic braking system of claim 1, wherein the hydraulic actuator is configured to be rotatably coupled to a frame of the bicycle.
10. A bicycle comprising the rear hydraulic braking system of claim 1.
11. A rear hydraulic braking system for an electric powered bicycle, the rear hydraulic braking system comprising: a rear brake assembly comprising a first brake pad and a second brake pad, the first brake pad disposed on a first side of a rear brake surface of a rear wheel, and the second brake pad disposed on a second side of the rear brake surface opposite the first side, wherein the rear brake assembly is configured to actuate such that the first brake pad and the second brake pad releasably engage the rear brake surface to slow a rotation of the rear wheel; a hydraulic actuator comprising a cylinder and a piston rotatably coupled to the rear brake assembly, the cylinder configured to hold a hydraulic fluid, and the piston configured to slide within the cylinder to compress the hydraulic fluid; and a hydraulic tubing fluidically coupled to the cylinder, the hydraulic tubing configured to direct compressed hydraulic fluid from the cylinder to a front brake assembly to actuate the front brake assembly to slow a rotation of a front wheel; wherein the rear brake assembly, when actuated, is configured to move with a rotation of the rear brake surface along an arched path to move the piston within the cylinder to urge the hydraulic fluid to flow through the hydraulic tubing to actuate the front brake assembly to slow the rotation of the front wheel.
12. The rear hydraulic braking system of claim 11, wherein the rear brake surface is a rear disc rotor.
13. The rear hydraulic braking system of claim 11, wherein the rear brake surface is a rim of the rear wheel.
14. An electric powered bicycle comprising the rear hydraulic braking system of claim 11.
15. A rear hydraulic braking system for a two-wheeled vehicle, the rear hydraulic braking system comprising: a rear brake assembly operatively comprising a first brake pad and a second brake pad, the first brake pad disposed on a first side of a rear brake surface of a rear wheel, and the second brake pad disposed on a second side of the rear brake surface opposite the first side, wherein the rear brake assembly is configured to actuate such that the first brake pad and the second brake pad releasably engage the rear brake surface to slow a rotation of the rear wheel; and a hydraulic actuator comprising a cylinder configured to hold a hydraulic fluid and a piston configured to slide within the cylinder to compress the hydraulic fluid, wherein the piston is coupled to the rear brake

assembly; wherein the rear brake assembly, when actuated, is configured to move with a rotation of the rear brake surface to move the piston within the cylinder to urge the hydraulic fluid to flow to actuate a front brake assembly to slow a rotation of a front wheel.

16. The rear hydraulic braking system of claim 15, wherein the rear brake surface is a rear disc rotor.

17. The rear hydraulic braking system of claim 15, wherein the rear brake surface is a rim of the rear wheel.

18. The rear hydraulic braking system of claim 15, wherein the two-wheeled vehicle is an electric powered bicycle.

19. The rear hydraulic braking system of claim 15, wherein the hydraulic actuator is configured to be rotatably coupled to a frame of the two-wheeled vehicle.

20. A two-wheeled vehicle comprising the rear hydraulic braking system of claim 15.

---