

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12394901
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Isik; Ozgur et al.

Cloaked low band elements for multiband radiating arrays

Abstract

A multiband antenna, having a reflector, and a first array of first radiating elements having a first operational frequency band, the first radiating elements being a plurality of dipole arms, each dipole arm including a plurality of conductive segments coupled in series by a plurality of inductive elements; and a second array of second radiating elements having a second operational frequency band, wherein the plurality of conductive segments each have a length less than one-half wavelength at the second operational frequency band.

Inventors: Isik; Ozgur (Gladesville, AU), Gripo; Philip Raymond (Toongabbie, AU), Thalakotuna; Dushmantha Nuwan Prasanna (Rosehill, AU), Liversidge; Peter J. (Glenbrook, AU)

Applicant: Outdoor Wireless Networks LLC (Claremont, NC)

Family ID: 1000008762764

Assignee: Outdoor Wireless Networks LLC (Richardson, TX)

Appl. No.: 18/527649

Filed: December 04, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240136713 A1	Apr. 25, 2024

Related U.S. Application Data

continuation parent-doc US 18147857 20221229 US 11870160 child-doc US 18527649
continuation parent-doc US 17038070 20200930 US 11552398 20230110 child-doc US 18147857
continuation parent-doc US 16711536 20191212 US 10819032 20201027 child-doc US 17038070
continuation parent-doc US 16655479 20191017 US 10547110 20200128 child-doc US 16711536
continuation parent-doc US 16277044 20190215 US 10498035 20191203 child-doc US 16655479

Publication Classification

Int. Cl.: **H01Q5/49** (20150101); **H01Q1/24** (20060101); **H01Q1/52** (20060101); **H01Q9/16** (20060101); **H01Q19/10** (20060101); **H01Q21/06** (20060101); **H01Q21/26** (20060101); **H01Q21/30** (20060101); **H01Q25/00** (20060101)

U.S. Cl.:

CPC **H01Q5/49** (20150115); **H01Q1/24** (20130101); **H01Q1/523** (20130101); **H01Q9/16** (20130101); **H01Q19/108** (20130101); **H01Q21/062** (20130101); **H01Q21/26** (20130101); **H01Q1/246** (20130101); **H01Q1/52** (20130101); **H01Q19/10** (20130101); **H01Q21/06** (20130101); **H01Q21/30** (20130101); **H01Q25/00** (20130101); **H01Q25/001** (20130101)

Field of Classification Search

CPC: H01Q (1/24); H01Q (1/523); H01Q (9/16); H01Q (19/108); H01Q (21/062); H01Q (21/26)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5012256	12/1990	Maddocks	N/A	N/A
6040805	12/1999	Huynh et al.	N/A	N/A
6417816	12/2001	Sadler et al.	N/A	N/A
6646611	12/2002	Plet et al.	N/A	N/A
6674405	12/2003	Wang	N/A	N/A
6847282	12/2004	Gomez et al.	N/A	N/A
6950006	12/2004	Shikama et al.	N/A	N/A
7088299	12/2005	Siegler et al.	N/A	N/A
8405564	12/2012	Kindt et al.	N/A	N/A
9276329	12/2015	Jones et al.	N/A	N/A
9553368	12/2016	Tonn	N/A	N/A
10224630	12/2018	Iellci	N/A	N/A
10230161	12/2018	Baron et al.	N/A	N/A
10454156	12/2018	Yang et al.	N/A	N/A
11552398	12/2022	Isik	N/A	H01Q 21/26
2002/0140618	12/2001	Plet et al.	N/A	N/A
2003/0034917	12/2002	Nishizawa et al.	N/A	N/A
2004/0032370	12/2003	Ito et al.	N/A	N/A
2004/0066341	12/2003	Ito et al.	N/A	N/A
2004/0183737	12/2003	Lindenmeier	N/A	N/A
2005/0073465	12/2004	Olson	N/A	N/A

2007/0090398	12/2006	McKinzie	N/A	N/A
2010/0156747	12/2009	Montgomery	N/A	N/A
2011/0133881	12/2010	Nakajima et al.	N/A	N/A
2012/0154236	12/2011	Apostolos et al.	N/A	N/A
2013/0164904	12/2012	Smith et al.	N/A	N/A
2014/0125539	12/2013	Katipally et al.	N/A	N/A
2014/0159977	12/2013	Jones	N/A	N/A
2015/0214617	12/2014	Shang et al.	N/A	N/A
2016/0235169	12/2015	Cohen	N/A	N/A
2016/0285169	12/2015	Shooshtari et al.	N/A	N/A
2017/0373385	12/2016	Alu et al.	N/A	N/A
2018/0331419	12/2017	Varnoosfaderani et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
1349674	12/2001	CN	N/A
1248363	12/2005	CN	N/A
1886864	12/2005	CN	N/A
1886864	12/2005	CN	N/A
102403572	12/2011	CN	N/A
202259701	12/2011	CN	N/A
103311651	12/2012	CN	N/A
103477496	12/2012	CN	N/A
103545621	12/2013	CN	N/A
103730728	12/2013	CN	N/A
103840254	12/2013	CN	N/A
103943970	12/2013	CN	N/A
203850436	12/2013	CN	N/A
104269649	12/2014	CN	N/A
104269649	12/2016	CN	N/A
105051975	12/2018	CN	N/A
2005176120	12/2004	JP	N/A
2005176120	12/2004	JP	N/A
2013038577	12/2012	JP	N/A
20130134793	12/2012	KR	N/A
2005055362	12/2004	WO	N/A
2006025248	12/2005	WO	N/A
2008151451	12/2007	WO	N/A
2014100938	12/2013	WO	N/A
2014146038	12/2013	WO	N/A

OTHER PUBLICATIONS

Notification of the First Office Action for Chinese Patent Application No. 201910210195.5, mailed Sep. 29, 2020, 39 pages. cited by applicant

“A Dictionary of Electronics and Electrical Engineering, Oxford University Press (5th Edition), 2018”. cited by applicant

“Ahmad et al., High Gain Array of Monopole Coupled Antenna for Wireless Applications, International Journal of Antennas and Propagation, vol. 12, 2012”. cited by applicant

“Communication Pursuant to Article 94(3) EPC in corresponding European Patent Application No. 15 750 581.9-1205 (May 15, 2019)”. cited by applicant

“Communication Pursuant to Article 94(3) EPC, corresponding to European Patent Application No. 19151403.3-1205, mailing date Apr. 15, 2021, 9 pages”. cited by applicant

“Dictionary of Electrical and Computer Engineering, McGraw-Hill, Sixth Edition, 2004”. cited by applicant

“EMI/RFI Solutions, Electro-Magnetic Compatibility, Vishay Intertechnology, Inc., 2000”. cited by applicant

“European Search Report in corresponding patent application No. EP22155629.3, mailed Apr. 29, 2022, 10 pages”. cited by applicant

“Extended European Search Report for corresponding European Application No. 19151403.3, mailed May 17, 2019”. cited by applicant

“First Examination Report in corresponding Indian Patent Application No. 201727013833; dated Jun. 30, 2020”. cited by applicant

“International Search Report and the Written Opinion of the International Searching Authority in corresponding PCT Application No. PCT/US2015/044020 (Nov. 12, 2015)”. cited by applicant

“Kaplan, S., Wiley Electrical and Electronics Engineering Dictionary, John Wiley & Sons, Inc., 2004”. cited by applicant

“Kraus, J., Electromagnetics, McGraw-Hill, Inc. (4th Edition), 1991”. cited by applicant

“Krause, J., Electromagnetics, Transmission line impedance, Ch. 12, p. 502, 1991”. cited by applicant

“Laplante, P., Comprehensive Dictionary of Electrical Engineering, CRC Press (2d Edition), 2005”. cited by applicant

“Laplante, P., Comprehensive Dictionary of Electrical Engineering, CRC Press, 1998”. cited by applicant

“Notification Concerning Transmittal of International Preliminary Report on Patentability in corresponding PCT Application No. PCT/US2015/044020 (Jun. 1, 2017)”. cited by applicant

“S. K. Padhi and M. E. Bialkowski, “Parametric study of a microstrip Yagi antenna,” in Proceedings of the Asia-Pacific Microwave Conference, pp. 715-718, Sydney, NSW, Australia, 2000”. cited by applicant

“Standards Coordinating Committee 10, The IEEE Standard Dictionary of Electrical and Electronics Terms, IEEE Std 100 (6th Edition) 1996”. cited by applicant

“Stutzman et al., Antenna Theory and Design, John Wiley & Sons, Inc. (3d Edition), 2013”. cited by applicant

“Stutzman et al., Cross Polarization for Antennas, Antenna Polarization and Polarization Measurements, Artech House, Inc., 1993”. cited by applicant

“Tapia, E.D., Design of Isofrequency Reconfigurable Repeaters, PHD Thesis, Universitat Politecnica de Catalunya, 2013”. cited by applicant

“Translation of Chinese Office Action, corresponding to Chinese Application No. 201580055284.7, mailing date: Aug. 30, 2019, 14 pgs.”. cited by applicant

Primary Examiner: Lauture; Joseph J

Attorney, Agent or Firm: Myers Bigel, P.A.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) The present application is a continuation application of and claims priority from U.S. patent application Ser. No. 18/147,857, filed Dec. 29, 2022, which is a continuation of U.S. patent application Ser. No. 17/038,070, filed

Sep. 30, 2020 (now U.S. Pat. No. 11,552,398), which is a continuation application of U.S. patent application Ser. No. 16/711,536, filed Dec. 12, 2019 (now U.S. Pat. No. 10,819,032), which is a continuation application of U.S. patent application Ser. No. 16/655,479 filed Oct. 17, 2019 (now U.S. Pat. No. 10,547,110), which is a continuation application of U.S. patent application Ser. No. 16/277,044, filed Feb. 15, 2019 (now U.S. Pat. No. 10,498,03), which is a continuation of U.S. patent application Ser. No. 15/517,906, filed Apr. 7, 2017 (now U.S. Pat. No. 10,439,285), which is a 35 U.S.C. § 371 national stage application of PCT International Application No. PCT/US2015/044020, filed Aug. 6, 2015, which itself claims priority to U.S. Provisional Patent Application No. 62/081,358, filed Nov. 18, 2014, the disclosure and content of each of the above applications is incorporated by reference herein.

FIELD OF THE INVENTION

(1) This invention relates to wide-band multi-band antennas with interspersed radiating elements intended for cellular base station use. In particular, the invention relates to radiating elements intended for a low frequency band when interspersed with radiating elements intended for a high frequency band. This invention is aimed at minimizing the effect of the low-band dipole arms, and/or parasitic elements if used, on the radio frequency radiation from the high-band elements.

BACKGROUND

(2) Undesirable interactions may occur between radiating elements of different frequency bands in multi band interspersed antennas. For example, in some cellular antenna applications, the low band is 694-960 MHz and the high band is 1695-2690 MHz. Undesirable interaction between these bands may occur when a portion of the lower frequency band radiating structure resonates at the wavelength of the higher frequency band. For instance, in multiband antennas where a higher frequency band is a multiple of a frequency of a lower frequency band, there is a probability that the low band radiating element, or some component or part of it, will be resonant in some part of the high band frequency range. This type of interaction may cause a scattering of high band signals by the low band elements. As a result, perturbations in radiation patterns, variation in azimuth beam width, beam squint, high cross polar radiation and skirts in radiation patterns are observed in the high band.

SUMMARY

(3) In one aspect of the present invention, a low band radiating element for use in a multiband antenna having at least a high band operational frequency and a low band operational frequency is provided. The low band element comprises a first dipole element having a first polarization and comprising a first pair of dipole arms and a second dipole element having a second polarization and comprising a second pair of dipole arms oriented at approximately 90 degrees to the first pair of dipole arms. Each dipole arm includes a plurality of conductive segments, each having a length less than one-half wavelength at the high band operational frequency, coupled in series by a plurality of inductive elements, having an impedance selected to attenuate high band currents while passing low band currents in the dipole arms. The inductive elements are selected to appear as high impedance elements at the high band operational frequency and as lower impedance elements at the low band operational frequency.

(4) In another aspect of the present invention, a multiband antenna is provided. The multiband antenna includes a reflector, a first array of first radiating elements and a second array of second radiating elements. The first radiating elements have a first operational frequency band and the second radiating elements have a second operational frequency band. The first radiating elements include two or more dipole arms. Each dipole arm includes a plurality of conductive segments coupled in series by a plurality of inductive elements. The conductive segments each have a length less than one-half wavelength at the second operational frequency band. The first radiating elements may comprise single dipole elements or cross dipole elements.

(5) The inductive elements are typically selected to appear as high impedance elements at the

second operational frequency band and as lower impedance elements at the first operational frequency band. The first operational frequency band typically comprises a low band of the multiband antenna and the second operational frequency band typically comprises a high band of the multiband antenna.

(6) In another aspect of the present invention, parasitic elements may be included on the multiband antenna to shape low band beam characteristics. For example, the parasitic elements may have an overall length selected to shape beam patterns in the first operational frequency band, and comprise conductive segments coupled in series with inductive elements selected to reduce interaction between the parasitic elements and radiation at the second operational frequency band. The conductive segments of the parasitic elements may also have a length of less than one half wave length at the second operational frequency band.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a schematic diagram of an antenna according to one aspect of the present invention.
- (2) FIG. 2 is a plan view of a portion of an antenna array according to another aspect of the present invention.
- (3) FIG. 3 is an isometric view of a low band radiating element and parasitic elements according to another aspect of the present invention.
- (4) FIG. 4 is a more detailed view of the low band radiating element of FIG. 3.
- (5) FIG. 5 is a first example of a parasitic element according to another aspect of the present invention.
- (6) FIG. 6 is a second example of a parasitic element accordingly to another aspect of the present invention.

DESCRIPTION OF THE INVENTION

(7) FIG. 1 schematically diagrams a dual band antenna **10**. The dual band antenna **10** includes a reflector **12**, an array of high band radiating elements **14** and an array of low band radiating elements **16**. Optionally, parasitic elements **30** may be included to shape azimuth beam width of the low band elements. Multiband radiating arrays of this type commonly include vertical columns of high band and low band elements spaced at pre-determined intervals See, for example, U.S. patent application Ser. No. 13/827,190, now U.S. Pat. No. 9,276,329 to Jones et al., which is incorporated by reference.

(8) FIG. 2 schematically illustrates a portion of a wide band dual band antenna **10** including features of a low band radiating element **16** according to one aspect of the present invention. High band radiating elements **14** may comprise any conventional crossed dipole element, and may include first and second dipole arms **18**. Other known high band elements may be used. The low band radiating element **16** also comprises a crossed dipole element, and includes first and second dipole arms **20**. In this example, each dipole arm **20** includes a plurality of conductive segments **22** coupled in series by inductors **24**.

(9) The low band radiating element **16** may be advantageously used in multi-band dual-polarization cellular base-station antenna. At least two bands comprise low and high bands suitable for cellular communications. As used herein, “low band” refers to a lower frequency band, such as 694-960 MHz, and “high band” refers to a higher frequency band, such as 1695 MHz-2690 MHz. The present invention is not limited to these particular bands, and may be used in other multi-band configurations. A “low band radiator” refers to a radiator for such a lower frequency band, and a “high band radiator” refers to a radiator for such a higher frequency band. A “dual band” antenna is a multi-band antenna that comprises the low and high bands referred to throughout this disclosure.

(10) Referring to FIG. 3, a low band radiating element **16** and a pair of parasitic elements **30** are

illustrated mounted on reflector **12**. In one aspect of the present invention, parasitic elements **30** are aligned to be approximately parallel to a longitudinal dimension of reflector **12** to help shape the beam width of the pattern. In another aspect of the invention, the parasitic elements may be aligned perpendicular to a longitudinal axis of the reflector **12** to help reduce coupling between the elements. The low band radiating element **16** is illustrated in more detail in FIG. 4. Low band radiating element **16** includes a plurality of dipole arms **20**. The dipole arms **20** may be one half wave length long. The low band dipole arms **20** include a plurality of conductive segments **22**. The conductive segments **22** have a length of less than one-half wavelength at the high band frequencies. For example, the wavelength of a radio wave at 2690 MHz is about 11 cm, and one-half wavelength at 2690 MHz would be about 5.6 cm. In the illustrated example, four segments **22** are included, which results in a segment length of less than 5 cm, which is shorter than one-half wavelength at the upper end of the high band frequency range. The conductive segments **22** are connected in series with inductors **24**. The inductors **24** are configured to have relatively low impedance at low band frequencies and relatively higher impedance at high band frequencies.

(11) In the examples of FIGS. 2 and 3, the dipole arms **20**, including conductive segments **22** and inductors **24**, may be fabricated as copper metallization on a non-conductive substrate using, for example, conventional printed circuit board fabrication techniques. In this example, the narrow metallization tracks connecting the conductive segments **22** comprise the inductors **24**. In other aspect of the invention, the inductors **24** may be implemented as discrete components.

(12) At low band frequencies, the impedance of the inductors **24** connecting the conductive segments **22** is sufficiently low to enable the low band currents continue to flow between conductive segments **22**. At high band frequencies, however, the impedance is much higher due to the series inductors **24**, which reduces high band frequency current flow between the conductive segments **22**. Also, keeping each of the conductive segments **22** to less than one half wavelength at high band frequencies reduces undesired interaction between the conductive segments **22** and the high band radio frequency (RF) signals. Therefore, the low band radiating elements **16** of the present invention reduce and/or attenuate any induced current from high band RF radiation from high band radiating elements **14**, and any undesirable scattering of the high band signals by the low band dipole arms **20** is minimized. The low band dipole is effectively electrically invisible, or “cloaked,” at high band frequencies.

(13) As illustrated in FIG. 3, the low band radiating elements **16** having cloaked dipole arms **20** may be used in combination with cloaked parasitic elements **30**. However, either cloaked structure may also be used independently of the other. Referring to FIGS. 1 and 3, parasitic elements **30** may be located on either side of the driven low band radiating element **16** to control the azimuth beam width. To make the overall low band radiation pattern narrower, the current in the parasitic element **30** should be more or less in phase with the current in the driven low band radiating element **16**. However, as with driven radiating elements, inadvertent resonance at high band frequencies by low band parasitic elements may distort high band radiation patterns.

(14) A first example of a cloaked low band parasitic element **30a** is illustrated in FIG. 5. The segmentation of the parasitic elements may be accomplished in the same way as the segmentation of the dipole arms in FIG. 4. For example, parasitic element **30a** includes four conductive segments **22a** coupled by three inductors **24a**. A second example of a cloaked low band parasitic element **30b** is illustrated in FIG. 6. Parasitic element **30b** includes six conductive segments **22b** coupled by five inductors **24b**. Relative to parasitic element **30a**, the conductive segments **22b** are shorter than the conductive segments **22a**, and the inductor traces **24b** are longer than the inductor traces **24a**.

(15) At high band frequencies, the inductors **24a**, **24b** appear to be high impedance elements which reduce current flow between the conductive segments **22a**, **22b**, respectively. Therefore the effect of the low band parasitic elements **30** scattering of the high band signals is minimized. However, at low band, the distributed inductive loading along the parasitic element **30** tunes the phase of the low band current, thereby giving some control over the low band azimuth beam width.

(16) In a multiband antenna according to one aspect of the present invention described above, the dipole radiating element **16** and parasitic elements **30** are configured for low band operation. However, the invention is not limited to low band operation, the invention is contemplated to be employed in additional embodiments where driven and/or passive elements are intended to operate at one frequency band, and be unaffected by RF radiation from active radiating elements in other frequency bands. The exemplary low band radiating element **16** also comprises a cross-dipole radiating element. Other aspects of the invention may utilize a single dipole radiating element if only one polarization is required.

Claims

1. A multi-band base station antenna, comprising: a reflector; a first array of first frequency band cross-dipole radiating elements mounted on the reflector; a second array of second frequency band cross-dipole radiating elements mounted on the reflector, where the lowest frequency in the second frequency band exceeds the highest frequency in the first frequency band; and a plurality of parasitic elements, where a first of the parasitic elements comprises a plurality of conductive segments and a plurality of metallization tracks, where the metallization tracks are narrower than the conductive segments, and each metallization track electrically connects a respective pair of the conductive segments.
2. The multi-band base station antenna of claim 1, wherein the parasitic elements are aligned to be parallel to a longitudinal dimension of the reflector.
3. The multi-band base station antenna of claim 1, wherein the parasitic elements are aligned to be perpendicular to a longitudinal dimension of the reflector.
4. The multi-band base station antenna of claim 1, wherein the metallization tracks and conductive segments are formed on a non-conductive substrate.
5. The multi-band base station antenna of claim 1, wherein the conductive segments each have a length that is less than one-half a wavelength of a highest frequency in the second frequency band.
6. The multi-band base station antenna of claim 1, wherein each metallization tracks acts as an inductor in the second frequency band.
7. The multi-band base station antenna of claim 1, wherein the first of the parasitic elements includes at least three metallization tracks.
8. The multi-band base station antenna of claim 1, wherein the first of the parasitic elements includes at least five metallization tracks.
9. The multi-band base station antenna of claim 1, wherein the conductive segments are arranged in a line.
10. A parasitic element for a base station antenna, comprising: at least four conductive segments; and at least three metallization tracks, wherein the metallization tracks are narrower than the conductive segments, and wherein each metallization track electrically connects a respective pair of the conductive segments.
11. The parasitic element of claim 10, wherein the metallization tracks and conductive segments are formed on a non-conductive substrate.
12. The parasitic element of claim 10, wherein the parasitic element includes at least four metallization tracks.
13. The parasitic element of claim 10, wherein the conductive segments are arranged in a line.
14. A parasitic element for a base station antenna, comprising: at least four conductive segments; and at least three inductors, wherein each inductor electrically connects a respective pair of the conductive segments.
15. The parasitic element of claim 14, wherein the metallization tracks and conductive segments are formed on a non-conductive substrate.
16. The parasitic element of claim 14, wherein the parasitic element includes at least four

metallization tracks.

17. The parasitic element of claim 14, wherein the conductive segments are arranged in a line.
