US Patent & Trademark Office
Patent Public Search | Text View

United States Patent	12383004
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Kettner; Michael et al.

Glove as well as wearable sensor device comprising a glove and an electronic module

Abstract

A work glove including a dorsal section, a strap section, a trigger and a holder for an electronic module. The dorsal section includes a first opening on the side-of-the-hand edge and the strap section extends from the thumb-side edge or the dorsal section includes a first opening on the thumb-side edge and the strap section extends from the side-of-the-hand edge of the dorsal section. The strap section passes through the first opening and a portion of the strap section that passed through the first opening fastens the dorsal section detachably. Moreover, a wearable sensor device is shown.

Inventors: **Kettner; Michael (Munich, DE), Juric; Danijel (Munich, DE), Armbruster; Simon (Munich, DE)**

Applicant: **Workaround GmbH** (Munich, DE)

Family ID: **85705534**

Assignee: **WORKAROUND GMBH (Munich, DE)**

Appl. No.: **17/964324**

Filed: **October 12, 2022**

Prior Publication Data

Document Identifier	Publication Date
US 20230112442 A1	Apr. 13, 2023

Foreign Application Priority Data

DE	10 2021 126 552.5	Oct. 13, 2021

Publication Classification

Int. Cl.: **A41D19/00** (20060101); **G06K7/10** (20060101); **G06K7/14** (20060101)

U.S. Cl.:

CPC **A41D19/0024** (20130101); **G06K7/10396** (20130101); **G06K7/10891** (20130101); **G06K7/1413** (20130101); **G06K7/1417** (20130101); G06K2007/10534 (20130101)

Field of Classification Search

CPC: A41D (19/015); A41D (19/0037); A41D (19/0024); A41D (19/0013); A41D (19/0003); A41D (19/0157); A41D (13/08); A41D (13/081); A41D (13/088); G06K (7/10396); G06K (7/10891); G06K (2007/10534)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1165970	12/1914	Harris	N/A	N/A
1173269	12/1915	Heidemann	N/A	N/A
1267436	12/1917	Martin	116/35R	A41D 19/0157
2172167	12/1938	Leventhal	N/A	N/A
3512776	12/1969	Thomas, Sr.	2/161.7	A41D 13/088
3700836	12/1971	Rackson	N/A	N/A
3790168	12/1973	Hashimoto	473/62	A41D 13/088
4504980	12/1984	Butcher	N/A	N/A
4575075	12/1985	Tarbox	N/A	N/A
4658441	12/1986	Smith	N/A	N/A
4766299	12/1987	Tierney	N/A	N/A
5133233	12/1991	Erwin	N/A	N/A
5191197	12/1992	Metlitsky	N/A	N/A
5212372	12/1992	Quick	N/A	N/A
5255167	12/1992	Toussaint	N/A	N/A
5319185	12/1993	Obata	N/A	N/A
5329106	12/1993	Hone	N/A	N/A
5340972	12/1993	Sandor	N/A	N/A
5365213	12/1993	Paull	340/321	G08B 21/0297
5396053	12/1994	Swartz	N/A	N/A
5397296	12/1994	Sydor et al.	N/A	N/A
5406649	12/1994	Bolembach	N/A	N/A
5459883	12/1994	Garceau-Verbeck	N/A	N/A
5514861	12/1995	Swartz	N/A	N/A
5550366	12/1995	Roustaei	N/A	N/A
5580154	12/1995	Coulter	N/A	N/A
5592694	12/1996	Yewer, Jr.	N/A	N/A
5610387	12/1996	Bard	N/A	N/A
5625180	12/1996	Hanson	N/A	N/A
5640712	12/1996	Hansen	N/A	N/A
5654534	12/1996	Coleman	N/A	N/A

5787896	12/1997	Sackett	128/880	A41D 19/01588
5898161	12/1998	Devita	N/A	N/A
5924136	12/1998	Ogean	N/A	N/A
6154199	12/1999	Butler	N/A	N/A
6232960	12/2000	Goldman	N/A	N/A
6234393	12/2000	Paratore	N/A	N/A
6341376	12/2001	Smerdon, Jr.	2/161.1	A41D 13/082
6505776	12/2002	Wilz, Sr.	N/A	N/A
6853293	12/2004	Swartz	N/A	N/A
6991364	12/2005	Yang	N/A	N/A
7307242	12/2006	Chen	N/A	N/A
7480944	12/2008	Nascimento	N/A	N/A
7504949	12/2008	Rouaix	N/A	N/A
7837112	12/2009	An	N/A	N/A
7959314	12/2010	Rodriguez	N/A	N/A
8038310	12/2010	Hale	N/A	N/A
8230522	12/2011	Bell	N/A	N/A
8235294	12/2011	Miller	N/A	N/A
8376759	12/2012	Debock	N/A	N/A
8449541	12/2012	Schneider	N/A	N/A
8523377	12/2012	York	N/A	N/A
8540389	12/2012	Tang	N/A	N/A
8562165	12/2012	Thompson	N/A	N/A
9082293	12/2014	Wellman	N/A	N/A
9235742	12/2015	Qaddoura	N/A	N/A
9301562	12/2015	Chen	N/A	N/A
9785877	12/2016	Fink	N/A	N/A
9842288	12/2016	Debates	N/A	N/A
9895106	12/2017	Graybill	N/A	N/A
9900061	12/2017	Lui	N/A	N/A
10064276	12/2017	Williams	N/A	N/A
10135213	12/2017	Brunnbauer	N/A	N/A
10537143	12/2019	Guenther	N/A	N/A
10789436	12/2019	Lim	N/A	N/A
10817689	12/2019	Mazzone	N/A	N/A
10996754	12/2020	Bosworth	N/A	N/A
D922063	12/2020	Kirchner	N/A	N/A
11044898	12/2020	Deeb	N/A	N/A
11059076	12/2020	Bauer	N/A	N/A
11093725	12/2020	Mistkawi	N/A	N/A
11121515	12/2020	Chahine	N/A	N/A
11182575	12/2020	Sakamoto	N/A	N/A
D943585	12/2021	Engineer	N/A	N/A
D944814	12/2021	Huber	N/A	N/A
D945423	12/2021	Lim	N/A	N/A
11326960	12/2021	Larsen	N/A	N/A
11361391	12/2021	Ottnad	N/A	N/A
D960162	12/2021	Lim	N/A	N/A
D964376	12/2021	Sittig	N/A	N/A

11464450	12/2021	Huang	N/A	N/A
11470895	12/2021	Guenther	N/A	N/A
11508018	12/2021	Yoshimoto	N/A	N/A
11520314	12/2021	Schwarz	N/A	N/A
11558909	12/2022	Hutter	N/A	N/A
11589625	12/2022	Oner	N/A	N/A
D986253	12/2022	Kettner	N/A	N/A
11759288	12/2022	Lenzenhuber	N/A	N/A
11792555	12/2022	Nöllgen	N/A	N/A
11899838	12/2023	Hogbin	N/A	N/A
11913145	12/2023	Laukamp	N/A	N/A
11914771	12/2023	Kirchner	N/A	N/A
2002/0080031	12/2001	Mann	N/A	N/A
2002/0163495	12/2001	Doynov	N/A	N/A
2002/0194668	12/2001	Kwon	N/A	N/A
2003/0006962	12/2002	Bajramovic	N/A	N/A
2003/0011469	12/2002	Bush	N/A	N/A
2003/0026170	12/2002	Yang	N/A	N/A
2004/0025227	12/2003	Jaeger	N/A	N/A
2004/0128736	12/2003	Raz	N/A	N/A
2005/0052412	12/2004	McRae	N/A	N/A
2006/0033710	12/2005	Bajramovic	N/A	N/A
2006/0044112	12/2005	Bridgelall	N/A	N/A
2006/0108425	12/2005	Wiklof	N/A	N/A
2007/0083968	12/2006	Stokes	N/A	N/A
2007/0083979	12/2006	Daniels	N/A	N/A
2007/0146127	12/2006	Stilp	N/A	N/A
2007/0245454	12/2006	Eklund	N/A	N/A
2007/0288104	12/2006	Yamauchi	N/A	N/A
2008/0054062	12/2007	Gunning	N/A	N/A
2008/0071429	12/2007	Kraimer	N/A	N/A
2008/0136778	12/2007	Hursh	N/A	N/A
2008/0262666	12/2007	Manning	N/A	N/A
2009/0056107	12/2008	Williams	N/A	N/A
2009/0057289	12/2008	Williams	N/A	N/A
2009/0057290	12/2008	Williams	N/A	N/A
2009/0121026	12/2008	Druker	N/A	N/A
2009/0156309	12/2008	Weston	N/A	N/A
2009/0179739	12/2008	Kim	N/A	N/A
2009/0247299	12/2008	Conticello	N/A	N/A
2010/0023314	12/2009	Hernandez-Rebollar	N/A	N/A
2010/0090949	12/2009	Tianqiao	N/A	N/A
2010/0097195	12/2009	Majoros	N/A	N/A
2010/0156783	12/2009	Bajramovic	N/A	N/A
2010/0234182	12/2009	Hoffman	N/A	N/A
2011/0016609	12/2010	Phelps	N/A	N/A
2011/0078842	12/2010	Tang	N/A	N/A
2011/0122601	12/2010	Waters	N/A	N/A
2011/0296576	12/2010	Mitchell	2/16	A41D 13/082

2012/0025945	12/2011	Yazadi	N/A	N/A
2012/0157263	12/2011	Sivak	N/A	N/A
2012/0187192	12/2011	Lee	N/A	N/A
2012/0223143	12/2011	Turbovich	N/A	N/A
2013/0087544	12/2012	Kremer	N/A	N/A
2013/0197720	12/2012	Kraimer	N/A	N/A
2013/0258644	12/2012	Comunale	N/A	N/A
2014/0096306	12/2013	Hill	N/A	N/A
2014/0125577	12/2013	Hoang	N/A	N/A
2014/0132410	12/2013	Chang	N/A	N/A
2014/0172134	12/2013	Meschter	N/A	N/A
2014/0194166	12/2013	Falck	N/A	N/A
2014/0214631	12/2013	Hansen	N/A	N/A
2014/0215686	12/2013	McMakin, Jr.	N/A	N/A
2014/0249944	12/2013	Hicks	N/A	N/A
2014/0282923	12/2013	Narayan	N/A	N/A
2014/0366249	12/2013	West	N/A	N/A
2015/0040880	12/2014	Tseng	N/A	N/A
2015/0070162	12/2014	Vorhies	N/A	N/A
2015/0130698	12/2014	Burgess	N/A	N/A
2015/0150321	12/2014	Vorhies	N/A	N/A
2015/0257733	12/2014	Corbett, III	N/A	N/A
2015/0286976	12/2014	Hirschfeld	N/A	N/A
2015/0314195	12/2014	Bekri	N/A	N/A
2015/0375042	12/2014	Schaffer	N/A	N/A
2016/0016065	12/2015	Tan	N/A	N/A
2016/0018901	12/2015	Woolley	N/A	N/A
2016/0033238	12/2015	Cooper	N/A	N/A
2016/0066636	12/2015	West	N/A	N/A
2016/0068214	12/2015	Tang	N/A	N/A
2016/0128406	12/2015	Shiue	N/A	N/A
2016/0161301	12/2015	Guenther	N/A	N/A
2016/0174897	12/2015	Sherman	N/A	N/A
2016/0284236	12/2015	Bavunoglu	N/A	N/A
2017/0068276	12/2016	Wagman	N/A	N/A
2017/0119553	12/2016	Cipriani	N/A	N/A
2017/0168565	12/2016	Cohen	N/A	N/A
2017/0215497	12/2016	Frederick	N/A	A61F 5/0118
2017/0265561	12/2016	Beers	N/A	N/A
2017/0296098	12/2016	Ban	N/A	N/A
2017/0338610	12/2016	Brunnbauer	N/A	N/A
2018/0027344	12/2017	Dzarnoski, Jr.	N/A	N/A
2018/0146720	12/2017	Sittig	N/A	N/A
2018/0213758	12/2017	Deeb	N/A	N/A
2018/0295908	12/2017	Hollo	N/A	N/A
2018/0326592	12/2017	Kogan	N/A	N/A
2018/0376043	12/2017	Schannath	N/A	N/A
2019/0197273	12/2018	Mazzone	N/A	N/A
2019/0209086	12/2018	Huang	N/A	N/A
2019/0213363	12/2018	Sugiura	N/A	N/A

2019/0216144	12/2018	York	N/A	N/A
2019/0364996	12/2018	Kettner	N/A	A41D 19/0024
2020/0022433	12/2019	Lu	N/A	N/A
2020/0134275	12/2019	Sakamoto	N/A	N/A
2020/0160016	12/2019	Sakamoto	N/A	N/A
2020/0237032	12/2019	Berlips	N/A	A41D 19/0027
2020/0245939	12/2019	Sittig	N/A	N/A
2020/0305522	12/2019	Ruhland	N/A	N/A
2020/0359721	12/2019	Meroe	N/A	N/A
2020/0404993	12/2019	Phillips	N/A	N/A
2021/0033472	12/2020	Turner	N/A	N/A
2021/0219639	12/2020	Kettner	N/A	N/A
2021/0262127	12/2020	Laukamp	N/A	N/A
2021/0307433	12/2020	Hollo	N/A	N/A
2021/0386132	12/2020	Goldberg-Poch	N/A	A41D 31/02
2022/0053854	12/2021	Oner	N/A	N/A
2022/0100895	12/2021	Kirchner	N/A	N/A
2022/0159355	12/2021	Nöllgen	N/A	N/A
2023/0112442	12/2022	Kettner	N/A	N/A
2023/0115522	12/2022	Hutter	N/A	N/A
2024/0164459	12/2023	Clark	N/A	N/A
2024/0237767	12/2023	Kettner	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
521938	12/2020	AT	N/A
521938	12/2020	AT	N/A
2109745	12/1991	CN	N/A
204217957	12/2014	CN	N/A
107616787	12/2017	CN	N/A
108272443	12/2017	CN	N/A
109891340	12/2018	CN	N/A
109891342	12/2018	CN	N/A
110327049	12/2018	CN	N/A
110647847	12/2019	CN	N/A
112218387	12/2020	CN	N/A
112294538	12/2020	CN	N/A
306506527	12/2020	CN	N/A
306506527	12/2020	CN	N/A
113144571	12/2020	CN	N/A
110327049	12/2020	CN	N/A
109891340	12/2021	CN	N/A
202005003216	12/2004	DE	N/A
202013105192	12/2012	DE	N/A
102014117164	12/2015	DE	N/A
202015107112	12/2015	DE	N/A
102015111506	12/2015	DE	N/A
102015113847	12/2015	DE	N/A
102015214331	12/2016	DE	N/A
102015122281	12/2016	DE	N/A

102015224308	12/2016	DE	N/A
102016109113	12/2016	DE	N/A
102016109117	12/2016	DE	N/A
102017107357	12/2017	DE	N/A
102016123093	12/2017	DE	N/A
202017102714	12/2017	DE	N/A
102017203495	12/2017	DE	N/A
102018202207	12/2018	DE	N/A
102018105578	12/2018	DE	N/A
102018203035	12/2018	DE	N/A
102018112945	12/2018	DE	N/A
102018105578	12/2019	DE	N/A
102019102685	12/2019	DE	N/A
102019102730	12/2019	DE	N/A
102019113964	12/2019	DE	N/A
102019118887	12/2020	DE	N/A
102019118969	12/2020	DE	N/A
102019131235	12/2020	DE	N/A
102020100985	12/2020	DE	N/A
102020106369	12/2020	DE	N/A
102020122573	12/2021	DE	N/A
102020125554	12/2021	DE	N/A
102021200888	12/2021	DE	N/A
102019131235	12/2021	DE	N/A
102021122485	12/2022	DE	N/A
102021134380	12/2022	DE	N/A
102022132061	12/2023	DE	N/A
102023000106	12/2023	DE	N/A
0613762	12/1993	EP	N/A
1894481	12/2007	EP	N/A
2578096	12/2012	EP	N/A
2693689	12/2013	EP	N/A
3069623	12/2015	EP	N/A
3208687	12/2016	EP	N/A
3381839	12/2017	EP	N/A
3644217	12/2019	EP	N/A
3654229	12/2019	EP	N/A
3381839	12/2021	EP	N/A
4012599	12/2021	EP	N/A
3529675	12/2021	EP	N/A
4374727	12/2023	EP	N/A
2386667	12/2002	GB	N/A
2386677	12/2002	GB	N/A
2422527	12/2005	GB	N/A
2441295	12/2007	GB	N/A
2567214	12/2018	GB	N/A
201700092386	12/2018	IT	N/A
202000002125	12/2020	IT	N/A
2001084329	12/2000	JP	N/A
2011094246	12/2010	JP	N/A

2020503582	12/2019	JP	N/A
7105766	12/2021	JP	N/A
20100024593	12/2009	KR	N/A
20110115497	12/2010	KR	N/A
20210127051	12/2020	KR	N/A
210103	12/2021	RU	N/A
M484318	12/2013	TW	N/A
9318675	12/1992	WO	N/A
9850839	12/1997	WO	N/A
02088918	12/2001	WO	N/A
03005176	12/2002	WO	N/A
2006077572	12/2005	WO	N/A
2008075859	12/2007	WO	N/A
2012036775	12/2011	WO	N/A
2014011196	12/2013	WO	N/A
2016012480	12/2015	WO	N/A
2017062621	12/2016	WO	N/A
2018073420	12/2017	WO	N/A
2018076067	12/2017	WO	N/A
2018099430	12/2017	WO	N/A
2019018702	12/2018	WO	N/A
2020117166	12/2019	WO	N/A
2021014179	12/2020	WO	N/A
2021099138	12/2020	WO	N/A
2021101402	12/2020	WO	N/A
2021156709	12/2020	WO	N/A
2022035820	12/2021	WO	N/A
2023019535	12/2022	WO	N/A
2024023009	12/2023	WO	N/A

OTHER PUBLICATIONS

Borghetti M. et al., “Sensorized Glove for Measuring Hand Finger Flexion for Rehabilitation Purposes,” IEEE Transactions on Instrumentation and Measurement, vol. 62, No. 12, Dec. 2013. cited by applicant

Dipietro L. et al., “A Survey of Glove-Based Systems and Their Applications,” IEEE Transactions on Systems, Man, and Cybernetics—Part C: Applications and Reviews, vol. 38, No. 4, Jul. 2008. cited by applicant

Kim, J-H. et al., 3-D Hand Motion Tracking and Gesture Recognition Using a Data Glove, IEEE International Symposium on Industrial Electronics (ISIE 2009), Seoul Olympic Parktel, Seoul, Korea, Jul. 5-8, 2009. cited by applicant

King, R. C. et al., “Development of a Wireless Sensor Glove for Surgical Skills Assessment,” IEEEE Transactions on Information Technology in Biomedicine, vol. 13, No. 5, Sep. 2009. cited by applicant

Simone, L. K. et al., “A low cost instrumented glove for extended monitoring and functional hand assessment,” Journal of Neuroscience Methods 160 (2007) 335-348. cited by applicant

Sturman, D.J. et al., “A Survey of Glove-based Input,” IEEE Computer Graphics & Applications (1994) 33-39. cited by applicant

Ziegler, J. et al., “Advanced Interaction Metaphors for RFID—Tagged Physical Artefacts,” 2011 IEEE International Conference on RFID—Technologies and Applications, 73-80. cited by applicant

Albert Schweitzer: “Rigid-Flex, Flex and Semi-Flex Leiterplatten Technologie”, Mar. 17, 2017,

https://www.flowcad.ch/cms/upload/downloads/PCBRoadshow20IFlex.pdf (89 pages). cited by applicant
Opposition filed against German Patent No. DE102015017430B3, on May 10, 2024 with translation. 137 pages. cited by applicant

---

Primary Examiner: Nguyen; Uyen T

Attorney, Agent or Firm: DILWORTH IP, LLC

Background/Summary

FIELD OF THE DISCLOSURE
(1) The disclosure relates to a glove, in particular a work glove as well as a wearable sensor device comprising a glove and an electronic module.
BACKGROUND
(2) Gloves comprising electrical triggers are known and are used, for example, in combination with one or several electronic modules. These electronic modules typically have sensors and can also be attached to the glove, resulting in a wearable sensor system, what is termed a “wearable”.
(3) For example, the electronic module is a barcode scanner and the trigger is used to trigger a scanning process. The trigger can also be used for other purposes, such as counting processes or operating further units of the wearable. Therefore, the electrical trigger must be simple to trigger, but also protected from being triggered accidentally.
(4) The gloves are also worn by a variety of different users who are naturally different in size and thus have different sized hands. It is therefore necessary to provide gloves in different sizes, thus increasing production, logistics and storage costs.
SUMMARY
(5) Thus, there is a need to provide a glove as well as wearable sensor device that has a universal size and can therefore be fastened to the hand reliably and securely irrespective of user's hand size.
(6) The object is solved by a glove, in particular a work glove, comprising a dorsal section, a strap section, a trigger and a holder for an electronic module that is attached to the dorsal section. The dorsal section comprises a thumb-side edge, a wrist-side edge and a side-of-the-hand edge. The dorsal section comprises a first opening on the side-of-the-hand edge and the strap section extends from the thumb-side edge or the dorsal section comprises a first opening on the thumb-side edge and the strap section extends from the side-of-the-hand edge of the dorsal section. In the closed state of the glove, the strap section passes through the first opening and a portion of the strap section that passed through the first opening fastens the dorsal section detachably.
(7) The disclosure is based on the finding that the glove, in particular the trigger section and the dorsal section, can be fastened to the user's hand durably, securely and reliably if a strap section secures the glove along the palm of the hand. By means of the first opening and a detachable fastening of the dorsal section, enough tensile force can be applied to the dorsal section to fasten this to the hand securely. Simultaneously, the fastening with the strap section is flexible so that the glove can be fastened to different-sized hands.
(8) In this regard, requirements related to occupational safety, such as avoiding loops and protruding material parts, e.g. on the dorsum of the hand, are met reliably.
(9) For example, the portion of the strap section that passed through the first opening is attached or fastened detachably to the dorsal section, in particular the wrist-side portion of the dorsal section.
(10) In particular, the strap section has a free end and an end that is permanently connected to the trigger section or the dorsal section and is opposite the free end. The free end is part of the area that

passes through the first opening.
(11) For example, an area for a user's hand is formed in the closed state between the strap section and the dorsal section.
(12) The strap section can be formed as a band and/or designed to fasten the glove onto a user's hand.
(13) For example, the dorsal section in the correctly worn state covers the dorsum of the user's hand and/or the strap section extends across the palm, in particular twice.
(14) The trigger section can also extend from the finger-side edge, in particular in the principal direction.
(15) Within the scope of this disclosure, the direction from the wrist-side edge towards the finger-side edge is regarded, for example, as the principal direction.
(16) In an embodiment, the dorsal section comprises a trigger section on which the trigger is attached, wherein the trigger section is provided on the thumb-side edge of the dorsal section and wherein the strap section extends from the trigger section or wherein the first opening is provided on the trigger section. In this way, the trigger section and thus the trigger are placed particularly reliably and are easily reachable on the user's hand.
(17) In an embodiment, the trigger section comprises a tongue that extends in the principal direction away from both the strap section as well as the dorsal section, in particular wherein the trigger is located at least in part on the tongue. By doing so, the trigger is positioned optimally on the metacarpophalangeal joint of the index finger without limiting the mobility of the finger.
(18) For even more reliable fastening of the trigger section, the trigger section can be provided between the strap section and the dorsal section and/or the strap section can start at the edge of the trigger section facing away from the dorsal section.
(19) For example, the strap section is made of a stretchable and/or elastic material, in particular along the longitudinal direction of the strap section, thereby making the glove particularly tight-fitting. The direction from the permanently connected end towards the free end is regarded as the longitudinal direction.
(20) In an embodiment, the strap section runs towards the wrist-side edge in the closed, in particular, correctly worn state counter to the principal direction and/or has a V-shaped form, in particular wherein the first opening is the tip of the V shape or the V-shaped form. In this way, the fastening of the glove onto the hand is improved further.
(21) For example, the user's thumb extends through an area that is defined by the strap section, in particular by the lines of the V-shaped form, and the thumb-side edge.
(22) In one aspect, the glove is designed without any loops for fingers and/or without a palm section, thereby making it possible to put the glove on easily. The strap section is not to be regarded as the palm section as the palm largely remains free even in the worn state.
(23) For reliable attachment of the trigger section, the trigger section can be provided between the strap section and the dorsal section and/or the strap section can start at the edge of the trigger section facing away from the dorsal section.
(24) For example, the trigger section is the only permanent connection between the strap section and the dorsal section.
(25) In an embodiment, a fastening means for detachable fastening of the portion of the strap section that passed through the first opening is located on the dorsal section, in particular on the wrist-side edge of the dorsal section. In this way, the detachable fastening of the strap section can be made even more reliable.
(26) For example, the fastening means comprises a hook-and-loop-fastener strip and the strap section comprises a complementary hook-and-loop-fastener strip, thereby realizing the detachable fastening particularly simply.
(27) Alternatively or additionally, the fastening means can comprise a second opening through which the strap section extends in the closed state, in particular wherein the strap section has on

one side two hook-and-loop-fastener strips that are complementary to each other. As a result, the detachable connection is made more secure.
(28) In particular, the portion of the strap section that passed through the first opening extends at least in part also through the second opening.
(29) So that the glove fits even more closely, the second opening can be located on the thumb-side edge and/or a main axis of the second opening extends parallel to the thumb-side edge.
(30) In one aspect, the fastening means is located in the principal direction closer to the wrist-side edge than the first opening, the trigger section and/or the permanently connected end of the strap section in order to improve the fastening of the glove further.
(31) The glove can be particularly tight-fitting if the first opening is located in the principal direction closer to the wrist-side edge than the trigger section and/or the permanently connected end of the strap section.
(32) In an embodiment, the dorsal section has a width between the thumb-side edge and the side-of-the-hand edge, wherein strap section has a length that is at least two times, in particular 2.5 times the width of dorsal section, thereby ensuring that the glove is deployable on many different sizes of hand.
(33) The trigger in the principal direction of the glove can be further away from the wrist-side edge than 75% of the holder, in particular the entire holder, so that the trigger is easily reachable.
(34) In an embodiment, the glove has a base body that comprises the dorsal section, the strap section and the trigger section, thereby making it possible to manufacture the glove simply.
(35) The dorsal section, the strap section and the trigger section can be designed together as one piece.
(36) To produce a reliable electrical connection between the trigger and the electronic module, the holder can have at least one electrical contact element that is connected electrically to the trigger by means of a cable, in particular a flex PCB cable.
(37) In an embodiment, the trigger and/or the cable are covered by a protective layer, in particular a protective layer that differs from the base body, thereby improving the service life of the glove.
(38) In an embodiment, the portion of the strap section that passed through the first opening and is not fastened to the dorsal section is fastened to another portion of the strap section in the closed state of the glove. In this way, excess length of the strap section is stowed away securely.
(39) Moreover, the object is solved by a wearable sensor device comprising a glove as previously described and an electronic module that is inserted into the holder, in particular wherein the electronic module comprises a camera, a scanner for identifiers such as barcodes, 2D codes or RFID tags and/or a display for displaying instructions to the user that are triggerable by actuating the trigger.
(40) The features and advantages described for the glove apply equally to the sensor device and vice versa.

Description

BRIEF DESCRIPTION OF THE DRAWINGS
(1) Additional advantages and features can be found in the following description as well as in the attached drawings to which reference is made. In the drawings:
(2) FIG. **1** shows a wearable sensor device according to the disclosure comprising a glove according to the disclosure in top view in a position spread out on a table.
(3) FIG. **2** shows an enlargement of the dorsal section and the trigger section of the glove according to FIG. **1**,
(4) FIGS. **3** and **4** show the glove according to FIG. **1** worn on a hand in a correctly worn state with views of the palm and dorsum of the hand respectively.

(5) FIG. **5** shows a top view according to FIG. **1** of a second embodiment of a glove according to the disclosure, and
(6) FIG. **6** shows the glove according to FIG. **5** worn on a user's hand in the correctly worn state with a view of the palm of the hand.

DETAILED DESCRIPTION

(7) Lists having a plurality of alternatives connected by “and/or”, for example “A, B and/or C” are to be understood to disclose an arbitrary combination of the alternatives, i.e. the lists are to be read as “A and/or B and/or C”. The same holds true for listings with more than three items.
(8) In FIG. **1**, a wearable sensor device **10** is shown comprising a glove **12** and an electronic module **14**.
(9) The electronic module **14** is, for example, a compact and robust device for industrial applications. In particular, the electronic module **14** comprises a camera, a scanner for identifiers such as barcodes, 2D codes or RFID tags and/or a display for displaying instructions to the user.
(10) In particular, the electronic module **14** is not a smart device such as a smartphone.
(11) The glove **12** is shown in FIG. **1** in a state in which it is spread out on a flat surface, for example spread out on a table.
(12) The glove **12** comprises a base body **16** that is made of an elastic material, such as neoprene, limitation leather, synthetic leather (for example microfibers) and/or spacer fabrics.
(13) The base body **16** and in particular the entire glove **12** do not have any fingers or appendages for fingers.
(14) The glove **12** and the base body **16** also do not have a palm section, i.e. a section that rests on the palm of the hand in the correctly worn state and covers the majority of the palm, in particular more than 50%.
(15) The glove **12** of the shown embodiment is thus not a full glove with fingers, but rather a glove which only covers the dorsum of a user's hand, provided it is being worn correctly. The glove **12** is thus similar to a bandage that only surrounds parts of the hand and does not need to be pulled over the hand, but rather is closed around the hand.
(16) The base body **16** comprises a dorsal section **18** with a trigger section **20** and a strap section **22**.
(17) The dorsal section **18** with the trigger section **20** and the strap section **22** are therefore designed as one piece.
(18) The dorsal section **18** comprises a thumb-side edge **24**, a wrist-side edge **26**, a side-of-the-hand edge **28** as well as a finger-side edge **30**. The edges **24**, **26**, **28**, **30** are located in this order counterclockwise.
(19) The designations “thumb-side”, “wrist-side”, “side-of the-hand” and “finger-side” relate to the position of the corresponding edge **24**, **26**, **28**, **30** in relation to the user's hand in the correctly worn state of the glove **12**.
(20) For simplification, a top side and an underside of the glove **12** or the base body **16** and its sections are referred to within the context of this disclosure. The top side is the side visible in FIG. **1** while the underside is the side hidden from view.
(21) With regard to the dorsal section **18** and the trigger section **20**, the top side is that side that is facing away from the user's hand when the glove **12** is worn correctly and accordingly the underside rests against the user's hand.
(22) The thumb-side edge **24** and the side-of-the-hand edge **28** are opposite each other. Similarly, the wrist-side edge **26** and the finger-side edge **30** are opposite one another.
(23) For simplification, the direction extending from the wrist-side edge **26** towards the finger-side edge **30** is regarded as the principal direction H within the context of this disclosure. This direction can be regarded as the extension of the user's arm if both the arm and the hand are fully extended. The traverse direction Q of the glove **12** is perpendicular to this.
(24) The trigger section **20** extends from the thumb-side edge **24** of the rest of the dorsal section **18**

in the traverse direction Q and also from the finger-side edge **30** in the principal direction H.
(25) For example, the trigger section **20** extends from the portion of the rest of the dorsal section **18** in which the finger-side edge **30** and the thumb-side edge **24** would intersect or merge into each other.
(26) In the shown embodiment, the strap section **22** extends from the trigger section **20**, more specifically from the side of the trigger section **20** that is facing away from the dorsal section **18**.
(27) The strap section **22** is formed as a band and has an end permanently connected to the trigger section **20** as well as a free end **32**. The free end **32** is opposite the end permanently connected to the trigger section **20**.
(28) The trigger section **20** is located between the strap section **22** and the dorsal section **18** and is thus the only permanent connection between the strap section **22** and the dorsal section **18**.
(29) The length of the strap section **22** from its free end **32** to the end permanently connected to the trigger section **20**, in particular to the trigger, is at least 250 mm, in particular at least 340 mm.
(30) The strap section **22** can be designed to be stretchable or elastic in its longitudinal direction, i.e. in a direction from the free end **32** to the end permanently connected to the trigger section **20**. For example, the material of the strap section **22** and the material of the base body **16** is stretchable and/or elastic in at least one direction.
(31) On the top side and/or the underside, the strap section **22** comprises a hook-and-loop-fastener strip **34** that extends in particular across at least half of the length of the strap section **22**.
(32) The length of the strap section **22** is, for example, twice as large, in particular at least two and a half times larger than the width of the dorsal section **18**, thus the distance between the thumb-side edge **24** and the side-of-the-hand edge **28** at the widest point.
(33) In this embodiment, but also in general, if the glove **12** is spread out on a flat surface as shown, an angle α starting at the strap section **22** and ending at the thumb-side edge **24** of the dorsal section **18** can be less than 100°, in particular less than 90°. The angle α is to be measured here in the mathematical direction of rotation (counterclockwise).
(34) The width of the strap section **22** is between 15 and 25 mm, in particular 20 mm.
(35) In FIG. **2**, a part of the glove **12** is shown enlarged, more specifically the dorsal section **18** and the trigger section **20**.
(36) It is clearly evident that a fastening means **36** and a holder **38** for the electronic module **14** are located and attached on the dorsal section **18** on its top side. In addition, the dorsal section **18** comprises a first opening **40**.
(37) In the first embodiment shown, the fastening means **36** is a hook-and-loop-fastener strip **42** that is complementary to the hook-and-loop-fastener strip **34** of the strap section **22**. This means that the hook-and-loop-fastener strip **34** and the hook-and-loop-fastener strip **42** fasten to each other when they come into contact with each other, thus forming a hook-and-loop fastener.
(38) The hook-and-loop-fastener strip **42** extends along the wrist-side edge **26** of the dorsal section **18**.
(39) For example, the hook-and-loop-fastener strip **42** starts at the thumb-side edge **24** and extends almost completely to the side-of-the-hand edge **28**, for example in the traverse direction Q.
(40) The fastening means **36**, thus the hook-and-loop-fastener strip **42** in the shown embodiment, is therefore located closer to the wrist-side edge **26** than the first opening **40**, the trigger section **20** and the permanently connected end of the strap section **22**.
(41) The first opening **40** is located on the side-of-the-hand edge **28** and has a length along a main axis **44** that is significantly greater than its length traverse to the main axis **44**.
(42) The first opening **40** is thus nearly slit-shaped. Moreover, the first opening **40** can be reinforced using an eyelet **46**.
(43) The main axis **44** runs in the shown embodiment parallel to the side-of-the-hand edge **28** of the dorsal section **18**.
(44) In this embodiment, but also in every other embodiment, the main axis **44** and the thumb-side

edge **24** can form an angle β of less than 90°, in particular less than 80°, wherein the angle β starting at the main axis **44** of the first opening **40** is to be measured in the mathematical direction of rotation (counterclockwise) when the glove **12** is spread out on a flat surface.
(45) Alternatively or additionally, the side-of-the-hand edge **28** with the thumb-side edge **24** can form an angle that is less than 90°, in particular less than 80°, wherein the angle γ starting at the side-of-the-hand edge **28** is to be measured in the mathematical direction of rotation (counterclockwise) when the glove **12** is spread out on a flat surface.
(46) The first opening **40** can be provided on a tab **48** of the dorsal section **18** that protrudes in relation to the holder **38**.
(47) The first opening **40** is located in the principal direction H closer to the wrist-side edge **26** than the trigger section **20** and the permanently connected end of the strap section **22**.
(48) This specification can relate to both the point closest to the wrist-side edge **26** as well as the center of area of the top view shown in FIG. **1**.
(49) The holder **38** is provided on the finger-side edge **30** of the dorsal section **18** and is attached to the top side of the dorsal section **18**.
(50) The holder **38** is adjacent to the finger-side edge **30** or projects over the finger-side edge **30**. In particular, the holder **38** is located parallel to the finger-side edge **30**.
(51) Two contact elements **49** used for the contacting of the electronic module **14** are provided on the holder **38**. The contact elements **49** project into a receiving space of the holder **38**, in which the electronic module **14** can be inserted.
(52) The electronic module **14** comprises correspondingly implemented mating contacts that contact to the contact elements **49** electrically when the electronic module **14** is inserted in the holder **38**.
(53) The trigger section **20** comprises a tongue **50** as well as a trigger **52**.
(54) The tongue **50** extends away from the wrist-side edge **26** in the principal direction H, namely further than the point of the strap section **22** and the point of the dorsal section **18** which are in each case furthest from the wrist-side edge **26**.
(55) The trigger **52** is located on the tongue **50** at least partially, in particular completely.
(56) The trigger **52** is, for example, a mechanical push button that is attached to the top side of the trigger section **20**.
(57) In the principal direction H, the trigger **52** is further away from wrist-side edge **26** than 75% of the holder **38**, in particular the entire holder **38**. This specification can be understood in relation to the surface of the holder **38** in the top view shown in FIGS. **1** and **2**.
(58) The trigger **52** is connected to the holder **38**, in particular the contact elements **49** of the holder **38**, by means of a cable **54** that is designed as a flex PCB cable in the shown embodiment.
(59) The trigger **52** and the cable **54** are covered by a protective layer **56** that is not shown in FIG. **2**. The protective layer **56** can be made of a material that differs from the material of base body **16**. In particular, the protective layer **56** has a first section that covers the trigger **52**, for example using a thermoplastic such as TPU, and a second section that covers the cable **54** and surrounds the trigger **52**.
(60) In FIGS. **3** and **4**, the glove **12** is shown in the closed state and at the same time on the user's hand in the correctly worn state. The closed state of the glove **12** can be attained by fastening the strap section **22** onto the dorsal section **18** as described hereinafter, more specifically the first opening **40** and the fastening means **36**.
(61) In the correctly worn state, the dorsal section **18** rests with its underside on the dorsum of the user's hand. The trigger section **20**, in particular the area of the trigger **52**, rests with the underside on the metacarpophalangeal joint of the index finger and the strap section **22** extends twice around the palm.
(62) To this end, the strap section **22** runs from the trigger section **20** through the first opening **40** that now rests on the side of the hand. Then, the portion of the strap section **22** that passed through

the first opening **40**, thus was guided through said opening, runs across the palm towards the fastening means **36**, thus in this case to the hook-and-loop-fastener strip **42**.
(63) The portion of the strap section **22** that passed through the first opening **40** thus reaches the fastening means **36** via the wrist-side edge **26** of the dorsal section **18** and is fastened there detachably onto the dorsal section **18** by means of the fastening means **36**. As a result, the dorsal section **18** is fastened by the strap section **22**.
(64) For example, the hook-and-loop-fastener strip **42** of the dorsal section **18** and the hook-and-loop-fastener strip **34** of the strap section **22** attach to each other.
(65) In doing so, the strap section **22** in total runs counter the principal direction H, thus from the trigger section **20** to the wrist-side edge **26**, although not directly.
(66) The excess length of the strap section **22**, thus a portion of the strap section **22** protruding beyond the fastening means **36**, can then be wound around the wrist and, if applicable, fixed securely in place by means of a clip or a hook-and-loop-fastener strip onto the dorsal section **18** or onto another portion of the strap section **22** itself.
(67) The user can now actuate the trigger **52** simply by moving the thumb. As a result, the electrical state of the contact element **49** changes, which can be recognized by the inserted electronic module **14**. Subsequently, the electronic module **14** can execute a predefined action, for example a scanning process by means of a barcode scanner. Thus, the electronic module **14** can be actuated by means of the trigger **52**.
(68) In the shown embodiments, the path of the strap section **22** in the closed state is a V-shape or V-shaped, wherein the first line of the V-shape starts at the trigger section **20** and the tip of the V-shape is formed by the first opening **40**, which is where the strap section **22** changes direction. The second line of the V-shape is then formed by the portion of the strap section **22** that passed through the first opening **40** and is fastened onto the fastening means **36**.
(69) In this way, a receiving space for the user's hand is formed between the strap section **22** and the dorsal section **18**.
(70) In particular, the thumb extends through an area that is defined by the lines of the V-shape and the thumb-side edge **24** of the dorsal section **18**.
(71) Thus, the dorsal section **18** and the entire glove **12** is fastened securely, reliably and permanently on the user's hand by means of the strap section **22**, irrespective of the size of the user's hand. Thus, the glove **12** is a universal size that fits any hand. There is thus a model for the right hand and a different model for the left hand. However, these models are only required in one universal size.
(72) In the shown embodiment, the strap section **22** extends from the trigger section **20**. It is also conceivable that the trigger section **20** extends from the side-of-the-hand edge **28** of the dorsal section **18** and the trigger section **20** has the first opening **40**.
(73) In FIGS. **5** and **6**, a second embodiment of the glove **12** according to the disclosure is shown that substantially corresponds to the first embodiment so that that only the differences are discussed hereinafter. Identical and functionally equivalent parts are provided with the same reference signs.
(74) In the second embodiment, the fastening means **36** is designed differently. The fastening means **36** now comprises a second opening **58** in the dorsal section **18**. The second opening **58** matches the form of the first opening **40** so that the strap section **22** can be passed through.
(75) The main axis **60** of the second opening **58** runs parallel to the thumb-side edge **24** and the second opening **58** adjoins the wrist-side edge **26**.
(76) The second opening **58** can also be reinforced using an eyelet **46**.
(77) The second opening **58** is located in particular closer to the wrist-side edge **26** than the first opening **40**.
(78) The strap section **22** now has two hook-and-loop-fastener strips **62**, **64** on its top side and/or underside which are complementary to each other so that they attach to each other.
(79) For example, both hook-and-loop-fastener strips **62**, **64** extend together across 50%, in

particular 85% of the length of the strap section **22**.
(80) In FIG. **6**, the glove **12** of the second embodiment is shown on the user's hand in the correctly worn state.
(81) As described for the first embodiment, the strap section **22** runs in a V-shape. The portion of the strap section **22** that passed through the first opening **40** is however guided through the second opening **58** that thus completes the second line of the V-shape.
(82) When the strap section **22** has been guided through the second opening **58**, the dorsal section **18** is fastened.
(83) The excess length of the strap section **22** can then be guided back the same way so that the excess length of the strap section **22** comes to rest across the second line of the V-shape and is fastened there by means of the hook-and-loop-fastener strips **62**, **64**.
(84) Alternatively, the excess length can be wrapped around the wrist and detachably fastened to the dorsal section **18**, for example by means of a hook-and-loop-fastener strip **66** that is similar to the one of the first embodiment. This hook-and-loop-fastener strip **66** can be part of the fastening means **36** so that it corresponds to hook-and-loop-fastener strip **34**.
(85) In this way, it is possible to ensure the secure fastening of the glove **12** and the dorsal section **18** to the user's hand irrespective of the size of the hand.

Claims

1. A glove comprising a dorsal section, a strap section, a trigger and a holder for an electronic module that is attached to the dorsal section, wherein the dorsal section comprises a thumb-side edge, a wrist-side edge and a side-of-the-hand edge, wherein the dorsal section has a first opening being a through hole extending through the dorsal section, wherein the strap section passes through the first opening in a closed state of the glove and a portion of the strap section that passed through the first opening fastens the dorsal section detachably, wherein portions of the holder and the first opening are equidistant from the wrist-side edge in a principal direction, the principal direction extending from the wrist-side edge towards a finger-side edge, wherein the first opening is on the side-of-the-hand edge and the strap section extends from the thumb-side edge, wherein a fastener for detachable fastening of the portion of the strap section that passed through the first opening is located on the dorsal section, and wherein the fastener comprises a second opening, through which the strap section extends in the closed state, wherein the second opening is located on the thumb-side edge, wherein the first opening is located in the principal direction closer to the wrist-side edge than at least one of a trigger section on which the trigger is attached or a permanently connected end of the strap section, and wherein the second opening is closer to the wrist-side edge than the first opening.
2. The glove according to claim 1, wherein the trigger section is provided on the thumb-side edge of the dorsal section, and wherein the strap section extends from the trigger section or wherein the first opening is provided on the trigger section.
3. The glove according to claim 2, wherein the trigger section comprises a tongue that extends away in the principal direction both from the strap section as well as from a rest of the dorsal section.
4. The glove according to claim 2, wherein the trigger section is provided between the strap section and a rest of at least one of the dorsal section or the strap section starts at an edge of the trigger section facing away from the rest of the dorsal section.
5. The glove according to claim 1, wherein the strap section runs towards the wrist-side edge in the closed state counter to the principal direction or a path of the strap section in the closed state is a V-shape.
6. The glove according to claim 1, wherein the glove is designed without any loops for fingers or a palm section in an open state.

7. The glove according to claim 1, wherein the fastener is located in the principal direction closer to the wrist-side edge than at least one of the first opening, the trigger section on which the trigger is attached, or the permanently connected end of the strap section.
8. The glove according to claim 1, wherein the glove has a base body that comprises the dorsal section, the strap section and the trigger section on which the trigger is attached.
9. The glove according to claim 1, wherein, when the glove is in an open state on a flat surface, an angle α between the strap section and a portion of the thumb-side edge of the dorsal section extending toward the strap section in the principal direction is less than 90°.
10. The glove according to claim 1, wherein the first opening is the only opening on the side-of-the-hand edge.
11. The glove according to claim 1, wherein the strap section has a free end and the end permanently connected to the trigger section, wherein a length of the strap section, from its free end to its end permanently connected to the trigger section, is at least 250 mm.
12. The glove according to claim 1, wherein a width of the strap section is smaller than 25 mm.
13. The glove according to claim 1, wherein a main axis of the first opening and a portion of the thumb-side edge extending toward the strap section in the principal direction form an angle β of less than 90°.
14. The glove according to claim 1, wherein the side-of-the-hand edge with the thumb-side edge form an angle that is less than 90°.
15. The glove according to claim 1, wherein the glove comprises only one strap section.
16. The glove according to claim 1, wherein a top edge of the holder is positioned above a top edge of the first opening in the principal direction.
17. A wearable sensor device comprising a glove and an electronic module that is inserted into a holder, wherein the glove comprises a dorsal section, a strap section, a trigger and the holder for the electronic module that is attached to the dorsal section, wherein the dorsal section comprises a thumb-side edge, a wrist-side edge and a side-of-the-hand edge, wherein the dorsal section has a first opening being a through hole extending through the dorsal section, wherein the strap section passes through the first opening in a closed state of the glove and a portion of the strap section that passed through the first opening fastens the dorsal section detachably, wherein portions of the holder and the first opening are equidistant from the wrist-side edge in a principal direction, the principal direction extending from the wrist-side edge towards a finger-side edge, wherein the first opening is on the side-of-the-hand edge and the strap section extends from the thumb-side edge, wherein a fastener for detachable fastening of the portion of the strap section that passed through the first opening is located on the dorsal section, and wherein the fastener comprises a second opening, through which the strap section extends in the closed state, wherein the second opening is located on the thumb-side edge, wherein the first opening is located in the principal direction closer to the wrist-side edge than at least one of a trigger section on which the trigger is attached or a permanently connected end of the strap section, and wherein the second opening is closer to the wrist-side edge than the first opening.
18. A glove, comprising: a dorsal section, a strap section, a trigger, and a holder for an electronic module that is attached to the dorsal section, wherein the dorsal section comprises a thumb-side edge, a wrist-side edge and a side-of-the-hand edge, wherein the dorsal section has a first opening being a through hole extending through the dorsal section, wherein the strap section passes through the first opening in a closed state of the glove and a portion of the strap section that passed through the first opening fastens the dorsal section detachably, wherein the glove comprises only one single strap section, wherein the first opening is on the side-of-the-hand edge and the strap section extends from the thumb-side edge, wherein a fastener for detachable fastening of the portion of the strap section that passed through the first opening is located on the dorsal section, and wherein the fastener comprises a second opening, through which the strap section extends in the closed state, wherein the second opening is located on the thumb-side edge, wherein the first opening is located

in a principal direction closer to the wrist-side edge than at least one of a trigger section on which the trigger is attached or a permanently connected end of the strap section, and wherein the second opening is closer to the wrist-side edge than the first opening.