

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12391112
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Kim; In Cheol

Air flap apparatus for vehicle

Abstract

The present disclosure relates to an air flap apparatus for a vehicle, which is improved to prevent an air flap from being rotated by a traveling wind generated when the vehicle travels at a high speed. The air flap apparatus for a vehicle includes a frame disposed behind a grill of a vehicle, an air flap that opens or closes an air inlet formed in the frame, a power transmission unit that is connected to the air flap and rotates the air flap, and a driving unit that is disposed outside the frame and generates power, wherein the power transmission unit includes a link that is connected to the air flap and rotates the air flap, and a loader that is connected to the driving unit, is rotated by the power generate by the driving unit, and stops movement of the link when the air flap closes the air inlet.

Inventors:	Kim; In Cheol (Yongin-si, KR)
Applicant:	HYUNDAI MOBIS CO., LTD. (Seoul, KR)
Family ID:	1000008765253
Assignee:	HYUNDAI MOBIS CO., LTD. (Seoul, KR)
Appl. No.:	18/205105
Filed:	June 02, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240300319 A1	Sep. 12, 2024

Foreign Application Priority Data

KR	10-2023-0030279	Mar. 08, 2023
----	-----------------	---------------

Publication Classification

Int. Cl.: B60K11/08 (20060101)

U.S. Cl.:

CPC B60K11/085 (20130101);

Field of Classification Search

CPC: B60K (11/08); B60K (11/085); B60H (2001/3478); B60H (1/00871); B60H (1/00671); B60H (1/00678); B60H (2001/00707)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
11987116	12/2023	Müller	N/A	B60R 19/52
2020/0215900	12/2019	Kim	N/A	B60K 11/06
2021/0114670	12/2020	Kim	N/A	F01P 7/10
2022/0080823	12/2021	Kim	N/A	F01P 7/10
2022/0250445	12/2021	Kim	N/A	B60H 1/3421
2022/0266655	12/2021	Kim	N/A	B60H 1/345
2023/0077641	12/2022	Byun	296/180.5	B60K 11/085
2023/0078614	12/2022	Byun et al.	N/A	N/A
2023/0125506	12/2022	Takita	165/96	B60K 11/085
2023/0182563	12/2022	Jeong	180/68.1	B60K 11/085
2023/0202289	12/2022	Jeong	180/68.1	B60K 11/085
2023/0286373	12/2022	Harter	N/A	B60K 11/085
2023/0415564	12/2022	Müller	N/A	F01P 7/10
2024/0246501	12/2023	Zhu	N/A	B60R 19/52
2025/0042242	12/2024	Kim	N/A	B60K 11/085

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
20 2022 105 146	12/2022	DE	N/A
10-2021-0033181	12/2020	KR	N/A

OTHER PUBLICATIONS

Office Action issued in German Patent Application DE 102023115037.5 dated Apr. 12, 2024, with English translation. cited by applicant

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

(1) This application claims priority to and the benefit of Korean Patent Application No. 10-2023-0030279 filed on Mar. 8, 2023, the disclosure of which is incorporated herein by reference in its entirety.

BACKGROUND

1. Field of the Invention

(2) The present disclosure relates to an air flap apparatus for a vehicle.

2. Discussion of Related Art

(3) To stably operate various heat exchangers in an engine room of a vehicle, external air should be smoothly supplied into the engine room. However, when the vehicle travels at a high speed, a large amount of outside air is introduced at a high speed, and accordingly, air resistance against the vehicle becomes very large. Accordingly, fuel efficiency of the vehicle is degraded.

(4) To solve this problem, an air flap apparatus in which a traveling wind passing through a grill installed in front of the engine room of the vehicle and flowing toward the engine room is introduced into the engine room or inflow of the traveling wind into the engine room is blocked, thereby helping improve fuel efficiency of the vehicle has been developed.

(5) The air flap apparatus may include an air flap, a driving unit that generates power to rotate the air flap, and a power transmission unit that connects the driving unit and the air flap to rotate the air flap while rotating with the power generated by the driving unit.

(6) Among them, the air flap may rotate to be opened or closed to allow the traveling wind introduced from the outside of the vehicle by the driving unit and the power transmission unit to flow into the engine room or block the inflow of the traveling wind into the engine room.

(7) However, an air flap device according to the related art, in a state in which an air flap faces a grill to rotate and block a traveling wind, when the traveling wind moving to an engine room comes into contact with the air flap while a vehicle travels at a high speed, the traveling wind forcibly rotates the air flap, and thus an unintended traveling wind is introduced into the engine room. When a torque of a driving unit is set to be strong to prevent this, the driving unit is overloaded and thus can fail. Accordingly, the smooth operation of the air flap apparatus cannot be achieved.

SUMMARY OF THE INVENTION

(8) The present disclosure is directed to providing an air flap apparatus for a vehicle, which is improved to prevent an air flap from being rotated by a traveling wind generated when the vehicle travels at a high speed.

(9) An air flap apparatus for a vehicle according to an embodiment of the present disclosure includes a frame disposed behind a grill of a vehicle, an air flap that opens or closes an air inlet formed in the frame, a power transmission unit that is connected to the air flap and rotates the air flap, and a driving unit that is disposed outside the frame and generates power, wherein the power transmission unit includes a link that is connected to the air flap and rotates the air flap, and a loader that is connected to the driving unit, is rotated by the power generate by the driving unit, and stops movement of the link when the air flap closes the air inlet.

(10) The link may include a link body that is connected to the air flap and the loader and allows reverse rotation by the loader, the loader may include a loader plate connected to the link body, and the air flap may be is rotatably configured to be disposed at a first position at which the air inlet is open and a second position at which the air inlet is closed.

- (11) When the air flap is disposed at the second position, the link body may be disposed parallel to the loader plate.
 - (12) When the air flap is disposed at the second position, the link body may be disposed to form an obtuse angle with respect to the loader plate.
 - (13) The link body may include a stopper protruding toward an outside of the air flap from a surface coupled to the loader to come into contact with the loader.
 - (14) The stopper may include a first inclined surface disposed below the link body in a lengthwise direction.
 - (15) The loader may include a loader shaft that connects the loader plate and the driving unit, is rotated by the driving unit, and rotates the loader plate.
 - (16) The loader plate may include a second inclined surface configured to be in contact with the first inclined surface of the link body when the loader plate is rotated, and when the second inclined surface is in contact with the first inclined surface, the first inclined surface and the second inclined surface may be arranged in parallel.
 - (17) The frame may include a guide groove configured to guide a movement direction of the link that moves interlocking to movement of the loader, and the guide groove includes a curved portion that guides movement of the link body when the air flap is rotated and a straight portion that guides the movement of the link body after the rotation of the air flap is finished.
 - (18) The straight portion may include a first area connected to the curved portion, and a second area spaced apart from the curved portion, and when the link body is moved from the first area to the second area, the first inclined surface and the second inclined surface may come into contact with each other.
-

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The above and other objects, features and advantages of the present disclosure will become more apparent to those of ordinary skill in the art by describing exemplary embodiments thereof in detail with reference to the accompanying drawings, in which:
- (2) FIG. 1 is a perspective view of an air flap apparatus for a vehicle according to an embodiment of the present disclosure;
- (3) FIG. 2 is an exploded perspective view of an air flap apparatus for a vehicle according to an embodiment of the present disclosure;
- (4) FIG. 3 is a view illustrating a coupled state of an air flap and a power transmission unit in a state in which the air flap is disposed at a first position;
- (5) FIG. 4 is a view illustrating the coupled state of the air flap and the power transmission unit in a state in which the air flap is disposed at a second position;
- (6) FIG. 5 is a cross-sectional view illustrating a first guide hole;
- (7) FIG. 6 is a cross-sectional view illustrating a second guide hole;
- (8) FIG. 7 is a view illustrating a state in which a second connection shaft of the air flap is disposed on an end of a curved portion of the second guide hole;
- (9) FIG. 8 is a view illustrating a state in which the second connection shaft of the air flap is disposed at a center of the curved portion of the second guide hole;
- (10) FIG. 9 is a view illustrating a state in which the second connection shaft of the air flap is disposed in a first area of a straight portion of the second guide hole;
- (11) FIG. 10 is a view illustrating a state in which the second connection shaft of the air flap is disposed in a second area of the straight portion of the second guide hole; and
- (12) FIG. 11 is a view illustrating a state in which a second link forms an obtuse angle with respect to a loader plate.

DETAILED DESCRIPTION OF EXEMPLARY EMBODIMENTS

(13) The present disclosure may be modified in various changes and may have various embodiments and is thus intended to describe specific embodiments with the accompanying drawings. However, it should be understood that the present disclosure is not limited to the specific embodiments and includes all changes, equivalents, and substitutions included in the spirit and scope of the present disclosure.

(14) Terms including ordinal numbers such as first and second may be used to describe various components, but the components are not limited by the terms. The terms are used only for the purpose of distinguishing one component from another component. For example, without departing from the scope of the present disclosure, a second component may be referred to as a first component, and similarly, the first component may be referred to as the second component. The term “and/or” includes any or a combination of a plurality of related listed items.

(15) It should be understood that, when it is referenced that a first component is “connected” or “coupled” to a second component, the first component may be directly connected or coupled to the second component, or a third component may be present between the first component and the second component. On the other hand, it should be understood that, when a first component is “directly connected” or “directly coupled” to a second component, a third component is not present therebetween.

(16) In the description of the embodiment, a case in which it is described that a first component is formed “on or under” a second component includes both a case in which the two components are in direct contact with each other and a case in which one or more other components are arranged between the two components. Further, when the term “on or under” is expressed, the term “on or under” may include the meanings of a downward direction as well as an upward direction based on one component.

(17) Terms used in the present application are used only to describe the specific embodiments and are not intended to limit the present disclosure. Singular expressions include plural expressions unless clearly otherwise indicated in the context. It should be understood in the present application that terms such as “include” or “have” are intended to indicate that there are features, numbers, steps, operations, components, parts, or combinations thereof that are described in the specification and do not exclude in advance the possibility of the presence or addition of one or more other features, numbers, steps, operations, components, parts, or combinations thereof.

(18) Unless otherwise defined, all terms used herein including technical or scientific terms have the same meanings as those commonly understood by those skilled in the art to which the present disclosure belongs. It will be further understood that terms, such as those defined in commonly used dictionaries, should be interpreted as having a meaning that is consistent with their meaning in the context of the relevant art and will not be interpreted in an idealized or overly formal sense unless expressly so defined herein.

(19) Hereinafter, an air flap apparatus for a vehicle will be described in detail with reference to the accompanying drawings, the same or corresponding components are designated by the same reference numerals regardless of the reference numerals, and the duplicated description thereof will be omitted.

(20) FIG. 1 is a perspective view of an air flap apparatus for a vehicle according to an embodiment of the present disclosure, FIG. 2 is an exploded perspective view of an air flap apparatus for a vehicle according to an embodiment of the present disclosure, FIG. 3 is a view illustrating a coupled state of an air flap and a power transmission unit in a state in which the air flap is disposed at a first position, FIG. 4 is a view illustrating the coupled state of the air flap and the power transmission unit in a state in which the air flap is disposed at a second position, FIG. 5 is a cross-sectional view illustrating a first guide hole, FIG. 6 is a cross-sectional view illustrating a second guide hole, and FIG. 7 is a view illustrating a state in which a second connection shaft of the air flap is disposed on an end of a curved portion of the second guide hole.

(21) Referring to FIGS 1 to 7, an air flap apparatus 1 for a vehicle according to the embodiment of the present disclosure includes a frame 100 disposed behind a grill (not illustrated) of the vehicle, an air flap 200 that opens or closes an air inlet I formed in the frame 100, a power transmission unit 300 that is connected to the air flap 200 and rotates the air flap 200, and a driving unit 400 that is disposed outside the frame 100 and generates power. In the present embodiment, a forward direction may be a direction from a passenger room to an engine room of the vehicle, and a rearward direction may be a direction from the engine room to the passenger room of the vehicle.

(22) The frame 100 may be disposed in the engine room. The frame 100 may have a quadrangular frame shape, and the inside thereof may be provided with an empty so that the air flap 200 may be disposed therein. The frame 100 may include side parts 120, a top part 140, and a bottom part 160. The air inlet I through which air introduced through the grill of the vehicle is introduced may be formed inside the frame 100. The air inlet I formed by the frame 100 may be opened or closed by the air flap 200.

(23) The side parts 120 may be disposed between the top part 140 and the bottom part 160. The side parts 120 may each be provided as a unit in which a first side portion 120a and a second side portion 120b are combined and may be provided as a plurality of side parts 120. The plurality of side parts 120 may be spaced apart from each other in a direction from a driver's seat to a passenger's seat in the passenger room. The first side portion 120a may support the top part 140 and the bottom part 160, and the second side portion 120b may be provided as a separate component coupled to the first side portion 120a.

(24) The side part 120 may include a first guide hole 122, a second guide hole 124, and a support hole 126.

(25) The first guide hole 122 may guide a movement direction of a link 320. As illustrated in FIG. 5, the first guide hole 122 may be formed in a directional area of the first side portion 120a and the second side portion 120b toward the air inlet I.

(26) The first guide hole 122 may form an area in which a first connection shaft 262 of the air flap 200, which will be described below, may move and may be disposed in a direction from the second side portion 120b toward the first side portion 120a. The first guide hole 122 may be formed in the second side portion 120b, and when the second side portion 120b is coupled to the first side portion 120a, one open side of the first guide hole 122 may be closed.

(27) The second guide hole 124 may guide a movement direction of a link 320, which will be described below and moves in conjunction with movement of a loader 340. The second guide hole 124 may be disposed above the first guide hole 122. The second guide hole 124 may include a curved portion 124a and a straight portion 124b.

(28) The curved portion 124a may be disposed at a position at which one area overlaps the first guide hole 122 in a direction from the second guide hole 124 toward the first guide hole 122. The curved portion 124a may guide the movement of the first connection shaft 262 of the air flap 200, which will be described below. Further, when the air flap 200 is rotated, the curved portion 124a may guide movement of a link body 322 which will be described below and is moved along the first connection shaft 262.

(29) The straight portion 124b may have a shape extending from one end of the curved portion 124a. The straight portion 124b may be disposed parallel to a first guide groove. The straight portion 124b may guide the movement of the link body 322 after the rotation of the air flap 200 is finished. The straight portion 124b may include a first area 124b1 and a second area 124b2.

(30) The first area 124b1 may be an area connected to the curved portion 124a. The first area 124b1 may allow the first connection shaft 262 of the air flap 200 to move linearly, the first connection shaft 262 being guided by the curved portion 124a to form a curved line.

(31) The second area 124b2 may be an area spaced apart from the curved portion 124a and may be an area connected to the first area 124b1. The second area 124b2 may guide a movement direction of the first connection shaft 262 of the air flap 200 reaching the first area 124b1. The second area

124b2 may be disposed on an outer side of the first guide hole **122**. The second side portion **120b** is coupled to the first side portion **120a**, one open side of the second area **124b2** may be closed.

(32) The support hole **126** may be formed at a coupling portion at which the first side portion **120a** and the second side portion **120b** meet each other. In more detail, a first groove formed in the first side portion **120a** and a second groove formed in the second side portion **120b** meet each other to form the circular support hole **126**. The support hole **126** may support a loader shaft **344** of the power transmission unit **300**, which will be described below.

(33) The top part **140** and the bottom part **160** may be arranged on ends of the side part **120**. The top part **140** and the bottom part **160** may be supported by the side part **120**.

(34) The air flap **200** may be disposed inside the frame **100**. In more detail, the air flap **200** may be disposed at a position at which the air inlet I formed inside the frame **100** may be opened or closed. The air flap **200** may rotate inside an air inlet. The air flap **200** may include an opening and closing part **220**, a third side part **240**, and a rotation part **260**.

(35) The opening and closing part **220** may be a rectangular plate. The opening and closing part **220** may open or close the air inlet. The opening and closing part **220** may be disposed in a direction in which the plurality of side parts **120** of the frame **100** are arranged.

(36) The third side part **240** may be disposed behind the opening and closing part **220**. The third side part **240** may support the opening and closing part **220**. The third side part **240** may be disposed behind the top part **140** and the bottom part **160**, and one side and the other side of the third side part **240** may be covered by the side part **120**. The third side part **240** may be rotated by the rotation part **260**.

(37) The rotation part **260** may be formed integrally with the third side part **240**. The rotation part **260** may be disposed in a direction from the third side part **240** to the outside of the third side part **240**. The rotation part **260** may be connected to the power transmission unit **300** and rotate the opening and closing part **220** and the third side part **240** by the power transmission unit **300**. The rotation part **260** may include a first connection shaft **262**, a support body **264**, and a second connection shaft **266**.

(38) The first connection shaft **262** may have a shape protruding from the third side part **240** toward the side part **120** of the frame **100**. The first connection shaft **262** may be formed by combining a semi-cylindrical protrusion and a cylindrical protrusion. The first connection shaft **262** may support the support body **264**. The first connection shaft **262** may be movably disposed in the first guide hole **122** of the side part **120** of the frame **100**. The first connection shaft **262** may be disposed on one end of the support body **264**. That is, the first connection shaft **262** may connect the third side part **240** and the support body **264**.

(39) The support body **264** may be disposed on one end of the first connection shaft **262**. The support body **264** may be a rectangular plate having a circular end. The support body **264** may support the second connection shaft **266**. The support body **264** may be disposed between the third side part **240** of the air flap **200** and the link body **322** of the power transmission unit **300**, which will be described below.

(40) The second connection shaft **266** may be disposed at the other end of the support body **264**. The second connection shaft **266** may have a shape protruding from the support body **264** toward the side part **120** of the frame **100**. The second connection shaft **266** may be provided in a cylindrical shape. The second connection shaft **266** may support the link body **322**, which will be described below. The second connection shaft **266** may be movably disposed in the second guide hole **124** of the side part **120** of the frame **100** while supporting the link body **322**.

(41) As illustrated in FIGS. 3 and 4, the air flap **200** may be disposed at each of a first position P1 and a second position P2 by the power transmission unit **300** moving through the driving unit **400**. The air flap **200** disposed at the first position P1 may open the air inlet I illustrated in FIG. 2, and the air flap **200** disposed at the second position P2 may close the air inlet I illustrated in FIG. 2.

(42) The power transmission unit **300** may help open or close the air inlet I of the air flap **200** while

being rotated by the driving unit **400**. The power transmission unit **300** may include the link **320** and the loader **340**.

(43) The link **320** may be connected to the air flap **200** to rotate the air flap **200**. The link **320** may move in conjunction of the movement of the loader **340** rotated by the driving unit **400**. The link **320** may include the link body **322**, a first coupling hole **324**, a locking portion **326**, and a stopper **328**.

(44) The link body **322** may be a rectangular plate having ends with rounded corners. The link body **322** may be disposed between the support body **264** of the air flap **200** and a loader plate **342** of the loader **340**, which will be described below.

(45) The first coupling hole **324** may be disposed at one end of the link body **322**. The first coupling hole **324** may support the second connection shaft **266** of the air flap **200**. When the second connection shaft **266** passes through the first coupling hole **324**, the link body **322** may be coupled to the first connection shaft **262**. The link body **322** may move in conjunction with movement of the second connection shaft **266** passing through the first coupling hole **324**. In more detail, the link body **322** may be rotated or moved forward or rearward by the second connection shaft **266** moving along the curved portion **124a** of the second guide hole **124**. Further, the link body **322** may be moved in a direction from the frame **100** toward the grill (not illustrated) of the vehicle or a direction opposite thereto by the second connection shaft **266** moving along the straight portion **124b** of the second guide hole **124**.

(46) The locking portion **326** may be disposed on the other end of the link body **322**. The locking portion **326** may protrude in the same direction as a direction in which the second connection shaft **266** of the air flap **200** protrudes. The locking portion **326** may pass through a second coupling hole **342a** of the loader **340**, which will be described below, to prevent separation of the link body **322** or the loader plate **342**, which will be described below.

(47) The stopper **328** may protrude from a surface coupled to the loader **340** toward the outside of the air flap **200**. The stopper **328** may be disposed between the first coupling hole **324** and the locking portion **326**. The stopper **328** may be in contact with the loader **340**.

(48) The stopper **328** may include a first inclined surface **328a**. The first inclined surface **328a** may be disposed below the stopper **328** in a lengthwise direction of the link body **322**. When the link **320** rotates along the air flap **200**, the first inclined surface **328a** may come into contact with the loader **340** to stop the rotation of the link **320**.

(49) The loader **340** may be connected to the driving unit **400**. The loader **340** may be rotated by power generated by the driving unit **400** and stop the movement of the link **320** when the air flap **200** closes the air inlet I. The loader **340** may include the loader plate **342** and the loader shaft **344**.

(50) The loader plate **342** may be disposed outside the link body **322**. Further, the loader plate **342** may be disposed in an inner space formed by coupling the first side portion **120a** and the second side portion **120b** of the frame **100**. The loader plate **342** may be provided as a plurality of loader plates **342**, and the plurality of loader plates **342** may be arranged in the plurality of side parts **120** that support the top part **140** and the bottom part **160** of the frame **100**. When the loader shaft **344** is rotated, the loader plate **342** may be rotated in the same direction as a direction in which the loader shaft **344** is rotated. The loader plate **342** may include the second coupling hole **342a** and a second inclined surface **342b**.

(51) The second coupling hole **342a** may be disposed at one end of the loader plate **342**. When the loader plate **342** is coupled to the link body **322**, the second coupling hole **342a** may be disposed at a position at which the locking portion **326** of the link **320** may be accommodated. The locking portion **326** may pass through the second coupling hole **342a**. The second coupling hole **342a** may have a shape corresponding to an outer shape of the locking portion **326**. When the loader plate **342** is rotated by the loader shaft **344** after the second connection shaft **266** passes through the second coupling hole **342a**, the locking portion **326** is misaligned with the second coupling hole **342a**, and thus the loader plate **342** may be fixed to the link body **322**.

(52) The second inclined surface **342b** may be formed at an end of the loader plate **342**. The second inclined surface **342b** may be in contact with the first inclined surface **328a** of the link body **322**. In more detail, when the loader plate **342** is rotated, the second inclined surface **342b** may come into contact with the first inclined surface **328a** to press the first inclined surface **328a**.

(53) When the second inclined surface **342b** is in contact with the first inclined surface **328a**, the first inclined surface **328a** and the second inclined surface **342b** may be arranged in parallel. Thus, since the second inclined surface **342b** uniformly presses the entire area of the first inclined surface **328a**, an operation in which the loader plate **342** stops the movement of the link **320** may be smoothly performed.

(54) The loader shaft **344** may connect the loader plates **342** arranged at the plurality of side parts **120** of the frame **100**. The loader shaft **344** may have a shape protruding from an inside of each loader plate **342** to the outside of a surface of the loader plate **342** facing the frame **100**. An end of the loader shaft **344** may be connected to the driving unit **400**. The loader shaft **344** may connect the loader plate **342** and the driving unit **400**. The loader shaft **344** may be rotated by the driving unit **400** to rotate the loader plate **342**. The loader shaft **344** may be formed integrally with the loader plate **342**, but the present disclosure is not limited thereto. The loader shaft **344** may be provided as a component separate from the loader plate **342**. An end of the loader shaft **344** may pass through the support hole **126** formed in the frame **100** and protrude outward from the frame **100**.

(55) The driving unit **400** may be coupled to the frame **100**. The driving unit **400** may be coupled to the end of the loader shaft **344** passing through the support hole **126** of the frame **100** while disposed outside the frame **100**. The driving unit **400** may generate power to rotate the loader shaft **344**. The driving unit **400** may include an actuator.

(56) Hereinafter, a process in which the air flap **200** is disposed from the first position **P1** to the second position **P2** and a structure in which the power transmission unit **300** supports the air flap **200** disposed at the second position **P2** will be described.

(57) FIG. **8** is a view illustrating a state in which the second connection shaft of the air flap is disposed at a center of the curved portion of the second guide hole, and FIG. **9** is a view illustrating a state in which the second connection shaft of the air flap is disposed in a first area of a straight portion of the second guide hole, and FIG. **10** is a view illustrating a state in which the second connection shaft of the air flap is disposed in a second area of the straight portion of the second guide hole.

(58) Referring to FIGS. **1** to **7**, the air flap **200** disposed at the first position **P1** opens the air inlet **I** illustrated in FIG. **2**. In this state, as illustrated in FIG. **7**, the first connection shaft **262** of the air flap **200** is disposed at a right end of the first guide hole **122** of the frame **100**, and the second connection shaft **266** is disposed at a right end of the curved portion **124a** of the second guide hole **124**. Further, the loader plate **342** is disposed at a position at which an angle close to a right angle with respect to the link body **322** is formed and is disposed at a position at which an angle close to parallel with the link body **322** is formed.

(59) Referring to FIGS. **1** to **8**, when the driving unit **400** is operated to generate power, the loader shaft **344** connected to the driving unit **400** may be rotated. In more detail, the loader shaft **344** may be rotated counterclockwise with respect to FIGS. **7** and **8**.

(60) In this case, the air flap **200** disposed at the first position **P1** may be rotated toward the second position **P2** by the power transmission unit **300**. In more detail, when the loader shaft **344** is rotated, the link body **322** may be rotated together with the loader plate **342** through the locking portion **326**. In this process, since the first connection shaft **262** of the air flap **200** serves as a rotation center between a fixed shaft and the air flap **200**, the air flap **200** may be rotated about the first connection shaft **262**.

(61) Since the air flap **200** is rotated about the first connection shaft **262**, the link body **322** connected to the second connection shaft **266** of the air flap **200** may be moved inside the curved

portion **124a** of the second guide hole **124** along the second connection shaft **266** rotated about the first connection shaft **262** of the air flap **200**. In this state, the air flap **200** is disposed between the first position **P1** and the second position **P2**.

(62) Referring to FIGS. **1** to **9**, when the driving unit **400** continuously generates power in the state of FIG. **8**, the loader shaft **344** connected to the driving unit **400** may be continuously rotated counterclockwise with respect to FIGS. **7** to **9**.

(63) In this case, the air flap **200** may be disposed at the second position **P2** in conjunction of the movement of the power transmission unit **300**. In more detail, when the loader shaft **344** is further rotated in the state of FIG. **8**, the loader plate **342** may rotate the link body **322** while being rotated together with the loader shaft **344**. The link body **322** may be rotated about the first connection shaft **262** of the air flap **200**.

(64) While the link body **322** is rotated, the second connection shaft **266** of the air flap **200** connected to the link body **322** may be moved from a central area of the curved portion **124a** of the second guide hole **124** to the first area **124b1** of the straight portion **124b**. Accordingly, the loader plate **342** connected to the link body **322** may be disposed parallel to the frame **100** in a height direction.

(65) Referring to FIGS. **1** to **10**, when the driving unit **400** continuously generates power in the state of FIG. **9**, the loader shaft **344** connected to the driving unit **400** may be continuously rotated counterclockwise with respect to FIGS. **7** to **9**.

(66) Accordingly, the loader plate **342** is rotated together with the loader shaft **344** so that the second inclined surface **342b** of the loader plate **342** may come into contact with the first inclined surface **328a** of the link body **322**. Since the second inclined surface **342b** presses the first inclined surface **328a** while the second inclined surface **342b** comes into contact with the first inclined surface **328a**, the link body **322** may be rotated in a reverse direction opposite to the direction in which the link body **322** is rotated in a process from FIG. **7** to FIG. **9**.

(67) In this state, since the loader plate **342** is continuously rotated together with the loader shaft **344**, the second inclined surface **342b** continuously presses the first inclined surface **328a**, and the second connection shaft **266** of the air flap **200** connected to the link body **322** may be moved from the first area **124b1** to the second area **124b2** of the straight portion **124b** of the second guide hole **124** of the frame **100**. Accordingly, the link body **322** may be disposed parallel to the loader plate **342**. Further, the first connection shaft **262** of the air flap **200** may be moved from a right end to a left end with respect to FIG. **10**. Thus, the support body **264** of the air flap **200** may be disposed parallel to the link body **322** of the power transmission unit **300**.

(68) When the link body **322** is disposed parallel to the loader plate **342** by the first inclined surface **328a** and the second inclined surface **342b** in contact with each other, the first connection shaft **262** is disposed at a left end of the first guide hole **122**, and the second connection shaft **266** is disposed in the second area **124b2** of the straight portion **124b** of the second guide hole **124**, the rotation of the air flap **200** can be prevented. Thus, even when air outside the vehicle passes through the grill and collides with the air flap **200**, a state in which the air flap **200** closes the air inlet **I** is stably maintained, and thus unnecessary inflow of the air into an engine of the vehicle can be prevented.

(69) In this way, in the air flap apparatus **1** for a vehicle according to the embodiment of the present disclosure, the first inclined surface **328a** and the second inclined surface **342b** are in contact with each other, the link body **322** is disposed parallel to the loader plate **342**, and thus closing stability of the air inlet **I** of the air flap **200** can be improved. Thus, excessive output of the driving unit **400** for preventing the rotation of the air flap **200** is prevented, and thus a lifetime of the driving unit can be maintained.

(70) FIG. **11** is a view illustrating a state in which a second link forms an obtuse angle with respect to a loader plate.

(71) Referring to FIG. **11**, the stopper **328** of the power transmission unit **300** may be disposed at a position at which the link body **322** may form an obtuse angle with respect to the loader plate **342**

inside the link body 322.

(72) In more detail, when the second inclined surface 342b continuously presses the first inclined surface 328a in a state in which the second inclined surface 342b of the loader plate 342 is in contact with the first inclined surface 328a of the stopper 328, as illustrated in FIG. 11, as the link body 322 and the loader plate 342 are rotated in directions opposite to each other, the link body 322 may form an obtuse angle with respect to the loader plate 342. In this way, even in a state in which the link body 322 and the loader plate 342 form an obtuse angle with respect to each other, the rotation of the air flap 200 can be prevented through the first inclined surface 328a and the second inclined surface 342b in contact with each other.

(73) In the air flap apparatus 1 for a vehicle according to the present disclosure, an arrangement state of the link body 322 and the loader plate 342 can change according to a position at which the stopper 328 is disposed in the link body 322, and even in various arrangement states of the link body 322 and the loader plate 342, the rotation of the air flap 200 can be prevented through the first inclined surface 328a and the second inclined surface 342b in contact with each other.

(74) According to an embodiment of the present disclosure, in a state in which an air flap closes an air inlet, a stopper and a loader push the air flap in a direction opposite to a direction in which a traveling wind is introduced. Accordingly, it is possible to prevent a phenomenon in which the air flap rotates even when the traveling wind comes into contact with the air flap.

(75) Although embodiments of the present disclosure have been described above, those skilled in the art may understand that the present disclosure may be variously modified and changed without departing from the spirit and scope of the present disclosure described in the appended claims. Further, differences related to these changes and modifications should be construed as being included in the scope of the present disclosure defined in the appended claims.

Claims

1. An air flap apparatus for a vehicle, comprising: a frame disposed behind a grill of a vehicle; an air flap configured to open or close an air inlet formed in the frame; an actuator disposed outside the frame and configured to provide rotational power; a link and a loader connected to the air flap and configured to rotate the air flap, the loader rotated by the rotational power provided by the actuator, and configured to stop movement of the link when the air flap closes the air inlet, wherein the link includes a link body that is connected to the air flap and the loader and allows reverse rotation by the loader, the loader includes a loader plate connected to the link body, the air flap is rotatably configured to be disposed at a first position at which the air inlet is open and a second position at which the air inlet is closed, and when the air flap is disposed at the second position, the link body is disposed parallel to the loader plate.
2. The air flap apparatus of claim 1, wherein, when the air flap is disposed at the second position, the link body is disposed to form an obtuse angle with respect to the loader plate.
3. The air flap apparatus of claim 1, wherein the link body includes a stopper protruding toward an outside of the air flap from a surface coupled to the loader to come into contact with the loader.
4. The air flap apparatus of claim 3, wherein the stopper includes a first inclined surface disposed below the link body in a lengthwise direction.
5. The air flap apparatus of claim 1, wherein the loader includes a loader shaft connecting the loader plate and the the actuator, rotated by the actuator, and configured to rotate the loader plate.
6. The air flap apparatus of claim 4, wherein the loader plate includes a second inclined surface configured to be in contact with the first inclined surface of the link body when the loader plate is rotated, and when the second inclined surface is in contact with the first inclined surface, the first inclined surface and the second inclined surface are arranged in parallel.
7. The air flap apparatus of claim 6, wherein the frame includes a guide groove configured to guide a movement direction of the link body that moves interlocking to movement of the loader, and the

guide groove includes: a curved portion configured to guide movement of the link body when the air flap is rotated; and a straight portion configured to guide the movement of the link body after the rotation of the air flap is finished.

8. The air flap apparatus of claim 7, wherein the straight portion includes: a first area connected to the curved portion; and a second area spaced apart from the curved portion, and when the link body is moved from the first area to the second area, the first inclined surface and the second inclined surface come into contact with each other.
