

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent Application Publication

20250258690

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

Bruno; John et al.

---

### HUB FOR MICRO FRONT-END SERVICES

---

#### Abstract

An example hub and registry module can be programmed to authenticate a user device attempting to access a contextual interface; access data to generate the contextual interface, the data being associated with the user device; determine operational information and personal information associated with the user device; combine the operational information and the personal information to generate contextual information associated with the user device; select one or more micro front-ends from a hub of micro front-ends based on the contextual information for the contextual interface; and provide the contextual interface to the user device, wherein the contextual interface includes the one or more micro front-ends.

---

**Inventors:** Bruno; John (Scottsdale, AZ), Falese; Sean Edward (Jenkintown, PA), Versini; Arnaud (Charlotte, NC)

**Applicant:** Wells Fargo Bank, N.A. (San Francisco, CA)

**Family ID:** 93744717

**Appl. No.:** 19/196846

**Filed:** May 02, 2025

#### Related U.S. Application Data

parent US continuation 18333222 20230612 parent-grant-document US 12321761 child US 19196846

---

#### Publication Classification

**Int. Cl.:** G06F9/451 (20180101); G06F16/957 (20190101); G06F16/958 (20190101)

**U.S. Cl.:**

## Background/Summary

### BACKGROUND

[0001] Users access many different types of sites to interact with businesses. These sites are programmed to provide information and desired functionality to the users. However, these sites can be difficult to create, particularly when different users have different needs and priorities. This can result in sites that may not be optimized for all users.

### SUMMARY

[0002] Embodiments are directed to a system including at least one processor and non-transitory computer-readable storage storing instructions that, when executed by the at least one processor, cause the system to generate a hub and registry module programmed to: determine a plurality of micro front-ends are conformant with one or more experience rules; register one or more of the plurality of micro front-ends in response to determining each of the one or more micro front-ends are conformant with the one or more experience rules; compose one or more micro front-ends into an experience for a user; and monitor performance of the one or more micro front-ends within the experience.

[0003] According to aspects of the present disclosure, the hub and registry module is further programmed to: determine a new version of a micro front-end of the plurality of micro front-ends is conformant with the one or more experience rules; store the new version of the micro front-end; replace a prior version of the micro front-end in the experience with the new version of the micro front-end; determine a change in the experience results in the new version of the micro front-end being incompatible with the experience; and revert the new version of the micro front-end to the prior version of the micro front-end.

[0004] According to other aspects of the present disclosure, the one or more experience rules are defined using a domain specific language. In some aspects, the domain specific language is JavaScript Object Notation.

[0005] According to aspects of the present disclosure, the hub and registry module is further programmed to generate a user interface on a display. According to other aspects of the present disclosure, the user interface includes, for a given micro front-end, one or more of a current version, a version history, a deployment status, an availability status, and a conformance status. According to further aspects of the present disclosure, the conformance status indicates one of a conformant status or a nonconformant status. According to other further aspects of the present disclosure, the conformance status comprises depicting a location on a scale from a conformant status to a nonconformant status. According to yet other further aspects of the present disclosure, the conformance status comprises a report summarizing conformance and nonconformance with each of the one or more experience rules.

[0006] According to other aspects of the present disclosure, the user interface comprises a dependency graph.

[0007] Other embodiments are directed to a method for managing a contextual micro front-end experience, the method includes receiving a micro front-end; determining the micro front-end conforms with one or more experience rules; registering the micro front-end; storing the micro front-end; deploying the micro front-end in response to a request to compose a contextual user experience; and monitoring performance of the micro front-end within the contextual user experience.

[0008] According to aspects of the present disclosure, the method further includes determining a new version of a micro front-end of the plurality of micro front-ends is conformant with the one or

more experience rules. According to further aspects of the present disclosure, the method further includes storing the new version of the micro front-end. According to still further aspects of the present disclosure, the method further includes replacing a prior version of the micro front-end with the new version of the micro front-end. According to yet further aspects of the present disclosure, the method further includes maintaining a prior version of the micro front-end along with the new version of the micro front-end. According to other further aspects of the present disclosure, the method further includes replacing a prior version of the micro front-end in the experience with the new version of the micro front-end.

[0009] According to other aspects of the present disclosure, the method further includes making a determination the new version of the micro front-end is incompatible with the experience.

According to further aspects of the present disclosure, the method further includes generating a report summarizing the determination the new version of the micro front-end is incompatible with the experience. According to still further aspects of the present disclosure, the method further includes determining a change in the experience results in the new version of the micro front-end being incompatible with the experience. According to yet further aspects of the present disclosure, the method further includes reverting the new version of the micro front-end to the prior version of the micro front-end.

[0010] The details of one or more techniques are set forth in the accompanying drawings and the description below. Other features, objects, and advantages of these techniques will be apparent from the description, drawings, and claims.

---

## Description

### DESCRIPTION OF THE DRAWINGS

[0011] FIG. 1 shows an example system programmed to generate contextual interfaces from a micro front-end hub using micro front-end components.

[0012] FIG. 2 shows example logical components of an example server device of the system of FIG. 1.

[0013] FIG. 3 shows an example method for generating a contextual interface for a user from the micro front-end hub of FIG. 1.

[0014] FIG. 4 shows an example method for registration and deployment of a micro front-end from the micro front-end hub of FIG. 1.

[0015] FIG. 5 shows an example user interface depicting conformance checks performed by the micro front-end hub of FIG. 1.

[0016] FIG. 6 shows an example user interface for performing administrative operations within the micro front-end hub of FIG. 1.

[0017] FIG. 7 shows an example user interface depicting a dependency graph for a micro front-end within the micro front-end hub of FIG. 1.

[0018] FIG. 8 shows an example user interface depicting an overview of micro front-ends stored in the micro front-end hub of FIG. 1.

[0019] FIG. 9 shows an example user interface depicting a report of a report on a micro front-end as generated by the micro front-end hub of FIG. 1.

[0020] FIG. 10 shows example components of the server of FIG. 2.

### DETAILED DESCRIPTION

[0021] Embodiments are directed to producing a contextual micro front-end experience. In particular, embodiments of the present disclosure relate to a hub (sometimes referred to as a control center) for maintaining and deploying micro front-ends into a contextual experience. In some contexts, the hub may be referred to as a marketplace.

[0022] Enterprises with legacy monolithic applications can benefit from an approach that easily

allows them to develop and publish related “micro front-ends”. Technology teams across the enterprise can develop reusable “micro front-end” components for other teams to consume in building their modern applications. Each team would develop in an efficient agile manner while reducing dependencies and risk to delivering value to customers.

[0023] In examples provided herein, applications with contextual interfaces can be composed of conforming micro front-end components that are available on a hub. Tools may be leveraged to help generate conforming micro front-ends for efficient development and consistency in desired behavior. In some examples, the hub provides both storage and conformance guiderails for the micro front-ends. The hub may be responsively integrated with contextual features and automatically adjust types, features, and version of deployed micro front-ends.

[0024] Examples provided herein relate to simplifying the development of web and mobile user experiences. The examples can standardize user experience layers and Application Programming Interface (API) integrations to provide personalized contextual interfaces for a user. The principles of the present disclosure may be implemented across various known and future experiences, including existing operating systems and applications with embedded micro front-ends. In some examples, these contextual interfaces can be composed of smaller micro front-end components that behave and can be released independently while conforming to specified control structures and standards. In some examples, conforming micro front-end components can be offered on a hub for consumption. Micro front-end components can appear on a user interface in a variety of forms depending on the desired contextual interface. The appearance of one or more deployed micro front-ends may be automatically adjusted by the hub or manually manipulated from a user interface.

[0025] In some examples, data known about users is leveraged to further enhance the personalized nature of the contextual interfaces. This can include composition of an aggregate digital interface through an easily consumable hub organized by common attributes and enabled for personalization. The hub may be responsively integrated with contextual features and deploy one or more micro front-ends to be accessible to a user based on particular contextual features.

[0026] In some examples, the contextual interfaces are provided in the financial services industry, although the interfaces can be equally applicable in other contexts.

[0027] Additional details regarding an example system including such micro front-ends are provided in U.S. patent application Ser. No. 17/663,572 filed on May 16, 2022, the entirety of which is hereby incorporated by reference.

[0028] In some embodiments, the hub includes registry capabilities. In example, the hub provides conformance criteria ensuring stored and/or registered micro front-ends comply with appropriate requirements. Ensuring conformance among registered micro front-ends may ensure coordination among various micro front-ends from multiple authors while providing a seamless contextual experience for a user.

[0029] The hub may actively engage with the user's contextual experience during runtime of the contextual experience. In examples, the hub engages to monitor and manage the ecosystem of micro front-ends deployed for a particular user. Coordination and monitoring of deployed micro front-ends by a centralized hub provides a more agile system and supports democratization of micro front-end development. Complexities of coordination are overcome by the hub enforcing conformance criteria on the micro front-ends.

[0030] In embodiments, the hub provides an active control center to monitor and adjust micro front-end deployment. For example, redundancies are distilled by providing a centralized control center to maintain the registry of micro front-ends and coordinate their deployment so that the storage or registry does not become cluttered with multiple redundant micro front-ends.

[0031] In some examples, the hub may operate using a domain specific language to define a set of rules. The domain specific language and/or the rules may be configured to ensure that only micro front-ends meeting conformance requirements can be registered and/or deployed by the hub.

[0032] In some examples, the hub may operate using a domain specific language and associated meta data to define a set of rules. In some embodiments, the domain specific language describes the micro front-end to the ecosystem such that the micro front-end can be accepted by the hub and integrated within experiences.

[0033] For instance, the domain specific language can provide the framework that is used to define how to render the micro front-end. Metadata can also be associated with the micro front-end to define how the micro front-end is configured to interface with the framework. Conformance of the micro front-end is derived from the metadata associated with the micro front-end's runtime characteristics. The metadata can be used to ensure that only micro front-ends meeting conformance requirements can be registered and/or deployed by the hub.

[0034] In some examples, the hub provides a user interface enabling visualization and control of micro front-ends present in the register or storage. Micro front-ends may be presented in the user interface in a current or a target state, or a user may select which state to view.

[0035] The centralized hub, with conformance and deployment capabilities, provides for component integration. For example, application programming interfaces (APIs) may integrate or interface with the hub to distribute hosted micro front-ends across a plurality of applications. Micro front-ends registered and maintained by the hub can be consumed by a variety of different applications. This allows sharing of micro front-ends and their functionality across a multitude of applications. For example, a particular user may prefer a particular functionality to be a part of their user experience with all the applications they engage with, which can then be provided by a shared micro front-end via the hub and the contextual experience.

[0036] The hub provides coordination among micro front-ends which may be interdependent. For example, the hub may ensure micro front-ends which rely on one another to operate are deployed together. In some examples, the hub monitors operation and interaction among registered and deployed micro front-ends.

[0037] The hub may provide centralized control of deployment and versioning of registered micro front-ends. For example, the hub may recall or otherwise deactivate version of micro front-ends which are no longer supported. The hub may revert a micro front-end to an earlier version if an issue emerges with a current or newer version.

[0038] The examples provided herein provide a practical application of the described technologies. Micro front-ends provide variety within the front-end of a user experience to allow for customization and contextualization of the experience for each user. However, the selection, deployment, and coordination of the various micro front-ends within a system raise issues of maintenance and coordination that may call for additional infrastructure within the system to solve.

[0039] Deployment and integration of micro front-ends is improved and, in some cases, may be optimized by the hub described herein. By providing a centralized base of experience for the user engaging in the micro front-ends, the micro front-ends can be maintained according to a common conformance criteria and relevant contextual information to allow for deployment uniformly from a common hub.

[0040] Integration of registry capabilities within the central hub aligns conformance, registry, storage, and deployment for coordinated system management and a seamless user experience for a plurality of users from a common base of experience. This allows up to the minute incremental delivery of an adaptive contextual experience to a user. In some examples, the adaptive contextual experience is generated by an artificial intelligence or machine learning system. Criteria considered by the system and reflected in the generated experience may include a micro front-end's or a user's role, a channel, a risk rating, user preferences, historical behavior by a user or a micro front-end, etc.

[0041] The centralized hub and its associated functions may eliminate downtime and support effective reuse of micro front-ends across a variety of experiences within the user's contextual experience, such as those related enterprise applications or externally embedded partner

experiences.

[0042] Incorporating a user interface with the hub makes available micro front-ends visible, and may include current and target states. In some embodiments, credentialed administrators also control and manage the micro front-end ecosystem from the hub user interface. For example, a credentialed administrator may downgrade, upgrade, or take out of service a particular version of micro front-end, may monitor usage of micro front-ends, restrict usage of one or more micro front-ends, update rules and metadata for micro front-ends, etc. In summary, the hub, and by extension the hub user interface, may function as a control center of the entire micro front-end ecosystem.

[0043] The hub may incorporate API's and other components to support integration and consumption of stored micro front-ends by a variety of applications. Many other advantages are possible.

[0044] FIG. 1 shows an example system **100** programmed to generate contextual interfaces from a micro front-end hub using micro front-end components.

[0045] The system **100** generally includes a client device **104** and a server device **108**. The components of the system **100** can include one or more computing devices, such as laptops, desktops, tablets, servers, server farms, etc. Each of the computing devices includes one or more storage media encoding instructions which, when executed by one or more processors, implement the functionality described herein.

[0046] Although multiple computing devices are shown in the system **100**, the functionality described herein can be implemented on one or many computing devices. In such examples, each of the computing devices communicate with the others through a network. The network can be any suitable data network, such as the internet, a wide area network, a local area network, a wired network, a wireless network, a cellular network, a satellite network, a near field communication network, or any operatively connected combination of these.

[0047] In the example shown, the client device **104** can include a plurality of devices that numbers in the hundreds or thousands. The client device **104** is programmed to provide a contextual interface for a user of the client device **104**.

[0048] The server device **108** can also include a plurality of devices, such as a server farm and/or cloud computing infrastructure. In this example, the example server device **108** includes a hub device **110** and a component authoring device **112**. Again, each of these devices can be implemented as a single device (e.g., all within the server device **108**) and/or as multiple discrete devices within the system **100**.

[0049] Generally, the example component authoring device **112** is programmed to create micro front-end components. The example hub device **110** is programmed to allow those micro front-end components to be registered and stored. The hub device **110** is also used to generate contextual interfaces at the client device **104** by orchestrating one or more micro front-ends to make up the contextual interface.

[0050] More specifically, the example hub device **110** is programmed to house a plurality of micro front-end components that can be used to generate a contextual interface for a user. In these examples, the micro front-end components can be combined and reused to generate the interfaces. In some examples, the hub device **110** defines conformance criteria that dictates various aspects of the micro front-end components that are allowed to be registered at the hub device **110**. The hub device **110** operates to provide a control center for maintenance and deployment of micro front-end components authored from the component authoring device **112** and implemented on the client device **104**.

[0051] The component authoring device **112** is programmed to facilitate the authoring of these micro front-end components. This can include providing tools that facilitate the development of the micro front-end components. The tools can assist in assuring that the micro front-end components meet the conformance criteria necessary for the micro front-end components to be registered by the hub device **110**. For example, in conjunction with the hub user interface associated with the hub

device **110**, discussed in more detail below in relation to FIGS. 5-7, micro front-ends failing to meet conformance criteria can be modified using tools associated with the component authoring device **112** to comply with the conformance criteria.

[0052] Each micro front-end authored using the component authoring device **112** can be received by the hub device **110** for registry, storage, and deployment. Each micro front-end may function as a stand alone component and, in some examples, may be viewed as self-contained mini-applications. The hub device **110** may store a registered collection of micro front-ends found to conform to a defined framework. The framework may be defined, for example, using a domain specific language and associated with the hub device **110**. The framework and/or domain specific language may be used to establish and enforce the conformance criteria. The micro front-ends stored in the hub device **110** may be hosted and, in some examples, published for consumption by user facing applications and other experiences. More details are provided below.

[0053] Referring now to FIG. 2, additional details about the server device **108** are shown. In this example, the server device **108** includes an authoring module **202**, a hub and registry module **204**, a context configuration module **206**, and a rendering module **208**. The hub and registry module **204** may include a monitoring module **210**, a conformance module **212**, and a deployment module **214**. Many other configurations are possible.

[0054] The example authoring module **202** is generally programmed to facilitate the creation of micro front-end components. As noted, the authoring module **202** can be accessible to developers, such as members of an organization associated with the system **100**. As described further below, the organization can, in one example, be a financial institution. Developers of the financial institution can access the authoring module **202** to create micro front-end components for use in creating contextual interfaces associated with the applications provided by the financial institution to users.

[0055] In some examples, the authoring module **202** can be interactive in nature, allowing for automatic and semi-automatic (e.g., with user input) micro front-end generation. For instance, the authoring module **202** can provide wizards and pre-programmed functionality that allow for easy, semi-automatic generation of new micro front-end components.

[0056] In some examples, the authoring module **202** is programmed to assure that the micro front-end components meet conformance criteria associated with the hub device **110**. Examples of such conformance criteria are described below.

[0057] Further, the authoring module **202** can be programmed to facilitate the reuse of resources as new micro front-end components are created. For instance, the authoring module **202** can be programmed to provide libraries of code that can be combined to provide desired functionality. Further, two or more existing micro front-end components can be combined in different manners to create a new micro front-end component with desired functionality. Many other configurations are possible. In some embodiments, authoring module **202** is further programmed to simplify micro front-end development and deployment by using APIs and/or database tables allowing for the automatic generation of, for example, an experience API or Graph Query Language endpoint.

[0058] The example hub and registry module **204** facilitates the registration of the micro front-end components with the hub device **110**. Hub and registry module **204** may include sub-components, such as monitoring module **210**, conformance module **212**, and deployment module **214**.

[0059] The monitoring module **210** monitors the conformance and state of stored, registered, and deployed micro front-ends. The monitoring module **210** tracks micro front-ends as they are moved and used throughout the system **100** and maintains an understanding of how the overall ecosystem of the system **100** and the user's contextual experience is behaving. Ecosystem behavior may include current activity and performance of micro front-ends deployed into an active user experience.

[0060] In some examples, the monitoring module **210** may calculate and provide analytics. Analytics may relate to a deployed micro front-ends, and characterize the performance of the micro

front-end within the application or other user experience. For example, a micro front-end's response time may be monitored and tracked. Performance of a micro front-end deployed in more than one application or experience may be tracked and compared across the different deployment locations. [0061] In embodiments, the monitoring module **210** may monitor an app or experience overall and evaluate the composite or collaborative performance of the one or more micro front-ends composing the experience.

[0062] Analytics may relate to a stored micro front-end that is not presently deployed and is passively presently in the hub.

[0063] In some examples, the monitoring module **210** provides a user interface. The user interface may display a “live” view of micro front-ends on the hub, such as registered micro front-ends presently available and/or a summary of micro front-end deployment. The user interface may display a dependency graph of relationships among micro front-ends, for example as a bubble graph. Data monitored by the monitoring module **210** and, in some embodiments, displayed on the user interface, may include the current version, the version history, deployment status, availability status, and conformance status.

[0064] In some examples, conformance status may include whether the micro front-end in conformant or nonconformant. In some examples, conformance status may indicate on a scale how close to conformance a micro front-end is and/or may include a conformance report summarizing conformance and nonconformance with individual rules. The conformance report may provide of summary of corrections required before conformance can be reached.

[0065] In some embodiments, the monitoring module **210** may interface with the authoring module **202** and monitor micro front-ends during building. The monitoring module **210** may promote communication between the authoring module **202** and the conformance module to support applying conformance criteria to micro front-ends during build time.

[0066] The monitoring module **210** may interface with the context configuration module **206** and the rendering module **208** to inform the building of the experience. For example, information on a micro front-end's performance or current status may implicate it's suitability for some experiences.

[0067] Conformance module **212** maintains and applies conformance criteria to micro front-ends received from authoring module **202** and stored in the hub. In one non-limiting example, the conformance module **212** of the hub and registry module **204** defines one or more API that allow new micro front-end components to be registered. In this example, the registration can be in the form of a domain specific language, such as a JavaScript Object Notation (JSON) contract, wherein the contract defines the conformance criteria required for each micro front-end component.

[0068] Contracts may establish, for example, that a micro front-end must implement a particular reload method, must generate a finished reloading event to other interested micro front-ends, must gather data, etc. A contract may establish a default placeholder user interface tile image, describe supported settings (e.g., a number of rows in a table a user can configure), etc. The language describing these and other contracts specific to the micro front-end ecosystem (domain) may be used to define metadata on the hub.

[0069] For instance, example conformance criteria can include one or more of technical, design, and/or performance attributes. Conformance can relate to how the micro front-end component will interact with standard capabilities defined for the system **100**. These can be broadly categorized into “control”, which is used to enforce the standard capabilities, and “data”, which defines the behavior of the micro front-end component.

[0070] The micro front-end components can “plug” into the “control” part. For example, to adequately personalize an experience for individual users we need to respect: a) user role entitlements (e.g., can they see the micro front-end, invoke feature, limits, etc.); b) user preferences; c) artificial intelligence-derived presentment of the micro front ends components based on a variety of factors; d) active experimentation underway; e) historical behavior by the micro front-end or a user; and so on.



[0071] Micro front-end components can implement methods to support these and other capabilities including to exchange and respond to state transitions, gather analytical data, adjust form factors and displays, activity targeting requests, participate in experiments, feedback, deep linking, tracing, and so on.

[0072] For instance, the technical attributes can include requirements on how the micro front-end components are created, such as using specific programming languages, and risk aspects, such as how the micro front-end components address confidential information (e.g., encryption requirements). The design attributes can include requirements on the “look and feel” of the interface generated by the micro front-end components, such as particular fonts, colors, and/or other design aspects. The performance attributes can provide certain metrics on how the micro front-end components perform, such as requiring, for example, a certain rendering and processing speeds. In further examples, associated system entitlements, such as for authorization, can define what can be done by a user, and settings define how micro front-ends can be configured, such as defining available selections by the user (e.g., table rows to show). Many other configurations are possible.

[0073] In some examples, the server device **108** allows for the definitions of user profiles. The user profiles can define particular attributes of the user that facilitate the creation of the micro front-end components. For instance, the profile of the user can define bibliographic information about the user (e.g., location, age, etc.), the user's role (e.g., job position and family environments), and the user's preferences.

[0074] In some embodiments, conformance rules may embody business rules and relate to business domains. For example, conformance rules relates to relationship or interdependency between data handled by multiple micro front-ends.

[0075] Conformance may be an automated determination based upon a defined set of rules which are integral with the hub and registry module **204**. In some embodiments, manual elements may be incorporated into the conformance determination. For example, a micro front-end may be updated to a new version, with the new version failing to satisfy the conformance criteria. User input may be prompted to revise the new version or approve a reversion to the prior version. In some embodiments, the conformance module **212** automatically reverts to the prior version and gives the user an opportunity to revise the new version. In some cases, a reversion to a prior version may be incompatible with other updates, such as system updates or updates to interdependent micro front-ends.

[0076] A micro front-end with no compatible version approved for registry may be automatically or manually disabled. In some examples, applications or experiences using the disabled micro front-end may also be disabled or reverted to a prior version of the micro front-end.

[0077] In embodiments, the conformance module **212** incorporates machine learning components. For example, the conformance module **212** may include a machine learning model and the conformance criteria may be defined by training the model to identify conforming and nonconforming micro front-ends. In embodiments, the machine learning model may be trained to predict imminent or otherwise potential future nonconformance, such as identifying that performance is slowing or may drop below conformance criteria.

[0078] In some examples, the model may be trained to output a report of conformance failures.

[0079] The conformance module **212** may generate a conformance report. The conformance report may indicate a status of conformant or nonconformant. The conformance report may indicate a location on a scale from conformant to nonconformant, indicating where on the scale a particular micro front-end falls in terms of conforming. The location may be determined, for example, as a percent calculation of the percent of conformance rules met. The conformance report may indicate a conformant or nonconformant status in relation to individual conformance rules. The conformance report may include a summary of corrections to be made to bring the micro front-end into conformance.

[0080] The deployment module **214** provides for distribution and coordination of micro front-ends within a user's contextual experience. Micro front-ends may be deployed from the hub and registry module **204** by the deployment module **214** into one or more user contextual experiences. Micro front-ends may be deployed singly or in groups of two or more. A particular micro front-end may be deployed to one or more applications or user experiences, with the deployment module **214** ensuring duplicate or redundant micro front-ends are not deployed to a same application or experience. Coordinated deployment of interdependent micro front-ends, such as one micro front-end that depends upon another micro front-end or two or more micro front-ends that each depend upon each other, may be managed by the deployment module **214**.

[0081] Once the micro front-end components are created using the authoring module **202** and registered by the hub and registry module **204**, the micro front-end components are ready to be used to create the contextual interfaces. When doing so, additional contextual information can be provided to the micro front-end components as the components are assembled for display to users.

[0082] The example context configuration module **206** is programmed to provide the additional contextual information to the micro front-end components as the components are assembled to be surfaced on a contextual interface. The contextual information is used to drive the selection of a set of micro front-ends that are composed to yield the user experience at that moment, along with data that is available to the selected set of micro front-ends. In some examples, the deployment module **214** generates a most relevant experience for the user based on the contextual information. Once the experience is generated by the deployment module **214**, the set of micro front-ends is deployed and rendered into the experience by the rendering module **208**, discussed in more detail below.

[0083] For example, a unified login micro front-end may be composed that is able to leverage contextual information such as a user-id, a user device, and a user location, each of which drives an entirely differentiated experience selecting from a variety of external or internal applications for the user using the same micro front-end.

[0084] Generally, the contextual information can include data associated with the user so that the micro front-end components are assembled in a more efficient manner. This contextual information can include, without limitation, operational information and personal information, as described further below.

[0085] For instance, the system **100** can also include a reusable information device **102** and a user information device **106** that provide additional contextual information for the system **100** as the contextual interface is generated for the user.

[0086] In this example, the reusable information device **102** is programmed to enhance efficiency in the development and deployment of the micro front-end components. More specifically, the reusable information device **102** can monitor the functionality of existing micro front-end components and suggest the reuse of those micro front-end components when new functionality is being developed.

[0087] For instance, in the example with the financial institution, each line of business can define certain aggregated experiences associated with the functionality provided for users. The reusable information device **102** can suggest existing micro front-end components from the hub device **110** which can provide some or all the desired functionalities.

[0088] For example, assume a line of business is developing a user experience associated with payment of a mortgage. A different line of business may have already developed one or more micro front-end components used for payment of an automobile loan. One or more of these micro front-end components could be identified by the reusable information device **102** and used to develop the user experience associated with payments for the mortgage. Many other examples exist.

[0089] One non-limiting example of defining functionality and development according to user interactions in order to enhance the efficiencies of developing and providing products and services is described in U.S. patent application Ser. No. 17/658,015 filed on Apr. 5, 2022, the entirety of which is hereby incorporated by reference.

[0090] The example user information device **106** is programmed to provide additional information that may be unique to the user. For instance, with the example involving the financial institution, the user information device **106** can access additional details about the user, such as user preferences and user financial information, such as financial products and account balances. This information can be provided from the user information device **106** to the context configuration module **206** when selecting the micro front-end components for the contextual interface, as described further below.

[0091] In addition to accessing information from the reusable information device **102** and the user information device **106**, the example context configuration module **206** can also be context-aware and use machine learning to further enhance the use of the micro front-end components to generate the contextual interfaces.

[0092] For instance, the context configuration module **206** can use machine learning to understand user context. This can include prior and/or current activity associated with the system **100**. For instance, a user context can be generated by the context configuration module **206** based upon what the user is currently doing. For instance, if the user is currently filling out a form on the system **100**, the context configuration module **206** can access information from the user information device **106** and present micro front-end components to facilitate entry on the form, such as being pre-filled with necessary information.

[0093] Further, the context configuration module **206** can use machine learning to understand user preferences and provide that context to the rendering module **208**. For instance, the context configuration module **206** can be programmed to learn about user, such as what the user wants to see, where, how, etc. For example, if the user continues to use certain functionality associated with certain micro front-end components and consistently cancels, hides, or otherwise removes other functionality, the context configuration module **206** can be programmed to use machine learning to understand those user preferences. The context configuration module **206** can provide information to the rendering module **208** to surface those micro front-end components that are more useful to the user and hide or otherwise suppress those that are not. Additional examples are provided below.

[0094] Further, the context configuration module **206** can determine preferences for the type of platforms used by the user. For instance, if the user prefers to access the system **100** via a mobile device, the context configuration module **206** can optimize the micro front-end components for mobile access. This can include changing functionality and user interface components to optimize access on a smaller screen and with different input types (e.g., touch).

[0095] In addition, the context configuration module **206** can be programmed to experiment to better understand preferences associated with individual users, groups of users, or an entire population of users. For instance, if a group of users, such as those over a certain age or having other common attributes, appears to struggle with functionality, the context configuration module **206** can be programmed to modify or suggest different micro front-end components with different functionality to address those shortcomings.

[0096] To accomplish this learning, the context configuration module **206** can experiment by suggesting different functionality and/or micro front-end components for different groups of users and determining which functionality and/or micro front-end components are preferred for particular users, groups of user, etc. Examples of such criteria for grouping of users includes: user role; preferences or likes; bibliographic commonality (e.g., age, gender, location, etc.), time of day, etc.

[0097] For instance, in one example, assume that a user accesses the system **100** every Friday afternoon to make a certain payment. Over time, the context configuration module **206** can use machine learning to identify such a trend. When the user accesses the system **100** on Friday afternoons, the context configuration module **206** can suggest the micro front-end components that facilitate the payment be surfaced by the rendering module **208** at a convenient location for the user so the user can efficiently make the payment. Many other configurations are possible.

[0098] One example of a system for providing a customized user experience is described in U.S.

patent application Ser. No. 18/174,054 filed on Feb. 24, 2023 and claiming the benefit of U.S. Provisional Application No. 63/268,935 filed on Mar. 7, 2022, the entirety of which is hereby incorporated by reference.

[0099] The example rendering module **208** is programmed to access one or more of the micro front-end components from the hub device **110** to generate the contextual interface for the user. The contextual information is used to drive the selection of a set of micro front-ends that are composed to yield the user experience at that moment, along with data that is available to the selected set of micro front-ends. In some examples, the deployment module **214** composes a set of micro front-ends to generate a most relevant experience for the user based on the contextual information and communicates the experience to the rendering module **208**. As noted, the rendering module **208** may also receive input directly from the context configuration module **206** when generating the contextual interface. Once the experience is generated, the set of micro front-ends is deployed and rendered into the experience by the rendering module **208**.

[0100] For instance, when a user accesses the system **100**, the context configuration module **206** and/or the rendering module **208** access the relevant micro front-end components from the hub and registry module **204**, and the rendering module **208** generates the contextual interface. This interface can then be displayed by a client device for the user, such as the client device **104**.

[0101] In some examples, the rendering module **208** is programmed to use the information from the context configuration module **206** so that the contextual interface is specific to the user or group of users. In this manner, the contextual interface can provide greater efficiencies in information and functionality for the user.

[0102] In some examples, the micro front-end components are used by the rendering module **208** to generate various aspects of the contextual interface. Examples of such aspects in the context of the financial institution example include one or more of: [0103] (1) header—navigation header functionality is made contextual using micro front-end components; [0104] (2) payments—functionality associated with wire payments is made contextual using micro front-end components; and [0105] (3) consolidated view of account balances—functionality associated with the display of accounts is made contextual using micro front-end components. [0106] This is a non-exhaustive list of the many aspects of the contextual interface that can be generated by the rendering module **208** using the micro front-end components.

[0107] In some examples, the rendering module **208** is programmed to change how the contextual interface is generated over time. For instance, the rendering module **208** can initially generate an interface that is standard across all users, groups of users, etc. Over time, the rendering module **208** can receive additional information about the user from the context configuration module **206**. Once sufficient context is developed, the rendering module **208** can be programmed to use the micro front-end components to generate the contextual interface for the user, thereby providing a customized, personalized interface. As noted herein, rendering by the rendering module **208** can be related to a variety of factors, and different users can get custom, personalized and contextual experiences based on those factors and their persona over time.

[0108] Further, as noted, the rendering module **208** can be programmed to experiment over time by generating different contextual interfaces for users to determine preferences, efficiencies, etc. This can assist the context configuration module **206** and the rendering module **208** in determining which contextual interface may be optimized for a particular user or group of users based upon machine learning.

[0109] Finally, the rendering module **208** can be programmed to make these changes automatically, such as by using machine learning. Further, the rendering module **208** can be programmed to allow the changes to be made manually by the user and/or developer. For instance, the system **100** can provide preferences that allow the user to select between a standard interface and the contextual interface, as desired. Many other configurations are possible.

[0110] Referring now to FIG. 3, an example method **300** for generating the contextual interface for

the user by the system **100** is shown. The example method **300** includes context configuration operations **302**, hub and registry operations **304**, and rendering operations **306**.

[0111] In this example, the user is authenticated at operation **310**. However, in other instances, the user need not be authenticated or otherwise known to generate the contextual interface.

[0112] Next, at operations **312** and **316**, relevant data needed to generate the contextual interface is accessed. As noted, this relevant data can include information known about the user. The data can also include machine learning associated with the user or group of users, such as user preferences, etc.

[0113] Next, at operations **318** and **320**, the information about the user is used to determine both the operational information and the personal information. As noted, these aspects are used to determine the context associated with the user so the contextual interface can be generated.

[0114] In this example, at operation **318**, such information as the user's computing environment, form factor for the user's computing device, application state on the computing device, and localization based upon location can be used as operational information. Likewise, information such as the user's segment or grouping, entitlements associated with the user's stature, role, and preferences can be used as personal information.

[0115] At operation **314**, the system **100** can use artificial intelligence to generate further information associated with the user. This information can relate to risks associated with the user, a profile generated for the user, and/or marketing information associated with the user, such as what products or services may be of most use to the user.

[0116] Next, at operation **324**, the operational and personal information and the information generating using artificial intelligence are combined to generate the contextual information associated with the user. As described further above, this contextual information is used to select the micro front-end components that are used to create the contextual interface for the user.

[0117] Next, at operation **330**, the relevant micro front-end components are selected from the hub.

[0118] At operation **332**, a determination is made by the system as to whether experimentation is being conducted. If so, control is passed to operation **336**, and experimental aspects of the micro front-end components can be selected. If not, control is instead passed to operation **334**, and standard version of the micro front-end components are selected. As noted, the experimentation can be used to determine preferences for the specific user and/or preferences for a group of users or globally for all users.

[0119] Finally, at operation **338**, the system **100** determines whether to provide the contextual interface to the user. If so, control is passed to operation **342**, and the contextual interface is rendered. If not, control is passed to operation **340**, and a standard interface is instead rendered. As noted, the decision whether to show the contextual interface can be automated, such as by the system **100** determining if enough contextual information is known for the user. Or, the decision can be manual, such as by allowing the user to decide whether to have the contextual or standard interface shown. Many configurations are possible.

[0120] Referring now to FIG. **4**, an example method **400** of registering and deploying micro front-ends in a contextual experience by the system **100** is shown.

[0121] At operation **402**, a micro front-end is received at the hub, such as hub and registry module **204** of FIG. **2**. The micro front-end may be a new micro front-end or a new version of an existing micro front-end. In some example, the micro front-end may be duplicative or redundant with a micro front-end already registered.

[0122] The micro front-end may be received from another component of the contextual experience system, such as an authoring module. In some instances, micro front-end development may be incorporated within the hub

[0123] At operation **404**, the received micro front-end is checked for conformity with experience rules. In some embodiments, experience rules are defined using a domain specific language associated with the hub. Experience rules may define features and function a micro front-end must

include to be registered and stored within the hub. For example, experience rules may be recorded as contracts written, using JSON notation, in a language specific to the micro front-end ecosystem. For example, the hub may incorporate domain specific language which requires a micro front-end to include the ability to accept a request to reload before the micro front-end is accepted and registered by the hub. Other non-limiting examples of experience rules which micro front-ends may be required to conform to include a requirement the micro front-end be able to indicate when loading is complete, a requirement the micro front-end be able to collect user data and, in some examples, a further requirement that the micro front-end does collect the user data, and a requirement the micro front-end respond within a certain amount of time to a request and, in some examples, a further requirement that different requests have different response time requirements. [0124] If the micro front-end is determined to not be in conformance, the micro front-end may be returned to development, such as at operation **402**. If the micro front-end is determined to be in conformance, the micro front-end is registered, as at operation **406**.

[0125] At operation **408**, the registered micro front-end is stored at or by the hub.

[0126] At operation **410**, the micro front-end may be deployed, such as by being composed into an application or other contextual user experience. If a micro front-end is not suited or selected for deployment in a particular application or experience, it may be returned or maintained in storage. If a micro front-end is selected for composition into an application or experience, the hub may continue to monitor the deployed micro front-end, as at operation **412**.

[0127] In some embodiments, the method **400** is iterative. At operation **414**, a determination is made whether to update the micro front-end. The update determination may be made periodically or in response to a state observed during monitoring the micro front-end, as at operation **412**.

[0128] If the determination is made, at operation **414**, to not update the micro front-end, monitoring of the micro front-end may resume, as at operation **412**.

[0129] If the determination is made, at operation **414**, to update the micro front-end, the update may be performed, as at operation **416**. Once the update is completed, the micro front-end's conformance may be confirmed, as at operation **404**. In some embodiments, conformance is built into the micro front-end through the iterative update process, by leveraging, for example, code generation, automated testing during builds, common software development kits, etc.

[0130] Referring now collectively to FIGS. 5-9, example user interfaces **500**, **600** for viewing and/or interacting with activity within the hub are shown. Example user interfaces **500**, **600** provide data related to and may be generated by hub device **110** of FIG. 1, such as by hub and registry module **204** of FIG. 2.

[0131] In some examples, credentialed administrators access and manage the micro front-end ecosystem from the hub user interface. The hub, and the associated user interface, may function as a control center of the entire micro front-end ecosystem. For example, a credentialed administrator may adjust the status of a particular version of micro front-end, may monitor and/or restrict micro front-end usage, update rules and metadata for micro front-ends, etc.

[0132] FIG. 5 shows an example user interface **500** depicting conformance checks performed by the micro front-end hub. User interface **500** depicts one example of a conformance report **502**. The conformance report **502** shows a conformance status **504** for each of a plurality of rules **506**. By providing an individual conformance status **504** for each rule **506**, the conformance report **502** provides one example of a summary of corrections to made to bring a micro front-end into compliance.

[0133] In some embodiments, user interface **500** incorporates interactive components reflected the control and management features of the hub. For example, a credentialed administrator may revert or update a version of a micro front-end from the interface, may get runtime metrics reflecting how the micro front-end is used within the ecosystem and experiences, may take a micro front-end out of service, may add restrictions for the use of a micro front-end, etc. from the hub by interacting with components of the interface **500**.

[0134] FIG. 6 shows an example user interface 550 for performing administrative operations within the micro front-end hub of FIG. 1. Admin user interface 550 may provide additional functionality and information about micro front-ends. Admin user interface 550 includes title 552, version status 554, performance data 556, usage data 558, preview 560, rules data 562, and launch function 564. [0135] Title 552 identifies the particular micro front-end being accessed. Version status 554 identifies available and, in embodiments, historic versions of the micro front-end in the hub. Individual versions are identified, such as through numbering, along with a status of each version and an access or storage location. Version status 554 may include a dependency graph for each version. An example dependency graph is shown and discussed in more detail below in respect to FIG. 7. Controls may be provided for each version, including, for example, control options to retire out-of-use but available versions and control options to revert an in-use version to another out-of-use version.

[0136] Performance data 556 provides measurement of one or more performance metrics. Monitored metrics may be identified by a category or metric title along with an associated measurements. Monitored metrics may include response time and percent of transactions completed, shown in the example of FIG. 6. Other, non-limiting, examples not shown include rendering speed and processing speed. Performance data 556, in embodiments, may include a indication of whether a present measurement of a metric fall within predetermined standards, e.g., within a service level agreement (SLA).

[0137] Usage data 558 provides measurement of one or more usage metrics. Monitored metrics may be identified by a category or metric title along with an associated measurements. Monitored metrics may include a number of customer requests or a number of schedule events.

[0138] In embodiments, usage metrics may be further defined by a time parameter. For example, usage measurements may be reported as per minute, per hour, per day, etc. In embodiments, usage metrics may further include a trend indicator, identifying whether measurements are trending upward, downward, steady, etc. The trend indicator may include a numerical and/or time-based indicator of change. The trend indicator may include a graphic or symbolic indicator of change.

[0139] In some embodiments, usage data 558 includes tracking of where or by whom usage of a particular micro front-end occurs. In embodiments, usage data 558 related to where in the micro front-end is being consumed may be referred to as consumer data and may be presented separately from usage data related to overall consumption of the micro front-end. Usage data 558 may include fields for identifying applications in which the micro front-end is incorporated and may include a measure of a number of sessions in which the application called the micro front-end. Usage data 558 may further indicator an owner of the application and identify the owner's license to use the particular micro front-end.

[0140] Preview 560 provides a view of the micro front-end version currently active that an administrator can view while making adjustments from the user interface 550. Rules data 562 provides an indication of active rules applicable to the micro front-end version currently in use. Launch function 564 enables an administrator to deploy changes made in the admin user interface 550 to the in use version of the micro front-end. Interface 550 may further include additional functionality, such as back, forward, reload, and home buttons, a search bar, and/or a menu tab or pop-out.

[0141] FIG. 7 shows an example user interface 566 a dependency graph for a micro front-end within the micro front-end hub of FIG. 1. User interface 566 is accessed, for example, by selecting to view a dependency graph from the versions data 554 of the admin user interface 550 of FIG. 6. User interface 566 includes title 568, version tabs 570, return function 572, graph 574, and related rules data 586. Graph 574 includes title 568 indicating the instant micro front-end, one or more related micro front-ends 576, relationship labels 582, and, in some embodiments, other related components 584. Each related micro front-end 576 includes a identifying title 578 and a relationship body 580.

[0142] Title **568** identifies the micro front-end to which the dependency graph being viewed relates. Version tabs **570** enable a user to navigate among dependency graphs relates to one or more versions of the a particular micro front-end. In some cases the dependency of a micro front-end may change between versions, changes which a user may view by using version tabs **570** to navigate among dependency graphs of the different version. Return function **572** enables a user to navigate back to an admin user interface, such as user interface **550** of FIG. **6**.

[0143] Graph **574** provides a graphical view of relationships between a subject micro front-end **575**, identified by title **568**, one or more related micro front-ends **576**, and, in some cases, other related components or systems **584**. Title **568** identifies the subject micro front-end **575** and may include additional information about the subject micro front-end **575**, such as identifying the version of the subject micro-front end to which the graph **574** being viewed relates. In some embodiments, the relevant version of the subject micro front-end **575** may be identified by version tabs **570**.

[0144] Related micro front-ends **576** are micro front-ends associated with rules establishing dependency on and/or from the subject micro front-end **575**. In embodiments, each related micro front-end **576** includes a identifying title **578** and a relationship body **580**. Identifying title **578** provides identifying information enabling related micro front-end **576** to be traced through other interfaces of the hub and system. In some implementations, identifying title **578** may include relevant version information. Relationship body **580** may include criteria associated with the rule establishing the relationship with the subject micro front-end **575**.

[0145] In the example shown in FIG. **7**, both related micro front-ends **576** depend upon subject micro front-end **575**, as reflected by relationship labels **582**. In this example, each relationship label **582** include an arrow indicating the direction of dependency and text identifying the nature of the dependency. For example, in one case, the related micro front-end **576** constitutively requires the subject micro front-end **575** and, in another case, the related micro front-end depends upon the subject micro front-end **575** when specific criteria is met. This criteria may be reflected in relationship body **580** and/or relationship label **582**. The subject micro front-end **575** in turn relies upon another related component **584**, as can be seen from the direction of the arrow and the text of relationship label **582**.

[0146] Related rules data **586** provides a display of rules establishing relationship between the related micro front-ends **576** and the micro front-end to which the graph **574** relates. In some cases, each relationship label **582** is defined by a rule shown in the related rules data **586**. Related rules data **586** may include fields identifying rules by name and/or version, identifying criteria associated with the rules, and identifying a status, e.g., active/inactive, for each rule. Interface **575** may further include additional functionality, such as back, forward, reload, and home buttons, a search bar, and/or a menu tab or pop-out.

[0147] FIG. **8** shows an example user interface **600** depicting an overview **602** of micro front-ends stored in the micro front-end hub. Example overview **602** provides a summary **604** of registered micro front-ends available in the hub. Example summary **604** is presented as a categorical list view, with each category containing a drop of includes micro front-ends. Other organization structures are envisioned. Other features, such as search feature **606**, may assist a user in navigating registered micro front-ends.

[0148] An explorer space **608** provides screen space on the user interface **600** to explore available micro front-ends. Example explorer space **608** displays individual micro front-ends as tiles **610**. Each tile **610** includes an individual identifier for the specific micro front-end, such as a title **612** or a descriptor. Individual identifiers may also include non-descriptive names or numbers. Each tile **610** may also include a summary **614** or other indicator a function provided by the micro front-end. Each tile **610** may also include button **616** or other means of linking or navigating to a more complete report of the micro front-ends functions and status.

[0149] FIG. **9** shows an example user interface **650** depicting a report **652** on a micro front-end.



Report **652** may be reached, for example, by following the button **616** or link on a dedicated tile **610** for the particular micro front-end on the hub overview **602** of FIG. **8**. Report **652** may repeat title **612** and summary **614** of tile **610** from the hub overview **602** for consistency and confirmation of having navigated to the desired report. Report **652** includes a demo **654** demonstrating operation of the micro front-ends according to current configuration parameters.

[0150] A specifications section **656** provides information related to authoring of the micro front-end. In some embodiment, the specifications section **656** may provide a link to a conformance report associated with the micro front-end, such as conformance report **502** of FIG. **5**. A details section **658** may specifically include details related to the micro front-end within the hub. For example, a status bar **660** may indicate the current status of the micro front-end from the perspective of the hub. A configuration section **662** may include information specific to the micro front-end's composition into applications and user experiences, including requirement the micro front-end may have to operate within an experience. A usage and analytics section **664** may include information related to the micro front-ends performance in deployment and operation.

[0151] Other information, not shown in the example of FIG. **9**, related to the micro front-end may be included in the report **652**. In some embodiments, particular rules associated with the micro front-end may be included. For example, a particular micro front-end may be restricted from certain users or experiences. The report **652** may reflect such a rule, for example in details section **658**. The rule may establish particular users or experiences in which in the micro front-end may be implemented or from which the micro front-end is excluded. In some embodiments, accessibilities and restrictions may also be adjusted, by a credentialed administrator, from within the report **652**, such as to add or change access grants or restrictions.

[0152] In examples directed to a micro front-end which is dependent upon or depended upon by another micro front-end, the dependencies may be included in the report **652**. For example, a report for micro front-end A, which is dependent upon micro front-end B, may include a rule indicating such a dependency, such as within details section **658** or configurations section **662**. The rule may establish the direction of dependency, showing micro front-end A cannot be deployed without micro front-end B. Likewise, another report for micro front-end B may include a rule indicating that micro front-end A depends upon micro front-end B. The rule may further provide indication that deployment of micro front-end B enables the deployment of other micro front-ends, e.g., micro front-end A.

[0153] The rule may reflect shared requirements between interdependent micro front-ends. For example, because micro front-end A is dependent upon micro front-end B, micro front-ends A and B may be required to be version aligned. The report for each of micro front-end A and B may indicate their current version and whether that version aligns with the interdependent micro front-end's version. As another example, a particular micro front-end, micro front-end C, may be configured with a rule that requires another micro front-end, micro front-end D, to be shown when micro front-end C is shown within a user experience. The requirement to show micro front-end D may be reflected in micro front-end C's report, such as in the specifications section **656** or the configurations section **662**.

[0154] FIG. **10** schematically shows example physical components of portions of the system **100** of FIG. **1**. In particular, additional components of the server device **108** are illustrated. In this example, the server device **108** provides the computing resources to perform the functionality associated with the system **100**. The other computing devices associated with the system **100**, such as the client device **104**, can be similarly configured.

[0155] The server device **108** can be an internally controlled and managed device (or multiple devices) of the business enterprise, e.g., the financial institution. Alternatively, the server device **108** can represent one or more devices operating in a shared computing system external to the enterprise or institution, such as a cloud. Via a network **700**, the components of the system **100** that are physically remote from one another can interact with one another.

[0156] The server device **108** includes a central processing unit or processor **702**, a system memory **708**, and a system bus **722** that couples the system memory **708** to the processor **702**.

[0157] The system memory **708** includes a random access memory (“RAM”) **710** and a read-only memory (“ROM”) **712**. A basic input/output system that contains the basic routines that help to transfer information between elements within the server device **108**, such as during startup, is stored in the ROM **712**.

[0158] The server device **108** further includes a mass storage device **714**. The mass storage device **714** is able to store software instructions and data.

[0159] The mass storage device **714** is connected to the processor **702** through a mass storage controller (not shown) connected to the system bus **722**. The mass storage device **714** and its associated computer-readable data storage media provide non-volatile, non-transitory storage for the server device **108**. Although the description of computer-readable data storage media contained herein refers to a mass storage device, such as a hard disk or solid state disk, it should be appreciated by those skilled in the art that computer-readable data storage media can be any available non-transitory, physical device or article of manufacture from which the central display station can read data and/or instructions.

[0160] Computer-readable data storage media include volatile and non-volatile, removable and non-removable media implemented in any method or technology for storage of information such as computer-readable software instructions, data structures, program modules or other data. Example types of computer-readable data storage media include, but are not limited to, RAM, ROM, EPROM, EEPROM, flash memory or other solid state memory technology, CD-ROMs, digital versatile discs (“DVDs”), other optical storage media, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, or any other medium which can be used to store the desired information and which can be accessed by the server device **108**.

[0161] According to various embodiments of the invention, the server device **108** may operate in a networked environment using logical connections to remote network devices through the network **700**, such as a wireless network, the Internet, or another type of network. The server device **108** may connect to the network **700** through a network interface unit **704** connected to the system bus **722**. It should be appreciated that the network interface unit **704** may also be utilized to connect to other types of networks and remote computing systems. The server device **108** also includes an input/output unit **706** for receiving and processing input from a number of other devices, including a touch user interface display screen, an audio input device, or another type of input device. Similarly, the input/output unit **706** may provide output to a touch user interface display screen or other type of output device.

[0162] As mentioned briefly above, the mass storage device **714** and/or the RAM **710** of the server device **108** can store software instructions and data. The software instructions include an operating system **718** suitable for controlling the operation of the server device **108**. The mass storage device **714** and/or the RAM **210** also store software instructions and applications **716**, that when executed by the processor **702**, cause the server device **108** to provide the functionality described above.

[0163] Although various embodiments are described herein, those of ordinary skill in the art will understand that many modifications may be made thereto within the scope of the present disclosure. Accordingly, it is not intended that the scope of the disclosure in any way be limited by the examples provided.

## Claims

1. A system, comprising: at least one processor; and non-transitory computer-readable storage storing instructions that, when executed by the at least one processor, cause the system to: authenticate a user device attempting to access a contextual interface; access data to generate the contextual interface, the data being associated with the user device; determine operational

- information and personal information associated with the user device; combine the operational information and the personal information to generate contextual information associated with the user device; select one or more micro front-ends from a hub of micro front-ends based on the contextual information for the contextual interface; and provide the contextual interface to the user device, wherein the contextual interface includes the one or more micro front-ends.
2. The system of claim 1, wherein artificial intelligence is used to combine the operational information and the personal information.
  3. The system of claim 1, comprising further instructions that, when executed by the at least one processor, cause the system to: determine whether experimentation is being conducted; and responsive to a determination that experimentation is being conducted, selecting experimental aspects of components of the one or more micro front-ends.
  4. The system of claim 3, comprising further instructions that, when executed by the at least one processor, cause the system to: determine whether experimentation is being conducted for a second contextual interface; and responsive to a determination that experimentation is not being conducted, selecting a standard version of components of the one or more micro front-ends.
  5. The system of claim 1, comprising further instructions that, when executed by the at least one processor, cause the system to generate a hub and registry module programmed to determine when a plurality of micro front-ends is conformant with one or more experience rules.
  6. The system of claim 5, wherein the hub and registry module is further programmed to: compose the one or more of the plurality of micro front-ends into an experience for a user; and monitor performance of the one or more of the plurality of micro front-ends within the experience, wherein the performance includes a response time for the one or more of the plurality of micro front-ends.
  7. The system of claim 5, wherein the hub and registry module is further programmed to: determine one of the one or more of the plurality of micro front-ends fails to satisfy the one or more experience rules; and responsive to a determination the one of the one or more of the plurality of micro front-ends fails to satisfy the one or more experience rules, revert the one of the one or more of the plurality of micro front-ends to a prior version of the one of the one or more of the plurality of micro front-ends.
  8. The system of claim 5, wherein the hub and registry module is further programmed to generate a user interface on a display, the user interface comprising an overview of the plurality of micro front-ends.
  9. The system of claim 5, wherein the one or more experience rules are defined using a domain specific language.
  10. The system of claim 9, wherein the domain specific language is JavaScript Object Notation.
  11. A method for generating a contextual interface, comprising: determining operational information and personal information associated with a user device; combining the operational information and the personal information to generate contextual information associated with the user device; selecting one or more micro front-ends from a hub of micro front-ends based on the contextual information for the contextual interface; determining experimentation is being conducted; responsive to determining that experimentation is being conducted, selecting experimental aspects of components of the one or more micro front-ends; and providing the contextual interface to the user device, and wherein the contextual interface includes the one or more micro front-ends.
  12. The method of claim 11, further comprising: determining experimentation is not being conducted for a second contextual interface; and responsive to determining that experimentation is not being conducted, selecting standard version of components of the one or more micro front-ends.
  13. The method of claim 11, wherein artificial intelligence is used to combine the operational information and the personal information.
  14. The method of claim 11, further comprising: determining if a plurality of micro front-ends is

conformant with one or more experience rules.

**15.** The method of claim 14, further comprising: composing the one or more of the plurality of micro front-ends into an experience for a user; and monitoring performance of the one or more of the plurality of micro front-ends within the experience, wherein the performance includes a response time for the one or more of the plurality of micro front-ends.

**16.** The method of claim 15, further comprising: determining one of the one or more of the plurality of micro front-ends fails to satisfy the one or more experience rules; and responsive to determining the one of the one or more of the plurality of micro front-ends fails to satisfy the one or more experience rules, reverting the one of the one or more of the plurality of micro front-ends to a prior version of the one of the one or more of the plurality of micro front-ends.

**17.** The method of claim 14, wherein the one or more experience rules are defined using a domain specific language.

**18.** The method of claim 17, wherein the domain specific language is JavaScript Object Notation.

**19.** A non-transitory computer readable medium having instructions stored thereon, the instructions causing one or more processors to: authenticate a user device attempting to access a contextual interface; access data to generate the contextual interface, the data being associated with the user device; determine operational information and personal information associated with the user device; combine the operational information and the personal information to generate contextual information associated with the user device; select one or more micro front-ends from a hub of micro front-ends based on the contextual information for the contextual interface; and provide the contextual interface to the user device, wherein the contextual interface includes the one or more micro front-ends.

**20.** The non-transitory computer readable medium of claim 19, wherein the instructions further cause the one or more processors to determine when a plurality of micro front-ends is conformant with one or more experience rules.

---