

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250258991

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

O'Rourke; Xavier

Systems and methods for processing designs

Abstract

Described herein is a computer implemented method for generating a new chart based on a source chart and a destination chart. The method includes accessing source chart data in respect of the source chart, wherein the source chart data defines a set of source chart data series and a set of source chart colours, and wherein each source chart data series is associated with a source chart colour and accessing destination chart data in respect of the destination chart, wherein the destination chart data defines a set of destination chart data series and a set of destination chart colours, and wherein each destination chart data series is associated with a destination chart colour. The method further includes determining that the number of source chart colours is greater than the number of destination chart colours and, in response, generating one or more new chart colours. The method further includes generating the new chart to include the set of source chart data series, associating a first source chart data series with a destination chart colour and associating a second source chart data series with a new chart colour.

Inventors: O'Rourke; Xavier (Sydney, AU)

Applicant: Canva Pty Ltd (Surry Hills, AU)

Family ID: 94387533

Assignee: Canva Pty Ltd (Surry Hills, AU)

Appl. No.: 19/196374

Filed: May 01, 2025

Foreign Application Priority Data

AU 2023210538

Jul. 31, 2023

Related U.S. Application Data

parent US continuation 18786527 20240728 PENDING child US 19196374

Publication Classification

Int. Cl.: G06F40/106 (20200101); G06F40/186 (20200101)

U.S. Cl.:

CPC G06F40/106 (20200101); G06F40/186 (20200101);

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION [0001] This application is a Continuation Application of U.S. Non-Provisional application Ser. No. 18/786,527, filed on Jul. 28, 2024, that claims priority to Australian Patent Application No. 2023210538, filed Jul. 31, 2023, which are each hereby incorporated by reference in their entirety.

TECHNICAL FIELD

[0002] The present disclosure is directed to various systems and methods for processing designs.

BACKGROUND

[0003] Computer applications for creating and working with designs exist. Some such applications may provide users with the ability to create designs in different formats.

[0004] As one example, an application may provide functionality for a user to create what will be referred to as document-format designs—e.g. designs that store content and associated metadata in a word-processing document type format. As another example, an application may provide functionality for a user to create what will be referred to as deck-format designs—e.g. designs that store content and associated metadata in a slide deck type format.

[0005] In some situations, a user may wish to use a design they have created as the basis for generating another design. For example, a user may wish to use content prepared in an original document-format design as the basis for a deck-format design.

[0006] Background information described in this specification is background information known to the inventors. Reference to this information as background information is not an acknowledgment or suggestion that this background information is prior art or is common general knowledge to a person of ordinary skill in the art.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0007] In the drawings:

[0008] FIG. 1 depicts two example designs: a document-format design and a deck-format design.

[0009] FIG. 2 is a block diagram of a networked environment in which embodiments of the present disclosure may be performed.

[0010] FIG. 3 is a block diagram of a computer processing system.

[0011] FIG. 4 depicts example graphical user interfaces.

[0012] FIG. 5 is a flowchart depicting operations performed to generate analysis data corresponding to a deck-format design.

[0013] FIG. 6 is a flowchart depicting operations performed to generate a new deck-format design based on document-format source design.

[0014] FIG. 7 depicts an example graphical user interface.

[0015] FIG. 8 is a flowchart depicting operations performed to generate source analysis data

corresponding to a document-format design.

[0016] FIG. **9** is a flowchart depicting operations performed to determine pagination candidates for content of a document-format design.

[0017] FIG. **10** is a flowchart depicting operations performed to calculate a page fit score for a candidate page of a pagination candidate.

[0018] FIG. **11** is a flowchart depicting operations performed to split a selected candidate page into multiple candidate pages.

[0019] FIGS. **12** and **13** are illustrations to assist in understanding the method for determining pagination candidates described in FIG. **9**.

[0020] FIG. **14** is a flowchart depicting operations performed to generate deck-format design generation data.

[0021] FIG. **15** is a flowchart depicting operations performed to generate a new deck descriptor for a (pagination candidate, template) pair.

[0022] FIG. **16** is a flowchart depicting operations performed to generate a new deck-format design.

[0023] FIG. **17** is a flowchart depicting operations performed to detect and resolve undesirable element collisions.

[0024] FIG. **18** depicts various element layout examples to illustrate element overlaps and collisions.

[0025] FIG. **19** is a flowchart depicting operations performed identify undesirable collisions.

[0026] FIG. **20** is a flowchart depicting operations performed to resolve undesirable collisions.

[0027] FIG. **21** is a flowchart depicting operations performed to map a set of source content segments to a set of destination elements.

[0028] FIG. **22** is a flowchart depicting alternative operations performed to map a set of source content segments to a set of destination elements.

[0029] FIG. **23** is a flowchart depicting operations performed to generate a set of design elements based on a set of source fills and a single destination element.

[0030] FIG. **24** depicts example grid arrangements.

[0031] FIG. **25** is a flowchart depicting operations performed to generate a new table based on a source table and a destination table.

[0032] FIG. **26** is a flowchart depicting operations performed to generate a table style list.

[0033] FIG. **27** depicts two example tables.

[0034] FIG. **28** is a flowchart depicting operations performed to generate a new deck-format design based on a deck-format source design.

[0035] FIG. **29** is a flowchart depicting operations performed to transfer a set of fills.

[0036] FIG. **30** is a flowchart depicting operations performed to transfer a table.

[0037] FIG. **31** is a flowchart depicting operations performed to transfer a chart.

[0038] FIG. **32** is a flowchart depicting operations performed to determine whether a destination fill can be replaced by a partial or complete type source.

[0039] FIG. **33** is a flowchart depicting operations performed to process a set of input paragraphs to determine a set of text hierarchy levels defined by those paragraphs.

[0040] FIG. **34** depicts an example page with input paragraphs having different text formats.

[0041] While the description is amenable to various modifications and alternative forms, specific embodiments are shown by way of example in the drawings and are described in detail. It should be understood, however, that the drawings and detailed description are not intended to limit the invention to the particular form disclosed. The intention is to cover all modifications, equivalents, and alternatives falling within the scope of the present disclosure.

DETAILED DESCRIPTION

[0042] In the following description numerous specific details are set forth in order to provide a thorough understanding of the present invention. It will be apparent, however, that the present

invention may be practiced without these specific details. In some instances, well-known structures and devices are shown in block diagram form in order to avoid unnecessary obscuring.

[0043] As discussed above, computer applications for use in creating and working with designs exist. Such applications may provide mechanisms for a user to create a design, edit the design by adding content to it, and output the design in various ways (e.g. by saving, displaying, printing, publishing, sharing, or otherwise outputting the design).

[0044] As also discussed above, an application may provide a user with the ability to create and work with designs of different formats. For example, the present disclosure described two different design formats that will be referred to as document-format designs (documents for short) and deck-format designs (decks for short). Documents and decks are described in detail below).

[0045] Certain embodiments of the present disclosure are directed to systems and methods for generating a new deck-format design based on a source document-format design.

[0046] As one example, a user may have source content in a document but want to convert that document design into a deck. For example, a user may initially prepare a document that includes an outline (or other content) for a deck. Techniques described herein operate to automatically identify a matching template design and then generate a new deck-format design that is based on the template but that includes the source content from the original document.

[0047] Other embodiments of the present disclosure are directed to systems and methods for generating a new deck-format design based on a source deck-format design.

[0048] As one example, a user may generate a source (deck-format) design but wish to change the layout of the elements in the design page(s). In this case, the techniques described herein operate to automatically identify a matching template design and then generate a new deck-format design that is based on the template but that includes the source content from the original deck.

[0049] Other embodiments of the present disclosure are directed to analysing a deck-format design to generate analysis data corresponding thereto. If the deck-format design is a destination design (e.g. a template), the analysis data may be used to match the template to a source design and/or generate a new design based on the template and a source design. If the deck-format design is a source design, the analysis data may be used to match the source design to one or more deck-format template designs and to generate one or more new designs based on the source design and the one or more matched template designs.

[0050] Other embodiments of the present disclosure are directed to analysing a document-format source design to generate analysis data corresponding thereto. The analysis data may be used to match the source design to one or more deck-format template designs and to generate one or more new designs based on the source design and the one or more matched template designs.

[0051] Other embodiments of the present disclosure are directed to processing a document-format design to generating one or more pagination candidates for that document-format design. In this context, a pagination candidate defines a set of candidate pages, with each relevant content segment of the document design being assigned to a candidate page.

[0052] Other embodiments of the present disclosure are directed to determining a deck-format design page (e.g. a template page) that matches a set of source content segments of a source design. The set of source content segments may, for example, be associated with a candidate page generated for the source design.

[0053] Other embodiments of the present disclosure are directed to determining a deck-format design (e.g. a template) that matches the content of a source design. The source design may be a deck-format design or a document-format design.

[0054] Other embodiments of the present disclosure are directed to mapping a set of source objects (that correspond to source content of a source design) to a set of destination objects (that correspond to elements of a destination deck-format design, such as a template).

[0055] Other embodiments of the present disclosure are directed to mapping a set of source fills to a set of destination fills where a number of source fills exceeds the number of destination fills.

[0056] Other embodiments of the present disclosure are directed to generating a set of design elements based on a set of source fills and a single destination element.

[0057] Other embodiments of the present disclosure are directed to generating a table based on a source table and a destination table.

[0058] Other embodiments of the present disclosure are directed to generating a chart based on a source chart and a destination chart.

[0059] Other embodiments of the present disclosure are directed to identifying and resolving undesirable element collisions. Such collisions may arise when transferring content from a source design to a destination design. This may include identifying and resolving what are referred to as undesirable partial collisions, undesirable container collisions, and/or undesirable page collisions.

[0060] Other embodiments of the present disclosure are directed to identifying and resolving intra-text hierarchy level conflicts that may arise when transferring text content from a source design to a destination design.

[0061] Other embodiments of the present disclosure are directed to identifying and resolving inter-text hierarchy level conflicts that may arise when transferring text content from a source design to a destination design.

[0062] Other embodiments of the present disclosure are directed to determining a whether a destination fill is appropriate for replacement by a partial type fill or not.

[0063] Other embodiments of the present disclosure are directed to processing input text to determine a set of text hierarchy levels defined by that input text.

Designs

[0064] The present disclosure is concerned with designs.

[0065] In the context of the present disclosure, a design includes content and has a design format. In particular, the present disclosure refers to document-format designs and deck-format designs. For ease of reference, a document-format design may be referred to as a document and a deck-format design may be referred to as a deck.

[0066] In the context of the present disclosure, a design may include various different types of content. For example, content may be fill type content that defines a fill such as a solid colour, a colour gradient, a graphic (e.g. a vector graphic), an image (e.g. a raster image), a video, or an alternative type of fill. As another example, content may be text-type content (e.g. a sequence of one or more characters). As another example, content may be chart content (e.g. a line chart, bar chart, or an alternative type of chart). Alternative content types are possible.

[0067] In the context of the present disclosure, a deck includes an ordered set of one or more explicitly defined pages. The pages of a deck may be referred to as slides. The content of a deck is defined by one or more deck elements (elements for short). Generally speaking, each element defines (or is associated with) content (e.g. text, one or more fills, a chart, a table, or other content) as well as data that defines which page of the deck the element (and, therefore, its associated content) is on, where on that page the content is positioned, and how the content is displayed.

[0068] In a deck, each element is associated with explicit position data. An element's position data includes a particular page and a particular position on that particular page that the element's content is to be displayed at. In a deck, adding a new element or removing an existing element does not generally change the position of other elements in the deck. Moreover, unless element's are grouped together (or automatic reflow operations are implemented), adjusting the position of one element will not generally cause the positions of other elements to change.

[0069] Generally speaking, decks may be appropriate for content that is predominantly visual and has relatively low amounts of text. Decks may also be appropriate where specific and precise positioning of content (independently of other content) is of particular importance. Examples of such designs may include, for example, presentation decks (also referred to as slide decks) and posters. A deck could, however, be used to display large amounts of solely text content if desired.

[0070] In the context of the present disclosure, the content of a document is defined by an ordered

set of one or more document items (items for short). Generally speaking, each item defines (or is associated with) content (e.g. text, a fill, a chart, or other content) as well as data that defines how that content is displayed.

[0071] In a document, items are not generally associated with explicit position data. Instead, the position at which the content of an item is displayed is relative to any preceding items in the document's ordered set of items. Accordingly, in a document adding a new item or removing an existing item generally will change the position of other (subsequent) items in the document. To illustrate this, consider a first item that defines the text “TEXT”. If a second item defining (for example) the text “PLACEHOLDER” is added to the document before the first item, the second item will (in a standard English language context) cause the text of the first item to be displayed further to the right and/or further down the page. Similarly, if the second item was then deleted from the document, this would cause the text of the first item to be shifted to the left and/or up the page.

[0072] Generally speaking, documents may be appropriate for content that includes relatively large amounts of text and/or where the independent positioning of content is desirable. This may be the case where relative positioning is preferable—for example to allow for content to move (or reflow) as new content is added, content is deleted, and/or the size of the document (e.g. its width—or the size of a window in which the document is displayed) changes. Examples of such designs may include, for example, letters, descriptions, papers (and other “word-processing” type documents).

[0073] Documents may also be used, however for other purposes. For example, a user wishing to create a deck for a particular purpose may initially create a document that provides an outline of the deck.

[0074] An example document-format is described below.

Example Deck-Format Design

[0075] In order to illustrate decks, a simplified deck-format design data schema will be described by way of example. Alternative schemas are possible.

[0076] In the present example, a deck is defined by a deck record. A deck record is a set of key/value pairs (e.g. a map or dictionary) that define attributes of the deck. A deck record may define various deck attributes, such as one or more of the following:

TABLE-US-00001 Example attribute Note E.g. Deck ID A unique identifier of the “deckId”: “abc123”, deck-format design. Dimensions Default dimensions “dimensions”: { (e.g. width and height) of “width”: 1080, the pages of the deck. “height”: 1080 }, Page data An array of page records “pages”: [(described further below). {page record 1}, ..., {page record n}]

[0077] In the present example, a deck record provides various deck-level attributes. These include an identifier and default page dimensions. Additional and/or alternative deck-level attributes are possible (for example attributes such as a version identifier, a creation date, a creator, and/or other attributes).

[0078] In the present example, the deck record also includes page data—an ordered set (e.g. an array) of one or more page records. Each page record defines a page of the deck. In this example, a page record's position in the ordered set serves to identify that page and also define its position in the deck (e.g. a page at array index n appears after a page at array index n-1 and before a page at array index n+1).

[0079] In the present example, each page record is also a set of key/value pairs. Example page record attributes are as follows:

TABLE-US-00002 Example attribute Note E.g. Background Defines a page “background”: {background fill}, background Element Defines elements “elements”: [data that have been {design element record 1}, added to the page ..., {design element record n}]

[0080] In this present example, each page record defines a background and element data.

[0081] The background is an optional attribute that defines any background fill for the page. A background fill may, for example, be a solid colour, a colour gradient, an image, or an alternative

fill. In other implementations, a page background may be defined as an element of the design page (e.g. as the first element of the page's elements array discussed below) rather than a page-level attribute.

[0082] The element data of a page record is an ordered set (e.g. an array) of design element records. Each design element record defines an element that has been added to the page.

Accordingly, in the present example the page record in which a design element record appears defines the particular page that element belongs to. Furthermore, in this example, a design element record's position in a page's element array serves to identify that element and defines its depth (or z-index) on the page. For example, an element at array index n is positioned above an element at array index $n-1$ and below an element at array index $n+1$. Element depth becomes relevant where non-transparent elements (or non-transparent portions of elements) overlap one another in the x/y plane. Element depth may be alternatively handled, however, for example, by storing depth as an explicit element attribute.

[0083] Generally speaking, an element defines content that has been added to a page of a deck—e.g. by copying/importing content from one or more libraries (e.g. libraries of images, animations, videos, etc.); by drawing/creating using one or more design tools (e.g. a text tool, a line tool, a rectangle tool, an ellipse tool, a curve tool, a freehand tool, and/or other design tools); or by otherwise adding content to a deck page.

[0084] In the present example, different element types are provided. The actual element types provided—and the attributes required or available to define those elements—will depend on implementation. In the present example, however, text, shape, table, chart, and group type elements are provided. These element types are described below.

[0085] All element types include position data that defines an element's position on the page the element belongs to. In the present example, an element's position is defined by an (x,y) coordinate pair.

[0086] In the present examples, a Cartesian coordinate system is used in which the origin of a page (i.e. $x=y, y=0$) is at the top-left: i.e. x coordinates increase from left to right, and y coordinates increase from top to bottom. In this coordinate system, the (x,y) coordinate pair defining an element's position defines the top left corner of the element prior to any rotation that may be associated with/applied to the element.

[0087] All element types also include size data that defines an element's size. In the present example, an element's size is defined by a width value and a height value.

[0088] An element's position and size data can be used to determine its bounding box. In the present disclosure, an element's bounding box can be defined by a set of four values: a top or minY coordinate (e.g. the element's y position); a left or minX coordinate (e.g. the element's x position); a bottom or maxY coordinate (e.g. the element's height); and a right or maxX coordinate (e.g. the element's width). For example, if an element's position data defines an (originX, originY) coordinate pair and its size data defines a width and a height, the bounding box values may be calculated (in the context of the coordinate system described above) as:

$\text{minX} = \text{originX};$

[00001] $\text{maxX} = \text{originY} + \text{width};$

$\text{minY} = \text{originY};$

$\text{maxY} = \text{originY} + \text{height}.$

[0089] In the present disclosure, the bounding boxes of shape, chart, and table type elements correspond to the extents of the element's visible content. For text elements, however, the bounding box may not necessarily correspond to the extents of the text content. In particular, the text content of a text element may expand beyond the element's bounding box (or not occupy the entirety of the element's bounding box). For text elements, an additional text-width attribute may be defined which defines the width at which text will wrap and, therefore, a text content mask. For text

elements, the text-width attribute may be less than, equal to, or greater than the element's size.width attribute, and as a consequence the content mask of a text element may extend beyond the text element's bounding box (as determined by its size and position attributes). In other implementations, a separate text-width attribute need not be used—in which case a text element's size.width attribute is used to determine the text-width attribute (e.g. text-width=size.width, or text-width=size-width—a text margin value).

[0090] All element types also include rotation data that defines an element's rotation. In the present example, an element's rotation is defined by a rotation value that defines a number of degrees that the element is rotated (e.g. 0=no rotation). In the present embodiments, any rotation applied to an element is about a centre of the element's bounding box.

[0091] In addition to attributes that define an element's position, size, and/or rotation, different element types will provide for additional attributes that define the content that the element is used to display. The following provides an example of such attributes.

[0092] In the present example, a text element is used to display text content and may include (or be associated with): [0093] Content data which, for a text element, is text data defining the text content itself (e.g. a set of one or more characters). Text characters may include control characters—e.g. defined character sequences (such as “\n” indicating a line break). [0094] Format data which, for a text element, is text format data that defines how the text characters are to be displayed. Text format data may include data such as font type, font colour, font style, font size, and/or other format data. Text format data include block level format data which applies to the text of an entire element and/or inline format data which applies to specific characters or spans of characters of the text content. Format data may also include list attributes which describe whether the element's text is arranged in a list of items or not (and, if so, may also define particular list markers—e.g. bullet points, consecutively increasing numbers, or other markers). [0095] Text alignment data which defines alignment of text in a bounding box. Text alignment data may include vertical alignment data (e.g. top, middle, bottom) and/or horizontal alignment data (e.g. left, centre, right). In the present embodiments, a text element's vertical alignment data defines the direction(s) in which text added to a text element expands (or shrinks) as new lines of text are added or removed. For example: when text is added to a top aligned text element the text expands downwardly; when text is added to a bottom aligned text element the text expands upwardly; when text is added to a middle aligned text element the text expands evenly upwardly and downwardly. [0096] Position, size, and rotation data as described above.

[0097] In certain embodiments, a text element may also include (or be associated with) text hierarchy level data that defines a hierarchy level (or levels) for the text characters. Text hierarchy levels are described further below.

[0098] In the present example, a shape element is used to display a fill and may include (or be associated with): [0099] Content data which, for a shape element, is fill data defining the fill content itself. Fill content may, for example, be a solid colour, a colour gradient, a graphic (e.g. a vector graphic), an image (e.g. a raster image), a video, or an alternative fill. [0100] Path data that defines a shape path, e.g. an external path or frame for the shape. The path data may, for example, define a geometric shape (e.g. a rectangle, square, triangle, circle, ellipse, or other geometric shape) or an arbitrary closed path (e.g. a hand-drawn path). In the present embodiments, any transparency of a shape's content overrides the path, in the sense that the path acts to mask the media's existing mask. [0101] Fill role data. For example a value indicating whether the fill content is what will be referred to a complete fill or a partial fill. In the present disclosure, a complete fill is a fill that does not include any transparent (or cut-out) regions while a partial fill is a fill that does include one or more transparent (or cut-out) regions. [0102] Position, size, and rotation data as described above. [0103] Certain shape elements may have additional attributes depending on the type of fill the shape element accommodates and/or other factors. By way of example, some or all shape elements may also include one or more of: [0104] Scaling data that defines whether a shape's fill stretches in

a vertical direction, stretches in a horizontal direction, or scales uniformly in both directions. [0105] Content size/position/rotation data that define the size/position/rotation of the shape's fill within the shape's bounding box (i.e. separate to the size/position/rotation of the shape element as a whole). This can effect cropping. [0106] Key colour data which describes a set of key colours of the shape. E.g. for certain images and animated images a set of key colours are defined which can then be used if the shape needs to be recoloured. In certain implementations, key colour data is stored for vector graphic images and animated images. [0107] Fill arrangement data. In certain implementations, a single shape element may provide an arrangement of multiple fills. In this case the multi-fill shape element may include fill arrangement data that defines how the multiples fills are arranged (e.g. as a grid or the like). In the present disclosure, if a shape element defines multiple fills each fill is processed as a distinct shape element. In this case the size and position attributes of each shape element are based on the parent (multi-fill) shape element's size and position attributes and the fill arrangement data. Other attributes (e.g. rotation and transparency) are inherited from the parent. [0108] Trim data. For example, for a shape that includes a video fill, trim data may define a start time and/or end time for the playback of that fill.

[0109] In the present example, a table element is used to display a table and may include (or be associated with): [0110] Table structure data which defines a structure of the table. The table structure data may, for example, define a number of columns and a number of rows. The table structure data may also define specific column and/or row attributes (e.g. column widths and/or row heights, expressed as either absolute values or as a proportion of the table's total width/height), or may omit such data (in which case column widths and row heights may be automatically determined based on the table's content). [0111] Content data which, for a table element, is cell data defining the content of each table cell. The cell data for a given cell may be text data (describing text content, as described above) or fill data (describing fill content, as described above). [0112] Format data. The format data for a table element may include cell format data which describes a cell format of each table cell. Cell format may include attributes such as background colour, font family, font weight, text colour, text decoration (e.g. underline), text style (e.g. italics), and/or other cell format attributes. The format data for a table may also include structural format data defining, for example, table and cell borders (e.g. line weight, line colour, line style). [0113] Position, size, and rotation data as described above.

[0114] In the present example, a chart element is used to display a chart and may include (or be associated with): [0115] Content data which, for a chart element, is chart data defining one or more data series that are to be presented in the chart. [0116] Chart type data defining a chart type that is to be used to display the one or more data series (e.g. a line chart, bar chart, pie chart, or an alternative form of chart). [0117] Format data. Chart format data may include, for example, a set of data series formats (and data associating each data series format with a data series of the chart). A data series format may define, for example, a data series colour, a data series fill pattern, and/or other format attributes. Chart format data may also include text format data in respect of chart labels or other text. [0118] Position, size, and rotation data as described above.

[0119] In the present example, a group element is used to group other elements together and may include (or be associated with): [0120] Content data which, for a group element, is a set of one or more design element records each of which defines a member element of the group. [0121] Position, size, and rotation data as described above. In the present embodiments, the position of an element that is a member of a group is treated as being relative to the position/size/rotation of the member element's parent element. To illustrate this, consider a group element (G1) that has a position of (10,10) and includes a member element (M1) that also has a position of (10,10). In this case, the final position of element M1 on a page will be (20,20) (i.e. element M1's position of (10,10) is a position within group element G1 and relative to the position of element G1). If the group element G1 was then moved to position (30, 40), the new position of member element M1 would be (40,50) (again, relative to the parent element's position).

[0122] Element groups may be handled in different ways. For example, each design element record may include a group identifier attribute that includes a value that indicates a particular element group that the element belongs to (if any). In this case, if one element of a particular group is resized or repositioned, any other elements that belong to that same group are also resized/repositioned to maintain their relative size/position in the group.

[0123] Additional and/or alternative element types to those described above may be provided. Further, a given element type may include attributes defining additional or alternative features of the element.

[0124] As can be seen from the above example, each element of a deck is associated with a particular page of the deck and includes at least position data that determines where on a deck page (in two-dimensional space) the element—and, therefore, the content associated with the element—is to be positioned. Moreover, with the exception of elements that are part of an element group (and are therefore associated with a parent element), an element's two-dimensional (e.g. x,y) position on its page is independent to any other element's that are added to that page (or the deck in general). That is, an element's two-dimensional position is not changed by adding additional elements to, or removing other elements from, the deck. If a new element is added on top of or underneath an existing element this may (depending on opacity settings) change the appearance of or occlude the existing element, however this does not change the page on which existing element appears or the existing element's position on that page.

Example Document-Format Design

[0125] In order to illustrate document-format designs (documents), an example document-format will be described. Alternative document-formats are, however, possible.

[0126] In the present example, a document is defined by a document record. A document record includes an ordered sequence (such as an array or other ordered set) of content data. In the present example, this will be referred to as an ordered sequence of document element records (or elements). While document element records are in some respects similar to design element records they are not the same. To avoid potential confusion, document element records may be referred to as item records (or items for short) (and document elements as defined by those records may be referred to as items). E.g.: [0127] docContent: [{item record 1}, {item record 2}, . . . {item record n}]

[0128] Generally speaking, an item defines content that has been added to a document. Different item types may be provided for different types of content that are able to be added to a document. The types of items available will depend on the system in question and the types of content that are permitted in a document. In the present embodiments, and by way of example, text, shape, table, and chart item types are provided.

[In the present example, a text item is used to display text content. A text item (which may be referred to as a text block) generally defines a vertically delineated block of text (e.g. a paragraph, a list item, or an alternatively delimited block of text). A text item may include (or be associated with): [0129] Text data. This may be similar to (or the same as) text element text format data as described above. [0130] Text format data. This may be similar to (or the same as) text element text format data as described above.

[0131] A text item may also include (or be associated with) text hierarchy level data that defines a hierarchy level (or levels) for the text characters. Text hierarchy levels are described further below.

[0132] In the present example, a shape item is used to display a fill and may include (or be associated with): [0133] Content data. This may be similar to (or the same as) shape element content data as described above. In the present embodiments a shape item is limited to defining a single fill. In other embodiments, a shape item may define multiple fills (though other modifications to the processing described below may be necessary to allow for this). [0134] Path data. This may be similar to (or the same as) shape element path data as described above. [0135] Fill role data. This may be similar to (or the same as) shape element fill role data as described

above.

[0136] In the present example, a table item is used to display a table and may include (or be associated with): [0137] Table data. This may be similar to (or the same as) table element table data as described above. [0138] Cell data. This may be similar to (or the same as) table element cell data as described above.

[0139] In the present example, a chart item is used to display a chart and may include (or be associated with): [0140] Chart data. This may be similar to (or the same as) chart element chart data as described above. [0141] Chart type data. This may be similar to (or the same as) chart element chart type data as described above. [0142] Chart format data. This may be similar to (or the same as) chart element chart format as described above.

[0143] In the present example, a group item is used to group other items together and may include (or be associated with): [0144] A set of one or more additional item records that define the items of the group.

[0145] In a document-format design, non-text items (e.g. shape, table, chart, and group type items in the present example) may be referred to as block items. Text items may also be referred to as block items if they are split at block boundaries (e.g. if each text item defines a vertically delineated block of text as described above). In addition to the block item attributes described above, block items may also include one or more additional attributes such as:

TABLE-US-00003 Item attribute Note flow A value indicating content flow - e.g. block (default) or inline. Similar to the CSS display property. width A defined width at which the element is rendered. Similar to the CSS width property. max_width An upper bound on the computed width. Similar to the CSS max-width property. min_width A lower bound on the computed width. Similar to the CSS min-width property. height A defined height at which the element is rendered. Similar to the CSS height property. max_height An upper bound on the computed height. Similar to the CSS max-height property. min_height A lower bound on the computed height. Similar to the CSS min-height property. margin Values indicating margins. May take absolute values (e.g. {top, right, bottom, left}) or a value indicating margins should be automatically calculated to horizontally center the element.

[0146] In the present examples, each item defined in a document's sequence of document element (or item) records is to be rendered in the same manner as a block-level element in an HTML rendering. Accordingly, and analogous to HTML block layout, an item inherits the width of its container unless it is explicitly overridden or bounded.

[0147] As can be seen, in a document the two-dimensional position of the content associated with a given item (and the page on which that content appears) depends on any preceding items (i.e. those that are before the particular item in the items array) and the particular item's attributes (e.g. flow, width height, and/or margin values). Moreover, the position of particular item's content- and/or the page on which the content appears—can vary depending on what other items are added to or removed from the document. Furthermore, in the present embodiments document items are not associated with explicit position data (e.g. (x,y) coordinates or other explicit two-dimensional position data) in the same way that deck elements are.

[0148] In addition to content data, a document record may include document metadata. Such metadata may, for example, be similar to or the same as the deck-level attributes of a deck as described above (and include attributes such as a document identifier, document creator, document creation date and the like).

Example Designs

[0149] In order to illustrate the deck and document-formats described above, FIG. 1 provides an example document **100** and an example deck **150**.

[0150] Document **100** includes the following content: [0151] text **102** that includes the typographic characters “This is a title”, bold, centred, Calibri 18 point font (which is assigned or determined to be text hierarchy level 1); [0152] text **104** that includes the typographic characters “This is a

subtitle”, centred, Calibri 10 point font (which is assigned or determined to be text hierarchy level 2); [0153] a table **106** with two columns and two rows, centred; [0154] additional content **108** that is not shown (this may, for example, be line breaks or other content that causes the vertical space between content **106** and **110**); [0155] text **110** that includes the typographic characters “This is a another subtitle”, left justified, Calibri 10 point font (which is assigned or determined to be text hierarchy level 2); [0156] image **112**, centred.

[0157] A simplified items array that defines the content of document **100** may be as follows:
TABLE-US-00004 docContent: [{item record re text item 102}, {item record re text item 104}, {item record re table item 106}, {item record re text item 108}, {item record re text item 110}, {item record re shape item 112}]

[0158] Deck **150** includes the similar content to document **100** (as indicated by use of the same reference numerals) with the exception that it does not include additional content **108** and the content is positioned on two separate pages **152** and **154**. A simplified pages array that defines the content of deck **150** may be as follows:

TABLE-US-00005 pages: [//page record for page 152 {elements: [{design element record re table element 106},{design element record re text element 102}, {design element record re text element 104},]}, //page record for page 154 {elements: [{design element record re shape element 112}, {design element record re text element 110}]}]

[0159] Relevantly, each design element record will include explicit position data (e.g. an (x,y) coordinate pair) that defines the position of the element on the deck page in question.

Text Hierarchy Levels

[0160] Certain operations and methods described herein make use of text hierarchy levels.

[0161] A text hierarchy level provides a measure of the significance of text content. Continuing with the examples above, the text content of a deck includes characters defined by (or associated with) the text elements of that deck, while the text content of a document includes characters defined by (or associated with) text type items of that document.

[0162] Text hierarchy levels may be represented in various ways. In the present embodiments, a numeric hierarchy is used with lower values indicating text of greater significance. E.g. level 1 text may correspond to a title, level 2 text to a sub-title, etc.

[0163] Text hierarchy levels may be determined in various ways.

[0164] In some embodiments, text hierarchy levels may be explicitly defined for any text. For example, when a user is adding text to a deck or a document they may explicitly set or apply a hierarchy level to that text (and if no hierarchy level is set then a default hierarchy level may be assigned).

[0165] In alternative embodiments, text hierarchy levels may be automatically determined by processing a given document or deck. Generally speaking, this may involve extracting the text content from a document or deck and analysing the text to determine different text hierarchy levels based on certain format attributes and/or text position information.

[0166] A method for analysing text to determine a set of text hierarchy levels is described with reference to FIG. **33**.

Example Design Platform

[0167] The features of the present disclosure are described in the context of a design platform. In the described embodiments, this platform includes server-side and client-side applications which operate to perform the various techniques described herein. One example of such a platform will be described with reference to networked environment **200** of FIG. **2**.

[0168] Networked environment **200** includes a server environment **210** and a client system **230** which communicate via one or more communications networks **140** (e.g. the Internet).

[0169] Generally speaking, the server environment **210** includes computer processing hardware **212** (discussed below) on which applications that provide server-side functionality to client applications (such as client application **232** described below) execute. In the present example,

server environment **210** includes a server application **214**, a design analysis application **216**, a pagination application **218**, a template matching application **220**, and a data storage application **222**.

[0170] In the present embodiment, the server application **214** executes to provide a client application endpoint that is accessible over communications network **140**. For example, where server application **214** serves web browser client applications the server application **214** will be a web server which receives and responds (for example) to HTTP requests. Where server application **214** serves native client applications, server application **214** will be an application server configured to receive, process, and respond to specifically defined API calls received from those client applications. The server environment **210** may include one or more web server applications and/or one or more application server applications allowing it to interact with both web and native client applications.

[0171] In the present example, server application **214** (and or other applications of server environment **210**) facilitate various functions related to creating and editing documents and designs. This may include, for example, document and design creation, editing, storage, searching, retrieval, publication, and viewing. The server application **214** (and/or other applications) may also facilitate additional functions that are typical of server systems—for example user account creation and management, user authentication, and/or other server side functions.

[0172] The functions performed by the design analysis application **216**, pagination application **218**, and template matching application **220** are described in detail below.

[0173] In the present example, the data storage application **222** operates to receive and process requests to persistently store and to retrieve data that is relevant to the operations performed and/or services provided by the server environment **210**. Such requests may be received from the server application **214**, other server environment applications, and/or (in some instances) directly from client applications such as **232**. Data relevant to the operations performed/services provided by the server environment **210** may include, for example, user account data, user document and design data (e.g. document and deck records defining documents and designs that have been created by users), template design data (e.g. deck records defining template designs), media data (e.g. data in respect of stock media such as pictures and videos that users may add to designs), and/or other data relevant to the operation of the server environment **210**.

[0174] The data storage application **222** may, for example, be a relational database management application or an alternative application for storing and retrieving data from data storage **224**. Data storage **224** may be any appropriate data storage device (or set of devices), for example one or more non transitory computer readable storage devices such as hard disks, solid state drives, tape drives, or alternative computer readable storage devices.

[0175] In server environment **210**, server application **214** persistently stores data to data storage device **224** via the data storage application **222**. In alternative implementations, however, the server application **214** may be configured to directly interact with data storage devices such as **224** to store and retrieve data (in which case a separate data storage application may not be needed). Furthermore, while a single data storage application **222** is described, server environment **210** may include multiple data storage applications. For example one data storage application **222** may be used for user account data, another for user document and design data, another for design template data and so forth. In this case, each data storage application may interface with one or more shared data storage devices and/or one or more dedicated data storage devices, and each data storage application may receive/respond to requests from various server-side and/or client-side applications (including, for example server application **214**).

[0176] As noted, the server environment **210** applications run on (or are executed by) computer processing hardware **212**. Computer processing hardware **212** includes one or more computer processing systems. The precise number and nature of those systems will depend on the architecture of the server environment **210**.

[0177] For example, in one implementation each server environment application may run on its own dedicated computer processing system. In another implementation, two or more server environment applications may run on a common/shared computer processing system. In a further implementation, server environment **210** is a scalable environment in which application instances (and the computer processing hardware **212**—i.e. the specific computer processing systems required to run those instances) are commissioned and decommissioned according to demand—e.g. in a public or private cloud-type system. In this case, server environment **210** may simultaneously run multiple instances of each application (on one or multiple computer processing systems) as required by client demand. Where server environment **210** is a scalable system it will include additional applications to those illustrated and described. As one example, the server environment **210** may include a load balancing application which operates to determine demand, direct client traffic to the appropriate server application instance **214** (where multiple server applications **214** have been commissioned), trigger the commissioning of additional server environment applications (and/or computer processing systems to run those applications) if required to meet the current demand, and/or trigger the decommissioning of server environment applications (and computer processing systems) if they are not functioning correctly and/or are not required for current demand.

[0178] Communication between the applications and computer processing systems of the server environment **210** may be by any appropriate means, for example direct communication or networked communication over one or more local area networks, wide area networks, and/or public networks (with a secure logical overlay, such as a VPN, if required).

[0179] Client system **230** hosts a client application **232** which, when executed by the client system **230**, configures the client system **232** to provide client-side functionality/interact with server environment **210** (or, more specifically, the server application **214** and/or other applications provided by the server environment **210**). Via the client application **232**, and as discussed in detail below, a user can access the various techniques described herein. Client application **232** may also provide a user with access to additional design and document related operations, such as creating, editing, saving, publishing, sharing, and/or other design and document related operations.

[0180] Via the client application **232**, a user can perform various operations such as creating, editing, saving, retrieving/accessing, publishing, and sharing documents and designs. Such operations may be performed solely by client application **232**, or may involve the client application **232** communicating with the server environment **210** for processing to be performed there (e.g. by the server application **214**).

[0181] The client application **232** may be a general web browser application which accesses the server application **214** via an appropriate uniform resource locator (URL) and communicates with the server application **214** via general world-wide-web protocols (e.g. http, https, ftp).

Alternatively, the client application **232** may be a native application programmed to communicate with server application **214** using defined application programming interface (API) calls and responses.

[0182] A given client system such as **230** may have more than one client application **232** installed and executing thereon. For example, a client system **230** may have a (or multiple) general web browser application(s) and a native client application.

[0183] In the present embodiments, client application **232** includes a content transfer module **234**, the operations of which will be described further below. The content transfer module may, for example, be a native part of the client application **232** or an add-on/plugin/extension to client application **232**. In alternative embodiments, the functionality performed by the content transfer module **234** may be performed by a separate application (running either on client system **230** or at the server environment **210**).

[0184] In the environment of FIG. 1, and the embodiments described below, various processing is described as being performed by different applications and modules thereof—e.g. the server

application **214**, the design analysis application **216**, the pagination application **218**, the template matching application **220**, the data storage application **222**, the client application **232**, and the content transfer module **234**. It will be appreciated, however, that in most cases the processing that is described could be performed by alternative applications or modules, and that such applications or modules may run either at a client system such as **230** or at a server environment such as **210**. As one example, the techniques described herein may be provided as part of a stand-alone application in which case all processing and data storage may be performed by a single computer processing system (which is configured by one or more applications or modules).

[0185] As noted, the techniques and operations described herein are performed by one or more computer processing systems.

[0186] By way of example, client system **230** may be any computer processing system which is configured (or configurable) by hardware and/or software—e.g. client application **232**—to offer client-side functionality. A client system **230** may be a desktop computer, laptop computer, tablet computing device, mobile/smart phone, or other appropriate computer processing system.

[0187] Similarly, the applications of server environment **210** are also executed by one or more computer processing systems. Server environment computer processing systems will typically be server systems, though again may be any appropriate computer processing systems.

[0188] FIG. **3** provides a block diagram of a computer processing system **300** configurable to implement embodiments and/or features described herein. System **300** is a general purpose computer processing system. It will be appreciated that FIG. **3** does not illustrate all functional or physical components of a computer processing system. For example, no power supply or power supply interface has been depicted, however system **300** will either carry a power supply or be configured for connection to a power supply (or both). It will also be appreciated that the particular type of computer processing system will determine the appropriate hardware and architecture, and alternative computer processing systems suitable for implementing features of the present disclosure may have additional, alternative, or fewer components than those depicted.

[0189] Computer processing system **300** includes at least one processing unit **302**. The processing unit **302** may be a single computer processing device (e.g. a central processing unit, graphics processing unit, or other computational device), or may include a plurality of computer processing devices. In some instances, where a computer processing system **300** is described as performing an operation or function all processing required to perform that operation or function will be performed by processing unit **302**. In other instances, processing required to perform that operation or function may also be performed by remote processing devices accessible to and useable (either in a shared or dedicated manner) by system **300**.

[0190] Through a communications bus **304** the processing unit **302** is in data communication with a one or more machine readable storage (memory) devices which store computer readable instructions and/or data which are executed by the processing unit **302** to control operation of the processing system **300**. In this example system **300** includes a system memory **306** (e.g. a BIOS), volatile memory **308** (e.g. random access memory such as one or more DRAM modules), and non-transitory memory **310** (e.g. one or more hard disk or solid state drives).

[0191] System **300** also includes one or more interfaces, indicated generally by **312**, via which system **300** interfaces with various devices and/or networks. Generally speaking, other devices may be integral with system **300**, or may be separate. Where a device is separate from system **300**, connection between the device and system **300** may be via wired or wireless hardware and communication protocols, and may be a direct or an indirect (e.g. networked) connection.

[0192] Generally speaking, and depending on the particular system in question, devices to which system **300** connects—whether by wired or wireless means—include one or more input devices to allow data to be input into/received by system **300** and one or more output device to allow data to be output by system **300**. Example devices are described below, however it will be appreciated that not all computer processing systems will include all mentioned devices, and that additional and

alternative devices to those mentioned may well be used.

[0193] For example, system **300** may include or connect to one or more input devices by which information/data is input into (received by) system **300**. Such input devices may include keyboard, mouse, trackpad, microphone, accelerometer, proximity sensor, GPS, and/or other input devices. System **300** may also include or connect to one or more output devices controlled by system **300** to output information. Such output devices may include devices such as a display (e.g. a LCD, LED, touch screen, or other display device), speaker, vibration module, LEDs/other lights, and/or other output devices. System **300** may also include or connect to devices which may act as both input and output devices, for example memory devices (hard drives, solid state drives, disk drives, and/or other memory devices) which system **300** can read data from and/or write data to, and touch screen displays which can both display (output) data and receive touch signals (input).

[0194] By way of example, where system **300** is a client system such as **230** it may include a display **318** (which may be a touch screen display), a camera device **320**, a microphone device **322** (which may be integrated with the camera device), a cursor control device **324** (e.g. a mouse, trackpad, or other cursor control device), a keyboard **326**, and a speaker device **328**.

[0195] System **300** also includes one or more communications interfaces **316** for communication with a network, such as network **140** of environment **200** (and/or a local network within the server environment **210**). Via the communications interface(s) **316**, system **300** can communicate data to and receive data from networked systems and/or devices.

[0196] System **300** may be any suitable computer processing system, for example, a server computer system, a desktop computer, a laptop computer, a netbook computer, a tablet computing device, a mobile/smart phone, a personal digital assistant, or an alternative computer processing system.

[0197] System **300** stores or has access to computer applications (also referred to as software or programs)—i.e. computer readable instructions and data which, when executed by the processing unit **302**, configure system **300** to receive, process, and output data. Instructions and data can be stored on non-transitory machine readable medium such as **310** accessible to system **300**. Instructions and data may be transmitted to/received by system **300** via a data signal in a transmission channel enabled (for example) by a wired or wireless network connection over an interface such as communications interface **316**.

[0198] Typically, one application accessible to system **300** will be an operating system application. In addition, system **300** will store or have access to applications which, when executed by the processing unit **302**, configure system **300** to perform various computer-implemented processing operations described herein. For example, and referring to the networked environment of FIG. 2 above, server environment **210** includes one or more systems which run a server application **214**, a design analysis application **216**, a pagination application **218**, a template matching application **220**, and a data storage application **222**. Similarly, client system **230** runs a client application **232**.

Example Design User Interfaces

[0199] In the present disclosure, client application **232** configures the client system **230** to provide user interface (UI). Generally speaking, the UI allows a user to create, edit, and output designs. The UI also allows a user to access and cause other functionality described herein to be performed.

[0200] To illustrate the types of features that client application **232** may provide, FIG. 4 provides two example user interfaces: UI **400** and UI **450**. UI **400** and **450** are similar, however UI **400** provides an example UI for creating/viewing a deck-format design while UI **450** provides an example UI for creating/viewing a document-format design.

[0201] UI **400** includes a preview area **402A** which is used to display a page **404A** of the deck being edited/viewed. Page **404A** includes a text element **455A** with the text “Hello”. A bounding box of text element **455A** is also displayed. An element's bounding box may be temporarily displayed on selection of the element. In this example, UI **400** further includes: next and previous page controls **406** (which, where next/previous pages exist, can be used to display a next or

previous page); page previews **408** (which, where multiple pages exist, provide previews of those pages); an add page control **410** (which can be activated by a user to cause a new page to be added to the deck).

[0202] UI **450** includes a preview area **402B** which is used to display a document **404B** (or part thereof). Document **404B** includes a text item **455B** with the text “Hello/n”. A bounding box of the text element is also displayed (which may be displayed on the text element **455A** being selected). In this example, a horizontal line **452** is displayed on the preview **404B** to indicate a page break and a scroll control **454** is provided to allow a user to scroll through the document. In addition a cursor **456** is displayed which indicates a current position in the document.

[0203] UI **400** and UI **450** of the present examples both include a zoom control **409** which a user can interact with to zoom into/out of the design currently displayed on the canvas **404**.

[0204] UI **400** and UI **450** of the present examples also include an asset preview area **411**. Asset preview area **411** displays previews **412** of assets that are available to users to assist in creating a design. Asset preview area **411** also includes a search control **416** via which a user can submit search data (e.g. a string of characters) to search for particular assets. Previews **412** of the search results returned are then displayed in the asset preview area **411**. In this example, a hide preview area control **418** is provided which can be activated to hide the asset preview area **411** (serving to enlarge the design preview area **402**).

[0205] Depending on implementation, the previews **412** displayed in asset preview area **411** (and the assets corresponding to those previews) may be accessed from various locations. For example, the search functionality invoked by search control **416** may cause client application **142** to search for assets that are stored in locally accessible memory of the system **230** on which client application **232** executes (e.g. non-transitory memory such as **310** or other locally accessible memory), assets that are stored at a remote server (and accessed via a server application running thereon), and/or assets stored on other locally or remotely accessible devices.

[0206] Different types of assets may be made available, for example media items, design templates, design styles (e.g. defined sets of colours, font types, and/or other assets/asset parameters), and/or other assets that a user may use when creating a design or document. For example, a preview **412** may be of a media item (e.g. a raster graphic, a vector graphic, a video, or an alternative element) and a user may add that media item to the design being edited by dragging and dropping the preview **412** onto the page **404**.

[0207] Where a user adds content to a deck page **404A** by dragging an asset preview **412** and dropping it on the page, application **232** will create a new element for the content and add that element to the relevant page array (e.g. by appending it to the array). In this case application **232** may determine the position of the design element based on the actual drop point and generate position data to capture this (e.g. an (x,y) coordinate pair corresponding to—or based on—the drop point).

[0208] Where a user adds content to a document page **404B** by dragging an asset preview **412** and dropping it on the page **404B**, application **232** will create a new item for the content and add that item to the document's content array. In certain implementations, application **232** will be configured to automatically add the dropped item at the location of the cursor **456**. For example, if the cursor was positioned at the end of the existing document content (as depicted in UI **450**), application **232** would add the new item to the end of the document's content array. Alternatively, if the cursor was positioned before the ‘H’ character in UI **450**, application **232** would insert the new item into the document's content array before the item defining the characters “Hello/n”. Inserting the new item may then cause the “Hello/n” characters to move—e.g. down the page.

[0209] Content may be added to a design in other ways. In this example, the preview area **411** displays a scroll control **414** allowing a user to scroll through previews **412**. Scroll control **414** may be hidden when user focus is not in the preview area **411**.

[0210] GUI **400** also includes an additional controls area **420** which, in this example, is used to

display additional controls. The additional controls **420** may include permanent controls (e.g. controls such as save, download, print, share, publish, and/or other controls that are frequently used/widely applicable and that client application **232** is configured to permanently display); user configurable controls (which a user can select to add to or remove from area **420**), and/or adaptive controls (which may automatically change depending, for example, on the type of content that is currently selected/being interacted with by a user). For example, if text content is currently selected, adaptive controls such as font style, type, size, position/justification, and/or other font related controls may be displayed. Alternatively, if vector graphic content is selected, adaptive controls such as fill attributes, line attributes, transparency, and/or other vector graphic related controls may be displayed.

[0211] In the present example, UI **400** includes a generate deck from deck control **422**, a select fills control **424**, a transfer table control **426**, and a transfer chart control **427**. In the present example, UI **450** includes a generate deck from document control **430**. The operation of these controls will be described further below.

[0212] Once a design has been created, application **104** may provide various options for outputting that design. For example, application **104** may provide a user with one or more options such as: saving the design to local memory of client system **230** (e.g. non-transitory memory **310**); saving the design to data store **224** of server environment **210**; printing the design to a printer (local or networked); communicating the design to another user (e.g. by email, instant message, or other electronic communication channel); publishing the design to a social media platform or other service (e.g. by sending the design data to a third party server system using appropriate API commands to publish the design); and/or by other output means.

[0213] It will be appreciated that UI **400** and UI **450** are provided by way of example only. Alternative user interfaces, with alternative layouts and/or that provide alternative tools and functions, are possible. Furthermore, while different example user interfaces have been depicted and shown for viewing/editing a deck or a document, this need not be the case and the same user interface may be used.

Deck-Format Design Templates

[0214] Certain embodiments described herein make use of a set of deck-format destination designs. In the present disclosure, such destination designs are referred to as template designs (or templates for short). In the present embodiment, each template in the set of design templates is a deck-format design. Templates may, for example, be stored at (and accessed from) at data storage **224** (and accessed via data storage application **222**).

[0215] Each template is a deck that includes one or more pages. Any existing deck may be used as a template. Typically, however, a deck will be selected as a template (by a human or automatic selection process) based on various criteria—e.g. the aesthetics of the deck, its format consistency, and/or other criteria.

[0216] As described in detail below, certain embodiments of the present disclosure involve identifying a template that matches a source design and then generating a new deck based on the source design and the template.

[0217] In order to facilitate these embodiments, a set of templates is identified and each template is analysed to generate corresponding analysis data. Generally speaking, the analysis data in respect of a template provides information in respect of the content that the template can accommodate.

[0218] Templates for inclusion in the set of templates may be identified in various ways. For example, human users may review existing decks and flag/nominate specific decks for inclusion. Alternatively, users may specifically create new decks that are designed to be used as templates. Alternatively, templates may be identified by one or more automatic processes. For example, an application may be configured to monitor the usage of decks that and if the number of times a particular deck is used exceeds a threshold value the application may automatically flag that deck as a template (or, alternatively, flag that deck as a potential template for review by a human user).

[0219] Once a deck has been identified as a template it is processed to generate corresponding analysis data, e.g. in accordance with method **500** as described below.

[0220] Method **500** may be performed in respect of a template at any appropriate time in order to establish (or add to) a set of templates for use in a deck generation process. By way of example, method **500** may be triggered based on explicit user input (e.g. a user that selects an existing deck and initiates analysis of that deck). Additionally, or alternatively, method **500** may be automatically triggered based on the occurrence of a defined trigger condition. Such conditions may include, for example: detecting that one or more decks has been flagged (by a human user or application) as a template; detecting that one or more existing templates has been modified; and/or detecting the occurrence other trigger conditions.

Deck-Format Design Analysis

[0221] Referring to FIG. 5, a method **500** for processing a deck-format design to generate corresponding analysis data will be described.

[0222] Method **500** may be performed in respect of a destination deck-format design, such as a template design, that content is to be transferred to (for example in a document to deck generation method such as method **600** or a deck to deck generation method such as method **2800**, both described below).

[0223] Method **500** may also be performed in respect of a source deck-format design that content is to be transferred from (for example in a deck to deck generation method such as method **2800** described below).

[0224] Method **500** describes processing a single deck to generate corresponding analysis data. If multiple decks are to be analysed, method **500** may be performed on each deck sequentially or in parallel.

[0225] In the present example, method **500** is described as being performed by design analysis application **216** (referred to as application **216** in this section for convenience). The processing described may, however, be performed by one or more alternative applications or modules.

[0226] Method **500** takes as input a deck-format design (or an identifier thereof) which will be referred to as the input deck. Generally speaking, the input deck will include one or more pages and each page will include one or more elements that define content positioned on that page. An example deck-format is described above.

[0227] Method **500** operates to process the elements of the input deck to generate deck analysis data. Where the input deck is a template (or destination) deck, the deck analysis data may be referred to as template analysis data. Where the input deck is a source deck, the deck analysis data may be referred to as source analysis data. The deck analysis data includes page analysis data for each page of the input deck.

[0228] In the present embodiments, and as described in detail below, the page analysis data for a particular page includes: [0229] A set of one or more analysis objects. Where method **500** is being performed to analyse a template (or destination) deck, the analysis objects will be referred to as destination objects. In this case, each analysis object (or destination object) generally defines a destination into which source content can be transferred. Where method **500** is being performed to analyse a source deck (e.g. a design that defines source content that is to be transferred from in a content transfer process), the analysis objects will be referred to as source objects. In this case, each analysis object (or source object) generally defines source content that is to be transferred. Each analysis object is associated with an element of the input deck (or with a deck page background) and provides information concerning that element. [0230] A page partition key that provides a first (and relatively general) measure of the types and amounts of content that the page can accommodate. Where the page partition key is generated in respect of a template (or destination) deck it may be referred to as a template page partition key. [0231] A page vector that provides a second (and more specific) measure of the types and amounts of content that the page can accommodate. Where the page vector is generated in respect of a template (or destination) deck it

may be referred to as a template page vector. [0232] Page content metrics, which provide a third measure of the types and amounts of content that the page can accommodate. In the present embodiments page content metrics are generated only for destination decks (e.g. templates) and need not be generated for source decks.

[0233] At **502**, application **216** selects an unprocessed page (e.g. a page record) of the input deck. Pages of the input design may be processed in any desired order (e.g. the order in which the pages appear in the input deck's pages array) or in parallel.

[0234] At **504**, application **216** determines whether the selected page should be discarded or not. Application **216** is configured to determine that a page should be discarded if the page meets certain discard criteria. Various discard criteria may be set. By way of example, discard criteria may include one or more of: the page including greater than a threshold number of elements; the page including greater than a threshold number of elements of a particular type (e.g. greater than x shape elements); the page including a defined element type (or content type) (e.g. an element or content type that is not supported); the page including associated notes (e.g. comments not part of the page's actual content) to a designer; the page being flagged/associated with a value indicating the page should be discarded.

[0235] If application determines that the page should be discarded, processing proceeds to **518** without generating page analysis data for the page. In this case an error may be generated indicating that analysis data could not be generated for the page. Otherwise, processing proceeds to **506**.

[0236] At **506**, application **216** selects the next unprocessed element (e.g. design element record) of the page selected at **502**. Elements of a page may be processed in any order (e.g. the order in which the element's appear in the selected page's elements array), or in parallel. If the page has a background (and this is not defined as an element of the page—e.g. it is defined as a page-level attribute), application **216** will initially select the page's background for processing (the background otherwise being treated as an element).

[0237] At **508**, application **216** generates one or more analysis objects that correspond to the element selected at **502**. In this context the term “object” refers to a set of data. This may, for example, be a set of key/value pairs or any other appropriate data structure or set of related data structures.

[0238] In some instances, a single element may define multiple separable content items. In this case, multiple analysis objects corresponding to that single element may be generated. As one example, a shape element may define a plurality of fills (e.g. in a grid or other arrangement). As noted above, in the present embodiment if a shape element defines a plurality of fills each separate fill is treated as a distinct shape element. Accordingly, if a shape element defines a plurality of fills an analysis object corresponding to each fill is generated.

[0239] As another example, if an element is a group element, application **216** may be configured to generate a separate analysis object corresponding to each member element of the group.

[0240] As another example, in certain embodiments, where the input deck is a source deck application **216** may be configured to analyse each text element to determine whether the element's text content defines multiple separable text segments. If application **216** determines that a text element of a source deck does define multiple separable text segments, application **216** may generate an analysis object corresponding to each separable text segment. Application **216** may determine whether a text element defines multiple separable text segments in various ways, for example according to the processing described with reference to **808**, **810**, and **812** below (or similar processing).

[0241] Generating an analysis object corresponding to an element involves determining and recording values for one or more analysis object attributes. In the present embodiments, the analysis object attributes that are generated for a given analysis object depend on the type of the element that the analysis object corresponds to (and the type of content that element defines) and

whether the input deck is a source deck (and, therefore, source objects are being generated) or a destination deck (and, therefore, destination objects are being generated).

[0242] In the present embodiments, analysis objects may be generated to include one or more of the analysis object attributes indicated in the following table (and described in detail thereafter).

Destination object attribute	Source object attribute	Target identifier	Target identifier (destination identifier)	(source identifier)	Content type	Content type	Receive-content	Transfer-content	Reading order	Reading order	Text hierarchy level	Text hierarchy level	Num. lines
Num. lines	Num chars	Num chars	Appropriate for fill roles	Fill role	Aspect ratio	Aspect ratio							

[0243] In the present embodiments, the target identifier attribute is generated for analysis objects corresponding to all element types.

[0244] The target identifier attribute is generated to identify the element of the input deck that the analysis object corresponds to and, if required, specific content of that element. The precise manner in which an element (and specific content thereof if required) is identified will depend on the deck data format that is used.

[0245] In the context of the deck data format described above, the target identifier attribute includes an element identifier that identifies a particular element that the analysis object corresponds to (e.g. by the index of the element in the relevant page's element array).

[0246] If a target object relates to a separable content item of a design element, the destination identifier attribute will also include data that identifies the specific separable content item of the element. For example, if a particular shape element defines a plurality of fills, the destination identifier may include an element identifier (identifying the particular shape element) and a fill identifier (e.g. a fill index or other identifier) that identifies the particular fill that the analysis object corresponds to. As another example, the target identifier for text content of a text element may in some cases include data that identifies the particular text of the element. This may, for example, include a start or first character identifier (e.g. a firstCharIndex indicating an index of the first character of the text) and a length value (e.g. character length value indicating the number of characters that the content includes).

[0247] If the element is a member of an element group, the target identifier may include a group member identifier that identifies the particular group member (e.g. the index of the element in the elements array of the parent group element).

[0248] If required, the target identifier may include a page identifier that identifies the specific page that the element belongs to (e.g. the index of the page in the input deck's pages array).

[0249] Where an analysis object is a destination object: the target identifier may be referred to as a destination identifier; the element identified may be referred to as a destination element; and any specific content identified may be referred to as a destination content segment. Where an analysis object is a source object: the target identifier may be referred to as a source identifier; the element identified may be referred to as a source element; and any specific content identified may be referred to as a source content segment.

[0250] In the present embodiments, a content type attribute is generated for analysis objects corresponding to all element types.

[0251] A content type analysis object attribute is generated to identify the type of content that the analysis object corresponds to: that is, the type of content that is defined by the element that the analysis object corresponds to. In the present example, content types corresponding to the content types described above are provided—e.g. text content (for text elements), fill content (for shape elements), table content (for table elements), and chart content (for chart elements). More granular content types (or sub-content types) may be provided. For example, a shape element may be capable of accommodating different types of fills—e.g. a background fill type (indicating the content is a page background fill), a graphic fill type (indicating the fill is a vector graphic), an image fill type (indicating the fill is a raster graphic), a colour fill type (indicating the fill is a solid colour or a colour gradient), a video fill type (indicating the fill is a video), and/or other fill types.

Other types may be provided depending on the content types supported by deck-format (and document-format) designs.

[0252] In the present embodiments, a receive-content or transfer-content attribute is generated for analysis objects corresponding to all content types.

[0253] If the input deck is a destination deck (e.g. a template), a receive-content attribute is generated to indicate whether or not the element that the analysis object corresponds to is an element that source content can be transferred into when a new deck is being generated. The receive-content attribute may be a Boolean (or other) variable. In the present embodiments, a receive content value of true indicates that the element can receive source content (and a value of false indicates the element cannot receive source content).

[0254] Application **216** may be configured to determine that a particular element of a destination deck is or is not to receive content based on various reception criteria.

[0255] By way of example, for a text element, application **216** may be configured to determine that a text element can receive content unless one or more of the following criteria are satisfied: the text of the element includes solely non-alphanumeric characters; the text of the element is a single character; the text of the element is a two-digit numeral. If application **216** determines that a text element satisfies any of these criteria it may determine that the text element is not to receive content and set a receive-content value indicating this (e.g. receiveContent=false).

[0256] As another example, application **216** may be configured to determine that a shape element can receive content if its fill is a media fill (e.g. a raster image or vector graphic rather than a colour or a colour gradient), a complete fill (with no transparencies, as discussed above), and either of the following is satisfied: its fill detected to contain a person (e.g. by an object detection algorithm such as YOLOv3 model or an alternative model/process); or its fill is not a page background and it has 6 or more colours in an 8-bit colour space. If a fill of a shape element does not satisfy these criteria application **216** may be configured to determine that the fill element cannot receive content.

[0257] As yet a further example, in certain embodiments, application **216** may be configured to determine that any analysis object in respect of a fill that is a partial fill cannot receive content. (In other embodiments, however, further logic may be applied to determine whether an analysis object corresponding to a partial fill can receive content or not.)

[0258] Application **216** may be configured to determine that all chart elements and all table elements can receive content and set receive-content values for analysis objects corresponding to such elements accordingly (e.g. receiveContent=true).

[0259] Other criteria for determining whether an element is to receive content may be applied.

[0260] If the input deck is a source deck, a transfer-content attribute is generated to indicate whether or not the source content of the element that the analysis object corresponds to is source content that is to be transferred when a new deck is being generated. The transfer-content attribute may be a Boolean (or other) variable. In the present embodiments, a transfer content value of true indicates that the content defined by the element is to be transferred (and a value of false indicates the content is not to be transferred).

[0261] Application **216** may be configured to determine that a particular element of a source deck defines source content that is to be transferred based on various transfer criteria. Alternatively, application **216** may be configured to determine that all source content defined by shape, text, chart, and table elements is to be transferred.

[0262] By way of example, application **216** may be configured to determine that text content of a text element is to be transferred unless it includes solely non-alphanumeric characters.

[0263] As another example, application **216** may be configured to determine that a fill defined by a shape element is to be transferred unless it (or the shape element) exceeds a defined aspect ratio. The defined aspect ratio may be set to try and capture fills that are relatively wide, which may indicate that the fill is being used as a separator. For example, if application **216** determines that a fill has an aspect ratio of greater than 10 (i.e. >10:1) it may determine that the fill is not to be

transferred and set a transfer-content value indicating this (e.g. transferContent=false). By way of further example, application **216** may be configured to determine that all charts and all tables are to be transferred and set transfer-content values for source objects corresponding to such content accordingly (e.g. transferContent=true).

[0264] In alternative implementations, a receive-content or transfer-content attribute need not be used. For example, application **216** may be configured to determine that all elements of a destination deck are able to receive content and all elements of a source deck define source content that is to be transferred. As an alternative example, application **216** may be configured so that an analysis object is not generated for any destination deck element that is determined not to be able to receive content or any source deck element that is determined not to have source content that is to be transferred.

[0265] In the present embodiments, a reading order analysis object attribute is generated for all analysis objects that have a receive-content or transfer-content attribute value of true.

[0266] A reading order attribute is generated to identify a position of the element that the analysis object corresponds to in the deck page's reading order. In the present context, the reading order of a deck page's elements indicates an order in which elements would be read by a viewer of the design. For example, a reading order consistent with written English language may be left-to-right, top-to-bottom. Accordingly, a reading order of '1' may indicate the element is likely to be the first element of the deck page that would be read, and a reading order value of '5' may indicate the element is likely to be the 5th element read.

[0267] In certain embodiments, an element's reading order is associated with the element (e.g. stored as an attribute of the element).

[0268] In other embodiments application **216** may be configured to analyse (or to cause another application to analyse) the page in question to determine the reading order of its elements. Such analysis may be performed in accordance with any appropriate method or algorithm. For example, application **216** (or an alternative application) may determine reading order in accordance with: an approach such as that described in Australian patent application 2022271398, filed on 15 Nov. 2022, titled "Systems and methods for generating webpage data for rendering a design" (or a similar approach); the approach described in the paper "Optimized XY-Cut for Determining a Page Reading Order" by Jean-Luc Meunier, Xerox Research Centre Europe, 6, chemin de Maupertuis F-38240 Meylan (January 2005) (or a similar approach); an alternative approach.

[0269] In the present embodiments, a text hierarchy level analysis object attribute is only generated for analysis objects corresponding to text elements that have a receive-content or transfer-content attribute value of true.

[0270] A text hierarchy level analysis object attribute is generated to indicate the hierarchy level of text defined by the element that the analysis object corresponds to. Text hierarchy levels are discussed above. In some instances, text elements may already be associated with a text hierarchy level. If text hierarchy levels are not available, however, application **232** may be configured to analyse the text defined by the input deck (e.g. as defined by text elements of the input deck) to determine text hierarchy levels and associate each text element (or separable text segment thereof) with a text hierarchy level. This may, for example, be done in accordance with method **3300** described below, however alternative approaches to determining text hierarchy levels may be used.

[0271] In the present embodiments, a num lines analysis object attribute is only generated for analysis objects corresponding to text elements that have a receive-content or transfer-content attribute value of true.

[0272] A num lines analysis object attribute is generated to provide a measure of the vertical size of the element that the analysis object relates to. Vertical size may be calculated and indicated in various ways—e.g. as a number of pixels, a number of lines, or in an alternative manner.

[0273] In the present embodiment, the num lines analysis object is generated to indicate a number of lines of text defined by the text content of the element that the analysis object corresponds to. In

the present embodiments, application **216** is configured to calculate the num lines attribute by calculating a number of explicitly defined lines, estimating a number of wrapped lines, and adding these two values together. Application **216** calculates the number of explicitly defined lines based on line, paragraph, or other breaks included in the text that indicate a new line. Application **216** estimates the number of wrapped lines based on the size of the text element (in particular the width for horizontally oriented text), the font properties (which determine the width and height of character glyphs when the text characters are rendered), and the number of characters in a given unbroken text section (that is, a section of text that is not explicitly broken by a manual line/paragraph/other break). Application **216** may be configured to calculate the num lines attribute (or cause another application to calculate the num lines attribute) in alternative ways.

[0274] In the present embodiments, a num chars analysis object attribute is only generated for analysis objects corresponding to text elements that have a receive-content or transfer-content attribute value of true.

[0275] A num chars analysis object attribute is generated to indicate the number of characters defined by the text content of the element that the analysis object corresponds to. In the present embodiments, application **216** calculates the number of characters to be the number of characters excluding any control characters (e.g. “\n” or other defined control characters) and excluding any leading or trailing whitespace.

[0276] In the present embodiments, an appropriate for fill roles or fill role analysis object attribute is only generated for analysis objects corresponding to shape elements that have a receive-content or transfer-content attribute value of true.

[0277] If the input deck is a destination deck (e.g. a template), an appropriate for fill roles analysis object attribute is generated for destination objects corresponding to complete fills only (noting that in the present embodiment destination objects in respect of partial fills are assigned a receive content attribute value of false). The appropriate for fill roles attribute is assigned a value that indicates whether the shape element the destination object corresponds to is appropriate for replacement by: source fill that is either a partial fill (with one or more transparencies) or a complete fill (with no transparencies); or a complete fill only. Generally speaking, application **216** may be configured to determine that a particular destination fill is not appropriate for replacement by a partial source fill if replacing the destination fill with such a source fill could expose other elements (or parts of other elements) that are behind the particular destination fill. In this case, the assumption is that the (and that were not intended to be exposed). Application **216** may determine the value of the appropriate for fill roles attribute for a fill-type destination object in various ways. An example method **3200** for determining the appropriate for fill roles attribute value for a destination fill that is a complete fill is described below.

[0278] If the input deck is a source deck, a fill role analysis object attribute is generated to indicate whether the shape element's fill is a complete fill (with no transparencies) or a partial fill (with one or more transparencies).

[0279] In the present embodiments, an aspect ratio analysis object attribute is not generated for analysis objects corresponding to text elements, but is generated for analysis objects corresponding to chart, fill, and table type elements that have a receive-content or transfer-content attribute value of true.

[0280] An aspect ratio analysis object attribute is generated to indicate the aspect ratio of the content defined by the element that the analysis object corresponds to. With the example design element record schema described above, application **216** may determine the aspect ratio attribute based on the size data of the design element record—e.g. element width divided by the element height.

[0281] To further illustrate template analysis objects, and by way of example only, an example analysis object corresponding to a page background of a destination deck' page (which, in this example has been defined a page-level attribute) is as follows:


```
TABLE-US-00007 { "destinationID": { "pageID": 0, // indicating the first page of the
template/ destination deck "elementID": -1 // indicating a background that is defined by a
page-level attribute }, "type": "BACKGROUND_FILL", "receiveContent": false,
"appropriateForFillRoles": "complete", "aspectRatio": 1.7777777777777777 }
```

[0282] By way of further example, an example analysis object corresponding to a source deck shape type element is as follows:

```
TABLE-US-00008 { "sourceID": { "pageID": 0, // indicating the first page of the source
deck "elementID": 0, // indicating the first element of the page's elements array }, "type":
" FILL", "transferContent": true, "readingOrderIndex": 8, "fillRole": "complete",
"aspectRatio": 0.5666415662650801 }
```

[0283] By way of further example, an analysis object corresponding to a source deck's text type element is as follows:

```
TABLE-US-00009 { "sourceID": { "pageID": 0, // indicating the first page of the source
deck "elementID": 2, // indicating the second element of the page's elements array
"firstCharIndex": 0, // indicating the content starts at character index 0 "charLength": 48 //
indicating the content is 48 characters long }, "type": "TEXT", "transferContent": true,
"readingOrderIndex": 3, "textHierarchyLevel": 3, "numLines": 1.6454545454545455,
"numChars": 46 }
```

[0284] At **510**, application **216** determines whether the currently selected page defines any unprocessed elements. If so, processing proceeds to **506** to select the next unprocessed element. If all elements on the page have been processed, processing proceeds to **512**.

[0285] At **512**, application **216** generates a page partition key for the currently selected page. As noted above, the page partition key provides general information on the type and amount of content that the page includes or accommodates. In the present embodiments, where the deck being analysed is a destination deck (e.g. a template) the page partition key is used when determining whether a particular page is a potential match for a particular rewrite of a source content candidate page (as described below at **1408** of method **1400**). Where the deck being analysed is a source deck, the page partition key is used when determining whether the page is a potential match for a particular destination deck page (e.g. a template deck page).

[0286] In the present embodiments, application **216** generates a page's partition key to include the following partition key values: text; fills; charts; and tables. The prefix PK may be used to indicate partition key.

[0287] The PK text value indicates the deck page's text element content. In the present embodiment, the PK text value is the number of text elements the deck page has. Alternatively, the PK text value may be the number of text-type analysis objects that have been generated for the page (which, in certain implementations, may be greater than the number of text elements).

[0288] The PK fills value generally indicates the deck page's fill content. In certain implementations, the PK fill value is a value indicating the number of fills of the deck page (e.g. the number of fill type analysis objects with a receiveContent or transferContent value of true). In alternative embodiments, the PK fills value may be a Boolean (or other) value that indicates whether the page includes at least one shape element that has a corresponding fill-type analysis object with a receiveContent or transferContent value of true.

[0289] The PK charts value generally indicates the deck page's chart content. In the present embodiment, the PK charts value is a count of the number of chart type elements in the deck page (or a count of the number of chart type analysis objects generated for the deck page).

[0290] The PK tables value generally indicates the deck page's table content. In the present embodiment, the PK tables value is a count of the number of table type elements in the deck page (or a count of the number of table type analysis objects generated for the deck page).

[0291] To illustrate the above, consider a destination deck page with: three text elements; three shape elements (with receiveContent values of true); one chart; and one table. A page partition key

for such a page may be as follows:

TABLE-US-00010 { “PK_text”: 3, “PK_fills”: 3, // or “PK_fills”: “True” if a Boolean value is used “PK_charts”: 1; “PK_tables”: 1 }

[0292] A deck page partition key may be generated to include additional and/or alternative values that can be used to generally describe the content that a page includes or can accommodate.

[0293] At **514**, application **216** generates a page vector for the currently selected page. As described above, the page vector provides more specific information (when compared to the page partition key) on the type and amount of content that the page includes or can accommodate. In the present embodiments, page vectors are used when calculating (rewrite, template page) scores (as described below at **1416** of method **1400**).

[0294] In the present embodiments, application **216** generates a page's page vector to generally describe the content of the deck page: that is, the source content that is to be transferred for a source design, or the content that the deck page can accommodate for a destination design (e.g. a template). In the present example, page vector values are generated to describe the following types of page content: characters; lines; fills; charts; and tables. Each of these is described below, with the prefix PV used to indicate page vector.

[0295] In the present example, where a page vector value is being generated for a destination deck (e.g. a template), only analysis objects that have a “receive content” attribute value of true are considered. Conversely, where a page vector value is being generated for a source deck, only source objects that have a “transfer content” attribute value of true are considered.

[0296] The PV characters and PV lines values provide information on the deck page's ability to accommodate text at a given hierarchy level (for a destination deck) or the text content at a given hierarchy level that is to be transferred (for a source deck).

[0297] The PV characters values include, for each text hierarchy level, a characters value that is based on the number of text characters at that hierarchy level. In the present embodiment, the PV characters attribute is a set (e.g. an array) of six values with: the value at array indices 0 to 4 being based on the number of characters (if any) at text hierarchy levels 1 to 5 respectively; and the value at array index 5 being based on the number of characters at text hierarchy level 6 (if any)+the number of characters with a text hierarchy level of greater than 6 (if any)+the number of characters with no text hierarchy level assigned (if any).

[0298] In the context of the analysis objects described above, the characters value for a particular text hierarchy level is set to zero if there are no characters associated with that hierarchy level.

Otherwise, the chars value for a particular text hierarchy level may be calculated by: [0299]

identifying the analysis objects that include a “text hierarchy level” attribute indicating the particular hierarchy level; [0300] for each analysis object identified, taking the base 10 log of the num chars attribute value; [0301] averaging the base 10 log values.

[0302] The PV lines values include, for each text hierarchy level, a lines value that is based on the estimated number of text lines at that hierarchy level (or, more generally, the estimated vertical capacity for text lines at that hierarchy level). In the present embodiment, the PV lines attribute is a set (e.g. an array) of six values with: the value at array indices 0 to 4 being based on the number of lines of text (if any) at text hierarchy levels 1 to 5 respectively; and the value at array index 5 being based on the number of lines of text at text hierarchy level 6 (if any)+the number of lines of text with a text hierarchy level of greater than 6 (if any)+the number of lines of text with no text hierarchy level assigned (if any).

[0303] In the context of the analysis objects described above, the lines value for a particular text hierarchy level may be calculated by: [0304] identifying the analysis objects that include a “text hierarchy level” analysis object attribute indicating the particular hierarchy level; [0305] calculating the average of the num lines attributes of the identified analysis objects.

[0306] The PV fills values provide information on the deck page's ability to accommodate fill content (for a destination deck) or the fill content that is to be transferred (for a source deck). In the

present embodiment, and in the context of the analysis objects described above, the PV fills values include: a minimum fill aspect ratio value; a maximum fill aspect ratio value; a complete fills value; and a partial fills value.

[0307] Application **216** may calculate the minimum and maximum fill aspect ratio values by: [0308] identifying each fill type analysis object that has a receive-content attribute indicating the fill is a valid destination or a transfer-content attribute indicating that the fill is to be transferred; [0309] for each identified analysis object, calculating the base-2 log of the analysis object's aspect ratio attribute value; and [0310] recording the minimum and maximum base-2 logs that are calculated (or a default value of 0). Recording the minimum and maximum base-2 logs assists in accommodating the most extreme cases.

[0311] The PV complete fills value provides information on the page's "complete" fills. In the present embodiment, the complete fills value is the proportion fill-type analysis objects that have a fill role value indicating a "complete" fill (that is, the proportion of fills that do not have any transparent regions).

[0312] The PV partial fills value provides information on the page's "partial" fills. In the present embodiment, the partial fills value is the proportion fill-type analysis objects that have a fill role value indicating a "partial" fill (that is, the proportion of fills that include one or more transparent regions).

[0313] The PV tables values provide information on the deck page's ability to accommodate table content (for a destination deck) or the table content that is to be transferred (for a source deck). In the present embodiment, the PV tables values include a minimum table aspect ratio value and a maximum table aspect ratio value. Application **216** may calculate these values by: [0314] identifying each table type analysis object that has a receive-content attribute indicating the table is a valid destination or a transfer-content attribute indicating that the table is to be transferred; [0315] for each identified analysis object, calculating the base-2 log of the analysis object's aspect ratio attribute value; [0316] recording the minimum and maximum base-2 log calculated (or a default value of 0).

[0317] The PV charts values provide information on the deck page's ability to accommodate chart content (for a destination deck) or the chart content that is to be transferred (for a source deck). In the present embodiment, the PV charts values include a minimum chart aspect ratio value and a maximum chart aspect ratio value. Application **216** may calculate these values by: [0318] identifying each chart type analysis objects that that has a receive-content attribute indicating the chart is a valid destination or a transfer-content attribute indicating that the chart is to be transferred; [0319] for each identified analysis object, calculating the base-2 log of the analysis object's aspect ratio attribute value; [0320] recording the minimum and maximum base-2 log calculated (or a default value of 0).

[0321] In this particular embodiment, therefore, a page vector includes the following elements: TABLE-US-00011 [<L1 chars value>, <L2 chars value>, <L3 chars value>, <L4 chars value>, <L5 chars value>, <L6 chars value>, <L1 lines value>, <L2 lines value>, <L3 lines value>, <L4 lines value>, <L5 lines value>, <L6 lines value>, <min fill aspect ratio value>, <max fill aspect ratio value>, <partial fills value>, <complete fills value>, <min tables aspect ratio value>, <max tables aspect ratio value>, <min charts aspect ratio value>, <max charts aspect ratio value>]

[0322] At **516**, application **216** generates page content metrics data for the page. In the present embodiments, content metrics data is only generated for destination decks (e.g. templates) and is used when generating pagination data for a source document (in particular, when computing a candidate page score at **904** of pagination method **900**).

[0323] In the present embodiments, the content metrics data generated for a destination deck (e.g. template) page includes the following content metric values. The prefix CM may be used to indicate content metrics. [0324] A CM characters value that is based on the number of characters on the template page. In the present embodiment, the CM characters value is the logarithm of the

total number of characters defined by the template page's text type analysis objects. The characters value may alternatively be the actual number of characters (or an alternative value based thereon). [0325] A CM lines value that is based on the number of lines of text on the template page. In the present embodiment, the CM lines attribute is the logarithm of the total number of lines defined the template page's text type analysis objects. The lines value may alternatively be the actual number of lines (or an alternative value based thereon) or another value that provides a measure of the vertical capacity that the template page has available for text content. [0326] A CM fills value that is based on the number of fills on the template page. In the present embodiment, the CM fills value is the number of fill type analysis objects, however an alternative value based on that number may be used. [0327] A CM tables value that is based on the number of tables on the template page. In the present embodiment, the CM tables value is the number of table type analysis objects, however an alternative value based on that number may be used. [0328] A CM charts value that is based on the number of charts on the template page. In the present embodiment, the CM charts value is the number of chart type analysis objects, however an alternative value based on that number may be used.

[0329] In the present embodiment, only analysis objects that have a “receive-content” attribute that is true contribute to content metric values. In addition, while the content metric values are described as being based on a deck page's analysis objects they could instead be based on the actual elements of the deck page.

[0330] At **518**, application **216** determines whether there are any unprocessed pages defined by the input deck. If so, processing proceeds to **502** to select the next unprocessed page. If not, processing proceeds to **520**.

[0331] At **520**, application **216** may store the analysis data that has been generated for the input deck. This will typically be more appropriate where method **500** has been used to analyse a destination deck (e.g. a template) (and, therefore, the analysis data will likely be reused). The analysis data may be stored in any appropriate way. For example, the analysis data may be stored as a single data object that is associated with the relevant deck record. Alternatively, each deck page's page analysis data (which includes the set of analysis objects generated at **508**, the page partition key generated at **512**, the page vector generated at **514**, and the content metrics if generated at **516**) may be stored (or otherwise associated) with that page's page record. In this case, and continuing the example deck schema described above, the page record format may be along the following lines:

```
TABLE-US-00012 {  “background”: {background fill},  “elements”: [{design element record 1}, ..., { design element record n}],  “analysisItems”:[{analysisItem 1}, ..., { analysisItem n}],  “partitionKey”: {...},  “page Vector”: {...},  “contentMetrics”: {...} }
```

Deck-Format Fallback Pages

[0332] Certain embodiments described herein make use of deck-format fallback pages (referred to as fallback pages for short)—or sets of destination objects that define deck-format fallback pages.

[0333] In the present embodiments, a fallback page is an existing deck-format page that has been flagged or identified as a fallback page. Fallback pages may be specifically created to be used as fallback pages, or may be pages of existing templates that are flagged as fallback pages.

[0334] Typically, fallback pages are relatively plainly styled deck-format pages that include varying content elements. Generally speaking, a collection of fallback pages that correspond to likely partition keys and number of fills in user inputs, but which will not be conspicuous when placed amidst pages of existing templates (or are plain enough to be restyled in accordance with various template styles) may be created or assembled.

[0335] To permit identification of fallback pages, a fallback page list (or other data structure) may be maintained. Such a list may, for example, include a plurality of (template identifier, page identifier) tuples, each tuple identifying a particular page of a particular template as a fallback page.

[0336] In the present embodiment, fallback pages are analysed in the same (or a similar) way as other template pages (e.g. as described with reference to FIG. 5 above). In the present embodiment, therefore, each fallback page has associated analysis data that includes a set of destination objects, a page partition key, and a page vector.

Generating a Deck-Format Design Based on a Document-Format Design

[0337] Certain embodiments of the present disclosure are directed to generating a deck based on a source document. Referring to FIG. 6, a computer implemented method **600** for doing so will be described.

[0338] In FIG. 6, processing is generally indicated as being performed by (or at) either client system **230** or server environment **210**. In this example, the server-side processing is described as being coordinated by server application **214** (which causes other server-side applications to perform various operations). In alternative embodiments, however, the operations of method **600** could be coordinated and/or performed by alternative applications, or could be performed by a single stand-alone application.

[0339] At **602**, client application **232** detects initiation of a document to deck generation process. Initiation of the document to deck generation process is associated with a document (which will be referred to as the source document). The source document includes source content and may, for example, be defined by a document record as described above.

[0340] The document to deck generation process may be initiated in various ways.

[0341] By way of example, the document to deck generation process may be initiated on detecting user input received at client application **232**. This may be user input activating a UI control such as control **430** described above. If the generate deck control **430** is activated while a document is currently open (and, for example, displayed in preview area **402**) or otherwise selected, client application **232** may determine that the open document is the source document. Alternatively, on detecting activation of the generate deck control **430** client application **232** may display a search interface that allows a user to search and/or browse for, and then select, a source document.

[0342] At **604**, in response to detecting initiation of the document to deck generation process, client application **232** generates a document to deck generation request and communicates this to the server environment **210** (in this example to server application **214**). The document to deck generation request includes data allowing the source document to be identified—e.g. an identifier of the source document (which can be used to retrieve the source document's data) or by providing the document data itself (e.g. a document record as described above).

[0343] At **606**, server application **214** receives the document to deck generation request.

[0344] At **608**, source analysis data in respect of the source document is generated. Generally speaking, the source analysis data provides information in respect of the content of the source document that needs to be transferred to (or included in) any deck that is to be generated.

[0345] In the present embodiment, server application **214** passes the source document (or an identifier thereof) to the design analysis application **216** to generate the source analysis data. An example method for processing a document to generate source analysis data is described below with reference to FIG. 8. The source analysis data generated by this process includes a set of one or more analysis objects. Analysis objects in respect of a source design will be referred to as source objects as, generally speaking, they define source content that may be transferred to a destination page (e.g. a template page) in a content transfer process. Each source object corresponds to (or is associated with) source content defined by the source document and provides information concerning that source content.

[0346] At **610**, pagination data in respect of the source document is generated.

[0347] In the present embodiments, server application **214** passes the source analysis data generated at **608** (or a reference thereto) to the pagination application **218** to generate the pagination data. An example method for processing source analysis data to generate pagination data is described below with reference to FIG. 9.

[0348] Generally speaking, the pagination data includes a set of one or more pagination candidates for the source document. Each pagination candidate includes a set of one or more candidate pages. Each candidate page is associated with a subset (one or more) of the source objects from the source analysis data (generated at **608**)—and, therefore, with the document content that the source object(s) correspond to. Accordingly, each candidate page may be considered to correspond to a page of source content. Each pagination candidate represents a complete pagination solution for the source document. That is, for a given pagination candidate each relevant source object in the source analysis data (and, therefore, all relevant source document content) is associated with at least one candidate page of that pagination candidate. Pagination data is described in detail below with reference to FIG. **9**.

[0349] In the present embodiments, the pagination data that is generated defines a set number of pagination candidates.

[0350] At **612**, deck generation data is generated. Generally speaking, the deck generation data includes data that can be used to generate a new deck based on relevant source content of the source document, a template, and in some cases one or more additional fallback or new deck pages.

[0351] In the present embodiments, server application **214** passes the pagination data generated at **610** (or a reference thereto) to the template matching application **220** to generate the deck generation data. An example method for processing pagination data to generate deck generation data is described below with reference to FIG. **14**.

[0352] At **614**, server application **214** communicates the deck generation data (generated at **612**) to the client system **230** (in this example to client application **232**).

[0353] At **616**, client application **232** receives the deck generation data.

[0354] At **618**, one or more new decks are generated. Each new deck that is generated is based on the deck generation data generated at **612** (or part thereof) and (in the present embodiments) the source analysis data (generated at **608**) and the content of the source document itself.

[0355] In the present embodiments, a new deck is generated by the content transfer module **234**. An example method for generating a new deck is described below with reference to FIG. **16**.

[0356] At **620**, client application **232** outputs at least one of the one or more decks generated at **618**. Client application **232** may be configured to output a (or multiple) decks in various ways.

[0357] FIG. **7** provides one example user interface **700** for outputting decks generated at **618**. UI **700** is similar to UI **400** and UI **450** of FIG. **4**. In UI **700**, however, the asset preview area **411** of user interfaces **400** and **450** has been replaced with a deck selection area **702**.

[0358] Deck selection area **702** includes previews **704** of new decks that have been generated. Each preview **704** may, for example, be a thumbnail of the first page of a new deck. Selection area **702** also includes a scroll control **706** (allowing a user to navigate and view further previews **704** of new decks) and a back control **708** (which closes the preview area **704** and may, for example, cause the asset preview area **411** to be redisplayed).

[0359] In response to user input selecting a particular deck preview **704**, client application **232** causes that deck to be displayed. In this particular embodiment, on user input selecting a particular deck preview **704** the client application **232** displays a particular (e.g. the first) page of the selected deck in preview area **710**. A user can then view the different pages of the selected deck, e.g. by interaction with next/previous page controls **712/714**. In addition, a user may select a particular deck via selection control **716** which causes the selected deck to be opened in an editor UI (e.g. UI **400** described above) and allows the user to edit and save/publish (or otherwise output) the deck in the same way that any other deck is edited.

[0360] In addition, client application **232** provides controls (e.g. in region **420**) that allow a user to output a selected deck in various ways. These may include controls that allow a user to: save the deck (e.g. to local memory such as **310** or remote data storage such as **224**); to export the deck to a different format (e.g. an image format, a pdf format, a webpage format, or an alternative format) and save the exported deck (to local or remote storage); to publish the deck to a social media or

other publication service; to share the deck (e.g. via email, instant message, or other mechanism); to print the deck; to initiate and invite participants to an online presentation using the deck; and/or to output or use the deck in other ways.

[0361] Alternative user interfaces for viewing and/or editing new decks that are generated at **618** are possible.

[0362] In some embodiments, a new deck may automatically be generated for each destination deck that is identified in the deck generation data. In alternative embodiments, client application **232** (or content transfer module **234**) may be configured to initially generate only one (or a subset) of possible new decks, and only generate further decks upon receiving user input to do so. For example, a single new deck may be initially generated, and subsequent new decks only generated if a user activates a ‘view next deck’ user interface control (which may be displayed in a UI such as **700**).

[0363] As a further alternative, application **232** (or content transfer module **234**) may be configured to initially generate only a single page of each new deck and display these single pages as deck previews to a user (e.g. in a preview interface such as **702** described above). This allows a user to get a sense of the visual style of the new decks. If a user then selects a particular deck, that deck can be fully generated and displayed as described above.

Document-Format Design Analysis

[0364] Referring to FIG. **8**, a method **800** for processing a document to generate source analysis data will be described.

[0365] Method **800** may be performed as part of a deck generation process such as that described above with reference to FIG. **6** (and, for example, be initiated by server application **214** as described at **608** above).

[0366] In the present example, method **800** is described as being performed by design analysis application **216** (referred to as application **216** in this section for convenience). The processing described may, however, be performed by one or more alternative applications or modules.

[0367] Method **800** takes as input a document (or an identifier thereof) which will be referred to as the source document. An example document-format is described above. Generally speaking, however, the document-format design will define an ordered sequence of document items.

[0368] Generally speaking, method **800** operates to process the items of the source document to generate a set of source objects. Each source object corresponds to (or is associated with) what will be referred to as a source content segment (that is, part of the source content defined by the source document) and provides information concerning that source content segment. In this context the term “object” refers to a set of data. This may, for example, be a set of key/value pairs or any other appropriate data structure or set of related data structures.

[0369] At **802**, application **216** selects the next document item. In the present example, the source document items are processed in order (e.g. according to the order of the items in the source document's items array).

[0370] At **804**, application **216** determines if the selected item is a text type document item or a non-text document item (e.g. a block item such as a shape, chart, or table in the present examples). If the selected item is not a text item, processing proceeds to **806**. If the selected item is a text item, processing proceeds to **808**.

[0371] In the present embodiments, each non-text document item defines a single source content segment. In particular, a shape type document item defines a single fill, table type document item defines a single table, and a chart type document item defines a single chart. At **806**, application **216** generates a source object in respect of the (non-text) document item and adds the source object to a set of source objects (e.g. by appending to a source objects array). Generating source objects is described further below. Processing then proceeds to **814**.

[0372] In the present embodiments, a text document item may define one or multiple source content segments. Accordingly, at **808** application **216** selects the next content segment in the

selected (text) document item. To do so, application **216** processes the characters of text in the selected item in order, selecting characters until a segment end is reached. In the present embodiments, text segments correspond to vertically delineated spans of text—e.g. paragraphs, list items, and/or other vertically delineated spans of text. Accordingly, characters are selected until a paragraph break or the like is reached (e.g. a control character such as a new line character). [0373] At **810**, application **216** generates a source object in respect of the (text) content segment selected at **808** and adds the source object to a set of source objects (e.g. by appending to a source objects array). Generating source objects is described further below. Processing then proceeds to **812**.

[0374] At **812**, application **216** determines whether the end of the selected text item has been reached. If so processing proceeds to **814**. If the end of the selected document item has not been reached, processing proceeds to **808** to select the next text segment in the item.

[0375] To illustrate source content segments, consider the following simplified document record: TABLE-US-00013 docContent: [{“type”: “text”, “chars”:“Document heading./nFirst sub-heading/n”, ...}, {“type”: “shape”, ...}, {“type”: “text”, “chars”:“Second sub-heading /n”, ...}] [0376] For this example, application **216** would: [0377] determine a first content segment to be the characters “Document heading./n” of the first (text) item in the array; [0378] a second content segment to be the characters “First sub-heading/n” of the first (text) item in the array; [0379] a third content segment to be the fill content defined by the second (shape) item in the array; [0380] a fourth content segment to be the characters “Second sub-heading /n” of the third (text) item in the array;

[0381] At **814**, application **216** determines whether the end of the source document has been reached (e.g. all document items have been processed). If the end of the source document has not been reached (and unprocessed content segments remain), processing proceeds to **802**. Otherwise, processing proceeds to **816**.

[0382] At **816**, application **216** returns the source analysis data. In the present example, this is the set of one or more source objects that have been generated at **806** and **808**.

[0383] Generating a source object corresponding to a content segment at **806** or **808** involves determining and recording values for one or more source object attributes (referred to as source object attributes for short). The source objects that are generated at **804** are, ultimately, used in conjunction with destination objects (which are described above at **508** of FIG. 5). To facilitate this, source objects are generated to include the same (or at least comparable) attributes as those of destination objects.

[0384] In the present embodiments, source objects are generated to include one or more of the following source object attributes: [0385] a target identifier attribute (which, when referring to a source object, will be referred to as a source identifier); [0386] a content type attribute; [0387] a transfer-content attribute; [0388] a reading order attribute; [0389] a text hierarchy level attribute; [0390] a num lines attribute; [0391] a num chars attribute; [0392] a fill role attribute; [0393] an aspect ratio attribute.

These attributes are described further below. Additional and/or alternative source object attributes may be provided.

[0394] In the present embodiments, the source identifier attribute is generated for source objects corresponding to all content types.

[0395] The source identifier attribute is generated to identify the source content that the source object corresponds to. The precise manner in which source content is identified will depend on the document schema that is used.

[0396] In the context of the document schema described above, the source identifier attribute includes an item identifier that identifies a particular document item that the source object corresponds to (e.g. the index of the item in the document's items array).

[0397] For text content, and noting that a single text item may define multiple content segments,

additional source identifier attributes may be generated to identify the specific text of the content segment. In the present embodiment these include a first character index (indicating the first character of the content segment) and a character length value (indicating the number of characters in the content segment).

[0398] In alternative implementations, instead of providing a source identifier attribute that identifies the source content that a source object corresponds to, the actual source content may be added to the source object. Depending on the size of the content defined by a content segment this may be more appropriate for text type content segments than for fills or other content types.

[0399] In the present embodiments, a content type attribute is generated for source objects corresponding to all item types.

[0400] The content type attribute is generated to identify the type of source content that the source object corresponds to (that is, the type of content defined by the content segment that the source object corresponds to). In the present example, content types that match the content (and item) types described above, and matching the destination object content types described above are provided—e.g. text, fill, table, and chart types. As described above with reference to destination objects, more granular content types (or content sub-types) may be provided—e.g. content types (or sub-types) that define different types of fills.

[0401] In the present embodiments, a transfer-content attribute is generated for source objects corresponding to all content types.

[0402] The transfer-content attribute is generated to indicate whether the source content that the source object corresponds to defines content that is to be transferred when generating a new deck. The transfer-content attribute may be a Boolean (or other) variable that takes, for example, a value of true if the content of the source object should be transferred and a value of false if not.

[0403] Application **216** may be configured to determine that a particular content segment is or is not to be transferred based on various transfer criteria.

[0404] By way of example, for a text content segment, application **216** may be configured to determine that the content is to be transferred unless it includes solely non-alphanumeric characters. E.g., if application **216** determines that a text segment does not include any alphanumeric characters it may determine that the text content segment is not to be transferred and set a transfer-content value indicating this (e.g. transferContent=false).

[0405] As another example, application **216** may be configured to determine that a fill defined by a shape item is to be transferred unless it exceeds a defined aspect ratio. The defined aspect ratio may be set to try and capture fills that are relatively wide, which may indicate that the fill is being used as a separator. For example, if application **216** determines that a fill has an aspect ratio of greater than 10 (i.e. >10:1) it may determine that the fill is not to be transferred and set a transfer-content value indicating this (e.g. transferContent=false).

[0406] Application **216** may be configured to determine that all chart content and all table content are to be transferred and set transfer-content values for source objects corresponding to such content accordingly (e.g. transferContent=true).

[0407] Other criteria for determining whether source content is to be transferred or not may be applied.

[0408] Furthermore, in alternative implementations a transfer-content attribute need not be used. For example, application **216** may be configured to determine that all source content is to be transferred. As an alternative example, application **216** may be configured so that a source object is not generated for any source content that is determined not to be able to be transferred.

[0409] In the present embodiments, a reading order attribute is generated for source objects corresponding to all types of content for which the transfer content attribute is true.

[0410] The reading order attribute is generated to identify a position of the source content that the source object corresponds to in the document's reading order. For a document, the reading order is the order of the content segment in the document record. Reading order may, therefore, be

determined by application **216** setting an initial reading order value at the start of method **800** (e.g. a value of 0 or 1), recording the current reading order value at the generation of each source object (e.g. at **806** or **808**), and following the generation of a source object incrementing the reading order value.

[0411] In the present embodiments, a text hierarchy level attribute is only generated for source objects corresponding to text content segments.

[0412] The text hierarchy level attribute is generated to indicate the hierarchy level of text-type source content that the source object corresponds to. Text hierarchy levels are discussed above. In some instances, text items may already be associated with a text hierarchy level. If text hierarchy levels are not available, however, application **232** may be configured to analyse the text defined by the source document (e.g. as defined by text items of the source document) to determine text hierarchy levels and associate each text item (or separable text segment thereof) with a text hierarchy level. This may, for example, be done in accordance with method **3300** described below, however alternative approaches to determining text hierarchy levels may be used.

[0413] In the present embodiments, a num lines attribute is only generated for source objects corresponding to text content segments.

[0414] The num lines attribute is generated to indicate a vertical distance that the text-type source content that the source object corresponds to may occupy. In the present embodiments, application **216** is configured to calculate the num lines attribute by estimating a number of wrapped lines defined by the content segment. Application **216** estimates the number of wrapped lines based on a defined line width and the number of characters in the content segment. The defined line width is selected to be comparable to a likely destination element that the text may be transferred to. Any appropriate defined line width may be used, for example a width of 80 characters or an alternative width.

[0415] In the present embodiments, a num chars attribute is only generated for source objects corresponding to text content segments.

[0416] The num chars attribute is generated to indicate the number of characters defined by the text-type source content that the source object corresponds to.

[0417] In the present embodiments, a fill role attribute is only generated for source objects corresponding to shape content segments.

[0418] The fill role attribute is generated to indicate whether the fill content that the source object corresponds to is a complete fill (with no transparencies) or a partial fill (with one or more transparencies).

[0419] In the present embodiments, an aspect ratio attribute is not generated for source objects corresponding to text content segments, but is generated for source objects corresponding to other source content types (e.g. chart, shape, and table type content segments).

[0420] The aspect ratio attribute is generated to indicate the aspect ratio of the source content that the source object corresponds to. With the example element record schema described above, application **216** may determine the aspect ratio attribute based on relevant size data—e.g. width/height.

[0421] To further illustrate source objects, and by way of example only, a source object corresponding to a text content segment defined by a first document item is as follows:

```
TABLE-US-00014 {  "sourceID": {      "itemID": 0, // indicating the first item in the
document's items array      "firstCharIndex": 0, // indicating the content starts at character index 0
      "charLength": 25 // indicating the content is 48 characters long  },  "type": "TEXT",
"transferContent": true,  "readingOrderIndex": 1,  "textHierarchyLevel": 1,  "numLines": 1,
  "numChars": 24 }
```

[0422] An example source object corresponding to a second text content segment defined by the first document item above is as follows:

```
TABLE-US-00015 {  "sourceID":      "itemID": 0, // indicating the first item in the document's
```

items array "firstCharIndex": 25, // indicating the content starts at character index 25
"charLength": 17 // indicating the content is 17 characters long }, "type": "TEXT",
"transferContent": true, "readingOrderIndex": 2, "textHierarchyLevel": 2, "numLines": 1,
 "numChars": 16 }

[0423] By way of further example, a source object corresponding to a fill segment (corresponding to a shape-type document item) is as follows:

TABLE-US-00016 { "sourceID": { "itemID": 1, // indicating the second item in the
document's items array }, "type": " FILL", "transferContent": true, "readingOrderIndex":
3, "fillRole": "complete", "aspectRatio": 0.5666415662650801 }

Pagination Data Generation

[0424] Referring to FIG. 9, an example method **900** for generating pagination data for a source document will be described.

[0425] Method **900** may be performed as part of a document to deck generation method (and, for example, be initiated by server application **214** as described at **610** above).

[0426] In the present example, method **900** is described as being performed by pagination application **218** (referred to as application **218** in this section for convenience). The processing described may, however, be performed by one or more alternative applications or modules.

[0427] In the present example, method **900** takes as input source analysis data that corresponds to a source document. Generally speaking, source analysis data defines a set of one or more source objects, each source object corresponding to particular source document content (e.g. a source document content segment as described above with reference to FIG. 8). Source analysis data may, for example, be generated according to method **800** described above. In the present example, the set of source objects is initially ordered based on the order of the source content in the source document. For example, the set of source objects may be ordered based on their reading order value.

[0428] Method **900** generates and returns pagination data. In the present embodiments, the pagination data is a set (e.g. an array) of one or more pagination candidates. Each pagination candidate is a set (e.g. an array) of one or more candidate pages. Each candidate page is a set (e.g. an array) of source objects (and, as described above, each source object corresponds to particular content of the source document). Each pagination candidate represents a complete pagination solution for the source document. That is, for a given pagination candidate each relevant source object in the source analysis data (and, therefore, all relevant source document content) is associated with at least one candidate page of that pagination candidate.

[0429] Any appropriate data structure may be used for the pagination data. By way of example, pagination data may be a set (e.g. an array) of pagination candidates, with each pagination candidate being a set (e.g. an array) of candidate pages. E.g.:

TABLE-US-00017 results: [[{candidate page 1}], // pagination candidate 1 [{candidate page 1}, // pagination candidate 2 {candidate page 2}, ...], ... [{candidate page 1}, // pagination candidate n {candidate page 2}, ...],]

[0430] Each candidate page may be defined by a candidate page record. The candidate page record for a given candidate page may include a set (e.g. an array) of source objects (or identifiers thereof). In the present embodiment, a candidate page record may also include a split level value and a page score (both of which are used in determining pagination candidates and are described below).

[0431] Any appropriate data structure may be used to record a candidate page. By way of example, a candidate page record may be as follows:

TABLE-US-00018 candidatePage: { "sourceObjects": [{source object 0}, ... {source object n}], "splitLevel": -1, "pageScore": null }

[0432] At **901**, application **218** initialises a results set (e.g. a list or array or other ordered dataset). The results set is initialised as an empty set, and pagination candidates are added to it over the

course of method **900**.

[0433] At **902**, application **218** generates an initial pagination candidate and adds this to the results set. The initial pagination candidate includes a single candidate page that includes all content of the source document (in this case represented by all source objects of the source document's analysis data). The split level value for the candidate page generated at **902** is either null or a value indicating that no split has yet been performed (e.g. -1 or an alternative value). A page score value for the initial candidate page is computed at **904**.

[0434] At **904**, application **218** computes a page score for the or each new candidate page in the last pagination candidate that was added to the result list. The page score for a candidate page is a measure of how well (or how poorly) the content defined by that candidate page is likely to fit a page of an available template deck. In the present embodiment each candidate page's page score is associated with the candidate page (e.g. via the "pageScore" attribute above).

[0435] A method **1000** for calculating a page score for a particular candidate page (at **904**) is described with reference to FIG. **10**.

[0436] At **1002**, application **218** generates content metrics data for the candidate page. The content metrics generated for a candidate page allows for broad, content-based comparisons between the candidate page and available template pages to be performed. To this end, the content metrics generated at **1002** are generated to include the same (or at least corresponding) values as the content metric values generated for template pages (described above with reference to **516** of FIG. **5**). Application may generate content metrics itself at **1002**, or may generate/send a request to the design analysis application **216** to do so.

[0437] In the present embodiment, therefore, the content metrics data generated for a candidate page includes the following values. The prefix CM may be used to indicate content metric. [0438] A CM characters value that is based on the number of characters on the candidate page. In the present embodiment, the CM characters value is the logarithm of the total number of characters defined by the candidate page's text type source objects. The characters value may alternatively be the actual number of characters (or an alternative value based thereon). [0439] A CM lines value based on the number of lines of text on the candidate page. In the present embodiment, the CM lines value is the logarithm of the total number of lines defined by the candidate page's text type source objects. The lines value may alternatively be the actual number of lines (or an alternative value based thereon). [0440] A CM fills value based on the number of fills on the candidate page. In the present embodiment, the CM fills value is the number of fill type source objects, however an alternative value based on that number may be used. [0441] A CM tables value based on the number of tables on the candidate page. In the present embodiment, the CM tables value is the number of table type source objects, however an alternative value based on that number may be used. [0442] A CM charts value based on the number of charts on the candidate page. In the present embodiment, the CM charts value is the number of chart type source objects, however an alternative value based on that number may be used.

[0443] In the present embodiment, only source objects that have a "transfer-content" attribute that is true contribute to content metric values. In addition, while the content metric values are described as being based on a candidate page's source objects they could instead be based on the actual source content (e.g. the source document content items).

[0444] At **1004**, application **218** calculates a viable template pages value for the candidate page.

[0445] The viable template pages value is based on a number of template pages that application **218** identifies to be viable for the particular candidate page. Generally speaking, application **218** determines that a particular template page is viable for a particular candidate page if the elements of the template page appear, at least at a broad level, to be capable of accommodating the content of the candidate page.

[0446] In the present embodiment, application **218** determines whether a particular template page is a viable fit for the candidate page based on the candidate page's content metrics data (generated at

1002) and the particular template page's content metrics data (which, in the present embodiment, is determined at **516** of method **500** when analysing the template page). In particular, application **218** determines that a particular template page is viable for the candidate page if the following conditions are met: [0447] Candidate page CM characters value \leq Template page CM characters value AND [0448] Candidate page CM lines value \leq Template page CM lines value AND [0449] Candidate page CM fills value \leq Template page CM fills value AND [0450] Candidate page CM tables value \leq Template page CM tables value AND [0451] Candidate page CM charts value \leq Template page CM charts value

[0452] Application **218** evaluates the candidate page against each template page in a set of template pages (which may be all available template pages or a subset thereof). Application **218** then records the number of template pages that are determined to be viable as the viable template pages value.

[0453] At **1006**, application **218** calculates a potential template pages value. In the present example, the potential template pages value is calculated by determining the different types of content on the candidate page (based on the types of the candidate page's source objects) and then determining the number of template pages that include at least one element of each of those types.

[0454] To illustrate this, consider a candidate page that includes a text-type source object and a table-type source object. If there are 100,000 template pages available, and of those: 40,000 template pages include a text-type element (or a text-type template page source object corresponding to such an element); and **500** template pages include a table-type element (or a table-type template page source object corresponding to such an element), then the potential template pages value is calculated as $\min(40000, 500) = 500$.

[0455] At **1008**, application **218** calculates a page score for the candidate page. In the present embodiment, the page score is calculated as the viable template pages value (calculated at **1004**) divided by the potential template pages value (calculated at **1006**).

[0456] Continuing with the above example, if the viable template pages value for the candidate page with a text-type source object and a chart-type source object was 300, and the potential template pages value was 500, then the page score for the candidate page would be $300/500 = 0.6$.

[0457] Returning to **906** of FIG. 9, once a page score has been calculated for each new candidate page in the last pagination candidate, application **218** determines if the last pagination candidate in the results set defines any splittable candidate pages. If so, processing proceeds to **908**. If not, processing proceeds to **916**.

[0458] In the present embodiments, application **218** determines that a candidate page can be split if it includes more than one text-type source object (e.g. if it has more than one source object that corresponds to a text content segment).

[0459] At **908**, application **218** selects a particular candidate page from the last pagination candidate to split. The selected candidate page will be referred to as the focal page. Application **218** determines the focal page to be the splittable candidate page from the last pagination candidate that has the lowest (or equal lowest) page score. If two splittable candidate pages have the same (equal) lowest page score, either may be selected as the focal page. For example, application **218** may select the first candidate page in the last pagination candidate with the equal lowest page score.

[0460] At **910**, application **218** determines a text hierarchy level that is to be used to split the focal page. This will be referred to as the split level. Application **218** determines the split level to be the next available text hierarchy level. This is the text hierarchy level that: occurs in the focal page; and is the next highest text hierarchy level after the split level that was used to create the focal page itself (In the present embodiments, text hierarchy level 1 is the highest, level 2 is the next highest, and so forth.)

[0461] In the present embodiment, the text hierarchy levels that occur in the candidate page are determined by reference to the text hierarchy level attributes of the candidate page's source objects. Further, the split level that was used to create the focal page itself is determined by reference to the split level attribute of the focal page. For example, if the splitLevel of the focal page was a value

indicating no split level has been used (e.g. -1, indicating that the focal page is the initial candidate page that was generated), application **218** will use text hierarchy level 1 (or the next highest text hierarchy level) to split the focal page into new pages. As another example, if the splitLevel of the focal page was 3 (indicating the focal page was generated by splitting a previous candidate page using text hierarchy level 3), application **218** will use text hierarchy level 4 (or the next highest text hierarchy level) to split the focal page into new pages.

[0462] At **912**, application **218** generates two or more new candidate pages. This is done by splitting the focal page identified at **908** using the split level determined at **910**. Generating new candidate pages can be done in various ways. An example method **1100** for splitting a focal page at **912** is described with reference to FIG. **11**.

[0463] At **1102**, application **218** generates anew candidate page (this will be referred to as the open page).

[0464] At **1104**, application **218** adds the first source object of the focal page to the open page. This serves to add the content segment defined by the first source object to the open page.

[0465] At **1106**, application **218** selects the next source object (and, therefore, the next content segment) of the focal page. Focal page source objects are selected in order (e.g. based on the order of source objects in the focal page's source objects array).

[0466] At **1108**, application **218** determines if the content segment of the selected source object is text content. In the present embodiment, this determination is based on the content type attribute of the selected source object. If the content segment is text content, processing proceeds to **1110**. Otherwise processing proceeds to **1116**.

[0467] At **1110**, application **218** determines if the text hierarchy level of the text content of the selected source object is equal to the split level determined at **910**. If so, processing proceeds to **1112**. Otherwise, processing proceeds to **1116**.

[0468] At **1112**, application **218** has determined that the selected source object defines text content at a text hierarchy level equal to the split level. In this case, application **218** closes the currently open candidate page. On closing the open page, application **218** associates the split level with the candidate page (e.g. via a split level attribute as described above), though this can be done at any appropriate time.

[0469] At **1114**, application **218** generates a new candidate page. This becomes the open page.

[0470] At **1116**, application **218** adds the selected source object to the open candidate page. This serves to add the content segment defined by the selected source object to the open page.

[0471] At **1118**, application **218** determines whether the focal page includes any further source objects (or, therefore, any further content segments). If so, processing proceeds to **1106** to select and process the next source object (and the next content segment defined by that source object). If all focal page source objects (and, therefore content segments) have been processed, processing proceeds to **1120**.

[0472] At **1120**, application **218** closes the open page (e.g. as described at **1112**). Splitting the focal page is then complete.

[0473] To illustrate splitting a focal page, consider a focal candidate page with **12** source objects as indicated by the array below.

TABLE-US-00019 candidatePage: { “sourceObjects”: [{S1, L1}, {S2, L2}, {S3, Ø}, {S4, L3}, {S5, L3}, {S6, Ø}, {S7, L4}, {S8, L1}, {S9, L2}, {S10, Ø}, {S11, L1}, {S12, L2}],
 “splitLevel”: -1, “pageScore”: 0.2 }

[0474] For ease of illustration, each source object in this example candidate page includes only a source identifier (indicated by the letter S) and either a text hierarchy level value (indicated by the letter T) or a Ø (indicating that the source object does not correspond to a text type content segment). In this example, therefore: source object {S1,L1} has a source identifier of “1” and a text hierarchy level hierarchy of “1”; source object {S3, Ø} has a source identifier of “3” and does not correspond to a text type content segment. If this hypothetical candidate page was identified (at

908) as the focal page, then application **218** would determine the split level (at **910**) to be 1 and generate three new candidate pages at **912**:

TABLE-US-00020 candidatePage: { //the first new candidate page “sourceObjects”: [{S1, L1}, {S2, L2}, {S3, \emptyset }, {S4, L3}, {S5, L3}, {S6, \emptyset }, {S7, L4}], “splitLevel”: 1, “pageScore”: } candidatePage: { //the second new candidate page “sourceObjects”: [{S8, L1}, {S9, L2}, {S10, \emptyset }], “splitLevel”: 1, “pageScore”: } candidatePage: { //the third new candidate page “sourceObjects”: [{S11, L1}, {S12, L2}], “splitLevel”: 1, “pageScore”: }

[0475] Returning to FIG. 9, at **914**, application **218** generates a new pagination candidate and adds this to the end of the results list (e.g. by appending it to the end of the result list). The new pagination candidate is generated to include all candidate pages of the previous pagination candidate (in their original order) except for the focal page. In the new pagination candidate, the focal page from the previous pagination candidate is replaced by the new candidate pages generated at **912** (in the order in which they were generated). Processing then proceeds to **904** (to compute candidate pages scores and determine if further candidate pages can be split).

[0476] At **916**, application **218** has determined that the last pagination candidate that was generated does not include any splittable candidate pages. At this point application **218** selects one or more pagination candidates that are to be returned.

[0477] By generating pagination candidates and adding them to the result list as described above, the pagination candidates in the result list will be naturally ordered from the most content-dense pagination candidate (the pagination candidate having the fewest candidate pages and, in this case, appearing at the start of the result list) to the least content-dense pagination candidate (the pagination candidate having the most candidate pages and, in this case, appearing at the end of the result list).

[0478] In certain embodiments, application **218** is configured to return a maximum number of pagination candidates. The maximum number of pagination candidates may be an input (along with the input source analysis data) to method **900** and determined (e.g. by server application **214**) based on product requirements. Alternatively, the maximum number may be a defined number (e.g. 5, 10, or an alternative maximum number). Further alternatively, application **218** may be configured to determine a number of pagination candidates to return. For example, application **218** may be configured to return a minimum of 2 and a maximum of 60% (or an alternative percentage) of the number of pagination candidates.

[0479] Once the number of pagination candidates that are to be returned has been determined (if required), application **218** selects the specific pagination candidates that are to be returned. This may be done in various ways. In one embodiment, application **218** is configured to ignore (e.g. discard or not select) any pagination candidate that includes a candidate page with a page score of 0. This may be the case for one or more of the candidate pages that are generated early in the process. For example, in the approach described the initial pagination candidate generated at **902** includes a single candidate page with all content of the source document. In many cases, this page may give a page score of 0 (e.g. due to the entire content of the source document including too much content for any single template page). After ignoring any pagination candidates that have one or more candidate pages with a page score of 0, application **218** may select the required number of pagination candidates by evenly sampling from the remaining pagination candidates in the result list. E.g. if the result list includes x remaining pagination candidates and n pagination candidates have been requested, application **218** may generate the pagination data to include every (floor (x/n)).sup.th pagination candidate from the remaining pagination candidates in the result list.

[0480] In alternative embodiments, application **218** may be configured to select all pagination candidates at **916** (or may be configured to select all pagination candidates except the first and last pagination candidates).

[0481] At **918**, application **218** returns the pagination candidates selected at **916** as the pagination data.

[0482] In certain embodiments, application **218** may be configured to identify text-type content segments that exceed a defined length and split those content segments. In the present examples, where content segments are associated with source objects, this is done by determining whether the num chars attribute of any source object exceeds a defined maximum number of characters. If a source object does have a content segment that exceeds the maximum number of characters, application **218** splits that source object into two or more new source objects.

[0483] The defined number of characters may be a set number, or may be periodically calculated. For example, application **218** may be configured to periodically calculate the maximum number of characters based on the template deck pages that are available. For example, application **218** may calculate the total number of characters on each template page available, then take the top xth (e.g. 99.sup.th) percentile and use that as the maximum number of characters.

[0484] In the present embodiment, where the content segment of a source object exceeds the maximum number of characters, application **218** splits the source object (and, therefore, the content segment defined by that source object) by identifying a last defined split character (e.g. a period, an exclamation mark, or an alternative split character) before the defined maximum number of characters and then creating a new source object for the characters up to and including that split character. The new source object will take the attributes of the original source object, except the charLength attribute will change to reflect the selected characters. The new source object is then added to the set of source objects before the original source object, and the firstCharIndex and charLength of the original source object are changed (to reflect the characters that have been removed from that source object). The (now changed) original source object can then be analysed and processed in the same way, and split further if it still defines too many characters.

[0485] Where application **218** is configured to split source objects that have content segments with too many characters this may be done at any appropriate time. For example, application **218** may analyse and split all source objects at the very beginning (e.g. before **902**). Alternatively, application **218** may analyse and split source objects at (or following) **912** (when new candidate pages are generated). Further alternatively, such analysis and splitting may be performed at the time of generating the source analysis data (e.g. when determining the next content segment at **802**).

[0486] To further illustrate pagination method **900**, consider the example document **1200** shown in FIG. **12**. This example document includes: two text-type content segments **1202** and **1218** which have text hierarchy level 1; two text-type content segments **1208** and **1216** which have text hierarchy level 2; two text-type content segments **1206** and **1214** which have text hierarchy level 3; two text-type content segments **1210** and **1212** which have text hierarchy level 4; and two fill-type content segments **1204** and **1220**. Simplified source objects for document **1200** (in which each source object includes only the text hierarchy level of the corresponding content segment or a 'Ø' indicating a non-text type content segment) may be represented as follows: [0487] [{1}, {Ø}, {3}, {2}, {4}, {4}, {3}, {2}, {1}, {Ø}]

[0488] FIG. **13** provides a representation of a segment tree **1300** that corresponds to document **1200** (and, in particular, to the analysis data above). Each node of segment tree **1300** indicates a candidate page, and each row indicates a pagination candidate. Each node is labelled with text in the form "PCx-y", where PC stands for pagination candidate, x indicates the pagination candidate number, and y indicates the candidate page number. E.g. the node labelled "PC3-2" indicates candidate page 2 of pagination candidate 3. Each node further indicates the set of source objects that have been assigned to the candidate page, a hypothetical page score, and a split level.

[0489] In generating the pagination candidates for example document **1200**, application **218** initially (at **902**) generates the initial pagination candidate which includes a single candidate page (node PC1-1 of tree **1300**).

[0490] In the first processing loop (**906** to **914**), a split level of 1 is determined (at **910**) and a second pagination candidate is generated that includes candidate pages indicated by nodes PC2-1 and PC2-2 of tree **1300**.

[0491] In the next processing loop (**906** to **914**): candidate page PC2-1 has the lowest page score and is identified as the focal page (at **908**); a split level of 2 is determined (at **910**); new candidate pages PC3-1, PC3-2, and PC3-3 of tree **1300** are generated (at **912**); and new pagination candidate is generated.

[0492] Processing continues in this manner, which leads to a set of pagination candidates as follows:

```
TABLE-US-00021 [  [[{1},{Ø},{3},{2},{4},{4},{3},{2},{1},{Ø}]] // pagination candidate 1
[[{1},{Ø},{3},{2},{4},{4},{3},{2}],[{1},{Ø}]] // pagination candidate 2  [[{1},{Ø},{3}],[{2},
{4},{4},{3}],[{2}],[{1},{Ø}]] // pagination candidate 3  [[{1},{Ø},{3}],[{2},{4},{4}],[{3}],
[{2}],[{1},{Ø}]] // pagination candidate 4  [[{1},{Ø},{3}],[{2}],[{4}],[{4}],[{3}],[{2}],[{1},
{Ø}]] // pagination candidate 5  [[{1},{Ø}],[{3}],[{2}],[{4}],[{4}],[{3}],[{2}],[{1},{Ø}]] //
pagination candidate 6 ]
```

[0493] Application **218** then selects specific pagination candidates to return (at **916**) and returns the selected candidates as pagination data at **918**. For example, pagination candidates 2, 3 and 4 may be selected.

Template Matching and Deck Generation Data

[0494] Turning to FIG. **14**, an example method **1400** for generating deck generation data will be described.

[0495] Method **1400** is described as being performed by template matching application **220** (referred to as application **220** in this section for convenience). The processing described may, however, be performed by one or more alternative applications or modules.

[0496] Method **1400** may be performed as part of a document to deck design generation process that is operating to generate a new deck based on a source document. In this case, method **1400** may be initiated by server application **214** as described at **612** above. When initiated at **612** described above, method **1400** takes as input pagination data. Pagination data may, for example, be generated according to method **900** described above (or a similar method). Generally speaking, such pagination data will define one or more pagination candidates. Each pagination candidate will include one or more candidate pages, and each candidate page will be associated with source document content. In the present example, each candidate page includes a set of one or more source objects (each source object being associated with source content defined by the source document).

[0497] Method **1400** may also (or alternatively) be performed as part of a deck to deck design generation process. In this case, method **1400** (or a modified version thereof) may be initiated by server application **214** as described at **2810** of method **2800** below. When initiated at **2810**, method **1400** takes as input a single pagination candidate: that is, a single set of one or more candidate pages, each candidate page corresponding to a page of a source deck. Each candidate page will include a set of one or more source objects that corresponds to the source content of the original source deck page.

[0498] In the present example, method **1400** generates deck generation data that can be used to generate one or more new decks based on the source content of the original source document. Deck generation data is described further below.

[0499] Initially, and as generally indicated at **1401**, application **220** identifies one or more matching templates for each pagination candidate and calculates a set of final template scores for each (pagination candidate, template) pairing. This involves processing blocks **1402-1418**. Where multiple pagination candidates are to be processed, the processing blocks of **1401** may be performed on each pagination candidate in sequence or in parallel.

[0500] In order to illustrate the processing performed at **1401**, a simplified example will be described alongside the description of processing blocks **1402-1418**. The simplified example is based on a pagination candidate that includes three candidate pages—e.g.:

```
TABLE-US-00022 //candidate page 1 source objects [  {"sourceID": 1, "type": "text",
"num_lines": 1}, //analysis item 0.1 ], //candidate page 2 analysis items [  {"sourceID": 2, "type":
```

```

"shape", "aspect_ratio": //analysis item 1.1 0.7},] //candidate page 3 analysis items [
{"sourceID": 3, "type": "text", "num_lines": 1}, //analysis item 2.1 {"sourceID": 4, "type":
"text", "num_lines": 1}, //analysis item 2.2 {"sourceID": 5, "type": "text", "num_lines": 1}
//analysis item 2.3 ]

```

[0501] The simplified example also assumes three available templates. Template 1 has a first page with a single text element and a second page with three text elements. Template 2 has a first page with a single text element, a second page with a single shape element, and a third page with a single text element. Template 3 has a single page with a single shape element. Simplified analysis data for such a template is as follows:

```

TABLE-US-00023 { //template 1 { "templateID": "template1", "pages": [
{"analysisItems": [{"type": "text", "destID": 1, "num_lines": 1}], //template 1 page 1 {
"analysisItems": [ //template 1 page 2 {"type": "text", "destID": 1,
"num_lines": 1}, {"type": "text", "destID": 2, "num_lines": 1}, {"type":
"text", "destID": 3, "num_lines": 1}, ] }, ], }, //template 2 {
"templateID": "template2", "pages": [ {"analysisItems": [{"destID": 1, "type":
"text", "num_lines": 3}], //template 2 page 1 {"analysisItems": [{"destID": 2, "type":
"shape", "aspect_ratio": 2}], //template 2 page 2 {"analysisItems": [{"destID": 3, "type":
"text", "num_lines": 1}], //template 2 page 3 ], }, //template 3 { "templateID":
"template3", "pages": [ {"analysisItems": [{"destID": 1 "type": "shape", aspect_ratio:
1}]} //template 3 page 1 ], }, }

```

[0502] For these three example templates, simplified page partition keys that include only a count of the number of texts and a count of the number of shapes would be as follows:

```

TABLE-US-00024 Template Page Partition key 1 1 [1, 0] // 1 text 0 shapes 1 2 [3, 0] // 3 texts 0
shapes 2 1 [1, 0] // 1 texts 0 shapes 2 2 [0, 1] // 0 text 1 shape 2 3 [1, 0] // 1 texts 0 shapes 3 1 [0, 1]
// 0 text 1 shape

```

[0503] In the present example, application **220** generates a set of one or more candidate page rewrites for each candidate page in the pagination candidate at **1402**. Each rewrite of a candidate page generally describes a different way in which the candidate page's source content (as defined by its set of source objects) can be grouped. In the present embodiment, each rewrite of a candidate page includes (or references) a set of one or more source objects.

[0504] When generating the one or more rewrites of a candidate page, application **220** will generate what will be referred to as an original rewrite (or an original version) of the candidate page. The original rewrite of a candidate page includes the same set of source objects that the candidate page itself includes.

[0505] In certain cases, application **220** may also generate one or more new rewrites of a candidate page. Any new rewrite of a candidate page may include at least one source object that identifies (or corresponds to) two or more of the candidate page's original source objects. A source object such as this may be referred to as a combined source object. If a rewrite includes a combined source object it will also include rewrite mapping data (which indicates the original source objects that map to the combined source object) and rewrite penalty data. The rewrite penalty data can be used when calculating a score that involves the rewrite (discussed below). The rewrite penalty data may be a value that can be directly used which calculating a score, or may be other data concerning the rewrite that can be used to determine a penalty value. As one example, the penalty data may provide information on the number and type of source objects (and/or the attributes of those objects) that have been combined.

[0506] In certain implementations, application **220** may be configured to generate a new rewrite by (if possible) generating a combined source object that corresponds to two or more original text type source objects. In particular, application **220** is configured to identify a span of text type source objects that could be assigned to a single text type element when generating a new deck (rather than being assigned to separate text elements). In this context, a span of text type source objects are

a set text type source objects that have contiguous reading order values. In the present embodiment, application **220** identifies a candidate text type source object by iterating from the top text hierarchy level down and finding the first text hierarchy level with more than one text-type source object (this text hierarchy level may be referred to as merge top). That merge top level and all subsequent text hierarchy levels are then considered for merging into a single text type source object. To do this, application **220** rewrites those several text type source objects as a single combined source object. In doing so, application **220**: combines relevant attributes such as num_lines and num_chars based on the original source objects that are being merged; assigns the combined source object a text hierarchy level value that is equal to the merge top value; and mapping the original source objects to the combined source object to ensure that all original texts are assigned to the same element when generating a new deck/transferring source content to that new deck.

[0507] To illustrate rewrites, consider the example candidate pages described above: [0508] When generating the set of rewrites for candidate page 1, an original rewrite of the candidate page is generated to include the original source objects of the candidate page. No other rewrites of candidate page 1 are generated. [0509] When generating the set of rewrites for candidate page 2, a single (original) rewrite is generated. [0510] When generating the set of rewrites for candidate page 3, an original rewrite is generated. In addition, anew rewrite is generated in which the three adjacent text analysis items of the candidate page are combined into (or mapped to) a single combined source object.

[0511] An example of a simplified representation of these rewrites is as follows:

```
TABLE-US-00025 //candidate page 1 rewrites [ // rewrite 1 (e.g. the original rewrite) {
    "sourceObjects": [ { "sourceID": 1, "type": "text", "num_lines": 1}, // source object 1
    ] } ] //candidate page 2 rewrites [ // rewrite 1 (e.g. the original rewrite) {
    "sourceObjects": [ { "sourceID": 2, "type": "shape", "aspect_ratio": 0.7}, // source
object 1 ] } ] //candidate page 3 rewrites [ // rewrite 1 (e.g. the original rewrite) {
    "sourceObjects": [ { "sourceID": 3, "type": "text", "num_lines": 1}, // source object 1
    { "sourceID": 4, "type": "text", "num_lines": 1}, // source object 2 { "sourceID": 5,
"type": "text", "num_lines": 1} // source object 3 ] }, // rewrite 2 {
    "mappingData": {3: 1, 4: 1, 5: 1}, // mapping data "mappingPenalty": [x], // mapping
penalty "sourceObjects": [ { "ID": 1, "type": "text", "num_lines": 3} // combined
source object 1 ] } ]
```

[0512] As can be seen, for the original rewrites no mapping data or mapping penalty is required. For the further rewrite candidate page 3, mapping data and a mapping penalty is provided. The mapping data is a set of (source object ID: combined source object ID) pairs, each pair mapping an original source object of the candidate page to a combined source object. In this example, all three source objects of candidate page 3 are mapped to a single combined source object (with identifier "1"). The mapping penalty provides data that can be used to apply a penalty to the rewrite.

[0513] In alternative embodiments, application **220** need not generate any candidate page rewrites (and may instead consider only the original candidate page in further processing).

[0514] At **1404**, application **220** generates a rewrite partition key for each candidate page rewrite generated at **1402**. Rewrite partition keys are generated to allow potential (rewrite, template page) matches to be determined (described below at **1408**). To facilitate this, rewrite partition keys are generated to include the same (or at least comparable) attributes as those of the deck page partition keys.

[0515] In the present embodiment, therefore, application **220** generates rewrite partition keys that include values that correspond to the deck page partition key values described at **512** of method **500** above—e.g.: [0516] a PK text value; [0517] a PK fills value; [0518] a PK charts value; and [0519] a PK tables value.

[0520] In the present embodiment, each of these rewrite partition key values is calculated or

determined in the same (or a similar) manner to the way its corresponding template page partition key value is calculated or determined (as described above at **512**). The exception is that while template page partition key values are generated with reference to certain attributes of a template page's destination objects, rewrite partition key values are generated with reference to certain (corresponding) attributes of a rewrite's source objects (which may include one or more combined source objects).

[0521] Continuing with the simple worked example, however, in which partition keys include only a count of the number of texts and a count of the number of fills, the partition keys for the rewrites are as follows:

TABLE-US-00026 Candidate page Rewrite Partition key 1 1 [1, 0] // 1 text 0 fills 2 1 [0, 1] // 0 texts 1 fill 3 1 [3, 0] // 3 texts 0 fills 3 2 [1, 0] // 1 text 0 fills

[0522] At **1406**, application **220** generates a candidate page vector for the candidate page being processed. Candidate page vectors are generated to allow for (rewrite, template) scores to be calculated (as described below at **1416**). To facilitate this, candidate page vectors are generated to include the same (or at least comparable) attributes as those of template page vectors. In the present embodiment, a candidate page's vector will be the same for any rewrites of the candidate page. In alternative embodiments, a rewrite vector may need to be generated for each different candidate page rewrite.

[0523] In the present embodiment, therefore, application **220** generates candidate page vectors that include values that correspond to the values of the template page vectors described at **514** of method **500** above. In particular, application **220** generates candidate page vectors that include: a character value for each text hierarchy level 1 to 6; [0524] a line value for each text hierarchy level 1 to 6; [0525] a min fill aspect ratio value; [0526] a max fill aspect ratio value; [0527] a partial fills value; [0528] a complete fills value; [0529] a min tables aspect ratio value; [0530] a max tables aspect ratio value; [0531] a min charts aspect ratio value; and a [0532] max charts aspect ratio value.

[0533] In the present embodiment, each of these candidate page vector values is calculated or determined in the same (or a similar) manner as its corresponding template page vector value (as described above at **514**). The exception is that while a template page vector is generated with reference to certain attributes of the template page's destination objects (and the content that the template page can accommodate), a candidate page vector is generated with reference to certain (corresponding) attributes of a candidate page's source objects (and, therefore, the source content that needs to be transferred to/accommodated by a template page). Further, in the present example, each candidate page vector value is calculated only with reference to source objects (and, therefore, the source content those objects correspond to) that have a "transfer content" attribute value that indicates source content that is to be transferred.

[0534] At **1408**, application **220** identifies potential (rewrite, template page) matches. These may be referred to as potential page matches for convenience. In the present embodiment, for each rewrite application **220** identifies which (if any) template pages are a potential match for that rewrite.

[0535] In the present embodiment, application **220** determines whether a particular template page is a potential match for a particular rewrite based on the template page partition key and the rewrite partition key. In particular, if all of a rewrite's partition key values match all of a template page's corresponding partition key values, application **220** determines that the rewrite and the template page are a potential match. Otherwise the template page is not a potential match.

[0536] As described above, in certain embodiments the partition key fills values of the template page and rewrite page indicate specific numbers of fills. In these embodiments, therefore, a template page will only be a potential match for a rewrite if the number of fills that the shape elements of the template page define is equal to the number of source content fills. In alternative embodiments, the partition key fills values instead take a Boolean (or other value) that only indicates whether the template page includes at least one shape element that can accommodate one

or more fills and whether the rewrite's source content includes one or more fills. In this case, if a rewrite defines one or more fills (and has a fills value of true) a template page will match if it also has a fills value of true (and therefore includes at least one shape element that can accommodate at least one fill). Whether the partition key fills values define an actual number of fills or a Boolean impacts how source fills are transferred as is discussed further below.

[0537] Application **220** may record potential (rewrite, template page) match data in any appropriate data structure. For illustrative purposes, the below table represents such data for the example template pages and rewrites described above:

TABLE-US-00027 Rewrite 1 Rewrite 2 Candidate template1: (page 1) NA page 1 template2: (page 1, page 3) Candidate template2: (page 2) NA page 2 template3: (page 1) Candidate template1: (page 2) template1: (page 1) page 3 template2: (page 1, page 3)

[0538] In this example, each internal cell of the table represents a specific rewrite of a specific candidate page and indicates which (if any) template pages match that specific rewrite. From this table it can be seen, for example, that potential template page matches for rewrite 1 of candidate page 1 are: template 1 page 1; template 2 page 1, and template 2 page 3.

[0539] At **1410**, application **220** calculates a preliminary template score for each template. In the present embodiment, a template's preliminary score is based on the number of candidate pages of the pagination candidate being processed that the template provides at least one potentially matching page for. Application **220** determines that a template page is a potential match for a candidate page if that template page is a potential match for any of that candidate page's rewrites (which in this example has been determined at **1408**).

[0540] Continuing the above example, the preliminary template scores (and preliminary template ranking) would be as follows:

TABLE-US-00028 template1: 2 //template 1 matches two candidate pages: 1 and 3 template2: 3 //template 2 matches three candidate pages: 1, 2, and 3 template3: 1 //template 3 matches one candidate page: 2

[0541] Based on the preliminary template scores application **220** can preliminarily rank the templates for the pagination candidate being processed.

[0542] At **1412**, application **220** preliminarily selects one or more templates for further analysis. This selection is based on the preliminary template scores calculated at **1410** and a maximum number (k) of templates for which further analysis is to be performed. The maximum number (k) may be a defined maximum number, a number calculated by application **220**, or may be a number of results that is provided as an input parameter to method **1400** (e.g. by server application **214**). In either case, application **220** preliminarily selects the k templates with the best preliminary template scores for further analysis.

[0543] Continuing with the above example, if the defined maximum number of templates (k) was 2, then application **220** would select template2 and template1 at **1412** as they have the highest preliminary template scores.

[0544] Conceptually, following preliminary selection of templates at **1412**, for each template ID, for each source page, a list of (rewrite, template page) pairs has been determined.

[0545] At **1414**, application **220** filters the (rewrite, template page) pairs to remove certain invalid pairs from further consideration. This filtering is performed to eliminate (rewrite, template page) pairs where the destination objects of the template page do not actually accommodate the source objects of the rewrite. This may occur due to the fact that the (rewrite, template page) pairs are initially identified at **1408** based on partition keys only.

[0546] Application **220** may be configured to apply various filtering rules to determine whether a particular (rewrite, template page) is invalid. For example, application **220** may determine invalidity based on whether source and/or destination objects define compatible fills (which may be determined based on the "appropriate for fill role" attributes of destination objects and the "fill role" attributes of source objects). As one example, application **220** may be configured to require

that a source fill having a complete “fill role” attribute can only be matched to a destination fill that has a “complete” “appropriate for fill role” attribute. In this case, and by way of example, if a (rewrite, template page) pair identifies a rewrite that includes a fill type source object that has a complete “fill role” attribute, but a template page that only includes a fill-type destination object with a partial “appropriate for fill role” attribute, this pair will be filtered out and not considered further.

[0547] At **1416**, application **220** calculates a set of (rewrite, template page) scores. These may be referred to as rewrite scores or candidate page scores for ease of reference. In particular, application **220** calculates a rewrite score for each (rewrite, viable template page) pairing. In this context, a viable template page is a template page of a template that: [0548] a) has been preliminarily selected (at **1412**); and [0549] b) has been identified as a potential match for the rewrite in question (as determined at **1408**).

[0550] In the present embodiment, application **220** calculates the rewrite score for a given (rewrite, template page) pair based on the relevant candidate page (or rewrite) vector and template page vector. In the present embodiment, for a particular rewrite and a particular template page, application **220** calculates the rewrite score as follows:

[00002] $\text{Rewritescore} = (\text{vectorscore} * \text{weight}) + \text{textsizepenalty} + \text{rewritepenalty}$

[0551] The vector score is the Euclidian distance between the candidate page (or rewrite) vector and the template page vector (the candidate page (or rewrite) and template page vectors both flattened into a single set of values if required). Any appropriate weight may be used, for example a weight of 1.

[0552] The text size penalty is a factor that application **220** calculates based on the number of lines. In particular, application **220** aggregates the numLines over the texts assigned to a specific destination, being the log base 2 of the maximum ratio between space required and the space available, as expressed by the numLines attribute. By way of further explanation, for each set of one or more source text objects assigned to a destination text object: the number of estimated lines consumed by those source text objects is summed and that value is then divided by the destination text object's numLines. For each (set of source text objects, destination object) pair, this provides a measure of the extent to which the set of source text objects exceeds the available space of the destination object. In the present embodiment, the text size penalty is concerned with the most egregious violation, so takes the max over the calculated ratios. A log of the maximum value is then used so that the text size penalty due to large ratios has increasingly marginal effect as the ratio increases.

[0553] The rewrite penalty is a penalty that is applied if the particular rewrite includes any merged content. In the present embodiment, the penalty is determined based on the rewrite penalty data described above. As noted, the rewrite penalty data may define an actual penalty value (e.g. 0.4 of another value), or may provide data that application **220** uses to calculate a rewrite penalty value.

[0554] In the above example, rewrite scores are calculated such that lower scores indicate better results. In other embodiments, rewrite scores may be calculated so that higher scores indicate better results. In either case, the rewrite scores that are calculated provide a mechanism for determining whether one rewrite is preferable to another.

[0555] Application **220** may be configured to calculate rewrite scores in alternative ways (and based on alternative data/values). For example, features can be extracted from the source objects, the destination, their combination, or in the context of the transformation performed when rewriting the source, and weights for these features can be learnt from data where the results have been ranked as a ground truth.

[0556] At **1418**, application **220** calculates a set of final template scores for the pagination candidate. This includes calculating a final template score for each template preliminarily selected for the pagination candidate at **1412**.

[0557] In the present embodiment, application **220** calculates the final template scores based on the

(rewrite, template page) scores calculated at **1416**. In particular, for each selected template application **220**: [0558] a) calculates a final candidate page score for each candidate page; and [0559] b) sums the final candidate page scores.

[0560] When calculating the final candidate page score for a particular template and a particular candidate page: [0561] a) If the particular template does not include any pages that are a potential match for any of the rewrites of the particular candidate page (e.g. based on the potential (rewrite, template page) matches determined at **1408**), a default “no-match” score is determined. The no-match score is set to penalise a template if it cannot match any rewrite of a candidate page. The “no match” score may, for example, be -100 . [0562] b) Otherwise, the final candidate page score is based on the relevant rewrite scores for the candidate page. In this context, a rewrite score is a relevant rewrite score for a particular candidate page if it is associated with any template page of the particular template or any rewrite of the particular candidate page. In certain embodiments, application **220** may select the optimal relevant rewrite score. In alternative embodiments, application **220** may be configured to use the relevant rewrite scores to determine a distribution of a random selection. For example, the relevant rewrite scores may be processed using a softmax function to produce a distribution from which a single result can be sampled. The temperature of the softmax can be configured based on whether a single best result is desired ($\text{temp}=0$), or otherwise how far from the single-best the distribution is to share probability mass. The rewrite score that is selected also defines the (rewrite, template page) pair that will be included in the deck generation data.

[0563] Continuing the above example, and assuming only template1 and template2 have been preliminarily selected at **1412**, application **220** would calculate final template scores as follows:

```
TABLE-US-00029    scoreTemplate1 :=    // final candidate page score for candidate page 1
score({candidatePage: 1, rewrite: 1, templateId: "template1",    templatePage: 1})    // final
candidate page score for candidate page 2    + SCORE_FOR_NO_MATCH    // final candidate
page score for candidate page 3    + min(    score({candidatePage: 3, rewrite: 1, templateId:
"template1",    templatePage: 2),    score({candidatePage: 3, rewrite: 2, templateId:
"template1",    templatePage: 1})    ) scoreTemplate2 :=    // final candidate page score for
candidate page 1    min(    score({candidatePage: 1, rewrite: 1, templateId: "template2",
templatePage: 1),    score({candidatePage: 1, rewrite: 1, templateId: "template2",
templatePage: 3})    )    // final candidate page score for candidate page 2    +
score({candidatePage: 2, rewrite: 1, templateId: "template2",    templatePage: 2})    // final
candidate page score for candidate page 3    + min(    score({candidatePage: 3, rewrite: 2,
templateId: "template2",    templatePage: 1),    score({candidatePage: 3, rewrite: 2,
templateId: "template2",    templatePage: 3})    )
```

[0564] In this example, candidate page 1 has a single rewrite (rewrite 1). [0565] Template1 has a single page that matches the rewrite (page 1). Therefore template1's final candidate page score for candidate page 1 is the rewrite score (candidate page 1 rewrite 1, template1 page 1). [0566] Template2 has two pages that match the rewrite (pages 1 and 3). Therefore template2's final candidate page score for candidate page 1 is the minimum of the (candidate page 1 rewrite 1, template2 page 1) rewrite score and the (candidate page 1 rewrite 1, template2 page 3) rewrite score.

[0567] In this example, candidate page 2 has a single rewrite (rewrite 1). [0568] Template1 has no pages that match the rewrite. Therefore template1's final candidate page score for candidate page 2 is the default ‘no-match’ score. [0569] Template2 has a single page m that matches the rewrite (page 2). Therefore template2's final candidate page score for candidate page 1 is the rewrite score (candidate page 2 rewrite 1, template2 page 2).

[0570] In this example, candidate page 3 has two rewrites (rewrites 1 and 2). [0571] Template 1 has one page that matches rewrite 1 of candidate page 3 (page 2) and one page that matches rewrite 2 of candidate page 3 (page 1). Therefore template1's final candidate page score for candidate page 3

is the minimum of the (candidate page 3 rewrite 1, template1 page 2) rewrite score and the (candidate page 3 rewrite 1, template1 page 1) rewrite score. [0572] Template2 has no pages that match rewrite 1 of candidate page 3, but two pages that match rewrite 2 of candidate page 3 (pages 1 and 3). Therefore template2's final candidate page score for candidate page 3 is the minimum of the (candidate page 3 rewrite 2, template2 page 1) rewrite score and the (candidate page 3 rewrite 2, template2 page 3) rewrite score.

[0573] Once a final template score for the or each pagination candidate has been calculated processing proceeds to **1420**.

[0574] If method **1400** is initiated at **612** (as part of a document to deck generation process), final template scores may be generated for multiple pagination candidates. At **1420**, therefore, application **220** has calculated a set of template scores for each pagination candidate. These scores may, for example, be recorded as a set of (pagination candidate identifier, template identifier, final template score) tuples—e.g.:

TABLE-US-00030 Pagination Template Final candidate ID template score 1 0001 ... 1 0003 ... 1 0004 ... 2 0001 ... 2 0002

[0575] If method **1400** is initiated at **2810** (as part of a deck to deck generation process), final template scores are generated for a single pagination candidate only (that is, the pagination candidate with candidate pages corresponding to the source deck's original pages).

[0576] At **1420**, application **220** makes a final selection of one or more (pagination candidate, template) pairs. The final selection is based on the final template scores calculate at **1418**.

[0577] In certain embodiments, application **220** may be configured to select a single (pagination candidate, template) pair—being the pair associated with the best or equal best final template score. In other embodiments, application **220** is configured to select the top n (pagination candidate, template) pairs. In still further embodiments, application **220** may be configured to use the final template scores to determine a distribution of a random selection. For example, the final template scores may be processed using a softmax function to produce a distribution. From this distribution, a single result can be sampled. The temperature of the softmax can be configured based on whether a single best is desired (temp=0), or otherwise how far from the single-best the distribution is to share probability mass.

[0578] In some implementations, application **220** may be configured to only select a single (pagination candidate, template) pair. In alternative implementations, application **220** may select a defined number of (pagination candidate, template) pairs. The defined number may be a predefined number of an input provided by the application calling method **1400**. For example, the defined number may be 8. In this case, application **220** computes the defined number (e.g. 8) (pagination candidate, template) pairs for each pagination candidate, concatenates the results, orders the results by score, then truncates at the defined number.

[0579] At **1422**, application **220** generates a new deck descriptor for each (pagination candidate, template) pair selected at **1420**. As described below, a new deck descriptor can be used to generate a new deck.

[0580] Generally speaking, the new deck descriptor for a particular (pagination candidate, template) pair includes data that allows a primary template to be identified (which may be referred to as the style template). In addition, for each candidate page of the pagination candidate, the new deck descriptor includes: [0581] data that allows a specific template page to be identified (which may be referred to as the destination page); and [0582] content map data that maps source content segments (which in this implementation are defined by the candidate page's source objects) to destination elements of the destination page (which in this implementation are defined by the destination page's destination objects).

[0583] As discussed further below, the destination page that is identified for given candidate page may be a page of the primary template, but need not be.

Generating a New Deck Descriptor

[0584] Turning to FIG. 15, a method **1500** for generating a new deck descriptor for a particular (pagination candidate, template) pair will be described. In method **1500**, the template of the (pagination candidate, template) pair being processed will be referred to as the primary template. [0585] Initially (and as indicated at **1502**), application **220** processes each candidate page of the particular pagination candidate. This processing is performed to determine a destination page for the candidate page and to generate content map data that maps the source content segments of the candidate page to the elements of the destination page (which may be referred to as destination elements). Candidate pages may be processed at **1502** in any order (or in parallel).

[0586] At **1504**, application **220** determines whether the candidate page being processed matches any page of the primary template (i.e. a page the template of the particular (pagination candidate, template) pair being processed). In the present embodiment, application **220** determines that the candidate page being processed matches a page of the primary template at **1506** if one or more rewrites of the candidate page match one or more pages of the primary template. In the present embodiment, this determination may be made with reference to the potential (rewrite, template page) matches identified by application **220** at **1408**.

[0587] If, at **1504**, the candidate page matches a page of the primary template, processing proceeds to **1506**. Otherwise, processing proceeds to **1508**.

[0588] At **1506**, application **220** identifies a particular page of the primary template as the destination page for the candidate page. In the present embodiment, application **220** identifies the destination page based on the (rewrite, template page) scores that are calculated at **1416**. In particular, application **220** determines the destination page to be the template page that is associated with the optimal (rewrite, template page) score. In the present embodiment, application **220** also associates a particular candidate page rewrite with the destination page (in this case the rewrite associated with the optimal (rewrite, template page) score). This allows the particular rewrite to be easily identified when generating content map data. Processing then proceeds to **1518**.

[0589] At **1508**, the candidate page does not match any page of the primary template. In this case, application **220** determines (over the course of **1508-1516**) a destination page for the candidate page that is not a page of the primary template.

[0590] At **1508**, application **220** identifies potential (rewrite, fallback page) matches. These may be referred to as potential fallback page matches for convenience. Specifically, for each rewrite application **220** identifies which (if any) fallback pages are a potential match for that rewrite. In the present embodiment, application **220** determines whether a particular fallback page is a potential match for a particular rewrite based on the fallback page partition key and the rewrite partition key. Application **220** may make this determination in the same (or a similar) way as determining whether a template page is a potential match for a candidate page rewrite (as described at **1408** above).

[0591] At **1510**, application **220** determines whether a fallback page exists for the candidate page. A fallback page will exist for the candidate page if at least one rewrite of the candidate page matches at least one fallback page. If a fallback page exists, processing proceeds to **1512**. Otherwise processing proceeds to **1514**.

[0592] At **1512**, application **220** identifies a particular fallback page as the destination page for the candidate page. In the present embodiment, application **220** identifies a particular fallback page by initially calculating a score for each (candidate page rewrite, matching fallback page) pair. Application **220** may calculate these scores in the same (or a similar) way to the manner in which (rewrite, template page) scores are calculated (as described above at **1416**). Application **220** then selects the fallback page that is associated with the optimal (rewrite, fallback page) score to be the destination page. In the present embodiment, application **220** also associates a particular candidate page rewrite with the destination page (in this case the rewrite associated with the optimal (rewrite, fallback page) score). Processing then proceeds to **1518**.

[0593] At **1514**, no fallback pages have been identified for the candidate page. In this case,

application **220** generates a new deck page to be the destination page. The new deck page is generated to accommodate the source content of the candidate page.

[0594] Application **220** (or an alternative application) may generate a new deck page in various ways. For example, application **220** may generate the new deck page by generating an element corresponding to each content segment of the candidate page's original rewrite (e.g. an element corresponding to each source object of the candidate page's original rewrite). For a given content segment (as defined by a given source object), application **220** generates an element of the appropriate type—e.g. based on the content-type attribute of the corresponding source object. Each element generated may have default parameters that are set for the element type (e.g. default font properties for a text element). Application **220** may then calculate positions for the new elements. As one example, application **220** may calculate positions so that: each element is horizontally centred on the page; the elements are vertically ordered (e.g. top to bottom) based on reading order (each element's reading order being based on the reading order attribute of the source object that the element corresponds to); and the elements are vertically distributed so that they do not overlap one another. Application **220** may position the elements in alternative ways.

[0595] Once a new deck page is generated at **1514**, application may save the new deck page as a temporary deck page. The new deck page may be used to generate a new deck in course, but persistent/ongoing storage of the new deck page beyond that is not required.

[0596] At **1516**, application **220** identifies the new deck page generated at **1514** as the destination page for the candidate page. In the present embodiment, application **220** also associates a particular candidate page rewrite with the destination page (which, in this particular example, is the original rewrite of the candidate page). Processing then proceeds to **1518**.

[0597] If method **1400** is initiated at **2810** (as part of a deck to deck generation process), alternative processing to **1508**, **1510**, **1512**, **1514**, and/or **1516** may be performed in the event that a given candidate page does not match a primary template page at **1504**. This difference is due to the fact that in a deck to deck generation process, the source content of the candidate page in question will already include a set of elements with explicit position data (while in a document to deck generation process, the source content document content will not include such data).

[0598] By way of example, if a candidate page does not match a primary template page at **1504** in the context of a deck-to-deck generation process, application **220** may retain the original candidate page (or generate a new page with elements based on the elements of the original candidate page). In this case application **220** may also generate an error or warning that causes a message to be displayed to a user that a template page could not be identified for the original deck page that the unmatched candidate page corresponds to.

[0599] By way of alternative example, if a candidate page does not match a primary template page at **1504** in the context of a deck-to-deck generation process, application **220** may attempt to identify a fallback page at **1508** (and, if a fallback page is identified, select that fallback page at **1512**). If a fallback page is identified, however, application **220** may then retain the original candidate page (or generate a new page with elements based on the elements of the original candidate page). In this case application **220** may also generate an error or warning that causes a message to be displayed to a user that a template page could not be identified for the original deck page that the unmatched candidate page corresponds to.

[0600] At **1518**, application **220** has identified a destination page (and a particular candidate page rewrite) for the candidate page being processed. Application **220** then generates content map data for the destination page. Generally speaking, the content map data maps each source object of the particular candidate page rewrite (and, therefore, each source object's corresponding source content segment) to a destination object of the destination page (and, therefore, each destination object's corresponding element). Content map data may, for example, be represented as a set of (source object ID, destination object ID) pairs. Two methods for generating content map data are described below with reference to FIG. **21** and FIG. **22**.

[0601] In some implementations, where a new deck page is generated at **1514** a set of destination objects may be generated for that new deck page so it can be processed at **1518** in the same way as other template pages. In other implementations, however, any new page generated at **1514** may be handled differently (noting that in the present example a new page includes elements that have been specifically created for the source content segments and can be directly mapped to the source content segments).

[0602] Once content map data for the destination page has been generated, processing proceeds to **1520**. At **1520**, application **220** generates the new deck descriptor for the particular (pagination candidate, template) pair. In the present embodiment, application **220** generates the new deck descriptor to include a primary template identifier and a new deck page dataset for each candidate page of the pagination candidate.

[0603] The primary template identifier is an identifier of the template of the particular (pagination candidate, template) pair.

[0604] The new deck page dataset for a given candidate page of the pagination candidate includes: a candidate page identifier (e.g. the index of the candidate page in pagination candidate's set of candidate pages); a destination page identifier (which identifies the destination page determined for that candidate page at **1506**, **1512**, or **1516**); and the content map data for that candidate page (as generated at **1518**).

[0605] Different destination page identifiers may be adopted depending on the destination page that has been identified. For example, if the destination page is a page of the primary template (identified at **1506**), the destination page identifier may be a single value that identifies the particular page of the primary template (noting the new deck descriptor already includes the primary template identifier). This single value may, for example, be the index of the destination page in the primary template's pages array). Alternatively, if the destination page is a fallback page (identified at **1512**), the destination page identifier may be a (template identifier, page identifier) tuple: the template identifier identifying the template that includes the destination page and the page identifier identifying the particular page of that template. Further alternatively, if the destination page is a new deck page (as generated at **1516**), the destination page identifier may be value that identifies that single, newly generated page.

[0606] Any appropriate data structure (or set of related data structures) may be used for a new deck descriptor. By way of example, each new deck descriptor may be a dictionary such as the following:

```
TABLE-US-00031    {  "primaryTemplateId": "<template identifier>",  "deckPages": [
{  "candidatePage": "<candidate page identifier>",    "destinationPage": <page identifier>,
    "contentMap": [...] }    {  "candidatePage": "<candidate page identifier>",
    "destinationPage": ("<template identifier>", <page identifier>),    "contentMap": [...] }  ]
}
```

[0607] At **1424**, application **220** generates and returns deck generation data. In the present embodiment, the deck generation data is a set (e.g. an array or other set) of the new deck descriptors generated at **1422**. Each new deck descriptor corresponds to a (pagination candidate, template) pair selected at **1420** and includes data that can be used to generate a new deck-format design (e.g. as described with reference to FIG. **16** below).

Content Mapping

[0608] This section describes two alternative methods (**2100** and **2200**) for mapping a set of source content segments to a set of destination elements. Method **2100** may be used to map source content segments of any type to destination elements, while method **2200** may be used to map source fills to destination elements in situations where there are more source fills than there are destination elements.

[0609] Method **2100** or method **2200** may, for example, be performed at **1518** of method **1500** above in order to generate content map data in respect of a particular candidate page (or candidate

page rewrite) and a particular destination template page. In this case, the set of source content segments is defined by a set of source objects that correspond the particular candidate page (or rewrite), and the set of destination elements is defined by a set of destination objects that correspond to a particular template page.

[0610] Method **2100** or **2200** may, however, be performed in different contexts in which source content segments and destination elements are alternatively identified and/or defined.

[0611] In the present embodiments, method **2100** and method **2200** each generate content map data that includes a set of content map items. Each content map item identifies a source content segment and a destination element. Where source content segments have corresponding source objects and destination elements have corresponding destination objects, each content map item may be a (source object identifier, destination object identifier) pair. Source content segments and destination elements may, however, be identified in other ways—e.g. by array index (or other) values that identify the source content segments and destination elements.

[0612] Methods **2100** and **2200** are described as being performed by template match application **220**. Methods **2100** and/or **2200** may, however, be performed by alternative applications. As one example, content mapping may be performed client side (e.g. by client application **232**).

[0613] In method **2100** of FIG. **21**, application **220** maps the set of source content segments (which may, for example, correspond to a candidate page's source objects) to the set of destination elements (which may, for example, correspond to a destination page's destination objects) based on reading order and content type values.

[0614] At **2102**, application **220** selects the next source content segment (or the source object corresponding thereto) that has not been mapped to a destination element. Application **220** selects source objects at **2102** in reading order, from earliest in reading order to latest in reading order.

[0615] At **2104**, application **220** determines the content type of the selected source content segment.

[0616] Where the source content segment has a corresponding source object, the reading order and/or content type may be determined based on a reading order and/or type attribute of the corresponding source object. Reading order and content type may, alternatively, be determined based on the source content segment itself (for content type) and the set of source content segments (for reading order). Furthermore, where source content segments are associated with source objects as described above, only source objects with a transfer-content attribute of true are selected at **2102**. Source objects with transfer-content attribute of false are ignored.

[0617] At **2106**, application **220** selects a destination element for the selected source object. Application **220** selects the destination object that has a content type that matches the content type of the source content segment and that is the earliest-in-reading-order element of that content type in the set of destination elements that has not yet had a source content segment mapped to it.

[0618] Where the destination element has a corresponding destination object, the reading order and/or content type may be determined based on a reading order and/or type attribute of the corresponding destination object. Reading order and content type may, alternatively, be determined based on the destination element itself (for content type) and the set of destination elements (for reading order). Furthermore, where destination elements are associated with destination objects as described above, only destination objects with a receive-content attribute of true are considered at **2106**. Destination elements with receive-content attribute of false are ignored.

[0619] At **2108**, application **220** maps the selected source content segment to the selected destination element. In the present embodiment, application **220** does so by generating a content map item that includes an identifier of the source content segment (or a corresponding source object) and an identifier of the destination element (or a corresponding destination object). The content map item can then be added to a set of content map items.

[0620] At **2110**, application **220** determines if there are any unmapped source content segments. If so, processing proceeds to **2102**. If not, processing proceeds to **2112**.

[0621] At **2112**, mapping the set of source content segments to the set of destination elements is complete. If required, application **220** may return content map data that includes the set of all content map pairs generated at **2108**.

[0622] Where method **2100** is performed for a candidate page rewrite (e.g. at **1518**), one or more source objects selected at **2102** may be a combined source object (i.e. a source objects that correspond or refer to two or more original source objects). Where a combined source object is selected at **2102**, application **220** maps all original source objects of the combined source object to the same (single) destination object.

[0623] To illustrate generation of the content map data according to method **2100**, consider the candidate page rewrite (which defines a set of source objects that correspond to source content segments) and destination page (which defines a set of destination objects that correspond to destination elements) represented in the tables below:

TABLE-US-00032 Source object index Candidate page rewrite source objects 0 “type”: “text”, “readingOrderIndex”: 1, “textHierarchyLevel”: 1 1 “type”: “text”, “readingOrderIndex”: 2, “textHierarchyLevel”: 2 2 “type”: “text”, “readingOrderIndex”: 3, “textHierarchyLevel”: 2 3 “type”: “text”, “readingOrderIndex”: 4, “textHierarchyLevel”: 2 4 “type”: “fill”, “readingOrderIndex”: 5 5 “type”: “chart”, “readingOrderIndex”: 6

TABLE-US-00033 Destination object index Destination page destination objects 0 “type”: “fill”, “readingOrderIndex”: 1 1 “type”: “text”, “readingOrderIndex”: 2, “textHierarchyLevel”: 2 2 “type”: “chart”, “readingOrderIndex”: 3 3 “type”: “text”, “readingOrderIndex”: 4, “textHierarchyLevel”: 2 4 “type”: “text”, “readingOrderIndex”: 5, “textHierarchyLevel”: 1

[0624] The above tables represent simplified source and destination objects showing type and reading order attribute values only. Further, source objects 2 and 3 are presented in a single row to indicate they are a combined source object in the candidate page rewrite.

[0625] In this example, application **220** would: [0626] map source object 0 to destination object 4 (which is the earliest unmapped text-type destination object with text hierarchy level 1); [0627] map source object 1 to destination object 1 (which is the earliest unmapped text-type destination object with text hierarchy level 2); [0628] map source object 2 to destination object 3 (which is the earliest unmapped text-type destination object with text hierarchy level 2); [0629] map source object 3 to destination object 3 (as source objects 2 and 3 are a combined source object); [0630] map source object 4 to destination object 0 (which is the earliest unmapped fill-type destination object); and map source object 5 to destination object 2 (which is the earliest unmapped chart-type destination object).

[0631] This mapping may be represented by an array of (source object, destination object) content map items such as: [0632] [(0,4), (1,1), (2,3), (3,3), (4,0), (5,2)]

[0633] Method **2100** assumes that each source object has a corresponding destination object that the source object can be mapped to. When method **2100** is performed at **1520**, method **2100** will be suitable where partition key fills values for candidate page rewrites and template pages is a numeric value indicating an actual number of source and destination fills.

[0634] As noted, however, in alternative embodiments the partition key fills values may instead take a Boolean (or other) value that indicates the presence or absence of source/destination fills but does not indicate the specific number of source/destination fills. In these embodiments, the number of shape-type destination elements of a template page (each shape-type destination element accommodating one or more fills) may be less than the number of fill type source content segments in the candidate page rewrite. If this occurs, method **2100** will not be suitable for mapping fills.

[0635] Turning to FIG. 22, an alternative method **2200** for mapping a set of fill type source content segments to a set of destination elements will be described. Method **2200** may be performed in scenarios where the number of source fills that need to be mapped exceeds the number of destination elements that can accommodate fills. For example, when content mapping is performed at **1518** described above, method **2200** may be performed when the primary key fills values are

Booleans and a candidate page rewrite's number of fill-type source objects with a transfer content value of true exceeds the destination page's number of fill-type destination objects with a receive content value of true.

[0636] Method **2200** is described with reference to source fills and frames. When method **2200** is performed at **1518**, a source fill is a fill of the source design from which content is being transferred (and will have a corresponding fill-type source object) and a frame is a shape-type destination element (which will have a corresponding fill-type destination object).

[0637] At **2202**, application **220** maps non-fill source content to destination elements. This mapping may be performed based on the reading orders of the non-fill source content segments (or their corresponding source objects) and destination elements (or their corresponding destination objects). For example, application **220** may map non-fill source content according to the operations of method **2100** as described above.

[0638] In order to map fill-type source content segments, application **220** performs a fill mapping process **2203** (which includes processing blocks **2204** to **2220**).

[0639] At **2204**, application **220** analyses the set of fill type source objects to identify a set of source fills. The set of source fills may be all fills defined by the set of source content segments or a subset of those fills. For example, where method **2200** is performed at **1518**, application **220** will ignore any fills defined by source objects having a transfer content attribute value of false.

[0640] At **2206**, application **220** identifies a set of one or more frames that the source fills are to be transferred to. In the present example, a frame is a destination element that can accommodate a source fill.

[0641] In the context of the present disclosure, a shape-type element defines (or is) a frame. Furthermore, if a shape-type destination element defines multiple separable fills (e.g. a grid of fills), each separable fill (e.g. each cell of that grid) will be considered a frame. Where method **2200** is performed at **1518**, application **220** may be configured to determine that each fill-type destination object with a receive-content attribute of true is a frame.

[0642] At **2208**, application **220** calculates an ideal size for each source fill identified at **2204**. A source fill's ideal size is a measure of the proportion of space the source fill would ideally occupy given the available space provided by the frames and the space required by the set of source fills. In the present embodiment, a source fill's ideal size is calculated as:

[00003]
$$\text{Idealsize} = \text{sourcefillsize} * (\text{Sumframesizes} / \text{sumsourcefillsizes})$$

Where:

[0643] Source fill size=the size of the source fill for which the ideal size is being calculated. A source fill's size is calculated as (source fill width*source fill height). [0644] Sum frame sizes=the sum of the frame sizes for all frames identified at **2206**. A frame's size is calculated as (frame width*frame height). [0645] Sum source fill sizes=the sum of the source fill sizes for all source fills identified at **2204**.

[0646] At **2210**, application **220** calculates a remaining capacity for each frame identified at **2206**. Initially, each frame's remaining capacity is its total capacity, which is calculated as (frame height*frame width). Where a frame corresponds to a shape-type element, the frame capacity is the element width*element height.

[0647] At **2212**, application **220** selects a next source fill that is to be assigned (or mapped) to a frame. Application **220** selects source fills in order of largest ideal size to smallest. I.e. in the first iteration, application **220** selects the source fill with the largest (or equal largest) ideal size, in the second iteration, application **220** selects the source fill with the next largest (or equal largest) size and so forth.

[0648] At **2214**, application **220** selects a frame for the selected source fill. Application **220** is configured to select the frame as the frame that has the greatest remaining capacity.

[0649] At **2216**, application **220** maps the selected source fill to the selected frame. This may be performed in various ways but generally involves associating an identifier of the selected source fill

with an identifier of the selected frame. As one example, in the context of the present disclosure, application may map the source object that corresponds to the source fill to the destination object that corresponds to the destination frame. In this case, mapping is performed by creating a (source object identifier, destination object identifier) content map item and adding this to a result set. [0650] At **2218**, application **220** updates the selected frame's remaining capacity. In the present embodiment, application **220** does this by subtracting the ideal size of the selected source fill from the current remaining capacity value of the selected frame—e.g.:

Remaining capacity=remaining capacity–selected source fill ideal size.

[0651] Updating a frame's remaining capacity may cause the remaining capacity to be less than zero.

[0652] At **2220**, application **220** determines if any of the source fills identified at **2204** have not yet been mapped to a frame. If so, processing proceeds to **2212** to select the next source fill.

[0653] If all source fills have been mapped to a frame, method **2200** is complete (as indicated at **2222**). If required, content map data may be returned that includes content map items in respect of any non-fill source content segments (generated at **2202**) and content map items in respect of source fills (generated at **2216**).

[0654] To illustrate method **2200**, consider a set of three source fills identified at **2204** and a set of two frames identified at **2206** as follows: [0655] Source fill SF 1: 900×700, [0656] Source fill SF 2: 400×500, [0657] Source fill SF 3: 100×300 [0658] Frame F1: 500×500 [0659] Frame F2: 700×400

[0660] For this example, source fill ideal sizes calculated at **2208** are as follows:

TABLE-US-00034 Source fill SF height SF width SF size SF Ideal size SF 1 900 700 630000 388,255.81 SF 2 400 500 200000 123,255.81 SF 3 100 300 30000 18,488.37

[0661] For this example, frame remaining capacity values calculated at **2210** are as follows:

TABLE-US-00035 Frame Frame height Frame width Remaining capacity F1 500 500 250,000 F2 700 400 280,000

[0662] In a first iteration, application **220**: selects source fill SF1 (having the largest ideal size) at **2212**; identifies frame F2 at **2214**; maps SF1 to F2 at **2216**; and update's F2's remaining capacity at **2218** as follows:

TABLE-US-00036 Frame Frame height Frame width Remaining capacity F1 500 500 250,000 F2 700 400 –108,255.81

[0663] In the second iteration, application **220**: selects source fill SF2 (having the next largest ideal size) at **2212**; identifies frame F1 at **2214**; maps SF2 to F1 at **2216**; and update's F1's remaining capacity at **2218** as follows:

TABLE-US-00037 Frame Frame height Frame width Remaining capacity F1 500 500 126,744.19 F2 700 400 –108,255.81

[0664] In the third iteration, application **220**: selects source fill SF3 at **2212**; identifies frame F1 at **2214**; maps SF3 to F1 at **2216**; and update's F1's remaining capacity at **2218** as follows:

TABLE-US-00038 Frame Frame Remaining Frame height width capacity F1 500 500 108,255.81 F2 700 400 –108,255.81

[0665] No unmapped source fills remain at **2220**, and at **2222** fill map data such as the following is returned (with appropriate identifiers used to identify the source fills and frames): [0666] [(SF1, F2), (SF2, F1), (SF3, F1)]

New Deck-Format Design Generation

[0667] Referring to FIG. **16**, an example method **1600** for generating a new deck-format design will be described.

[0668] Method **1600** may be performed as part of a document to deck generation process (e.g. at **618** of method **600** described above). Method **1600** may also, or alternatively, be performed as part of a deck to deck generation process (e.g. at **2816** of method **2800** described below)

[0669] In the present example, method **1600** is described as being performed by client application **232** (referred to as application **232** in this section for convenience). In particular, in the present embodiment method **1600** is performed by the content transfer module **234**. The processing described may, however, be performed by one or more alternative applications or modules (running on client system **230** and/or at server environment **210**).

[0670] In the present embodiment, method **1600** takes as input (or has access to) a new deck descriptor (which is included in deck generation data). As described above, the new deck descriptor includes a primary template identifier and a set of one or more new deck page dataset. Each new deck page dataset includes a candidate page identifier, a destination page identifier and content map data.

[0671] If, at **618** of method **600**, multiple new deck-format designs are to be generated (each being based on a new deck descriptor), method **1600** may be performed for each new deck descriptor sequentially or in parallel.

[0672] Method **1600** is described as being performed with reference to a source design. If method **1600** is being performed as part of method **600** described above, the source design will be a source document (i.e. a document-format design) and each source object defined in the new deck page dataset will identify content segment of that source document. If method **1600** is being performed as part of method **2800** (as discussed further below), the source design will be a source deck (i.e. a deck-format design) and each source object defined in the new deck page dataset will identify an element (or part of an element's content) of that source deck.

[0673] At **1602**, application **230** initialises a new deck-format design (referred to as the new deck). In the present embodiment, the new deck is initialised based on (and includes relevant data from) the primary template identified by the primary template identifier.

[0674] By way of example, and referring to the example deck record format described above, application **230** may initialise the new design to have: a new (automatically generated) deck identifier; dimensions that are the same as those of the primary template; and page data that is initially empty. In some embodiments, the new design may also include an associated template attribute which is populated with data that identifies the primary template on which the new deck is based.

[0675] Following **1602**, and as generally indicated at **1604**, application **230** processes each deck page dataset in the new deck descriptor being processed to generate a corresponding new deck page. The deck page datasets may be processed in any order or in parallel. In the present embodiment, processing a selected deck page dataset to generate a corresponding new deck page involves operations **1606** to **1622**.

[0676] At **1606**, application **230** initialises a new deck page. In the present embodiment, application initialises the new deck page by creating a copy of the destination page that is identified by the destination page identifier of the selected new deck page dataset.

[0677] Following initialisation of the new deck page at **1606**, application **230** transfers source content to the new deck page initialised at **1606**. Generally speaking, the content transfer process uses the content map data to map source objects (and, therefore, the corresponding source content segments) to destination objects (and, therefore, the corresponding destination elements). Each destination element is then edited (or replaced with one or more replacement elements) based on the source content segment(s) that correspond to the destination element.

[0678] In the present embodiment, application **230**: transfers fill-type source objects (or source fills) at **1608**; transfers text-type source objects (or source text) at **1610**; transfers table-type source objects (or source tables) at **1618**; and transfers chart-type source objects (or source charts) at **1620**. The processing described at each of these stages is described below. While the source content transfer processing is described in a particular order, the different types of source content could be transferred in an alternative order.

[0679] At **1608**, application **230** transfers any source fills (which may correspond to fill-type source

objects).

[0680] In the present disclosure, two general scenarios exist for transferring fills. In one scenario, the number of source fills matches the number of destination fills. This may be the case, for example, when the partition key fills values for template pages and candidate pages record an actual number of fills (or fill-type source/destination objects). In the other scenario, the number of source fills may be different to the number destination fills. This may be the case, for example, when the partition key fills values for template pages and candidate pages record a Boolean (or other) value that indicates whether one or more fills are present rather than the actual number of fills.

[0681] In the present example, where the number of source fills matches the number of destination fills, the content map data will map each source fill to a specific shape-type destination page element—e.g. per content map data that is generated according to method **2100** described above. In this case, application **230** may transfer source fills by processing each fill-type source object in turn. For a selected fill-type source object, application **230** identifies (via the content map data) the relevant fill-type destination object which will, in turn, identify a shape-type element of the design page. Application **230** then updates the content data of the shape-type element that has been identified based on the source fill.

[0682] When transferring a source fill to a destination element, if the size and/or aspect ratio of the source fill do not match those of the destination element application **230** may adjust the source fill (or relevant attributes in respect thereof) so it occupies the entire area of the destination element. For example, application **230** may uniformly resize the source fill (i.e. without changing the source fill's aspect ratio) so that its shortest dimension (e.g. height or width) is equal to the corresponding dimension of the destination element and centre the source fill in the destination element.

[0683] If the number of source fills does not match the number of destination page fills (and, in particular, if the number of source fills is greater than the number of destination fills), the content map data may map multiple source fills to a single destination fill. Such content map data may be generated according to method **2200** as described above. In this case, application **230** may transfer source fills by processing the content map data to identify: any destination fills that have a single source fill mapped to them; any destination fills that have a no source fill mapped to them; and any destination fills that have multiple source fills mapped to them.

[0684] For each destination fill that has a single source fill mapped to it, application **230** may transfer the single source fill to the destination fill as described above—e.g. by identifying the relevant destination element and transferring the single source fill to that element.

[0685] For each destination fill that has no source fill mapped to it, application **230** may be configured to identify and delete the relevant destination element. Alternatively, application **230** may be configured to retain the destination element with its original fill or to retain the destination element but replace its original fill with a default fill. The default fill may, for example, be designed to be eye catching (e.g. via use of colours, animations, words, and/or other visual features) so a user can easily identify it as an original template fill that was not replaced.

[0686] For each destination fill that has multiple source fills mapped to it, application **230** may perform processing to transfer the multiple source fills to the single destination element. An example method **2300** for doing so is described below with reference to FIG. **23**.

[0687] At **1610**, application **230** transfers text-type source content (which may correspond to text-type source objects). In the present embodiment, this involves processing each text-type source object—or each content map record in respect of such an object—according to processing blocks **1612**, **1614**, and **1616**.

[0688] Processing blocks **1612**, **1614**, and **1616** will be described with reference to source text content and a destination element. The source text content is the text of a text-type source content segment that may have a corresponding source object. The destination element may have a corresponding destination object, and is the element that is mapped to the source content segment

by the content map data.

[0689] At **1612**, application **230** extracts the text-type source text content. In the present embodiment, application **230** extracts the source content by generating a text content object that corresponds to the source content. An example text content object is below (though it will be appreciated that different attributes and/or different formats are possible):

```
TABLE-US-00039    TextContent: { characters: <...>,    readingOrderIndex: <...>,  
textHierarchyLevel: <...>,    listLevel: <...>,    listMarkerType: <...>, }
```

[0690] In this example, the characters attribute of the text content object defines the actual text characters of the source content segment. The text characters may, for example, be identified based on the source identifier attribute of the source object in question and (unless stored as part of that source object) retrieved from the source design using that identifier.

[0691] In certain embodiments, application **230** is configured to trim certain white space characters from source text when extracting it. This may include, for example trimming leading and trailing “ ” (space) characters from a paragraph of text. E.g. if the source content is text such as “Here. \n”, application **230** may trim the leading and trailing space characters to result in extracted characters of “Here.\n”.

[0692] In the present embodiment, when extracting text characters application **230** is configured to preserve certain predefined inline format attributes of the source text. In particular, application **230** may preserve inline format attributes such as bold, italic, underline (and/or other attributes) which may be used to emphasise particular words or phrases. Application **230** may also preserve other inline formatting such as links.

[0693] In the present embodiment, application **230** is also configured to include certain text metadata in the text content object. This may include, for example, metadata defining: what list-level the text is (if any); what list-markers (if any) have been used; what hierarchy level the text is (which, in this example, can be extracted from the source object); and what the reading order index of the text is (which, in this example, can be extracted from the source object).

[0694] As described above, in certain circumstances a source object may be a combined source object that maps to two or more original source objects. When extracting text characters from a combined source object, application **230** processes each original source object in turn to extract the relevant text and append it to any text already extracted from previous original source objects. When appending the text from an original source object to text that has already been extracted application **230** may create a new paragraph (or new list item or the like as is relevant)—e.g. by inserting a leading newline character to the text before appending it.

[0695] At **1614**, application **230** generates a new element.

[0696] In the present example, to generate the new element application **230** initially creates a copy of the destination element that the selected source content segment has been mapped to. The copy includes the original destination element's attributes (e.g. content, size, position, rotation, format, etc.).

[0697] Application **230** then updates the new element's data. Updating the new element's data includes replacing the element's original content (i.e. the text of the original destination element) with the text of the source content segment being processed.

[0698] In the present embodiment, when generating the new text element at **1614** application **230** determines if list attributes of the new element need to be updated and, if so, updates those attributes. For example, if list attributes of the source content segment define a bulleted list but the destination element originally defined basic text (i.e. not a list), the list attributes of the new element are updated to indicate a bulleted list. Conversely, if list attributes of the source content segment define basic text but the destination element list attributes originally defined a bulleted list, the list attributes of the new element are updated to indicate basic text.

[0699] In the present embodiment, when generating the new text element at **1614** application **230** also analyses the source content segment and the destination element to determine whether one or

more inline/block format collisions exist. In the present context, an inline/block format collision may occur if relevant inline formatting of the source text would be overridden by an original block level format attribute of the new element. If application **230** determines that an inline/block format collision exists it updates the new element to remove the block level format attribute that creates the collision.

[0700] To illustrate inline/block format collisions, consider source content text of “I am very happy” (with inline formatting attributes set so the word “very” is in bold) and a destination element for that source content that has a block level attribute set so that all text of the destination element was bold. In this case, application **230** would remove the block level bold attribute from the destination element. If this was not done, then the destination element would display the entire source content text in bold, thus losing the original emphasis of the word “very”.

[0701] Application **230** may be configured to analyse various inline format attributes when determining whether one or more inline/block level format collisions exist, for example attributes that define one or more of: bold font; italics font; underlined font; strikethrough font; font colour; and/or other font formats.

[0702] At **1616**, application **230** replaces the relevant element of the new deck page (e.g. the destination element identified by the destination objection of the content map item) with the new element generated at **1614**. That is, application **230** deletes the original destination element and inserts in its place the new element. In the context of the example deck-format and destination objects described above, the new deck page will include an array of design element records and the destination object will identify one of those design element records (e.g. by an array index). In this case replacing the destination element of the new deck page includes replacing the design element record at the index indicated by the destination ID of the destination object.

[0703] Once all text-type source content segments have been transferred, processing proceeds to **1618**.

[0704] At **1618**, application **230** transfers source tables (which may correspond to table-type source objects).

[0705] Application **230** may transfer source tables in various ways. For example, for each source table application **230** may: extract the source table content (e.g. in a similar manner to **1612**); generate a new element based on the destination element that the source table is mapped to and the extracted table content (e.g. in a similar manner to **1614**); and replace the original destination element with the new element (e.g. in a similar manner to **1616**).

[0706] In certain implementations, application **230** may be configured to transfer a table in accordance with method **2500** as described below with reference to FIG. 25 (or in accordance with a similar method).

[0707] At **1620**, application **230** transfers source charts (which may correspond to chart-type source objects).

[0708] Application **230** may transfer source charts in various ways. For example, for each source chart application **230** may: extract the source chart content (e.g. in a similar manner to **1612**); generate a new element based on the destination element that the source chart is mapped to and the extracted chart content (e.g. in a similar manner to **1614**); and replace the original destination element with the new element (e.g. in a similar manner to **1616**).

[0709] In certain embodiments, application **230** generates a new chart based on the source chart and the destination chart according to method **3100** described below with reference to FIG. 31.

[0710] In the examples above, transferring content involves generating new elements that correspond to original elements of the destination page (e.g. at **1614**) and then replacing the original elements with those new elements. In alternative embodiments, application **230** may instead edit the relevant elements of the new deck page as required (excepting where a single deck page element may need to be replaced by multiple new elements, for example when multiple source fills map to a single destination fill).

[0711] A possible result of transferring text-type source content to the new deck page at **1610** is that one or more undesirable element collisions may be introduced. In particular, transferring source text may result in a text element of the new page occupying a larger area than it originally did (due to there being more source text than the element originally accommodated). In order to address this, application **230** analyses the new deck page to detect and resolve any undesirable collisions at **1622**. Generally speaking, this involves detecting what are referred to as undesirable element collisions (where pairs of elements that did not overlap or extend too close to one another in the original template page do so following the content transfer) and undesirable page collisions (where an element extends off or too close to an edge of the page). Such collisions are then resolved by shrinking the text of one or both elements in question.

[0712] While detecting and resolving undesirable conflicts is described as being performed once all source content has been transferred this could be performed at any time after text-type source content segments have been transferred.

[0713] An example method **1700** for detecting and resolving undesirable collisions is described with reference to FIG. **17**.

[0714] Following detection and resolution of undesirable collisions, generation of the new deck page is complete. Once all new deck pages have been generated, the deck is returned at **1624**.

[0715] In certain embodiments, additional operations may be performed on a new deck prior to the deck being returned. For example, in some cases the primary template which is used to generate a new deck may be associated with a colour pallet (e.g. a defined set of colours that are used in the template and are typically complimentary). In this case, the deck generated at **1602** and **1604** may be recoloured using the template colour palette. Such recolouring may, for example, be performed in accordance with a method such as method **500** described in Australian patent application 2021273643, filed on 26 Nov. 2021 and titled “Systems and methods for automatically recolouring a design”. In this case, the colour palette associated with the primary template and the deck generated at **1602** and **1604** of the present disclosure may be used as the input colour palette and input design of method **500** of Australian patent application 2021273643.

Element Collision Detection and Resolution

[0716] Turning to FIG. **17**, a method **1700** for detecting and resolving undesirable element collisions will be described.

[0717] Method **1700** may, for example, be performed at **1622** of method **1600**. Method **1700** may, however, be performed in other contexts. For example, method **1700** may be performed following a user (human or programmatic) editing the text of one or more text elements of a design page in order to determine whether those edits have resulted in any undesirable collisions (and, if so, to automatically resolve those collisions).

[0718] At **1702**, application **230** identifies any pre-existing overlaps.

[0719] When method **1700** is performed at **1622** of method **1600**, a pre-existing overlap is an overlap present in the original template page that the new template page corresponds to.

[0720] When method **1700** is performed in the context of text edits having been made to a design page, a pre-existing overlap is an overlap that was present in the design page before the text edits being made.

[0721] In order to identify pre-existing overlaps, application **230** analyses the page elements with reference to their original sizes and positions. In particular, application **230** analyses original element bounding boxes—that is, the bounding boxes of the page's elements as they were in the original template page on which the new deck page is based. In the present embodiment, in order to identify pre-existing overlaps application **230** analyses the elements of the new deck page following the content transfer performed at **1610** (noting that although content has been transferred no element sizes have yet been altered). In alternative embodiments, application **230** could be configured to identify pre-existing overlaps by analysing the elements of the original deck page on which the new deck page was based.

[0722] In the present embodiment, application **230** is configured to identify two general types of overlaps. These are referred to as element overlaps and page overlaps. An element overlap occurs when one element extends into another element (or into a defined element margin around that element). A page overlap occurs when an element extends beyond the edge of the page (or into a defined page margin).

[0723] In order to identify pre-existing overlaps, application **230** may process each element of the page in turn (or in parallel). For each element, application **230** determines any element overlaps that the element is involved in and any page overlaps that the element is involved in.

[0724] In the present embodiment, in order to determine element overlaps for a selected element application **230** performs a pair-wise analysis of a selected element with each other element on the page. In the present context, application **230** will determine that a selected element (e.g. a first element E1) is involved in an element overlap with another element (e.g. a second element E2) if any one of the following conditions are met:

$$E1_{\min Y} \leq E2_{\max Y} + \text{elementmargin}$$

[00004] $E1_{\max Y} \geq E2_{\min Y} - \text{elementmargin}$

$$E1_{\min X} \leq E2_{\max X} + \text{elementmargin}$$

$$E1_{\max X} \geq E2_{\min X} - \text{elementmargin}$$

[0725] In this example, application **230** is configured to take into account an element margin when determining element overlaps. Any appropriate element margin value may be used. For example an element margin of 50 pixels may be used. In alternative embodiments application **230** need not take into account an element margin in determining element type collisions.

[0726] In the present embodiment, if application **230** determines that an element (e.g. E1) overlaps another element (e.g. E2) it also determines a type of overlap: a contained overlap (indicating that element E1 is entirely contained within element E2) or a partial overlap (indicating element D1 overlaps but is not entirely contained within element E2). Application **230** may determine that a first element E1 is contained entirely within (or coterminous with) a second element (E2) if all of the following conditions are met:

$$E1_{\min Y} \geq E2_{\min Y}$$

[00005] $E1_{\max Y} \leq E2_{\max Y}$

$$E1_{\min X} \geq E2_{\min X}$$

$$E1_{\max X} \leq E2_{\max X}$$

[0727] In order to determine page overlaps for a selected element, application **230** determines whether any edges of the selected element's bounding box extend beyond an edge of the page (or, in the present embodiment, into a page margin). In the present context, application **230** determines page overlaps as follows:

TABLE-US-00040 Element overlaps with If Top page edge $\min Y < 0 + \text{page margin}$ Bottom page edge $\max Y > \text{page height} - \text{page margin}$ Left page edge $\min X < 0 + \text{page margin}$ Right page edge $\max X > \text{page width} - \text{page margin}$

[0728] In this example, application **230** is configured to take into account a page margin when determining page overlaps. Any appropriate page margin value may be used. For example a page margin of 100 pixels may be used. Alternatively, the page margin value may be set to the same value as the element margin value. In alternative embodiments application **230** need not take into account a page margin in determining page type overlaps.

[0729] In the present embodiment, application **230** records each pre-existing overlap that is identified (if any) in a pre-existing overlaps dataset. A simplified example of such a dataset is described below, however pre-existing overlaps may be recorded in other ways.

TABLE-US-00041 pre-existingOverlaps: elementOverlaps: shape-E1: [(text-E2, partial)], text-E2: [(shape-E1, partial)], shape-E3: [(text-E4, partial)], text-E4: [(shape-E3, contained)], text-E5: [] } pageOverlaps: shape-E1: [], text-E2: [],

shape-E3: [], text-E4: [], shape-E5: [bottomEdge] } }

[0730] In this example, the pre-existing overlaps dataset includes a set of element overlap records (recording all pre-existing element overlaps identified) and a set of page overlap records (recording all pre-existing page overlaps identified).

[0731] Each element overlap record is a key-value pair. The key identifies a particular page element (e.g. by its element array index or an alternative identifier) and, in this example, the element type. The value of a given element overlap records identifies each element (if any) that the key element overlaps (in this example in an array of element identifiers). In this example, for each element that the key element overlaps with, the overlap type is recorded—in particular a value indicating a partial overlap or a contained overlap.

[0732] Each page overlap record is also a key-value pair. The key identifies a particular page element and, in this example, the element type. The value of a given page overlap record identifies the page edge(s) that the key element overlaps (in this example an array of page edge identifiers).

[0733] The element and page overlaps of the above table are illustrated in example **1800** of FIG. **18**, which depicts: elements E1 and E2 partially overlapping one another; element E4 being contained within element E3; and element E5 extending over the bottom page edge (PE).

[0734] At **1704**, application **230** performs a reflow operation on the text elements of the new page (i.e. the new text elements as generated/added at **1610**). Generally speaking, the reflow operation serves to recalculate the bounding box for each text element on the new page based on its content (as updated during the content transfer performed at **1610**).

[0735] By way of example, application **230** may calculate a new bounding box for a text element based on the actual text content (following transfer) and the space that content occupies. This, in turn, may be based on the text characters and relevant text format attributes (e.g. font size, font family, list attributes, and/or any other relevant attributes that impact the space that text occupies).

[0736] If application **230** calculates anew bounding box for a text element (which may be smaller or larger than the element's original bounding box), application **230** updates the relevant attributes of that element's record (e.g. the size (width and height) attributes).

[0737] To illustrate reflowing, consider example **1802** of FIG. **18** which depicts: a text element (E6) before content transfer (i.e. the original element); the new element (E6') that corresponds to element E6 after content transfer but before the reflow process; and the new element E6' after the reflow process. As can be seen, the bounding box **18-4** of original element E6 encompasses the original text. Following the content transfer (and prior to the reflow operation), the text of new element E6 extends beyond the bounding box **1804** (which, prior to reflow, is the original element's bounding box). Following the reflow operation, a new bounding box **1804'** has been determined for new element E6' (the new bounding box sized according to the new text).

[0738] At **1706**, and after the page elements have been reflowed, application **230** processes the updated page elements to identify current overlaps.

[0739] In the present embodiment, application **230** identifies current overlaps in the same (or a similar) way as pre-existing overlaps are identified at **1702**: the exception being that instead of the analysis being based on the elements' original bounding boxes (e.g. before being resized at **1704**) the analysis is based on the elements' updated bounding boxes (e.g. after being resized at **1704**).

[0740] In the present embodiment, application **230** records current overlaps in a current overlaps dataset that has a format that mirrors the pre-existing overlaps dataset: that is, a set of current element overlap records and a set of current page overlap records.

[0741] To illustrate, consider examples **1808** and **1810** of FIG. **18**. Example **1808** depicts an original template page **1812** (prior to content transfer) that includes a shape element E7 (with a single circle shape fill), a text element E8 (with text “Original title”), a text element E9 (with text “Original body text that was only two lines”), a shape element E10 (with a single rounded corner rectangle fill), and a text element E11 (with text “Greeting”). Element bounding boxes are indicated as dashed line rectangles. Example **1812** depicts a new page **1812'** that is based on the

template above of example **1808** following content transfer and reflow. New page **1812'** includes elements E7', E8', E9', E10'. And E11' that correspond to original elements E7, E8, E9, E10, and E11 of example **1808**. Following content transfer: the text of element E7' is "New title that is longer", which has resulted in element E7' overlapping with element E8' (and vice versa); the text of element E9' is "New body text that includes more characters and therefore more lines than the original text an now goes off the page", which has resulted in element E9' overlapping the bottom page edge; and the text of element E11' is "New greeting" which has resulted in element E11' extending out of element E10' (which originally contained element E5' entirely).

[0742] For clarity, examples **1808'** and **1810'** provide versions of examples **1808** and **1810** respectively in which only bounding boxes are shown (with the example text and fills removed).

[0743] Example pre-existing overlap and current overlap datasets corresponding to examples **1808** and **1810** are as follows:

TABLE-US-00042 Pre-existing overlap dataset Current overlap dataset pre-existingOverlaps: {
currentOverlaps: { elementOverlaps: { elementOverlaps: { shape-E7: [(text-E8, partial)],
shape-E7: [(text-E8, partial)], text-E8: [(shape-E7, partial)], text-E8: [(shape-E7,
partial), (text-E9, partial)], text-E9: [], text-E9: [(text-E8, partial)], shape-E10:
[(text-E11, partial)], shape-E10: [(text-E11, partial)], text-E11: [(shape-E10, contained)]
text-E11: [(shape-E10, partial)] } } pageOverlaps: { pageOverlaps: { shape-E7:
[], shape-E7: [], text-E8: [], text-E8: [], text-E9: [], text-E9:
[bottomEdge], shape-E10: [], shape-E10: [], text-E11: [] text-E11: [] } }
} }

[0744] At **1708**, application **230** identifies undesirable collisions on the page. Generally speaking, an undesirable collision is a collision that has been introduced due to the content transfer performed at **1610** (e.g. a collision that was not present in the original template page but is present in the new template page following content transfer). In the present embodiment, only text elements have the potential to be resized and introduce a collision that was not present in the original page.

[0745] A method **1900** for identifying undesirable collisions is described below with reference to FIG. **19**. Method **1900** returns a set of collision objects. Each collision object in the set identifies an undesirable collision (and the set may be empty if no undesirable collisions are identified).

[0746] At **1710**, application **230** resolves the undesirable collisions identified at **1708**. A method **2000** for resolving undesirable collisions is described below with reference to FIG. **20**.

[0747] In certain embodiments, once undesirable collisions have been resolved at **1710** method **1700** is complete. In other embodiments, application **230** may be configured to re-check for undesirable collisions following **1710** (e.g. by re-performing operation blocks **1706** and **1708**) and, if further undesirable collisions are identified, resolve those collisions (e.g. by re-performing operation block **1710**). Application **230** may be configured to repeat operation blocks **1706**, **1708**, and **1710** a predetermined number of times (e.g. 1, 2, or another number of times), or to repeat these operation blocks until no undesirable collisions are identified at **1708**.

[0748] In the present embodiment, application **230** analyses elements at **1702** to identify pre-existing overlaps. In alternative embodiments, template pages may be analysed to identify pre-existing overlaps at any appropriate time (e.g. when a template page is originally created or the first time a template page is used in to generate a new deck) and the pre-existing overlap data may be stored and associated with the template page. In this case, before performing analysis to identify pre-existing overlaps application **230** may be configured to check if pre-existing overlap data for the template page already exists and, if so, retrieve that from the relevant location rather than re-determining pre-existing overlaps.

[0749] While method **1700** is described in the context of generating a new deck page, method **1700** may be performed (or be adapted to be performed) to detect and resolve collisions on any set of two or more design elements where there are original elements (that is, elements with original bounding boxes) and corresponding updated elements (that is, original elements that have been

updated or replaced with corresponding elements that may have different bounding boxes).

Identifying Undesirable Collisions

[0750] At **1708** of method **1700** application **230** identifies undesirable collisions. A method **1900** for identifying undesirable collisions will be described with reference to FIG. **1900**.

[0751] Method **1700** involves processing each current overlap that is recorded in the current overlaps dataset. In the present embodiment, application **230** iterates through each overlap that is defined in turn (however overlaps could be processed in any order or in parallel). With the example current overlap data as described above, a given overlap record may define multiple overlaps. For example, the current overlap record “text-E8: [(shape-E7, partial), (text-E9, partial)]” defines two overlaps: E8.fwdarw.E7 and E8.fwdarw.E9.

[0752] It is noted that in the present implementation the ordering of an overlap record (and the collision it defines) is relevant. That is, the overlap text-E8: [(text-E9, partial)](which may be referred to in short hand as E8.fwdarw.E9 or as E8 overlapping E9) is not the same—and is handled separately to—the overlap text-E9: [(text-E8, partial)](e.g. E9.fwdarw.E8 or E9 overlapping E8).

[0753] At **1902**, application **230** determines if there are one or more current overlaps that have not yet been processed. If so, processing proceeds to **1904**. If all current overlaps have been processed, the identification of undesirable collisions is complete (as indicated at **1912**).

[0754] At **1904**, application **230** selects one of the unprocessed current overlaps for processing.

[0755] At **1906**, application **230** determines a collision type that the selected current overlap may indicate.

[0756] In the present embodiment, application **230** is configured to identify one of three collision types: a partial collision, a container collision, or a page collision. These types of collisions are determines as follow:

TABLE-US-00043 Collision type Determined if: Partial The current overlap is a partial element type overlap and there is either: no corresponding element overlap in the pre-existing overlap data; or there is a corresponding pre-element overlap in the pre-existing data and it is also a partial element type overlap Container The current overlap is a partial element type overlap and there is a corresponding element overlap in the pre-existing data and it is a contained element type overlap, Page The current overlap is a page type overlap

[0757] To illustrate these collision types, consider the example pre-existing and current overlap datasets that correspond to examples **1808** and **1810** described above, which indicate the following collisions and collision types:

TABLE-US-00044 Collision Collision type E7.fwdarw.E8 Partial E8.fwdarw.E7 Partial E8.fwdarw.E9 Partial E9.fwdarw.E8 Partial E10.fwdarw.E11 Partial E11.fwdarw.E10 Container E9.fwdarw.bottomEdge Page

[0758] At **1908**, application **230** determines if the selected overlap indicates an undesirable collision. If so processing proceeds to **1910** where application **1910** generates undesirable collision data (in this case a collision object) in respect of the undesirable collision. If application **230** determines that the selected overlap does not define an undesirable collision (e.g. that the overlap is acceptable), processing returns to **1902**.

[0759] The processing performed at **1908** (to determine whether an overlap is an undesirable collision) and **1910** (to generate a collision object if needed) depends on various factors, including the type of collision the overlap defines, whether the overlap was a pre-existing overlap, and (in some instances) the extent of the overlap.

[0760] The collision object generated at **1910** for an undesirable collision depends on the type of the collision (which, in turn, depends on the type of overlap the collision corresponds to). In the present embodiments, each collision object identifies two objects (either a first and a second element or a first element and a page edge), a penetration direction, and a penetration distance. The penetration direction identifies a direction that the first element penetrates into the second element

or over the page edge. The penetration distance indicates how much area needs to be recovered (or, phrased alternatively, how much the element(s) in question need to reduce in size) in order to resolve the collision. The penetration distance may, for example, be calculated in pixels.

[0761] The processing performed at **1908** and **1910** for each different collision type (partial, container, and page) will be described in turn.

Undesirable Partial Type Collision

[0762] As noted, a current overlap may indicate an undesirable partial collision if the current overlap is a partial element type overlap and there is either: no corresponding element overlap in the pre-existing overlap data; or there is a corresponding pre-element overlap in the pre-existing data and it is also a partial element type overlap

[0763] For an overlap record that indicates a partial collision, application **230** determines if the overlap indicates an undesirable collision at **1908** as follows.

[0764] Initially, application **230** determines if the selected current overlap is an introduced overlap (that is, the overlap was introduced as a result of the content transfer and reflow) or a pre-existing overlap. This is done by comparing the current overlap data with the pre-existing overlap data. If the selected overlap has a corresponding overlap defined in the pre-existing overlap data, application **230** determines that that selected overlap is a pre-existing overlap. If not the current overlap is an introduced overlap.

[0765] To illustrate, consider the following example pre-existing overlap data and current overlap data:

TABLE-US-00045 Pre-existing overlap dataset Current overlap dataset pre-existingOverlaps: {
currentOverlaps: { elementOverlaps: { elementOverlaps: { shape-E7: [(text-E8, partial)],
shape-E7: [(text-E8, partial)], text-E8: [(shape-E7, partial)], text-E8: [(shape-E7,
partial), (text-E9, partial)], text-E9: [], text-E9: [(text-E8, partial)], }
} } }

[0766] In this example, the current E7.fwdarw.E8 overlap is pre-existing while the current E8.fwdarw.E9 and E9.fwdarw.E8 overlaps are introduced.

[0767] If the current partial element overlap was pre-existing, application **230** determines that the overlap does not indicate an undesirable collision and processing returns to **1902**. Otherwise, application **230** analyses the partial element overlap further.

[0768] In the present embodiment, application **230** takes into account element expansion direction when determining whether a partial element overlap indicates an undesirable collision. In the present examples, a text element's expansion direction is based on a vertical alignment attribute of the element which may take one of three values: top, middle, bottom. A text element that is top aligned has a downward expansion direction: when a new line is added to such an element, the element expands downwards. A text element that is middle aligned has both upward and downward expansion directions: when a new line is added to such an element, the element expands upwards and downwards to accommodate the text. A text element that is bottom aligned has an upward expansion direction: when a new line is added to such an element, the element expands upwards.

[0769] By way of example, when determining whether a partial element overlap of text elements E1.fwdarw.E2 indicates an undesirable collision, application **230** determines whether the expansion direction of E1 is towards element E2. If not, application **230** determines that the overlap does not indicate an undesirable collision and processing returns to **1902**. If the expansion direction of E1 is toward element E2, the collision is considered further.

[0770] To illustrate this, consider example **1816** of FIG. **18** which depicts overlapping elements (or element bounding boxes) E12' and E13'. When considering the partial element overlap record for E12'.fwdarw.E13': if the expansion direction of element E12' was upward (i.e. away from element E13'), application **230** would determine that the overlap does not indicate an undesirable collision; if the expansion direction of element E12' was downward (i.e. towards element E13') or both upward and downward (e.g. due to middle aligned text), application **230** would analyse the overlap

further. In contrast, when considering the partial element overlap E13'.fwdarw.E12': if the expansion direction of element E13' was upward (i.e. towards element E12') or both upward and downward, application **230** would analyse the overlap record further; if the expansion direction of element E13' was downward (i.e. away from element E12'), application **230** would determine that the overlap does not indicate an undesirable collision.

[0771] If application **230** does not determine that the partial element overlap is acceptable (and does not indicate an undesirable collision) due to being a pre-existing overlap or due to the expansion direction, application **230** calculates a penetration distance for the partial element overlap.

[0772] In the present example, application **230** calculates the penetration distance based on a pre-existing penetration distance and a current penetration distance.

[0773] The pre-existing penetration distance is the penetration distance calculated based on the elements' original bounding boxes—e.g. the bounding boxes of elements E1 and E2 prior to reflow. The current penetration distance is the penetration distance for those elements following reflow.

[0774] In the present embodiment, application **230** calculates the penetration distance for an element E1 that encroaches into an element E2 as the distance that E1 encroaches into E2 plus the predefined element margin.

[0775] If the original penetration distance is less than or equal to 0, the final penetration distance is the current penetration distance. If the original penetration distance is greater than 0, the final penetration distance is:

Final penetration distance=current penetration distance–pre-existing penetration distance

[0776] Taking the pre-existing penetration distance into account when calculating the (final) penetration distance takes into account the possibility that a designer may have deliberately designed a template page to have two elements close together (closer than the defined element margin).

[0777] To illustrate the penetration distance calculation, consider examples **1814** and **1816** of FIG. **18**. Example **1814** depicts a pair of original element bounding boxes E12 and E13 (e.g. before reflow). In this example the pre-existing penetration distance (PPD) may be calculated as [(E12 maxY+element margin)–E13 minY], which will give a negative value (≤ 0). Example **1816** then depicts element bounding boxes E12' and E13', which depict element bounding boxes E12 and E13 after reflow. In this example, the current penetration distance (CPD) may be calculated as [(E12' maxY+element margin)–E13' minY]. For examples **1814** and **1816**, therefore, the final penetration distance is equal to the current penetration distance.

[0778] In contrast, consider examples **1818** and **1820** of FIG. **18**. In example **1818**, the pre-existing penetration distance (PPD) between elements E14 and E5 is a value greater than zero. Accordingly, for examples **1818** and **1820** the final penetration distance will be calculated as the current penetration distance (CPD) minus the pre-existing penetration distance (PPD).

[0779] If the final penetration distance is less than or equal to the pre-existing penetration distance, application **230** determines that the overlap does not indicate an undesirable collision and processing returns to **1902**. Otherwise application **230** determines that the overlap does indicate an undesirable collision and processing proceeds to **1910** to generate a collision object. As the collision object corresponds to a partial element overlap it may be referred to as a partial collision object.

[0780] In the present embodiment, application **230** generates a partial collision object that includes data identifying: [0781] a first element, which is the key element identified by the element overlap record (e.g. text-E3); [0782] a second element, which is the relevant element from the key element's array (e.g. text-E2); [0783] a penetration direction, which is the direction that the first element penetrates into the second element; and [0784] a penetration distance, which is the final penetration distance as calculated above.

Undesirable Container Type Collision

[0785] As noted, a current overlap may indicate an undesirable container type collision if the current overlap is a partial element type overlap and there is a corresponding element overlap in the pre-existing data and it is a contained element type overlap.

[0786] In the present embodiment, application **230** is configured to determine that all container collisions are undesirable at **1908**.

[0787] Where an undesirable container collision is determined, application **230** generates a container collision object at **1910** that includes data identifying: [0788] a first element; [0789] a second element; [0790] a penetration direction; and [0791] a penetration distance.

[0792] The first element, which may be referred to as the contained element, is the key element identified by the element overlap record (e.g. text-E11 in the above example).

[0793] The second element, which may be referred to as the containing element, is the relevant element from the key element's array (e.g. shape-E10 in the above example).

[0794] The penetration direction indicates the direction that the contained element extends out of the containing element. For example, in example **1810** a penetration direction of downwards would be recorded.

[0795] The penetration distance is calculated as the distance that the contained element has increased/expanded in the penetration direction.

[0796] To illustrate, in examples **1808** and **1810** the penetration distance would be $E11' \text{ maxY} - E11 \text{ maxY}$ (that is, the contained element's updated bounding box maxY value minus its original bounding box maxY value). In contrast, if E11' extended out of E10' in an upward direction, the penetration distance for the upward penetration would be $E11 \text{ minY} - E11' \text{ minY}$ (that is, the contained element's original bounding box minY value minus its updated bounding box minY value).

[0797] In certain scenarios, a contained element may extend out of its container in multiple directions. This may occur if the text of the contained element is middle aligned (and the contained element has expanded both upwardly and downwardly). In such a scenario: the penetration direction may be either up or down (or a value indicating both); and the penetration distance is calculated as the value that is the largest of an upward penetration distance (e.g. the distance that the contained element has increased/expanded in the upward direction) and a downward penetration distance (e.g. the distance that the contained element has increased/expanded in the downward direction).

Undesirable Page Type Collisions

[0798] As noted, a current overlap may indicate an undesirable page type collision if the current overlap is a page type overlap.

[0799] In the present embodiment, application **230** is configured to determine that any current page overlap that involves a text element is an undesirable page collision (regardless of whether a corresponding pre-existing page overlap existed or not).

[0800] Where an undesirable page edge collision is determined, application **230** generates a page collision object at **1912** that includes data identifying: [0801] a first element; [0802] a page edge; [0803] a penetration direction; and [0804] a penetration distance.

[0805] The first element is the element identified by the page overlap record (e.g. text-E3).

[0806] The page edge is the page edge identified by the page overlap record (e.g. "bottomEdge").

[0807] The penetration direction is the direction that the first element penetrates over the page edge (or into the page margin). For a page edge collision, the direction will always match the page edge in question—e.g. if the page edge is the bottom page edge, the direction will be down. If the top page edge the direction will be up.

[0808] Application **230** calculates the penetration distance for a page edge collision based on the page margin discussed above and the extent to which the element extends off the page (or into that margin). By way of example, for an element E1 that has a page overlap with the bottom edge of the

boxes at **2012**. In this example, elements E16 and E17 have top aligned text (and, therefore, a downward expansion direction). Given this, application **230** determines that element E16 is responsible for the collision at **2010** and then resizes element E16 at **2012**. In this example, element E16's minY, minX, and maxX remain the same but a new maxY is obtained (new maxY=max Y of E16 following reflow-penetration distance).

[0822] With the design element record format described above, application **230** may resize an element as follows:

TABLE-US-00047 Element resize direction Element resized by Up (i.e. reduce element's minY) height = height – penetration distance Down (i.e. increase element's minY) minY = minY + penetration distance height = height – penetration distance Left (i.e. reduce element's minX) width = width – penetration distance Right (i.e. increase element's minX) minX = minX + penetration distance width = width – penetration distance

[0823] For a partial collision where a both elements are responsible, application **230** resizes both elements at **2012**. This is similar to the above, except instead of application **230** resizing one element using the entire penetration distance it portions the penetration distance between the two elements—e.g. so that one element is reduced by a first portion of the penetration distance and the other element is reduced by the a second portion of the penetration distance (the first and second portions adding to give the entire penetration distance).

[0824] For example, if a partial collision involving two responsible elements E1 and E2 is determined, and element E1 expanded 100 pixels from its original size and element E2 also expanded 100 pixels from its original size, application **230** would proportion the penetration distance equally (e.g. E1 penetration distance portion=E2 penetration distance portion=penetration distance/2). In contrast, if element E1 expanded by 150 pixels and element E2 expanded by 50 pixels then element E1 would be assigned a larger share of the penetration distance.

[0825] Application **230** may, for example, calculate penetration distance (PD) portions for elements E1 and E2 that are both responsible for a partial collision as follow.

$$E1PDportion = PD * (E1expansion / (E1expansion + E2expansion))$$
$$E2PDportion = PD * (E2expansion / (E1expansion + E2expansion))$$

[0826] Once the element penetration distance portions have been calculated, application may resize the elements as described above (except each element is resized based in its portion of the penetration distance rather than the entire penetration distance).

[0827] Examples **1828**, **1830**, and **1832** of FIG. **18** illustrate an example of a partial collision between two elements E18 and E19 and in which both elements re responsible (E18 expanding downwards and E19 expanding upwards). As can be seen after resizing (E18" and E19" in example **1832**) both elements have reduced in height.

[0828] If a responsible element of a collision is a group element, application **230** determines the portion of the penetration distance that belongs to that group element (the group's portion) and then further portions the group's portion between its member elements. Proportioning a group's penetration distance portion between its members may be performed in a similar manner to proportioning the penetration distance between elements that are jointly responsible for a partial collision as described above (e.g. based on expansion direction and how much a given member element has expanded from its original size).

[0829] For a container collision or a page edge collision a single element will be responsible. In this case, application **230** resizes the single element at **2012**. This is similar to resizing an element that is the solely responsible for a partial collision as described above.

[0830] Once the responsible element(s) has/have been resized at **2012**, application shrinks the text of each responsible element at **116**. In particular, for a given responsible element application **230** shrinks the text so it fits within the resized element (e.g. within the resized element's bounding box). Application may perform this operation in various ways. This may be referred to as a first

text resizing operation.

[0831] By way of example, application **230** may be configured to identify the largest possible font size that the text of the element can be and still fit within the bounding box. Application **230** may identify the largest possible font size by progressively reducing the font size and determining, at each reduced font size, whether the text fits. Alternative approaches are possible.

[0832] In certain embodiments, application **230** may be configured to only reduce text size to a defined minimum font size (e.g. 8 point or an alternative minimum). If the text is reduced to the minimum font size and still does not fit within the bounding box, application **230** may leave the text at the minimum font size rather than further shrinking it. In this case application **230** may also generate a text size error (e.g. a message, flag, or other indicator) to indicate that the element in question does not contain its text. The text size error may then be used by application **230** (or another application) to generate an alert to a user to draw the element in question to their attention so they can manually edit the text and/or element (and/or surrounding elements). Such an alert may, for example, involve visually distinguishing the element in a user interface when the design that includes the element is being viewed. An element may be visually distinguished in a variety of ways, e.g. by one or more of: using a particular colour to highlight the element; flashing the element on/off (i.e. displaying then not displaying the element); displaying a graphic or text overlay indicating the element; displaying the element (or a thumbnail of the element) in an exceptions user interface; and/or an alternative mechanism.

[0833] Further alternatively, if the minimum font size is reached application **230** may generate a text size error (as described above), but continue to reduce the font size until the text does fit.

Identifying Resolving Single Word Wrapping

[0834] At **2016**, application **230** determines if any single-word wrapping exists in the responsible element(s). If so, each responsible element that has single-word wrapping is processed at **2018**. If not, processing proceeds to **2020**.

[0835] In the present embodiment, application **230** is configured to determine that single-word wrapping occurs in an element if any single word in that element is less than a defined number of characters and wraps across multiple lines. In this context, a single word is a continuous sequence of characters that does not include a relevant separator character. A relevant separator character may be a character such as a space, a hyphen, a new line, or any other relevant separator character. The defined number of characters may, for example, be **15** (but any appropriate number may be used, or no defined number of characters may be used).

[0836] If application **230** determines that single word wrapping does exist in a responsible element, processing proceeds to **2018**. At **2018**, application resizes the text to resolve the single-word wrapping that has been identified. This may be referred to as a second text resizing operation. Application **230** may resize text at **2018** in the same (or a similar) manner to the text resizing performed at **2014**.

[0837] When resizing text at **2018**, application **230** may make use of a minimum font size as described above with reference to **2014**. If the minimum font size is reached without the single word wrapping being resolved application **230** may generate an error.

[0838] Following resolution (or attempted resolution) of the single word wrapping processing proceeds to **2020**.

Identifying Resolving any Intra-Hierarchy Conflicts

[0839] At **2020**, application **230** identifies whether any text resizing performed at **2014** or **2018** has introduced what will be referred to as an intra-hierarchy conflict. If so, processing proceeds to **2022**. Otherwise processing proceeds to **2024**.

[0840] In the present disclosure, an intra-hierarchy conflict exists if text that is at the same text hierarchy level has different font sizes. Consider, for example, a page with four text elements at text hierarchy level n and for which: the text of elements E1 and E2 have a font size 12, the text of element E3 has a font size of 14, and the text of element E4 has a font size of 10. In this case, an

intra-hierarchy conflict exists for text hierarchy level n.

[0841] Application **230** may be configured to identify (at **2020**) and resolve (at **2022**) intra-hierarchy conflicts in various ways.

[0842] For example, application **230** may be configured to analyse each text hierarchy level hierarchy included in the page elements in turn. For each text hierarchy level hierarchy application **230** identifies all font sizes used for text at that hierarchy level. If all font sizes for the level are the same, no intra-intra hierarchy conflict exists for that hierarchy level. If not, a conflict does exist. In this case application **230** resolves the conflict at **2020** by determining the smallest font size that is used for the hierarchy level in question and then adjusting all text at that hierarchy level to that smallest font size.

[0843] In the above example where an intra-hierarchy conflict exists for text hierarchy level n, therefore, application **230** would set all text at hierarchy level n to be font size 10 (the smallest font size at that level).

[0844] Resizing text to resolve an intra-hierarchy conflict at **2022** may be referred to as a third text resizing operation.

[0845] Once any intra-hierarchy conflicts have been resolved at **2022** processing proceeds to **2024**. Identifying Resolving any Inter-Hierarchy Conflicts

[0846] At **2024**, application **230** identifies whether any text resizing performed at **2014** or **2018** (or **2020**) has introduced what will be referred to as an inter-hierarchy conflict. If so, processing proceeds to **2026**. If not, collision resolution is complete (as indicated at **2028**).

[0847] In the present disclosure, an inter-hierarchy conflict exists if the font size of text at a lower text hierarchy level is larger than font size of text at a higher text hierarchy level. For example, in the context of the present disclosure text at hierarchy level 1 (which may, for example, be heading text) would typically be expected to be larger than text at hierarchy level 2 (which may, for example be subheading text). Similarly, text at hierarchy level 2 would typically be expected to be larger than text at hierarchy level 3 (which may, for example be body text).

[0848] Application **230** may be configured to identify (at **2024**) and resolve (at **2026**) inter-hierarchy conflicts in various ways.

[0849] For example, application **230** may initially analyse the page elements to generate an ordered set of the text hierarchy level font sizes (e.g. highest hierarchy level to lowest). Application **230** may then work through the ordered set of hierarchy level font sizes (e.g. highest hierarchy level to lowest), comparing the font size of each hierarchy level to the font size of the next lowest hierarchy level. For a given pair of hierarchy levels Ln and Lm (where Ln is higher in the hierarchy than Lm): if the font size associated with Ln is less than or equal to the font size associated with Lm, application **230** determines a new (reduced) font size for hierarchy level Lm that is less than the font size associated with Ln. In this way, any font size change that is made to a particular hierarchy level ends up cascading down to lower text hierarchy levels.

[0850] In certain implementations, application **230** may be configured to determine a new font size for a given hierarchy level Lm based on any other hierarchy levels that are lower than Lm. For example, in some instances a limited number of usable font sizes may be available (e.g. if the font size of lower hierarchy levels is already approaching a minimum font size). In this case, application **230** may make relatively small adjustments to the font size of a given hierarchy level Lm (e.g. current font size—1 point, current font size—2 points, or an alternative adjustment). Alternatively, if there are a large number of available font sizes application may make relatively large adjustments to the font size of a given hierarchy level Lm (e.g. current font size—4 point, current font size—6 points, or an alternative adjustment).

[0851] By way of example, the following table depicts four text hierarchy levels and font sizes before and after resolving the inter-hierarchy conflict that exists between levels 2 and 3 (due to level 3 having larger font size text than level 2). In this example, the font size of level 3 is reduced to 10 and (in turn) the font size of level 4 is reduced to 8.

TABLE-US-00048 Font size Font size Text before resolving after resolving hierarchy inter-hierarchy inter-hierarchy level conflict conflict 1 22 22 2 12 12 3 16 10 4 10 8

[0852] Resizing text to resolve an inter-hierarchy conflict at **2026** may be referred to as a fourth text resizing operation.

[0853] In certain embodiments, and as described above, application **230** may be configured to only reduce text size to a defined minimum font size (e.g. 8 point or an alternative minimum). In this case, if any inter-hierarchy conflicts cannot be resolved without reducing the font size of one or more text elements beyond the minimum font size application **230** may leave the text at the minimum font size rather than further shrinking it. In this case application **230** may generate a text size error, e.g. as described above. Alternatively, if the minimum font size is reached application **230** may generate a text size error (as described above), but reduce the font size below the minimum font size in order to resolve the inter-hierarchy conflict(s).

[0854] Once application **230** has resolved (or attempted to resolve) any inter-hierarchy conflicts at **2026**, collision resolution is complete (as indicated at **2028**).

[0855] While identifying and correcting intra-hierarchy conflicts at **2006** is described in the broader context of method **2000** this processing (or similar processing) may be performed to identify and correct intra-hierarchy conflicts in other contexts. For example, an application may be configured to process any selected text with appropriate attributes (e.g. text hierarchy level and font size attributes) according to the processing described at **2020** and **2022** (or similar processing) to identify and resolve intra-hierarchy conflicts. The selected text may, for example, be the text of a document-format design (e.g. a set of text items), the text of a deck-format design (e.g. a set of text elements of a deck), the text of a page of a deck-format design (e.g. a set of text elements of a deck page), or text that is otherwise selected by a user or application (e.g. a specific set of text elements or text items selected by a user or application).

[0856] While identifying and correcting inter-hierarchy conflicts at **2008** is described in the broader context of method **2000** this processing (or similar processing) may be performed to identify and correct inter-hierarchy conflicts in other contexts. For example, an application may be configured to process any selected text with appropriate attributes (e.g. text hierarchy level and font size attributes) according to the processing described at **2024** and **2026** (or similar processing) to identify and resolve inter-hierarchy conflicts. The selected text may, for example, be the text of a document-format design, the text of a deck-format design, the text of a page of a deck-format design, or text that is otherwise selected by a user or application.

Generating a Set of Design Elements Based on a Set of Source Fills and a Single Destination Element

[0857] Turning to FIG. **23**, a method **2300** for generating a set of design elements based on a set of source fills and a single destination element will be described.

[0858] Method **2300** may, for example, be performed at **1608** of method **1600** where multiple source content fills map to a single destination fill (the single destination fill corresponding to a destination element).

[0859] Method **2300** may also, or alternatively, be performed in other contexts where multiple source fills need to be mapped to a single destination element. One example of such a context is described below with reference to method **2900**.

[0860] Method **2300** will be described as being performed by client application **232** (and may, in particular, be performed by content transfer module **234**). Method **2300** may, however, be performed by an alternative application that runs on either client system **230** or at server environment **210**.

[0861] Method **2300** takes as input (or has access to) a set of source fills and a destination element.

[0862] In the context of the present disclosure, the destination element is a shape element of a deck-format design page (which may be referred to as the destination page).

[0863] When method **2300** is performed at **1608** of method **1600** the set of source fills is the set of

two or more source fills that map to a single destination fill and the destination element is the element in respect of the single destination fill those source fills map to. In this case, each source fill corresponds to a source content segment and may have corresponding source object. The destination element may correspond to a single shape-type element of a design, or to a particular component fill of such a shape-type element (which may also be treated as a shape-type element). The destination fill may have a corresponding destination object.

[0864] In alternative contexts, the set of source fills may be a set of fills (or images) that have been specifically selected by a user (or application) and the destination element may be a shape-type element that has also been specifically selected.

[0865] Method **2300** also has access to what will be referred to as a set of grid arrangements. Generally speaking, each grid arrangement defines a set of grid sections that provide a particular arrangement for a number of fills.

[0866] In the present embodiment, a grid arrangement is defined by a grid arrangement dataset. The grid arrangement dataset is a two-dimensional array of length X, with X being the number of sections of the grid arrangement (and, therefore, the number of fills accommodated by the arrangement).

[0867] Each element of a grid arrangement represents a rectangular grid section and is defined by grid section data which defines a grid section origin (e.g. a start X and a start Y coordinate) and a grid section size (e.g. a width value and a height value). In the present embodiment, the grid section data for a given grid section is a further array (which may be referred to as a grid section array) of four values: [x, y, width, height], where x: [0868] x=a starting (or origin) X value of the grid section (expressed as percentage of the total width of the grid arrangement, $0 \leq x < 1$), [0869] y=a starting (or origin) Y value of the grid section (expressed as percentage of the total height of the grid arrangement, $0 \leq y < 1$) [0870] width=a width of the grid section (expressed as percentage of the total width of the grid arrangement, $0 < \text{width} \leq 1$) [0871] height=a height of the grid section (expressed as percentage of the total height of the grid arrangement, $0 < \text{height} \leq 1$)

[0872] To illustrate grid arrangements, FIG. **24** depicts two example grids **2402** and **2404**. Grid **2402** corresponds to the following grid arrangement: [0873] $[[0, 0, 1, 0.5], [0, 0.5, \frac{1}{3}, 0.5], [\frac{1}{3}, 0.5, \frac{2}{3}, 0.25], [\frac{1}{3}, 0.75, \frac{2}{3}, 0.25]]$

[0874] Grid **2404** corresponds to the following grid arrangement: [0875] $[[0, 0, 0.5, 0.5], [0.5, 0, 0.5, 0.5], [0, 0.5, 0.5, 0.5], [0.5, 0.5, 0.5, 0.5]]$

[0876] For illustrative purposes, each grid section in FIG. **24** has been annotated with its corresponding grid section array.

[0877] As will be appreciated, grid arrangements describing additional and/or alternative grid arrangements and accommodating different numbers of sections are possible

[0878] At **2302**, application **232** selects a grid arrangement for the multiple source fills that are to be transferred. In the present embodiment, application **232** analyses the source fills and the grid arrangements to determine a grid arrangement that will require the least amount of cropping. This is described with reference to processing blocks **2304-2322**.

[0879] At **2304**, application **232** calculates a set of source fill aspect ratios. This includes calculating the aspect ratio of each source fill to be transferred. A source fill's aspect ratio is calculated as its fill width/fill height.

[0880] At **2306**, application **232** orders the source fill aspect ratios in the set—for example from largest to smallest.

[0881] At **2308**, application **232** identifies relevant grid arrangements from the set of available grid arrangements. At **2308**, a relevant grid arrangement is any grid arrangement that defines a number of grid segments that is equal to the number of source fills to be transferred. With grid arrangement arrays as discussed above, relevant grid arrangements are any that have a length equal to the number of source fills.

[0882] At **2310**, application **232** preliminarily selects one or more of the relevant grid arrangements

identified at **2302**. If a single relevant grid arrangement is identified at **2302**, application **232** selects that single relevant grid arrangement. In this case application **232** may omit processing **2312** for the single grid arrangement and select it as the final grid arrangement per **2322**. If a large set of grid arrangements are maintained, and a large number of relevant grid arrangements are identified, application **232** may be configured to select a subset of relevant grid arrangements at **2310**. For example, application **232** may randomly select a defined maximum number of grid arrangements from the relevant grid arrangements at **2310**. In other cases, application **232** may preliminarily select all relevant grid arrangements at **2310**.

[0883] At **2312**, application **232** calculates a final grid arrangement score for each grid arrangement selected at **2310** (unless a single relevant grid arrangement has been identified, in which case **2312** is omitted). This is described with reference to processing blocks **2314-2320** which are performed for each selected grid arrangement.

[0884] At **2314**, application **232** calculates a set of grid section aspect ratios for the selected grid arrangement. This includes calculating the aspect ratio of each grid section defined by the selected grid arrangement. For a given grid section, application **232** calculates the grid section ratio as:

Grid section aspect ratio=grid section width*destination element width/(grid section height*destination element height)

[0885] The destination element's width and height are taken into account when calculating a grid section's aspect ratio as the width/height of a given destination element can result in different grid sections and different grid section aspect ratios. To illustrate this, consider examples **2406** and **2408** of FIG. **24**, each of which depict the following example grid arrangement: [0886] [[0, 0, 1, 0.5], [0, 0.5, 1/3, 0.5], [1/3, 0.5, 2/3, 0.25], [1/3, 0.75, 2/3, 0.25]]

[0887] At **2316**, application **232** orders the grid section aspect ratios in the set. The grid section aspect ratios are ordered in the same way as the source fill aspect ratios are ordered at **2306**—e.g. largest to smallest. This allows matching (grid section, source fill) pairs to be identified. In this context, matching (grid section, source fill) pairs are based on aspect ratio size—e.g. so the grid section with the largest aspect ratio is matched to the source fill with the largest aspect ratio, the grid section with the second largest aspect ratio is match to the source fill with the second largest aspect ratio and so forth.

[0888] At **2318**, application **232** calculates an aspect ratio difference for each matching source fill/grid section aspect ratio pair. In the present embodiment, where the source fill and grid segment aspect ratios have been sorted, this can be done based on an index basis. E.g. aspect ratio difference [i]=absolute value(source fill aspect ratio[i]-grid segment aspect ratio[i]).

[0889] At **2320**, application **232** calculates a final grid arrangement score for the selected grid arrangement. In the present embodiment, the final grid arrangement score is based on the aspect ratio differences calculated for the selected grid arrangement at **2318**. In particular, the final grid arrangement score may be the sum of the aspect ratio differences calculated at **2318**.

[0890] At **2322**, once a final grid arrangement score has been calculated for each selected grid arrangement, application **232** selects a final grid arrangement. The final grid arrangement is selected based on the final grid arrangement scores—e.g. the arrangement with the optimal score (which in the present example is the smallest score).

[0891] At **2324**, application **232** transfers the source fills to the destination element (and destination page). This transfer is based on the grid arrangement selected at **2322** and involves processing blocks **2326** to **2334**.

[0892] At **2326**, application **232** generates a set of deck-format design elements. In particular, application **232** generates a shape-type element corresponding to each grid section of the grid arrangement selected at **2322**. This result in generating a number of elements that is equal to the number of source fills. In the present embodiment, each element generated at **2326** is a copy of the original destination element.

[0893] At **2328**, application **232** adjusts each replacement element's size and position. Application **232** associates each replacement element with a particular section of the selected grid and adjusts the element's size and position data based on the grid section's data.

[0894] For a given replacement element with original position and size data of (X.sub.0, Y.sub.0, Width.sub.0, Height.sub.0) and a grid section with data of (X.sub.1, Y.sub.1, Width.sub.1, Height.sub.1), the replacement element's new size and position data may be calculated as follows:

$$X_{new} = X_0 + (X_1 * Width_0)$$

$$Y_{new} = Y_1 + (Y_1 * Height_0)$$

[00007] $Width_{new} = Width_0 * Width_1$

$$Height_{new} = Height_0 * Height_1$$

[0895] If the original element (and, therefore, the replacement element) is associated with a viewbox having original X, Y, Width, and Height values of vbX.sub.0, vbY.sub.0, vbWidth.sub.0, and vbHeight.sub.0, the view box for the replacement element can be similarly adjusted based on the grid section's data—e.g.:

$$vbX_{new} = vbX_0 + (vbX_1 * vbWidth_0)$$

$$vbY_{new} = vbY_1 + (vbY_1 * vbHeight_0)$$

[00008] $vbWidth_{new} = vbWidth_0 * vbWidth_1$

$$vbHeight_{new} = vbHeight_0 * vbHeight_1$$

[0896] At **2330**, application **232** assigns each source fill to a matching replacement element. At **2330**, application **232** identifies matching (source fill, replacement element) pairs based on the aspect ratios of the source fills and replacement elements—e.g. so the replacement element with the largest aspect ratio is matched to the source fill with the largest aspect ratio, the replacement element with the second largest aspect ratio is match to the source fill with the second largest aspect ratio and so forth. By way of example, application **232** may assign source fills to replacement elements as follows. Application may generate an aspect-ratio ordered set of source fills—e.g. by calculating each source fill's aspect ratio and then ordering the source fills based thereon (e.g. largest to smallest). Application **232** may also generate an aspect-ratio ordered set of replacement elements—e.g. by calculating each replacement element's aspect ratio and then ordering the replacement elements based thereon (e.g. largest to smallest). For each index i, application may then assign source fill [i] to replacement element [i].

[0897] At **2332**, application **232** transfers each source fill to its assigned replacement element. This may involve, for example, updating the replacement element's content data with data that identifies (or is) the source fill.

[0898] At **2334**, application **232** adds the replacement elements to the destination page. With the example deck-format described above, application **232** may add the replacement elements to the destination page by replacing the original design element record in respect of the destination element with the replacement design element records.

[0899] Method **2300** is then complete.

Generating a New Table Based on a Source Table and a Destination Table

[0900] Turning to FIG. **25**, a method **2500** for generating anew table based on a source table and a destination table will be described.

[0901] Method **2500** may, for example, be performed at **1618** of method **1600**. In the context of method **1600**: the source table is a table-type source content segment (and has a corresponding table-type source object); the destination table is a table defined by a table-type element of a deck-format design page (and has a corresponding table-type destination object); the source table is mapped to the destination table via the content map data. If multiple tables are to be transferred at **1618**, method **2500** may be performed for each table.

[0902] Method **2500** may, however, also (or alternatively) be used (or be adapted to be used) in any context where a source table is to be transferred to a destination element. One example of such a method is described below with reference to FIG. **30**.

[0903] Method **2500** will be described as being performed by client application **232** (and may, in particular, be performed by module **234**). Method **2300** may, however, be performed by an alternative application that runs on either client system **230** or at server environment **210**.

[0904] At **2502**, application **232** generates a set of source table cell styles. The set of source table cell styles includes cell styles that are defined by cells of the source table. In the present example, the set of source table cell styles is an ordered list of source cell style records, each source cell style record corresponding to a unique cell style defined by the source table.

[0905] At **2504**, application **232** generates a set of destination table cell styles. The set of destination table cell styles includes cell styles that are defined by cells of the destination table. In the present example, the set of destination table cell styles is an ordered list of destination cell style records, each destination cell style record corresponding to a unique cell style defined by the destination table.

[0906] Application **232** may be configured to generate the sets of source and destination cell styles in various ways. An example method for generating a set of cell styles is described below with reference to FIG. **26**.

[0907] At **2505**, application **232** generates a new table. The new table includes the table content of the source table (e.g. the text or other content of the table cells) but other attributes that are taken from the destination table (e.g. size and, if relevant, position). In the present embodiment, application **232** generates the new table at **2505** in accordance with processing blocks **2506** and **2508**.

[0908] At **2506**, application **232** generates a new table.

[0909] In certain implementations, application **232** may generate the new table by creating a copy of the destination table. For example, application **234** may create copy of the table-type design element record that defines the destination table (if the destination table is in a deck-format design) or a copy of the table-type document element record that defines the destination table (if the destination table is in a document-format design).

[0910] In other implementations, application may generate the new table by creating a copy of the source table.

[0911] At **2508**, application **232** updates the new table as initially generated at **2506**.

[0912] Where the new table generated at **2506** is a copy of the destination table, application **232** updates the new table so to copy the source table's cell content to the new table. This includes copying the actual content of the source table cells (not including any table style or formatting or other attributes such as size, position, rotation, etc.) from the source table to the new table. If any table structure data is required (e.g. data defining a number of rows and columns) this may also be copied. Application **232** may copy source table content to the new table by, for example, extracting data from the relevant source table attribute(s) and writing that to the relevant attribute(s) of the new table.

[0913] Where the new table generated at **2506** is a copy of the source table, the new table already includes the source content. In this case, application **232** updates the new table at **2508** by copying (or adding) relevant attributes from the destination table. This may include, for example, attributes such as size, position, rotation, and/or other destination table attributes.

[0914] Following **2508**, the new table includes a set of new table cells. Each new table cell corresponds to a cell of the source table and includes the text content of that source table cell.

[0915] At **2509**, application **232** updates the cell styles of the new table. This involves processing each cell of the new table to determine and apply a style that was defined by the original destination table and involves processing blocks **2510** to **2518**.

[0916] At **2510**, application **232** selects the next unprocessed cell of the new table (that is, a cell

that has not yet had a destination table cell style applied to it). The cells of the new table may be processed in any order.

[0917] At **2512**, application **232** determines an index of the style record in the source table style list that defines the style of the selected cell. This will be referred to as the selected cell's style index.

[0918] At **2514**, application **232** determines a new style for the selected cell. The selected cell's new style is the style defined by the style record at the style index of the destination table style list. If the selected cell's style index is an invalid index for the destination table style list, the last style record of the destination table style list is used.

[0919] To illustrate, assume a scenario in which the selected cell's style index (as determined at **2512**) is i , and the length of the destination table style list is j . If i is less than or equal to j , then the new style for the selected cell is the style defined by the style record at index i of the destination table style list. Conversely, if i is greater than j , then the new style for the selected cell is the style defined by the style record at index j of the destination table style list.

[0920] At **2516**, application **232** applies the new style determined at **2514** to the selected cell. In the present embodiments, this includes: setting the selected cell's background to the background colour defined by the new style; and setting the selected cell's text attributes to the text attributes defined by the new style.

[0921] At **2518**, application **232** determines whether there are any cells of the new table that have not yet been processed (e.g. that have not yet had a new style determined for them). If so, processing proceeds to **2710**. If all cells of the new table have been processed, processing proceeds to **2520**.

[0922] At **2520**, application **232** determines a font scaling factor. This may be determined in various ways.

[0923] In the present embodiment, application **232** is configured to determine the font scaling factor to be the minimum of a defined minimum scaling factor and a calculated scaling factor. The defined min scaling factor may, for example, be 5.

[0924] Application **232** may calculate a font scaling factor for the table as a whole—for example a single scaling factor that results in all text of all cells fitting into the cell areas. Alternatively, application **232** may calculate a different font scaling factor for each different cell style—e.g. for a given cell style, a scaling factor that results in all text of all cells that have that style fitting into the cell areas. Alternatively, application **232** may calculate font scaling factors for each cell independently.

[0925] To calculate a font scaling factor for a cell (or a set of cells), application **232** may progressively increase (or decrease) the font scaling factor until the cell (or all cells in the set of cells) accommodate the cell text.

[0926] At **2522**, application **232** applies the font-size scaling factor(s) to the new table cells.

[0927] At **2550**, application **232** replaces the destination table with the new table.

[0928] In the context of the present disclosure, and with the example design formats described above: if the destination table is defined by an element of a deck-format design, replacing the original destination table involves replacing the design element record that defines the destination table with the design element record defining the new table; if the destination table is defined by a document element record of a document-format design, replacing the original destination table involves replacing the document element record that defines the destination table with the document element record defining the new table.

[0929] Transfer of the source table is then complete.

Generating a Set of Table Cell Styles

[0930] In method **2500**, application **232** processes tables to generate sets of cell styles. At **2502** the table is a source table (and the style list generate is a source table style list) and at **2504** the table is a destination table (and the style list generated is a destination table style list).

[0931] A method **2600** for processing an input table (which may be a source table or a destination

table) to generate a set of cell styles will be described with reference to FIG. 26. In this embodiment, the set of cell styles generated is an ordered list of cell style records.

[0932] At **2602**, application **232** initialises an empty set. This will be referred to as the style set. Any appropriate data structure may be used, provided ordering can be achieved (either by virtue of an object's position in the data structure or use of an explicit 'order' attribute of each object). The style set may, for example, be a list or array.

[0933] At **2604**, application **232** selects the next unprocessed cell of the input table. In the present embodiment, table cells are selected in a reading order. E.g. a first-in-reading-order cell will be initially selected, followed by a second-in-reading-order cell and so forth. For many languages, including English, reading order is left to right, top to bottom. To illustrate this, consider example tables **2700** and **2750** of FIG. 27. In these tables the cell numbers indicate their reading order. E.g. in table **2700** which has two columns and two rows, the left-to-right, top-to-bottom reading order is: cell 1 at (row 1, column 1) (e.g. the top left cell); cell 2 at (row 1, column 2); cell 3 at (row 2, column 1); cell 4 at (row 2, column 2).

[0934] At **2606**, application **232** extracts style attributes from the selected cell. The style attributes extracted will depend on implementation and what style attributes can be defined for a table cell.

[0935] By way of example, the style attributes extracted may include one or more of: cell background colour; cell font family; cell font weight; cell text colour; cell text decoration (e.g. underline); cell font style (e.g. italics); and/or other style attributes.

[0936] If the selected cell has text with multiple values for a given style attribute, the most common (or equally most common) value is selected for that attribute. For example, if a cell defines text with five characters in red and 3 in blue, the text colour of red will be selected as the text colour attribute defined by the cell.

[0937] At **2608**, application **232** generates a style record based on the extracted style attributes.

[0938] Application **232** may generate a style record in any appropriate way and in any appropriate format. For example, the style record may be an array with a defined element order—e.g. element index 0=background colour, element index 1=font family, etc.

[0939] At **2610**, application **232** determines if the style record generated at **2608** exists in the style list. In certain embodiments, application **232** may apply a font size tolerance when determining if the style record generated at **2608** exists in the style list. The font size tolerance may, for example, be 5% (or an alternative tolerance). In this case, if the style record generated at **2608** is the same as a style record in the style list except the font sizes are different, if the font size of the style record generated at **2608** and the existing style record are within the tolerance of each other (e.g. within 5%), application **232** will determine that the style record generated at **2608** does exist.

[0940] If, at **2610**, the style record generated at **2608** does not exist in the style list, processing proceeds to **2612**.

[0941] At **2612**, application **232** adds the record generated at **2608** to the style set. In the present embodiment the record is added to the end of (e.g. appended to) the style set. Processing then proceeds to **2614**.

[0942] If, at **2610**, the style record generated at **2608** already exists in the style list, the record generated at **2608** is discarded (i.e. not added to the style list) and processing proceeds to **2614**.

[0943] At **2614**, application **232** determines if there are any unprocessed cells in the table. If so, processing proceeds to **2604**.

[0944] If, at **2614**, all cells have been processed generation of the style list is complete. In this case processing proceeds to **2616** where the style set is returned.

[0945] To illustrate method **2600**, consider example tables **2700** and **2750** of FIG. 27.

[0946] Consider also a simplified style record that is an array of strings in the following order:

[0947] [background colour, font family, bold (true/false), italics (true/false)]

[0948] Table **2700** includes four cells with two unique styles: a first style (applied to cells 1 and 2) is indicated by bold Calibri text; a second style (applied to cells 3 and 4) is indicated by normal

(non-bold) Calibri text. For a table such as this, and a style record of the following application **232** may generate a style list such as the following: [0949] Style list=[["white", "Calibri", "T", "F"], ["white", "Calibri", "F", "F"]]

[0950] Table **2750** includes four cells with three unique styles: a first style (applied to cells 1, 2, and 3) is indicated by bold Calibri text; a second style (applied to cells 4 and 7) is indicated by italic Calibri text; a third style (applied to cells 5, 6, 8, and 9) is indicated by normal (non-bold and non-italic) Calibri text. For a table such as this, application **232** may generate a style list such as the following: [0951] Style list=[["white", "Calibri", "T", "F"], ["white", "Calibri", "F", "T"], ["white", "Calibri", "F", "F"]]

Generating a Deck-Format Design Based on a Deck-Format Design

[0952] Certain embodiments of the present disclosure are directed to generating a deck-format design based on another (source) deck-format design. This may include generating a single deck format design page based on a single (source deck format design page. Referring to FIG. **28**, a computer implemented method **2800** for doing so will be described.

[0953] In FIG. **28**, processing is generally indicated as being performed by (or at) either client system **230** or server environment **210**. In this example, the server-side processing is described as being coordinated by server application **214** (which causes other server-side applications to perform various operations). In alternative embodiments, however, the operations of method **2800** could be coordinated and/or performed by alternative applications, or could be performed by a single stand-alone application.

[0954] Certain processing blocks of method **2800** are the same (or at least similar) to corresponding processing blocks of method **600** described above (in respect of generating a deck based on a document). Such processing blocks will not be described in detail again.

[0955] At **2802**, client application **232** detects initiation of a deck to deck generation process. Initiation of the deck to deck generation process is associated with a deck (which will be referred to as the source deck). The source deck includes source content and may, for example, be defined by a deck record as described above.

[0956] The deck to deck generation process may be initiated in various ways.

[0957] By way of example, the deck to deck generation process may be initiated on detecting user input received at client application **232**. This may be user input activating a UI control such as control **422** described above. If the generate deck control **422** is activated while a deck is currently open (and, for example, displayed in preview area **402**) or otherwise selected, client application **232** may determine that the open deck is the source deck. Alternatively, on detecting activation of the generate deck control **422** client application **232** may display a search interface that allows a user to search and/or browse for, and then select, a source deck.

[0958] At **2804**, in response to detecting initiation of the deck to deck generation process, client application **232** generates a deck to deck generation request and communicates this to the server environment **210** (in this example to server application **214**). The deck generation request includes data allowing the source deck to be identified—e.g. an identifier of the source deck (which can be used to retrieve the source deck's data) or by providing the deck data itself (e.g. a deck record as described above).

[0959] At **2806**, server application **214** receives the deck to deck generation request.

[0960] At **2808**, source analysis data in respect of the source deck is generated. Generally speaking, the source analysis data provides information in respect of the content of the source deck that needs to be transferred to (or included in) any deck that is to be generated.

[0961] In the present embodiment, server application **214** passes the source deck (or an identifier thereof) to the design analysis application **216** to generate the source analysis data.

[0962] Application **216** may generate the source analysis data for the source deck according to method **500** described with reference to FIG. **5** (or a similar method). In this case, method **500** generates a set of source objects (e.g. at **508**).

[0963] As the source data will already define one or more discrete deck pages, a pagination process is not required in deck generation method **2800**. Accordingly, when generating source analysis data in respect of a deck-format design there is no need to generate content metrics data (per **516** of method **500**).

[0964] For consistency of terminology, the source data generated at **2808** will be referred to as defining a pagination candidate. In this case the pagination candidate includes a set of one or more candidate pages. Each candidate page corresponds to a (or the singular) page of the source deck, and includes a set of one or more source objects that correspond to the page's elements (or the source content defined by those elements).

[0965] At **2810**, deck generation data is generated. In the present embodiments, server application **214** passes the source analysis data (which, as noted, may be referred to as a pagination candidate) generated at **2808** (or a reference thereto) to the template matching application **220** to generate the deck generation data.

[0966] The deck generation data generated at **2180** may be the same as (or similar to) the deck generation data generated at **612** of method **600**. Moreover, the deck generation data may be generated by a method that is the same or similar as method **1400** described above.

[0967] At **2812**, server application **214** communicates the deck generation data (generated at **2810**) to the client system **230** (in this example to client application **232**).

[0968] At **2814**, client application **232** receives the deck generation data.

[0969] At **2816**, one or more new decks are generated. Each new deck that is generated is based on the deck generation data generated at **2810** (or part thereof) and (in the present embodiments) the source analysis data (generated at **2808**) and the content of the source deck itself.

[0970] In the present embodiments, a new deck is generated by the content transfer module **234**. A new deck may be generated according to method **1600** described above (or a similar method).

[0971] At **2818**, client application **232** outputs at least one of the one or more decks generated at **2816**. Client application **232** may be configured to output a (or multiple) decks as described at **620** of method **600**, though may output one or more decks in alternative ways (and/or using alternative user interfaces to UI **700** of FIG. 7).

[0972] Method **2800** may be performed in respect of either a multi-page deck-format design or a single page deck-format design.

[0973] When method **2800** is performed in respect of a multi-page deck, the processing performed operates to generate one or more new multi-page deck. The new deck includes new pages that correspond to (and include the original content of) the original pages. Each page of the new deck, however, will (unless a matching template page could not be identified at **1504** and/or a fallback page could not be identified at **1508**) have different content layouts. Moreover, in many cases the set of new pages for each new deck will all—or at least predominantly—have come from the same deck template and therefore have a common style across them. This provides a user with a convenient way of automatically generating new multi-page decks based on the content of their original multi-page deck. The user can then view the new multi-page decks and select one (or more) for downstream use (either use as is or for further editing).

[0974] When method **2800** is performed in respect of a single deck page, the processing performed operates to generate one or more new single deck pages. Once again, unless a matching template page could not be identified at **1504** and/or a fallback page could not be identified at **1508**, each new deck page will have a different content layout to the original page. This provides a user with a convenient way of automatically generating new page layouts for the content of their original page. The user can then view the new deck pages and select one (or more) for downstream use (either use as is or for further editing).

Fill Transfer

[0975] Methods **2200** and **2300** described above (with reference to FIGS. 22 and 23) include processing for mapping a set of source fills to a set of destination frames (or destination elements).

Methods **2200** and **2300** may be performed in various contexts (other than at processing block **1518** of FIG. **15** and processing block **1608** of FIG. **16**).

[0976] One example of such an alternative context is described with reference to fill transfer method **2900** of FIG. **29**.

[0977] Method **2900** is described as being performed by client application **232** (referred to as application **232** in this section for convenience). The processing described may, however, be performed by one or more alternative applications or modules (running on client system **230** and/or at server environment **210**).

[0978] At **2902**, application **232** identifies a set of one or more design elements that can accommodate fills. The one or more design elements may, for example, be shape-type elements. Application **232** may identify the set of one or more design elements based on one or more element selection user inputs. Such user inputs may include, for example, user input(s) selecting element(s) displayed on a page **404A** of a user interface such as UI **400**.

[0979] At **2904**, application **232** identifies a set of one or more fills (or images) that are to be transferred to the one or more design elements identified at **2902**. Application **232** may identify the set of one or more fills based on one or more fill selection user inputs.

[0980] At **2906**, application **232** initiates a fills transfer process. Application **232** may initiate the fills transfer process in response to a source fills user input or may automatically initiate the fills transfer process following identification of the design elements and fills.

[0981] Application **232** may be configured to detect various fill selection user inputs (at **2904**) and source fills user inputs (at **2906**).

[0982] As one example, the fill selection user input may include a user activating a “select fills” control such as control **424** of UI **400** described above. In response, application **232** may display a fill selection UI that permits further user input to browse/search for and select one or more fills. In this case, the source fills input may, for example, be user input selecting a “source fills” control provided in the fill select UI.

[0983] As an alternative example, the fill selection user input may include user input selecting one or more fill previews **412** that are displayed in a preview area such as **411** of UI **400**. In this case, the source fills input may be user input selecting a “source fills” UI control (displayed, for example, in region **420** or another UI region) or may be user input that drags the selected preview(s) to one of the selected elements.

[0984] At **2908**, application **232** maps the set of one or more fills to the set of one or more design elements. Application **232** may map the set of one or more fills to the set of one or more design elements according to the processing described with reference to method **2200** above (or similar processing)—and in particular the processing described with reference to processing blocks **2208** to **2222**.

[0985] In certain embodiments, application **232** may be configured to replace any fills of the design element(s) with the selected fills. In this case, application **232** maps the fill(s) identified at **2904** to the design element(s) identified at **2902**. In other embodiments, application **232** may be configured to add the selected fill(s) to any existing fill(s) of the one or more design element(s). In this case, application **232** maps a combined set of fills that includes the fills identified at **2904** and the existing fills of the element(s) identified at **2902** to the design element(s) identified at **2902**. In further embodiments, application **232** may provide a user with the option of either replacing or adding to any existing element fills (e.g. via an appropriate UI control).

[0986] At **2910**, application **232** transfers the set of one or more fills to the set of one or more design elements based on the fill to element mapping performed at **2908**. Application **232** may transfer the set of one or more fills to the set of one or more design elements according to method **2300** described above (or a similar method).

Table Transfer

[0987] Methods **2500** described above (with reference to FIG. **25**) described processing performed

to generate a new table based on a source table and a destination table. Method **2500** may be performed in various contexts (other than at processing block **1618** of method **1600**). One example of such an alternative context is described with reference to table transfer method **3000** of FIG. **30**. [0988] Method **3000** is described as being performed by client application **232** (referred to as application **232** in this section for convenience). The processing described may, however, be performed by one or more alternative applications or modules (running on client system **230** and/or at server environment **210**).

[0989] At **3002**, application **232** identifies a source table. The source table may, for example, be (or be defined by) a table-type design element. Application **232** may identify the source table based on one or more source table selection user inputs. Such user inputs may include, for example, a user input selecting a table-type element displayed on a page **404A** of a user interface such as UI **400**. By way of further example, a source table selection user input may be user input corresponding to a “copy” command while a table (or table element) is selected (e.g. a keyboard input, activation of a menu or other user interface control, or an alternative input).

[0990] At **3004**, application **232** identifies a destination table. Application **232** may identify the destination table based on one or more destination table selection user inputs. As one example, the destination table selection user input may include user input selecting a different table that is displayed in a user interface (such as UI **400**). The different table may be on the same design page as the source table, on a different design page of the same design that the source table was selected from, or on a page of a different design to the design that the source table was selected from.

[0991] At **3006**, application **232** initiates a table transfer process. Application **232** may initiate the table transfer process in response to a transfer table user input. A transfer table user input may, for example, be user input selecting a “transfer table” UI control (such as UI control **426** described above). By way of further example, the transfer table user input may be user input corresponding to a “paste” command following selection of a destination table (e.g. a keyboard input, activation of a menu or other user interface control, or an alternative input). Alternatively, application **232** may be configured to automatically initiate the transfer table process following identification of the source table and destination table.

[0992] At **3008**, application **232** generates a new table based on the source table and the destination table. Application **232** may generate the new table according to method **2500** described above (or a similar method).

Chart Transfer

[0993] Turning to FIG. **31**, a method **3100** for generating a new chart based on a source chart and a destination chart will be described. Method **3100** (or certain processing of method **3100**) may, for example, be performed at **1620** of method **1600** described above. Method **3100** may, however, be performed in other context where a new chart is to be generated based on a source chart and a destination chart.

[0994] Method **3100** is described as being performed by client application **232** (referred to as application **232** in this section for convenience). The processing described may, however, be performed by one or more alternative applications or modules (running on client system **230** and/or at server environment **210**).

[0995] At **3102**, application **232** identifies a source chart. The source chart may, for example, be (or be defined by) a chart-type design element. Application **232** may identify the source chart based on one or more source chart selection user inputs. Such user inputs may include, for example, a user input selecting a chart-type element displayed on a page **404A** of a user interface such as UI **400**. By way of further example, a source chart selection user input may be user input corresponding to a “copy” command while a chart (or chart element) is selected (e.g. a keyboard input, activation of a menu or other user interface control, or an alternative input).

[0996] In the present embodiment, the source chart will include (or be associated with) source chart content data, source chart colour data, and source chart type data. The source chart content data

will define one or more data series that the chart displays. The source chart colour data will define one or more colours that are used to display the source chart data series. Typically each data series will be associated with a separate colour, however in some cases two or more different data series may be associated with the same colour. The source chart type data defines a chart type which, in turn, determines how the data series are displayed. Various chart types may be available, for example: a bar chart type; a line chart type; a pie chart type; a scatter plot chart type; and or other chart types.

[0997] At **3104**, application **232** identifies a destination chart. Application **232** may identify the destination chart based on one or more destination chart selection user inputs. As one example, the destination chart selection user input may be user input selecting a different chart that is displayed in a user interface (such as UI **400**). The different chart may be on the same design page as the source chart, on a different design page of the same design that the source chart was selected from, or on a page of a different design to the design that the source chart was selected from.

[0998] In the present embodiment, the destination chart will include (or be associated with) destination chart content data (defining one or more data series of the destination chart), destination chart colour data (defining one or more colours that are used to display the data series), and destination chart type data (defining a destination chart type).

[0999] At **3106**, application **232** initiates a chart transfer process. Application **232** may initiate the chart transfer process in response to a transfer chart user input. A transfer chart user input may, for example, be user input selecting a “transfer chart” UI control (such as UI control **428** described above). By way of further example, the transfer chart user input may be user input corresponding to a “paste” command following selection of a destination chart (e.g. a keyboard input, activation of a menu or other user interface control, or an alternative input). Alternatively, application **232** may be configured to automatically initiate the transfer chart process following identification of the source table and destination table.

[1000] Where method **3100** is performed at **1620** of method **1600**, the source chart and destination chart are determined based on the content map data (e.g. a content map item that maps a particular source chart to a particular destination chart), and chart transfer is automatically initiated.

[1001] At **3108**, application **232** generates a new chart.

[1002] The new chart includes the source chart content data.

[1003] Where the destination chart is defined by a chart-type design element, the new chart may include relevant attributes from that element—for example size, position, rotation attributes that define where the chart is positioned on a design page.

[1004] In certain implementations, application **232** may be configured to associate the new chart with the destination chart type. In this case, application **232** is configured to determine whether destination chart type is compatible with the source chart data series. If so, application **232** will associate the new chart with the destination chart type. If not, application **232** will associate the new chart with the source chart type.

[1005] In other implementations, application **232** may be configured to associate the new chart with the source chart type.

[1006] At **3110**, application **232** determines whether one or more new chart colours are required.

[1007] If the number of source chart colours is greater than the number of destination chart colours, application **232** determines that one or more new chart colours are required and processing proceeds to **3112**.

[1008] If the number of source chart colours is less than or equal to the number of destination chart colours, application **232** determines that new chart colours are not required and processing proceeds to **3114**.

[1009] At **3112**, application **232** generates one or more new chart colours.

[1010] Application **232** may be configured to generate n new chart colours so that the number of destination chart colours and the number of new chart colours is equal to the number of source

chart colours.

[1011] Alternatively, application **232** may be configured to generate n new chart colours so that the number of destination chart colours and the number of new chart colours is equal to the number of source chart data series.

[1012] In the present embodiments, application **232** generates each new chart colour based on the destination chart colours.

[1013] As one example, application **232** may generate each new colour as a variant of a particular destination chart colour. For example, a new chart colour may be generated as a brightness or luminance variant of a destination chart colour.

[1014] As another example, application **232** may generate a new chart colour to be a colour that is complementary to a destination chart colours (e.g. selecting a new colour that is opposite a destination chart colour on a colour wheel).

[1015] Where multiple new colours are provided, application **232** may generate destination chart colour variants in order—for example: generating a first-in-order new colour as a variant of a first-in-order destination chart colour; generating a second-in-order new colour as a variant of a second-in-order destination chart colour; and so forth. If the number of new colours that needs to be generated exceeds the number of destination chart colours, application **232** may cycle back through the destination chart colours. In this case, application **232** will generate a different variant of a given destination chart colour each time. For example if four new colours are required and there are two destination colours, application **232** may generate: a first variant of the first destination colour; a first variant of the second destination colour; a second variant of the first destination colour; and a second variant of the second destination colour.

[1016] Once the one or more new chart colours are generated, processing proceeds to **3114**.

[1017] At **3114**, application **232** assigns each data series of the new chart (which correspond to the source chart data series) to a data series colour. If no new chart colours were required, then each data series as assigned to a destination chart colour. If one or more new chart colours were required, then one or more data series will be assigned to a destination chart colour and one or more data series will be assigned to a new chart colour as generated at **3112**.

[1018] Application **232** may be configured to assign chart colours in order. For example, application **232** may assign: a first-in-order data series to a first in order destination chart colour (the first in order destination chart colour being the destination chart colour assigned to a first in order destination chart data series); a second-in-order data series to a second-in-order destination chart colour (the second in order destination chart colour being the destination chart colour assigned to a second in order destination chart data series); and so forth. Once all destination chart colours have been assigned to data series, application may then start assigning new chart colours to data series. New chart colours may also be assigned to data series in order (e.g. in the order they were generated).

[1019] Application **232** may be configured to generate new chart colours so that the number of destination chart colour and the number of new chart colours is equal to the number of source chart colours.

[1020] Once each new chart data series has been assigned to a colour, generation of the new chart is complete. Where the new chart is being included in a design, application **232** may replace a design element that defined the destination chart with an element defining the new chart (or may update the data of the design element that defined the destination chart with the new chart data).
Determining if a Destination Fill can be Replaced by a Partial Fill

[1021] Turning to FIG. **32**, a method **3200** for determining a whether a destination fill can be replaced by a partial or complete type source fill or not will be described.

[1022] As described above, in the context of the present disclosure a partial fill is a fill with one or more transparent regions while a complete fill is a fill with no transparent regions.

[1023] In many situations a design (such as s template design) may be designed with a fill

positioned on top of (i.e. at a higher depth) one or more other elements. In some cases, an overlying fill such as this may be a partial fill with the designer's intention being that one or more transparencies of the partial fill will expose the underlying element(s) (or parts thereof). In other cases, however, an overlying fill may be a complete fill with the designer's intention being that the overlying fill covers any underlying element(s) (or portions thereof) so they are not visible. Given this, replacing a complete fill with a partial fill may be appropriate in some circumstances but not others. Method **3200** is performed to determine whether a fill of a design (such as a template) should only be replaced by a complete fill or whether it can be replaced by a partial fill.

[1024] In the present example, method **3200** determines whether a destination fill that is a complete fill must be replaced by a complete source fill, or whether it could be replaced by a partial source fill or a complete source fill.

[1025] Method **3200** may, for example, be performed as part of method **500** described above. In this case method **3200** is performed to determine a value for the appropriate for fill role attribute of a fill type destination object (the destination object corresponding to a shape-type element that defines a fill). Method **3200** may, however, be performed in other contexts.

[1026] Method **3200**, operates to set an `acceptsPartial` value for a fill to either true (indicating that a partial fill can be transferred to the destination fill) or false (indicating that only a complete fill can be transferred to the destination fill).

[1027] Method **3200** is described as being performed by design analysis application **216** (referred to as application **216** in this section for convenience). The processing described may, however, be performed by one or more alternative applications or modules.

[1028] At **3202**, application **216** determines (or retrieves) element bounding boxes (which may be referred to as the original element bounding boxes) and depth (e.g. z-index) values for a set of elements. When method **3200** is performed as part of method **500**, the set of elements is a set of elements of a template page. When method **3200** is performed in other contexts the set of elements may be an alternative set of elements—e.g. a subset of a deck-format design page's elements that are selected by a user or an application. As described above, each element's original bounding box may be calculated based on by size and position attributes (and may be a set of (minX, minY, maxX, maxY) values). In the example above, each elements z-index (or depth) is determined based on the position of the element in the page's elements array.

[1029] At **3204**, application **216** calculates expanded element bounding boxes for each element in the set of elements. Application **216** may calculate expanded element bounding boxes in various ways. For example, application **216** may calculate expanded bounding boxes by expanding each element's bounding box by a predefined fixed margin (e.g. of 3 pixels or an alternative number of pixels). Alternatively, application **216** may calculate an element's expanded bounding box by a margin that is relative to (and calculated based on) the element's original bounding box size. For example, application **216** may calculate an element's expanded bounding box based on an expansion factor that is applied to the element's original bounding box. The expansion factor may, for example, be 1.02, 1.05, 1.1 or an alternative expansion factor). Further alternatively, application **216** may calculate an element's expanded bounding box by a margin that is relative to (and calculated based on) the size of the page that the set of elements are part of.

[1030] At **3206**, application **216** selects a next fill from the set of elements being processed. In the present examples a fill is defined by a shape-type element (and be associated with a fill-type destination object). Application **216** may select fills from the set of elements in any order.

[1031] At **3208**, application **216** determines if the fill is rectangular (as opposed to being cropped to another shape such as a circle or other non-rectangular path/shape). If the fill is not rectangular, application **216** determines that the selected fill cannot accept partial fills and at **3210** sets `acceptsPartial=false`. Processing then proceeds to **3224**.

[1032] If, at **3208**, the selected fill is rectangular, processing to **3212**. At **3212**, application **216** initialises the `acceptsPartial` value for the selected fill to True.

[1033] Over processing blocks **3214** to **3222**, application **216** compares the selected fill to one or more of the other elements in the set of elements. For each other element application **216** determines whether certain properties of the element are such that the element makes the selected fill inappropriate for replacement by a partial fill. If application **216** identifies an element that makes the selected fill inappropriate for replacement by a partial fill, no further element need to be considered for the selected fill. If a given element does not make the selected fill inappropriate for replacement by a partial fill, application **216** proceeds to compare the selected fill with other elements in the set of elements (unless all other elements have already been considered). If none of the elements make the selected fill inappropriate for replacement by a partial fill, application **216** determines that the selected fill is appropriate for replacement by a partial fill. This process is described in further detail below.

[1034] At **3214**, application **216** selects the next element from the set of elements to compare with the selected fill. Elements may be selected in any order (though the element corresponding to the selected fill itself need not be selected).

[1035] At **3216**, application **216** determines whether the selected element is behind the selected fill and contains the selected fill. This determination is based on the z-index values and expanded bounding boxes (as calculated at **3204**) of the selected fill and the selected element. Application **216** will determine that the selected element contains the selected fill if all of its bounding box edges are beyond or the same as the bounding box edges of the selected fill—e.g. if all of the following conditions are met for a selected fill F1 and a selected element E1:

$$\begin{aligned} &F1_{\min Y} \geq E1_{\min Y} \\ [00009] &F1_{\max Y} \leq E1_{\max Y} \\ &F1_{\min X} \geq E1_{\min X} \\ &F1_{\max X} \leq E1_{\max X} \end{aligned}$$

[1036] If, at **3216**, application **216** determines that the selected element is behind the selected fill and fully contains the selected fill, application **216** determines that the selected element does not make the selected fill inappropriate for replacement by a partial fill. In this case processing the selected element is complete and processing proceeds to **3222** (with the selected fill's `acceptsPartial=true` value maintained).

[1037] If, at **3216**, application **216** determines that the selected element is not behind the selected fill or the selected element does not fully contain the selected fill, processing proceeds to **3218**.

[1038] At **3218**, application **216** determines whether the selected fill and the selected element intersect. Application **216** will determine that the selected fill and the selected element intersect if their expanded bounding boxes overlap (irrespective of the depth or z-index of the selected fill and selected element).

[1039] If, at **3218**, the selected fill and the selected element do intersect, application **216** determines that the selected fill cannot accept partial fills and at **3220** sets `acceptsPartial=false`. Processing then proceeds to **3224**.

[1040] If, at **3218**, the selected fill and the selected element do not overlap, application **216** determines that the selected element does not make the selected fill inappropriate for replacement by a partial fill. In this case processing the selected element is complete and processing proceeds to **3222**.

[1041] At **3222**, application **216** determines whether there are further elements to compare the currently selected fill to. If so, processing proceeds to **3214** to select the next element. If not, processing proceeds to **3224**.

[1042] At **3224**, application **216** records the ‘appropriate for fill roles’ attribute value for the selected fill. In the present example, if the “`acceptsPartial`” value is true, application **216** records an ‘appropriate for fill roles’ attribute value that indicates the fill is appropriate for (and can be replaced with) either partial or complete fills. If the “`acceptsPartial`” value is false, application **216** records an ‘appropriate for fill roles’ attribute value that indicates the fill is only appropriate for

(and can only be replaced with) complete fills. Processing then proceeds to **3226**.

[1043] At **3226**, application **216** determines whether there are further fills analyse. If so, processing proceeds to **3206** to select the next fill. If not, processing is complete (as indicated at **3228**).

Determining Text Hierarchy Levels

[1044] Turning to FIG. **33**, a method **3300** for processing a set of input paragraphs to determine a set of text hierarchy levels defined by those paragraphs will be described.

[1045] Method **3300** may, for example, be performed as part of (or in advance of) method **500** described above. In this case, each text type content segment of the input deck (or each text type analysis object) is an input paragraph.

[1046] Method **3300** may, for example, be performed as part of (or in advance of) method **800** described above. In this case, each text type content segment of the source document (or each text type source object) is an input paragraph.

[1047] Method **3300** may, however, be performed in other contexts. For example. Method **3300** may be performed to determine a set of text hierarchy levels for any set of input paragraphs that have been selected by a user or application.

[1048] For illustrative purposes, method **3300** will be described with reference to example page **3400** of FIG. **34**. Example page **3400** depicts seven input paragraphs which have text formats as follows.

TABLE-US-00049 Input Font List indent. All para ID. size level Underline caps Bold 1 30 0 (not list) N N N 2 18 0 Y N N 3 17 0 N N Y 4 18 1 N N N 5 18 1 N N Y 6 18 0 N N N 7 18 1 N N N

[1049] Generally speaking, method **3300** involves generating a working set of input paragraphs (or input paragraph identifiers) and then progressively sub-dividing that working set into subgroups of input paragraphs based on various format attributes that the input paragraphs may be associated with (or the absence of such format attributes). At the end of the method, the subgroups of the working set define the text hierarchy levels (and the order of those subgroups in the working set define the order of the hierarchy levels).

[1050] At **3302**, application **216** generates a working set of input paragraphs. This may, for example, be an array of paragraph identifiers. Application **216** orders the working set of input paragraphs based on the input paragraph font sizes, from largest font size to smallest font size. In the present embodiment, if a single input paragraph includes multiple font sizes, application **216** determines that the font size for the input paragraph is the font size with the largest number of non-whitespace characters of the input paragraph. If a paragraph includes two or more font sizes that have the same largest number of non-whitespace characters, application **216** may be configured to determine the largest font size with the same largest number of non-whitespace characters to be the paragraph's font size.

[1051] To illustrate, the working set corresponding to the input paragraphs of example page **3400** may be as follows (using input paragraph identifiers): [1052] [1, 2, 4, 5, 6, 7, 3]

[1053] At **3304**, application **216** divides the working set of input paragraphs into font size groups. This may be referred to as a first-in-order subdivision of the working set.

[1054] In certain embodiments, each distinct font size determined at **3302** is assigned to its own font size group. To illustrate this embodiment, dividing the working set above would result in the following font size groups:

TABLE-US-00050 Group 1 Group 2 Group 3 [[1] [2, 4, 5, 6, 7] [3] Font = 30 Font = 18 Font = 17

[1055] In other embodiments, application **232** applies a tolerance when generating font size groups. The tolerance may, for example, be 10%. To illustrate this embodiment, dividing the working set above would result in the following font size groups:

TABLE-US-00051 Group 1 Group 2 [1] [2, 4, 5, 6, 7, 3]] Font = 30 Font = 18 & 17

[1056] The remaining examples are provided in the context of these font size sub-groups (i.e. with a tolerance applied).

[1057] At **3306**, application **216** subdivides each font size group in the working set based one or

more list attributes. This may be referred to as a first-in-order subdivision of the existing groups of the working set. In particular, application **216** subdivides each font size group based on list indentation levels (or the absence of list indentation). A new subgroup is created for each list indentation level encountered. For each font size group that is subdivided, application **216** orders the list indentation level sub-groups from the smallest list indentation level to the largest list indentation level. To illustrate this, subdividing the working set above based on list indentation level provides:

TABLE-US-00052 Group 1 Group 2.2 Group 2.2 [[1] [2, 6, 3] [4, 5, 7]] Font = 30 Font = 18 & 17
Font = 18 & 17 List = none List = none List = 1

[1058] In this example, group 1 remains unchanged and group 2 has been subdivided into group 2.1 (no list indent) and group 2.2 (list indent level 1).

[1059] At **3308**, application **216** analyses each group in the working set that is not associated with a list to determine whether subdivision of that group based on an underline format is required. For any group in the working set that is not associated with a list and that includes one or more input paragraphs that are underline paragraphs and one or more input paragraphs that are not underline paragraphs, application **216** divides that group into an underline subgroup (that includes the underline input paragraphs) and a non-underline subgroup (that includes the non-underline input paragraphs). This may be referred to as a second-in-order subdivision of the working set.

Application **216** then orders the underline/non-underline subgroups in that order (e.g. underline followed by non-underline). In the present embodiment, application **216** will determine that a paragraph is an underline paragraph only if all non-whitespace characters of that paragraph are underlined characters. If any non-whitespace characters of a paragraph are not underlined characters, application **216** determines that the paragraph is not an underline paragraph.

[1060] To illustrate this, subdividing the working set above based on underline provides:

TABLE-US-00053 Group 1 Group 2.2.1 Group 2.2.2 Group 2.2 [1] [2] [6, 3] [4, 5, 7]] Font = 30
Font = 18 & 17 Font = 18 & 17 Font = 18 & 17 List = none List = none List = none List = 1
Underline = no Underline = yes Underline = no Underline = no

[1061] In this example, group 1 remains unchanged, group 2.2 has been divided into group 2.2.1 (underline) and 2.2.2 (non-underline), and group 2.2 remains unchanged (as it has list indentation).

[1062] At **3310**, application **216** analyses each group in the working set that is not associated with a list to determine whether subdivision of that group based on an all-caps format is required. For any group in the working set that is not associated with a list and that includes one or more input paragraphs that are all-caps paragraphs and one or more input paragraphs that are not all-caps paragraphs, application **216** divides that group into an all-caps subgroup (that includes the all-caps input paragraphs) and a non-all-caps subgroup (that includes the non-all-caps input paragraphs). This may be referred to as a third-in-order subdivision of the working set. Application **216** then orders the all-caps/non-all-caps subgroups in that order (e.g. all-caps followed by non-all-caps). In the present embodiment, application **216** will determine that a paragraph is an all-caps paragraph only if all non-whitespace characters of that paragraph are all-caps characters. If any non-whitespace characters of a paragraph are not all-caps characters, application **216** determines that the paragraph is not an all-caps paragraph.

[1063] In the present example, none of the input paragraphs include all-caps text so the working set does not change.

[1064] At **3312**, application **216** analyses each group in the working set that is not associated with a list to determine whether subdivision of that group based on a bold format is required. For any group in the working set that is not associated with a list and that includes one or more input paragraphs that are bold paragraphs and one or more input paragraphs that are not bold paragraphs, application **216** divides that group into a bold subgroup (that includes the bold input paragraphs) and a non-bold subgroup (that includes the non-bold input paragraphs). This may be referred to as a fourth-in-order subdivision of the working set. Application **216** then orders the bold/non-bold

subgroups in that order (e.g. bold followed by non-bold). In the present embodiment, application **216** will determine that a paragraph is a bold paragraph only if all non-whitespace characters of that paragraph are bold characters. If any non-whitespace characters of a paragraph are not bold characters, application **216** determines that the paragraph is not a bold paragraph.

[1065] To illustrate this, subdividing the working set above based on bold format provides:

TABLE-US-00054 Group 1 Group 2.2.1 Group 2.2.2.1 Group 2.2.2.2 Group 2.2 [[1] [2] [3] [6] [4, 5, 7]] Font = 30 Font = 18 & 17 Font = 18 & 17 Font = 18 & 17 Font = 18 & 17 List = none List = none List = none List = none List = 1 Underline = no Underline = yes Underline = no Underline = no Underline = no All-caps = no All-caps = no All-caps = no All-caps = no All-caps = no Bold = no Bold = no Bold = yes Bold = no Bold = no

[1066] In this example: group 1 remains unchanged; group 2.2.1 remains unchanged; group 2.2.2 has been divided into group 2.2.2.1 (bold) and 2.2.2.2 (non-bold); and group 2.2 remains unchanged (as it has list indentation).

[1067] At **3314**, determination of the text hierarchy levels is complete. In particular, each subgroup in the working set defines a different text hierarchy level (and the input paragraphs that belong to that hierarchy level) and the order of the subgroups defines the order of the hierarchy levels (the subgroup at index 0 of the working set being associated with the topmost text hierarchy level). In the above example, therefore, five distinct text hierarchy levels have been identified: text hierarchy level 1 (with input paragraph 1); text hierarchy level 2 (with input paragraph 2); text hierarchy level 3 (with input paragraph 3); text hierarchy level 4 (with input paragraph 6); and text hierarchy level 5 (with input paragraphs 4, 5, and 7).

[1068] At **3314** application **216** may return the text hierarchy levels along with the associated input paragraphs and/or associated format attributes. In addition, or alternatively, application **216** may associate each text hierarchy level with its associated input paragraph(s) (and/or with analysis objects corresponding to those paragraphs and/or with design elements corresponding to those paragraphs).

[1069] The particular format attributes that are used at each subdivision described above have been identified to generate set of text hierarchy levels that extract core text structure well for both graphic designs (which may, for example, be deck-format designs) and for word processing documents (which may, for example, be document-format designs). In alternative implementations, however, the particular format that is used at each subdivision may be varied.

CLAUSES

[1070] Further examples of specific feature combinations taught within the present disclosure are set out in the following sets of numbered clauses.

Clause Set A

[1071] Clause a.1. A computer implemented method for generating analysis data in respect of a deck-format design, the method including: [1072] accessing deck-format design data in respect of the deck-format design, the deck-format design data defining a first page of the deck format design, the first page including a set of one or more design elements, each element of the one or more design elements including position data that defines a position at which the element is positioned on the first page and content data defining content that is to be displayed on the first page; [1073] selecting a first design element of the one or more design elements, the content data of the first element defining first content; and [1074] generating a first analysis object corresponding to the first element, the first analysis object including a first set of analysis object attributes, the first set of analysis object attributes including: [1075] a first target identifier attribute that identifies the first element; [1076] a first type attribute that identifies a content type of the first content; and [1077] a first reading order attribute that identifies a position of the first element in a reading order of the one or more design elements; and [1078] associating the first analysis object with the first page.

[1079] Clause a.2. The computer implemented method of clause a.1, wherein the first content includes a first separable content item and a second separable content item, and wherein: [1080] the

first analysis object corresponds to the first separable content item; and [1081] the first target identifier attribute identifies both the first element and the first separable content item.

[1082] Clause a.3. The computer implemented method of clause a.2, wherein the method further includes: [1083] generating a second analysis object corresponding to the second separable content item, the second analysis object including a second set of analysis object attributes, the second set of analysis object attributes including a second target identifier attribute that identifies the first element and the second separable content item; and [1084] associating the second analysis object with the first page.

[1085] Clause a.4. The computer implemented method of clause a.2 or a.3, wherein the first element is a shape type element, the first separable content item is a first fill, and the second separable content item is a second fill.

[1086] Clause a.5. The computer implemented method of clause a.2 or a.3, wherein the first element is a text type element, the first separable content item is a first vertically delineated block of text, and the second separable content item is a second vertically delineated block of text.

[1087] Clause a.6. The computer implemented method of any one of clauses a.1 to a.5, wherein: [1088] the first element is a text type element and the first content is text content having a text hierarchy level; and [1089] the first set of analysis object attributes further includes a text hierarchy level attribute that records the text hierarchy level of the text content.

[1090] Clause a.7. The computer implemented method of any one of clauses a.1 to a.6, wherein the first element is a text type element and the first content is text content, the first set of analysis object attributes includes a characters attribute, and the method further includes: [1091] analysing the text content to calculate a characters value, the characters value being based on a number of characters of the text content; and [1092] recording the characters value using the characters attribute.

[1093] Clause a.8. The computer implemented method of any one of clauses a.1 to a.7, wherein the first element is a text type element and the first content is text content, the first set of analysis object attributes includes a lines attribute, and the method further includes: [1094] analysing the text content to calculate a lines value, the lines value providing a measure of the vertical capacity of the first element; and [1095] recording the lines value using the lines attribute.

[1096] Clause a.9. The computer implemented method of any one of clauses a.1 to a.8, wherein the deck-format design is a destination design that is to be used as a destination in a design generation process, and wherein the first set of analysis object attributes further includes a receive content attribute, and wherein the method further includes: [1097] analysing the first element to determine if the first element is an element that can receive source content in a content transfer process; and [1098] assigning the receive content attribute with a value indicating whether the first element is an element that can receive source content or not.

[1099] Clause a.10. The computer implemented method of any one of clauses a.1 to a.9, wherein the deck-format design is a destination design that is to be used as a destination in a design generation process, and wherein the first set of analysis object attributes further includes an appropriate for fill role attribute, and wherein the method further includes: [1100] analysing the first design element to determine if a fill defined by the first design element can be replaced by a partial-type replacement fill that includes one or more transparent regions; and [1101] in response to determining that the fill defined by the first design element can be replaced by a partial-type replacement fill, assigning the appropriate for fill role attribute with a value indicating that the fill defined by the first design element can be replaced by a partial-type replacement fill.

[1102] Clause a.11. The computer implemented method of clause a.10, wherein analysing the first design element to determine if the fill defined by the first design element can be replaced by a partial-type replacement fill is performed in accordance with the method of any one of clauses p.1 to p.15.

[1103] Clause a.12. The computer implemented method of any one of clauses a.1 to a.8, wherein

the deck-format design is a source design that is to be used in a design generation process, and wherein the first set of analysis object attributes further includes a transfer content attribute, and wherein the method further includes: [1104] analysing the first element to determine if the first content is source content that is to be transferred in a content transfer process; and [1105] assigning the transfer content attribute with a value indicating whether the first content is source content or not.

[1106] Clause a.13. The computer implemented method of any one of clauses a.1 to a.18, wherein the design is a source design that is to be used in a design generation process, and wherein the first set of analysis object attributes further includes a fill role attribute, and wherein the method further includes: [1107] analysing the first design element to determine if a fill defined by the first design element is a partial-type fill that includes one or more transparent regions or a complete-type fill that does not include any transparent regions; and [1108] in response to determining that the fill defined by the first design element is a partial-type fill, assigning the fill role attribute with a value indicating that the fill defined by the first design element is a partial-type fill.

[1109] Clause a.14. The computer implemented method of any one of clauses a.1 to a.13, further including: [1110] generating a partition key in respect of the first page, the partition key including a plurality of partition key values that provide a first measure of the type and amount of content that can be accommodated by the first page; and [1111] associating the partition key with the first page.

[1112] Clause a.15. The computer implemented method of clause a.14, wherein generating the partition key includes generating a partition key texts value, the partition key texts value indicating a number of text type elements in the set of one or more elements.

[1113] Clause a.16. The computer implemented method of clause a.14 or a.15, wherein generating the partition key includes generating a partition key fills value, the partition key fills value indicating a number of fills that the set of one or more elements can accommodate.

[1114] Clause a.17. The computer implemented method of any one of clauses a.15 to a.16, wherein generating the partition key includes generating a partition key charts value, the partition key charts value indicating a number of charts that the set of one or more elements can accommodate.

[1115] Clause a.18. The computer implemented method of any one of clauses a.14 to a.17, wherein generating the partition key includes generating a partition key tables value, the partition key tables value indicating a number of tables that the set of one or more elements can accommodate.

[1116] Clause a.19. The computer implemented method of any one of clauses a.1 to a.18, further including: [1117] generating a page vector in respect of the first page, the page vector including a plurality of page vector values that provide a second measure of the type and amount of content that can be accommodated by the first page; and [1118] associating the page vector with the first page.

[1119] Clause a.20. The computer implemented method of clause a.19, wherein generating the page vector includes generating a set of one or more page vector characters values, wherein a first page vector characters value is associated with a first text hierarchy level and is based on a number of text characters in the first page that are at the first text hierarchy level.

[1120] Clause a.21. The computer implemented method of clause a.19 or a.20, wherein generating the page vector includes generating a set of one or more page vector lines values, wherein a first page vector lines value is associated with a first text hierarchy level and is based on a number of lines of text in the first page that are at the first text hierarchy level.

[1121] Clause a.22. The computer implemented method of any one of clauses a.19 to a.21, wherein generating the page vector includes generating one or more page vector values selected from a group including: a fills aspect ratio value that is based on aspect ratios of any fills in the first page; a partial fills value that is based on a number of partial-type fills in the first page; a complete fills value that is based on a number of complete-type fills in the first page; a charts aspect ratio value that is based on aspect ratios of any charts in the first page; a tables aspect ratio value that is based on aspect ratios of any tables in the first page.

[1122] Clause a.23. The computer implemented method of any one of clauses a.1 to a.22, further including: [1123] generating a set of content metric values in respect of the first page, the set of content metric values including a plurality of content metric values that provide a third measure of the type and amount of content that can be accommodated by the first page; and [1124] associating the set of content metrics with the first page.

[1125] Clause a.24. The computer implemented method of clause a.23, wherein generating the set of content metric values includes generating one or more content metric values selected from a group including: a content metric characters value that is based on a number of characters on the first page; a content metric lines value that is based on a number of lines of text on the first page; a content metric fills value that is based on a number of fills on the first page; a content metric tables value that is based on a number of tables on the first page; and a content metric charts value that is based on a number of charts on the first page.

Clause Set B

[1126] Clause b.1. A computer implemented method for generating analysis data in respect of a document-format design, the method including: [1127] accessing document-format design data in respect of the document-format design, the document-format design data defining an ordered sequence of one or more content items, each content item of the one or more content items defining content of the document-format design; [1128] selecting a first content item of the one or content items, the content data of the first content item defining first content; and [1129] generating a first source object corresponding to the first content item, the first source object including a first set of source object attributes, the first set of source object attributes including: [1130] a first source identifier attribute that identifies the first content item; [1131] a first type attribute that identifies a content type of the first content; and [1132] a first reading order attribute that identifies a position of the first content item in a reading order of the one or more content items; and [1133] associating the first source object with the document-format design.

[1134] Clause b.2. The computer implemented method of clause b.1, wherein the first content includes a first separable content item and a second separable content item, and wherein: [1135] the first source object corresponds to the first separable content item; and [1136] the first source identifier attribute identifies both the first content item and the first separable content item.

[1137] Clause b.3. The computer implemented method of clause b.2, wherein the method further includes: [1138] generating a second source object corresponding to the second separable content item, the second source object including a second set of source object attributes, the second set of source object attributes including a second source identifier attribute that identifies the first content item and the second separable content item; and [1139] associating the second source object with the document-format design.

[1140] Clause b.4. The computer implemented method of clause b.2 or b.3, wherein the first content item is a text type content item, the first separable content item is a first vertically delineated block of text, and the second separable content item is a second vertically delineated block of text.

[1141] Clause b.5. The computer implemented method of any one of clauses b.1 to b.4, wherein the first set of source object attributes further includes a transfer content attribute, and wherein the method further includes: [1142] analysing the first content item to determine if the first content is source content that is to be transferred in a content transfer process; and [1143] assigning the transfer content attribute with a value indicating whether the first content is source content or not.

[1144] Clause b.6. The computer implemented method of any one of clauses b.1 to b.5, wherein: [1145] the first content item is a text type content item and the first content is text content having a text hierarchy level; [1146] the first set of source object attributes further includes a text hierarchy level attribute that records the text hierarchy level of the text content.

[1147] Clause b.7. The computer implemented method of any one of clauses b.1 to b.6, wherein the first content item is a text type content item and the first content is text content, the first set of

source object attributes includes a characters attribute, and the method further includes: [1148] analysing the text content to calculate a characters value, the characters value being based on a number of characters of the text content; and [1149] recording the characters value using the characters attribute.

[1150] Clause b.8. The computer implemented method of any one of clauses b.1 to b.7, wherein the first content item is a text type content item and the first content is text content, the first set of source object attributes includes a lines attribute, and the method further includes: [1151] analysing the text content to calculate a lines value, the lines value providing a measure of the vertical distance that the text content may occupy; and [1152] recording the lines value using the lines attribute.

[1153] Clause b.9. The computer implemented method of clause b.8, further including calculating the lines value by estimating a number of wrapped lines required to accommodate the characters of the text content.

[1154] Clause b.10. The computer implemented method of any one of clauses b.1 to b.9, wherein the first content item is not associated with explicit position data that defines a display position of the first content item in the document.

[1155] Clause b.11. The computer implemented method of any one of clauses b.1 to b.10, wherein a display position of the first content item is determined based on where a sequence position of the first content item in the ordered sequence of one or more content items.

[1156] Clause b.12. The computer implemented method of any one of clauses b.1 to b.11, further including: [1157] generating a set of analysis items, the set of analysis items including an analysis item corresponding to each of the one or more content items; [1158] processing the set of analysis items to determine a first subset of analysis items, the first subset of analysis items defining a candidate page.

[1159] Clause b.13. The computer implemented method of clause b.12, further including generating a partition key in respect of the candidate page, the partition key including a plurality of partition key values that provide a first measure of the type and amount of content defined by the first subset of analysis items.

[1160] Clause b.14. The computer implemented method of clause b.13, wherein generating the partition key includes generating a partition key texts value, the partition key texts value indicating a number of text type analysis items in the first subset of analysis items.

[1161] Clause b.15. The computer implemented method of any one of clauses b.13 or b.14, wherein generating the partition key includes generating a partition key fills value, the partition key fills value indicating a number of fills defined by analysis items in the first subset of analysis items.

[1162] Clause b.16. The computer implemented method of any one of clauses b.13 to b.15, wherein generating the partition key includes generating a partition key charts value, the partition key charts value indicating a number of charts defined by analysis items in the first subset of analysis items.

[1163] Clause b.17. The computer implemented method of any one of clauses b.13 to b.16, wherein generating the partition key includes generating a partition key tables value, the partition key tables value indicating a number of tables defined by analysis items in the first subset of analysis items.

[1164] Clause b.18. The computer implemented method of any one of clauses b.12 to b.17, further including: [1165] generating a page vector in respect of the candidate page, the page vector including a plurality of page vector values that provide a second measure of the type and amount of content defined by the first subset of analysis items.

[1166] Clause b.19. The computer implemented method of clause b.18, wherein generating the page vector includes generating a set of one or more page vector characters values, wherein a first page vector characters value is associated with a first text hierarchy level and is based on a number of text characters in the first subset of analysis items that are at the first text hierarchy level.

[1167] Clause b.20. The computer implemented method of clause b.18 or b.19, wherein generating the page vector includes generating a set of one or more page vector lines values, wherein a first

page vector lines value is associated with a first text hierarchy level and is based on a number of lines of text in the first subset of analysis items that are at the first text hierarchy level.

[1168] Clause b.21. The computer implemented method of any one of clauses b.18 to b.20, wherein generating the page vector includes generating one or more page vector values selected from a group including: a fills aspect ratio value that is based on aspect ratios of any fills in the first subset of analysis items; a partial fills value that is based on a number of partial-type fills in the first subset of analysis items; a complete fills value that is based on a number of complete-type fills in the first subset of analysis items; a charts aspect ratio value that is based on aspect ratios of any charts in the first subset of analysis items; a tables aspect ratio value that is based on aspect ratios of any tables in the first subset of analysis items.

[1169] Clause b.22. The computer implemented method of any one of clauses b.12 to b.21, further including: [1170] generating a set of content metric values in respect of the candidate page, the set of content metric values including a plurality of content metric values that provide a third measure of the type and amount of content defined by the first subset of analysis items.

[1171] Clause b.23. The computer implemented method of clause b.22, wherein generating the set of content metric values includes generating one or more content metric values selected from a group including: a content metric characters value that is based on a number of characters in the first subset of analysis items; a content metric lines value that is based on a number of lines of text in the first subset of analysis items; a content metric fills value that is based on a number of fills in the first subset of analysis items; a content metric tables value that is based on a number of tables in the first subset of analysis items; and a content metric charts value that is based on a number of charts in the first subset of analysis items.

[1172] Clause b.24. The computer implemented method of any one of clauses b.12 to b.23, wherein processing the set of analysis items to determine the first subset of analysis items is performed in accordance with a method according to any one of clauses c.1 to c.13.

Clause Set C

[1173] Clause c.1. A computer implemented method including: [1174] accessing a set of one or more source objects, wherein: [1175] each source object is associated with a source content segment of a document-format design and a set of source object attributes that include a source identifier attribute that identifies the source content segment; and [1176] the set of one or more source objects includes a plurality of text type source objects, wherein each text type source object corresponds to a text type source content segment and wherein the set of source object attributes for each text type source object includes a text hierarchy level attribute that defines a text hierarchy level; [1177] generating a first pagination candidate that includes a first set of one or more candidate pages, the first set of one or more candidate pages including a first candidate page that is associated with a first subset of source objects from the one or more source objects and a second candidate page that is associated with a second subset of source objects from the one or more source objects; [1178] selecting the first candidate page; [1179] splitting the first candidate page by: [1180] determining a first split level, the first split level corresponding to a first text hierarchy level; [1181] determining a third subset of source objects that includes one or more source objects from the first subset of source objects that are selected based on the first split level; [1182] determining a fourth subset of source objects that includes one or more source objects from the first subset of source objects that are different to the one or more source objects in the third subset of source objects and are selected based on the first split level; [1183] generating a third candidate page that is associated with the third subset of source objects; [1184] generating a fourth candidate page that is associated with the fourth subset of source objects; and [1185] generating a second pagination candidate that includes a second set of one or more candidate pages, the second set of one or more candidate pages including the third candidate page and the fourth candidate page.

[1186] Clause c.2. The computer implemented method of clause c.1, wherein determining the third subset of source objects includes: [1187] adding a first source object from the first subset of source

objects to the third subset of source objects; [1188] selecting a second source object from the first subset of source objects, the second source object being a next-in-order source object to the first source object; [1189] determining if the second source object is associated with the first text hierarchy level; and [1190] in response to determining that the second source object is not associated with the first text hierarchy level, adding the second source object to the third subset of source objects.

[1191] Clause c.3. The computer implemented method of clause c.1, wherein determining the third and fourth subsets of source objects includes: [1192] adding a first source object from the first subset of source objects to the third subset of source objects; [1193] selecting a second source object from the first subset of source objects, the second source object being a next-in-order source object to the first source object; [1194] determining if the second source object is associated with the first text hierarchy level; and [1195] in response to determining that the second source object is associated with the first text hierarchy level, adding the second source object to the fourth subset of source objects.

[1196] Clause c.4. The computer implemented method of any one of clauses c.1 to c.3, wherein the method further includes: [1197] calculating a first page score for the first candidate page, the first page score providing a measure of how well the source content defined by the first subset of source objects is likely to be accommodated by an available deck-format design page; [1198] calculating a second page score for the second candidate page, the second page score providing a measure of how well the source content defined by the second subset of source objects is likely to be accommodated by an available deck-format design page; and [1199] selecting the first candidate page in response to determining that the first page score is a more optimal page score than the second page score.

[1200] Clause c.5. The computer implemented method of clause c.4, wherein the first page score is calculated based on a first set of content metrics, the first set of content metrics including one or more content metric values selected from a group including: a content metric characters value that is based on a number of characters defined by the first subset of source objects; a content metric lines value that is based on a number of lines of text defined by the first subset of source objects; a content metric fills value that is based on a number of fills defined by the first subset of source objects; a content metric tables value that is based on a number of tables defined by the first subset of source objects; and a content metric charts value that is based on a number of charts defined by the first subset of source objects.

[1201] Clause c.6. The computer implemented method of any one of clauses c.1 to c5, wherein the first split level is determined based on a previous split level that was used to generate the first candidate page.

[1202] Clause c.7. The computer implemented method of clause c.6, wherein the first split level is determined to be the text hierarchy level that is associated with at least one source object in the first subset of source objects and is a next-in-order text hierarchy level when compared to the previous split level.

[1203] Clause c.8. The computer implemented method of any one of clauses c.1 to c7, wherein the second pagination candidate is generated so that the second set of one or more candidate pages includes the second candidate page.

[1204] Clause c.9. The computer implemented method of any one of clauses c.1 to c8, wherein the first set of one or more candidate pages is associated with all source objects in the set of one or more source objects and the second set of one or more candidate pages is associated with all source objects in the set of one or more source objects.

[1205] Clause c.10. The computer implemented method of any one of clauses c.1 to c9, further including generating an initial pagination candidate that includes an initial candidate page that is associated with all source objects in the set of one or more source objects, and wherein the first candidate page and the second candidate page are generated by splitting the initial candidate page.

[1206] Clause c.11. The computer implemented method of any one of clauses c.1 to c10, further including: [1207] selecting the third candidate page; [1208] splitting the third candidate page by: [1209] determining a second split level, the second split level corresponding to a second text hierarchy level, the second text hierarchy level being a lower hierarchy level than the first text hierarchy level; [1210] determining a fifth subset of source objects that includes one or more source objects from the third subset of source objects that are selected based on the second split level; [1211] determining a sixth subset of source objects that includes one or more source objects from the third subset of source objects that are different to the one or more source objects in the fifth subset of source objects and are selected based on the second split level; [1212] generating a fifth candidate page that is associated with the fifth subset of source objects; [1213] generating a sixth candidate page that is associated with the sixth subset of source objects; and [1214] generating a third pagination candidate that includes a third set of one or more candidate pages, the third set of one or more candidate pages including the fifth candidate page and the sixth candidate page.

[1215] Clause c.12. The computer implemented method of clause c.11, wherein the method further includes: [1216] calculating a third page score for the third candidate page, the third page score providing a measure of how well the source content defined by the third subset of source objects is likely to be accommodated by an available deck-format design page; [1217] calculating a fourth page score for the fourth candidate page, the fourth page score providing a measure of how well the source content defined by the fourth subset of source objects is likely to be accommodated by an available deck-format design page; and [1218] selecting the third candidate page in response to determining that the third page score is a more optimal page score than the fourth page score.

[1219] Clause c.13. The computer implemented method of clause c.12 or clause c.13, wherein the third pagination candidate is generated so that the third set of one or more candidate pages includes the second candidate page and the fourth candidate page.

[1220] Clause c.14. The computer implemented method of any one of clauses c.1 to c.13, wherein the set of one or more source objects is included in analysis data generated according to the method of any one of clauses b.1 to b.23.

[1221] Clause c.15. The computer implemented method of any one of clauses c.1 to c.14, further including: [1222] identifying a first deck-format design template that matches the first pagination candidate, the first deck-format design template including a template page corresponding to each candidate page in the first set of one or more candidate pages; and [1223] generating a first new deck-format design based on the first deck-format design template and the first pagination candidate.

[1224] Clause c.16. The computer implemented method of any one of clauses c.1 to c.15, further including: [1225] identifying a second deck-format design template that matches the second pagination candidate, the second deck-format design template including a template page corresponding to each candidate page in the second set of one or more candidate pages; and [1226] generating a second new deck-format design based on the second deck-format design template and the second pagination candidate.

Clause Set D

[1227] Clause d.1. A computer implemented method including: [1228] accessing a first set of source objects, wherein each source object in the first set of source objects corresponds to source content of a source design and the first set of source objects correspond to a first source page; [1229] generating a first source page partition key, the first source page partition key being in respect of an original version of the first source page and including a plurality of partition key values that provide a first measure of the type and amount of source content of the original version of the first source page; and [1230] identifying a first set of or more template pages, wherein each template page in the first set of one or more template pages is a specific page of a specific template that potentially matches the first source page, and wherein identifying the first set of one or more

template pages includes: [1231] comparing the first source page partition key to a first template page partition key that is associated with a first template page; and [1232] determining that the first template page potentially matches the first source page if the first source page partition key matches the first template page partition key.

[1233] Clause d.2. The computer implemented method of clause d.1, wherein the first set of template pages includes the first template page and a second template page, and wherein the method further includes: [1234] calculating a first score in respect of the original version of the first source page and the first template page, wherein the first score being calculated based on: [1235] a first source page vector that is associated with the first source page and includes a plurality of page vector values that provide a second measure of the type and amount of source content of the first source page; and [1236] a first template page vector that is associated with the first template page and includes a plurality of page vector values that provide a second measure of the type and amount of content that can be accommodated by the first template page; [1237] calculating a second score in respect of the original version of the first source page and the second template page, the second score being calculated based on the first source page vector and a second template page vector that is associated with the second template page; and [1238] selecting the first template page as a final match for the original version of the first source page based on the first score and the second score.

[1239] Clause d.3. The computer implemented method of clause d.1 or clause d.2, further including: [1240] generating a first rewrite of the first source page; [1241] generating a second source page partition key, the second source page partition key being in respect of the first rewrite of the first source page and including a plurality of partition key values that provide a first measure of the type and amount of source content defined by the first rewrite of the first source page; [1242] identifying that a third template page is a potential match for the first rewrite of the first source page based on the second source page partition key and a third template page partition key that is associated with the third template page; and [1243] including the third template page in the first set of template pages.

[1244] Clause d.4. The computer implemented method of clause d.3, wherein generating the first rewrite of the first source page includes combining source content defined by two or more of the source objects together.

[1245] Clause d.5. The computer implemented method of any one of clauses d.1 to d.4, wherein the first source page partition key is generated to include a partition key texts value that is based on a number of source objects in the first set of source objects that define text-type source content.

[1246] Clause d.6. The computer implemented method of any one of clauses d.1 to d.5, wherein the first source page partition key is generated to include a partition key fills value that is based on a number of fills defined in the first set of source objects.

[1247] Clause d.7. The computer implemented method of any one of clauses d.1 to d.6, wherein the first source page partition key is generated to include a partition key charts value that is based on a number of charts defined in the first set of source objects.

[1248] Clause d.8. The computer implemented method of any one of clauses d.1 to d.7, wherein the first source page partition key is generated to include a partition key tables value that is based on a number of tables defined in the first set of source objects.

[1249] Clause d.9. The computer implemented method of clause d.2 or any one of clauses d.3 to d.8 when dependent on clause d.2, wherein the first source page vector includes a set of one or more characters values, wherein a first characters value is associated with a first text hierarchy level and is based on a number of text characters that are defined in the first set of source objects and that are at the first text hierarchy level.

[1250] Clause d.10. The computer implemented method of clause d.2 or any one of clauses d.3 to d.9 when dependent on clause d.2, wherein the first source page vector includes a set of one or more lines values, wherein a first lines value is associated with a first text hierarchy level and is

based on a number of lines of text that are defined in the first set of source objects and that are at the first text hierarchy level.

[1251] Clause d.11. The computer implemented method of clause d.2 or any one of clauses d.3 to d.10 when dependent on clause d.2, wherein the first source page vector includes one or more values selected from a group including: [1252] a characters value that is based on a number of characters defined in the first set of source objects; [1253] a lines value that is based on a number of lines of text defined by the set of one or more source objects; a fills aspect ratio value that is based on aspect ratios of any fills that are defined in the first set of source objects; [1254] a partial fills value that is based on a number of partial-type fills that are defined in the first set of source objects; [1255] a complete fills value that is based on a number of complete-type fills that are defined in the first set of source objects; [1256] a charts aspect ratio value that is based on aspect ratios of any charts that are defined in the first set of source objects; [1257] a tables aspect ratio value that is based on aspect ratios of any tables that are defined in the first set of source objects.

[1258] Clause d.12. The computer implemented method of any one of clauses d1 to d.11, wherein each source object in the first set of source objects includes a set of source object attributes, and wherein a first source object of set of source objects is associated with first source content and has a first set of source object attributes that include: [1259] a source identifier attribute that identifies the first source content; [1260] a type attribute that identifies a content type of the first source content; and [1261] a reading order attribute that identifies a position of the first source content in a reading order.

[1262] Clause d.13. The computer implemented method of clause d.12, wherein the first source content is text type content that is associated with a particular text hierarchy level and the first set of source object attributes includes at least one of a text hierarchy level attribute that records the particular text hierarchy level; a characters attribute that has a value that is based on a number of characters of the first content; and a lines attribute that has a value that provides a measure of vertical distance that the first content may occupy.

[1263] Clause d.14. The computer implemented method of any one of clauses d1 to d.13, wherein the first set of source objects is a candidate page generated according to the method of any one of clauses c.1 to c.14.

[1264] Clause d.15. The computer implemented method of any one of clauses d1 to d.14, further including generating a new deck-format design page based on the first template page and the source content of the source design.

Clause Set E

[1265] Clause e.1. A computer implemented method including: [1266] accessing data in respect of a first pagination candidate, wherein: [1267] the first pagination candidate is associated with a first set of candidate pages; [1268] each candidate page in the first set of candidate pages is associated with a set of source objects; and [1269] each source object corresponds to source content of a source design; [1270] identifying a set of potentially matching template pages for each candidate page in the first set of candidate pages, wherein identifying the set of potentially matching template pages includes determining that a first template page of a first template potentially matches a first candidate page; [1271] calculating a set of preliminary template scores for the first pagination candidate, wherein calculating the set of preliminary template scores for the first pagination candidate includes calculating a first preliminary template score in respect of the first template based on a number of candidate pages that are associated with the first pagination candidate and that are matched by a page of the first template; and [1272] preliminarily selecting one or more templates for the first pagination candidate based on the set of preliminary template scores.

[1273] Clause e.2. The computer implemented method of clause e.1, further including: [1274] calculating a set of candidate page scores for the first pagination candidate, wherein each candidate page score is in respect of a particular candidate page of the first pagination candidate and a particular template page of a preliminarily selected template; and [1275] calculating a set of final

template scores for the first pagination candidate based on the set of candidate page scores calculated for the first pagination candidate, wherein each final template score is in respect of the first pagination candidate and a particular template, and wherein calculating the set of final template scores for the first pagination candidate includes calculating a first final template score that is in respect of the first template and that is based any candidate page scores that are in respect of a page of the first template.

[1276] Clause e.3. The computer implemented method of clause e.2, wherein the method further includes generating a first candidate page vector for the first candidate page, the first candidate page vector including a plurality of page vector values that provide a second measure of the type and amount of source content defined by the first candidate page, and wherein: [1277] calculating the set of candidate page scores for the first pagination candidate includes calculating a first candidate page score in respect of the first candidate page and the first template page; and [1278] the first candidate page score is based on the first candidate page vector and a first template page vector that is associated with the first template page.

[1279] Clause e.4. The computer implemented method of clause e.3, wherein calculating the first candidate page score includes calculating the Euclidean distance between the first candidate page vector and the first template page vector.

[1280] Clause e.5. The computer implemented method of clause e.3 or e.4, wherein calculating the first candidate page score includes calculating a text size penalty, and wherein the text size penalty is a measure of the extent to which the first template page accommodates text type source content of the first candidate page.

[1281] Clause e.6. The computer implemented method of any one of clauses e.3 to e.5, wherein the first candidate page vector is generated to include a set of one or more characters values, wherein a first characters value is associated with a first text hierarchy level and is based on a number of text characters that are defined by the first candidate page's source content and that are at the first text hierarchy level.

[1282] Clause e.7. The computer implemented method of any one of clauses e.3 to e.6, wherein the first candidate page vector is generated to include a set of one or more lines values, wherein a first lines value is associated with a first text hierarchy level and is based on a number of lines of text that are defined by the first candidate page's source content and that are at the first text hierarchy level.

[1283] Clause e.8. The computer implemented method of any one of clauses e.3 to e.8, wherein the first candidate page vector is generated to include one or more values selected from a group including: a characters value that is based on a number of characters defined by the first candidate page's source content; a lines value that is based on a number of lines of text defined by the first candidate page's source content; a fills aspect ratio value that is based on aspect ratios of any fills that are defined by the first candidate page's source content; a partial fills value that is based on a number of partial-type fills that are defined by the first candidate page's source content; a complete fills value that is based on a number of complete-type fills that are defined by the first candidate page's source content; a charts aspect ratio value that is based on aspect ratios of any charts that are defined by the first candidate page's source content; a tables aspect ratio value that is based on aspect ratios of any tables that are defined by the first candidate page's source content.

[1284] Clause e.9. The computer implemented method of any one of clauses e.2 to e.8, wherein calculating the set of final template scores for the first pagination candidate includes calculating a second final template score associated with a second template, and wherein the method further includes: [1285] selecting the first template as a final match for the first pagination candidate page based on the first final template score and the second final template score.

[1286] Clause e.10. The computer implemented method of any one of clauses e.1 to e.9, wherein determining that the first template page potentially matches the first candidate page includes:

[1287] generating a first candidate page partition key, the first candidate page partition key

including a plurality of partition key values that provide a first measure of the type and amount of the first candidate page's source content; [1288] comparing the first candidate page partition key to a first template page partition key that is associated with the first template page; and [1289] determining that the first template page potentially matches the first candidate page if the first candidate page partition key matches the first template page partition key.

[1290] Clause e.11. The computer implemented method of clause e.10, wherein the first candidate page partition key is generated to include one or more of: a partition key texts value that indicates a number of source objects in the first candidate page's set of one or more source objects that define text-type source content; a partition key fills value that indicates a number of source objects in the first candidate page's set of one or more source objects that define fill type source content; a partition key charts value that indicates a number of source objects in the first candidate page's set of one or more source objects; a partition key tables value that indicating a number of source objects in the first candidate page's set of one or more source objects the set of one or more source objects that define table type source content.

[1291] Clause e.12. The computer implemented method of any one of clauses e.1 to e.11, further including generating a first rewrite of the first candidate page, and wherein: [1292] identifying the set of potentially matching template pages for the first candidate page includes determining that the first template page of matches the first rewrite of the first candidate page.

[1293] Clause e.13. The computer implemented method of clause e.12, wherein generating the first rewrite of the first candidate page includes combining source content defined by two or more of the source objects that are associated with the first candidate page.

[1294] Clause e.14. The computer implemented method of any one of clauses e.1 to e.13, further including generating a new deck-format design based on the first pagination candidate and the first template.

[1295] Clause e.15. The computer implemented method of clause e.14, wherein generating the new deck-format design includes generating a deck-format design descriptor corresponding to the first pagination candidate, wherein the deck-format design descriptor includes a first new page dataset that corresponds to the first candidate page, and wherein the first new page dataset includes: [1296] a first destination page identifier that identifies the first template page of the first template; and [1297] content map data that maps a first object associated with the first candidate page to a first destination object associated with the first template page.

[1298] Clause e.16. The computer implemented method of any one of clauses e.1 to e.15, wherein the first pagination candidate is generated according to the method of any one of clauses c.1 to c.14.

Clause Set F

[1299] Clause f.1. A computer implemented method including: [1300] accessing a first set of source objects that relate to a first page of a source design, wherein each source object is associated with a set of source object attributes that include: [1301] a source identifier attribute that identifies source content of the source design; [1302] a type attribute that identifies a content type of the source content; and [1303] a reading order attribute that identifies a position of the source content in a reading order of the source design; [1304] accessing a first set of destination objects that relate to a first page of a destination design, wherein the destination design is a deck-format design and each destination object is associated with a set of destination object attributes that includes: [1305] a destination identifier attribute that identifies a destination element of the destination design; [1306] a type attribute that identifies a content type of the destination element; and [1307] a reading order attribute that identifies a position of the destination element in a reading order of the destination design; [1308] generating, based on the first set of source objects and the first set of destination objects, a first content map that maps each source object in the first set of source objects to a destination object in the first set of destination objects.

[1309] Clause f.2. The computer implemented method of clause f.1, wherein: [1310] the first set of

source objects includes one or more text-type source objects, each text-type source object having a type attribute that identifies text type content; [1311] the first set of destination objects includes one or more text-type destination objects, each text-type destination object having a type attribute that identifies text type content; and [1312] generating the first content map includes: [1313] selecting a first source object from the first set of source objects, wherein the first source object is a text-type source object, and the first source object is a first-in-reading-order text-type source object in the first set of source objects that has not already been mapped to a destination object; [1314] identifying a first destination object from the first set of destination objects, wherein the first destination object is a text-type destination object, and the first destination object is a first-in-reading-order text-type destination object in the first set of destination objects that has not already been mapped to a source object; and [1315] mapping the first source object to the first destination object.

[1316] Clause f.3. The computer implemented method of clause f.1, wherein: [1317] the first set of source objects includes one or more text-type source objects, wherein each text-type source object has a type attribute that identifies text type content, and wherein each text type source object includes a text hierarchy level attribute that identifies a text hierarchy level; [1318] the first set of destination objects includes one or more text-type destination objects, wherein each text-type destination object has a type attribute that identifies text type content; and wherein each text type destination object includes a text hierarchy level attribute that identifies a text hierarchy level; and [1319] generating the first content map includes: [1320] selecting a first source object from the first set of source objects, wherein the first source object is a text-type source object associated with a first text hierarchy level, and the first source object is the first-in-reading-order text-type source object in the first set of source objects that is associated with the first text hierarchy level and that has not been mapped to a destination object; [1321] identifying a first destination object from the first set of destination objects, wherein the first destination object is a text-type destination object associated with the first text hierarchy level, and the first destination object is the first-in-reading-order text-type destination object in the first set of destination objects that is associated with the first text hierarchy level and that has not been mapped to a source object; and [1322] mapping the first source object to the first destination object.

[1323] Clause f4. The computer implemented method of clause f.3, wherein generating the first content map includes: [1324] selecting a second source object from the first set of source objects, wherein the second source object is a text-type source object associated with a second text hierarchy level, and the second source object is the first-in-reading-order text-type source object in the first set of source objects that is associated with the second text hierarchy level and that has not been mapped to a destination object; [1325] identifying a second destination object from the first set of destination objects, wherein the second destination object is a text-type destination object associated with the second text hierarchy level, and the second destination object is the first-in-reading-order text-type destination object in the first set of destination objects that is associated with the second text hierarchy level and that has not been mapped to a source object; and [1326] mapping the second source object to the second destination object.

[1327] Clause f5. The computer implemented method of any one of clauses f.1 to f.4, wherein: [1328] the first set of source objects includes one or more fill-type source objects, each fill-type source object having a type attribute that identifies fill type content; [1329] the first set of destination objects includes one or more fill-type destination objects, each fill-type destination object having a type attribute that identifies fill type content; and [1330] generating the first content map includes: [1331] selecting a third source object from the first set of source objects, wherein the third source object is a fill-type source object, and the third source object is a first-in-reading-order fill-type source object in the first set of source objects that has not already been mapped to a destination object; [1332] identifying a third destination object from the first set of destination objects, wherein the third destination object is a fill-type destination object, and the third

destination object is a first-in-reading-order fill-type destination object in the first set of destination objects that has not already been mapped to a source object; and [1333] mapping the third source object to the third destination object.

[1334] Clause f6. The computer implemented method of any one of clauses f.1 to f.5, wherein:

[1335] the first set of source objects includes one or more chart-type source objects, each chart-type source object having a type attribute that identifies chart type content; [1336] the first set of destination objects includes one or more chart-type destination objects, each chart-type destination object having a type attribute that identifies chart type content; and [1337] generating the first content map includes: [1338] selecting a fourth source object from the first set of source objects, wherein the fourth source object is a chart-type source object, and the fourth source object is a first-in-reading-order chart-type source object in the first set of source objects that has not already been mapped to a destination object; [1339] identifying a fourth destination object from the first set of destination objects, wherein the fourth destination object is a chart-type destination object, and the fourth destination object is a first-in-reading-order chart-type destination object in the first set of destination objects that has not already been mapped to a source object; and [1340] mapping the fourth source object to the fourth destination object.

[1341] Clause f7. The computer implemented method of any one of clauses f.1 to f.6, wherein:

[1342] the first set of source objects includes one or more table-type source objects, each table-type source object having a type attribute that identifies table type content; [1343] the first set of destination objects includes one or more table-type destination objects, each table-type destination object having a type attribute that identifies table type content; and [1344] generating the first content map includes: [1345] selecting a fifth source object from the first set of source objects, wherein the fifth source object is a table-type source object, and the fifth source object is a first-in-reading-order table-type source object in the first set of source objects that has not already been mapped to a destination object; [1346] identifying a fifth destination object from the first set of destination objects, wherein the fifth destination object is a table-type destination object, and the fifth destination object is a first-in-reading-order table-type destination object in the first set of destination objects that has not already been mapped to a source object; and [1347] mapping the fifth source object to the fifth destination object.

[1348] Clause f8. The computer implemented method of any one of clauses f.2 to f.7, wherein the first source object is a combined source object that is associated with a sixth source object and a seventh source object, and wherein mapping the first source object to the first destination object includes mapping the sixth source object to the first destination object and mapping the seventh source object to the first destination object.

[1349] Clause f.9. The computer implemented method of clause f.1, wherein: [1350] the first set of source objects includes one or more source objects of a first content type, each source object of the first content type having a type attribute that identifies the first content type; [1351] the first set of destination objects includes one or more destination objects of the first content type, each destination object of the first content type having a type attribute that identifies the first content type; and [1352] generating the first content map includes: [1353] selecting a first source object from the first set of source objects, wherein the first source object is of the first content type, and the first source object is a first-in-reading-order source object of the first content type in the first set of source objects that has not already been mapped to a destination object; [1354] identifying a first destination object from the first set of destination objects, wherein the first destination object is a destination object of the first content type, and the first destination object is a first-in-reading-order destination object of the first content type in the first set of destination objects that has not already been mapped to a source object; and [1355] mapping the first source object to the first destination object.

[1356] Clause f.10. The computer implemented method of any one of clauses f.1 to f.9, wherein the source design is a document-format design and the set of source objects includes at least one source

object generated according to the method of any one of clauses b.1 to b.11.

[1357] Clause f.11. The computer implemented method of any one of clauses f.1 to f.10, wherein the set of source objects corresponds to a candidate page generated according to the method of any one of clauses c.1 to c.16.

[1358] Clause f.12. The computer implemented method of any one of clauses f.1 to f.9, wherein the source design is a deck-format design and the set of source objects is a set of analysis objects that includes at least one analysis object that is generated according to the method of any one of clauses a.1 to a.8 or a.12 to a.13.

[1359] Clause f.13. The computer implemented method of any one of clauses f.1 to f.12, wherein the set of destination objects is a set of analysis objects that includes at least one analysis object that is generated according to the method of any one of clauses a.1 to a.11.

Clause Set G

[1360] Clause g.1. A computer implemented method for mapping a set of source fills to a set of destination frames, the method including: [1361] calculating an ideal fill size for each source fill in the set of source fills; [1362] calculating a remaining capacity value for each destination frame in the set of destination frames; and [1363] mapping the set of source fills to the set of destination frames, wherein mapping the set of source fills to the set of destination frames includes: [1364] selecting a first source fill, the first source fill being the source fill that has the largest ideal fill size and that has not been mapped to any destination frame; [1365] determining that a first destination frame has a largest remaining capacity value; [1366] and in response to determining that the first destination frame has the largest remaining capacity value; [1367] mapping the first source fill to the first destination frame; and [1368] updating the first destination frame's remaining capacity value.

[1369] Clause g.2. The computer implemented method of clause g.1, wherein updating the first destination frame's remaining capacity value includes subtracting the ideal fill size of the first source fill from a current remaining capacity value of the first destination frame.

[1370] Clause g.3. The computer implemented method of g.1 or g.2, further including calculating the ideal fill size for the first source fill based on a size of the first source fill.

[1371] Clause g.4. The computer implemented method of g.1 or g.2, further including calculating the ideal fill size for the first source fill based on a size of the first source fill, a total frame capacity value, and a total source fill size value.

[1372] Clause g.5. The computer implemented method of clause g.4, wherein the total frame capacity value is calculated by summing together frame capacity values of each frame in the set of destination frames.

[1373] Clause g.6. The computer implemented method of clauses g.4 or g.5, wherein the total source fill size value is calculated by summing together source fill sizes of each source fill in the set of source fills.

[1374] Clause g.7. The computer implemented method of any one of clauses g.4 to g.6, wherein the ideal fill size for the first source fill is calculated as the first source fill's size multiplied by (the total frame capacity divided by the total source fill size).

[1375] Clause g.8. The computer implemented method of any one of clauses g.1 to g.7, wherein after mapping the first source fill to the first destination frame, mapping the set of source fills to the set of destination frames further includes: [1376] selecting a second source fill, the second source fill being the source fill that has the largest ideal fill size and that has not been mapped to any destination frame; [1377] determining that the first destination frame has the largest remaining capacity value; and [1378] in response to determining that the first destination frame has the largest remaining capacity value: [1379] mapping the second source fill to the first destination frame; and [1380] updating the first destination frame's remaining capacity value based on the second source fill.

[1381] Clause g.9. The computer implemented method of any one of clauses g.1 to g.7, wherein

after mapping the first source fill to the first destination frame, mapping the set of source fills to the set of destination frames further includes: [1382] selecting a second source fill, the second source fill being the source fill that has the largest ideal fill size and that has not been mapped to any destination frame; [1383] determining that a second destination frame has the largest remaining capacity value; and [1384] in response to determining that the second destination frame has the largest remaining capacity value: [1385] mapping the second source fill to the second destination frame; and [1386] updating the second destination frame's remaining capacity value based on the second source fill.

[1387] Clause g.10. The computer implemented method of any one of clauses g.1 to g.9, further including automatically processing a document format design to extract the set of source fills from that document format design.

[1388] Clause g.11. The computer implemented method of any one of clauses g.1 to g.9, further including automatically processing a page of a deck format design to extract the set of source fills from that page.

[1389] Clause g.12. The computer implemented method of any one of clauses g.1 to g.9, further including receiving a first set of one or more user inputs selecting the set of source fills.

[1390] Clause g.13. The computer implemented method of any one of clauses g.1 to g.12, wherein each frame in the set of destination frames corresponds to an element of a deck-format design page.

[1391] Clause g.14. The computer implemented method of any one of clauses g.1 to g.13, further including automatically processing a page of a deck format design to determine the set of destination frames.

[1392] Clause g.15. The computer implemented method of any one of clauses g.1 to g.13, further including receiving a second set of one or more user inputs selecting the set of destination frames.

Clause Set H

[1393] Clause h.1. A computer implemented method for generating a set of replacement design elements based on a set of source fills and a destination element, the method including: [1394] selecting a set of grid arrangements, wherein each grid arrangement defines a set of grid sections and wherein each grid section is associated with grid section data defining a grid section size and a grid section origin; [1395] calculating a final grid arrangement score for each grid arrangement, the final grid arrangement score for a selected grid arrangement being a measure of how well the set of grid sections of the selected grid arrangement accommodate the source fills; [1396] selecting a first grid arrangement from the set of grid arrangements based on the final grid arrangement scores; and [1397] generating the set of replacement design elements, wherein each replacement design element is based on the destination element and corresponds to a different grid section defined by the first grid arrangement, and wherein generating the set of replacement design elements includes generating a first replacement design element corresponding to a first grid section by; [1398] determining a size and position of the first replacement design element based on the first grid section; [1399] assigning a first source fill to the first replacement design element; and [1400] transferring the first source fill to the first replacement design element.

[1401] Clause h.2. The computer implemented method of clause h.1, wherein the grid section data of the first grid section defines the first grid section's origin by an origin X value and an origin Y value.

[1402] Clause h.3. The computer implemented method of clause h.2, wherein the origin X value is expressed as a proportion of a total width of the first grid arrangement and the origin Y value is expressed as a proportion of a total height of the first grid arrangement.

[1403] Clause h.5. The computer implemented method of any one of clauses h.1 to h.4, wherein the grid section data of the first grid section defines the first grid section's size by a grid section width value and a grid section height value.

[1404] Clause h.6. The computer implemented method of clause h.5, wherein the grid section width value is expressed as a proportion of a total width of the first grid arrangement and the grid section

height value is expressed as a proportion of a total height of the first grid arrangement.

[1405] Clause h.7. The computer implemented method of any one of clauses h.1 to h.7, wherein calculating the final grid arrangement score for the first grid arrangement includes: [1406] calculating a set of aspect ratio differences for the first grid arrangement, wherein each aspect ratio difference corresponds to a particular grid section of the first grid arrangement and a matched source fill; and [1407] calculating the final grid arrangement score based on the set of aspect ratio differences.

[1408] Clause h.8. The computer implemented method of clause h.7, wherein calculating the set of aspect ratio differences for the first grid arrangement includes: [1409] calculating an aspect ratio for each source fill; [1410] calculating an aspect ratio for each grid section of the first grid arrangement; [1411] identifying matching source fill/grid section pairs based on the source fill aspect ratios and the grid section aspect ratios; and [1412] calculating an aspect ratio difference for each matching source fill/grid section pair based on the aspect ratio of the pair's source fill and the aspect ratio of the pair's grid section.

[1413] Clause h.9. The computer implemented method of clause h.8, wherein the first grid section has a largest grid section aspect ratio and a first source fill has a largest fill aspect ratio, and wherein identifying matching source fill/grid section pairs includes identifying the first grid section and the first fill as a matching source fill/grid section pair.

[1414] Clause h.10. The computer implemented method of any one of clauses h.1 to h.9, wherein determining the size and position of the first replacement design element includes determining the size of the first replacement design element based on the first grid section's size and determining the position of the first replacement design element based on the first grid section's origin.

[1415] Clause h.11. The computer implemented method of any one of clauses h.1 to h.10, wherein assigning the first source fill to the first replacement design element is based on an aspect ratio of the first source fill and an aspect ratio of the replacement design element.

[1416] Clause h.12. The computer implemented method of clause h.11, wherein a first replacement design element has a largest replacement design element aspect ratio and the first fill has a largest fill aspect ratio.

[1417] Clause h.13. The computer implemented method of any one of clauses h.1 to h.12, wherein selecting the set of grid arrangements includes identifying and selecting one or more grid arrangements that define a number of grid sections that is equal to a number of source fills in the set of source fills.

[1418] Clause h.14. The computer implemented method of any one of clauses h.1 to h.13, wherein the destination element is an element of a deck-format design page, and the method further includes replacing the destination element with the set of replacement design elements.

[1419] Clause h.15. The computer implemented method of any one of clauses h.1 to h.14, further including: [1420] receiving a first set of one or more user inputs selecting the set of source fills; and [1421] receiving a second set of one or more user inputs selecting the destination element.

[1422] Clause h.16. The computer implemented method of any one of clauses h.1 to h.14, wherein the set of source fills and the destination element are automatically determined.

[1423] Clause h.17. The computer implemented method of any one of clauses h.1 to h.14, wherein the destination element defines a destination frame and wherein set of source fills is mapped to the destination frame according to a method of any one of clauses g.1 to g.15.

Clause Set I

[1424] Clause i.1. A computer implemented method for generating a new table based on a source table and a destination table, the source table including a set of source table cells and the destination table including a set of destination table cells, the method including: [1425] generating a set of source cell styles, wherein each source cell style is a cell style defined by at least one source table cell; [1426] generating a set of destination cell styles, wherein each destination cell style is a cell style defined by at least one destination table cell; [1427] generating the new table,

wherein the new table includes a set of new table cells that correspond to the set of source table cells and wherein each new table cell includes cell content of the corresponding source table cell; and [1428] restyling the set of new table cells by, for each new table cell: [1429] identifying a destination cell style from the set of destination cell styles; and [1430] applying the destination cell style to the new table cell.

[1431] Clause i.2. The computer implemented method of clause i.1, further including: [1432] calculating a first font scaling factor, the first font scaling factor corresponding to a first set of new table cells; and [1433] adjusting a font size of text content of the first set of new table cells based on the first font scaling factor.

[1434] Clause i.3. The computer implemented method of clause i.2, wherein the first font scaling factor is calculated so that text content of each new table cell in the first set of new table cells fits with the new table cell.

[1435] Clause i.4. The computer implemented method of clause i.2 or clause i.3, wherein the first set of new table cells includes all new table cells.

[1436] Clause i.5. The computer implemented method of clause i.2 or clause i.3, wherein the first set of new table cells includes all new table cells in the set of new table cells that have a same destination cell style applied to them.

[1437] Clause i.6. The computer implemented method of any one of clauses i.1 to i.5, wherein generating the set of source cell styles includes: [1438] selecting a first source cell from the set of source table cells, the first source cell being a first-in-reading-order cell of the set of source table cells; [1439] determining a cell style of the first source cell; and [1440] adding the cell style of the first source cell to the set of source cell styles.

[1441] Clause i.7. The computer implemented method of clause i.6, wherein generating the set of source cell styles further includes: [1442] selecting a second source cell from the set of source table cells, the second source cell being a second-in-reading-order cell of the set of source table cells; [1443] determining a cell style of the second source cell; [1444] determining whether the set of source cell styles includes the cell style of the second source cell; and [1445] in response to determining that the set of source cell styles does not include the cell style of the second source cell, adding the cell style of the second source cell to the set of source cell styles.

[1446] Clause i.8. The computer implemented method of any one of clauses i.1 to i.7, wherein generating the set of destination cell styles includes: [1447] selecting a first destination cell from the set of destination table cells, the first destination cell being a first-in-reading-order cell of the set of destination cells; [1448] determining a cell style of the first destination cell; and [1449] adding the cell style of the first destination cell to the set of destination cell styles.

[1450] Clause i.9. The computer implemented method of clause i.8, wherein generating the set of destination cell styles further includes: [1451] selecting a second destination cell from the set of destination table cells, the second destination cell being a second-in-reading-order cell of the set of destination cells; [1452] determining a cell style of the second destination cell; [1453] determining whether the set of destination cell styles includes the cell style of the second destination cell; and [1454] in response to determining that the set of destination cell styles does not include the cell style of the second destination cell, adding the cell style of the second destination cell to the set of destination cell styles.

[1455] Clause i.10. The computer implemented method of any one of clauses i.1 to i.9, wherein restyling the set of new table cells includes, for a selected new table cell: [1456] identifying a particular source cell style from the set of source cell styles that matches the cell style of the selected new table cell; [1457] identifying a particular destination cell style from the set of destination cell styles, the particular destination cell style being the destination cell style that corresponds to the particular source cell style; and [1458] applying the particular destination cell style to the selected new table cell.

[1459] Clause i.11. The computer implemented method of any one of clauses i.1 to i.9, wherein:

[1460] the set of source cell styles is an ordered set of source cell style records; [1461] the set of destination cell styles is an ordered set of destination cell style records; and [1462] restyling the set of new table cells includes, for a selected new table cell: [1463] identifying a particular source cell style record from the set of source cell style records, the particular source cell style record defining a cell style of the selected new table cell and having a first position in the ordered set of source cell style records; [1464] identifying a particular destination cell style record from the set of destination cell style records, the particular destination cell style record being the destination cell style record at the first position in the ordered set of destination cell style records; and [1465] applying the cell style defined by the particular destination cell style record to the selected new table cell.

[1466] Clause i.12. The computer implemented method of any one of clauses i.1 to i.11, wherein each cell style is defined by a set of one or more cell style attributes selected from a group including: a cell background colour attribute; a cell font family attribute; a cell font weight attribute; a cell text colour attribute; a cell text decoration attribute (e.g. underline); a cell font style (e.g. italics) attribute; and/or other style attributes.

[1467] Clause i.13. The computer implemented method of any one of clauses i.1 to i.12, wherein generating the new table includes creating a copy of the source table and updating the copy of the source table based on one or more attributes of the destination table.

[1468] Clause i.14. The computer implemented method of clause i.13, wherein updating the copy of the source table includes one or more of: updating a size attribute of the copy based on a size attribute of the destination table; and updating a position attribute of the copy based on a position attribute of the destination table.

[1469] Clause i.15. The computer implemented method of any one of clauses i.1 to i.12, wherein generating the new table includes creating a copy of the destination table and updating the copy of the destination table based on cell content of the source table.

[1470] Clause i.16. The computer implemented method of any one of clauses i.1 to i.15 wherein the destination table is defined by a destination element of a deck-format design page, and the method further includes replacing the destination element with a new element defining the new table.

[1471] Clause i.17. The computer implemented method of any one of clauses i.1 to i.16, further including: [1472] receiving a first set of one or more user inputs selecting the source table; and [1473] receiving a second set of one or more user inputs selecting the destination table.

[1474] Clause i.18. The computer implemented method of any one of clauses i.1 to i.16, wherein the source table and the destination table are automatically determined.

[1475] Clause i.19. The computer implemented method of any one of clauses i.1 to i.16, wherein the source table and the destination table are determined based on a content map generated according to the method of any one of clauses f.1 to f.13

Clause Set J

[1476] Clause j.1. A computer implemented method for generating a new chart based on a source chart and a destination chart, the method including: [1477] accessing source chart data in respect of the source chart, wherein the source chart data defines a set of source chart data series and a set of source chart colours, and wherein each source chart data series is associated with a source chart colour; [1478] accessing destination chart data in respect of the destination chart, wherein the destination chart data defines a set of destination chart data series and a set of destination chart colours, and wherein each destination chart data series is associated with a destination chart colour; [1479] determining that the number of source chart colours is greater than the number of destination chart colours; [1480] in response to determining that the number of source chart colours is greater than the number of destination chart colours, generating one or more new chart colours; [1481] generating the new chart to include the set of source chart data series; [1482] associating a first source chart data series with a destination chart colour; [1483] associating a second source chart data series with a new chart colour.

[1484] Clause j.2. The computer implemented method of clause j.1, wherein each of the one or

more new chart colours is generated based on a destination chart colour.

[1485] Clause j.3. The computer implemented method of clause j.2, wherein generating a first new chart colour includes: [1486] selecting a first destination chart colour; and [1487] generating the first new chart colour as a variant of the first destination chart colour.

[1488] Clause j.4. The computer implemented method of clause j.3, wherein the first new chart colour is generated as a brightness variant of the first destination chart colour.

[1489] Clause j.5. The computer implemented method of clause j.3, wherein the first new chart colour is generated as a luminance variant of the first destination chart colour.

[1490] Clause j.6. The computer implemented method of any one of clauses j.1 to j.5, wherein the source chart is associated with a first chart type that defines how the set of source chart data series are displayed and the destination chart is associated with a second chart type that defines how the set of destination chart data series are displayed, and wherein the new chart is associated with the second chart type.

[1491] Clause j.7. The computer implemented method of any one of clauses j.1 to j.5, wherein the source chart is associated with a first chart type that defines how the set of source chart data series are displayed and the destination chart is associated with a second chart type that defines how the set of destination chart data series are displayed, and wherein the new chart is associated with the first chart type.

[1492] Clause j.8. The computer implemented method of clause j.6, wherein the first and second chart types are selected from a group including: a bar chart type; a line chart type; a pie chart type; and a scatter plot chat type.

[1493] Clause j.9. The computer implemented method of any one of clauses j.1 to j.8, further including: [1494] receiving a first set of one or more user inputs selecting the source chart; and [1495] receiving a second set of one or more user inputs selecting the destination chart.

[1496] Clause j.10. The computer implemented method of any one of clauses j.1 to j.8, wherein the source chart and the destination chart are automatically determined.

[1497] Clause j.11. The computer implemented method of any one of clauses j.1 to j.8, wherein the source chart and the destination chart are determined based on a content map generated according to the method of any one of clauses f.1 to f.13.

Clause Set K

[1498] Clause k.1. A computer implemented method including: [1499] accessing data describing a set of original elements, wherein each original element has an original bounding box; [1500] processing the set of original elements to identify a set of pre-existing element overlaps, wherein each pre-existing element overlap identifies a pair of original elements which are determined to be overlapping based on their original bounding boxes; [1501] accessing data describing a set of updated elements, wherein each updated element corresponds to an original element and has an updated bounding box, and wherein the updated bounding box of at least one updated element is different to the original bounding box of the corresponding original element; and [1502] identifying a first undesirable collision, wherein identifying the first undesirable collision includes: [1503] determining that a first current element overlap exists, wherein the first current element overlap is in respect of a first updated element and a second updated element and is identified based on a first updated bounding box of the first updated element and a second updated bounding box of the second updated element; and [1504] determining that the first current element overlap is an introduced overlap, wherein determining that the first current element overlap is an introduced overlap includes determining that there is no pre-existing overlap in respect of a first original element that corresponds to the first updated element overlapping a second original element that corresponds to the second updated element.

[1505] Clause k.2. The computer implemented method of clause k.1, wherein identifying the first undesirable collision further includes: [1506] determining a first expansion direction, wherein the first expansion direction is a direction in which content of the first updated element would expand

if additional content was added to the first updated element; and [1507] determining that the first expansion direction is a direction from the first updated element to the second updated element.

[1508] Clause k.3. The computer implemented method of clause k.2, wherein the first expansion direction is determined based on a text alignment attribute of the first updated element.

[1509] Clause k.4. The computer implemented method of any one of clauses k.1 to k.3, wherein identifying the first undesirable collision further includes: [1510] calculating a first pre-existing penetration distance, the first pre-existing penetration distance being based on a distance that a first original bounding box of the first original element plus an element margin penetrates into a second original bounding box of the second original element; [1511] calculating a first current penetration distance, the first current penetration distance being based on a distance that the first updated element's updated bounding box plus the element margin penetrates into the second updated element's updated bounding box; and [1512] determining that the first current penetration distance is greater than the first pre-existing penetration distance.

[1513] Clause k.5. The computer implemented method of any one of clauses k.1 to k.4, wherein the first updated element is a text type element.

[1514] Clause k.6. The computer implemented method of any one of clauses k.1 to k.5, wherein the second updated element is a text type element.

[1515] Clause k.7. The computer implemented method of any one of clauses k.1 to k.6, wherein determining that the first current element overlap exists includes determining that the first updated bounding box extends into an element margin around the second updated bounding box.

[1516] Clause k.8. The computer implemented method of any one of clauses k.1 to k.7, further including: [1517] determining that the first updated element is solely responsible for the first undesirable collision; and [1518] resolving the first undesirable collision by resizing the first updated bounding box.

[1519] Clause k.9. The computer implemented method of clause k.8, wherein determining that the first updated element is solely responsible for the first undesirable collision includes: [1520] determining a first expansion direction, wherein the first expansion direction is a direction in which content of the first updated element would expand if additional content was added to the first updated element; [1521] determining a second expansion direction, wherein the second expansion direction is a direction in which content of the second updated element would expand if additional content was added to the second updated element; [1522] determining that the first expansion direction is a direction from the first updated element to the second updated element; and [1523] determining that the second expansion direction is not a direction from the second updated element to the first updated element.

[1524] Clause k.10. The computer implemented method of clause k.8 or clause k.9, wherein resolving the first undesirable collision includes: [1525] calculating a first penetration distance; [1526] resizing the first updated bounding box based on the first penetration distance; and [1527] shrinking content of the first updated element to fit within the resized first updated bounding box.

[1528] Clause k.11. The computer implemented method of k.10 when dependent on k.4, wherein the first penetration distance is calculated as the first pre-existing penetration distance subtracted from the first current penetration distance.

[1529] Clause k.12. The computer implemented method of any one of clauses k.1 to k.7, further including: [1530] determining that the first updated element and the second updated element are jointly responsible for the first undesirable collision; and [1531] resolving the first undesirable collision by resizing the first updated bounding box and resizing the second updated bounding box.

[1532] Clause k.13. The computer implemented method of clause k.12, wherein determining that the first updated element and the second update element are jointly responsible for the first undesirable collision includes: [1533] determining a first expansion direction, wherein the first expansion direction is a direction in which content of the first updated element would expand if additional content was added to the first updated element; [1534] determining a second expansion

direction, wherein the second expansion direction is a direction in which content of the second updated element would expand if additional content was added to the second updated element; [1535] determining that the first expansion direction is a direction from the first updated element to the second updated element; and [1536] determining that the second expansion direction is a direction from the second updated element to the first updated element.

[1537] Clause k.14. The computer implemented method of clause k.12 or clause k.13, wherein resolving the first undesirable collision includes: [1538] calculating a first penetration distance; [1539] calculating a first proportion of the first penetration distance and a second proportion of the first penetration distance; [1540] resizing the first updated bounding box based on the first proportion of the first penetration distance; [1541] shrinking content of the first updated element to fit within the resized first updated bounding box; [1542] resizing the second updated bounding box based on the second proportion of the first penetration distance; and [1543] shrinking content of the second updated element to fit within the resized second updated bounding box.

[1544] Clause k.15. The computer implemented method of clause k.14 when dependent on k.4, wherein the first penetration distance is calculated as the first pre-existing penetration distance subtracted from the first current penetration distance.

[1545] Clause k.16. The computer implemented method of clause k.14 or clause k.15 wherein: [1546] the first and second proportions of the first penetration distance are calculated based on a first expansion value and a second expansion value, wherein: [1547] the first expansion value is based on a distance that the first updated bounding box has expanded when compared to a first original bounding box of the first original element; and [1548] the second expansion value is based on a distance that the second updated bounding box has expanded when compared to a second original bounding box of the second original element.

[1549] Clause k.17. The computer implemented method of any one of clauses k.8 to k.16, wherein resizing the first updated bounding box includes one or both of: reducing a height of the first updated bounding box based on the first penetration distance; and adjusting a vertical position of the first updated bounding box based on the first penetration distance.

[1550] Clause k.18. The computer implemented method of any one of clauses k.8 to k.17, wherein the first updated element is a text type element with first text content and shrinking the content of the first updated element includes making a first reduction to a font size of the first text content.

[1551] Clause k.19. The computer implemented method of clause k.18, further including: [1552] determining whether any single-word wrapping exists in the first text content; and [1553] in response to determining that single-word wrapping exists in the first text content, making a second reduction to the font size of the first text content to eliminate the single-word wrapping.

[1554] Clause k.20. The computer implemented method of any one of clauses k.1 to k.20 further including identifying a second undesirable collision according to a method of clause l.1 or clause l.2.

[1555] Clause k.21. The computer implemented method of clause k.21, further including resolving the second undesirable collision according to a method of any one of clauses l.3 to l.9.

Clause Set L

[1556] Clause l.1. A computer implemented method including: [1557] accessing data describing a set of original elements, wherein each original element has an original bounding box; [1558] processing the set of original elements to identify a set of pre-existing element overlaps, wherein each pre-existing element overlap identifies a pair of original elements which are determined to be overlapping based on their original bounding boxes; [1559] accessing data describing a set of updated elements, wherein each updated element corresponds to an original element and has an updated bounding box, and wherein the updated bounding box of at least one updated element is different to the original bounding box of the corresponding original element; and [1560] identifying a second undesirable collision, wherein identifying the second undesirable collision includes: [1561] determining that a second current element overlap exists, wherein the second current

element overlap is in respect of a third updated element and a fourth updated element and is identified based on a third updated bounding box of the third updated element overlapping a fourth updated bounding box of the fourth updated element; [1562] determining that the third updated bounding box is not contained entirely within the second updated bounding box; and [1563] determining that the second current element overlap has a corresponding a pre-existing overlap, wherein the corresponding pre-existing overlap is in respect of a third original element that corresponds to the third updated element and a fourth original element that corresponds to the fourth updated element, and wherein a third original bounding box of the third original element is contained entirely within a fourth original bounding box of the fourth original element.

[1564] Clause 1.2. The computer implemented method of clause 1.1, wherein the third updated element is a text type element.

[1565] Clause 1.3. The computer implemented method of clause 1.1 or clause 1.2, further including resolving the second undesirable collision by: [1566] calculating a second penetration distance; [1567] resizing the third updated bounding box based on the second penetration distance; and [1568] shrinking content of the third updated element to fit within the resized third updated bounding box.

[1569] Clause 1.4. The computer implemented method of clause 1.3, wherein the second penetration distance is based on an amount that the third updated bounding box has expanded compared to the third original bounding box

[1570] Clause 1.5. The computer implemented method of clause 1.3 or clause 1.4, wherein calculating the second penetration distance includes: [1571] determining a second penetration direction, the second penetration direction being a direction that the third updated bounding box extends out of the fourth updated bounding box; and [1572] calculating the second penetration distance as the distance that the third updated bounding box has expanded in the second penetration direction when compared to the third original bounding box.

[1573] Clause 1.6. The computer implemented method of any one of clauses 1.3 to 1.5, wherein resizing the third updated bounding box includes reducing a height of the third updated bounding box based on the second penetration distance.

[1574] Clause 1.7. The computer implemented method of any one of clauses 1.3 to 1.6, wherein resizing the third updated bounding box includes adjusting a vertical position of the third updated bounding box based on the second penetration distance.

[1575] Clause 1.8. The computer implemented method of any one of clauses 1.3 to 1.7, wherein the third updated element is a text type element with third text content and shrinking the content of the third updated element includes making a first reduction to a font size of the third text content.

[1576] Clause 1.9. The computer implemented method of clause 1.8, further including: [1577] determining whether any single-word wrapping exists in the third text content; and [1578] in response to determining that single-word wrapping exists in the third text content, making a second reduction to the font size of the third text content to eliminate the single-word wrapping.

[1579] Clause 1.10. The computer implemented method of any one of clauses 1.1 to 1.9 further including identifying a first undesirable collision according to a method of any one of clauses k.1 to k.7.

[1580] Clause 1.11. The computer implemented method of clause 1.10, further including resolving the first undesirable collision according to a method of any one of clauses k.8 to k.19.

Clause Set M

[1581] Clause m.1. A computer implemented method including: [1582] accessing element data defining a set of elements, each element defining text content and being associated with a text hierarchy level; [1583] analysing the element data to determine that a first intra-hierarchy conflict exists, wherein determining that the first intra-hierarchy exists includes: [1584] identifying a first element that defines first text content and is associated with a first text hierarchy level; [1585] identifying a second element that defines second text content and is associated with the first text

hierarchy level; and [1586] determining that a font size of the first text content is different to a font size of the second text content; and [1587] resolving the first intra-hierarchy conflict by reducing the font size of the first text content or the font size of the second text content.

[1588] Clause m.2. The computer implemented method of clause m.1, wherein resolving the first intra-hierarchy conflict includes: [1589] determining that the font size of the first text content is larger than the font size of the second text content; and [1590] setting the font size of the first text content to be equal to the font size of the second text content.

[1591] Clause m.3. The computer implemented method of clause m.2, further including: [1592] identifying a third element that is associated with the first text hierarchy level and that defines third text content; [1593] determining that a font size of the third text content is different to the font size of the second text content; and [1594] setting the font size of the third text content to be equal to the font size of the second text content.

[1595] Clause m.4. The computer implemented method of any one of clauses m.1 to m.3, further including: [1596] analysing the element data to determine that a second intra-hierarchy conflict exists, wherein determining that the second intra-hierarchy exists includes: [1597] identifying a fourth element that defines fourth text content and is associated with a second text hierarchy level; [1598] identifying a fifth element that defines fifth text content and is associated with the second text hierarchy level; and [1599] determining that a font size of the fourth text content is different to a font size of the fifth text content; and [1600] resolving the first intra-hierarchy conflict by reducing the font size of the fourth text content or the font size of the fifth text content.

[1601] Clause m.5. The computer implemented method of clause m.4, wherein resolving the second intra-intra hierarchy conflict includes: [1602] determining that the font size of the fourth text content is larger than the font size of the fifth text content; and [1603] setting the font size of the fourth text content to be equal to the font size of the fifth text content.

[1604] Clause m.6. The computer implemented method of any one of clauses m.1 to m.5, wherein the method is performed after resolving one or more undesirable element collisions, wherein the one or more undesirable element collisions are resolved according to the method of any one of clauses k.8 to k.20 or any one of clauses l.3 to l.9.

Clause Set N

[1605] Clause n.1. A computer implemented method including: [1606] accessing element data defining a set of elements, each element defining text content and being associated with a text hierarchy level; [1607] analysing the element data to determine that a first inter-hierarchy conflict exists with respect to a first text hierarchy level, wherein determining that the first inter-hierarchy conflict exists includes: [1608] identifying a first element that defines first text content and is associated with the first text hierarchy level; [1609] identifying a second element that defines second text content and is associated with a second text hierarchy level, wherein the second text hierarchy level is a lower text hierarchy level than the first text hierarchy level; and [1610] determining that a font size of the second text content is greater than or equal to a font size of the first text content; and [1611] resolving the first inter-hierarchy conflict by setting the font size of the second text content to a first new font size, the first new font size being smaller than the font size of the first text content.

[1612] Clause n.2. The computer implemented method of clause n.1, further including: [1613] identifying a third element that defines third text content and is associated with the second text hierarchy level; and [1614] setting the font size of the third text content to the first new font size.

[1615] Clause n.3. The computer implemented method of clause n.1 or clause n.2, wherein the first text hierarchy level is a highest text hierarchy level and the second text hierarchy level is a second highest text hierarchy level, and the method further includes: [1616] analysing the element data to determine that a second inter-hierarchy conflict exists with respect to the second text hierarchy level, wherein determining that the second inter-hierarchy conflict exists includes: [1617] identifying a fourth element that defines fourth text content and is associated with a third text

hierarchy level, wherein the third text hierarchy level is a lower text hierarchy level than the second text hierarchy level; and [1618] determining that a font size of the fourth text content is greater than or equal to the first new font size; and [1619] resolving the second inter-hierarchy conflict by setting the font size of the fourth text content to a second new font size, the second new font size being smaller than the first new font size.

[1620] Clause n.4. The computer implemented method of any one of clauses n.1 to n.3, wherein the method is performed after resolving one or more undesirable element collisions, wherein the one or more undesirable element collisions are resolved according to the method of any one of clauses k.8 to k.20 or any one of clauses l.3 to l.9.

[1621] Clause n.5. The computer implemented method of any one of clauses n.1 to n.4, wherein the method is performed after identifying and resolving one or more intra-hierarchy conflicts, wherein the one or more intra-hierarchy conflicts are resolved according to the method of any one of clauses m.1 to m.5.

Clause Set O

[1622] Clause o.1. A computer implemented method including: [1623] accessing a set of input paragraphs, wherein each input paragraph is associated with one or more format attributes, and wherein the one or more format attributes of each input paragraph includes a font size attribute; [1624] generating an ordered set of input paragraph identifiers, wherein each input paragraph identifier identifies an input paragraph of the set of input paragraphs, and wherein the ordered set of input paragraph identifiers is ordered based on the font size attributes associated with each input paragraph; and [1625] progressively subdividing the ordered set of input paragraph identifiers into a set of input paragraph subgroups, wherein the progressive subdividing is based on the one or more format attributes of the one or more input paragraphs and on completion each input paragraph subgroup defines a different text hierarchy level.

[1626] Clause o.2. The computer implemented method of clause o.1, wherein progressively subdividing the ordered set of input paragraph identifiers includes performing a first-in-order subdivision in which the ordered set of input paragraphs are grouped into subgroups based on font size.

[1627] Clause o.3. The computer implemented method of clause o.2, wherein: [1628] progressively subdividing the ordered set of input paragraph identifiers includes performing a second-in-order subdivision; and [1629] the second-in-order subdivision includes subdividing the subgroups of input paragraph identifiers that are in the ordered set of input paragraph identifiers following the first-in-order subdivision based on a first format type.

[1630] Clause o.4. The computer implemented method of clause o.3, wherein the first format type is list indentation.

[1631] Clause o.5. The computer implemented method of clause o.3. or clause o.4, wherein: [1632] progressively subdividing the ordered set of input paragraph identifiers includes performing a third-in-order subdivision; and [1633] the third-in-order subdivision includes subdividing the subgroups of input paragraph identifiers that are in the ordered set of input paragraph identifiers following the second-in-order subdivision based on a second format type.

[1634] Clause o.6. The computer implemented method of clause o.5, wherein the second format type is underline.

[1635] Clause o.7. The computer implemented method of clause o.5 or clause o.6, wherein: [1636] progressively subdividing the ordered set of input paragraph identifiers includes performing a fourth-in-order subdivision; and [1637] the fourth-in-order subdivision includes subdividing the subgroups of input paragraph identifiers that are in the ordered set of input paragraph identifiers following the third-in-order subdivision based on a third format type.

[1638] Clause o.8. The computer implemented method of clause o.7, wherein the third format type is all-caps.

[1639] Clause o.9. The computer implemented method of clause o.7 or clause o.8, wherein: [1640]

progressively subdividing the ordered set of input paragraph identifiers includes performing a fifth-in-order subdivision; and [1641] the fifth-in-order subdivision includes subdividing the subgroups of input paragraph identifiers that are in the ordered set of input paragraph identifiers following the fourth-in-order subdivision based on a fourth format type.

[1642] Clause o.10. The computer implemented method of clause o.9, wherein the fourth format type is bold.

Clause Set P

[1643] Clause p.1. A computer implemented method including: [1644] accessing data defining a set of design elements, wherein the set of design elements includes a first element defining a first fill and one or more other elements; and [1645] analysing the first element to determine if the first fill is suitable for replacement by a second fill that has one or more transparent regions by: [1646] selecting a second element from the one or more other elements for analysis; and [1647] analysing the second element to determine whether the second element makes the first fill unsuitable for replacement by the second fill, [1648] wherein: [1649] in response to determining that the second element makes the first fill unsuitable for replacement by the second fill, returning a value that indicates that the first fill is unsuitable for replacement by the second fill; and [1650] in response to determining that the second element does not make the first fill unsuitable for replacement by the second fill: [1651] determining whether the one or more other elements includes a third element that has not been selected for analysis; and [1652] in response to determining that the one or more other elements includes the third element, selecting the third element for analysis and analysing the third element to determine whether the third element makes the first fill unsuitable for replacement by the second fill.

[1653] Clause p.2. The computer implemented method of clause p.1, wherein in response to determining that the one or more other elements does not include the third element, returning a value that indicates that the first fill is suitable for replacement by the second fill.

[1654] Clause p.3. The computer implemented method of clause p.1 or clause p.2, wherein analysing the second element includes: [1655] determining whether the second element is behind the first element and contains the first element.

[1656] Clause p.4. The computer implemented method of clause p.3, wherein determining whether the second element is behind the first element is based on a first depth value that defines a depth of the first element and a second depth value that defines a depth of the second element.

[1657] Clause p.5. The computer implemented method of clause p.3 or clause p.4, wherein determining whether the second element contains the first element is based on a first bounding box of the first element and a second bounding box of the second element.

[1658] Clause p.6. The computer implemented method of any one of clauses p.3 to p.5, wherein in response to determining that the second element is behind the first element and contains the first element, analysing the second element further includes: [1659] determining that the second element does not make the first fill unsuitable for replacement by the second fill.

[1660] Clause p.7. The computer implemented method of any one of clauses p.3 to p.5, wherein in response to determining that the second element is not behind the first element or does not contain the first element, analysing the second element further includes: [1661] determining whether the first element and the second element intersect.

[1662] Clause p.8. The computer implemented method of clause p.7 when dependent on clause p.5, wherein determining whether the first element and the second element intersect is based on the first bounding box of the first element and the second bounding box of the second element.

[1663] Clause p.9. The computer implemented method of clause p.7 or clause p.8, wherein in response to determining that the first element and the second element intersect, analysing the second element further includes: [1664] determining that the second element makes the first fill unsuitable for replacement by the second fill.

[1665] Clause p.10. The computer implemented method of clause p.7 or clause p.8, wherein in

response to determining that the first element and the second element do not intersect, analysing the second element further includes: [1666] determining that the second element does not make the first fill unsuitable for replacement by the second fill.

[1667] Clause p.11. The computer implemented method of clause p.5 or clause p.8, wherein the first bounding box is an original bounding box of the first element and the second bounding box is an original bounding box of the second element.

[1668] Clause p.12. The computer implemented method of clause p.5 or clause p.8, wherein the first bounding box is a modified bounding box of the first element and the second bounding box is a modified bounding box of the second element.

[1669] Clause p.13. The computer implemented method of clause p.12, further including: [1670] calculating the first bounding box by expanding an original bounding box of the first element by a fixed margin; and [1671] calculating the second bounding box by expanding an original bounding box of the second element by the fixed margin.

[1672] Clause p.14. The computer implemented method of clause p.12, further including: [1673] calculating the first bounding box by expanding an original bounding box of the first element by an expansion factor; and [1674] calculating the second bounding box by expanding an original bounding box of the second element by the expansion factor.

[1675] Clause p.15. The computer implemented method of any one of clauses p.1 to p.14, further including: [1676] analysing a fourth element that defines a third fill to determine if the third fill is suitable for replacement by a fourth fill that has one or more transparent regions by: [1677] determining whether the third fill is a rectangular fill; and [1678] in response to determining that the third fill is the rectangular fill, determining that the third fill unsuitable for replacement by the fourth fill and returning a value that indicates that the third fill is unsuitable for replacement by the fourth fill.

Clause Set Q

[1679] Clause q.1. A computer implemented method for generating a new deck format design based on a source design, the method including: [1680] processing the source design to generate source design analysis data, the source design analysis data defining a first candidate page, the first candidate page associated with a first set of source objects, each source object corresponding to source content of the source design; [1681] analysing a first template to determine if the first template design matches the source design, wherein the first template is a deck format design that includes a first template page, and wherein analysing the first template design is based on the source design analysis data and first template design analysis data, the first template design analysis data defining a first set of destination objects, each destination object in the first set of destination objects corresponding to an element of the first template page; [1682] determining that the first template matches the source design; [1683] generating a first new deck descriptor, the first new deck descriptor being in respect of the first template and including first content map data, the first content map data mapping a first source object from the set of source objects to a first destination object from the first set of destination objects; and [1684] generating the new deck format design based on the source design and the first new deck descriptor.

[1685] Clause q.2. The computer implemented method of clause q.1, wherein determining that the first template matches the source design includes determining that the first template page matches the first candidate page.

[1686] Clause q.3. The computer implemented method of clause q.1 or q.2, wherein: [1687] the source design analysis data defines a plurality of candidate pages; [1688] the first template includes a plurality of template pages; and [1689] determining that the first template matches the source design includes determining that two or more template pages match two or more candidate pages.

[1690] Clause q.4. The computer implemented method of clause q.2 or clause q.3, wherein: [1691] the method further includes generating a first partition key, the first partition key corresponding to the first candidate page and including a plurality of partition key values that provide a first measure

of the type and amount of source content defined by the first set of source objects; and [1692] determining that the first template page matches the first candidate page is based on a comparison of the first partition key and a second partition key, the second partition key corresponding to the first template page.

[1693] Clause q.5. The computer implemented method of clause q.4, wherein generating the first partition key includes generating one or more first partition key values selected from a group including: [1694] a partition key texts value that indicates a number of text type source objects in the set of one or more source objects, each text type source object corresponding to a text type source content segment of the source design; [1695] a partition key fills value that indicates a number of fill type source objects in the set of one or more source objects, each fill type source object corresponding to a fill of the source design; [1696] a partition key charts value that indicates a number of chart type source objects in the set of one or more source objects, each chart type source object corresponding to a chart of the source design; and [1697] a partition key tables value that indicates a number of table type source objects in the set of one or more source objects, each table type source object corresponding to a table of the source design.

[1698] Clause q.6. The computer implemented method of any one of clauses q.2 to q.5, wherein: [1699] the method further includes generating a first page vector, the first page vector corresponding to the first candidate page and including a plurality of page vector values that provide a second measure of the type and amount of source content defined by the first set of source objects; and [1700] determining that the first template page matches the first candidate page is based on a comparison of the first page vector and a second page vector, the second page vector corresponding to the first template page.

[1701] Clause q.7. The computer implemented method of clause q.6, wherein generating the first page vector includes generating a set of one or more page vector characters values, wherein a first page vector characters value is associated with a first text hierarchy level and is based on a number of characters that are defined by source objects in the first set of source objects that are text-type source objects and that are associated with the first text hierarchy level.

[1702] Clause q.8. The computer implemented method of clause q.6 or q.7, wherein generating the first page vector includes generating a set of one or more page vector lines values, wherein a first page vector lines value is associated with a first text hierarchy level and is based on a number of lines of text that are defined by source objects in the first set of source objects that are text-type source objects and that are associated with the first text hierarchy level.

[1703] Clause q.9. The computer implemented method of any one of clauses q.6 to q.8, wherein generating the first page vector includes generating one or more page vector values selected from a group including: [1704] a fills aspect ratio value that is based on aspect ratios of any fill type source objects in the set of one or more source objects, each fill type source object corresponding to a fill of the source design; [1705] a charts aspect ratio value that is based on aspect ratios defined by any chart type source objects in the set of one or more source objects, each chart type source object corresponding to a chart of the source design; and [1706] a tables aspect ratio value that is based on aspect ratios defined by any table type source objects in the set of one or more source objects, each table type source object corresponding to a table of the source design.

[1707] Clause q.10. The computer implemented method of any one of clauses q.1 to q.9, wherein processing the source design to generate the source design analysis data includes generating a first source object corresponding to first source content of the first candidate page, and wherein the first source object is associated with a first set of source object attributes that include: [1708] a source identifier attribute that identifies the first source content; [1709] a type attribute that identifies a content type of the first source content; and [1710] a reading order attribute that identifies a position of the first source content in a reading order of the first candidate page.

[1711] Clause q.11. The computer implemented method of clause q.10, wherein the first set of source object attributes further includes one or more of [1712] a transfer content attribute that

indicates whether the first source content is to be transferred to the new deck format design or not; [1713] a text hierarchy level attribute that indicates a text hierarchy level of the first content if the first content is text type content; [1714] a characters attribute that is based on a number of characters of the first content if the first content is text type content; and [1715] a lines attribute that is based on a vertical distance that the first content occupies if the first content is text type content. [1716] Clause q.12. The computer implemented method of any one of clauses q.1 to q.11, further including generating a first rewrite of the first candidate page, and wherein determining that the first template matches the source design includes determining that the first template page matches the first rewrite of the first candidate page.

[1717] Clause q.13. The computer implemented method of clause q.12, wherein generating the first rewrite of the first source page includes combining the source content defined by two or more of the source objects together.

[1718] Clause q.14. The computer implemented method of any one of clauses q.1 to q.13, wherein: [1719] the first content map data is generated according to the method of any one of clauses f.1 to f.13

[1720] Clause q.15. The computer implemented method of any one of clauses q.1 to q.14, wherein: [1721] the first content map data maps a first source object from the set of source objects and a second source object from the set of source objects to a first destination object from the first set of destination objects; [1722] the first source object and the second source object are fill type source objects that define first and second source fills respectively; [1723] the first destination object is a fill type destination object that corresponds to a shape type destination element; and [1724] generating the new deck format design includes transferring the first and second source fills to the shape type destination element according to the method of any one of clauses h.1 to h.14.

[1725] Clause q.16. The computer implemented method of any one of clauses q.1 to q.16, wherein: [1726] the first content map data maps a third source object from the set of source objects to a second destination object from the first set of destination objects; [1727] the third source object is a table type source object that corresponds to a source table; [1728] the second destination object is a table type destination object that corresponds to a table type destination element; and [1729] generating the new deck format design includes transferring the source table to the table type destination element according to the method of any one of clauses i.1 to i.16.

[1730] Clause q.17. The computer implemented method of any one of clauses q.1 to q.16, wherein: [1731] the first content map data maps a fourth source object from the set of source objects to a third destination object from the first set of destination objects; [1732] the fourth source object is a chart type source object that corresponds to a source chart; [1733] the third destination object is a chart type destination object that corresponds to a chart type destination element; and [1734] generating the new deck format design includes transferring the source chart to the chart type destination element according to the method of any one of clauses j.1 to j.8.

[1735] clause q.18. The computer implemented method of any one of clauses q.1 to q.17, wherein the source design is a document-format design and analysing the source design to generate source design analysis data is performed in accordance with the method of any one of clauses b.1 to b.11.

[1736] clause q.19. The computer implemented method of clause q.18, wherein the first candidate page is generated according the method of any one of clauses c.1 to c.13.

[1737] clause q.20. The computer implemented method of any one of clauses q.1 to q.19, wherein the source design is a deck format design, and analysing the source design to generate source design analysis data is performed in accordance with the method of any one of clauses a.1 to a.8 or any one of clauses a.23 to a.24.

[1738] clause q.21. The computer implemented method of any one of clauses q.1 to q.20, wherein the first template design is a deck format design, and the method further includes generating the first and first template design analysis data in accordance with the method of any one of clauses a.1 to a.11 or any one of clauses a.14 to a.24.

Clause Set r

[1739] Clause r.1. A computer processing system including: [1740] one or more processing units; and [1741] one or more non-transitory computer-readable storage media storing instructions, which when executed by the one or more processing units, cause the one or more processing units to perform a method according to: any one of clauses a.1 to a.24; any one of clauses b.1 to b.24; any one of clauses c.1 to c.16; any one of clauses d.1 to d.15; any one of clauses e.1 to e.16; any one of clauses f.1 to f.13; any one of clauses g.1 to g.15; any one of clauses h.1 to g.17; any one of clauses i.1 to i.19; any one of clauses j.1 to j.11; any one of clauses k.1 to k.21; any one of clauses l.1 to l.11; any one of clauses m.1 to m.6; any one of clauses n.1 to n.5; any one of clauses o.1 to o.10; any one of clauses p.1 to p.15; and/or any one of clauses q.1 to q.21.

[1742] Clause r.2. One or more non-transitory storage media storing instructions executable by one or more processing units to cause the one or more processing units to perform a method according to: any one of clauses a.1 to a.24; any one of clauses b.1 to b.24; any one of clauses c.1 to c.16; any one of clauses d.1 to d.15; any one of clauses e.1 to e.16; any one of clauses f.1 to f.13; any one of clauses g.1 to g.15; any one of clauses h.1 to g.17; any one of clauses i.1 to i.19; any one of clauses j.1 to j.11; any one of clauses k.1 to k.21; any one of clauses l.1 to l.11; any one of clauses m.1 to m.6; any one of clauses n.1 to n.5; any one of clauses o.1 to o.10; any one of clauses p.1 to p.15; and/or any one of clauses q.1 to q.21.

[1743] In the embodiments described above, processing is described as being performed by specific applications or modules. Variations are possible, and generally speaking an operation that is described as being performed by one particular application or module could be performed by an alternative application or module.

[1744] The flowcharts illustrated in the figures and described above define processing blocks operations in particular orders to explain various features. In some cases the processing described and illustrated may be able to be performed in a different order to that shown/described, one or more operations may be combined into a single operation, a single operation may be divided into multiple separate operations, and/or the function(s) achieved by one or more of the described/illustrated operations may be achieved by one or more alternative operations. Still further, the functionality/processing of a given flowchart operation could potentially be performed by different systems or applications than that described.

[1745] In the above description, certain operations and features are explicitly described as being optional. This should not be interpreted as indicating that if an operation or feature is not explicitly described as being optional it should be considered essential. Even if an operation or feature is not explicitly described as being optional it may still be optional.

[1746] The present disclosure provides various user interface examples. It will be appreciated that alternative user interfaces are possible. Such alternative user interfaces may provide the same or similar user interface features to those described and/or illustrated in different ways, provide additional user interface features to those described and/or illustrated, or omit certain user interface features that have been described and/or illustrated.

[1747] In some instances the present disclosure and/or claims use the terms “first,” “second,” etc. to identify and distinguish between features. When used in this way, these terms are not used in an ordinal sense and are not intended to imply any particular order. For example, a first feature could equally be referred to a second feature without departing from the scope of the described examples. Furthermore, when used to differentiate features, a second feature could exist without a first feature or a second feature could occur or be ordered before a first feature.

[1748] Unless otherwise stated, the terms “include” and “comprise” (and variations thereof such as “including”, “includes”, “comprising”, “comprises”, “comprised” and the like) are used inclusively and do not exclude further features, components, integers, steps, or elements.

[1749] It will be understood that the embodiments disclosed and defined in this specification extend to alternative combinations of two or more of the individual features mentioned in or

evident from the text, drawings, or clauses. All of these different combinations constitute alternative embodiments of the present disclosure.

[1750] The present specification describes various embodiments with reference to numerous specific details that may vary from implementation to implementation. No limitation, element, property, feature, advantage or attribute that is not expressly recited in a claim should be considered as a required or essential feature. Accordingly, the specification and drawings are to be regarded in an illustrative rather than a restrictive sense.

Claims

1. A computer implemented method for generating a new chart based on a source chart and a destination chart, the method including: accessing source chart data in respect of the source chart, wherein the source chart data defines a set of source chart data series and a set of source chart colours, and wherein each source chart data series is associated with a source chart colour; accessing destination chart data in respect of the destination chart, wherein the destination chart data defines a set of destination chart data series and a set of destination chart colours, and wherein each destination chart data series is associated with a destination chart colour; determining that the number of source chart colours is greater than the number of destination chart colours; in response to determining that the number of source chart colours is greater than the number of destination chart colours, generating one or more new chart colours; generating the new chart to include the set of source chart data series; associating a first source chart data series in the new chart with a destination chart colour; and associating a second source chart data series in the new chart with a new chart colour.
2. The computer implemented method of claim 1, wherein each of the one or more new chart colours is generated based on a destination chart colour.
3. The computer implemented method of claim 2, wherein generating a first new chart colour includes: selecting a first destination chart colour; and generating the first new chart colour as a variant of the first destination chart colour.
4. The computer implemented method of claim 3, wherein the first new chart colour is generated as a brightness variant of the first destination chart colour.
5. The computer implemented method of claim 3, wherein the first new chart colour is generated as a luminance variant of the first destination chart colour.
6. The computer implemented method of claim 1, wherein the source chart is associated with a first chart type that defines how the set of source chart data series are displayed and the destination chart is associated with a second chart type that defines how the set of destination chart data series are displayed, and wherein the new chart is associated with the second chart type.
7. The computer implemented method of claim 1, wherein the source chart is associated with a first chart type that defines how the set of source chart data series are displayed and the destination chart is associated with a second chart type that defines how the set of destination chart data series are displayed, and wherein the new chart is associated with the first chart type.
8. The computer implemented method of claim 6, wherein the first chart type is selected from a group including: a bar chart type; a line chart type; a pie chart type; and a scatter plot chart type.
9. The computer implemented method of claim 6, wherein the second chart type is selected from a group including: a bar chart type; a line chart type; a pie chart type; and a scatter plot chart type.
10. The computer implemented method of claim 1, further including: receiving a first set of one or more user inputs selecting the source chart; and receiving a second set of one or more user inputs selecting the destination chart.
11. The computer implemented method of claim 1, wherein the source chart and the destination chart are automatically determined.
12. A computer processing system including: one or more processing units; and one or more non-

transitory computer-readable storage media storing instructions, which when executed by the one or more processing units, cause the one or more processing units to perform a method including: accessing source chart data in respect of the source chart, wherein the source chart data defines a set of source chart data series and a set of source chart colours, and wherein each source chart data series is associated with a source chart colour; accessing destination chart data in respect of the destination chart, wherein the destination chart data defines a set of destination chart data series and a set of destination chart colours, and wherein each destination chart data series is associated with a destination chart colour; determining that the number of source chart colours is greater than the number of destination chart colours; in response to determining that the number of source chart colours is greater than the number of destination chart colours, generating one or more new chart colours; generating the new chart to include the set of source chart data series; associating a first source chart data series in the new chart with a destination chart colour; and associating a second source chart data series in the new chart with a new chart colour.

13. The computer processing system of claim 12, wherein each of the one or more new chart colours is generated based on a destination chart colour.

14. The computer processing system of claim 13, wherein generating a first new chart colour includes: selecting a first destination chart colour; and generating the first new chart colour as a variant of the first destination chart colour.

15. The computer processing system of claim 14, wherein the first new chart colour is generated as a brightness variant of the first destination chart colour.

16. The computer processing system of claim 14, wherein the first new chart colour is generated as a luminance variant of the first destination chart colour.

17. The computer processing system of claim 12, wherein the source chart is associated with a first chart type that defines how the set of source chart data series are displayed and the destination chart is associated with a second chart type that defines how the set of destination chart data series are displayed, and wherein the new chart is associated with the second chart type.

18. The computer processing system of claim 12, wherein the source chart is associated with a first chart type that defines how the set of source chart data series are displayed and the destination chart is associated with a second chart type that defines how the set of destination chart data series are displayed, and wherein the new chart is associated with the first chart type.

19. The computer processing system of claim 17, wherein the first chart type is selected from a group including: a bar chart type; a line chart type; a pie chart type; and a scatter plot chart type.

20. One or more non-transitory storage media storing instructions executable by one or more processing units to cause the one or more processing units to perform a method including: accessing source chart data in respect of the source chart, wherein the source chart data defines a set of source chart data series and a set of source chart colours, and wherein each source chart data series is associated with a source chart colour; accessing destination chart data in respect of the destination chart, wherein the destination chart data defines a set of destination chart data series and a set of destination chart colours, and wherein each destination chart data series is associated with a destination chart colour; determining that the number of source chart colours is greater than the number of destination chart colours; in response to determining that the number of source chart colours is greater than the number of destination chart colours, generating one or more new chart colours; generating the new chart to include the set of source chart data series; associating a first source chart data series in the new chart with a destination chart colour; and associating a second source chart data series in the new chart with a new chart colour.
