

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250255740

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

Diedering; Jason S. et al.

LOADING SYSTEMS FOR COLLAPSIBLE PROSTHETIC HEART VALVE DEVICES AND METHODS THEREOF

Abstract

Loading systems for prosthetic heart valve devices are disclosed. A loading funnel is provided within a watertight interior space that is at least partially filled or fillable with biocompatible fluid. Funnel may have a cylindrical end to which is connected a delivery catheter having a lumen that will receive the collapsed prosthetic heart valve device. An expanded prosthetic heart valve device may be placed within the funnel and pushed or pulled into the funnel which provides a predictable, reliable and repeatable surface for collapsing the prosthetic heart valve device. Ultimately the prosthetic heart valve device is collapsed and translated into the lumen of the delivery catheter for further translation therealong and release into the heart chamber of interest.

Inventors: Diedering; Jason S. (Minneapolis, MN), Kumar; Saravana B. (Minnetonka, MN)

Applicant: 4C Medical Technologies, Inc. (Maple Grove, MN)

Family ID: 72747629

Appl. No.: 19/024389

Filed: January 16, 2025

Related U.S. Application Data

parent US continuation 17893446 20220823 parent-grant-document US 12232991 child US 19024389

parent US continuation 16848328 20200414 parent-grant-document US 11452628 child US 17893446

us-provisional-application US 62833862 20190415

Publication Classification

Int. Cl.: A61F2/95 (20130101); A61F2/24 (20060101)

U.S. Cl.:

CPC **A61F2/9525** (20200501); **A61F2/243** (20130101); **A61F2/2436** (20130101);
 A61F2/2439 (20130101);

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application claims the benefit of U.S. Provisional Application Ser. No. 62/833,862, filed Apr. 15, 2019 and entitled LOADING SYSTEMS FOR COLLAPSIBLE PROSTHETIC HEART VALVE DEVICES AND METHODS THEREOF, the entire contents of which are hereby incorporated by reference.

STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT
[0002] Not Applicable

BACKGROUND OF THE INVENTION

Field of the Invention

[0003] The invention relates to devices, systems and features for loading of stents including but not limited to prosthetic heart valve devices into delivery catheters.

Description of the Related Art

[0004] The human heart comprises four chambers and four heart valves that assist in the forward (antegrade) flow of blood through the heart. The chambers include the left atrium, left ventricle, right atrium and right ventricle. The four heart valves include the mitral valve, the tricuspid valve, the aortic valve and the pulmonary valve. See generally FIG. 1.

[0005] The mitral valve is located between the left atrium and left ventricle and helps control the flow of blood from the left atrium to the left ventricle by acting as a one-way valve to prevent backflow into the left atrium. Similarly, the tricuspid valve is located between the right atrium and the right ventricle, while the aortic valve and the pulmonary valve are semilunar valves located in arteries flowing blood away from the heart. The valves are all one-way valves, with leaflets that open to allow forward (antegrade) blood flow. The normally functioning valve leaflets close under the pressure exerted by reverse blood to prevent backflow (retrograde) of the blood into the chamber it just flowed out of. For example, the mitral valve when working properly provides a one-way valving between the left atrium and the left ventricle. opening to allow antegrade flow from the left atrium to the left ventricle and closing to prevent retrograde flow from the left ventricle into the left atrium. This retrograde flow, when present, is known as mitral regurgitation or mitral valve regurgitation.

[0006] FIG. 2 illustrates the relationship between the left atrium, annulus, chordae tendineae and the left ventricle relative to the mitral valve leaflets. As is shown, the upper surface of the annulus forms at least a portion of the floor or lower surface of the left atrial chamber, so that for purposes of description herein, the upper surface of the annulus is defined as marking the lower boundary of the left atrial chamber.

[0007] Native heart valves may be, or become, dysfunctional for a variety of reasons and/or conditions including but not limited to disease, trauma, congenital malformations, and aging. These types of conditions may cause the valve structure to fail to close properly resulting in regurgitant retrograde flow of blood from the left ventricle to the left atrium in the case of a mitral valve failure. FIG. 3 illustrates regurgitant blood flow with an exemplary dysfunctional mitral valve.

[0008] Mitral valve regurgitation is a specific problem resulting from a dysfunctional mitral valve that allows at least some retrograde blood flow back into the left atrium from the right atrium. In some cases, the dysfunction results from mitral valve leaflet(s) that prolapse up into the left atrial chamber, i.e., above the upper surface of the annulus instead of connecting or coapting to block

retrograde flow. This backflow of blood places a burden on the left ventricle with a volume load that may lead to a series of left ventricular compensatory adaptations and adjustments, including remodeling of the ventricular chamber size and shape, that vary considerably during the prolonged clinical course of mitral regurgitation.

[0009] Regurgitation can be a problem with native heart valves generally, including tricuspid, aortic and pulmonary valves as well as mitral valves.

[0010] Native heart valves generally, e.g., mitral valves, therefore, may require functional repair and/or assistance, including a partial or complete replacement. Such intervention may take several forms including open heart surgery and open heart implantation of a replacement heart valve. See e.g., U.S. Pat. No. 4,106,129 (Carpentier), for a procedure that is highly invasive, fraught with patient risks, and requiring not only an extended hospitalization but also a highly painful recovery period.

[0011] Less invasive methods and devices for replacing a dysfunctional heart valve are also known and involve percutaneous access and catheter-facilitated delivery of the replacement valve. Most of these solutions involve a replacement heart valve attached to a structural support such as a stent, commonly known in the art, or other form of wire network designed to expand upon release from a delivery catheter. See, e.g., U.S. Pat. No. 3,657,744 (Ersek); U.S. Pat. No. 5,411,552 (Andersen). The self-expansion variants of the supporting stent assist in positioning the valve, and holding the expanded device in position, within the subject heart chamber or vessel. This self-expanded form also presents problems when, as is often the case, the device is not properly positioned in the first positioning attempt and, therefore, must be recaptured and positionally adjusted. This recapturing process in the case of a fully, or even partially, expanded device requires re-collapsing the device to a point that allows the operator to retract the collapsed device back into a delivery sheath or catheter, adjust the inbound position for the device and then re-expand to the proper position by redeploying the positionally-adjusted device distally out of the delivery sheath or catheter.

Collapsing the already expanded device is difficult because the expanded stent or wire network is generally designed to achieve the expanded state which also resists contractive or collapsing forces.

[0012] Besides the open heart surgical approach discussed above, gaining access to the valve of interest is achieved percutaneously via one of at least the following known access routes: transapical; transfemoral; transatrial; and transseptal delivery techniques.

[0013] Generally, the art is focused on systems and methods that, using one of the above-described known access routes, allow a partial delivery of the collapsed valve device, wherein one end of the device is released from a delivery sheath or catheter and expanded for an initial positioning followed by full release and expansion when proper positioning is achieved. See, e.g., U.S. Pat. Nos. 8,852,271 (Murray, III); U.S. Pat. No. 8,747,459 (Nguyen); U.S. Pat. No. 8,814,931 (Wang); U.S. Pat. No. 9,402,720 (Richter); U.S. Pat. No. 8,986,372 (Murray, III); and U.S. Pat. No. 9,277,991 (Salahieh); and U.S. Pat. Pub. Nos. 2015/0272731 (Racchini); and 2016/0235531 (Ciobanu).

[0014] In addition, all known prosthetic heart valves are intended for full replacement of the native heart valve. Therefore, these replacement heart valves, and/or anchoring or tethering structures, physically extend out of the left atrial chamber, in the case of mitral valves, and engage the inner annulus and/or valve leaflets, in many cases pinning the native leaflets against the walls of the inner annulus, thereby permanently eliminating all remaining functionality of the native valve and making the patient completely reliant on the replacement valve. In other cases, the anchoring structures extend into the left ventricle and may anchor into the left ventricle wall tissue and/or the sub-annular surface at the top of the left ventricle. Others may comprise a presence in, or engagement with, a pulmonary artery.

[0015] Obviously, there will be cases when native valve has lost virtually complete functionality before the interventional implantation procedure. In this case the preferred solution will comprise an implant that does not extend outside of, e.g., the left atrium, and that functions to completely

replace the native valve function. However, in many other cases, the native valve remains functional to an extent and may, or may not, continue to lose functionality after the implantation procedure. A preferred solution in this case comprises delivery and implantation of a valve device that will function both as a supplemental or augmentation valve without damaging the native leaflets in order to retain native valve leaflet functionality as long as present, while also being fully capable of replacing the native function of a valve that slowly loses most or all of its functionality post-implantation of the prosthetic valve.

[0016] Known delivery systems for prosthetic heart valve devices can be improved by at least reducing loading forces and minimizing air introduction into the system during loading of the prosthetic heart valve device into a delivery catheter for collapsed transport through the patient's vasculature through the delivery catheter lumen to the subject heart chamber, e.g., atrium or ventricle. Once the collapsed prosthetic heart valve device is translated distally out of the delivery catheter lumen, it may expand from the collapsed transport configuration to an expanded working configuration(s).

[0017] Various embodiments of the several inventions disclosed herein address these, inter alia, issues.

Description

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

[0018] FIG. 1 illustrates certain features of the heart in cross-section.

[0019] FIG. 2 illustrates a cross-sectional perspective view of the left side of the heart.

[0020] FIG. 3 illustrates a cross-sectional view of the heart showing retrograde blood flow resulting from mitral valve regurgitation compared with normal blood flow.

[0021] FIG. 4 illustrates a perspective view of one embodiment of the present invention.

[0022] FIG. 5 illustrates a side view of one embodiment of the present invention.

[0023] FIG. 6A illustrates an exemplary method step for loading a collapsible prosthetic heart valve device into the lumen of a delivery catheter according to embodiments of the present invention.

[0024] FIG. 6B illustrates an exemplary method step for loading a collapsible prosthetic heart valve device into the lumen of a delivery catheter according to embodiments of the present invention.

[0025] FIG. 6C illustrates an exemplary method step for loading a collapsible prosthetic heart valve device into the lumen of a delivery catheter according to embodiments of the present invention.

[0026] FIG. 6D illustrates an exemplary method step for loading a collapsible prosthetic heart valve device into the lumen of a delivery catheter according to embodiments of the present invention.

[0027] FIG. 6E illustrates an exemplary method step for loading a collapsible prosthetic heart valve device into the lumen of a delivery catheter according to embodiments of the present invention.

[0028] FIG. 7A illustrates a perspective view of one embodiment of the present invention.

[0029] FIG. 7B illustrates a cross-sectional view cutaway view of one embodiment of the present invention.

[0030] FIG. 8 illustrates an exploded view of one embodiment of the present invention.

[0031] FIG. 9A illustrates an exemplary method step for loading a collapsible prosthetic heart valve device into the lumen of a delivery catheter according to embodiments of the present invention.

[0032] FIG. 9B illustrates an exemplary method step for loading a collapsible prosthetic heart valve device into the lumen of a delivery catheter according to embodiments of the present invention.

[0033] FIG. 9C illustrates an exemplary method step for loading a collapsible prosthetic heart valve device into the lumen of a delivery catheter according to embodiments of the present invention.

[0034] FIG. 9D illustrates an exemplary method step for loading a collapsible prosthetic heart valve device into the lumen of a delivery catheter according to embodiments of the present invention.

invention.

[0035] FIG. **9E** illustrates an exemplary method step for loading a collapsible prosthetic heart valve device into the lumen of a delivery catheter according to embodiments of the present invention.

[0036] FIG. **9F** illustrates an exemplary method step for loading a collapsible prosthetic heart valve device into the lumen of a delivery catheter according to embodiments of the present invention.

[0037] FIG. **10** illustrates a perspective view of one embodiment of the present invention.

[0038] FIG. **11** illustrates an exploded view of one embodiment of the present invention.

[0039] FIG. **12A** illustrates an exemplary method step for loading a collapsible prosthetic heart valve device into the lumen of a delivery catheter according to embodiments of the present invention.

[0040] FIG. **12B** illustrates an exemplary method step for loading a collapsible prosthetic heart valve device into the lumen of a delivery catheter according to embodiments of the present invention.

[0041] FIG. **12C** illustrates an exemplary method step for loading a collapsible prosthetic heart valve device into the lumen of a delivery catheter according to embodiments of the present invention.

[0042] FIG. **12D** illustrates an exemplary method step for loading a collapsible prosthetic heart valve device into the lumen of a delivery catheter according to embodiments of the present invention.

[0043] FIG. **12E** illustrates an exemplary method step for loading a collapsible prosthetic heart valve device into the lumen of a delivery catheter according to embodiments of the present invention.

[0044] FIG. **12F** illustrates an exemplary method step for loading a collapsible prosthetic heart valve device into the lumen of a delivery catheter according to embodiments of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

[0045] Generally, various embodiments of the present invention are directed to devices and methods for optimizing loading of a prosthetic heart valve device comprising a collapsible and expandable frame, e.g., a stent or other collapsible and expandable device into a delivery catheter lumen. The embodiments described herein optimize delivery of a prosthetic heart valve device by (1) reducing loading forces during collapsing and translating through the delivery catheter lumen; and/or (2) by reducing, minimizing or eliminating air introduction into the system comprising the prosthetic heart valve device and/or the lumen of the delivery catheter.

[0046] FIGS. **4** and **5** illustrate one embodiment of the present invention comprising a container, e.g., a bag that may be scalable, at least partially filled with a biocompatible fluid such as saline or other fluid. FIG. **4** shows one embodiment of the basic structure while FIG. **5** provides a method **200** with method steps illustrated in combination with the structure of FIG. **4**.

[0047] Thus, turning to FIGS. **4** and **5**, one embodiment of a loading system **100** is illustrated.

Loading system **100** comprises a resealable container **102**, e.g., a bag, that is adapted to hold a biocompatible fluid **104** therein, e.g., saline within an interior defined by the container **102**.

Container may comprise a resealable opening **103** and a valved line or flush tube **105** to, inter alia, admit fluid into the container **102**. A funnel **106** is disposed within the interior of the container, e.g., bag, **102** and immersed within the biocompatible fluid **104** held therein. Funnel **106**, as known in the art, comprises an upper opening **110** that tapers down through a conical portion **112**, terminating at a cylindrical portion **114** opposite the upper opening **114**, wherein the upper opening **110** comprises a larger radius than the cylindrical portion **114**.

[0048] The container **102** further comprises an access opening **108** into the interior of the container **102**. This access opening **108** may be engaged by the distal cylindrical and/or conical tube portion(s) **110**, **112** of the funnel **106**, wherein the interconnection between the funnel **106** and the container **102** is generally sealed or at least partially water tight, to prevent fluid egress therefrom.

Still more alternatively, the proximal end of a delivery catheter **120** may be disposed within the interior of the container **102**, engaging the cylindrical portion **114** of funnel and immersed within the biocompatible fluid, wherein the interconnection between the proximal end of the delivery catheter **120** and the container **102** and/or funnel **106** is adapted to prevent substantial loss of fluid **104** when present.

[0049] Alternatively, the access opening **108** into the container's interior may comprise a self-sealing material that may be punctured by either the cylindrical portion **114** or conical portion **112** of the funnel **106** or by the proximal end of the catheter **120**, but self-seals to prevent fluid loss after the puncture is achieved. A valve as shown in FIG. 7B may also be used.

[0050] Accordingly, either the cylindrical portion **114** or conical portion **112** of the funnel **106** may extend outwardly from the container **102** through an access opening **108**, or the proximal end of the delivery catheter **120** may extend into the interior of the container **102** to connect with the cylindrical portion **114** of the funnel **106**. What is required in any case is a fluid connection between the cylindrical portion **112** or conical portion **112** of the funnel **106** with the proximal end of the delivery catheter.

[0051] As shown, an expanded and collapsible prosthetic heart valve device **150** is placed into the container **102** through the resealable opening **103**, placed into the fluid-filled interior of the container **102**, positioned in the upper opening **110** of funnel **106** and pressed downward into the funnel's conical portion **112**, thereby collapsing the heart valve device **150** in a manner that is repeatable and predictable with even distribution of loading forces around the collapsing frame **152**, e.g., stent or equivalent as shown, of device **150**. This prevents highly undesirable stressing of certain regions or elements of the frame **152** of the prosthetic heart valve device **150**, including in the case of a stent, individual cells and/or struts comprising the outer collapsible frame **152**.

[0052] As shown, in some embodiments an inner valve support **154**, supporting prosthetic valve leaflets therein (leaflets not shown but as well-known to the skilled artisan) that is also a collapsible and expandable structure, may extend radially within the interior of the prosthetic heart valve device's outer frame **152**. As shown, translation of the device **150** into the funnel also functions to collapse the inner valve support in a predictable, repeatable and evenly distributed loading force manner. Ultimately the device **150** is predictably and repeatably collapsed in a controlled manner until device **150** is loaded into the lumen of the delivery catheter **120** that is connected with container **102**.

[0053] In addition to the reduction and/or evenly distributed, and predictably distributed, loading forces described above, this embodiment eliminates air introduction into the system, e.g., the prosthetic heart valve device **150** and the lumen of the delivery catheter, by immersion into the biocompatible fluid **104**. Once immersed into the fluid **104**, no air is present at the funnel **106**. only fluid **104** and the collapsing device **150** may enter the delivery catheter lumen.

[0054] As shown, certain embodiments of the container **102** may comprise a bag that comprises a seal or resealable opening **103** midway along its length to provide a region that is completely filled with fluid **104** and within which the expanded device **150** is completely immersed. Tipping the container **102**, or bag, upright so that the access opening **108** is at the bottom side results in any air rising to the top of the bag or container **102**, with the fluid **104** and prosthetic heart valve device **150** being completely immersed. From there, controlled collapsing of the immersed heart valve device **150** as described above is achieved into the cylindrical portion **114** of the funnel **106** and then the fully collapsed device **150** may be translated distally into the lumen of the delivery catheter **120** toward the subject heart chamber.

[0055] The connection of the container **102** and/or funnel **106** with the delivery catheter **120** may remain in place during translation of the collapsed device **150** or the delivery catheter **120** may be disconnected from the container **102** and/or funnel **106** after collapsed translation of the device **150** into the lumen of the delivery catheter **120**.

[0056] FIGS. 6A-6E provide illustration of one exemplary method using the embodiments

described above. Thus, as shown in FIG. 6A at step 202, the container, in this case a bag, **102** is provided in an upright position, with the access opening **108** at the bottom of the container **102**. A flush tube or line **105**, in fluid connection with an external fluid reservoir (not shown), is connected and that allows controlled fluid **104** flow therethrough into the container's interior by, e.g., a stopcock as shown. Alternatively, the container **102** may simply be filled through the scalable opening **103**.

[0057] In FIG. 6B at step 204, the expanded prosthetic stent **150** and any related delivery tools, e.g., a push and/or pull wire(s) are introduced into the biocompatible fluid **104**, e.g., through the sealable opening **103**. The bag or container **102** may either be pre-filled with biocompatible fluid **104**, e.g., saline, before introducing the expanded device **150** into the container **102** or may be filled with biocompatible fluid **104** after the device **150** is introduced into the container **102**. FIG. 6C illustrates at step 206, introducing the device **150** into the container with subsequent filling of biocompatible fluid.

[0058] FIG. 6D at step 208 then shows the collapsing of the device **150** into the catheter lumen via the controlled collapsing through the funnel **106** structure as described above. The device **150** may be pulled from a distal end of the catheter lumen using a detachable wire (pull wire) connected to the prosthetic heart valve device **150** or may be pushed into the proximal end of lumen of the catheter **120**. If a detachable pull wire is used, it may be detached and removed from the lumen of the catheter **120** when the collapsed prosthetic device **150** is loaded within the delivery catheter's lumen, or pull wire may be left in place.

[0059] FIG. 6E shows step 210, the detachment of the container **120** and funnel **106** from the delivery catheter **120** after the collapsed device **150** is loaded within the delivery catheter **120**.

[0060] Turning now to FIGS. 7A-9F, another embodiment for a loading system for a collapsible prosthetic heart valve device is provided. The basic functionality behind this device is similar to that discussed above in that a funnel-type device is used to provide evenly distributed loading forces with great predictability to the collapsing prosthetic heart valve device and wherein the collapsing is done while the prosthetic heart valve device is immersed in biocompatible fluid and wherein the collapsed device is loaded into the lumen of a delivery catheter.

[0061] Here, as shown in the Figures, the expanded prosthetic heart valve device **150** is placed into the funnel **106'** and may be connected with a pull wire extending through the lumen of the delivery catheter **120** and extending from the proximal and distal ends of the delivery catheter **120** to allow engagement of the pull wire and the device **150** at a proximal end of the delivery catheter and enabling of a pulling force engagement at the distal end of the delivery catheter **120** to urge the device **150** into and through the lumen of the delivery catheter **120**. A valve may be provided in the cylindrical portion **114'** or conical portion **112'** of the funnel **106'** as seen in FIG. 7B to help ensure fluid sealing before and during the loading process.

[0062] Also as shown, the proximal end of delivery catheter **120** may be attached or engaged with the cylindrical portion **114'** or conical portion **112'** of the funnel **106'** to create a fluid communication between the funnel **106'** and the lumen of the delivery catheter **120**. These steps are shown in FIGS. 9A (step 302) and 9B (step 304).

[0063] As shown in FIG. 9C and step 306, once the expanded prosthetic heart valve device **150** is placed in the funnel **106'** as shown, a connecting top **160** is connected with, and covering, the upper opening **110'** of the funnel **106** to create a substantially watertight interior. A fluid infusion line **105** may be in fluid communication with the substantially watertight interior as shown for infusing biocompatible fluid **104** such as saline into the interior to immerse the device **150** therein once the connecting top **160** is secured to the funnel **106'**. The securement of the connecting top **160** to the upper opening **110'** of the funnel **106'** may be done by several known methods and mechanisms, including but not limited to screw threads.

[0064] As shown in FIG. 9D and step 308, once the substantially watertight interior is defined and created, and at least partially filled with biocompatible fluid **104** via fluid supply line **105**, a fluid

communication is created between the watertight interior and the lumen of the delivery catheter **120**.

[0065] Now, as in FIG. **9E** and step **310**, the collapsing of the immersed prosthetic heart valve device **150** may be initiated by pulling distally on pull wire. Next, as in FIG. **9F** and step **312**, when the collapsed device **150** has reached a predetermined position within the lumen of the delivery catheter **120**, the funnel **106'** and catheter **120** may be disengaged or disconnected. Moreover, at that point pull wire may be disconnected and removed from the lumen of delivery catheter **120**, or pull wire may remain attached.

[0066] Turning now to an alternate embodiment of a loading system as illustrated in FIGS. **10-12F**. A funnel **106''** is provided in detachable engagement or connection with a delivery catheter **120**, wherein a fluid connection is created between the funnel **106''** and the lumen of the delivery catheter **120**. As in all previous embodiments, the lumen of the cylindrical or conical portion of the funnel **106''** is substantially axially aligned with the lumen of the delivery catheter **120** when loading the prosthetic heart device **150** therein.

[0067] In this embodiment, as with various previously described embodiments, the delivery catheter **120** and the funnel **106''** are connected or engaged as in FIG. **12A** and step **402** and, as in FIG. **12B** and step **404**, the prosthetic heart valve device **150** is attached using, e.g., a pull wire threaded through the lumen of the delivery catheter **120** and adapted to hold the expanded prosthetic heart valve device **150** in position within the funnel **106''** as well as to provide a distal force that forces the collapsing of the prosthetic heart valve device **150** into the lumen of the funnel's cylindrical or conical portion and, ultimately, into the lumen of the delivery catheter **120**.

[0068] As shown in FIG. **12C** and step **406**, once the expanded prosthetic heart valve device **150** is positioned in the funnel **106''** the funnel may be attached magnetically to a base or cap **180** comprising an interior sized, shaped and adapted to receive at least a portion of the expanded prosthetic device **150** therein. As also shown in FIG. **10**, the top portion of the expanded device **150** is disposed within the base or cap **180**. Moreover, a series of ribs or supports **182** may be provided within base or cap **180** to support the expanded device, wherein the ribs or supports **182** are at least partially immersed in biocompatible fluid. In other embodiments, the ribs may be omitted. The cylindrical or conical portion of the funnel, as in all prior embodiments discussed herein, may comprise a valve to prevent air and/or fluid moving into the lumen of the delivery catheter **120**.

[0069] Turning to FIG. **12D** and step **408**, once the funnel **106''** and the base or cap **180** are magnetically coupled together a substantially watertight sealed interior is defined and created thereby. A fluid infusion line may be in fluid communication with the base or cap **180**, or with the funnel, to provide controlled infusion of biocompatible fluid into the watertight sealed interior and to fully, or at least partially, immerse the expanded device **150**, or the base or cap **180** may simply be manually filled with fluid **104**. At this point, as in FIG. **12E** and step **410**, the collapsing of the prosthetic heart valve device **150** may be initiated by pulling distally on the pull wire, collapsing the device **150** as described above and including in some cases the inner valve support, into the funnel lumen and ultimately into the lumen of the delivery catheter **120**, past the valve of the funnel lumen (when present).

[0070] When the collapsed prosthetic heart valve device **150** is at a predetermined position within the lumen of the delivery catheter **120** is "loaded" therein and the catheter **120** and the funnel **106''** may be disconnected. This is shown in FIG. **12F** and step **412**.

[0071] In all embodiments, when the collapsed prosthetic heart valve device is "loaded" within the lumen of the delivery catheter, it may be delivered via the delivery catheter through the patient's vasculature to the heart chamber of interest using any acceptable access route and/or delivery technique, including but not limited to: transapical; transfemoral; transatrial; and transseptal delivery techniques

[0072] The description of the invention and its applications as set forth herein is illustrative and is not intended to limit the scope of the invention. Features of various embodiments may be combined

with other embodiments within the contemplation of this invention. Variations and modifications of the embodiments disclosed herein are possible, and practical alternatives to and equivalents of the various elements of the embodiments would be understood to those of ordinary skill in the art upon study of this patent document. These and other variations and modifications of the embodiments disclosed herein may be made without departing from the scope and spirit of the invention.

Claims

1-19. (canceled)

20. A loading system for an expandable and collapsible prosthetic heart valve device, comprising: a loading funnel including a conical portion and a cylindrical portion, the loading funnel being configured to hold the prosthetic heart valve device therein; a receptacle configured to be coupled to the loading funnel to define a watertight interior; a fluid infusion line, wherein, in operation, biocompatible fluid is transmitted to the watertight interior through the fluid infusion line to fill the watertight interior with biocompatible fluid to immerse the prosthetic heart valve device and to eliminate air from the watertight interior; a delivery catheter configured to be removably engaged with the loading funnel to position a lumen of the delivery catheter in fluid communication with a lumen of the loading funnel; and a pull wire configured to be removably connected with the prosthetic heart valve device, wherein, in operation, the pull wire extends through the lumen of the delivery catheter and beyond a distal end of the delivery catheter; wherein: the pull wire is configured to pull the prosthetic heart valve device through the loading funnel and into the delivery catheter.

21. The loading system of claim 20 wherein the loading funnel is configured to collapse the prosthetic heart valve device when the prosthetic heart valve device is pulled through the loading funnel.

22. The loading system of claim 20 further comprising the prosthetic heart valve device disposed in the loading funnel.

23. The loading system of claim 22 wherein the prosthetic heart valve device comprises an outer stent frame and an inner valve support disposed within the outer stent frame, wherein the outer stent frame surrounds the inner valve support and the loading system is configured to collapse both the outer stent frame and the inner valve support.

24. The loading system of claim 20 wherein the receptacle includes a self-sealing access opening.

25. The loading system of claim 20 wherein the loading funnel includes a self-sealing access opening.

26. The loading system of claim 20 wherein the cylindrical portion of the loading funnel includes a valve to prevent air and fluid from moving into the lumen of the delivery catheter.

27. The loading system of claim 20 wherein the conical portion of the loading funnel includes a valve to prevent air and fluid from moving into the lumen of the delivery catheter.

28. The loading system of claim 20 wherein the delivery catheter is configured to be removably engaged with the conical portion of the loading funnel.

29. The loading system of claim 20 wherein the delivery catheter is configured to be removably engaged with the cylindrical portion of the loading funnel.

30. The loading system of claim 20 wherein the receptacle is a bag including a resealable opening.

31. The loading system of claim 30 wherein the fluid infusion line is in fluid communication with the bag.

32. The loading system of claim 20 wherein the receptacle is configured to be removably coupled to the loading funnel.

33. The loading system of claim 32 wherein screw threads removably couple the receptacle to the loading funnel.

34. The loading system of claim 32 wherein the fluid infusion line is in fluid communication with

the receptacle.

35. The loading system of claim 32 wherein the receptacle includes one or more magnets and the receptacle is configured to be magnetically coupled to the funnel.

36. The loading system of claim 35 wherein the receptacle includes ribs for supporting the prosthetic heart valve device in the receptacle.

37. The loading system of claim 35 wherein the fluid infusion line is in fluid communication with the receptacle.

38. The loading system of claim 35 wherein the fluid infusion line is in fluid communication with the funnel.
