

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent	12393104
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Liang; Lei

---

### Electronic device and camera module thereof having a driver that drives a slider to move, a lens component rotating with movement of the slider

---

#### Abstract

An electronic device and a camera module thereof are provided. The camera module includes a lens component, a module bracket, a driving component on the module bracket, and at least three connection components. The at least three connection components are arranged around the periphery of the lens component. Each connection component includes a first fitting portion provided on the module bracket, a second fitting portion provided on the lens component, and a first sliding portion and a second sliding portion connected to each other. The first sliding portion is slidably fitted with the first fitting portion, and the second sliding portion is slidably fitted with the second fitting portion. Extension directions of the first fitting portion and the second fitting portion are both different from the direction of the optical axis of the lens component.

---

<b>Inventors:</b>	<b>Liang; Lei (Dongguan, CN)</b>
<b>Applicant:</b>	<b>VIVO MOBILE COMMUNICATION CO., LTD. (Dongguan, CN)</b>
<b>Family ID:</b>	<b>1000008764421</b>
<b>Assignee:</b>	<b>VIVO MOBILE COMMUNICATION CO., LTD. (Dongguan, CN)</b>
<b>Appl. No.:</b>	<b>18/214516</b>
<b>Filed:</b>	<b>June 26, 2023</b>

#### Prior Publication Data

<b>Document Identifier</b>	<b>Publication Date</b>
US 20230341751 A1	Oct. 26, 2023

#### Foreign Application Priority Data

CN	202011585976.1	Dec. 28, 2020
----	----------------	---------------

## Related U.S. Application Data

continuation parent-doc WO PCT/CN2021/141067 20211224 PENDING child-doc US 18214516

---

## Publication Classification

**Int. Cl.:** H04N5/335 (20110101); G03B17/12 (20210101); H04N23/55 (20230101)

**U.S. Cl.:**

**CPC** G03B17/12 (20130101); H04N23/55 (20230101);

## Field of Classification Search

**CPC:** G03B (17/12)

---

## References Cited

### U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4359256	12/1981	Gallusser	439/314	H01R 13/623
10025164	12/2017	Weidner	N/A	G03B 17/12
11050939	12/2020	Sasaki et al.	N/A	N/A
12292619	12/2024	Liu	N/A	G06F 1/163
2015/0331221	12/2014	Koiwai	359/701	G02B 7/10
2017/0139225	12/2016	Lim	N/A	N/A
2024/0111126	12/2023	Liu	N/A	G02B 7/102
2024/0179388	12/2023	Chen	N/A	H04N 23/57

### FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
206193372	12/2016	CN	N/A
110673656	12/2019	CN	N/A
111355872	12/2019	CN	N/A
111367036	12/2019	CN	N/A
111565264	12/2019	CN	N/A
111654612	12/2019	CN	N/A
211429403	12/2019	CN	N/A
111988515	12/2019	CN	N/A
112702494	12/2020	CN	N/A

## OTHER PUBLICATIONS

International Search Report issued in corresponding International Application No.

PCT/CN2021/141067, mailed Jan. 27, 2022, 7 pages. cited by applicant

First Office Action issued in corresponding CN Patent Application No. 202011585976.1, dated Jan. 11, 2022, 5 pages. cited by applicant

---

*Primary Examiner:* Vieaux; Gary C

## Background/Summary

(1) The present application is a continuation of International Application No. PCT/CN2021/141067, filed on Dec. 24, 2021, which claims priority to Chinese Patent Application No. 202011585976.1, filed on Dec. 28, 2020. The entire contents of each of the above-referenced applications are expressly incorporated herein by reference.

### TECHNICAL FIELD

(1) The present application belongs to the technical field of communication devices, and specifically relates to an electronic device and a camera module thereof.

### BACKGROUND

(2) With the advancement of science and technology, electronic devices such as mobile phones play an important role in people's work and life, and electronic devices are usually equipped with cameras to facilitate users to shoot images. When a user shoots in a hand-held manner, a captured image or video is prone to be blurred due to shaking of the user. In the related art, a camera module is usually equipped with an optical anti-shake component to improve the clarity of a captured image and video. However, the structure of the current optical anti-shake component is relatively complicated, and the assembly and design are difficult, resulting in high costs of electronic devices.

### SUMMARY

(3) The present application discloses an electronic device and a camera module, so that the camera module has an anti-shake effect, the structure is relatively simple, and costs are low.

(4) The embodiments of the present application are implemented as follows:

(5) In a first aspect, the embodiment of the present application discloses a camera module, which includes a lens component, a module bracket, a driving component, and at least three connection components, where the at least three connection components are arranged around the periphery of the lens component, each of the connection components includes a slider, a first fitting portion, and a second fitting portion, the slider includes a first sliding portion and a second sliding portion connected to each other, the first sliding portion and the first fitting portion are slidably fitted with each other, the second sliding portion and the second fitting portion are slidably fitted with each other, the first fitting portion is arranged on the module bracket, the second fitting portion is arranged on the lens component, and a preset angle is formed between extending directions of the first fitting portion and the second fitting portion, and the extending directions of the first fitting portion and the second fitting portion are both inclined relative to a direction of an optical axis of the lens component, the driving component is arranged on the module bracket, and the driving component is connected to the slider, the driver is used to drive the corresponding slider to move, and an optical axis of the lens component rotates relative to the module bracket along with movement of the slider.

(6) In a second aspect, the embodiment of the present application discloses an electronic device, including the above-mentioned camera module.

(7) An embodiment of the present application provides a camera module. The camera module includes a lens component, a module bracket, a driving component, and at least three connection components. Each connection component includes a slider, a first fitting portion, and a second fitting portion. Both the first fitting portion and the second fitting portion are slidably connected to the slider, the first fitting portion is arranged on the module bracket, and the second fitting portion is arranged on the lens component, so that the lens component can connect to the module bracket through the at least three connection components. The driving component is connected to the slider so as to drive the slider to move. There is an acute angle between extension directions of the first

fitting portion and the second fitting portion, and both the extension directions are inclined relative to a direction of an optical axis of the lens component. By making the driving component drive the slider to move, the optical axis of the lens component can rotate relative to the module bracket. In the process of shooting with the above-mentioned camera module, if the camera module shakes due to user shaking, the slider can be driven to move through the driving component, so that the camera produces shaking opposite to the shaking, so as to compensate for relative rotation between the optical axis of the camera module and a viewfinder area caused by the user shaking, so that a relative position or relative angle between the viewfinder area of the camera module and the optical axis of the lens component remains unchanged, which makes the camera module have an anti-shake function. Moreover, the structure for providing the anti-shake function in the above-mentioned camera component is relatively simple, and the difficulty of assembly and design is relatively low, thereby reducing the costs of electronic devices.

---

## Description

### BRIEF DESCRIPTION OF DRAWINGS

- (1) The accompanying drawings described herein are intended to provide a further understanding of the present application, and constitute a portion of the present application. Example embodiments of the present application and descriptions thereof are intended to describe the present application, and do not constitute limitations on the present application. In the accompanying drawings:
- (2) FIG. 1 is a schematic structural diagram of a camera module according to an embodiment of the present application;
- (3) FIG. 2 is a schematic diagram of a camera module in another direction according to an embodiment of the present application;
- (4) FIG. 3 is an exploded schematic view of a camera module according to an embodiment of the present application; and
- (5) FIG. 4 is a schematic diagram of a sliding component in a camera module according to an embodiment of the present application.

### DETAILED DESCRIPTION

- (6) To make the objectives, technical solutions, and advantages of the present application clearer, the following clearly describes the technical solutions of the present application with reference to the specific embodiments of the present application and the corresponding accompanying drawings. Apparently, the described embodiments are merely some rather than all of embodiments of the present application. All other embodiments obtained by a person of ordinary skill in the art based on embodiments of the present application without creative efforts shall fall within the protection scope of the present application.
- (7) The technical solutions disclosed in embodiments of the present application are described in detail below with reference to the accompanying drawings.
- (8) As shown in FIG. 1 to FIG. 4, the present application discloses a camera module, which includes a lens component **100**, a module bracket **200**, a driving component **320**, and at least three connection components.
- (9) The lens component **100** may include at least one lens, and the light outside the camera module is incident into the camera module through the lens component **100**. The module bracket **200** is the installation basis of the lens module, and the module bracket **200** can provide a protection function for the lens component **100**. The module bracket **200** can be made of materials such as metal or plastic, and there are various shapes and specific structures. For example, the module bracket **200** can be a cylindrical structure, and the module bracket **200** is arranged around the outside of the lens component **100**, and ensures that the bottom **210** and at least a part of a side **220** of the lens

component **100** can be surrounded by the module bracket **200**, so as to improve the service life of the camera module.

(10) At least three connection components are arranged around the periphery of the lens component **100**, and the lens component **100** and the module bracket **200** are connected to each other through the connection components. Each connection component includes a slider **310**, a first fitting portion **221**, and a second fitting portion **330**, and the slider **310** further includes a first sliding portion **311** and a second sliding portion **312**, and the first sliding portion **311** and the second sliding portion **312** are connected to each other, the first sliding portion **311** and the first fitting portion **221** are slidably fitted with each other, the second sliding portion **312** and the second fitting portion **330** are slidably fitted with each other, the first fitting portion **221** is arranged on the module bracket **200**, and the second fitting portion **330** is disposed on the lens component **100**, so that the lens component **100** and the module bracket **200** can be connected to each other through the connection component. Besides, as mentioned above, the number of connection components is at least three, at least three connection components are arranged around the periphery of the lens component **100**, and the slider **310**, the first fitting portion **221**, and the second fitting portion **330** in each connection component are all in the above-mentioned fitting relationship, which can ensure that a reliable connection can be formed between the lens component **100** and the module bracket **200**.

(11) In some embodiments, the shapes of the first sliding portion **311** and the second sliding portion **312** may be the same or different, and may form a fixed connection relationship or a movable connection relationship, which is not limited herein. The structural forms of the first fitting portion **221** and the second fitting portion **330** can be the same or different, and can be structures such as chutes, slide bars, or slide rails, as long as the first fitting portion **221** and the second fitting portion **330** can provide a sliding guide function for the slider **310** so as to form a sliding fitting relationship with the slider. In some embodiments, at least three connection components have a same structure, so as to reduce the difficulty of spare parts and assembling, and also improve the fitting stability between the connection components.

(12) In the connection component, a preset angle  $\alpha$  is formed between the extension directions of the first fitting portion **221** and the second fitting portion **330**, and  $0^\circ < \alpha < 90^\circ$ , that is, the first fitting portion **221** and the second fitting portion **330** are neither parallel nor perpendicular, and a specific size of the preset included angle can be determined according to actual requirements such as a preset adjustment range of the lens component **100**. This is not limited herein. Moreover, the extension directions of the first fitting portion **221** and the second fitting portion **330** are both inclined to the direction of the optical axis of the lens component **100**, that is, the extension directions of the first fitting portion **221** and the second fitting portion **330** are not parallel with the direction of the optical axis, so that the extension directions of the first fitting portion **221** and the second fitting portion **330** both have a first component perpendicular to the direction of the optical axis. Besides, since a preset included angle is provided between the extension directions of the first fitting portion **221** and the second fitting portion **330**, the extension direction of at least one of the first fitting portion **221** and the second fitting portion **330** also has a second component parallel to the direction of the optical axis.

(13) The driving component **320** is arranged on the module bracket **200**, and the driving component **320** may be a linear motor, an air cylinder or a hydraulic cylinder or the like. The driving component **320** is connected to the slider **310**. In some embodiments, the driving head of the driving component **320** may be connected to the slider **310**, and the driving component **320** can drive the slider **310** to move accordingly. That is, the driving component **320** can drive the slider **310** connected to the driving component **320** to move. Based on that the extension directions of the first fitting portion **221** and the second fitting portion **330** satisfy the above condition, the slider **310** can always be slidably fitted with the first fitting portion **221** and the second fitting portion **330** during the movement process. Furthermore, since the slider **310** can always slide on the first fitting portion **221** and the second fitting portion **330** at the same time, and one of the first fitting portion

**221** and the second fitting portion **330** may not have a component parallel to the direction of the optical axis, a part of the first fitting portion **221** and a part of the second fitting portion **330** that can fit with the slider **310** at the same time have an equal first component perpendicular to the direction of the optical axis. In this way, when the slider moves, movement amounts relative to the lens component **100** and the module bracket **200** perpendicular to the direction of the optical axis are equal.

(14) Moreover, based on the fact that there is a preset included angle between the extension directions of the first fitting portion **221** and the second fitting portion **330**, components that are of the part of the first fitting portion **221** and the part of the second fitting portion **330** that can fit with the slider **310** at the same time and that are parallel to the direction of the optical axis are unequal. Therefore, it can be ensured that with the movement of the slider **310**, the lens component **100** (the part or position connected to the slider **310**) can move relative to the module bracket **200** along the direction of the optical axis, which can make the optical axis of the lens component **100** rotate relative to the module bracket **200**, so that the orientation of the lens component **100** changes.

(15) In some embodiments, both the extension directions of the first fitting portion **221** and the second fitting portion **330** have a second non-zero component parallel to the direction of the optical axis. In another embodiment of the present application, for example, as shown in FIG. 3, the extending direction of the second fitting portion **330** may be perpendicular to the direction of the optical axis, that is, the extension direction of the second fitting portion **330** does not have the second component parallel to the direction of the optical axis. In other words, a value of the second component of the extension direction of the second fitting portion **330** parallel to the direction of the optical axis is zero. This can ensure that the optical axis of the lens component **100** can rotate relative to the module bracket **200**, and can reduce the difficulty of assembling the second fitting portion **330**.

(16) An embodiment of the present application provides a camera module. The camera module includes a lens component **100**, a module bracket **200**, a driving component **320**, and at least three connection components. Each connection component includes a slider **310**, a first fitting portion **221**, and a second fitting portion **330**, the first fitting portion **221** and the second fitting portion **330** are both slidably connected to the slider **310**, the first fitting portion **221** is arranged on the module bracket **200**, and the second fitting portion **330** is arranged on the lens component **100**, so that the lens component **100** can be connected to the module bracket **200** through the at least three connection components. The driving component **320** is connected to the slider **310** to drive the slider **310** to move. There is an acute angle between the extension directions of the first fitting portion **221** and the second fitting portion **330**, and both the extension directions of the first fitting portion **221** and the second fitting portion **330** are inclined relative to the direction of the optical axis of the lens component **100**. By making the driving component **320** drive the slider **310** to move, the optical axis of the lens component **100** can rotate relative to the module bracket **200**. In the process of shooting with the above-mentioned camera module, if the camera module shakes due to user shaking, the slider **310** can be driven to move through the driving component **320**, so that the camera produces shaking opposite to the shaking, so as to compensate for relative rotation between the optical axis of the camera module **100** and a viewfinder area caused by the user shaking, so that a relative position (or relative angle) between the viewfinder area of the camera module and the optical axis of the lens component **100** remains unchanged, which makes the camera module have an anti-shake function. Moreover, the structure for providing the anti-shake function in the above-mentioned camera component is relatively simple, and the difficulty of assembly and design is relatively low, thereby reducing the costs of electronic devices.

(17) In the above-mentioned camera module, the number of connection components is at least three. In some embodiments, the number of driving components **320** can be two. By arranging the two driving components **320** in correspondence with the two sliders **310** respectively, the optical axis of the lens component **100** can basically be driven to rotate in multiple directions relative to

the module bracket **200**. In another embodiment of the present application, the number of driving components **320** may be the same as the number of connection components, and there is a one-to-one correspondence, which can improve the reliability of fitting between the lens component **100** and the module bracket **200**, and can improve the adjustment precision. Besides, the rotation angle range of the optical axis of the lens component **100** relative to the module bracket **200** can be expanded to improve the adjustment ability.

(18) In addition, in the camera module disclosed in the above embodiments, an angle detection device such as a gyroscope that can detect the rotation of the camera module relative to the viewfinder area can be provided, so that during the shooting process, the angle detection device can be used to measure rotation of the optical axis of the lens component **100** relative to the viewfinder area (a living creature or object) is measured. Then, according to the rotation, the corresponding driving component **320** can be made to work, and then the optical axis of the lens component **100** can move along a preset direction by a preset angle, to compensate for the rotation of the camera module, so as to ensure that the relative position between the optical axis of the lens component **100** and the viewfinder area remains basically unchanged.

(19) Since the camera module can usually be used in an electronic device, and devices such as gyroscopes and gravity sensors are standard configurations of electronic devices, with the help of devices such as gyroscopes and gravity sensors in electronic devices, the angle by which the camera module rotates relative to the viewing area is measured. When the technical solution is adopted, on the one hand, the cost of the camera module can be reduced, on the other hand, the overall size of the camera module can also be reduced, and the utilization rate of devices such as gyroscopes and gravity sensors in electronic devices can be improved, to reduce the overall costs to some extent.

(20) For example, the camera module provided in the embodiment of the present application further includes a positioning component, the positioning component is arranged on the lens component **100**, the positioning component fits with the second sliding portion **312**, and the positioning component can be a detachable limiting structure. When the positioning component and the second sliding portion **312** are mutually limited, the second sliding portion **312** cannot move relative to the second fitting portion **330**. Correspondingly, when the positioning component is removed, the second sliding portion **312** can restore the capability of moving relative to the second fitting portion **330**.

(21) The positioning component has a first state and a second state. When the positioning component is in the first state, the second sliding portion **312** is slidably fitted with the second fitting portion **330**, that is, the second fitting portion **330** and the slider **310** are in a released state. In the above state, the driving component **320** drives the slider **310** to move, allowing the optical axis of the lens component **100** to rotate relative to the module bracket **200** with the movement of the slider **310**. In this embodiment, it can be considered that there is no interaction between the positioning component and the second sliding portion **312**, and the movement of the slider **310** and the lens component **100** is the same as that of the above embodiment, and will not be repeated herein.

(22) When the positioning component is in the second state, the second sliding portion **312** is relatively fixed to the second fitting portion **330**, that is, the second sliding portion **312** can be locked on the second fitting portion **330** by means of the positioning component. In this case, the slider **310** and the lens component **100** are relatively fixed, and the slider **310** can drive the lens component **100** to move along the first fitting portion **221**. As mentioned above, the first fitting portion **221** has a component perpendicular to the direction of the optical axis of the lens component **100**. Therefore, when the driving component **320** drives the slider **310** to move along the first fitting portion **221**, the lens component **100** can rotate relative to the module bracket **200** along the direction of the optical axis of the lens component **100**.

(23) In the case of adopting the above technical solution, by changing the state of the positioning

component, the lens component **100** can rotate around its own optical axis. In this case, the orientation of the lens component **100** remains unchanged, and the relative angle between the lens component **100** and the viewing area can be changed. In addition, the optical axis of the lens component **100** can rotate relative to the module bracket **200**, so that the orientation of the lens component **100** can be changed, thereby improving the ability of the camera module to adjust its own orientation, making the camera module more effective in anti-shake, and improving the user experience.

(24) In another embodiment of the present application, both the driving component **320** and the positioning component may include electromagnets, and correspondingly, the slider **310** may include magnetic parts. That is, the driving component **320** can drive the slider **310** to move through the magnetic force, and the positioning component can position the slider **310** on the second fitting portion **330** through the magnetic force. In the case of adopting the above-mentioned embodiment, the driving component **320** and the positioning component can be operated by turning on and off the power, and the driving force of the driving component **320** can be changed by changing the magnitude of the current passing through the driving component **320**, so that the slider **310** moves to the corresponding position. Correspondingly, whether the positioning component fixes the slider **310** on the second fitting portion **330** can be controlled by turning on and off the power. The control process is relatively simple and convenient, and there is no need to design a more complicated mechanical connection. The structure can reduce the difficulty of designing, assembling and controlling the driving component **320** and the positioning component.

(25) In some embodiments, the driving component **320** may include two electromagnets, and the two electromagnets are respectively arranged at the opposite ends of the first fitting portion **221**. When it is necessary to drive the slider **310** to move, the two electromagnets may both apply repulsive force to the slider **310**. Besides, by controlling the magnitude of the magnetic force of the two electromagnets, the slider **310** can be positioned at different positions of the first fitting portion **221**, thereby driving the optical axis of the lens component **100** to rotate in different directions by a corresponding angle.

(26) In another embodiment of the present application, the driving component **320** may include a plurality of electromagnets separated from each other, and the plurality of electromagnets are arranged along the extension direction of the first fitting portion **221**. In a process of controlling the slider **310** to move, the electromagnet located at the end of the first fitting portion **221** can be controlled to apply a repulsive force to the slider **310**, so that the slider **310** moves along the first fitting portion **221**. Besides, by correspondingly controlling the operation of the electromagnet close to the slider **310**, the slider **310** can move to any position of the first fitting portion **221**. Then, by controlling the electromagnets on opposite sides of the slider **310** to attract the opposite ends of the slider **310**, the slider **310** can also be positioned and held at the adjusted position. Therefore, the rotation direction and rotation angle of the optical axis of the lens component **100** relative to the module bracket **200** can be adjusted by controlling the position of the slider **310**.

(27) In some embodiments, the positioning component may include two electromagnets located at opposite ends of the second fitting portion **330** respectively. When the two electromagnets are both energized, they can both apply a repulsive force to the slider **310**, so that the slider **310** is positioned at a certain position on the second fitting portion **330**, and the slider **310** and the second fitting portion **330** remain fixed. When the positioning component is in a power-off state, the slider **310** can slide along the second fitting portion **330** driven by the driving component **320**.

(28) In some alternative embodiments, the positioning component can be arranged at a certain position of the second fitting portion **330**, and the positioning component can apply an adsorption force to the slider **310** when the positioning component is in the energized state, so that the slider **310** is fixed at the second fitting portion **330** due to mutual attraction with the positioning component, and the slider **310** can only move relative to the first fitting portion **221**. Of course, the driving component **320** and the positioning component can also be other electromagnets capable of



achieving the above functions, which will not be listed herein. In addition, the magnetic parts included in the slider **310** can also be electromagnets. In another embodiment of the present application, the slider **310** can be a permanent magnet, so as to reduce the difficulty of designing and assembling the camera module, and can reduce the cost of the camera module.

(29) As mentioned above, the module bracket **200** can be a cylindrical structural member. In order to improve the reliability of the connection between the connection component and the module bracket **200**, for example, as shown in FIG. 3, the module bracket **200** includes a bottom **210** and a side **220**. The side **220** and the bottom **210** are connected to each other and enclose to form an accommodating cavity, and at least a part of the lens component **100** is accommodated in the accommodating cavity, so that the module bracket **200** can provide more comprehensive protection for the lens component **100**. The side **220** includes four side walls with two side walls opposite to each other, and any two adjacent side walls are perpendicular to each other, and each side wall is provided with a first fitting portion **221** to improve the fitting stability of the first fitting portion **221** and the module bracket **200**. Moreover, in the above-mentioned embodiment, the number of connection components arranged around the lens component **100** can be four, which can further improve the connection stability between the lens component **100** and the module bracket **200**.

(30) In addition, two of the four connection components are arranged opposite to each other, and the two opposite connection components form a group, and connection lines between two opposite connection components in the two groups are perpendicular to each other. During the anti-shake process of the camera module, the rotation of the optical axis of the lens component **100** relative to the module bracket **200** can be decomposed into two components that rotate in mutually perpendicular planes. By adopting the above technical solution, the rotation of the optical axis of the lens component **100** on two mutually perpendicular planes can be realized by the two groups of driving components **320**, which can reduce the difficulty of adjusting the lens component **100**, and improve the adjustment precision of the lens component **100** to some extent.

(31) As mentioned above, the lens component **100** and the module bracket **200** can be connected to each other through the connection component. In order to further improve the connection reliability between the lens component **100** and the module bracket **200**, the camera module provided in the embodiment of the present application can also include a connecting shaft **500** and a bushing, and the bushing and the connecting shaft **500** are rotatably connected along the direction of the optical axis of the lens component **100**, so as to ensure that the lens component **100** and the module bracket **200** can rotate relatively around the optical axis of the lens component **100**. Besides, the bushing and the connecting shaft **500** are movably fitted in the direction of the optical axis of the lens component **100**, so as to ensure that the optical axis of the lens component **100** can rotate relative to the module bracket **200**. One of the connecting shaft **500** and the bushing is connected to the lens component **100**, and the other is connected to the module bracket **200**. Therefore, in addition to the connection component, the lens component **100** and the module bracket **200** can also be connected through the connecting shaft **500** and the bushing, to further improve the connection reliability of the lens component **100** and the module bracket **200**.

(32) In some embodiments, both the bushing and the connecting shaft **500** can be cylindrical structural members, and the interior of the bushing can be provided with a cylindrical cavity. By making the inner size of the bushing larger than the size of the connecting shaft **500**, the connecting shaft **500** can rotate relative to the bushing along the direction of the optical axis. This can also ensure that the connecting shaft **500** can be inclined relative to the bushing, thereby ensuring that the optical axis of the lens component **100** can rotate relative to the module bracket **200**.

(33) In another embodiment of the present application, the connecting shaft **500** includes a first limiting portion and a second limiting portion, the first limiting portion has a first end surface and a second end surface arranged opposite to each other, and the second limiting portion includes a third end surface and a fourth end surface arranged opposite to each other. The first end surface is fixed to the module bracket **200**, that is, the first limiting portion is fixedly connected to the module

bracket **200**. The second end surface is connected to the third end surface, that is, the second limiting portion is fixed on the first limiting part. The first end surface, the second end surface, the third end surface, and the fourth end surface are coaxially arranged and all have a circular structure. This ensures that the side surface connected between the first end surface and the second end surface in the first limiting portion, and the side surface connected between the third end surface and the fourth end surface in the second limiting portion can both be ring-shaped structural members, so that the rotation fitting between the connection shaft **500** and the bushing is relatively tight. In some embodiments, the first limiting portion and the second limiting portion can be conical structural members, or the side surfaces of the first limiting portion and the second limiting portion can both protrude outward or be concave inward.

(34) At the same time, the areas of the first end face and the fourth end face are larger than the area of the second end face, the areas of the first end face and the fourth end face are larger than the area of the third end face, and a part of the bushing can extend into a position between the first end surface and the fourth end surface, so as to be connected to the connecting shaft **500**. That is, relative to the first end surface and the fourth end surface, the second end surface and the third end surface are retracted, so that an avoidance space for fitting with the bushing can be formed between the first end surface and the second end surface. A part of the bushing can protrude into the avoidance space, so that the bushing is connected to the connecting shaft **500**. In this embodiment, it can be considered that both the connecting shaft **500** and the bushing are approximately hourglass-shaped structures.

(35) In the case that the connecting shaft **500** and the bushing adopt the above structure, the structure between the first end surface and the fourth end surface of the connecting shaft **500** can provide a limiting function for the bushing, so that the fitting relationship between the bushing and the connecting shaft **500** is more stable. Moreover, by designing the dimensions of the connecting shaft **500** and the bushing, it can be ensured that the connecting shaft **500** and the bushing can rotate relatively around the optical axis of the lens component **100**, and it can also be ensured that the bushing can produce a certain inclination relative to the connecting shaft **500**, so that the optical axis of the lens component **100** can rotate relative to the module bracket **200**.

(36) As mentioned above, the structures of the first fitting portion **221** and the second fitting portion **330** can be various. Since the first fitting portion **221** is arranged on the module bracket **200**, and the main functions of the module bracket **200** are installation and protection. In some embodiments, the first fitting portion **221** is a chute. The setting of the chute basically does not affect the structural strength of the module bracket **200**, and basically does not damage the function of the module bracket **200**. Moreover, by making the first sliding portion **311** of the slider **310** extend into the chute, the gap between the module bracket **200** and the lens component **100** can be relatively smaller, which can reduce the overall size of the camera module.

(37) In some embodiments, the chute may be a blind chute, that is, the chute is not disposed through the module bracket **200**, and in another embodiment of the present application, the chute may be disposed through the module bracket **200**. As mentioned above, the module bracket **200** may include the side **220**, and the side **220** includes side walls, and each side wall may be provided with a chute. In this case, the chute is provided through the side wall. On one hand, the processing difficulty of the chute can be reduced, and on the other hand, this can also prevent the slider **310** from being stuck at the bottom **210** of the chute, and improve the stability of fitting between the slider **310** and the chute.

(38) Since the second fitting portion **330** is installed on the lens component **100**, in order to prevent the lens component **100** from being damaged due to arrangement of the second fitting portion **330**. In some embodiments, the second fitting portion **330** is a slide bar, and the opposite ends of the slide bar can be fixed on the lens component **100** by means of bonding or the like, so that the second fitting portion **330** can provide a guiding function for the slider **310** and at the same time this can prevent the second fitting portion **330** from damaging the lens component **100**. In some

embodiments, in order to further prevent the setting of the second fitting portion **330** from possibly damaging the lens component **100**, for example, as shown in FIG. 3, a lens bracket **600** may be provided outside the lens component **100**, and the two are fixedly connected. The second fitting portion **330** may be installed outside the lens bracket **600**.

(39) In the case that the second fitting portion **330** is a sliding bar, the second sliding portion **312** of the slider **310** can be sleeved on the sliding bar. In some embodiments, the second sliding portion **312** can be provided with a through hole **312a**, and the second sliding portion **312** can be sleeved outside the sliding bar through the through hole **312a**, so as to further improve the reliability of the sliding fit relationship between the sliding bar and the slider **310**.

(40) As mentioned above, the first sliding portion **311** and the second sliding portion **312** of the slider **310** are connected to each other. When the driving component **320** drives the slider **310** to move, the optical axis of the lens component **100** can rotate relative to the module bracket **200**. Obviously, in the aforementioned process, there must be a rotation axis when the lens component **100** and the module bracket **200** rotate relative to each other. For example, the number of connection components is four. The four connection components distributed sequentially along the direction of the optical axis of the lens component **100** are respectively a first connection component, a second connection component, a third connection component, and a fourth connection component, where the first connection component and the third connection component are arranged opposite to each other, and the second connection component and the fourth connection component are arranged opposite to each other. When the driving component **320** connected to the first connection component drives the slider **310** in the first connection component to move, the position of the lens component **100** connected to the first connection component can move along the direction of the optical axis of the lens component **100** relative to the module bracket **200**. In this process, the rotation axis of the lens component **100** is a connecting line between the second connection component and the fourth connection component.

(41) Since the second connection component (and the fourth connection component) are both connected to the lens component and the module bracket, during the relative rotation of the lens component **100** and the module bracket **200**, the lens component **100** also moves relative to the first sliding portion **311** (the first fitting portion **221** slidably connected to the module bracket **200**) rotates, and correspondingly, the module bracket **200** also rotates relative to the second sliding portion **312** (the second fitting portion **330** slidably connected to the lens component **100**).

(42) Based on the above situation, for example, at least one of the first fitting portion **221** and the second fitting portion **330** is a chute, and a structure corresponding to the chute is a cylindrical structural member. In some embodiments, for example, the first fitting portion **221** is a chute. The first sliding portion **311** can be a cylindrical structural member, and the first sliding portion **311** extends into the first fitting portion **221**, so that the first sliding portion **311** can rotate in the first fitting portion **221**, and the second sliding portion **312** can rotate relative to the first fitting portion **221**, so as to ensure that the lens component **100** can rotate relative to the module bracket **200** with the slider **310** as the axis, so that the optical axis of the lens component **100** changes relative to the module bracket **200**, thereby changing the orientation of the lens component **100**. In the case that both the first fitting portion **221** and the second fitting portion **330** are chutes, and the first sliding portion **311** and the second sliding portion **312** are both cylindrical structural members, it is more possible to ensure that the lens component **100** can rotate relative to module bracket **200** with the slider **310** as the axis.

(43) In another embodiment of the present application, in order to improve the fitting stability between the first sliding portion **311** and the first fitting portion **221**, for example, the first sliding portion **311** is a bar-shaped structure, and the first sliding portion **311** extends along the extension direction of the first fitting portion **221**. This basically prevents relative rotation between the first sliding portion **311** and the first fitting portion **221**, ensuring a strong connection between the first sliding portion **311** and the first fitting portion **221**. Correspondingly, the second sliding portion **312**

can also be a bar-shaped structure, and the second sliding portion **312** extends along the extension direction of the second fitting portion **330**, thereby ensuring that there is high matching stability and connection tightness between the second sliding portion **312** and the second fitting portion **330**, to achieve the purpose of improving the connection reliability between the lens component **100** and the module bracket **200**.

(44) Moreover, the first sliding portion **311** and the second sliding portion **312** are rotationally connected, thereby ensuring that the slider **310** of the above structure can provide a function similar to a rotating shaft for the rotation of the lens component **100**, and ensuring that the optical axis of the lens component **100** can rotate relative to the module bracket **200**, thereby changing the orientation of the lens component **100**. In some embodiments a structural member such as a rotating base can be provided between the first sliding portion **311** and the second sliding portion **312** to ensure that a rotational connection relationship can be formed between the first sliding portion **311** and the second sliding portion **312**. In addition, as mentioned above, the first fitting portion **221** can be a chute. In order to reduce the difficulty of moving the first sliding portion **311** in the first fitting portion **221**, the opposite ends of the first sliding portion **311** can be provided with arc guide surfaces.

(45) As mentioned above, the lens component **100** and the module bracket **200** are connected through a connection component. In some embodiments, a connecting shaft **500** and a bushing may also be provided between the lens component **100** and the module bracket **200**, so as to improve connection reliability between the lens component **100** and the module bracket **200**.

(46) In another embodiment of the present application, for example, as shown in FIG. 2 and FIG. 3, the camera module may further include an elastic connector **400** through which the lens component **100** and the module bracket **200** are connected to each other. Under the action of the elastic connector **400**, the reliability of the connection between the lens component **100** and the module bracket **200** can be improved. Besides, after the driving component **320** drives the lens component **100** to move relative to the module bracket **200**, the elastic connector **400** can also enable the lens component **100** to have a tendency to restore its initial state. After the driving force is removed by the driving component **320**, the elastic connector **400** can restore the lens component **100** to its initial position. Therefore, the lens component **100** does not need to reset with the help of the driving component **320**, reducing the control difficulty of the lens component **100**.

(47) In some embodiments, the elastic connector **400** may be connected to a side of the lens component **100** away from a light-incident side, that is, the elastic connector **400** is disposed between the bottom **210** of the lens component **100** and the bottom **210** of the module bracket **200**. In some embodiments, as shown in FIG. 2 and FIG. 3, the elastic connector **400** may be disposed around the outside of the side wall of the lens component **100** and connected to the inner wall of the side **220** of the module bracket **200**. A number of elastic connectors **400** can be multiple, and multiple elastic connectors **400** are arranged around the side wall of the lens component **100** around the optical axis of the lens component **100**. One end of each elastic connector **400** is connected to the lens component **100**, and the other end is connected to the module bracket **200**, so that the elastic connecting member **400** acts like a “suspension spring”. In addition, in order to minimize the hindrance effect exerted by the elastic connector **400** on the lens component **100** when the lens component **100** rotates around its own optical axis relative to the module bracket **200**, the extension direction of the elastic connector **400** can have a component along the direction of the optical axis. In other words, opposite ends of the elastic connector **400** are separated from each other along the direction of the optical axis of the lens component **100**.

(48) Based on the camera module disclosed in any of the above embodiments, the embodiment of the present application also provides an electronic device, and the electronic device includes the camera module provided in any of the above embodiments. Of course, the electronic device also includes a display module, a housing, and other devices such as batteries, which will not be introduced one by one herein.

(49) The electronic device disclosed in embodiments of the present application may be a smart phone, a tablet computer, an e-book reader, or a wearable device. The electronic device may also be another device. This is not limited in embodiments of the present application.

(50) The embodiments of the present application focus on describing differences between the embodiments, and different optimization features of the embodiments may be combined to form better embodiments provided that they are not contradictory. Considering brevity, details are not described herein again.

(51) The foregoing descriptions are merely embodiments of the present application, and are not intended to limit the present application. Various changes and modifications may be made to the present application by a person skilled in the art. Any modifications, equivalent substitutions, improvements, and the like made within the spirit and principle of the present application should be included within the scope of the claims of the present application.

## Claims

1. A camera module, comprising a lens component; a module bracket; a driving component; and at least three connection components, wherein: the at least three connection components are arranged around the periphery of the lens component, each of the connection components comprises a slider, a first fitting portion, and a second fitting portion, the slider comprises a first sliding portion and a second sliding portion connected to each other, the first sliding portion and the first fitting portion are slidably fitted with each other, the second sliding portion and the second fitting portion are slidably fitted with each other, the first fitting portion is arranged on the module bracket, the second fitting portion is arranged on the lens component, a preset angle is formed between extending directions of the first fitting portion and the second fitting portion, the extending directions of the first fitting portion and the second fitting portion are both different from a direction of an optical axis of the lens component, the driving component is arranged on the module bracket, and the driving component is connected to the slider, the driver is used to drive the corresponding slider to move, and the lens component rotates relative to the module bracket along with movement of the slider.

2. The camera module according to claim 1, further comprising a positioning component, wherein: the positioning component is arranged on the lens component, and the positioning component fits with the second sliding portion, the positioning component has a first state and a second state, when the positioning component is in the first state, the second sliding portion slidably fits with the second fitting portion, and the driving component drives the slider to move, the optical axis of the lens component rotates relative to the module bracket along with the movement of the slider; when the positioning component is in the second state, the second sliding portion fits and the fitting portion are relatively fixed, the driving component drives the slider to move, and the lens component rotates around its own optical axis relative to the module bracket along with the movement of the slider.

3. The camera module according to claim 2, wherein both the driving component and the positioning component comprise electromagnets, and the slider comprises a magnetic element.

4. The camera module according to claim 2, wherein: the module bracket comprises a bottom and a side, and the side is connected to the bottom to form an accommodating cavity, at least a part of the lens component is accommodated in the accommodating cavity, the side comprises four side walls with two side walls opposite to each other, any two adjacent side walls are perpendicular to each other, and each of the side walls is provided with the first fitting portion.

5. The camera module according to claim 2, further comprising a connecting shaft and a bushing, wherein: the bushing and the connecting shaft are rotatably connected in a direction around the optical axis of the lens component, the bushing and the connecting shaft are movably fitted in the direction of the optical axis of the lens component, one of the connecting shaft and the bushing is

connected to the lens component, and the other is connected to the module bracket.

6. The camera module according to claim 5, wherein the connecting shaft comprises a first limiting portion and a second limiting portion, wherein the first limiting portion has a first end surface and a second end surface arranged opposite to each other, and the second limiting portion comprises a third end face and a fourth end face arranged opposite to each other, wherein: the first end face is fixed to the module bracket, the second end face is connected to the third end face, and the first end face, the second end face, and the third end face and the fourth end face are coaxially arranged and are all circular structures; areas of the first end face and the fourth end face are both larger than an area of the second end face, and areas of the first end face and the fourth end face are both larger than an area of the third end face; and a part of the fitting portion protrudes between the first end surface and the fourth end surface to be connected to the connecting shaft.

7. The camera module according to claim 1, wherein the first fitting portion is a slide groove, and the second fitting portion is a slide bar.

8. The camera module according to claim 1, wherein: the first sliding portion is a bar-shaped structure, and the first sliding portion extends along the extension direction of the first fitting portion; the second sliding portion is a bar-shaped structure, and the second sliding portion extends along the extension direction of the second fitting portion; and the first sliding portion and the second sliding portion are rotatably connected to each other.

9. The camera module according to claim 1, further comprising an elastic connector, wherein the lens component and the module bracket are connected through the elastic connector.

10. An electronic device, comprising a camera module comprising: a lens component; a module bracket; a driving component; and at least three connection components, wherein: the at least three connection components are arranged around the periphery of the lens component, each of the connection components comprises a slider, a first fitting portion, and a second fitting portion, the slider comprises a first sliding portion and a second sliding portion connected to each other, the first sliding portion and the first fitting portion are slidably fitted with each other, the second sliding portion and the second fitting portion are slidably fitted with each other, the first fitting portion is arranged on the module bracket, the second fitting portion is arranged on the lens component, a preset angle is formed between extending directions of the first fitting portion and the second fitting portion, the extending directions of the first fitting portion and the second fitting portion are both different from a direction of an optical axis of the lens component, the driving component is arranged on the module bracket, and the driving component is connected to the slider, the driver is used to drive the corresponding slider to move, and the lens component rotates relative to the module bracket along with movement of the slider.

11. The electronic device according to claim 10, wherein the camera module further comprises a positioning component, wherein: the positioning component is arranged on the lens component, and the positioning component fits with the second sliding portion, the positioning component has a first state and a second state, when the positioning component is in the first state, the second sliding portion slidably fits with the second fitting portion, and the driving component drives the slider to move, the optical axis of the lens component rotates relative to the module bracket along with the movement of the slider; when the positioning component is in the second state, the second sliding portion fits and the fitting portion are relatively fixed, the driving component drives the slider to move, and the lens component rotates around its own optical axis relative to the module bracket along with the movement of the slider.

12. The electronic device according to claim 11, wherein both the driving component and the positioning component comprise electromagnets, and the slider comprises a magnetic element.

13. The electronic device according to claim 11, wherein: the module bracket comprises a bottom and a side, and the side is connected to the bottom to form an accommodating cavity, at least a part of the lens component is accommodated in the accommodating cavity, the side comprises four side walls with two side walls opposite to each other, any two adjacent side walls are perpendicular to

each other, and each of the side walls is provided with the first fitting portion.

14. The electronic device according to claim 11, wherein the camera module further comprises a connecting shaft and a bushing, wherein: the bushing and the connecting shaft are rotatably connected in a direction around the optical axis of the lens component, the bushing and the connecting shaft are movably fitted in the direction of the optical axis of the lens component, one of the connecting shaft and the bushing is connected to the lens component, and the other is connected to the module bracket.

15. The electronic device according to claim 14, wherein the connecting shaft comprises a first limiting portion and a second limiting portion, wherein the first limiting portion has a first end surface and a second end surface arranged opposite to each other, and the second limiting portion comprises a third end face and a fourth end face arranged opposite to each other, wherein: the first end face is fixed to the module bracket, the second end face is connected to the third end face, and the first end face, the second end face, and the third end face and the fourth end face are coaxially arranged and are all circular structures; areas of the first end face and the fourth end face are both larger than an area of the second end face, and areas of the first end face and the fourth end face are both larger than an area of the third end face; and a part of the fitting portion protrudes between the first end surface and the fourth end surface to be connected to the connecting shaft.

16. The electronic device according to claim 10, wherein the first fitting portion is a slide groove, and the second fitting portion is a slide bar.

17. The electronic device according to claim 10, wherein: the first sliding portion is a bar-shaped structure, and the first sliding portion extends along the extension direction of the first fitting portion; the second sliding portion is a bar-shaped structure, and the second sliding portion extends along the extension direction of the second fitting portion; and the first sliding portion and the second sliding portion are rotatably connected to each other.

18. The electronic device according to claim 10, wherein the camera module further comprises an elastic connector, wherein the lens component and the module bracket are connected through the elastic connector.

---