

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250260978

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

LIU; Jennifer

SYSTEM AND METHOD FOR SECURITY PROTECTION OF NAS MESSAGES

Abstract

Systems and methods that provide NAS security protection for mobile networks. In one embodiment, a network element of a mobile network performs a NAS procedure in multiple phases to establish a NAS communication session with User Equipment (UE) when no NAS security context exists. For a first phase, the network element receives an initial NAS message from the UE populated with a subset of NAS protocol Information Elements (IEs) designated for security-related handling, selects a NAS security algorithm for the NAS security context, and sends a response to the UE that indicates the NAS security algorithm. For a second phase, the network element receives a subsequent NAS message from the UE having a NAS message container that contains the initial NAS message populated with each of the NAS protocol IEs for the NAS procedure, and decrypts the NAS message container of the subsequent NAS message using the NAS security algorithm.

Inventors: LIU; Jennifer (Plano, TX)

Applicant: NOKIA TECHNOLOGIES OY (Espoo, FI)

Family ID: 69950018

Appl. No.: 19/194827

Filed: April 30, 2025

Related U.S. Application Data

parent US continuation 18756812 20240627 PENDING child US 19194827

parent US continuation 18197049 20230513 parent-grant-document US 12081978 child US 18756812

parent US continuation 17278487 20210322 parent-grant-document US 11689920 WO

continuation PCT/FI2019/050685 20190924 child US 18197049

us-provisional-application US 62735732 20180924

Publication Classification

Int. Cl.: **H04W12/06** (20210101); **H04W12/037** (20210101); **H04W12/0431** (20210101);
H04W76/25 (20180101); **H04W84/04** (20090101)

U.S. Cl.:

CPC **H04W12/06** (20130101); **H04W12/037** (20210101); **H04W12/0431** (20210101);
H04W76/25 (20180201); **H04W84/042** (20130101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application is a continuation of U.S. Non-Provisional patent application Ser. No. 18/756,812 filed Jun. 27, 2024 and entitled “System and Method for Security Protection of NAS Messages,” which is a continuation of U.S. Non-Provisional patent application Ser. No. 18/197,049, filed May 13, 2023 and entitled “System and Method for Security Protection of NAS Messages,” which issued on Sep. 3, 2024 as U.S. Pat. No. 12,081,978, which is a continuation of U.S. Non-Provisional patent application Ser. No. **17/278,487**, filed Mar. **22, 2021** and entitled “System and Method for Security Protection of NAS Messages,” which issued on Jun. 27, 2023 as U.S. Pat. No. 11,689,920, which is a National Stage Entry of International Patent Application Serial No. PCT/FI2019/050685, filed Sep. 24, 2019, which claims the benefit of priority to U.S. Provisional Patent Application Ser. No. 62/735,732, filed on Sep. 24, 2018, the entire disclosures of each of which are hereby incorporated herein by reference in their entireties for all purposes.

FIELD

[0002] This disclosure is related to the field of communication systems and, in particular, to security in networks.

BACKGROUND

[0003] Service providers or carriers implement mobile networks to offer numerous voice and data services to end users of mobile phones or other mobile devices/terminals, which are referred to generally as User Equipment (UE). Some examples of voice services are voice calls, call forwarding, call waiting, etc. Some examples of data services are Internet access, streaming audio, streaming video, online gaming, Internet Protocol television (IP-TV), etc. A mobile network is a type of network where the last link to the end user is wireless. A mobile network generally includes a core network, and one or more Radio Access Networks (RAN) that exchange signaling and data with UEs over a radio interface. A typical mobile network is logically separated into a user plane and a control plane. The user plane is the logical plane responsible for carrying user data being sent over the network, and the control plane is the logical plane responsible for carrying the signaling used to establish communications for a UE. The Third Generation Partnership Project (3GPP) specifications partition cellular protocols into two strata: the Non-Access Stratum (NAS) and the Access Stratum (AS). The AS consists of communications between the UE and the RAN (e.g., eNodeB) occurring via a Radio Frequency (RF) channel. The NAS consists of non-radio signaling traffic between a UE and the core network (e.g., a Mobility Management Entity (MME) for LTE or Access and Mobility Management Function (AMF) for a network generation network). The 3GPP has implemented security procedures to protect control plane messages (e.g., NAS messages) from various attacks. However, it may be beneficial to identify enhanced security procedures that provide further protection for control plane messages.

SUMMARY

[0004] Embodiments described herein provide enhanced protection for NAS messages. ANAS procedure (e.g., registration of a UE) includes a set of Information Elements (IEs) that carry information. The embodiments described below set forth ways of protecting the IEs or a subset of the IEs that are sent in NAS messages. Thus, the information carried in the IEs is less vulnerable to malicious attacks.

[0005] One embodiment comprises a network element of a mobile network. The network element includes a processor(s), and memory including computer program code executable by the processor. The processor is configured to cause the network element to perform a NAS procedure in multiple phases to establish a NAS communication session between the network element and a UE. For a first phase of the NAS procedure, the processor is further configured to cause the network element to receive an initial NAS message from the UE, where the initial NAS message is populated with a subset of NAS protocol IEs, from the NAS protocol IEs for the NAS procedure, that are designated for security-related handling. The processor is further configured to cause the network element to process the subset of the NAS protocol IEs to determine that a NAS security context does not exist for the UE, select a NAS security algorithm for the NAS security context, and send a response to the UE that indicates the NAS security algorithm and a security key set identifier of the NAS security context. For a second phase of the NAS procedure, the processor is further configured to cause the network element to receive a subsequent NAS message from the UE having a NAS message container that contains the initial NAS message encrypted based on the NAS security algorithm, and decrypt the NAS message container of the subsequent NAS message, where the initial NAS message contained in the NAS message container of the subsequent NAS message is populated with each of the NAS protocol IEs for the NAS procedure.

[0006] In another embodiment, for the first phase, the subset of the NAS protocol IEs are encrypted in the initial NAS message using a public key of a Home Public Land Mobile Network (HPLMN) for the UE. The processor is further configured to cause the network element to initiate decryption of the subset of the NAS protocol IEs.

[0007] In another embodiment, the network element comprises an Access and Mobility Management Function (AMF) element of the mobile network.

[0008] In another embodiment, the processor is further configured to cause the network element to send the subset of NAS protocol IEs as encrypted to a Unified Data Management (UDM) element to decrypt the subset of NAS protocol IEs based on a private key of the HPLMN.

[0009] In another embodiment, the initial NAS message comprises a registration request message. The subset of the NAS protocol IEs designated for security-related handling consists of a mobile identity for the UE, a UE security capability indicating one or more NAS security algorithms supported by the UE, a registration type, and a security key set identifier for a NAS security context.

[0010] In another embodiment, the response comprises a security mode command message that indicates the NAS security algorithm and the security key set identifier, and the subsequent NAS message received from the UE comprises a security mode complete message having the NAS message container that contains the initial NAS message encrypted based on the NAS security algorithm.

[0011] In another embodiment, the mobile network comprises a Fifth-Generation (5G) network.

[0012] Another embodiment comprises a method of performing a NAS procedure to establish a NAS communication session between a UE and a network element of a mobile network. For a first phase of the NAS procedure, the method comprises receiving an initial NAS message at the network element from the UE, where the initial NAS message is populated with a subset of NAS protocol IEs, from the NAS protocol IEs for the NAS procedure, that are designated for security-related handling. Further for the first phase, the method comprises processing the subset of the NAS protocol IEs at the network element to determine that a NAS security context does not exist for the UE, selecting a NAS security algorithm at the network element for the NAS security

context, and sending a response from the network element to the UE that indicates the NAS security algorithm and a security key set identifier of the NAS security context. For a second phase of the NAS procedure, the method comprises receiving a subsequent NAS message at the network element from the UE having a NAS message container that contains the initial NAS message encrypted based on the NAS security algorithm, and decrypting the NAS message container of the subsequent NAS message at the network element, where the initial NAS message contained in the NAS message container of the subsequent NAS message is populated with each of the NAS protocol IEs for the NAS procedure.

[0013] In another embodiment, for the first phase, the subset of the NAS protocol IEs are encrypted in the initial NAS message using a public key of a HPLMN for the UE, and the method further comprises initiating decryption of the subset of the NAS protocol IEs.

[0014] In another embodiment, the network element comprises an AMF element of the mobile network, and the step of initiating decryption of the subset of the NAS protocol IEs comprises sending the subset of NAS protocol IEs as encrypted to a UDM element to decrypt the subset of NAS protocol IEs based on a private key of the HPLMN.

[0015] In another embodiment, the initial NAS message comprises a registration request message, and the subset of the NAS protocol IEs designated for security-related handling consists of a mobile identity for the UE, a UE security capability indicating one or more NAS security algorithms supported by the UE, a registration type, and a security key set identifier for a NAS security context.

[0016] In another embodiment, the response comprises a security mode command message that indicates the NAS security algorithm and the security key set identifier, and the subsequent NAS message received from the UE comprises a security mode complete message having the NAS message container that contains the initial NAS message encrypted based on the NAS security algorithm.

[0017] In another embodiment, for the first phase of the NAS procedure, the method comprises the following steps at the UE: identifying the subset of the NAS protocol IEs for the NAS procedure that are designated for security-related handling, inserting the subset of NAS protocol IEs in the initial NAS message, sending the initial NAS message from the UE to the network element, and receiving the response from the network element that indicates the NAS security algorithm and the security key set identifier for the NAS security context. For the second phase of the NAS procedure, the method comprises the following steps at the UE: inserting the NAS protocol IEs for the NAS procedure in the initial NAS message, inserting the initial NAS message in the NAS message container of the subsequent NAS message, encrypting the NAS message container of the subsequent NAS message using the NAS security algorithm, and sending the subsequent NAS message from the UE to the network element.

[0018] In another embodiment, for the first phase, the method further includes encrypting, at the UE, the subset of the NAS protocol IEs in the initial NAS message using a public key of a HPLMN for the UE.

[0019] Another embodiment comprises a UE that includes a processor(s), and a memory including computer program code executable by the processor. The processor is configured to cause the UE to initiate a NAS procedure in multiple phases to establish a NAS communication session between the UE and a network element of a mobile network. For a first phase of the NAS procedure, the processor is further configured to cause the UE to identify, from NAS protocol IEs for the NAS procedure, a subset of the NAS protocol IEs that are designated for security-related handling. The processor is further configured to cause the UE to insert the subset of NAS protocol IEs in an initial NAS message, send the initial NAS message to the network element, and receive a response from the network element that indicates a NAS security algorithm and security key set identifier for a NAS security context. For a second phase of the NAS procedure, the processor is further configured to cause the UE to insert the NAS protocol IEs for the NAS procedure in the initial

NAS message, insert the initial NAS message in a NAS message container of a subsequent NAS message, encrypt the NAS message container of the subsequent NAS message using the NAS security algorithm, and send the subsequent NAS message to the network element.

[0020] In another embodiment, for the first phase, the processor is further configured to cause the UE to encrypt the subset of the NAS protocol IEs in the initial NAS message using a public key of a HPLMN for the UE.

[0021] In another embodiment, the processor is further configured to cause the UE to encrypt the subset of the NAS protocol IEs in the initial NAS message using the public key when the UE has the public key programmed on a UMTS Subscriber Identify Module (USIM), and send the initial NAS message to the network element without encrypting the subset of the NAS protocol IEs in the initial NAS message when the UE does not have the public key programmed on the USIM.

[0022] In another embodiment, the initial NAS message comprises a registration request message, and the subset of NAS protocol IEs designated for security-related handling consists of a mobile identity for the UE, a UE security capability indicating one or more NAS security algorithms supported by the UE, a registration type, and a security key set identifier for a NAS security context.

[0023] In another embodiment, the processor is configured to cause the UE to encrypt the subset of the NAS protocol IEs in the initial NAS message using a public key of a HPLMN for the UE when the registration type does not indicate an emergency, and send the initial NAS message to the network element without encrypting the subset of the NAS protocol IEs in the initial NAS message when the registration type indicates an emergency.

[0024] In another embodiment, the response comprises a security mode command message that indicates the NAS security algorithm and the security key set identifier, and the subsequent NAS message comprises a security mode complete message having the NAS message container that contains the initial NAS message encrypted based on the NAS security algorithm.

[0025] Another embodiment comprises a network element of a mobile network. The network element includes a means for causing the network element to perform a NAS procedure in multiple phases to establish a NAS communication session between the network element and a UE. For a first phase of the NAS procedure, the network element includes a means for receiving an initial NAS message from the UE, where the initial NAS message is populated with a subset of NAS protocol IEs, from the NAS protocol IEs for the NAS procedure, that are designated for security-related handling. The network element further includes a means for processing the subset of the NAS protocol IEs to determine that a NAS security context does not exist for the UE, a means for selecting a NAS security algorithm for the NAS security context, and a means for sending a response to the UE that indicates the NAS security algorithm and a security key set identifier of the NAS security context. For a second phase of the NAS procedure, the network element further includes a means for receiving a subsequent NAS message from the UE having a NAS message container that contains the initial NAS message encrypted based on the NAS security algorithm, and a means for decrypting the NAS message container of the subsequent NAS message, where the initial NAS message contained in the NAS message container of the subsequent NAS message is populated with each of the NAS protocol IEs for the NAS procedure.

[0026] The above summary provides a basic understanding of some aspects of the specification. This summary is not an extensive overview of the specification. It is intended to neither identify key or critical elements of the specification nor delineate any scope of the particular embodiments of the specification, or any scope of the claims. Its sole purpose is to present some concepts of the specification in a simplified form as a prelude to the more detailed description that is presented later.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0027] Some embodiments of the invention are now described, by way of example only, and with reference to the accompanying drawings. The same reference number represents the same element or the same type of element on all drawings.

[0028] FIG. **1** illustrates a mobile network in an illustrative embodiment.

[0029] FIG. **2** illustrates an Evolved Packet Core (EPC) network.

[0030] FIG. **3** illustrates a non-roaming architecture of a next generation network.

[0031] FIG. **4** illustrates a roaming architecture of a next generation network.

[0032] FIG. **5** illustrates a radio protocol stack.

[0033] FIG. **6** is a block diagram of a UE in an illustrative embodiment.

[0034] FIG. **7** is a block diagram of a network element in an illustrative embodiment.

[0035] FIG. **8** is a flow chart illustrating a method of performing a NAS procedure in a UE in an illustrative embodiment.

[0036] FIG. **9** is a flow chart illustrating a method of performing a NAS procedure in a network element in an illustrative embodiment.

[0037] FIG. **10** is a message diagram showing a NAS procedure when a UE has no security context in an illustrative embodiment.

[0038] FIG. **11** is a flow chart illustrating a method of performing a NAS procedure in UE **110** in another illustrative embodiment.

[0039] FIG. **12** is a flow chart illustrating a method of performing a NAS procedure in a network element in another illustrative embodiment.

[0040] FIG. **13** is a message diagram showing a NAS procedure when a UE has no security context in an illustrative embodiment.

[0041] FIG. **14** is a flow chart illustrating a method of performing a NAS procedure in a UE in another illustrative embodiment.

[0042] FIG. **15** is a flow chart illustrating a method of performing a NAS procedure in a network element in another illustrative embodiment.

[0043] FIG. **16** is a message diagram showing a NAS registration procedure when a UE has a valid security context in an illustrative embodiment.

[0044] FIG. **17** is a message diagram showing a NAS service request procedure when a UE has a valid security context in an illustrative embodiment.

[0045] FIG. **18** is a message diagram showing a NAS de-registration procedure when a UE has a valid security context in an illustrative embodiment.

[0046] FIGS. **19A-19B** illustrate a flow chart illustrating a method of performing a NAS procedure in a UE in an illustrative embodiment.

[0047] FIG. **20** is a flow chart illustrating a method of performing a NAS procedure in a network element in an illustrative embodiment.

[0048] FIG. **21** is a message diagram showing a NAS registration procedure when a UE has a NAS security context but the NAS security context is not valid or is not found in an illustrative embodiment.

[0049] FIG. **22** is a message diagram showing a NAS service request procedure when a UE has a NAS security context but the NAS security context is not valid or is not found in an illustrative embodiment.

DETAILED DESCRIPTION

[0050] The figures and the following description illustrate specific exemplary embodiments. It will thus be appreciated that those skilled in the art will be able to devise various arrangements that, although not explicitly described or shown herein, embody the principles of the embodiments and are included within the scope of the embodiments. Furthermore, any examples described herein are intended to aid in understanding the principles of the embodiments, and are to be construed as

being without limitation to such specifically recited examples and conditions. As a result, the inventive concept(s) is not limited to the specific embodiments or examples described below, but by the claims and their equivalents.

[0051] FIG. 1 illustrates a mobile network **100** in an illustrative embodiment. Mobile network **100** (also referred to as a cellular network) is a type of network where the last link is wireless, and provides voice and/or data services to a plurality of devices. Mobile network **100** may be a Third Generation (3G), a Fourth Generation (4G), and/or a next generation network (e.g., Fifth Generation (5G)).

[0052] Mobile network **100** is illustrated as providing communication services to UEs **110** (along with other UEs not shown). UEs **110** may be enabled for voice services, data services, Machine-to-Machine (M2M) or Machine Type Communications (MTC) services, and/or other services. A UE **110** may be an end user device such as a mobile phone (e.g., smartphone), a tablet or PDA, a computer with a mobile broadband adapter, etc.

[0053] Mobile network **100** includes one or more Radio Access Networks (RAN) **120** that communicate with UEs **110** over a radio interface **122**. RAN **120** may support Evolved-UMTS Terrestrial Radio Access Network (E-UTRAN) access, Wireless Local Area Network (WLAN) access, fixed access, satellite radio access, new Radio Access Technologies (RAT), etc. As an example, RAN **120** may comprise an E-UTRAN or Next Generation RAN (NG-RAN) that includes one or more base stations **124** that are dispersed over a geographic area. A base station **124** may comprise an entity that uses radio communication technology to communicate with a UE on the licensed spectrum, and interface the UE with a core network. Base stations **124** in an E-UTRAN are referred to as Evolved-NodeBs (eNodeB). Base stations **124** in an NG-RAN are referred to as gNodeBs (NR base stations) and/or ng-eNodeBs (LTE base stations supporting a 5G Core Network). As another example, RAN **120** may comprise a WLAN that includes one or more Wireless Access Points (WAP) **125**. A WLAN is a network in which a UE is able to connect to a Local Area Network (LAN) through a wireless (radio) connection. A WAP **125** is a node that uses radio communication technology to communicate with a UE over the unlicensed spectrum, and provides the UE access to a core network. One example of WAP **125** is a WiFi access point that operates on the 2.4 GHz or 5 GHz radio bands. The term “base station” as used herein may refer to an eNodeB, a gNodeB, an ng-eNodeB, a WAP, etc.

[0054] UEs **110** are able to attach to cell **126** of RAN **120** to access a core network **130**. RAN **120** therefore represents the radio interface between UEs **110** and core network **130**. Core network **130** is the central part of mobile network **100** that provides various services to customers who are connected by RAN **120**. One example of core network **130** is the Evolved Packet Core (EPC) network as suggested by the 3GPP for LTE. Another example of core network **130** is a 5G core network as suggested by the 3GPP. Core network **130** includes network elements **132**, which may comprise servers, devices, apparatus, or equipment (including hardware) that provide services for UEs **110**. Network elements **132**, in an EPC network, may comprise a Mobility Management Entity (MME), a Serving Gateway (S-GW), a Packet Data Network Gateway (P-GW), etc. Network elements **132**, in a 5G network, may comprise an Access and Mobility Management Function (AMF), a Session Management Function (SMF), a Policy Control Function (PCF), an Application Function (AF), a User Plane Function (UPF), etc.

[0055] FIG. 2 illustrates an Evolved Packet Core (EPC) network **200**, which is the core network for LTE. EPC network **200** includes a Mobility Management Entity (MME) **214**, a Serving Gateway (S-GW) **215**, a Packet Data Network Gateway (P-GW) **216**, a Home Subscriber Server (HSS) **217**, and a Policy and Charging Rules Function (PCRF) **218**, but may include other elements not shown, such as IP Multimedia Subsystem (IMS) Application Servers. Within the EPC network **200**, the user data (also referred to as the “user plane”) and the signaling (also referred to as the “control plane”) are separated. MME **214** handles the control plane within EPC network **200**. For instance, MME **214** handles the signaling related to mobility and security for E-UTRAN access. MME **214**

is responsible for tracking and paging UE **110** in idle mode. S-GW **215** and P-GW **216** handle the user plane. S-GW **215** and P-GW **216** transport data traffic between UE **110** and external data networks **240** (DN or Packet Data Network (PDN)). S-GW **215** is the point of interconnect between the radio-side and EPC network **200**, and serves UE **110** by routing incoming and outgoing IP packets. S-GW **215** is also the anchor point for the intra-LTE mobility (i.e., in case of handover between eNodeBs), and between LTE and other 3GPP accesses. P-GW **216** is the point of interconnect between EPC network **200** and external data networks **240** (i.e., point of ingress or egress for data network **240**), and routes packets to and from data network **240**. HSS **217** is a database that stores user-related and subscriber-related information. PCRF **218** provides a Policy and Charging Control (PCC) solution in EPC network **200**, and is a node or entity of EPC network **200** that formulates PCC rules for services requested by an end user.

[0056] MME **214** connects to RAN **120** (i.e., eNodeB) through the S1-MME interface, and S-GW **215** connects to RAN **120** through the S1-U interface. MME **214** connects to S-GW **215** through the S11 interface, and connects to HSS **217** through the S6a interface. PCRF **218** connects to P-GW **216** through the Gx interface, which provides the transfer of policy and charging rules from PCRF **218** to a Policy and Charging Enforcement Function (PCEF) in P-GW **216**. PCRF **218** connects to S-GW **215** through the Gxx interface, and S-GW **215** connects to P-GW **216** through the S5 interface.

[0057] FIG. **3** illustrates a non-roaming architecture **300** of a next generation network. The architecture in FIG. **3** is a reference point representation, as is further described in 3GPP TS 23.501 (v15.3.0), which is incorporated by reference as if fully included herein. Architecture **300** is comprised of Network Functions (NF) for a core network, and the network functions for the control plane are separated from the user plane. The control plane of the core network includes an Authentication Server Function (AUSF) **310**, a Unified Data Management (UDM) **312**, a Network Slice Selection Function (NSSF) **313**, an Access and Mobility Management Function (AMF) **314**, a Session Management Function (SMF) **316**, a Policy Control Function (PCF) **318**, and an Application Function (AF) **320**. The user plane of the core network includes one or more User Plane Functions (UPF) **324** that communicate with data network **240**. UE **110** is able to access the control plane and the user plane of the core network through (R) AN **120**.

[0058] AUSF **310** is configured to support authentication of UE **110**. UDM **312** is configured to store subscription data/information for UE **110**. UDM **312** may store three types of user data: subscription, policy, and session-related context (e.g., UE location). AMF **314** is configured to provide UE-based authentication, authorization, mobility management, etc. SMF **316** is configured to provide the following functionality: session management (SM), UE Internet Protocol (IP) address allocation and management, selection and control of UPF(s), termination of interfaces towards PCF **318**, control part of policy enforcement and Quality of Service (QoS), lawful intercept, termination of SM parts of NAS messages, Downlink Data Notification (DNN), roaming functionality, handle local enforcement to apply QoS for Service Level Agreements (SLAs), charging data collection and charging interface, etc. If UE **110** has multiple sessions, different SMFs may be allocated to each session to manage them individually and possibly provide different functionalities per session. PCF **318** is configured to support a unified policy framework to govern network behavior, and to provide policy rules to control plane functions for QoS enforcement, charging, access control, traffic routing, etc. AF **320** provides information on a packet flow to PCF **318**. Based on the information, PCF **318** is configured to determine policy rules about mobility and session management to make AMF **314** and SMF **316** operate properly.

[0059] UPF **324** supports various user plane operations and functionalities, such as packet routing and forwarding, traffic handling (e.g., QoS enforcement), an anchor point for Intra-RAT/Inter-RAT mobility (when applicable), packet inspection and policy rule enforcement, lawful intercept (UP collection), traffic accounting and reporting, etc. Data network **240** is not part of the core network, and provides Internet access, operator services, 3rd party services, etc. For instance, the

International Telecommunication Union (ITU) has classified 5G mobile network services into three categories: Enhanced Mobile Broadband (eMBB), Ultra-reliable and Low-Latency Communications (uRLLC), and Massive Machine Type Communications (mMTC) or Massive Internet of Things (MIOT). eMBB focuses on services that have high bandwidth requirements, such as HD videos, Virtual Reality (VR), and Augmented Reality (AR). uRLLC focuses on latency-sensitive services, such as automated driving and remote management. mMTC and MIOT focuses on services that include high requirements for connection density, such as smart city and smart agriculture. Data network **240** may be configured to provide these and other services.

[0060] Architecture **300** includes the following reference points. The N1 reference point is implemented between UE **110** and AMF **314**. The N2 reference point is implemented between (R) AN **120** and AMF **314**. The N3 reference point is implemented between (R) AN **120** and UPF **324**. The N4 reference point is implemented between the SMF **316** and UPF **324**. The N5 reference point is implemented between PCF **318** and AF **320**. The N6 reference point is implemented between UPF **324** and data network **240**. The N7 reference point is implemented between the SMF **316** and PCF **318**. The N8 reference point is implemented between UDM **312** and AMF **314**. The N9 reference point is implemented between two UPFs **324**. The N10 reference point is implemented between UDM **312** and SMF **316**. The N11 reference point is implemented between AMF **314** and SMF **316**. The N12 reference point is implemented between AMF **314** and AUSF **310**. The N13 reference point is implemented between UDM **312** and AUSF **310**. The N reference point is implemented between two AMFs. The N15 reference point is implemented between PCF **318** and AMF **314** in the case of a non-roaming scenario. The N22 reference point is implemented between NSSF **313** and AMF **314**.

[0061] FIG. **4** illustrates a roaming architecture **400** of a next generation network. The architecture in FIG. **4** is a local breakout scenario in reference point representation, as is further described in 3GPP TS 23.501 (v15.3.0). In a roaming scenario, a Visited Public Land Mobile Network (VPLMN) **402** and a Home PLMN (HPLMN) **404** are shown. An HPLMN **404** identifies the PLMN in which the profile of a mobile subscriber is held. A VPLMN is a PLMN upon which the mobile subscriber has roamed when leaving their HPLMN. Users roaming to other networks will receive subscription information from the HPLMN **404**. In a local breakout scenario, PCF **318** (hPCF), UDM **312**, and AUSF **310** are in the HPLMN **404** for UE **110**. The other network functions, including a visited PCF (vPCF) **418**, are in the VPLMN **402**.

[0062] FIG. **5** illustrates a radio protocol stack **500**, such as for radio interface **122**. As described herein, the user plane **512** comprises a set of protocols used to transfer the actual user data through a network, and the control plane **514** comprises protocols used to control and establish the user connections and bearers within the network. For the user plane **512** and the control plane **514**, radio protocol stack **500** includes the physical (PHY) layer **501**, the Medium Access Control (MAC) layer **502**, the Radio Link Control (RLC) layer **503**, and the Packet Data Convergence Protocol (PDCP) layer **504**. The control plane **514** additionally includes the Radio Resource Control (RRC) layer **505** and the Non-Access Stratum (NAS) layer **506**.

[0063] The physical layer **501** carries all information from the MAC transport channels over the radio interface. Data and signaling messages are carried on physical channels between the different levels of physical layer **501**. The physical channels are divided into physical data channels and physical control channels. The physical data channels may include the Physical Downlink Shared Channel (PDSCH), the Physical Broadcast Channel (PBCH), the Physical Multicast Channel (PMCH), the Physical Uplink Shared Channel (PUSCH), and the Physical Random Access Channel (PRACH). The physical control channels may include the Physical Control Format Indicator Channel (PCFICH), the Physical Hybrid ARQ Indicator Channel (PHICH), the Physical Downlink Control Channel (PDCCH), and the Physical Uplink Control Channel (PUCCH).

[0064] The MAC layer **502** is responsible for mapping between logical channels and transport channels, multiplexing of MAC Service Data Units (SDUs) from one or different logical channels

onto transport blocks (TB) to be delivered to the physical layer on transport channels, de-multiplexing of MAC SDUs from one or different logical channels from transport blocks delivered from the physical layer on transport channels, scheduling information reporting, error correction through Hybrid Automatic Repeat Request (HARM), priority handling between UEs by means of dynamic scheduling, priority handling between logical channels of one UE, and logical channel prioritization. The RLC layer **503** is responsible for transfer of upper layer Protocol Data Units (PDUs), error correction through ARQ, and concatenation, segmentation and reassembly of RLC SDUs. The RLC layer **503** is also responsible for re-segmentation of RLC data PDUs, reordering of RLC data PDUs, duplicate detection, RLC SDU discard. RLC re-establishment, and protocol error detection. The PDCP layer **504** is responsible for header compression and decompression of IP data, transfer of data (user plane or control plane), maintenance of PDCP Sequence Numbers (SNs), in-sequence delivery of upper layer PDUs at re-establishment of lower layers, duplicate elimination of lower layer SDUs at re-establishment of lower layers for radio bearers mapped on RLC Acknowledged Mode (AM), ciphering and deciphering of user plane data and control plane data, integrity protection and integrity verification of control plane data, timer-based discard, duplicate discarding, etc. The RRC layer **505** is responsible for the broadcast of System Information related to the NAS, broadcast of System Information related to the Access Stratum (AS), paging, establishment, maintenance, and release of an RRC connection between the UE and RAN, security functions including key management, establishment, configuration, maintenance, and release of point-to-point Radio Bearers (RB). The NAS layer **506** represents the highest stratum of the control plane **514** between the UE and the core network (e.g., MME/AMF), and supports the mobility of the UE and the session management procedures to establish and maintain IP connectivity between the UE and the core network.

[0065] One of the objectives of networks is to improve overall system security. One particular area of concern is security protection of NAS messages. In the embodiments described herein, a UE **110** and a network element **132** are enhanced to provide additional security protection of NAS messages.

[0066] FIG. **6** is a block diagram of a UE **110** in an illustrative embodiment. UE **110** includes a radio interface component **602**, one or more processors **604**, a memory **606**, a user interface component **608**, and a battery **610**. Radio interface component **602** is a hardware component that represents the local radio resources of UE **110**, such as an RF unit **620** (e.g., transceiver) and one or more antennas **622**, used for wireless communications with a base station (e.g., base station **124**) via radio or “over-the-air” signals. Processor **604** represents the internal circuitry, logic, hardware, software, etc., that provides the functions of UE **110**. Processor **604** may be configured to execute instructions **640** for software that are loaded into memory **606**. Processor **604** may comprise a set of one or more processors or may comprise a multi-processor core, depending on the particular implementation. Memory **606** is a computer readable storage medium for data, instructions **640**, applications, etc., and is accessible by processor **604**. Memory **606** is a hardware storage device capable of storing information on a temporary basis and/or a permanent basis. Memory **606** may comprise a random-access memory, or any other volatile or non-volatile storage device. User interface component **608** is a hardware component for interacting with an end user. For example, user interface component **608** may include a display **650**, screen, touch screen, or the like (e.g., a Liquid Crystal Display (LCD), a Light Emitting Diode (LED) display, etc.). User interface component **608** may include keyboard or keypad **652**, a tracking device (e.g., a trackball or trackpad), a speaker, a microphone, etc. UE **110** also includes a Universal Integrated Circuit Card (UICC) **660**, which is a hardware device that provides security and integrity functions for UE **110**. UICC **660** may host a Universal Subscriber Identity Module (USIM) **662** that stores or indicates one or more public keys for the HPLMN for UE **110** along with other credentials. UE **110** may include various other components not specifically illustrated in FIG. **6**.

[0067] Processor **604** may implement one or more applications **630**. These applications **630** may

access downlink (DL) data through RAN **120** and core network **130**, and may also generate uplink (UL) data for transfer to a destination through RAN **120** and core network **130**. Processor **604** also implements a NAS controller **634** that is configured to control NAS procedures, as is described in more detail below.

[0068] FIG. **7** is a block diagram of a network element **132** in an illustrative embodiment. Network element **132** is a server, device, apparatus, equipment (including hardware), system, means, etc., that handles security and registration for a UE. For example, network element **132** may comprise an MME **214** in an LTE network, an AMF element **314** of a next generation network, etc. In this embodiment, network element **132** includes the following subsystems: a network interface component **702**, a security manager **704**, and a registration manager **706** that operate on one or more platforms. Network interface component **702** may comprise circuitry, logic, hardware, means, etc., configured to exchange control plane messages or signaling with other network elements and/or UEs (e.g., through RAN **120**). Network interface component **702** may operate using a variety of protocols (including NAS protocol) or reference points. Security manager **704** may comprise circuitry, logic, hardware, means, etc., configured to handle authentication and/or security procedures for a UE, such as to create a NAS security context, select a NAS security algorithm(s) for a NAS security context, etc. Registration manager **706** may comprise circuitry, logic, hardware, means, etc., configured to handle registration for a UE.

[0069] One or more of the subsystems of network element **132** may be implemented on a hardware platform comprised of analog and/or digital circuitry. One or more of the subsystems of network element **132** may be implemented on a processor **730** that executes instructions stored in memory **732**. Processor **730** comprises an integrated hardware circuit configured to execute instructions, and memory **732** is a non-transitory computer readable storage medium for data, instructions, applications, etc., and is accessible by processor **730**.

[0070] Network element **132** may include various other components not specifically illustrated in FIG. **7**.

[0071] A NAS procedure may be performed or invoked when a NAS security context already exists between a UE and an Access Security Management Entity (e.g., AMF, MME, etc.). The purpose of NAS security is to securely deliver NAS messages between the UE and the Access Security Management Entity in the control plane using NAS security keys. The NAS security keys are generated each time authentication is performed for a UE. After the NAS security setup is completed, the UE and the Access Security Management Entity get to share a NAS encryption key and a NAS integrity key, which are used in encryption and integrity protection, respectively, of NAS messages before transmitting. A NAS procedure may also be performed or invoked when no NAS security context exists. This scenario is described first.

EXAMPLE 1

No Security Context

[0072] FIG. **8** is a flow chart illustrating a method **800** of performing a NAS procedure in UE **110** in an illustrative embodiment. The steps of method **800** will be described with reference to UE **110** in FIG. **6**, but those skilled in the art will appreciate that method **800** may be performed in other networks or architectures. Also, the steps of the flow charts described herein are not all inclusive and may include other steps not shown, and the steps may be performed in an alternative order.

[0073] It may be assumed for this embodiment that there is no NAS communication session between UE **110** and network element **132**. It may be further assumed that UE **110** is in a non-connected mode (e.g., idle mode), and is transitioning to connected mode. NAS controller **634** in UE **110** initiates a NAS procedure to establish a NAS communication session between UE **110** and network element **132** (step **802**). For example, the NAS procedure may comprise a registration procedure. Each NAS procedure includes a set of mandatory NAS protocol IEs, and may also include a set of optional NAS protocol IEs for transmitting information. Thus, NAS controller **634** may identify the NAS protocol IEs (mandatory and optional) for the NAS procedure.

[0074] In this embodiment, the NAS procedure is performed in multiple phases **831-832**. For the first phase **831** of the NAS procedure, NAS controller **634** identifies a subset of NAS protocol IEs that are designated for security-related handling (step **804**). The subset of NAS protocol IEs designated for security-related handling refers to the IEs used to create or establish a NAS security context for a UE. It may be desirable to provide minimal information in the first phase **831**, so the subset of NAS protocol IEs may include a minimum number of IEs for the NAS procedure that are used to establish a NAS security context. For a registration procedure, in one example, the subset of NAS protocol IEs may consist of a mobile identity for the LE (e.g., 5G-GUTI or Subscription Concealed).

[0075] Identifier (SUCI)), a UE security capability indicating one or more security algorithms supported by the UE, a registration type (e.g., initial, mobility, periodic, emergency, etc.), and a security key set identifier for a NAS security context of the UE (e.g., ngKSI, eKSI, etc.).

[0076] NAS controller **634** may format or generate an initial NAS message for the NAS procedure, such as a registration request of type “initial” An initial NAS message refers to the first NAS message that is sent after a UE transitions from a non-connected mode (e.g., idle mode) to a connected mode. NAS controller **634** includes or inserts the subset of NAS protocol IEs in the initial NAS message (step **806**). In the first phase **831**, the initial NAS message is populated with the subset of NAS protocol IEs, and the IEs that are populated in the initial NAS message are limited to (i.e., consists only or exclusively of) the subset of NAS protocol IEs that are selected for security-related handling. Because the initial NAS message does not include all of the mandatory NAS protocol IEs for the NAS procedure, the initial NAS message is considered a “partial” message in the first phase **831**. The other mandatory NAS protocol IEs that are excluded from the subset will be included in another NAS message (as part of the second phase **832**). NAS controller **634** then sends the initial NAS message to network element **132** (step **810**).

[0077] Before sending the initial NAS message, NAS controller **634** may optionally encrypt the subset of NAS protocol IEs in the initial NAS message using a public key of the HPLMN for UE **110** (optional step **808**). Each HPLMN may assign public keys according to the Elliptic Curve Integrated Encryption Scheme (ECIES). Depending on the protection scheme, there may be multiple public keys. The public keys of the HPLMN are typically provisioned on USIM **662** of UE **110**. Thus, NAS controller **634** is able to encrypt the subset of NAS protocol IEs identified for the first phase **831** in the initial NAS message. A decision on whether or not to encrypt the subset of NAS protocol IEs using the public key may be based on a policy or criteria. For example, NAS controller **634** may encrypt the subset of NAS protocol IEs when the registration type does not indicate an emergency (e.g., registration type=initial), and may send the initial NAS message without encryption when the registration type indicates an emergency. In another example, NAS controller **634** may encrypt the subset of NAS protocol IEs when UE **110** has the public key programmed on its USIM **662**, and may send the initial NAS message without encryption when UE **110** does not have the public key programmed on USIM **662**.

[0078] FIG. **9** is a flow chart illustrating a method **900** of performing a NAS procedure in a network element **132** in an illustrative embodiment. The steps of method **900** will be described with reference to network element **132** in FIG. **7**, but those skilled in the art will appreciate that method **900** may be performed in other networks or architectures.

[0079] For the first phase **831**, network interface component **702** of network element **132** receives the initial NAS message from UE **110** (step **902**). After receiving the initial NAS message, security manager **704** may optionally process the initial NAS message to determine whether information is encrypted using the public key of the HPLMN. When the initial NAS message is encrypted, security manager **704** may initiate decryption of the subset of NAS protocol IEs in the initial NAS message (optional step **904**). In one example, security manager **704** may be configured to decrypt the subset of NAS protocol IEs internally. In another example, security manager **704** may send the subset of NAS protocol IEs to another network element (e.g., a UDM element **312**) to decrypt the

subset of NAS protocol IEs.

[0080] Security manager **704** processes the subset of NAS protocol IEs, and determines that no NAS security context exists for UE **110** (step **906**). Because no NAS security context exists, security manager **704** may initiate an authentication procedure to authenticate UE **110** (step **908**). The authentication procedure (e.g., Authentication and Key Agreement (AKA)) is used to perform mutual authentication between UE **110** and mobile network **100**. Although authentication procedures may vary, in general, security manager **704** may send an authentication request to UE **110** along with an authentication token (optional step **910**) through network interface component **702**. In response to the authentication request, UE **110** handles authentication steps on its end, and attempts to validate the authentication token (see step **812** of FIG. **8**). If successful, UE **110** considers mobile network **100** to be authenticated. UE **110** computes a response token, and sends an authentication response with the response token, which is received by security manager **704** (optional step **912**) through network interface component **702**. Security manager **704** (or another network element) may then determine whether the response token is valid (e.g., compare the response token with an expected response token). If the response token is valid, then security manager **704** considers UE **110** authenticated.

[0081] With UE **110** validated, security manager **704** initiates a NAS security procedure to establish a NAS security context (step **914**). For the NAS security procedure, security manager **704** selects one or more NAS security algorithms for the NAS security context (step **916**), and derives one or more NAS security keys (e.g., KAMF, KASME, etc.). A NAS security algorithm may include a NAS ciphering algorithm and integrity protection algorithm. Security manager **704** then sends a response to UE that indicates or includes the NAS security algorithm(s) and a security key set identifier selected for the NAS security context (step **918**) through network interface component **702**. The response may comprise a Security Mode Command that includes the NAS security algorithm(s), a security key set identifier (e.g., ngKSI, eKSI, etc.), and other information.

[0082] In FIG. **8**, NAS controller **634** of UE **110** receives the response from network element **132** that indicates the NAS security algorithm(s) and security key set identifier (step **814**). With the information provided in the response from network element **132**, a NAS security context is established between UE **110** and network element **132**. Thus, subsequent NAS messages between UE **110** and network element **132** may be secured using the NAS security context.

[0083] For the second phase **832** of the NAS procedure, NAS controller **634** includes or inserts the NAS protocol IEs for the NAS procedure in the initial NAS message (step **816**). The initial NAS message is a copy, duplicate, or same type of initial NAS message that was previously sent to network element **132** in the first phase **831**. In this step, the initial NAS message includes the entire set of NAS protocol IEs for the NAS procedure (mandatory and optional (if desired)). Because the initial NAS message includes each of the mandatory NAS protocol IEs for the NAS procedure, the initial NAS message is considered a “complete” NAS message in the second phase **832**.

[0084] NAS controller **634** of UE **110** may format or generate a subsequent NAS message for the NAS procedure. For example, the subsequent NAS message may comprise a Security Mode Complete message. NAS controller **634** includes or inserts the initial NAS message in a NAS message container of the subsequent NAS message (step **818**). A NAS message container is a type of IE used to encapsulate a plain NAS message. NAS controller **634** encrypts the NAS message container of the subsequent NAS message using the NAS security algorithm(s) (step **820**). Thus, the complete initial NAS message is encrypted in the NAS message container of the subsequent NAS message. NAS controller **634** then sends the subsequent NAS message to network element **132** (step **822**).

[0085] In FIG. **9**, for the second phase **832**, network interface component **702** receives the subsequent NAS message from UE **110** (step **920**). Security manager **704** decrypts the NAS message container of the subsequent NAS message using the NAS security algorithm(s) (step **922**) to access the complete initial NAS message. Security manager **704** or other subsystems of network

element **132** may then process the NAS protocol IEs from the complete initial NAS message to further perform the NAS procedure. For example, registration manager **706** may send a registration accept message to UE **110**, and receive a registration complete message from UE **110** (optional step **924**). One technical benefit of this process is that only the NAS protocol IEs that are needed to establish a NAS security context are sent as unencrypted or encrypted according to the HPLMN public key in a partial initial NAS message, while a complete initial NAS message is encrypted in a subsequent NAS message, which provides further security protection.

[0086] FIG. **10** is a message diagram showing a NAS procedure when a UE has no security context in an illustrative embodiment. The NAS procedure shown in FIG. **10** is a registration procedure, but similar concepts may apply to other NAS procedures. This example is shown in FIG. **10** as a network, with network element **132** comprising an AMF element **314**.

[0087] This NAS procedure is again performed in multiple phases. For the first phase, UE **110** generates or formats an initial registration request for a NAS registration procedure. The NAS registration procedure has a set of NAS protocol IEs (mandatory and optional) that are used to transfer information. In this embodiment, UE **110** does not populate the initial registration request with a full set of NAS protocol IEs in the first phase. Instead, UE **110** identifies the NAS protocol IEs that are essential for establishing a NAS security context. Thus, UE **110** identifies a subset of the NAS protocol IEs that are designated for security-related handling. In this example, the subset of NAS protocol IEs may consist of a 5G Globally Unique Temporary Identity (5G-GUTI), the UE security capability, registration type, and ngKSI. UE **110** inserts the subset of NAS protocol IEs in the initial registration request. Because the initial registration request does not include all of the mandatory NAS protocol IEs for the NAS registration procedure, the initial registration request is a “partial” request in the first phase. UE **110** may also insert other information in the initial registration request, such as the SUCI generated by UE **110**. In this example, UE **110** encrypts the subset of NAS protocol IEs using the HPLMN public key, and sends the initial registration request to AMF element **314** (S1). The protection scheme and public key identifier used for encryption is the same as the protection scheme and public key identifier indicated in the SUCI. However, as was described above, encryption of the subset of NAS protocol IEs using the HPLMN public key is optional. If the protection scheme of SUCI is NULL, then the subset of NAS protocol IEs is not encrypted.

[0088] In response to receiving the initial registration request, AMF element **314** routes the information to the UE's home UDM for decrypting based on UE's PLMN ID and Routing ID. Thus, AMF element **314** formats or generates an authentication request (i.e., Nausf_UEAuthentication_Authenticate Request), and inserts the encrypted subset of NAS protocol IEs in the authentication request, along with other information (e.g., SUCI and serving network name). AMF element **314** then sends the authentication request to AUSF element **310** (S2). In response to receiving the authentication request, AUSF element **310** formats or generates an authentication request (i.e., Nudm_UEAuthentication_Get Request), and inserts the encrypted subset of NAS protocol IEs in the authentication request, along with other information. AUSF element **310** then sends the authentication request to UDM element **312** (S3).

[0089] In response to the authentication request, UDM element **312** decrypts the subset of NAS protocol IEs using the HPLMN private key (i.e., using the information according to the protection scheme selected for SUCI) so that the subset of NAS protocol IEs are readable. UDM element **312** also hosts functions related to the Authentication Credential Repository and Processing Function (ARPF), which selects an authentication method and computes the authentication data and keying materials (e.g., tokens) for the AUSF element **310** (if needed). UDM element **312** formats or generates an authentication response (i.e., Nudm_UEAuthentication_Get Response) for AUSF element **310**, and inserts the decrypted subset of NAS protocol IEs, the authentication vector (AV), and other information in the authentication response. UDM element **312** then sends the authentication response to AUSF element **310** (S4). In response to receiving the authentication

response. AUSF element **310** formats or generates an authentication response (i.e., Nausf_UEAuthentication_Authenticate Response) for AMF element **314**, and inserts the decrypted subset of NAS protocol IEs, the AV, and other information in the authentication response. AUSF element **310** then sends the authentication response to AMF element **314** (S5).

[0090] AMF element **314** is configured to perform an authentication procedure with UE **110** using information provided by UDM/AUSF. For example, AMF element **314** sends an authentication request to UE **110** along with an authentication token (S6) from the AV, and UE **110** attempts to validate the authentication token. If successful, UE **110** computes a response token, and sends an authentication response with the response token, which is received by AMF element **314** (S7). AMF element **314** formats or generates another authentication request (i.e., Nausf_UEAuthentication_Authenticate Request), and inserts the response token from UE **110** in the authentication request, along with other information. AMF element **314** then sends the authentication request to AUSF element **310** (S8). AUSF element **310** verifies whether the response token from UE **110** matches an expected response token, and sends an authentication response (i.e., Nausf_UEAuthentication_Authenticate Response) to AMF element **314** indicating success/failure of the authentication.

[0091] When UE **110** is authenticated to the network. AMF element **314** initiates a NAS security procedure to establish a NAS security context. AMF element **314** selects a NAS security algorithm (or multiple algorithms) for ciphering and integrity protection. AMF element **314** formats or generates a Security Mode Command message, and inserts an indicator of the NAS security algorithm(s), the ngKSI, and other information in the Security Mode Command message. AMF element **314** then sends the Security Mode Command message to UE **110** (S10).

[0092] For the second phase of the NAS procedure, UE **110** uses the ngKSI and NAS security algorithm to derive corresponding keys for protecting subsequent NAS messages. A NAS security context is therefore established between UE **110** and AMF element **314**. UE **110** includes or inserts the NAS protocol IEs for NAS registration procedure in the initial registration request, which is a copy, duplicate, or same type of message as the initial registration request previously sent in the first phase. The initial registration request includes all of the mandatory NAS protocol IEs, and any optional NAS protocol IEs that are used to transfer information. The additional NAS protocol IEs may include: Non-current native NAS key set identifier, 5G Mobility Management (MM) capability, Requested Network Slice Selection Assistance Information (NSSAI), last visited registered Tracking Area Identifier (TAI), S1 UE network capability, uplink data status, PDU session status, Mobile Initiated Connection Only (MICO) indication. UE status, additional GUTI, allowed PDU session status. UE's usage setting, requested Discontinuous Reception (DRX) parameters, EPS NAS message container, and payload container. Thus, the initial registration request is a “complete” request in the second phase, as it includes all of the mandatory NAS protocol IEs. UE **110** formats or generates a Security Mode Complete message, and inserts the complete initial registration request in a NAS message container of the Security Mode Complete message. UE **110** encrypts the NAS message container of the Security Mode Complete message using the NAS security algorithm of the NAS security context. Thus, the complete initial registration request is encrypted in the NAS message container of the Security Mode Complete message. UE **110** then sends the Security Mode Complete message to AMF element **314** (S1).

[0093] AMF element **314** receives the Security Mode Complete message from UE **110**, and decrypts the NAS message container of the Security Mode Complete message to access the NAS protocol IEs from the complete initial registration request. AMF element **314** then continues with the registration procedure, such as by sending a registration accept message to UE **110** (S12). UE **110** replies to AMF element **314** with a registration complete message (S13), at which point UE **110** is registered with the network to access services.

EXAMPLE 2

No Security Context

[0094] In another example of a NAS procedure when no security context exists, FIG. 11 is a flow chart illustrating a method **1100** of performing a NAS procedure in UE **110** in an illustrative embodiment. NAS controller **634** in UE **110** initiates a NAS procedure to establish a NAS communication session between UE **110** and network element **132** (step **1102**). NAS controller **634** identifies the NAS protocol IEs (mandatory and optional) for the NAS procedure (step **1104**). NAS controller **634** may format or generate a first initial

NAS message for the NAS procedure, and includes or inserts the NAS protocol IEs in the first initial NAS message (step **1106**). In this step, the first initial NAS message includes the entire set of NAS protocol IEs for the NAS procedure (mandatory and optional (if desired)). Because the first initial NAS message includes each of the mandatory NAS protocol IEs for the NAS procedure, the first initial NAS message is considered a “complete” NAS message.

[0096] NAS controller **634** also formats or generates a second initial NAS message that is a duplicate of the first initial NAS message (step **1108**). A duplicate message refers to a message of the same type for a NAS procedure. For example, if the first initial NAS message is a registration request, then the second initial NAS message is also a registration request. However, the IEs that are populated in the duplicate message may be different than the original message. NAS controller **634** includes or inserts the first initial NAS message in a NAS message container of the second initial NAS message (step **1110**). NAS controller **634** encrypts the NAS message container of the second initial NAS message using a public key of the HPLMN for UE **110** (step **1112**). Thus, the complete first initial NAS message is encrypted in the NAS message container of the second initial NAS message. NAS controller **634** then sends the second initial NAS message to network element **132** (step **1114**).

[0097] FIG. 12 is a flow chart illustrating a method **1200** of performing a NAS procedure in a network element **132** in an illustrative embodiment. Network interface component **702** of network element **132** receives the second initial NAS message from UE **110** (step **1202**). When the NAS message container is encrypted as in this example, security manager **704** initiates decryption of the NAS message container (step **1204**) to access the first initial NAS message. In one example, security manager **704** may be configured to decrypt the NAS message container. In another example, security manager **704** may send the NAS message container to another network element (e.g., a UDM element **312**) to decrypt the NAS message container.

[0098] With the NAS message container decrypted, security manager **704** has access to the first initial NAS message. The first initial NAS message is populated with the NAS protocol IEs for the NAS procedure. Security manager **704** may process the NAS protocol IEs, and determine that no NAS security context exists for UE **110** (step **1206**). Because no NAS security context exists, security manager **704** may initiate an authentication procedure to authenticate UE **110** (step **1208**). For the authentication procedure, security manager **704** may send an authentication request to UE **110** along with an authentication token (optional step **1210**) through network interface component **702**. In response to the authentication request, UE **110** handles authentication steps on its end, and attempts to validate the authentication token (see step **1116** of FIG. 11). If successful, UE **110** considers mobile network **100** to be authenticated. UE **110** computes a response token, and sends an authentication response with the response token, which is received by security manager **704** (optional step **1212**) through network interface component **702**. Security manager **704** (or another network element) may then determine whether the response token is valid (e.g., compare the response token with an expected response token). If the response token is valid, then security manager **704** considers UE **110** authenticated.

[0099] With UE **110** validated, security manager **704** initiates a NAS security procedure to establish a NAS security context (step **1214**). For the NAS security procedure, security manager **704** selects one or more NAS security algorithms for the NAS security context (step **1216**), and derives one or more NAS security keys (e.g., KAMF, KASME, etc.). Security manager **704** then formats or generates a Security Mode Command, and sends the Security Mode Command to UE

110 that indicates or includes the NAS security algorithm(s) and security key set identifier selected for the NAS security context (step **1218**) through network interface component **702**.

[0100] In FIG. **11**, NAS controller **634** of UE **110** receives the Security Mode Command from network element **132** that indicates the NAS security algorithm(s) (step **1118**). With the information provided in the Security Mode Command, a NAS security context is established between UE **110** and network element **132**. Thus, subsequent NAS messages between UE **110** and network element **132** may be secured using the NAS security context. NAS controller **634** of UE **110** may then format or generate a Security Mode Complete message, and send the Security Mode Complete message to network element **132** (step **1120**). In FIG. **12**, network interface component **702** receives the Security Mode Complete from UE **110** (step **1220**). Security manager **704** may decrypt any subsequent NAS messages using the NAS security algorithm(s). One technical benefit of this process is that only the NAS protocol IEs that are needed to establish a NAS security context are inserted as unencrypted in a partial initial NAS message, while a complete initial NAS message is encrypted in the partial initial NAS message, which provides further security protection.

[0101] FIG. **13** is a message diagram showing a NAS procedure when a UE has no security context in an illustrative embodiment. The NAS procedure shown in FIG. **13** is a registration procedure, but similar concepts may apply to other NAS procedures. UE **110** generates or formats a registration request for a NAS registration procedure. In this embodiment, UE **110** populates the registration request with a full set of NAS protocol IEs. Thus, the registration request is a complete registration request.

[0102] UE **110** also generates or formats another registration request that is a duplicate of the complete registration request. The other registration request is of type “initial”, and is therefore an initial registration request. Instead of populating each of the mandatory NAS protocol IEs in the complete registration request. UE **110** inserts the complete registration request in a NAS message container of the initial registration request. UE **110** may also insert other information in the initial registration request, such as the SUCI generated by UE **110**. In this example, UE **110** encrypts the NAS message container of the initial registration request using the HPLMN public key, and sends the initial registration request to AMF element **314** (S1).

[0103] In response to receiving the initial registration request, AMF element **314** routes the information to the UE's home UDM for decrypting based on UE's PLMN ID and Routing ID). Thus, AMF element **314** formats or generates an authentication request (i.e., Nausf_UEAuthentication_Authenticate Request), and inserts the encrypted NAS message container of the initial registration request in the authentication request, along with other information. AMF element **314** then sends the authentication request to AUSF element **310** (S2). In response to receiving the authentication request, AUSF element **310** formats or generates an authentication request (i.e., Nudm_UEAuthentication_Get Request), and inserts the encrypted NAS message container in the authentication request, along with other information. AUSF element **310** then sends the authentication request to UDM element **312** (S3).

[0104] In response to the authentication request, UDM element **312** decrypts the encrypted NAS message container using the HPLMN private key so that the complete registration request is readable. UDM element **312** also selects an authentication method and computes the authentication data and keying materials (e.g., tokens) for the AUSF element **310** (if needed). UDM element **312** formats or generates an authentication response (i.e., Nudm_UEAuthentication_Get Response) for AUSF element **310**, and inserts the decrypted NAS message container, the authentication vector (AV), and other information in the authentication response. UDM element **312** then sends the authentication response to AUSF element **310** (S4). In response to receiving the authentication response, AUSF element **310** formats or generates an authentication response (i.e., Nausf_UEAuthentication_Authenticate Response) for AMF element **314**, and inserts the decrypted NAS message container, the AV, and other information in the authentication response. AUSF element **310** then sends the authentication response to AMF element **314** (S5).

[0105] AMF element **314** is configured to perform an authentication procedure with UE **110** using information provided by UDM/AUSF. For example, AMF element **314** sends an authentication request to UE **110** along with an authentication token (S6) from the AV, and UE **110** attempts to validate the authentication token. If successful, UE **110** computes a response token, and sends an authentication response with the response token, which is received by AMF element **314** (S7). AMF element **314** formats or generates another authentication request (i.e., Nausf_UEAuthentication_Authenticate Request), and inserts response token from UE **110** in the authentication request, along with other information. AMF element **314** then sends the authentication request to AUSF element **310** (S8). AUSF element **310** verifies whether the response token from UE **110** matches an expected response token, and sends an authentication response (i.e., Nausf_UEAuthentication_Authenticate Response) to AMF element **314** indicating success/failure of the authentication.

[0106] When UE **110** is authenticated to the network. AMF element **314** initiates a NAS security procedure to establish a NAS security context. AMF element **314** selects a NAS security algorithm (or multiple algorithms) for ciphering and integrity protection. AMF element **314** formats or generates a Security Mode Command message, and inserts an indicator of the NAS security algorithm, the ngKSI, and other information in the Security Mode Command message. AMF element **314** then sends the Security Mode Command message to UE **110** (S10). UE **110** uses the ngKSI and NAS security algorithm to derive corresponding keys for protecting subsequent NAS messages. A security context is therefore established between UE **110** and AMF element **314**. UE **110** formats or generates a Security Mode Complete message, and sends the Security Mode Complete message to AMF element **314** (S11).

[0107] AMF element **314** continues with the registration procedure, such as by sending a registration accept message to UE **110** (S12). UE **110** replies to AMF element **314** with a registration complete message (S13), at which point UE **110** is registered with the network to access services.

EXAMPLE 3

Security Context Exists—Security Context is Valid

[0108] In further examples, a NAS procedure may be performed or invoked when a NAS security context already exists between a UE and an Access Security Management Entity (e.g., AMF, MME, etc.). The following provides examples of a NAS procedure when a NAS security context exists.

[0109] FIG. **14** is a flow chart illustrating a method **1400** of performing a NAS procedure in UE **110** in an illustrative embodiment. NAS controller **634** in UE **110** initiates a NAS procedure to establish (or re-establish) a NAS communication session between UE **110** and network element **132** (step **1402**). NAS controller **634** identifies a subset of the NAS protocol IEs that are designated for security-related handling (step **1404**). NAS controller **634** formats or generates a first NAS message for the NAS procedure, such as a registration request of type “mobility”, “periodic”, etc. NAS controller **634** includes or inserts the subset of NAS protocol IEs in the first NAS message (step **1406**).

[0110] NAS controller **634** also formats or generates a second NAS message that is a duplicate of the first NAS message. NAS controller **634** includes or inserts the NAS protocol IEs for the NAS procedure in the second NAS message (step **1408**). In this step, the second NAS message includes the entire set of NAS protocol IEs for the NAS procedure (mandatory and optional (if desired)). Because the second NAS message includes each of the mandatory NAS protocol IEs for the NAS procedure, the second NAS message is considered a “complete” NAS message.

[0111] NAS controller **634** includes or inserts the second NAS message in a NAS message container of the first NAS message (step **1410**). NAS controller **634** encrypts the NAS message container of the first NAS message using a NAS security algorithm of the NAS security context (step **1412**). Thus, the complete second NAS message is encrypted in the NAS message container of the first NAS message. NAS controller **634** then sends the first NAS message to network

element **132** (step **1414**).

[0112] FIG. **15** is a flow chart illustrating a method **1500** of performing a NAS procedure in a network element **132** in an illustrative embodiment. Network interface component **702** of network element **132** receives the first NAS message from UE **110** (step **1502**). Security manager **704** processes the subset of NAS protocol IEs in the first NAS message to identify the NAS security context for UE **110** (step **1504**). Security manager **704** then decrypts the NAS message container of the first NAS message using the NAS security context to access the second NAS message contained in the NAS message container (step **1506**). With the NAS message container in the first NAS message decrypted, security manager **704** has access to the second NAS message as decrypted. The second NAS message is populated with the NAS protocol IEs for the NAS procedure. Thus, security manager **704** may process the NAS protocol IEs in the second NAS message to continue with further handling for the NAS procedure (step **1508**). One technical benefit of this process is that only the NAS protocol IEs that are needed to identify the NAS security context are sent as unencrypted in the first NAS message, while the complete second NAS message is encrypted in the first NAS message, which provides further security protection.

[0113] FIG. **16** is a message diagram showing a NAS registration procedure when a UE has a valid security context in an illustrative embodiment. UE **110** generates or formats a first registration request for a NAS registration procedure. In this embodiment, UE **110** populates the first registration request with a subset of NAS protocol IEs that are designated for security-related handling. This information is used to indicate a NAS security context to AMF element **314**. For example, the subset of NAS protocol IEs may include a 5G-GUTI, a registration type, and an ngKSI. UE **110** also formats or generates a second registration request that is a duplicate of the first registration request. UE **110** includes or inserts the NAS protocol IEs for the NAS registration procedure in the second registration request. In this step, the second registration request includes the entire set of NAS protocol IEs for the NAS registration procedure (mandatory and optional (if desired)). Because the second registration request includes each of the mandatory NAS protocol IEs for the NAS registration procedure, the second registration request is considered a “complete” registration request.

[0114] UE **110** includes or inserts the second registration request in a NAS message container of the first registration request, and encrypts the NAS message container of the first registration request using a NAS security algorithm of the NAS security context. Thus, the complete second registration request is encrypted in the NAS message container of the first registration request. UE **110** then sends the first registration request to AMF element **314** (S1).

[0115] In response to receiving the first registration request. AMF element **314** identifies or retrieves the NAS security context based on the subset of NAS protocol IEs included in the first registration request. AMF element **314** then decrypts the encrypted NAS message container of the first registration request using the NAS security context so that the second registration request is readable. AMF element **314** is therefore able to process the entire set of NAS protocol IEs for the NAS registration procedure, and continue handling for the NAS registration procedure. For instance. AMF element **314** sends a registration accept message to UE **110** (S2). UE **110** replies to AMF element **314** with a registration complete message (S3), at which point UE **110** is registered with the network to access services.

[0116] FIG. **17** is a message diagram showing a NAS service request procedure when a UE has a valid security context in an illustrative embodiment. UE **110** generates or formats a first service request for the NAS service request procedure. In this embodiment, UE **110** populates the first service request with a subset of NAS protocol IEs that are designated for security-related handling, which is used to indicate a NAS security context to AMF element **314**. In this example, the subset of NAS protocol IEs may include a 5G-S-TMSI and an ngKSI. UE **110** also formats or generates a second service request that is a duplicate of the first service request. UE **110** includes or inserts the NAS protocol IEs for the NAS service request procedure in the second service request. In this step,

the second service request includes the entire set of NAS protocol IEs for the NAS service request procedure (mandatory and optional (if desired)). Because the second service request includes each of the mandatory NAS protocol IEs for the NAS service request procedure, the second service request is considered a “complete” service request.

[0117] UE **110** includes or inserts the second service request in a NAS message container of the first service request, and encrypts the NAS message container of the first service request using a NAS security algorithm of the NAS security context. Thus, the complete second service request is encrypted in the NAS message container of the first service request. UE **110** then sends the first service request to AMF element **314** (S1).

[0118] In response to receiving the first service request, AMF element **314** identifies or retrieves the NAS security context based on the subset of NAS protocol IEs included in the first service request. AMF element **314** then decrypts the encrypted NAS message container of the first service request using the NAS security context so that the second service request is readable. AMF element **314** is therefore able to process the entire set of NAS protocol IEs for the NAS service request procedure, and continue handling for the NAS service request procedure. For instance, AMF element **314** sends a service accept message to UE **110** (S2).

[0119] FIG. **18** is a message diagram showing a NAS de-registration procedure when a UE has a valid security context in an illustrative embodiment. UE **110** generates or formats a first de-registration request for the NAS de-registration procedure. In this embodiment, UE **110** populates the first de-registration request with a subset of NAS protocol IEs that are designated for security-related handling, which is used to indicate a NAS security context to AMF element **314**. In this example, the subset of NAS protocol IEs may include a 5G-S-TMSI and an ngKSI. UE **110** also formats or generates a second de-registration request that is a duplicate of the first de-registration request. UE **110** includes or inserts the NAS protocol IEs for the NAS de-registration procedure in the second de-registration request. In this step, the second de-registration request includes the entire set of NAS protocol IEs for the NAS de-registration procedure (mandatory and optional (if desired)). Because the second de-registration request includes each of the mandatory NAS protocol IEs for the NAS de-registration procedure, the second de-registration request is considered a “complete” de-registration request.

[0120] UE **110** includes or inserts the second de-registration request in a NAS message container of the first de-registration request, and encrypts the NAS message container of the first de-registration request using a NAS security algorithm of the NAS security context. Thus, the complete second de-registration request is encrypted in the NAS message container of the first de-registration request. UE **110** then sends the first de-registration request to AMF element **314** (S1).

[0121] In response to receiving the first de-registration request, AMF element **314** identifies or retrieves the NAS security context based on the subset of NAS protocol IEs included in the first de-registration request. AMF element **314** then decrypts the encrypted NAS message container of the first de-registration request using the NAS security context so that the second de-registration request is readable. AMF element **314** is therefore able to process the entire set of NAS protocol IEs for the NAS de-registration procedure, and continue handling for the NAS de-registration procedure. For instance, AMF element **314** sends a de-registration accept message to UE **110** (S2).
EXAMPLE 4

Security Context Exists—Security Context is Invalid or Not Found

[0122] FIGS. **19A-19B** are a flow chart illustrating a method **1900** of performing a NAS procedure in UE **110** in an illustrative embodiment. NAS controller **634** in UE **110** initiates a NAS procedure to establish (or re-establish) a NAS communication session between UE **110** and network element **132** (step **1902**). For the first phase **1931** of the NAS procedure, NAS controller **634** identifies a subset of the NAS protocol IEs that are designated for security-related handling (step **1904**). NAS controller **634** formats or generates a first NAS message for the NAS procedure, and includes or inserts the subset of NAS protocol IEs in the first NAS message (step **1906**).

[0123] NAS controller **634** also formats or generates a second NAS message that is a duplicate of the first NAS message. NAS controller **634** includes or inserts the NAS protocol IEs for the NAS procedure in the second NAS message (step **1908**). In this step, the second NAS message includes the entire set of NAS protocol IEs for the NAS procedure (mandatory and optional (if desired)). Because the second NAS message includes each of the mandatory NAS protocol IEs for the NAS procedure, the second NAS message is considered a “complete” NAS message.

[0124] NAS controller **634** includes or inserts the second NAS message in a NAS message container of the first NAS message (step **1910**). NAS controller **634** encrypts the NAS message container of the first NAS message using a NAS security algorithm of the NAS security context (step **1912**). Thus, the complete second NAS message is encrypted in the NAS message container of the first NAS message. NAS controller **634** then sends the first NAS message to network element **132** (step **1914**).

[0125] FIG. **20** is a flow chart illustrating a method **2000** of performing a NAS procedure in a network element **132** in an illustrative embodiment. For the first phase **1931** of the NAS procedure, network interface component **702** of network element **132** receives the first NAS message from UE **110** (step **2002**). Security manager **704** processes the subset of NAS protocol IEs in the first NAS message, and fails to identify a valid NAS security context for UE **110** (step **2004**). For example, even though a NAS security context exists, security manager **704** may not be able to identify the NAS security context based on the subset of NAS protocol IEs provided in the first NAS message, the NAS security context identified based on the subset of NAS protocol IEs is invalid, etc. Because a valid NAS security context is not found, security manager **704** initiates an authentication procedure to authenticate UE **110** (step **2006**). Even though the authentication procedure may have been performed previously, security manager **704** performs an authentication procedure again when no valid NAS security context is found. As part of the authentication procedure, security manager **704** may send an authentication request to UE **110** along with an authentication token (optional step **2008**) through network interface component **702**. In response to the authentication request, UE **110** attempts to validate the authentication token (see step **1916** of FIG. **19A**). If successful, UE **110** considers mobile network **100** to be authenticated. UE **110** computes a response token, and sends an authentication response with the response token, which is received by security manager **704** (optional step **2010**) through network interface component **702**. Security manager **704** (or another network element) may then determine whether the response token is valid (e.g., compare the response token with an expected response token). If the response token is valid, then security manager **704** considers UE **110** authenticated. With UE **110** validated, security manager **704** initiates a NAS security procedure to establish a new NAS security context (step **2012**). For the NAS security procedure, security manager **704** selects one or more NAS security algorithms for the new NAS security procedure (step **2014**), and derives one or more NAS security keys. Security manager **704** then sends a response to UE **110** that indicates or includes the NAS security algorithm(s) and a security key set identifier selected for the new NAS security context (step **2016**) through network interface component **702**. The response may comprise a Security Mode Command that includes the NAS security algorithm(s), a security key set identifier (e.g., ngKSI, eKSI, etc.), and other information.

[0126] In FIG. **19A**, NAS controller **634** receives the response from network element **132** that indicates the NAS security algorithm(s) and security key set identifier (step **1918**). With the information provided in the response from network element **132**, the new NAS security context is established between UE **110** and network element **132**. Thus, subsequent NAS messages between UE **110** and network element **132** may be secured using the new NAS security context.

[0127] For the second phase **1932** of the NAS procedure in FIG. **19B**, NAS controller **634** of UE **110** may then format or generate a subsequent NAS message for the NAS procedure. For example, the subsequent NAS message may comprise a Security Mode Complete message. NAS controller **634** includes or inserts the second NAS message for the NAS procedure in a NAS message

container of the subsequent NAS message (step **1920**). As described above, the second NAS message includes the entire set of NAS protocol IEs for the NAS procedure (mandatory and optional (if desired)), and is considered a “complete” NAS message. NAS controller **634** encrypts the NAS message container of the subsequent NAS message using the NAS security algorithm(s) (step **1922**) of the new NAS security context. NAS controller **634** then sends the subsequent NAS message to network element **132** (step **1924**).

[0128] In FIG. **20**, for the second phase **1932**, network interface component **702** receives the subsequent NAS message from UE **110** (step **2018**). Security manager **704** decrypts the NAS message container of the subsequent NAS message using the NAS security algorithm(s) (step **2020**) of the new NAS security context to access the complete second NAS message. Security manager **704** or other subsystems of network element **132** may then process the NAS protocol IEs from the complete second NAS message to provide further handling for the NAS procedure. One technical benefit of this process is that only the NAS protocol IEs that are needed to identify the NAS security context are sent as unencrypted in the first NAS message. When a valid NAS security context is not found, a new NAS security context is established and a complete NAS message is encrypted in a subsequent NAS message according to the new NAS security context, which provides further security protection.

[0129] FIG. **21** is a message diagram showing a NAS registration procedure when a UE has a NAS security context but the NAS security context is not valid or is not found in an illustrative embodiment. For the first phase of the NAS procedure, UE **110** generates or formats a first registration request for a NAS registration procedure. In this embodiment, UE **110** populates the first registration request with a subset of NAS protocol IEs that are designated for security-related handling. This information is used to indicate the NAS security context to AMF element **314**. For example, the subset of NAS protocol IEs may include a 5G-GUTI, a registration type, and an ngKSI. UE **110** also formats or generates a second registration request that is a duplicate of the first registration request. UE **110** includes or inserts the NAS protocol IEs for the NAS registration procedure in the second registration request. In this step, the second registration request includes the entire set of NAS protocol IEs for the NAS registration procedure (mandatory and optional (if desired)). Because the second registration request includes each of the mandatory NAS protocol IEs for the NAS registration procedure, the second registration request is considered a “complete” registration request.

[0130] UE **110** includes or inserts the second registration request in a NAS message container of the first registration request, and encrypts the NAS message container of the first registration request using a NAS security algorithm of the NAS security context. Thus, the complete second registration request is encrypted in the NAS message container of the first registration request. UE **110** then sends the first registration request to AMF element **314** (S1).

[0131] In response to receiving the first registration request, AMF element **314** attempts to identify or retrieve the NAS security context based on the subset of NAS protocol IEs included in the first registration request. In this example, AMF element **314** is not able to identify a valid NAS security context for UE **110**. Thus, AMF element **314** is unable to decrypt the NAS message container of the first registration request. To allow for secure communications, AMF element **314** initiates a new authentication procedure to create a new NAS security context. AMF element **314** formats or generates an authentication request (i.e., Nausf UEAuthentication_Authenticate Request), and sends the authentication request to AUSF element **310** (S2). In response to receiving the authentication request, AUSF element **310** formats or generates an authentication request (i.e., Nudm_UEAuthentication_Get Request), and sends the authentication request to UDM element **312** (S3).

[0132] In response to the authentication request, UDM element **312** de-conceals the SUCI, and sends an authentication response (i.e., Nudm_UEAuthentication_Get Response) to AUSF element **310** (S4). In response to receiving the authentication response, AUSF element **310** formats or

generates an authentication response (i.e., Nausf_UEAuthentication_Authenticate Response) for AMF element **314**, and sends the authentication response to AMF element **314** (S5).

[0133] AMF element **314** is configured to perform an authentication procedure with UE **110** using information provided by UDM/AUSF. For example, AMF element **314** sends an authentication request to UE **110** along with an authentication token (S6), and UE **110** attempts to validate the authentication token. If successful, UE **110** computes a response token, and sends an authentication response with the response token, which is received by AMF element **314** (S7). AMF element **314** formats or generates another request authentication (i.e., Nausf_UEAuthentication_Authenticate Request), and inserts the response token from UE **110** in the authentication request, along with other information. AMF element **314** then sends the authentication request to AUSF element **310** (S8). AUSF element **310** verifies whether the response token from UE **110** matches an expected response token, and sends an authentication response (i.e., Nausf_UEAuthentication_Authenticate Response) to AMF element **314** indicating success/failure of the authentication.

[0134] When UE **110** is authenticated to the network, AMF element **314** initiates a NAS security procedure to establish the new NAS security context. AMF element **314** selects a NAS security algorithm (or multiple algorithms) for ciphering and integrity protection. AMF element **314** formats or generates a Security Mode Command message, and inserts an indicator of the NAS security algorithm, the ngKSI, and other information in the Security Mode Command message. AMF element **314** then sends the Security Mode Command message to UE **110** (S10).

[0135] For the second phase of the NAS procedure, UE **110** uses the ngKSI and NAS security algorithm to derive corresponding keys for protecting subsequent NAS messages. A new NAS security context is therefore established between UE **110** and AMF element **314**. UE **110** formats or generates a Security Mode Complete message, and inserts the second registration request in a NAS message container of the Security Mode Complete message. As described above, the second registration request includes the entire set of NAS protocol IEs for the NAS registration procedure (mandatory and optional (if desired)), and is considered a “complete” NAS message. UE **110** encrypts the NAS message container of the Security Mode Complete message using the NAS security algorithm of the new NAS security context. Thus, the second registration request is encrypted in the NAS message container of the Security Mode Complete message. UE **110** then sends the Security Mode Complete message to AMF element **314** (S11).

[0136] AMF element **314** receives the Security Mode Complete message from UE **110**, and decrypts the NAS message container of the Security Mode Complete message to access the NAS protocol IEs from the second registration request. AMF element **314** then continues with the NAS registration procedure, such as by sending a registration accept message to UE **110** (S12). UE **110** replies to AMF element **314** with a registration complete message (S13), at which point UE **110** is registered with the network to access services.

[0137] FIG. 22 is a message diagram showing a NAS service request procedure when a UE has a NAS security context but the NAS security context is not valid or is not found in an illustrative embodiment. For the first phase of the NAS procedure, UE **110** generates or formats a first service request for a NAS service request procedure. In this embodiment, UE **110** populates the first service request with a subset of NAS protocol IEs that are designated for security-related handling. This information is used to indicate the NAS security context to AMF element **314**. For example, the subset of NAS protocol IEs may include a 5G-S-TMSI and an ngKSI. UE **110** also formats or generates a second service request that is a duplicate of the first service request. UE **110** includes or inserts the NAS protocol IEs for the NAS service request procedure in the second service request. In this step, the second service request includes the entire set of NAS protocol IEs for the NAS service request procedure (mandatory and optional (if desired)). Because the second service request includes each of the mandatory NAS protocol IEs for the NAS service request procedure, the second service request is considered a “complete” service request.

[0138] UE **110** includes or inserts the second service request in a NAS message container of the

first service request, and encrypts the NAS message container of the first service request using a NAS security algorithm of the NAS security context. Thus, the complete second service request is encrypted in the NAS message container of the first service request. UE **110** then sends the first service request to AMF element **314** (S1).

[0139] In response to receiving the first service request, AMF element **314** attempts to identify or retrieve the NAS security context based on the subset of NAS protocol IEs included in the first service request. In this example, AMF element **314** is not able to identify a valid NAS security context for UE **110**. Thus, AMF element **314** is unable to decrypt the NAS message container of the first service request. To allow for secure communications, AMF element **314** initiates a new authentication procedure to create a new NAS security context. AMF element **314** formats or generates an authentication request (i.e., Nausf_UEAuthentication_Authenticate Request), and sends the authentication request to AUSF element **310** (S2). In response to receiving the authentication request, AUSF element **310** formats or generates an authentication request (i.e., Nudm_UEAuthentication_Get Request), and sends the authentication request to UDM element **312** (S3).

[0140] In response to the authentication request, UDM element **312** de-conceals the SUCI, and sends an authentication response (i.e., Nudm_UEAuthentication_Get Response) to AUSF element **310** (S4). In response to receiving the authentication response, AUSF element **310** formats or generates an authentication response (i.e., Nausf_UEAuthentication_Authenticate Response) for AMF element **314**, and sends the authentication response to AMF element **314** (S5).

[0141] AMF element **314** is configured to perform an authentication procedure with UE **110** using information provided by UDM/AUSF. For example, AMF element **314** sends an authentication request to UE **110** along with an authentication token (S6), and UE **110** attempts to validate the authentication token. If successful, UE **110** computes a response token, and sends an authentication response with the response token, which is received by AMF element **314** (S7). AMF element **314** formats or generates another authentication request (i.e., Nausf_UEAuthentication_Authenticate Request), and inserts the response token from UE **110** in the authentication request, along with other information. AMF element **314** then sends the authentication request to AUSF element **310** (S8). AUSF element **310** verifies whether the response token from UE **110** matches an expected response token, and sends an authentication response (i.e., Nausf_UEAuthentication_Authenticate Response) to AMF element **314** indicating success/failure of the authentication.

[0142] When UE **110** is authenticated to the network, AMF element **314** initiates a NAS security procedure to establish the new NAS security context. AMF element **314** selects a NAS security algorithm (or multiple algorithms) for ciphering and integrity protection. AMF element **314** formats or generates a Security Mode Command message, and inserts an indicator of the NAS security algorithm, the ngKSI, and other information in the Security Mode Command message. AMF element **314** then sends the Security Mode Command message to UE **110** (S10).

[0143] For the second phase of the NAS procedure, UE **110** uses the ngKSI and NAS security algorithm to derive corresponding keys for protecting subsequent NAS messages. A new NAS security context is therefore established between UE **110** and AMF element **314**. UE **110** formats or generates a Security Mode Complete message, and inserts the second service request in a NAS message container of the Security Mode Complete message. As described above, the second service request includes the entire set of NAS protocol IEs for the NAS service request procedure (mandatory and optional (if desired)), and is considered a “complete” NAS message. UE **110** encrypts the NAS message container of the Security Mode Complete message using the NAS security algorithm of the new NAS security context. Thus, the second service request is encrypted in the NAS message container of the Security Mode Complete message. UE **110** then sends the Security Mode Complete message to AMF element **314** (S11).

[0144] AMF element **314** receives the Security Mode Complete message from UE **110**, and decrypts the NAS message container of the Security Mode Complete message to access the NAS

protocol IEs from the second service request. AMF element **314** then continues with the NAS service request procedure, such as by sending a registration accept message to UE **110** (S12). UE **110** replies to AMF element **314** with a registration complete message (S13).

[0145] Any of the various elements or modules shown in the figures or described herein may be implemented as hardware, software, firmware, or some combination of these. For example, an element may be implemented as dedicated hardware. Dedicated hardware elements may be referred to as “processors”, “controllers”, or some similar terminology. When provided by a processor, the functions may be provided by a single dedicated processor, by a single shared processor, or by a plurality of individual processors, some of which may be shared. Moreover, explicit use of the term “processor” or “controller” should not be construed to refer exclusively to hardware capable of executing software, and may implicitly include, without limitation, digital signal processor (DSP) hardware, a network processor, application specific integrated circuit (ASIC) or other circuitry, field programmable gate array (FPGA), read only memory (ROM) for storing software, random access memory (RAM), non-volatile storage, logic, or some other physical hardware component or module.

[0146] Also, an element may be implemented as instructions executable by a processor or a computer to perform the functions of the element. Some examples of instructions are software, program code, and firmware. The instructions are operational when executed by the processor to direct the processor to perform the functions of the element. The instructions may be stored on storage devices that are readable by the processor. Some examples of the storage devices are digital or solid-state memories, magnetic storage media such as a magnetic disks and magnetic tapes, hard drives, or optically readable digital data storage media.

[0147] As used in this application, the term “circuitry” may refer to one or more or all of the following: [0148] (a) hardware-only circuit implementations (such as implementations in only analog and/or digital circuitry); [0149] (b) combinations of hardware circuits and software, such as (as applicable): [0150] (i) a combination of analog and/or digital hardware circuit(s) with software/firmware; and [0151] (ii) any portions of hardware processor(s) with software (including digital signal processor(s)), software, and memory (ies) that work together to cause an apparatus, such as a mobile phone or server, to perform various functions); and [0152] (c) hardware circuit(s) and or processor(s), such as a microprocessor(s) or a portion of a microprocessor(s), that requires software (e.g., firmware) for operation, but the software may not be present when it is not needed for operation.

[0153] This definition of circuitry applies to all uses of this term in this application, including in any claims. As a further example, as used in this application, the term circuitry also covers an implementation of merely a hardware circuit or processor (or multiple processors) or portion of a hardware circuit or processor and its (or their) accompanying software and/or firmware. The term circuitry also covers, for example and if applicable to the particular claim element, a baseband integrated circuit or processor integrated circuit for a mobile device or a similar integrated circuit in server, a cellular network device, or other computing or network device.

[0154] Although specific embodiments were described herein, the scope of the disclosure is not limited to those specific embodiments. The scope of the disclosure is defined by the following claims and any equivalents thereof.

Claims

1. A User Equipment (UE) comprising: at least one processor; and at least one memory storing instructions therein that, when executed by the at least one processor, cause the UE to perform at least: (i) in an instance in which a Non-Access Stratum (NAS) security context exists between the UE and an Access and Mobility Management Function (AMF) in a mobile network, initiating a NAS procedure to establish a NAS communication session between the UE and the mobile

network by causing the UE to perform: (a) identifying, from among a full set of NAS protocol Information Elements (IEs) used for the NAS procedure, a subset of NAS protocol IEs that are designated for security-related handling for the NAS procedure; (b) inserting, into a first NAS message, the subset of NAS protocol IEs that are designated for security-related handling for the NAS procedure; (c) inserting, into a NAS message container of the first NAS message, a second NAS message, the second NAS message containing therein the full set of NAS protocol IEs, the full set of NAS protocol IEs in the second NAS message including the subset of NAS protocol IEs designated for security-related handling for the NAS procedure and one or more additional NAS protocol IEs; (d) encrypting, using a NAS security algorithm of the NAS security context, the NAS message container; and (e) sending the first NAS message to the AMF; and (ii) in an instance in which no NAS security context exists for the UE, initiating the NAS procedure in multiple phases to establish the NAS communication session between the UE and the AMF in the mobile network by, (a) for a first phase: identifying, from among a full set of NAS protocol IEs used for the NAS procedure, a subset of NAS protocol IEs that consists only of NAS protocol IEs that are designated for security-related handling for the NAS procedure; inserting, into a first NAS message, the subset of NAS protocol IEs that consists only of NAS protocol IEs that are designated for security-related handling for the NAS procedure; sending the first NAS message to the AMF; and receiving, from the AMF, a response that indicates a NAS security algorithm and a security key set identifier associated with a NAS security context for use by the UE, and (b) for a second phase: inserting, into a second NAS message, the full set of NAS protocol IEs used in the NAS procedure, the full set of NAS protocol IEs including the subset of NAS protocol IEs that consists only of NAS protocol IEs designated for security-related handling for the NAS procedure and one or more additional NAS protocol IEs, wherein a type of the second NAS message is a same type as the type of the first NAS message; inserting, into a NAS message container of a subsequent NAS message, the second NAS message; encrypting the NAS message container of the subsequent NAS message using the NAS security algorithm; and sending the subsequent NAS message to the AMF.

2. The UE of claim 1, wherein the instructions stored in the at least one memory, when executed by the at least one processor, cause the UE to perform, during the first phase of the NAS procedure, the generating the first initial NAS message by further causing the UE to perform: encrypting, using a public key of a Home Public Land Mobile Network (HPLMN) for the UE, the subset of NAS protocol IEs that consists only of NAS protocol IEs that are designated for security-related handling.

3. The UE of claim 2, wherein the instructions stored in the at least one processor, when executed by the at least one processor, further cause the UE to perform: in an instance in which a public key is programmed on a Universal Mobile Telecommunications System (UMTS) Subscriber Identity Module (USIM) of the UE, encrypting, using the public key programmed on the USIM of the UE, the subset of NAS protocol IEs in the first NAS message that consists only of NAS protocol IEs designated for security-related handling for the NAS procedure before sending the first NAS message to the AMF; and in an instance in which a public key is not programmed on the USIM of the UE, refraining from encrypting the subset of NAS protocol IEs in the first NAS message before sending the first NAS message to the AMF.

4. The UE of claim 1, wherein the first NAS message comprises a registration request message and, in an instance in which no NAS security context exists between the UE and the AMF in the mobile network, the subset of NAS protocol IEs that consists only of NAS protocol IEs designated for security-related handling comprises one or more of: a mobile identity for the UE, a UE security capability indicating one or more NAS security algorithms supported by the UE, a registration type associated with the registration request message, or a security key set identifier for a NAS security context.

5. The UE of claim 4, wherein the instructions stored in the at least one processor, when executed by the at least one processor, further cause the UE to perform: in an instance in which the

registration type associated with the registration request message indicates a non-emergency, encrypting the subset of NAS protocol IEs in the first NAS message using a public key of the HPLMN for the UE; and in an instance in which the registration type associated with the registration request message indicates an emergency, refraining from encrypting the subset of NAS protocol IEs in the first NAS message.

6. The UE of claim 1, wherein the response comprising the NAS security algorithm and the security key set identifier is a security mode command message, and wherein the subsequent NAS message is a security mode complete message.

7. An Access and Mobility Management Function (AMF) configured for communicating in a mobile network, the AMF comprising: at least one processor; and at least one memory comprising instructions stored therein that, when executed by the at least one processor, cause the AMF to perform at least: (i) in an instance in which a Non-Access Stratum (NAS) security context exists between the AMF and a user equipment (UE) performing a NAS procedure to establish a NAS communication session between the UE and the mobile network by causing the AMF to perform: (a) receiving, from the UE, a first NAS message including a subset of NAS protocol Information Elements (IEs) from among a full set of NAS protocol IEs for the NAS procedure, the subset of NAS protocol IEs being designated for security-related handling, the first NAS message further comprising a NAS message container, the NAS message container including therein a second NAS message that contains the full set of NAS protocol IEs including the subset of NAS protocol IEs designated for security-related handling and one or more additional NAS protocol IEs, the NAS message container in the first NAS message being encrypted using a NAS security algorithm associated with the NAS security context; (b) establishing a new NAS security context between the AMF and the UE; (c) generating a new NAS security algorithm and a new NAS security key set identifier associated with the new NAS security context; and (d) sending, to the UE, the new NAS security algorithm and the new NAS security key set identifier associated with the new NAS security context, and (ii) in an instance in which a NAS security context does not exist for the UE, performing a NAS procedure in multiple phases to establish the NAS communication session between the UE and the AMF by, (a) for a first phase of the NAS procedure: (1) receiving, from the UE, a first NAS message including a subset of NAS protocol IEs from among a full set of NAS protocol IEs for the NAS procedure, the subset of NAS protocol IEs consisting only of NAS protocol IEs that are designated for security-related handling; and (2) sending, to the UE, a response that indicates a NAS security algorithm and a security key set identifier associated with a NAS security established between the AMF and the UE, and (b) for a second phase of the NAS procedure: (1) receiving, from the UE, a subsequent NAS message, wherein the subsequent NAS message comprises a second NAS message within a NAS message container of the subsequent NAS message, wherein the second NAS message has a type that is a same message type as the type of the first NAS message, wherein the second NAS message includes therein the full set of NAS protocol IEs for the NAS procedure, wherein the full set of NAS protocol IEs including the subset of NAS protocol IEs that consists only of NAS protocol IEs designated for security-related handling and one or more additional NAS protocol IEs, and wherein the NAS message container of the subsequent NAS message is encrypted using the NAS security algorithm.

8. The AMF of claim 7, wherein, in an instance in which the NAS security context exists for the UE, the subset of NAS protocol IEs that consists only of NAS protocol IEs designated for security-related handling in the first NAS message are encrypted by the UE using a public key of a Home Public Land Mobile Network (HPLMN) for the UE.

9. The AMF of claim 8, wherein the first NAS message comprises a registration request message, and wherein the subset of NAS protocol IEs comprises one or more of: a mobile identity for the UE, a UE security capability indicating one or more NAS security algorithms supported by the UE, a registration type associated with the registration request message, or a security key set identifier for a NAS security context.

10. The AMF of claim 7, wherein, in an instance in which the NAS security context exists for the UE, the response comprising the NAS security algorithm and the security key set identifier is a security mode command message, and wherein the subsequent NAS message is a security mode complete message.

11. A method comprising: (i) in an instance in which a Non-Access Stratum (NAS) security context exists between a user equipment (UE) and an Access and Mobility Management Function (AMF) in a mobile network, initiating, by the UE, a NAS procedure to establish a NAS communication session between the UE and the AMF by: (a) identifying, from among a full set of NAS protocol Information Elements (IEs) used for the NAS procedure, a subset of NAS protocol IEs that are designated for security-related handling for the NAS procedure; (b) inserting, into a first NAS message, the subset of NAS protocol IEs that are designated for security-related handling; (c) inserting, into a NAS message container of the first NAS message, a second NAS message, the second NAS message containing therein the full set of NAS protocol IEs including the subset of NAS protocol IEs that are designated for security-related handling for the NAS procedure and one or more additional NAS protocol IEs; (d) encrypting, using a NAS security algorithm of the security context, the NAS message container; and (e) sending the first NAS message to the AMF; and (ii) in an instance in a NAS security context does not exist between the UE and the AMF in the mobile network, initiating, using the UE, a NAS procedure in multiple phases to establish a NAS communication session between the UE and the AMF of the mobile network by, (a) for a first phase: (1) identifying, from among a full set of NAS protocol IEs used for the NAS procedure, a subset of NAS protocol IEs that consists only of NAS protocol IEs that are designated for security-related handling for initiating the NAS procedure; (2) inserting, into a first NAS message, the subset of NAS protocol IEs; (3) sending the first NAS message to the AMF using the UE; and (4) receiving, at the UE, from the AMF, a response that indicates a NAS security algorithm and a security key set identifier associated with a NAS security context for use by the UE, and (b) for a second phase: (1) inserting, into a second NAS message, the full set of NAS protocol IEs including the subset of NAS protocol IEs that consists only of NAS protocol IEs designated for security-related handling and one or more additional NAS protocol IEs, wherein a type of the second NAS message is a same message type as the type of the first NAS message; (2) inserting, into a NAS message container of a subsequent NAS message, the second NAS message; (3) encrypting the NAS message container of the subsequent NAS message using the NAS security algorithm; and (4) sending the subsequent NAS message to the AMF.

12. The method of claim 11, wherein, for the first phase of the NAS procedure, said generating the first NAS message further comprises: encrypting, by the UE, using a public key of a Home Public Land Mobile Network (HPLMN) for the UE, the subset of NAS protocol IEs in the first NAS message.

13. The method of claim 11, further comprising: in an instance in which no NAS security contexts exists between the UE and the AMF and a public key of an HPLMN for the UE is programmed on a Universal Mobile Telecommunications System (UMTS) Subscriber Identity Module (USIM) of the UE, encrypting the subset of NAS protocol IEs in the first NAS message using the public key before sending the first NAS message to the AMF; and in an instance in which no NAS security context exists between the UE and the AMF and no public key of the HPLMN is programmed on the USIM of the UE, refraining from encrypting the subset of NAS protocol IEs in the first NAS message before sending the first NAS message to the AMF.

14. The method of claim 11, wherein, in an instance in which a NAS security context exists between the UE and the AMF, the first NAS message comprises a registration request message and the subset of NAS protocol IEs comprises one or more of: a mobile identity for the UE, a UE security capability indicating one or more NAS security algorithms supported by the UE, a registration type associated with the registration request message, or a security key set identifier for a NAS security context.

15. The method of claim 14, further comprising: in an instance in which the registration type associated with the registration request message indicates a non-emergency, encrypting the subset of NAS protocol IEs in the first NAS message using the NAS security algorithm of the NAS security context before sending the first NAS message to the AMF; and in an instance in which the registration type associated with the registration request message indicates an emergency, refraining from encrypting the subset of NAS protocol IEs in the first NAS message before sending the first NAS message to the AMF.

16. The method of claim 11, wherein the response comprising the NAS security algorithm and the security key set identifier is a security mode command message, and the subsequent NAS message is a security mode complete message.

17. A method comprising: (i) in an instance in which a NAS security context exists between an Access and Mobility Management Function (AMF) of a mobile network and a user equipment (UE), carrying out a Non-Access Stratum (NAS) procedure, using the AMF, to establish a NAS communication session between the UE and the AMF, by: (a) receiving, from the UE, a first NAS message including therein a subset of NAS protocol Information Elements (IEs) from among a full set of NAS protocol IEs for the NAS procedure, the subset of NAS protocol IEs being designated for security-related handling, the first NAS message further comprising a NAS message container, the NAS message container including therein a second NAS message that contains the full set of NAS protocol IEs including the subset of NAS protocol IEs designated for security-related handling and one or more additional NAS protocol IEs, the NAS message container in the first NAS message being encrypted using a NAS security algorithm associated with the NAS security context; (b) establishing a new NAS security context between the AMF and the UE; (c) generating a new NAS security algorithm and a new NAS security key set identifier associated with the new NAS security context; and (d) sending, to the UE, a response indicating the new NAS security algorithm and the new NAS security key set identifier associated with the new NAS security context between the AMF and the UE, and (ii) in an instance in which a NAS security context does not exist between the AMF and the UE, carrying out a NAS procedure, using the AMF, in multiple phases, to establish the NAS communication session between the UE and the AMF by, (a) for a first phase of the NAS procedure: (1) receiving, at the AMF, from the UE, a first NAS message including therein a subset of NAS protocol IEs from among a full set of NAS protocol IEs for the NAS procedure, the subset of NAS protocol IEs consisting only of NAS protocol IEs that are designated for security-related handling for the NAS procedure; (2) sending, to the UE, using the AMF, a response indicating a NAS security algorithm and a security key set identifier associated with a NAS security context established between the AMF and the UE, and (b) for a second phase of the NAS procedure: (1) receiving, at the AMF, from the UE, a subsequent NAS message, wherein the subsequent NAS message includes therein a NAS message container, wherein the NAS message container includes therein a second NAS message, wherein the second NAS message has a type that is a same message type as the type of the first NAS message, wherein the second NAS message contains therein the full set of NAS protocol IEs for the NAS procedure including the subset of NAS protocol IEs that consists only of NAS protocol IEs that are designated for security-related handling and one or more additional NAS protocol IEs, and wherein the NAS message container in the subsequent NAS message is encrypted using the NAS security algorithm.

18. The method of claim 17, wherein, in an instance in which no NAS security context exists between the UE and the AMF and the UE has a public key of a Home Public Land Mobile Network (HPLMN) for the UE, the subset of NAS protocol IEs in the first NAS message are encrypted using the public key of the HPLMN for the UE.

19. The method of claim 17, wherein the first NAS message comprises a registration request message, and wherein the subset of NAS protocol IEs comprises one or more of: a mobile identity for the UE, a UE security capability indicating one or more NAS security algorithms supported by the UE, a registration type associated with the registration request message, or the security key set

identifier for the NAS security context.

20. The method of claim 17, wherein the response indicating the NAS security algorithm and the security key set identifier is a security mode command message, and the subsequent NAS message is a security mode complete message.
