

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12392096
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Xiong; Wei

Light-emitting traffic cone

Abstract

A light-emitting traffic cone includes: a cone body, having a hollow space; a base, connected to the cone body; and a light-emitting assembly, disposed on the base, the light-emitting assembly at least including a light-emitting body and a power supply, the light-emitting body being electrically connected to the power supply, and the light-emitting body being disposed at a position corresponding to the hollow space so that light emitted by the light-emitting body can irradiate into the hollow space. The light-emitting traffic cone can improve a warning effect.

Inventors:	Xiong; Wei (Ningbo, CN)
Applicant:	CIXI SHUANGWEI ROAD FACILITIES CO., LTD. (Ningbo, CN)
Family ID:	1000008765410
Assignee:	CIXI SHUANGWEI ROAD FACILITIES CO., LTD. (Ningbo, CN)
Appl. No.:	18/540919
Filed:	December 15, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240175221 A1	May. 30, 2024

Foreign Application Priority Data

CN	202121345086.3	Jun. 17, 2021
----	----------------	---------------

Related U.S. Application Data

continuation-in-part parent-doc WO PCT/CN2021/112961 20210817 PENDING child-doc US 18540919

Publication Classification

Int. Cl.: E01F9/615 (20160101); E01F9/608 (20160101); E01F9/619 (20160101); E01F9/654 (20160101); E01F9/688 (20160101); F21S9/03 (20060101)

U.S. Cl.:

CPC E01F9/617 (20160201); E01F9/608 (20160201); E01F9/615 (20160201); E01F9/619 (20160201); E01F9/654 (20160201); E01F9/688 (20160201); F21S9/037 (20130101);

Field of Classification Search

CPC: E01F (9/617); E01F (9/608); E01F (9/619); E01F (9/654); E01F (9/688); E01F (9/615); F21S (9/037); F21S (9/03); H02J (7/35); Y02B (20/72)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7878678	12/2010	Stamatatos	116/63P	B60Q 1/2696
9127420	12/2014	Ko	N/A	E01F 9/615
9512578	12/2015	Dvoracek	N/A	E01F 9/654
2015/0116991	12/2014	Miano	362/157	E01F 9/615
2023/0340738	12/2022	Selevan	N/A	E01F 9/654

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2808998	12/2005	CN	N/A
200985493	12/2006	CN	N/A
205259093	12/2015	CN	N/A
209114359	12/2018	CN	N/A
211036763	12/2019	CN	N/A
1062624	12/1966	GB	N/A
2018141362	12/2017	JP	N/A
20160002662	12/2015	KR	E01F 9/654
M571879	12/2017	TW	N/A

Primary Examiner: Tweel, Jr.; John A

Attorney, Agent or Firm: Bayramoglu Law Offices LLC

Background/Summary

CROSS REFERENCE TO THE RELATED APPLICATIONS (1) This application is the continuation-in-part application of International Application No. PCT/CN2021/112961, filed on Aug. 17, 2021, which is based upon and claims priority to Chinese Patent Application No. 202121345086.3, filed on Jun. 17, 2021, the entire contents of which are incorporated herein by reference.

TECHNICAL FIELD

(1) The present invention relates to the field of barricade technologies, and in particular, to a light-emitting traffic cone.

BACKGROUND

(2) Traffic cones are widely used in roads and construction, can be used for isolation warnings in urban intersection lanes, sidewalks, and dangerous areas, and can also be used for maintenance and repair, or the like of urban roads and expressways.

(3) However, in a low visibility environment such as at night, a cone body surface of a conventional traffic cone is usually adhered with a reflective film or covered with a reflective cone sleeve, and the reflective film is irradiated by a light fixture and then light is reflected to a pedestrian or driver's eyes to provide warning information. This is a passive warning. Once the light fixture is faulty, a risk of an accident is greatly increased. In addition, the reflective film is likely to fall off accidentally, and as the service time increases, a reflection effect of the reflective film decreases, weakening a warning effect of the traffic cone. Therefore, a traffic cone capable of improving a warning effect is needed.

SUMMARY

(4) The present invention provides a light-emitting traffic cone, which can improve a warning effect.

(5) To resolve the foregoing technical problem, the present invention provides a light-emitting traffic cone, including: a cone body, having a hollow space; a base, connected to the cone body; and a light-emitting assembly, disposed on the base, where the light-emitting assembly at least includes a light-emitting body and a power supply, the light-emitting body is electrically connected to the power supply, and the light-emitting body is disposed at a position corresponding to the hollow space so that light emitted by the light-emitting body can irradiate into the hollow space.

(6) According to the foregoing technical solution, preferably, the light-emitting assembly further includes an accommodating box, the power supply is connected to the accommodating box, and the accommodating box is detachably connected to the base.

(7) According to the foregoing technical solution, preferably, the power supply is a battery or a solar power supply.

(8) According to the foregoing technical solution, preferably, the power supply includes the battery and the solar power supply, and the battery is disposed in the accommodating box.

(9) According to the foregoing technical solution, preferably, the base is provided with an accommodating opening, the accommodating box is clamped in the accommodating opening, the solar power supply includes a solar panel, and the solar panel is disposed on a top surface of the accommodating box.

(10) According to the foregoing technical solution, preferably, the light-emitting body is disposed in the accommodating box, and the light-emitting body is disposed obliquely toward the hollow space so that the light emitted by the light-emitting body can irradiate into the hollow space.

(11) According to the foregoing technical solution, preferably, the light-emitting traffic cone further includes a buzzer, and the buzzer is electrically connected to the power supply.

(12) According to the foregoing technical solution, preferably, the light-emitting traffic cone further includes a distance sensor, the distance sensor is electrically connected to the buzzer, and the distance sensor is electrically connected to the power supply.

(13) According to the foregoing technical solution, preferably, a reflective tape is disposed on an outer surface of the cone body.

(14) According to the foregoing technical solution, preferably, a control switch configured to control the light-emitting assembly is disposed on the base.

(15) The present invention provides a light-emitting traffic cone, which is provided with the light-emitting assembly, and can actively emit light, thereby effectively improving a warning effect of

the traffic cone in a case of low illumination or no illumination. The light-emitting assembly is modularized and disposed detachably, and can be directly replaced if the light-emitting assembly is faulty. A plurality of light-emitting assemblies may be disposed to improve brightness, thereby improving a warning effect. The hollow space is disposed in the cone body, and a plurality of light-emitting traffic cones may be stacked, to reduce accommodating space and reduce transportation costs.

(16) The foregoing descriptions are merely an overview of the technical solutions of the present invention. To understand the technical means of the present invention more clearly, the technical means may be implemented according to the content of this specification. In addition, to make the foregoing and other objectives, features, and advantages of the present invention clearer and easier to understand, the following describes specific implementations of the present invention.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a schematic diagram of a three-dimensional structure of a light-emitting traffic cone according to an embodiment of the present invention;

(2) FIG. 2 is a schematic diagram of a three-dimensional structure of a light-emitting traffic cone according to an embodiment of the present invention; and

(3) FIG. 3 is a schematic diagram of a structure of a light-emitting module of a light-emitting traffic cone according to an embodiment of the present invention.

(4) In the figures: **1**. cone body; **2**. base; **3**. light-emitting assembly; **4**. control switch; **5**. reflective tape; **6**. hollow space; **7**. buzzer; **8**. distance sensor; **201**. accommodating opening; **301**. accommodating box; **302**. power supply; **303**. battery; **304**. solar panel; and **305**. light-emitting body.

DETAILED DESCRIPTION OF THE EMBODIMENTS

(5) To make the objectives, features, and advantages of the present invention clearer and easier to understand, the following clearly and comprehensively describes the technical solutions in the embodiments of the present invention with reference to the accompanying drawings in the embodiments of the present invention. Clearly, the described embodiments are merely some rather than all of the embodiments of the present invention. All other embodiments obtained by a person skilled in the art based on the embodiments of the present invention without creative efforts fall within the protection scope of the present invention.

(6) Referring to FIG. 1 to FIG. 3, an embodiment of the present invention provides a light-emitting traffic cone, including: a cone body **1**, having a hollow space **6**; a base **2**, connected to the cone body **1**; and a light-emitting assembly **3**, disposed on the base **2**, where the light-emitting assembly **3** at least includes a light-emitting body **305** and a power supply **302**, the light-emitting body **305** is electrically connected to the power supply **302**, and the light-emitting body **305** is disposed at a position corresponding to the hollow space **6** so that light emitted by the light-emitting body **305** can irradiate into the hollow space **6**.

(7) This embodiment provides a light-emitting traffic cone, which is provided with the light-emitting assembly **3**, and can actively emit light, thereby effectively improving a warning effect of the traffic cone in a case of low illumination or no illumination. The light-emitting assembly **3** is modularized and disposed detachably, and can be directly replaced if the light-emitting assembly **3** is faulty. A plurality of light-emitting assemblies **3** may be disposed to improve brightness, thereby improving a warning effect. The hollow space **6** is disposed in the cone body **1**, and a plurality of light-emitting traffic cones may be stacked, to reduce accommodating space and reduce transportation costs.

(8) In a further feasible manner of this embodiment, the light-emitting assembly **3** further includes

an accommodating box **301**, the power supply **302** is connected to the accommodating box **301**, and the accommodating box **301** is detachably connected to the base **2**.

(9) In this embodiment, the accommodating box **301** and the base **2** are detachably connected, so that when the light-emitting assembly **3** is faulty, the light-emitting assembly **3** is detached for maintenance. If the fault is difficult to eliminate, the light-emitting assembly **3** can be replaced as a whole.

(10) In a further feasible manner of this embodiment, the power supply **302** is a battery **303** or a solar power supply.

(11) In this embodiment, the power supply **302** is the battery **303** or the solar power supply, to adapt to different use environments.

(12) In a further feasible manner of this embodiment, the power supply **302** includes the battery **303** and the solar power supply, the battery **303** is disposed in the accommodating box **301**, the solar power supply includes a solar panel **304**, and the solar panel **304** is exposed to the outside of the accommodating box **301**.

(13) In this embodiment, a light-transmissive hood is disposed on a top of the solar panel **304**, to prevent the solar panel from being damaged due to extrusion, and prevent rain, dust, or the like from entering the light-emitting assembly **3**. The light-transmissive hood is higher than the base **2**, to avoid water or dust accumulation on the light-transmissive hood, affecting power generation efficiency of the solar panel. To prevent an upper traffic cone from squeezing a light-transmissive hood of a lower traffic cone during stacking, a bottom of the accommodating box **301** is higher than a bottom of the base **2**, to form accommodating space that matches a shape and a size of the light-transmissive hood, so that when a plurality of traffic cones are stacked, the light-transmissive hood can be placed in the accommodating space.

(14) In a further feasible manner of this embodiment, the base **2** is provided with an accommodating opening **201**, the accommodating box **301** is clamped in the accommodating opening **201**, and the solar panel **304** is disposed on a top surface of the accommodating box **301**.

(15) In this embodiment, the accommodating opening **201** provided on the base **2** facilitates mounting of the accommodating box **301**, and provides solar energy absorption space for the solar panel **304**.

(16) In a further feasible manner of this embodiment, the light-emitting body **305** is disposed in the accommodating box **301**, and the light-emitting body **305** is disposed obliquely toward the hollow space **6** so that the light emitted by the light-emitting body **305** can irradiate into the hollow space **6**.

(17) In this embodiment, the light-emitting body **305** improves a warning effect of the light-emitting traffic cone through the emitted light.

(18) In a further feasible manner of this embodiment, the light-emitting traffic cone further includes a buzzer **7**, and the buzzer **7** is electrically connected to the power supply **303**.

(19) In this embodiment, the buzzer **7** is further disposed, and the buzzer **7** makes a sound to remind pedestrians, especially the blind, to pay attention to a position of the traffic cone, to prevent the blind from colliding with the traffic cone to be injured. In addition, currently, many people are accustomed to looking down at mobile phones during walking, and the buzzer **7** can also remind this group of people to pay attention to the position of the traffic cone.

(20) In a further feasible manner of this embodiment, the light-emitting traffic cone further includes a distance sensor **8**, the distance sensor **8** is electrically connected to the buzzer **7**, and the distance sensor **8** is electrically connected to the power supply **303**.

(21) In this embodiment, the distance sensor is further disposed, and the distance sensor controls operation of the buzzer. If the distance sensor detects that a human body or an object approaches, the distance sensor controls the buzzer to make a sound. The distance sensor controls operation of the buzzer, which not only can warn a pedestrian, but also can prevent the buzzer from operating for a long time, resulting in a reduced service life of the buzzer.

(22) In a further feasible manner of this embodiment, a reflective tape 5 is disposed on an outer surface of the cone body 1.

(23) In this embodiment, the reflective tape 5 can improve a warning effect when a lighting condition is poor or a light-emitting module is faulty.

(24) In a further feasible manner of this embodiment, a control switch 4 configured to control the light-emitting assembly 3 is disposed on the base 2.

(25) In this embodiment, the control switch 4 can disable the light-emitting body 305 when the light-emitting assembly 3 does not need to be used, thereby effectively prolonging a service life of the light-emitting assembly 3 and reducing power consumption. A shield is disposed above the control switch 4, to effectively prevent the control switch 4 from being touched by mistake, and prevent rain or dust from entering the switch or the light-emitting assembly 3.

(26) Specifically, in this embodiment, the light-emitting assembly 3 includes the accommodating box 301, the power supply 302, and the light-emitting body 305. The battery 303 and the light-emitting body 305 are detachably disposed inside the accommodating box 301, to facilitate maintenance and replacement. The light-emitting assembly 3 is clamped as a whole on the base 2 by using the accommodating box 301, to facilitate detachment of the light-emitting assembly 3 as a whole for maintenance and replacement. The light emitted by the light-emitting body 305 irradiates the hollow space 6 of the cone body 1. Turn-on or turn-off of the light-emitting body 305 is controlled by using the control switch 4. The control switch 4 is disposed on the base 2, and the shield is disposed above the control switch 4, to effectively prevent the control switch 4 from being touched by mistake, and prevent rain or dust from entering the switch or the light-emitting assembly 3. The cone body 1 is disposed on the base 2, and the hollow space 6 is disposed in the body 1, so that a plurality of light-emitting traffic cones of the same structure can be stacked, to reduce accommodating space and reduce transportation costs. The reflective tape 5 is disposed on the exterior of the cone body 1, to improve a warning effect when a lighting condition is poor or a light-emitting module is faulty.

(27) In the descriptions of this specification, reference terms such as “an embodiment”, “some embodiments”, “example”, “specific example”, or “some examples” mean that specific features, structures, materials, or characteristics described with reference to the embodiments or the examples are included in at least one embodiment or example of the present invention. In addition, the described specific features, structures, materials, or characteristics can be properly combined in any one or more of the embodiments or the examples. In addition, a person skilled in the art can integrate and combine different embodiments or examples and features in different embodiments or examples described in this specification, provided that the embodiments or the examples and the features do not conflict with each other.

(28) In addition, terms “first” and “second” are used only for description purposes, and cannot be understood as an indication or an implication of relative importance or an implicit indication of a quantity of indicated technical features. Therefore, features defined with “first” or “second” may explicitly or implicitly include at least one of the features. In the descriptions of the present invention, “a plurality of” means two or more, unless otherwise specifically limited.

(29) The foregoing descriptions are merely specific implementations of the present invention, but are not intended to limit the protection scope of the present invention. Any variation or replacement readily figured out by a person skilled in the art within the technical scope disclosed in the present invention shall fall within the protection scope of the present invention. Therefore, the protection scope of the present invention shall be subject to the protection scope of the claims.

Claims

1. A light-emitting traffic cone, comprising: a cone body, having a hollow space; a base, connected to the cone body; and a light-emitting assembly, disposed on the base, wherein the light-emitting

assembly at least comprises a light-emitting body and a power supply, the light-emitting body is electrically connected to the power supply, and the light-emitting body is disposed at a position corresponding to the hollow space so that light emitted by the light-emitting body is allowed to irradiate into the hollow space; wherein the light-emitting assembly further comprises an accommodating box, the power supply is connected to the accommodating box, and the accommodating box is detachably connected to the base, wherein the power supply comprises a battery and a solar power supply, and the battery is disposed in the accommodating box, and wherein the base is provided with an accommodating opening, the accommodating box is clamped in the accommodating opening, the solar power supply comprises a solar panel, and the solar panel is disposed on a top surface of the accommodating box.

2. The light-emitting traffic cone according to claim 1, wherein the light-emitting body is disposed in the accommodating box, and the light-emitting body is disposed obliquely toward the hollow space so that the light emitted by the light-emitting body is allowed to irradiate into the hollow space.

3. The light-emitting traffic cone according to claim 1, further comprising a buzzer, wherein the buzzer is electrically connected to the power supply.

4. The light-emitting traffic cone according to claim 3, further comprising a distance sensor, wherein the distance sensor is electrically connected to the buzzer, and the distance sensor is electrically connected to the power supply.

5. The light-emitting traffic cone according to claim 1, wherein a reflective tape is disposed on an outer surface of the cone body.

6. The light-emitting traffic cone according to claim 1, wherein a control switch configured to control the light-emitting assembly is disposed on the base.
