

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12396257
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Yang; Gi Young et al.

Integrated circuit including integrated standard cell structure

Abstract

An integrated circuit including a first active region and a second active region extending in a first direction and spaced apart from each other in a second direction intersecting the first direction; a power rail and a ground rail extending in the first direction and spaced apart from the first and second active regions and each other in the second direction; source/drain contacts extending in the second direction on at least a portion of the first or second active region, gate structures extending in the second direction and on at least a portion of the first and second active regions, a power rail configured to supply power through source/drain contact vias, and a ground rail configured to supply a ground voltage through source/drain contact vias.

Inventors: Yang; Gi Young (Seoul, KR), You; Hyeon Gyu (Hwaseong-si, KR), Kim; Ga Room (Hwaseong-si, KR), Lim; Jin Young (Seoul, KR), Kim; In Gyum (Bucheon-si, KR), Jung; Hak Chul (Seoul, KR)

Applicant: SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

Family ID: 1000008764800

Assignee: SAMSUNG ELECTRONICS CO., LTD. (N/A, KR)

Appl. No.: 18/344794

Filed: June 29, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230343788 A1	Oct. 26, 2023

Foreign Application Priority Data

KR	10-2019-0171535	Dec. 20, 2019
KR	10-2020-0069127	Jun. 08, 2020

Related U.S. Application Data

division parent-doc US 17029475 20200923 US 11735592 child-doc US 18344794

Publication Classification

Int. Cl.: **G11C5/06** (20060101); **G06F30/392** (20200101); **G11C11/412** (20060101);
H01L23/528 (20060101); **H10D84/90** (20250101); **H10D89/10** (20250101)

U.S. Cl.:

CPC **H10D84/907** (20250101); **G06F30/392** (20200101); **G11C5/06** (20130101);
G11C11/412 (20130101); **H01L23/528** (20130101); **H10D89/10** (20250101);

Field of Classification Search

CPC: H10D (84/907); H10D (89/10); G06F (30/392); G11C (11/412)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8816402	12/2013	Becker	257/211	H10B 10/00
9367654	12/2015	Chang et al.	N/A	N/A
9837353	12/2016	Shen et al.	N/A	N/A
9859898	12/2017	Anderson et al.	N/A	N/A
10043571	12/2017	Liaw	N/A	N/A
10068806	12/2017	Pritchard et al.	N/A	N/A
10146900	12/2017	Sahu et al.	N/A	N/A
10170422	12/2018	Chen et al.	N/A	N/A
10510688	12/2018	Sio et al.	N/A	N/A
2014/0003133	12/2013	Lin et al.	N/A	N/A
2016/0300839	12/2015	Kim et al.	N/A	N/A
2017/0083653	12/2016	Sahu et al.	N/A	N/A
2017/0154848	12/2016	Fan et al.	N/A	N/A
2017/0236823	12/2016	Lee et al.	N/A	N/A
2018/0108646	12/2017	Lee et al.	N/A	N/A
2018/0158811	12/2017	Subhash	N/A	H10D 89/10
2019/0096891	12/2018	Liaw	N/A	N/A
2019/0122987	12/2018	Chen et al.	N/A	N/A
2019/0198491	12/2018	Do et al.	N/A	N/A
2019/0206459	12/2018	Lu et al.	N/A	N/A
2019/0319022	12/2018	Song et al.	N/A	N/A
2019/0393205	12/2018	Lee et al.	N/A	N/A
2020/0058681	12/2019	Lai et al.	N/A	N/A
2020/0105768	12/2019	Liaw	N/A	N/A
2020/0135741	12/2019	Liaw	N/A	N/A
2020/0194058	12/2019	Hsu et al.	N/A	N/A

2020/0321355	12/2019	Jeong et al.	N/A	N/A
2020/0328216	12/2019	Liaw	N/A	N/A
2021/0035986	12/2020	Yu et al.	N/A	N/A
2021/0098466	12/2020	Liaw	N/A	N/A
2021/0193683	12/2020	Yang et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
1020160025056	12/2015	KR	N/A
1020180038239	12/2017	KR	N/A
1020180075017	12/2017	KR	N/A
1020180101698	12/2017	KR	N/A

OTHER PUBLICATIONS

US 9,886,540 B2, 02/2018, Sahu et al. (withdrawn) cited by applicant

Notice of Allowance in Korean Appln. No. 10-2020-0069127, mailed on Dec. 24, 2024, 6 pages (with English translation). cited by applicant

Primary Examiner: Natalini; Jeff W

Assistant Examiner: Belousov; Alexander

Attorney, Agent or Firm: Fish & Richardson P.C.

Background/Summary

(1) This application is a division of U.S. application Ser. No. 17/029,475, filed Sep. 23, 2020, which claims priority from Korean Patent Application No. 10-2019-0171535 filed on Dec. 20, 2019, in the Korean Intellectual Property Office and from Korean Patent Application No. 10-2020-0069127 filed on Jun. 8, 2020, in the Korean Intellectual Property Office, the disclosures of which are incorporated herein by reference in their entireties.

BACKGROUND

1. Field of the Disclosure

(1) The present disclosure relates to integrated circuits including an integrated standard cell structure.

2. Description of the Related Art

(2) An integrated circuit may be designed based on standard cells. In more detail, a layout of the integrated circuit may be generated by arranging the standard cells according to data defining the integrated circuit and routing the arranged standard cells. Such standard cells are predesignated and stored in a cell library.

(3) As semiconductor manufacturing processes are miniaturized, the size of patterns in a standard cell may be reduced, and the size of the standard cell may also be reduced.

SUMMARY

(4) The present disclosure is directed to providing integrated circuits allowing the density of a layout to be improved, the stability of a process for manufacturing a semiconductor device to be improved, and the performance and reliability of a designed semiconductor device to be improved by routing source/drain through source/drain contacts.

(5) However, aspects of the present inventive concepts are not restricted to the one set forth herein. The above and other aspects of the present inventive concepts will become more apparent to one of

ordinary skill in the art to which the present inventive concepts pertains by referencing the detailed description of the present inventive concepts given below.

(6) According to some example embodiments, there is provided an integrated circuit comprising a first active region and a second active region extending in a first direction and spaced apart from each other in a second direction intersecting the first direction; a power rail extending in the first direction and spaced apart from the first active region in the second direction; a ground rail extending in the first direction and spaced apart from the second active region and the power rail in the second direction; a first source/drain contact extending in the second direction, on at least a portion of the first active region, and configured to receive power from the power rail through a first source/drain contact via; a second source/drain contact extending in the second direction, on at least a portion of the second active region spaced apart from the first source/drain contact in the second direction, and connected to the ground rail through a second source/drain contact via to be grounded; a first gate structure extending in the second direction and on at least a portion of the first active region and at least a portion of the second active region spaced apart from the first source/drain contact and the second source/drain contact in the first direction; a third source/drain contact extending in the second direction and on at least a portion of the first active region and at least a portion of the second active region spaced apart from the first gate structure in the first direction; a second gate structure extending in the second direction and on at least a portion of the first active region spaced apart from the third source/drain contact in the first direction; a third gate structure extending in the second direction and on at least a portion of the second active region spaced apart from the third source/drain contact in the first direction and spaced apart from the second gate structure in the second direction; a fourth source/drain contact on at least a portion of the first active region and at least a portion of the second active region spaced apart from the second gate structure and the third gate structure in the first direction; a fourth gate structure extending in the second direction and on at least a portion of the first active region spaced apart from the fourth source/drain contact in the first direction; a fifth gate structure extending in the second direction and on at least a portion of the second active region spaced apart from the fourth source/drain contact in the first direction and spaced apart from the fourth gate structure in the second direction; a fifth source/drain contact on at least a portion of the first active region and at least a portion of the second active region spaced apart from the fourth gate structure and the fifth gate structure in the first direction; a sixth gate structure extending in the second direction and on at least a portion of the first active region and at least a portion of the second active region spaced apart from the fifth source/drain contact in the first direction; a sixth source/drain contact extending in the second direction and on at least a portion of the first active region spaced apart from the sixth gate structure in the first direction; and a seventh source/drain contact extending in the second direction and on at least a portion of the second active region spaced apart from the sixth gate structure in the first direction and spaced apart from the sixth source/drain contact in the second direction.

(7) According to some example embodiments, there is provided an integrated circuit comprising a first inverter including a first p-channel metal-oxide-semiconductor transistor and a first n-channel metal-oxide-semiconductor transistor, which are gated through a first metal line to which a first input voltage is configured to be applied, and configured to output a first inverted voltage by inverting the first input voltage, wherein a drain of the first NMOS transistor and a drain of the first PMOS transistor are routed through a first source/drain contact, a first metal line extends in a first direction, and the first source/drain contact extends in a second direction perpendicular to the first direction; a first transmission gate including a second PMOS transistor gated through a second metal line to which a first active voltage is configured to be applied and a second NMOS transistor gated through a third metal line to which a second active voltage is configured to be applied, wherein a source of the second PMOS transistor and a drain of the second NMOS transistor are routed through the first source/drain contact, and a drain of the second PMOS transistor and a

source of the second NMOS transistor are routed through the second source/drain contact; and a first tri-state inverter including a third PMOS transistor gated through a fourth metal line to which the second active voltage is configured to be applied, a third NMOS transistor gated through a fifth metal line to which the first active voltage is configured to be applied, and a fourth PMOS transistor and a fourth NMOS transistor, which are gated through a sixth metal line to which a second input voltage is configured to be applied, and configured to invert the second input voltage, wherein a drain of the third PMOS transistor and a drain of the third NMOS transistor are routed through the second source/drain contact.

(8) According to some example embodiments, there is provided an integrated circuit comprising a first inverter configured to invert a first input voltage and output a first inverted voltage; a first transmission gate configured to receive the first inverted voltage; a second inverter configured to invert a second input voltage and output a second inverted voltage; and a second transmission gate configured to receive the second inverted voltage, wherein the first transmission gate includes a first n-channel metal-oxide-semiconductor transistor and a first p-channel metal-oxide-semiconductor transistor that are spaced apart from each other in a first direction, wherein a drain of the first NMOS transistor and a source of the first PMOS transistor are connected through a first source/drain contact extending in a second direction, which intersects the first direction and the first transmission gate receives the first inverted voltage through the first source/drain contact, the second transmission gate includes a second NMOS transistor and a second PMOS transistor that are spaced apart from each other in the first direction, wherein a drain of the second NMOS transistor and a source of the second PMOS transistor are connected through a second source/drain contact extending in the second direction and the second transmission gate receives the second inverted voltage through the second source/drain contact, a source of the first NMOS transistor, a drain of the first PMOS transistor, a source of the second NMOS transistor, and a drain of the second PMOS transistor are connected to each other through a third source/drain contact extending in the second direction, the first NMOS transistor and the second PMOS transistor are gated by a first active voltage, and the first PMOS transistor and the second NMOS transistor are gated by a second active voltage.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The above and other aspects and features of the present disclosure will become more apparent by describing example embodiments thereof in detail with reference to the attached drawings, in which:
- (2) FIG. 1 is a circuit diagram for describing a tri-state inverter according to some example embodiments.
- (3) FIG. 2 is a perspective view for describing the region R of the tri-state inverter shown in FIG. 1 according to some example embodiments.
- (4) FIG. 3 is a layout diagram for describing the region R of the tri-state inverter shown in FIG. 1 according to some example embodiments.
- (5) FIG. 4 is a perspective view for describing the region R of the tri-state inverter shown in FIG. 1 according to some example embodiments.
- (6) FIG. 5 is a layout diagram for describing the region R of the tri-state inverter shown in FIG. 1 according to some example embodiments.
- (7) FIG. 6 is a layout diagram including an integrated circuit according to some example embodiments.
- (8) FIG. 7 is a block diagram illustrating the first cell C_1 shown in FIG. 6 according to some example embodiments.

- (9) FIG. 8 is a circuit diagram of FIG. 7 according to some example embodiments.
- (10) FIG. 9 is a circuit diagram illustrating the scan circuit S_C shown in FIG. 8 according to some example embodiments.
- (11) FIG. 10 is a layout diagram of FIG. 9 according to some example embodiments.
- (12) FIGS. 11 to 13 are layout diagrams of FIG. 9 according to some example embodiments.
- (13) FIG. 14 is a layout diagram illustrating the FEOL of FIG. 10 according to some example embodiments.
- (14) FIG. 15 is a layout diagram of FIG. 15 according to some example embodiments.
- (15) FIG. 16 is a layout diagram illustrating the MOL of FIG. 10 according to some example embodiments.
- (16) FIG. 17 is a layout diagram illustrating the BEOL of FIG. 10 according to some example embodiments.
- (17) FIGS. 18 and 19 are cross-sectional views taken along line A-A' of FIG. 10.
- (18) FIGS. 20 and 21 are cross-sectional views taken along line B-B' of FIG. 10.
- (19) FIGS. 22 and 23 are cross-sectional views taken along line C-C' of FIG. 10.
- (20) FIGS. 24 and 25 are enlarged views for describing a region SDTR shown in FIG. 10 according to some example embodiments.
- (21) FIGS. 26 and 27 are enlarged views for describing a region GTR shown in FIG. 10 according to some example embodiments.
- (22) FIG. 28 is a circuit diagram illustrating the scan circuit S_C shown in FIG. 8 according to some example embodiments.
- (23) FIGS. 29 to 31 are layout diagrams of FIG. 28 according to some example embodiments.
- (24) FIG. 32 is a circuit diagram illustrating the scan circuit S_C shown in FIG. 8.
- (25) FIGS. 33 to 35 are layout diagrams of FIG. 32 according to some example embodiments.
- (26) FIG. 36 is a circuit diagram illustrating the master latch M_L shown in FIG. 8 according to some example embodiments.
- (27) FIGS. 37 and 38 are layout diagrams of FIG. 36 according to some example embodiments.
- (28) FIG. 39 is a circuit diagram illustrating the master latch M_L shown in FIG. 8 according to some example embodiments.
- (29) FIGS. 40 and 41 are layout diagrams of FIG. 39 according to some example embodiments.
- (30) FIG. 42 is a circuit diagram illustrating the master latch M_L shown in FIG. 8 according to some example embodiments.
- (31) FIGS. 43 and 44 are layout diagrams of FIG. 42 according to some example embodiments.

DETAILED DESCRIPTION

- (32) FIG. 1 is a circuit diagram for describing a tri-state inverter according to some example embodiments.
- (33) Referring to FIG. 1, a tri-state inverter 1 includes a first p-channel metal-oxide-semiconductor (PMOS) transistor P1, a second PMOS transistor P2, a first n-channel metal-oxide-semiconductor (NMOS) transistor N1, and a second NMOS transistor N2.
- (34) A source of the first PMOS transistor P1 is connected to a power voltage VDD, and a drain of the first PMOS transistor P1 is connected to a source of the second PMOS transistor P2. A drain of the second PMOS transistor P2 is connected to a drain of the second NMOS transistor N2, and a source of the second NMOS transistor N2 is connected to a drain of the first NMOS transistor N1. A source of the first NMOS transistor N1 is grounded.
- (35) The first PMOS transistor P1 and the first NMOS transistor N1 are gated by an input voltage V_{in} . The second PMOS transistor P2 is gated by an inverted active signal EN. The second NMOS transistor N2 is gated by an active signal EN.
- (36) That is, when the active signal EN is at a logic high level, the tri-state inverter 1 inverts the input voltage and outputs the inverted input voltage as an output voltage V_{out} . In contrast, when the active signal EN is at a logic low level, the tri-state inverter 1 is in a high impedance as the output

voltage Vout.

(37) The drain of the second PMOS transistor P2 is connected to the drain of the second NMOS transistor N2 in anode at which the tri-state inverter 1 outputs the output voltage VOUT, and the region is defined as a region R. Referring to FIGS. 2 and 3, a connection state of the region R will be described.

(38) FIG. 2 is a perspective view for describing the region R of the tri-state inverter shown in FIG. 1 according to some example embodiments.

(39) Referring to FIG. 2, a region R1 for the region R may be largely composed of three layers in a third direction z.

(40) The lowest layer in the third direction z includes a first PMOS transistor gate structure 200 and a first source/drain contact 100 that constitute the second PMOS transistor P2. In addition, the lowest layer includes a first NMOS transistor gate structure 210 and a second source/drain contact 110 that constitute the second NMOS transistor N2.

(41) In order to electrically connect the first source/drain contact 100 to the second source/drain contact 110, a first_first via V1_1 and a first_second via V1_2 extending in the third direction z are disposed in the region R1. The first_first via V1_1 and the first_second via V1_2 are connected to the first source/drain contact 100 and the second source/drain contact 110, respectively.

(42) In order to electrically connect the first source/drain contact 100 to the second source/drain contact 110, a first_first metal line M1_1 and a first_second metal line M1_2 extending in a first direction x are disposed in the region R1 in a middle-height layer in the third direction z. The first_first metal line M1_1 and the first_second metal line M1_2 are connected to the first_first via V1_1 and the first_second via V1_2, respectively.

(43) In order to electrically connect the first source/drain contact 100 to the second source/drain contact 110, a second_first via V2_1 and a second_second via V2_2 extending in the third direction z are disposed in the region R1. The second_first via V2_1 and the second_second via V2_2 are connected to the first_first metal line M1_1 and the first_second metal line M1_2, respectively.

(44) In order to electrically connect the first source/drain contact 100 to the second source/drain contact 110, a second metal line M2 extending in the first direction x is disposed in the region R1 in the highest layer in the third direction z. The second metal line M2 connects the second_first via V2_1 to the second_second via V2_2.

(45) That is, the region R1 for the region R is formed of a total of three layers in the third direction z to allow the drain of the second PMOS transistor P2 to be connected to the drain of the second NMOS transistor N2.

(46) A layout diagram of the region R1 will be described with reference to FIG. 3.

(47) FIG. 3 is a layout diagram for describing the region R of the tri-state inverter shown in FIG. 1.

(48) Referring to FIG. 3, a first active region ACT1 defined by extending in the first direction x is disposed in the region R1. In addition, a second active region ACT2 defined by extending in the first direction x is disposed in the region R1. The first active region ACT1 may be a region in which a p-type transistor is formed. For example, the first active region ACT1 may include a well region doped with n-type impurities. The second active region ACT2 may be a region in which an n-type transistor is formed. For example, the second active region ACT2 may include a well region doped with p-type impurities. The first active region ACT1 and the second active region ACT2 may be disposed to be spaced apart from each other in a second direction y.

(49) The first PMOS transistor gate structure 200 may be disposed on the first active region ACT1 at the lowest height in the third direction z. The first source/drain contact 100 may be disposed to be spaced apart from the first PMOS transistor gate structure 200 in the first direction x. The first_first via V1_1 extending in the third direction z may be disposed on the first source/drain contact 100. The first_first metal line M1_1 extending in the first direction x may be disposed on the first_first via V1_1. The second_first via V2_1 extending in the third direction z is connected to the first_first metal line M1_1.

(50) The first NMOS transistor gate structure **210** may be disposed on the second active region **ACT2** at the lowest height in the third direction *z*. The second source/drain contact **110** may be disposed to be spaced apart from the first NMOS transistor gate structure **210** in the first direction *x*. The first_second via **V1_2** extending in the third direction *z* may be disposed on the second source/drain contact **110**. The first_second metal line **M1_2** extending in the first direction *x* may be disposed on the first_second via **V1_2**. The second_second via **V2_2** extending in the third direction *z* is connected to the first_second metal line **M1_2**.

(51) Subsequently, the first source/drain contact **100** is electrically connected to the second source/drain contact **110** by connecting the second_first via **V2_1** to the second_second via **V2_2** and disposing the second metal line **M2** which extends in the second direction *y*.

(52) As described above with reference to the region **R1**, in order to connect a plurality of source/drain contacts, a structure connected with the height of largely three layers in the third direction *z* is required. That is, as the height of the layers increases, the stability of the process of designing a semiconductor integrated circuit may be degraded. In addition, the degree of freedom of a metal line may be reduced, and pin congestion may be increased.

(53) Accordingly, in some example embodiments for the region **R** as shown in FIG. 1, a plurality of source/drain contacts may be connected while lowering the height of layers like in a region **R2** to be described below with reference to FIGS. 4 and 5.

(54) FIG. 4 is a perspective view for describing the region **R** of the tri-state inverter shown in FIG. 1 according to some example embodiments.

(55) Referring to FIG. 4, a region **R2** for the region **R** may be largely composed of two layers in a third direction *z*.

(56) The lowest layer in the third direction *z* includes a first PMOS transistor gate structure **200** constituting the second PMOS transistor **P2**. In addition, the lowest layer includes a first NMOS transistor gate structure **210** constituting the second NMOS transistor **N2**.

(57) Unlike the region **R1** described above, the region **R2** according to some example embodiments connects the second PMOS transistor **P2** to the second NMOS transistor **N2** through one first source/drain contact **100**. Subsequently, a first via **V1** extending in the third direction *z* is disposed in the region **R2**. A first metal line **M1** extending in a first direction *x* is disposed on the first via **V1**.

(58) That is, the region **R2** for the region **R** is formed of a total of two layers in the third direction *z* to allow the drain of the second PMOS transistor **P2** to be connected to the drain of the second NMOS transistor **N2**.

(59) A layout diagram of the region **R2** will be described with reference to FIG. 5.

(60) FIG. 5 is a layout diagram for describing the region **R** of the tri-state inverter shown in FIG. 1.

(61) Referring to FIG. 5, a first active region **ACT1** defined by extending in the first direction *x* is disposed in the region **R2**. In addition, a second active region **ACT2** defined by extending in the first direction *x* is disposed in the region **R2**. The first active region **ACT1** may be a region in which a p-type transistor is formed. For example, the first active region **ACT1** may include a well region doped with n-type impurities. The second active region **ACT2** may be a region in which an n-type transistor is formed. For example, the second active region **ACT2** may include a well region doped with p-type impurities. The first active region **ACT1** and the second active region **ACT2** may be disposed to be spaced apart from each other in a second direction *y*.

(62) The first PMOS transistor gate structure **200** may be disposed on the first active region **ACT1** at the lowest height in the third direction *z*. The first NMOS transistor gate structure **210** may be disposed on the second active region **ACT2** at the lowest height in the third direction *z*. Subsequently, the second PMOS transistor **P2** is connected to the second NMOS transistor **N2**, and the first source/drain contact **100** extending in the second direction *y* is disposed. The first source/drain contact **100** may be disposed to be spaced apart from the first PMOS transistor gate structure **200** and the first NMOS transistor gate structure **210** in the first direction *x*. The first via

V1 extending in the third direction z is connected to the first source/drain contact **100**. The first metal line M1 extending in the first direction x may be disposed on the first via V1 to electrically connect the second PMOS transistor P2 to the second NMOS transistor N2.

(63) As described above with reference to the region R2, in order to connect a plurality of source/drain contacts, a structure connected with the height of largely two layers in the third direction z is required. That is, as the height of the layers is lowered, the stability of the process of designing a semiconductor integrated circuit may be improved. In addition, the degree of freedom of a metal line may be increased, and pin congestion may be reduced.

(64) Of course, the above-described circuit diagram, layout diagram, and perspective view of the tri-state inverter are not limited to those illustrated in the drawings and may be connected to each other in various ways.

(65) Hereinafter, an integrated circuit according to some example embodiments including the connection method of the region R2 described above will be described.

(66) FIG. 6 is a layout diagram including an integrated circuit according to some example embodiments.

(67) Referring to FIG. 6, a layout 2 including the integrated circuit according to some example embodiments includes a power rail 10 configured to supply a power voltage and a ground rail 20 connected to a ground power.

(68) The layout 2 according to some example embodiments includes a plurality of cells (e.g., first to fourth cells C_1 to C_4). The number and/or configuration of the plurality of cells is not limited to those illustrated in this drawing.

(69) The first cell C_1 and the second cell C_2 are adjacent to each other and may be disposed between the power rail 10 and the ground rail 20. The third cell C_3 and the fourth cell C_4 are adjacent to each other and may be disposed between the power rail 10 and the ground rail 20.

(70) Each of the first to fourth cells C_1 to C_4 may include an input circuit In, a master latch circuit M_L, a slave latch circuit S_L, an output circuit Out, and a clock generation circuit CLK_gen. That is, although each of the first to fourth cells C_1 to C_4 is illustrated as a master-slave flip-flop, the circuit constituting the first to fourth cells C_1 to C_4 is not limited thereto.

(71) Each of the cells may be supplied with a power voltage through the power rail 10 and grounded through the ground rail 20.

(72) Hereinafter, in order to exclude overlapping descriptions, a layout diagram including the integrated circuit according to some example embodiments will be described in detail by taking the master-slave flip-flop of the first cell C_1 as an example. Of course, the description of the first cell C_1 may also be applied to the remaining cells (the second to fourth cells C_2 to C_4).

(73) FIG. 7 is a block diagram illustrating the first cell C_1 shown in FIG. 6. FIG. 8 is a circuit diagram of FIG. 7. For reference, only the input circuit In, the master latch circuit M_L, and the slave latch circuit S_L in the master-slave flip-flop of the first cell C_1 will be described as an example for convenience of description.

(74) Referring to FIGS. 7 and 8, the master-slave flip-flop of the first cell C_1 including the integrated circuit according to some example embodiments may include a scan circuit S_C, a master latch M_L, and a slave latch S_L. For reference, the scan circuit S_C may mean the input circuit In shown in FIG. 6.

(75) The scan circuit SS may include a scan multiplexer SM. The scan multiplexer SM may receive a data signal D, a scan active signal Se, and a scan input signal Si and may output any one of the data signal D and the scan input signal Si to a signal node SN according to the control signal.

(76) In more detail, the scan multiplexer SM outputs the scan input signal Si to the signal node SN when the scan active signal SE is at a logic high (H) level. On the other hand, the scan multiplexer SM may output the data signal D to the signal node SN when the scan active signal Se is at a logic low (L) level.

(77) In more detail, the scan multiplexer SM may include a plurality of transmission gates as

illustrated in FIG. 9 below, or a tri-state inverter and a transmission gate as illustrated in FIGS. 28 and 32.

(78) Hereinafter, the scan multiplexer SM including the integrated circuit according to some example embodiments will be described with reference to FIGS. 9 to 35.

(79) FIG. 9 is a circuit diagram illustrating the scan circuit S_C shown in FIG. 8.

(80) Referring to FIG. 9, a scan circuit S_C(R3_1) includes a fourth inverter INV4 configured to receive and invert the data signal D, and a fifth inverter INV5 configured to receive and invert the scan input signal Si. In addition, the scan circuit S_C(R3_1) includes a first transmission gate TG1 configured to transfer the inverted data signal D and a second transmission gate TG2 configured to transfer the inverted scan input signal Si.

(81) A third PMOS transistor P3 of the first transmission gate TG1 and a fourth NMOS transistor N4 of the second transmission gate TG2 share a first common node CN1 and may be gated through the scan active signal Se. In addition, the first transmission gate TG1 and the second transmission gate TG2 may output one of the data signal D and the scan input signal Si through the signal node SN.

(82) Here, a drain of each of a first PMOS transistor P1 and a first NMOS transistor N1 constituting the fourth inverter INV4, a drain of a third NMOS transistor N3 constituting the first transmission gate TG1, and a source of the third PMOS transistor P3 constituting the first transmission gate TG1 may be connected through one source/drain contact.

(83) In addition, a drain of each of a second PMOS transistor P2 and a second NMOS transistor N2 constituting the fifth inverter INV5, a drain of the fourth NMOS transistor N4 constituting the first transmission gate TG1, and a source of a fourth PMOS transistor P4 constituting the first transmission gate TG2 may be connected through one source/drain contact.

(84) In the following, a structure in which a plurality of transistors are connected through one source/drain contact will be described with reference to a layout diagram of FIG. 10.

(85) FIG. 10 is a layout diagram of FIG. 9. FIGS. 11 to 13 are layout diagrams of FIG. 9 according to some example embodiments. Hereinafter, in order to avoid duplicate descriptions, the common parts of FIGS. 10 to 13 will be described only through FIG. 10, and only the differences will be briefly described with reference to the corresponding drawings.

(86) Referring to FIG. 10, the first to fourth PMOS transistors P1 to P4 may be formed on a first active region ACT1 extending in a first direction x. Further, the first to fourth NMOS transistors N1 to N4 may be formed on a second active region ACT2 extending in the first direction x and disposed to be spaced apart from the first active region ACT1 in a second direction y.

(87) For reference, as illustrated in FIG. 11, first active fins (e.g., a first fin F1 and a second fin F2) protruding from the first active region ACT1 in a third direction z may be formed on the first active region ACT1. In addition, second active fins (e.g., a third fin F3 and a fourth fin F4) protruding from the second active region ACT2 in the third direction z may be formed on the second active region ACT2. The first active fins (e.g., the first fin F1 and the second fin F2) and the second active fins (e.g., the third fin F3 and the fourth fin F4) may be disposed to be spaced apart from each other in the second direction y. The first active fins (e.g., the first fin F1 and the second fin F2) and the second active fins (e.g., the third fin F3 and the fourth fin F4) may each extend in the first direction x.

(88) Referring to FIG. 10 again, a power rail 10 may be disposed at an upper portion of the first active region ACT1 in the second direction y. In addition, a ground rail 20 may be disposed at a lower portion of the second active region ACT2 in the second direction y.

(89) A scan circuit S_C(R3_1a) including the integrated circuit according to some examine embodiments may include a plurality of gate structures and a plurality of source/drain contacts extending in the second direction y and disposed to be spaced apart from each other in the first direction x.

(90) For example, a first source/drain contact 100 and a second source/drain contact 110 may be

disposed on the first active region ACT1 and the second active region ACT2, respectively, to be spaced apart from each other in the second direction y. That is, the first source/drain contact **100** may be connected to the power rail **10** through a first source/drain contact via VSD1 to supply the power voltage to the first PMOS transistor P1. In addition, the second source/drain contact **110** may be connected to the ground rail **20** through a third source/drain contact via VSD3 to ground the first NMOS transistor N1.

(91) A first gate structure **200** is disposed to be spaced apart from the first and second source/drain contacts **100** and **110** in the first direction x. The first gate structure **200** may be disposed on the first active region ACT1 and the second active region ACT2.

(92) A third source/drain contact **120** may be disposed to be spaced apart from the first gate structure **200** in the first direction x. The third source/drain contact **120** may extend in the second direction y and may be disposed on the first active region ACT1 and the second active region ACT2. That is, the drain of the first PMOS transistor P1 and the drain of the first NMOS transistor N1 may be connected to each other through the third source/drain contact **120**. In addition, the source of the third PMOS transistor P3 may be connected to the drain of the third NMOS transistor N3 through the third source/drain contact **120**. That is, the drain of the first PMOS transistor P1, the drain of the first NMOS transistor N1, the source of the third PMOS transistor P3 and the drain of the third NMOS transistor N3 may be connected to each other through the third source/drain contact **120**. By connecting a plurality of transistors through one source/drain contact (e.g., the third source/drain contact **120**), the height of the integrated circuit according to some example embodiments may be lowered.

(93) Thus, the stability of a process for designing a semiconductor integrated circuit including the integrated circuit according to some example embodiments may be improved. In addition, the degree of freedom of a metal line may be increased, and pin congestion may be reduced.

(94) A second gate structure **210** may be disposed on the first active region ACT1 to be spaced apart from the third source/drain contact **120** in the first direction x. In addition, a third gate structure **220** may be disposed on the second active region ACT2 to be spaced apart from the third source/drain contact **120** in the first direction x.

(95) A fourth source/drain contact **130** may be disposed to extend in the second direction y and to be spaced apart from the second gate structure **210** and the third gate structure **220** in the first direction x. A drain of the third PMOS transistor P3 may be connected to a source of the third NMOS transistor N3 through the fourth source/drain contact **130**. In addition, a drain of the fourth PMOS transistor P4 may be connected to a source of the fourth NMOS transistor N4 through the fourth source/drain contact **130**. That is, the drain of the third PMOS transistor P3, the source of the third NMOS transistor N3, the drain of the fourth PMOS transistor P4, and the source of the fourth NMOS transistor N4 may be connected to each other through the fourth source/drain contact **130**. By connecting a plurality of transistors through one source/drain contact (e.g., the fourth source/drain contact **130**), the height of the integrated circuit according to some example embodiments may be lowered.

(96) Thus, the stability of a process for designing a semiconductor integrated circuit including the integrated circuit according to some example embodiments may be improved. In addition, the degree of freedom of a metal line may be increased, and pin congestion may be reduced.

(97) A fourth gate structure **230** may be disposed on the first active region ACT1 to be spaced apart from the fourth source/drain contact **130** in the first direction x. In addition, a fifth gate structure **240** may be disposed on the second active region ACT2 to be spaced apart from the fourth source/drain contact **130** in the first direction x.

(98) A fifth source/drain contact **140** may be disposed to be spaced apart from the fourth gate structure **230** and the fifth gate structure **240** in the first direction x. The fifth source/drain contact **140** may extend in the second direction y and may be disposed on the first active region ACT1 and the second active region ACT2. That is, the source of the fourth PMOS transistor P4 and the drain

of the fourth NMOS transistor N4 may be connected to each other through the fifth source/drain contact **140**. In addition, the drain of the second PMOS transistor P2 may be connected to the drain of the second NMOS transistor N2 through the fifth source/drain contact **140**. That is, the source of the fourth PMOS transistor P4, the drain of the fourth NMOS transistor N4, the drain of the second PMOS transistor P2, and the drain of the second NMOS transistor N2 may be connected to each other through the fifth source/drain contact **140**. By connecting a plurality of transistors through one source/drain contact (e.g., the fifth source/drain contact **140**), the height of the integrated circuit according to some example embodiments may be lowered.

(99) Thus, the stability of a process for designing a semiconductor integrated circuit including the integrated circuit according to some example embodiments may be improved. In addition, the degree of freedom of a metal line may be increased, and pin congestion may be reduced.

(100) A sixth gate structure **250** may be disposed on the first active region ACT1 and the second active region ACT2 to be spaced apart from the fifth source/drain contact **140** in the first direction x. Further, a sixth source/drain contact **150** may be disposed on the first active region ACT1 to be spaced apart from the sixth gate structure **250** in the first direction x. The sixth source/drain contact **150** may be connected to the power rail **10** through a second source/drain contact via VSD2 to supply the power voltage to the second PMOS transistor P2. In addition, a seventh source/drain contact **160** may be disposed on the second active region ACT2 to be spaced apart from the sixth gate structure **250** in the first direction x. The seventh source/drain contact **160** may be connected to the ground rail **20** through a fourth source/drain contact via VSD4 to ground the second NMOS transistor N2.

(101) Next, the structure and operation in which the signal is applied, together with structures extending in the third direction z, will be described.

(102) A fifth gate contact GC5 extending in the third direction z may be disposed on the first gate structure **200**. In addition, a first gate contact via VG1 extending in the third direction z may be disposed on the fifth gate contact GC5. The first gate contact via VG1 may be connected to a first_first metal line M1_1 extending in the first direction x. That is, the first gate structure **200** may be electrically connected to the first_first metal line M1_1, the first gate contact via VG1, and the fifth gate contact GC5 to receive the data signal D. Thus, the first PMOS transistor P1 and the first NMOS transistor N1 may be gated through the data signal D.

(103) The fifth gate contact GC5 and the first gate contact via VG1, which are electrically connected to the first gate structure **200**, are illustrated in this drawing as being disposed on the second active region ACT2, but are not limited thereto, and may be disposed on the first active region ACT1 as illustrated in FIGS. 12 and 13.

(104) A first gate contact GC1 extending in the third direction z may be disposed on the second gate structure **210**. In addition, a second gate contact via VG2 extending in the third direction z may be disposed on the first gate contact GC1. The second gate contact via VG2 may be connected to a first_second metal line M1_2 extending in the first direction x. That is, the second gate structure **210** may be electrically connected to the first_second metal line M1_2, the second gate contact via VG2, and the first gate contact GC1 to receive the scan active signal Se. Thus, the third PMOS transistor P3 may be gated through the scan active signal Se.

(105) The positions of the first gate contact GC1 and the second gate contact via VG2, which are electrically connected to the second gate structure **210**, are not limited thereto.

(106) A third gate contact GC3 extending in the third direction z may be disposed on the third gate structure **220**. In addition, a third gate contact via VG3 extending in the third direction z may be disposed on the third gate contact GC3. The third gate contact via VG3 may be connected to a first_third metal line M1_3 extending in the first direction x. That is, the third gate structure **220** may be electrically connected to the first_third metal line M1_3, the third gate contact via VG3, and the third gate contact GC3 to receive an inverted active signal Se. Thus, the third NMOS transistor N3 may be gated through the inverted active signal Se.

(107) The positions of the third gate contact GC3 and the third gate contact via VG3, which are electrically connected to the third gate structure **220**, are not limited thereto.

(108) A second gate contact GC2 extending in the third direction z may be disposed on the fourth gate structure **230**. In addition, a fourth gate contact via VG4 extending in the third direction z may be disposed on the second gate contact GC2. The fourth gate contact via VG4 may be connected to a first_fifth metal line M1_5 extending in the first direction x. That is, the fourth gate structure **230** may be electrically connected to the first_fifth metal line M1_5, the fourth gate contact via VG4, and the second gate contact GC2 to receive the inverted active signal Se. Thus, the fourth PMOS transistor P4 may be gated through the inverted active signal Se.

(109) The positions of the second gate contact GC2 and the fourth gate contact via VG4, which are electrically connected to the fourth gate structure **230**, are not limited thereto.

(110) A fourth gate contact GC4 extending in the third direction z may be disposed on the fifth gate structure **240**. In addition, a fifth gate contact via VG5 extending in the third direction z may be disposed on the fourth gate contact GC4. The fifth gate contact via VG5 may be connected to a first_sixth metal line M1_6 extending in the first direction x. That is, the fifth gate structure **240** is electrically connected to the first_sixth metal line M1_6, the fifth gate contact via VG5, and the fourth gate contact GC4 to receive the scan active signal Se. Thus, the fourth NMOS transistor N4 may be gated through the scan active signal Se.

(111) The positions of the fourth gate contact GC4 and the fifth gate contact via VG5, which are electrically connected to the fifth gate structure **240**, are not limited thereto.

(112) A sixth gate contact GC6 extending in the third direction z may be disposed on the sixth gate structure **250**. In addition, a sixth gate contact via VG6 extending in the third direction z may be disposed on the sixth gate contact GC6. The sixth gate contact via VG6 may be connected to a first_seventh metal line M1_7 extending in the first direction x. That is, the sixth gate structure **250** may be electrically connected to the first_seventh metal line M1_7, the sixth gate contact via VG6, and the sixth gate contact GC6 to receive the scan input signal Si. Thus, the second PMOS transistor P2 and the second NMOS transistor N2 may be gated through the scan input signal Si.

(113) The sixth gate contact GC6 and the sixth gate contact via VG6, which are electrically connected to the sixth gate structure **250**, are illustrated in this drawing as being disposed on the first active region ACT1, but are not limited thereto, and may be disposed on the second active region ACT2 as illustrated in FIGS. **12** and **13**.

(114) A fifth source/drain contact via VSD5 extending in the third direction z may be disposed on the fourth source/drain contact **130**. In addition, a first_fourth metal line M1_4 extending in the first direction x may be disposed on the fifth source/drain contact via VSD5 and may be connected to the outside.

(115) The fifth source/drain contact via VSD5, which is electrically connected to the fourth source/drain contact **130**, is illustrated in this drawing as being disposed on the first active region ACT1, but is not limited thereto, and may be disposed on the second active region ACT2 as illustrated in FIG. **13**.

(116) The plurality of gate structures (e.g., the first to sixth gate structures **200** to **250**) and the plurality of source/drain contacts (e.g., the first to seventh source/drain contacts **100** to **160**), which are disposed to be adjacent to each other in the first direction x, may be spaced apart from each other by 1 contacted poly pitch (CPP). As an example, the first gate structure **200** and the first source/drain contact **100** adjacent to each other may be spaced apart from each other by 1 CPP.

(117) For example, assume that the first gate structure **200** and the first source/drain contact **100** are adjacent to each other. When the distance between a center line of the first gate structure **200** extending in the second direction y and a center line of the first source/drain contact **100** extending in the second direction y is 1 CPP, it means that the other gate structure or source/drain contact is not disposed between the first gate structure **200** and the first source/drain contact **100**.

(118) Further, the metal lines (e.g., the first_first metal line M1_1 to the first_seventh metal line

M1_7), which are disposed to be adjacent to each other in the second direction y, may be spaced apart from each other by 1 CPP. As an example, the first_first metal line M1_1 and the first_third metal line M1_3 adjacent to each other may be spaced apart from each other by 1 CPP.

(119) For example, assume that the first_first metal line M1_1 and the first_third metal line M1_3 are adjacent to each other. When the distance between a center line of the first_first metal line M1_1 extending in the first direction x and a center line of the first_third metal line M1_3 extending in the first direction x is 1 CPP, it means that the other metal line is not disposed between the first_first metal line M1_1 and the first_third metal line M1_3.

(120) For reference, referring to FIG. 11, the first gate structure 200 and the sixth gate structure 250 may surround the first active fins (e.g., the first fin F1, the second fin F2) and the second active fins (e.g., the third fin F3, and the fourth fin F4). In addition, the second gate structure 210 and the fourth gate structure 230 may surround the first active fins (e.g., the first fin F1 and the second fin F2). In addition, the third gate structure 220 and the fifth gate structure 240 may surround the second active fins (e.g., the third fin F3 and the fourth fin F4).

(121) Each of the layout diagrams of FIGS. 10 to 13 is divided into a front-end-of-line (FEOL), a middle-of-line (MOL), and a back-end-of-line (BEOL) and will be described with reference to FIGS. 14 to 17. In order to avoid duplicate descriptions, description will be made with reference to the layout diagram of FIG. 10.

(122) FIG. 14 is a layout diagram illustrating the FEOL of FIG. 10. FIG. 15 is another layout diagram according to some example embodiments exemplarily illustrating FIG. 14. FIG. 16 is a layout diagram illustrating the MOL of FIG. 10. FIG. 17 is a layout diagram illustrating the BEOL of FIG. 10.

(123) Referring to FIG. 14, the first active region ACT1 and the second active region ACT2 extending in the first direction x are disposed to be spaced apart from each other in the second direction y.

(124) The first active region ACT1 may be a region in which a p-type transistor is formed. For example, the first active region ACT1 may include a well region doped with n-type impurities. The second active region ACT2 may be a region in which an n-type transistor is formed. For example, the second active region ACT2 may include a well region doped with p-type impurities.

(125) Although not illustrated in the drawing, a first active fin protruding from the first active region ACT1 in the third direction z may be formed on the first active region ACT1. In addition, a second active fin protruding from the second active region ACT2 in the third direction z may be formed on the second active region ACT2. The first active fin and the second active fin may be formed to be spaced apart from each other in the second direction y. In addition, the first active fin and the second active fin may each extend in the first direction x.

(126) Referring to FIG. 15, the thicknesses of active regions in a plurality of cells (e.g., a 1a-th cell C1a, a 1b-th cell C1b, and a 1c-th cell C1c) in the second direction y may be different.

(127) For example, a 1a-th active region ACT1a of the 1a-th cell C1a may be formed from a boundary A1 of the 1a-th cell C1a to a boundary A4 of the 1a-th cell C1a, which is spaced apart from a 2a-th active region ACT2a. Similarly, the 2a-th active region ACT2a of the 1a-th cell C1a may be formed from a boundary B1 of the 1a-th cell C1a to a boundary B4 of the 1a-th cell C1a, which is spaced apart from the 1a-th active region ACT1a. That is, the 1a-th active region ACT1a and the 2a-th active region ACT2a may be disposed to be spaced apart from each other in the second direction y by a first length D1.

(128) A 1b-th active region ACT1b of the 1b-th cell C1b adjacent to the 1a-th cell C1a may be formed from a boundary A1 of the 1b-th cell C1b to a boundary A3 of the 1b-th cell C1b, which is spaced apart from a 2b-th active region ACT2b. Similarly, the 2b-th active region ACT2b of the 1b-th cell C1b may be formed from a boundary B1 of the 1b-th cell C1b to a boundary B3 of the 1b-th cell C1b, which is spaced apart from the 1b-th active region ACT1b. That is, the 1b-th active region ACT1b and the 2b-th active region ACT2b may be disposed to be spaced apart from each other in

the second direction y by a second length D2.

(129) A **1c**-th active region ACT**1c** of the **1c**-th cell C**1c** adjacent to the **1b**-th cell C**1b** may be formed from a boundary A**1** of the **1c**-th cell C**1c** to a boundary A**2** of the **1c**-th cell C**1c**, which is spaced apart from a **2c**-th active region ACT**2c**. Similarly, the **2c**-th active region ACT**2c** of the **1c**-th cell C**1c** may be formed from a boundary B**1** of the **1c**-th cell C**1c** to a boundary B**2** of the **1c**-th cell C**1c**, which is spaced apart from the **1c**-th active region ACT**1c**. That is, the **1c**-th active region ACT**1c** and the **2c**-th active region ACT**2c** may be disposed to be spaced apart from each other in the second direction y by a third length D3.

(130) The shape and arrangement of the active regions disposed in successive cells is not limited to those illustrated in this drawing.

(131) Referring to FIG. 16, the plurality of source/drain contacts (e.g., the first to seventh source/drain contacts **100** to **160**) and the plurality of gate structures (e.g., the first to sixth gate structures **200** to **250**) may be disposed to be spaced apart from each other in the first direction x. The plurality of source/drain contacts (e.g., the first to seventh source/drain contacts **100** to **160**) and the plurality of gate structures (e.g., the first to sixth gate structures **200** to **250**) may each extend in the second direction y.

(132) The plurality of gate structures (e.g., the first to sixth gate structures **200** to **250**) and the plurality of source/drain contacts (e.g., the first to seventh source/drain contacts **100** to **160**), which are disposed to be adjacent to each other in the first direction x, may be spaced apart from each other by 1 CPP. As an example, the first gate structure **200** and the first source/drain contact **100** adjacent to each other may be spaced apart from each other by 1 CPP.

(133) For example, assume that the first gate structure **200** and the first source/drain contact **100** are adjacent to each other. When the distance between the center line of the first gate structure **200** extending in the second direction y and the center line of the first source/drain contact **100** extending in the second direction y is 1 CPP, it means that the other gate structure or source/drain contact is not disposed between the first gate structure **200** and the first source/drain contact **100**.

(134) Referring to FIG. 17, the plurality of metal lines (e.g., the first_first to first_seventh metal lines M**1_1** to M**1_7**), the power rail **10**, and the ground rail **20** may be disposed to be spaced apart from each other in the second direction y. The plurality of metal lines (e.g., the first_first to first_seventh metal lines M**1_1** to M**1_7**), the power rail **10**, and the ground rail **20** may each extend in the first direction x.

(135) The first source/drain contact via VSD**1** and the second source/drain contact via VSD**2** for transferring the power voltage to the source/drain contact may be disposed on the power rail **10**. In addition, the third source/drain contact via VSD**3** and the fourth source/drain contact via VSD**4** for grounding the source/drain contact may be disposed on the ground rail **20**.

(136) The first_first metal line M**1_1**, the first_second metal line M**1_2**, the first_third metal line M**1_3**, the first_fifth metal line M**1_5**, the first_sixth metal line M**1_6**, and the first_seventh metal line M**1_7** may be respectively connected to the plurality of gate contacts (e.g., the first to sixth gate contacts GC**1** to GC**6**), for gating the gate structures, and the plurality of gate contact vias (e.g., the first to sixth gate contact vias VG**1** to VG**6**) disposed in the plurality of gate contacts. The plurality of gate contacts (e.g., the first to sixth gate contacts GC**1** to GC**6**) and the plurality of gate contact vias (e.g., the first to sixth gate contact vias VG**1** to VG**6**) may extend in the third direction z.

(137) The metal lines (e.g., the first_first to first_seventh metal lines M**1_1** to M**1_7**), which are disposed to be adjacent to each other in the second direction y, may be spaced apart from each other by 1 CPP. As an example, the first_first metal line M**1_1** and the first_third metal line M**1_3** adjacent to each other may be spaced apart from each other by 1 CPP.

(138) For example, assume that the first_first metal line M**1_1** and the first_third metal line M**1_3** are adjacent to each other. When the distance between the center line of the first_first metal line M**1_1** extending in the first direction x and the center line of the first_third metal line M**1_3** extending in the first direction x is 1 CPP, it means that the other metal line is not disposed between

the first_first metal line **M1_1** and the first_third metal line **M13**.

(139) Cross-sectional views of the layout diagrams of FIGS. **10** to **13** will be described with reference to FIGS. **18** to **23**. In order to avoid duplicate descriptions, description will be made with reference to the layout diagram of FIG. **10**.

(140) FIGS. **18** and **19** are cross-sectional views taken along line A-A' of FIG. **10**. FIGS. **20** and **21** are cross-sectional views taken along line B-B' of FIG. **10**. FIGS. **22** and **23** are cross-sectional views taken along line C-C' of FIG. **10**.

(141) Referring to FIG. **18**, the semiconductor integrated circuit including the integrated circuit according to some example embodiments may have a fin-type transistor (FinFET) structure including a channel region of a fin-type pattern shape.

(142) The fin-type transistor according to some example embodiments may be formed above a substrate Sub and on the active region (e.g., the first active region **ACT1**) disposed on the substrate Sub.

(143) The substrate Sub may be a silicon substrate or a silicon-on-insulator (SOI). Alternatively, the substrate Sub may include silicon germanium, silicon germanium on insulator (SGOI), indium antimonide, lead tellurium compound, indium arsenide, indium phosphide, gallium arsenide, and/or gallium antimonide, but the present disclosure is not limited thereto.

(144) The first active region **ACT1** may be defined along the first direction x. The first active region **ACT1** may be defined by a deep trench. The first active region **ACT1** may be a region in which a p-type transistor is formed. For example, the first active region **ACT1** may include a well region doped with n-type impurities. The first active region **ACT1** may protrude from the substrate Sub. The first active region **ACT1** may include an epitaxial layer grown from the substrate Sub.

(145) The fin-type transistor according to some example embodiments includes the plurality of gate structures (e.g., the first gate structure **200**, the second gate structure **210**, the fourth gate structure **230**, and the sixth gate structure **250**), a source/drain region **300**, a silicide layer **310**, a first interlayer insulating film **400**, and a second interlayer insulating film **500**.

(146) Each of the plurality of gate structures (e.g., the first gate structure **200**, the second gate structure **210**, the fourth gate structure **230**, and the sixth gate structure **250**) may include a gate spacer **202**, a gate insulating film **204**, a gate electrode **206**, and a capping pattern **208**.

(147) The structure of each of the plurality of gate structures is not limited to that illustrated in this drawing.

(148) The plurality of gate structures (e.g., the first gate structure **200**, the second gate structure **210**, the fourth gate structure **230**, and the sixth gate structure **250**) and the source/drain region **300** may extend in the second direction y on the first active region **ACT1**.

(149) The gate spacer **202** may extend in the third direction z along both sidewalls of the gate insulating film **204**. The gate insulating film **204** may be disposed between the gate electrode **206** and the gate spacer **202** and below the capping pattern **208**. The capping pattern **208** may be disposed on each of the gate electrode **206** and the gate insulating film **204**. The gate spacer **202**, the gate insulating film **204**, and the capping pattern **208** may include an insulating material.

(150) The source/drain region **300** may be formed by removing a portion of the first active region **ACT1** to form a recess and then filling the recess through an epitaxial process. The source/drain region **300** may be formed on the first active region **ACT1**. The source/drain region **300** may be doped with impurities of a conductivity type which is different from that of the semiconductor pattern formed on the first active region **ACT1**.

(151) The fin-type transistor according to some example embodiments further includes a plurality of gate contacts (e.g., the first gate contact **GC1** and the second gate contact **GC2**), a plurality of gate contact vias (e.g., the second gate contact via **VG2** and the fourth gate contact via **VG4**), a plurality of source/drain contacts (e.g., the first source/drain contact **100**, the third source/drain contact **120**, the fifth source/drain contact **140**, and the sixth source/drain contact **150**), a third interlayer insulating film **600**, a fourth interlayer insulating film **700**, and a plurality of metal lines

(e.g., the first_second metal line M1_2 and the first_fifth metal line M1_5) in order to receive electric signals.

(152) The silicide layer **310** may be disposed between the source/drain region **300** and each of the plurality of source/drain contacts (e.g., the first source/drain contact **100**, the third source/drain contact **120**, the fifth source/drain contact **140**, and the sixth source/drain contact **150**).

(153) The plurality of source/drain contacts (e.g., the first source/drain contact **100**, the third source/drain contact **120**, the fifth source/drain contact **140**, and the sixth source/drain contact **150**) may be electrically connected to each other through the source/drain region **300** and the silicide layer **310**. Each of the plurality of source/drain contacts (e.g., the first source/drain contact **100**, the third source/drain contact **120**, the fifth source/drain contact **140**, and the sixth source/drain contact **150**) may be formed in the third direction z and may extend in the second direction y.

(154) The plurality of gate contacts (e.g., the first gate contact GC1 and the second gate contact GC2) may be electrically connected to the gate structures (e.g., the second gate structure **210** and the fourth gate structure **230**), respectively. The plurality of gate contact vias (e.g., the second gate contact via VG2 and the fourth gate contact via VG4) may be electrically connected to the plurality of gate contacts (e.g., the first gate contact GC1 and the second gate contact GC2), respectively. The plurality of gate contact vias (e.g., the second gate contact via VG2 and the fourth gate contact via VG4) may be electrically connected to the metal lines (e.g., the first_second metal line M1_2 and the first_fifth metal line M1_5), respectively.

(155) The first interlayer insulating film **400** may surround the plurality of gate structures (e.g., the first gate structure **200**, the second gate structure **210**, the fourth gate structure **230**, and the sixth gate structure **250**) and the plurality of source/drain contacts (e.g., the first source/drain contact **100**, the third source/drain contact **120**, the fifth source/drain contact **140**, and the sixth source/drain contact **150**).

(156) The second interlayer insulating film **500** may be formed on the first interlayer insulating film **400**. The second interlayer insulating film **500** may surround the plurality of source/drain contacts (e.g., the first source/drain contact **100**, the third source/drain contact **120**, the fifth source/drain contact **140**, and the sixth source/drain contact **150**).

(157) The third interlayer insulating film **600** may be formed on the second interlayer insulating film **500**. The third interlayer insulating film **600** may surround the plurality of gate contact vias (e.g., the second gate contact via VG2 and the fourth gate contact via VG4).

(158) The fourth interlayer insulating film **700** may be formed on the third interlayer insulating film **600**. The fourth interlayer insulating film **700** may surround the metal lines (e.g., the first_second metal line M1_2 and the first_fifth metal line M1_5).

(159) The first to fourth interlayer insulating films **400** and **700** may include an insulating material.

(160) Referring to FIG. **19**, the semiconductor integrated circuit including the integrated circuit according to some example embodiments may have a multi-bridge channel field effect transistor (MBCFET) structure including a plurality of nanowires. Descriptions overlapping with FIG. **18** will be omitted, and the description will be mainly focused on the differences.

(161) A first nanowire **201**, a second nanowire **203**, and a third nanowire **205** may be sequentially disposed to be spaced apart from each other on the substrate Sub or the first active region ACT1 in the third direction z. The first to third nanowires **201** to **205** may extend in the second direction y.

(162) The gate electrode **206**, the gate insulating film **204** surrounding the gate electrode **206**, and the gate spacer **202** formed on sidewalls of the gate insulating film **204** may surround each of the first to third nanowires **201** to **205**.

(163) The gate spacer **202** is illustrated as being formed of a single layer, but the present disclosure is not limited thereto. That is, in some example embodiments, the gate spacer **202** may be formed of multiple films.

(164) The gate insulating film **204** may be disposed between the gate electrode **206** and the gate spacer **202**, between the gate electrode **206** and the third nanowire **205**, between the gate electrode

206 and the second nanowire **203**, between the gate electrode **206** and the first nanowire **201**, and between the gate electrode **206** and the first active region **ACT1**.

(165) The source/drain region **300** may be disposed on at least one side of each of the first to third nanowires **201** to **205**. In addition, the source/drain region **300** may be in contact with each of the first to third nanowires **201** to **205**.

(166) Referring to FIG. **20**, a plurality of source/drain regions **300** and **302** may be formed on the first active region **ACT1** and the second active region **ACT2**, respectively, disposed on the substrate **SUB**. Descriptions overlapping with the above descriptions will be omitted.

(167) At least a portion of the plurality of source/drain regions **300** and **302** may be included in the source/drain region of the plurality of transistors. The source/drain region **300** formed on the first active region **ACT1** and the source/drain region **302** formed on the second active region **ACT2** may be doped with impurities of different conductivity types.

(168) A cell isolation film **350** may be formed on the substrate **Sub**. The cell isolation film **350** may fill a deep trench separating the first active region **ACT1** from the second active region **ACT2**. The cell isolation film **350** may extend in the first direction **x**. The cell isolation film **350** may include an insulating material.

(169) A source/drain contact cut pattern **410** may be disposed on the cell isolation film **350**. The source/drain contact cut pattern **410** may extend in the first direction **x**. The source/drain contact cut pattern **410** may include an insulating material.

(170) The source/drain contact cut pattern **410** may cut the source/drain contacts at the boundary of the cells. The source/drain contact cut pattern **410** may be in contact with the source/drain contacts (e.g., the first source/drain contact **100** and the second source/drain contact **110**).

(171) A first source/drain upper contact **102** is formed on the first source/drain contact **100**, and the first source/drain upper contact **102** and the first source/drain contact **100** may fill a trench defined by the silicide layer **310**.

(172) Similarly, a second source/drain upper contact **112** is formed on the second source/drain contact **110**, and the second source/drain upper contact **112** and the second source/drain contact **110** may fill a trench defined by a silicide layer **312**.

(173) The second interlayer insulating film **500** is disposed between the first source/drain upper contact **102**, the first source/drain contact **100**, the second source/drain upper contact **112**, and the second source/drain contact **110**. The second interlayer insulating film **500** may be disposed on the first interlayer insulating film.

(174) The first source/drain contact via **VSD1** may be disposed on the first source/drain upper contact **102**. In addition, the third source/drain contact via **VSD3** may be disposed on the second source/drain upper contact **112**.

(175) The power rail **10** may be disposed on the first source/drain contact via **VSD1**, and the ground rail **20** may be disposed on the third source/drain contact via **VSD3**.

(176) The third interlayer insulating film **600** may be disposed on the second interlayer insulating film **500**, and the fourth interlayer insulating film **700** may be disposed on the third interlayer insulating film **600**.

(177) With reference to FIG. **21**, the difference from FIG. **20** will be mainly described. In FIG. **21**, the silicide layers **310** and **312** may be formed only between the source/drain regions **300** and **302** unlike in FIG. **20**. That is, the silicide layer **310** may not be formed on an outer sidewall of each of the first source/drain contact **100** and the first source/drain upper contact **102** in the first direction **x**. In addition, the silicide layer **312** may not be formed on an outer sidewall of each of the second source/drain contact **110** and a second source/drain upper contact **112** in the first direction **x**.

(178) Referring to FIG. **22**, the semiconductor integrated circuit including the integrated circuit according to some example embodiments may have a fin-type transistor (FinFET) structure including a channel region of a fin-type pattern shape. Hereinafter, the description overlapping with FIG. **18** will be omitted.

(179) The fin-type transistor according to some example embodiments may be formed above the substrate Sub and on the active regions (e.g., the first active region ACT1 and the second active region ACT2) disposed on the substrate Sub.

(180) A first active upper region ACT1_U may be formed on the first active region ACT1. In addition, a second active upper region ACT2_U may be formed on the second active region ACT2. The gate insulating film 204 may be formed along the first active upper region ACT1_U and the second active upper region ACT2_U. In addition, the gate insulating film 204 may also be formed in a region in which the gate electrode 206 meets the cell isolation film 350.

(181) The gate electrode 206 may be formed on the gate insulating film 204. The gate electrode 206 may be cut by a gate cut pattern 404 and a gate cut pattern spacer 402 formed on sidewalls of the gate cut pattern 404. In addition, the capping pattern 208 on the gate electrode 206 may also be cut by the gate cut pattern 404 and the gate cut pattern spacer 402 formed on the sidewalls of the gate cut pattern 404. The gate cut pattern 404 and the gate cut pattern spacer 402 may include an insulating material.

(182) The second gate contact GC2 and the third gate contact GC3 may be electrically connected to the gate electrode 206 through the capping pattern 208. The fourth gate contact via VG4 and the fifth gate contact via VG5 may be electrically connected to the second gate contact GC2 and the third gate contact GC3, respectively. The first_fifth metal line M1_5 is disposed on the fourth gate contact via VG4 so that the inverted scan active signal Se may be applied to the gate electrode 206 disposed on the first active region ACT1. In addition, the first_sixth metal line M1_6 is disposed on the fifth gate contact via VG5 so that the scan active signal Se may be applied to the gate electrode 206 disposed on the second active region ACT2.

(183) The second interlayer insulating film 500 is formed on the capping pattern 208, the gate cut pattern 404, and the gate cut pattern spacer 402, the third interlayer insulating film 600 is formed on the second interlayer insulating film 500, and the fourth interlayer insulating film 700 is formed on the third interlayer insulating film 600.

(184) Referring to FIG. 23, the semiconductor integrated circuit including the integrated circuit according to some example embodiments may have an MBCFET structure including a plurality of nanowires. Description will be mainly focused on the differences from FIG. 22.

(185) In FIG. 23, the first to third nanowires 201 to 205 may be included on each of the first active upper region ACT1_U and the second active upper region ACT2_U unlike in FIG. 22. Each of the nanowires is surrounded by the gate electrode 206 and the gate insulating film 204.

(186) An enlarged top view as viewed from the top when the source/drain contact is cut, and an enlarged top view as viewed from the top when the gate structure is cut will be described with reference to FIGS. 24 to 27.

(187) FIGS. 24 and 25 are enlarged views for describing a region SDTR shown in FIG. 10. FIGS. 26 and 27 are enlarged views for describing a region GTR shown in FIG. 10.

(188) Referring to FIG. 24, a region SDTRa of the region SDTR is illustrated in which the previously cut first source/drain contact 100 and sixth source/drain contact 150 are disposed on the layout diagram.

(189) The cut portions of the first source/drain contact 100 and the sixth source/drain contact 150 may have a convex shape. The cut portion of each of the first source/drain contact 100 and the sixth source/drain contact 150 may be an end thereof in the second direction y.

(190) On the other hand, referring to FIG. 25, a cross-sectional view is illustrated in which the first and sixth source/drain contacts 100 and 150 are cut after being formed in the second direction y across both the first active region and the second active region. That is, a region SDTRb of the region SDTR is illustrated.

(191) The cut portions of the first source/drain contact 100 and the sixth source/drain contact 150 may have a concave shape. The cut portion of each of the first source/drain contact 100 and the sixth source/drain contact 150 may be an end thereof in the second direction y.

(192) Referring to FIG. 26, a region GTR of the region GTR is illustrated in which the previously cut second gate structure 210 and third gate structure 220 are disposed on the layout diagram.

(193) The cut portions of the second gate structure 210 and the third gate structure 220 facing each other have a convex shape. The cut portions of the second gate structure 210 and the third gate structure 220 facing each other may be ends of the second gate structure 210 and the third gate structure 220, respectively.

(194) On the other hand, referring to FIG. 27, a cross-sectional view is illustrated in which the second gate structure 210 and the third gate structure 220 are cut after being continuously formed in the second direction y across both the first active region and the second active region. That is, a region GTRb of the region GTR is illustrated.

(195) The cut portions of the second gate structure 210 and the third gate structure 220 may have a convex shape. The cut portions of the second gate structure 210 and the third gate structure 220 facing each other may be ends of the second gate structure 210 and the third gate structure 220, respectively. The second gate structure 210 and the third gate structure 220 formed continuously in the second direction y across both the first active region and the second active region may be formed by cutting like being punched with a punch.

(196) FIG. 28 is a circuit diagram illustrating the scan circuit S_C shown in FIG. 8.

(197) Referring to FIG. 28, unlike the scan circuit S_C(R3_1) shown in FIG. 9, the circuit that receives the data signal D may be configured as a first tri-state inverter TRI1.

(198) That is, a scan circuit S_C(R3_2) including the integrated circuit according to some example embodiments may invert and output the data signal D under the control of the scan active signal. The description of the tri-state inverter is overlapped with the description of FIG. 1, and thus the description thereof will be omitted.

(199) FIGS. 29 to 31 are layout diagrams according to some example embodiments exemplarily illustrating FIG. 28. Hereinafter, in order to avoid duplicate descriptions, the common parts of FIGS. 29 to 31 are described only through FIG. 29, and only the differences will be briefly described with reference to the corresponding drawings.

(200) Referring to FIG. 29, first to fourth PMOS transistors P1 to P4 may be formed on a first active region ACT1 extending in a first direction x. Further, first to fourth NMOS transistors N1 to N4 may be formed on a second active region ACT2 extending in the first direction x and disposed to be spaced apart from the first active region ACT1 in a second direction y.

(201) A power rail 10 may be disposed at an upper portion of the first active region ACT1 in the second direction y. In addition, a ground rail 20 may be disposed at a lower portion of the second active region ACT2 in the second direction y.

(202) A scan circuit S_C(R3_2a) including the integrated circuit according to some example embodiments may include a plurality of gate structures and a plurality of source/drain contacts extending in the second direction y and disposed to be spaced apart from each other in the first direction x.

(203) For example, a first source/drain contact 100 and a second source/drain contact 110 may be disposed on the first active region ACT1 and the second active region ACT2, respectively, to be spaced apart from each other in the second direction y. That is, the first source/drain contact 100 may be connected to the power rail 10 through a first source/drain contact via VSD1 to supply the power voltage to the first PMOS transistor P1. In addition, the second source/drain contact 110 may be connected to the ground rail 20 through a third source/drain contact via VSD3 to ground the first NMOS transistor N1.

(204) A first gate structure 200 is disposed to be spaced apart from the first and second source/drain contacts 100 and 110 in the first direction x. The first gate structure 200 may be disposed on the first active region ACT1 and the second active region ACT2.

(205) A third source/drain contact 120 and a fourth source/drain contact 130 may be disposed on the first active region ACT1 and the second active region ACT2, respectively, to be spaced apart

from each other in the second direction y and to be spaced apart from the first gate structure **200** in the first direction x.

(206) A second gate structure **210** may be disposed on the first active region ACT1 to be spaced apart from the third source/drain contact **120** and the fourth source/drain contact **130** in the first direction x. In addition, a third gate structure **220** may be disposed on the second active region ACT2 to be spaced apart from the third source/drain contact **120** and the fourth source/drain contact **130** in the first direction x.

(207) A fifth source/drain contact **140** may be disposed to extend in the second direction y and to be spaced apart from the second gate structure **210** and the third gate structure **220** in the first direction x. A drain of the third PMOS transistor P3 may be connected to a drain of the third NMOS transistor N3 through the fifth source/drain contact **140**. In addition, a drain of the fourth PMOS transistor P4 may be connected to a source of the fourth NMOS transistor N4 through the fifth source/drain contact **140**. That is, the drain of the third PMOS transistor P3, the drain of the third NMOS transistor N3, the drain of the fourth PMOS transistor P4, and the source of the fourth NMOS transistor N4 may be connected to each other through the fifth source/drain contact **140**. By connecting a plurality of transistors through one source/drain contact (e.g., the fifth source/drain contact **140**), the height of the integrated circuit according to some example embodiments may be lowered.

(208) Thus, the stability of a process for designing a semiconductor integrated circuit including the integrated circuit according to some example embodiments may be improved. In addition, the degree of freedom of a metal line may be increased, and pin congestion may be reduced.

(209) A fourth gate structure **230** may be disposed on the first active region ACT1 to be spaced apart from the fifth source/drain contact **140** in the first direction x. In addition, a fifth gate structure **240** may be disposed on the second active region ACT2 to be spaced apart from the fifth source/drain contact **140** in the first direction x.

(210) A sixth source/drain contact **150** may be disposed to be spaced apart from the fourth gate structure **230** and the fifth gate structure **240** in the first direction x. The sixth source/drain contact **150** may extend in the second direction y and may be disposed on the first active region ACT1 and the second active region ACT2. That is, a source of the fourth PMOS transistor P4 and a drain of the fourth NMOS transistor N4 may be connected to each other through the sixth source/drain contact **150**. In addition, a drain of the second PMOS transistor P2 may be connected to a drain of the second NMOS transistor N2 through the sixth source/drain contact **150**. That is, the source of the fourth PMOS transistor P4, the drain of the fourth NMOS transistor N4, the drain of the second PMOS transistor P2, and the drain of the second NMOS transistor N2 may be connected to each other through the sixth source/drain contact **150**. By connecting a plurality of transistors through one source/drain contact (e.g., the sixth source/drain contact **150**), the height of the integrated circuit according to some example embodiments may be lowered.

(211) Thus, the stability of a process for designing a semiconductor integrated circuit including the integrated circuit according to some example embodiments may be improved. In addition, the degree of freedom of a metal line may be increased, and pin congestion may be reduced.

(212) A sixth gate structure **250** may be disposed on the first active region ACT1 and the second active region ACT2 to be spaced apart from the sixth source/drain contact **150** in the first direction x. In addition, a seventh source/drain contact **160** may be disposed on the first active region ACT1 to be spaced apart from the sixth gate structure **250** in the first direction x. The seventh source/drain contact **160** may be connected to the power rail **10** through a second source/drain contact via VSD2 to supply the power voltage to the second PMOS transistor P2. In addition, an eighth source/drain contact **170** may be disposed on the second active region ACT2 to be spaced apart from the sixth gate structure **250** in the first direction x. The eighth source/drain contact **170** may be connected to the ground rail **20** through a fourth source/drain contact via VSD4 to ground the second NMOS transistor N2.

(213) Next, the structure and operation to which the signal is applied, together with structures extending in a third direction z, will be described.

(214) A fifth gate contact GC5 extending in the third direction z may be disposed on the first gate structure **200**. In addition, a first gate contact via VG1 extending in the third direction z may be disposed on the fifth gate contact GC5. The first gate contact via VG1 may be connected to a first_first metal line M1_1 extending in the first direction x. That is, the first gate structure **200** may be electrically connected to the first_first metal line M1_1, the first gate contact via VG1, and the fifth gate contact GC5 to receive the data signal D. Thus, the first PMOS transistor P1 and the first NMOS transistor N1 may be gated through the data signal D.

(215) The fifth gate contact GC5 and the first gate contact via VG1, which are electrically connected to the first gate structure **200**, are illustrated in this drawing as being disposed on the first active region ACT1, but are not limited thereto, and may be disposed on the second active region ACT2 as illustrated in FIGS. **30** and **31**.

(216) A first gate contact GC1 extending in the third direction z may be disposed on the second gate structure **210**. In addition, a second gate contact via VG2 extending in the third direction z may be disposed on the first gate contact GC1. The second gate contact via VG2 may be connected to a first_second metal line M1_2 extending in the first direction x. That is, the second gate structure **210** may be electrically connected to the first_second metal line M1_2, the second gate contact via VG2, and the first gate contact GC1 to receive the scan active signal Se. Thus, the third PMOS transistor P3 may be gated through the scan active signal Se.

(217) The positions of the first gate contact GC1 and the second gate contact via VG2, which are electrically connected to the second gate structure **210**, are not limited thereto.

(218) A third gate contact GC3 extending in the third direction z may be disposed on the third gate structure **220**. In addition, a third gate contact via VG3 extending in the third direction z may be disposed on the third gate contact GC3. The third gate contact via VG3 may be connected to a first_third metal line M1_3 extending in the first direction x. That is, the third gate structure **220** may be electrically connected to the first_third metal line M1_3, the third gate contact via VG3, and the third gate contact GC3 to receive the inverted active signal Se. Thus, the third NMOS transistor N3 may be gated through the inverted active signal Se.

(219) The positions of the third gate contact GC3 and the third gate contact via VG3, which are electrically connected to the third gate structure **220**, are not limited thereto.

(220) A second gate contact GC2 extending in the third direction z may be disposed on the fourth gate structure **230**. In addition, a fourth gate contact via VG4 extending in the third direction z may be disposed on the second gate contact GC2. The fourth gate contact via VG4 may be connected to a first_fifth metal line M1_5 extending in the first direction x. That is, the fourth gate structure **230** may be electrically connected to the first_fifth metal line M1_5, the fourth gate contact via VG4, and the second gate contact GC2 to receive the inverted active signal Se. Thus, the fourth PMOS transistor P4 may be gated through the inverted active signal Se.

(221) The positions of the second gate contact GC2 and the fourth gate contact via VG4, which are electrically connected to the fourth gate structure **230**, are not limited thereto.

(222) A fourth gate contact GC4 extending in the third direction z may be disposed on the fifth gate structure **240**. In addition, a fifth gate contact via VG5 extending in the third direction z may be disposed on the fourth gate contact GC4. The fifth gate contact via VG5 may be connected to a first_sixth metal line M1_6 extending in the first direction x. That is, the fifth gate structure **240** is electrically connected to the first_sixth metal line M1_6, the fifth gate contact via VG5, and the fourth gate contact GC4 to receive the scan active signal Se. Thus, the fourth NMOS transistor N4 may be gated through the scan active signal Se.

(223) The positions of the fourth gate contact GC4 and the fifth gate contact via VG5, which are electrically connected to the fifth gate structure **240**, are not limited thereto.

(224) A sixth gate contact GC6 extending in the third direction z may be disposed on the sixth gate

structure **250**. In addition, a sixth gate contact via **VG6** extending in the third direction **z** may be disposed on the sixth gate contact **GC6**. The sixth gate contact via **VG6** may be connected to a first_seventh metal line **M1_7** extending in the first direction **x**. That is, the sixth gate structure **250** may be electrically connected to the first_seventh metal line **M1_7**, the sixth gate contact via **VG6**, and the sixth gate contact **GC6** to receive the scan input signal **Si**. Thus, the second PMOS transistor **P2** and the second NMOS transistor **N2** may be gated through the scan input signal **Si**. (225) The sixth gate contact **GC6** and the sixth gate contact via **VG6**, which are electrically connected to the sixth gate structure **250**, are illustrated in this drawing as being disposed on the second active region **ACT2**, but are not limited thereto, and may be disposed on the first active region **ACT1** as illustrated in FIGS. **30** and **31**.

(226) A fifth source/drain contact via **VSD5** extending in the third direction **z** may be disposed on the fifth source/drain contact **140**. In addition, a first_fourth metal line **M1_4** extending in the first direction **x** may be disposed on the fifth source/drain contact via **VSD5** and may be connected to the outside.

(227) The fifth source/drain contact via **VSD5**, which is electrically connected to the fifth source/drain contact **140**, is illustrated in this drawing as being disposed on the first active region **ACT1**, but is not limited thereto, and may be disposed on the second active region **ACT2** as illustrated in FIG. **31**.

(228) The plurality of gate structures (e.g., the first to sixth gate structures **200** to **250**) and the plurality of source/drain contacts (e.g., the first to eighth source/drain contacts **100** to **170**), which are disposed to be adjacent to each other in the first direction **x**, may be spaced apart from each other by 1 CPP. As an example, the first gate structure **200** and the first source/drain contact **100** adjacent to each other may be spaced apart from each other by 1 CPP.

(229) For example, assume that the first gate structure **200** and the first source/drain contact **100** are adjacent to each other. When the distance between a center line of the first gate structure **200** extending in the second direction **y** and a center line of the first source/drain contact **100** extending in the second direction **y** is 1 CPP, it means that the other gate structure or source/drain contact is not disposed between the first gate structure **200** and the first source/drain contact **100**.

(230) Further, the metal lines (e.g., the first_first to first_seventh metal lines **M1_1** to **M1_7**), which are disposed to be adjacent to each other in the second direction **y**, may be spaced apart from each other by 1 CPP. As an example, the first_first metal line **M1_1** and the first_second metal line **M1_2** adjacent to each other may be spaced apart from each other by 1 CPP.

(231) For example, assume that the first_first metal line **M1_1** and the first_second metal line **M1_2** are adjacent to each other. When the distance between a center line of the first_first metal line **M1_1** extending in the first direction **x** and a center line of the first_second metal line **M1_2** extending in the first direction **x** is 1 CPP, it means that the other metal line is not disposed between the first_first metal line **M1_1** and the first_second metal line **M1_2**.

(232) FIG. **32** is a circuit diagram illustrating the scan circuit **S_C** shown in FIG. **8**.

(233) Referring to FIG. **32**, unlike the scan circuit **S_C(R3_1)** shown in FIG. **9**, the circuit that receives the scan input signal **Si** may be configured as a second tri-state inverter **TRI2**.

(234) That is, a scan circuit **S_C(R3_3)** including the integrated circuit according to some example embodiments may invert and output the scan input signal **Si** under the control of the scan active signal. The description of the tri-state inverter is overlapped with the description of FIG. **1**, and thus the description thereof will be omitted.

(235) FIGS. **33** to **35** are layout diagrams according to some example embodiments exemplarily illustrating FIG. **32**. Hereinafter, in order to avoid duplicate descriptions, the common parts of FIGS. **33** to **35** are described only through FIG. **33**, and only the differences will be briefly described with reference to the corresponding drawings.

(236) Referring to FIG. **33**, first to fourth PMOS transistors **P1** to **P4** may be formed on a first active region **ACT1** extending in a first direction **x**. Further, first to fourth NMOS transistors **N1** to

N4 may be formed on a second active region **ACT2** extending in the first direction **x** and disposed to be spaced apart from the first active region **ACT1** in a second direction **y**.

(237) A power rail **10** may be disposed at an upper portion of the first active region **ACT1** in the second direction **y**. In addition, a ground rail **20** may be disposed at a lower portion of the second active region **ACT2** in the second direction **y**.

(238) A scan circuit **S_C(R3_3a)** including the integrated circuit according to some example embodiments may include a plurality of gate structures and a plurality of source/drain contacts extending in the second direction **y** and disposed to be spaced apart from each other in the first direction **x**.

(239) For example, a first source/drain contact **100** and a second source/drain contact **110** may be disposed on the first active region **ACT1** and the second active region **ACT2**, respectively, to be spaced apart from each other in the second direction **y**. That is, the first source/drain contact **100** may be connected to the power rail **10** through a first source/drain contact via **VSD1** to supply the power voltage to the first PMOS transistor **P1**. In addition, the second source/drain contact **110** may be connected to the ground rail **20** through a third source/drain contact via **VSD3** to ground the first NMOS transistor **N1**.

(240) A first gate structure **200** is disposed to be spaced apart from the first and second source/drain contacts **100** and **110** in the first direction **x**. The first gate structure **200** may be disposed on the first active region **ACT1** and the second active region **ACT2**.

(241) A third source/drain contact **120** may be disposed to be spaced apart from the first gate structure **200** in the first direction **x**. The third source/drain contact **120** may extend in the second direction **y** and may be disposed on the first active region **ACT1** and the second active region **ACT2**. That is, a drain of the first PMOS transistor **P1** and a drain of the first NMOS transistor **N1** may be connected to each other through the third source/drain contact **120**. In addition, a source of the third PMOS transistor **P3** may be connected to a drain of the third NMOS transistor **N3** through the third source/drain contact **120**. That is, the drain of the first PMOS transistor **P1**, the drain of the first NMOS transistor **N1**, the source of the third PMOS transistor **P3** and the drain of the third NMOS transistor **N3** may be connected to each other through the third source/drain contact **120**. By connecting a plurality of transistors through one source/drain contact (e.g., the third source/drain contact **120**), the height of the integrated circuit according to some example embodiments may be lowered.

(242) Thus, the stability of a process for designing a semiconductor integrated circuit including the integrated circuit according to some example embodiments may be improved. In addition, the degree of freedom of a metal line may be increased, and pin congestion may be reduced.

(243) A second gate structure **210** may be disposed on the first active region **ACT1** to be spaced apart from the third source/drain contact **120** in the first direction **x**. In addition, a third gate structure **220** may be disposed on the second active region **ACT2** to be spaced apart from the third source/drain contact **120** in the first direction **x**.

(244) A fourth source/drain contact **130** may be disposed to extend in the second direction **y** and to be spaced apart from the second gate structure **210** and the third gate structure **220** in the first direction **x**. A drain of the third PMOS transistor **P3** may be connected to a source of the third NMOS transistor **N3** through the fourth source/drain contact **130**. In addition, a drain of the fourth PMOS transistor **P4** may be connected to a source of the fourth NMOS transistor **N4** through the fourth source/drain contact **130**. That is, the drain of the third PMOS transistor **P3**, the source of the third NMOS transistor **N3**, the drain of the fourth PMOS transistor **P4**, and the source of the fourth NMOS transistor **N4** may be connected to each other through the fourth source/drain contact **130**. By connecting a plurality of transistors through one source/drain contact (e.g., the fourth source/drain contact **130**), the height of the integrated circuit according to some example embodiments may be lowered.

(245) Thus, the stability of a process for designing a semiconductor integrated circuit including the

integrated circuit according to some example embodiments may be improved. In addition, the degree of freedom of a metal line may be increased, and pin congestion may be reduced.

(246) A fourth gate structure **230** may be disposed on the first active region ACT1 to be spaced apart from the fourth source/drain contact **130** in the first direction x. In addition, a fifth gate structure **240** may be disposed on the second active region ACT2 to be spaced apart from the fourth source/drain contact **130** in the first direction x.

(247) A fifth source/drain contact **140** and a sixth source/drain contact **150** may be disposed to be spaced apart from the fourth gate structure **230** and the fifth gate structure **240** in the first direction x. The fifth source/drain contact **140** may extend in the second direction y and may be disposed on the first active region ACT1. The sixth source/drain contact **150** may extend in the second direction y and may be disposed on the second active region ACT2.

(248) A sixth gate structure **250** may be disposed on the first active region ACT1 and the second active region ACT2 to be spaced apart from the fifth source/drain contact **140** and the sixth source/drain contact **150** in the first direction x. In addition, a seventh source/drain contact **160** may be disposed on the first active region ACT1 to be spaced apart from the sixth gate structure **250** in the first direction x. The seventh source/drain contact **160** may be connected to the power rail **10** through a second source/drain contact via VSD2 to supply the power voltage to the second PMOS transistor P2. In addition, an eighth source/drain contact **170** may be disposed on the second active region ACT2 to be spaced apart from the sixth gate structure **250** in the first direction x. The eighth source/drain contact **170** may be connected to the ground rail **20** through a fourth source/drain contact via VSD4 to ground the second NMOS transistor N2.

(249) Next, the structure and operation in which the signal is applied, together with structures extending in a third direction z, will be described.

(250) A fifth gate contact GC5 extending in the third direction z may be disposed on the first gate structure **200**. In addition, a first gate contact via VG1 extending in the third direction z may be disposed on the fifth gate contact GC5. The first gate contact via VG1 may be connected to a first_first metal line M1_1 extending in the first direction x. That is, the first gate structure **200** may be electrically connected to the first_first metal line M1_1, the first gate contact via VG1, and the fifth gate contact GC5 to receive the data signal D. Thus, the first PMOS transistor P1 and the first NMOS transistor N1 may be gated through the data signal D.

(251) The fifth gate contact GC5 and the first gate contact via VG1, which are electrically connected to the first gate structure **200**, are illustrated in this drawing as being disposed on the second active region ACT2, but are not limited thereto, and may be disposed on the first active region ACT1 as illustrated in FIGS. 34 and 35.

(252) A first gate contact GC1 extending in the third direction z may be disposed on the second gate structure **210**. In addition, a second gate contact via VG2 extending in the third direction z may be disposed on the first gate contact GC1. The second gate contact via VG2 may be connected to a first_second metal line M1_2 extending in the first direction x. That is, the second gate structure **210** may be electrically connected to the first_second metal line M1_2, the second gate contact via VG2, and the first gate contact GC1 to receive the scan active signal Se. Thus, the third PMOS transistor P3 may be gated through the scan active signal Se.

(253) The positions of the first gate contact GC1 and the second gate contact via VG2, which are electrically connected to the second gate structure **210**, are not limited thereto.

(254) A third gate contact GC3 extending in the third direction z may be disposed on the third gate structure **220**. In addition, a third gate contact via VG3 extending in the third direction z may be disposed on the third gate contact GC3. The third gate contact via VG3 may be connected to a first_third metal line M1_3 extending in the first direction x. That is, the third gate structure **220** may be electrically connected to the first_third metal line M1_3, the third gate contact via VG3, and the third gate contact GC3 to receive the inverted active signal Se. Thus, the third NMOS transistor N3 may be gated through the inverted active signal Se.

(255) The positions of the third gate contact GC3 and the third gate contact via VG3, which are electrically connected to the third gate structure **220**, are not limited thereto.

(256) A second gate contact GC2 extending in the third direction z may be disposed on the fourth gate structure **230**. In addition, a fourth gate contact via VG4 extending in the third direction z may be disposed on the second gate contact GC2. The fourth gate contact via VG4 may be connected to a first_fifth metal line M1_5 extending in the first direction x. That is, the fourth gate structure **230** may be electrically connected to the first_fifth metal line M1_5, the fourth gate contact via VG4, and the second gate contact GC2 to receive the inverted active signal Se. Thus, the fourth PMOS transistor P4 may be gated through the inverted active signal Se.

(257) The positions of the second gate contact GC2 and the fourth gate contact via VG4, which are electrically connected to the fourth gate structure **230**, are not limited thereto.

(258) A fourth gate contact GC4 extending in the third direction z may be disposed on the fifth gate structure **240**. In addition, a fifth gate contact via VG5 extending in the third direction z may be disposed on the fourth gate contact GC4. The fifth gate contact via VG5 may be connected to a first_sixth metal line M1_6 extending in the first direction x. That is, the fifth gate structure **240** is electrically connected to the first_sixth metal line M1_6, the fifth gate contact via VG5, and the fourth gate contact GC4 to receive the scan active signal Se. Thus, the fourth NMOS transistor N4 may be gated through the scan active signal Se.

(259) The positions of the fourth gate contact GC4 and the fifth gate contact via VG5, which are electrically connected to the fifth gate structure **240**, are not limited thereto.

(260) A sixth gate contact GC6 extending in the third direction z may be disposed on the sixth gate structure **250**. In addition, a sixth gate contact via VG6 extending in the third direction z may be disposed on the sixth gate contact GC6. The sixth gate contact via VG6 may be connected to a first_seventh metal line M1_7 extending in the first direction x. That is, the sixth gate structure **250** may be electrically connected to the first_seventh metal line M1_7, the sixth gate contact via VG6, and the sixth gate contact GC6 to receive the scan input signal Si. Thus, the second PMOS transistor P2 and the second NMOS transistor N2 may be gated through the scan input signal Si.

(261) The sixth gate contact GC6 and the sixth gate contact via VG6, which are electrically connected to the sixth gate structure **250**, are illustrated in this drawing as being disposed on the first active region ACT1, but are not limited thereto, and may be disposed on the second active region ACT2 as illustrated in FIGS. **34** and **35**.

(262) A fifth source/drain contact via VSD5 extending in the third direction z may be disposed on the fourth source/drain contact **130**. In addition, a first_fourth metal line M1_4 extending in the first direction x may be disposed on the fifth source/drain contact via VSD5 and may be connected to the outside.

(263) The fifth source/drain contact via VSD5, which is electrically connected to the fourth source/drain contact **130**, is illustrated in this drawing as being disposed on the first active region ACT1, but is not limited thereto, and may be disposed on the second active region ACT2 as illustrated in FIG. **34**.

(264) The plurality of gate structures (e.g., the first to sixth gate structures **200** to **250**) and the plurality of source/drain contacts (e.g., the first to eighth source/drain contacts **100** to **170**), which are disposed to be adjacent to each other in the first direction x, may be spaced apart from each other by 1 CPP. As an example, the first gate structure **200** and the first source/drain contact **100** adjacent to each other may be spaced apart from each other by 1 CPP.

(265) For example, assume that the first gate structure **200** and the first source/drain contact **100** are adjacent to each other. When the distance between a center line of the first gate structure **200** extending in the second direction y and a center line of the first source/drain contact **100** extending in the second direction y is 1 CPP, it means that the other gate structure or source/drain contact is not disposed between the first gate structure **200** and the first source/drain contact **100**.

(266) Further, the metal lines (e.g., the first_first to first_seventh metal lines M1_1 to M1_7),

which are disposed to be adjacent to each other in the second direction y, may be spaced apart from each other by 1 CPP. As an example, the first_first metal line M1_1 and the first_second metal line M1_2 adjacent to each other may be spaced apart from each other by 1 CPP.

(267) For example, assume that the first_first metal line M1_1 and the first_second metal line M1_2 are adjacent to each other. When the distance between a center line of the first_first metal line M1_1 extending in the first direction x and a center line of the first_second metal line M1_2 extending in the first direction x is 1 CPP, it means that the other metal line is not disposed between the first_first metal line M1_1 and the first_second metal line M1_2.

(268) Referring to FIG. 8 again, the master latch M_L may include a first transmission unit TSU1, a first latch unit LU1, and a first inverter INV'.

(269) The master latch M_L may store the data signal D input through the signal node SN and output the data signal D to a first master latch node MLN1. In more detail, the master latch M_L may output the input data signal D based on a first clock signal En and a second clock signal (En) which is the inverted first clock signal.

(270) The first transmission unit TSU1 of the master latch M_L may be configured as a transmission gate including the integrated circuit according to some example embodiments or may be configured as a tri-state inverter. The first latch unit LU1 of the master latch M_L may be configured as a transmission gate including the integrated circuit according to some example embodiments or may be configured as a tri-state inverter.

(271) Hereinafter, the master latch M_L including the integrated circuit according to some example embodiments will be described with reference to FIGS. 36 to 44.

(272) FIG. 36 is a circuit diagram illustrating the master latch M_L shown in FIG. 8. For reference, the description of the slave latch S_L overlaps the description of the master latch M_L, and thus the master latch M_L will be described as an example. Of course, the description of the master latch M_L may also be applied to the slave latch S_L.

(273) Referring to FIG. 36, the first transmission unit TSU1 includes a fourth inverter INV4 and a first transmission gate TG1, and the first latch unit LU1 includes a third tri-state inverter TRI3.

(274) The first transmission unit TSU1 including the integrated circuit according to some example embodiments receives the data signal D through the signal node SN and transmits the data signal D to the first master latch node MLN1. In more detail, the signal input to the signal node SN is inverted by the fourth inverter INV4 composed of a first PMOS transistor P1 and a first NMOS transistor N1. In addition, the inverted signal of the signal input to the signal node SN may be output to the first master latch node MLN1 by the first transmission gate TG1 composed of a second PMOS transistor P2 and a second NMOS transistor N2.

(275) The third tri-state inverter TRI3 composed of a third PMOS transistor P3, a third NMOS transistor N3, a fourth PMOS transistor P4, and a fourth NMOS transistor N4 may latch the data input to the first master latch node MLN1 under the control of the first clock signal En and the second clock signal En. The description of the tri-state inverter overlaps with the description of FIG. 1, and thus the description thereof will be omitted.

(276) FIGS. 37 and 38 are layout diagrams according to some example embodiments exemplarily illustrating FIG. 36. Hereinafter, in order to avoid duplicate descriptions, the common parts of FIGS. 37 and 38 are described only through FIG. 37, and only the differences will be briefly described with reference to the corresponding drawings. In addition, for simplicity of the description, a layout diagram of a region R4_1 of a master latch M_L1 will be mainly described.

(277) When region R4_1a of the region R4_1 is described with reference to FIG. 37, the first to fourth PMOS transistors P1 to P4 may be disposed on a first active region ACT1 extending in a first direction x. Further, the first to fourth NMOS transistors N1 to N4 may be formed on a second active region ACT2 extending in the first direction x and disposed to be spaced apart from the first active region ACT1 in a second direction y.

(278) A power rail 10 may be disposed at an upper portion of the first active region ACT1 in the

second direction y. In addition, a ground rail **20** may be disposed at a lower portion of the second active region ACT2 in the second direction y.

(279) The region R4_1a of the master latch M_L1 including the integrated circuit according to some example embodiments may include a plurality of gate structures and a plurality of source/drain contacts extending in the second direction y and disposed to be spaced apart from each other in the first direction x.

(280) For example, a first source/drain contact **100** and a second source/drain contact **110** may be disposed on the first active region ACT1 and the second active region ACT2, respectively, to be spaced apart from each other in the second direction y. That is, the first source/drain contact **100** may be connected to the power rail **10** through a first source/drain contact via VSD1 to supply the power voltage to the first PMOS transistor P1. In addition, the second source/drain contact **110** may be connected to the ground rail **20** through a third source/drain contact via VSD3 to ground the first NMOS transistor N1.

(281) A first gate structure **200** is disposed to be spaced apart from the first and second source/drain contacts **100** and **110** in the first direction x. The first gate structure **200** may be disposed on the first active region ACT1 and the second active region ACT2.

(282) A third source/drain contact **120** may be disposed to be spaced apart from the first gate structure **200** in the first direction x. The third source/drain contact **120** may extend in the second direction y and may be disposed on the first active region ACT1 and the second active region ACT2. That is, a drain of the first PMOS transistor P1 and a drain of the first NMOS transistor N1 may be connected to each other through the third source/drain contact **120**. In addition, a source of the second PMOS transistor P2 may be connected to a drain of the second NMOS transistor N2 through the third source/drain contact **120**. That is, the drain of the first PMOS transistor P1, the drain of the first NMOS transistor N1, the source of the second PMOS transistor P2, and the drain of the second NMOS transistor N2 may be connected to each other through the third source/drain contact **120**. By connecting a plurality of transistors through one source/drain contact (e.g., the third source/drain contact **120**), the height of the integrated circuit according to some example embodiments may be lowered.

(283) Thus, the stability of a process for designing a semiconductor integrated circuit including the integrated circuit according to some example embodiments may be improved. In addition, the degree of freedom of a metal line may be increased, and pin congestion may be reduced.

(284) A second gate structure **210** may be disposed on the first active region ACT1 to be spaced apart from the third source/drain contact **120** in the first direction x. In addition, a third gate structure **220** may be disposed on the second active region ACT2 to be spaced apart from the third source/drain contact **120** in the first direction x.

(285) A fourth source/drain contact **130** may be disposed to extend in the second direction y and to be spaced apart from the second gate structure **210** and the third gate structure **220** in the first direction x. A drain of the second PMOS transistor P2 may be connected to a source of the second NMOS transistor N2 through the fourth source/drain contact **130**. A drain of the third PMOS transistor P3 may be connected to a drain of the third NMOS transistor N3 through the fourth source/drain contact **130**. That is, the drain of the second PMOS transistor P2, the source of the second NMOS transistor N2, the drain of the third PMOS transistor P3, and the drain of the third NMOS transistor N3 may be connected to each other through the fourth source/drain contact **130**. By connecting a plurality of transistors through one source/drain contact (e.g., the fourth source/drain contact **130**), the height of the integrated circuit according to some example embodiments may be lowered.

(286) Thus, the stability of a process for designing a semiconductor integrated circuit including the integrated circuit according to some example embodiments may be improved. In addition, the degree of freedom of a metal line may be increased, and pin congestion may be reduced.

(287) A fourth gate structure **230** may be disposed on the first active region ACT1 to be spaced

apart from the fourth source/drain contact **130** in the first direction x. In addition, a fifth gate structure **240** may be disposed on the second active region ACT2 to be spaced apart from the fourth source/drain contact **130** in the first direction x.

(288) A fifth source/drain contact **140** and a sixth source/drain contact **150** may be disposed to be spaced apart from the fourth gate structure **230** and the fifth gate structure **240** in the first direction x. The fifth source/drain contact **140** may extend in the second direction y and may be disposed on the first active region ACT1. The sixth source/drain contact **150** may extend in the second direction y and may be disposed on the second active region ACT2.

(289) A sixth gate structure **250** may be disposed on the first active region ACT1 and the second active region ACT2 to be spaced apart from the fifth source/drain contact **140** and the sixth source/drain contact **150** in the first direction x. In addition, a seventh source/drain contact **160** may be disposed on the first active region ACT1 to be spaced apart from the sixth gate structure **250** in the first direction x. The seventh source/drain contact **160** may be connected to the power rail **10** through a second source/drain contact via VSD2 to supply the power voltage to the fourth PMOS transistor P4. In addition, an eighth source/drain contact **170** may be disposed on the second active region ACT2 to be spaced apart from the sixth gate structure **250** in the first direction x. The eighth source/drain contact **170** may be connected to the ground rail **20** through a fourth source/drain contact via VSD4 to ground the fourth NMOS transistor N4.

(290) Next, the structure and operation in which the signal is applied, together with structures extending in a third direction z, will be described.

(291) A fifth gate contact GC5 extending in the third direction z may be disposed on the first gate structure **200**. In addition, a first gate contact via VG1 extending in the third direction z may be disposed on the fifth gate contact GC5. The first gate contact via VG1 may be connected to a first_first metal line M1_1 extending in the first direction x. That is, the first gate structure **200** may be electrically connected to the first_first metal line M1_1, the first gate contact via VG1, and the fifth gate contact GC5 to receive the data signal D. Thus, the first PMOS transistor P1 and the first NMOS transistor N1 may be gated through the data signal D.

(292) The fifth gate contact GC5 and the first gate contact via VG1, which are electrically connected to the first gate structure **200**, are illustrated in this drawing as being disposed on the first active region ACT1, but are not limited thereto, and may be disposed on the second active region ACT2 as illustrated in FIG. 38.

(293) A first gate contact GC1 extending in the third direction z may be disposed on the second gate structure **210**. In addition, a second gate contact via VG2 extending in the third direction z may be disposed on the first gate contact GC1. The second gate contact via VG2 may be connected to a first_second metal line M1_2 extending in the first direction x. That is, the second gate structure **210** may be electrically connected to the first_second metal line M1_2, the second gate contact via VG2, and the first gate contact GC1 to receive the first clock signal En. Thus, the second PMOS transistor P2 may be gated through the first clock signal En.

(294) The positions of the first gate contact GC1 and the second gate contact via VG2, which are electrically connected to the second gate structure **210**, are not limited thereto.

(295) A third gate contact GC3 extending in the third direction z may be disposed on the third gate structure **220**. In addition, a third gate contact via VG3 extending in the third direction z may be disposed on the third gate contact GC3. The third gate contact via VG3 may be connected to a first_third metal line M1_3 extending in the first direction x. That is, the third gate structure **220** may be electrically connected to the first_third metal line M1_3, the third gate contact via VG3, and the third gate contact GC3 to receive the second clock signal En. Thus, the second NMOS transistor N2 may be gated through the second clock signal En.

(296) The positions of the third gate contact GC3 and the third gate contact via VG3, which are electrically connected to the third gate structure **220**, are not limited thereto.

(297) A second gate contact GC2 extending in the third direction z may be disposed on the fourth

gate structure **230**. In addition, a fourth gate contact via VG4 extending in the third direction z may be disposed on the second gate contact GC2. The fourth gate contact via VG4 may be connected to a first_fifth metal line M1_5 extending in the first direction x. That is, the fourth gate structure **230** may be electrically connected to the first_fifth metal line M1_5, the fourth gate contact via VG4, and the second gate contact GC2 to receive the second clock signal En. Thus, the third PMOS transistor P3 may be gated through the second clock signal En.

(298) The positions of the second gate contact GC2 and the fourth gate contact via VG4, which are electrically connected to the fourth gate structure **230**, are not limited thereto.

(299) A fourth gate contact GC4 extending in the third direction z may be disposed on the fifth gate structure **240**. In addition, a fifth gate contact via VG5 extending in the third direction z may be disposed on the fourth gate contact GC4. The fifth gate contact via VG5 may be connected to a first_sixth metal line M1_6 extending in the first direction x. That is, the fifth gate structure **240** is electrically connected to the first_sixth metal line M1_6, the fifth gate contact via VG5, and the fourth gate contact GC4 to receive the first clock signal En. Thus, the third NMOS transistor N3 may be gated through the first clock signal En.

(300) The positions of the fourth gate contact GC4 and the fifth gate contact via VG5, which are electrically connected to the fifth gate structure **240**, are not limited thereto.

(301) A sixth gate contact GC6 extending in the third direction z may be disposed on the sixth gate structure **250**. In addition, a sixth gate contact via VG6 extending in the third direction z may be disposed on the sixth gate contact GC6. The sixth gate contact via VG6 may be connected to a first_seventh metal line M1_7 extending in the first direction x. That is, the sixth gate structure **250** may be electrically connected to the first_seventh metal line M1_7, the sixth gate contact via VG6, and the sixth gate contact GC6 to receive a signal at a second master latch node. Thus, the fourth PMOS transistor P4 and the fourth NMOS transistor N4 may be gated through the signal at the second master latch node.

(302) The sixth gate contact GC6 and the sixth gate contact via VG6, which are electrically connected to the sixth gate structure **250**, are illustrated in this drawing as being disposed on the second active region ACT2, but are not limited thereto, and may be disposed on the first active region ACT1 as illustrated in FIG. 38.

(303) A fifth source/drain contact via VSD5 extending in the third direction z may be disposed on the fourth source/drain contact **130**. In addition, a first_fourth metal line M1_4 extending in the first direction x may be disposed on the fifth source/drain contact via VSD5 and may be connected to the outside.

(304) The fifth source/drain contact via VSD5, which is electrically connected to the fourth source/drain contact **130**, is illustrated in this drawing as being disposed on the first active region ACT1, but is not limited thereto, and may be disposed on the second active region ACT2 as illustrated in FIG. 38.

(305) The plurality of gate structures (e.g., the first to sixth gate structures **200** to **250**) and the plurality of source/drain contacts (e.g., the first to eighth source/drain contacts **100** to **170**), which are disposed to be adjacent to each other in the first direction x, may be spaced apart from each other by 1 CPP. As an example, the first gate structure **200** and the first source/drain contact **100** adjacent to each other may be spaced apart from each other by 1 CPP.

(306) For example, assume that the first gate structure **200** and the first source/drain contact **100** are adjacent to each other. When the distance between a center line of the first gate structure **200** extending in the second direction y and a center line of the first source/drain contact **100** extending in the second direction y is 1 CPP, it means that the other gate structure or source/drain contact is not disposed between the first gate structure **200** and the first source/drain contact **100**.

(307) Further, the metal lines (e.g., the first_first to first_seventh metal lines M1_1 to M1_7), which are disposed to be adjacent to each other in the second direction y, may be spaced apart from each other by 1 CPP. As an example, the first_sixth metal line M1_6 and the first_seventh metal

line M1_7 adjacent to each other may be spaced apart from each other by 1 CPP.

(308) For example, assume that the first_sixth metal line M1_6 and the first_seventh metal line M1_7 are adjacent to each other. When the distance between a center line of the first_sixth metal line M1_6 extending in the first direction x and a center line of the first_seventh metal line M1_7 extending in the first direction x is 1 CPP, it means that the other metal line is not disposed between the first_sixth metal line M16 and the first_seventh metal line M17.

(309) FIG. 39 is a circuit diagram illustrating the master latch M_L shown in FIG. 8.

(310) When the difference between a master latch M_L2 of FIG. 39 and the master latch M_L1 of FIG. 36 is mainly described with reference to the master latch M_L2 of FIG. 39, the first latch unit LU1 includes a second transmission gate TG2 and a fifth inverter INV5.

(311) The first latch unit LU1 including the integrated circuit according to some example embodiments may latch a signal at the first master latch node MLN1. In more detail, a signal at a second master latch node MLN2 is inverted by the fifth inverter INV5 composed of a fourth PMOS transistor P4 and a fourth NMOS transistor N4. In addition, the signal in which the signal at the second master latch node MLN2 is inverted may be output to the first master latch node MLN1 by the second transmission gate TG2 composed of a third PMOS transistor P3 and a third NMOS transistor N3.

(312) The first latch unit LU1 may latch the data signal D, which is input to the first master latch node MLN1, under the control of the first clock signal En and the second clock signal En.

(313) FIGS. 40 and 41 are layout diagrams according to some example embodiments exemplarily illustrating FIG. 39. Hereinafter, in order to avoid duplicate descriptions, the common parts of FIGS. 40 and 41 are described only through FIG. 40, and only the differences will be briefly described with reference to the corresponding drawings. In addition, for simplicity of the description, a layout diagram of a region R4_2 of the master latch M_L2 will be mainly described.

(314) When region R4_2a of the region R4_2 is described with reference to FIG. 40, first to fourth PMOS transistors P1 to P4 may be disposed on a first active region ACT1 extending in a first direction x. Further, first to fourth NMOS transistors N1 to N4 may be formed on a second active region ACT2 extending in the first direction x and disposed to be spaced apart from the first active region ACT1 in a second direction y.

(315) A power rail 10 may be disposed at an upper portion of the first active region ACT1 in the second direction y. In addition, a ground rail 20 may be disposed at a lower portion of the second active region ACT2 in the second direction y.

(316) The region R4_2a of the region R4_2 of the master latch M_L2 including the integrated circuit according to some example embodiments may include a plurality of gate structures and a plurality of source/drain contacts extending in the second direction y and disposed to be spaced apart from each other in the first direction x.

(317) For example, a first source/drain contact 100 and a second source/drain contact 110 may be disposed on the first active region ACT1 and the second active region ACT2, respectively, to be spaced apart from each other in the second direction y. That is, the first source/drain contact 100 may be connected to the power rail 10 through a first source/drain contact via VSD1 to supply the power voltage to the first PMOS transistor P1. In addition, the second source/drain contact 110 may be connected to the ground rail 20 through a third source/drain contact via VSD3 to ground the first NMOS transistor N1.

(318) A first gate structure 200 is disposed to be spaced apart from the first and second source/drain contacts 100 and 110 in the first direction x. The first gate structure 200 may be disposed on the first active region ACT1 and the second active region ACT2.

(319) A third source/drain contact 120 may be disposed to be spaced apart from the first gate structure 200 in the first direction x. The third source/drain contact 120 may extend in the second direction y and may be disposed on the first active region ACT1 and the second active region ACT2. That is, a drain of the first PMOS transistor P1 and a drain of the first NMOS transistor N1

may be connected to each other through the third source/drain contact **120**. In addition, a source of the second PMOS transistor **P2** may be connected to a drain of the second NMOS transistor **N2** through the third source/drain contact **120**. That is, the drain of the first PMOS transistor **P1**, the drain of the first NMOS transistor **N1**, the source of the second PMOS transistor **P2**, and the drain of the second NMOS transistor **N2** may be connected to each other through the third source/drain contact **120**. By connecting a plurality of transistors through one source/drain contact (e.g., the third source/drain contact **120**), the height of the integrated circuit according to some example embodiments may be lowered.

(320) Thus, the stability of a process for designing a semiconductor integrated circuit including the integrated circuit according to some example embodiments may be improved. In addition, the degree of freedom of a metal line may be increased, and pin congestion may be reduced.

(321) A second gate structure **210** may be disposed on the first active region **ACT1** to be spaced apart from the third source/drain contact **120** in the first direction **x**. In addition, a third gate structure **220** may be disposed on the second active region **ACT2** to be spaced apart from the third source/drain contact **120** in the first direction **x**.

(322) A fourth source/drain contact **130** may be disposed to extend in the second direction **y** and to be spaced apart from the second gate structure **210** and the third gate structure **220** in the first direction **x**. A drain of the second PMOS transistor **P2** may be connected to a source of the second NMOS transistor **N2** through the fourth source/drain contact **130**. In addition, a drain of the third PMOS transistor **P3** may be connected to a source of the third NMOS transistor **N3** through the fourth source/drain contact **130**. That is, the drain of the second PMOS transistor **P2**, the source of the second NMOS transistor **N2**, the drain of the third PMOS transistor **P3**, and the source of the third NMOS transistor **N3** may be connected to each other through the fourth source/drain contact **130**. By connecting a plurality of transistors through one source/drain contact (e.g., the fourth source/drain contact **130**), the height of the integrated circuit according to some example embodiments may be lowered.

(323) Thus, the stability of a process for designing a semiconductor integrated circuit including the integrated circuit according to some example embodiments may be improved. In addition, the degree of freedom of a metal line may be increased, and pin congestion may be reduced.

(324) A fourth gate structure **230** may be disposed on the first active region **ACT1** to be spaced apart from the fourth source/drain contact **130** in the first direction **x**. In addition, a fifth gate structure **240** may be disposed on the second active region **ACT2** to be spaced apart from the fourth source/drain contact **130** in the first direction **x**.

(325) A fifth source/drain contact **140** may be disposed to be spaced apart from the fourth gate structure **230** and the fifth gate structure **240** in the first direction **x**. The fifth source/drain contact **140** may extend in the second direction **y** and may be disposed on the first active region **ACT1** and the second active region **ACT2**. That is, a source of the third PMOS transistor **P3** and a drain of the third NMOS transistor **N3** may be connected to each other through the fifth source/drain contact **140**. In addition, a drain of the fourth PMOS transistor **P4** may be connected to a drain of the fourth NMOS transistor **N4** through the fifth source/drain contact **140**. That is, the source of the third PMOS transistor **P3**, the drain of the third NMOS transistor **N3**, the drain of the fourth PMOS transistor **P4**, and the drain of the fourth NMOS transistor **N4** may be connected to each other through the fifth source/drain contact **140**. By connecting a plurality of transistors through one source/drain contact (e.g., the fifth source/drain contact **140**), the height of the integrated circuit according to some example embodiments may be lowered.

(326) Thus, the stability of a process for designing a semiconductor integrated circuit including the integrated circuit according to some example embodiments may be improved. In addition, the degree of freedom of a metal line may be increased, and pin congestion may be reduced.

(327) A sixth gate structure **250** may be disposed on the first active region **ACT1** and the second active region **ACT2** to be spaced apart from the fifth source/drain contact **140** in the first direction

x. Further, a sixth source/drain contact **150** may be disposed on the first active region ACT1 to be spaced apart from the sixth gate structure **250** in the first direction x. The sixth source/drain contact **150** may be connected to the power rail **10** through a second source/drain contact via VSD2 to supply the power voltage to the fourth PMOS transistor P4. In addition, a seventh source/drain contact **160** may be disposed on the second active region ACT2 to be spaced apart from the sixth gate structure **250** in the first direction x. The seventh source/drain contact **160** may be connected to the ground rail **20** through a fourth source/drain contact via VSD4 to ground the fourth NMOS transistor N4.

(328) Next, the structure and operation in which the signal is applied, together with structures extending in a third direction z, will be described.

(329) A fifth gate contact GC5 extending in the third direction z may be disposed on the first gate structure **200**. In addition, a first gate contact via VG1 extending in the third direction z may be disposed on the fifth gate contact GC5. The first gate contact via VG1 may be connected to a first_first metal line M1_1 extending in the first direction x. That is, the first gate structure **200** may be electrically connected to the first_first metal line M1_1, the first gate contact via VG1, and the fifth gate contact GC5 to receive the data signal D. Thus, the first PMOS transistor P1 and the first NMOS transistor N1 may be gated through the data signal D.

(330) The fifth gate contact GC5 and the first gate contact via VG1, which are electrically connected to the first gate structure **200**, are illustrated in this drawing as being disposed on the first active region ACT1, but are not limited thereto, and may be disposed on the second active region ACT2 as illustrated in FIG. 41.

(331) A first gate contact GC1 extending in the third direction z may be disposed on the second gate structure **210**. In addition, a second gate contact via VG2 extending in the third direction z may be disposed on the first gate contact GC1. The second gate contact via VG2 may be connected to a first_second metal line M1_2 extending in the first direction x. That is, the second gate structure **210** may be electrically connected to the first_second metal line M1_2, the second gate contact via VG2, and the first gate contact GC1 to receive the first clock signal En. Thus, the second PMOS transistor P2 may be gated through the first clock signal En.

(332) The positions of the first gate contact GC1 and the second gate contact via VG2, which are electrically connected to the second gate structure **210**, are not limited thereto.

(333) A third gate contact GC3 extending in the third direction z may be disposed on the third gate structure **220**. In addition, a third gate contact via VG3 extending in the third direction z may be disposed on the third gate contact GC3. The third gate contact via VG3 may be connected to a first_third metal line M1_3 extending in the first direction x. That is, the third gate structure **220** may be electrically connected to the first_third metal line M1_3, the third gate contact via VG3, and the third gate contact GC3 to receive the second clock signal En. Thus, the second NMOS transistor N2 may be gated through the inverted active signal En.

(334) The positions of the third gate contact GC3 and the third gate contact via VG3, which are electrically connected to the third gate structure **220**, are not limited thereto.

(335) A second gate contact GC2 extending in the third direction z may be disposed on the fourth gate structure **230**. In addition, a fourth gate contact via VG4 extending in the third direction z may be disposed on the second gate contact GC2. The fourth gate contact via VG4 may be connected to a first_fifth metal line M1_5 extending in the first direction x. That is, the fourth gate structure **230** may be electrically connected to the first_fifth metal line M1_5, the fourth gate contact via VG4, and the second gate contact GC2 to receive the second clock signal En. Thus, the third PMOS transistor P3 may be gated through the second clock signal En.

(336) The positions of the second gate contact GC2 and the fourth gate contact via VG4, which are electrically connected to the fourth gate structure **230**, are not limited thereto.

(337) A fourth gate contact GC4 extending in the third direction z may be disposed on the fifth gate structure **240**. In addition, a fifth gate contact via VG5 extending in the third direction z may be

disposed on the fourth gate contact GC4. The fifth gate contact via VG5 may be connected to a first_sixth metal line M1_6 extending in the first direction x. That is, the fifth gate structure 240 may be electrically connected to the first_sixth metal line M1_6, the fifth gate contact via VG5, and the fourth gate contact GC4 to receive the first clock signal En. Thus, the third NMOS transistor N3 may be gated through the first clock signal En.

(338) The positions of the fourth gate contact GC4 and the fifth gate contact via VG5, which are electrically connected to the fifth gate structure 240, are not limited thereto.

(339) A sixth gate contact GC6 extending in the third direction z may be disposed on the sixth gate structure 250. In addition, a sixth gate contact via VG6 extending in the third direction z may be disposed on the sixth gate contact GC6. The sixth gate contact via VG6 may be connected to a first_seventh metal line M1_7 extending in the first direction x. That is, the sixth gate structure 250 may be electrically connected to the first_seventh metal line M1_7, the sixth gate contact via VG6, and the sixth gate contact GC6 to receive the signal at the second master latch node. Thus, the fourth PMOS transistor P4 and the fourth NMOS transistor N4 may be gated through the signal at the second master latch node.

(340) The sixth gate contact GC6 and the sixth gate contact via VG6, which are electrically connected to the sixth gate structure 250, are illustrated in this drawing as being disposed on the first active region ACT1, but are not limited thereto, and may be disposed on the second active region ACT2 as illustrated in FIG. 41.

(341) A fifth source/drain contact via VSD5 extending in the third direction z may be disposed on the fourth source/drain contact 130. In addition, a first_fourth metal line M1_4 extending in the first direction x may be disposed on the fifth source/drain contact via VSD5 and may be connected to the outside.

(342) The fifth source/drain contact via VSD5, which is electrically connected to the fourth source/drain contact 130, is illustrated in this drawing as being disposed on the first active region ACT1, but is not limited thereto, and may be disposed on the second active region ACT2 as illustrated in FIG. 41.

(343) The plurality of gate structures (e.g., the first to sixth gate structures 200 to 250) and the plurality of source/drain contacts (e.g., the first to seventh source/drain contacts 100 to 160), which are disposed to be adjacent to each other in the first direction x, may be spaced apart from each other by 1 CPP. As an example, the first gate structure 200 and the first source/drain contact 100 adjacent to each other may be spaced apart from each other by 1 CPP.

(344) For example, assume that the first gate structure 200 and the first source/drain contact 100 are adjacent to each other. When the distance between a center line of the first gate structure 200 extending in the second direction y and a center line of the first source/drain contact 100 extending in the second direction y is 1 CPP, it means that the other gate structure or source/drain contact is not disposed between the first gate structure 200 and the first source/drain contact 100.

(345) Further, the metal lines (e.g., the first_first to first_seventh metal lines M1_1 to M1_7), which are disposed to be adjacent to each other in the second direction y, may be spaced apart from each other by 1 CPP. As an example, the first_first metal line M1_1 and the first_third metal line M1_3 adjacent to each other may be spaced apart from each other by 1 CPP.

(346) For example, assume that the first_first metal line M1_1 and the first_third metal line M1_3 are adjacent to each other. When the distance between a center line of the first_first metal line M1_1 extending in the first direction x and a center line of the first_third metal line M1_3 extending in the first direction x is 1 CPP, it means that the other metal line is not disposed between the first_first metal line M1_1 and the first_third metal line M1_3.

(347) FIG. 42 is a circuit diagram illustrating the master latch M_L shown in FIG. 8.

(348) When the difference between a master latch M_L3 of FIG. 42 and the master latch M_L2 of FIG. 39 is mainly described with reference to the master latch M_L3 of FIG. 42, the first transmission unit TSU1 includes a third tri-state inverter TRI3.

(349) The third tri-state inverter **TRI3** including a first PMOS transistor **P1**, a first NMOS transistor **N1**, a second PMOS transistor **P2**, and a second NMOS transistor **N2** may invert the data signal **D**, which is received from the signal node **SN**, under the control of the first clock signal **En** and the second clock signal **En**.

(350) The first latch unit **LU1** is the same as the first latch unit shown in FIG. **40**, and thus a description thereof will be omitted.

(351) FIGS. **43** and **44** are layout diagrams of FIG. **42** according to some example embodiments. Hereinafter, in order to avoid duplicate descriptions, the common parts of FIGS. **43** and **44** are described only through FIG. **43**, and only the differences will be briefly described with reference to the corresponding drawings. In addition, for simplicity of the description, a layout diagram of a region **R4_3** of the master latch **M_L3** will be mainly described.

(352) When region **R4_3a** of the region **R4_3** is described with reference to FIG. **43**, first to fourth PMOS transistors **P1** to **P4** may be disposed on a first active region **ACT1** extending in a first direction **x**. Further, first to fourth NMOS transistors **N1** to **N4** may be formed on a second active region **ACT2** extending in the first direction **x** and disposed to be spaced apart from the first active region **ACT1** in a second direction **y**.

(353) A power rail **10** may be disposed at an upper portion of the first active region **ACT1** in the second direction **y**. In addition, a ground rail **20** may be disposed at a lower portion of the second active region **ACT2** in the second direction **y**.

(354) The region **R4_3a** of the region **R4_3** of the master latch **M_L3** including the integrated circuit according to some example embodiments may include a plurality of gate structures and a plurality of source/drain contacts extending in the second direction **y** and disposed to be spaced apart from each other in the first direction **x**.

(355) For example, a first source/drain contact **100** and a second source/drain contact **110** may be disposed on the first active region **ACT1** and the second active region **ACT2**, respectively, to be spaced apart from each other in the second direction **y**. That is, the first source/drain contact **100** may be connected to the power rail **10** through a first source/drain contact via **VSD1** to supply the power voltage to the second PMOS transistor **P2**. In addition, the second source/drain contact **110** may be connected to the ground rail **20** through a third source/drain contact via **VSD3** to ground the second NMOS transistor **N2**.

(356) A first gate structure **200** is disposed to be spaced apart from the first and second source/drain contacts **100** and **110** in the first direction **x**. The first gate structure **200** may be disposed on the first active region **ACT1** and the second active region **ACT2**.

(357) A third source/drain contact **120** and a fourth source/drain contact **130** may be disposed on the first active region **ACT1** and the second active region **ACT2**, respectively, to be spaced apart from each other in the second direction **y** and to be spaced apart from the first gate structure **200** in the first direction **x**.

(358) A second gate structure **210** may be disposed on the first active region **ACT1** to be spaced apart from the third source/drain contact **120** and the fourth source/drain contact **130** in the first direction **x**. In addition, a third gate structure **220** may be disposed on the second active region **ACT2** to be spaced apart from the third source/drain contact **120** and the fourth source/drain contact **130** in the first direction **x**.

(359) A fifth source/drain contact **140** may be disposed to extend in the second direction **y** and to be spaced apart from the second gate structure **210** and the third gate structure **220** in the first direction **x**. A drain of the first PMOS transistor **P1** may be connected to a drain of the first NMOS transistor **N1** through the fifth source/drain contact **140**. In addition, a drain of the third PMOS transistor **P3** may be connected to a source of the third NMOS transistor **N3** through the fifth source/drain contact **140**. That is, the drain of the first PMOS transistor **P1**, the drain of the first NMOS transistor **N1**, the drain of the third PMOS transistor **P3**, and the source of the third NMOS transistor **N3** may be connected to each other through the fifth source/drain contact **140**. By

connecting a plurality of transistors through one source/drain contact (e.g., the fifth source/drain contact **140**), the height of the integrated circuit according to some example embodiments may be lowered.

(360) Thus, the stability of a process for designing a semiconductor integrated circuit including the integrated circuit according to some example embodiments may be improved. In addition, the degree of freedom of a metal line may be increased, and pin congestion may be reduced.

(361) A fourth gate structure **230** may be disposed on the first active region ACT1 to be spaced apart from the fifth source/drain contact **140** in the first direction x. In addition, a fifth gate structure **240** may be disposed on the second active region ACT2 to be spaced apart from the fifth source/drain contact **140** in the first direction x.

(362) A sixth source/drain contact **150** may be disposed to be spaced apart from the fourth gate structure **230** and the fifth gate structure **240** in the first direction x. The sixth source/drain contact **150** may extend in the second direction y and may be disposed on the first active region ACT1 and the second active region ACT2. That is, a source of the third PMOS transistor P3 and a drain of the third NMOS transistor N3 may be connected to each other through the sixth source/drain contact **150**. In addition, a drain of the fourth PMOS transistor P4 may be connected to a drain of the fourth NMOS transistor N4 through the sixth source/drain contact **150**. That is, the source of the third PMOS transistor P3, the drain of the third NMOS transistor N3, the drain of the fourth PMOS transistor P4, and the drain of the fourth NMOS transistor N4 may be connected to each other through the sixth source/drain contact **150**. By connecting a plurality of transistors through one source/drain contact (e.g., the sixth source/drain contact **150**), the height of the integrated circuit according to some example embodiments may be lowered.

(363) Thus, the stability of a process for designing a semiconductor integrated circuit including the integrated circuit according to some example embodiments may be improved. In addition, the degree of freedom of a metal line may be increased, and pin congestion may be reduced.

(364) A sixth gate structure **250** may be disposed on the first active region ACT1 and the second active region ACT2 to be spaced apart from the sixth source/drain contact **150** in the first direction x. In addition, a seventh source/drain contact **160** may be disposed on the first active region ACT1 to be spaced apart from the sixth gate structure **250** in the first direction x. The seventh source/drain contact **160** may be connected to the power rail **10** through a second source/drain contact via VSD2 to supply the power voltage to the fourth PMOS transistor P4. In addition, an eighth source/drain contact **170** may be disposed on the second active region ACT2 to be spaced apart from the sixth gate structure **250** in the first direction x. The eighth source/drain contact **170** may be connected to the ground rail **20** through a fourth source/drain contact via VSD4 to ground the fourth NMOS transistor N4.

(365) Next, the structure and operation in which the signal is applied, together with structures extending in a third direction z, will be described.

(366) A fifth gate contact GC5 extending in the third direction z may be disposed on the first gate structure **200**. In addition, a first gate contact via VG1 extending in the third direction z may be disposed on the fifth gate contact GC5. The first gate contact via VG1 may be connected to a first_first metal line M1_1 extending in the first direction x. That is, the first gate structure **200** may be electrically connected to the first_first metal line M1_1, the first gate contact via VG1, and the fifth gate contact GC5 to receive the data signal D. Thus, the second PMOS transistor P2 and the second NMOS transistor N2 may be gated through the data signal D.

(367) The fifth gate contact GC5 and the first gate contact via VG1, which are electrically connected to the first gate structure **200**, are illustrated in this drawing as being disposed on the first active region ACT1, but are not limited thereto, and may be disposed on the second active region ACT2 as illustrated in FIG. 44.

(368) A first gate contact GC1 extending in the third direction z may be disposed on the second gate structure **210**. In addition, a second gate contact via VG2 extending in the third direction z

may be disposed on the first gate contact GC1. The second gate contact via VG2 may be connected to a first_second metal line M1_2 extending in the first direction x. That is, the second gate structure **210** may be electrically connected to the first_second metal line M1_2, the second gate contact via VG2, and the first gate contact GC1 to receive the first clock signal En. Thus, the first PMOS transistor P1 may be gated through the first clock signal En.

(369) The positions of the first gate contact GC1 and the second gate contact via VG2, which are electrically connected to the second gate structure **210**, are not limited thereto.

(370) A third gate contact GC3 extending in the third direction z may be disposed on the third gate structure **220**. In addition, a third gate contact via VG3 extending in the third direction z may be disposed on the third gate contact GC3. The third gate contact via VG3 may be connected to a first_third metal line M1_3 extending in the first direction x. That is, the third gate structure **220** may be electrically connected to the first_third metal line M1_3, the third gate contact via VG3, and the third gate contact GC3 to receive the second clock signal En. Thus, the first NMOS transistor N1 may be gated through the second clock signal En.

(371) The positions of the third gate contact GC3 and the third gate contact via VG3, which are electrically connected to the third gate structure **220**, are not limited thereto.

(372) A second gate contact GC2 extending in the third direction z may be disposed on the fourth gate structure **230**. In addition, a fourth gate contact via VG4 extending in the third direction z may be disposed on the second gate contact GC2. The fourth gate contact via VG4 may be connected to a first_fifth metal line M1_5 extending in the first direction x. That is, the fourth gate structure **230** may be electrically connected to the first_fifth metal line M1_5, the fourth gate contact via VG4, and the second gate contact GC2 to receive the second clock signal En. Thus, the third PMOS transistor P3 may be gated through the second clock signal En.

(373) The positions of the second gate contact GC2 and the fourth gate contact via VG4, which are electrically connected to the fourth gate structure **230**, are not limited thereto.

(374) A fourth gate contact GC4 extending in the third direction z may be disposed on the fifth gate structure **240**. In addition, a fifth gate contact via VG5 extending in the third direction z may be disposed on the fourth gate contact GC4. The fifth gate contact via VG5 may be connected to a first_sixth metal line M1_6 extending in the first direction x. That is, the fifth gate structure **240** is electrically connected to the first_sixth metal line M1_6, the fifth gate contact via VG5, and the fourth gate contact GC4 to receive the first clock signal En. Thus, the third NMOS transistor N3 may be gated through the first clock signal En.

(375) The positions of the fourth gate contact GC4 and the fifth gate contact via VG5, which are electrically connected to the fifth gate structure **240**, are not limited thereto.

(376) A sixth gate contact GC6 extending in the third direction z may be disposed on the sixth gate structure **250**. In addition, a sixth gate contact via VG6 extending in the third direction z may be disposed on the sixth gate contact GC6. The sixth gate contact via VG6 may be connected to a first_seventh metal line M1_7 extending in the first direction x. That is, the sixth gate structure **250** may be electrically connected to the first_seventh metal line M1_7, the sixth gate contact via VG6, and the sixth gate contact GC6 to receive the scan input signal Si. Thus, the fourth PMOS transistor P4 and the fourth NMOS transistor N4 may be gated through the scan input signal Si.

(377) The sixth gate contact GC6 and the sixth gate contact via VG6, which are electrically connected to the sixth gate structure **250**, are illustrated in this drawing as being disposed on the first active region ACT1, but are not limited thereto, and may be disposed on the second active region ACT2 as illustrated in FIG. 44.

(378) A fifth source/drain contact via VSD5 extending in the third direction z may be disposed on the fifth source/drain contact **140**. In addition, a first_fourth metal line M1_4 extending in the first direction x may be disposed on the fifth source/drain contact via VSD5 and may be connected to the outside.

(379) The fifth source/drain contact via VSD5, which is electrically connected to the fifth

source/drain contact **140**, is illustrated in this drawing as being disposed on the first active region **ACT1**, but is not limited thereto, and may be disposed on the second active region **ACT2** as illustrated in **FIG. 44**.

(380) The plurality of gate structures (e.g., the first to sixth gate structures **200** to **250**) and the plurality of source/drain contacts (e.g., the first to eighth source/drain contacts **100** to **170**), which are disposed to be adjacent to each other in the first direction **x**, may be spaced apart from each other by 1 CPP. As an example, the first gate structure **200** and the first source/drain contact **100** adjacent to each other may be spaced apart from each other by 1 CPP.

(381) For example, assume that the first gate structure **200** and the first source/drain contact **100** are adjacent to each other. When the distance between a center line of the first gate structure **200** extending in the second direction **y** and a center line of the first source/drain contact **100** extending in the second direction **y** is 1 CPP, it means that the other gate structure or source/drain contact is not disposed between the first gate structure **200** and the first source/drain contact **100**.

(382) Further, the metal lines (e.g., the first_first to first_seventh metal lines **M1_1** to **M1_7**), which are disposed to be adjacent to each other in the second direction **y**, may be spaced apart from each other by 1 CPP. As an example, the first_first metal line **M1_1** and the first_third metal line **M1_3** adjacent to each other may be spaced apart from each other by 1 CPP.

(383) For example, assume that the first_first metal line **M1_1** and the first_third metal line **M1_3** are adjacent to each other. When the distance between a center line of the first_first metal line **M1_1** extending in the first direction **x** and a center line of the first_third metal line **M1_3** extending in the first direction **x** is 1 CPP, it means that the other metal line is not disposed between the first_first metal line **M1_1** and the first_third metal line **M1_3**.

(384) In concluding the detailed description, those skilled in the art will appreciate that many variations and modifications may be made to the example embodiments without substantially departing from the principles of the present inventive concepts. Therefore, the disclosed example embodiments are used in a generic and descriptive sense only and not for purposes of limitation.

Claims

1. An integrated circuit comprising: a first inverter including a first p-channel metal-oxide-semiconductor (PMOS) transistor and a first n-channel metal-oxide-semiconductor (NMOS) transistor, which are gated through a first metal line to which a first input voltage is configured to be applied, and configured to output a first inverted voltage by inverting the first input voltage, wherein a drain of the first NMOS transistor and a drain of the first PMOS transistor are routed through a first source/drain contact, a first metal line extends in a first direction, and the first source/drain contact extends in a second direction perpendicular to the first direction; a first transmission gate including a second PMOS transistor gated through a second metal line to which a first active voltage is configured to be applied and a second NMOS transistor gated through a third metal line to which a second active voltage is configured to be applied, wherein a source of the second PMOS transistor and a drain of the second NMOS transistor are routed through the first source/drain contact, and a drain of the second PMOS transistor and a source of the second NMOS transistor are routed through a second source/drain contact; and a first tri-state inverter including a third PMOS transistor gated through a fourth metal line to which the second active voltage is configured to be applied, a third NMOS transistor gated through a fifth metal line to which the first active voltage is configured to be applied, and a fourth PMOS transistor and a fourth NMOS transistor, which are gated through a sixth metal line to which a second input voltage is configured to be applied, and configured to invert the second input voltage, wherein a drain of the third PMOS transistor and a drain of the third NMOS transistor are routed through the second source/drain contact.

2. The integrated circuit of claim 1, further comprising: a first active region extending in the first

direction and including the first to fourth PMOS transistors; a second active region extending in the first direction and including the first to fourth NMOS transistors; a power rail extending in the first direction and configured to supply a power voltage to the first PMOS transistor and the fourth PMOS transistor; and a ground rail extending in the first direction and configured to supply a ground voltage to the first NMOS transistor and the fourth NMOS transistor, wherein the first active region and the second active region are spaced apart from each other by a first distance in the second direction intersecting the first direction, the first active region and the power rail are spaced apart from each other by a second distance in the second direction, and the second active region and the ground rail are spaced apart from each other by a third distance in the second direction.

3. The integrated circuit of claim 2, wherein the second distance is equal to the third distance.
4. The integrated circuit of claim 2, wherein a sum of the second distance and the third distance is greater than the first distance.
5. The integrated circuit of claim 2, wherein a sum of the second distance and the third distance is less than the first distance.
6. The integrated circuit of claim 1, further comprising: a first gate contact configured to apply the first input voltage to the first metal line; a second gate contact configured to apply the first active voltage to the second metal line; a third gate contact configured to apply the second active voltage to the third metal line; a fourth gate contact configured to apply the second active voltage to the fourth metal line; a fifth gate contact configured to apply the first active voltage to the fifth metal line; and a sixth gate contact configured to apply the second input voltage to the sixth metal line.
7. The integrated circuit of claim 6, wherein heights of the second gate contact and the fourth gate contact in the second direction are equal to each other.
8. The integrated circuit of claim 6, wherein heights of the second gate contact and the fourth gate contact in the second direction are different from each other.
9. The integrated circuit of claim 6, wherein heights of the fourth gate contact and the sixth gate contact in the second direction are different from each other.
10. The integrated circuit of claim 6, wherein heights of the fourth gate contact and the sixth gate contact in the second direction are equal to each other.
11. The integrated circuit of claim 6, wherein heights of the first gate contact and the sixth gate contact in the second direction are different from each other.
12. The integrated circuit of claim 1, further comprising: a first active region extending in the first direction and including the first to fourth PMOS transistors, wherein a first gate contact configured to apply the first input voltage to the first metal line, a second gate contact configured to apply the first active voltage to the second metal line, and a fourth gate contact configured to apply the second active voltage to the fourth metal line are on the first active region; a second active region extending in the first direction and including the first to fourth NMOS transistors, wherein a third gate contact configured to apply the second active voltage to the third metal line, a fifth gate contact configured to apply the first active voltage to the fifth metal line, and a sixth gate contact configured to apply the second input voltage to the sixth metal line are on the second active region; a power rail extending in the first direction and configured to supply a power voltage to the first PMOS transistor and the fourth PMOS transistor; and a ground rail extending in the first direction and configured to supply a ground voltage to the first NMOS transistor and the fourth NMOS transistor, wherein the first active region and the power rail are spaced apart from each other by a first distance in the second direction, and the second active region and the ground rail are spaced apart from each other by a second distance in the second direction.
13. The integrated circuit of claim 12, wherein the power rail and the first gate contact are spaced apart from each other by a third distance in the second direction, the power rail and the second gate contact are spaced apart from each other by a fourth distance in the second direction, the power rail and the fourth gate contact are spaced apart from each other by a fifth distance in the second direction, and the shortest distance among the third to fifth distances is greater than the first

distance.

14. The integrated circuit of claim 12, wherein the power rail and the third gate contact are spaced apart from each other by a third distance in the second direction, the power rail and the fifth gate contact are spaced apart from each other by a fourth distance in the second direction, the power rail and the sixth gate contact are spaced apart from each other by a fifth distance in the second direction, and the shortest distance among the third to fifth distances is greater than the second distance.
