

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12389817
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Nishii; Yasuto et al.

Autonomous travel method, work vehicle, and autonomous travel system

Abstract

A combine harvester is a work vehicle that pre-creates a plurality of travel routes parallel to a preset outline of a field and performs autonomous travel based on the travel routes, and includes a control device and a mobile terminal. The control device functions as the autonomous travel controller to control autonomous travel on the basis of the travel route. The mobile terminal is equipped with a terminal control device, and the terminal control device functions as the route adjustment controller that performs route adjustment control to adjust the outermost route when autonomously traveling on the outermost route that is along the outline of the field from among the plurality of travel routes.

Inventors: Nishii; Yasuto (Okayama, JP), Murayama; Masaaki (Okayama, JP), Yamaguchi; Yuji (Okayama, JP)

Applicant: Yanmar Holdings Co., Ltd. (Osaka, JP)

Family ID: 1000008766965

Assignee: Yanmar Holdings Co., Ltd. (Osaka, JP)

Appl. No.: 18/220788

Filed: July 11, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240040947 A1	Feb. 08, 2024

Foreign Application Priority Data

JP	2022-121244	Jul. 29, 2022
----	-------------	---------------

Publication Classification

Int. Cl.: A01B69/00 (20060101); A01B69/04 (20060101)

U.S. Cl.:

CPC A01B69/008 (20130101);

Field of Classification Search

CPC: A01B (69/008)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2020/0064863	12/2019	Tomita	N/A	A01B 69/00
2022/0408630	12/2021	Nishii	N/A	A01B 69/008
2024/0032452	12/2023	Suzuki	N/A	G05D 1/0219

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
3557360	12/2018	EP	A01D 41/1278
2021083332	12/2020	JP	A01B 69/008
2021038613	12/2020	KR	N/A
20210038613	12/2020	KR	A01B 69/008
2021067923	12/2020	KR	N/A
20210067923	12/2020	KR	G05D 1/248
WO-2018116770	12/2017	WO	A01B 69/00
WO-2021106389	12/2020	WO	A01B 69/008
WO-2022118572	12/2021	WO	G05D 1/0219

Primary Examiner: Chen; Shelley

Background/Summary

CROSS-REFERENCE

(1) This application claims foreign priority of JP2022-121244 filed Jul. 29, 2022, the disclosure of which is hereby incorporated by reference in its entirety.

TECHNICAL FIELD

(2) This disclosure relates to an autonomous travel method, a work vehicle, and an autonomous travel system for a work vehicle that performs autonomous travel based on a travel route parallel to an outline of a field.

BACKGROUND ART

(3) Conventionally, a work vehicle working in a field can acquire and use an outline of a field based on position information when the work vehicle travels along an outer periphery of the field. For example, a work vehicle such as a combine harvester presets the outline of the field acquired

during the previous year's reaping operation or this year's planting operation, uses it during this year's reaping operation, creates multiple travel routes parallel to the outline of the field in advance, and performs autonomous travel based on the travel routes.

(4) For example, in Patent Document 1 discloses a controller of a combine harvester functions as a travel route creation unit that creates a travel route corresponding to a field, and as an autonomous travel control unit that controls autonomous travel and autonomous reaping along the travel route. The travel route creation unit sets a route for reaping while traveling in a liner manner, and sets a travel route by combining a plurality of linear routes for an area consisting of unreaped culms in the field.

PRIOR ART DOCUMENT

Patent Document

(5) Patent Document 1: Japanese Laid-open Patent Publication No. 2021-185852

SUMMARY OF INVENTION

Technical Problem

(6) Meanwhile, even if the plurality of travel routes parallel to the preset outline of the field is created in advance, there is a case where a work vehicle autonomously travels on a route different from the preset travel route. For example, when a combine harvester, which is a work vehicle, performs reaping operation in the field, it first creates a travel route parallel to the outline of the field and along the outer periphery of the field in order to perform reaping travel around along the outer periphery of the field. For example, if a travel route is set at a position recommended for headland formation, the headland can be formed along the outline of the field by performing reaping travel along the travel route. At this time, even if a travel route is created so that a travel direction is a predetermined circulating direction (e.g., counterclockwise direction), depending on a positional relationship between a position and direction of an entrance into the field or a position and direction of the work vehicle when starting reaping, and the travel route created in advance, the work vehicle may perform reaping travel in a direction opposite to the travel direction. At this time, the work vehicle may not be able to perform autonomous travel properly.

(7) In addition, although a work vehicle creates the travel route on the basis of a center position of a machine body, a length from the center of the body of the work machine, which performs reaping operation and the like, to the left end thereof may be different from a length from the center thereof to the right end thereof. At this time, if a travel route with a travel direction is created so that a shorter end side of the work machine is located on the outer periphery side of the field (ridge side), a longer end side of the work machine deviates to the outside of the field when traveling the travel route in a direction opposite to the travel direction. On the other hand, if a travel route with a travel direction is created so that the longer end side of the work machine is located on the outer periphery side of the field (ridge side), the shorter end side of the work machine does not reach the outer periphery side of the field and leaves an unreaped area when traveling the travel route in a direction opposite to the travel direction. In this way, the work vehicle may not be able to perform autonomous travel properly.

(8) In order to perform autonomous travel of this year, the work vehicle creates multiple travel routes based on the outline of the field which was acquired during work of the previous year. However, if the work area to be automatically traveled of this year, i.e., the outline of the field, is different from that of the previous year, the multiple travel routes created based on the outline of the previous year's field cannot provide appropriate autonomous travel suitable for the work area of this year.

(9) An object of the present disclosure is to provide an autonomous travel method, a work vehicle, and an autonomous travel system capable of appropriately performing autonomous travel regardless of a travel route that is created in advance.

Solution to Problem

(10) In order to solve the above mentioned problem, an autonomous travel method of the present

disclosure is an autonomous travel method for a work vehicle that pre-creates a plurality of travel routes parallel to a preset outline of a field and performs autonomous travel based on the travel routes, the method including the steps of: performing autonomous travel control to control the autonomous travel based on the travel routes; and performing route adjustment control to adjust an outermost route when the autonomous travel is performed on the outermost route along the outline of the field among the plurality of travel routes.

(11) In order to solve the above mentioned problem, a work vehicle of the present disclosure is a work vehicle for pre-creating a plurality of travel routes parallel to a preset outline of a field and performing autonomous travel based on the travel routes, including: an autonomous travel controller to control the autonomous travel based on the travel routes; and a route adjustment controller to perform route adjustment control for adjusting an outermost route when the autonomous travel is performed on the outermost route along the outline of the field among the plurality of travel routes.

(12) In order to solve the above mentioned problem, an autonomous travel system of the present disclosure is an autonomous travel system of a work vehicle for pre-creating a plurality of travel routes parallel to a preset outline of a field and performing autonomous travel based on the travel routes, including: an autonomous travel controller to control the autonomous travel based on the travel routes; and a route adjustment controller to perform route adjustment control for adjusting an outermost route when the autonomous travel is performed on the outermost route along the outline of the field among the plurality of travel routes.

Advantageous Effects of Invention

(13) The present disclosure provides an autonomous travel method, a work vehicle, and an autonomous travel system capable of appropriately performing autonomous travel regardless of a travel route that is created in advance.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1 is a side view illustrating a combine harvester according to an embodiment of the present disclosure,

(2) FIG. 2 is a block diagram illustrating the combine harvester according to the embodiment of the present invention,

(3) FIG. 3 is a plan view illustrating an example of a field in which a pre-created travel route is set in the combine harvester according to the embodiment of the present disclosure,

(4) FIG. 4 is a plan view illustrating an example of a field in which a travel route with an outermost route adjusted is set in the combine harvester according to the embodiment of the present disclosure,

(5) FIG. 5 is a plan view illustrating an example of a work screen displayed on a mobile terminal of the combine harvester according to the embodiment of the present disclosure,

(6) FIG. 6 is a flowchart illustrating exemplarily autonomous travel operation of the combine harvester according to the embodiment of the present invention, and

(7) FIG. 7 is a plan view illustrating an example of the field in which a travel route is set at the third route mode in the combine harvester according to the embodiment of the present disclosure.

DESCRIPTION OF EMBODIMENTS

(8) Now, a combine harvester **1**, which is an embodiment of a work vehicle according to an embodiment of the present disclosure, is described with reference to FIG. 1, etc. The combine harvester **1** travels in a field as a target to be worked by automatic driving or manual operation, and performs work such as reaping in order to perform a harvest work of crops from grain culms planted in the field. The combine harvester **1** is configured to, for example, control steering by

automatic driving, as well as perform automatic work that controls a traveling speed in response to a manual operation, unmanned work that controls steering and a traveling speed by automatic driving, and can autonomously travel, turn, and work within the field.

(9) While traveling on the route of straight rows in which a predetermined row number within the reaping possible row number is a work width (reaping width) for a plurality of rows of grain culms, the combine harvester **1** performs reaping work for the straight rows. The combine harvester **1** is set to a traveling mode of either a manual travel mode or an autonomous travel mode. When the manual travel mode is set, the combine harvester **1** is configured to perform manual travel according to steering of a steering part **9** by an operator.

(10) On the other hand, when the autonomous travel mode is set, the combine harvester **1** is configured to perform autonomous straight travel to perform autonomous reaping while autonomously traveling along a travel route parallel to a predetermined reference.

(11) For example, as shown in FIG. **2**, the combine harvester **1** is equipped with a control device **40**, and by using the outline side that configures the preset outline of the field as a reference line, the control device **40** creates a travel route parallel to the reference line in advance. The travel route indicates the position where a center of the combine harvester **1** (machine body center) in a machine-body-width direction (left-right direction) passes through the field.

(12) When the autonomous travel mode is set, the combine harvester **1** sets either a work width reference mode or a vehicle's own position reference mode as a route mode of the travel route for autonomous travel.

(13) When the work width reference mode is set, the combine harvester **1** creates multiple travel routes parallel to the outline of the field (any of outline sides) and at work width intervals of the combine harvester **1** from the outline of the field. In this case, the combine harvester **1** performs outer periphery reaping travel, in which the combine harvester **1** circulates along the outer periphery of the field and travels while reaping, based on a travel route parallel to the outline of the field, so that a headland area is formed in the field. Furthermore, in the work area formed inside the headland, the combine harvester **1** performs autonomous straight travel for each travel route set parallel to the outline of the field.

(14) On the other hand, when the vehicle's own position reference mode is set, the combine harvester **1** creates a single travel route that is parallel to the outline of the field and passes through the combine **1**'s own vehicle position. In this case, the combine harvester **1** sets the travel route each time it starts the autonomous straight travel.

(15) As illustrated in FIG. **1**, the combine harvester **1** includes a traveling part **2**, a reaping part **3**, a threshing part **4**, a sorting part **5**, an accumulation part **6**, a discharged straw processing part **7**, a power unit **8**, and a steering part **9**, and is configured as a so-called normal-type combine harvester. While traveling by the traveling part **2**, the combine harvester **1** threshes, by the threshing part **4**, grain culms reaped by the reaping part **3**, sorts the grains by the sorting part **5**, and stores the grains in the accumulation part **6**. The combine **1** processes threshed and discharged straw with the discharged straw processing part **7**. By the power supplied by the power unit **8**, the combine harvester **1** drives the traveling part **2**, the reaping part **3**, the threshing part **4**, the sorting part **5**, the accumulation part **6**, and the discharged straw processing part **7**.

(16) The traveling part **2** is provided below a machine body frame **10**, and includes a pair of crawler-type traveling device **11** on each side and a transmission (not shown). By the power (for example, rotational power) transmitted from an engine **31** of the power unit **8**, the traveling part **2** rotates a crawler of the crawler-type traveling device **11**, thereby to cause the combine harvester **1** to travel in the front/rear direction, or causes the combine harvester **1** to turn to the right/left direction. The transmission transmits power (rotational power) of the power unit **8** to the crawler-type traveling device **11** and is capable of shifting the rotational power.

(17) The reaping part **3** is installed in front of the traveling part **2** and is a work machine that reaps a predetermined reaping width (work width) of culms in the unreaped area (work area). In the

present embodiment, the reaping part **3** is configured so that the width direction of the combine harvester **1** (left and right direction) is the work width direction, and the lengths from the center of the combine harvester **1** to both ends in the work width direction are different. For example, the reaping part **3** is configured so that the length from the center of the machine body to one end (e.g., right end) is shorter than the length from the center of the machine body to the other end (e.g., left end), in other words, the reaping part **3** is configured to have one end with a shorter length and the other end with a longer length. For example, the reaping part **3** is provided with a divider **13**, a scraping reel **14**, a mowing blade **15**, a scraping auger **16**, a feeder house **17**, and a conveyor **18**.

(18) The divider **13** is provided protruding forward from the left front end and right front end of the reaping part **3**, and guides grain culms in the unreaped area within the reaping width. The scraping reel **14** is located behind the divider **13**, and is rotatable around a rotation axis extending in the left-right direction. The scraping reel **14** is rotationally driven so as to assist in reaping the grain culms guided by the divider **13**, thereby to scrape the tip side of the grain culms while causing the grain culms to stand. The mowing blade **15** is positioned below the scraping reel **14**, and cuts the culm end side of the grain culm scraped by the scraping reel **14** thereby reaping the grain culm.

(19) The scraping auger **16** is located behind the scraping reel **14** and mowing blade **15**, and is provided rotatable around a rotation axis extending in the left-right direction. The scraping auger **16** is rotationally driven thereby to scrape the grain culms mowed by the mowing blade **15** and convey the grain culms rearward.

(20) The feeder house **17** extends forward from the machine body frame **10** to be positioned behind the scraping auger **16**, and is supported by the machine body frame **10** rotatable around the drive shaft **18a** of the conveyor **18**. Furthermore, the feeder house **17** rotates, thereby to raise and lower the divider **13**, the scraping reel **14**, the mowing blade **15** and the scraping auger **16**, which are provided in front of the feeder house **17**, i.e., raising and lowering the reaping part **3**. The combine harvester **1** is equipped with a lifting device **19** on the machine body frame **10** that raises and lowers the reaping part **3** by rotating the feeder house **17**. The lifting device **19** includes, for example, a hydraulic cylinder powered by the engine **31**.

(21) The conveyor **18** is rotatably provided within the feeder house **17**, and moves as the feeder house **17** rotates. The conveyor **18** is rotationally driven thereby to convey the grain culms, which are conveyed into the feeder house **17** by the scraping auger **16**, further rearward to the threshing part **4**.

(22) The threshing part **4** is provided behind the feeder house **17** of the reaping part **3**, and threshes the grain culms conveyed from the feeder house **17**. The threshing part **4** is provided with a handling drum **22** and a receiving net **23**. The handling drum **22** threshes grains from the grain culms conveyed from the feeder house **17**, and conveys the threshed grain culms, that is, discharged straw, to the discharged straw processing part **7**. The receiving net **23** supports the grain culms conveyed by the handling drum **22**, and sifts and drops the grains.

(23) The sorting part **5** is provided below the threshing part **4**. The sorting part **5** includes a swing sorting device **25**, an air blow sorting device **26**, a grain conveying device (not shown), and a waste straw discharging device (not shown). The swing sorting device **25** sifts the threshed grain that falls from the threshing part **4** and sorts the threshed grains into grain, straw waste, etc. The air blow sorting device **26** further sorts the threshed grains that fall from the threshing part **4** or the threshed grains that are sorted by the swing sorting device **25** into grains, straw wastes, etc., by air blow. The grain conveying device conveys to the accumulation part **6** grains sorted by the swing sorting device **25** and the air blow sorting device **26**. The waste straw discharging device discharges to the outside of the machine the waste straw and the like sorted by the swing sorting device **25** and the air blow sorting device **26**.

(24) The accumulation part **6** is disposed on the right side of the threshing part **4**. The accumulation part **6** includes a grain tank **28** and a grain discharging device **29**. The grain tank **28** reserves the grains conveyed from the sorting part **5**. The grain discharging device **29** is composed of a

discharging auger or the like, and discharges the grains stored in the grain tank **28** to any place.

(25) The discharged straw processing part **7** is disposed behind the threshing part **4**. The discharged straw processing part **7** includes a discharged straw conveying device (not shown) and a discharged straw cutting device (not shown). The discharged straw processing part **7**, by the discharged straw conveyor, conveys the discharged straws which are conveyed from the threshing part **4** to the discharged straw cutting device, cuts the straws by the discharged straw cutting device, and discharges the cut straws to behind the combine harvester **1**.

(26) The power part **8** is disposed above the traveling part **2**, and in front of the accumulation part **6**. The power unit **8** includes an engine **31** that generates rotational power. The power unit **8** transmits rotational power generated by the engine **31**, to the traveling part **2**, the reaping part **3**, the threshing part **4**, the sorting part **5**, the accumulation part **6**, and the discharged straw processing part **7**. Furthermore, the combine harvester **1** is equipped with a fuel tank (not shown) to store fuel to be supplied to the engine **31** of the power unit **8**.

(27) The steering part **9** is disposed above the power unit **8**. Around a driver's seat on which the operator is seated, the steering part **9** is provided with operation tools for steering the combine harvester **1**. The steering part **9** includes as the operation tools a steering wheel which is a steering wheel to instruct the machine body of the combine harvester **1** to turn, a main gearshift lever and a sub gearshift lever which are a speed changing tool to instruct the combine harvester **1** to make a speed change in forward and backward travel, and the like. Manual traveling of the combine harvester **1** is performed by the traveling part **2** that accepts operation of the steering wheel, the main gearshift lever and the sub gearshift lever of the steering part **9**. Also, the steering part **9** includes a mechanism for operating reaping work by the reaping part **3**, threshing work by the threshing part **4**, discharging work by the grain discharging device **29** of the accumulation part **6**, and the like.

(28) The combine harvester **1** includes a positioning unit **33** that uses a satellite positioning system such as GPS to acquire the combine harvester **1**'s own position. The positioning unit **33** receives a positioning signal from a positioning satellite via a positioning antenna, and acquires position information of the positioning unit **33**, i.e., the combine harvester **1**'s own position, based on the positioning signal.

(29) Next, a control device **40** of the combine harvester **1** is described with reference to FIG. **2**. The control device **40** is composed of a computer such as a CPU and is connected to a storage unit **41** such as ROM, RAM, hard disk drive, flash memory, etc. and a communication unit **42** which communicates with external devices.

(30) The storage unit **41** stores program and data to control a variety of components and a variety of functionalities of the combine harvester **1**, and the control device **40** executes arithmetic processing based on the program and data stored in the storage unit **41** to control the variety of components and the variety of functionalities. The control device **40**, for example, acquires the combine harvester **1**'s own position by controlling the positioning unit **33** and also acquires a travel direction at the combine harvester **1**'s own position.

(31) Via a wireless communication antenna, the communication unit **42** is capable of wirelessly communicating with the external devices such as a mobile terminal **50** belonging to the operator. The control device **40** controls the communication unit **42** to perform wireless communication with a mobile terminal **50**, and transceives a variety of information to and from the mobile terminal **50**.

(32) As shown in FIG. **3** or **4**, the control device **40** receives field information and a travel route **63** that are set for the field **60**, which is a target to be worked by the combine harvester **1**, from the mobile terminal **50** via the communication unit **42**, and stores them in the storage unit **41**.

(33) In FIGS. **3** and **4**, the field **60** has an unreaped area **61** (unworked area) where the reaping is not yet performed, and a reaped area (worked area) where the reaping operation of the culms is already completed, and also the figures shows an example in which the travel route **63** is set.

(34) The field information includes information such as shape, size, and position information

(coordinates, etc.) of field area along the outer periphery of the field **60**, as well as information such as shape, size, and position information (coordinates, etc.) of the unreaped area **61** in the field **60**. For example, the travel route **63** includes traveling information about autonomous travel and work information about work such as reaping and the like. The traveling information includes the travel position in the field **60** as well as the travel direction and the set vehicle speed at each travel position. The work information includes information associated with the work such as operation or stop of the reaping, the reaping speed and reaping height at each travel position.

(35) Furthermore, the control device **40** operates as an autonomous travel controller **45** by executing the program stored in the storage unit **41**. The autonomous travel controller **45** realizes an autonomous travel step of the autonomous travel method according to the present disclosure.

(36) The autonomous travel controller **45** controls, when the autonomous travel mode is set, the autonomous traveling (autonomous straight travel) of the combine harvester **1** based on the travel route **63** set for the field **60**. Upon autonomous travel is initiated, the autonomous travel controller **45** acquires the combine harvester **1**'s own position from the positioning unit **33**, and controls the power unit **8** and the traveling part **2** and the reaping part **3** such that the combine harvester **1** performs autonomous travel along the travel route **63** based on the combine harvester **1**'s own position, the field information, and the travel route **63**.

(37) The mobile terminal **50** is one of components of the combine harvester **1**, which can remotely operate the combine harvester **1**, and is composed of a tablet terminal including a touch panel, a laptop personal computer, or the like, for example. An operation device similar to the mobile terminal **50** may be provided in the steering part **9**. In the present disclosure, the autonomous travel system includes the combine harvester **1** and the mobile terminal **50**. The mobile terminal **50** may be configured separately from the combine harvester **1** or integrally to the combine harvester **1**.

(38) As shown in FIG. **2**, the mobile terminal **50** includes a terminal control device **51** composed of a computer such as a CPU, and the terminal control device **51** is connected to a terminal storage unit **52** such as a ROM, a RAM, a hard disk drive, a flash memory or the like, a terminal communication unit **53** that communicates with an external devices. The mobile terminal **50** includes a display unit **54**, such as a touch panel or a monitor, for displaying various information to output them to the operator, and the display unit **54** which is composed of the touch panel functions as an input unit for accepting input operation of various information from the operator.

(39) The terminal storage unit **52** stores a program and data for controlling various components and various functions of the mobile terminal **50**. The terminal control device **51** executes arithmetic process based on the program and the data stored in the terminal storage unit **52**, thereby controlling the various components and the various functions of the mobile terminal **50**. The terminal storage unit **52** stores field information and the travel route **63** of the field **60**, which is a target to be worked by the combine harvester **1**.

(40) The terminal communication unit **53** is communicably connected to the communication unit **42** in the combine harvester **1** via a wireless communication antenna. The terminal control device **51** controls the terminal communication unit **53** to perform wireless communication with the combine harvester **1**, and transceives various information to and from the combine harvester **1**.

(41) The terminal control device **51** operates as a field selection unit **55**, a travel route creation unit **56**, a route adjustment controller **57**, a display control unit **58**, and an alarm notification unit **59** by executing the program stored in the terminal storage unit **52**. The field selection unit **55**, the travel route creation unit **56**, the route adjustment controller **57**, the display control unit **58**, and the alarm notification unit **59** realize a field selection step, a travel route creation step, a route adjustment control step, a display control step, and an alarm notification step of the autonomous travel method according to the present disclosure, respectively.

(42) The mobile terminal **50** enables the operator to set any of the manual travel mode and the autonomous travel mode according to the operator's operation, and also enables the operator to set any of the route modes such as the work width reference mode and the vehicle's own position

reference mode. For example, in the mobile terminal **50**, the terminal control device **51** functions as a traveling mode setting unit to set the traveling mode and as a route mode setting unit to set the route mode according to operation on the setting screen (not shown) displayed at the display unit **54** by the display control unit **58**. In other words, the terminal control device **51** realizes the travelling mode setting step for setting the traveling mode and the route mode setting step for setting the route mode of the autonomous travel method according to the present disclosure.

(43) The field selection unit **55** manually or automatically selects the field **60** which is a target to be worked by autonomous travel. For example, the field selection unit **55** displays, on the display unit **54**, a field selection screen (not shown) for selectively operating the field **60** that corresponds to the field information preset and stored in the terminal storage unit **52**. Once any of the fields **60** is selected on the field selection screen in response to the manual operation, the field selection unit **55** selects the selected field **60** as the target to be worked and reads out the field information from the terminal storage unit **52**. For example, the mobile terminal **50** stores the field information acquired during reaping work of the previous year by the combine harvester **1** in the terminal storage unit **52**, and stores the field information acquired during works of this year by other work vehicles (e.g., planting work by a rice transplanter or tilling work by a tractor) in the terminal storage unit **52**.

(44) When creation of a new field is operated on the field selection screen, the field selection unit **55** selects, as the target to be worked, the new field in the vehicle's own position of the combine harvester **1**. In this case, when the combine harvester **1** performs the reaping travel while circulating along the outer periphery of the new field, the field selection unit **55** receives from the combine harvester **1** the vehicle's own position of the combine harvester **1** that is positioned by the positioning unit **33** of the combine harvester **1**, and records the position information of the outer periphery or the position information of the route of reaping travel, thereby to create the field information of the new field and store the created field information in the terminal storage unit **52**.

(45) The travel route creation unit **56** creates in advance the travel route **63** along which the combine harvester **1** autonomously travels, based on the field information of the field **60** selected by the field selection unit **55**, by using the outline side **60a** constituting the outline of the field **60** as a reference line, creates the travel route **63** parallel to the reference line, stores it in the terminal storage unit **52**, and transmits it to the combine harvester **1** via the terminal communication unit **53**. At this time, the travel route creation unit **56** sets, as the reference line, the outline side **60a** that is closest to the combine harvester **1**'s own position and has the smallest angle to a travel direction of the combine harvester **1**, among the multiple outline sides that configures the outline of the field **60**.

(46) The travel route creation unit **56**, for example, sets the travel route **63** according to the set route mode when the field **60** to be worked is selected. When the work width reference mode is set as the route mode, the travel route creation unit **56** creates a plurality of travel routes **63** that are parallel to the outline side **60a** which is the reference line of the field **60** and are arranged at intervals of the work width of the combine harvester **1** from the outline side **60a** of the field **60**.

(47) On the other hand, when the vehicle's own position reference mode is set as the route mode, the travel route creation unit **56** creates a single travel route **63** that is parallel to the outline side **60a** which is the reference line of the field **60** and passes through the combine harvester **1**'s own position.

(48) Furthermore, when the work width reference mode is set, the travel route creation unit **56** creates the travel route **63** by setting the travel direction so that a shorter one end (e.g., right end) of the reaping part **3** follows the outline side of the field **60**, as the travel route **63** (outermost route **64**) closest to the outline side **60a** that is the reference line. In this case, for example, the travel route creation unit **56** may preferably set the travel route **63** in such a position that the travel direction along a direction corresponding to the outline side **60a**, which is the reference line, is recommended in a predetermined circulating direction (e.g., counterclockwise direction) along the outer periphery of the field **60**. As another example, when creating the travel route **63**, the travel

route creation unit **56** may set the travel direction in advance as the travel route **63**. For example, in a predetermined circulating direction, the travel direction corresponding to the outline side **60a**, which is the reference line of the travel route **63** may be set to the travel route **63**.

(49) When the autonomous travel mode is set as the traveling mode, and if the travel route **63** is created using the preset field information and the autonomous travel is performed on the outermost route **64** along the predetermined outline side **60a** that constitutes the outline of the field **60**, the route adjustment controller **57**, as shown in FIG. **4**, performs route adjustment control to adjust the outermost route **64**. At this time, the route adjustment controller **57** adjusts as route adjustment control the outermost route **64** so as to be parallel to the outline side **60a** of the field **60** and pass through the combine harvester **1**'s own position. In FIG. **4**, the outermost route **64a** before adjustment is shown as a dashed line, and the outermost route **64b** after adjustment is shown as a solid line.

(50) Therefore, when the work width reference mode is set as the route mode, the route adjustment controller **57** can adjust the outermost route **64** so as to pass through the combine harvester **1**'s own position, without switching route modes, by performing route adjustment control. At this time, the route adjustment controller **57** adjusts as route adjustment control any travel routes **63** other than the outermost route **64** among the plurality of travel routes **63** so as to be arranged at intervals of a work width from the adjusted outermost route **64b**. In FIG. **4**, the travel route **63a** before adjustment is shown as a dashed line, and the travel route **63b** after adjustment is shown as a solid line.

(51) The route adjustment controller **57** may determine whether or not the separation distance between the outermost route **64a** and the combine harvester **1**'s own position exceeds a predetermined separation threshold in a direction orthogonal to the outermost route **64a** of the travel route **63a** created in advance, and perform route adjustment control according to the determination result. For example, the route adjustment controller **57** may perform route adjustment control if the separation distance exceeds the separation threshold, while it may not perform route adjustment control if the separation distance is equal to or less than the separation threshold.

(52) When the work width reference mode is set, the autonomous travel controller **45** of the combine harvester **1** enables shift to autonomous travel after route adjustment control by the route adjustment controller **57** is performed, but when route adjustment control is not performed, it disables shift to autonomous travel. On the other hand, when the vehicle's own position reference mode is set, the autonomous travel controller **45** of the combine harvester **1** may enable shift to autonomous travel without performing route adjustment control by the route adjustment controller **57**. Alternatively, the route adjustment controller **57** may perform route adjustment control each time when autonomous travel of the outermost route **64** is started, regardless of the route mode.

(53) The route adjustment controller **57** performs route adjustment control before autonomous travel of the outermost route **64** is started. For example, when the work screen **70** for performing autonomous travel is displayed on the display unit **44**, the route adjustment controller **57** performs route adjustment control in response to operation of the route adjustment button **77** on the work screen **70**. Alternatively, when the travel start button **72** is operated without the route adjustment button **77** being operated on the work screen **70**, the route adjustment controller **57** recommends performing route adjustment control to the operator before the autonomous travel is started. At this time, if operation of route adjustment control is not performed, the route adjustment controller **57** does not perform route adjustment control, and the autonomous travel controller **45** of the combine harvester **1** disables shift to autonomous travel.

(54) The route adjustment controller **57** may not perform route adjustment control to any travel routes **63** other than the outermost route **64** among the plurality of travel routes **63** before the autonomous travel is started.

(55) The route adjustment controller **57** may also update the preset field information based on the

adjusted outermost route **64b**. For example, the route adjustment controller **57** calculates the position information of an outermost edge of the combine harvester **1** when the combine harvester **1** is placed at each position of the adjusted outermost route **64b** based on the positional relationship between the center of the machine body of the combine harvester **1** and the outermost edge of the combine harvester **1** (edge of the reaping part **3**), and calculates a new outline side along the adjusted outermost route **64b**. The route adjustment controller **57** then updates the field information of the field **60** selected as the work target, which is the preset field information, by the new outline side.

(56) When the autonomous travel mode is set, the display control unit **58** controls the display unit **54** to cause the work screen **70** to be displayed, which is used for performing autonomous travel in the field **60** that is a target to be worked, as illustrated in FIG. 5, based on the field information of the field **60** selected by the field selection unit **55**. The display control unit **58** causes the work screen **70** to display at least a map column **71** and to display travel start button **72** operably. In addition, the display control unit **58** causes the work screen **70** to display a field registration name **74** that is based on the field information, and a reaping available distance **75** that is based on the storage capacity (vacant capacity) of the grain tank **28** in which the combine harvester **1** stores grain. The display control unit **58** also causes the work screen **70** to display a route adjustment button **77** for performing route adjustment control.

(57) The display control unit **58** causes the map column **71** to display the outline of the field **60**, the travel route **63** set for the field **60**, and an own vehicle marker **76** of the combine harvester **1** at the combine harvester **1**'s own position positioned by the positioning unit **33**. In FIG. 5, the travel route **63** is shown as a double-dashed line. When the travel route **63** is set as a travel direction, the display control unit **58** may cause the map column **71** to indicate a corresponding travel direction with an arrow or the like when to display the travel route **63**. The display control unit **58** identifiably displays the unreaped area **61** and the reaped area **62** in the range of the field **60**, by varying a display method such as a line type, a line color, or a background color. In addition, the display control unit **58** updates the position of the own vehicle marker **76**, the range of the unreaped area **61** and the range of the reaped area, according to the progress of the reaping travel of the combine harvester **1**.

(58) When the work width reference mode is set as the route mode and the start condition for autonomous travel is met, the display control unit **58** causes the route adjustment button **77** to be selectable, while when the vehicle's own position reference mode is set as the route mode or the start condition is not met, the display control unit **58** causes the route adjustment button **77** to be unselectable. The display control unit **58** may cause the route adjustment button **77** to be selectable when the preset field information is selected (e.g., when performing reaping operation in the field **60** after two or more years), while the display control unit **58** may cause the route adjustment button **77** to be unselectable when the field information of a new field is selected (e.g., when performing reaping operation of the field **60** in the first year).

(59) The display control unit **58** causes the travel start button **72** to be selectable when a start condition for the autonomous travel is met, while the display control unit **58** causes the travel start button **72** to be unselectable when the start condition for the autonomous travel is not met. Once the travel start button **72** is selected, the display control unit **58** transmits the field information, information about the travel route **63** as well as a start instruction of autonomous travel to the combine harvester **1**. The combine harvester **1** starts autonomous travel along the travel route **63** in response to the start instruction.

(60) Furthermore, when the travel start button **72** is selected, if the work width reference mode is set as the route mode, the preset field information is selected, and the route adjustment control of the outermost route **64** of the plurality of travel routes **63** is not yet performed, the display control unit **58** performs recommendation control that recommends performing route adjustment control before issuing the start instruction of autonomous travel. The recommendation control with the

display control unit **58** may include, for example, display of a recommendation message, audio output, or display of a recommendation screen (not shown) to encourage operation of the route adjustment control using the route adjustment button **77**, or to encourage operation of the route adjustment control by operation on the recommendation screen. Furthermore, when the travel start button **72** is selected, if the vehicle's own position reference mode is set as the route mode, the field information of the new field is selected, and the route adjustment control of the outermost route **64** of the plurality of travel routes **63** is already performed, the display control unit **58** may issue the start instruction of autonomous travel.

(61) Alternatively, if the work width reference mode is set as the route mode, the preset field information is selected, and the route adjustment control of the outermost route **64** of the plurality of travel routes **63** is not yet performed, the display control unit **58** may cause the travel start button **72** to be unselectable and cause the route adjustment button **77** to be selectable.

(62) When the route adjustment control is performed by the route adjustment controller **57**, the display control unit **58** updates the travel route to the travel route **63b** including the adjusted outermost route **64b** and causes the work screen **70** to display it. The display control unit **58** may enable cancellation operation of the route adjustment control, and when the cancellation operation is performed, the display control unit **58** may cause the work screen **70** to display the previously pre-created travel route **63a**.

(63) While the combine harvester **1** performs autonomous travel, the display control unit **58** causes the work screen to display a travel stop button (not depicted) to stop autonomous travel instead of the travel start button **72** so as to be selectable and display the route adjustment button **77** so as to be unselectable. Once the travel stop button is selected, the display control unit **58** issues a stop instruction to the combine harvester **1**. In response to the stop instruction, the combine harvester **1** stops autonomous travel. Once the combine harvester **1** stops autonomous travel, the display control unit **58** causes the work screen to display the travel start button **72** instead of a travel stop button and display the route adjustment button **77** so as to be selectable.

(64) The alarm notification unit **59** provides an alarm by display or audio output when it detects a situation where the combine harvester **1** cannot continue to perform autonomous travel safely. For example, when the combine harvester **1** autonomously travels along the travel route **63** that is created by using the outline side **60a** of the field **60** as the reference line, the alarm notification unit **59** determines, based on the combine harvester **1**'s own position and travel direction of the combine harvester **1** and the field information, whether or not the distance from the combine harvester **1** to each outline side **60a** of the field **60** in the advancing direction of the combine harvester **1** is equal to or less than a predetermined distance threshold. The alarm notification unit **59** does not issue an alarm if the distance to the outline side **60a** exceeds the distance threshold, but issues an alarm if the distance to the outline side **60a** is equal to or less than the distance threshold. The distance threshold is set based on a braking distance that the combine harvester **1** can safely stop, etc.

(65) However, when the combine harvester **1** autonomously travels on the outermost route **64**, in regard to the outline side **60a** that is parallel to and closest to the outermost route **64** (that is, the outline side **60a** that is the reference line for the outermost route **64** before route adjustment control is performed), the alarm notification unit **59** does not determine whether or not the distance to the outline side **60a** is equal to or less than the distance threshold, and does not issue the alarm even if the distance is equal to or less than the distance threshold. On the other hand, even when the combine harvester **1** autonomously travels on the outermost route **64**, in regard to the outline side other than the outline side **60a** that is the reference line of the outermost route **64**, the alarm notification unit **59** determine whether or not the distance is equal to or less than the distance threshold, and issues the alarm if the distance is equal to or less than the distance threshold.

(66) Next, an example of operation of autonomous travel of the combine harvester **1** according to the present embodiment is described with reference to a flowchart illustrating in FIG. 6.

(67) In the combine harvester **1**, it is assumed that the autonomous travel mode is set as the

traveling mode and the work width reference mode is set as the route mode. First, at the mobile terminal **50**, the field selection unit **55** selects the field **60** to be worked from the field information that is set in advance and stored in the terminal storage unit **52**, and the travel route creation unit **56** creates a plurality of travel routes **63** parallel to the outline side **60a** of the field **60** (step **S1**).

(68) On the mobile terminal **50**, the display control unit **58** causes a work screen **70** to display the outline of the field **60** and a plurality of travel routes **63**. If the start operation of autonomous travel is performed by the travel start button **72** on the work screen **70** (step **S2**: Yes), before starting autonomous travel, the route adjustment controller **57** determines whether or not the travel route **63** to be worked is the outermost route **64** (step **S3**). If it is determined that the travel route **63** to be worked is not the outermost route **64** (step **S3**: No), the combine harvester **1** starts autonomous travel along the travel route **63** (step **S4**). If an unworked travel route **63** remains (step **S5**: Yes), the combine harvester **1** shifts to the next travel route **63** for autonomous travel. If no unworked travel route **63** remains (step **S5**: No), the autonomous travel is finished.

(69) On the other hand, if it is determined that the travel route **63** to be worked is the outermost route **64** (step **S3**: Yes), in a case where the route adjustment controller **57** further determines that the work width reference mode is set, the preset field information is selected, and the route adjustment control for the outermost route **64** is not yet performed, etc. the route adjustment controller **57** recommends route adjustment control to the operator (step **S6**).

(70) In response to recommendation by operation of the route adjustment control, if the operator operates route adjustment control by means of the route adjustment button **77** or the like (step **S7**: Yes), the route adjustment controller **57** performs route adjustment control of the outermost route **64**, and further adjusts travel routes **63** other than the outermost route **64** so as to be arranged at intervals of work width from the adjusted outermost route **64b** (step **S8**). Then, the combine harvester **1** starts autonomous travel along the adjusted outermost route **64b** (step **S4**), and if an unworked travel route **63b** remains (step **S5**: Yes), the combine harvester **1** shifts to the next travel route **63b** for autonomous travel, and if no unworked travel route **63b** remains (step **S5**: No), the combine harvester **1** finishes autonomous travel.

(71) As described above, according to the present embodiment, the combine harvester **1** is a work vehicle that creates in advance a plurality of travel routes **63** parallel to the preset outline of the field **60** and performs autonomous travel based on the travel route **63**, and is equipped with the control device **40** and the mobile terminal **50**. The control device **40** functions as the autonomous travel controller **45** to control autonomous travel on the basis of the travel route **63**. The mobile terminal **50** is equipped with a terminal control device **51**, and the terminal control device **51** functions as the route adjustment controller **57** that performs route adjustment control to adjust the outermost route **64** when autonomously traveling on the outermost route **64** that is along the outline of the field **60** from among the plurality of travel routes **63**.

(72) In other words, in the present disclosure, an autonomous travel method for a work vehicle such as a combine harvester **1** that prepares in advance a plurality of travel routes **63** parallel to a predetermined outline of a field **60** and performs autonomous travel based on the travel routes **63**, comprising: an autonomous travel control process for controlling autonomous travel based on the plurality of travel routes **63**; and When the autonomous travel of the outermost route **64** that is along the outline of the field **60** from among the plurality of travel routes **63** is performed, the route adjustment control process performs route adjustment control to adjust said outermost route **64**.

(73) This allows the combine harvester **1** to adjust the outermost route **64** regardless of the pre-created travel route **63a** when automatically traveling on the outermost route **64** of the field **60** and to perform appropriate autonomous travel based on the adjusted outermost route **64b**. Therefore, even if the current outline of the field **60**, along which the autonomous travel is to be performed, differs from the preset outline of the field **60**, the autonomous travel can be performed on the appropriate outermost route **64b** that suits the current outline of the field **60**. For example, even if the current outline of the field **60** is narrower than the preset outline of the field **60**, the outermost

route **64b** can be set so that the combine harvester **1** does not deviate outside the current outline of the field **60**. In addition, even if the current outline of the field **60** is wider than the preset outline of the field **60**, the outermost route **64b** can be set so that a gap between the current outline and the preset outline of the field **60**, which becomes an unreaped area **61**, is not left.

(74) For example, the route adjustment controller **57** adjusts as route adjustment control the outermost route **64** so as to be parallel to the outline of the field **60** and pass through the combine harvester **1**'s own position. This allows the outermost travel route **64** to be adjusted to any position desired by the operator, so that the outermost route **64b** can be set so that the combine **1** does not deviate outside the outline of the field **60**. Thus, the combine harvester **1** can perform autonomous travel appropriately regardless of the pre-created travel route **63a**.

(75) Furthermore, for example, when starting autonomous travel on the outermost route **64**, if the route adjustment control operation is performed, the autonomous travel controller **45** performs route adjustment control and then shifts to autonomous travel, while if the route adjustment control operation is not performed, the autonomous travel controller **45** does not shift to autonomous travel. This allows the route adjustment control of the outermost route **64** to be performed in response to any operation by the operator, and if no operation is performed by the operator, the route adjustment control of the outermost route **64** is not performed, so that the combine harvester **1** can be more reliably prevented from deviating outside the outline of the field **60** and thus perform autonomous travel appropriately.

(76) Specifically, the terminal control device **51** of the mobile terminal **50** functions as a route mode setting unit that sets, as the route mode of the travel route **63** for performing autonomous travel, one of the modes which include: a work width reference mode in which a plurality of travel routes **63** are created so as to be parallel to the outline of the field **60** and arranged at intervals of the work width of the combine harvester **1** from the outline of the field **60**; and a vehicle's own position reference mode in which travel routes **63** are created so as to be parallel to the outline of the field **60** and pass through the combine harvester **1**'s own position. When the work width reference mode is set, the route adjustment controller **57** adjusts as route adjustment control the outermost route **64** so as to be parallel to the outline of the field **60** and pass through the combine harvester **1**'s own position, as well as sets a plurality of travel routes **63** at intervals of the work width of the combine harvester **1** from the adjusted outermost route **64**. This allows the outermost route **64b** to be adjusted to any position desired by the operator, even if the work width reference mode is set, and the outermost route **64b** can be set so that the combine harvester **1** does not deviate outside the outline of the field **60**. Since the other travel routes **63** are also adjusted to suit the adjusted outermost route **64b**, autonomous travel can be appropriately performed without resetting the reference line or recreating the plurality of travel routes **63**.

(77) The terminal control device **51** of the mobile terminal **50** functions as the alarm notification unit **59** that determines whether or not the distance from the combine harvester **1** to each outline side **60a** constituting the outline of the field **60** in the travel direction of the combine harvester **1** is equal to or less than a predetermined distance threshold and issues an alarm when the distance is equal to or less than the distance threshold. When autonomous travel is performed on the outermost route **64**, the alarm notification unit **59** excludes the outline side **60a**, which is parallel to and closest to the outermost route **64**, from the target to be alarmed. This allows autonomous travel on the outermost route **64** to be continued without issuing an alarm, even when the outermost route **64** is adjusted making an angle with respect to the preset outline of the field **60**.

(78) When the route adjustment controller **57** adjusts the pre-created outermost route **64a** by the route adjustment control, it updates the set outline of the field **60** based on the adjusted outermost route **64b**. This allows the set outline of the field **60** to be updated to suit the field **60** in which the current autonomous travel is performed, and it is possible to use the updated outline effectively for subsequent autonomous travel.

(79) In the embodiment described above, it is described as an example that the route adjustment

controller **57** of the combine harvester **1** performs route adjustment control when the route adjustment control operation is performed for the recommendation operation of the route adjustment control, when the route adjustment button **77** for route adjustment control is operated on the work screen **70**, or when the start operation of autonomous travel, such as the travel start button **72**, is performed on the work screen **70**. However, the present disclosure is not limited to this example.

(80) For example, in another embodiment, the route adjustment controller **57** may determine orientation of the combine harvester **1** with respect to the outermost route **64** based on the combine harvester **1**'s own position, a travel direction, field information, and the travel route **63** before autonomous travel on the outermost route **64** is started, and perform route adjustment control according to the determination result.

(81) The reaping part **3** of the combine harvester **1** has different lengths from the center of the machine body to both ends in the work width direction (machine width direction). Therefore, for example, as shown in FIG. **3**, when the outermost route **64** is created in advance by the travel route creation unit **56** so that a shorter one end of the reaping part **3** is along the outline of the field **60**, if the combine harvester **1** is placed on the outermost route **64** with orientation that the longer other end of the reaping part **3** is along the outline of the field **60**, the longer other end of the reaping part **3** deviates outside the outline of the field **60**. Alternatively, when the outermost route **64** is created in advance by the travel route creation unit **56** so that the longer other end of the reaping part **3** is along the outline of the field **60**, if the combine harvester **1** is placed on the outermost route **64** with orientation that the shorter one end of the reaping part **3** is along the outline of the field **60**, one end of the reaping part **3** does not reach the outline of the field **60** and thus the unreaped area **61** is left. In contrast, when the route adjustment controller **57** determines, for example, that the orientation of the combine harvester **1** with respect to the outermost route **64** is opposite to the orientation assumed when the outermost route **64** is created, the route adjustment controller **57** performs route adjustment control to adjust the outermost route **64** so as to suit the outline of the field **60** regardless of orientation of the combine harvester **1**.

(82) The route adjustment controller **57** may perform route adjustment control in response to operation of the route adjustment button **77** or operation of the route adjustment control for the recommendation operation of the route adjustment control, as well as according to the determination result of the orientation of the combine harvester **1** with respect to the outermost route **64**.

(83) As described above, according to the other embodiment, the route adjustment controller **57** performs route adjustment control when autonomous travel in a direction opposite to the travel direction set for the outermost route **64** is performed.

(84) Specifically, for autonomous travel of the combine harvester **1** equipped with the reaping part **3**, which is a work machine having different lengths from the center of the machine body to both ends, when the outermost route **64** is created in advance so that one end of the reaping part **3** is along the outline of the field **60**, and when the combine harvester **1** performs autonomous travel on the outermost route **64** so that one end of the reaping part **3** is along the outline of the field **60** (i.e., the orientation of the combine harvester **1** is opposite to the orientation assumed when the outermost route **64** is created), the route adjustment controller **57** performs route adjustment control. When the outermost route **64** is created in advance by setting the travel direction so that one end of the reaping part **3** is along the outline of the field **60**, and when autonomous travel in a direction opposite to the travel direction set for the outermost route **64** is performed, the route adjustment controller **57** may perform the route adjustment control.

(85) This makes it possible to perform autonomous travel on the appropriate outermost route **64** that suits the outline of the field **60**, even when autonomous travel in a direction opposite to the travel direction assumed in advance for the outermost route **64** is performed. For example, even if the combine **1** is placed on the outermost route **64** with orientation so that the longer other end of

the reaping part **3** is along the outline of the field **60** when the outermost travel route **64** is created in advance so that the shorter one end of the reaping part **3** is along the outline of the field **60**, it is possible to set the outermost route **64** such that the other end of the reaping part **3** does not deviate outside the outline of the field **60** by performing the route adjustment control. Even if the combine **1** is placed on the outermost route **64** with orientation so that the shorter end of the reaping part **3** is along the outline of the field **60** when the outermost travel route **64** is created in advance so that the longer other end of the reaping part **3** is along the outline of the field **60**, it is possible to set the outermost route **64** such that the unreaped area **61** is not left in the gap between one end of the reaping part **3** and the outline of the field **60**.

(86) Alternatively, in another embodiment, before autonomous travel on the outermost route **64** is started, the route adjustment controller **57** may determine the positional relationship between the reaping part **3** of the combine harvester **1** and the outline of the field **60** based on the combine harvester **1**'s own position, the travel direction of the combine harvester **1**, the field information, and the travel route **63**, and the route adjustment control, and perform the route adjustment control according to the determination result. For example, when the route adjustment controller **57** calculates the position information of one end of the reaping part **3** and determines that the reaping part **3** is located outside the outline of the field **60**, it determines that the reaping part **3** deviates outside the outline of the field **60** and performs route adjustment control.

(87) The route adjustment controller **57** may perform route adjustment control in response to operation of the route adjustment button **77** or operation of the route adjustment control for the recommendation operation of the route adjustment control, as well as according to the determination result of the positional relationship between the reaping part **3** of the combine harvester **1** and the outline of the field **60**.

(88) As described above, according to the other embodiment, when one end of the reaping part **3** equipped with the combine harvester **1** is located outside the outline of the field **60** in the machine width direction, the route adjustment controller **57** performs route adjustment control.

(89) This allows the outermost route **64** to be set preventing one end of the reaping part **3** from deviating outside the outline of the field **60**.

(90) In the above embodiment, it is described as an example that the route adjustment controller **57** adjusts as route adjustment control the outermost route **64** so as to be parallel to the outline side **60a** of the field **60** and pass through the combine harvester **1**'s own position, but the present disclosure is not limited to this example. For example, in another embodiment, the route adjustment controller **57** may adjust as route adjustment control the outermost route **64** so as to get close to the outline side **60a** of the field **60** or separate away from the outline side **60a** of the field **60** by a predetermined shift width.

(91) Alternatively, in another embodiment, the route adjustment controller **57** may switch as route adjustment control the route mode from the work width reference mode to another mode and recreate the travel route **63** for the outermost route **64** by the travel route creation unit **56**. For example, the route adjustment controller **57** switches as route adjustment control the route mode from the work width reference mode to the vehicle's own position reference mode, and the travel route creation unit **56** recreates a single travel route **63** for the outermost route **64**, which is parallel to the outline of the field **60** and passes through the combine harvester **1**'s own position.

(92) Before switching the route mode from the work width reference mode to another mode, the route adjustment controller **57** may notify the operator of the switching of the route mode by means of a screen display by the display unit **54** or an audio output, or it may recommend operating the switching of the route mode to the operator.

(93) As described above, according to another embodiment, the combine harvester **1** sets, as the route mode to set the travel route **63** for performing autonomous travel, one of the modes which include: a work width reference mode in which a plurality of travel routes **63** are set so as to be parallel to the outline of the field **60** and arranged at intervals of the work width of the combine

harvester **1** from the outline of the field **60**; and a vehicle's own position reference mode in which travel routes **63** are set so as to be parallel to the outline of the field **60** and pass through the combine harvester **1**'s own position. When the work width reference mode is set, the route adjustment controller **57** switches as route adjustment control the route mode from the work width reference mode to the vehicle's own position reference mode.

(94) This allows route adjustment control to recreate and adjust the travel route **63** in the appropriate route mode for the outermost route **64**, thereby performing appropriate autonomous travel based on the adjusted outermost route **64**.

(95) In the embodiment described above, it is described as an example that the combine harvester **1** sets either one of the work width reference mode or the vehicle's own position reference mode as a route mode, but the present disclosure is not limited to this example. For example, the combine harvester **1** can set a third route mode other than the work width reference mode and the vehicle's own position reference mode as a route mode, and the travel route creation unit **56** may, when the third route mode is set, create the travel route **63** of the outermost route **64** so as to be parallel to the outline of the field **60** and pass through the combine harvester **1**'s own position, as well as create a plurality of travel routes **63** parallel to the outline of the field **60** and at intervals of the work width of the combine harvester **1** from the created outermost route **64**. In other words, in the third route mode, as shown by the solid or dashed lines in FIG. 7, the outermost route **64** is created in the vehicle's own position reference mode, and in the area inside the outermost route **64**, as shown by the single-dotted line in FIG. 7, a plurality of travel routes **63** are created in the work width reference mode in which the outermost route **64** is set as the reference line.

(96) In another embodiment described above, when the route adjustment controller **57** switches the route mode from the work width reference mode to another mode as route adjustment control, it may switch the route mode to the third route mode and recreate the travel route **63** for the outermost route **64** by the travel route creation unit **56**.

(97) In the embodiment mentioned above, it is described as an example that when the work width reference mode is set as the route mode, as shown in FIG. 5, the display control unit **58** displays a plurality of travel routes **63** in the map column **71**, but the present disclosure is not limited to this example. As another example, the display control unit **58** may hide only the outermost route **64** of the plurality of travel routes **63**. For example, a headland can be formed along the outline side **60a** which is the reference line of the travel route **83** by performing autonomous travel (autonomous straight travel) of the combine harvester **1** based on the outermost route **64**, but the operator may form the headland manually by performing manual travel of the combine harvester **1** along the outline side **60a**. Thus, the display control unit **58** may hide only the outermost route **64** in response to any operation by the operator, or when the manual travel mode is set, the display control unit **58** may hide only the outermost route **64** or the plurality of travel routes **63** including the outermost route **64**. After a manual travel along the outline side **60a** is performed, the travel route creation unit **56** may create a plurality of travel routes **63** by using the route of the manual travel as a reference line.

(98) In the embodiment mentioned above, it is described as an example that a combine harvester **1** is configured as a normal combine harvester, but the present disclosure is not limited to this example. The combine harvester **1** may also be configured as a head-feeding type combine harvester, and the present disclosure is preferable for a combine harvester **1** equipped with the reaping part **3** having different lengths from the center of the machine body to both ends. In the above embodiments, an example in which the work vehicle is composed of the combine harvester **1** is described, but the present disclosure is not limited to this example. For example, the work vehicle of the present disclosure may be composed of other agricultural machinery, or other work vehicles other than agricultural machinery, and the present disclosure is preferable for the work vehicle equipped with work machine having different lengths from the center of the machine body to both ends.

(99) Note that the present disclosure can be appropriately changed unless contrary to gist or spirit of the present disclosure that can be read out from the claims and the whole specification, and an autonomous travel method, a working vehicle, and an autonomous travel system accompanied by such a change are also included in the spirit of the present disclosure.

APPENDICES

(100) Appended below is a summary of the present disclosure extracted from the embodiments described above. It should be noted that respective components and processing functions described in the appendices below can be selected and combined as appropriate.

Appendix 1

(101) An autonomous travel method for a work vehicle that pre-creates a plurality of travel routes parallel to a preset outline of a field and performs autonomous travel based on the travel routes, the method comprising the steps of: performing autonomous travel control to control the autonomous travel based on the travel routes; and performing route adjustment control to adjust an outermost route when the autonomous travel is performed on the outermost route along the outline of the field among the plurality of travel routes.

Appendix 2

(102) The autonomous travel method according to appendix 1, wherein the step of performing route adjustment control includes, as the route adjustment control, adjusting the outermost route so that the outermost route is parallel to the outline of the field and passes through the work vehicle's own position.

Appendix 3

(103) The autonomous travel method according to appendix 1 or 2, wherein when the autonomous travel is started on the outermost route, the step of performing autonomous travel control includes, if operation of the route adjustment control is performed, enabling shift to the autonomous travel after the route adjustment control is performed, and if operation of the route adjustment control is not performed, disabling shift to the autonomous travel.

Appendix 4

(104) The autonomous travel method according to appendix 1 or 2, wherein the step of performing route adjustment control is performed when the autonomous travel is performed in a direction opposite to a travel direction set for the outermost route.

Appendix 5

(105) The autonomous travel method according to appendix 4, wherein the step of performing route adjustment control is performed, when the outermost route is pre-created so that one end of the work machine is along the outline of the field and when the work machine performs autonomous travel on the outermost route so that the other end of the work machine is along the outline of the field, in order to perform autonomous travel of the work vehicle equipped with a work machine having different lengths from a center of a machine body to both ends in a machine width direction.

Appendix 6

(106) The autonomous travel method according to appendix 1 or 2, wherein the step of performing route adjustment control is performed when one end of a work machine mounted on the work vehicle is positioned outside the outline of the field in a machine width direction.

Appendix 7

(107) The autonomous travel method according to any one of appendices 1 to 3 further comprising the step of setting a route mode for setting, as a route mode of the travel route on which the autonomous travel is performed, either a work width reference mode in which the plurality of travel routes are set so that the plurality of travel routes are parallel to the outline of the field and arranged at intervals of a work width of the work vehicle from the outline of the field, or a vehicle's own position reference mode in which the travel routes are set so that the travel routes are parallel to the outline of the field and pass through the work vehicle's own position, wherein the step of

performing route adjustment control includes, as the route adjustment control, when the work width reference mode is set, adjusting the outermost route so that the outermost route is parallel to the outline of the field and passes through the work vehicle's own position, and creating the plurality of travel routes at intervals of the work width of the work vehicle from the adjusted outermost route.

Appendix 8

(108) The autonomous travel method according to any one of appendices 1 to 3 further comprising the step of setting a route mode for setting, as a route mode for setting the travel route on which the autonomous travel is performed, either a work width reference mode in which the plurality of travel routes are set so that the plurality of travel routes are parallel to the outline of the field and arranged at intervals of a work width of the work vehicle from the outline of the field, or a vehicle's own position reference mode in which the travel routes are set so that the travel routes are parallel to the outline of the field and pass through the work vehicle's own position, wherein the step of performing route adjustment control includes, as the route adjustment control, when the work width reference mode is set, switching the route mode from the work width reference mode to the vehicle's own position reference mode.

Appendix 9

(109) The autonomous travel method according to any one of appendices 1 to 8 further comprising the step of determining whether or not a distance from the work vehicle to each of outline sides forming the outline of the field in an advancing direction of the work vehicle is equal to or less than a predetermined distance threshold, and issuing an alarm when the distance is equal to or less than the distance threshold, wherein the step of issuing an alarm includes excluding an outline side that is parallel to the outermost route and nearest to the outermost route from a target to be alarmed when the autonomous travel is performed on the outermost route.

Appendix 10

(110) The autonomous travel method according to any one of appendices 1 to 9, wherein the step of performing route adjustment control includes updating the preset outline of the field based on the adjusted outermost route when the pre-created outermost route is adjusted by the route adjustment control.

Appendix 11

(111) A work vehicle for pre-creating a plurality of travel routes parallel to a preset outline of a field and performing autonomous travel based on the travel routes, comprising: an autonomous travel controller to control the autonomous travel based on the travel routes; and a route adjustment controller to perform route adjustment control for adjusting an outermost route when the autonomous travel is performed on the outermost route along the outline of the field among the plurality of travel routes.

Appendix 12

(112) The work vehicle according to appendix 11, wherein the route adjustment controller adjusts, as the route adjustment control, the outermost route so that the outermost route is parallel to the outline of the field and passes through the work vehicle's own position.

Appendix 13

(113) The work vehicle according to appendix 11 or 12, wherein when the autonomous travel is started on the outermost route, the autonomous travel controller, if operation of the route adjustment control is performed, enables shift to the autonomous travel after the route adjustment control is performed, and if operation of the route adjustment control is not performed, disables shift to the autonomous travel.

Appendix 14

(114) The work vehicle according to appendix 11 or 12, wherein the route adjustment controller performs the route adjustment control when the autonomous travel is performed in a direction opposite to a travel direction set for the outermost route.

Appendix 15

(115) The work vehicle according to appendix 14, wherein the route adjustment controller performs the route adjustment control, when the outermost route is pre-created so that one end of the work machine is along the outline of the field and when the work machine performs autonomous travel on the outermost route so that the other end of the work machine is along the outline of the field, in order to perform autonomous travel of the work vehicle equipped with a work machine having different lengths from a center of a machine body to both ends in a machine width direction.

Appendix 16

(116) The work vehicle according to appendix 11 or 12, wherein the route adjustment controller performs the route adjustment control when one end of a work machine mounted on the work vehicle is positioned outside the outline of the field in a machine width direction.

Appendix 17

(117) The work vehicle according to any one of appendices 11 to 13 further comprising a route mode setting unit sets, as a route mode of the travel route on which the autonomous travel is performed, either a work width reference mode in which the plurality of travel routes are set so that the plurality of travel routes are parallel to the outline of the field and arranged at intervals of a work width of the work vehicle from the outline of the field, or a vehicle's own position reference mode in which the travel routes are set so that the travel routes are parallel to the outline of the field and pass through the work vehicle's own position, wherein the route adjustment controller adjusts, as the route adjustment control, when the work width reference mode is set, the outermost route so that the outermost route is parallel to the outline of the field and passes through the work vehicle's own position, and creates the plurality of travel routes at intervals of the work width of the work vehicle from the adjusted outermost route.

Appendix 18

(118) The work vehicle according to any one of appendices 11 to 13 further comprising a route mode setting unit sets, as a route mode for setting the travel route on which the autonomous travel is performed, either a work width reference mode in which the plurality of travel routes are set so that the plurality of travel routes are parallel to the outline of the field and arranged at intervals of a work width of the work vehicle from the outline of the field, or a vehicle's own position reference mode in which the travel routes are set so that the travel routes are parallel to the outline of the field and pass through the work vehicle's own position, wherein the route adjustment controller switches, as the route adjustment control, when the work width reference mode is set, the route mode from the work width reference mode to the vehicle's own position reference mode.

Appendix 19

(119) The work vehicle according to any one of appendices 11 to 18 further comprising an alarm notification unit to determine whether or not a distance from the work vehicle to each of outline sides forming the outline of the field in an advancing direction of the work vehicle is equal to or less than a predetermined distance threshold, and issue an alarm when the distance is equal to or less than the distance threshold, wherein the alarm notification unit excludes an outline side that is parallel to the outermost route and nearest to the outermost route from a target to be alarmed when the autonomous travel is performed on the outermost route.

Appendix 20

(120) The work vehicle according to any one of appendices 11 to 19, wherein the route adjustment controller updates the preset outline of the field based on the adjusted outermost route when the pre-created outermost route is adjusted by the route adjustment control.

Appendix 21

(121) An autonomous travel system of a work vehicle for pre-creating a plurality of travel routes parallel to a preset outline of a field and performing autonomous travel based on the travel routes, comprising: an autonomous travel controller to control the autonomous travel based on the travel routes; and a route adjustment controller to perform route adjustment control for adjusting an outermost route when the autonomous travel is performed on the outermost route along the outline

of the field among the plurality of travel routes.

Appendix 22

(122) The autonomous travel system according to appendix 21, wherein the route adjustment controller adjusts, as the route adjustment control, the outermost route so that the outermost route is parallel to the outline of the field and passes through the work vehicle's own position.

Appendix 23

(123) The autonomous travel system according to appendix 21 or 22, wherein when the autonomous travel is started on the outermost route, the autonomous travel controller enables, if operation of the route adjustment control is performed, shift to the autonomous travel after the route adjustment control is performed, and the autonomous travel controller disables, if operation of the route adjustment control is not performed, shift to the autonomous travel.

Appendix 24

(124) The autonomous travel system according to appendix 21 or 22, wherein the route adjustment controller performs the route adjustment control when the autonomous travel is performed in a direction opposite to a travel direction set for the outermost route.

Appendix 25

(125) The autonomous travel system according to appendix 24, wherein the route adjustment controller performs the route adjustment control when the outermost route is pre-created so that one end of the work machine is along the outline of the field and when the work machine performs autonomous travel on the outermost route so that the other end of the work machine is along the outline of the field, in order to perform autonomous travel of the work vehicle equipped with a work machine having different lengths from a center of a machine body to both ends in a machine width direction.

Appendix 26

(126) The autonomous travel system according to appendix 21 or 22, wherein the route adjustment controller performs the route adjustment control when one end of a work machine mounted on the work vehicle is positioned outside the outline of the field in a machine width direction.

Appendix 27

(127) The autonomous travel system according to any one of appendices 21 to 23 further comprising a route mode setting unit sets, as a route mode of the travel route on which the autonomous travel is performed, either a work width reference mode in which the plurality of travel routes are set so that the plurality of travel routes are parallel to the outline of the field and arranged at intervals of a work width of the work vehicle from the outline of the field, or a vehicle's own position reference mode in which the travel routes are set so that the travel routes are parallel to the outline of the field and pass through the work vehicle's own position, wherein the route adjustment controller adjusts, as the route adjustment control, when the work width reference mode is set, the outermost route so that the outermost route is parallel to the outline of the field and passes through the work vehicle's own position, and creates the plurality of travel routes at intervals of the work width of the work vehicle from the adjusted outermost route.

Appendix 28

(128) The autonomous travel system according to any one of appendices 21 to 23 further comprising a route mode setting unit sets, as a route mode for setting the travel route on which the autonomous travel is performed, either a work width reference mode in which the plurality of travel routes are set so that the plurality of travel routes are parallel to the outline of the field and arranged at intervals of a work width of the work vehicle from the outline of the field, or a vehicle's own position reference mode in which the travel routes are set so that the travel routes are parallel to the outline of the field and pass through the work vehicle's own position, wherein the route adjustment controller switches, as the route adjustment control, when the work width reference mode is set, the route mode from the work width reference mode to the vehicle's own position reference mode.

Appendix 29

(129) The autonomous travel system according to any one of appendices 21 to 28 further comprising an alarm notification unit to determine whether or not a distance from the work vehicle to each of outline sides forming the outline of the field in an advancing direction of the work vehicle is equal to or less than a predetermined distance threshold, and issue an alarm when the distance is equal to or less than the distance threshold, wherein the alarm notification unit excludes an outline side that is parallel to the outermost route and nearest to the outermost route from a target to be alarmed when the autonomous travel is performed on the outermost route.

Appendix 30

(130) The autonomous travel system according to any one of appendices 21 to 29, wherein the route adjustment controller updates the preset outline of the field based on the adjusted outermost route when the pre-created outermost route is adjusted by the route adjustment control.

REFERENCE SIGNS LIST

(131) **1** Combine harvester (work vehicle) **3** Reaping part **40** Control device **45** Autonomous travel controller **50** Mobile terminal **51** Terminal control device **56** Travel route creation unit **57** Route adjustment controller **59** Alarm notification unit **60** Field **63** Travel route

Claims

1. An autonomous travel method for a work vehicle that pre-creates a plurality of travel routes parallel to a preset outline of a field and performs autonomous travel based on the travel routes, the method comprising the steps of: performing autonomous travel control to control the autonomous travel based on the travel routes; and performing route adjustment control to adjust an outermost route that is along the outline of the field from among the plurality of travel routes, when the autonomous travel is performed on the outermost route, wherein when the autonomous travel is started on the outermost route, the autonomous travel control includes, if an operation for the route adjustment control is performed, enabling shift to the autonomous travel after the route adjustment control is performed, and if the operation for the route adjustment control is not performed, disabling shift to the autonomous travel.
2. The autonomous travel method according to claim 1, wherein the route adjustment control includes, as the route adjustment control, adjusting the outermost route so that the outermost route is parallel to the outline of the field and passes through the work vehicle's own position.
3. The autonomous travel method according to claim 1, wherein the route adjustment control is performed when the autonomous travel is performed in a direction opposite to a travel direction set for the outermost route.
4. The autonomous travel method according to claim 1, wherein the route adjustment control is performed when the outermost route is pre-created so that one end of a work machine having different lengths from a center of a machine body to both ends in a machine width direction is along the outline of the field and when the work machine performs the autonomous travel on the outermost route so that the other end of the work machine is along the outline of the field in order to perform the autonomous travel of the work vehicle equipped with the work machine.
5. The autonomous travel method according to claim 1, wherein the route adjustment control is performed when one end of a work machine mounted on the work vehicle is positioned outside the outline of the field in a machine width direction.
6. The autonomous travel method according to claim 1 further comprising route mode setting for setting, as a route mode of the travel route on which the autonomous travel is performed, either a work width reference mode in which the plurality of travel routes are set so that the plurality of travel routes are parallel to the outline of the field and arranged at intervals of a work width of the work vehicle from the outline of the field, or a vehicle's own position reference mode in which the travel routes are set so that the travel routes are parallel to the outline of the field and pass through the work vehicle's own position, wherein the route adjustment control includes, as the route

- adjustment control, adjusting the outermost route so that the outermost route is parallel to the outline of the field and passes through the work vehicle's own position, and creating the plurality of travel routes at intervals of the work width of the work vehicle from the adjusted outermost route, when the work width reference mode is set.
7. The autonomous travel method according to claim 1 further comprising route mode setting for setting, as a route mode for setting the travel route on which the autonomous travel is performed, either a work width reference mode in which the plurality of travel routes are set so that the plurality of travel routes are parallel to the outline of the field and arranged at intervals of a work width of the work vehicle from the outline of the field, or a vehicle's own position reference mode in which the travel routes are set so that the travel routes are parallel to the outline of the field and pass through the work vehicle's own position, wherein the route adjustment control includes, as the route adjustment control, switching the route mode from the work width reference mode to the vehicle's own position reference mode, when the work width reference mode is set.
8. The autonomous travel method according to claim 1 further comprising alarm issuing of determining whether or not a distance from the work vehicle to each of outline sides forming the outline of the field in an advancing direction of the work vehicle is equal to less than a predetermined distance threshold, and issuing an alarm when the distance is equal to or less than the distance threshold, wherein the alarm issuing includes excluding an outline side that is parallel to the outermost route and nearest to the outermost route from a target to be alarmed when the autonomous travel is performed on the outermost route.
9. The autonomous travel method according to claim 1, wherein the route adjustment control includes updating the preset outline of the field based on the adjusted outermost route when the pre-created outermost route is adjusted by the route adjustment control.
10. A work vehicle for pre-creating a plurality of travel routes parallel to a preset outline of a field and performing autonomous travel based on the travel routes, comprising: an autonomous travel controller to control the autonomous travel based on the travel routes; and a route adjustment controller to perform route adjustment control for adjusting an outermost route that is along the outline of the field from among the plurality of travel routes, when the autonomous travel is performed on the outermost route, wherein when the autonomous travel is started on the outermost route, the autonomous travel controller includes, if an operation for the route adjustment controller is performed, enabling shift to the autonomous travel after the route adjustment controller is performed, and if the operation for the route adjustment controller is not performed, disabling shift to the autonomous travel.
11. An autonomous travel system of a work vehicle for pre-creating a plurality of travel routes parallel to a preset outline of a field and performing autonomous travel based on the travel routes, comprising: an autonomous travel controller to control the autonomous travel based on the travel routes; and a route adjustment controller to perform route adjustment control for adjusting an outermost route that is along the outline of the field from among the plurality of travel routes, when the autonomous travel is performed on the outermost route, wherein when the autonomous travel is started on the outermost route, the autonomous travel controller includes, if an operation for the route adjustment controller is performed, enabling shift to the autonomous travel after the route adjustment controller is performed, and if the operation for the route adjustment controller is not performed, disabling shift to the autonomous travel.
-