

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent	12394450
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Mariani; Marcello et al.

---

### Integrated assemblies having shield lines between neighboring transistor active regions

---

#### Abstract

Some embodiments include an integrated assembly having digit lines supported by a base and extending along a first direction. A shield-connection-line is supported by the base and extends along the first direction. Transistor active regions are over the digit lines. Each of the active regions includes a channel region between an upper source/drain region and a lower source/drain region. The lower source/drain regions are coupled with the digit lines. Capacitors are coupled with the upper source/drain regions. Wordlines extend along a second direction which crosses the first direction. The wordlines include gate regions adjacent the channel regions. Shield lines extend along the second direction. The shield lines are above the digit lines and are coupled with the shield-connection-line.

---

**Inventors:** Mariani; Marcello (Milan, IT), Rigano; Antonino (Cernusco sul Naviglio, IT)

**Applicant:** Micron Technology, Inc. (Boise, ID)

**Family ID:** 1000008762464

**Assignee:** Micron Technology, Inc. (Boise, ID)

**Appl. No.:** 18/114692

**Filed:** February 27, 2023

#### Prior Publication Data

Document Identifier	Publication Date
US 20230206959 A1	Jun. 29, 2023

#### Related U.S. Application Data

continuation parent-doc US 16667289 20191029 US 11636882 child-doc US 18114692

---

## Publication Classification

**Int. Cl.:** G11C5/00 (20060101); G11C5/02 (20060101); G11C5/06 (20060101); H10B12/00 (20230101)

**U.S. Cl.:**

**CPC** G11C5/005 (20130101); G11C5/025 (20130101); G11C5/063 (20130101); H10B12/315 (20230201);

## Field of Classification Search

**CPC:** G11C (5/005); G11C (5/025); G11C (5/063); G11C (7/02); H10B (12/315); H10B (12/053); H10B (12/482); H10B (12/30)

---

## References Cited

### U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6872999	12/2004	Uetake	N/A	N/A
8368137	12/2012	Mokhlesi et al.	N/A	N/A
9245976	12/2015	Cho et al.	N/A	N/A
9773728	12/2016	Juengling	N/A	N/A
9773888	12/2016	Pulugurtha et al.	N/A	N/A
11636882	12/2022	Mariani	257/296	H10B 12/315
2003/0072172	12/2002	Somasekhar et al.	N/A	N/A
2009/0003025	12/2008	Mokhlesi et al.	N/A	N/A
2011/0303974	12/2010	Kim et al.	N/A	N/A
2012/0106281	12/2011	Kim et al.	N/A	N/A
2013/0320433	12/2012	Cho et al.	N/A	N/A
2018/0182762	12/2017	Juengling	N/A	N/A
2018/0331029	12/2017	Sukekawa	N/A	N/A
2019/0206869	12/2018	Kim	N/A	H10B 12/20
2019/0295941	12/2018	Ramaswamy	N/A	N/A

### FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2004-040042	12/2003	JP	N/A
10-2004-0059014	12/2003	KR	N/A
10-2013-0134813	12/2012	KR	N/A

### OTHER PUBLICATIONS

EP EP 20881766 Supplemental SR, Nov. 11, 2022, Micron Technology, Inc. cited by applicant  
WO PCT/US2020/056173 IPRP, May 3, 2022, Micron Technology, Inc. cited by applicant  
WO PCT/US2020/056173 Search Rept., Feb. 2, 2021, Micron Technology, Inc. cited by applicant  
WO PCT/US2020/056173 Writ. Opin., Feb. 2, 2021, Micron Technology, Inc. cited by applicant  
TW TW 109137376 SR Trans., Jul. 26, 2021, Micron Technology, Inc. cited by applicant

---

Primary Examiner: Gauthier; Steven B

Assistant Examiner: King; Sun Mi Kim

Attorney, Agent or Firm: Wells St. John P.S.

---

## Background/Summary

RELATED PATENT DATA (1) This patent resulted from a continuation of U.S. patent application Ser. No. 16/667,289 filed Oct. 29, 2019, which is hereby incorporated by reference herein.

### TECHNICAL FIELD

(1) Integrated assemblies. Integrated assemblies having shield lines between neighboring transistor active regions.

### BACKGROUND

(2) Memory is one type of integrated circuitry, and is used in computer systems for storing data. An example memory is DRAM (dynamic random-access memory). DRAM cells may each comprise a transistor in combination with a capacitor. The DRAM cells may be arranged in an array; with wordlines extending along rows of the array, and with digit lines extending along columns of the array. The wordlines may be coupled with the transistors of the memory cells. Each memory cell may be uniquely addressed through a combination of one of the wordlines with one of the digit lines.

(3) A problem which may be encountered in conventional memory architectures is that crosstalk (disturbance) may occur between adjacent memory cells, leading to loss of data. The crosstalk becomes increasing problematic as memory architectures are scaled to increasing levels of integration. It would be desirable to alleviate or prevent such undesired crosstalk.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a diagrammatic top-down view a region of an example integrated assembly.

(2) FIG. 2 is a diagrammatic cross-sectional side view along the line 2-2 of FIG. 1.

(3) FIG. 2A is a diagrammatic cross-sectional side view similar to that of FIG. 2, and showing additional materials.

(4) FIG. 3 is a diagrammatic cross-sectional side view along the line 3-3 of FIG. 1.

(5) FIG. 4 is a diagrammatic cross-sectional side view along the line 4-4 of FIG. 1.

(6) FIGS. 5-7 are diagrammatic cross-sectional side views of an example integrated assembly at example sequential process stages of an example method.

(7) FIGS. 8-13 are diagrammatic schematic views of example memory devices.

### DETAILED DESCRIPTION OF THE ILLUSTRATED EMBODIMENTS

(8) Some embodiments include memory devices having transistor-active-region-pillars distributed in a matrix comprising rows and columns. Digit lines are under the transistor-active-region-pillars and extend along the columns. At least one shield-connection-line extends parallel to the digit lines and is laterally offset from the digit lines. Wordlines are over the digit lines and said at least one shield-connection-line, and extend along the rows. Shield lines are over the digit lines and extend along the same direction as the wordlines. The shield lines are coupled with said at least one shield-connection-line. Each of the transistor-active-region-pillars has one side adjacent a wordline, and has an opposing side adjacent a shield line. Example embodiments are described with reference to FIGS. 1-13.

(9) Referring to FIGS. 1-4, an example integrated assembly (construction, architecture) **10** includes pillars **12** arranged in a matrix. The matrix includes rows **14** and columns **16**. The rows extend along an illustrated x-axis direction, and the columns extend along an illustrated y-axis direction. The pillars **12** extend vertically along an illustrated z-axis direction.

(10) The vertically-extending pillars **12** comprise semiconductor material **18**. The semiconductor material **18** may comprise any suitable composition(s); and in some embodiments may comprise, consist essentially of, or consist of one or more of silicon, germanium, III/V semiconductor material (e.g., gallium phosphide), semiconductor oxide, etc.; with the term III/V semiconductor material referring to semiconductor materials comprising elements selected from groups III and V of the periodic table (with groups III and V being old nomenclature, and now being referred to as groups **13** and **15**). In some embodiments, the semiconductor material **18** may comprise, consist essentially of, or consist of silicon.

(11) Each of the semiconductor pillars **12** comprises a conductively-doped lower source/drain region **20**, a conductively-doped upper source/drain region **22**, and a channel region **24** between the source/drain regions **20** and **22**. Dashed lines **21** are provided to diagrammatically illustrate approximate boundaries between the lower source/drain regions **20** and the channel regions **24**, and dashed lines **23** are provided to illustrate approximate boundaries between the upper source/drain regions **22** and the channel regions **24**.

(12) The source/drain regions **20** and **22** may be doped with any suitable dopant to any suitable concentration. For instance, the source/drain regions **20** and **22** may be n-type doped regions which are doped with one or both of arsenic and phosphorus to a dopant concentration of at least about  $10^{22}$  atoms/cm<sup>3</sup>. Alternatively, the source/drain regions **20** and **22** may be p-type doped regions which are doped with, for example, boron.

(13) The channel regions **24** may comprise a suitable concentration of one or more suitable dopants to achieve a desired threshold voltage. The dopants may include one or more of boron, phosphorus, arsenic, etc., and the dopant concentration may be less than or equal to about  $10^{18}$  atoms/cm<sup>3</sup>.

(14) The regions **20**, **22** and **24** may be transistor active regions, and the pillars **12** may be considered to correspond to transistor-active-region-pillars.

(15) Digit lines (also referred to as bitlines or sense lines) **26** are under the pillars **12** and extend along the y-axis direction. The digit lines are shown in dashed-line view (phantom view) in FIG. 1 to indicate that they are under other materials.

(16) Wordlines (also referred to as access lines) **28** are adjacent the pillars **12** and extend along the x-axis direction.

(17) In some embodiments, one of the x-axis and y-axis directions may be referred to as a first direction, and the other may be referred to as a second direction. Accordingly, either the wordlines or the digit lines may be considered to extend along a first direction, and the other of the wordlines or the digit lines may be considered to extend along a second direction which crosses the first direction. In the illustrated embodiment, the second direction is orthogonal to the first direction (i.e., the x-axis and y-axis directions are orthogonal to one another). In other embodiments, the wordlines may extend along a direction which crosses the direction of the digit lines, but which is not orthogonal to the direction of the digit lines.

(18) The digit lines **26** comprise conductive digit line material **30**, and the wordlines **28** comprise conductive wordline material **32**. The materials **30** and **32** may comprise any suitable electrically conductive composition(s); such as, for example, one or more of various metals (e.g., titanium, tungsten, cobalt, nickel, platinum, ruthenium, etc.), metal-containing compositions (e.g., metal silicide, metal nitride, metal carbide, etc.), and/or conductively-doped semiconductor materials (e.g., conductively-doped silicon, conductively-doped germanium, etc.). The materials **30** and **32** may comprise a same composition as one another, or may comprise different compositions relative to one another. In some example embodiments, the materials **30** and **32** comprise one or more

metals (e.g., comprise one or more of titanium, tungsten, titanium silicide, titanium nitride, tungsten silicide, tungsten nitride, etc.); and accordingly may be referred to as metal-containing materials.

(19) The wordlines **28** comprise gate regions **34** adjacent the channel regions **24**. In operation, sufficient voltage applied to the gate regions **34** will induce an electric field within associated channel regions **24** which enables current flow through the channel regions to thereby electrically couple the associated source/drain regions **20** and **22** to one another. If the voltage to a gate region is below a threshold level, the current will not flow through the associated channel region, and the associated source/drain regions will not be electrically coupled with one another. The selective control of the coupling/decoupling of the source/drain regions through the level of voltage applied to the gate regions may be referred to as gated coupling of the source/drain regions. The gate regions **34** may be considered to be operatively proximate the associated channel regions **24**, with the term “operatively proximate” meaning that the gate regions are within appropriate proximity of the associated channel regions to induce appropriate electric fields within the associated channel regions to achieve gated coupling of the associated source/drain regions.

(20) Shield lines **36** extend through the matrix of the pillars **12**, with the shield lines extending along the x-axis direction and being above the digit lines **26**. The shield lines **36** comprise conductive material **38**. The conductive material **38** may comprise any suitable electrically conductive composition(s); such as, for example, one or more of various metals (e.g., titanium, tungsten, cobalt, nickel, platinum, ruthenium, etc.), metal-containing compositions (e.g., metal silicide, metal nitride, metal carbide, etc.), and/or conductively-doped semiconductor materials (e.g., conductively-doped silicon, conductively-doped germanium, etc.). In some embodiments, the conductive material **38** may be a metal-containing material.

(21) A shield-connection-line **40** is adjacent the matrix of the pillars **12**, and is electrically coupled with the shield lines **36**. The shield-connection-line **40** is shown in dashed-line (phantom) view in FIG. **1** to indicate that it is under other materials.

(22) The shield-connection-line comprises the same conductive material **30** as the digit lines **26**. In some embodiments, the shield-connection-line **40** may be patterned from a same conductive expanse as the digit lines **26** (as discussed below with reference to FIGS. **5-7**). In the illustrated embodiment, the shield-connection-line **40** comprises a same height,  $H$ , as the digit lines **26** (as shown in FIG. **4**).

(23) In some embodiments, the digit lines **26** and the shield-connection-line **40** may all be considered to be conductive lines which extend along the direction of the y-axis, and which all comprise a common composition as one another and a common height as one another.

(24) The shield lines **36** are electrically coupled with the shield-connection-line **40** at interconnect regions **42**. In the illustrated embodiment, such interconnect regions comprise a conductive material **44** which extends from the shield-connection-line **40** to the shield lines **36**. The conductive material **44** may comprise any suitable electrically conductive composition(s); such as, for example, one or more of various metals (e.g., titanium, tungsten, cobalt, nickel, platinum, ruthenium, etc.), metal-containing compositions (e.g., metal silicide, metal nitride, metal carbide, etc.), and/or conductively-doped semiconductor materials (e.g., conductively-doped silicon, conductively-doped germanium, etc.).

(25) The semiconductor pillars **12** may be incorporated into a memory array (e.g., a DRAM array) **49**. The lower source/drain regions **20** of the semiconductor pillars are electrically coupled with the digit lines **26** (and in the shown embodiment are directly against the digit lines **26**), and the upper source/drain regions **22** of the pillars may be electrically coupled with storage elements **46**. The storage elements **46** are only shown along the cross-sectional side views of FIGS. **2** and **4**, and are not shown along the top-down view of FIG. **1** in order to simplify FIG. **1**.

(26) The storage elements **46** may be any suitable devices having at least two detectable states; and in some embodiments may be, for example, capacitors, resistive-memory devices, conductive-

bridging devices, phase-change-memory (PCM) devices, programmable metallization cells (PMCs), etc. In the illustrated example embodiment, the storage elements **46** are capacitors. Each of the capacitors has one node coupled with an upper source/drain region **22** of an associated semiconductor pillar **12**, and has another node coupled with a reference source **48**. The reference source **48** may be at any suitable voltage; such as, for example, ground, VCC/2, etc.

(27) Each of the storage elements **46** may be considered to be comprised by a memory cell **50** of the memory array **49**. The columns of the memory array are along the columns **16** and comprise the semiconductor pillars **12** coupled with a common digit line **26** (i.e., associated with the common digit line). The rows of the memory array are along the rows **14** and comprise the pillars **12** having channel regions operatively proximate gate regions along a common wordline **28** (i.e., associated with the common wordline). Each of the memory cells **50** is uniquely addressed by one of the digit lines **16** in combination with one of the wordlines **14**. The gate regions **34**, together with the transistor active regions of pillars **12**, may be considered to correspond to access devices (access transistors) associated with the individual memory cells.

(28) As discussed in the Background section, a problem which may be encountered in conventional memory architectures is undesired crosstalk between neighboring devices (e.g., transistor active regions). The embodiment of FIGS. 1-4 advantageously provides the shield lines **36** between memory cells **50** that are neighboring to one another along the columns **16**. Such may alleviate, or even prevent, undesired crosstalk between such memory cells; and accordingly may be a substantial improvement relative to conventional configurations.

(29) In some embodiments, each of the pillars **12** may be considered to have a first side **52** and an opposing second side **54** (shown relative to one of the pillars **12** in the top-down view of FIG. 1, and in the cross-sectional side view of FIG. 2). The first side **52** is proximate an associated one of the wordlines **28**, and the second side **54** is proximate an associated one of the shield lines **36**.

(30) In some embodiments, the semiconductor pillars **12** along a common column **16** may be considered to be spaced from one another by alternating first and second gaps **56** and **58** along the y-axis direction (with the gaps **56** and **58** being labeled in FIG. 2). Two of the wordlines **28** are within each of the first gaps **56**, and one of the shield lines **36** is within each of the second gaps **58**.

(31) In some embodiments, the shield-connection-line **40** may be coupled with a reference-voltage-source **60**. Such reference-voltage-source may be at any suitable voltage; including, for example, ground, VCC/2, etc. The reference-voltage-source may be passive (i.e., maintained at a static voltage during operation of the memory array **49**) or may be active (e.g., modulated between one or more different voltages during operation of the memory array **49**).

(32) In some embodiments, the digit lines **26** may be considered together to be a group **62**, and the shield-connection-line **40** may be considered to be outward of such group, and along one side of the group.

(33) Although the embodiment of FIGS. 1-4 shows a single shield-connection-line, in other embodiments (described below with reference to FIGS. 10-13) there may be two or more of the shield-connection-lines.

(34) The shield-connection-line **40** and the digit lines **26** are supported by an underlying insulative base **64**. Such base may comprise any suitable composition(s); and may, for example, comprise, consist essentially of, or consist of one or more of silicon nitride, silicon dioxide, aluminum oxide, etc.

(35) The base **64** is shown to be supported by a semiconductor substrate **66**. The substrate **66** may comprise semiconductor material; and may, for example, comprise, consist essentially of, or consist of monocrystalline silicon. The term “semiconductor substrate” means any construction comprising semiconductive material, including, but not limited to, bulk semiconductive materials such as a semiconductive wafer (either alone or in assemblies comprising other materials), and semiconductive material layers (either alone or in assemblies comprising other materials). The term “substrate” refers to any supporting structure, including, but not limited to, the semiconductor

substrates described above.

(36) A gap is provided between the substrate **66** and the base **64** to indicate that there may be other materials or devices provided between the substrate **66** and the base **64**. For instance, in some embodiments the reference source **60** may be provided under the memory array **49** and between the substrate **66** and the base **64**. Also, the wordlines **28** may be coupled with wordline drivers (not shown), and the digit lines **26** may be coupled with sense amplifiers (not shown); and the wordline drivers and/or the sense amplifiers may be provided under the memory array **49**. In some embodiments, the wordline drivers, sense amplifiers and/or reference source may comprise CMOS circuitry (and/or other suitable logic circuitry) which is provided under the memory array **49**.

(37) The illustrated arrangement of FIGS. **1-4** does not show insulative materials in order to simplify the drawings. However, it is to be understood that one or more insulative materials may be provided over and around the illustrated conductive structures. FIG. **2A** shows the configuration of FIG. **2**, and further shows example insulative materials **68** and **70**.

(38) The insulative material **70** corresponds to gate dielectric material provided between the gate regions **34** and the channel regions **24**. Such gate dielectric material may comprise any suitable composition(s); and in some embodiments may comprise, consist essentially of, or consist of silicon dioxide.

(39) The insulative material **68** provides support under the conductive structures **28** and **36**, provides isolation between the structures **28** and **36**, and provides a surface over the structures **28** and **36**. The insulative material **68** may comprise any suitable composition(s); and in some embodiments may comprise, consist essentially of, or consist of one or more of silicon nitride, silicon dioxide, aluminum oxide, etc. Although the materials **68** and **70** are shown to be homogeneous, it is to be understood that in other embodiments one or both of the materials **68** and **70** may comprise discrete combinations of two or more different compositions. For instance, the insulative material provided under the wordlines **28** to support such wordlines may be different than the insulative material provided over and between the wordlines **28**.

(40) In some embodiments, the digit lines **26** and the shield-connection-line **40** may be patterned from a common conductive expanse. FIG. **5** shows the integrated assembly **10** at a process stage which may be utilized during formation of the digit lines **26** and the shield-connection-line **40**, and shows the assembly along a same view as is utilized above for FIG. **4**.

(41) The assembly of FIG. **5** includes an expanse **72** of the conductive material **30** over the base **64**.

(42) FIG. **6** shows a process stage which may follow that of FIG. **5**, and shows the expanse **72** (FIG. **5**) patterned into the digit lines **26** and the conductive-shield-line **40**.

(43) FIG. **7** shows a process stage which may follow that of FIG. **6**, and shows the semiconductor material **18** provided over the digit lines **26** and patterned into the pillars **12**. Although the semiconductor material **18** is shown provided after the patterning of the material **30** into the digit lines **26**, it is to be understood that in other embodiments the semiconductor material may be provided over the expanse **72** of FIG. **5** and that at least some of the patterning of the semiconductor material may occur during the patterning of the digit lines **26**.

(44) The memory array **49** of FIGS. **1-4** is schematically illustrated in FIGS. **8** and **9**. Such figures show the illustrated wordlines **28** as wordlines WL-1, WL-2, WL-3, WL-4, WL-5 and WL-6, and show the illustrated digit lines **26** as digit lines DL-1, DL-2, DL-3, DL-4, DL-5 and DL-6. The digit lines **26** are within the group **62**. The shield-connection-line **40** is along one side of such group, and is offset from the group. The shield-connection-line **40** is coupled with the reference-voltage-source **60**, and is also coupled with the shield lines **36**. The illustrated shield lines are shown as Shield-1 and Shield-2.

(45) FIG. **8** shows the memory cells **50** generically as MC, with each memory cell being uniquely addressed by the combination of one of the wordlines **28** and one of the digit lines **26**. FIG. **9** shows example memory cells **50** to comprise an access transistor **74** in combination with a capacitor **46**. The access transistor **74** may comprise the active-region-pillars **12** and gate regions

**34** described above with reference to FIGS. **1-4**.

(46) The memory array **49** may comprise any suitable number of memory cells **50**, and in some embodiments may comprise hundreds, thousands, millions, etc., of the memory cells.

(47) In some embodiments, multiple shield-connection-lines may be provided along a memory array. FIGS. **10-13** illustrate example embodiments utilizing two or more shield-connection-lines.

(48) FIG. **10** shows the memory array **49** in a configuration having a first shield-connection-line **40a** along a first side **75** of the group **62** of the digit lines **26**, and a second shield-connection-line **40b** along a second side **77** of the group **62** of the digit lines **26**. The shield-connection lines **40a** and **40b** are shown to be electrically coupled with first and second reference-voltage-sources **60a** and **60b**, respectively. In some embodiments, the reference-voltage-sources **60a** and **60b** may be separate from one another, and may be operated differently relative to one another. In other embodiments, the reference-voltage-sources **60a** and **60b** may be part of the same (common) reference-voltage-source.

(49) The shield lines **36** are sequentially labeled as **36a-36f** so they may be distinguished relative to one another. The shield lines **36a**, **36c** and **36e** are coupled with the first shield-connection-line **40a**; and the shield lines **36b**, **36d** and **36f** are coupled with the second shield-connection-line **40b**. In some embodiments, the shield lines **36a**, **36c** and **36e** may be considered to be a first set of the shield lines, and the shield lines **36b**, **36d** and **36f** may be considered to be a second set of the shield lines. In the embodiment of FIG. **10**, each of the shield lines **36** is coupled with only one of the shield-connection lines **40**, and the connections to the shield-connection lines are distributed sequentially to the different shield-connection-lines along the y-axis direction (specifically, the connections to the shield-connection lines alternate between connections to the first shield-connection-line **40a** and connections to the second shield-connection-line **40b** along the direction of the y-axis).

(50) In some embodiments, the digit lines **26** and the shield-connection-lines **40a** and **40b** may be together considered to be a group of conductive lines. The shield-connection-lines **40a** and **40b** may be considered to be edge lines of such group of conductive lines; with the shield-connection-line **40a** being a first edge line along a first side of the group of the conductive lines, and the shield-connection-line **40b** being a second edge line along a second side of the group of the conductive lines. The second side of the group of the conductive lines is in opposing relation relative to the first side of the group of the conductive lines.

(51) FIG. **11** shows the memory array **49** in an arrangement analogous to that of FIG. **10**, but in which the connections to the shield-connection-lines **40a** and **40b** are distributed in batches along the y-axis direction. Specifically, the shield lines **36a**, **36b** and **36c** correspond to a first batch of shield lines coupled with the shield-connection-line **40a**, and the shield lines **36d**, **36e** and **36f** correspond to a second batch of shield lines coupled with the second shield-connection-line **40b**. Both of the shield-connection-lines **40a** and **40b** are outward of the group **62** of the digit lines **26**, with the shield-connection-line **40a** being along the first side **75** side of the group **62** of the digit lines **26** and the shield-connection-line **40b** being along the opposing second side **77** of the group **62** of the digit lines **26**.

(52) The shield-connection-lines **40a** and **40b** are connected to the reference-voltage-sources **60a** and **60b**, respectively. Such reference-voltage-sources may be part of a common reference-voltage-source, or may be separate reference-voltage-sources operated independently of one another.

(53) FIG. **12** shows the memory array **49** in an arrangement similar to that of FIG. **11**, but in which both of the first and second shield-connection-lines are along the same side **75** of the group **62** of the digit lines **26**.

(54) FIG. **13** shows another embodiment of the memory **49**, and shows three shield-connection-lines **40a**, **40b** and **40c** outward of the group **62** of the digit lines **26**. Two of the shield-connection lines are along the first side **75** of the group **62** of the digit lines **26** (specifically, the shield-connection-lines **40a** and **40b**), and the third of the shield-connection-lines is along the second side



77 of the group 62 of the digit lines 26 (specifically, the shield-connection-line 40c). In other embodiments, additional shield-connection-lines may be provided along one or both of the sites 75 and 77 of the group 62 of the digit lines 26, and/or one or more of the shield-connection-lines 40a, 40b and 40c may be omitted.

(55) The shield-connection-lines 40a, 40b and 40c are shown coupled with reference-voltage-sources 60a, 60b and 60c. Such reference-voltage-sources may be part of a common reference-voltage-source, or at least two of the reference-voltage-sources may be separate reference-voltage-sources operated independently of one another.

(56) The assemblies and structures discussed above may be utilized within integrated circuits (with the term “integrated circuit” meaning an electronic circuit supported by a semiconductor substrate); and may be incorporated into electronic systems. Such electronic systems may be used in, for example, memory modules, device drivers, power modules, communication modems, processor modules, and application-specific modules, and may include multilayer, multichip modules. The electronic systems may be any of a broad range of systems, such as, for example, cameras, wireless devices, displays, chip sets, set top boxes, games, lighting, vehicles, clocks, televisions, cell phones, personal computers, automobiles, industrial control systems, aircraft, etc.

(57) Unless specified otherwise, the various materials, substances, compositions, etc. described herein may be formed with any suitable methodologies, either now known or yet to be developed, including, for example, atomic layer deposition (ALD), chemical vapor deposition (CVD), physical vapor deposition (PVD), etc.

(58) The terms “dielectric” and “insulative” may be utilized to describe materials having insulative electrical properties. The terms are considered synonymous in this disclosure. The utilization of the term “dielectric” in some instances, and the term “insulative” (or “electrically insulative”) in other instances, may be to provide language variation within this disclosure to simplify antecedent basis within the claims that follow, and is not utilized to indicate any significant chemical or electrical differences.

(59) The terms “electrically connected” and “electrically coupled” may both be utilized in this disclosure. The terms are considered synonymous. The utilization of one term in some instances and the other in other instances may be to provide language variation within this disclosure to simplify antecedent basis within the claims that follow.

(60) The particular orientation of the various embodiments in the drawings is for illustrative purposes only, and the embodiments may be rotated relative to the shown orientations in some applications. The descriptions provided herein, and the claims that follow, pertain to any structures that have the described relationships between various features, regardless of whether the structures are in the particular orientation of the drawings, or are rotated relative to such orientation.

(61) The cross-sectional views of the accompanying illustrations only show features within the planes of the cross-sections, and do not show materials behind the planes of the cross-sections, unless indicated otherwise, in order to simplify the drawings.

(62) When a structure is referred to above as being “on”, “adjacent” or “against” another structure, it can be directly on the other structure or intervening structures may also be present. In contrast, when a structure is referred to as being “directly on”, “directly adjacent” or “directly against” another structure, there are no intervening structures present. The terms “directly under”, “directly over”, etc., do not indicate direct physical contact (unless expressly stated otherwise), but instead indicate upright alignment.

(63) Structures (e.g., layers, materials, etc.) may be referred to as “extending vertically” to indicate that the structures generally extend upwardly from an underlying base (e.g., substrate). The vertically-extending structures may extend substantially orthogonally relative to an upper surface of the base, or not.

(64) Some embodiments include an integrated assembly having conductive lines supported by a base and extending along a first direction. Some of the conductive lines are digit lines and at least

one of the conductive lines is a shield-connection-line. Semiconductor pillars are over the digit lines. Each of the semiconductor pillars includes a channel region between an upper source/drain region and a lower source/drain region. The lower source/drain regions are coupled with the digit lines. Storage elements are coupled with the upper source/drain regions. Wordlines extend along a second direction which crosses the first direction. The wordlines include gate regions adjacent the channel regions. Shield lines extend along the second direction. Each of the shield lines is coupled with an associated one of the shield-connection-lines. Each of the semiconductor pillars has a first side proximate an associated one of the wordlines, and has a second side proximate an associated one of the shield lines.

(65) Some embodiments include an integrated assembly having digit lines supported by a base and extending along a first direction. At least one shield-connection-line is supported by the base and extends along the first direction. Transistor active regions are over the digit lines. Each of the active regions includes a channel region between an upper source/drain region and a lower source/drain region. The lower source/drain regions are coupled with the digit lines. Capacitors are coupled with the upper source/drain regions. Wordlines extend along a second direction which crosses the first direction. The wordlines include gate regions adjacent the channel regions. Shield lines extend along the second direction. The shield lines are above the digit lines and are coupled with one or more of said at least one shield-connection-lines.

(66) Some embodiments include an integrated assembly having conductive lines supported by a base and extending along a first direction. Some of the conductive lines are digit lines and one of the conductive lines is a shield-connection-line. The conductive lines all comprise a same material as one another and all comprise a same height as one another. Vertically-extending pillars are over the digit lines. Each of the vertically-extending pillars comprises a channel region between an upper source/drain region and a lower source/drain region. The lower source/drain regions are coupled with the digit lines. Storage elements are coupled with the upper source/drain regions. Wordlines extend along a second direction which crosses the first direction. The wordlines include gate regions adjacent the channel regions. Shield lines extend along the second direction. Each of the shield lines is coupled with the shield-connection-line.

(67) In compliance with the statute, the subject matter disclosed herein has been described in language more or less specific as to structural and methodical features. It is to be understood, however, that the claims are not limited to the specific features shown and described, since the means herein disclosed comprise example embodiments. The claims are thus to be afforded full scope as literally worded, and to be appropriately interpreted in accordance with the doctrine of equivalents.

## Claims

1. An integrated assembly, comprising: conductive lines supported by a base and extending along a first direction; some of the conductive lines being digit lines and a plurality of the conductive lines being shield-connection-lines; semiconductor pillars over the digit lines; each of the semiconductor pillars comprising a channel region between an upper source/drain region and a lower source/drain region; the lower source/drain regions being coupled with the digit lines; wordlines extending along a second direction which crosses the first direction; the wordlines including gate regions adjacent the channel regions; and shield lines extending along the second direction; each of the shield lines being coupled with an associated one of the shield-connection-lines.
2. The integrated assembly of claim 1 wherein: the semiconductor pillars are arranged in a matrix comprising rows and columns; the columns comprise the associated semiconductor pillars coupled with a common digit line; the semiconductor pillars are spaced from one another by gaps along the first direction; the gaps along a common column alternate between first gaps and second gaps; two of the wordlines are within each of the first gaps; and one of the shield lines is within each of the

second gaps.

3. The integrated assembly of claim 1 further comprising a reference-voltage-source at ground voltage.
4. The integrated assembly of claim 1 further comprising a reference-voltage-source at non-ground voltage.
5. The integrated assembly of claim 1 further comprising storage elements coupled with the upper source/drain regions, wherein the storage elements are comprised by memory cells of a memory array; each of the memory cells being uniquely addressed with one of the digit lines in combination with one of the wordlines.
6. The integrated assembly of claim 5 wherein the memory array comprises DRAM.
7. An integrated assembly, comprising: conductive lines supported by a base and extending along a first direction; some of the conductive lines being digit lines and one of the conductive lines being a shield-connection-line; the conductive lines all comprising a same material as one another and all comprising a same height as one another; wordlines extending along a second direction which crosses the first direction; each of the wordlines including a gate region adjacent a channel region; and shield lines extending along the second direction; each of the shield lines being coupled with the shield-connection-line.
8. The integrated assembly of claim 7 further comprising vertically-extending pillars over the digit lines; each of the vertically-extending pillars comprising the channel region between an upper source/drain region and a lower source/drain region; the lower source/drain regions being coupled with the digit lines.
9. The integrated assembly of claim 8 wherein the each of the vertically-extending pillars has a first side and an opposing second side; the first side being proximate one of the wordlines, and the second being proximate one of the shield lines.
10. The integrated assembly of claim 7 wherein the shield-connection-line is coupled with a reference-voltage-source.
11. The integrated assembly of claim 7 wherein the shield-connection-line is a first shield-connection-line; wherein another one of the conductive lines is a second shield-connection-line; wherein the shield lines coupled with the first shield-connection-line are a first set of the shield lines; and further comprising a second set of the shield lines coupled with the second shield-connection-line.
12. The integrated assembly of claim 11 wherein the first and second shield-connection-lines are coupled to a common reference-voltage-source.
13. The integrated assembly of claim 11 wherein the first shield-connection-line is coupled to a first reference-voltage-source and the second shield-connection-line is coupled to a second reference-voltage-source which is different from the first reference-voltage-source.
14. The integrated assembly of claim 11 wherein the conductive lines are together a group of conductive lines; said group of conductive lines having a first side and a second side, with the second side being in opposing relation to the first side; and wherein one of the first and second shield lines is along the first side and the other of the first and second shield lines is along the second side.
15. The integrated assembly of claim 11 wherein the conductive lines are together a group of conductive lines; said group of conductive lines having a first edge line along one side of the group of conductive lines, and having a second edge line along a second side of the group of conductive lines, with the second side being in opposing relation to the first side; and wherein the first and second shield lines correspond to the first and second edge lines, respectively.
16. The integrated assembly of claim 11 wherein the conductive lines are together a group of conductive lines; said group of conductive lines having a first side and a second side, with the second side being in opposing relation to the first side; and wherein the first and second shield lines are both along the first side.

17. The integrated assembly of claim 7 wherein said same material of the conductive lines is a metal-containing material.

18. An integrated assembly, comprising: digit lines supported by a base and extending along a first direction; a plurality of shield-connection-lines supported by the base and extending along the first direction, the digit lines and the plurality of shield-connection lines comprising a same material as one another; transistor active regions over the digit lines; each of the active regions comprising a channel region between an upper source/drain region and a lower source/drain region; the lower source/drain regions being coupled with the digit lines; capacitors coupled with the upper source/drain regions; wordlines extending along a second direction which crosses the first direction; the wordlines including gate regions adjacent the channel regions; and shield lines extending along the second direction; the shield lines being above the digit lines, each of the shield lines being coupled to only one of said plurality of shield-connection-lines, connections to the plurality of shield-connection-lines being sequentially distributed to the different shield-connection-lines along the first direction.

19. The integrated assembly of claim 18 wherein said same material is a metal-containing material.

---