

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12383408
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	De Wilde; Lieven et al.

Revision glenoid device method

Abstract

A glenoid component in one embodiment includes a base component with a planar upper circular rim defining a first plane, a receptacle opening to the first plane, and a lower planar circular surface defining a second plane parallel to the first plane. An articulating component of the glenoid component includes an upper articulating surface, a lower cylindrical coupling portion configured to be inserted into the receptacle, and an overhang portion located above the lower cylindrical coupling portion and beneath the upper articulating surface. The overhang portion includes a planar lower surface extending outwardly from the lower cylindrical coupling portion and configured to abut the planar upper circular rim of the base component when the articulating component is coupled to the base component.

Inventors:	De Wilde; Lieven (Ghent, BE), Lappin; Kyle (Ft. Wayne, IN)
Applicant:	DePuy Synthes Products, Inc. (Raynham, MA)
Family ID:	46829099
Assignee:	DePuy Synthes Products, Inc. (Raynham, MA)
Appl. No.:	17/388918
Filed:	July 29, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20210353424 A1	Nov. 18, 2021

Related U.S. Application Data

continuation parent-doc US 16214676 20181210 US 11076963 child-doc US 17388918
division parent-doc US 14027907 20130916 US 10172715 20190108 child-doc US 16214676
division parent-doc US 13051062 20110318 US 8551177 20131008 child-doc US 14027907

Publication Classification

Int. Cl.: **A61F2/40** (20060101); **A61B17/16** (20060101); **A61F2/30** (20060101); **A61F2/46** (20060101); A61B17/17 (20060101); A61B17/86 (20060101)

U.S. Cl.:

CPC **A61F2/4081** (20130101); **A61B17/1684** (20130101); **A61F2/30771** (20130101); A61B17/1778 (20161101); A61B17/86 (20130101); A61F2002/3021 (20130101); A61F2002/30224 (20130101); A61F2002/30331 (20130101); A61F2002/30616 (20130101); A61F2002/30617 (20130101); A61F2002/3069 (20130101); A61F2002/30736 (20130101); A61F2002/30769 (20130101); A61F2002/30784 (20130101); A61F2002/3092 (20130101); A61F2002/3093 (20130101); A61F2002/4677 (20130101)

Field of Classification Search

CPC: A61F (2/40-4081)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2487203	12/1948	Wilber	N/A	N/A
3855638	12/1973	Pilliar	N/A	N/A
4030143	12/1976	Elloy et al.	N/A	N/A
4964865	12/1989	Burkhead et al.	N/A	N/A
5030219	12/1990	Matsen et al.	N/A	N/A
5080673	12/1991	Burkhead et al.	N/A	N/A
5180384	12/1992	Mikhail	N/A	N/A
5324295	12/1993	Shapiro	N/A	N/A
5489310	12/1995	Mikhail	N/A	N/A
5800551	12/1997	Williamson et al.	N/A	N/A
5919195	12/1998	Wilson et al.	N/A	N/A
6010535	12/1999	Shah	N/A	N/A
6045302	12/1999	Orr	N/A	N/A
6228900	12/2000	Shen et al.	N/A	N/A
6245074	12/2000	Allard et al.	N/A	N/A
6281264	12/2000	Salovey et al.	N/A	N/A
6364910	12/2001	Shultz et al.	N/A	N/A
6379386	12/2001	Resch et al.	N/A	N/A
6679916	12/2003	Frankle et al.	N/A	N/A
6699289	12/2003	Iannotti et al.	N/A	N/A
6783549	12/2003	Stone et al.	N/A	N/A
7294133	12/2006	Zink et al.	N/A	N/A
7329284	12/2007	Maroney et al.	N/A	N/A
7338498	12/2007	Long et al.	N/A	N/A
7604665	12/2008	Iannotti et al.	N/A	N/A
8764836	12/2013	De Wilde et al.	N/A	N/A

2003/0125809	12/2002	Iannotti et al.	N/A	N/A
2004/0097947	12/2003	Wolford et al.	N/A	N/A
2004/0193168	12/2003	Long et al.	N/A	N/A
2005/0278030	12/2004	Tornier et al.	N/A	N/A
2006/0015112	12/2005	McGovern	N/A	N/A
2006/0020344	12/2005	Shultz et al.	N/A	N/A
2006/0069443	12/2005	Deffenbaugh	N/A	N/A
2006/0069444	12/2005	Deffenbaugh	N/A	N/A
2006/0111787	12/2005	Bailie et al.	N/A	N/A
2006/0195194	12/2005	Gunther	N/A	N/A
2006/0276905	12/2005	Calamel	N/A	N/A
2007/0016304	12/2006	Chudik	N/A	N/A
2007/0038302	12/2006	Shultz et al.	N/A	N/A
2007/0055249	12/2006	Jensen et al.	N/A	N/A
2007/0251356	12/2006	Tribby	N/A	N/A
2007/0260321	12/2006	Stchur	N/A	N/A
2008/0306600	12/2007	Huebner	N/A	N/A
2009/0171462	12/2008	Poncet	623/19.12	A61F 2/4059
2009/0270993	12/2008	Maisonneuve et al.	N/A	N/A
2010/0070044	12/2009	Maroney et al.	N/A	N/A
2010/0087876	12/2009	Gunther	N/A	N/A
2010/0161065	12/2009	Williams, Jr. et al.	N/A	N/A
2010/0249938	12/2009	Gunther et al.	N/A	N/A
2010/0274359	12/2009	Brunnarius et al.	N/A	N/A
2010/0331990	12/2009	Mroczkowski et al.	N/A	N/A
2011/0012318	12/2010	Northwood	N/A	N/A
2011/0028977	12/2010	Rauscher et al.	N/A	N/A
2011/0035013	12/2010	Winslow et al.	N/A	N/A
2012/0089233	12/2011	Capon et al.	N/A	N/A
2012/0130499	12/2011	Long	N/A	N/A
2012/0191201	12/2011	Smits	N/A	N/A
2013/0123930	12/2012	Burt	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
693446	12/2002	CH	N/A
1639949	12/2005	EP	N/A
1815825	12/2006	EP	N/A
2704747	12/1993	FR	N/A
2940607	12/2009	FR	N/A
2406278	12/2004	GB	N/A
H11127256	12/1989	JP	N/A
2003230584	12/2002	JP	N/A
2010150223	12/2009	WO	N/A
2011005205	12/2010	WO	N/A

OTHER PUBLICATIONS

Erichsen, "Injuries of the Nervous System on Railway and Other Injuries of the Nervous System", The Classic Article in Clinical Orthopaedics and Related Research, Mar. 1997, pp. 47-51, No. 458,

Walton and Moberry, London (5 pages). cited by applicant

Iannotti JP, Gabriel JP, Schneck SL, Evans BG, Misra S., "The normal glenohumeral relationships. An anatomical study of one hundred and forty shoulders." *J. Bone Joint Surg Am.* 1992;74(4); 491-500. No doi found. (11 pages). cited by applicant

Karduna AR, Williams GR, Williams JL, Iannotti JP., "Glenohumeral Joint translations before and after total shoulder arthroplasty." *J Bone Joint Surg* 1997;79-A, 1166-74. No doi found. (10 pages). cited by applicant

Lee SB, Kim KJ, O'Driscoll SW, Morrey BF, An KN., "Dynamic glenohumeral stability provided by the rotator cuff muscles in the mid-range and end-range of motion." A study in cadavera. *J. Bone Joint Surg Am.* 2000;82(6):849-57. No doi found (10 pages). cited by applicant

Lewis GS, Bryce CD, Davison AC, Hollenbeak CS, Piazza SJ, Armstrong AD., "Location of the optimized centerline of the glenoid vault: a comparison of two operative techniques with use of three-dimensional computer modeling." *J Bone Joint Surg Am.* 2010;92:1188-94. doi:10-2106/JBJS.I.00131. (8 pages). cited by applicant

Mahfouz M, Nicholson G, Komistek R, Hovis D, Kubo M., "In vivo determination of the dynamics of normal, rotator cuff-deficient, total, and reverse replacement shoulders." *J Bone Joint Surg Am.* 2005;87 Suppl 2:107-13. doi:10.2106/JBJS.E.00483 (8 pages). cited by applicant

Massimini DF, Li G, Warner JP., "Glenohumeral contact kinematics in patients after total shoulder arthroplasty." *J Bone Joint Surg Am.* Apr. 2010;92(4):916-26. doi:10.2106/JBJS.H.01610. (12 pages). cited by applicant

Matsen FA., "Early effectiveness of shoulder arthroplasty for patients who have primary glenohumeral degenerative joint disease." *J Bone and Joint Surg* 1996;78-A:260-4. No doi found. (6 pages). cited by applicant

Nyffeler RW, Sheikh R, Atkinson TS, Jacob HA, Favre P, Gerber C., "Effects of glenoid component version on humeral head displacement and joint reaction forces: an experimental study." *J Shoulder Elbow Surg.* 2006; 15:625-9. doi:10.1016/j.jse.2005.09.016. (5 pages). cited by applicant

Nyffeler RW, Werner CM, Sukthankar A, Schmid MR, Gerber C., "Association of a large lateral extension of the acromion with rotator cuff tears." *J. Bone Joint Surg Am.* 2006;88-800-5. No doi found (7 pages). cited by applicant

Pappas GP, Blemker SS, Beaulieu CF, McAdams TR, Whalen ST, Gold GE., "In vivo anatomy of the Neer and Hawkins sign positions for shoulder impingement." *J Shoulder Elbow Surg* 2006;15:40-9. doi:10.1016/j.jse.2005.04.007. (10 pages). cited by applicant

Pearl ML, Krurtz S., "Geometric analysis of commonly used prosthetic systems for proximal humeral replacement." *J Bone Joint Surg* 1999;81-A:660-71. No doi found (13 pages). cited by applicant

Scalise JJ, Codsí MJ, Bryan J, Brems JJ, Iannotti JP., "The influence of three-dimensional computed tomography images of the shoulder in preoperative planning for total shoulder arthroplasty." *J Bone Joint Surg Am.* 2008;90:2438-45. doi: 10.2106/JBJS.G.01341. (9 pages). cited by applicant

Schiffert SC, Rozencwaig R, Antoniou J, Richardson ML, Matsen FA III., "Anteroposterior centering of the humeral head on the glenoid in vivo." *Am J Sports Med.* 2002;30(3):382-7. No doi found. (7 pages). cited by applicant

Soslowky LJ, Flatow EL, Bigliani LU, Pawluk RJ, Ateshian GA, Mow VC., "Quantitation of in situ contact areas at the glenohumeral joint: a biomechanical study." *J Orthop Res.* 1992; 10:524-34. doi: 10.1002/jor. 1100100407. (11 pages). cited by applicant

Takase K, Yamamoto K, Imakiire A, Burkhead WZ Jr., "The radiographic study in the relationship of the glenohumeral joint." *J Orthop Res.* 2004;22:298-305. doi:10.1016/S0736-0266(03)00187-6 (8 pages). cited by applicant

Tokgoz N, Kanatli U, Voyvoda NK, Gultekin S, Bolukbasi S, Tall ET., "The relationship of glenoid

and humeral version with supraspinatus tendon tears.” *Skeletal Radion.* 2007;36:509-14. No doi found. (6 pages). cited by applicant

Werner CML, Weishaupt D, Blumenthal S, Curt A, Favre P, Gerber C., “Effect of experimental suprascapular nerve block on active glenohumeral translations in vivo.” *J Orthop Res* 2006;24:491-500. doi:10.1002/jor.20011. (10 pages). cited by applicant

Antuna et al., “Glenoid revision surgery after total shoulder arthroplasty,” *Journal of Shoulder Elbow Surgery*, 2001, pp. 217-224, vol. 10, Rochester, MN (8 pages). cited by applicant

Bolleau P. Walch G., “The three dimensional geometry of the proximal humerus. Implications for the surgical technique and prosthetic design.” *J. Bone Joint Surg Br* 1997;79-B:857-65. doi:10.1302/0301-620X.79B5.7579 (9 pages). cited by applicant

Boyer PJ, Massimini DF, Gill TJ, Papannagari R, Stewart SL, Warner JP, Li G., “In vivo articular cartilage contact at the glenohumeral joint: preliminary report.” *J. Orthop Sci.* 2008;13:359-65. doi:10.1007/s00776-008-1237-3 (7 pages). cited by applicant

Bryce CD, Davison AC, Lewis GS, Wang , Flemming DJ, Armstrong AD., “Two dimensional glenoid version measurements vary with coronal and sagittal scapular rotation.” *J Bone Joint Surg Am.* 2010;92-692-9. doi. 10.2106/JBJS.1.00177 (8 pages). cited by applicant

Codsi et al., “Normal glenoid vault anatomy and validation of a novel glenoid implant shape,” *Journal of Shoulder Elbow Surgery*, May/Jun. 2008, pp. 471-478, vol. 17, Austria (8 pages). cited by applicant

Couteau B, Mansat , Darmana R, Mansat M., Egan J., “Morphological and mechanical analysis of the glenoid by 3D geometric reconstruction using computed tomography.” *Clin Biomech* 2000;15(suppl1):8-12. doi:10.1016/S0268-0033(00)00052-8 (5 pages). cited by applicant

Couteau B, Mansat P. Estivales E, Darmana R. Mansat M., Egan J., “Finite element analysis of the mechanical behavior of a scapula implanted with a glenoid prosthesis.” *Clin Biomech* 2001;16:566-75. doi: 10.1016/S0268-0033(01)00029-8 (10 pages). cited by applicant

Couteau B, Mansat P, Mansat M, Darmana R, Egan J., “In vivo characterization of glenoid with use of computed tomography.” *J Shoulder Elbow Surg* 2001;116-22 (7 pages). cited by applicant

De Wilde LF, Verstraeten T, Speeckaert W, Karelse A., “Reliability of the glenoid plane.” *J Shoulder Elbow Surg.* 2010;19:414-22. doi:10.1016/j.jse.2009.10.005. (9 pages). cited by applicant

Graichen H, Hinterwimmer S, von Eisenhart-Rothe R, Vogl T. Englmeier KH, Eckstein F., “Effect of abducting and adducting muscle activity on glenohumeral translation, scapular kinematics and subacromial space width in vivo.” *Journal of Biomechanics* 2005;38:755-60. doi:10.1016/j.jbiomech.2004.05.020. (6 pages). cited by applicant

Graichen H, Stammberger T. Bonel H, Karl-Hans E, Relser M, Eckstein F., “Glenohumeral translation during active and passive elevation of the shoulder—a 3D open-MRI study.” *Journal of Biomechanics* 2000;33:609-13. doi:10.1016/S0021-9290(99)00209-2. (5 pages). cited by applicant

Harryman DT, Sidles JA, Harris SL, Lippitt SB, Matsen FA., “The effect of articular conformity and the size of the humeral head component on laxity and motion after glenohumeral arthroplasty.” *J. Bone Joint Surg Am* 1995;77-A:555-63. No doi found. (10 pages). cited by applicant

Huysmans PE, Haen PS, Kidd M, Dhert WJ, Willems JW., “The shape of the inferior part of the glenoid: a cadaveric study.” *J Shoulder Elbow Surg.* 15(6):759-63. doi:10.1016/j.jse.2005.09.001 (5 pages). cited by applicant

Karelse et al., “The Pillars of the Scapula”, *Clinical Anatomy*, 2007, pp. 392-399, vol. 20, Belgium (8 pages). cited by applicant

Jeske, H.C. et al., “Normal Glenoid Rim Anatomy and the Reliability of Shoulder Instability Measurements Based on Intrasite Correlation,” *Surg. Radiol. Anat.*, vol. 31, pp. 623-625. Mar. 2009 (3 pages). cited by applicant

Bey, Michael J., et al., “ Measuring Dynamic In-Vivo Glenohumeral Joint Kinematics: Technique and Preliminary Results,” *Journal of Biomechanics* 41 (2008), pp. 711-714. (4 pages). cited by applicant

Chant, Chris B., et al., "Humeral Head Retroversion in Competitive Baseball Players and Its Relationship to Glenohumeral Rotation Range of Motion," *Journal of Orthopaedic & Sports Physical Therapy*, Sep. 2007, vol. 37, No. 9, pp. 514-520. (7 pages). cited by applicant

Conzen, Annemarie and Eckstein, Felix, MD, "Quantitative Determination of Articular Pressure in the Human Shoulder Joint," *Journal of Shoulder and Elbow Surgery*, vol. 9, No. 3, May/Jun. 2000, pp. 196-204. (9 pages). cited by applicant

De Wilde, Lieven F. MD, et al., "Glenohumeral Relationship in the Transverse Plane of the Body," *Journal of Shoulder and Elbow Surgery*, vol. 12, No. 3, May/Jun. 2003, pp. 260-267. (8 pages). cited by applicant

De Wilde, L.F., et al., "About the Variability of the Shape of the Glenoid Cavity," *Surgical and Radiologic Anatomy* (2004) 26; pp. 54-59. (6 pages). cited by applicant

Fleiss, Joseph L., "Analysis Of Data From Multiclinic Trials," *Controlled Clinical Trials* 7: 267-275 (1986). (9 pages). cited by applicant

Hertel, Ralph M.D., "Geometry of the Proximal Humerus and Implications for Prosthetic Design," *Journal of Shoulder and Elbow Surgery*, Jul./Aug. 2002, vol. 11, No. 4, pp. 331-338. (8 pages). cited by applicant

Mansat, M. and Fourcade, D., "Preoperative Planning in Shoulder Prosthesis," *Acta Orthopaedica Belgica* (1995) vol. 61—Suppl. Jan. 1995. (6 pages). cited by applicant

Middernacht, Bart, MD, et al., "Consequences of Scapular Anatomy for Reversed Total Shoulder Arthroplasty," *Clinical Orthopaedics and Related Research* (2008) 466: 1410-1418. (9 pages). cited by applicant

Moon, P. and Spencer, D.E., *Rectangular Coordinates (x,y,z). Field Theory Handbook, Including Coordinate Systems, Differential Equations, and Their Solutions* (1988), New York: Springer-Verlag, pp. 9-11 (Table 1.01). (3 pages). cited by applicant

Pearl, Michael L., M.D. and Volk, Albert G., M.D., "Coronal Plane Geometry of the Proximal Humerus Relevant to Prosthetic Arthroplasty," *Journal of Shoulder and Elbow Surgery*, vol. 5, No. 4, Jul./Aug. 1996, pp. 320-326. (7 pages). cited by applicant

Pearl, ML and Volk, AG, "Retroversion of the Proximal Humerus in Relationship to Prosthetic Replacement Arthroplasty," *Journal of Shoulder and Elbow Surgery*, Jul. 1995, vol. 4, No. 4, pp. 286-289. (4 pages). cited by applicant

Randelli, M., M.D. and GAMBRIOLI, P.L., M.D., "Glenohumeral Osteometry by Computed Tomography in Normal and Unstable Shoulders," *Clinical Orthopaedics and Related Research*, No. 208, Jul. 1986, pp. 151-156. (6 pages). cited by applicant

Robertson, Douglas D., M.D., et al., "Three-Dimensional Analysis of the Proximal Part of the Humerus: Relevance to Arthroplasty," *The Journal of Bone and Joint Surgery*, vol. 82-A, No. 11, Nov. 2000, pp. 1594-1602. (9 pages). cited by applicant

Rougraff, Bruce T., M.D., et al., "Does Length of Symptoms Before Diagnosis of Sarcoma Affect Patient Survival?" *Clinical Orthopaedics and Related Research* (2007), No. 462, pp. 181-189. (9 pages). cited by applicant

Shrout, Patrick E. and Fleiss, Joseph L., "Intraclass Correlations: Uses in Assessing Rater Reliability," *Psychological Bulletin*, 1979, vol. 86, No. 2, pp. 420-428. (9 pages). cited by applicant

Soslowsky, Louis J., Ph.D. et al., "Articular Geometry of the Glenohumeral Joint," *Clinical Orthopaedics and Related Research*, No. 285, Dec. 1992, pp. 181-190. (10 pages). cited by applicant

Tetreault, Patrice, et al., "Glenoid Version and Rotator Cuff Tears," *Journal of Orthopaedic Research* 22 (2004) pp. 202-207. (6 pages). cited by applicant

Warner, Jon J.P., M.D et al., "Articular Contact Patterns of the Normal Glenohumeral Joint," *Journal of Shoulder and Elbow Surgery*, Jul./Aug. 1998, vol. 7, No. 4, pp. 381-388. (8 pages). cited by applicant

Westerhoff, P., et al., "In Vivo Measurement of Shoulder Joint Loads During Activities of Daily

Living,” Journal of Biomechanics 42 (2009), pp. 1840-1849. (10 pages). cited by applicant

Williams, Gerald R., Jr., M.D., and Iannotti, Joseph P., M.D. PhD., “Options for Glenoid Bone Loss: Composites of Prosthetics and Biologics,” Journal of Shoulder and Elbow Surgery, Sep./Oct. 2007, vol. 16, No. 5S, pp. 267S-272S. (6 pages). cited by applicant

Wirth, Michael A., M.D. and Rockwood, Charles A., Jr., M.D., “Complications of Shoulder Arthroplasty,” Clinical Orthopaedics and Related Research, Oct. 1994, No. 307, pp. 47-69. (23 pages). cited by applicant

Wirth, Michael A. and Rockwood, Charles A., Jr., “Current Concepts Review—Complications of Total Shoulder-Replacement Arthroplasty,” Journal of Bone & Joint Surgery, Apr. 1996, vol. 78-A, No. 4, pp. 603-616. (15 pages). cited by applicant

Frederick et al., “Shoulder Arthroplasty: The Socket Perspective,” J Shoulder Elbow Surg. 2007; 16:241S-247S. cited by applicant

International Preliminary Report on Patentability in corresponding PCT application PCT/US2012/029034, report issued Sep. 24, 2013 (7 pages). cited by applicant

Extended European Search Report corresponding to European Application No. 16167719.0-1654, dated Sep. 6, 2016 (16 pages). cited by applicant

Extended European Search Report corresponding to European Application No. 12760274.6, dated Jun. 27, 2014 (6 pages). cited by applicant

Extended Search Report corresponding to European Application No. 12760199.5, dated Aug. 7, 2014 (6 pages). cited by applicant

Australian Examination Report corresponding to application No. 2012231298, date of issue Sep. 17, 2015, (4 pages). cited by applicant

Chinese Search Report corresponding to application No. 201280023890.7, date Jun. 5, 2015, (2 pages). cited by applicant

Japanese Office Action corresponding to application No. 2013-558132, date mailed Jan. 12, 2016 (5 pages). cited by applicant

Extended European Search Report corresponding to European Patent Application 12760666.3, dated May 13, 2014 (10 pages). cited by applicant

Middernacht et al., “Consequences of Scapular Anatomy for Reversed Total Shoulder Arthroplasty,” Clinical Orthopedics and Related Research (2008) 466:1410-1418 (9 pages). cited by applicant

Piasecki et al. Review Article: “Glenoid Bone Deficiency in Recurrent Anterior Shoulder Instability: Diagnosis and Management,” J Am Acad. Ortho. Surg. 2009, vol. 17, pp. 482-493 (12 pages). cited by applicant

Primary Examiner: Watkins; Marcia L

Attorney, Agent or Firm: Maginot, Moore & Beck

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This is a continuation of co-pending U.S. application Ser. No. 16/214,676, filed on Dec. 10, 2018, which issued Aug. 3, 2021 as U.S. Pat. No. 11,076,963, which is a divisional application of U.S. application Ser. No. 14/027,907, filed on Sep. 16, 2013, now U.S. Pat. No. 10,172,715 which issued Jan. 8, 2019 and which is a divisional application of U.S. application Ser. No. 13/051,062, filed on Mar. 18, 2011, now U.S. Pat. No. 8,551,177 which issued Oct. 8, 2013, the entire disclosures of which are incorporated herein by reference, which references U.S. patent application Ser. No. 13/051,011, entitled

“Circular Glenoid Method for Shoulder Arthroscopy”, which was filed on Mar. 18, 2011, U.S. patent application Ser. No. 13/051,026, entitled “Combination Reamer/Drill Bit for Shoulder Arthroscopy”, which was also filed on Mar. 18, 2011, and U.S. patent application Ser. No. 13/051,041, entitled “Device and Method for Retroversion Correction Cone for Shoulder Arthroscopy”, which was also filed on Mar. 18, 2011, the contents of which are each incorporated herein by reference.

TECHNICAL FIELD OF THE INVENTION

(1) The present invention relates generally to the field of orthopedics, and, more particularly, to glenoid component apparatuses for shoulder arthroplasty and methods for using them.

BACKGROUND

(2) As depicted in FIG. 1, a typical shoulder or glenohumeral joint is formed in a human body where the humerus **10** movably contacts the scapula **12**. The scapula **12** includes a glenoid fossa **14** that forms a socket against which the head of the humerus **10** articulates. At this socket, the scapula **12** includes cartilage **16** that facilitates such articulation. Beneath the cartilage is subchondral bone **18** that forms a wall of a glenoid vault **20** that defines a cavity which contains cancellous bone **22**. The subchondral bone **18** that forms the glenoid vault **20** defines a glenoid rim **24** at a periphery of the glenoid vault **20** that is attached to the cartilage **16**. During the lifetime of a patient, the glenoid fossa **14** may become worn, especially at its posterior and/or superior portions thereby causing severe shoulder pain and limiting the range of motion of the patient's shoulder joint. To alleviate such pain and increase the patient's range of motion, a shoulder arthroplasty may be performed. Arthroplasty is the surgical replacement of one or more bone structures of a joint with one or more prostheses.

(3) Shoulder arthroplasty often involves replacement of the glenoid fossa of the scapula with a prosthetic glenoid component. The conventional glenoid component typically provides a generally laterally or outwardly facing generally concave bearing surface against which a prosthetic humeral head (or, alternatively, the spared natural humeral head in the case of a glenoid hemi-arthroplasty) may bear during operation of the joint. The conventional glenoid component typically also includes a generally medially or inwardly projecting stem for fixing the glenoid component in a cavity constructed by suitably resecting the glenoid fossa **14** and suitably resecting cancellous bone **22** from the glenoid vault **20**.

(4) The goal of shoulder arthroplasty is to restore normal kinematics to the shoulder. Accordingly, known systems attempt to replicate the normal kinematics by carefully controlling the geometry of the articulating surfaces in the joint as well as the positioning of the prostheses in the bones in which the prostheses are implanted. Thus, the articulating surface of a humeral component is typically spherical and positioning of the humeral component is accomplished by using the anatomical neck of the humerus as the reference plane for reconstruction of the humeral head.

(5) In known systems, the glenoid component is positioned in the geometric center of the glenoid fossa. The geometric center is established by generating a line from the most superior point of the glenoid rim to the most inferior point of the glenoid rim (“Saller's line”). A second line is generated between the most posterior point of the glenoid rim and the most anterior point of the glenoid rim. The intersection of the two generated lines is considered to be the geometric center of the area circumscribed by the glenoid rim. By way of example, FIG. 2 depicts a sagittal view of the scapula **12**. In FIG. 2, Saller's line **30** extends between the most superior point **32** of the glenoid rim **24** and the most inferior point **34** of the glenoid rim **24**. A second line **36** extends from the most posterior point **38** of the glenoid rim **24** and the most anterior point **40** of the glenoid rim. The geometric center **42** of the glenoid fossa **14** is located at the intersection of the line **36** and Saller's line **30**. As used herein, the terms anterior, posterior, superior, and inferior, unless otherwise specifically described, are used with respect to the orientation of the scapula **12** as depicted in FIG. 2.

(6) Over time, implanted glenoid components can become loosened. Loosened components can

result in increased pain for an individual. Correction of the problem, however, may be problematic. For example, replacement of components which are loosened may be complicated by a number of different glenoid deficiencies. Glenoid deficiencies may be classified as central (a void area in the central region of the glenoid fossa), peripheral (a void area in the glenoid rim area), or combined (a void area extending from the central region of the glenoid fossa to the glenoid rim area).

Replacement of components in the presence of mild or moderate deficiencies, particularly when limited to the central region, may be accomplished using known components with or without bone grafting to fill remaining void areas. In cases involving large central deficiencies and combined deficiencies, however, other procedures such as allografting are required. Once the grafted material has been incorporated into the glenoid, a second surgery is performed to implant a replacement component into the allograft.

(7) An alternative to grafting procedures is customization of components for the particular patient deficiency. Of course, customization increases the costs for a given procedure. Moreover, obtaining reproducible results is difficult when each procedure is unique.

(8) There remains a need for a glenoid component that allows for establishing normal kinematics in revision procedures. There is a further need for a technique, instrumentation, and implant that facilitates positioning of such a component even when the glenoid has a variety of deficiencies. A glenoid component that can be positioned in a manner that reduces the amount of bone that is required to be removed without overly complicating the implant procedure is also needed.

SUMMARY OF THE INVENTION

(9) The present invention in one embodiment provides a method of implanting a revision glenoid component including accessing a previously implanted glenoid component in a scapula, removing the previously implanted glenoid component, identifying an inferior glenoid circle center of the scapula, preparing a glenoid fossa of the scapula to receive a revision glenoid component, selecting a revision glenoid component, and implanting the selected revision glenoid component based upon the identified inferior glenoid circle center in the prepared glenoid fossa.

(10) In another embodiment, a method of implanting a revision glenoid component includes obtaining an image of a scapula, identifying an inferior glenoid circle center of the scapula based upon the image, selecting a revision glenoid component, removing a previously implanted glenoid component from the scapula, preparing a glenoid fossa of the scapula to receive a prosthesis, and implanting the selected revision glenoid component in the prepared glenoid fossa based upon the identified inferior glenoid circle center.

(11) In a further embodiment a glenoid component includes a base component with a planar upper circular rim defining a first plane, a receptacle opening to the first plane, a lower planar circular surface defining a second plane parallel to the first plane, and a conical outer wall extending from the upper circular rim to the lower planar circular surface. The glenoid component includes an articulating component with an upper articulating surface and a lower coupling portion configured to be inserted into the receptacle.

(12) The above-noted features and advantages of the present invention, as well as additional features and advantages, will be readily apparent to those skilled in the art upon reference to the following detailed description and the accompanying drawings, which include a disclosure of the best mode of making and using the invention presently contemplated.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 depicts a coronal view of an anatomically normal shoulder joint.

(2) FIG. 2 depicts a sagittal view of the shoulder joint of FIG. 1;

(3) FIG. 3 depicts a front perspective view of a retroversion glenoid component that may be

implanted in a scapula in accordance with principles of the invention;

(4) FIG. 4 depicts a front perspective view of the base of the retroversion glenoid component of FIG. 3 that may be implanted in a scapula in accordance with principles of the invention;

(5) FIG. 5 depicts a top plan view of the base of the retroversion glenoid component of FIG. 3;

(6) FIG. 6 depicts a side cross-sectional view of the base of the retroversion glenoid component of FIG. 3;

(7) FIG. 7 depicts a front perspective view of the articulating component of the retroversion glenoid component of FIG. 3;

(8) FIG. 8 depicts a side cross-sectional view of the articulation component of the retroversion glenoid component of FIG. 3;

(9) FIG. 9 depicts a side cross-sectional view of the retroversion glenoid component of FIG. 3;

(10) FIG. 10 depicts a medical procedure that may be used to implant the retroversion glenoid component base of FIG. 3 into a scapula using a kit that includes a guide pin and a combined reaming/planing tool;

(11) FIG. 11 depicts a sagittal view of a scapula with an implanted glenoid component which exhibits severe central bone loss resulting in undesired movement of the implanted glenoid component and which has been accessed in accordance with the procedure of FIG. 10;

(12) FIG. 12 depicts a sagittal view of the scapula of FIG. 11 after the previously implanted glenoid component has been removed;

(13) FIG. 13 depicts a front perspective view of the scapula of FIG. 11 with a guide pin placement guide positioned to guide placement of the guide pin such that the guide pin is aligned with the glenoid axis of the scapula;

(14) FIG. 14 depicts a side perspective view of the guide pin of FIG. 13 used to guide a combined reaming/planning device that may be included in a kit;

(15) FIG. 15 depicts a partial bottom perspective view of the combined reaming/planning device of FIG. 14 showing a planning portion and a reaming portion;

(16) FIG. 16 depicts a side perspective view of the scapula of FIG. 14 after a cavity has been reamed and after the glenoid has been repaired by using bone graft and a compactor to replace bone loss areas about the cavity;

(17) FIG. 17 depicts the side perspective view of the scapula of FIG. 16 with the guide hole of a base component aligned with the guide pin such that the base component will be positioned in alignment with the glenoid axis of the scapula;

(18) FIG. 18 depicts a sagittal plan view of the scapula of FIG. 17 with the base component rotated such that fasteners inserted into two of the fastener holes of the base can access a lateral pillar and a spina pillar of the scapula;

(19) FIG. 19 depicts a cross-sectional view of the scapula of FIG. 18 with the coupling portion of the selected articulation component aligned with the receptacle of the base component; and

(20) FIG. 20 depicts a cross-sectional view of the scapula of FIG. 19 with the articulation component coupled with the base component such that the nadir of the articulation component is positioned at the glenoid axis of the scapula.

DETAILED DESCRIPTION

(21) Like reference numerals refer to like parts throughout the following description and the accompanying drawings.

(22) FIG. 3 depicts a retroversion glenoid component **100**. The glenoid component **100** includes a base component **102** and an articulation component **104**. With further reference to FIGS. 4-6, the base component **102** includes a wall **106** which extends between a lip **108** and a bottom surface **110**. At the lip **108**, the wall **106** defines a circular outer periphery that is slightly larger than the circular outer periphery of the wall **106** at the bottom surface **110**.

(23) The lip **108** defines a receptacle **112** which is substantially cylindrical. The receptacle **112** extends from the lip **108** to a lower surface **114**. Three fastener holes **116**, **118**, and **120** extend

through the lower surface **114** and the bottom surface **110**. A guide hole **122** also extends through the lower surface **114** and the bottom surface **110**. The guide hole **122** and the receptacle **112** are centrally located. Accordingly, the guide hole **122**, the receptacle **112**, and the outer wall **106** define a unitary axis **124**.

(24) The articulating component **104**, depicted in FIGS. **6** and **7**, includes a spherical articulating surface **134** and a coupling portion **136**. The coupling portion **136** is substantially cylindrical in shape and sized with a diameter slightly larger than the diameter of the receptacle **112**. The articulating surface is positioned with a nadir **138** located on a central axis **140** of the articulating component **104**. Accordingly, when the articulation component **104** is coupled with the base component **102** as depicted in FIG. **9**, the nadir **138** is located on the axis **124** of the base component.

(25) The glenoid component **100** in this embodiment is modular, but in other embodiments may be integrally formed. Integrally formed units may be made from a durable biocompatible plastic or any other suitable durable biocompatible material. For example, the glenoid component **100** may be made from a polyethylene. One particular polyethylene that is well suited for glenoid component **100** is a high molecular weight polyethylene, for example ultra-high molecular weight polyethylene (“UHMWPE”). One such UHMWPE is sold as by Johnson & Johnson of New Brunswick, New Jersey as MARATHON™ UHMWPE and is more fully described in U.S. Pat. Nos. 6,228,900 and 6,281,264 to McKellop, which are incorporated herein by reference.

(26) In the embodiment of FIG. **3** wherein the articulation component **104** and the base component **102** are separately formed, the various components may be made from different materials. Thus, the articulating surface **134** may be made from UHMWPE, while the coupling portion **136** and the base component **102** may be made from a suitable biocompatible metal such as, for example, a cobalt chromium alloy, a stainless steel alloy, a titanium alloy, or any other suitable durable material. In this embodiment, the articulating surface **134** is secured to the coupling portion **136** in any suitable manner. For example, articulating surface **134** may be bonded to coupling portion **136**, or articulating surface **134** could be made from polyethylene and compression molded to coupling portion **136**. Alternately, the articulating surface **134** may be glued to the coupling portion **136**, for example, an adhesive. Alternatively, articulating surface **134** may be mechanically interlocked to the coupling portion **136** by taper locking or otherwise press-fitting the articulating surface **134** into the coupling portion **136** and the coupling portion **136** may include any other suitable interlocking features, for example, rib(s), lip(s), detent(s), and/or other protrusion(s) and mating groove(s), channel(s), or indent(s) (not shown).

(27) In alternative embodiments, one or more of the outer wall **106** and the bottom surface **110** may include a porous coating to facilitate bone in-growth into the glenoid component **100**. The porous coating may be any suitable porous coating and may for example be POROCOAT®, a product of Johnson & Johnson of New Brunswick, New Jersey and more fully described in U.S. Pat. No. 3,855,638 to Pilliar, which is incorporated herein by reference.

(28) The glenoid component **100** may be included in a kit incorporating instrumentation that may be used to facilitate implantation of the glenoid component **100**. Such instrumentation may include reamers and guide pins, as discussed more fully below. Additionally, the kit may include base components having different heights and widths. Typical heights may range between 10 and 30 millimeters (mm). The kit may further include articulation components having different diameters. In one embodiment, a kit includes articulation components having a variety of diameters ranging from about 23 mm to about 30 mm.

(29) Preferably, each of the base components in a kit has a receptacle **112** that is shaped and dimensioned the same as the receptacle **112** of each of the other base components **102** while each of the articulation components **104** has a coupling portion **136** that is shaped and dimensioned the same as the coupling portion **136** of each of the other articulation components **104**. Accordingly, any of the articulation components **104** may be coupled with any of the base components **102** in the

kit.

(30) A kit including the glenoid component **100** may be used to implant the glenoid component **100** into a scapula that has previously received a glenoid component in accordance with a procedure **150** depicted in FIG. **10**. In accordance with the procedure **150**, a scapula is accessed at block **152** in accordance with a desired surgical approach. The previously implanted glenoid component is then removed at block **154**. At block **156**, the center of an inferior glenoid circle, further described in co-pending U.S. patent application Ser. No. 13/051,011, is identified for the scapula. While visual identification of the inferior glenoid circle and hence the center of the inferior glenoid circle is possible once the scapula is accessed at block **152**, the center of the inferior glenoid circle may alternatively be identified prior to or after incising a patient with the aid of imaging or other techniques.

(31) Once the center of the inferior glenoid circle is identified at block **156**, a glenoid axis which extends through the center of the inferior glenoid circle and is perpendicular to the articulating surface of the glenoid is identified (block **158**). In alternative approaches, the glenoid axis may extend through the scapula at locations other than the center of the inferior glenoid circle. The glenoid axis may be identified prior to or after incising a patient with the aid of imaging or other techniques.

(32) Next, a guide pin is positioned in the scapula such that the longitudinal axis of the guide pin is coextensive with the glenoid axis (block **160**). A circular cavity is then reamed in the glenoid (block **162**) and the glenoid surface is planed (block **164**). The circular cavity is preferably slightly larger than the diameter of the revision glenoid base component **102**. This allows for positioning of the base component **102** without placing stress on the glenoid which may be significantly compromised as discussed more fully below. At block **166**, a bone graft compactor is used over the guide pin, if needed, to fill in void areas of the glenoid which are not needed for receiving the revision glenoid component. The guide hole **122** of the base component **102** is then aligned with and inserted onto the guide pin (block **168**).

(33) Using the guide pin as a guide, the base component **102** is then implanted in the prepared glenoid (block **170**). Because the guide pin is positioned on the glenoid axis and because the guide pin is positioned within the guide hole **122**, using the guide pin ensures that the central axis **124** of the base component (see FIG. **6**) is aligned with the glenoid axis. At block **172**, the base component **122** may further be rotated about the guide pin to align one or more of the fastener holes **116**, **118**, and **120** with a respective one of the pillars of the scapula as described by A. Karellse, et al., "Pillars of the Scapula", *Clinical Anatomy*, vol. 20, pp. 392-399 (2007). Typically, at least two of the fastener holes **116**, **118**, and **120** may be positioned so as to access the lateral and spina pillars. Rotation of the base component **102** is facilitated since the cavity in the glenoid is slightly larger than the base component **102** as discussed above.

(34) The guide pin may then be removed (block **174**) and one or more fasteners may be inserted through fastener holes **116**, **118**, and **120** to affix the base component **102** to the scapula (block **176**). To ensure firm fixation of the base component **102**, it is preferred that one or even two fasteners extend into solid bone material within one or more of the pillars of the scapula. The fastener holes **116**, **118**, and **120** may be configured to allow for variable angle fastener placement to assist in achieving a firm fixation. A desired articulation component is then obtained (block **178**) and the coupling portion **136** is aligned with the receptacle **112** (block **180**). The coupling portion **136** is then moved into the receptacle **112** and the articulation component **104** is coupled to the base component **102** (block **182**). Coupling may be facilitated by forming the coupling portion **136** and the receptacle **112** to form a friction fit, Morse taper, etc. Once the articulation component **104** is coupled to the base component **102**, the nadir **138** will be aligned with the glenoid axis since the articulation component **104** is configured to couple with the base component **102** such that the nadir **138** is on the axis **140** as discussed above.

(35) FIGS. **11-20** depict a scapula **50** at various points of the procedure **220**. In FIG. **11**, the scapula

12 is depicted after block **152** with a previously implanted glenoid component **52**. FIG. **12** depicts the scapula **50** after the component **52** has been removed. The scapula **50** in FIG. **12** exhibits severe central bone loss which has resulted in instability of the glenoid component **52**. The methods and devices disclosed herein may be used in performing a retroversion glenoid implantation in the presence of a variety of glenoid deficiencies including central, peripheral, and combined deficiencies ranging from mild to severe. Because the base component **102** is not press fit in to the scapula as discussed above, the potential of fracturing a portion of the scapula even in the presence of severe deficiencies is reduced.

(36) FIG. **13** depicts a guide pin **190** and a guide pin placement guide **192** that may be included in a kit used to perform a revision glenoid component implantation procedure. The guide pin placement guide **192** is positioned on the scapula **50** substantially centered upon the inferior glenoid circle. The guide pin **190** is thus positioned in the scapula **50** with the longitudinal axis of the guide pin **190** aligned with the glenoid axis.

(37) FIG. **14** depicts the scapula **50** with the guide pin **190** used to guide a combination reaming device **194** that may also be included in a kit in accordance with the present disclosure. The combination reaming device **194** includes a shaft **196** and a working portion **198**. The shaft **196** and the working portion **198** are cannulated to allow the guide pin **190** to be used to precisely position the combination device **194**. The working portion **198** includes an outer planing portion **202** and a central reaming portion **204**. The planing portion **202** and the central reaming portion **204** allow for simultaneous reaming and planing of the glenoid surface. Alternatively, two separate devices may be used sequentially.

(38) Once the scapula **50** has been reamed and planed, some areas of deficiency may be present. Accordingly, bone grafting material may be used to fill the void areas. In one embodiment, a kit includes a cannulated compactor which is shaped like the reaming portion **204**. The cannulated compactor may be guided by the guide pin **190** to compact bone graft material **210** (see FIG. **16**) while maintaining or finally forming a cavity **212** that is shaped slightly larger than the outer wall **106** of the base component **102**.

(39) The guide hole **202** is then aligned with the guide pin **190** as depicted in FIG. **17** and the base component **102** is guided by the pin **190** into the cavity **212**. The base component **102** is then rotated within the cavity **212** as desired to position the fastener holes **116**, **118**, or **120** to allow a fastener passed therethrough to be fixed into solid bone. By way of example, FIG. **18** depicts the base component **102** positioned such that a fastener passing through the fastener hole **116** may be fixed in the lateral pillar while a fastener passing through the fastener hole **118** may be fixed in the spina pillar. Thus, even though some or all of the base component **102** may be positioned on bone graft **210** (see, e.g., FIG. **19**), the base component may be solidly fixed to the scapula **50**. Thus, even when bone graft material **210** is used to fill in deficient areas of the scapula **50**, a second surgery is not required.

(40) Once the base **102** is fixed to the scapula **50** and the guide pin **190** is removed, in any desired sequence, the coupling portion **136** of the selected articulation component **104** is aligned with the receptacle **112** of the base component **102** as depicted in FIG. **19**. The coupling portion **136** is then moved into the receptacle **112** and the articulation component **104** is coupled to the base component **102** in any desired manner, such as by a Morse taper fit between the coupling portion **136** and the receptacle **112**, resulting in the configuration of FIG. **20**. In FIG. **20**, the nadir **138** is located on the glenoid axis since the base component **102** was fixed with the axis **124** of the guide hole **122** aligned with the glenoid axis as discussed above.

(41) While the foregoing examples detailed only a single glenoid component **100**, a kit may incorporate a number of different glenoid components. Each glenoid component in the kit may be of a different diameter. Additionally, the procedure **150** may be modified in a number of ways in addition to those discussed above. By way of example, while in the above example the glenoid component **100** was implanted with the nadir **138** aligned with the inferior glenoid circle center at

block **182**, the nadir **138** may alternatively be offset from the inferior glenoid circle center. For example, the nadir **138** may be offset from the inferior glenoid circle center by about 1.1 mm in a direction superiorly and posteriorly from the inferior glenoid circle center by positioning the guide pin **190** at the offset location at block **160**. Imaging and computer based systems may be used to assist in the positioning of the glenoid component at this location.

(42) Moreover, while a specific sequence was described in the procedure **150**, many of the steps may be performed in a different order and/or simultaneously with other of the steps.

(43) In accordance with the methods described above, a glenoid component with a spherical articulating surface is implanted at or very near to the spinning point of a shoulder in a revision procedure. Because of the location of the glenoid component, a humeral component with a radius of curvature matched to the radius of curvature of the articulating surface may be used to provide a constrained fit. As used herein, the term “matched” means a difference in the radii of curvature of the articulating surfaces of less than 2 mm.

(44) The foregoing description of the invention is illustrative only, and is not intended to limit the scope of the invention to the precise terms set forth. Further, although the invention has been described in detail with reference to certain illustrative embodiments, variations and modifications exist within the scope and spirit of the invention as described and defined in the following claims.

Claims

1. A method of implanting a glenoid component, comprising: selecting a base component including a planar upper circular rim defining a first plane, a receptacle opening to the first plane, and a lower planar circular surface defining a second plane parallel to the first plane; preparing a glenoid fossa of a scapula to receive the selected base component; implanting the selected base component in the prepared glenoid fossa; selecting an articulating component with an upper articulating surface, a lower cylindrical coupling portion, and an overhang portion located above the lower cylindrical coupling portion and beneath the upper articulating surface, the overhang portion including a planar lower surface extending outwardly from the lower cylindrical coupling portion; inserting the lower cylindrical coupling portion into the receptacle; and abutting the planar upper circular rim of the base component with the planar lower surface, wherein a portion of the planar lower surface abutting the planar upper circular rim defines an abutting portion maximum diameter, the upper articulating surface defines an articulating surface maximum diameter, the abutting portion maximum diameter is larger than the articulating surface maximum diameter, the planar upper circular rim defining a rim maximum diameter, and the rim maximum diameter is greater than the abutting portion maximum diameter.
2. The method of claim 1, wherein implanting the selected base component comprises: implanting the selected base component such that the first plane is coplanar with a surface of the glenoid fossa.
3. The method of claim 2, wherein implanting the selected base component further comprises: fastening the base component to the glenoid fossa using a plurality of fasteners, each of the plurality of fasteners extending through a respective one of a plurality of fastener holes extending from the receptacle through the lower planar circular surface.
4. The method of claim 1, wherein preparing the glenoid fossa of the scapula to receive the base component comprises: forming a cavity in the glenoid fossa using a reamer, the cavity shaped complementary to, and larger than, the base component.
5. The method of claim 1, wherein: selecting the base component includes selecting a base component having a first maximum height in a direction perpendicular to the first plane, and a receptacle with a receptacle maximum diameter along the first plane; and the receptacle maximum diameter is greater than the first maximum height.
6. The method of claim 5, wherein: selecting the articulating component includes selecting an articulating component with a second maximum height in the direction perpendicular to the first

plane when the articulating component is inserted into the receptacle; and the receptacle maximum diameter is greater than the second maximum height.

7. The method of claim 6, wherein: selecting the articulating component further includes selecting an articulating component with an articulating component maximum diameter along the first plane; and the rim maximum diameter is larger than the articulating component maximum diameter.

8. A method of implanting a glenoid component, comprising: selecting a base component including a planar upper circular rim defining a first plane, a receptacle opening to the first plane, and a lower planar circular surface defining a second plane parallel to the first plane; preparing a glenoid fossa of a scapula to receive the selected base component by forming a cavity in the glenoid fossa using a reamer, the cavity shaped complementary to, and larger than, the base component; implanting the selected base component in the prepared glenoid fossa; selecting an articulating component with an upper articulating surface, a lower cylindrical coupling portion, and an overhang portion located above the lower cylindrical coupling portion and beneath the upper articulating surface, the overhang portion including a planar lower surface extending outwardly from the lower cylindrical coupling portion; inserting the lower cylindrical coupling portion into the receptacle; and abutting the planar upper circular rim of the base component with the planar lower surface.

9. The method of claim 8, wherein implanting the selected base component comprises: implanting the selected base component such that the first plane is coplanar with a surface of the glenoid fossa.

10. The method of claim 9, wherein implanting the selected base component further comprises: fastening the base component to the glenoid fossa using a plurality of fasteners, each of the plurality of fasteners extending through a respective one of a plurality of fastener holes extending from the receptacle through the lower planar circular surface.

11. The method of claim 10, wherein: selecting the base component includes selecting a base component having a first maximum height in a direction perpendicular to the first plane, and a receptacle with a receptacle maximum diameter along the first plane; and the receptacle maximum diameter is greater than the first maximum height.

12. The method of claim 11, wherein: selecting the articulating component includes selecting an articulating component with a second maximum height in the direction perpendicular to the first plane when the articulating component is inserted into the receptacle; and the receptacle maximum diameter is greater than the second maximum height.

13. The method of claim 12, wherein: selecting the articulating component further includes selecting an articulating component with an articulating surface that defines an articulating surface maximum diameter along the first plane; selecting the base component includes selecting a base component having an upper circular rim that defines a rim maximum diameter along the first plane; and the rim maximum diameter is larger than the articulating surface maximum diameter.

14. The method of claim 13, wherein: selecting the articulating component further includes selecting an articulating component with an articulating component maximum diameter along the first plane; and the rim maximum diameter is larger than the articulating component maximum diameter.

15. The method of claim 8, wherein selecting the articulating component comprises: selecting an articulating component with an overhang portion that defines an overhang maximum diameter and an upper articulating surface that defines an articulating surface maximum diameter, wherein the overhang maximum diameter is larger than the articulating surface maximum diameter.

16. A method of implanting a glenoid component, comprising: selecting a base component including a planar upper circular rim defining a first plane, a receptacle opening to the first plane, and a lower planar circular surface defining a second plane parallel to the first plane; preparing a glenoid fossa of a scapula to receive the selected base component; implanting the selected base component in the prepared glenoid fossa such that the first plane is coplanar with a surface of the glenoid fossa; selecting an articulating component with an upper articulating surface, a lower cylindrical coupling portion, and an overhang portion located above the lower cylindrical coupling

portion and beneath the upper articulating surface, the overhang portion including a planar lower surface extending outwardly from the lower cylindrical coupling portion; inserting the lower cylindrical coupling portion into the receptacle; and abutting the planar upper circular rim of the base component with the planar lower surface.
